DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Issued by Sandia National Laboratories, operated for the United States
Department of Energy by Sandia Corporation.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability to responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Printed in the United States of America
Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161
Price: Printed Copy \$4.50 ; Microfiche \$3.00

PAGES 1 to 2
WERE INTENTIONALLY
LEFT BLANK

SAND81-8013
Unlimited Release
Printed October 1981

A SOLID-ELECTROLYTE OXIDE-ION ELECTRODE FOR MOLTEN NITRATES

D. A. Nissen
Exploratory Chemistry Division I
Sandia National Laboratories, Livermore 251 1238

ABSTRACT

An oxide ion sensitive electrode of the type $\text{Pb}, \text{PbO}/\text{ZrO}_2(\text{Y}_2\text{O}_3)//$ was constructed and its performance tested in the binary, equimolar molten salt $\text{NaNO}_3\text{-KNO}_3$ over the temperature range $336\text{-}350^\circ\text{C}$. The response of this electrode to oxide ion concentrations over the range $10^{-6}\text{-}10^{-10}$ moles/kg is linearly dependent upon $\log [\text{O}^{2-}]$, and $dE/d\log[\text{O}^{2-}]$ corresponds to a two-electron process.

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

	<u>Page</u>
Introduction	9
Experimental Procedure	12
Results and Discussion	14
Conclusion	18
References	19

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1.	Experimental Cell and Reference Electrode	13
2.	Pb, PbO Indicator Electrode Potential vs. $\log \frac{(\text{CrO}_4^{=})^2}{(\text{Cr}_2\text{O}_7^{=})}$	15
3.	Titration Curve of Dichromate with Carbonate	17

A SOLID ELECTROLYTE OXIDE ION ELECTRODE FOR MOLTEN NITRATES

Introduction

Oxide ion conducting ceramics such as stabilized zirconia have assumed increased scientific interest and technical significance in recent years as solid electrolytes. Indicator electrodes employing zirconia stabilized with CaO, MgO, or Y₂O₃ have been used in the metallurgical industry to measure oxygen activity in gases and molten metals. They have also been used in laboratory research to determine the dissociation pressure of solid oxides, the solubility of oxygen in liquid metals, and the oxide ion activity in molten salts and glasses.

The introduction of 10-20 at. percent of the oxides of lower valent cations such as Ca⁺² or Y⁺³, stabilizes the cubic fluorite structure of ZrO₂ and leads to the formation of anion vacancies in order to maintain charge neutrality. Oxide ion conduction then occurs through this one-dimensional structure¹.

Stabilized zirconia can function as a semi-permeable membrane in molten salts, and is able to transport oxide ions into and out of these liquids². The reversibility of the process

has been demonstrated under potentiometric conditions, i.e. when very small currents are passed as, for example, when stabilized zirconia forms part of an indicator electrode^{1,2}. Electrodes employing stabilized zirconia, and which are sensitive to the concentration of oxide ions, have been described^{3,4}.

The oxide ion sensitive electrode used in this study is one where the oxygen partial pressure is fixed by a metal-metal oxide couple. The electrode may be represented as

where the double line represents the zirconia membrane that separates the electrode from the bulk melt. In this case the electrode reaction is

$$E = E^0 - \frac{RT}{2F} \ln \frac{a_{O=}}{P_{O_2}} \quad (3)$$

Since the oxygen partial pressure is fixed by the Pb, PbO equilibrium the constant terms can be incorporated into E^0 and equation 3 reduces to

$$E = E^0 - \frac{RT}{2F} \ln a_{O=} \quad (4)$$

As a consequence of the gradient in oxide ion activity across the zirconia membrane a potential is developed which is given by

$$E = -\frac{RT}{2F} \ln \frac{(a_{O=})_1}{(a_{O=})_2} \quad (5)$$

where 1 and 2 correspond to the inside and outside of the zirconia membrane, respectively. It is assumed in equation (5) that the zirconia membrane functions in a manner analogous to a liquid junction and that the transport number of the oxide ion equals one.^{5,8} Therefore, the potential of electrode (a), with respect to the reference electrode, is given by

$$E = E^0 - \frac{RT}{2F} \ln (a_{O=})_1 - \frac{RT}{2F} \ln \frac{(a_{O=})_1}{(a_{O=})_2} \quad (6)$$

Since the oxide ion activity inside the zirconia membrane is fixed, these terms may be incorporated with E^0 to give

$$E = E^{0'} + \frac{RT}{2F} \ln (a_{O=})_2 \quad (7)$$

Thus, the potential of electrode (a) can be directly related to the activity of the oxide ion in the $\text{NaNO}_3 - \text{KNO}_3$ melt.

While the electrode potential is a measure of the activity of the oxide ion, equation (7), it is not possible to associate a particular cell emf with a specific oxide ion activity unless an independently determined value of E^0 , the standard electrode potential, as well as phase boundary potentials are available. At the present state of knowledge in molten salts these data are generally not available. However, in this study we are primarily concerned with the response of the Pb, PbO/ZrO₂ electrode to changes in the oxide ion concentration rather than its absolute value. Thus we shall, as a first approximation, assume that the Pb, PbO/ZrO₂ electrode potential is a measure of the oxide ion concentration.

Metal-metal oxide electrodes like (a) have been used quite successfully in both research and industrial applications. Generally, the most frequently used metal-metal oxide couples are Cu-Cu₂O, Fe-FeO, Ni-NiO, or Pb-PbO (other couples are also possible)⁴. For our experiments we chose the Pb-PbO couple because this particular couple has been investigated extensively. The electrode process is unambiguous and reversible and the mutual solubility of the

reproducibility of the electrode at low temperature (350°C) should be improved by the presence of a liquid phase (Pb, m.p. 327°C).

In order to evaluate the response of the Pb, PbO/ZrO₂ electrode it was necessary to vary the oxide ion concentration of the NaNO₃-KNO₃ melt in a systematic manner. Typically, this is done by adding weighed amounts of Na₂O. However, this approach was not taken for several reasons: Na₂O is very difficult to obtain commercially in high purity (typically it is 95-97 percent pure), even Na₂O synthesized in the laboratory under carefully controlled conditions contains several percent Na₂O₂⁷; Na₂O is hydroscopic and difficult to maintain unreacted in other than inert atmospheres. Evidence has recently appeared indicating that even in the absence of molecular oxygen oxide ions may react with molten alkali nitrates (at temperatures below 350°C) to form peroxide and superoxide ions^{5,8,9}

Therefore, the approach taken here was to establish a known oxide ion concentration by means of a Lux-Flood acid-base reaction

where A and B are the conjugate acid-base pair, e.g.

In the Lux-Flood acid-base concept an acid is an oxide ion acceptor and a base is an oxide ion donor^{10,11}. In these experiments the oxide ion concentration was determined by the chromate-dichromate equilibrium

That is,

$$[O^=] = \frac{[CrO_4^=]^2}{[Cr_2O_7^=]K} \quad (14)$$

where K is the equilibrium constant for reaction (13) in the NaNO₃-KNO₃

melt. Thus, the oxide ion concentration is uniquely determined by the ratio of chromate to dichromate, equation (14). Strictly speaking, eqn. (14) should be written in terms of the activities of its components. However, the equilibrium constants reported by Kust¹² for reaction (13) were calculated from concentrations. It is entirely self-consistent therefore, to use eqn. (14) to calculate oxide ion concentrations. It is only necessary to assume that the activity coefficients are independent of concentration which seems reasonable in solutions this dilute ($<10^{-1}$ mole/kg). Reaction (13) has been well characterized in $\text{NaNO}_3\text{-KNO}_3$ and there appear to be no side reactions of any consequence below 350°C ¹².

Experimental Procedure

The cell used to measure changes in oxide ion concentration of the $\text{NaNO}_3\text{-KNO}_3$ may be represented as

where the double line represents the zirconia membrane. The Ag, AgNO_3 reference electrode, used to monitor the potential of the Pb, PbO electrode, was contained in a thin Pyrex membrane. Because it exhibits ideal Nernst behavior and the metal has no observable tendency to dissolve in molten silver and is highly reversible to its ions, the Ag, AgNO_3 electrode has been used extensively in molten nitrates as a reference electrode.^{13,14} The Pb, PbO electrode was contained in a closed end stabilized zirconia tube (Corning Glass Works, Solon, Ohio) one-half inch in diameter and 12 inches long. Three different compositions were tried: ZrO_2 -8 wt. percent Y_2O_3 , and ZrO_2 -3 wt. percent MgO and ThO_2 -15 wt. percent Y_2O_3 . No difference in electrochemical behavior was detected. All these compositions exhibited excellent thermal shock resistance and appeared visually to be unattacked by immersion in the nitrate melt at 350°C for periods of up to 14 days.

The Pb, PbO electrode was made by mixing together approximately equal volumes of 99.9% pure Pb shavings and the tetragonal form of PbO, litharge. Connection to the Pb, PbO electrode was made by a 304 stainless steel rod. Visually the rod appeared to be unattacked by the Pb, PbO mixture and the constancy and reproducibility of the EMF measurements seemed to confirm this. The stainless steel rod was held in place by an O-ring compression seal that also served to maintain atmospheric integrity.

Figure 1 is an illustration of the experimental apparatus and the Pb, PbO electrode. In order to avoid any reaction between the nitrate melt and the container that might affect the results, the melts were held in a gold crucible. The chromel-alumel thermocouple used to monitor the melt temperature was sheathed in gold.

Figure 1. Experimental Cell and Reference Electrode

Argon was used in this study to provide an inert, controlled atmosphere over the melt. It was carefully purified by passage through an 800°C titanium bed to remove oxygen and water and then through an Ascarite column to remove any carbon dioxide. To prevent back-diffusion of atmospheric gases, the effluent gas was also passed through a sulfuric acid bubbler. In addition to careful purification of the gases, all the salts used in this program were routinely purified by recrystallization from distilled water. Following the recrystallization operation the salts were stored in a vacuum oven at 150°C.

The potential between the Pb, PbO indicator electrode and the Ag, AgNO₃ reference electrode was measured with a high impedance electrometer (Keithley Model 616). The output from the electrometer was recorded on a Hewlett-Packard Model 7100B strip chart recorder.

In order to establish a particular oxide ion concentration the appropriate weighed quantities of vacuum-dried K₂CrO₄ and K₂Cr₂O₇ were added to the melt and argon was bubbled through the melt to help establish a uniform concentration. Changes in the oxide ion concentration could be made by adding weighed amounts of either K₂CrO₄ or K₂Cr₂O₇ depending upon the change desired. The solutions were kept relatively dilute with the CrO₄⁼ and Cr₂O₇⁼ concentrations varying between 5×10^{-1} - 3×10^{-5} moles/kg.

Except for the lowest oxide ion concentration ($< 10^{-12}$ moles/kg) the response of the Pb, PbO/ZrO₂ electrode to changes in the oxide ion concentration was very rapid. Once the equilibrium potential had been reached (~ 5 - 10 min) it remained very stable ($\pm 0.0005V$) for as long as 48 hours. At the lower oxide ion concentrations about an hour was required for the potential to stabilize.

Results and Discussion

The results of 60 experiments in which the response of the Pb, PbO/ZrO₂ electrode to variations in the oxide ion concentration of a NaNO₃-KNO₃ melt, as determined by the CrO₄⁼/Cr₂O₇⁼ ratio, are shown in Figure 2. Also included are the relevant oxide ion concentrations calculated from equation (14). To aid in interpretation of the data presented in this Figure all the potential values for a given concentration have been averaged. The spread is $\pm 0.005V$.

Over the oxide ion concentration range 10^{-10} to 10^{-6} moles/kg the Pb, PbO/ZrO₂ electrode potential is a linear function of the logarithm of the oxide ion concentration with a slope equal $2.3 RT/2F$. As the oxide ion concentration falls below 10^{-10} moles/kg the indicator electrode potential begins to show a pronounced departure from this relationship. At oxide ion concentrations below 10^{-12} moles/kg the Pb, PbO/ZrO₂ electrode potential appears to be invariant with concentration. While lines of differing slope may be drawn through the data shown in Figure 2 to include more of the data points, the precision of the measurements is such that this treatment of the data is unjustified.

Figure 2. Pb, PbO Indicator Electrode Potential vs. $\log \frac{(\text{CrO}_4^=)^2}{(\text{Cr}_2\text{O}_7^=)}$

If equation (2) represents the potential determining reaction that takes place at the Pb, PbO/ZrO₂ electrode a slope of 2.3 RT/2F would be expected. The question then is, why does the concentration dependence of the Pb, PbO electrode potential change when the oxide ion concentration falls below 10⁻¹⁰ moles/kg? Since the dichromate concentration at this oxide ion concentration is ~10⁻³ moles/kg significant changes in its activity coefficient are considered unlikely. It is possible that at very low oxide ion concentrations (<10⁻¹⁰ moles/kg) reactions which cause a decrease in the oxide ion concentrations and whose products are undetectable by the Pb, PbO/ZrO₂ electrode, begin to become significant. As a consequence, the oxide ion concentration is actually lower than would be predicted from equation (7). As the nominal oxide ion concentration falls below 10⁻¹² moles/kg essentially all of it is converted to a species undetectable by the Pb, PbO/ZrO₂ electrode and consequently the electrode potential becomes invariant with changes in the nominal oxide ion concentration. Reactions such as

in which the oxide ion reacts with small amounts of oxygen in the melt may be responsible. These reactions are particularly credible in light of Stern's observation that zirconia-based electrodes are apparently only responsive to changes in the oxide ion concentration.^{5,15} The activity coefficient of the oxide ion in this melt, while unknown, appears to be reasonably constant over the concentration range 10⁻¹⁰ - 10⁻⁶ mole/kg because of the linear variation of potential with concentration.

As a measure of the response of the Pb, PbO/ZrO₂ electrode a series of potentiometric acid-base titrations were performed. The reaction that was followed was

which is, in effect, a titration of the Lux-Flood acid Cr₂O₇²⁻ by the base CO₃²⁻. This reaction was first studied by Shams el Din who showed it to be uncomplicated¹⁶. The presence of chromate in the melt appears to have no effect on the titration¹⁷. In these experiments weighed quantities of vacuum-dried reagent grade Na₂CO₃ were added to various ratios of Cr₂O₇²⁻/CrO₄²⁻ in NaNO₃-KNO₃ at temperatures between 335-350°C. The response of the Pb, PbO/ZrO₂ electrode for a typical titration at 336°C is shown in Figure 3. The equivalence point is quite sharp and corresponds to a change in potential of about 500 mV. The results of three different titration at 336 ± 2°C are given in Table I.

The agreement between the concentration of Cr₂O₇²⁻ in the melt and that determined analytically is reasonably good. These experiments indicate that even at temperatures below 350°C the Pb, PbO/ZrO₂ electrode responds rapidly and reproducibly to changes in the oxide ion concentration and that the charge-transfer is reversible.

Figure 3. Titration Curve of Dichromate With Carbonate

TABLE I

TITRATION OF DICHROMATE WITH CARBONATE IN $\text{NaNO}_3\text{-KNO}_3$ $T = 336 \pm 2^\circ\text{C}$

Exp't.	$[\text{Cr}_2\text{O}_7^{2-}]$ added (moles)	$[\text{Cr}_2\text{O}_7^{2-}]$ found (moles)	Percent Recovered
DN-1	9.91×10^{-3}	9.86×10^{-3}	99.5
DN-2	1.02×10^{-3}	1.00×10^{-3}	98
DN-3	1.04×10^{-2}	1.07×10^{-2}	103

Conclusion

The electrode $\text{Pb, PbO/ZrO}_2 (\text{Y}_2\text{O}_3)$ has been demonstrated to be sensitive to oxide ion concentrations over the range 10^{-10} to 10^{-6} moles/kg in molten $\text{NaNO}_3\text{-KNO}_3$ between 336 and 350°C . Over this concentration range the concentration dependence of the electrode potential is linear with a slope corresponding to a two-electron process. The response of the Pb, PbO/ZrO_2 electrode to changes in the oxide ion concentration is very rapid, and once the equilibrium potential has been reached ($\sim 5\text{-}10$ min) it remains very stable (± 0.0005 V) for as long as 48 hours.

REFERENCES

1. R. M. Dell and A. Hooper, "Solid Electrolytes, General Principles Characterization, Material, Applications," P. Hagennuller and W. Van Gool, eds. Academic Press, New York, 1978, p. 292.
2. M. L. Deanhardt and K. H. Stern, J. Phys. Chem., 84, 2831 (1980).
3. K. H. Stern, J. Electrochem. Soc., 127, 2375 (1980).
4. J. H. E. Jeffes and R. Sridhar, "Electromotive Force Measurement in High Temperature Systems," C. B. Alcock, ed., American Elsevier, New York, 1968, p. 199.
5. D. R. Flinn and K. H. Stern, J. Electroanal Chem., 63, 39 (1975).
6. J. O' M. Bockris and G. W. Mellors, J. Phys. Chem., 60, 1321 (1956).
7. G. Brauer, "Handbook of Preparative Inorganic Chem." Vol. 1, 2nd ed., Academic Press, New York, 1963, p. 975.
8. P. G. Zamboni, J. Electroanal Chem., 45, 451 (1973).
9. J. D. Burke and D. H. Kerridge, Electrochem. Acta, 19, 251 (1976).
10. H. Lux, Z. Electrochem., 45, 303 (1939).
11. H. Flood and T. Forland, Acta Chem. Scand., 1, 592 (1947).
12. R. Kust, Inorg. chem., 6, 2239 (1967).
13. S. N. Flengas and E. Rideal, Proc. Royal Soc., A233, 443 (1956).
14. R. W. Laity in "Reference Electrodes," D. J. G. Ives and G. J. Janz, eds., Academic Press, New York, 1961, p. 585.
15. K. H. Stern, Electrochem. Acta, 24, 509 (1979).
16. A. M. Shams el Din and A. A. A. Gerges, J. Electroanal, Chem., 4, 309 (1962).
17. J. D. Van Norman and R. A. Osteryoung, Anal. Chem., 32, 398 (1960).
18. K. H. Stern, J. Phys. Chem., 72, 1963 (1968).
19. J. D. Van Norman and R. A. Osteryoung, Anal. Chem., 32, 398 (1960).
20. O. Kubaschewski, E. LL. Evans, and C. B. Alcock, "Metallurgical Thermochemistry," 4th ed. Pergamon Press, New York, 1967, p. 426.

UNLIMITED RELEASE

INITIAL DISTRIBUTION:

Division of Thermal and Mechanical Energy Storage Systems
MS 6B025 Room 1G-100
Forrestal Building
U.S. Department of Energy
Washington, D. C. 20585
Attn: M. Gurevich
S. Strauch
J. H. Swisher

Division of Solar Thermal Energy Systems
U.S. Department of Energy
600 E Street N.W., Room 419
Washington, D.C. 20585
Attn: W. Auer
G. W. Braun
K. Cherian
M. U. Gutstein
J. E. Rannels

D. Schueler
Albuquerque Operations Office
Special Programs Division
U.S. Department of Energy
P. O. Box 5400
Albuquerque, NM 87115

San Francisco Operations Office
U.S. Department of Energy
1333 Broadway
Oakland, CA 94612
Attn: D. Elliott
L. Prince

C. M. Kramer
Code 6130
Naval Research Lab
Washington, D. C. 20375

Dr. Robert A. Osteryoung
Department of Chemistry
State University of New York at Buffalo
Buffalo, NY 14214

Prof. Harald A. Oye
Institutt for uorganisk kjemi
Norges tekniske hogskole
Universitetet i Trondheim
N-7034 Trondheim - NTH, NORWAY

John Neill
Advanced Energy Concepts
Suite I
11722 Sorrento Valley Rd.
San Diego, CA 92121

Aerospace Corporation
2350 El Segundo Blvd.
El Segundo, CA 90009
Attn: P. Mathur
L. R. Sitney

Babcock and Wilcox Company
P. O. Box 351
Barberton, OH 44203
Attn: William F. Clancey
Murray Wiener, Power Generation Group

Bill Oberjohn
Babcock and Wilcox
Box 835
Alliance, OH 44601

Dr. C. A. Bolthrunis
Badger Energy, Inc.
One Broadway
Cambridge, MA 02142

Robert L. Lessley
Bechtel Corporation
50 Beale St.
San Francisco, CA 94119

James P. Maddox
Biphase Energy Systems
2800 Airport Ave.
Santa Monica, CA 90405

William D. Beverly
Boeing Engineering and Construction Co.
P. O. Box 3707
Seattle, WA 98124

George H. Rowe
Combustion Engineering
1000 Prospect Hill Road
Windsor, CT 06095

Pierre Spiteri
EDF
Les Renaudierz
Ecuelles, France

Sydney H. White
EIC Labs., Inc.
55 Chapel Street
Newton, MA 02158

Electric Power Research Institute
P. O. Box 10412
3412 Hillview Ave.
Palo Alto, CA 94303
Attn: J. Bigger
T. R. Schneider

Donald C. Erickson
Energy Concepts Co.
627 Ridgely
Annapolis, MD 21401

T. V. Narayanan
Foster Wheeler
12 Peach Tree Hill Road
Livingston, NJ 07039

Donald J. Spellman
Gas Cooled Reactor Assoc.
3344 N. Torrey Pines Road
La Jolla, CA 92137

General Atomic Co.
P. O. Box 81608
San Diego, CA 92138
Attn: Thomas H. Van Hagan
Daniel L. Vrabie

Fred F. Witt
General Electric
3172 Porter Drive
Palo Alto, CA 94304

Soeren S. Nielsen
Gould, Inc.
40 Gould Center
Rolling Meadows, IL 60008

Alan Snelson
ITT Research Institute
10 W 35 Street
Chicago, IL 60616

Jet Propulsion Laboratory
4800 Oak Grove Dr.
Pasadena, CA 91103
Attn: J. Becker
R. Manvi
J. Sheldon
V. Truscello

Skip Gross
MSA Research
Evans City, PA 16033

Martin Marietta Corporation
Box 179
Denver, CO 80201
Attn: Charles N. Bolton
Russell A. Chihoski
David W. Neiswander
Tom Tracey

McDonnell Douglas
5301 Bolsa Ave.
Huntington Beach, CA 92647
Attn: Donald L. Endicott
George F. Greenwald
Russell T. Neher

J. H. DeVan
Oak Ridge National Laboratory
Oak Ridge, TN 37830

Olin Corporation
275 Winchester Ave.
New Haven, CT 06511
Attn: Louis C. Fiorucci
Stephen L. Goldstein
Joe K. Mensah

Olin Corporation
120 Long Ridge Road
Stamford, CT 06904
Attn: Norman Christopher
Gerald A. Habib
Robert E. Smith

Pacific Gas and Electric
3400 Crow Canyon Road
San Ramon, CA 94583
Attn: Helena T. Rowland
Jay Raggio
Harold E. Seielstand

Dr. R. W. Foreman
Park Chemical Company
8074 Military Avenue
Detroit, MI 48204

Richard D. Smith
Rocket Research Company
York Center
Redmond, WA 98052

Robert J. Walter
Rocketdyne
6633 Canoga Ave.
Canoga Park, CA 91360

Rockwell International/ETEC
8900 De Soto Ave.
Canoga Park, CA 91304
Attn: Jerry B. Brukiewa, ETEC
A. Z. Frangos
Rick L. Howerton, ETEC
Ted Johnson, ESG

Solar Energy Research Institute
1536 Cole Blvd.
Golden, CO 80401
Attn: B. Butler
B. P. Gupta
R. G. Nix
R. Ortiz (Library)
P. A. Roberts
P. Russell
K. Touryan
C. Wyman

George Yenetchi
Solar Thermal Systems
Division of Exxon Enterprises, Inc.
P. O. Box 592
Florham Park, NJ 07932

Kenneth Ladd
Southwestern Public Service Co.
P. O. Box 1261
Amarillo, TX 79170

Donald J. Liffengren
Stearns-Roger
4500 S. Cherry Creek Drive
Denver, CO 80217

Robert M. N. Killen
United Engineers and Construction
Suite 300
3344 N. Torrey Pines Ct.
La Jolla, CA 92137

John B. Mulligan
United Engineers and Construction
30 S. 17th Street
Philadelphia, PA 19103

Niven D. Morgan, Jr.
Vertac Chemical Corporation
Suite 241
3000 Knight Office Place
Shreveport, LA 71105

Stuart A. Shiels
Advanced Reactors Division
Westinghouse Electric Corporate
Box 158
Madison, PA 15663

C. Winter, 400
H. J. Saxton, 2520
R. A. Guidotti, 2523
A. Narath, 4000
J. H. Scott, 4700
G. E. Brandvold, 4710; Attn: B. W. Marshall, 4713
R. P. Stromberg, 4714
V. L. Dugan, 4720; Attn: J. V. Otts, 4721
J. F. Banas, 4722
J. A. Leonard, 4725

J. K. Galt, 5000
J. E. Schirber, 5150
R. M. Biefeld, 5154
G. D. Stucky, 5154
R. S. Claassen, 5800
R. G. Kepler, 5810
M. J. Davis, 5830
M. M. Karnowsky, 5832
J. W. Mumford, 5832
R. W. Rohde, 5832
N. J. Magnani, 5840; Attn: D. W. Schaefer, 5841
T. B. Cook, 8000
W. E. Alzheimer, 8120; Attn: R. J. Gallagher, 8124
A. N. Blackwell, 8200
B. F. Murphey, 8300
D. M. Schuster, 8310
R. W. Bradshaw, 8313
R. W. Mar, 8313
D. A. Nissen, 8313
S. H. Goods, 8316
J. C. Swearingen, 8316
R. Rinne, 8320; Attn: C. F. Melius, 8326
L. Gutierrez, 8400
R. Baroody, 8410
R. C. Wayne, 8430
C. S. Selvage, 8450
P. J. Eicker, 8451
A. C. Skinrood, 8452
R. W. Carling, 8453 (25)
L. G. Radosevich, 8453
W. G. Wilson, 8453

C. M. Tapp, 8460

Publications Division, 8265, for TIC (27)

Publications Division, 8265/Technical Library Processes Division, 3141

Technical Library Processes Division, 3141 (3)

M. A. Pound, 8214, for Central Technical Files (3)

[illegible]