CONF-830971--2

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36

LA-UR--83-2477

DE83 017295

TITLE: MAGNETS FOR THE PROTON STORAGE RING AT LOS ALAMOS

AUTHOR(S): Alex Harvey

SUBMITTED TO: MT-8, VIIIth International Conference on Magnet Technology
Grenoble, France
September 5-9, 1983

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution or to allow others to do so, for U.S. Government purposes.

The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

MASTER

MAGNETS FOR THE PROTON STORAGE RING AT LOS ALAMOS

Alex Harvey

Los Alamos National Laboratory, Los Alamos, NM 87545

Résumé - L'Anneau d'Accumulation de Protons à Los Alamos garnira les protons à 800 MeV venant de l'accélérateur LAMPF. Les aimants sont, pour la plupart, actionnés par le courant continu, et sont de bon qualité. Caractéristiques spéciales comprend la construction des laminations pour un aimant de 36° de courbe utilisant une barre droite; des aimants septums avec l'isolation de verre "sol-gel;" et une dipole d'haute pente pour la conversion des particules H⁻ à H⁰ pour insertion dans l'anneau.

Abstract - The Proton Storage Ring at Los Alamos will store 800-MeV protons from the LAMPF accelerator. The magnets are mostly dc excited, of high quality. Special features include construction of a curved 36° laminated dipole core on a straight reference bar, septum magnets with sol-gel glassy insulation, and a high-gradient dipole to strip H⁻ to H⁰ for injection.

The Proton Storage Ring (PSR)[1] now under construction at Los Alamos, New Mexico, will take H⁻ particles at 800 MeV from the LAMPF accelerator, and store them as protons, in either one long bunch per turn or six short bunches per turn, before they are extracted to a spallation target. The PSR is 28 m in diameter, comprising ten 1.2-T dipoles and twenty 180-mm-bore quadrupoles with 4.5-T/m gradient, in a DOFO structure.

The dipole magnets were made of 1.5-mm-thick low-carbon-steel laminations, to achieve reproducible magnetic properties from magnet to magnet by shuffling laminations from the various heats required to produce the 150 tons of steel used. Because the magnets bend the particles 36°, they are curved, and a significant factor in achieving the 0.05-mm tolerance to the specified 4.058-m radius of the magnet was the use of a straight stacking bar for the core. This close tolerance was required because the pole faces are shimmed to achieve a flat field from the minimum-sized magnet. Mating with the bar is a notch in the bottom of each lamination, with the location of the center of the notch in the nth lamination given by

$$d_n = d_1 + \frac{1}{2} \left\{ 4R^2 - [L - t(2n - 1)]^2 \right\}^{1/2} - \frac{1}{2} \left[4R^2 - (L - t)^2 \right]^{1/2},$$

where

R is the stacked core radius (4.058 m),

L is the overall core stack length (2.203 m), and

t is the mean stack length per lamination, measured under the final core load of 75 tons.

The advantage of this innovative scheme[2] is, of course, that laminations do not move relative to their neighbors as the core is compressed. The notch is cut in the lamination, using a digital read-out positioning table, at a workstation adjacent to the stacking fixture. Figure 1 shows the first dipole, with a measuring coil in the aperture. The two-dimensional field is uniform to 1 part in 10⁴ over 105-mm diam, in excellent agreement with MIRT[3] calculations.

To measure these, and other, dipoles, a three-axis point-by-point mapping machine has been constructed (Fig. 2). Capable of covering a volume of 0.5 m by 0.5 m by 2 m in

Fig. 1. PSR main ring dipole.

Fig. 2. Three-axis measuring machine.

variable increments, the device is controlled by an LSI-11 microcomputer. The "point" measuring coil[4] can be oriented to read the X, Y, or Z component of the magnetic field. Apart from some temperature sensitivity in the v-to-f convertor[5] and its associated integrating counter, this device is operating satisfactorily.

The ring quadrupoles must be high quality, but are short (about 0.5-m effective length). The pole-tip design was accomplished by transforming the quadrupole to dipole geometry, shimming the pole face using MIRT, and then transforming back to quadrupole. Duodecapole is eliminated by adding cylindrical shim stacks at the appropriate[6] places on the pole ends.

The injection and extraction beamlines associated with the PSR have dipoles and quadrupoles with less demanding field quality. However, we have found it advantageous to require harmonic analysis of the quadrupoles, with a limit on sextupole of 0.1% of the quadrupole. This not only checks the symmetry of the iron construction, but also identifies coils with errors in the number of turns--a problem with some quadrupoles. In Fig. 3 can be seen a beamline quadrupole, 155-mm bore (with very low sextupole!), and pole-end chamfers to minimize duodecapole.[7]

Septum magnets in the extraction system have current densities up to 88 A/mm.[2] Insulation systems being considered for the septum conductors are porcelain enamel (0.2-mm thick) and sol-gel glass[8] (0.05-mm thick). The sol-gel technique is attractive because of the very thin insulation layer possible. It is impermeable to moisture and has the radiation-resistance of glass, as well as its high temperature capability. The procedure for applying the coating comprises oxidizing the copper surface to promote bonding, spraying on the glass in a solvent base, drying the coating to a gel, and firing the conductor in air. The model septum shown in Fig. 4 is used to evaluate techniques to control leakage fields, such as coil extensions, ferromagnetic shields and compensation windings.[9]

As part of the injection system, there is a high-gradient (200-T/m) dipole of 10-mm aperture to strip the H^- ions to H^0 , [10] for insertion into the ring through a hole in the return yoke of a ring dipole. Although a resistive electromagnet is feasible, some consideration is being given to a samarium-cobalt permanent magnet for this application.

Fig. 3. 155-mm beamline quadrupole.

Fig. 4. Septum development model.

Most of the magnet components of PSR are manufactured by industry (the septa are the exception). Costs for these procurements are given in Table I; tooling is not included.

Table I

<u>Magnet</u>	<u>Number</u>	<u>Designation[11]</u>	<u>Weight (kg)</u>	<u>Cost \$K per unit</u>
80-mm quadrupole	4	3 QN 14/5	408	6.5
100-mm quadrupole	4	4 Q 20/2	871	8.5
100-mm quadrupole	9	4 Q 20/4	740	9.1
100-mm quadrupole	3	4 Q 20/4	519	7.2
155-mm quadrupole	13	6 Q 24/6	1584	10.5
180-mm quadrupole	21	7 Q 16 P/4	1733	12.7
100-mm dipole	5	H 13 IV 62/4	2475	16.0
Main ring dipoles	11	H 12 IV 97 R/12	14 651	89.0
127-mm dipole	1	H 16 V 74/8	9208	34.6
127-mm dipole	1	H 16 V 36/6	4703	25.0

REFERENCES

- [1] Lawrence, G. P., et al, Paper presented at the Xth Int. Conf. on High Energy Accelerators, CERN, Geneva, July 1980, Los Alamos Scientific Laboratory document LA-UR-80-1946.
- [2] Glavish, H., and MacKinnon, B., Private communication, GMW Consultants, Redwood City, CA.

- [3] MIRT is part of a family of electro- and magneto-static design codes maintained by the Los Alamos National Laboratory. The codes are all derived from original work by Alan M. Winslow, J. Comp. Phys. 2, 149-172, 1967.
- [4] Thomason, M. O., Los Alamos Scientific Laboratory report LA-5304-MS, June 1973.
- [5] Dynamic Measurements Corp., Winchester, MA, USA, model 7287.
- [6] Libach, K., and Yourd, R., Lawrence Radiation Laboratory report UCRL-18916, March 1969.
- [7] Hakenzahl, W. V., MT-4, Conf-720908, Brookhaven National Laboratory, p. 469 (1972).
- [8] Brinker, C. J., and Mukherjee, S. P., J. of Math. Sci. 16, p. 1980 (1981).
- [9] Keizer, R. K., CERN 74-13, Geneva 1974.
- [10] Jason, A. J. et al, IEEE Trans. Nucl. Sci. 28, p. 2704 (June 1981).
- [11] Harvey, A., MT-4, Conf-720908, Brookhaven National Laboratory, p. 456 (1972).