2

DOE/PC/89779--T4

Technical Progress Report

#6

DOE/PC/89779--T4

to

DE92 004863

United States Department of Energy
Pittsburgh Energy Technology Center

Attention: Douglas Gyorke, Project Manager
Rhonda Dupree, Contract Specialist
Kay Downey, Office of Technology Transfer

COMPARISON OF LIME AND IRON OXIDE
FOR HIGH TEMPERATURE SULFUR REMOVAL

DOE/DE-FG22-890C89779

by

Kenneth J. Reid, Principal Investigator

Period Covered

March 1, 1991 - May 31, 1991

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DEC 31 1991

ABSTRACT¹

Slagging combustors with injected lime or limestone are being considered as replacements for conventional coal burners. They have advantages in that they can be staged to reduce NO_x and SO_x emissions. Lime or limestone are the currently preferred sorbent materials but iron oxide, as an alternative to lime or limestone, may be effective not only as a desulfurizing agent, but, under the right conditions of oxygen potential, it can act as a flux to produce a glassy slag. This glassy slag should be dense and environmentally inert.

During this reporting period further progress has been made toward completion of the equipment configuration.

In the previous quarter, control of the central core of the double vortex combustion column was shown to be of vital importance and the main focus of work this quarter was in this area.

Test work with the steel prototype using solids injection into the flame showed that optimal coincidence of the flame zone and the solid entrainment trajectories was not being accomplished. Further work was therefore carried out with the glass model to seek visual insights into the controlling phenomena.

By modifying the inner vortex drive method and careful adjustment of the inner and outer drive flow ratios, improvements in particle residence time and solids trajectories were achieved but satisfactory coincidence of the gas dynamics (flame) and solids dynamics (particle trajectories) was still elusive. These observations were disappointing compared to previous experience with larger units burning sawdust.

Following a detailed evaluation of the test work completed to date and previous empirical results, it was postulated that the diameter of the unit was an important parameter, particularly at smaller sizes, and that the selection of a 6" diameter for the present study made the required flame/solids balance extremely difficult.

In order to address this problem it was proposed to alter the geometry of the unit to a conical form rather than the current cylindrical form since for the same outer drive diameter at the smaller end of the cone, the diameter would be larger at the bottom and provide a larger volume in which to achieve the required balance between the inner and outer vortex driving forces.

¹ Key words underlined

DOE/DE-FG22-89PC89779
Technical Progress Report
March 1, 1991 - May 31, 1991

BURNER DESIGN TESTS

Further test work has been carried out on the back plate inner drive mechanism which is responsible for providing the required degree of vorticity in the core of the double vortex fluid dynamic cell.

Three basic inner drive devices were fabricated and tested covering static vanes, rotating vanes and a static disk configuration.

Static vanes were fabricated out of sheet metal with 8 vanes and with an inclined angle of approximately 30 degrees.

The vane plate was attached to the back plate center drive orifice and covered with a gas injection port assembly to permit the controlled introduction of the inner drive gas. Test solids were also introduced into the gas injection port.

For the rotating vane test work, the vane plates used for the static vane tests were modified to permit mounting on the shaft of a suitable drive motor with a range of rotating speeds from 3600 to 10,000 rpm.

The static disk configuration followed the basic principles of the Tesla turbine and employed 8 plates stacked .125" apart. Gas feed was tangential to an outer plenum with the required vorticity generated by shear against the plate walls as the gas spirals inwardly. The inner chamber of the spiral stack was conical with a bottom diameter of 3/4 inch.

Solids were injected axially at the center of the bottom plate of the disk assembly.

Test work with these inner drive units established the following basic principles:

- the fixed vane system is simple to manufacture but is less efficient in the conversion of potential flow to vorticity;
- the spinning vane has the advantage of adjustable rpm and has a high efficiency for the generation of vorticity;
- drawbacks of the spinning vane are its complexity in design and operation;
- the stacked disk system has a high conversion efficiency and is of intermediate complexity for construction.

After the initial comparative test work further work was carried out using the stacked disk system. This work provided increased efficiency for the introduction of vorticity into the core with the result that control of the core geometry was achieved.

The ability to adjust the inner core geometry by this method was now approaching the ability to control the outer region of the double vortex geometry by adjusting the outer drive flow and it was felt that considerable progress had been made in resolving and understanding this problem.

However, although this test program was able to provide for improvements compared to the work of the previous quarter, particularly with respect to increased solids retention in the double vortex field an acceptable degree of coincidence between the solids trajectories and the flame geometry was still lacking.

This observation was disappointing since earlier work (prior to initiation of this project) with larger diameter burners for wood waste had performed satisfactorily.

As a result of the failure to achieve suitable gas/solids coincidence in the small prototype steel combustor with the various inner drive units, considerable time was spent reviewing previous experience with dynamic containment systems and identifying parametric trends.

The major conclusion from this analysis was that the inherent stability of the double vortex fluid dynamic geometry improves as the diameter of the unit increases. The converse of this observation is that control is increasingly difficult as the diameter decreases.

For the injection of solids it was also concluded that residence time and solids trajectories are adversely influenced as the density of the solid particles increases.

Reasons for these observation were proposed as follows:

In smaller diameter units the mixing zone becomes exceedingly narrow with the consequence of imposing extremely large velocity gradients. Such a system is inherently more difficult to control and has a correspondingly narrow operating range.

These considerations account for the difficulties encountered in the small (6" diameter) steel unit using taconite concentrate (sg 4.5).

The obvious solution of using a larger diameter test unit is not practical since the gas flow for stable flame performance increases rapidly with diameter. The size of the test program - gas flows, controls, exhaust management etc. are set by the test unit diameter and the auxiliary systems for the current project have been designed for the 6-inch diameter burner.

After further analysis it was concluded that a conical design for the combustion chamber would be a rational solution. With the outer drive at the small end of a cone the inner drive could be located at the center of the larger diameter bottom plate and have a much larger volume to work with compared to the cylindrical geometry.

The proposed conical geometry has two contributing beneficial factors:

- a) at the narrow, (outer drive) end the diameter is smaller than in an equivalent cylindrical unit and the solids retention characteristics are improved.
- b) at the wider (inner drive) end the diameter is larger than in the equivalent cylindrical unit and the high velocity gradient problem is relieved.

A quick empirical evaluation of this hypothesis using some scrap cones provided enough encouragement to proceed in this direction.

Although the continuing problems with gas/solid flow stabilization have impeded the sorbent test program there is clearly no point in carrying out sorption tests without satisfactory flame/solids flow dynamics. A greater understanding of the complex fluid dynamic fields involved in this project is being assembled and it is still proposed to carry out sorption tests before the end of the project in order to provide some data that will support the proof of principle of sulfur sorption in the dynamic containment geometry.

END

**DATE
FILMED**

2 / 18 / 92