DOE/BC/14246-8
Distribution Category UC-122

MICROBIAL FIELD PILOT STUDY

DOE/BC/14246--8

DE92 001031

By
R. M. Knapp
M. J. McInerney
D. E. Menzie
J. L. Chisholm

March 1992

Work Performed Under Contract No. DE-FG22-89BC14246

Prepared for
U.S. Department of Energy
Assistant Secretary for Fossil Energy

Fred W. Burtch, Project Manager
Bartlesville Project Office
P. O. Box 1398
Bartlesville, OK 74005

Prepared by
University of Oklahoma
Norman, OK 73019

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *EP*

TABLE OF CONTENTS

	Page
LIST OF TABLES	iii
LIST OF FIGURES	iv
ABSTRACT	v
1. ECOLOGY OF THE RESERVOIR	1
1.1 Introduction	1
1.2 Materials and Methods	1
1.3 Results	5
1.4 Discussion	8
References	10
2. SURFACE FACILITIES DESIGN	26
3. THE SOUTHEAST VASSAR VERTZ SAND UNIT (SEVVSU)	32
References	35
4. CORE FLOOD EXPERIMENTS	40
4.1 Introduction	40
4.2 Experiments	40
4.3 Microbial Enhanced Oil Recovery Mechanisms	41
4.4 Experimental Results	44
4.5 Discussion	45
4.6 Conclusions	46
References	49
5. MICROBIAL MODELING	59
5.1 Introduction	59
5.2 Model Validation	59
5.3 Conclusions	60
References	61
6. RESERVOIR CHARACTERIZATION AND SIMULATION	67
References	68

LIST OF TABLES

TABLE	PAGE
1.1 Chemical analysis of SEVVSU brines	12
1.2 Chemical analysis of SEVVSU brines	13
1.3 Concentrations of sulfate and sulfide in SEVVSU brines	14
1.4 Numbers of different groups of bacteria in SEVVSU brines	15
1.5 Substrate utilization by anaerobic halophiles isolated from SEVVSU brines	16
1.5 Substrate utilization (continued)	17
1.6 Glucose fermentation products of the anaerobic halophiles isolated from SEVVSU brines ^a	18
3.1 Southeast Vassar Vertz Sand Unit	36
3.2 Field Pilot Volumetric Data	37

LIST OF FIGURES

FIGURE	PAGE
1.1 Oklahoma Geological Regions	19
1.2 Net Thickness Map of Southeast Vassar Vertz Sand Unit (SEVVSU)	20
1.3 Effect of NaCl concentration on the growth of strain VS-732	21
1.4 Effect of NaCl concentration on the growth of strain VS-751	22
1.5 Effect of NaCl concentration on the growth of strain VS-752	23
1.6 Effect of NaCl concentration on the growth of strain VS-511	24
1.7 Effect of NaCl concentration on the growth of strain TTL-30	25
2.1 Injection Well Facility	28
2.2 Procedure for Nutrient Treatment Injection	29
2.3 SEVVSU Pilot Gathering System	30
2.4 Facilities at Tank Battery	31
3.1 Well Sites	38
3.2 Isopach Map of Net Vertz Sand	39
4.1 Experimental Set-up	52
4.2 Wetting and Non-wetting Relative Permeability Curves	53
4.3 Capillary Desaturation Curve (CDC) (after Stalkup)	54
4.4 Effect of Nutrient Treatments on the PRF, Cumulative Oil Recovery and Gas Production (Core 6)	55
4.5 Effect of Nutrient Treatments on the PRF, Cumulative Oil Recovery and Gas Production (Core 9)	56
4.6 Effect of Nutrient Treatments on the PRF, Cumulative Oil Recovery and Gas Production (Core 10)	57
4.7 Effect of Nutrient Treatments on the PRF, Cumulative Oil Recovery and Gas Production (Core 11)	58
5.1 Cumulative Production of Total Gases (CO ₂ & N ₂) During MEOR Process (Core #6)	62
5.2 Consumption of Glucose During MEOR Process (Core #6)	63
5.3 Consumption of Ammonium During MEOR Process (Core #6)	64
5.4 Consumption of Nitrate During MEOR Process (Core #6)	65
5.5 Permeability Reduction During MEOR Processes (Core #6)	66
6.1 Fieldwide Cumulative Water Production	69
6.2 SEVVSU Environment of Deposition	70

ABSTRACT

The objective of this project is to perform a microbial enhanced oil recovery field pilot in the Southeast Vassar Vertz Sand Unit (SEVVSU) in Payne County, Oklahoma. Indigenous, anaerobic, nitrate reducing bacteria will be stimulated to selectively plug flow paths which have been preferentially swept by a prior waterflood. This will force future flood water to invade bypassed regions of the reservoir and increase sweep efficiency.

This report covers progress made during the second year, January 1, 1990 to December 31, 1990, of the Microbial Field Pilot Study project. Information on reservoir ecology, surface facilities design, operation of the unit, core experiments, modeling of microbial processes, and reservoir characterization and simulation are presented in the report.

To better understand the ecology of the target reservoir, additional analyses of the fluids which support bacteriological growth and the microbiology of the reservoir were performed. The results of the produced and injected water analysis show increasing sulfide concentrations with respect to time.

In March of 1990 Mesa Limited Partnership sold their interest in the SEVVSU to Sullivan and Company. In April, Sullivan and Company assumed operation of the field. The facilities for the field operation of the pilot were refined and implementation was begun.

Core flood experiments conducted during the last year were used to help define possible mechanisms involved in microbial enhanced oil recovery. The experiments were performed at SEVVSU temperature using fluids and inoculum from the unit.

The model described in last year's report was further validated using results from a core flood experiment. The model was able to simulate the results of one of the core flood experiments with good quality.

Additional efforts at improving the quality of the reservoir description through computer simulation resulted in a history match of the cumulative water production within 5% of the observed values. Individual wells have some variation that suggests further improvements can be made.

1. ECOLOGY OF THE RESERVOIR

V. Bhupathiraju, P. Sharma, M.J. McInerney, R.M. Knapp

1.1 INTRODUCTION

Microbially enhanced oil recovery (MEOR) processes require that microorganisms, either indigenous or injected, anaerobically metabolize added nutrients and produce useful products such as gases, biosurfactants, polymers, etc., under the environmental conditions that exist in the reservoir (Clark et al., 1981, McInerney and Westlake, 1990). Therefore, it is necessary that the chemical composition of the brines be determined, and the ecological and physiological factors governing the microbial ecology of the reservoir be evaluated before any MEOR process is initiated. It is also necessary to determine the nutrient source that will best stimulate the desired microbial growth and to examine which type of microbial activity would achieve the maximum effect in enhanced recovery of oil. In addition, a thorough understanding of the physiology and metabolism of the microorganisms native to the oil reservoir is essential for predicting and interpreting the success of a MEOR project.

Our research over the past several years has focused on the use of indigenous microorganisms and their metabolic products to improve volumetric sweep efficiency. The procedure involves the addition of a nutrient mixture to stimulate the growth of microorganisms in highly permeable regions saturated with water. The growth of microorganisms in these regions blocks the pores to immobilize the channelling water, and improve the volumetric sweep efficiency and recover additional oil.

As an ongoing part of the MEOR field pilot study in the Southeast Vassar Vertz Sand Unit (SEVVSU) in Payne County, Oklahoma: a) chemical analyses of the brines were performed on a routine basis, b) physiologically important groups of bacteria in the brines were enumerated and c) five strictly anaerobic and obligately halophilic bacteria isolated from the brines in the pilot area were characterized.

1.2 MATERIALS AND METHODS

Description of the Study Area

The Southeast Vassar Vertz Sand Unit (SEVVSU), is located 10 miles southwest of Stillwater, in Payne County, in the Oklahoma Northern Shelf Area (Figure 1.1). The Vertz Sand Unit belongs to the Wabaunsee group, is Pennsylvanian in age, and is productive at 1800 feet true vertical depth. Geological studies indicate that the Vertz sandstone was formed by a meandering braided stream depositional system and, that it is a well-ordered sandstone with little vertical permeability. A net isopach map of the SEVVSU reservoir is shown in Figure 1.2.

The field was discovered in 1966 and was operated on primary production until 1974. In 1974, a line drive water flood was initiated starting from the southwest portion of the reservoir (wells 7-6, 5-2, and 4-1) and proceeding in a northeasterly direction. In November, 1990, wells 3-3, 7-3, 7-5, and 9-2 were actively injecting water. All wells behind the active injectors in the southwest portion of the reservoir were provided only sufficient water to maintain

enough pressure to insure that the flood front moved in a northeasterly direction. A source well for "make-up" waterflood injection brine produces water from a shallow formation.

The reservoir has sheet like elongated geometry and dips gently to the southwest (Figure 1.2). An aquifer exists to the west and southwest. A flow barrier has been hypothesized to exist between the northern and the southern sections of the reservoir. [This permeability barrier is indicated by the dashed line north of well 5-1 and angled to the northeast through the northwest quarter of section 13 (Figure 1.2).] This barrier was identified by a dry hole in this region and by the lack of communication of the flood waters across the barrier.

The proposed field pilot test is planned in the Southwest Quarter of Section 13 behind the line drive waterflood injectors. Wells 5-1, 5-2, and 7-1 will be converted to production wells and well 7-2 will be the injector for the pilot. The drawdown of fluids to the west caused by the above three production wells and the active line of injectors to the northeast is expected to confine all of the fluid injected into well 7-2 to the pilot area. The plan is to inject nutrient slugs into the injection water stream of well 7-2, with a brine spacer separating each nutrient slug. After the nutrient treatment cycle, water flooding will continue during the length of the test. Based on the current interpretation of the paleocurrent direction, the preferential flow path is believed to be from 7-2 to 7-1. If the microbial processes work as expected, the permeability in this area will be reduced by the in situ growth of the microorganisms. This should then divert flow to wells 5-1 and 5-2.

Sampling Procedure

Brine samples were periodically collected from several locations in the SEVVSU reservoir. The sampling sites included the waterflood brine source well, the injection pump manifold, wells 1A-1, 1A-3, 1A-7, 1A-9, 5-1, 7-2, 8-2, and 8-3. Samples from the pump manifold represent a composite of the brine from the source well and coproduced brine from the Vassar reservoir. Samples from wells 1A-1, 1A-3, 1A-9, 5-1, 7-2, 8-2, and 8-3 represent a mixture of the connate reservoir water and the source well water used in the water flood. Water produced from well 1A-7 is believed to be native reservoir brine. Fluids were allowed to flow for several minutes before sampling. During this time pH, temperature, and the H₂S concentration of the brine were measured. Samples were collected in sterile two-liter Schott (Bellco Glass, Inc., Vineland, N.J.) bottles. In most cases, each bottle was allowed to overflow for 20-30 seconds to avoid the introduction of oxygen into the samples. Bottles were stoppered, taken back to the laboratory, flushed with oxygen-free nitrogen and analyzed within four hours for bacterial numbers. The samples were stored at 4°C until all the analyses were completed.

Chemical Analyses

Salinity, hardness, alkalinity, iron, sulfide, nitrite and nitrate analyses were performed using Hach chemical analysis kits (Hach Chemical Co., 3rd eds. 1975.). Specific gravity, total dry residues and suspended solids were determined using standard procedures (American Public Health Association, 16th eds., 1985). Sulfate analyses were performed by barium precipitation (Hach Chemical Co., 3rd eds. 1975.). Hydrogen sulfide was determined colorimetrically

(Tanner, 1989). Known amounts of NaCl, sulfate and sulfide were added to brine samples to test the accuracy and reliability of the salinity, sulfate and sulfide analyses, respectively.

Bacteriological Analyses

All enumeration studies were done by the most probable number (MPN) technique (Cochran, 1950). The MPN numbers were estimated using three tubes per dilution (Banwart, 1981). All media used in the enumeration studies contained 15% w/v NaCl. Aerobic and anaerobic heterotrophic bacteria were enumerated using medium containing plate count broth (Knapp et al., 1989). Anaerobic molasses nitrate-using bacteria were enumerated using molasses-ammonium nitrate medium (Knapp et al., 1989). Sulfate-reducing bacteria were enumerated using API-RST medium (Tanner et al., 1985). Methanogenic bacteria were enumerated using mineral salts medium containing 10 mM each of, acetate, methanol, and formate and with a 80% H₂:20% CO₂ (20 psi) gas phase. Methods for preparation and use of anaerobic media were those of Bryant (1972) as modified by Balch and Wolfe (1976). All tubes were incubated at 35°C for 45 days or until no more growth was observed. Growth of aerobic heterotrophs, anaerobic heterotrophs and molasses-nitrate users was indicated by turbidity. Growth of sulfate reducers was indicated by turbidity and the formation of a black FeS precipitate. Growth of methanogens was indicated by turbidity and production of methane. All tubes showing growth were examined by phase contrast microscopy.

Isolation and Culture Methods

Several anaerobic halophilic bacteria were isolated from the brines. Anaerobic heterotrophic halophiles were isolated by serially diluting brine samples in 15% saline solution and plating them on plate count agar with 15% NaCl. Plates were incubated anaerobically at room temperature. Isolated colonies were restreaked several times to obtain pure cultures. Anaerobic nitrate-using halophiles were enriched in molasses nitrate medium with 15% NaCl. These enrichments were serially diluted and agar roll tubes with molasses nitrate medium with 15% NaCl were inoculated. Several isolated colonies were selected and transferred to similar medium. Seven anaerobic heterotrophic halophiles and thirty anaerobic nitrate-using halophiles were isolated. Of these, four anaerobic heterotrophic halophilic strains designated VS-732, VS-751, VS-752, VS-511, and one molasses-using halophilic strain designated TTL-30 were selected for further studies. Molasses nitrate medium with 15% NaCl was modified by reducing the NaCl concentration to 12%, deleting molasses, including glucose (5%, w/v), casamino acids (1%, w/v) and yeast extract (1%, w/v), and a gas phase of 80% N₂:20% CO₂ to grow and maintain all the isolates. For experiments requiring a medium prepared without CO₂, bicarbonate was replaced with PIPES (piperazine-N,N'-bis[2-ethanesulfonic acid]) dipotassium salt (1.5 g/l). Vitamins (Balch and Wolfe 1976) were added to culture medium whenever complex medium was not used. Cultures were routinely checked under phase contrast microscope to insure purity.

Growth and Metabolic Characteristics

All experiments were done in duplicate and the results represent mean values. The ability of the isolated strains to utilize different substrates were tested by replacing yeast extract, casamino acids, and glucose with the test compound, at 10 mM (unless otherwise indicated) and comparing the growth ($A_{660\text{nm}}$) and the amount of acetate produced, with that obtained in uninoculated control tubes with each substrate. The ability of the isolates to utilize amino acid mixtures was also tested. The amino acid combinations tested included the following: alanine-glycine, leucine-proline, isoleucine-tryptophan, valine-ornithine, phenyl alanine-leucine and histidine-sarcosine. The effect of the gas phase on the growth of the isolates was tested by changing the gas phase from 80% N_2 :20% CO_2 to 80% H_2 :20% CO_2 . The ability to use carbon monoxide was determined using different gas phase concentrations (100% CO , 75% CO :25% N_2 , 50% CO :50% N_2 , 25% CO :75% N_2). The effect of external electron acceptors on the growth of the isolates was tested in medium with glucose as an electron donor. Compounds tested as electron acceptors included elemental sulfur, sodium sulfate, sodium thiosulfate, sodium sulfite, sodium nitrate, and sodium nitrite at a concentration of 0.3%(w/v).

Miscellaneous Tests

Gram staining was performed using both heat-fixed smears and smears fixed with acetic acid (Dussault, 1955). Antibiotic susceptibility tests were performed by adding various filter-sterilized antibiotics to the growth medium. Antibiotics tested included chloramphenicol, tetracycline, penicillin, cyclohexamide, each at 10 $\mu\text{g/ml}$. The effect of sodium azide on growth, at 50 $\mu\text{g/ml}$ was also tested. Susceptibility to the above inhibitors was determined by comparison of growth at A_{660} in medium containing the inhibitor, to controls that lacked it.

Analytical Techniques

Growth was followed by measuring the increase in absorbance at 660 nm using a Bausch and Lomb Spectronic 21 Spectro-photometer. Microscopic examinations were performed using an Olympus Photomicrographic System Model DM-10AD phase contrast microscope. Glucose was measured colorimetrically by the glucose oxidase method (Sigma Chemical Co., St Louis, MO.) using a Beckman DU 64 Spectrophotometer. Volatile fatty acids and alcohols were analyzed with a Varian Model 3400 series Gas Chromatograph using a Carbopack c/o 3% Carbowax 20m/0.1% H_3PO_4 , 30"x1/4" ODx4mm ID glass column operating at a temperature of 130°C and 60°C respectively. The operating temperatures for injector, and detector were 170°C, 175°C respectively. Nitrogen was used as the carrier gas at 55 ml/min. Samples for volatile fatty acids were acidified by adding 0.2 ml of 25% H_3PO_4 to 0.8 ml of sample. A 1 μl injection volume was used for the analysis of fatty acids and alcohols. Fatty acid analyses were also performed using a high-pressure liquid chromatograph, equipped with a Bio-Rad, 300x7.8mm Aminex HPX-87H column and an isocratic mobile phase of 0.016 N H_2SO_4 at a flow rate of 0.9 ml/min. Hydrogen was analyzed using a RGA 3 Reduction Gas Analyzer fitted with a 3'x1/8" column packed with 60/80 mesh spherocarb, operating at temperature of 90°C. The detector temperature was set at 264°C. Nitrogen was used as the carrier gas at 20 ml/min.

CO₂ and CH₄ were measured with a gas chromatograph equipped with a thermal conductivity detector and a Poropak Q column (Supelco, Inc.) (Jenneman et al., 1986). All gas analyses were performed using gas tight syringes. Calibration curves for gases were prepared by adding high purity gases with a gas tight syringe to 160ml serum bottles flushed with oxygen free nitrogen and sealed with a black rubber stopper. All products were identified and quantified by comparison of retention times and peak areas with those of known standards. Identification of fatty acids and alcohols was also confirmed by the addition of internal standards.

1.3 RESULTS

Chemical Analyses of the Brines

Since a thorough understanding of the fluids in the reservoir is essential for initiating a microbially enhanced oil recovery process, chemical analyses were performed on a routine basis, to provide a description of the dominant chemical species in the brines. The chemical compositions of the brines from SEVVSU reservoir are shown in Tables 1.1 and 1.2. All brines were highly saline with total dry residue ranging from about 13% (w/v) for the source well, 15 to 19% for the water flooded portion of the reservoir (wells 1A-1, 1A-9, 8-2, and 8-3), to over 20% for well 1A-7. Salinity as sodium chloride ranged from 11% for the source well to over 19% for well 1A-7. The brines from the injection manifold, the pilot area (wells 7-2 and 5-1), and the water flooded portion of the reservoir had intermediate salinities ranging from 14 to 16%, except for well 8-3 which was around 18%. The brines contained high levels of divalent cations, particularly calcium, as indicated by the hardness data, ranging from 1 to 3%. The brines also contained low levels of suspended solids (0.2 to 0.3%). Moderate levels of alkalinity were detected in most of the brines, indicating the presence of carbonates. Detectable levels of iron and nitrate were present in all brines, however little or no nitrite or phosphate were detected. The temperature of the brines ranged between 20° and 30°C, and the pH was close to neutrality.

The sulfate and sulfide content of the brines were monitored to assess the potential for anaerobic corrosion problems in the reservoir. Sulfate and sulfide concentrations are presented chronologically in Table 1.3 with sulfate concentrations from April of 1989 (sulfides were not measured). Consistent with the previous history of the reservoir, high levels of sulfate were detected in the source well. The brines from the injection manifold, which is an aggregate of the water from the source well and water reused in the water flooding process, generally contained high levels of sulfate when compared to the brine from the water flooded portion of the reservoir. Brines from well 1A-9 had rather high levels of sulfate and sulfide when compared to brines from other portions of the reservoir which had been water flooded. Samples from well 1A-7 which were previously (1987) devoid of both sulfate and sulfide recorded substantial increase in the levels of sulfate (from <1 to 230 mg/ml) and sulfide (from <0.1 to 0.8 mg/ml). The brines from the pilot area (well 7-2), which is presently not actively being water flooded, had high levels of sulfate during the first two samplings in 1989. The sulfate levels in the brines sampled in July of 1989 were lower than the previous two samplings in April 1989 and June 1989. In contrast, a substantial increase in sulfide concentrations was observed.

The source of sulfate in the waterflooded area of the field is the brine from the source well. As the concentration of the source well brine increases the sulfate concentration also increases. The increases of sulfate and sulfide in the 1A-7 produced water indicate arrival of the floodfront at this location. The decrease in sulfate coupled with the increase in sulfide at the 7-2 may indicate metabolic activity by sulfate reducing bacteria in the vicinity of the pilot. During the field pilot ammonium nitrate will be injected with the carbohydrate source to limit growth of sulfate reducing bacteria and the associated production of hydrogen sulfide (Jenneman et al, 1986).

Bacteriological Analyses

Because of the high salinities of the brines, it was important to determine whether the brines contained indigenous microbial populations which could be useful in enhanced oil recovery. Physiologically important groups of bacteria were routinely enumerated using a three tube most probable number method (Table 1.4). Aerobic heterotrophic bacteria, anaerobic heterotrophic bacteria, anaerobic molasses nitrate-using bacteria, and sulfate reducing bacteria were enumerated on three separate occasions. Methanogenic bacteria were enumerated on two separate occasions.

Anaerobic heterotrophic bacteria (< 1 to 4.6×10^3) were generally more numerous than aerobic heterotrophic bacteria (< 1 to 7.5×10^2). Anaerobic molasses nitrate-using bacteria were consistently found in all brines and in higher concentrations (< 1 to 1.1×10^5) than the other tested groups of bacteria. Sulfate reducing bacteria were present in all the brines, however, in lower numbers (< 1 to 4.6×10^2) than aerobic heterotrophic bacteria, anaerobic heterotrophic bacteria, or anaerobic molasses nitrate-using bacteria. Relatively high numbers of sulfate reducing bacteria were present in the brines from the source well and the injection manifold, which is consistent with the amount of sulfate and sulfide detected in these brines. Brines from well 1A-7 which did not previously have any sulfate reducing bacteria or sulfide, had a substantial increase in sulfate reducing bacteria. Substantial levels of methanogenic bacteria ranging from 2 to 46/ml were detected in only two of the tested brines, namely the brines from the injection manifold and well 7-2. The brines from the source well and the water flooded portions of the reservoir had few or no detectable methanogens. All tested groups of bacteria were generally present in higher concentrations in the brines from the injection manifold. In comparison to the other brines from the water flooded portions of the reservoir, brines from well 7-2 had higher levels of all the tested groups of bacteria, with the exception of aerobic heterotrophic bacteria. Relatively low numbers of all the tested groups of bacteria were observed in all the brines sampled during February of 1990.

In an attempt to enrich for, and isolate halophilic methanogens, culture media showing turbidity and methane production were transferred into fresh methanogenic medium containing either H_2/CO_2 , formate or acetate as the substrate. Tubes incubated at $35^\circ C$ for 4 weeks were routinely monitored for growth and methane production. Although methane production was observed in all the tubes, visible growth was observed only in tubes containing acetate as the substrate. Tubes containing H_2/CO_2 as the substrate, had substantial methane production and pressure decreases (under vacuum in some cases), indicating the utilization of H_2/CO_2 . After repeated re seeding of H_2/CO_2 to these enrichments, substantial methane production was again

observed (data not shown); however, absorbance increase was low (<0.15 at 660 nm). The same was the case for tubes containing formate as the substrate. Attempts to isolate these bacteria in pure culture were not successful and further studies on these bacteria were not performed. The enrichments, however, are being maintained for future studies.

Cellular Growth and Metabolic Characteristics of the Halophilic Bacteria Isolated from the Brines

Four anaerobic heterotrophic halophiles designated as VS-732, VS-751, VS-752, VS-511, and one molasses nitrate-using halophile designated TTL-30 were characterized. Strains VS-732, VS-751 and VS-752, and VS-511 were isolated from wells 7-3, 7-5, and 5-1 respectively. All five were Gram-negative, non-sporeforming rod shaped bacteria. Cells of strains VS-751 and VS-752 were straight rods, appearing single, in pairs, occasionally as long chains, and measuring $0.7\text{-}0.8 \times 2\text{-}3.3 \mu\text{m}$, and $0.3\text{-}0.4 \times 2.6\text{-}4 \mu\text{m}$, respectively. Cells of strains VS-732 and VS-511 were relatively smaller, occurring either singly or in pairs, with dimensions of $0.5\text{-}0.8 \times 0.7\text{-}1.9 \mu\text{m}$ and $0.5\text{-}0.7 \times 1.3\text{-}2.6 \mu\text{m}$, respectively. Cells of strains VS-732, VS-751, and VS-752 were motile, while that of strains VS-511 and TTL-30 were non-motile.

All five strains were unable to grow in an aerobic medium and required high concentrations of NaCl for growth. At least 6% NaCl (w/v) was required for the growth of all the strains. At NaCl concentrations less than 6% the cells lysed. Strains VS-732 and VS-752 grew at NaCl concentrations ranging between 6 and 25%, with optimum growth occurring at 6% and 9 to 12%, respectively (Figure 1.3 and Figure 1.5). The range of NaCl concentrations for the growth of strains VS-751 and VS-511 was between 9 and 18%, with optimum growth occurring at 12% (Figure 1.4 and Figure 1.6). The optimal NaCl requirement for strain TTL-30 was 15%, with growth occurring between 6 and 22% (Figure 1.7). None of the strains grew at NaCl concentration greater than 25%. The optimum temperature for growth of strains VS-751, VS-752, and TTL-30 was between 23 and 45°C, and for strains VS-732, and VS-511 was between 23 and 37°C. The doubling time for strains VS-751, VS-511, and VS-732 was 7.2, 8, and 11 hours, respectively, and that for strains VS-752 and TTL-30 was around 10 hours. All strains were catalase and oxidase negative and inhibited by chloramphenicol, tetracycline, and penicillin, but not cyclohexamide or azide.

The effect of added electron acceptors on the growth of the strains was tested in medium containing glucose as the carbon source. None of the tested electron acceptors appeared to stimulate the growth of the strains, except for sulfite which stimulated the growth of strain TTL-30. Nitrate neither stimulated nor inhibited the growth of the strains. Elemental sulfur, sulfate, thiosulfate, and nitrite inhibited the growth of all the strains. The change of gas phase from N_2/CO_2 to H_2/CO_2 in tubes containing glucose as the carbon source and no added electron acceptors, stimulated the growth of strains VS-511 and VS-732, but completely inhibited the growth of strain TTL-30. The presence of a carbon monoxide gas phase at any of the tested concentrations in medium with and without glucose, completely inhibited growth of all the strains.

Energy sources for the strains were tested by adding an individual carbon source at 10 mM (unless otherwise indicated) to the mineral salts medium containing 12% NaCl, and 0.025% yeast extract. A variety of compounds were able to serve as energy sources (Table 1.5).

Substrate utilization was indicated by both growth (A660) and product (acetate) formation. Substrates utilized by all the strains included arabinose, fructose, galactose, glucose, inulin, mannose, sucrose, and trypticase. Substrates not utilized by any of the strains included the following: ascorbate, crotonate, dihydroxybenzoate, gallic acid, methanol, propionate, phenoxyacetate, and resorcinol. The ability of the strains to utilize amino acid mixtures was also tested. Amino acid mixtures such as alanine-glycine, leucine-proline, isoleucine-tryptophan, valine-ornithine, phenylalanine-leucine, and histidine-sarcosine also were not utilized by any of the strains.

The glucose fermentation products of the strains were determined in 160 ml serum bottles containing a mineral salts medium with 1% (w/v) glucose, 0.025% yeast extract and a gas phase of nitrogen, Table 1.6. Analysis of culture fluids after 96 hours of incubation at 35°C, by gas and liquid chromatography indicated the following products: ethanol, acetate, formate, and CO₂/H₂ in the case of strains VS-732, and VS-751; acetate, ethanol, and CO₂/H₂ in the case of strains VS-752 and TTL-30; and ethanol, acetate, and CO₂/H₂ in the case of strain VS-511. For strain VS-732 an unidentified peak was detected in HPLC chromatograms, as a product of glucose metabolism. Lactate, malate, succinate, butyrate, propionate, valerate, isovalerate, and caproate were not detected in any of the culture fluids. Based on the amounts of substrate used and the products formed, the following fermentation balances were derived:

Strain VS-732:

Strain VS-751:

Strain VS-752:

Strain VS-511:

Strain TTL-30:

1.4 DISCUSSION

Brines from most mid continent United States oil reservoirs contain high concentrations of NaCl, thus tolerance to NaCl is one of the most important characteristics needed for organisms to be useful in MEOR. Bacteria are known which grow at high NaCl concentrations (approximately 32%) (Kushner 1978). However, it would be preferable to have organisms which can grow over wide ranges of salinities. Several halotolerant anaerobic bacteria have recently been described (Rodrigues-Valera, 1988), however, relatively little is known about obligately anaerobic, moderately or extremely halophilic bacteria. We have isolated and characterized five anaerobic obligately halophilic bacteria from SEVVSU brines capable of

growing in highly saline environments. Based on the morphological characteristics, gram reaction, ability to grow at a wide concentration range of NaCl, optimal salt requirement for growth, ability to utilize a variety of substrates, and fermentative products produced from glucose, these strains seem to be very different from previously reported anaerobic halophiles such as *Clostridium lortetii* (Oren, 1983), *Halobacteroides halobius* (Oren et al., 1984), *Haloanaerobium prevaleans* (Zeikus et al., 1983) and *Halobacteroides acetoethylicus* (Rengpipat et al., 1988). The ability to grow at high salt concentration ranges, use a fermentable carbohydrate substrate, produce polymer and substantial amounts of gas, make these strains suitable candidates for microbially selective plugging processes in hypersaline environments. Since these bacteria are all obligately anaerobic and halophilic, they will not survive outside of the reservoir and do not pose any serious health risk.

REFERENCES

- American Public Health Association, American Water Works and Water Pollution Control Federation: Standard Methods for the Examination of Water and Waste Water. Sixteenth Edition, American Public Health Association, Washington, DC (1985) 92-100, 856-859.
- Balch, W. E., and Wolfe, R. S., 1976. "New Approach to the Cultivation of Methanogenic Bacteria: 2-Mercaptoethanesulfonic acid (HS-CoM)-dependant Growth Of Methanobacterium ruminantium in a pressurized Atmosphere." Appl. Environ. Microbiol. 32:781-791.
- Banwart, G.J., 1981. Basic Food Microbiology. AVI Publishing Co., Westport.
- Bryant, M. P., 1972. Commentary on the Hungate Technique for Culture of Anaerobic Bacteria. Amer. J. Chem. Nutr. 25: 1324-1328.
- Clark, J.B., Munnecke, D.M., and Jenneman, G. E., 1981. In Situ Microbial Enhancement of Oil Production. Dev. Ind. Microbial. 22:695-701.
- Cochran, W. G., 1950. Estimation of Bacterial Densities by means of the "Most Probable Number". Biometrics 6, 105-116.
- Hach Chemical Co. 1985. Hach Water and Wastewater Analysis Procedure Manual, 3rd Edition. Hach Chemical Co., Ames, IA.
- Jenneman, G.E., McInerney, M.J., and Knapp, R.M., 1986. Effect of Nitrate on Biogenic Sulfide Production. Appl. Environ. Microbiol. 51:1205-1211.
- Knapp, R.M., McInerney, M.J., and Menzie, D.E., Raiders, R.A., 1989. Microbial Field Pilot Study, Final Report, DCE/BC/14084-6, National Technical Informational Services, Springfield, VA.
- Kushner, D.J., 1978. "Life in High Salt and Solute Concentrations: Halophilic Bacteria," in Microbial Life in Extreme environments, D.J. Kushner (eds.). Academic Press, New York, pp317-368.
- McInerney, M.J., and Westlake, D.W.S., 1990. "Microbially Enhanced Oil Recovery" in Microbial Mineral Recovery, H. L. Ehrlich and C. L. Brierley (eds.). McGraw-Hill Publishing Company, New York, pp 409-445.
- Oren, A., 1983. Clostridium lortetii sp. nov. a halophilic obligately anaerobic bacterium producing endospore with attached gas vacuoles. Arch. Microbiol. 136:42-48.

Oren, A., Weisburg, W.G., Kessel, M., Woese, C.R., 1984. *Halobacteroides halobius* gen. nov., sp. nov., a moderately halophilic obligatory anaerobic bacterium from the bottom sediments of the dead sea. *System. Appl. Microbiol.* 5:58-70.

Rengpipat, S., Langworthy, T.A., and Zeikus, G.J., 1988. *Halobacteroides acetoethylicus* sp. nov., a New Obligately Anaerobic Halophile Isolated from Deep Subsurface Hypersaline Environments. *System. Appl. Microbiol.* 11:28-35.

Rodriguez-Valera, F., 1988. Halophilic bacteria, Volume I, CRC Press, Boca Raton, FL, pp 1-29.

Tanner, R.S., Haack, T.K., Semet, R.F., and Greenley, D.E., 1985. A Mild Steel Tubular Flow System for Biofilm Monitoring. *Proceedings of the United Kingdom National Academy of Corrosion Engineers Corrosion '85*, Harrogate, UK, 259-269.

Tanner, R. S., 1989. Monitoring Sulfate-Reducing Bacteria: Comparison of Enumeration Media. *J. Micro. Methods.* 10: 83-90.

Zeikus, J.G., Hegge, P.W., Thompson, T.E., Phelps, T.J., Langworthy, T.A., 1983. Isolation and description of *Haloanaerobium prevalens* gen. nov., sp. nov., an obligately anaerobic halophile common to Great Salt Lake Sediments. *Curr. Microbiol.* 9:225-234.

TABLE 1.1 CHEMICAL ANALYSIS OF SEVVSU BRINES

Sample source ^a	Specific gravity	Major components (mg/ml)				
		Total dry residue	Total suspended solids	Total hardness as CaCO ₃	Calcium hardness as CaCO ₃	NaCl salinity
Source well ^c	1.082 ± 0.01	127.5 ± 1.5	1.9 ± 0.3	21.6 ± 0.0	16.2 ± 1.1	117 ± 4.0
Pump manifold ^d	1.102 ± 0.01	166.6 ± 3.8	1.8 ± 0.2	24.5 ± 0.7	17.6 ± 0.4	159 ± 3.7
Well 1A-1 ^d	1.075 ± 0.02	165.7 ± 6.1	2.7 ± 0.5	26.3 ± 0.1	18.2 ± 0.9	161 ± 5.6
Well 1A-7 ^b	1.146	206.0	2.8	32.6	21.9	197
Well 1A-9 ^d	1.079 ± 0.02	170.2 ± 2.1	2.4 ± 0.7	26.8 ± 0.2	18.7 ± 0.8	166 ± 1.4
Well 5-1 ^b	1.090	153	ND	24.6	16.5	143
Well 7-2 ^d	1.110 ± 0.02	165.3 ± 3.3	2.9 ± 0.5	25.8 ± 0.6	18.9 ± 2.3	153 ± 1.0
Well 8-2 ^b	1.046	165	ND	32.6	21.8	158
Well 8-3 ^c	1.126 ± 0.01	189.0 ± 3.7	1.9 ± 0.3	30.2 ± 0.3	22.0 ± 0.5	184 ± 1.7

^aLocation of sample sites are given in figure 2.

^bValues represent results from one determination.

^cValues represent mean ± standard deviation of results from two samplings.

^dValues represent mean ± standard deviation of results from three samplings.
ND, Not determined.

TABLE 1.2 CHEMICAL ANALYSIS OF SEVVSU BRINES

Sample source ^a	pH	Temperature	Trace components (mg/l)			
			Total alkalinity	Iron	Phosphate	Nitrate Nitrite
Source well ^c	6.3 ± 0.3	25 ± 3.2	34 ± 2	10 ± 0	1 ± 0	7.5 ± 2.5 < 0.2 ± 0
Pump manifold ^d	7.1 ± 0.1	28 ± 5.4	80 ± 6	10 ± 0	1 ± 0	6.6 ± 2.3 < 0.2 ± 0
Well 1A-1 ^d	7.0 ± 0.1	26 ± 2.5	147 ± 27	19 ± 9	1 ± 0	6.2 ± 2.1 < 0.2 ± 0
Well 1A-7 ^b	6.7	32	66	30	1	10 < 0.2
Well 1A-9 ^d	6.5 ± 0.3	26 ± 2.5	127 ± 18	18 ± 4	1 ± 0	7.5 ± 2.5 < 0.2 ± 0
Well 5-1 ^b	7.0	25	38	10	1	5 < 0.2
Well 7-2 ^d	6.4 ± 0.4	31 ± 0.5	83 ± 40	46 ± 24	1 ± 0	5.0 ± 0.0 < 0.2 ± 0
Well 8-2 ^b	6.5	21	ND	10	1	5 < 0.2
Well 8-3 ^c	6.7 ± 0.2	25 ± 1.0	43 ± 13	27 ± 5	1 ± 0	5.0 ± 0.0 < 0.2 ± 0

^aLocation of sample sites are given in figure 2.

^bValues represent results from one determination.

^cValues represent mean ± standard deviation of results from two samplings.

^dValues represent mean ± standard deviation of results from three samplings.
ND, Not determined.

TABLE 1.3 CONCENTRATIONS OF SULFATE AND SULFIDE IN SEVVSU BRINES

Sample Source ^a	Concentration (mg/l)					
	June 87 ^b		April 89		June 89	
	Sulfate	Sulfide	Sulfate	Sulfide	Sulfate	Sulfide
Source Well	2430	<0.1	ND	ND	2000	<0.1
Pump Manifold	944	0.3	2850	ND	1050	10.2
Well 1A-1	ND	ND	1425	<0.1	330	16.0
Well 1A-7	<1	<0.1	ND	ND	230	0.8
Well 1A-9	ND	ND	1700	5.0	500	26.0
Well 7-2	780	1.2	2600	1	440	3.6
Well 8-3	ND	ND	1050	<0.1	330	<0.1

^a The location of the sampling sites are given in Fig. 2.

^b Data from Knapp et al., 1990.

ND, Not determined.

TABLE 1.4 NUMBERS OF DIFFERENT GROUPS OF BACTERIA IN SEVVSU BRINES

Sample source ^a	Most probable number (per ml) ^b										
	Aerobic heterotrophic bacteria		Anaerobic heterotrophic bacteria		Sulfate reducing bacteria		Methane producing bacteria		Molasses nitrate-using bacteria		
	J-89	F-90 Jn-90	J-89	F-90 Jn-90	J-89	F-90 Jn-90	F-90 Jn-90	F-90 Jn-90	J-89	F-90 Jn-90	
SW	150	<1 110	110	<1 210	110	<1 150	-	<1	46	<1 110	
PM	460	2 750	2400	1100 4600	21	240 460	2	21	110000	7500 11000	
Well 1A-1	210	2	46	4	23	<1	-	-	4	46	
Well 1A-3		2		460		110	-	-		460	
Well 1A-7	110		110		21		-	-	2		
Well 1A-9	240	2 460	43	2 46	9	4 15	-	9	210	460 430	
Well 7-2	24	2 23	750	460 1100	75	46 110	4	46	2400	1100 2100	
Well 8-3	110		110		15				24000		

^a The location of the sampling sites are shown in Fig 1.2.

^b MPN values, three tubes per dilution, were determined using media described in text. Incubation period for all cultures was 6 weeks except for methanogens which was 8 weeks. J-89, July 1989; F-90, February 1990; Jn-90, June 1990.

Abbreviations: SW, source well; PM, pump manifold; -, Not detected.

TABLE 1.5 SUBSTRATE UTILIZATION BY ANAEROBIC HALOPHILES ISOLATED FROM SEVVSU BRINES

Substrate ^{a, b}	Acetate produced ^c (mM)				
	VS-732	VS-751	VS-752	VS-511	TTL-30
Arabinose	1.7 ± 0.1 (0.19) ^d	4.6 ± 0.2 (0.28)	6.8 ± 0.4 (0.25)	3.7 ± 0.2 (0.22)	3.0 ± 0.6 (0.22)
Cellobiose	0.9 ± 0.1 (0.14)	3.7 ± 0.2 (0.31)	ND (0.19)	2.6 ± 0.3 (0.23)	-
Ethylene glycol	-	-	-	1.3 ± 0.2 (0.18)	-
Formate	-	-	0.7 ± 0.3 (0.15)	-	-
Fructose	2.7 ± 0.3 (0.25)	3.4 ± 0.2 (0.33)	2.4 ± 0.3 (0.22)	4.3 ± 0.3 (0.26)	7.3 ± 0.4 (0.35)
Fucose	3.5 ± 0.3 (0.22)	-	-	2.5 ± 0.4 (0.20)	NA (0.19)
Galactose	2.1 ± 0.1 (0.18)	3.1 ± 0.2 (0.24)	6.0 ± 0.1 (0.28)	2.8 ± 0.2 (0.25)	4.8 ± 0.4 (0.21)
Glucose	6.9 ± 0.5 (0.30)	5.8 ± 0.4 (0.42)	8.2 ± 0.5 (0.32)	6.4 ± 0.2 (0.35)	8.9 ± 0.8 (0.40)
Glucosamine	-	-	2.3 ± 0.2 (0.18)	ND (0.15)	3.1 ± 0.2 (0.15)
Glycerol	-	-	4.6 ± 0.1 (0.25)	1.0 ± 0.2 (0.16)	4.9 ± 0.3 (0.18)
Inulin	4.1 ± 0.2 (0.28)	5.7 ± 0.3 (0.25)	5.7 ± 0.2 (0.28)	6.2 ± 0.3 (0.24)	5.5 ± 0.5 (0.20)
Lactose	-	1.9 ± 0.1 (0.17)	0.9 ± 0.2 (0.15)	ND (0.27)	-
Maltose	4.2 ± 0.1 (0.22)	-	1.5 ± 0.1 (0.19)	5.2 ± 0.4 (0.27)	3.2 ± 0.2 (0.23)
Mannitol	-	-	-	2.6 ± 0.5 (0.23)	-
Mannose	2.5 ± 0.2 (0.19)	3.3 ± 0.2 (0.24)	2.7 ± 0.3 (0.20)	2.1 ± 0.2 (0.22)	5.6 ± 0.2 (0.22)

(continued on next page)

TABLE 1.5 (continued from previous page)

Substrate <i>b</i>	Acetate produced ^c (mM)				
	VS-732	VS-751	VS-752	VS-511	TTL-30
Peptone	2.1 ± 0.2 (0.18)	6.0 ± 0.6 (0.21)	-	ND	9.8 ± 0.4 (0.25)
Pyruvate	-	5.1 ± 0.6 (0.21)	3.9 ± 0.3 (0.19)	1.1 ± 0.1 (0.14)	-
Pyrogallic acid	-	-	1.2 ± 0.2 (0.16)	-	1.6 ± 0.3 (0.14)
Rhamnose	-	-	1.0 ± 0.2 (0.15)	-	-
Sorbose	-	-	-	1.1 ± 0.2 (0.15)	-
Succinate	-	-	5.7 ± 0.5 (0.22)	-	-
Sucrose	3.5 ± 0.3 (0.24)	3.4 ± 0.2 (0.25)	2.6 ± 0.3 (0.22)	4.8 ± 0.6 (0.28)	6.7 ± 0.2 (0.27)
Trypticase	1.5 ± 0.2 (0.15)	1.6 ± 0.2 (0.22)	1.6 ± 0.5 (0.19)	2.3 ± 0.2 (0.18)	7.1 ± 0.6 (0.22)
Xylose	3.3 ± 0.4 (0.25)	-	0.8 ± 0.2 (0.15)	2.2 ± 0.2 (0.19)	-

^a A 2% inoculum grown on the same substrate was employed in all the experiments.

^b Substrate was added at 10 mM to mineral salts medium described in text, except peptone, trypticase and inulin which were added at 1% (wt/vol), 1% (wt/vol), and 1mM respectively. Substrates tested but not utilized include: ascorbate, butyrate, crotonate, dihydroxybenzoate, gallic acid, inositol, lactate, malate, methanol, methionine, propionate, phenoxyacetate, and recorcinol.

^c Acetate production was determined by gas chromatography after five days of incubation at 35°C. Values are corrected for small amounts of acetate formed in medium without substrate. No acetate formation was found in inoculated, autoclaved controls or in uninoculated controls. Values represent mean ± standard deviation of two replicates.

^d Numbers in parenthesis indicate an average of maximum absorbance after five days incubation at 35°C. Abbreviations: -, not utilized; ND, not determined;

TABLE 1.6 GLUCOSE FERMENTATION PRODUCTS OF THE ANAEROBIC HALOPHILES ISOLATED FROM SEVVSU BRINES

Strain ^a	Glucose Consumed (mmol/l)	Products ^b (mmol/l)				%CR	%HR
		Ethanol	Acetate	Formate	CO ₂ ^c		
VS-732 ^d	10.2 ± 0.16	10.5 ± 0.10	7.1 ± 0.32	3.3 ± 0.10	17.7 ± 0.38	4.9 ± 0.59	91 88
VS-751	9.6 ± 0.11	13.1 ± 0.35	5.6 ± 0.19	3.1 ± 0.15	18.5 ± 0.19	5.0 ± 0.38	103 101
VS-752	5.7 ± 0.14	6.0 ± 0.02	8.4 ± 0.33	ND ^g	9.7 ± 0.18	2.1 ± 0.07	112 107
VS-511	10.3 ± 0.20	14.4 ± 0.47	6.9 ± 0.16	ND	18.0 ± 0.27	5.5 ± 0.58	98 102
TTL-30	3.8 ± 0.22	1.6 ± 0.10	6.0 ± 0.18	ND	8.3 ± 0.47	1.3 ± 0.05	102 79

^a Cultures were grown in 160 ml serum bottles containing 30 ml mineral salts medium with 1% (wt/vol) glucose, 0.025% (wt/vol) yeast extract, and a gas phase of nitrogen. Volatile acids and alcohols in the liquid phase, and CO₂ and H₂ in the gas phase were analyzed at the beginning of the experiment and after 96 hrs of incubation at 35°C.

^b Values are corrected for small amounts of products formed in medium without substrate. No product formation or substrate loss was found in inoculated, autoclaved controls or in uninoculated controls. Values represent mean ± standard deviation of two replicates.

^c Values were normalized to 20°C and 1 atmosphere.

^d An unidentified compound has been detected as a product of glucose fermentation. Abbreviations: CR, carbon recovery; HR, hydrogen recovery; ND, Not detected.

FIGURE 1.1 OKLAHOMA GEOLOGICAL REGIONS
(AFTER OKLAHOMA GEOLOGICAL SURVEY, 1972)

S - "Make-up" Injection Water Well

SOUTHEAST VASSAR	Microbially Enhanced
VERTZ SAND UNIT	Oil Recovery Lab:
	Dr. Roy M. Knapp
Isopach Map	
Net Vertz Sand	School of Petroleum and
C.I. = 2 ft.	Geological Engineering
DJG - Nov 20, 1990	
Soc 13-T19N-R1W	University of Oklahoma
Poyne Co., Okla.	Norman, Oklahoma

SCALE 1: 20000.
0.2 0.4 MILE
0.2 0.4 KMS

FIGURE 1.2 NET THICKNESS MAP OF SOUTHEAST VASSAR VERTZ SAND UNIT (SEVVSU)

FIGURE 1.3 EFFECT OF NaCl CONCENTRATION ON THE GROWTH OF STRAIN VS-732. Cells were grown at 35°C in mineral salts medium containing yeast extract, casamino acids, glucose, and the NaCl concentration indicated. After different incubation periods at 35°C the absorbance of the cultures was measured and the growth rates were calculated from the exponential part of the growth curves.

FIGURE 1.4 EFFECT OF NaCl ON THE GROWTH OF STRAIN VS-751. Cells were grown at 35°C in mineral salts medium containing yeast extract, casamino acids, glucose, and the NaCl concentration indicated. After different incubation periods at 35°C the absorbance of the cultures was measured and the growth rates were calculated from the exponential part of the growth curves.

FIGURE 1.5. EFFECT OF NaCl CONCENTRATION ON THE GROWTH OF STRAIN VS-752. Cells were grown at 35°C in mineral salts medium containing yeast extract, casamino acids, glucose, and the NaCl concentrate indicated. After different incubation periods at 35°C the absorbance of the cultures was measured and the growth rates were calculated from the exponential part of the growth curves.

FIGURE 1.6 EFFECT OF NaCl CONCENTRATION ON THE GROWTH OF STRAIN VS-511. Cells were grown at 35°C in mineral salts medium containing yeast extract, casamino acids, glucose, and the NaCl concentration indicated. After different incubation periods at 35°C the absorbance of the cultures was measured and the growth rates were calculated from the exponential part of the growth curves.

FIGURE 1.7 EFFECT OF NaCl CONCENTRATION ON THE GROWTH OF STRAIN TTL-30. Cells were grown at 35°C in mineral salts medium containing yeast extract, casamino acids, glucose, and the NaCl concentration indicated. After different incubation periods at 35°C the absorbance of the cultures was measured and the growth rates were calculated from the exponential part of the growth curves.

2. SURFACE FACILITIES DESIGN

J.L. Chisholm, R.M. Knapp, M.J. McInerney, D.E. Menzie

The surface facilities design associated with the Microbial Field Pilot Study has significantly changed during the last year. Primarily, the design has been simplified. The surface facilities will lift and collect fluid from the production wells, separate the produced fluid, and mix and inject the nutrient mixture used in the pilot.

The injection well, 7-2, has been recompleted with a packer run on a 2.5 inch tubing string set immediately above the perforations in the Vertz sandstone. The well was worked over and acidized to restore injectivity. The well was returned to injection December 13, 1990, with an injection pressure of 653 psig at the surface. A 10 inch, 125 micron Nowata filter was installed on the injection well to remove iron sulfide particulate matter in the injected brine. Initial injection rate was around 170 bbl per day. At the injection rate of about 300 bbl per day at 750 psig surface pressure is expected.

An overall plan of the injection well facility is shown in Figure 2-1. The SEVVSU triplex pump is the existing injection pump for the field. This pump will provide brine for preparing the nutrient mixture and the injection of brine spacers between treatments of the nutrient mixture. A 500 bbl "frac" tank will be used to mix the brine water, molasses, and ammonium nitrate and store the nutrient mixture during injection. A small pump will constantly circulate this mixture to maintain uniform consistency. A "Y-trap" strainer will be used to remove large particulate matter from the mixture. The Halliburton Polyflood pump will be used to inject the fluid into the injection well flow line. As shown on the figure, flow from the Halliburton pump and the SEVVSU triplex pump will combine in the flow line. The total fluid volume injected will be metered at the well head. The surface injection pressure will also be monitored. Any drop in injectivity will be evaluated to determine if wellbore facial plugging has occurred. Prior to injection, the fluid will be pumped through two 30 inch 125 micron filters.

Halliburton Research and Technical Services Department has loaned the project a refurbished Polyflood injection pump unit for the field pilot study. The unit is a self contained, skid mounted, 440 three-phase motor with variable eddy current drive connected to a triplex pump. The pump will be able to pump up to 6 gallons/ minute of the nutrient mixture into the flowline. The maximum expected injection pressure of 800 psi and mixture viscosity of 20 cp are well within the pump's capacity. The skid is equipped with two 30 inch filtration units downstream of the triplex pump.

Figure 2-2 is the plan for a nutrient injection treatment. One hundred barrels of SEVVSU brine will be pumped into the "frac" tank. Approximately 6.5 tons of ammonium nitrate prills (pelletized ammonium nitrate) will be added to the tank using a grain auger. The tank will be circulated ("rolled") using a gas powered pump until the ammonium nitrate is completely dissolved.

Twenty-two and a half tons (90 to 93 bbl) of molasses will be delivered and pumped into the "frac" tank. The molasses truck's unloading pumps can completely unload the truck and avoid the need to heat the molasses or add viscosity reducers to it. The liquid will be circulated until the mixture is completely mixed. In the "frac" tank, the mixture will be 43% molasses,

10% ammonium nitrate, and 47% brine. The liquid viscosity should be about 20 centipoise. Recirculation will continue throughout the injection treatment.

Using the Halliburton pump, the "frac" tank mixture of nutrients and brine will be pumped into the injection line. The filters are connected so that they can be used individually. This will allow a filter element to be changed without stopping injection. A 50 psi pressure drop across the filters will indicate the need to change the filter element. During the injection, the filter elements will be changed as needed.

After mixing with 350 bbl of simultaneously injected brine from the SEVVSU pump in the Well 7-2 tubing, the nutrient concentration should be about 20% molasses/4.6% ammonium nitrate at the perforations. This will be followed by a brine pad of about 1650 bbl assuming an injection rate of 300 bpd injected over 5.5 days. When the nutrients disperse in this brine the nutrient concentration will be about 4.4% molasses/1.0% ammonium nitrate.

Figure 2.3 is a schematic of the field pilot gathering system. Wells 5-1, 5-2, and 7-1 are the producing wells. Produced fluids will be returned to the tank battery through the flowlines that served these wells when they were injectors. Fluids will be combined at the manifold. Gauges to measure surface tubing pressure and meters to record total fluid volume are installed on wells 5-1 and 7-1. Well 5-2, located in the middle of a wheat field and with some accessibility problems, is metered and gauged at the manifold. It will not be possible to record bottom hole flowing pressures on the production wells while pumping. As the SEVVSU has almost no produced gas, no regular sampling of gas is planned. The SEVVSU triplex pump, injection line to the 7-2, and the nutrient treatment surface facilities are also shown on this figure.

Figure 2-4 shows the tank battery facilities. The three producing wells' flowlines are connected to a manifold at the tank battery. At the manifold, each well's flow may be isolated so that a portable sampling separator can determine individual well water/oil ratios. As mentioned earlier the 5-2 is metered and gauged at the manifold. Produced fluids from the pilot wells are comingled and separated in a gunbarrel separator. Oil produced from the pilot wells will be stored in two oil tanks to measure the tertiary oil produced. Produced water will be returned to the main water storage tanks for reuse in the SEVVSU water flood.

FIGURE 2.1: INJECTION WELL FACILITY

PROCEDURE FOR NUTRIENT TREATMENT INJECTION

1. Add 100 bbl of SEVVSU brine to Frac Tank.
2. Add ~ 6.5 tons of Ammonium Nitrate pellets. Circulate mixture in tank until Ammonium Nitrate is completely dissolved.
3. Molasses Arrives on location.
4. Pump molasses (~ 90 bbl) into Frac Tank. Circulate mixture until Molasses/Brine is fully mixed.
5. Pump Frac Tank mixture of Molasses/Brine into injection line using Halliburton pump while continuing injection from SEVVSU pump (replace filter elements as needed).

Combined injection stream should be about 20% molasses at the sandface.

FIGURE 2.2: PROCEDURE FOR NUTRIENT TREATMENT INJECTION

FIGURE 2.3: SEVVSU PILOT GATHERING SYSTEM

FIGURE 2.4: FACILITIES AT TANK BATTERY

3. THE SOUTHEAST VASSAR VERTZ SAND UNIT (SEVVSU)

J.L. Chisholm, D.J. Garvey, R.M. Knapp, D.E. Menzie

The pilot will be performed in the Southeast Vassar Vertz Sand Unit. Figure 1.1 is a map of the geological regions of the State of Oklahoma (Oklahoma Geological Survey, 1972). As shown on the figure, the Southeast Vassar field is located about 50 miles north northeast of Oklahoma City, Oklahoma. It is located on the northern shelf area of the Anadarko Basin. The Vertz sandstone belongs to the Wabauisee Group of Pennsylvanian age. Well locations for the Southeast Vassar field are shown in Figure 3.1. The field was discovered in 1966. It was unitized in 1974 and a line drive waterflood was initiated soon thereafter. The flood direction is from southwest toward the northeast. As each production well exceeded a 10 to 1 water-oil ratio, it was converted to an injection well. The injection wells behind the active injectors are used to maintain pressure to insure that injected water continues to drive to the northeast. These pressure maintenance wells take little or no water. By 1987, the line of active injector wells was along the east edge of the southwest quarter of Section 13, wells 3-3, 1-3, and 7-5. As of the end of 1990, no additional conversions of wells to injectors have occurred.

The Vertz sandstone was probably formed by a meandering stream depositional system. Willhite (1986) presents an example of such an environment in his Figure 7.38. The Vertz is a uniform well-ordered sandstone which fines upward very gradually and has a basal lag of pebble size clasts. The sandstone has little vertical permeability variation and the preferential horizontal permeability lies in the direction of the stream current of the original depositional environment. In a meandering stream system, a channel may become cut off forming an oxbow lake. If the abandoned channel is not subsequently reworked prior to system burial, it will fill with silt and form a clay plug. This could create a permeability barrier in the sandstone reservoir.

A net sand isopach of the Southeast Vassar Vertz Sand Unit is shown in Figure 3.2. The dashed lines north of Well 5-1 and in the east part of the field are the location of suspected permeability barriers in the field. The barrier locations were identified by a dry hole and the lack of flood water communication across the barriers. The flow path of the depositional stream system appears to have been from northeast to southwest. This is likely the direction of the preferential permeability in the reservoir.

By December, 1990, the cumulative oil production from the Southeast Vassar was 2.45 million stock tank barrels (STB) and 18 wells were operating as injectors or producers. The formation has a vertical depth of around 1800 ft. The original reservoir pressure was 850 psi at 92°F. Oil gravities from hydrometer readings range from 38 to 42 degrees API. Gas gravities from 0.70 to 1.18 (air = 1.0) have been measured using a gas chromatograph. In the reservoir simulation study, an oil gravity of 40 degrees API and a gas gravity of 0.85 were used to estimate fluid properties from the correlations by Vasquez and Beggs (1980). The oil and water viscosities are 2.9 cp and 1.1 cp, respectively and were determined using Canon-Fenske viscometers (ASTM, 1987).

The Dykstra-Parsons permeability variation factor (Dykstra and Parsons, 1950), was 0.35 from core permeabilities indicating little vertical variability in permeability. The high recovery obtained by the waterflood is consistent with this. In the region of the reservoir behind the flood front, it is estimated that primary and secondary recovery have produced almost 60% of the

original oil in place. The mobile oil phase in the region planned for the pilot study may be as low as 5% of the original oil in place.

The characteristics of the SEVVSU are summarized in Table 3.1. Jenneman (1989) lists criteria for MEOR target reservoirs. Comparing the SEVVSU to these criteria, the Vassar's temperature, 33°C, is less than 75°C. The porosity, 18-24%, suggests an average pore size distribution of 7 to 15 μm indicating the effective transportability of microbes through the porous media. Permeabilities range from 100 to 500 md, well above the limiting permeability of 75 md. The Vassar's oil gravity is above 18°API. The pressure range is not extreme and bacterial activity flourishes over the entire range. The pH of the Vassar brine is 7.0. Acidity values between 4 and 9 are suggested for MEOR activity.

The microbial field pilot study is planned for the southwest quarter of Section 13 behind the line of active waterflood injectors, Figure 3.2. Pumping units have been installed on wells 5-1, 5-2, and 7-1. The 7-2 well will be used as the injection well for the pilot. Workover operations have been performed to restore injectivity. With the three producers establishing a drawdown to the west and the active injectors functioning to the east, it is expected that all water injected in well 7-2 will be confined to the pilot area. Production and injection data on the four pilot wells will be collected for at least one month prior to nutrient injection to establish a baseline of reservoir performance. Treatments of about five hundred barrels of approximately 25% nutrient solution will be injected into the injection well weekly for from six to twelve weeks. Each nutrient treatment will be followed by untreated waterflood brine. By pumping nutrients followed by a brine pad, metabolism is discouraged in the near wellbore area which maintains injectivity and allows for transport of unmetabolized nutrients deeper into the reservoir. After all treatment have been injected, the pilot area will be operated as a simple waterflood. The production rates and pressures will be monitored and fluids sampled at the production wells until the reservoir has stabilized or for 18 months. Volumetric data regarding the field pilot is presented in Table 3.2. This table combines information from this chapter and the discussion of surface facilities and operations from Chapter 2.

Based upon the current interpretation of stream flow during original deposition of the Vertz sandstone, the preferential flow path is believed to be from the 7-2 to the 7-1. The effects of the injection are expected to be first seen at the 7-1 well. If the microbial process works as expected, this path will experience a permeability reduction caused by the *in situ* growth of microorganisms. Later volumes of injected water will be diverted to wells 5-1 and 5-2. The goal of the pilot is to demonstrate that the flow paths can be changed in this region due to the growth and metabolism of indigenous bacteria. The field pilot may enhance oil recovery by sweeping some of the previously bypassed oil.

Between the time the proposal was submitted to the Department of Energy and its subsequent funding, the Southeast Vassar Vertz Sand Unit working interest owned by Tenneco Exploration and Production Company (the unit operator) was sold to Mesa Limited Partnership. Conversations between the principal investigators, University Legal Counsel, and Mesa Limited Partnership resulted in an agreement for the future operation of this field pilot study. This agreement was executed in late September, 1989. Mesa agreed to allow the continued use of the field and provide some technical assistance in the installation and operation of the field pilot. Correspondence and meetings in Amarillo, TX, with Mesa's Production and Reservoir personnel were moving toward a firm agreement on operating policies and testing protocols on this project.

In March, 1990, Mesa Limited Partnership announced the sale of the SEVVSU to Sullivan and Company of Tulsa, OK. This sale was completed in April, 1990, and Sullivan began operation of the field. Four trips to Tulsa resulted in an understanding concerning the operation of the field pilot study and an agreement between Sullivan and Company and the University of Oklahoma. This agreement was finalized in October of 1990.

In November and December of 1990, workovers were performed on wells 5-1, 5-2, 7-1, and 7-2. The 7-2 was acidized and fractured and returned to active injection on December 13, 1990. The 5-1, 5-2, and 7-1 were cleaned and acidized and pumping equipment was installed. Production from these three wells was not initiated as a pressure fall-off and interference test was planned using a "shut-in" of the 7-2 well in January, 1991.

REFERENCES

American Society of Testing and Materials, 1987. "D445, Kinematic Viscosity of Transparent and Opaque Liquids (and calculation of Dynamic Viscosity), and D446, Glass Capillary Kinematic Viscometers," 1987 Annual Book of ASTM Standards, Volume 05.D1, pp. 235-261.

Jenneman, G.E., "The Potential for In-Situ Microbial Applications", in Microbial Enhanced Oil Recovery, Donaldson, E.C., Chilingarian, G.V., Yen, T.F., (editors), Elsevier, Amsterdam, The Netherlands, 1989.

Dykstra, H. and R. L. Parsons, 1950. "The prediction of oil recovery by waterflood," Secondary Recovery of Oil in the United States, API, pp. 160-174.

Oklahoma Geological Survey, 1972, Geology and Earth Resources of Oklahoma, University of Oklahoma, Norman, OK.

Vasquez, M. and H. D. Beggs. "Correlations for Fluid Physical Property Prediction." *Journal of Petroleum Technology*, June, 1980, Vol. 269, pp. 968-970.

Willhite, G. P., 1986, Waterflooding, SPE Textbook Series, Vol. 3, Society of Petroleum Engineers, Richardson, TX, p. 244.

Table 3.1 Southeast Vassar Vertz Sand Unit

Formation	Vertz Sandstone
Geologic Age	Pennsylvanian, Wabaunsee Group
Depositional System	Braided Stream
Location	Payne County, Oklahoma T 18 N, R 1 W, Sec. 12, 13, 14
True Vertical Depth	1800 ft. (550m)
Formation Temperature	92°F (33°C)
Pilot Area Formation Thickness	12 - 16 ft (3.7-4.9m)
Porosity	18 - 24%
Permeability	100 - 500md
Brine Salinity	15 -19% NaCl equivalent
pH	≈7
Original Oil In Place	7.13 MMSTB
Recovery Factor (12-31-90)	34%
Recovery Factor Behind Floodfront	50 - 60% (estimate)
Oil Saturation in Pilot Area	25% (estimate)
Oil Gravity	40 (38 - 42) °API
Gas Gravity	0.85 (0.75 - 1.18) (air = 1)
Oil Viscosity (STP)	2.9 cp
Water Viscosity (STP)	1.1 cp
Solution Gas	Near dead (≈0 scf/stb)
Formation Pressures	
Average Reservoir Pressure	1100 psi (estimate)
Producing Well Bottomhole Pressure	100 psi (estimate)
Injection Well Bottomhole Pressure	1700 psi
Initial Reservoir Pressure	870 psi (hydrostatic)

Table 3.2 Field Pilot Volumetric Data

Area Bounded by Field Pilot Wells	20 acres
Average Thickness in Pilot Area	14 feet
Oil Production in Pilot Area (Primary and Secondary)	592 bbl/acre-ft
Original Oil in Place in Pilot Area	1034 bbl/acre-ft
EOR Target (Mobile Oil in Pilot Area)	52 bbl/acre-ft
Pessimistic MEOR Produced Oil	0 bbl/acre-ft
Optimistic MEOR Produced Oil	17 bbl/acre-ft
One Treatment of MEOR Nutrients and Associated Fluids	
Molasses (22.5 tons)	93 bbl
Ammonium Nitrate (6.5 tons)	21 bbl
Oil Field Brine	351 bbl
Brine Pad Following Nutrients	1650 bbl
Total Reservoir Pore Volume in Pilot Area	434,500 bbl
Aqueous Pore Volume in Pilot Area	325,800 bbl
Volume Injected per Treatment	2,115 bbl

S - "Make-up" Injection Water Well

SOUTHEAST VASSAR	Microbially Enhanced
VERTZ SAND UNIT	Oil Recovery Lab:
	Dr. Roy M. Knapp
Isopach Map	
Net Vertz Sand	School of Petroleum and
C.I. = 2 ft.	Geological Engineering
DJG - Nov 20, 1990	
Sec 13-T10N-R1W	University of Oklahoma
Payne Co., Okla.	Norman, Oklahoma

SCALE 1: 20000.
0 0.2 0.4 MILE
0 0.2 0.4 KMS

FIGURE 3.2: ISOPACH MAP OF NET VERTZ SAND

4. CORE FLOOD EXPERIMENTS AND MEOR MECHANISMS

J.L. Chisholm, S.V. Kashikar, R.M. Knapp, M.J. McInerney, D.E. Menzie,
N.J. Silfanus

4.1 INTRODUCTION

For the development of microbially enhanced oil recovery (MEOR) as a viable technology in the petroleum industry, it is important that the mechanisms involved in this process be understood. MEOR has the potential to recover a portion of the residual oil remaining after waterflooding through changes brought about by metabolic activity. The changes include selective plugging of the reservoir and modification of the reservoir fluids and their saturations. The latter two of these will be discussed in the following sections.

4.2 EXPERIMENTAL METHODS

The experiments reported were conducted to provide information about the mechanisms of oil recovery caused by microbial activity within a core. Specifically, samples of microorganisms from well 1A-9 in the Southeast Vassar Vertz Sand Unit (SEVVSU), Payne County, Oklahoma were investigated for their potential in microbial enhancement of oil recovery. All experiments were performed using oil and brine taken from the SEVVSU. The NaCl salinity of the brine was 15%. The experiments were performed at reservoir temperature using the apparatus in Figure 4.1. The cores were prepared and experiments conducted using the techniques of Silfanus (1990) and Knapp, et al. (1990). The experiments were performed using the three step treatments described below.

Four MEOR core floods were performed with apparatus arranged as shown in Figure 4.1. For each experiment a core was cleaned, dried, and flushed with brine, oil, and brine again, such that the core's final condition was water wet at residual oil saturation. The MEOR treatments were begun by an injection of nutrient rich brine containing bacteria. The experiment proceeded with three steps per treatment. First, the core was shut in and allowed to incubate. Second, the effluent end of the core was opened and fluids were produced under the influence of any internal driving force. Third, the core was flooded and fluids were produced under the influence of the flood. The displacing liquid was a nutrient rich brine which represented the carbon source for the next incubation. These three steps were repeated for each treatment.

The effective permeability reduction factor (PRF) is defined as:

$$PRF = \frac{K_{wi}}{K_{wsor}} 100 \quad (1)$$

In the MEOR processes, a series of nutrient treatments were used to improve oil recovery. The incremental oil recovery associated with each nutrient treatment is the oil produced by the release of pressure caused by the in situ gas produced during incubation of the core with nutrients plus the oil that is produced by the injection of the subsequent treatment. The recovery factor (RF) is defined as:

$$RF = \frac{N_p}{OIPW} 100, \% \quad (2)$$

4.3 MICROBIAL ENHANCED OIL RECOVERY MECHANISMS

Metabolism within the reservoir changes the chemical nature of the formation fluids. Bacteria often produce products such as surfactants, polymers, and co-surfactants (alcohols) which change the properties of the water phase and the interaction between the fluid phases and the fluids and the matrix. In particular, changes in the interfacial tension can be related to microscopic sweep efficiency. The production of gases is associated with almost all biogenetic activity. This gas can either dissolve in the pore fluids or exist as a free gas phase within the porous medium. In the latter case, the relative permeabilities in the medium will be changed and the presence of a free gas phase can affect the residual oil saturation.

The presence of cell bodies in the porous media also causes changes in the reservoir characteristics. Bacteria can exist both in the flowing water phase and as sessile (attached) bacteria along pore walls. The sessile bacteria occupy space within the pores. Often they have polymeric films or coatings. This reduces the volume available for flowing fluids and reduces both effective porosity and permeability. In cases where the nutrient source for the bacteria is provided by the injected brine, growth is concentrated in preferential flow paths for the water phase. When these flow paths are effectively blocked by cell bodies, subsequent injections of brine will be forced to follow other flow paths. They will then encounter and displace oil that may have been bypassed by the original waterflood.

Biogenic Gas Effects

Several chemical changes occur as a result of the MEOR processes which affect the fluids in the reservoir. Microbial processes result in a change in the relative permeability relationship by the presence of biogenetic gas. The metabolism of many microorganisms results in the production of carbon dioxide, hydrogen, nitrogen, or possibly methane, which can create a free gas phase at low pressures in the reservoir.

A free gas phase has been found to decrease residual oil saturation. Holmgren and Morse (1951) and Kyte et al. (1956) studied waterflood recoveries with varying initial gas and oil saturations. They observed that increasing the initial free gas saturation caused the residual oil saturation to decrease. The presence of the gas phase caused a decrease in residual oil saturation of six to ten percent of pore volume. Lower residual oil saturations were obtained at successive flooding stages when gas was present compared to those floods performed in the absence of gas.

An idealized set of relative permeability curves for wetting and non-wetting phases is presented in Figure 4.2. At the conclusion of a waterflood in a core the saturation of the wetting phase, S_w , will be at a maximum. In the case of Figure 4.2, the maximum S_w is 0.9. At this point the relative permeability of the non-wetting phase is zero. Assume the non-wetting phase initially is residual oil. If the core is flooded with a nutrient rich brine slug inoculated with a viable bacteria and allowed to incubate, biogenetic gas will be produced by bacterial metabolism. The result of this metabolic gas is an increase in pore pressure in the core.

If the core is allowed to produce fluids under the influence of its internal pore pressure, the first fluid produced will be water. However, as the water is produced and pore pressure drops, gas will come out of solution and volumetrically replace the produced water. Referring again to Figure 4.2, the wetting phase saturation has, by production, been reduced to some value less than 0.9. Now, the relative permeability of the non-wetting phase; oil plus gas, has a small value. Further production by reduction of pore pressure will consist of brine and a small quantity of oil with some entrained gas.

When the core is flooded with nutrient rich brine, the core will be swept with a Buckley-Leverett (1942) piston-like front of the new fluid. Behind this floodfront the saturation of the wetting phase will be near 0.9 and the relative permeability of the non-wetting phase almost zero. However, the saturations downstream of the piston-like front are still at the values they were at the end of the production by internal pressure step. For example, S_w might equal 0.85 and the non-wetting phase is still mobile. As these fluids are pushed by the floodfront some additional oil and gas will be produced from the core.

This process of oscillating the fluid saturations about the residual oil saturation condition provides a mechanism for enhanced oil recovery. As previously stated, the presence of a free gas phase can reduce residual oil saturation. Based on Holmgren and Morse's (1951) 6 to 10 percent of total pore volume decrease in residual oil saturation this can represent from a fifth to a third of the residual oil in place after waterflooding which might be recovered through this mechanism.

Interfacial Tension

Biosurfactants and cosurfactants (alcohols) are produced as a byproduct of metabolism (Javaheri, et al, 1985) These chemicals lower the interfacial tension at the oil-water interface and displace oil that cannot be displaced by water alone. Capillary forces that trap residual oil in porous media are reduced by lowering interfacial tension. One of the problems of surfactant flooding is the adsorption of surfactant on the surface in the reservoir rock. This decreases the concentration of the surfactant below that required to perform the task. This problem maybe less likely to occur if the surfactant is produced in situ (Hitzman, 1991).

Melrose and Bradner (1974) defined the capillary number (N_{ca}) to relate the magnitude of viscous forces to the magnitude of the capillary forces as:

$$N_{ca} = \frac{V\mu_w}{\sigma_{ow}} \quad (3)$$

The reduction in interfacial tension caused by in situ surfactant and alcohol generation increases microscopic displacement efficiency in the porous medium and reduces the residual oil saturation (Moore and Slobod, 1956) This is illustrated in Figure 4.3 [Stalkup (1984)] where the residual non-wetting phase (oil) saturation is plotted as a function of dimensionless capillary number. This result is also indicated by Stegemeier (1977).

A relationship between the capillary number after i treatments, N_{ca}^i , and the capillary number before treatment, N_{ca}^o , can be developed. This relationship is based on the definition of capillary number and permeability reduction factor (PRF). Substituting $\frac{u}{\phi}$ for V and comparing capillary number after the i th treatment, N_{ca}^i and the original capillary number before treatments, N_{ca}^o yields:

$$N_{ca}^i = \frac{V_i\mu_w}{\sigma_{ow}} = \frac{\frac{u_i}{\phi_i}\mu_w}{\sigma_{ow}^i} \quad (4)$$

$$N_{ca}^o = \frac{V_o \mu_w}{\sigma_{ow}} = \frac{\frac{u_o}{\phi_o} \mu_w}{\sigma_{ow}^o} \quad (5)$$

$$\frac{N_{ca}^i}{N_{ca}^o} = \frac{\frac{\frac{u_i}{\phi_i} \mu_w}{\sigma_{ow}^i}}{\frac{\frac{u_o}{\phi_o} \mu_w}{\sigma_{ow}^o}} \quad (6)$$

If the viscosity of water is the same before and after the treatment (as was the case in the experiments discussed later) and the Darcy velocity, u , is kept constant for each treatment, the ratio of capillary numbers becomes:

$$\left[\frac{N_{ca}^i}{N_{ca}^o} \right] = \left[\frac{\phi_o}{\phi_i} \right] \left[\frac{\sigma_{ow}^o}{\sigma_{ow}^i} \right] \quad (7)$$

A correlation of the rate of change in porosity versus the rate of change in permeability due to selective plugging by microorganisms was introduced by Civan et al. (1988) from fines migration theory:

$$PRF = \frac{K_i}{K_o} = \left[\frac{\phi_i}{\phi_o} \right]^3 \quad (8)$$

Substituting this expression into the capillary number ratio results in:

$$\left[\frac{N_{ca}^i}{N_{ca}^o} \right] = \left[\frac{1}{PRF} \right]^{1/3} \left[\frac{\sigma_{ow}^o}{\sigma_{ow}^i} \right] \quad (9)$$

Physically, two aspects of microbial activity combine to affect the value of the capillary number and the oil recovery associated with its change. First, the chemicals produced by metabolism reduce interfacial tension. This reduces the pressure drop across a phase boundary and enhances the microscopic sweep efficiency. Second, as the major pores become plugged (decrease in PRF), if the Darcy velocity, u , remains constant, the interstitial velocity, V , increases in the smaller pores. These pores which were not previously flooded are then swept by this water. Some bypassed oil is produced by this process. These processes operate at the microscopic level in the core.

Selective Plugging

Almost all producing zones have variable permeability due to stratification, depositional environment, or diagenesis. This phenomena creates preferential flow paths for the displacing fluid (water). The invading fluid moves rapidly through the more permeable zones and more slowly in the less permeable zones. Once a continuous flow path has been established between the injection well and the production well, an increasing portion of injection water flows along this path. Thus, more oil is swept

from the higher permeability zones, and less from the lower permeable portions. This reservoir heterogeneity greatly affects the recovery efficiency of the fluid displacement process. Selective plugging of these high permeability zones by microorganisms can improve sweep efficiency. Two types of microbial plugging have been identified: plugging by non-viable cells and plugging by viable microorganisms.

Merkt (1943) reported the use of non-viable microorganisms in changing the permeability. Since dead cells do not produce slime, precipitates, etc, non-viable cells can only act as particulate agents. Kalish, et al. (1964) found that viable bacteria had a greater effect on permeability reduction per bacterium injected than did non-slime-forming or non-viable bacteria. Viable microorganisms have the ability to adhere to the rock and produce an extracellular polysaccharide which covers the cells and the rock surface forming a polymer film. These actions result in more effective plugging than particulate plugging by dead cells. As the bacteria flourish and reproduce these activities exponentially increase. Thus, the cells become an effective plugging agent.

Sessile bacteria occupy pore space. This effectively reduces the apparent porosity available to flowing fluids. Further, the pore surface characteristics are changed by the presence of sessile bacteria. Selective plugging represents a macroscopic change in the reservoir.

Crawford (1961, 1962) was one of the first investigators to suggest the in situ growth of bacteria could rectify permeability stratification. Other investigators have concluded that viable microorganisms can penetrate porous media, reduce permeability by as much as 90%, preferentially plug higher permeability zones and larger pores, and produce chemicals and gases which improve recovery. Updegraff (1983), Myers and Samiroden (1967), Jenneman, et al. (1983, 1984, 1985), Torbati, et al. (1986), Raiders et al. (1985, 1986a, 1986b), Jack et al. (1982), and Bryant and Douglas (1987) have all investigated the effects of viable microorganisms in porous media.

4.4 EXPERIMENTAL RESULTS

Four Berea sandstone cores were used in these experiments. The cores were six inches in length and two inches in diameter. The oil, brine, and bacteria were all taken from the SEVVSU.

Figure 4.4 shows permeability reduction factor (PRF), cumulative incremental oil recovery factor, and gas production for core C06. C06 had an absolute permeability of 724 md and a brine permeability after waterflood of 55 md. The porosity was 22% and the oil saturation following waterflooding, S_{or} , was 29.6%. At the end of the treatments, approximately 10 PV of nutrient mixture had been injected and 84.2% of the oil in place after waterflooding had been recovered. The total gas produced was 217.6 ml measured at ambient laboratory conditions with an average concentration of 70.2% of N_2 and 25.1% CO_2 . At the end of the nutrient treatments, 2.6 PV of Vassar brine were injected through the core, and the PRF value stabilized at 4.9%.

In core C06, no significant oil and gas were recovered during the first three treatments. However, the permeability reduction factor was reduced during this period. Curiously, during the period of first significant gas production (treatments 4 and 5) PRF rose briefly. After three treatments, the microorganisms had acclimated to the core environment and began to utilize the carbon sources, resulting in the production of biogenic gas and other microbial products. The surface tension of the effluent samples was found to be 52% of the injected nutrient mixture. The viscosity of the effluent was the same as the injected nutrient mixture.

Figure 4.5 shows PRF, cumulative incremental oil recovery and gas production

for core C09. The absolute permeability was 219 md and the brine permeability after waterflood was 53 md. The porosity was 19.2% and the S_{or} was 30.4%. At the end of eight treatments, after approximately 6 PV of nutrient mixture had been injected, 53.9% of the oil in place after waterflooding was recovered. The cumulative gas production was 135 ml. After the final nutrient treatments, 2.2 PV of Vassar brine were injected through this core and the PRF stabilized at 15.5%. In this core, significant gas production began with the second treatment. PRF rose with this initial gas and then fell quickly with treatment 3.

Cores C10 and C11 were initially considered marginal successes. At the conclusion of 6 and 8 treatments these cores had produced 0.0% and 8.7% of the oil remaining after waterflooding respectively. These cores had lower absolute permeabilities than cores C06 and C09. Jenneman et al. (1985) has indicated that permeabilities less than 100 md appear to limit the ability of microbes to penetrate the media, proliferate, and produce byproducts. When treatments were stopped, C10 and C11 were left in an incubator. After 103 days incubation, core C11 had 13 psig of internal pore pressure. Treatments were resumed on C11 with significant production of gas and oil. Soon thereafter, treatments on core C10 were resumed and C10 produced significant oil and gas as well.

Core 10 had an absolute permeability of 152 md and a brine permeability after waterflood of 9.4 md. The porosity of C10 was 19% and the S_{or} was 36.8%. Because of the high pressure drop across the front half of the core prior to the long incubation, C10 was thought to have had facial plugging on the inlet sand face. After treatments were resumed significant oil and gas recovery were observed. After four additional treatments, bringing the total number of treatments to 10, C10 had a recovery factor of 30.4% of oil in place after waterflooding. Gas production was 64.3 ml and final the PRF was 3.6%. C10 had a very slight rise in PRF associated with first gas production. Results for C10 are given in Figure 4.6.

Core C11 had an absolute permeability of 76 md and a brine permeability after waterflood of only 7 md. The porosity of C11 was 17.2% and the S_{or} was 41.3%. After eight treatments, the recovery factor was 8.7%. Based on the conclusions of Jenneman et al. (1985) mentioned above, low recovery of oil was expected given the low initial permeability. After the long incubation, core C11 was treated six additional times, bringing the total number of treatments to 14, and eventually recovered 45.7% of the oil remaining after waterflooding. A leak in the Luer Lock connection as depicted in Figure 4.1 caused incomplete gas recovery. At least ten ml of gas were produced and the final PRF was 5.7%. Once again, PRF rose with the first two treatments in which significant gas was produced. C11 results are presented in Figure 4.7.

4.5 DISCUSSION OF RESULTS

For Cores C06 and C09, as the permeability reduction factor started to decrease below 25%, oil recovery increased substantially. This suggests that microorganisms had preferentially plugged the larger pores within the core and diverted the flow of the brine to the smaller pores (unswept regions) where more oil was trapped, apparently increasing the displacement efficiency of the flood. In C06, carbon and nitrogen analyses were also performed. CO_2 , N_2 , acetate, butyrate and ethanol were detected in the effluent samples. The results show that microorganisms proliferated and produced metabolic products that helped recover more oil.

Microscopic displacement efficiency also increased by changes in the chemical composition of the fluid. One of the products, ethanol, is soluble in the oil. Ethanol production can increase microscopic displacement efficiency by decreasing the

viscosity of oil. The surface tensions of the effluent brine samples were lower than the initial nutrient samples. This suggests that biosurfactant was also produced. Thus, microbial processes led to reduction of the oil viscosity and surface tension which increased oil mobility and capillary number.

For core C06, using a stabilized PRF of 5% and a surface tension 52% of original value (results following 14 treatments) and assuming that the reduction in the interfacial tension between oil and water was the same as the reduction in surface tension, the change in the capillary number ratio for core C06 is

$$\left[\frac{N_{ca}^i}{N_{ca}^o} \right] = \left[\frac{1}{0.05} \right]^{1/3} \left[\frac{1}{0.52} \right] = 5.2$$

The capillary number after treatment 14 was 5.2 times the initial capillary number. From Figure 4.3, assuming $N_{ca}^o = 10^{-6}$, the increase of 5.2 in capillary number could have caused a decrease in residual oil saturation of as much as 4% and the increase in capillary number could explain recovery of 6% to 13% of the oil left after waterflooding.

A time lag appears to exist with respect to microbial activity. This may be roughly correlated to absolute permeability. Initial microbial activity is low because of the low initial cell population. Once cell populations increase, significant microbial activity occurs. In lower permeability cores, the time required for the induced bacteria to permeate the core and establish a significant population increases. Cores C06 and C09, with higher absolute permeability, began to produce gas and oil within three treatments of experiment initiation. Hindsight indicates that treatments of C11 never should have been stopped. The necessary seed population appears to have developed after seven treatments. Core C10 appears to have needed some part of the 100+ days of incubation to achieve this necessary seed population.

Significant microbial activity was associated first with increases in pore pressure and then with significant gas production. It should be noted that PRF dropped with the first treatment in all cases and preceded the advent of either pressure increase or gas production. Whether this is the result of particulate plugging by the cells or some metabolic activity within the core that has no external manifestation is not known.

In addition, currently no predictable explanation exists for the brief increase in brine permeability associated with the first significant gas production. This period lasts only one or two treatments and the magnitude of the permeability recovery is not strongly associated with any core characteristic. After the first few treatments with significant gas production the PRF again begins to decrease. The phenomena appears similar to "bridge-breaking" in particulate plugged porous media.

4.6 CONCLUSIONS

- (1) Increases in oil recovery from Berea sandstone cores were accompanied by production of biogenic gas, acids, ethanol and biomass by native bacteria collected from well 1A-9 of SEVVSU.
- (2) Production of biogenic gas decreased the residual oil saturation due to relative permeability changes associated with the creation of a free gas phase in the cores. This can explain the recovery of up to a third of the oil left after waterflooding.

- (3) The increase in capillary number can explain up to 13% of additional oil recovery from core C06 .
- (4) The above mechanisms were active in the core experiments but do not fully explain the the additional oil production observed from the cores. The contributions to recovery of other mechanisms, such as selective pore plugging, have not yet been quantified. There may be other active mechanisms that have not yet been identified.
- (5) A successful MEOR core flood has been performed in a core with 76 md absolute permeability.
- (6) A time lag before significant gas and oil production has been associated with the target cores absolute permeability.

NOMENCLATURE

- K_{wi} : effective brine permeability of the core during i-th treatment, mD
- K_{wsor} : effective brine permeability of the core at residual oil saturation, mD
- N_{ca} : capillary number, dimensionless
- N_p : cumulative oil production after MEOR treatments, ml
- $OIPW$: Oil In Place after Waterflood (S_{or} *PV), ml
- PRF : effective permeability reduction factor, percent
- RF : recovery factor, percent
- u : the Darcy velocity
- V : interstitial velocity, $\frac{u}{\phi}$
- μ_w : viscosity of displacing fluid
- σ_{ow} : interfacial tension between oil and the displacing fluid
- ϕ : porosity, dimensionless fraction

superscript or subscript:

- i : treatment number, condition after treatment i
- o : original, condition before treatments began

REFERENCES

Bryant, R.S. and Douglas, J., "Evaluation of Microbial Systems in Porous Media for Enhanced Oil Recovery", SPE 16092, presented at the Society of Petroleum Engineers International Symposium on Oilfield Chemistry, San Antonio, Tx, Feb. 1987.

Buckley, S.E., Leverett, M.C., "Mechanism of Fluid Displacement in Sands", Transactions, AIME, Vol. 146:107-116 (1942).

Civan, F., Knapp, R.M., and Ohen, H.A., "Automatic Estimation of Model Parameters for Swelling and Migration of Fine Particles in Porous Media", Paper presented at the AIChE Meeting in New Orleans, LA, (March 6-10, 1988).

Crawford, P.B., "Possible Bacterial Correction of Stratification Problems", *Prod. Monthly*, Vol. 25:10-11 (1961).

Crawford, P.B., "Water Technology: Continual Changes Observed in Bacterial Stratification Rectification", *Prod. Monthly*, Vol 26:12 (1962).

Hitzman, D.O., "Microbial Enhanced Oil Recovery - The Time is Now", Microbial Enhancement of Oil Recovery - Recent Advances, E.C. Donaldson, editor, Elsevier, 1991, p. 18.

Holmgren, C.R. and Morse, R.A., "Effect of Free Gas Saturation on Oil Recovery by Waterflooding", Transactions, AIME, Vol. 192:285-296 (1951).

Javaheri, M., Jenneman, G.E., McInerney, M.J., Knapp, R.M., "Anaerobic Production of a Biosurfactant by *Bacillus licheniformis* JF-2", *Applied Environmental Microbiology*, (September 1985), 689-700.

Jenneman, G.E., Knapp, R.M., Menzie, D.E., Revus, D.E., Clark, J.B., and Munnecke, D.M., "Transport Phenomena and Plugging in Berea Sandstone Cores Using Microorganisms", In, E.C. Donaldson and J.B. Clark, (eds.) *Proceedings of the 1982 International Symposium on Microbial Enhancement of Oil Recovery*, Nat. Tech. Inf. Serv., Springfield, VA, CONF-8205140 (1983) 71-75.

Jenneman, G.E., Knapp, R.M., McInerney, M.J., Menzie, D.E., and Revus, D.E., "Experimental Studies of In-Situ Microbial Enhanced Oil Recovery", *Soc. Pet. Engr. J.*, (Feb. 1984) 33-37.

Jenneman, G.E., McInerney, M.J., Knapp, R.M., "Microbial Penetration through Nutrient-Saturated Berea Sandstone", *Applied and Environmental Microbiology*, Aug. 1985, pp. 383-391.

Jack, T.R., Thompson, B.G., and DiBlasio, E., "The Potential for Use of Microbes in the Production of Heavy Oil", *Proceedings of the 1982 International Conference On the Microbial Enhancement of Oil Recovery*, Nat. Tech. Inf. Serv., Springfield, VA, CONF-8205140, (1983), 88-93.

Kalish, P.J., Stewart, J.E., Rogers, W.F., and Benneth, E.O., "The Effect of Bacteria on Sandstone Permeability", *J. Pet. Tech.* (1964), vol 16, 805-814.

Knapp, R.M., Silfanus, N.J., McInerney, M.J., Menzie, D.E., Chisholm, J.L., "Microbial Mechanisms for Enhanced Oil Recovery from High Salinity Core Environments", presented at American Institute of Chemical Engineers 1990 Spring Annual Meeting, March 18-22, Orlando, Fl.

Kyte, J.R., Stanclift, R.J., Jr., Stephen, S.C., Jr., and Rapoport, L.A., "Mechanism of Water Flooding in The Presence of Free Gas", *Transactions, AIME* (1956) 207, 215-221.

Melrose, J.C. and Brandner, C.F., "Role of Capillary Forces in Determining Microscopic Displacement Efficiency for Oil Recovery by Waterflooding", *J. Cdn. Pet. Tech.*, (Oct - Dec, 1974) 54-62.

Merkt, E.E., "The Effect of Bacteria on the Permeability of Oil Reservoir Rocks", Thesis, University of Texas, Austin, Texas, (1943) 14-29.

Moore, T.F. and Slobod, R.L., "The Effect of Viscosity and Capillarity on The Displacement of Oil by Water", *Prod. Monthly*, (Aug, 1956) 20-30.

Myers, G.E., and Samiroden, W.D., "Bacterial Penetration in Petroliferous Rocks", *Prod. Month* (April 1967) 22-25.

Raiders, R.A., Freeman, D.C., Jenneman, G.E., Knapp, R.M., McInerney, M.J., and Menzie, D.E., "The Use of Microorganisms to Increase the Recovery of Oil Form Cores", Paper SPE 14336 presented at the 60th Annual Meeting of the Society of Petroleum Engineers of AIME, Las Vegas, NV, Sept. 1985.

Raiders, R.A., McInerney, M.J., Revus, D.E., Torbati, H.M., Knapp, R.M., and Jenneman, G.E., "Selectivity and Depth of Microbial Plugging in Berea Sandstone Cores", *J. Indust. Microbial.* (1985a) 195-203.

Raiders, R.A., Maher, T.F., Knapp, R.M., and McInerney, M.J., "Selective Plugging and Oil Displacement in Crossflow Core Systems by Microorganisms", paper SPE 15600 presented at the 61st Annual Meeting of the Society of Petroleum Engineers of AIME, New Orleans, LA, Oct. 1986b.

Silfanus, N.J., "Microbial Mechanisms for Enhanced Oil Recovery from High Salinity Core Environments", Masters Thesis, University of Oklahoma, Norman, Oklahoma, 1990.

Stalkup, F.I., Jr., Miscible Displacement, Monograph series, SPE, Richardson, TX (1984).

Stegemeier, G.L., "Mechanism of Entrapment and Mobilization of Oil in Porous Media", in Improved Oil Recovery by Surfactant and Polymer Flooding, Shah, D.O., Schechter, R.S., ed., Academic Press, Inc., New York, New York, 1977.

Torbati, H.M., Raiders, R.A., Donaldson, E.C., McInerney, M.J., Jenneman, G.E., and Knapp, R.M., "Effect of Microbial Growth and Pore Entrance Size Distribution in Sandstone Cores", *J. Indust. Microbial.* (1986) 227-234.

Updegraff, D.M., "The Effect of Microorganisms on the Permeability and Porosity of

Petroelum Reservoir Rock", in Microbial Enhanced Oil Recovery, Zajic, J.E., Cooper, D.C., Jack, T.R., Kosaric, N., editors, PennWell Books, Tulsa, OK, (1983), pp. 37-44.

FIGURE 4.1 EXPERIMENTAL SET-UP

FIGURE 4.2 WETTING AND NON-WETTING RELATIVE PERMEABILITY CURVES

**FIGURE 4.3 CAPILLARY DESATURATION CURVE (CDC)
(AFTER STALKUP)**

FIGURE 4.4 EFFECT OF NUTRIENT TREATMENTS ON THE PRF, CUMULATIVE OIL RECOVERY AND GAS PRODUCTION

FIGURE 4.5 EFFECT OF NUTRIENT TREATMENTS ON THE PRF, CUMULATIVE OIL RECOVERY AND GAS PRODUCTION

FIGURE 4.6 EFFECT OF NUTRIENT TREATMENTS ON THE PRF, CUMULATIVE OIL RECOVERY AND GAS PRODUCTION

FIGURE 4.7 EFFECT OF NUTRIENT TREATMENTS ON THE PRF, CUMULATIVE OIL RECOVERY AND GAS PRODUCTION

5. MICROBIAL MODELING

Xu Zhang, R.M. Knapp, M.J. McInerney, P. Sharma, V. Bhupathiraju

5.1 INTRODUCTION

A three-phase, seven species, one dimensional model has been developed to simulate microbial process growth and metabolism in porous media. Six flowing species (glucose, ammonium nitrate, acetate, carbon dioxide, nitrogen and biomass) as well as the sessile (affixed to pore walls) biomass are described by the equations. These equations are modified based on the process regime in effect during different periods of the treatment.

The equations are solved numerically by finite difference approximations. The material balance equations use the third-order upwind convective differencing scheme (Leonard, 1984) to minimize numerical dispersion and oscillation. Parameters used in the equations are derived from chemical equations, reference texts, experimental results, or are modified by trial and error to achieve a match of experimental results. Details of the model were described in last year's annual report (Knapp, et al., 1990).

A two substrate, zero-dimensional simplification of this program was tested against the results obtained from growth experiments of *Escherichia coli* in sand-packed cores. The experiment was closely modeled by the simulator. Specifically, the consumption of the substrates (glucose and nitrate) achieved a close match. Production of acetate and nitrogen were also well simulated.

5.2 MODEL VALIDATION

A one-dimensional version of the model was used to quantify biomass growth, product generation, substrate consumption, and to predict permeability reduction in laboratory core experiments.

Experimental studies have been conducted to investigate microbial mechanisms that recover oil remaining after waterflooding (Silfanus, 1990). The injection incubation, and continued nutrient rich flood protocols used in Silfanus' experiment on Core #6 were simulated using the model. A good match between experimental and simulation results was obtained for total gas production (Figure 6.1) through the first 10 nutrient treatments.

The simulation indicated that after Treatment 10, the glucose consumption (carbon source for metabolism) should have reached its maximum level (Figure 6.2), and that approximately 20% of the glucose should have remained unused in the effluent since the ammonium (nitrogen source for bacterial growth) should have been totally consumed (Figure 6.3). The model chemical balance assumes that for every mole of glucose consumed, 1.2 moles of ammonium should be utilized for bacterial growth. Nitrate use predicted by the simulator was lower than that measured during the experiment (Figure 6.4). The reason may be that nitrogen N_2 is considered as the only product from nitrate in the model. If nitrate was being used to produce products not monitored during the experiment nor considered in the simulator, low nitrate use would be the expected simulation result.

Since no significant growth and production appear to have occurred during the first four treatments (Figures 6.2 and 6.3), the observed experimental permeability reduction during this

period may have been due to bacterial retention or facial plugging in the core. The ratio of the brine permeability after the i th treatment to the original brine permeability is defined as the permeability reduction factor (PRF), shown in Figure 6.5. After treatment four, in situ growth of bacteria and large production of biogenic gas (Figure 6.1) resulted in a sharp reduction of permeability. However, simulation results have higher values of PRF than those of the experimental results (Figure 6.5). There may be two reasons for this phenomenon. First, glucose consumption was underpredicted by the model. Second, bacterial plugging was considered to be the only factor reducing water permeability in the model. However, biogenic gas, either mobile or immobile, could also reduce the relative permeability to the flowing water phase. Unfortunately, it must be concluded that the equation used to estimate the permeability reduction factor in the model is not adequate for actual predictions.

5.3 CONCLUSIONS

1. The model described in last year's annual report, Knapp, et al., (1990), has been further validated by comparison with a one-dimension sandstone core experiment. Results suggest additional understanding of the metabolic process would improve the quality of the model.
2. The equation used to estimate PRF is not adequate for predictive purposes.

REFERENCES

Knapp, R. M., M. J. McInerney, D. E. Menzie and J. L. Chisholm. 1990. "Microbial Field Pilot Study: Annual Report for the Period November 22, 1988 - December 31, 1989", DOE/BC/14246-5, 68-96.

Leonard, B. P., 1984. "Third-order upwinding as a rational basis for computational fluid dynamics", Computational Techniques and Applications: CTAC-83, Editors, J. Noye and C. Fletcher, 106-120.

Silfanus, N. J., 1990. Microbial Mechanisms for Enhanced Oil Recovery from High Salinity Core Environments, M.S. Thesis, The University of Oklahoma, 78 pp.

FIGURE 5.1: CUMULATIVE PRODUCTION OF TOTAL GASES (CO₂ & N₂) DURING MEOR PROCESS (CORE #6)

**FIGURE 5.2: CONSUMPTION OF GLUCOSE DURING MEOR PROCESSES
(CORE #6)**

**FIGURE 5.3: CONSUMPTION OF AMMONIUM DURING MEOR PROCESSES
(CORE #6)**

**FIGURE 5.4: CONSUMPTION OF NITRATE DURING MEOR PROCESSES
(CORE #6)**

FIGURE 5.5: PERMEABILITY REDUCTION DURING MEOR PROCESSES (CORE #6)

6. RESERVOIR CHARACTERIZATION AND SIMULATION

D.J. Garvey, Xu Zhang, R.M. Knapp

Prior to 1990, the BOAST (Fanchi, et al, 1982) numerical reservoir simulator was used to model the Southeast Vassar Vertz Sand Unit (SEVVSU). In February 1990, the input data file representing the SEVVSU model was converted for use with the BOAST II (Fanchi, et al, 1987) reservoir simulator. By December 1990, a conversion of the input data file for use with the ECL ECLIPSE 100 black oil simulator was underway.

During this period the geological model of the reservoir underwent considerable evolution, both as a result of history matching efforts, and from information about the operating history provided by the current operator of the field, Sullivan and Co.

The controlled parameter in the simulation is oil production. The history matching parameters are total field water production, the timing of the onset of water production in individual wells, and individual well water production. The match between observed and simulated fieldwide water production is within 5 percent (Figure 6.1), indicating that the reservoir capacity and aquifer support have been adequately modeled.

The matches of the onset of water production for individual wells are considered to be excellent, indicating that local variations in reservoir capacity as well as oil/water relative permeability have been adequately modeled.

The matches between observed and simulated water production for individual wells is more variable. In the area of the pilot study the match is within 5% and is considered acceptable. With the exception of two areas which will be discussed separately, simulated water production in the wells in the remainder of the field match the observed data to within 10%.

Wells 1A-5 and 1A-7 have an unusually early onset of water production. In addition, the chemical analyses of the water produced from these wells indicates that it may be from a source which is different from that of the water in the main body of the SEVVSU. Attempts were made to model this part of the reservoir as a separate sand lens with its own oil-water contact and water source. However, discussions with the operator, Sullivan and Co., indicate that the source of the water may be a separate Upper Vertz sand which is present "uphole" in the 1A-5 and 1A-7 and is believed to be communicating through the casing annulus to the SEVVSU reservoir.

Wells 8-2 and 8-3 also have observed water productions which have been difficult to match. It appears that a very low permeability zone exists between these wells and the main body of the reservoir. The history match here is marginal at best.

The geological model which has evolved as a result of these efforts is that of a braided stream containing longitudinal bar sands (Figure 6.2). Clay drapes or clay filled channel cuts are interpreted as the permeability barriers which have been included in the model.

REFERENCES

Fanchi, J. R., K. J. Harpole and S. W. Bujnowski, 1982. "BOAST: a three-dimensional, three-phase black oil applied simulation tool (Version 1.1)", DOE/BC/10033.3, U.S. Department of Energy, Bartlesville, OK, 180 pp.

Fanchi, J. R., J. E. Kennedy and D. L. Dauben, 1987. "BOAST II: a three-dimensional, three-phase black oil applied simulation tool", DOE/BC-88/2/SP, U.S. Department of Energy, Bartlesville, OK 161 pp plus Appendices A.1 - K.173.

Cumulative Water Production FOR THE SEVVSU FIELD

FIGURE 6.1 FIELDWIDE CUMULATIVE WATER PRODUCTION

FIGURE 6.2 SEVVSU ENVIRONMENT DEPOSITION BRAIDED STREAM WITH LONGITUDINAL BAR SANDS

END

DATE
FILMED

4 / 30 / 92