MASTER

**Drag Force on a Conductive
Spherical Drop in a Nonuniform
Magnetic Field**

J. Walker
W. M. Wells

OAK RIDGE NATIONAL LABORATORY
OPERATED BY UNION CARBIDE CORPORATION · FOR THE DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
NTIS price codes—Printed Copy: A03; Microfiche A01

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

Contract No. W-7405-eng-26

FUSION ENERGY DIVISION

DRAG FORCE ON A CONDUCTIVE SPHERICAL DROP
IN A NONUNIFORM MAGNETIC FIELD

J. Walker
W. M. Wells

September 1979

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37830
operated by
UNION CARBIDE CORPORATION
for the
DEPARTMENT OF ENERGY

leg

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

CONTENTS

ABSTRACT	v
INTRODUCTION	1
1. GEOMETRY, ASSUMPTIONS, AND GOVERNING EQUATIONS	3
2. CURRENT PATHS AND VALUES	6
3. BODY FORCE AND DRAG FORCE	10
4. PRESSURE AND DROP DEFORMATION	13
5. SIDEWARD DISPLACEMENT	17
REFERENCE	21

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

ABSTRACT

A high velocity lithium droplet cloud traversing the magnetic field of a fusion reactor may be useful for collecting plasma ions and their energy. In this report, the forces associated with such motion in nonuniform magnetic fields are derived.

INTRODUCTION

Fusion reactors may require magnetic divertors to carry off plasma impurities. A magnetic divertor consists of conductors properly arrayed to distort flux lines in the edge of the plasma into a configuration where they are more or less removed from the plasma region. This edge plasma will follow the diverted flux and can, in principle, be collected. This provides a mechanism to prevent impurities from the wall from reaching the bulk of the plasma and also to divert impurities away from the wall as they leave the plasma.

Collection of both the incident ions and the associated heat flux promises to be a technological challenge. In the former case, the ion collection load is estimated to be of the order of 10^{23} /sec and the attendant surface heat flux is expected to be in excess of 100 MW. The particle collection load is largely D and T ions. Proposals for accomplishing these tasks have involved the use of solid hydride formers and the use of liquid lithium, also a hydride former. In the case of the solid, the feasibility of the requisite number of load-unload cycles ($\sim 10^5$) while maintaining good structural and heat transfer properties is doubtful. Also, the process for ion removal may involve excessive frequency and temperatures.

Proposals for the use of liquid lithium have entailed gravity-driven flow in strong magnetic field and also in contact with a solid metal boundary. This situation leads to excessive resistance to flow and to insufficient velocity. This is because of magnetohydrodynamic (MHD) effects associated with current that flows through the stationary return path.

It has been proposed¹ that droplets of lithium formed from high velocity jets be utilized to accomplish these two functions. The jets would be formed by nozzles away from the large magnetic fields. In a short distance the jets are expected to break up. The drops would traverse the strong magnetic field region and then be collected in a region removed from the magnetic field. The essential difference compared with the earlier proposals is that moving, electrically conductive liquid is not in contact with a stationary current return path while traversing the strong magnetic field.

This report presents the theory to treat the motion of droplets making this journey. The first author derived the theory and the second author provided the context for this work.

1. GEOMETRY, ASSUMPTIONS, AND GOVERNING EQUATIONS

The spherical drop of liquid metal has a radius a and is moving in the z direction with velocity V , as indicated in Fig. 1. The coordinate system is fixed in space, and the center of the sphere is located at the origin of the coordinate system at the instant of analysis. There is a transverse magnetic field in the y direction which varies in strength in the z direction, $B_y(z)$. We can write a Taylor series for this field about $z = 0$,

$$B_y(z) = B_y(0) + z \frac{\partial B_y}{\partial z}(0) + \frac{1}{2} z^2 \frac{\partial^2 B_y}{\partial z^2}(0) + \dots$$

ORNL-DWG 79-2007 FED

Fig. 1. Spherical drop of liquid metal.

If the distance over which the magnetic field strength changes is much larger than the radius of the spherical drop, then

$$B_y(0) \gg a \frac{\partial B_y}{\partial z}(0) \gg \frac{1}{2} a^2 \frac{\partial^2 B_y}{\partial z^2}(0) \dots$$

We therefore retain only the first two terms in this Taylor series,

$$B_y(z) = B_0 + z \frac{\partial B_0}{\partial z},$$

where $B_0 = B_y(0)$, $\partial B_0 / \partial z = \partial B_y / \partial z(0)$, and the second term is much smaller than the first.

The governing equations for incompressible fluid are

$$\rho \left[\frac{\partial \underline{V}}{\partial t} + (\underline{V} \cdot \nabla) \underline{V} \right] = -\nabla p + \underline{j} \times \underline{B} + \eta \nabla^2 \underline{V}, \quad (1a)$$

$$\nabla \cdot \underline{V} = 0, \quad (1b)$$

$$\nabla \cdot \underline{j} = 0, \quad (1c)$$

$$\underline{j} = \sigma(-\nabla \phi + \underline{V} \times \underline{B}), \quad (1d)$$

where $\underline{V}$, p , $\underline{j}$, $\underline{B}$, and ϕ are the fluid velocity, pressure, electric current density, magnetic field, and electric potential, respectively, and ρ , η , and σ are the fluid's density, viscosity, and electrical conductivity, respectively. These equations assume that the magnetic Reynolds number $R_m = \mu \sigma V a \ll 1$, where μ is the fluid's magnetic permeability, and that the magnetic field is steady, rather than a function of time.

We write

$$\underline{V} = V \hat{k} + \underline{V}',$$

where V is the drop velocity, which is the same at every point in the drop, and $\hat{k}$ is a unit vector in the z direction. The body forces obtained under the assumption that the drop moves as a rigid body, i.e., $\underline{V}' \equiv 0$, cannot in fact be balanced entirely by a pressure gradient. Therefore, there must be some internal motion relative to the rigid body motion. However, we will show that the velocity in this relative motion is comparable to the change in drop velocity resulting from the drag force on the drop, and this is much smaller than the initial drop velocity.

Therefore we assume that $|\underline{V'}| \ll V$ and neglect $\underline{V'}$, and we also assume that $\partial \underline{V} / \partial t$ is negligible. Therefore Eq. (1a) becomes

$$\underline{\nabla p} = \underline{j} \times \underline{B} . \quad (2)$$

2. CURRENT PATHS AND VALUES

To describe current paths, we recognize that $\underline{B} = B_0 \hat{\underline{j}}$, much smaller terms being neglected, where $\hat{\underline{j}}$ is a unit vector in the y direction. Introducing this into Eq. (2) and taking the curl of this equation gives

$$B_0 \frac{\partial \hat{\underline{j}}}{\partial y} = 0$$

because $\underline{\nabla} \times \underline{\nabla} p = 0$, $\underline{\nabla} \times (\hat{\underline{j}} \times \hat{\underline{j}}) = (\partial \hat{\underline{j}} / \partial y) - (\underline{\nabla} \cdot \hat{\underline{j}}) \hat{\underline{j}}$, and $\underline{\nabla} \cdot \hat{\underline{j}} = 0$. Consider a cylindrical coordinate system (r, θ, y) with base vectors $\hat{\underline{e}}_r$, $\hat{\underline{e}}_\theta$, and $\hat{\underline{e}}_y$, as illustrated in Fig. 2. Note that $\hat{\underline{e}}_y = \hat{\underline{j}}$. The "top" and "bottom" surfaces of the drop as seen by the magnetic field are given by

$$y = \pm (a^2 - r^2)^{1/2}.$$

ORNL-DWG 79-2008 FED

Fig. 2. Cylindrical coordinate system for describing current paths.

Because the surrounding vacuum carries no electric current, the boundary condition on the electric current in the liquid is

$$\hat{\underline{j}} \cdot \hat{\underline{n}} = 0$$

at the surface, where $\hat{\underline{n}}$ is an outward unit normal on the surface. The unit normal can be found with the following procedure. A scalar function is defined by

$$F(r, \theta, y) = \pm y - (a^2 - r^2)^{1/2} .$$

This function equals zero on the drop surface, so this surface is a surface of constant value for this function. The gradient of any scalar function is perpendicular to the function's constant value surfaces, so

$$\underline{\nabla} F = r(a^2 - r^2)^{-1/2} \hat{\underline{e}}_r \pm \hat{\underline{e}}_y$$

is perpendicular to the drop surface. Normalizing to get unit length, we obtain

$$\hat{\underline{n}} = a^{-1} r \hat{\underline{e}}_r \pm a^{-1} (a^2 - r^2)^{1/2} \hat{\underline{e}}_y \text{ at } y = \pm (a^2 - r^2)^{1/2} .$$

The boundary condition on the electric current is

$$a^{-1} r j_r \pm a^{-1} (a^2 - r^2)^{1/2} j_y = 0 \text{ at } y = \pm (a^2 - r^2)^{1/2} .$$

Since $\partial j / \partial y = 0$, j_r , j_θ , and j_y are functions of r and θ alone, so the boundary conditions become

$$a^{-1} r j_r(r, \theta) + a^{-1} (a^2 - r^2)^{1/2} j_y(r, \theta) = 0 ,$$

$$a^{-1} r j_r(r, \theta) - a^{-1} (a^2 - r^2)^{1/2} j_y(r, \theta) = 0 .$$

When these equations are added, they give $j_r(r, \theta) = 0$, and when they are subtracted, they give $j_y(r, \theta) = 0$. Therefore, $j_\theta(r, \theta)$ is the only nonzero current. Equation (1c) becomes $\partial j_\theta / \partial \theta = 0$, so j_θ is a function of r alone and $\underline{j} = j_\theta(r) \hat{\underline{e}}_\theta$.

By ignoring the nonuniformity in the magnetic field, we have come to the conclusion that the electric current flows around cylinders which are concentric with the diameter parallel to the magnetic field, and that the current on one of these cylinders is constant, as illustrated in Fig. 3(a). If we were to include the nonuniformity of the field, the effect would be to distort the cylinders slightly. Where the field strength is stronger, the characteristic surface must be longer and parallel to $\underline{B}$, and vice versa. Thus, if $\underline{B}$ is increasing in the z direction, the surface might look like the diagram in Fig. 3(b). Note that the total current flowing around a surface is constant, so that where the magnetic field is strong and the surface is long, the current density will be small, and where the field is weak and the surface is short, the current density will be large. Because the body force is equal to the product of current density and field strength, and because where the field is large the current is small and vice versa, the forces are somewhat insensitive to nonuniform field effects. Because $a \partial B_0 / \partial z \ll B_0$, all nonuniform field effects on the shape of the characteristic surfaces and on variation of current density around these surfaces will be neglected.

ORNL - DWG 79-2009 FED

Fig. 3. Pattern of electric flow current (a) without and (b) with nonuniformity of field.

To compute the value of $j_\theta(r)$ on one of the cylinders of radius r (see Fig. 4), we consider the θ component of Ohm's law, Eq. (1d). The velocity of the fluid is the drop velocity, so that $\underline{V} = V\hat{k}$, where V is a constant; $\hat{k} = \cos \theta \hat{e}_r - \sin \theta \hat{e}_\theta$; and $\underline{V} = V \cos \theta \hat{e}_r - V \sin \theta \hat{e}_\theta$. The magnetic field is in the y direction, so that

$$\underline{B} = \left(B_0 + z \frac{\partial B_0}{\partial z} \right) \hat{j} = \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right) \hat{e}_y,$$

because $z = r \cos \theta$ and $\hat{j} = \hat{e}_y$. Therefore the θ component of Eq. (1d) is

$$j_\theta(r) = -\sigma \left[r^{-1} \frac{\partial \phi}{\partial \theta} + V \cos \theta \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right) \right].$$

When this equation is integrated from $\theta = 0$ to $\theta = 2\pi$ and the result is divided by 2π , it gives

$$j_\theta(r) = -\frac{1}{2} \sigma V r \frac{\partial B_0}{\partial z},$$

because $\phi(\theta = 0) = \phi(\theta = 2\pi)$.

ORNL-DWG 79-2010 FED

Fig. 4. Model for computing $j_\theta(r)$.

3. BODY FORCE AND DRAG FORCE

The Lorentz body force per unit volume is

$$\begin{aligned} \underline{f} &= \underline{j} \times \underline{B} = -\frac{1}{2} \sigma V r \frac{\partial B_0}{\partial z} \hat{\underline{e}}_\theta \times \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right) \hat{\underline{e}}_y \\ &= -\frac{1}{2} \sigma V r \frac{\partial B_0}{\partial z} \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right) \hat{\underline{e}}_r . \end{aligned}$$

This is illustrated in Fig. 5. First we are interested in the net force on the drop in the z direction because this is the drag force on the drop due to MHD effects. We calculate

$$dF_z = \underline{f} \cdot \hat{\underline{k}} dV ,$$

where $\hat{\underline{k}} = \cos \theta \hat{\underline{e}}_r - \sin \theta \hat{\underline{e}}_\theta$ and $dV = dr(r d\theta) dy$. To integrate over the entire drop, we integrate from $\theta = 0$ to $\theta = 2\pi$, from $y = -(a^2 - r^2)^{1/2}$ to $y = (a^2 - r^2)^{1/2}$, and from $r = 0$ to $r = a$, so that

ORNL-DWG 79-2011 FED

Fig. 5. Lorentz body force per unit volume.

$$F_z = \int_0^a \int_{-(a^2-r^2)^{1/2}}^{(a^2-r^2)^{1/2}} \int_0^{2\pi} \left[-\frac{1}{2} \sigma V r \frac{\partial B_0}{\partial z} \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right) \right] \times \cos \theta r d\theta dy dr .$$

If the integrations with respect to y and θ are carried out, the result is

$$F_z = -\pi \sigma V \left(\frac{\partial B_0}{\partial z} \right)^2 \int_0^a (a^2 - r^2)^{1/2} r^3 dr .$$

The result of integrating is

$$F_z = -\frac{2}{15} \pi a^5 \sigma V \left(\frac{\partial B_0}{\partial z} \right)^2 .$$

Because the field gradient appears squared, the force is opposed to the motion whether the field is increasing or decreasing in the direction of the motion. The magnetic field strength is given by a graph like the one in Fig. 6. It seems reasonable to assume that B_y is given by

$$B_y = \frac{1}{2} B_u [1 - \cos (\pi z/L)]$$

ORNL DWG 79 2012 FED

Fig. 6. Magnetic field strength.

for $0 \leq z \leq L$, so that

$$\frac{\partial B_y}{\partial z} = \frac{\pi B_u}{2L} \sin(\pi z/L) .$$

Because $F_z = m \, dV/dt$, where $m = (4/3)\pi a^3 \rho$ is the mass of the drop, and because $V = dz/dt$, we have

$$\frac{F_z}{V} = - \frac{2}{15} \pi a^5 \sigma \left(\frac{\partial B_0}{\partial z} \right)^2 = \frac{4}{3} \pi a^3 \rho \frac{dV/dt}{dz/dt}$$

or

$$\frac{dV}{dz} = - \frac{\sigma a^2}{10\rho} \left(\frac{\partial B_0}{\partial z} \right)^2 .$$

Introducing the expression assumed for the field gradient where the drop enters the field, we obtain an expression for the change in drop velocity during the entry,

$$\Delta V = - \frac{\sigma a^2}{10\rho} \left(\frac{\pi B_u}{2L} \right)^2 \int_0^L \sin^2(\pi z/L) \, dz$$

or

$$\Delta V = -\pi^2 a^2 \sigma B_u^2 / 80\rho L .$$

This is the change in the drop's velocity during its motion from outside the magnetic field to the region of uniform magnetic field. An equal decrease in velocity results during the drop's motion from the uniform field region to a point outside the field, so that the total change in velocity of a drop moving across the field region is

$$\Delta V = -\pi^2 a^2 \sigma B_u^2 / 40\rho L .$$

4. PRESSURE AND DROP DEFORMATION

Equation (2), together with the result for the Lorentz body force, gives

$$\frac{\partial p}{\partial r} = -\frac{1}{2} \sigma V r \frac{\partial B_0}{\partial z} \left(B_0 + r \cos \theta \frac{\partial B_0}{\partial z} \right).$$

The second term in the parentheses is much smaller than the first, and we will neglect it. We should note, however, that it is the second term that accounts for the drag force, because the first produces a symmetric force field with no net resultant. Therefore we are neglecting forces comparable to the drag force F_z when we neglect this term. The neglected term implies that p depends on θ , but because the electromagnetic or Lorentz body force is radial, it cannot balance the pressure force $r^{-1} \partial p / \partial \theta$, and Eq. (1a) implies that $\underline{V}$ is not equal to the constant value of the drop's velocity. However, this unbalanced pressure force is also comparable to the drag force, and the deviations from the rigid body velocity are comparable to the ΔV just computed. If the change in the drop's velocity due to entering and leaving the field, namely ΔV , is much smaller than the drop's velocity V , then the motion in the drop relative to the drop's velocity, namely $\underline{V}'$, is also much smaller than the drop's velocity V . This justifies the assumption (made in Sect. 1) that $|\underline{V}'| \ll V$.

Neglecting the second term inside the parentheses, we integrate the equation to obtain the pressure,

$$p = p_0 - \frac{1}{4} \sigma V r^2 B_0 \frac{\partial B_0}{\partial z},$$

where p_0 is the (unknown) pressure at $r = 0$.

In the absence of any MHD effects, i.e., outside the field or in the uniform field region, the pressure in the drop is constant. If s is the surface tension force per unit length, then $\pi a^2 p_s = 2\pi a s$, or $p_s =$

$2s/a$, as shown schematically in Fig. 7(a). With MHD effects present, the pressure is a function of radial distance from the diameter parallel to the field, as shown in Fig. 7(b). In the figure we introduce the term p_1 [$= p(r = a)$]. Then $p_1 > p_0$ for $(\partial B_0/\partial z) < 0$ and $p_1 < p_0$ for $(\partial B_0/\partial z) > 0$. Because locally the pressure is related to the surface tension through the surface curvature, $r_c p \sim s$ or $r_c \sim s/p$. This relationship is shown in Fig. 8. Where the pressure is larger, the radius of curvature is smaller, and vice versa. For $(\partial B_0/\partial z) > 0$, $p_1 < p_0$, and for $(\partial B_0/\partial z) < 0$, $p_1 > p_0$. The resulting deformations for these cases are shown in Fig. 9. Because it is the difference in pressure which causes the deformation, a coefficient to estimate the deformation is the

ORNL-DWG 79-2013 FED

Fig. 7. (a) Constant pressure in the drop, no MHD effects present. (b) Pressure as a function of radial distance from the diameter parallel to the field, MHD effects present.

ORNL-DWG 79-2014 FED

Fig. 8. Relation of pressure to surface tension.

ORNL-DWG 79-2015 FED

Fig. 9. Deformation of the drop (a) when $p_1 < p_0$ and (b) when $p_1 > p_0$.

ratio of the maximum pressure difference inside the drop, neglecting the deformation, to the pressure in a drop due to surface tension alone.

That is,

$$\Delta p = p(r = 0) - p(r = a) = \frac{1}{4} \sigma V a^2 B_0 \frac{\partial B_0}{\partial z} ,$$

so

$$\frac{\Delta p}{p_s} = \frac{a^3}{8s} \sigma V B_0 \frac{\partial B_0}{\partial z} .$$

This is a dimensionless coefficient that should reflect the degree of drop deformation. It should be much less than 1 to indicate negligible drop deformation.

5. SIDEWARD DISPLACEMENT

A nonuniform magnetic field always implies curvature to the field lines. We can see this from Ampère's law, which for $R_m \ll 1$ is

$$\nabla \times \underline{B} = 0.$$

For $\underline{B} = B_y(y,z)\hat{j} + B_z(y,z)\hat{k}$, i.e., a plane magnetic field with no x component and no x dependence, this equation becomes

$$\frac{\partial B_z}{\partial y} = \frac{\partial B_y}{\partial z}.$$

Because $\partial B_y / \partial z \neq 0$, $B_z \neq 0$. The field line curvature is illustrated in Fig. 10. The effect of the magnetic field line curvature can be seen in Fig. 11. The characteristic surfaces tilt with the field lines, and the force previously computed as F_z acts perpendicular to the characteristic surfaces and field lines. This force has a component perpendi-

ORNL-DWG 79-2016 FED

Fig. 10. Field line curvature.

Fig. 11. Effect of field line curvature on a drop.

cular to the velocity as well as parallel to it. If F_{z_0} is the F_z computed before for $B_z = 0$, then

$$F_z = F_{z_0} \cos \alpha \approx F_{z_0}$$

$$F_y = F_{z_0} \sin \alpha \approx F_{z_0} \tan \alpha \approx F_{z_0} (B_z / B_y) ,$$

assuming that α is small.

Since $B_z = 0$ at the plane of symmetry, taken here as the $y = 0$ plane, we can determine B_z from

$$B_z(y, z) = \int_0^y \frac{\partial B_y}{\partial z} (y^*, z) dy^* .$$

In the drop blanket of thickness T shown in Fig. 12, the largest effect will be felt by the drop at the edge of the drop blanket. If we note that $\partial B_y / \partial z$ is the same as $\partial B_0 / \partial z$, then we can estimate B_z at the edge of the blanket as

$$B_z = \frac{1}{2} T \frac{\partial B_0}{\partial z} .$$

Fig. 12. Drop blanket of thickness T.

As a typical B_y , we choose $B_u/2$, where B_u is the field strength in the uniform field region. Therefore,

$$F_y = F_{z0} T \frac{\partial B_0}{\partial z} \bigg/ B_u = m \frac{d^2 y}{dt^2}.$$

Integration gives

$$\Delta y = \tau^2 F_{z0} T \frac{\partial B_0}{\partial z} \bigg/ 2mB_u,$$

where Δy is the displacement of a drop at the edge of the blanket away from the other drops and τ is the time spent in the nonuniform field region. Because

$$\tau = L/v,$$

where L is the length of the nonuniform field region, as before, and expressions for m and F_{z0} have been given, we obtain

$$\Delta y = a^2 L^2 T \sigma \left(\frac{\partial B_0}{\partial z} \right)^3 \bigg/ 20 \rho V B_u.$$

As a drop enters the magnetic field, it will move away from the plane of symmetry by this displacement, and as it leaves the magnetic field, it returns to its original distance from the plane of symmetry. This is shown schematically in Fig. 13.

ORNL-DWG 79-2049 FED

Fig. 13. Displacement of a drop as it moves through a region of uniform magnetic field.

REFERENCE

1. W. M. Wells, *ORNL TNS Program - Evaluation of the Bundle Divertor*, ORNL/TM-6727, to be published.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

ORNL/TM-6976
Dist. Category UC-20 d

INTERNAL DISTRIBUTION

1. W. R. Becraft	17. J. L. Scott
2. L. A. Berry	18. T. E. Shannon
3. E. E. Bloom	19. J. Sheffield
4. T. G. Brown	20. D. Steiner
5. J. D. Callen	21. J. S. Watson
6. D. D. Cannon	22-32. W. M. Wells
7. J. L. Dunlap	33. G. W. Wiseman
8. W. A. Houlberg	34-35. Central Research Library
9. T. J. Huxford	36-37. Fusion Energy Division
10. M. S. Lubell	Library
11. J. W. Lue	38. Fusion Energy Division
12. O. B. Morgan	Communications Center
13. Y-K. M. Peng	39-40. Laboratory Records Department
14. R. L. Reid	41. Laboratory Records, ORNL-RC
15. M. W. Rosenthal	42. ORNL Patent Office
16. C. Sardella	43. Document Reference Section

EXTERNAL DISTRIBUTION

44. D. J. Anthony, General Electric Co., Bldg. 23, Rm. 290, 1 River Rd., Schenectady, NY 12345
45. J. E. Baublitz, Office of Fusion Energy, Department of Energy, Washington, DC 20545
46. D. S. Beard, Office of Fusion Energy, Department of Energy, Washington, DC 20545
47. S. L. Bogart, Science Applications, Inc., 8400 Westpark Drive, McLean, VA 22102
48. R. Botwin, Grumman Aerospace Corp., Bethpage, NY 11714
49. J. F. Clarke, Office of Fusion Energy, Department of Energy, Washington, DC 20545
50. F. E. Coffman, Office of Fusion Energy, Department of Energy, Washington, DC 20545
51. D. Cohn, Massachusetts Institute of Technology, Cambridge, MA 02139
52. Library, Culham Laboratory, Abingdon, Oxon, OX14 3DB, United Kingdom
53. H. W. Deckman, Advanced Energy Systems Laboratory, Government Research Laboratories, Exxon Research and Engineering Co., P.O. Box 8, Linden, NJ 07036
54. C. A. Flanagan, Westinghouse Electric Corp., Fusion Power Systems, P.O. Box 10864, Pittsburgh, PA 15236
55. H. K. Forsen, Exxon Nuclear Co., Inc., 777 106th Ave., Bellevue, WA 98009

56. H. P. Furth, Princeton Plasma Physics Laboratory, Princeton University, P.O. Box 451, Princeton, NJ 08540
57. R. W. Gould, Mail Stop 116-81, California Institute of Technology, Pasadena, CA 91125
58. R. Hancox, Culham Laboratory, Abingdon, Oxon, OX14 3DB, United Kingdom
59. C. R. Head, Office of Fusion Energy, Department of Energy, Washington, DC 20545
60. R. L. Hirsch, Exxon Research and Engineering Co., P.O. Box 101, Florham Park, NJ 07932
61. M. A. Hoffman, Lawrence Livermore Laboratory, P.O. Box 808, Livermore, CA 94550
62. Anthony Hsu, Office of Fusion Energy, Department of Energy, Washington, DC 20545
63. D. L. Jassby, Princeton Plasma Physics Laboratory, Princeton University, P.O. Box 451, Princeton, NJ 08540
64. V. A. Maroni, Argonne National Laboratory, 9700 South Cass Ave., Argonne, IL 60439
65. D. M. Meade, Princeton Plasma Physics Laboratory, Princeton University, P.O. Box 451, Princeton, NJ 08540
66. P. B. Mohr, Lawrence Livermore Laboratory, P.O. Box 808, Livermore, CA 94550
67. M. R. Murphy, Office of Fusion Energy, Department of Energy, Washington, DC 20545
68. J. M. Rawls, General Atomic Co., P.O. Box 81608, San Diego, CA 92138
69. P. Reardon, Princeton Plasma Physics Laboratory, Princeton University, P.O. Box 451, Princeton, NJ 08540
70. T. Reuther, Office of Fusion Energy, Department of Energy, Washington, DC 20545
71. M. Roberts, Office of Fusion Energy, Department of Energy, Washington, DC 20545
72. P. H. Sager, Jr., General Atomic Co., P.O. Box 81608, San Diego, CA 92138
73. G. Schilling, Princeton Plasma Physics Laboratory, Princeton University, P.O. Box 451, Princeton, NJ 08540
74. W. M. Stacey, Jr., School of Nuclear Engineering, Georgia Institute of Technology, Atlanta, GA 30332
75. F. Thomas, Grumman Aerospace Corp., Bethpage, NY 11714
76. T. C. Varljen, Westinghouse Electric Corp., Fusion Power Systems, P.O. Box 10864, Pittsburgh, PA 15236
77. S. S. Waddle, Department of Energy, Oak Ridge Operations, P.O. Box E, Oak Ridge, TN 37830
- 78-88. J. S. Walker, University of Illinois, Urbana, IL 61801
89. J. Willis, Office of Fusion Energy, Department of Energy, Washington, DC 20545
90. W. Wilkes, Mound Laboratories, Miamisburg, OH 45432
91. E. Ziurys, Office of Fusion Energy, Department of Energy, Washington, DC 20545
92. K. Zwilsky, Office of Fusion Energy, Department of Energy, Washington, DC 20545

93. Office of Assistant Manager, Energy Research and Development,
Department of Energy, Oak Ridge Operations, P.O. Box E,
Oak Ridge, TN 37830
- 94-244. Given distribution as shown in TID-4500, Magnetic Fusion
Energy (Distribution Category UC-20 d, Fusion Systems)