HYDROGEN AS A FUEL

A report by the
HYDROGEN PANEL of the
Committee on Advanced Energy Storage Systems
Energy Engineering Board
Assembly of Engineering
National Research Council

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NATIONAL ACADEMY OF SCIENCES
Washington, D.C. 1979

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE: The project that is the subject of this report was approved by the Governing Board of the National Research Council, whose members are drawn from the Councils of the National Academy of Sciences, the National Academy of Engineering, and the Institute of Medicine. The members of the committee responsible for the report were chosen for their special competences and with regard for appropriate balance.

This report has been reviewed by a group other than the authors according to procedures approved by a report review committee consisting of members of the National Academy of Sciences, the National Academy of Engineering, and the Institute of Medicine.

This study was supported under Contract No. EY-76-C-02-2708-012 between the U.S. Department of Energy and the National Academy of Sciences.

PREFACE

Hydrogen, one of the most abundant elements, does not appear in a pure form in the natural state but is bound into a variety of molecules and compounds that include water and hydrocarbons. It is widely used as a feedstock in the chemical and petroleum refining industries, where it is usually obtained from reforming of methane (natural gas) or petroleum. Although hydrogen has excellent combustion characteristics, it is little used as a fuel (except in space rockets) because of the economic advantages of using hydrocarbons directly as fuel. Small amounts of very pure hydrogen are also produced from water by electrolysis. In principle, hydrogen can also be produced by thermochemical splitting of the water molecule.

The hydrocarbon sources for hydrogen are non-renewable and, hence, are subject to becoming much more costly or more difficult to obtain in the future. By contrast, water as a hydrogen source can be considered as practically limitless in availability. Furthermore, hydrogen from non-carbon sources can be both produced and used without introducing carbon-oxides into the atmosphere. Therefore, there are numerous technical incentives for developing national capabilities to produce, transport, and store hydrogen from non-carbon sources as a possible major future energy carrier.

The production timetable, the technical risks, and the uncertain need for greater hydrogen capabilities make it appropriate for the government to sponsor hydrogen R&D in coordination with that being conducted by the private sector. Such R&D activities are included in the programs of the U.S. Department of Energy (DOE). The DOE has assigned the responsibility for R&D on hydrogen production from non-carbon sources, as well as on all hydrogen transport and storage problems, to the Energy Storage Systems Division. Recognizing the complex factors that will govern the need for enhanced non-carbon-sourced hydrogen capabilities, the Energy Storage Systems Division requested the National Research Council to determine suitable criteria for establishing the pace, timing, and technical content of appropriate R&D programs.

In response to the DOE request, the Research Council's Committee on Advanced Energy Storage Systems established a Hydrogen Panel comprised of a chairman and four members from the committee, augmented with five additional experts. The panel met a number of times from March 1978 to

March 1979 to receive presentations and to engage in discussions on the topic. During the course of its deliberations, the panel concluded that the criteria for hydrogen production, transport, and storage R&D programs could not be developed without a concurrent examination of the status and problems of the principal hydrogen uses. Consequently, a consideration of potential future hydrogen uses became a major part of the study.

This report presents the panel's findings, as approved by the Committee on Advanced Energy Storage Systems. The general technical and economic characteristics of hydrogen sources are discussed in Chapter II; the outlook for future feedstock uses in Chapter III; and some of the general problems associated with the transport and storage of hydrogen in Chapter IV. Chapters V through VII present the prospects and problems associated with the widespread future use of hydrogen as a heating, automotive, and aircraft fuel, respectively. The status of fuel cells and their role in future hydrogen applications is examined in Chapter VIII. Chapter IX offers a broad perspective that the panel holds should be applied in determining the content of hydrogen R&D programs. Chapter X summarizes known international activities in the hydrogen field. Finally, Chapter XI presents the principal findings and recommendations reached by the panel with regard to the formulation of a U.S. hydrogen R&D program.

The panel is grateful to the following individuals who contributed to this study as invited participants in briefings and discussions: Vic Biederman, Institute of Gas Technology; G. Daniel Brewer, Lockheed California Co.; Roosevelt Fernandez, Niagara Mohawk Power Co.; Fritz Kalhammer, Electric Power Research Institute; Lester Machta, U.S. National Oceanographic and Atmospheric Administration; John Pangborn, Institute of Gas Technology; Frank Salzano, Brookhaven National Laboratory; S. Srinivasan, Brookhaven National Laboratory; Russell Stebar, General Motors Corporation; James Swisher, U.S. Department of Energy, and Ronald Wooley, Billings Energy Corporation.

HYDROGEN PANEL
COMMITTEE ON ADVANCED ENERGY STORAGE SYSTEMS

Gerald L. Decker, *Chairman*, Kaiser Aluminum and Chemical Corporation

S. William Gouse, Jr., The MITRE Corporation

Derek P. Gregory, Institute of Gas Technology

Robert L. Hirsch, Exxon Research and Engineering Company

Kenneth C. Hoffman, Mathtech, Inc.

Ida R. Hoos, University of California at Berkeley

John E. Johnson, Union Carbide Corporation

John P. Longwell, Massachusetts Institute of Technology

William E. Siri, University of California at Berkeley

C. M. Sliepcevich, University of Oklahoma

Ronald Smelt, Lockheed Aircraft Corporation (Retired)

CONSULTANT

Bruce W. Wilkinson, Michigan State University

COMMITTEE ON ADVANCED ENERGY STORAGE SYSTEMS

John P. Longwell, *Chairman*, Massachusetts Institute of Technology

Paul F. Chenea, General Motors Corporation

David L. Douglas, Electric Power Research Institute

Kenneth C. Hoffman, Mathtech, Inc.

Ida R. Hoos, University of California

Robert A. Huggins, Stanford University

Robert K. Koger, North Carolina Utilities Commission

Heinz G. Pfeiffer, Pennsylvania Power and Light Company

Paul Rappaport, Solar Energy Research Institute

Robert B. Rosenberg, Gas Research Institute

Ronald Smelt, Lockheed Aircraft Corporation (Retired)

Jimmie J. Wortman, Research Triangle Institute

STAFF

DeMarquis D. Wyatt, Executive Secretary

CONTENTS

I	Summary	1
II	Hydrogen Sources	4
III	Hydrogen as a Feedstock	16
IV	Hydrogen Transport and Storage	21
V	Hydrogen as a Heating Fuel	30
VI	Automotive Uses of Hydrogen	37
VII	Aircraft Use of Hydrogen	49
VIII	The Fuel Cell in Hydrogen Energy Systems	60
IX	Hydrogen R&D Evaluation	67
X	International Hydrogen Programs	71
XI	Findings and Recommendations	74

CHAPTER I

SUMMARY

A panel of the Committee on Advanced Energy Storage Systems of the Assembly of Engineering has examined the status and problems of hydrogen manufacturing methods, hydrogen transmission and distribution networks, and hydrogen storage systems. This examination, culminating at a time when rapidly changing conditions are having noticeable impact on fuel and energy availability and prices, was undertaken with a view to determining suitable criteria for establishing the pace, timing, and technical content of appropriate federally sponsored hydrogen R&D programs. The increasing urgency to develop new sources and forms of fuel and energy may well impact on the scale and timing of potential future hydrogen uses.

Hydrogen is currently important as a major chemical intermediate, as a reducing gas, and for a variety of special applications. These requirements can be expected to increase by factors of 3-6 over the next twenty years, depending upon the extent to which ore reduction processes and the refining of shale oil and synthetic fuels from coal come into use. These growths, from the present hydrogen consumption level of about one quad (10^{15} Btu) per year, can probably be accommodated by normal market expansions of present manufacturing and distribution capabilities. New capabilities will only be needed if sizeable markets develop for hydrogen as a fuel.

Hydrogen has a future fuel potential, and it may ultimately serve as a replacement for natural gas or petroleum by delivering and storing energy derived from non-fossil (nuclear and solar) sources. As such, hydrogen would be considered as a carrier of energy, analogous to electricity, rather than as a primary energy source. As long as fossil fuel sources are economically available, natural or synthetic hydrocarbons will remain the preferred energy carriers in competition with electricity. If, however, it becomes necessary to shift fuel dependence from fossil to non-fossil sources, hydrogen might become competitive to electricity because of more favorable transmission and distribution characteristics, end uses which lend themselves to gaseous fuels, and probably cheaper storage techniques.

The potentially largest hydrogen fuel market could come in the automotive field if a market for non-gasoline vehicles is established. The threat of gasoline scarcity and price escalations may accelerate public acceptance of such cars. The electric car, seen as a possible second car for the daily conduct of in-town errands or for more sophisticated fleet uses, could be enticing if the technology can be improved. Low-cost highly efficient hydrogen/air fuel cells, which are theoretically achievable, might compete successfully with advanced batteries as automobile power sources.

Future civil transport aircraft may also create a hydrogen fuel market. In particular, if the development of a long-range supersonic transport were to be adopted as a national goal, serious consideration should be given to the use of hydrogen as the SST fuel.

Cost considerations presently inhibit the use of hydrogen as a fuel. If a fuel market for hydrogen is to be developed, it is probable that the hydrogen would have to be derived from either non-carbon sources or as an end product of a coal/synthetic-fuel chain. Costs of either fossil or non-fossil based hydrogen will be higher than the costs of synthetic hydrocarbons that are suitable for fuels. Any reduction in hydrogen costs would also reduce the large fraction of synthetic fuel costs that derive from their hydrogen enrichment. Thus, relative cost ratios of coal-sourced hydrogen and coal liquids should not be expected to change appreciably in the future. As a consequence, it is by no means certain that a widespread market for hydrogen as a fuel will materialize until it is forced by hydrocarbon limitations.

Such limitations may arise from resource depletions, production barriers, or from environmental restrictions on the use of hydrocarbons, including limitations of as yet uncontrolled CO₂ emissions. Thus, in spite of reservations about the timing and rate of impact of hydrogen as a fuel, there is a need for a well conceived R&D program to study some of the basic problems that may constrain hydrogen's entrance into the national fuel economy. Specifically:

- o Basic exploratory research on innovative concepts related to the production, transmission, distribution, storage, or use of hydrogen should be pursued even if near-term market needs cannot be identified.
- o The federal program should be complete enough to provide a data base that will enable sound evaluations and decisions to be made in the future about more costly development and demonstration programs.
- o Such large-scale system development and demonstration decisions should be deferred until a market need is identified and it is established that the private sector will not undertake the necessary effort.
- o Particular attention should be given to research seeking to understand and resolve potential safety problems associated with introducing all phases of the hydrogen production-use chain into the energy complex.

The U.S. program on hydrogen should continue to recognize the possibility of foreign research leadership based on the greater potential needs in other nations for hydrogen fuels. The U.S. program should not completely duplicate foreign efforts, but should be sufficiently advanced

in its own right to enable the nation to participate in meaningful international technology exchange programs. The U.S. research should be in areas clearly applicable to domestic interests.

CHAPTER II

HYDROGEN SOURCES

In nature, hydrogen occurs in chemical combination with other elements. It exists with oxygen as water in its most abundant form, with carbon in fossil fuels and biological materials, and with various elements in inorganic materials. To obtain elemental hydrogen, energy must be supplied to break the chemical bonds that tie it to the other elements. A hydrogen-carbon separation only requires about one-sixth as much energy as a hydrogen-oxygen split.

Two basic methods are utilized to produce hydrogen -- water decomposition, and steam-carbon reactions. Chemically, water decomposition can be represented as:

The overall steam-carbon reaction can be simply depicted as:

where X is the number of chemically combined hydrogen atoms for each carbon atom. It is important to note that with the steam-carbon reaction, hydrogen is produced from water as well as from the hydrocarbon.

These two basic chemical reactions form the backbone of the hydrogen production processes described in this chapter.

Hydrogen Production Via Catalytic Steam Reforming

Steam reforming, as its name implies, utilizes the steam-carbon reaction to produce hydrogen. In this process a light hydrocarbon feedstock, such as methane, is reacted with steam in the presence of a catalyst at about 1500°F and 250 psig. This produces synthesis gas, a mixture of carbon monoxide and hydrogen, and the reaction can be chemically represented as:

The energy required for the reaction is transferred to the hydrocarbon and steam across furnace tubes. Part of the hydrocarbon feedstock is typically used as fuel for the furnace to provide the required heat input. The synthesis gas is then cooled and reacted with additional steam in the shift reaction which is conducted at about 660°F in the presence of another catalyst:

Thus, the overall steam-carbon reaction is:

Half of the hydrogen product is provided by the methane feed stock and the other half is provided by the steam. Hydrogen can be produced from any light hydrocarbon feed stock that can be vaporized, but methane is the most desirable because it has the highest hydrogen/carbon ratio of any of the hydrocarbons.

The crude hydrogen produced by steam reforming contains impurities such as carbon dioxide, carbon monoxide, methane, and water vapor. Therefore, the hydrogen requires additional purification by various absorption and adsorption processes. When all the energy inputs needed to achieve the complete reformation are considered, the net thermal efficiency of steam reforming (defined as the energy content of the hydrogen divided by the overall energy content of the feedstock and any supplemental energy sources) is about 70 percent¹.

The environmental impacts of the steam reforming process are relatively minor as long as natural gas or other light hydrocarbon feedstocks remain available. It is also the cheapest current method for producing hydrogen. The long-term viability of the process is uncertain, however, because of the increasing cost and uncertain supplies of the light hydrocarbons. Explicit projections of fuel availability are not possible because of the lack of firm data on the extent of natural gas reserves, the impact of price deregulations on new gas discoveries, etc.

Hydrogen Production Via Coal Gasification

The production of hydrogen from coal is typically a partial oxidation process which involves several chemical reactions. Finely ground coal is reacted with steam and oxygen at a high temperature. The steam gasification reaction with the coal produces hydrogen. The heat required for the steam gasification reaction is supplied by the oxygen gasification reaction which burns part of the coal with oxygen. The hydrogen yield is increased by the water gas shift reaction which converts carbon monoxide from the steam gasification reaction into hydrogen. Hydrogen production from coal is similar to steam reforming, but is substantially more difficult to conduct because coal, a solid, is difficult to handle, is relatively unreactive, and requires the removal of ash present in coal as slag from the gasification reactor. Coal also may contain considerable sulfur, which

must also be removed. Another difficulty with coal feed is that its hydrogen/carbon ratio (approximately 0.8) is much lower than that of methane.

The chemical reactions in the process are:

The overall reaction for producing hydrogen from coal can be expressed as:

The hydrogen produced by coal gasification contains impurities such as carbon dioxide and hydrogen sulfide. These are removed by various treatment methods to obtain product hydrogen.

When all energy inputs are considered, the net thermal efficiency of coal gasification is about 61 to 66 percent, depending upon the specific process¹. The Koppers-Totzek and Lurgi processes are two of the commercialized coal gasification processes that can be employed to produce hydrogen. Other processes are currently being developed to improve the efficiency and economics of coal gasification.

Presently coal gasification is the cheapest and most secure near-term alternative to steam reforming for hydrogen production. The major environmental effects of coal gasification processes are related to coal mining and its associated operations of coal crushing, grinding, and drying, and to the removal and disposal of pollution effluents in the gasification processes.

Hydrogen Production Via Electrolysis

Currently, electrolysis is the only commercial method available for obtaining hydrogen directly from water decomposition. Electrolysis is accomplished by passing a direct current between two electrodes immersed in an electrolyte; hydrogen gas is formed at the cathode and oxygen gas is formed at the anode. The electrolyte acts as an ion exchange medium that permits hydrogen ions to flow through the solution. Current technology uses an aqueous potassium hydroxide (KOH) solution as the electrolyte. An alternative electrolyte which shows considerable promise, but which still requires substantial development, is the Solid Polymer Electrolyte (SPE) currently being developed by the General Electric Company.

Chemically, water decomposed by electrolysis can be represented as:

The crude hydrogen produced by electrolysis is approximately 99 percent pure and may not require any further purification. The oxygen produced is easily separated for possible use and provides a credit to the economics of the process.

Electricity is generated from coal, nuclear, or oil sources at around 35% efficiency. The conversion efficiency from electricity to electrolytic hydrogen is in the range of 60 to 70% for commercially available electrolysis cells² and may be as high as 90% by the SPE method¹. Thus, overall efficiencies for electrolytic hydrogen production will range from 21 to 25% for commercially available methods, and may reach as high as 32% for the SPE method.

The major environmental effects of electrolytic production of hydrogen are those associated with the production of the input electricity. With nuclear-based powerplants, these are primarily disposal of waste heat and nuclear wastes. Typical problems with coal-based plants include solids handling, sulfur emissions, and air pollution problems.

Important advantages of electrolytically produced hydrogen are the relatively small size of the typical electrolytic cell and the potential of electrolytic hydrogen production with off-peak electric power. Also, electrolysis may be well suited to linkages with intermittent energy sources, such as solar power³ or small hydropower sources⁴.

Hydrogen Production Via Closed-Cycle Thermochemical Decomposition of Water

Electrolytic hydrogen manufacture suffers from inherent thermodynamic limitations based on the efficiency of converting thermal energy to electricity (approximately 35 percent) and an expected maximum electrolytic efficiency of 90 percent. Therefore, researchers are trying to develop thermochemical processes which use heat and various chemicals to produce hydrogen directly from water.

Thermochemical production of hydrogen involves the decomposition of water by thermal energy (heat). Water can be decomposed directly in one step at very high temperatures (about 2000°C), or it can be decomposed by a sequence of chemical reactions whose net effect is the decomposition of water to hydrogen and oxygen. High temperatures are usually required for one or more steps in the multiple process. An example of a thermochemical process is the Euratom Mark IX cycle. The chemical reactions for cycle are:

(Temperature)

The net reaction is:

Currently, only two non-fossil fueled energy sources exist for obtaining the necessary reaction temperatures: the high temperature, gas-cooled nuclear reactor (HTGR)^{5,6} and focused solar radiation⁷. Many different thermochemical processes are possible, but the most efficient employ high temperatures. Estimates of energy expenditures in the chemical separations, pumping, etc., lead to conclusions that the upper limit of net energy efficiency will be about 55%⁸.

A potentially serious problem with closed-cycle thermochemical hydrogen production is the loss of significant amounts of reactants. Some of the proposed reactants, such as mercury, cause undesirable environmental effects. Most of the proposed cycles would require the handling of corrosive substances at high temperatures, with attendant materials problems. Other environmental problems can arise from the release of waste heat, but the development of more efficient processes would reduce this effect.

Thermochemical processes are still in the conceptual research stage and are not proven technologies. As a consequence, production cost estimates for hydrogen from such processes are uncertain. Preliminary conceptual studies of a Schulten-methanol process with an overall thermal efficiency of 37.5% based on a helium cooled nuclear reactor indicate that the nuclear heat source plant might account for about one-third and the hydrogen plant about two-thirds of an overall capital investment that would lead to gaseous hydrogen costs in the range of \$12-18/10⁶ Btu (in 1976 dollars), depending on the method of financing⁹.

Summary Comparison of Hydrogen Manufacturing Processes

A comparison of various aspects of the four major hydrogen production methods are summarized in Table I¹. Technologies are available for catalytic steam reforming of natural gas or other light hydrocarbon feedstocks, for coal gasification, and for electrolysis. Research is underway on thermochemical processes for producing hydrogen directly from water using heat, pressure, and various chemicals.

When natural gas feedstocks become scarce or comparatively expensive, coal gasification may be expected to become the preferred alternative hydrogen production method. Electrolysis has the advantage of not depending on fossil fuel feedstock resources, but its widespread application will be limited by its low net energy efficiency and consequent high capital investment requirements when electrical generation capital is also considered. It has an additional advantage, however, of being practical in small unit size that can be operated at low voltages, hence electrolysis can be suitably integrated into solar-electrical collection systems.

Economics of Hydrogen Production

The cost of hydrogen as a potential fuel should be compared with other non-petroleum energy sources with which it might compete. In order to do this, a consistent set of assumptions must be employed. A recent study¹⁰

TABLE 1 Comparison of Hydrogen Production Alternatives

Process	Steam Reforming	Coal Gasification	Electrolysis	Thermochemical Decomposition
Appropriate Overall Thermal Efficiency	70%	60-65%	32%(SPE) 21-25%(KOH)	Upper limit 55%
State-of-the-art	Well known technology	Mature technology available	Proven reliable technology	Research stages, not a proven technology
Environmental Effects	Depletion of natural gas and other light hydrocarbons	Impacts of coal mining; air pollution likely to be less than via electricity generated from coal	Pollution problems with electricity generation	High efficiency means less resource use; possible release of potentially harmful chemicals
Advantages	Presently the cheapest method (USA)	Cheapest and most secure near-term alternative to methane reforming; abundant coal reserves in U.S.	Small plant size, can use non-fossil sources	Can use non-fossil sources
Disadvantages	Scant long-term potential due to limitations on methane supply	Ultimate limitation is exhaustion of coal resources, requires large plant size	High cost, low net energy efficiency	Materials problems in reactant containment; large complex plant expected
Estimated Hydrogen Production Costs \$/10 ⁶ BTU Product (1980 \$)	6.80	9.50	19.65	

has reduced the published cost estimates for various synthetic fuels to a common base. The assumptions used in the calculations include:

1. 1980 dollars.
2. 100% equity financing for fuel manufacturing.
3. Capital recovery factor of \$0.2/yr per dollar investment. This roughly corresponds to a 10% DCF return.
4. Cost escalation of 7% per year prior to 1980 and 5% per year thereafter.
5. Investments based on a U.S. Gulf location, except for facilities which must be located in other regions.
6. The following plant sizes:

SNG	250 Million Ft ³ /day
Hydrogen	880 " " "
Low Btu Gas	1350 " " "
Liquids	50 Thousand Barrels/day

7. Electricity Cost: \$ 0.03/kWh
8. Mine-mouth Coal Cost: \$ 0.96/10⁶ Btu
9. Natural Gas Cost: \$ 3.15/10⁶ Btu

Based upon these assumptions, the comparative projected costs of alternate synthetic fuels (in \$/10⁶ Btu) at the manufacturing plant would be:

Hydrogen from Methane	\$ 6.80
Hydrogen from Coal	9.50
Hydrogen from Electrolysis	19.65
Gasoline from Coal	7.80 - 10.55
Gasoline from Shale	5.05
Methane from Coal	6.00

The hydrogen costs cited above are for gaseous hydrogen. Additional costs of about \$4.40/10⁶ Btu will be incurred if liquid hydrogen is desired. For comparison, electricity at \$0.03/kWh corresponds to \$8.80 per million Btu.

The costs that are quoted above and used elsewhere in this report may or may not agree with specific costs quoted in other studies. These costs came from a report ¹⁰ that surveyed the literature and normalized the estimates of others to a common economic basis. Where ranges of costs were found, a nominal value was chosen that was based upon the maturity of the technology and upon judgment derived from experience in the petroleum industry. It is believed that the resultant costs are

thereby self-consistent. Furthermore, the interests in the present study are not so much in absolute values as in relative values which indicate the relative economic obstacles facing new technologies for hydrogen production.

These data make it clear why methane is the currently favored source of hydrogen. When natural gas becomes unobtainable or overly expensive, processes based upon the abundant coal reserves will supplant natural gas as the preferred source. Coal-based hydrogen is not economic today because of the disproportionately high equipment investment needed to liberate hydrogen from water in the overall gasification process.

A pure water-splitting process based on electrolysis is even more capital intensive. For such processing to gain significant market entry, the most important need is for a reduction in the energy investment rather than a reduction in the water splitting investment, per se. A costless electrolyzer would not make water splitting competitive. Clearly a more efficient process is necessary to reduce the energy input requirement and its concomitant investment. For instance, a thermal or direct solar splitting process of twice the electrolyzer efficiency but with no greater capital investment would be of substantial interest. If, however, the capital cost was more akin to that of a coal gasification plant, a severe investment barrier would still exist which would favor the more energy efficient and, therefore, economically attractive coal gasification approach. Within the coal gasification system approach, on the other hand, a reduction in necessary plant investment would be more beneficial economically than an efficiency improvement.

Environmental considerations also favor methane as a hydrogen resource base. Since adverse environmental impacts tend to be inversely proportional to the production cycle efficiencies, environmental criteria will tend to rank alternate hydrogen source preferences in the same way as do economic considerations.

Solar-derived Hydrogen

Solar energy is being studied as an adjunct to both electrochemical and thermochemical processes to improve process efficiencies. Solar-derived biomass can also be used in a process similar to coal gasification. Biomass-based hydrogen plants will tend to be smaller than coal-based plants because of biomass supply problems. Overall production economics might, therefore, favor coal-based hydrogen production, but lower sulfur content and reduced pollutant emissions might, in some cases, favor biomass-based hydrogen production.

Biophotolysis, the production of hydrogen from water and sunlight by photosynthetic catalysts, is of longer-term research interest. To date, much of the laboratory research in this form of hydrogen production has centered on single-stage systems using a heterocystous blue-green algae. The key technical problem is oxygen formation in the reactor which tends to inhibit hydrogen evolution. Accordingly, two-stage reactions in which hydrogen and oxygen are produced in separate chambers are presently under investigation.

The practical efficiency limit for conversion of solar energy into hydrogen by biophotolysis is approximately 3 percent. Experiments to date have not approached this limit. However, there are certain inherent advantages to a biological approach to hydrogen production:

- o Biological systems can operate at low temperatures (10-40°C) as opposed to the high temperatures normally required for the chemical and thermochemical processes.
- o The major resource requirements would be solar energy, land, and a hydrogen donor (probably water).
- o The production of hydrogen via biological routes would not involve the formation of CO₂, as is the case in conventional hydrogen synthesis.

Criteria for R&D Program Planning

Since the major reason for the hydrogen cost difference from different processes is plant capital cost, which is a function of plant complexity, it is important that R&D aim at capital reductions. There are several ways to bring down capital costs. In coal gasification, for example, one approach would be the development of a catalytic process that could operate at lower energy expenditures, at lower temperatures and higher pressures, and without significant poisoning of catalysts and/or difficult clean-up problems. In principle this should be possible. Other approaches might develop from a critical examination of the coal gasification route to determine steps that are amenable to R&D attack.

Since a significant technology base now exists for the production of synthesis gas from coal, future R&D should be aimed at developing significant improvements and/or breakthroughs. However, breakthroughs are often dependent upon invention and are difficult to anticipate. Program managers should be watchful for innovative ideas.

In order to identify potential evolutionary improvements, it is important that program planners and managers understand the economics of the entire fuel cycle associated with hydrogen production, the sensitivity of those economics to changing environmental and safety standards, and the way in which certain technical approaches can minimize concerns.

Specifically, the following observations can be made about the principal hydrogen production processes:

- o Standard Electrolysis Conventional electrolyzers with conversion efficiencies of the order of 70% are commercially available on the world market. Advanced electrolyzers show promise of approaching 100% efficiency. Overall efficiency is only 20-35%, so extensive federal R&D to capture the last few percentage points of improvement for either class of electrolyzer is not warranted. Basic research on fundamental problems and exploratory work on innovative concepts

holding promise of reducing hydrogen costs should be continued, however. System development and demonstration activities should be deferred until a significant market need is identified and it is determined that timing or risk factors make private sector efforts unlikely.

- o High Temperature Electrolysis The use of high pressures and temperatures in conjunction with electric power to produce hydrogen by electrolysis appears to offer the possibility for lower power requirements, which could substantially lower the cost of hydrogen production. Basic research in this area would be worth pursuing with federal funds.
- o Coal Gasification A major gasification effort exists in the DOE Fossil Energy program. Before any modifications or additions are made to that program in order to accelerate hydrogen production technologies, careful systems analyses will be required. The panel is not aware of any such studies having been performed. Following these systems studies, it may be desirable to institute some experiments to maximize hydrogen production and/or to initiate some pilot-plant scale research aimed specifically at developing new hydrogen production technologies. Capital cost reductions for gasification equipment should be a prime objective.
- o Thermochemical Processes Here, there are a broad array of possibilities--at present there is no clearly superior process and further research is needed. Thermochemical techniques have the potential of being more efficient than electrolysis but they will probably yield more expensive hydrogen than that produced from fossil fuels. The commercialization potential is so distant that there is a justifiable federal R&D role in this process area.
- o Solar Water-splitting Some promising research is underway in this field, but attractive costs have not yet been established. Federal support of both basic and applied research in this field would be desirable.

REFERENCES

1. Corneil, H.G., F.J. Heinzelmann, and E.W.S. NicholSEN. *Production Economics for Hydrogen, Ammonia, and Methanol During the 1980-2000 Period*. Linden, N.J.: Exxon Research and Engineering Co., Government Research Laboratories, April 1977.
2. *Hydrogen and Other Synthetic Fuels, A Summary of the Work of the Synthetic Fuels Panel*. Prepared for the Federal Council on Science and Technology R&D Goals Study, September 1972.
3. Dickson, E.M., J.W. Ryan, and M.H. Smulyan. *The Hydrogen Energy Economy: A Realistic Appraisal of Prospects and Impacts*. New York: Praeger, 1977.
4. Johnson, D.C., and W.J.D. Escher. *Hydrogen from Small Existing Falling Water Sites: An Initial Feasibility Assessment*. Final Report by the Institute of Gas Technology, Chicago, Ill., under Brookhaven National Laboratory Contract No. BNL 423391-S, June 1978.
5. Barnert, H. and R. Schulten. "Nuclear Water-Splitting and High Temperature Reactors." Pp 115-128 in *Hydrogen Energy*, ed. T.N. Veziroglu. New York: Plenum, 1975.
6. Quade, R.N. and A.T. McMain. "Hydrogen Production with a High Temperature Gas-Cooled Reactor (HTGR)." Pp 137-154 in *Hydrogen Energy*, ed. T.N. Veziroglu. New York: Plenum, 1975.
7. Hildebrandt, A.F. and L.L. Vant-Hull. "A Tower-Top Point Focus Solar Energy Collector." Pp 35-44 in *Hydrogen Energy*, ed. T.N. Veziroglu. New York: Plenum, 1975.
8. DeBeni, G. "Thermochemical Water Splitting with Nuclear Heat." Pp 113-121 in *Proceedings of the Cornell International Symposium and Workshop on the Hydrogen Economy*, ed. S. Linke. Ithica, N.Y.: Cornell University, April 1975.

9. *A Technoeconomic Analysis of Large Scale Thermochemical Production of Hydrogen.* Prepared by the University of Kentucky, Lexington, Ky., and Combustion Engineering - Lummus, Bloomfield, N.J. for EPRI, Palo Alto, Calif. EPRI Final Report EM-287, December 1976.
10. Cart, E.N., Jr., A.R. Cunningham, and D. Carter. *Alternative Energy Sources for Non-Highway Transportation.* Linden, N.J.: Exxon Research and Engineering Co., Government Research Laboratories. Draft prepared under DOE Contract EC-77-C-05-5408, June 1978.

CHAPTER III

HYDROGEN AS A FEEDSTOCK

Hydrogen is a major industrial feedstock that is used for the production of many organic and inorganic chemicals such as ammonia and methanol. Great quantities of hydrogen are also used in petroleum refining, both in hydrocracking and in hydrotreating operations. Small quantities of hydrogen are currently used in the reduction of iron ore and in the "hardening" of oils and fats by hydrogenation. Several estimates of the quantities of hydrogen used for these purposes is shown in Table II for the years 1973 and 1974.

For ammonia and methanol production, oil refinery operations, and ore reduction, the hydrogen is manufactured at or close by the consuming plant so that this so-called "captive" hydrogen does not appear as a marketed commodity. Also, hydrogen for these applications may contain significant amounts of nitrogen or carbon monoxide. For these reasons, it is difficult to obtain reliable data on the quantities of hydrogen actually being used, thus accounting for the large variations of use estimates in Table II.

A major new demand for hydrogen, again likely to be "captive" and relatively impure, will occur as a synthetic fuels industry develops. The addition of hydrogen is required to convert coal, (roughly $\text{CH}_{0.8}$), to liquid hydrocarbons (CH_2) or synthetic natural gas (CH_4). Significant quantities of hydrogen will also be required for the refining and upgrading of oils from shale sources, although the hydrogen content of shale oil is naturally near that of petroleum. As a consequence, much less hydrogen is needed for shale oil than for coal synthetic liquids.

Estimates of future hydrogen demand levels for non-fuel uses are no more uniform than the estimates of current consumption. Table III presents a range of estimates for the years 1985 and 2000. The large variations in the estimates for the expansion of currently existing feedstock markets reflect varying assumptions about the future economic and energy growth of the country. Overall, however, these demands can be expected to double or triple by the year 2000. There are also major differences in estimates of the hydrogen requirements for emerging technologies, such as ore reduction and synthetic fuels production. There are understandable uncertainties about the future rates of growth for these industries. In particular, the growth rate of the synthetic fuels industry is very conjectural because of the uncertainties of the future availability of

TABLE II Hydrogen Use Estimates, 10^{15} Btu

Year Organization Reference	1973 JPL 1	1973 BNL 2	1974 IGT 3
Ammonia	.359	.34	.371
Methanol and other Chemicals	.098	.12	.068
Oil Refinery Operations	.466	.34	.253
Ore Reduction	Negl.	.006	.006
Fats and Oils Hydrogenation	.005	.005	.002
Other	.065	.03	.027
Total	.993	.841	.727

TABLE III Projections of U.S. Hydrogen Demand, 10^{15} Btu

Year Organization Reference	1985				2000		
	IGT 3	JPL 2	EXXON 2	Bu.Mines 2	JPL 2	EXXON 2	Bu.Mines 2
Ammonia	.46	.73	.54	} .65	1.73	.90	} 1.03
Methanol and Other Chemicals	.10	.22	.29		.61	.60	
Oil Refinery Operations	.25	.66	.28	.47	.78	.56	.65
Ore Reduction	.02	.06	NE*	.01	.22	NE	.03
Fats and Oils Hydrogenation	.007	.01	.01	NE	.03	.03	NE
Synthetic Fuels	.66	.03	NE	.22	1.71	NE	2.87
Other	.04	.15	NE	.05	.40	NE	.12
Total	1.54	1.86	1.12	1.40	5.48	2.09	4.70

*Not Estimated

natural gas and petroleum coupled with the enormous capital resource requirements for synthetic fuels plant construction.

It is anticipated that the hydrogen required for syn-fuels processing will normally be made from the raw fuel itself (i.e., coal or shale), but some consideration has been given to the external production of hydrogen from a non-fossil source. Other than by using natural gas or oil, on-site production from coal is the cheapest hydrogen production process available. However, the price of coal is steadily rising. The non-fossil hydrogen sources that can be driven by renewable or extremely large energy sources (solar or fusion) are not likely to rise as much in cost in the long term. Thus, at some point in the future it may be economically advantageous to utilize some outside source of hydrogen. That point will be strongly influenced by the quantities of remaining non-renewable resources and their recovery costs. For example, hydrogen produced from a nuclear-electrolyzer plant might be used to assist coal gasification or liquefaction in lieu of additional coal consumption when coal resources begin to deplete.

There will be a basic problem if an external hydrogen supply is retrofitted to an already developed coal conversion process. In the case of coal hydrogasification, for example, the existing process is designed so as to leave just enough char from the primary gasifier so that it will, in turn, produce exactly the right amount of hydrogen for the process. Thus, operating a hydrogasification process on external hydrogen requires a completely new set of design configurations for the primary gasifier, because no char production is required. Similarly, considerable rebuilding of an existing ammonia plant would have to be undertaken if its feed were hydrogen instead of natural gas, because an additional means of separating nitrogen from the air input (currently carried out by the natural gas reformer) would have to be provided.

REFERENCES

1. Kelley, James H. *Hydrogen Tomorrow - Demand and Technology Requirements*. Pasadena, Calif.: Jet Propulsion Laboratory, December 1975.
2. Beller, M.N., N. Bhagat, H. Davitian, A. Doernberg, K. Hoffman and W. Sevian. *Hydrogen Energy Assessment*, ed. F.J. Salzano. Upton, N.Y.: Brookhaven National Laboratory, March 1977.
3. Biederman, N.P., K. Darrow, and A. Konopka. *Utilization of Off Peak Power to Produce Industrial Hydrogen*. Palo Alto, Calif.: Electric Power Research Institute Report EPRI 320-1, August 1975.

CHAPTER IV

HYDROGEN TRANSPORT AND STORAGE

Hydrogen is characterized by a high energy density on a weight basis (more than twice that of methane or gasoline), but only a moderate energy density on a volumetric basis; in gaseous form about one-third that of methane, and in liquid form about one-half that of gasoline or jet fuel. These characteristics pose specific requirements for hydrogen transport and storage systems. The transport of hydrogen and associated costs are strongly influenced by the location of production sites and the scale of production compatibility with the infrastructure for its transmission, distribution and use. For instance, if it is to be produced for mixing with natural gas in relatively small percentages, the present infrastructure for the delivery and use of gas is satisfactory. However, if hydrogen is considered as a complete replacement for natural gas, the effects on all areas of the energy system may be substantial.

It should be noted that prior to 1950, substantial quantities of hydrogen mixed with CO were produced from coal and distributed in cities as town gas. Some cities in Europe have distributed a 50% by volume mixture of H₂ with CO in city distribution systems. These systems generally operate at low pressure. Furthermore, hydrogen is currently an industrial commodity, derived primarily from natural gas, and the technology for handling it is familiar to industry.

Transmission

Hydrogen is presently shipped as a cryogenic fluid in insulated tank cars or trucks, or as a gas in tube trailers (manifolded banks of large compressed gas cylinders). Transport as a liquid requires liquifaction of the hydrogen gas which is power intensive and expensive (6kWh per lb, and about \$4.4 per 10⁶ Btu). Trailer transport as a gas is expensive and is not suitable for handling large quantities of hydrogen.

At present hydrogen gas is not generally transmitted through long distance pipelines, however the wealth of experience with natural gas pipeline transmission permits extrapolation to hydrogen applications. Two possibilities exist: (1), the transmission of hydrogen through the existing natural gas pipeline system, or (2) the construction of new dedicated hydrogen pipeline systems.

The existing natural gas system is complex; it contains a total of about a million miles of pipe, of which two-thirds are used for distribution, one-quarter for transmission and storage, and the remainder for gas field and gathering use. Transmission line sizes range from 4 1/2 inches to 42 inches in diameter, with the weighted average in the order of 20 inches.

The integrity of this pipeline system for handling hydrogen must be established. In the event of leakage, methane line leak rates will theoretically be magnified by factors of 2-3 in volumetric terms for hydrogen transmission (based upon the square root of the molecular weight ratio of the two gases). There would be little leak differences on an energy basis, however, since hydrogen has a volumetric energy density only one-third that of natural gas. In addition to existing leaks, hydrogen embrittlement and cracking of natural gas pipelines carrying hydrogen has been experimentally observed at 2000 psi pressures¹. Further investigations are needed to determine if there would also be problems at lower pressures.

The use of natural gas pipelines for hydrogen transmission would be expected to result in somewhat higher transmission costs. Reference 2 has calculated optimized transmission costs in the range of 2-4¢/10⁶Btu/100 miles for natural gas and 4-6¢/10⁶Btu/100 miles for hydrogen for the same pipeline diameters and pumping pressures. By comparison, electrical transmission costs range from 37¢ to \$1.05/10⁶Btu/100 miles for overhead transmission systems (depending on the transmission voltages and power ratings) and it is estimated that future underground superconducting transmission systems that would minimize aesthetic and environmental problems will yield electrical transmission costs in the range of \$1-\$2/10⁶Btu/100 miles².

The cost estimation of a new hydrogen pipeline system is difficult. The advantage of a new system is that it can be optimally designed to handle hydrogen, but cost escalations in recent years have been drastic. Large variations are encountered in the installation of a given size of line, depending upon the complexities of the routing, and variation in regional labor costs. Installed pipeline costs can vary by factors of one to four in a given year as a result of the parameters involved. The cost of pipe and labor are the largest components of the installed cost. In 1975, 24-inch gas lines cost about \$135,000 per mile of installed pipe; 30-inch line costs ranged from \$180,000 to \$415,000 per mile³. To carry equivalent hydrogen energy, tradeoffs of pressure versus pipe diameter would need to be considered. There are economies of scale involved in building larger pipelines, and the cost factors of three over natural gas pipelines may be reduced to as low as two in an optimized case for transmitting hydrogen.

The basic problem to contemplate for the future is the cost of installing an energy transmission and delivery system to link new nuclear and solar energy sources to customers. If much of the existing natural gas system can be used, benefit can be taken of the imbedded value of this existing equipment. In the unlikely event that a new, dedicated transmission and distribution system for hydrogen has to be considered, the relative costs of this and of substantially renewed or reinforced electricity delivery and storage system must be compared in economic

terms. While these comparisons have not been rigidly made, there are clear indications that the hydrogen system will be less capital intensive.

Storage Capabilities

Natural gas transmission systems operate most efficiently and at lower cost when run continuously at maximum capacity. Therefore, at periods of low demand gas is pumped to storage reservoirs, preferably located in the consuming regions, to later be withdrawn to serve peak loads which may exceed the capacity of the main transmission system. In general, depleted gas wells are used for storage. In 1975, 296 (79%) of the 376 underground storage pools were depleted gas wells⁴. Alternative storage methods are use of depleted oil wells, salt mine caverns, aquifers, and above-ground storage in tanks, which may be cryogenic.

The total underground reservoir capacity in the U.S. is estimated at 2.3×10^{15} Btu of working gas. Working gas is not the total amount in the reservoir; it is the amount normally withdrawn and transmitted, in addition to the "cushion gas" which is kept in the reservoir to provide the driving force to deliver stored working gas. The ultimate capacity of methane in the U.S. is estimated at 6.6×10^{15} Btu, where ultimate refers to the amount capable of being stored at the highest pressure that the well can withstand. However, this ultimate capacity is not necessarily achievable because of equipment limitations in attaining such pressures, for economic reasons of installing additional equipment, or for location-demand limitations on desirable storage.

Underground caverns can undoubtedly also be employed for hydrogen storage. Using the volumetric ratio of heating value of three to one for natural gas to hydrogen, the working gas capacity of the storage facilities would be in the order of 0.8×10^{15} Btu and the ultimate capacity about 2.2×10^{15} Btu.

Despite the use of existing underground caverns, storage is not cheap. There are large investments in installing pipe systems to and from the reservoirs, and in compression equipment. The total cost of service for underground natural gas storage (excluding the cost of the gas) is estimated at about 75¢/ 10^6 Btu (\$1975). A facility in Kansas presently being completed, which will store 36×10^9 cubic feet of natural gas, has an estimated associated capital cost of 27 million dollars. These costs include a main pipeline to the reservoir, station piping, two compressors, gas field lines, and associated station and electrical costs. This facility can cycle 12×10^9 cubic feet per year, with a daily peak rate capability of 130×10^6 cubic feet. In terms of hydrogen this would translate to 1.2×10^{13} Btu of storage, with a daily peak throughput of 4×10^{12} Btu. Storage costs would be in the order of \$2.00/ 10^6 Btu, an appreciable increment to production and transmission cost. Within the constraints of this rather limited perspective, the apparent high cost warrants an in-depth comparison with other underground storage alternatives as well as with cryogenic storage for hydrogen.

About 25% of the annual gas delivered to demand is stored. The storage cost is rolled into the delivered cost of gas. Thus, the \$2.00/10⁶ Btu hydrogen storage cost would translate into about 50¢/10⁶ Btu of total delivered gas.

A key problem in the utilization of hydrogen in some applications is the need for compact, lightweight, and safe storage. This is especially true in proposed automotive applications. Currently available high pressure gas storage techniques are inadequate and the approach of using the cryogenic liquid has safety problems as well as being energy intensive. During recent years, the use of metal hydrides for hydrogen storage has been under development. Metal hydrides offer the potential of low cost and safe hydrogen storage through their ability to react with hydrogen to form decomposable hydrides. Metal hydride storage systems are more complex than those required for compressed gas storage, but the storage pressure is only about one-tenth as high (250 vs. 2250 psi). A heat exchanger is required for cooling the particle bed during hydriding and for heating the bed to release hydrogen. The heat that must be supplied is generally available at the point of hydrogen consumption.

A metal hydride formed from a 50-50 atom ratio of titanium and iron, the cheapest and most convenient to use, offers a working storage capacity of approximately 1.5% hydrogen by weight. A desirable feature of FeTiH_x is that hydriding-dehydriding reactions occur at ordinary temperatures. Tap water can be used for cooling and heating of the hydride via a heat exchanger. The reaction rates are very rapid but are limited by the rate of heat transfer. During the course of these reactions the pressure usually ranges between 500 and 15 psi. FeTi materials do not lose hydrogen storage capacity even after thousands of cycles when ultra-high-purity (99.999%) hydrogen is used. Hydrogen of this purity, at the 500 psi required for hydriding can be available from certain advanced state-of-the-art water electrolyzers. In circumstances where hydrogen causes poisoning of the hydride, it can be reactivated by heating and evacuation. Oxygen, CO, H₂O, are common poisons. Poisoning has one beneficial effect in that accidental contact with air stops hydrogen release so that in the event of tank rupture the damage is likely to be minimal.

The pressure-composition properties of FeTiH_x can be favorably altered by substituting another transition metal for part of the iron (Fe). Systems containing substituted manganese (Mn) appear to be the most practical, and extensive studies have identified TiFe_{0.9}Mn_{0.1}H_x. The main advantage gained through the use of Mn is simplified activation of the alloy. Whereas FeTi alloys require heating to about 300°C (572°F), followed by evacuation and cycling contact with hydrogen for up to two weeks, TiFe_{0.9}Mn_{0.1} alloy can be activated in a day or two at room temperature. The resulting hydride is more stable than FeTiH_x; thus, a slightly lower pressure can be used to attain a full charge, or for the same pressure a slightly higher hydrogen content can be attained.

Magnesium hydrides can store several times as much hydrogen per unit weight, but are of limited application because of the substantial energy required to maintain reaction temperatures at about 300°C (572°F) for hydriding and dehydriding. The formation of magnesium hydride (MgH₂) is

catalyzed by the addition of copper (Cu) or nickel (Ni). The system containing 10% Ni by weight as a magnesium-nickel compound mixed with magnesium appears to be the most effective with respect to hydrogen weight fraction and kinetics. In working systems it should be possible to achieve a hydrogen content of about 5% by weight. The alloy cost is about one-half that of TiFe-based alloys, but the thermal load is nearly three times as high.

The high hydrogen concentration of Mg-based hydrides allows their use in automobiles--where weight is an important factor. The elevated temperature requirements suggest the use of dual-hydride systems which employ a Ti-Fe-based hydride for cold starting, and Mg-based hydride heated by exhaust gases for cruising. Working systems of this type have been demonstrated by Daimler-Benz AG of West Germany in a passenger car and a bus. The dual-hydride system uses the best features of each hydride and provides the performance which neither hydride can do alone. These dual systems can double the hydrogen content over FeTi alone (from 1.5 to 3.0%).

A third class of hydrides, the AB_5 type (rare earths) also function at ordinary temperatures and are easily activated. $LaNi_5H_6$, the first of this class of metal hydrides, was found to be expensive due to the presence of lanthanum. Investigations seeking lower cost substitutes have resulted in the development of two useful alloys which are considerably less expensive. One is based on the substitution of cerium-free Mischmetal (M), an unrefined rare-earth alloy, as the source for La. The second alloy is based on the substitution of calcium (Ca) and Mischmetal for La, a typical composition being $Ca_{0.7}M_{0.3}Ni_5$. By changing the relative amounts of Ca and M the pressure characteristics of the system can be usefully varied over an appreciable range. These compositional changes have reduced the raw materials costs to about 30% of that for $LaNi_5$ alloy, but they are still substantially higher than those for the FeTi-based alloys. Consequently, the modified AB_5 alloys will probably be limited to applications which require their particular behavioral properties and where the higher costs can be justified. In terms of weight percent hydrogen and thermal load, AB_5 -type hydrides are comparable to FeTi-based hydrides.

Metal hydrides can also be applied in non-mechanical (chemical) compression of hydrogen. In this application, hydrogen is absorbed into the bed at low temperature with the attendant rejection of the heat of reaction. The hydrogen is then driven off the bed at high temperature and thus high pressures are achieved. This can be the basis of compressor or power cycle applications as well as heat pumping.

A comparatively new and novel method of storing hydrogen at very high pressure in hollow glass microspheres (microballoons) has been proposed. The technique is based on the high permeation rate of hydrogen through certain glasses at temperatures of $\sim 200^\circ\text{C}$ (392°F). Charging would be done at pressures near 400 atmospheres (6000 psi), and after cooling to ambient temperature the leakage rate would be low. Considerable energy is required for hydrogen pressurization. Like Mg-based hydrides, this storage technique would function best for a transportation application when coupled with a FeTi-based hydride, or for short-term storage needs

of up to one week. A working system of glass microballoons has yet to be demonstrated. This material has the potential to be charged with hydrogen from impure gas stream as the diffusion rate in the microballoons is selective for hydrogen.

Technology Advance for Metal Hydride Hydrogen Storage Systems

In order for hydrogen storage systems to realize their full application potential, state-of-the-art advance is required to achieve higher storage capacity per unit weight, to permit operation over effective pressure and temperature ranges, to improve heat and mass flow characteristics consistent with attaining controllable absorption/desorption of hydrogen, to maximize recyclability of storage systems via contamination resistance thus reducing life cycle costs, and to reduce initial cost of materials through identification of low cost alloys and their associated production processes.

Low weight-high capacity systems development aims for a hydrogen storage capacity of 3% minimum. Automotive applications will require such systems if range and acceleration characteristics, as experienced in accepted practice, are to be retained. Current technology requires use of dual hydrides (FeTiH_x and MgH_x) or hybrid storage systems. Weight is of lesser concern in stationary applications or in limited market, special purpose vehicles such as fork lifts and mine vehicles, where the added weight is beneficial as ballast and low pollution is of prime consideration.

The ability to rapidly absorb and release hydrogen at relatively low temperatures will not only provide the designer with added flexibility in seeking out applications, but, more importantly, systems operating in the lower temperature regimes will reflect energy and cost savings. Metallurgical and molecular phenomenology should be addressed such that hydriding-dehydriding reactions are controllable. Technology advances relate to the selection of materials with appropriate electron-to-atom ratio and the introduction of additives to control interstitial "holes" as well as the use of catalysts that permit controlled interaction between hydrogen and the intermetallics.

Heat and mass flow enhancement through innovative designs will permit rapid and controllable absorption and delivery of hydrogen, necessary for automotive fueling as well as compressor and power cycle applications. Materials packaging, configuration control and advanced heat exchange designs are identifiable approaches.

Recyclability of metal hydrides has been demonstrated where care is exercised in utilizing high purity hydrogen. The development of contamination resistant materials and/or means for cost-effectively separating and purifying hydrogen will do much toward reducing life cycle costs of storage systems.

Cost effectiveness can be achieved through maximizing the capacity for hydrogen retention and extending the use life of storage materials. Low cost alloys and alloy production techniques must be sought such as:

investigations into the lowest cost production of FeTi from ilmenite ore, the use of rare-earth oxides (Mischmetals), as well as hybrid systems utilizing other occluders such as microspheres.

This general concept of using metal hydrides or other chemical compounds to store hydrogen is sound, but exploratory work must be continued to discover low cost, lightweight materials with high hydrogen storage capacity. Current programs emphasize known classes of materials and are working to make only incremental improvements. A broader look at other chemical and physical systems, low in cost, which can hold large quantities of hydrogen at low pressures and temperatures is warranted.

Distribution Problems

The discussion of hydrogen transmission can be related to distribution as well, but distribution presents a larger problem. The use of existing natural gas distribution systems is possible, but many of these systems are quite leaky. As an example, one gas utility has a 7% natural gas loss in its system (sendout minus metered deliveries). Assuming most of this loss is due to leaks and metering errors, the migration tendency of hydrogen could raise the loss rate by a factor of two to four by volume (about the same energy loss rate). Although small-scale experiments at IGT and PSE&G duplicating distribution systems and materials currently in use for natural gas have shown no problem when employing hydrogen for periods up to 6 months, it must be assumed that a carefully controlled experimental mockup does not duplicate systems which have been field-installed and subject to corrosion and vibration problems encountered by the network for time periods of fifty years or more. True evaluation of the integrity of such systems for hydrogen use must involve additional controlled experiments in sections of existing distribution systems of known age and materials.

R&D Recommendations

Transmission

This does not appear to be a high technology area, and the amount of required R&D is relatively small. Emphasis must be placed on the testing and identification of low cost materials, such as low alloy steels. Hydrogen is presently widely used in industry, and there exists a large body of experience with it in piping systems. Research to understand the mechanism of hydrogen embrittlement would be of value in identification of desirable low alloy steels, and would give confidence in their long term behavior.

Storage

There is a need to confirm that hydrogen can be stored in large bulk quantities, for example, underground as is currently the practice with natural gas. If current natural gas underground storage practices can be applied to hydrogen, as is generally believed to be the case, seasonal production from hydroelectric, solar, or other renewable resources would allow more effective utilization of such resources.

Basic work should be undertaken to discover new small scale chemical systems suitable for hydrogen storage. Desirable features to be sought are low cost, high hydrogen capacity per unit of volume and weight, non-toxic materials, and lack of potential fire hazards.

Distribution

This is a low technology area where R&D emphasis should focus on materials compatibility, permeability, and energy metering techniques. These are areas where industry has the ability to deal with problems when the need arises.

Systems Studies

There is a need to understand how the existing energy infrastructure would be modified if hydrogen were available in large quantities. In general, it would be expected that hydrogen would be used as a natural gas supplement or substitute. The modification of existing systems for hydrogen use would have to include attention to chemical, physical, or other safety problems that might arise. Future systems studies should emphasize the differences as well as the similarities between hydrogen and natural gas systems in expected applications in order to obtain a better measure of hydrogen's compatibility with the existing infrastructure and the extent and degree of changes required.

REFERENCES

1. Swisher, J.H., S.C. Keeton, A.J. West, and A.T. Jones. *Survey of Hydrogen Compatibility Problems in Energy Storage and Energy Transmission Applications*. Sandia Laboratories Report No. SAND 74-8219 (1974).
2. Konopka A., and J. Wurm. "Transmission of Gaseous Hydrogen." Paper presented at the *9th Intersociety Energy Conversion Engineering Conference* in San Francisco, Calif., August 26-30, 1974. Chicago, Ill.: Institute of Gas Technology.
3. Ewing, R.C. "Pipeline Economics." Pp 61 to 70 in *Oil and Gas Journal* 73. Tulsa, Oka.: Petroleum Publishing Co., August 18, 1975.
4. Goff, T.M., and W.C. Chambers. "Seasonal Energy Storage Requirements." Paper presented to the *Systems Study and Economic Sessions of the ERDA Contractors' Review Meeting on Chemical Energy Storage and Hydrogen Energy Systems* in Airlie, Va., November 8-9, 1976. DOE Report CON-761134.

CHAPTER V

HYDROGEN AS A HEATING FUEL

Hydrogen has been discussed as an eventual successor to natural gas and/or SNG as a heating fuel in the residential, commercial, and industrial sectors. Such a succession will probably only occur, however, under the following conditions:

1. Hydrogen becomes available at a lower price than gaseous hydrocarbon fuels, or
2. The use of hydrocarbon fuels is restricted for environmental reasons, and
3. Hydrogen is available at the point of use at a lower price or more conveniently than electricity.

The substitution of hydrogen for natural gas or SNG would only occur, for example, if the price of gas (and the coal from which SNG is made) escalates far more rapidly than the price of nuclear or solar energies that could be the source of non-fossil hydrogen, or if constraints are placed on the rate at which coal is mined or its derivatives are burned. Even so, the conversion of electrical energy to hydrogen would depend upon the demonstration of real hydrogen storage and transmission advantages in comparison with electricity or the economic advantages of continuing the use of emplaced gas-fired heating and cooking equipment.

The concept of hydrogen replacement of natural gas was seriously considered in a period (1971-72)¹ when future gas supplies were thought to be severely limited and when vast supplies of very cheap nuclear generated electricity were visualized. Prospects for future gas supplies now look considerably brighter due to optimism about the "unconventional" gas sources (geopressured aquifers, tight sands, Devonian shales, coal seams, and methane hydrates) and to the incentives for new gas exploration due to price deregulation. Recent projections by the American Gas Association² forecast slightly increasing U.S. domestic gas production (including Alaskan gas) through the year 1990. On the other hand, the U.S. Department of Commerce projects a decrease of about 9% in natural gas consumption between 1976 and 2000³ and the Gas Requirements Committee estimates a 14% decrease by 1985⁴.

User System Conversions

When circumstances finally make hydrogen competitive as a heating fuel, there will be problems associated with the conversion of user burner systems to operate safely and efficiently with it. Initially, it would be expected that hydrogen would enter the gas system on an incremental basis, gradually building up to quantities that would be a significant percentage of overall energy supplies. At first sight it might be considered practical to slowly build up the hydrogen content in the natural gas system, so that a gradual conversion from natural gas to hydrogen takes place over a number of years. This concept is not practical, however, because hydrogen-methane mixtures are not fully "interchangeable" with natural gas. The required continual series of adjustments or modifications to user's burners would be prohibitively expensive, and metering of a gas with a continuously varying heating value presents very great difficulties.

Whenever the send-out natural gas or pipeline gas that is distributed to gas appliances is altered by blending or supplementation, the chemical, physical, and combustion characteristics of the new gas may vary considerably from those of the original pipeline gas. If one fuel gas can be substituted for another on an atmospheric burner to maintain approximately the same thermal output and trouble-free operation, without alteration to the burner or to the gas pressure, the gases are said to be interchangeable. A burner adjusted at the manufacturer's rated heat input on pipeline natural gas (adjustment gas) will have flames that are free of 1) yellow-tipping, 2) flashback into the burner ports (on ignition, shutdown, or from a stable condition), and 3) lift-off (blow-off) from the burner ports. If another gas is used without readjusting the burner, the flame quality (combustion characteristics) can be considered as an indication of whether or not the gas is interchangeable with the natural gas.

The most definitive method for determining interchangeability is to combust the mixtures on the appliance burners that will utilize the gases. However, mathematical methods have been derived empirically, based on laboratory studies, that give predicted solutions to gas blending combustion problems. While laboratory combustion tests are used to determine interchangeability, the empirical mathematical methods are used to predict interchangeability and to help reduce the amount of laboratory testing. The methods commonly used to predict gas interchangeability are (a) the American Gas Association Laboratory Interchangeability Indexes, (b) the Elmer R. Weaver Interchangeability Indexes, and (c) the P. Delbourg Indexes (French). Calculations to determine the values of the indexes of the three mathematical methods are usually made by computer.

It should be noted that these empirical mathematical methods are approximately 40 years old. They were derived from data taken on burners that are in all probability no longer in service. Also, many of the new substitute gas mixtures are not typical of any of the test gases originally used to derive these methods. These mathematical methods are used only as estimates to help reduce the number of laboratory combustion tests.

Interchangeability of Hydrogen with Natural Gas

The Public Service Electric & Gas Company (of New Jersey) studied various aspects of the delivery of hydrogen/natural gas blends via existing utility systems⁵. One objective of the investigation was to determine the maximum amount of hydrogen that could be blended in natural gas, maintaining the reliability and efficiency of typical burners with minimal or no adjustment or conversion.

A preliminary calculation, using Weaver Indexes of Interchangeability, indicated that mixtures containing up to approximately 20% hydrogen should be interchangeable with natural gas. It appeared that these mixtures would be critical with respect to flashback. Laboratory tests undertaken to substantiate the analytical findings included the following results:

- o Gas blends containing more than 6-11% hydrogen (by volume) are the limiting mixtures for target type pilot burners. The limiting conditions result from the tendency of target type pilot burner flames to burn back at the orifice and not above it, as designed, so that the thermocouple, whose purpose is to sense the flame and keep the gas turned on, does not get hot enough and extinguishes the burner. Modification of the orifice in the pilots or increasing the supply pressure to a minimum of seven inches water column will permit the use of gas blends with 20% hydrogen.

- o Gas blends containing more than 20-22% hydrogen are the limiting mixtures for main burners operating in the open. Limiting mixtures are 22-25% for main burners tested in appliances. Performance was limited by flashback under turn down conditions with a tendency to noise when the flame was turned off. Minor changes in burner adjustment, such as adjustment of primary air, has little effect on the amount of hydrogen which can be satisfactorily utilized.

Although no tests were performed on industrial equipment, it was concluded that the limiting percentages of hydrogen found for residential equipment should operate satisfactorily on industrial equipment because it is readily adjustable to meet variations in gas composition. Some industries, such as glass, would probably welcome the addition of hydrogen to natural gas since a more clearly defined sharp flame results.

The comparison of the experimental with the analytical results indicates that the Weaver Indexes of Interchangeability do not accurately predict the interchangeability of hydrogen and natural gas mixtures. Additional work needs to be undertaken to modify these indexes to arrive at a method which is universally applicable.

The study also concluded that a statistical analysis of the number of types of burners in use needs to be undertaken so that accurate predictions can be made as to the costs of conversion, and the extent of the problems which may occur with various substitute gases.

Interchangeability of Natural Gas with Hydrogen

If hydrogen sources are steadily developed with a view to ultimately replacing natural gas with hydrogen, and this hydrogen is progressively blended with natural gas, there will come a time when, in a given geographic area, the hydrogen gas mixture becomes non-interchangeable with natural gas. At this point, it will be necessary to visit each user and adjust, modify, or replace every appliance and burner. This procedure was followed in the U.S., Japan, and Europe when natural gas replaced manufactured gas. This very expensive and time-consuming exercise can only be contemplated once, so that a once-and-for-all conversion to pure hydrogen must be carried out. It would be advantageous to know, at that time, the interchangeability characteristics of hydrogen-natural gas mixtures with pure hydrogen, so that burners may be adjusted to maximize the opportunity to "supplement" hydrogen with natural gas until such time as natural gas can be completely phased out.

The only interchangeability studies reported to date have dealt with natural gas/hydrogen mixtures containing up to 25% hydrogen. No studies appear to have been carried out at the opposite end of the scale for mixtures of hydrogen containing relatively small quantities of natural gas. Ultimately, such studies will be necessary before a planned change-over from 100% natural gas to 100% hydrogen could be contemplated.

An important feature of hydrogen combustion is that it can be made to take place on a catalyst. Because the catalytic surface is a participant in the chemical reaction sequence of combustion, the "energy barrier" between the reactants and products of combustion can sometimes be reduced. This allows the combustion to take place at lower temperatures.

Although low-temperature catalysts are platinum based, they will probably not be very expensive. With the loadings used in present experimental studies, about 20¢ worth of platinum is required to release 1000 Btu/hr. At that rate, an average house would require a capital investment of about \$10 to \$15 worth of platinum for the catalytic burner for all of its space-heating requirements.

Catalytic appliances (space heaters, for example) do not have to vent their combustion products to the outside except as needed for humidity control. (Usually, 25% or more of a fuel's heat of combustion is lost with the combustion gases as they are vented.) Also, catalytic igniters could be used to start flame-type combustion in atmospheric hydrogen burners. This would eliminate the need for pilot lights. Note that methane does not ignite on a cold catalyst, nor does stable low-temperature catalytic combustion occur with methane, so that the attributes of a catalytic burner are not available unless a high percentage of hydrogen is available in the fuel gas. (Very hydrogen-rich mixtures would probably require the addition of an odorant to facilitate detection of leaks or flameouts.)

Gas-Electricity Integration

An interesting concept has been proposed and studied independently by two combined gas-electric utilities (Public Service Electric and Gas Company of New Jersey and Niagara Mohawk Power Corporation) for integrating fuel cells and electrolyzers so that energy can be transferred in either direction between the gas and electric systems.

During periods of excess electricity generation (i.e., "off-peak" periods), electrolyzers would be operated and the product hydrogen fed into the gas system. (As long as the proportion of hydrogen to natural gas remains below about 10%, there is no concern about interchangeability.) The electricity system thus builds up an energy "credit" in the gas pipeline "bank." During periods of peak electric demand, gas (now a mixture, but largely natural gas) is drawn from the gas system to feed fuel cells which generate power for the electric grid. Although regulations sometimes discourage the use of natural gas for electricity generation, these utilities believe that as long as they are operating on their "Btu credit" already deposited in the gas system, such a transfer will be allowable.

At present, there is no operable "reversible" fuel cell-electrolyzer, so that two independent systems must be incorporated. In principle, there is no reason to prevent a truly reversible unit being developed that would function both as an electrolyzer and a hydrogen-air fuel cell; but no research on this is presently underway.

Niagara Mohawk has conceptualized an integrated gas-electric system in their service area. Electrolyzer units would be located close to gas regulator stations, where hydrogen would be fed into the gas grid. Fuel cells fed from the grid would be located close to heavy electrical loads. The fuel cells would be supplemented by a secondary fuel supply.

An analysis by Niagara Mohawk compared the secondary fuel consumption of this concept on their system with that required by several storage technologies. The analysis showed that per kWhr of electrical output (3412 Btu), the electrolyzer-fuel cell system would need a total fuel input of 15,437 Btu for state-of-the-art fuel cells, or 12,864 Btu for advanced fuel cells. By comparison, it was calculated that pumped hydro storage and compressed air storage systems would need 15,385 and 14,400 Btu, respectively. These comparisons were based on an assumed 15% capacity factor and the naphtha-reformer fuel cell combination operating at an additional 30% capacity factor, with 42% efficiency for the fuel cell and 95% for the electrolyzer.

The integrated power concept is not without problems. In addition to those related to the technical development of efficient, cost effective components, Niagara Mohawk particularly noted the delays in scheduling baseload nuclear and high efficiency coal fired plants for supplying the electrolyzer power and the regulatory problems that may arise from fluctuations in delivered gas heating value. In addition, they noted the possibility of leaks in older gas distribution lines, particularly in older cast iron pipes.

Conclusions and Recommendations

1. Sufficient experimental work has been carried out to indicate the general range of interchangeability of hydrogen-natural gas mixtures with natural gas alone for existing natural gas burners. It may be conservatively estimated that 10% by volume of hydrogen can be added to natural gas without customer problems. The exact critical level, however, depends on the type of burner or pilot, the formulation of natural gas, and whether other additives, such as SNG, refinery off-gas, or sewage digester gas, has been added to it along the way. Detailed experimental studies must be carried out to clarify this because no mathematical model is accurate enough to predict interchangeability for hydrogen.
2. Experimental and analytic studies should also be carried out to determine the interchangeability range of small amounts of natural gas in hydrogen for burners specifically designed for pure hydrogen operation.
3. Experimental conversions of a small number of widely different types of natural gas burners (residential and industrial) for hydrogen use should be carried out to confirm that no unforeseen problems occur. If the conversion goes without problems, then further research work on this aspect can be safely delayed until nearer the time when it is needed.
4. One of the major assumptions in planning for a conversion from gas to hydrogen is that the user conversion cost involved will be far less than for converting to electricity. This should be tested soon. Detailed comparative cost analyses should be carried out on the actual costs involved in converting end-use equipment from gas and oil to hydrogen, in comparison to converting from gas and oil to electricity.
5. Experimental measurements of the overall efficiency of space heating using unvented catalytic hydrogen heaters should be made to compare with conventional gas and electric heating systems. This efficiency data, taken on a "whole house" basis, is needed to carry out meaningful comparisons of the overall hydrogen energy delivery system with the alternatives.
6. There is a prospect for the interchange of energy between gas and electric systems using electrolyzers and fuel cells. This can assist in meeting the daily and seasonal peaks experienced by both systems. On an efficiency basis, the concept is attractive. Costs have not been developed, but would obviously be lower if a combined fuel cell-electrolyzer unit can be developed to replace the need for two entirely separate units. However, before related research is initiated, consideration must be given to the serious regulatory problems that could inhibit the use of this concept, especially in areas where gas and electric utilities are separate entities.

REFERENCES

1. Gregory, Derek P. "A Brief History of the Hydrogen Energy Movement." In Symposium Papers, *Hydrogen for Energy Distribution*, sponsored by the Institute of Gas Technology, Chicago, Ill., July 24-28, 1978.
2. Moll, H.J., and R.L. Itteilag. "A Forecast of Economic Demand for Gas Energy in the U.S. Through 1990." *American Gas Association Monthly*, March 1979.
3. *Forecast of Likely U.S. Energy Supply/Demand Balances for 1985 and 2000 and Implications for U.S. Energy Policy*. Washington, D.C.: Domestic and International Business Administration. U.S. Department of Commerce, NTIC Report PB-266 240, January 20, 1977.
4. Gas Requirements Committee. *Future Gas Consumption of the United States, Volume 7*. Denver, Colo.: The University of Denver Research Institute, September 1977.
5. Guerra, C.R., J.E. Griffith, K. Kelton, and D.C. Nielsen. "Natural Gas Supplementation with Hydrogen." Pp 267-272 in *Proceedings of the DOE Chemical Energy Storage and Hydrogen Energy Systems Contracts Review*, Hunt Valley, Md., November 16-17, 1977. Pasadena, Calif.: Jet Propulsion Laboratory, Publication JPL 78-1, February 1978.

CHAPTER VI

AUTOMOTIVE USES OF HYDROGEN

The use of either hydrogen or electric batteries as power sources for automobiles is considered by some to be technologically feasible, environmentally desirable, and, in the long run, necessary when supplies of hydrocarbon fuels become limited. Unfortunately, current system studies indicate that such vehicles would have substantially higher cost than gasoline powered internal combustion engine (ICE) vehicles of comparable range, payload, and acceleration. These cost obstacles to commercialization make questions regarding optimum timing and rate for research, development, and commercialization activities in support of such systems difficult to resolve. The difficulties are compounded by future uncertainties regarding the availability of both fossil and non-fossil energy supplies, by uncertainties regarding future environmental emissions requirements, and by the myriad of possible, but undeveloped, automotive propulsion systems involving batteries, fuel cells, flywheels, and heat-engine hybrids that might use alternative fuels such as synthetic hydrocarbons, methanol, and gaseous or liquid hydrogen.

This discussion will examine the comparative costs and weights of conventional gasoline-powered cars, those theoretically possible with advanced storage battery power systems, and those believed achievable with several hydrogen powered systems. This part of the discussion will be based on the study conducted at the Lawrence Livermore Laboratory entitled "Energy Systems for Automotive Propulsion."¹ These performance comparisons will be augmented by a treatment of the environmental and safety considerations involved in the use of hydrogen as an automotive fuel in order to round out a view on the future potential for hydrogen powered vehicles.

Costs and Weights

In reference 1, costs and weights are estimated for gasoline powered ICE vehicles having ranges and accelerations corresponding to potential battery-powered electric vehicles. The assumed vehicle characteristics

and their resultant curb weights are shown below together with the assumed fuel efficiencies (in miles per gallon) for current and projected 1990-2000 five passenger ICE cars.

<u>Vehicle</u>	<u>HP</u> <u>LB</u>	<u>Curb Wt</u> <u>(lb)</u>	<u>Range</u> <u>(mi)</u>	Merge Acceleration 30-55 mph	Fuel Eff. mi/gal ^(a)	
				<u>(Sec)</u>	<u>Current</u>	<u>1990-2000</u>
Five Passenger						
ICE-Equivalent	.03	2500	250	8	22.7	33
Intermediate Performance	.02	2150	150	10	30.0	35
Limited Performance	.016	2030	75	14	33.3	42

^a Combined EPA Cycle

Similar estimates are available in reference 1 for two-passenger cars, for multi-purpose vans, and for light trucks; however, the main features of vehicle comparisons are shown for the five-passenger vehicles which would also probably have the greatest market potential.

Some of the results of the studies of reference 1 are summarized in Table IV, which shows the estimated curb weights and costs for a range of gasoline, hydrogen, and battery powered automobiles. In addition to initial purchase costs, Table IV includes life cycle costs (expressed in \$/mile) for an assumed 100,000 miles of driving over a ten-year car lifetime. In the determination of life-cycle costs, the study assumed gasoline prices ranging from \$0.61/gallon in 1980 to \$0.73/gal. in 2000 (in 1975 dollars). Correspondingly, residential electricity costs ranged from \$0.0363 to \$0.0384/kWh and hydrogen costs were assumed to be \$10/10⁶ Btu for gaseous hydrogen and \$11.7/10⁶ Btu for liquid hydrogen. Experience has already indicated that the projected gasoline costs are low. According to the data cited in Chapter III, the assumed electrical and hydrogen costs to the consumer are also likely to be low. Chapter III estimates future electricity production costs to be \$0.03/kWh and gaseous hydrogen costs at the manufacturing plant to range from \$6.80/10⁶ Btu for hydrogen from methane to \$9.50/10⁶ Btu for hydrogen from coal. Additional costs of \$4.40/10⁶ Btu at the plant would be expected for the manufacture of liquid hydrogen.

TABLE IV Projected Weights and Costs for 5-Passenger Automobiles in the 1990-2000 Time Period

	Curb Weight (lbs)	Cost, '75\$		Ratio to Baseline ICE	
		Initial	10-Yr. Life Cycle (\$/mi)	Curb Wt	Life Cycle Cost
<u>ICE Equivalent</u>					
Baseline ICE	2500	2555	.097	1.0	1.0
LH ₂	3361	4444	.149	1.3	1.5
FeTiH _x	9041	19790	.466	3.6	4.8
MgH ₂ (10% Ni)	6035	9723	.259	2.4	2.7
<u>Intermediate Performance</u>					
Baseline ICE	2150	2297	.091	1.0	1.0
LH ₂	2852	3601	.124	1.3	1.4
FeTiH _x	4303	7301	.195	2.0	2.1
MgH ₂ (10% Ni)	3821	5629	.164	1.8	1.8
NiZn	4864	9531	.260	2.3	2.9
Li-Al/FeS _x	3826	7938	.221	1.8	2.4
Na/S Ceramic	3866	7543	.211	1.8	2.3
<u>Limited Performance</u>					
Baseline ICE	2030	2215	.085	1.0	1.0
LH ₂	2628	3199	.113	1.3	1.3
FeTiH _x	3168	4373	.134	1.6	1.6
MgH ₂ (10% Ni)	2977	3695	.120	1.5	1.4
Adv. Pb/Acid	5300	6258	.183	2.6	2.2
NiZn	2827	4727	.142	1.4	1.7
Li-Al/FeS _x	2996	5672	.166	1.5	2.0
Na/S Ceramic	3020	5415	.159	1.5	1.9

Overall, the level of operating costs assumed in reference 1 are lower than those discussed in Chapter III by approximately a factor of two if retailing costs are taken into account. For gasoline, gaseous hydrogen, and battery powered cars, the ratio of automobile life cycle costs would probably not differ markedly; however, the LH_2 costs in reference 1 are so low in comparison with GH_2 that the LH_2 vehicle life-cycle costs are unrealistically low. It is estimated that with more realistic LH_2 costs the apparent advantage over gaseous hydrogen systems would tend to diminish.

Table IV includes three classes of vehicles ranging from those that are performance-equivalent to standard ICE vehicles down to limited range and performance urban-type cars. In all cases, the life cycle cost calculations assumed 100,000 miles of driving over a ten-year period. It seems unlikely that the limited performance urban vehicles would, in fact, accumulate the same mileage as full performance, gasoline equivalent cars. The life-cycle cost ratios are, therefore, probably weighted in favor of the limited performance vehicles.

Performances equivalent to gasoline powered standard automobiles are shown to be obtainable with either liquid hydrogen or gaseous hydrogen vehicles using hydride storage. As the table indicates, however, none of the projected battery systems offer this potential within reasonable weight and cost limits. For all classes of vehicle performance, the hydrogen and the battery powered vehicles are shown to weigh more and to cost more, on both an initial and life-cycle basis, than equivalent gasoline-powered vehicles. The hydride storage cars weigh more and are more costly than the liquid hydrogen cars, with the magnesium hydride system being appreciably lighter and cheaper than the iron titanium hydride system. The iron titanium hydride system remains under consideration, however, because it can operate at room temperature and has a lower heat of decomposition. The magnesium hydride requires a temperature of over 300°C to give a desirable hydrogen fuel pressure. (Advanced batteries, such as Li-Al/FeS_x and Na/S also operate at temperatures in excess of 300°C .) Combined $\text{MgH}_2\text{-FeTiH}_x$ hydride systems show promise but were not considered in the reference study.

By reducing maximum power (vehicle acceleration) and total stored energy (range), more reasonable battery systems can be designed. The "limited performance" vehicle, having only 25% of the range and 60% of the acceleration of the baseline ICE vehicle, is of interest to consider as a specialized urban vehicle. While the operating cost for the ICE vehicle is only reduced by 15% and for the LH_2 vehicle by 25%, heavy systems such as the FeTiH_x show a 70% cost reduction and batteries become competitive with the hydrogen powered systems. For this limited performance system, the three hydrogen systems can be considered equivalent within the limit of accuracy of these studies and about 50% more expensive than a limited performance ICE system. They are also estimated to be about 25% more expensive than the full performance ICE vehicle. A battery- or hydrogen-driven two-passenger vehicle, which is estimated to cost about the same as a five-passenger full-performance ICE system, would still be more expensive than a two-passenger ICE system.

At an intermediate performance with 150-mile range, the advanced lead acid battery is too heavy to be considered and the advantages of the advanced LiAl/FeS_x and Na/S systems are apparent. The NiZn battery is considered a nearer term possibility than the other systems. Here, as in the case of the limited performance system, the hydrogen systems are estimated to be somewhat less costly than battery systems.

The option of a dual fuel ICE where hydrogen is burned on short trips and gasoline is burned for increased power and long trips was not studied but has been demonstrated using FeTiH_x storage*. This option would probably be intermediate in cost and weight between two single fuel cases and might be superior in cost and performance to the battery systems. It also has the advantage of being potentially retrofittable to existing gasoline-powered automobiles.

A vehicle powered with a hydrogen-air fuel cell, which was not studied in reference 1, would offer the potential advantage of reducing hydrogen consumption by a factor of 2-4, because of higher operating efficiencies, as compared with the hydrogen ICE vehicles that were analyzed. The advantages of electric propulsion coupled with increased range (as compared with advanced storage batteries) make the fuel cell an option of interest--if cells of adequate performance could be built.

Up to this time, there has been little focused development of fuel cell powered vehicles. There have, however, been several demonstrations which show their feasibility^{2,3}. A recent joint study by the Los Alamos Scientific Laboratory, Brookhaven National Laboratory, and the U.S. Army MERADCOM forms a basis for projections of future performance⁴. This study developed design and performance characteristics for 15kW commuter vehicles and delivery vans and for 60kW buses. The performance of current internal combustion and/or diesel engine vehicles for each of the applications was used as a base line for comparing both component sizing and performance evaluations.

The phosphoric acid fuel cell, fueled with either propane or methanol, was selected for this study. The data for the fuel cell were based on projections from 2.5kW methanol reformer fuel cells designed, fabricated, and tested at the Energy Research Corporation. To provide acceptable performance, the fuel cell was assumed to be coupled in a hybrid mode with lead-acid batteries that would provide short duration power supplements during accelerations. Table V compares the characteristics of the projected subcompact car with the earlier experimental vehicles.

The entire propulsion system for the projected vehicle (15kW fuel cell, methanol reformer, motor, and 4 kWh lead-acid batteries) would fit under the hood of a Volkswagen Rabbit and would give performance comparable to that of a diesel powered vehicle, with a net increase in weight of approximately 600 lbs. Using cost and vehicle markup data from the Ford Motor Company, Volkswagen, and the U.S. Department of Transportation, and assuming \$200/kw for the fuel cell reformer system, a fuel cell

*Ronald Wooley, Billings Energy Corporation, in a presentation to the panel, April 26, 1978.

TABLE V Demonstrated and Projected Characteristics of Fuel Cell Powered Vehicles.

	G.M. Electrovan	Kordesch Car	Projected Subcompact
Reference	(2)	(3)	(4)
Power Train	Fuel Cell H ₂ -O ₂	Hybrid Fuel Cell/Batt. H ₂ -Air/Lead Acid	Hybrid Fuel Cell/Batt. Methanol H ₂ -Air/ Lead Acid
Rated Power, kW	32	6	15
Peak Power, kW	160	22	35
Curb Weight, lbs.	7,100	2,000	3,000
Power Train Weight, lbs.	3,930	700	800
Top Speed, mph	70	55	75
Cruising Speed, mph		40	55
Acceleration			
0-60 mph, sec.	30		
0-30 mph, sec.			14
Start-up time, min.			10
Fuel Consumption	55m/lb H ₂	55m/lb H ₂	26 mpg/methanol
Cost, \$			7,000

powered Volkswagen Rabbit would have an estimated sticker price of about \$7,300, as compared with \$4,400 for a diesel powered car. Fuel consumption was calculated for both 55 mph cruise and the J227 metropolitan driving cycle. Substantial improvements in vehicle system efficiency were found; however, with the projected fuel costs assumed for 1990, no clear cut economic advantage was found based on fuel savings. It was projected that reduced maintenance costs and improved reliability could be very favorable factors in the market place. The results of the study suggest that the sequence of entry of fuel cell vehicles will be city buses, highway buses, delivery vehicles, and then passenger vehicles.

When the energy costs from Chapter III of this report are examined together with the data from Table IV, there is a clear indication that hydrocarbon fueled vehicles will be superior to hydrogen or battery powered vehicles from the viewpoint of both performance and cost as long as coal or other carbon sources are available for the production of hydrocarbon fuels at the indicated coal liquefaction cost level. It is also indicated that hydrogen fueled ICE systems can compete in performance and cost with battery powered systems. A major difficulty

with the use of hydrogen is the lack of a distribution system, although the use of home or retail electrolytic generation units would offer a reasonably simple, though costly, route to the introduction of hydrogen fueled vehicles. When the probable costs of electrolytically derived hydrogen are considered, the development of a hydrogen-air fuel cell suitable for automotive use would appear to be required for hydrogen to be broadly competitive with advanced battery systems.

Environmental Factors

Hydrogen and battery powered automobiles have the advantage of producing substantially lower pollutant levels on the roadway than today's hydrocarbon powered engines, however, other factors must also be taken into consideration. If electricity, hydrogen, and hydrocarbons are manufactured from coal, the total atmospheric loading of pollutants will come predominantly from conversion of coal to these higher grade resources. For today's power plants, delivering electricity to the home at about 30% efficiency, a 50% efficient electric car would require consumption of about 100 BTU of coal for every 15 BTU of work applied to the wheels. Emissions of CO_2 and NO from a power plant generating the charging electricity from coal would be much greater than those from a comparable hydrocarbon burning automobile. In addition, sulfur oxides and particulates are also produced. The fact that automobile emissions tend to be concentrated in urban areas is, of course, an important consideration; however, to be truly low polluting, the electric car would have to use nuclear or solar based electricity.

Hydrogen and hydrocarbons can be made from coal with about 50% efficiency; however, use in a heat engine at about 10-20% efficiency gives an overall efficiency range of 5-10% compared to ~15% for the battery system. To a first order, the amount of coal that would have to be mined and converted would be inversely proportional to these efficiencies. However, the apparent increase in coal needed for the heat engine vehicles is counteracted to varying degrees by the greater weight (and power requirement) of battery and hydrogen powered systems for the same work delivered to the wheels.

Electrolytic manufacture of hydrogen and its subsequent use in a heat engine would consume more than twice the electricity, or coal, as the battery system so that the environmental effects from coal production and use would be more than doubled.

Hydrogen burned in a heat engine, of course, does not produce CO , CO_2 , hydrocarbons, or soot; however, some nitric oxide is produced. The amount of nitric oxide can exceed that produced in current hydrocarbon burning automobiles if combustion is carried out at near stoichiometric mixture ratios*; however, taking advantage of hydrogen's capability of burning in very lean fuel mixtures, the NO_x emissions can be held well below present or proposed NO_x emission standards so that hydrogen can

*Russell Stebar, G.M. Technical Center, in a presentation to the panel, March 15, 1978.

be relatively clean burning in this regard. It is probable that if the difference in weight and cost between hydrogen or battery vehicles and hydrocarbon powered vehicles were made available for emissions control in hydrocarbon vehicles, pollutants (except CO₂) could be reduced to low levels compared to present day practice. Vehicle advantages based on differences in automotive generated pollutants are therefore not universally persuasive; their validity will depend on the specific circumstances involved in production of the fuel or electricity and on vehicle design and use. In the event that a diminution of CO₂ emissions becomes necessary in the future, substitution of nuclear and solar energy for coal and oil in power generation and for heating would appear to be a major first step, since increasing coal consumption to generate electricity for charging vehicular batteries or to generate hydrogen would be counterproductive.

By using nuclear generated heat, electricity, and hydrogen in conversion of coal to transportation quality hydrocarbons, the 50% of coal consumed in synthetic fuels manufacture could be eliminated, giving a factor of two reduction in net CO₂ emissions for a given amount of hydrocarbon fuel. However, since petroleum is expected to be a major source of hydrocarbons for many years (particularly if hydrocarbon use for stationary heating and power generation were eliminated, thus stretching out the world supply), the major reductions in CO₂ emissions for transportation systems would have to result from higher transportation efficiency and from use of battery and hydrogen powered transportation systems. This could provide a powerful incentive for use of these systems.

In summary, in cases where electricity and hydrogen are generated from coal, the overall environmentally based driving force for electric and hydrogen powered vehicles seems questionable. Local considerations might make their use locally advantageous; however, under these circumstances the option of specially controlled hydrocarbon burning vehicles should also be considered in view of the major cost and weight penalties for battery and hydrogen systems.

If nuclear based electricity were to be used for hydrogen production and battery charging, the environmental advantages of hydrogen or battery systems will be more substantial -- particularly if CO₂ emissions require control in the future.

Safety

Any high energy fuel is potentially dangerous, and gasoline with its high volatility can be considered especially so. Hydrogen with its wide flammability and explosion limits must also be considered hazardous, and it is probable that high energy batteries will also offer special hazards. In order to introduce a new high energy system to public use, careful documentation of hazards relative to the existing alternatives is required.

Large scale manufacture of hydrogen can be considered well established in industrial practice; however, electrolytic generation by the consumer would have the potential of producing explosive mixtures. Here the basis for comparison might be garage storage of a gasoline-containing automobile and home battery charging.

Transportation of liquid or gaseous hydrogen to retail outlets is of concern and could be compared to truck transportation of gasoline and LPG. Transportation of hydrogen stored as hydrides seems relatively safe but would also require further examination, although the high weights of hydrides necessary for commercial lot shipments would probably preclude their use.

Techniques for retail dispensing of liquid hydrogen would require considerable development and exhaustive testing to establish equal or better safety than gasoline and LPG dispensing.

Operational and crash safety are of obvious interest. In the case of liquid hydrogen, flame and spill characteristics are radically different from hydrocarbon flames. It is possible that for a given size spill or leak, hydrogen may be less dangerous than gasoline; however, insufficient work has been done to establish quantitatively even major features such as spreading tendency of a spill, relative flame radiation, and explosion hazards. In the case of hydrides it seems probable that they are on the whole safer than gasoline although some storage of gaseous hydrogen under pressure will be necessary and the hazards involved will require study as will the possibility of crank case and intake manifold explosions. It will probably be necessary to add odorents to hydrogen to enhance its detection in the event of a spill.

Of course, comparable studies should be made of any high energy battery system since safety in home charging and in high energy crashes cannot be assumed.

A major program for development of these alternative systems should include a responsible and extensive study of safety hazards relative to present practices. A criterion for adoption of a new system should be equal or better safety than for the existing system being replaced.

Response to Fuel Shortages

It seems quite probable that when oil available for importation becomes limited, we will go through a period where liquid fuel needs cannot be met by domestic facilities for production from coal and oil shale. Because of the long response time for developing mines and conversion plants, as well as electric power generating facilities, there might be a rather prolonged period involving energy allocation and/or fuel rationing. The individual needs for transportation brought about by such a situation, could well provide the incentive for purchases of expensive, limited performance vehicles based on use of electricity, assuming they are available. Although public resistance to vehicles of lower performance levels has seemed a stumbling block to their acceptance, the prospect of gasless Sundays and long lines at the gas pumps has given immediate impetus to the notion that cars need to be "re-invented." Such a situation would

not seem to lend itself to construction of special facilities for hydrogen production and distribution as a top priority; however, the use of home electrolytically generated hydrogen to be used initially in a retrofitted gasoline powered automobile which could also use such rationed gasoline as was available, might well be the lowest cost route for an individual to extend his transportation capabilities. One could also expect a developing market for a variety of battery-powered vehicles at such a time. An analysis of the merits and problems of such a retrofit system to determine their merit as a facile entry into electricity-based vehicles is needed to evaluate current demonstrations such as those at the Billings Corporation and the Riverside bus demonstration where FeTiH_x storage is combined with existing gasoline powered systems.

International Considerations

The preceding discussions have been primarily based on a projected energy future for the United States where we have the very real and relatively attractive option of meeting our liquid fuel needs from coal and oil shale. This option is not available in most of Europe and in Japan, as well as in many of the lesser developed countries. In these countries, growing reliance on nuclear generated power and lack of coal and shale oil, and also less need for long distance automobile travel, can be expected to produce a driving force for electric and hydrogen powered vehicles that could result in an earlier bona fide market for such systems than in this country. The possibility of an export market therefore exists, or, as in the case of the small vehicle, the commercial lead may be taken overseas.

Conclusions

1. Both hydrogen fueled and battery powered vehicles will be uniformly heavier and more expensive than comparable performance gasoline powered systems designed for passenger use. The cost advantage of the hydrocarbon-powered vehicle will probably remain as long as synthetic hydrocarbon fuels can be made available.
2. Liquid hydrogen powered ICE equivalent systems are lighter and cheaper than hydride storage hydrogen systems or battery powered systems.
3. For systems of limited performance and range, the hydrogen systems are projected to be somewhat lighter and lower in cost than advanced battery systems; however, the difference is small and may be within the error of the estimate.
4. No estimates were found for costs and performance of hydrogen/gasoline dual fuel systems or hydrogen/fuel cell systems. Both of these have potentially important advantages as compared with hydrogen burning engines.
5. If hydrogen, electricity and gasoline are all made from coal, energy consumption and cost are comparable for all three systems. None of these systems can be considered environmentally clean because of the needed large

coal consumption. Vehicle emissions can potentially be controlled in all cases if the weight and cost differences between the gasoline automobile and others are partly used for high performance emissions controls on the gasoline system.

6. A restriction on CO₂ emissions would emphasize the need for nuclear or solar heat and power and would tend to favor use of hydrogen and electric powered automobiles, although the carbon consumed in manufacturing gasoline could be cut in half by use of nuclear heat for coal liquefaction and refining.

7. Major technologically advanced countries that lack coal and shale resources, such as Japan and parts of Western Europe, will have a strong incentive to rely on nuclear power and could well find it advantageous to develop and use hydrogen and battery-powered automobiles before the United States.

8. If imported and domestic petroleum production falls below our national needs before sufficient facilities are constructed to produce liquid fuels from coal and oil shale, there may well be usual pressures for public use of electrically based automobiles. For this situation, retrofitting gasoline-powered automobiles to run on home electrolytically generated hydrogen could be an alternative to purchase of a separate hydrogen or battery powered vehicle; however, the energy cost per mile for this option would be greater than that for either gasoline or battery powered systems.

9. If in the long-term electricity and hydrogen generated from nuclear or solar power sources become the only automobile energy alternatives, combustion of hydrogen in a heat engine will not be competitive on an energy-consumption or energy-cost basis; however, use of hydrogen in a fuel cell-powered automobile has the potential of being competitive or superior to battery-powered systems.

10. Although existing fuel cells do not meet the requirements for automotive systems, there are no known scientific barriers to development of a hydrogen-air fuel cell which could compete with advanced batteries. There is no organized program aimed at this goal, in contrast to substantial activity in the advanced battery field. A research program aimed at ultimately developing advanced hydrogen-air fuel cells is recommended.

11. The safety of public use of hydrogen will be a matter of general concern. Clear comparison and demonstration of the safety relative to use of gasoline and battery-powered vehicles does not exist and is needed.

REFERENCES

1. Behrin, E., J. Bolger, C.L. Hudson, J.G. O'Connell, B. Rubin, M.W. Schwartz, C.H. Waide and W.J. Walsh. *Energy Storage Systems for Automobile Propulsion*. Livermore, Calif.: Lawrence Livermore Laboratory, ECRL-52303, December 1977.
2. Marks, C., E.A. Rishavy, and F.A. Wyczalek. *Electrovan-A Fuel Cell Powered Vehicle*. Warrendale, Pa.: Society of Automotive Engineers. SAE Paper 67016, 1967.
3. Kordesch, K.V. *Journal of Electrochemical Society* 118:812. Princeton, N.J.: Electrochemical Society, Inc., 1971.
4. McCormick, B., J.R. Huff, S. Srinivasan, J. McBreen, and R. Bobbett. *Application Scenario for Fuel Cells in Transportation*. Informal report for Los Alamos Scientific Laboratories, Los Alamos, N.M. Report No. LA 7634-MS, February 1979.

CHAPTER VII

AIRCRAFT USE OF HYDROGEN

The potential use of liquid hydrogen as an aircraft fuel has been of interest for many years because of the performance gains available, in principle, from the very high heat of combustion per unit weight and the outstanding cooling capacity for very high speed flight. The use of hydrogen as a rocket fuel for space flight is well established and is currently the only major application of hydrogen for propulsion purposes. Here the high heat of combustion combined with low molecular weight is of preemptive importance in high performance rocket systems. For aircraft, the low molecular weight is not important, as such. However, the very high heat of combustion and clean burning characteristics have resulted in a continuing program of study and some limited experimental work sponsored by NASA.

Performance

The overall performance comparison of LH_2 with conventional hydrocarbon fuels is best understood from an examination of the Breuget range equation:

$$R = I_{sp} \cdot \frac{L}{D} \cdot V \cdot \ln \frac{W_o}{W_f}$$

Where: R range
 I_{sp} engine specific impulse, lb thrust/lb fuel/sec
 L aircraft lift
 D aircraft drag
 V velocity of flight
 W_o weight at start of cruise
 W_f weight at end of cruise

The advantage of hydrogen appears in the specific impulse which, for a turbojet engine, is proportional to the lower heating value of the fuel. The ratio of heating values for LH_2 and jet fuel is approximately 2.6, offering the potential for a very large range advantage to hydrogen. Unfortunately, some of this advantage is lost due to the low density and

and low storage temperature of LH_2 , which results in a fourfold increase in required tank volume, as compared with JP fuel, and an even greater increase in tank weight due to insulation requirements. The increase in tank weight reduces the W_o/W_f ratio. The lift/drag ratio also decreases about 20% because of the larger fuselage required to house the hydrogen tankage.

Rather complex systems studies are required to compare optimized aircraft designs for these two greatly different fuels. Several such studies have been carried out under NASA sponsorship.^{1,2} In the past the Department of Defense has also studied and sponsored work in this area, but current studies do not show significant advantages for hydrogen fueled aircraft for conventional military missions.³

In studies of civil transport aircraft it is customary to fix the number of passengers to be carried and the design flight Mach number. Optimum configurations, power plants, etc., are then selected and the size and weight of the aircraft are calculated as a function of range. An example of such a calculation is indicated for a subsonic, $M=0.85$, system in Figure 1, taken from reference 1. The takeoff mass of the hydrogen fueled aircraft is less for all ranges shown, with the difference increasing as the design range increases. (This figure illustrates the very long ranges attainable with large subsonic aircraft.)

Table VI, from reference 4, compares the performance of two 400 passenger, $M = 0.85$, 5500 N. Mi. aircraft designed for the two fuels. The hydrogen aircraft is lighter, has smaller wings but a longer body, and the cost is estimated to be about 5% lower. Energy consumption, as measured by Btu/seat mile, is 18% lower. As inferred by Fig. 1, these performance advantages increase as design operating range increases.

TABLE VI Comparison of LH_2 and Jet-A Subsonic Transport Aircraft

		LH_2	Jet-A	$\frac{\text{Jet-A}}{\text{LH}_2}$
Gross Weight	lb	377,800	532,420	1.41
Block Fuel Weight	lb	50,710	172,720	3.41
Operating Empty Weight	lb	230,000	243,400	1.06
Thrust, per engine	lb	24,080	35,940	1.49
Wing Area	ft^2	3,243	4,259	1.31
Wing Span	ft	170.8	195.8	1.17
Fuselage Length	ft	215.6	197.0	0.91
Takeoff Distance	ft	7,945	7,967	1.00
Landing Distance	ft	5,810	5,210	1.12
Lift/Drag (Cruise)		16.43	18.18	1.11
Spec. Fuel Cons. (Cruise)	lb/lb/hr	0.202	0.603	2.99
Aircraft Price	$\$10^6$	38.1	40.9	1.07
Energy Utilization	Btu/Seat mile	1,189	1,445	1.22

An indication of the operating ranges of interest is given in Table VII, taken from reference 5. The 5500 mile range (10,215 km) chosen for the comparison in Table VI is seen to be adequate for non-stop flights to all destinations considered except Australia. Such aircraft would be useful for both Pacific and Atlantic service. While greater ranges can be built into subsonic aircraft, the increase in weight and cost is substantial.

A subsonic trip time approaching 12 hours for a 5500 mile trip is sufficiently long that the potential for reduction to about 4.5 hours for a Mach 2.7 SST becomes attractive. A comparison of takeoff gross weights for 250 passenger aircraft is shown in Figure 2¹. At a range of 5500 miles the ratio of takeoff gross weights is 2.6, and the advantage of a hydrogen fueled aircraft is clearly evident. Unfortunately, a detailed comparison of supersonic aircraft designed for a 5500 mile

TABLE VII Projected 1990 International Air Traffic

<u>Destination-Pairs</u>	<u>Distance N.Mi.</u>	<u>Estimated Passengers Per Day</u>
North America - Europe	3180	65,000
North America - Japan	4730	8,600
North America - South America	4200	6,800
Europe - Japan (Polar)	5250	3,000
Europe - Australia	9170	3,000
North America - Australia	6550	2,600
Europe - South America	4960	2,200

range is not available; however, such a comparison has been made for a 4200 mile range, suitable for transatlantic service, and is shown on Table VIII. Here the advantage of hydrogen is larger than for the subsonic 5500 mile comparison of Table VI. For example, the ratio of takeoff gross weights is 2.04 for the supersonic case as compared with 1.41 for the subsonic case. From the curves of Figure 2, the takeoff weight advantage of the LH_2 fueled aircraft would be expected to increase substantially as design range is increased from 4200 to 5500 miles. It is clear that the greatest performance advantage for LH_2 would occur in supersonic flight, particularly since it would permit the construction of a practical size aircraft capable of useful Pacific service, where long flight times place a greater value on speed than on the relatively short transatlantic flights.

TABLE VIII Comparison: Jet A-1 and LH₂ Fueled Supersonic Transports of Advanced Design

		Jet A-1	LH ₂	Jet A-1 LH ₂
Payload	lb	49,000	49,000	
Range	n.mi.	4,200	4,200	
Cruise Speed	Mach	2.7	2.7	
Takeoff Gross Weight	lb	750,000	368,000	2.04
Operating Empty Weight	lb	309,700	223,100	1.39
Fuel Weight, Mission	lb	326,000	81,440	4.01
Fuel Weight, Total	lb ₃	391,300	95,900	4.08
Fuel Volume	ft ²	8,290	21,700	0.38
Wing Area	ft	10,822	6,880	1.57
Wing Loading, Takeoff	lb/ft ²	69.3	53.5	1.30
Wing Loading, Landing	lb/ft ²	39.1	41.7	0.94
Span	ft	132.5	105.6	1.25
Overall Length	ft	297	328	0.91
Lift/Drag (Cruise)		8.5	6.99	1.22
Energy Utilization	Btu/Seat mile	6102	4274	1.43

Environmental Performance

Several of the emission problems encountered with hydrocarbon fueled aircraft would be eliminated by use of hydrogen. These include CO, soot, polynuclear aromatics, SO₂ and odor. The high reactivity of hydrogen makes possible very lean combustion which can, by reducing flame temperature, reduce formation of nitric oxide to extremely low levels. These characteristics virtually eliminate any contributions to air pollution problems in the vicinity of the airport.

Effects on the upper atmosphere are of continuing interest⁷. Supersonic and long range subsonic aircraft inject their combustion products into the stratosphere and are accused of potentially reducing ozone concentration and therefore increasing skin cancer caused by ultraviolet radiation that would otherwise have been absorbed by stratospheric ozone. While more recent work has indicated smaller effects than projected in the original CIAP study, essential elimination of the NO can be considered an advantage. While CO₂ is eliminated, the amount of water vapor injected is approximately doubled. No important effect on ozone is expected; however, atmospheric modeling studies have indicated a very small net atmospheric warming effect (~0.01°K) for a large SST fleet.

For the hydrogen aircraft, Tables VI and VIII suggest some reduction in noise and sonic boom due to the smaller size of the aircraft. Overall, the use of hydrogen as an aircraft fuel can be considered to be an improvement over hydrocarbon use.

Safety

The high volatility and wide inflammability limits of hydrogen and its ability to detonate when mixed with air raise a different set of safety problems than are encountered with conventional jet fuel. The problems encountered in ground handling and storage are discussed in Chapter VIII. In the aircraft, the problem of mortality resulting from crashes is of greatest interest.

Two major cases need to be considered. A hard crash offering injury to ground personnel is a major consideration, as is a soft crash resulting in fuel spills and fire. In both cases major hazards clearly exist for both LH_2 and conventional jet fuels. Comparison is complex because of the radically different physical and combustion properties of the two fuels and definitive studies have not been carried out, although a substantial program is being considered by NASA.

There have been no definitive studies of soft crashes, and it is not clear that LH_2 is either more or less hazardous than JP fuel. The difficulty of arriving at firm conclusions is illustrated by the long debate concerning the relative hazards of low flash point jet fuel (JP-4) and the high flash kerosene type (Jet A). Both have been used and studied extensively. While laboratory studies indicated a somewhat greater hazard for JP-4, the results were not sufficiently convincing to overcome the cost and supply incentive connected with its use. Statistical studies of crashes over many years have shown a small but definitive increase in survival probability for Jet A, and JP-4 is now being phased-out of commercial and military use. Careful and objective studies of the relative hazards are needed if work is to continue on the application of hydrogen.

Operations

Airport modification to add LH_2 fueling capability to the existing jet fuel supply system would be a major undertaking. Boeing and Lockheed have, under contract to NASA, carried out studies on modifying the San Francisco and Chicago (O'Hare) airports to supply LH_2 to all wide bodied aircraft². Gaseous hydrogen was assumed to be delivered to the terminal by pipeline for liquefaction and distribution. The general conclusions were:

- o Sufficient land available
- o No unsolvable technical problems
- o Turnaround times similar for aircraft using hydrocarbon fuel
- o Facilities would cost about \$470 million at O'Hare and \$340 million at San Francisco, including liquifaction costs.

This is clearly a major undertaking; however, it is encouraging that modification as contrasted to construction of special airports was deemed feasible.

Aircraft Research and Development Needs

Several studies of R&D needs have indicated no major technological barriers requiring fundamental advances; the problems appear to be largely in the development and feasibility demonstration categories. Reference 6 suggests that, as a minimum, R & D would be needed to develop duct-burning turbofan engines designed to operate efficiently on hydrogen fuel, and lightweight cryogenic insulation, e.g., PVC or polyurethane foam, which is impervious to air, which can be bonded to an aluminum tank, and which can demonstrate an acceptable effective useful life.

The Research, Development, Test and Evaluation (RDT&E) cost of any new aircraft is high. For a supersonic system, the following are given in Reference 6:

<u>Cost Element</u>	<u>Aircraft Costs, \$10⁶</u>	
	<u>Jet Fuel</u>	<u>LH₂</u>
RDT&E		
Engine	950	650
Airframe	<u>3,327</u>	<u>2,661</u>
Total	4,277	3,320
Recurring R & D on production aircraft, each	6.7	4.8

Basis

- o 1973 dollars
- o Production of 300 aircraft

The RDT&E cost of the aircraft system is large compared to anticipated costs for research on special hydrogen related components.

Combining the uncertainties of a new supersonic aircraft with the uncertainties and problems of switching to a radically different fuel will be a strong inhibiting factor. It has been suggested in Reference 6 that a logical evolution would be to demonstrate LH₂ in a subsonic system by modification of existing long-range aircraft. In particular, current wide-body subsonic transports might be lengthened to accommodate LH₂ tanks and a normal load of cargo. An international cargo route would need to be established, involving four airports and two years of operation. Costs were roughly estimated to be somewhat under one billion dollars and would require eight years. A program of this general nature would appear necessary to establish the basis for development of a new aircraft and to establish the necessary international confidence in the wisdom of such a change.

Operating Cost

An estimate of operating cost (without fuel) in 1973 dollars for the 4200 mile M 2.7 supersonic aircraft of Reference 6 is shown below:

Direct Operating Cost ¢/Seat Mile

<u>Item</u>	<u>Jet A-1</u>	<u>LH₂</u>
Flight Crew	.088	.093
Insurance	.181	.137
Depreciation	.583	.441
Maintenance	<u>.468</u>	<u>.376</u>
Total	1.32	1.05
Estimate for 1980	2.9	2.3

It is seen that somewhat lower operating costs (without fuel) are projected for the LH₂ airplane. Since the fuel costs under consideration are for 1980, it is necessary to scale up the 1973 costs given. A factor of 2.2 was used on past and projected increases in construction costs.

The cost of several aircraft fuels at an airport bulk distribution station is shown below⁸:

<u>Source Fuel</u>	<u>\$/10⁶ BTU</u>	<u>Ratio Coal Based LH₂ Jet Fuel</u>
LH ₂ - from coal	18.8	
- from electricity	22.3	--
Jet Fuel from		
- coal liquefaction	9.0	2.1
- oil shale	4.9	3.8

Oil shale based jet fuel is substantially cheaper than jet fuel from coal; however, since coal represents a much larger resource and since it is more generally available on a world-wide basis than shale oil, the coal based costs are given greatest emphasis.

Using the above fuel costs, the following operating costs are derived:

	<u>Jet A-1</u>	<u>LH₂</u>
D.O.C. (without fuel) ¢/seat mile	2.9	2.3
Fuel Cost ¢/seat mile	<u>5.5</u>	<u>8.0</u>
Total	8.4	10.3
Ratio of Costs $\frac{\text{LH}_2}{\text{Jet A-1}}$		1.23

Of interest is the dominant role of fuel costs when synthetic fuels must be used. In this example, the D.O.C. for LH_2 would be 23% higher than for coal derived Jet A. If shale oil derived jet A were available, on the other hand, LH_2 costs would be 125% higher.

This comparison at 4200-mile range places LH_2 at a distinct economic disadvantage. By scaling between two different studies (1) and (6), a rough estimate of the relative total D.O.C. indicates that at the 5500-mile range the LH_2 aircraft would be approximately .8 times the Jet A aircraft D.O.C. and that this advantage would grow rapidly at longer ranges, although as previously noted, a 5500-mile range appears adequate for a large fraction of the longer flights.

If jet fuel from shale oil were available, the LH_2 5500-mile aircraft would lose its economic advantage -- its operation is estimated to be 1.5 times as expensive as the Jet A aircraft.

The LH_2 costs used in this study were based on existing technology. New technology for reducing hydrogen costs might be expected to produce the savings of the order of 20% during this century. It must be remembered, however, that a large fraction of coal-based jet fuel cost will be due to the large hydrogen consumption and that improvements of roughly the same magnitude for coal liquefaction and refining costs can also be anticipated. On this basis, no radical improvement in the relative costs of LH_2 and synthetic jet fuel is foreseen, and because of the large cost differential between shale oil (and jet fuel from tar deposits) and jet fuel from coal, it can be anticipated that substantial use will be made of these resources in an effort to reduce aircraft operating costs.

Conclusions

1. Liquid hydrogen fueled aircraft offer performance advantages over hydrocarbon fueled systems in terms of lower energy consumptions per seat-mile, lighter aircraft, and lower emissions of recognized pollutants.
2. These advantages are greatest for long-range supersonic aircraft where the 5500-mile range needed for Pacific service approaches the limit practically achievable with hydrocarbon fuel.
3. The high cost of LH_2 relative to coal derived jet fuel results in a higher direct operating cost for the normally considered 4200-mile range.
4. At ranges of 5500 miles or greater, LH_2 fueled supersonic aircraft would have lower operating costs than coal based hydrocarbon fueled systems.
5. The crash safety problem for passengers and for by-standers requires further definition.
6. No serious engine development problems are anticipated. Airframe, tank and fuel handling problems appear manageable without the requirement for major technological advances; however, development of the optimum design and systems will require substantial effort.

FIGURE 1 Mass Characteristics of LH₂ and JP-A Passenger Transport Aircraft. Design Mach No. 0.85.

FIGURE 2 Effect of Fuel and Design Range on Takeoff Gross Weight for a Mach 2.7 SST.

REFERENCES

1. Whitlow, J.B., R.J. Weber, and K.C. Civinskis. *Preliminary Appraisal of Hydrogen and Methane Fuel in a Mach 2.7 Supersonic Transport*. Prepared by and for Lewis Research Center and U.S. Army Air Mobility R&D Laboratories, Cleveland, Ohio: K.C., NASA TMX-68222, May 3, 1973.
2. Wilcofski, R.A. *Review of Studies of Applications of Hydrogen to Aircraft and Airline Operation*. Informal presentation to NRC Ad Hoc Committee on Aircraft Fuel Conservation, April 8, 1977.
3. Mikolowsky, W.T., L.W. Noggle, with contributions by W.F. Hederman, and R.E. Horvath. *An Evaluation of Very Large Airplanes and Alternative Fuels*. Rand Corp. R-1889-AF, December 1976.
4. Brewer, G.D. *Fuel for Tomorrow's Commercial Aircraft*. Presentation at Workshop on Societal Aspects of Hydrogen Energy Systems, Reston, Va., June 4-8, 1978.
5. *Market and System Analysis for Potential Global Transport Application of Reusable Orbital Transport*. Burbank, Calif.: Lockheed Corp. NASA CR-67279, July 29, 1965.
6. Brewer, G.D. and R.E. Morris. *Advanced Supersonic Technology Concept Study - Hydrogen Fueled Configuration*. Burbank, Calif.: Lockheed Corp. NASA CR-2534, April 1975.
7. Oliver, R.C., E. Bauer, H. Hidalgo, K.A. Gardner, and W. Wasylkivskyj. *Aircraft Emissions: Potential Effects on Ozone and Climate: A Review-Final Progress Report*. Washington, D.C.: U.S. Department of Transportation FAA Report FAA-EQ-73-3, March 1977.
8. Cart, E.N., Jr., A.R. Cunningham, and D. Carter. *Alternative Energy Sources for Non-Highway Transportation*. Linden, N.J.: Exxon Research and Engineering Co., Government Research Laboratories. Draft report prepared under DOE Contract EC 77-C-05-5408, June 1978.

CHAPTER VIII

THE FUEL CELL IN HYDROGEN ENERGY SYSTEMS

The fuel cell is a promising device for stationary and mobile energy conversion that provides the opportunity for major improvements in conversion efficiency. It is most effectively fueled with hydrogen, which can be uniquely utilized by the fuel cell to produce electricity. Thus, the development of this conversion device could be a central element in the expansion of future hydrogen markets.

The fuel cell has some interesting features when viewed from a systems perspective. Because it is modular in construction, the investment cost is not especially sensitive to size or scale. Thus, it is an attractive device for decentralized power production, including mobile applications. In mobile applications it offers high efficiency and the flexibility for making effective use of liquid fuels or for the direct use of hydrogen.

The current problems and limitations of fuel cells which inhibit their widespread commercialization are associated with the electrode catalysts and involve their low power density and low lifetimes. These problems are being addressed in current R&D programs. If this work is successful the fuel cell could revolutionize the configuration of our energy system. The following discussions of the impact of the fuel cell are based on an anticipation of future success in the ongoing development work and in the supporting research in materials and catalysts and define the potential role of hydrogen under such circumstances. The fuel cell and hydrogen energy systems are examined together to: (1) evaluate the interrelationships of the development of complementary technologies; (2) identify the barriers and incentives to co-implementation of the technologies in selected energy consuming sectors; (3) define R&D requirements for overcoming the identified techno-economic barriers; and (4) project fuel cell commercialization prospects as they may be enhanced by coupling with hydrogen energy systems technology.

Fuel Cells Overview

Fuel cells may be characterized as modular, pollution-free, high efficiency, energy conversion systems that offer flexibility of applications over power ranges from kilowatts to multi-megawatts. Fuel cell systems may exhibit differences in electrolyte (acid, alkaline, solid polymer,

molten carbonate, solid oxides) and associated electrode structures and catalysts. These systems are at various stages of development with cost/performance characteristics that can be matched to given stationary and mobile applications. In all cases, the reactants are hydrogen and an oxidizing agent -- usually oxygen supplied from air. In molten carbonate and solid oxide fuel cells, carbon monoxide can serve as the fuel. The hydrogen-halogen systems, which offer the added advantages of reversibility, permit operation as electrolyzers as well as fuel cells, i.e., they are regenerative fuel cells.

General Characteristics of Fuel Cells

The general characteristics of fuel cells may be summarized as follows:

Alkaline

- o Low temperature operation (60° to 250°C)
- o High efficiency (~50%)
- o Non-noble metal catalysts
- o Requires CO₂ removal from oxidant and fuel streams
- o Proven in space applications

Phosphoric Acid

- o Low temperature operation (150° to 225°C)
- o Tolerant of CO₂ in fuel and oxidant streams
- o Lowest in efficiency (~40%)
- o High state of development
- o Need noble metal catalysts

Solid Polymer Electrolyte

- o Low temperature operation (80° to 150°C)
- o Moderate efficiency (~45%)
- o Noble metal catalysts
- o Less tolerant of contaminants than others
- o Generally expensive materials
- o Advanced state-of-the-art

Molten Carbonate

- o High temperature operation (~650°C)
- o Requires corrosion resistant materials
- o CO₂ in the oxidant stream is a requirement
- o Tolerant to CO
- o Does not require noble metal catalysts
- o Moderate efficiency (>45%)
- o Engineering development in early stages

Solid Oxides

- o High temperatures operation (700° to 1,000°C)
- o Potentially high efficiency (>50%)
- o Very fast reaction kinetics
- o Tolerant to CO
- o Least advanced state-of-the-art
- o Mechanical complexity
- o Materials constraints

Hydrogen-Halogen

- o Regenerative
- o Closed cycle operation
- o Requires electrical input
- o Uses halogen and halogen acids
- o High electric-to-electric efficiency (~70%)
- o Hazardous in high population areas
- o Potential use in small and large solar systems
- o Based on current industrial technology, but needs more development work

The phosphoric acid system is currently undergoing field tests. Alkaline systems have major applications in space and underwater systems. A solid polymer system has been used successfully in the space program; further development efforts are now under way. Molten carbonate fuel cells are regarded as second generation fuel cells for utility applications, and development efforts are in progress. Solid oxide systems are considered potential third generation fuel cells, but major materials problems need to be solved in order for these systems to be commercialized. Table IX illustrates the considerable progress made in fuel cell technology over a 10-year period in acid, alkali, and solid polymer electrolyte fuel cells. The high power densities, obtained in the solid polymer system, though only with oxygen as the oxidant, gives hopes

TABLE IX Improvements in H₂/Air Fuel Cells

Reference	H ₂ /Air		Acid, H ₂ /Air			SPE, H ₂ /O ₂	
	Alkaline						
	(1) 1967	(1) 1977	(2) 1967	(2) 1977	(3) 1977	(4) 1967	(4) 1977
Current Density, mA/cm ²	100	200	300	300	400	15-42	700
Cell Voltage	0.75	0.7	0.55	0.65	0.6	0.6-0.7	0.68
Power Density, mW/cm ²	75	140	165	195	240	10-25	476
Operating Temperature, °C	65-75	80	160	190	25	25	82-100
Thermal Efficiency, %	51	47	37	44	41	40	46
Catalyst Loading, mg/cm ²	1	0.2	20	0.76	4	65	8
Startup Time	3.5 hrs	5m			15m	3 hrs	3-5 m
Life Hours	5,000	NA		12,000	600	1000	40,000

gives hopes for developing fuel cell powered vehicles. The development of acid fuel cells with trifluoromethane-sulfonic acid as the electrolyte is in its infancy; however, due to the low operating temperature and reasonably high power density, this system shows promise for transportation applications. With pure hydrogen as the fuel, the present performance of the alkaline fuel cell is sufficient to consider it as a power source for electric vehicles. The hydrogen will have to be carried on the vehicle as a compressed gas or as a metal hydride.

Because it may be difficult to depart from the use of liquid fuels, the most attractive option for electric vehicles is the methanol reformer/phosphoric acid fuel cell. The reformation of methanol to hydrogen occurs at close to 200°C, and the waste heat from the phosphoric acid fuel cell can be used for this reaction. The overriding factors at the present time are cost, weight, and volume. If the power densities in the H_3PO_4 fuel cell can be doubled, a fuel cell-battery hybrid vehicle could be a reality within the next 20 years.

Complementary Systems Applications

Fuel cell and hydrogen energy technologies can be complementary over the full spectrum of stationary and mobile energy conversion/storage systems applications. The mutual benefits to hydrogen market expansions from emerging fuel cell commercialization are apparent. Ready availability of hydrogen transported from a central production site via pipelines would increase fuel cell system efficiencies, reduce capital costs, and make more effective use of valuable land by eliminating external reformers. As acceptance of fuel cells increases, so will the need for hydrogen production. In effect, economies of scale may derive from shifting the individual external reformers to centrally located hydrogen production centers.

The electric utility industry, sponsored by the U.S. Department of Energy and private sector funding, is engaged in a field test demonstration of a 4.8 MW fuel cell electric power-generating unit in downtown New York City. Substantial public resistance was encountered when it was learned that a fuel requirement of 50,000 gallons per week of naphtha (the major component of gasoline) would be handled at the site. A large 26 MW unit, identified by the utilities as the optimum size for decentralized power generation in urban load centers, will require in excess of 300,000 gal/wk of fuel. Hydrogen, if made available from remote coal gasification or electrochemical process centers by pipeline, would avoid the logistics and storage associated with providing liquid fuels to the sites.

With the possible exception of molten carbonate systems, it is highly unlikely that fuel cells will be used in the centralized power generation mode since competing alternatives (nuclear, coal) appear more viable from an economics and logistics view. A logical application of the fuel cell is at the substation or decentralized level or in a total energy system. In either case there is the potential to use a substantial portion of the waste heat if the fuel cell is applied in the commercial or multi-family residential size range as dispersed substations supplying both electricity and heat.

Total energy systems utilizing fuel cells are a potentially attractive option that can take full advantage of design cost/performance tradeoffs permitted by fuel cell systems. The fuel cell's unique load-following characteristics at constant efficiency allows matching to thermal and electric loads at overall efficiencies (electric and thermal) that can approach 90%. Further, the designer can trade off electrochemical efficiency through the use of cheaper catalysts and electrode structures that will not only reduce cost but will also provide greater proportions of sensible heat. These systems could be an extension of the TARGET concept pursued by the gas industry, and could be implemented successfully if scarce natural gas supplies were to be supplemented by hydrogen.

Hydrogen storage and delivery systems coupled to fuel cells have the potential to provide a propulsion alternative to the gasoline powered vehicle that need not unduly compromise commonly accepted driving parameters such as range, acceleration, and rapid refueling. Electric vehicles propelled by fuel cells can provide a three-fold efficiency improvement over internal combustion engines on a normal driving cycle. The development of lightweight hydrogen storage systems would further increase range and acceleration capabilities. Alkaline electrolyte fuel cells are leading candidates for transportation applications because of their high performance and low cost features; however, power density is limited and there would be a need to consider hybrid propulsion systems having short-term high power potentials in order to compete in performance with the internal combustion engine.

Economics

The capability of the fuel cell to impact substation electricity production, total energy system, or transportation costs will be directly proportional to capital costs and to fuel efficiency improvements. For example, in the case of automobiles, a fuel-cell driven vehicle would be at least 2.5 to 3 times more efficient than an internal combustion engine also fueled with hydrogen, with corresponding reductions in fuel costs per mile. The increase in efficiency is less dramatic in comparing electricity production via combined cycle turbines, (perhaps a 30% increase), but there is a further potential for greater mechanical simplicity and lower environmental impacts with fuel cells. In total energy systems, the fuel cell may be applied in very small sizes at highly dispersed sites, with the advantage of furnishing on site waste heat at reduced energy distribution costs.

Gas turbines are available to electric utilities having peak load demands. Capital costs are in the range of \$200-\$300/kW, with operating efficiencies of the order of 23-25%. One cost projection for 40 kW fuel cell systems indicates that large markets could reduce capital investment requirements to as low as \$385/kW. With the overall efficiency of state-of-the-art fuel cells approaching 40%, it is evident that there is a potential economic niche for the fuel cells of the future.

The time frame for the commercialization of fuel cells will depend upon the rate at which R&D produces performance improvements and upon the economic trends of competing alternatives. The price escalation rates for conventional hydrocarbon fuels will play a major role in the rate of market penetration of hydrogen-fueled fuel cell systems. Applications of stationary systems in utilities have near- to mid-term commercialization prospects, with total energy systems following closely in the energy markets. While mobile applications have substantial long-term market potentials, initial penetrations will probably be confined to specialty vehicles in closed-loop fleet markets.

REFERENCES

1. Kordesch, K.V., *Journal of Electrochemical Society* 118: 815. Princeton, N.J.: Electrochemical Society, Inc., 1971
2. Fickett, A.P. "Fuel Cell Electrocatalysis: Where Have We Failed?" Pp 546-558 in *Proceedings of the Symposium on Electrode Materials and Processes for Energy Conversion and Storage*, Volume 77-6. Princeton, N.J.: The Electrochemical Society, 1977.
3. Janskiewicz, S., M. George, and B.S. Baker. "Aqueous Sulfonic Acid Electrolyte Fuel Cell." Pp 103-106 in *National Fuel Cell Seminar Abstracts*, Boston, Mass., June 21-23, 1977.
4. McElroy, J. "Status of Solid Electrolyte Fuel Cell Technology." Pp 176-179 in *National Fuel Cell Seminar Abstracts*. San Francisco, Calif., July 11-13, 1978.

CHAPTER IX

HYDROGEN R&D EVALUATION

Whether, when, and to what extent hydrogen may be regarded as a likely contender in the energy arena will depend on a web of factors--technical, economic, environmental, legal, and institutional. Therefore, a realistic assessment of hydrogen calls for analysis of the full range of benefits and costs associated with its generation, transmission, storage, and end use. The assessment process will be far from simple, however, in that some of the environmental concerns mitigated by hydrogen's clean burning and non-polluting properties will be exacerbated by probable sources and methods for its expanded generation. Moreover, the extended time periods over which uncertain cost estimates must be projected make economic comparisons difficult. To rate tomorrow's potential fuel by yesterday's market values could prejudice the case against research into and development of new energy options, possibly at the very moment in history when international politics and policy must play a more important role in decisions about energy than today's cost accounting estimates.

Hydrogen's advantages are conventionally identified as its abundance, its clean burning, its high energy content, and the fact that it can be recycled. It is capable of serving all energy sectors--commercial, residential, and industrial--and can be used in automobiles, aircraft, and rocket engines as well as for a heating fuel. A drawback, according to present reckoning, is that by today's comparative standards it is expensive. A synthetic fuel, it is a carrier and not a source of energy. The fact that it must be produced from hydrocarbons or from water means that various categories of costs must enter into the picture, specifically the environmental, economic, and social costs associated with the energy resources from which the hydrogen would be derived. Elusive, but just as important, are the opportunity costs that must be taken seriously in an era when upheavals of the international political scene that are associated with the production and consumption of energy from many of the present hydrocarbon sources have profound effects on the total energy picture.

Whether, when, and to what extent hydrogen will seem to be a desirable fuel may depend on factors outside the technical state-of-the-art and more on the state of the world. Nonetheless, the technical know-how is a sine qua non; hydrogen cannot be regarded as a logical option unless the technical particulars of its generation, transmission, and storage are explored to their full potential.

Customary cost/benefit analyses make it clear that hydrogen's benign end-use properties will be partially offset by the deliterious effects of its production. When coal sources are considered, air quality, land use, consumption of other resources (especially water), and disposal of wastes have all been identified as problems that could adversely affect hydrogen's desirability¹. Even hydrogen production from water would not be an unmixed blessing because of the myriad of concerns with both nuclear and coal-fired electrical power plants. A recent workshop, jointly sponsored by the National Bureau of Standards, the Department of Energy, the National Science Foundation, the Electric Power Research Institute, the National Oceanic and Atmospheric Administration, and the Committee on Science and Technology of the U.S. House of Representatives, specifically recommended that a proper assessment of hydrogen as a fuel should move beyond the usual questions based on a limited view of economics and technology². A detailed comparison of hydrogen with other fuels taking into full account all of the social and environmental ramifications should be performed. An important question that would emerge would be whether the reduction in external impacts at the point of use would be sufficient to outweigh the costs associated with production. Such a focus might be useful in setting R&D policy by identifying problem areas where a breakthrough in technology at some crucial stage might alter advantageously the balance between costs and benefits.

Even with the sources of hydrogen remaining virtually unchanged, certain environmental considerations may tip the balance in its favor. Assuming that coal becomes a major source of hydrogen in the future, even such environmental problems as land disturbance, water use, and air pollution associated with hydrogen production might be less harmful than the direct burning of coal. If coal must be used to meet our near-term energy needs, conversion to hydrogen may be attractive, both economically and environmentally, based on air quality considerations.

According to a study conducted by the National Academy of Sciences³, the continuing increase of carbon dioxide in the atmosphere is a matter of great concern. While there is no agreement on the exact nature of or the timetable for climatic effects of CO₂ release, the consequences may be dire. The report concludes, "The prospect of damaging climatic changes may thus be a stimulus for greater efforts at conservation and a more rapid transition to alternate energy sources than is justified by economic considerations alone."

The narrow application of conventional "engineering economics" in technology assessments of hydrogen fuel futures may form too limited a framework for valid energy R&D decisions to be made. In fact, the cost/benefit analysis performed prematurely can become a deadening guideline in the design of R&D programs. Many of the benefits may be long in coming; many of the values may elude quantification. Under such circumstances, preoccupation with economic considerations may divert attention from the wider set of societal issues that only come into focus if we view the future with a premise that hydrogen may become a feasible energy option.

Judicious restriction of the cost/benefit analysis to the resolution of near term development and demonstration decisions is indicated. Such major, near-term funding decisions should bear the scrutiny of economic analyses; the longer term, more basic research opportunities should not.

In the consideration of appropriate R&D to establish the role and place for hydrogen in the energy equation, it will be important that its safety aspects be thoroughly explored and understood before decisions are attempted regarding its deployment as a consumer fuel. The hazards associated with its use must be carefully assessed for each potential application, for although hydrogen may be safer than gasoline or methane for some applications, it may be more hazardous in others. Actually, a great amount of technical information on hydrogen safety properties is already in hand⁴, but there will be a tendency to attack hydrogen as a highly flammable and explosive fuel because it is a new and unfamiliar fuel. Such criticism must be anticipated at a time when the public is increasingly insistent that it be allowed to participate in making technical decisions affecting its future. It will be imperative, therefore, that gaps in information about the safety of hydrogen be filled before the public is asked to accept a new fuel form.

REFERENCES

1. McBride, J.P., R.E. Moore, J.P. Witherspoon, and R.E. Blanco. "Radiological Impact of Airborne Effluents of Coal and Nuclear Plants." Pp 1045-1050 in *Science*, December 8, 1978.
2. Moss, L.I. "Summary and Critique of Environmental Issues Drawn from Hydrogen Workshop." *Workshop on Societal Aspects of Hydrogen Energy Systems*, NBS, DOE, NSF, EPRI, NOAA, and U.S. House of Representatives, Reston, Va., June 4-7, 1978.
3. Geophysics Study Committee, Geophysics Research Board. *Energy and Climate*. Washington, D.C.: National Academy of Sciences, 1977.
4. Hord, J. "How Safe is Hydrogen?" In Symposium papers, *Hydrogen for Energy Distribution*, sponsored by the Institute of Gas Technology. Chicago, Ill., July 24-28, 1978.

CHAPTER X

INTERNATIONAL HYDROGEN PROGRAMS

Present efforts on hydrogen programs in some countries of Western Europe are greater than in the United States. These programs encompass work on hydrogen production by electrochemical and thermochemical means, use in transportation vehicles, and as supporting work on pipeline transmission and distribution. Projects are generally a mix of long-term and near-term technologies for applications which are self-evident to countries which have a few or no native energy resources, but are totally dependent on imported energy. Some European countries and Japan have no significant fossil fuel resources, i.e., oil, natural gas or coal. Their interest in alternative fuels which can be derived from abundant, e.g., nuclear or renewable non-fossil resources, is imperative for their ultimate survival. Countries like Brazil and our neighbors in Canada, who have abundant hydroelectric resources, are well aware that hydrogen production from such resources is an attractive option. In Germany, work is in progress on advanced high temperature nuclear reactors which have the potential to be the source of energy to produce hydrogen by electrolytic means coupled with high efficiency electric conversion devices, or with direct heat using thermochemical production processes. The Japanese see a logical connection between solar energy and hydrogen production processes.

It is of value to mention some special accomplishments in the area of hydrogen made abroad in various countries.

In the Netherlands, pioneering work was done on metal hydrides of the rare earths such as LaNi_5 . A systems study was done which showed that combined electric and hydrogen systems may be optimal in the Netherlands. Presently, there are no intensive R&D programs on hydrogen, but they are a participant in the International Energy Agency (IEA) effort in electrolytic hydrogen production, i.e., Annex IV and V.

The European Community, which consists of a collection of western European countries who contribute to the R&D budget, supports major programs on hydrogen at the Joint Research Centre (JRC) at Ispra. In addition, major contractual efforts in hydrogen are in progress with industrial firms. The JRC has the largest effort in the world on thermochemical hydrogen production. An important piece of work has been a major marketing study on future uses of hydrogen. They have recently demonstrated a bench-scale hybrid electro-chemical-thermochemical hydrogen production process, i.e., Mark-13.

West Germany has similar interest in hydrogen production and does work on thermochemical processes that can be driven by high temperature nuclear heat sources under development. The leading manufacturer of advanced electrolyzers is Lurgi Company, which is located in West Germany. The Daimler-Benz Company of West Germany has major work in progress on hydrogen-fueled vehicles. Their most significant accomplishment is the design and operation of vehicles operating on dual hydride bed of iron titanium and magnesium-nickel alloys originally developed in the U.S. Presently, discussions regarding possible programs in this area have been begun between U.S. DOE and the German Federal Ministry for Research and Technology. In these discussions, they have indicated that a 30 man-year effort is in progress in Germany.

Both Italy and Switzerland have work in progress on advanced alkaline electrolyzers. The De Nora Corporation and Brown Boveri of Italy and Switzerland, respectively, have built some of the largest industrial electrolysis plants and are each supporting in-house R&D efforts, as well as working on contracts from their respective governments.

In Japan, the "Sunshine Project" is a broad-base hydrogen research program. Emphasis is on solar-assisted hydrogen production. They have done pioneer work on direct electrolytic production from sunlight with semi-conductors which has stimulated similar work in the U.S.

Advanced electrolyzer development is under way in Canada in a joint effort between Electrolyzer Corporation of America, Noranda Corporation and the Canadian Government. Large undeveloped hydroelectric resources exist in Canada which could be developed quickly in the medium term. There is good reason to believe that a portion of this renewable resource could be sold to the U.S. Evidence for hydrogen markets in the U.S. could encourage development of these hydroelectric resources in Canada.

In Brazil, with its vast remote hydroelectric resources in the Amazon, there are programs in progress to develop electrolyzer technology and ultimately an electrolytic equipment industry. The Gas Company of Rio, which today delivers a 50-50 vol. % mixture of hydrogen and carbon monoxide (H_2 -CO) has interest in adding electrolytic hydrogen to their city gas distribution system. They presently produce the H_2 -CO mixture by reforming naptha imported from the Middle East. Discussion between U.S. DOE and the Brazilian Government on possible cooperative programs was initiated, but further discussions have been delayed pending resolution of unrelated issues.

Some of the work mentioned above is covered under existing or pending IEA agreements on hydrogen production, i.e., Annexes I, II, and IV and V, respectively. The Annexes deal with thermochemical hydrogen production (I and II), assessment (III), and electrolyte production (IV and V). The participants in these Annexes are:

- o Belgium
- o Canada
- o European Economic Community
- o Germany
- o Italy
- o Japan
- o Netherlands
- o Sweden
- o Switzerland
- o United Kingdom
- o United States

The IEA cooperative activities are either in progress or about to be finalized. Formal exchange of information on Annexes I, II and III has begun. Copies of these Annexes are available from DOE.

The French, although not a participant in the IEA effort, have a major program in place on development of advanced electrolytic hydrogen production processes (Electricite De France). They foresee important industrial uses of hydrogen in the near term, and eventually a hydrogen pipeline grid in France. Gas De France has completed a preliminary study of the feasibility of underground storage of hydrogen and found no major technical obstacles. They have expressed an interest in possible exchange of information with similar DOE programs.

SUMMARY

1. Various cooperative efforts are in progress or pending between U.S., European countries and the Japanese on hydrogen production.
2. The level of effort in hydrogen R&D in western Europe is significantly greater than in the U.S.
3. Possible cooperative efforts on hydrogen-fueled vehicles are under discussions with the Germans.
4. Discussions with Brazil regarding possible cooperative efforts were begun but are delayed for unrelated reasons.
5. Cooperative programs with the Canadians in the area of hydrogen production are logical because of the close proximity of the source (Canadian hydroelectric) and markets (U.S.) as well as good political relations between the two countries.
6. Informal inquiries have been made by BNL to the French on possible interest in exchange of information with the U.S. on DOE programs dealing with underground storage of hydrogen.

CHAPTER XI

FINDINGS AND RECOMMENDATIONS

Hydrogen is currently important in the U.S. economy as a major chemical intermediate, as a reducing gas, and for a variety of special applications. It has a potential as a fuel for such applications as automobiles and aircraft, where its cleanliness and high energy content offer operating advantages, and may ultimately serve as a replacement for natural gas or petroleum by delivering and storing energy derived from non-fossil (nuclear and solar) sources. In this latter case hydrogen would be considered as a carrier of energy, analogous to electricity, rather than as a primary energy source.

Current annual consumption of the order of 3 trillion standard cubic feet corresponds to an energy content of about 1 quad (10^{15} Btu). Most is produced and consumed onsite as a feedstock commodity by the chemical and petroleum refining industries that comprise about 95 percent of the present market. Most of the remaining "merchant" hydrogen is also used for feedstock purposes. Little is consumed as a fuel. High performance space rockets constitute the principal current fuel users, although industrial waste gases containing hydrogen are occasionally blended with natural gas for heating purposes, and there are a number of locations where pure hydrogen, produced as a byproduct, is burned on its own for industrial heating applications.

As long as fossil fuel sources continue to remain available and useable at reasonable costs, natural or synthetic hydrocarbons will probably continue to compete with electricity as the preferred energy carriers of the future. If, however, either fuel depletions or environmental restrictions limit the future economical availability of conventional fossil fuel sources, it will become necessary to shift fuel dependence in part or wholly from fossil to non-fossil sources. When, for example, oil and gas supplies become limited, there will be an impetus to expand nuclear and solar energy resources and to accelerate the manufacture of synthetic fuels, including hydrogen, from coal.

Although the U.S. is fortunate in having enough coal reserves to last a very long time, even at accelerated rates of consumption, it cannot be assumed that unlimited supplies of coal will be available in the future. It may not prove possible to markedly expand coal production rates because of labor shortages or environmental restriction on extraction, processing, or shipment. Other environmental restrictions at the point of use may make the consumption of coal increasingly expensive.

Finally, a possibility exists that carbon combustion may be curtailed in the future in order to control increases in atmospheric CO₂ content.

If it becomes necessary to limit coal consumption, the alternate energy sources would appear to be either nuclear (fission and/or fusion) or solar, which, generally speaking, yield either heat or electricity as their primary outputs. Cost effective means do not exist for the long-distance transmission of heat per se. Therefore such energy sources would have to be converted to electricity or to some other form of energy carrier, such as hydrogen, to make them widely useful. Several reasons suggest that hydrogen might be competitive to electricity as an energy carrier in spite of its higher production cost:

- o The costs and environmental impacts of hydrogen transmission and distribution are more favorable than those for electricity.
- o Some end uses lend themselves to hydrogen use. For example, it should be more economic to convert existing oil and gas burning equipment to use hydrogen than to replace it with equivalent electrical equipment,
- o It should be simpler and cheaper to store hydrogen than to store electricity.

An improved understanding of coal use problems in general, and CO₂ problems in particular, including the dimensions of necessary solutions, may become clear within a decade. Because results may be negative in terms of expanded coal consumption, it would be prudent to have R&D results in hand by that time that would enable early implementing decisions on alternate energy resources to be made, including those that would relate to the future role and extent of hydrogen as a fuel. This does not mean that hydrogen production capabilities need to be poised in useful form. The deployment of large amounts of non-fossil energy sources would take a number of years, during which the hydrogen production technologies could be refined and constructed. Thus, although basic and applied research on non-carbon hydrogen production techniques and technologies should be conducted within the next few years in order to provide a technical foundation for possible implementation, the more expensive development and demonstration activities can probably be deferred until the need for non-carbon-sourced hydrogen is more positively understood.

In contrast to the uncertainties about the future of hydrogen as a fuel, the present trend of steady increases in the use of feedstock hydrogen is expected to continue. By the year 2000, for example, estimates of such consumption range up to three times current levels for the industrial areas now using hydrogen. New requirements for ore reduction and for the refining of shale oil and synthetic fuels from coal could add further additional hydrogen markets if these processes become widely used. These added feedstock requirements will probably either be met by expanded methane reforming -- only about 3% of the total U.S. annual natural gas consumption is currently used for such purposes -- or, as economic or political factors dictate, by coal conversion processes.

It is fairly certain that a widespread market for hydrogen as a fuel will not materialize until it is forced by hydrocarbon limitations. Prospects for the near-term adoption of hydrogen as a fuel are considered to be low. For example, there is no economic reason to contemplate the conversion of natural gas to hydrogen in order to serve as an alternate gaseous heating fuel. On the other hand, while there are some urban air pollution improvements that could accrue if hydrogen were used as a propulsive fuel in place of liquid hydrocarbons, it is questionable that large amounts of natural gas would be diverted from gaseous heating and feedstock roles to manufacture hydrogen for use as a transportation fuel. Thus, if a fuel market for hydrogen is developed, it is probable that the fuel would have to come either from non-carbon sources or as an end product of a coal/synthetic-fuel chain. Neither route is economically attractive for the near term in comparison with competitive fuels from the same raw materials.

Electrolysis is very capital intensive because of the large required investments for electricity generation. Similarly, although hard designs of thermochemical systems for decomposing water are not available, analyses of preliminary concepts indicate large capital investments may be necessary. Thus, although the feedstock (water) costs are virtually nil, the end product cost of non-carbon hydrogen is high.

Unfavorable economics are also encountered in the derivation of hydrogen from coal. In comparison with the manufacture of synthetic natural gas (SNG), hydrogen extraction from coal requires a greater capital investment and more energy. As a result, gaseous hydrogen can be expected to cost 20 to 50% more than SNG, per Btu. Synthetic coal liquids, which are more expensive than SNG, could approximate gaseous hydrogen in cost; however, since both the fuel distribution infrastructure for transportation fuels and the ultimate user vehicles are geared to liquid hydrocarbons, overall transportation system cost advantages would be expected to remain with the synthetic liquid fuels. Any reduction in the future costs of producing hydrogen will also reduce the cost of synthetic liquid fuels, since much of the latter's cost derives from its hydrogen enrichment. Thus, relative cost ratios of coal-sourced hydrogen and coal liquids should not be expected to change appreciably in the future.

Generally speaking, cost considerations will inhibit the use of hydrogen as a transportation fuel unless the environmental penalties of using synthetic gasoline or diesel fuels prove to be high. In the case of automobiles, potential hydrogen applications will be competing with synthetic fuels in the near-term and advanced storage battery electric cars in the longer term. The development of a low cost, highly efficient hydrogen/air fuel cell might capture automotive markets for hydrogen in the competition with advanced batteries, since there are not the same fundamental, basic chemical limitations to fuel cell performance that there are to batteries--but hydrogen/air fuel cells are not receiving current R&D attention.

Civil transport aircraft of the future may also create a market for hydrogen as a transportation fuel. Because of its high energy density, a liquid-hydrogen fueled supersonic aircraft would be able to operate at ranges in excess of those possible with hydrocarbon fuels, and thus make non-stop trans-Pacific type flights practical. If a national goal for the development of a long-range supersonic transport were to be adopted, serious consideration should be given to the use of hydrogen as a fuel.

In spite of reservations about the timing and rate of impact of hydrogen as a fuel, there is a need for a well conceived R&D program to study some of the basic problems that constrain its entrance into the economy. Specifically, the following principles should guide the formulation of a U.S. program in support of hydrogen systems:

- o Basic exploratory research should be pursued on innovative concepts for hydrogen production, transmission, storage, and utilization through the laboratory demonstration stages. Such research should be pursued even if near-term market needs cannot be identified.
- o The federal program should include R&D elements designed to create a national data base of sufficient depth and quality that sound evaluations can be made of program alternatives in the future selection of coherent and timely development and demonstration programs.
- o The federal program should defer large-scale system development and demonstration activities aimed at hydrogen production until a market need of significant magnitude is clearly identified and it is established that the timing or risks make it unlikely that the private sector will undertake these R&D phases.
- o The architects of hydrogen R&D programs should remain alert to developments in applications areas that might enhance the need for hydrogen, and thus accelerate consideration of development and demonstration programs for production, transmission, and storage systems.
- o Program priority should be given to exploratory research on concepts that hold promise of significantly reducing hydrogen production costs, particularly for coal/hydrogen systems where the cost reductions could also benefit synthetic fuel costs.
- o Research should be initiated on hydrogen/air fuel-cells suitable for transportation applications to provide an alternative to battery powered automobiles in the event that future hydrocarbon fuel limitations are encountered.
- o In addition to work on hydrogen production concepts, appropriate R&D should also be conducted on potential problems associated with the transmission and storage of hydrogen as a consumer fuel. Particular attention should be given to the identification and resolution of potential safety problems for all phases of the hydrogen chain from

production to consumption. Such studies should be conducted in a timely fashion so as to contribute to the overall evaluation of the feasibility of proposed hydrogen systems.

In constructing an appropriate R&D program, it must be recognized that other nations are also engaged in hydrogen research based upon their perceived possible future needs for non-carbon-sourced hydrogen. These needs may be both earlier and greater than those of the U.S., depending upon each nation's lifestyle and access to natural gas and coal. The present U.S. program accepts the probability that these foreign needs may bring a likelihood of foreign technology leadership, and does not attempt to fully duplicate foreign research efforts. This should continue as the basic U.S. position; however, the U.S. should maintain an R&D program that is sufficiently advanced to enable it to participate in meaningful international technology exchange programs. The research areas in the U.S. program should, however, be those that are clearly applicable to its domestic interests and energy outlook.