PNL--7488-Ver.1.3

DE92 005334

SOLID WASTE PROJECTION MODEL:
DATABASE (VERSION 1.3)

Technical Reference Manual

C. L. Blackburn

November 1991

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EXECUTIVE SUMMARY

The Solid Waste Projection Model (SWPM) system is an analytical tool developed by Pacific Northwest Laboratory (PNL) for Westinghouse Hanford Company (WHC). The SWPM system provides a modeling and analysis environment that supports decisions in the process of evaluating various solid waste management alternatives.

This document, one of a series describing the SWPM system, contains detailed information regarding the software and data structures utilized in developing the SWPM Version 1.3 Database. This document is intended for use by experienced database specialists and supports database maintenance, utility development, and database enhancement.

Those interested in using the SWPM database should refer to the SWPM Database User's Guide. This document is available from either the PNL Project Manager (D. L. Stiles, 509-376-4154) or the WHC Restoration Projects Section Manager (509-376-5568).

CONTENTS

EXECUTIVE SUMMARY	iii
1.0 INTRODUCTION	1.1
2.0 DATABASE SYSTEM REQUIREMENTS AND STRUCTURE	2.1
2.1 SOLID WASTE PROJECTION MODEL DATABASE SYSTEM GOAL	2.1
2.2 HARDWARE REQUIREMENTS	2.1
2.3 SOFTWARE REQUIREMENTS	2.2
2.4 FILE TYPES	2.2
2.5 FILE NAMING AND LOCATION CONVENTIONS	2.4
2.5.1 Report Files, Tables, Procedures	2.4
2.5.2 Data Tables	2.4
2.5.4 FAL Scripts	2.5
2.5.5 Procedure Libraries and Related Files	2.6
2.5.6 Ad Hoc Files	2.6
2.6 DIRECTORY STRUCTURE	2.6
2.7 DATABASE STRUCTURE	2.10
2.8 DATA STRUCTURE DICTIONARY	2.12
3.0 DATABASE PROCESSES AND APPLICATIONS	3.1
3.1 PROCESS DICTIONARY	3.2
APPENDIX A - REQUIRED NETWORK CONFIGURATION	A.1
APPENDIX B - PARADOX DEFAULT SETTINGS	B.1
APPENDIX C - TECHNICAL NOTES	
APPENDIX D - REFERENCE DATA LIBRARY PROCESS	D.1
APPENDIX E - PROCEDURE LIBRARY DICTIONARY	E.1

FIGURES

1.1 The Solid Waste Management System Representation	1.1
1.2 The SWPM System	1.2
1.3 Data Used to Characterize a Waste Management System	1.2
2.1 Primary Processes Performed by the SWPM Database	2.2
2.2 SWPM Forecast Data Entity Relationship Diagram	2.11

TABLES

2.1 SWPMDB Data Tables and Fields	2.13
C9.1 SWPM Database Application Menu Options	C9.3

1.0 INTRODUCTION

The Solid Waste Projection Model (SWPM) system is an analysis tool developed for Westinghouse Hanford Company's (WHC's) Restoration Projects Section by Pacific Northwest Laboratory (PNL)^(a) to assist analysis of complex waste management issues. The SWPM system provides the ability to develop projections of solid waste volumes and characteristics and evaluate alternative waste treatment and disposal strategies.

A generic representation of the system modeled by SWPM is shown in Figure 1.1. Waste is received from waste generating facilities and is distributed to various operations. Operations are defined as either "treatments" or "disposals" and are linked to other operations to represent a given waste management scheme. Each operation has an associated storage option to track waste volumes that arrive in excess of defined capacity.

The SWPM system consists of three modules: the database, the user interface, and the model. Figure 1.2 shows how the components of the system interact.

The SWPM database, which is described in this technical reference manual, performs three important functions for the SWPM system. First, the database provides secure storage for waste volume forecasts and for system characterizations. Second, it writes the Reference Data Library for input to the model. Last, it uses the information to generate data reports for performing studies without the model. Information such as physical attributes of wastes or waste packaging can be summarized using standard data reports. The database reports can also be used to verify or review the information stored in the system.

The database storing information for the SWPM system uses Paradox database software. Data are entered and maintained through menus and custom data entry screens. There are two distinct types of data in the database. As shown in Figure 1.3, volumes and characteristics that describe the waste from the waste generators, as well as the cost, capacity, and flow instructions for the treatment, storage, and disposal (TSD) operations, are maintained.

Figure 1.1. The Solid Waste Management System Representation

(a) The Pacific Northwest Laboratory is operated by the Battelle Memorial Institute for the U.S. Department of Energy under Contract DE ACO6-76RLO 1830.

Figure 1.2. The SWPM System

Figure 1.3. Data Used to Characterize a Waste Management System

The database, with its menu structure and data entry screens, provides the ability to assemble and maintain many different waste volume forecasts and any number of TSD alternatives, and to make large-scale changes to this information.

This *Database Technical Reference Manual* describes Version 1.3 of the SWPM database, discusses the hardware and software requirements necessary to operate the database, and defines the directory and the data structure in which the information is stored. Five additional documents, which provide instructions in the use, maintenance, and application of the SWPM system, complete the set of documentation. These documents are

the *System Overview*, *Database User's Guide*, the *Model User's Guide*, the *Model Technical Reference Manual*, and the *System Administration Manual*. The following is a brief description of each of the six manuals:

- *System Overview* - provides an overview of the SWPM system and an assessment of potential applications
- *Database User's Guide* - provides instructions for data entry, maintenance, and reporting
- *Model User's Guide* - provides instructions for model operation and execution
- *Model Technical Reference Manual* - describes model software and applications
- *Database Technical Reference Manual* - describes database software, utilities, and structure
- *System Administration Manual* - provides instructions for long-term system administration and maintenance.

This *Database Technical Reference Manual* is provided as a reference guide for a knowledgeable database specialist. Chapter 2 of this manual addresses hardware and software requirements and the structure of the SWPM database. Chapter 3 details the essential operations and functions performed by the database and the specific routines, tables, and scripts which must be accessed and maintained to provide continuing database support.

It is important to note that this manual does not contain any user help information, nor does it attempt to assist the analyst in reporting data or in utilizing SWPM data for analyses. The *Database User's Guide* and the *System Overview* will provide the information required for these purposes.

2.0 DATABASE SYSTEM REQUIREMENTS AND STRUCTURE

This chapter provides the database specialist with a description of the SWPM database system and explains the essential structure of the database.

2.1 SOLID WASTE PROJECTION MODEL DATABASE SYSTEM GOAL

The goal of the SWPM database is to provide the environment for collecting and maintaining the data required for input to the SWPM. In addition, the SWPM database provides forecast data summary reports. The primary processes performed by the SWPM database are:

- maintain waste generator data
- maintain TSD data
- maintain model variable dictionary data
- maintain feature codes and descriptions
- produce forecast data summary reports
- produce the reference data library files.

Figure 2.1 shows the primary processes performed by the SWPM database, the flow of information between the processes, and the external sources and destinations for data. The processes shown on this diagram correspond generally to the options available on SWPM database menus.

2.2 HARDWARE REQUIREMENTS

The SWPM database application works on an IBM PC, XT, AT or PS2 microcomputer. At least 640k of random access memory (RAM) is required and 2 to 4 megabytes (MB) of extended or expanded memory are very helpful. A machine with at least an 80386 processor is highly recommended to avoid long waits for certain processing tasks to finish. Some SWPM processes need between 10 and 20 MB of free disk area for work space. This space must be available on the device to which the user's Paradox private directory is assigned. If the SWPM database is to be entirely resident on the user's computer, as much as 15 MB of additional disk space may be taken up by application files.

Access to the network is required, although a user may create a local copy of the database and use a stand-alone version of Paradox. Appendix A includes information about network connections needed for access to SWPM data.

Figure 2.1. Primary Processes Performed by the SWPM Database

2.3 SOFTWARE REQUIREMENTS

The SWPM database application runs under DOS Version 3.2 or higher. The application requires Version 3.5 or later of the Paradox relational database management system. Paradox controls the storage and retrieval of information on the computer and provides facilities used by the database developer to create menus, forms, and reports. Certain changes to default parameter settings for the Paradox installation are required. See Appendix B.

If the network installation of Paradox 3.5 is to be used, access to the network server containing the software is required. In addition, the user must be authorized by the owner of the Paradox Multi-pack to operate Paradox under the network license. See Appendix A for information about the server connection required to access SWPM data, application software, and Paradox.

2.4 FILE TYPES

Several types of files are used throughout the SWPM database. File types are identified by the file extension, a 1 to 3-character suffix appended to the file name. Listed below are descriptions of the types of files used by the SWPM database:

- .BAT** DOS batch file - Batch files are used to execute a series of DOS commands.
- .DB** Paradox database table - These are the files in which data are stored.
- .Fnn** Paradox form - Forms are used to view and maintain data. They have the same file name as the related database table. Forms have a file name extension of either ".F" (for the default form) or ".Fnn", where 'nn' is a form number from 1 to 14. As a result of this convention, there can be no more than 15 forms for each table.
- .LIB** Paradox library - Libraries contain compiled versions of scripts. Each library may have one or more compiled scripts.
- .PX** Paradox primary index - If a table has key fields, a primary index file with the same name as the table is created and maintained automatically.
- .Rnn** Paradox report specification - Report specifications are used to display data to a printer, screen, or file. Each has the same file name as the related database table. Reports have a file name extension of either ".R" (for the default report) or ".Rnn", where 'nn' is a report number from 1 to 14. As a result of this convention, the number of reports associated with one table is limited to 15.
- .RPF** Forecast data file produced by the Reference Data Library (RDL) process. These files contain data extracted from the database, reformatted to a form acceptable for input to the model and stored as ASCII text.
- .RPS** Similar to .RPF files, except contains scenario data.
- .RPT** Report text files - SWPM database reports are routinely written to this type of file as well as sent to the printer. Report text files are readable by a text editor and can be printed using the DOS PRINT or COPY command.
- .SET** Paradox image settings - These control numeric precision, column widths, table lengths, and other table or field defaults. They have the same file name as their corresponding data table. There is a maximum of 1 setting file for each data table.
- .SC** Paradox script - A script is similar to a program or subroutine. Script files contain either lines of Paradox Application Language (PAL) code or saved queries.
- .TXT** Plain text files - This type of file is created by certain data conversion processes which may later import these text files into Paradox data tables. Plain text files are readable by any text editor.
- .VAL** Paradox validity check - Validity check files contain information used to set maximum, minimum, and default values for a field. They also determine if the value for a field must exist elsewhere in the database before it may be used. They have the same file name as their corresponding data table.

2.5 FILE NAMING AND LOCATION CONVENTIONS

2.5.1 Report Files, Tables, Procedures

Report scripts: PAL\Rnnn.SC, where 'nnn' is report ID number assigned when the report is added to the Report Manager table

Report tables: WORK\Rnnn.DB

Report specifications: WORK\Rnnn.Rxx, where 'xx' is the Paradox report number

Report queries: Q\Rnnn_x.SC, where 'x' indicates order of use

Note: Some reports use common queries. In such cases, the query is named for the first report to be implemented using the query. Other queries may have compound names indicating applicability to more than one report process.

Report text files: R\Rnnn.RPT

Example: For report R312, the following file names apply -

PAL\R312.SC - script to create the report data

WORK\R312.DB - table in which report data is placed

WORK\R312.R - file containing Paradox report specification

Q\R312_2.SC - one of the queries used to extract data

R\R312.RPT - text of the report

2.5.2 Data Tables

Forecast data: D\'name'.DB, where 'name' is the entity to which the data applies

Example: D\FOREVOL.DB - table containing forecast volumes

Temporary data entry: WORK\E\'name'.DB, where 'name' is defined as for forecast data above

Example: WORK\E\FOREVOL.DB - table to which forevol data are entered for validation prior to being automatically added to d\FOREVOL.DB

Lookup, validation data: V\$\'name'.DB, where 'name' is the class of item to be validated using the contents of this table

Example: V\$WCLASS.DB - table used to validate waste class usage throughout the application; also controls order of appearance on forms and reports

Other data: 'dir\'\'name'.db, where 'dir' is the directory containing the table named by 'name'

Examples: ACTION\ACTION.DB - table containing action item list for project team members

D\NOTEPAD.DB - table containing notes about items and issues identified during data entry

2.5.3 Queries

General purpose: Q\'name'.SC - where name usually relates to the process within which the query is used

Examples: Q\R310_4.SC - the fourth query used in the process to create report R310

Q\VOLSUM1.SC - a query used in creating volume summary information

Up/Download QA: QA/Q\'name'.SC - a query used to perform quality assurance testing on data uploaded to the network

Example: QA/Q\MIS_FORE.SC - a query used to detect missing WG forecasts in the uploaded FOREVOL table

2.5.4 PAL Scripts

General purpose: PAL\'name'.SC - where 'name' relates to the process performed by the script

Examples: PAL\HCD.SC - the script that defines actions to be taken while entering HCD data

PAL\R309.SC - the script that performs data manipulation required to produce report R309

Library procedures: UTIL\'name'.SC, PAL\'name'.SC, or 'dir\'\'name'.SC - where 'name' is usually similar to the function defined by the script and 'dir' is a special purpose directory other than the UTIL or PAL directories

Examples: UTIL\RPTMGR.SC - the script that defines the Report Manager procedure, RPTMGR(), that is compiled and stored in library LIB\UTIL.LIB

PAL\FEAEDIT.SC - the script containing several procedure definitions that are compiled and written to library LIB\FEAEDIT.LIB

MENU\MENU.SC - the script defining the table-driven menu procedure that is compiled and written to LIB\UTIL.LIB

Tools: TOOLS\'name'.SC - where 'name' is the name of a development software tool created for some specific task

Example: TOOLS\RPTSUM.SC - the script that will create report totals for one or more columns during the development of a report

2.5.5 Procedure Libraries and Related Files

Libraries: LIB\name'.LIB - where 'name' is the name assigned to the library of procedures

Examples: LIB\UTIL.LIB - a library containing a number of miscellaneous procedures

LIB\FORDEDE.LIB - a library containing data entry procedures for most of the forecast data tables

Procedure source: See Section 2.5.4 - Library procedures above for conventions and examples

Compile scripts: LIB\name'.SC - where 'name' is the name of the library to which procedures compiled by this script will be written

Example: LIB\UTIL.SC - a script that deletes the existing LIB\UTIL.LIB, compiles all utility procedures and writes them into a newly created LIB\UTIL.LIB

2.5.6 Ad Hoc Files

All tables, queries and related files are placed in subdirectories of ADHOC\ . These subdirectories are generally named with the requester's initials and sequence number such as ADHOC\PSK001. Explanatory notes for ad hoc tasks are kept in the project files.

2.6 DIRECTORY STRUCTURE

The SWPM database directory structure is designed to meet a number objectives:

- to separate data and software
- to avoid, as much as possible, hard coding disk drive designations and application directory names in programs, so that the application is relatively portable to other network drives or workstations
- to provide a coherent, easily understood structure that will simplify maintenance, administration and further development
- to facilitate uploading to and downloading from a network reference database using sound quality assurance (QA) procedures.

The general structure was adapted from a column by Brian J. Smith in "Data Based Advisor" magazine. Certain additions were made to meet SWPM requirements and to further extend the method of disk space organization advocated in the column.

A diagram of the directory structure follows.

SWPM DATABASE DIRECTORY STRUCTURE

The following is a description of the directories and their contents.

\\SWPMDB91	The SWPMDB91 directory contains the application startup script and, occasionally, other files. No permanent data or program storage is to be done in this directory.
\\SWPMDB91\\D	The D directory contains data tables and related files reflecting the FY 1991 forecast.
\\SWPMDB91\\DOC	The SWPMDB91 DOC directory should only contain subdirectories.
\\SWPMDB91\\DOC\\DIAGRAMS	Diagrams appearing in the SWPM database documentation are stored here. Files in this subdirectory with ".GEM" as file name extensions were created with Gem Draw Plus. Diagrams created with WordPerfect use ".DOC" for extensions.
\\SWPMDB91\\DOC\\MEMO	Correspondence such as memos, DSIs, and other related documents are found in this subdirectory.
\\SWPMDB91\\DOC\\TABLES	This directory contains tables, forms, reports, and scripts for collecting information about tables and fields used in the database. Table 2.1 of this technical reference is created from the Paradox tables and other objects found here.
\\SWPMDB91\\DOC\\TECH	This directory contains technical documentation describing processes, database structures, and other matters of interest to the database designer, administrator, and programmer.
\\SWPMDB91\\DOC\\USER	Database user documentation files are stored in this directory.
\\SWPMDB91\\DTSD	Paradox tables and related files containing TSD data are kept in this directory.
\\SWPMDB91\\DV	This directory contains tables, scripts, and other files required for data validation reporting. These reports are used to verify data entry and to provide feedback to organizations that submitted forecast information to the SWPM project. (See Appendix C for technical notes on data validation reporting.)
\\SWPMDB91\\LIB	The SWPMDB91\\LIB directory contains procedure libraries and the necessary scripts to create and compile the libraries. The contents of the libraries are defined when certain PAL scripts are executed and written to the libraries as compiled programs. (Each individual procedure is documented in Appendix E.)

\SWPMDB91\MENU	This directory holds the menu table and related files and scripts that define the menu structure and functions available in SWPMDB91. Using this feature, menu maintenance generally involves making simple changes to a table rather than modifying program code. (See Appendix C for technical notes on the menu system.)
\SWPMDB91\MVD	The SWPMDB91\MVD directory contains tables and related files that hold the model variable dictionary.
\SWPMDB91\PAL	Scripts of PAL code are kept here. These scripts are for purposes that include data manipulation prior to reporting, source code for compiled procedures, and other application support.
\SWPMDB91\Q	This directory contains query scripts used in SWPM database processing. Generally, queries are called by PAL scripts stored in \SWPMDB91\PAL or by library procedures.
\SWPMDB91\QA	This is the parent directory of subdirectories containing tables and scripts used in quality assurance processes that are run against data uploaded to the network. (See Appendix C, Section 7, for technical notes on the upload/download processing and related QA.)
\SWPMDB91\R	All report text files are stored here. Most processes that generate reports in this application store them as plain text in this directory in addition to or instead of sending the reports to the printer. Also, data and other files supporting the Report Manager function are stored located in this directory.
\SWPMDB91\RDL	Files generated by the Reference Data Library (RDL) process are stored here.
\SWPMDB91\UTIL	This directory holds a number of separate procedure scripts which are compiled into the UTIL library by another script, UTIL.SC, located in the \SWPMDB91\LIB directory. UTIL library procedures are used to perform such chores as managing report generation, moving field contents, rounding numbers, and calculating the difference between times. These procedures may be called by scripts, other procedures, or from menus.
\SWPMDB91\V	The SWPMDB91\V directory contains lookup tables and other files that define data validity checks to be performed during data entry and update. The lookup tables are also used to control report order and to provide alternative or expanded names for terminology used in the database.

\\SWPMDB91\\WORK	This directory contains tables that receive data created during processing. Most standard SWPM database reports require extraction and manipulation of data that are then passed into work tables located here. Reports are generated from these work tables. Intermediate results of processes are also stored in this directory, although tables created this way may be deleted when the process finishes.
-------------------------	---

The following directories contain files that are used in conjunction with the SWPM database but are not actually part of the application:

\\SWPMDB91\\ACTION	The action item list display, edit, and report functions use data and other objects located in this directory. (See Appendix C for technical notes on the action item list.)
\\SWPMDB91\\ADHOC	Scripts, tables and spreadsheet files created in response to special requests are kept here. When the work is complete, all files created for a particular ad hoc task are moved to subdirectories of this directory for safekeeping.
\\SWPMDB91\\TOOLS	A number of scripts for use by developers are kept here. These programs are not application specific. They serve to assist in such tasks as the creation and maintenance of reports and forms. (See Appendix C, Section 11, for technical notes on tools.)

2.7 DATABASE STRUCTURE

The database structure for the SWPM database is an evolution of earlier designs. The structure is based on requirements posed by the sponsor, the needs of the model, the ability of the waste generator organizations to provide the requested data, and limitations imposed by database management systems. The basic forecast structure is the 19 data tables shown on the entity-relationship (E-R) diagram in Figure 2.2. This diagram depicts the types of data in the system (entities), the attributes of the entities, and the relationship between the types of data. The E-R diagram presented here displays only the major forecast tables. To avoid a cluttered diagram, some minor tables are only documented in the data dictionary. The following conventions are used on the diagrams:

- Boxes represent entities. For instance, **WG** (Waste Generator) is the name of an entity on the E-R diagram. Entities on the diagram become tables in the implemented database.
- Names within a box are the attributes of an entity. **WG Abbrev** is an attribute of the **WG** entity. Attributes define the columns (also referred to as fields) of a database table.
- Bullets in front of attribute names indicate that the field is the key for that table. When more than one field is marked, the designated fields form a compound key. Keys are unique within each table and establish the default order in which rows are displayed in the Paradox work space.

Figure 2.2. SWPM Forecast Data Entity Relationship Diagram

- The lines between entities indicate relationships between the entities. The line connecting WG and Forecast entities shows that a WG produces one or more Forecasts. The connecting lines also show that each Forecast relates to one or more rows in the FOREVOL table. In the database implementation, the relationships are established in queries, multi-table reports and forms, and within procedures programmed in PAL.
- Numbers in brackets following each entity name are the approximate number of rows of data to be found in that table of the database. There is no enforcement of row limitations in the design. Paradox table sizes are limited only by disk space.

2.8 DATA STRUCTURE DICTIONARY

The data structure dictionary in Table 2.1 provides detailed information about the database tables and fields. It lists all tables, the row structure of each table, and includes descriptions of each table and field. All tables in Figure 2.2 are shown here, along with supporting tables that are excluded from the figure for clarity.

Table 2.1. SWPMDB Data Tables and Fields

ACTION\ACTION: This table contains the current list of action items assigned to various members of a work group.

1 ASSIGNED TO	A3	Initials of person to whom this item is assigned.
2 PRIORITY	N	Priority number assigned to this item for this assigned person.
3 ACTION ITEM	A80	Description of action item.
4 DUE DATE	D	Date by which item is to be accomplished.
5 COMPLETION DATE	D	Date on which item is actually accomplished.

ACTION\ACTRPT: This table receives the action items selected for inclusion on a report.

1 ASSIGNED TO	A3	Initials of person to whom this item is assigned.
2 PRIORITY	N	Priority number assigned to this item for this assigned person.
3 ACTION ITEM	A80	Description of action item.
4 DUE DATE	D	Date by which item is to be accomplished.
5 COMPLETION DATE	D	Date on which item is actually accomplished.

ACTION\HISTORY: This table contains completed action items that have been moved here from ACTION\ACTION.

1 ASSIGNED TO	A3	Initials of person to whom this item is assigned.
2 PRIORITY	N	Priority number assigned to this item for this assigned person.
3 ACTION ITEM	A80	Description of action item.
4 DUE DATE	D	Date by which item is to be accomplished.
5 COMPLETION DATE	D	Date on which item is actually accomplished.

Table 2.1. (Contd)

DOC/TABLES/\$VALCHK: This table contains the list of validity checks that may be defined for Paradox table columns and the report order for documentation.

1 VALCHK TYPE	A15	The type of validity check.
2 ORDER	N	The order in which the validity check appears on reports generated for documentation.

DOC/TABLES/TAB: This table contains the list of all tables in the SWPM database.

1 TABLE NAME	A30	The name of the table, including its path relative to the SWPM directory.
2 DESCRIPTION	A160	The description of this table.

DOC/TABLES/TABFLD: This table contains the list of fields in each table of the SWPM database.

1 TABLE NAME	A30	The name of the table that contains this field.
2 FIELD NUMBER	S	The order in which this field appears in the table structure.
3 FIELD NAME	A25	The name of the field.
4 FIELD TYPE	A5	The Paradox field type (N, S, D, A'nn', etc.)
5 DESCRIPTION	A160	The description of this field.
6 LOWVALUE	A20	The minimum value that may be entered into this field.
7 HIGHVALUE	A20	The maximum value that may be entered into this field.
8 DEFAULT	A20	The value that will be entered automatically, if no explicit entry is made by the user.
9 TABLELOOKUP	A20	The name of a table that contains all values that are valid for this field.
10 PICTURE	A20	The template that controls the type and format of data entered into this field.
11 REQUIRED	A3	Contains "Yes" if the user must enter a value for this field.

Table 2.1. (Contd)

DTSD\DIST_F: This table holds the waste generator fractions. Each record defines an operation and the fraction it receives from a waste generator.

1	WG ABBREV	A12	The abbreviation for a waste generator name.
2	TSD WC ABBREV	A12	The abbreviation for a treatment, storage and disposal (TSD) waste class name.
3	OPER ABBREV	A12	The abbreviation for an operation name.
4	DIST_F	N	The decimal fraction of waste volume from the specified waste generator that is provided to the specified operation.
5	DIST REF	A12	The reference material used to describe the values for this record.

DTSD\OPER: This table is a list of operations recognized by SWPM. Included are names and cost data for all valid operations.

1	OPER ABBREV	A12	The abbreviation for an operation name.
2	TSD WC ABBREV	A12	The abbreviation for a treatment, storage and disposal (TSD) waste class name.
3	OPER NAME	A30	The name of operation.
4	TRT/DSP FLAG	A3	A flag indicating whether the specified operation is a treatment or disposal.
5	OP_CAT_ABBREV	A16	The abbreviation for an operation category.
6	OPER COST	N	The cost, in dollars per cubic feet, for the specified operation.
7	TRT RATIO	N	The volume reduction (or increase) ration for waste flowing into an operation versus waste leaving an operation.
8	STOR COST	N	The cost for storage, in dollars per cubic foot, associated with an operation.
9	OPER REF	A12	The reference material used to describe the values for this record.

Table 2.1. (Contd)

DTSD\OPERCAP: This table contains the capacities for operations. Each record contains data for one operation for one year. All valid operations have at least one record.

1	OPER_ABBREV	A12	The abbreviation for an operation name.
2	WC	A12	TSD waste class abbreviation.
3	YEAR	N	Year of operation.
4	CAPACITY	N	Annual volume capacity that can be processed by the treatment or disposal operation.
5	CAP_REF	A12	The reference material used to describe the values for this record.

DTSD\OPERFLOW: This table contains TSD operations for each waste class and the next operation(s) in the process.

1	OPER ABBREV	A12	The abbreviation for an operation name.
2	TSD WC ABBREV	A12	The abbreviation for a treatment, storage and disposal (TSD) waste class name.
3	NEXT OPER ABBREV	A12	The abbreviation for the next operation to be performed.
4	NEXT TSD WC ABBREV	A12	The abbreviation for the name of the TSD waste class resulting from this operation.
5	FLOW FRACTION	N	The fraction of waste flowing to the next operation.
6	FLOW REF	A12	The reference material used to describe the values for this record.

DTSD\OPERWC: This table contains operation names and the TSD waste classes associated with each operation.

1	OPER ABBREV	A12	The abbreviation for an operation name.
2	TSD WC ABBREV	A12	The abbreviation for a treatment, storage and disposal (TSD) waste class name.
3	OPER NAME	A30	The name of operation.

Table 2.1. (Contd)

4 TRT/DSP FLAG	A3	A flag indicating whether the specified operation is a treatment or disposal.
5 OP_CAT_ABBREV	A16	The abbreviation for an operation category.
6 OPER COST	N	The cost, in dollars per cubic feet, for the specified operation.
7 TRT RATIO	N	The volume reduction (or increase) ration for waste flowing into an operation versus waste leaving an operation.
8 STOR COST	N	The cost for storage, in dollars per cubic foot, associated with an operation.
9 OPER REF	A12	The reference material used to describe the values for this record.

DV\#CONT: This table contains a list of all possible PCD/container combinations for use in data verification reporting.

1 PCD ABBREV	A14	The abbreviation for a physical content descriptor.
2 CONT ABBREV	A14	The abbreviation for a container name.

DV\#HCD: This table contains a list of all possible PCD/HCD combinations for use in data verification reporting.

1 PCD ABBREV	A14	The abbreviation for a physical content descriptor.
2 HCD ABBREV	A14	The abbreviation for a hazardous content descriptor.

DV\#PCD: This table contains a list of all possible PCD/waste class combinations for use in data verification reporting.

1 PCD ABBREV	A12	The abbreviation for a physical content descriptor.
2 WCLASS ABBREV	A12	The abbreviation for a waste class name.

DV\#WEIGHT: This table contains a list of all possible weight collection year/waste class combinations for use in data verification reporting.

1 WCLASS ABBREV	A14	The abbreviation for a waste class name.
2 YEAR	A14	The year forecasted.

Table 2.1. (Contd)

DV\PA1: This table receives volume data for a selected WG in the course of producing data verification reports. The volume report is then produced from this table.

1	WCLASS ABBREV A14		The abbreviation for a waste class name.
2	WG ABBREV	A25	The abbreviation for a waste generator name.
3	1992	N	Volume forecast for the year 1992.
4	1993	N	Volume forecast for the year 1993.
5	1994	N	Volume forecast for the year 1994.
6	1995	N	Volume forecast for the year 1995.
7	1996	N	Volume forecast for the year 1996.
8	1997	N	Volume forecast for the year 1997.
9	1998	N	Volume forecast for the year 1998.
10	1999	N	Volume forecast for the year 1999.
11	2000	N	Volume forecast for the year 2000.
12	2001	N	Volume forecast for the year 2001.
13	2002	N	Volume forecast for the year 2002.
14	2003	N	Volume forecast for the year 2003.
15	2004	N	Volume forecast for the year 2004.
16	2005	N	Volume forecast for the year 2005.
17	2006	N	Volume forecast for the year 2006.
18	2007	N	Volume forecast for the year 2007.
19	2008	N	Volume forecast for the year 2008.
20	2009	N	Volume forecast for the year 2009.
21	2010	N	Volume forecast for the year 2010.

Table 2.1. (Contd)

22	2011	N	Volume forecast for the year 2011.
23	2012	N	Volume forecast for the year 2012.
24	2013	N	Volume forecast for the year 2013.
25	2014	N	Volume forecast for the year 2014.
26	2015	N	Volume forecast for the year 2015.
27	2016	N	Volume forecast for the year 2016.
28	2017	N	Volume forecast for the year 2017.
29	2018	N	Volume forecast for the year 2018.
30	2019	N	Volume forecast for the year 2019.
31	2020	N	Volume forecast for the year 2020.
32	2021	N	Volume forecast for the year 2021.
33	HELD	N	Volume forecast for held waste.
34	TOTAL	N	Volume forecast for the 30-year period plus held waste.

DV\PA2: This table receives PCD and container data for a selected WG in the course of producing data verification reports. A report is then produced from this table.

1	PERCENT	N	Fraction of a waste class characterized by this PCD.
2	PCD ABBREV	A14	The abbreviation for a physical content descriptor (PCD).
3	1000-5000 BX	N	Fraction of the PCD in this container type.
4	128-500 BX	N	Fraction of the PCD in this container type.
5	4X4X8 BX	N	Fraction of the PCD in this container type.
6	500-1000 BX	N	Fraction of the PCD in this container type.
7	55G DRUM	N	Fraction of the PCD in this container type.
8	< 128 BX	N	Fraction of the PCD in this container type.

Table 2.1. (Contd)

9 DUMP TRUCK	N	Fraction of the PCD in this container type.
10 ODD DRUM	N	Fraction of the PCD in this container type.
11 OTHER	N	Fraction of the PCD in this container type.
12 PLASTIC WRAP	N	Fraction of the PCD in this container type.
13 SEALED EQUIP	N	Fraction of the PCD in this container type.
14 TANKER TRUCK	N	Fraction of the PCD in this container type.
15 TRUPACT BX	N	Fraction of the PCD in this container type.
16 TOTAL	N	Total of all container fractions for this PCD (must equal 1).

DVPA3: This table receives HCD data for a selected WG in the course of producing data verification reports. Reports by waste group are then produced from this table.

1 PCD ABBREV	A14	The abbreviation for a physical content descriptor.
2 ACIDIC	N	Fraction of the PCD contaminated with this HCD.
3 ASBESTOS	N	Fraction of the PCD contaminated with this HCD.
4 CAUSTIC	N	Fraction of the PCD contaminated with this HCD.
5 COMBUSTIBLE	N	Fraction of the PCD contaminated with this HCD.
6 EXPLOSIVE	N	Fraction of the PCD contaminated with this HCD.
7 FLAMMABLE	N	Fraction of the PCD contaminated with this HCD.
8 HEAVY METALS	N	Fraction of the PCD contaminated with this HCD.
9 IRRITATIVE	N	Fraction of the PCD contaminated with this HCD.
10 LISTED RCRA	N	Fraction of the PCD contaminated with this HCD.
11 ORGANIC MATLS	N	Fraction of the PCD contaminated with this HCD.
12 OTHER CORR	N	Fraction of the PCD contaminated with this HCD.

Table 2.1. (Contd)

13 OTHER IGN	N	Fraction of the PCD contaminated with this HCD.
14 OTHER REACTIVE	N	Fraction of the PCD contaminated with this HCD.
15 OTHER TOXIC	N	Fraction of the PCD contaminated with this HCD.
16 OXIDIZER	N	Fraction of the PCD contaminated with this HCD.
17 PCB < 50 PPM	N	Fraction of the PCD contaminated with this HCD.
18 PCB > 50, < 500	N	Fraction of the PCD contaminated with this HCD.
19 PCB > 500	N	Fraction of the PCD contaminated with this HCD.
20 TOXIC MATLS	N	Fraction of the PCD contaminated with this HCD.
21 TOTAL	N	Total of all HCD fractions for this PCD (must equal 1).

DV\PA4: This table receives weight data for a given WG in the course of producing data verification reports. Reports by waste group are then produced from this table.

1 WCLASS ABBREV	A14	The abbreviation for a waste class name.
2 1992	N	Weight of waste forecasted for 1992.
3 1993	N	Weight of waste forecasted for 1993.
4 1994	N	Weight of waste forecasted for 1994.
5 1995	N	Weight of waste forecasted for 1995.
6 1996	N	Weight of waste forecasted for 1996.
7 1997-2021	N	Average annual weight of waste forecasted for 1997-2021.
8 HELD	N	Weight of held waste forecasted.

Table 2.1. (Contd)

D\CONT: This table holds the volume percentages applicable to each container type for the physical contents of each waste class produced by waste generators.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
2	SCENARIO ABBREV	A14	The abbreviation for a scenario name.
3	WCLASS ABBREV	A14	The abbreviation for a waste class name.
4	PCD ABBREV	A14	The abbreviation for a physical content descriptor.
5	CONT ABBREV	A14	The abbreviation for a container name.
6	PERCENT	N	Decimal fraction of waste class/PCD combination packaged in this container type.

D\FORECAST: This table identifies all available volume forecasts in the database.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
2	SCENARIO ABBREV	A14	The abbreviation for a scenario name.

D\FOREVOL: This table contains forecast volumes by year and waste class for each waste generator.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
2	SCENARIO ABBREV	A14	The abbreviation for a scenario name.
3	WCLASS ABBREV	A14	The abbreviation for a waste class name.
4	YR	A12	The year forecasted.
5	VOL	N	The volume of waste forecasted.

D\HCD: This table holds the hazardous content percentages for the physical contents of each waste class produced by waste generators.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
---	-----------	-----	--

Table 2.1. (Contd)

2	SCENARIO ABBREV	A14	The abbreviation for a scenario name.
3	WCLASS ABBREV	A14	The abbreviation for a waste class name.
4	PCD ABBREV	A14	The abbreviation for a physical content descriptor.
5	HCD ABBREV	A14	The abbreviation for a hazardous content descriptor.
6	PERCENT	N	Decimal fraction of a waste class/pcd combination represented by this hazardous content descriptor.

D\NOTEPAD: This table contains notes made using the SWPM database application notepad function.

1	TABLE NAME	A20	The table name currently active (view or edit mode) when the note was taken.
2	FIELD NAME	A20	The field name in which the cursor was positioned when the note was taken.
3	FIELD CONTENT	A80	The content of the current field.
4	NOTES	A160	The text of the note.
5	NOTE DATE	D	The system supplied date at the time the note was taken.
6	USER NAME	A20	The Paradox user name of the person taking the note.

D\NOTERES: This table contains notes originally placed in D\NOTEPAD and removed after each item was resolved.

1	TABLE NAME	A20	The table name currently active (view or edit mode) when the note was taken.
2	FIELD NAME	A20	The field name in which the cursor was positioned when the note was taken.
3	FIELD CONTENT	A80	The content of the current field.
4	NOTES	A160	The text of the note.
5	NOTE DATE	D	The system supplied date at the time the note was taken.

Table 2.1. (Contd)

6 USER NAME	A20	The Paradox user name of the person taking the note.
7 RESOLUTION DATE	D	The date on which action was taken or completed that resolved the notepad item.
8 RESOLVING ACTION	A160	A description of the action taken.
9 POSTED BY	A20	The name of the user posting the resolution to the notepad item.

D\PCD: This table holds the volume percentages of physical contents of each waste class produced by waste generators.

1 VG ABBREV	A14	The abbreviation for a waste generator name.
2 SCENARIO ABBREV	A14	The abbreviation for a scenario name.
3 PCD ABBREV	A14	The abbreviation for a physical content descriptor.
4 WCLASS ABBREV	A14	The abbreviation for a waste class name.
5 PERCENT	N	Decimal fraction of a waste class represented by this physical content descriptor.

D\SCENARIO: This table contains the waste generator scenarios defined in the database.

1 SCENARIO ABBREV	A14	The abbreviation for a scenario name.
2 SCENARIO NAME	A32	The name of the scenario.
3 SCENARIO BASE YR	A4	The base year for the scenario.
4 SCENARIO DESCRIPTION	A150	The description of the scenario.

D\UPDNLOG: This table contains a log of all upload and download activity between the network database and users' local copies of the data.

1 LOG DATE	D	The system supplied date when the log entry was made.
2 LOG TIME	A10	The system supplied time when the log entry was made.

Table 2.1. (Contd)

3	USER	A20	The Paradox user name of the person performing the upload or download.
4	ACTION	A40	The nature of the action - upload, download, etc.

D\WEIGHT: This table contains weight of forecasted waste volumes for waste generators by year and waste class.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
2	SCENARIO ABBREV	A14	The abbreviation for a scenario name.
3	WCLASS ABBREV	A14	The abbreviation for a waste class name.
4	YEAR	A14	The year being forecasted.
5	WEIGHT	N	Weight in pounds.

D\WG: This table contains the list of all valid waste generators, their full names, classification and group affiliation.

1	WG ABBREV	A14	The abbreviation for a waste generator name.
2	WG NAME	A30	The full waste generator name.
3	WGCLASS ABBREV	A14	The abbreviation for the class to which this waste generator belongs.
4	RECEIVED DATE	D	The date on which the forecast was received from the waste generator.
5	COMPLETED DATE	D	The date when data entry for the forecast was finished.
6	WG GROUP NAME	A16	The name of the WG group to which this waste generator belongs.

MENUMENUOPT: This table contains data that determine the menu structure of the SWPM database application.

1	MENU ABBREV	A10	The name of the menu group to which this menu option belongs.
2	MENU OPT #	N	A number that established the order in which this item appears in its group.

Table 2.1. (Contd)

3 MENU OPT	A15	The name for this option that will appear as a menu selection.
4 MENU DESC	A70	The description of this option to appear on the second line of the menu bar.
5 MENU PROC	A80	The action to be taken - proc, script, message, etc - when this option is chosen.
6 MENU REPORT ORDER	N	The order of appearance of this menu group - the same for all options in a group.

MVD\SUBSDICT: This table contains the definitions of model subscripts. Subscripts are parameters that are passed to a variable.

1 SUBS_ABBREV	A12	The abbreviation of subscript name.
2 SUBS_NAME	A30	The full name of a subscript.
3 SUBS_SEQ	N	The sequence number of this subscript for the variable to which it applies.
4 SUBS_TYPE	A10	The data type of the subscript.
5 SUBS_UNITS	A10	The unit of measure in which the value of this subscript is recorded.
6 SUBS_MIN_VALUE	N	The minimum value which may be assigned to the subscript. This field is defined for continuous value subscripts.
7 SUBS_MAX_VALUE	N	The maximum value which may be assigned to the subscript. This field is defined for continuous value subscripts.
8 SUBS_COMMENT	A255	The description of this subscript.

MVD\VALDICT: This table contains the values that a subscript may have. This is only used for subscripts with discrete (as opposed to continuous) values.

1 SUBS_ABBREV	A12	The abbreviation of subscript name.
2 SUBS_VALUE_SHORT	A12	An abbreviated value which the subscript may contain.
3 SUBS_VALUE_LONG	A40	The full-length value which the subscript may contain.
4 SUBS_VALUE_DESC	A255	A description of this possible subscript value.

Table 2.1. (Contd)

MVD\VARDICT: This table contains the definitions of variables used by the model. Variables represent a type of information, such as waste volumes or abbreviation lists.

1	VAR_ABBREV	A20	The abbreviation for a variable name.
2	VAR_NAME	A50	The full name of the variable.
3	VAR_TYPE	A10	The data type for the specified variable.
4	RPF_TYPE	A10	The data type of the field which should be passed to the reference data library files.
5	VAR_RPF_USE	A1	A flag indicating the type of variable (waste generator or treatment).
6	VAR_DICT_USE	A1	A flag indicating whether the variable should be output to the RDL. (Some variables are for comment only).
7	VAR_PARAMS	A40	Parameters associated with this variable.
8	VAR_SPARSE_ARRAY	A1	A flag indicating if the variable is sparsely populated.
9	VAR_DEFAULT_VALUE	A25	The default value for the variable.
10	VAR_COMMENT	A255	The description of the variable.
11	VAR_UPDATE_DATE	D	The date when this variable was last updated.
12	VAR_UPDATE_WHO	A3	The initials of the person who performed the last update.
13	VAR_DELETE_DATE	D	The date when this variable was deleted.
14	VAR_DELETE_WHO	A3	The initials of the person who deleted this variable.
15	VAR_DISP_SEQ	N	The order in which this variable appears in reports.

MVD\VARSUBS: This table is used to link variables and subscripts in many-to-many relationships.

1	VAR_ABBREV	A20	The abbreviation for a variable name.
2	VAR_SUBS_SEQ	N	The sequence number assigned to the variable-subscript relationship to reflect the order of the subscript list.
3	SUBS_ABBREV	A12	The abbreviation of the subscript name.

Table 2.1. (Contd)

R\SWPMRPT: This table holds a list of all available database reports.

1 RPT ID	A5	The identifier assigned to this report format.
2 RPT ABBREV	A8	The table name from which the report will be generated.
3 REPORT NUMBER	A1	The report number given to this report specification (R, 1, 2, 3, etc.)
4 RPT NAME	A45	The title of this report - a condensed version of the text of the first title line.
5 RPT SCRIPT	A8	The script or procedure name to be invoked to create the report.
6 COMMENTS	A65	Comments about the report content or process.
7 FORMAT NOTES	A65	Notes concerning the format of the report.
8 DATE MODIFIED	D	The last date on which the report format was modified - manually maintained.
9 DATE LAST RUN	D	The last date on which the report was run - automatically maintained.
10 RUN TIME	A10	The time in minutes and tenths of minutes that the report process took when last run.
11 TABLE LOCATION	A8	The subdirectory in which the report table named in Rpt Abbrev is found - default is WORK\.
12 RPT FILE SIZE	N	The amount of space in bytes that DOS has allocated to the file containing the report output.

V\SCONT: This lookup table holds the information about each valid container type.

1 CONT ABBREV	A14	The abbreviation for a container name.
2 CONT NAME	A32	The full container name.
3 CONT REPORT ORDER	N	The order in which data for this container type is to appear on reports.
4 CONT FORM ORDER	N	The order in which data for this container is to appear or be entered on forms.
5 CONT GROUP ABBREV	A14	The name of the container group to which this container belongs.

Table 2.1. (Contd)

6 CONT DESCRIPTION A255 The description of this container type.

V\CONTGRP: This lookup table defines the available groups of containers.

1 CONT GROUP ABBREV	A14	The name of the container group. This is the same as the container abbreviation for containers that are by themselves in a group.
2 CONT GROUP NAME	A32	The long form of the container group name.
3 CONT GROUP RPT ORDER	N	The order in which this group appears with respect to other groups on a report.

V\SDICT: This table contains the SWPM project dictionary; a list of acronyms, the terms they stand for and their definitions.

1 GROUP	A30	The group to which this dictionary entry belongs.
2 ACRONYM	A16	The acronym defined in this dictionary entry.
3 TERM	A40	The term for which the acronym stands.
4 DEFINITION	A255	The definition or explanation of the acronym entry.
5 REFERENCE	A20	The source of the definition.

V\SDICTGRP: This lookup table contains the list of valid dictionary groups.

1 GROUP	A30	The name of a group of related dictionary entries.
2 GROUP REPORT ORDER	N	The order in which the group is to appear on reports.

V\SHCD: This lookup table contains information about each valid hazardous content descriptor.

1 HCD ABBREV	A14	The abbreviation for a hazardous content descriptor.
2 HCD NAME	A32	The full name of the hazardous content descriptor.
3 HCD REPORT ORDER	N	The order in which the data for this HCD is to appear on reports.

Table 2.1. (Contd)

4	HCD FORM ORDER	N	The order in which the data for this HCD is to appear or be entered on forms.
5	HCD GROUP ABBREV	A14	The name of the HCD group to which this HCD belongs.
6	HCD DESCRIPTION	A255	The description of this HCD.

V\$HCDGRP: This lookup table defines the available groups of HCDs.

1	HCD GROUP ABBREV	A14	The name of the HCD group. This is the same as the HCD abbreviation for HCDs that are by themselves in a group.
2	HCD GROUP NAME	A32	The long form of the HCD group name.
3	HCD GROUP RPT ORDER	N	The order in which this group appears with respect to other groups on a report.

V\$PCD: This lookup table contains information about each valid physical content descriptor.

1	PCD ABBREV	A14	The abbreviation for a physical content descriptor.
2	PCD NAME	A32	The full name of the physical content descriptor.
3	PCD REPORT ORDER	N	The order in which data for this PCD appears on reports.
4	PCD FORM ORDER	N	The order in which data for this PCD appears or is entered on forms.
5	PCD GROUP ABBREV	A14	The name of the PCD group to which this PCD belongs.
6	PCD DESCRIPTION	A255	The description of this PCD.

V\$PCDGRP: This lookup table defines the available groups of PCDs.

1	PCD GROUP ABBREV	A14	The name of the PCD group. This is the same as the PCD abbreviation for PCDs that are by themselves in a group.
2	PCD GROUP NAME	A32	The long form of the PCD group name.
3	PCD GROUP RPT ORDER	N	The order in which this group appears with respect to other groups on a report.

Table 2.1. (Contd)

V\STSDWC: This lookup table contains information about valid treatment, storage and disposal (TSD) waste classes.

1 TSD WC ABBREV	A12	The abbreviation for a treatment, storage and disposal (TSD) waste class name.
2 TSD WC NAME	A32	The full name of the TSD waste class.
3 TSD WC FORM ORDER	N	The order in which data about this TSD waste class appears or is entered on forms.
4 TSD WC REPORT ORDER	N	The order in which data about this TSD waste class appears on reports.

V\SWCAT: This lookup table contains information about valid waste categories.

1 WCAT ABBREV	A14	The abbreviation for a waste category.
2 WCAT NAME	A32	The full name of the waste category.
3 WCAT FORM ORDER	N	The order in which data for this waste category appears or is entered on forms.
4 WCAT REPORT ORDER	N	The order in which data for this waste category appears on reports. Categories of a similar handling type will appear together with this ordering.
5 ALT REPORT ORDER	N	The order in which data for this waste category appears on reports. Categories of similar composition will appear together with this ordering.
6 TYPE	A15	The type of handling to which this waste category is subject - remote or contact.
7 WCAT GROUP	A14	The waste group to which this waste category belongs.

V\SWCATGRP: This lookup table defines the available groups of waste categories.

1 WCAT GROUP	A14	The abbreviated name of the waste group - established by the nature of the waste without regard to level or handling requirement.
2 REPORT ORDER	N	The order relative to other waste groups that this group appears on reports.

Table 2.1. (Contd)

V\$WCLASS: This lookup table contains information about valid waste classes.

1	WCLASS ABBREV	A14	The abbreviation for a waste class name.
2	WCLASS NAME	A32	The full name of the waste class.
3	WCAT ABBREV	A14	The abbreviation for a waste category.
4	TSD WCLASS ABBREV	A14	The abbreviation for the equivalent TSD waste class.
5	WCLASS REPORT ORDER	N	The order in which data about this waste class appears on reports.
6	WCLASS FORM ORDER	N	The order in which data about this waste class appears or is entered on forms.
7	ALT REPORT ORDER	N	Unused.

V\$WGCLASS: This lookup table contains information about valid waste generator classes.

1	WGCLASS ABBREV	A14	The abbreviation for a waste generator class.
2	WGCLASS NAME	A24	The full name for the waste generator class.
3	WGCLASS REPORT ORDER	N	The order in which data for this waste generator class appears on reports.
4	WGCLASS FORM ORDER	N	The order in which data for this waste generator class appears or is entered on forms.
5	WGCLASS DESCRIPTION	A255	The description of this waste generator class.

V\$WGGROUP: This lookup table contains information about valid waste generator groups.

1	WG GROUP NAME	A16	The name of the waste generator group.
2	WG GROUP REPORT ORDER	N	The order in which data about this waste generator group appears on reports.

Table 2.1. (Contd)

WORKECONT: This table receives all container data entry prior to data validation checking and passing of data to D\CONT for permanent storage.

1	WCLASS ABBREV	A14	The abbreviation for a waste class name.
2	PCD ABBREV	A14	The abbreviation for a physical content descriptor.
3	55G DRUM	N	Fraction of the PCD in this container type.
4	ODD DRUM	N	Fraction of the PCD in this container type.
5	PLASTIC WRAP	N	Fraction of the PCD in this container type.
6	DUMP TRUCK	N	Fraction of the PCD in this container type.
7	TANKER TRUCK	N	Fraction of the PCD in this container type.
8	SEALED EQUIP	N	Fraction of the PCD in this container type.
9	4X4X8 BOX	N	Fraction of the PCD in this container type.
10	TRUPACT BOX	N	Fraction of the PCD in this container type.
11	< 128 BOX	N	Fraction of the PCD in this container type.
12	128-500 BOX	N	Fraction of the PCD in this container type.
13	500-1000 BOX	N	Fraction of the PCD in this container type.
14	1000-5000 BOX	N	Fraction of the PCD in this container type.
15	OTHER	N	Fraction of the PCD in this container type.

WORKEFOREVOL: This table receives all volume data entry prior to data validation checking and passing of data to D\FOREVOL for permanent storage.

1	WCLASS ABBREV	A14	The abbreviation for a waste class name.
2	HELD	N	Volume forecast for Held waste.
3	1992	N	Volume forecast for the year 1992.
4	1993	N	Volume forecast for the year 1993.

Table 2.1. (Contd)

5 1994	N	Volume forecast for the year 1994.
6 1995	N	Volume forecast for the year 1995.
7 1996	N	Volume forecast for the year 1996.
8 1997	N	Volume forecast for the year 1997.
9 1998	N	Volume forecast for the year 1998.
10 1999	N	Volume forecast for the year 1999.
11 2000	N	Volume forecast for the year 2000.
12 2001	N	Volume forecast for the year 2001.
13 2002	N	Volume forecast for the year 2002.
14 2003	N	Volume forecast for the year 2003.
15 2004	N	Volume forecast for the year 2004.
16 2005	N	Volume forecast for the year 2005.
17 2006	N	Volume forecast for the year 2006.
18 2007	N	Volume forecast for the year 2007.
19 2008	N	Volume forecast for the year 2008.
20 2009	N	Volume forecast for the year 2009.
21 2010	N	Volume forecast for the year 2010.
22 2011	N	Volume forecast for the year 2011.
23 2012	N	Volume forecast for the year 2012.
24 2013	N	Volume forecast for the year 2013.
25 2014	N	Volume forecast for the year 2014.
26 2015	N	Volume forecast for the year 2015.

Table 2.1. (Contd)

27	2016	N	Volume forecast for the year 2016.
28	2017	N	Volume forecast for the year 2017.
29	2018	N	Volume forecast for the year 2018.
30	2019	N	Volume forecast for the year 2019.
31	2020	N	Volume forecast for the year 2020.
32	2021	N	Volume forecast for the year 2021.

WORK\EHCD: This table receives all HCD data entry prior to data validation checking and passing of data to D\HCD for permanent storage.

1	WCLASS ABBREV	A14	The abbreviation for a waste class name.
2	PCD ABBREV	A14	The abbreviation for a physical content descriptor.
3	CAUSTIC	N	Fraction of the PCD contaminated with this HCD.
4	ACIDIC	N	Fraction of the PCD contaminated with this HCD.
5	OTHER CORR	N	Fraction of the PCD contaminated with this HCD.
6	FLAMMABLE	N	Fraction of the PCD contaminated with this HCD.
7	COMBUSTIBLE	N	Fraction of the PCD contaminated with this HCD.
8	OXIDIZER	N	Fraction of the PCD contaminated with this HCD.
9	OTHER IGN	N	Fraction of the PCD contaminated with this HCD.
10	HEAVY METALS	N	Fraction of the PCD contaminated with this HCD.
11	TOXIC MATLS	N	Fraction of the PCD contaminated with this HCD.
12	ORGANIC MATLS	N	Fraction of the PCD contaminated with this HCD.
13	OTHER TOXIC	N	Fraction of the PCD contaminated with this HCD.
14	IRRITATIVE	N	Fraction of the PCD contaminated with this HCD.

Table 2.1. (Contd)

15 EXPLOSIVE	N	Fraction of the PCD contaminated with this HCD.
16 OTHER REACTIVE	N	Fraction of the PCD contaminated with this HCD.
17 LISTED RCRA	N	Fraction of the PCD contaminated with this HCD.
18 ASBESTOS	N	Fraction of the PCD contaminated with this HCD.
19 PCB < 50 PPM	N	Fraction of the PCD contaminated with this HCD.
20 PCB > 50, < 500	N	Fraction of the PCD contaminated with this HCD.
21 PCB > 500	N	Fraction of the PCD contaminated with this HCD.

WORK\EPD: This table receives all PCD data entry prior to data validation checking and passing of data to D\PCD for permanent storage.

1 PCD ABBREV	A14	The abbreviation for a physical content descriptor.
2 CH_LLW_I	N	The fraction of the waste class made up of this PCD.
3 CH_LLW_III	N	The fraction of the waste class made up of this PCD.
4 CH_LLW_GTCIII	N	The fraction of the waste class made up of this PCD.
5 RH_LLW_I	N	The fraction of the waste class made up of this PCD.
6 RH_LLW_III	N	The fraction of the waste class made up of this PCD.
7 RH_LLW_GTCIII	N	The fraction of the waste class made up of this PCD.
8 CH_LLMW_I	N	The fraction of the waste class made up of this PCD.
9 CH_LLMW_III	N	The fraction of the waste class made up of this PCD.
10 CH_LLMW_GTCIII	N	The fraction of the waste class made up of this PCD.
11 RH_LLMW_I	N	The fraction of the waste class made up of this PCD.
12 RH_LLMW_III	N	The fraction of the waste class made up of this PCD.
13 RH_LLMW_GTCIII	N	The fraction of the waste class made up of this PCD.

Table 2.1. (Contd)

14 HAZ	N	The fraction of the waste class made up of this PCD.
15 CH_TRU	N	The fraction of the waste class made up of this PCD.
16 RH_TRU	N	The fraction of the waste class made up of this PCD.
17 CH_TRUM	N	The fraction of the waste class made up of this PCD.
18 RH_TRUM	N	The fraction of the waste class made up of this PCD.

WORK\WEIGHT: This table receives all weight data entry prior to data validation checking and passing of data to D\WEIGHT for permanent storage.

1 WCLASS ABBREV	A14	The abbreviation for a waste class name.
2 HELD	N	Weight of held waste forecasted.
3 1992	N	Weight of waste forecasted for 1992.
4 1993	N	Weight of waste forecasted for 1993.
5 1994	N	Weight of waste forecasted for 1994.
6 1995	N	Weight of waste forecasted for 1995.
7 1996	N	Weight of waste forecasted for 1996.
8 1997-2021	N	Average annual weight of waste forecasted for 1997-2021.

3.0 DATABASE PROCESSES AND APPLICATIONS

The primary processes performed by the SWPM database are shown in Figure 2.1. These processes correspond approximately to menu options on the main menu. Selecting one of these options displays another menu or initiates some activity. The SWPM Menu Structure is shown below. Section 3.1 describes each of the processes shown as the lowest level of each menu diagram branch.

SWPM MENU STRUCTURE

3.1 PROCESS DICTIONARY

The process dictionary provides a description for each of the processes shown as bottom level selections in the menu structure diagram. This dictionary also provides the name of the PAL script(s) or procedure(s) used to perform the process and the names of forms and reports involved. Unless otherwise noted, PAL scripts are located in the \SWPMDB91\PAL directory. The processes are listed in their order of appearance on the SWPM Menu Structure.

Menu path: **Forecast\IDFore** - select WG/forecast combination for data entry/update or data validation reporting - no provision for updates

Main script/procedure: ForeEdit()
Called scripts/procedures:
Tables, forms and reports: d\FORECAST

Menu path: **Forecast\ForeVol** - data entry/update of volume data for the WG/forecast combination selected in **IDFore** above. Activity is performed in a work table using Data Entry Toolkit procedures after which data are added back to d\FOREVOL. See Appendix C, Section 8, for technical notes on the Data Entry Toolkit implementation.

Main script/procedure: Forevol_DE()
Called scripts/procedures:
Tables, forms and reports: d\FOREVOL, work\EFOREVOL

Menu path: **Forecast\PCD** - data entry/update of PCD percentage data for the WG/forecast combination selected in **IDFore** above. Activity is performed in a work table using Data Entry Toolkit procedures after which data are added back to d\PCD.

Main script/procedure: PCD_DE
Called scripts/procedures:
Tables, forms and reports: d\PCD, work\epcd

Menu path: **Forecast\HCD** - data entry/update of HCD percentage data for the WG/forecast combination selected in **IDFore** above. Activity is performed in a work table using Data Entry Toolkit procedures after which data are added back to d\HCD.

Main script/procedure: HCD_DE
Called scripts/procedures:
Tables, forms and reports: d\HCD, work\ehcd

Menu path: **Forecast\Cont** - data entry/update of container percentage data for the WG/forecast combination selected in **IDFore** above. Activity is performed in a work table using Data Entry Toolkit procedures after which data are added back to d\Cont.

Main script/procedure: Cont_DE
Called scripts/procedures:
Tables, forms and reports: d\Cont, work\econt

Menu path: Forecast\Wt - data entry/update of weight data for the WG/forecast combination selected in IDFore above. Activity is performed in a work table using Data Entry Toolkit procedures after which data are added back to d\Weight.

Main script/procedure: Weight_DE
Called scripts/procedures:
Tables, forms and reports: d\Weight, work\eweight

Menu path: Forecast\DataVal\A_Packet - Data validation report packet A, low level waste class reports

Main script/procedure: dv\DatPukeA.sc
Called scripts/procedures: dv\DPI.sc, dv\DPII.sc, dv\DPIV.sc and various queries in the dv subdirectory
Tables, forms and reports: dv\PA1, dv\PA2, dv\PA4 and associated reports

Menu path: Forecast\DataVal\B_Packet - Data validation report packet B, low level mixed and hazardous waste class reports

Main script/procedure: dv\DatPukeB.sc
Called scripts/procedures: dv\DPI.sc, dv\DPII.sc, dv\DPiII.sc, dv\DPIV.sc and various queries in the dv subdirectory
Tables, forms and reports: dv\PA1, dv\PA2, dv\PA3, dv\PA4 and associated reports

Menu path: Forecast\DataVal\C_Packet - Data validation report packet C, TRU waste class reports

Main script/procedure: dv\DatPukeC.sc
Called scripts/procedures: dv\DPI.sc, dv\DPII.sc, dv\DPIV.sc and various queries in the dv subdirectory
Tables, forms and reports: dv\PA1, dv\PA2, dv\PA4 and associated reports

Menu path: Forecast\DataVal\D_Packet - Data validation report packet D, TRU mixed waste class reports

Main script/procedure: dv\DatPukeD.sc
Called scripts/procedures: dv\DPI.sc, dv\DPII.sc, dv\DPiII.sc, dv\DPIV.sc and various queries in the dv subdirectory
Tables, forms and reports: dv\PA1, dv\PA2, dv\PA3, dv\PA4 and associated reports

Menu path: Forecast\DataVal\Every_One - Performs all four data validation report processes

Main script/procedure: dv\Pukeall.sc
Called scripts/procedures: dv\DatPukeA.sc, dv\DatPukeB.sc, dv\DatPukeC.sc, dv\DatPukeD.sc
Tables, forms and reports: dv\PA1, dv\PA2, dv\PA3, dv\PA4 and associated reports

Menu path: TSD\Oper - Maintain TSD operations table

Main script/procedure: TSDEDIT()
Called scripts/procedures:
Tables, forms and reports: dtstd\OPER

Menu path: **TSD\Dist_F** - Maintain TSD distribution fraction table

Main script/procedure: **TSDEDIT()**

Called scripts/procedures:

Tables, forms and reports: **dtst\DIST_F**

Menu path: **TSD\OperFlow** - Maintain TSD operation flow table

Main script/procedure: **TSDEDIT()**

Called scripts/procedures:

Tables, forms and reports: **dtst\OPERFLOW**

Menu path: **TSD\OperCap** - Maintain TSD operation capacities table

Main script/procedure: **TSDEDIT()**

Called scripts/procedures:

Tables, forms and reports: **dtst\OPERCAP**

Menu path: **RDL** - Executes reference data library creation process. (This process is detailed in Appendix D.)

Main script/procedure: **WriteRDL()**

Called scripts/procedures: **WriteRPS()**, **WriteRPF()** and certain queries

Tables, forms and reports: input tables: **work\FVCONVX**, **dtst\OPER**, **mvd\VARDict**, **d\WG**, **dtst\OPERFLOW**, **dtst\OPERCAP**, **dtst\DIST_F**, various work tables, output tables: **work\RPS**, **work\RPF** (and text file versions)

Menu path: **UP\DOWNLOAD\Upload** - uploads forecast data from a local database to the network. Usage is logged.

Main script/procedure: **Upload()**

Called scripts/procedures: **Updnlog()**

Tables, forms and reports: **d\updnlog**, **d\WG**, **d\CONT**, **d\HCD**, **d\PCD**, **d\Forevol**, **d\Weight**, **d\Notepad**

Menu path: **UP\DOWNLOAD\Download\Software** - downloads SWPM database application software, work tables, and other files required to support SWPM database access from the network to the user's choice of local disk drives.

Main script/procedure: **Dnld()**

Called scripts/procedures: **Updnlog()**, **DNLDSoft.BAT**

Tables, forms and reports: **d\updnlog**, also, see content of **\SWPMDB91\DNLDSoft.BAT** for file names copied to the local drive.

Menu path: UP/DOWNLOAD\Download\Data - downloads SWPM database forecast data tables and related files from the network to the user's choice of local disk drives.

Main script/procedure: Dnld()
Called scripts/procedures: Updnlog(), DNLDDATA.BAT
Tables, forms and reports: d\updnlog, also, see content of \SWPMDB91\DNLDDATA.BAT for file names copied to the local drive.

Menu path: UP/DOWNLOAD\Download\Codes - downloads SWPM database tables and related files containing support data from the network to the user's choice of local disk drives.

Main script/procedure: Dnld()
Called scripts/procedures: Updnlog(), DNLDPCODE.BAT
Tables, forms and reports: d\updnlog, also, see content of \SWPMDB91\DNLDPCODE.BAT for file names copied to the local drive.

Menu path: Codes\WG - maintain waste generator table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: d\WG

Menu path: Codes\WClass\WClass - maintain waste class table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: v\WClass

Menu path: Codes\WClass\WCat - maintain waste category table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: v\WCat

Menu path: Codes\WClass\TSD_WClass - maintain TSD waste class table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: v\TSDWC

Menu path: Codes\Types\PCD - maintain PCD types table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: v\SPCD

Menu path: Codes\Types\HCD - maintain HCD types table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\HCD

Menu path: Codes\Types\Cont - maintain container types table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\$Cont

Menu path: Codes\Groups\WG_Class - maintain waste generator class table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\WGCLASS

Menu path: Codes\Groups\WG_Group - maintain waste generator group table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\$WGGROUP

Menu path: Codes\Groups\PCD - maintain PCD groups table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\$PCDGRP

Menu path: Codes\Groups\HCD - maintain HCD groups table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\HCDGRP

Menu path: Codes\Groups\Cont - maintain container groups table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\$CONTGRP

Menu path: Codes\Groups\WCat - maintain waste category groups table

Main script/procedure: FeaEdit()

Called scripts/procedures:

Tables, forms and reports: v\WCATGRP

Menu path: **Codes\Scenario** - maintain forecast scenario table

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: d\Scenario

Menu path: **Codes\Forecast** - maintain forecast table (WG and scenario association)

Main script/procedure: FeaEdit()
Called scripts/procedures:
Tables, forms and reports: d\Forecast

Menu path: **Codes\Dictionary** - maintain SWPM project dictionary tables

Main script/procedure: DictEdit()
Called scripts/procedures:
Tables, forms and reports: v\SDict, v\SDictgrp

Menu path: **Report_Mgr\PRTNEW** - Process, store and print selected report

Main script/procedure: RPTMGR() - source: UTIL\RPTMGR.SC
Called scripts/procedures: Called script depends on report selected in WAIT TABLE. See Report Manager technical notes in Appendix C, Section 5, for more information.
STORE_RPT() - source: UTIL\STORERPT.SC
TIMEDIFF() - source: UTIL\TIMEDIFF.SC
Tables, forms and reports: r\SWPMRPT.DB
Others depend on report selection

Menu path: **Report_Mgr\NEW** - Process and store selected report

Main script/procedure: Same as PRTNEW
Called scripts/procedures: Same as PRTNEW, except does not use STORE_RPT
Tables, forms and reports: Same as PRTNEW

Menu path: **Report_Mgr\REPRINT** - Store and print selected report

Main script/procedure: Same as PRTNEW
Called scripts/procedures:
Tables, forms and reports: Same as PRTNEW

Menu path: **Report_Mgr\STORE** - Store selected report

Main script/procedure: Same as NEW
Called scripts/procedures:
Tables, forms and reports: Same as PRTNEW

Menu path: **Report_Mgr\TABLE** - return to report selection table

Main script/procedure: Same as PRTNEW

Called scripts/procedures:

Tables, forms and reports: Same as PRTNEW

Process description: Brings table r\SWPMRPT back into view for further report selection

Menu path: **Report_Mgr\QUIT** - cancel report manager

Main script/procedure: Same as PRTNEW

Called scripts/procedures:

Tables, forms and reports:

Process description: Provides an obvious exit from the Report Manager, especially for users who call this procedure with a hotkey

Menu path: **ACTION** - Maintain action item list table

Main script/procedure: Action() - source: UTIL\ACTION.SC

Called scripts/procedures:

Tables, forms and reports: Action\Action.DB - holds list of items
Action\Acthist.db - holds completed items
Action\Actrpt.DB - holds select items for reports
Action\Actrpt.R - Action item report
Action\Actrpt.R1 - Overdue report

APPENDIX A

REQUIRED NETWORK CONFIGURATION

APPENDIX A

REQUIRED NETWORK CONFIGURATION

A.1 SERVER CONNECTIONS

All SWPM users who wish to access the data and application software on the network need to connect to the network server as follows:

USE J: \\PNL5\SWPM 'password'

The use of "J" for the drive designation is recommended. The application will run with other drive letters, but problems with Paradox table sharing may result. Also, the drive letter indicates to the application whether the network reference database is in use. If a local copy (or the network drive is called something besides "J:"), standard reports will be labeled as "Unofficial." This is done on the assumption that they may be generated from a local, uncontrolled copy of the database. See Appendix C, Section 10, for technical notes on the SWPM start-up script, where the drive designation is examined.

Users who also wish to use the network version of Paradox must connect to the server on which the software is installed. This includes users who have made a local copy of the network Paradox software for performance improvement. Enter the following:

USE K: \\PNL10\PDOX35 'password'

The use of a drive letter other than "K" may hinder the ability of Paradox to manage multiuser access to the SWPM database.

Get the current passwords from the SWPM database administrator.

A.2 WORKING DIRECTORY

All SWPM application software assumes that the user's current working directory is J:\SWPMDB91. This can be set from the Paradox menu by selecting **Tools More Directory** and then entering the directory name. In addition, the default working directory can be changed by playing the CUSTOM script. A third method is to include the directory change command in INIT.SC, a script that Paradox runs immediately after it is first executed. This script should be located in the private directory for network users and, for standalone users, in the directory that contains the Paradox software.

APPENDIX B

PARADOX DEFAULT SETTINGS

APPENDIX B

PARADOX DEFAULT SETTINGS

These settings are established by playing the CUSTOM script and choosing items to set from the menus presented. This script can be found in the directory containing the network Paradox software or in the directory containing a stand-alone Paradox installation.

The directions below show the progression of menu selections needed for each parameter and assume that you are starting from the top level menu. Menu selections are shown in bold. Other text must be typed in.

Set default length of page to 60 lines -

Reports LengthOfPage 60

Send form feeds at end of every report page -

Reports FormFeed FormFeeds

Treat blanks as zeros for calculating purposes -

Defaults Blank=Zero Yes

Set private directory to hard disk with 20mb of free space -

Net SetPrivate "private directory name"

When complete, select **Do_It!** or press F2. Choose **HardDisk** if you are working from a stand-alone Paradox installation or **NetWork** if you are running network software. In the latter case, override the suggested directory and save the configuration to the directory in which your local copy of the network software is installed.

APPENDIX 1C

TECHNICAL NOTES

APPENDIX C

TECHNICAL NOTES

SECTION 1 - ACTION ITEM LIST

C.1 DESCRIPTION

The action item list is a table of action items assigned to group members. Each member or the team leader may define action items and expected completion dates. Any user may print a listing of his or her own items or the entire list. A list of overdue items is also available. When an item is complete, a user can enter an actual completion date to close the item out.

C.2 DESCRIPTIONS AND LOCATIONS OF FILES

Location of files (unless otherwise specified):

J:\SWPMD90\ACTION

PAL scripts and procedures:

ACTION() - Procedure that performs action item tracking function. Contained in LIB\UTIL.LIB.

ACTION.SC - Located in UTIL subdirectory. Contains PAL code that compiles into ACTION().

Tables and related objects:

ACTION.DB - Table containing information about action items. This table is available for editing during while the procedure is operating using Paradox WAIT TABLE.

ACTRPT.DB - Table to hold data for reports. Contents are replaced whenever an action item list report is selected.

ACTHIST.DB - Table to store completed action items for historical reference.

ACTION.R - Report specification used to generate a report showing either all action items or a subset of items assigned to a particular person.

ACTION.R1 - Report specification used to generate an overdue report. Selection process compares current system date and due date to select items that have not been completed and have a scheduled completion date earlier than today.

C.3 EXECUTION OF THE ACTION ITEM LIST FUNCTION

The action item tracking function is available from the SWPM main menu. The **Action** selection is part of the **MAIN** menu group. Lower level menus are coded into the procedure.

The SWPM action item table ACTION\ACTION.DB is viewed in Coedit mode via WAIT TABLE. The user may edit all fields as well as delete and insert items. At this time no privilege level controls are installed, although future enhancements may include an installation option to differentiate between user and supervisor level editing. The user may choose 3 types of reports, a complete action item listing, a listing that is restricted to items assigned to a particular person and a report showing items that are overdue.

Presently, no automated means of removing completed items to the history table ACTION\ACTHIST has been provided. An history report will also be created as a future enhancement.

SECTION 2 - DATA VALIDATION REPORTING

C2.1 DESCRIPTION

This set of processes runs data validation reports for the WG selected from the SWPM application. The reports are intended to allow visual verification of forecast data in the database for a given waste generator. They are also designed to accompany new forecast data request forms sent to waste generators, to show the content of the previous forecast.

The reports are divided into 4 packets:

- low level waste - packet A
- low level mixed and hazardous - packet B
- TRU waste - packet C
- TRU mixed waste - packet D

Each packet has either three or four sets of reports depending on waste types included in the packet:

- waste volume
- physical content and container percentages
- hazardous constituent percentages (included in packets B and D only)
- weight

C2.2 DESCRIPTIONS AND LOCATIONS OF FILE

Location of files (unless otherwise specified):

J:\SWPMDB90\DV

C2.2.1 PAL Scripts

- DATPUKEA.SC - This process runs the first packet, low level waste. It calls all sub-packet scripts except the HCD sub-packet DPIIL.SC. This process and the next three depend on the SWPM application to get a WG name from the user. They will abort if no WG has been selected.
- DATPUKEB.SC - Runs the second packet, low level mixed and hazardous.
- DATPUKEC.SC - Runs the third packet, TRU waste.

- DATPUKED.SC - Runs the fourth packet, TRU mixed waste.
- PUKEALL.SC - Executes DATPUKEA - DATPUKED in sequence. Assumes that the WG name has been defined.
- DPI.SC - Produces volume report for currently defined WG and waste class grouping. Called by DATPUKEA,B,C,D. Resulting data go to table PA1.DB.
- DPII.SC - Produces physical contents and containment reports for currently defined waste class and WG. Called by DATPUKEA,B,C,D. Resulting data go to table PA2.DB.
- DPIII.SC - Produces hazardous constituent reports for currently defined waste class and WG. Called by DATAPUKEB,D. Resulting data go to table PA3.DB.
- DPIV.SC - Produces weight report for currently defined waste class grouping and WG. Called by DATPUKEA,B,C,D. Resulting data go to table PA4.DB.

C2.2 Query Scripts

- PA1_1.SC - PA1_3.SC - played by DPI.SC
- PA2_1.SC - PA2_6.SC - played by DPII.SC
- PA3_1.SC - PA3_4.SC - played by DPIII.SC
- PA4_1.SC - PA4_6.SC - played by DPIV.SC

C2.3 Tables

- PA1.DB - holds data for volume report as specified in PA1.R.
- PA2.DB - holds data for physical content and containment report as specified in PA2.DB.
- PA3.DB - holds data for hazardous constituent report as specified in PA3.R.
- PA4.DB - holds data for weight report as specified in PA4.R.
- #"table name".DB - tables used for inclusive joins to force the presence of desired line items in results.

C2.3 EXECUTION OF THE DATA VALIDATION REPORTS

All processes are run by selection from the SWPM menu. The **DataVal** selection is part of the FORECAST menu group. It chains to the DATAVAL menu group which includes selections for each packet individually and for the entire set of packets to be run in sequence. Unlike other SWPM database report processes, output is sent directly to the printer and is not stored as text files.

SECTION 3 - NOTEPAD

C3.1 DESCRIPTION

This feature allows a user to make notes into a database table that serve to document non-routine changes to tables, unresolved problems, decisions affecting content of fields or any other matter that warrants a written notation. The notes are available to others via a report selection on the Report Manager or by viewing the notepad table. Due to some differences in required implementation, this function actually includes a family of related scripts and procedures that appear similarly when used. The three implementations are:

1. General use, outside of application scripts or procedures - use NOTEPAD()
2. During Wait Table procedures - use NOTEPAD2()
3. During Data Entry Toolkit operation - use NOTE_SET(), NOTES_A() and NOTES_B().

The notepad opens as a two-line window near the bottom of the screen and will accept up to 160 characters per note. It automatically records the user name, the name of the current table, the name of the current field, and the content of the current field to provide an environmental context to the note. The number of allowable notes is unlimited. However, during a given data entry session in the Data Entry Toolkit implementation, array space is available for only 15 notes. An error message results if the number is exceeded. In such a case, the user must exist and reenter the process. This forces the procedures involved to dump the notes to the notepad table and reinitialize the arrays.

C3.2 DESCRIPTIONS AND LOCATIONS OF FILES

C3.2.1 Scripts and Procedures

NOTEPAD()	Procedure that performs standard notepad function, usable in routine interactive Paradox work where an application script does not have control. Contained in LIB\UTIL.LIB.
NOTEPAD2()	Procedure that performs WAIT TABLE version of notepad function. Contained in LIB\UTIL.LIB.
NOTE_SET()	Initializes arrays for Data Entry Toolkit notepad implementation. Used in conjunction with NOTES_A() and NOTES_B(). Contained in LIB\FOREDE.LIB.
NOTES_A()	During Data Entry Toolkit operations where this procedure is referenced, notes and other data are captured into arrays initialized by NOTE_SET(). Contained in LIB\FOREDE.LIB.

NOTES_B()	Immediately after a data entry process using the Data Entry Toolkit, NOTE_SET() and NOTES_A(), this procedure must be called to write data in the arrays to the notepad table. Contained in LIB\FOREDE.LIB.
NOTEPAD.SC	Located in UTIL subdirectory. Compiles into NOTEPAD().
NOTEPAD2.SC	Located in UTIL subdirectory. Compiles into NOTEPAD2(). Similar to NOTEPAD.SC, except that the procedure created is intended to be called by other procedures or scripts that have a table in WAIT TABLE status. Requires procedures LU_sSAVE and LU_sRESTORE to be run before and after.
NOTE_SET.SC	Located in UTIL Subdirectory. Source script for NOTE_SET(). Compiled by UTIL\FOREDE.SC.
NOTES_A.SC	Located in UTIL Subdirectory. Source script for NOTES_A(). Compiled by UTIL\FOREDE.SC.
NOTES_B.SC	Located in UTIL Subdirectory. Source script for NOTES_B(). Compiled by UTIL\FOREDE.SC.
2.2	Tables and related objects:
NOTEPAD.DB	Contains note entered through NOTEPAD window, as well as environmental information (table name, field name, user, etc.)
NOTEPAD.R	Report specification for report used to list contents of notepad.

C3.3XIMPLEMENTATION

- 3.1 NOTEPAD() - this version can be executed as a miniscript or via hotkey. Ctrl N is recommended. SWPM startup script contains the following line:

SETKEY 14 notepad()

- 3.2 NOTEPAD2() - execution should only be from another procedure. It requires the use of LU_sSAVE() and LU_sRESTORE() to save and then restore to the current state. Certain variables initialized by LU_sSAVE() are used to record the table and field names as well as the field contents in the notepad. The following example is a code fragment that would presumably be one of several CASE sections in a SWITCH structure:

```

CASE retval = 14: ; Invoked in this example by ^N
  Loc_sSAVE()    ; call this first to save location in
                  ; table being edited
  Do_it!         ; ends EDIT or COEDIT
  notepad2()     ; executes procedure
  Loc_sRestore() ; restores position in original table
  Coeditkey      ; return to edit mode

```

3.3 NOTE_SET(), NOTES_A() and NOTES_B() - to be executed within a data entry process that uses the Data Entry Toolkit.

3.3.1 Invoke NOTE_SET() within the procedure, before the DO WAIT command occurs. This procedure creates arrays to temporarily store the note and other data to be captured in the notepad. The procedure allocates array space for as many as 15 notes.

3.3.2 Invoke NOTES_B() immediately after exiting the DO WAIT, in order to store any notes that were captured in arrays.

3.3.3 NOTES_A() is implemented indirectly. A keystroke level procedure must be defined in the Data Entry Toolkit setup for each table for which the notepad is to be used. The keystroke procedure (UTIL\KEYBLK.SC, for example) must then check for a particular keystroke (^N, in this case) used to invoke the notepad. In addition, the script used to define entry, exit and keystroke procedures and usable keys must allow the keystroke. See WORK\EFORVOL.SC as an example. The TKPosKey variable in such a script is used to define key availability.

SECTION 4 - PROJECT DICTIONARY

C4.1 DESCRIPTION

This function provides a means of compiling a dictionary of terms associated with the SWPM project for publication in Westinghouse documents and to serve as a reference for internal use. Terms are grouped into families so that reports containing a subset of the dictionary can be produced for specific audiences. Dictionary maintenance has been added to the Codes data maintenance submenu for ease of access. When standard reports are defined, they will be included in the Report Manager.

C4.2 DESCRIPTIONS AND LOCATIONS OF FILES

C4.2.1 PAL Scripts and Procedures

- DICTEDIT() - Procedure called from the SWPM application menu that enables user to edit the dictionary table.
- UTIL\DICTEDIT - Source script for DICTEDIT(). Compiled by LIB\UTIL.SC into library LIB\UTIL.LIB.
- v\SDICTRPT.SC - Query used to extract the desired rows from v\SDICT.DB to be added into v\SDICTRPT.DB for reporting purposes. As of the time of the preparation of this documentation, only items within groups for which a sort order is defined are selected.

C4.2.2 Tables and Related Objects

- v\SDICT.DB - Table containing acronyms, the terms they stand for and other information
- v\SDICT.F - Form used for data entry
- v\SDICT.R - Report specification
- v\SDICTGRP.DB - Table containing a list of valid group names. Used as a lookup table for validating the group field in the dictionary table v\SDICT.DB
- v\SDICTRPT.DB - Table containing the subset of the dictionary table to be included in a report. Same structure as v\SDICT.DB.
- v\SDICTRPT.R - Report specification used to produce dictionary report.

C4.3 PERFORMING DICTIONARY MAINTENANCE

Select **Codes** from the main SWPM menu. Then choose **Dictionary** from the codes menu. The dictionary table is displayed on a data entry form with information at the bottom showing available functions. New items can be inserted at any time by pressing [Ins]. Searching and undoing are also supported. A report selection is available, but it only displays a message advising the user that reports are not yet implemented. See instructions below for generating a report.

C4.4 PRINTING DICTIONARY REPORTS

Reporting has not been implemented from the dictionary screen, as of the time this document was written. Reports are generated by selecting the subset of rows in the dictionary table to be printed and placing them in the dictionary report table. Selection can be accomplished using a saved query such as q\SDICTRPT or other means. The Answer table thus created should be added to v\SDICTRPT after it has first been emptied. Alternatively, the same report format can be generated directly from v\SDICT if the entire table is to be used in the report.

SECTION 5 - REPORT MANAGER

C5.1 DESCRIPTION

The Report Manager is designed to generate reports using selections made from a table of report names. It was intended to eliminate the need to code report processing into every script that creates data for reporting. Since project requirements include storage of report text as well as generation of hard copy, routing of report output to text files is also handled within this function. The Report Manager was intended as a generic tool to be usable in other Paradox applications. The method of defining a report in the report table was made fairly general but assumes a standard Paradox application directory structure. The structure needed is similar to that proposed by Brian J. Smith in his column titled "Up the Organization" published in the June 1990 issue of "Data Based Advisor" magazine. SWPM database applications for FY90 and FY91 conform to the model advanced by Smith, although certain directories were defined in addition to those in his scheme.

C5.2 DESCRIPTIONS AND LOCATIONS OF FILES

Location of files (unless otherwise specified):

J:\SWPMDB91\R

C5.2.1 PAL Scripts and Procedures

RPTMGR() - Procedure that performs Report Manager function. Contained in LIB\UTIL.LIB.

STORE_RPT() - Procedure that writes a report out to a text file. Located in LIB\UTIL.LIB. See Appendix E.

RPTMGR.SC - Located in UTIL subdirectory. Contains PAL code that compiles into RPTMGR(). Allows selection of report to be run and/or printed via WAIT TABLE on table R\SWPMRPT.DB. See description of menu choices in Section 3.1 - Process Dictionary. This script also contains code for RPTMSG(), a dummy procedure used when no data manipulation processing is required before a report can be generated.

UTIL.SC - Located in LIB subdirectory. Compiles all UTIL library procedures, including RPTMGR() into LIB\UTIL.LIB, entirely replacing the old version of the library.

C5.2.2 Tables and Related Objects

SWPMRPT.DB - Table containing information about all available SWPM database reports. RPTMGR() allows this table to be viewed and a report chosen under the control of WAIT TABLE. See Table 2.1 for information about the structure of this table.

SWPMRPT.R - Report specification used to generate a report showing information about all available SWPM reports.

C5.3 ADDING A REPORT TO THE REPORT MANAGER

C5.3.1 Entering the New Report into the Report Manager Table

The following steps describe the entry of data to specific columns of table R\SWPMRPTDB. It is assumed that this table is in the Paradox workspace in Edit mode.

Column	Entry Required
RPT ID	Enter a unique ID for the report. This is the key to this table. Can be included anywhere on the report output by placing a calculated field named "rptid" in the Paradox report specification. This column is also used to define the name of the text file to which the report will be written.
RPT ABBREV	The name of the table from which the report will be produced. Do not include its path here.
REPORT NUMBER	The Paradox report number R, 1, 2, ..., 14 that indicates one of the 15 possible reports defined for the table named in RPT ABBREV . The content of this field relates to the file name extension of the file containing the report specification. Extensions are ".R", ".R1", etc., preceded by the table name.
RPT NAME	The report title to be displayed on the Report Manager selection screen. Should be all or most of the first line of the report title.
RPT SCRIPT	The script or procedure that will create the report data. Omit the extension if it is a script. Include "()" after the name for procedures. Procedures must be available for Paradox to find via AUTOLIB or other means. Use a "do nothing" process here if no data preparation is required, such as "RPTMSG()". If a script is referenced, it must be in the directory defined by variable 'smdir'. This variable is defined in the Report Manager procedure and is set to "PAL\" for this application.
COMMENTS	Comments describing this report that will appear on report R300 - SWPM Database Reports.
FORMAT NOTES	An additional comment field used to describe the format of the report.
DATE MODIFIED	The date on which format changes were last made, or the date on which a report was added into the table.
DATE LAST RUN	No entry needed. This field is updated automatically when the report is run.
RUN TIME	No entry needed. Recorded automatically in minutes and tenths of minutes each time report is run.

TABLE LOCATION	Define the directory that contains the table defined by the contents of RPT ABBREV . If omitted, the Report Manager procedure uses the contents of a variable named 'tbl_dir', defined at the start of the procedure script. Defined as "WORK" in this application.
RPT FILE SIZE	The space allocated by DOS to the report text file named by the content of RPT ID plus ".RPT" as the file name extension. Since paper orientation, report width and font selection all are contributors to output volume, the relationship between file size and number of pages to print is indirect. This information is captured to give the user at least a very general idea of how much print will be generated.

C5.3.2 Other Preparation

Unless otherwise noted, the following instructions assume that default file names and directory locations are used.

1. Create required queries and scripts. The initial script or procedure used to begin processing must be named to match the contents of field **RPT SCRIPT**. If no processing is needed, procedure "rptmsg()" can be referenced in the table. This avoids an error due to a nonexistent procedure or script, but no processing is performed. Queries should be placed in the Q\ subdirectory, although no enforcement of query location is provided by the Report Manager.
2. If it does not already exist, create the table from which the report will be generated. If the table is created specifically to hold data extracted to produce a report, the table should be located in the WORK\ subdirectory. Using a table located anywhere else requires naming the directory location in the **TABLE LOCATION** field of the report table.
3. Create the report specification for the table defined in instruction 2 above. This report may be connected to an existing table, or may already exist. It is standard practice to include the report ID on the output. The source database of the report can be displayed similarly by placing a calculated field using variable 'rptsrc'. 'Rptsrc' is set by the script PAL\STARTSWP.SC when the application is started.

C5.3.3 Documenting a New Report

In most cases, internal comments in the report script and text entered into the **COMMENTS** field in the report table are sufficient documentation to enable someone with some Paradox knowledge to find and modify the reports as needed. A new report list (report R300) should be run and placed in all report notebooks. Users will then see that the report exists, and they can run it as needed.

C5.4 Execution of the Report Manager

The Report Manager is selectable from the SWPM database main menu. The **Report_Mgr** selection is part of the **MAIN** menu group. Lower level menu selections are coded in the procedure. The Paradox miniscript menu selection can be used to run the Report Manager by pressing [Alt] [F10] to display the

PAL menu, selecting **Miniscript** and then entering "rptmgr()". A hotkey such as [Alt] [P] can also be used to invoke the Report Manager, if such a key is predefined with the SETKEY command.

After execution begins, the SWPM report table R\SWPMRPT.DB is viewed in WAIT TABLE mode. The table used is defined as variable "rpttable" in the procedure script. The user makes a choice by pointing at the desired report and pressing the Do_it! key [F2]. A screen of information is then displayed that gives some indication how long the entire report process takes and how big the print file will be. Last run date is also shown.

SECTION 6 - TABLE/FIELD DOCUMENTOR

C6.1 DESCRIPTION

The table and field documentor captures as much information describing a table and its fields as possible directly from the SWPM database. That information is stored in Paradox tables where it can be supplemented with manually entered descriptions of each item for documentation purposes. The result of this function is a report that serves as Table 2.1 of the Technical Reference Manual.

C6.2 DESCRIPTIONS AND LOCATIONS OF FILES

C6.2.1 Procedures and Scripts

TABDOC() -	Procedure that prompts for a table name to include in the documentation table, TAB. It checks for existence of the table and then makes sure it has not already been documented. If a directory name is given instead of a table, then a list of tables within the directory is displayed for selection. Field information is also captured and placed in TABFLD. Included in LIB\UTIL.LIB.
util\TABDOC.SC -	Source script for TABDOC(). Compiled by LIB\UTIL.SC into library LIB\UTIL.LIB.
doc\tables\BLNKFLDS.SC -	Query used to display rows in TABFLD that have no descriptions.
doc\tables\FLDDESC.SC -	"Changeto" query used to define descriptions for a number of common fields.
doc\tables\FLDDESC2.SC -	Similar to FLDDESC.SC, except it only changes descriptions that are blank.

C6.2.2 Tables and Related Objects

doc\tables\TAB.DB -	Table containing table names and descriptions.
doc\tables\TABFLD.DB -	Table containing information about fields, such as the table name in which they appear and their types and descriptions.
doc\tables\TAB.F -	Multi-table form used for entering descriptions for both tables and fields.
doc\tables\TABFLD.F -	Form imbedded in TAB.F.
doc\tables\TABFLD.R -	Report specification used to print Table 2.1 pages of the Technical Reference Manual.

C6.4 OPERATION

C6.4.1 Establish J:\SWPMDB91 as the working directory.

C6.4.2 Execute procedure TABDOC() using the **Miniscript** selection from the PAL menu.

C6.4.3 Enter a directory name and select a table from the list displayed, or type in the directory and table name combination directly. Wait until the message "Addition of 'table name' complete." appears. Then supply another table name or press [Esc] to quit.

SECTION 7 - UPLOAD/DOWNLOAD PROCESSING AND QA

C7.1 DESCRIPTION

Upload and download processing allow the movement of SWPM data between network disk drives and local disks in PCs connected to the network. The purpose of this facility is to allow users to copy a reference database to their own PCs to get the performance benefit of using a local hard disk and to allow changes to the data while preserving the reference database. It also supports the practice of entering forecast data on a local machine and uploading batches of data to the network. When data are moved from local installations to the network, certain QA procedures are applied before the data become part of or replace the existing network reference database.

In addition to the movement of forecast data, the download portion of this facility also allows users to copy the SWPM database application itself. The creation of a runnable copy involves the movement of software and a number of tables of support data that are not user updatable but are needed by the application. This class of table includes the entire V\ subdirectory, the waste generator and forecast tables and other tables that support the menu system and Report Manager. A complete download is done, therefore, in three steps: forecast data, software, and "codes" data (support tables).

C7.2 DESCRIPTIONS AND LOCATIONS OF FILES

Location of files (unless otherwise specified):

J:\SWPMDB90\QA

C7.2.1 PAL Scripts

QALVL1.SC - executes QA review of uploaded data
util\DNLD.SC - defines procedure DNLD() preps for download, calls batch files
util\UPLOAD.SC - defines procedures Upload() and UpDnLog()

C7.2.2 Procedures

Dnld() - preps for download, calls DOS batch files
DnLd_Drive() - checks for readiness and space on target drive
Upload() - preps for and performs upload to network drive
UpDnLog() - records activities in log table d\UPDNLOG.DB

C7.2.3 Query Scripts

See QA\Q\ directory or process description section below

C7.2.4 Tables

The following are identical in structure to tables by the same names in the D\ subdirectory. These are tables that have been uploaded to the network from a local work station. Prior to uploading, the database administrator must manually all previous versions of the tables in the \SWPMUPLD\ directory.

\SWPMUPLD\CONT.DB	- container table
\SWPMUPLD\HCD.DB	- HCD table
\SWPMUPLD\PCD.DB	- PCD table
\SWPMUPLD\FOREVOL.DB	- forecast volume table
\SWPMUPLD\WG.DB	- waste generator table
\SWPMUPLD\NOTEPAD.DB	- notepad
\SWPMUPLD\WEIGHT.DB	- weight table

Other tables:

D\UPDNLOG.DB	- upload/download log table
QA\WORK\'name'.DB	- created only to record a QA problem - 'name' indicates type of problem and contents are problem items. All tables in this directory are deleted at the start of QA processing.

C7.2.5 DOS Batch Files

The following batch files perform the three components of the download process. They write over existing SWPM database files on the local work station. It is necessary that the \SWPMDB91 directory already exist on the designated target disk drive.

\SWPMDB91\DNLDSoft.BAT	- download application software
\SWPMDB91\DNLDData.BAT	- download forecast data
\SWPMDB91\DNLDCode.BAT	- download "codes" data

C7.3 PROCESS DESCRIPTIONS

C7.3.1 Download Processing

- 3.1.1 The user selects one of three download processes, **Software**, **Data**, or **Codes**.
- 3.1.2 The user designates a disk drive to receive the download via menu. This designation is made only once, immediately after the first selection is made in 3.1.1. After that, it is assumed that all other downloads go to the same place.
- 3.1.3 The drive chosen is selected for availability and free space by procedure DnLd_Drive(). As coded, it expects 2mb of free space or the procedure stops. This may not be appropriate in some cases, since the download process may be replacing existing data rather than occupying space that is currently free.

- 3.1.4 A number of checks are made prior to processing. The appropriate DOS batch file must be available and a directory on the target drive must exist.
- 3.1.5 If the user has chosen **Data** as the download process, an additional confirmation is required. This is the only one of the three download phases that is destructive to files that are user changeable.
- 3.1.6 The beginning of the process is logged. A row is written to table D\UPDNLOG.DB to record the event, who did it, and when.
- 3.1.7 The batch file is called with the disk drive and "SWPM" passed as parameters. It skips certain messages when the second parameter is used, otherwise a warning is issued. Under circumstances when the warning does appear, the batch file is not being run from within the SWPMDB application.
- 3.1.8 At the successful completion of the download, another entry is made to the log table to show that the process completed normally.

C7.3.2 Upload Processing

- 3.2.1 The user confirms via selecting **Begin** from a menu.
- 3.2.2 The availability of the network is verified by checking for the log table.
- 3.2.3 The user's current working drive/directory combination is checked. If the drive designation is "J:", the standard letter for the network installation, then an upload to the network is illogical and the process terminates with an error message.
- 3.2.4 The start of the upload process is noted in the log table.
- 3.2.5 The SWPM upload area, directory \SWPMUPLD, is checked. In order for the upload process to proceed, none of the tables to be uploaded can exist in this directory. This requirement is intended to avoid wiping out previous uploads that have yet to be processed by the database administrator.
- 3.2.6 Each table is uploaded with the Paradox Copy command. This ensures that the entire family is transferred during the process.
- 3.2.7 After all tables are copied, the completion of the process is logged.

C7.3.3 QA Processing

- 3.3.1 The presence of all uploaded tables is verified. If any are missing, processing terminates.
- 3.3.2 All tables are deleted from the QA\WORK\ directory.

- 3.3.3 Using query QA\Q\WG_MISS.SC, the incoming waste generator table is checked for rows that are not present in the network WG table. If any are found, a warning message appears and the missing WG names are stored in table QA\WORK\WG_MISS.
- 3.3.4 Using query QA\Q\WG_XTRA.SC, the incoming waste generator table is checked for rows that are in addition to those in the network WG table. If any are found, a warning message appears and the extra WG names are stored in table QA\WORK\WG_XTRA.
- 3.3.5 Incoming volume, container, HCD, PCD and weight tables are checked to verify that they contain only WG names that are present in the network WG table. The following queries are used:

QA\Q\WG_CONT.SC
QA\Q\WG_FORE.SC
QA\Q\WG_HCD.SC
QA\Q\WG_PCD.SC
QA\Q\WG_WT.SC

If any problems are found, the unrecognized WG names are written to tables with the same names as the queries, located in QA\WORK.

- 3.3.6 Incoming volume, container, HCD, PCD and weight tables are checked against V\SWCLass to verify that they contain only valid waste class names. The following queries are used:

QA\Q\WC_CONT.SC
QA\Q\WC_FORE.SC
QA\Q\WC_HCD.SC
QA\Q\WC_PCD.SC
QA\Q\WC_WT.SC

If any problems are found, data from the rows containing unrecognized waste classes are written to tables with the same names as the queries, located in QA\WORK.

- 3.3.7 PCD names used in incoming PCD, HCD and container tables are checked against V\SPCD. The following queries are used:

QA\Q\PCD_CONT.SC
QA\Q\PCD_HCD.SC
QA\Q\PCD_PCD.SC

If any problems are found, data from the rows containing unrecognized PCDs are written to tables with the same names as the queries, located in QA\WORK.

- 3.3.8 HCD names used in the incoming HCD table are checked against V\SHCD. The following query is used:

QA\Q\HCD_HCD.SC

If any problems are found, data from the rows containing unrecognized HCDs are written to tables with the same name as the query, located in QA\WORK.

- 3.3.9 Container names used in the incoming container table are checked against V\SCont. The following query is used:

QA\Q\CONT_CON.SC

If any problems are found, data from the rows containing unrecognized containers are written to tables with the same name as the query, located in QA\WORK.

- 3.3.10 Incoming container, HCD and PCD tables are checked to verify that distribution fractions sum to 1. The following queries are used:

QA\Q\SUM_CONT.SC

QA\Q\SUM_HCD.SC

QA\Q\SUM_PCD.SC

If any problems are found, data from the rows containing errors in distribution fractions are written to tables with the same names as the queries, located in QA\WORK.

- 3.3.11 Incoming volume, container, HCD, PCD and weight tables are checked for rows that do not logically connect to rows in other tables. The following queries are used:

QA\Q\ORPH_CON.SC

QA\Q\ORPH_FOR.SC

QA\Q\ORPH_HCD.SC

QA\Q\ORPH_PCD.SC

QA\Q\ORPH_WTSC

If any orphan rows are found, data from the rows are written to tables with the same names as the queries, located in QA\WORK.

- 3.3.12 The incoming volume table is checked for the existence of WG forecasts that are not in the existing volume table D\FOREVOL.DB. If any are found, an informational message is displayed. The following queries are used:

QA\Q\NEW_FOR1.SC

QA\Q\NEW_FOR2.SC

QA\Q\NEW_FOR3.SC

If new forecasts are found, the WG names are written to table QA\WORK\NEW_FORE.DB.

- 3.3.13 The incoming volume table is checked against the existing volume table for WG forecasts that are missing. If any are in D\FOREVOL but not in \SWPMUPLD\FOREVOL, an informational message is displayed. The following query is used:

QA\QMIS_FORE.SC

If missing forecasts are detected, the WG names are written to table QA\WORK\MIS_FORE.DB.

C7.4 EXECUTION AND OPERATION OF DOWNLOAD, UPLOAD, AND QA PROCESSING

C7.4.1 Download Execution and Operation

The download process is selectable from the SWPM database main menu by choosing **Up/Download**. This selection is included in the MAIN menu group in the menu table. Then **Download** is chosen from the next menu. This selection is part of the Upload menu group. One additional menu, from which one of three download processes is selected, is coded into Dnld().

Operating instructions are included in the User's Guide.

C7.4.2 Upload Execution and Operation

The upload process is selectable from the SWPM database main menu by choosing **Up/Download**. This selection is included in the MAIN menu group in the menu table. Then **Upload** is chosen from the next menu. This selection is part of the Upload menu group. One additional menu, from which the user confirms the intention to perform an upload, coded into UpLoad().

Operating instructions are included in the user's manual.

C7.4.3 QA Execution and Operation

QA processing is initiated from the Paradox menu by playing script QA\QALVL1.SC. Prior to its operation, the \SWPMUPLD area must have been cleared of uploaded tables, and the user should have executed an upload. No intervention is required during the QA process.

When QA processing is complete, messages will reveal any problems detected. Each problem occurrence will result in a table entry in the QA\WORK\ directory.

These problems must be resolved before proceeding.

C7.5 PASSING DATA INTO THE REFERENCE DATABASE

C7.5.1 Back up the reference database, i.e., the entire J:\SWPMDB91 directory tree.

C7.5.2 Determine the type of upload - incremental or complete

If a missing forecast message appeared during QA script operation, the uploaded data may be incremental. Forecasts should not have been deleted locally, so the incoming data may be intended to be added to rather than to replace the network database.

C7.5.3

If the upload is to be treated as incremental - to be added to existing network data, perform the following steps using the TOOLS MORE ADD menu selections from the Paradox menu:

- 5.3.1 Add the contents of each of the following tables to its counterpart in the D\ directory:

\SWPMUPLD\Forevol
\SWPMUPLD\PCD
\SWPMUPLD\Cont
\SWPMUPLD\HCD
\SWPMUPLD\Weight

- 5.3.2 Add the contents of \SWPMUPLD\notepad to D\notepad similar to above. In this case, check for duplicates by querying on D\notepad to see if the Answer table has fewer records (Paradox only includes one occurrence of duplicates). If the Answer table is smaller, empty D\notepad and add Answer to it.
- 5.3.3 Updates to the WG table must be handled on a case-by-case basis. It may be appropriate to replace the network version of D\WG if the local user has updated fields in existing rows and no updates to the network copy have been made that will be lost.

C7.5.4 If the upload is to be treated as a complete database, to be used to replace existing network data, perform the following steps using the TOOLS COPY TABLE menu selections from the Paradox menu:

- 5.4.1 Copy each of the following tables to its counterpart in the D\ directory:

\SWPMUPLD\Forevol
\SWPMUPLD\PCD
\SWPMUPLD\Cont
\SWPMUPLD\HCD
\SWPMUPLD\Weight

- 5.4.2 The notepad table should be treated as in Section 5.3.2 above, to allow for updates that may have been made in both the network and local versions.
- 5.4.3 See Section 5.3.3 above for suggestions on how to process the incoming WG table.
- 5.5 Do not delete tables in the \SWPMUPLD directory until immediately before the next upload. They serve as a backup of the most recent upload and will prevent further uploads by users until the database administrator is ready for them.

SECTION 8 - FORECAST DATA ENTRY

C8.1 DESCRIPTION

Forecast data entry in SWPM is accomplished using the extended facilities provided by the Paradox Data Entry Toolkit (DET) and procedures written specifically for each table. General explanations of DET usage are beyond the scope of this document, but the process of conducting and controlling data entry as applied to SWPM will be explained.

There are a number of objectives addressed in the way data entry procedures are designed and implemented in SWPM:

- Data integrity - volume, percentage and weight data must be logically consistent with each other and internally consistent
- Standardization of terms, order of presentation, abbreviations, etc. - lists of each type of term (waste classes, waste generator names, physical content descriptors, etc.) are provided and their usage is enforced
- Ease of use - those responsible for data entry should not have to know the names of tables, scripts, procedures and other Paradox objects
- Ease of maintenance - an attempt was made to implement processes consistently and use nonspecific parameter-driven procedures where it was advantageous to do so.

C8.2 DESCRIPTIONS AND LOCATIONS OF FILES

C8.2.1 Procedures and Scripts

Data entry process procedures - These procedures typically extract data for a previously specified waste generator from the permanent table, where it is kept in normal form, into a temporary table resembling a spreadsheet in format. For volume data the user is restricted to valid waste classes. For weight and PCD data, the user may only enter data for waste classes that have non-zero volumes coming from the waste generator in question. For HCD and container data, the user may provide values only for waste class/PCD combinations for which non-zero data were previously entered. When percentage data are involved (PCD, HCD and container), the requirement that data sum to 100% is enforced.

These procedures invoke DET facilities using the DO WAIT command.

Upon completion of data entry and successful validation of the data, any existing rows for the current waste generator/forecast combination are deleted from the permanent table and data from the temporary table are added back to the permanent table.

Data entry process procedure names and source scripts -

	<u>Procedure</u>	<u>Source</u>
Forecast volumes:	FOREVOL_DE()	pal\FOREVOL.SC
PCDs:	PCD_DE()	pal\PCD.SC
HCDs:	HCD_DE()	pal\HCD.SC
Containers:	Cont_DE()	pal\CONT.SC
Weight:	Weight_DE()	pal\WEIGHT.SC

Library: lib\FOREDE.LIB

Field arrival procedures - These procedures are invoked by DET as user moves to a new field in data entry table. They generally serve to total up data for the current column or row and display the totals at the top of the screen. They also show the current WG/forecast, row label and/or column name, since some of this information will otherwise scroll off the screen.

Field arrival procedure names and source scripts -

	<u>Procedure</u>	<u>Source</u>
Forecast volumes:	ForeVol_NewFld()	pal\FOREVOL.SC
PCDs:	PCD_NewFld()	pal\PCD.SC
HCDs:	HCD_NewFld()	pal\HCD.SC
Containers:	Cont_NewFld()	pal\CONT.SC
Weight:	Weight_NewFld()	pal\WEIGHT.SC

Library: lib\FOREDE.LIB

Field departure procedure - This procedure is called when departing a field. It rounds the field to three decimal places. It also may be used in other instances outside of DET-controlled processes where rounding is needed.

Field departure procedure name and source script -

	<u>Procedure</u>	<u>Source</u>
All forecast data:	RndPer()	util\RNDPER.SC

Library: lib\UTIL.LIB

Keystroke procedure - This procedure is invoked for every keystroke during all forecast data entry processes performed under the control of the DET. It is used to block entry in certain columns and check for special keystrokes, such as the notepad hotkey.

Keystroke procedure name and source script -

	<u>Procedure</u>	<u>Source</u>
All forecast data:	KeyBlk()	util\KEYBLK.SC

Library: lib\UTIL.LIB

DET definition procedures - These procedures provide all the definitions that the DET needs to control data entry. They include the table name to which data will be entered and various procedures to be invoked for arrivals, departures, keystrokes, and so forth. They also map all keys to codes that indicate whether and how each key can be used. These procedures are written by the DET using information supplied interactively while using TKMenu.

Warning: DET definition procedures are usually created with complete path names associated with tables and files referenced in the procedure. To maintain portability, the drive and application directory names should be removed from these paths before the procedures are compiled and written to the library file.

DET definition procedure names and source scripts -

	<u>Procedure</u>	<u>Source</u>
Forecast volumes:	TKEForeVol_None()	work\EFOREVOL.SC
PCDs:	TKEpcd_None()	work\EPCD.SC
HCDs:	TKEhcd_None()	work\EHCD.SC
Containers:	TKEcont_None()	work\ECONT.SC
Weight:	TKEweight_None()	work\EWEIGHT.SC

Library: lib\FOREDE.LIB

DET "Borrow" files - These files are created by TKMenu and are referenced within the DET definition script created during the same process. They are of use when the definition procedure is compiled but apparently not used at other times. Even though a borrow file may exist for a given table, a new one is generated each time TKMenu is used.

Borrow file names -

All tables: BORROW'n'.SC, where 'n' is a serial number one larger than used in existing borrow file names.

C8.2.2 Tables and Related Objects

work\EFOREVOL.DB - work table to which volume data are entered
work\EPCD.DB - work table to which PCD data are entered
work\EHCD.DB - work table to which HCD data are entered
work\ECONT.DB - work table to which container data are entered
work\EWEIGHT.DB - work table to which weight data are entered

d\FORVOL.DB	- permanent table containing volume data
d\PCD.DB	- permanent table containing PCD data
d\HCD.DB	- permanent table containing HCD data
d\CONT.DB	- permanent table containing container data
d\WEIGHT.DB	- permanent table containing weight data

C8.3 IMPLEMENTATION

Complete instructions on DET usage, especially TKMenu, are left to the Paradox PAL manual. The following is an outline of steps necessary to add a DET process to SWPM. Maintenance of existing processes will necessarily involve skipping some of the steps listed.

- 3.1 Create the table to which data will be entered
- 3.2 Develop new or identify existing procedures to be used for arrivals, departures, and keystrokes.
- 3.3 Develop the procedure that will be executed to perform the data entry process by invoking the DET Do Wait command.
- 3.4 Execute the TKMenu script in the DET and use the **SetUpDoWait** selection to define the process.
- 3.5 Modify the DET definition procedure to remove complete path names that it contains.
- 3.6 Compile the DET definition procedure and the procedure created in 3.3 above into a library that will be accessible by the application.
- 3.7 Try it.

SECTION 9 - MENU SYSTEM

C9.1 DESCRIPTION

To make the application menu easy to maintain, the menu structure is defined by data in a table. A procedure is available to read the table, find the correct group of menu items, display them in the proper order and take whatever action is defined for the selection chosen by the user. The table also has an associated report to create a part of the documentation of the SWPM database application.

C9.2 DESCRIPTIONS AND LOCATIONS OF FILES

C9.2.1 PAL Scripts and Procedures

MENUEXE() - the procedure that uses the menu table to display user options in the familiar Paradox menu style

menu\MENU.SC - source script for procedure MENUEXE()

C9.2.2 Tables and Related Objects

menu\MENUOPT.DB - table containing the data that define the application menu structure

menu\MENUGRP.DB - a lookup table of valid menu group names

menu\MENUOPT.R - menu report for documentation

C9.3 ADDING AN ITEM TO THE APPLICATION MENU

- 3.1 Determine which menu the item should appear within. See the SWPM Menu Structure in Section 3.
- 3.2 Examine Table E9.1 at the end of this Section to determine the menu group name in which the new item belongs.
- 3.3 Insert a row in the menu table menu\MENUOPT, defining fields as follows:

Field Name	Contents
Menu Abbrev	The name of the group to which this item belongs. This controls which menu the item appears in. This field is linked to menu\MENUGRP and its contents must appear in that table.
Menu Opt #	The order in which this item appears on its menu.
Menu Opt	The name to appear on the menu.
Menu Desc	The description of the menu item to appear on the second line of the menu bar.
Menu Proc	The action to be taken when the item is selected. It can be a command, script name or procedure.
Menu Report Order	The order in which this group appears on the report. Must be the same for all members of the group. This could be supplied by a field in menu\MENUGRP but was implemented this way prior to the creation of the lookup table.

Table C9.1. SWPM Database Application Menu Options

Option #	Option Title	Option Description / Procedure or Script Executed
Menu Group: (1) MAIN		
1	Forecast	Maintain FY-1991 Forecast Data MenuExe("FORECAST", GV_SysNam, Menu_Desc[i], "", TRUE)
2	TSD	Maintain Treatment / Storage / Disposal Data MenuExe("TSD", GV_SysNam, Menu_Desc[i], "", TRUE)
4	RDL	Produce Reference Data Library Files WriteRDL()
5	Up/Download	Upload forecast or Download data , codes and software MenuExe("UPLOAD",GV_SysNam,"UPLOAD/DOWNLOAD PROCESSING","", TRUE)
8	Codes	Maintain Codes MenuExe("CODES", GV_SysNam, Menu_Desc[i], "", TRUE)
9	Report_Mgr	SWPM Report Manager - use to select reports to process / print Rptmgr()
10	Action	Action Item List Edit and Reports action()

Option #	Option Title	Option Description / Procedure or Script Executed
Menu Group: (2) FORECAST		
1	IDFore	Identify Forecast / Period To Be Maintained ForeEdit()
2	ForeVol	Maintain Waste Volumes By Waste Class and Year ForeVol_DE (WGAbbrev, ScAbbrev)
4	PCD	Maintain Waste Percentages By PCD and Waste Class PCD_DE (WGAbbrev, ScAbbrev)
5	HCD	Maintain Waste Percentages By PCD and HCD HCD_DE (WGAbbrev, ScAbbrev)
6	Cont	Maintain Waste Percentages By PCD and Container Type Cont_DE (WGAbbrev, ScAbbrev)

Table C9.1. (Contd)

Option #	Option Title	Option Description / Procedure or Script Executed
7	Wt	Maintain Waste Weights By Waste Class and Year Class Weight_DE (WGAbbrev, ScAbbrev)
8	DataVal	Produce Reports for Data Validation and Reporting to WGs MenuExe("DATAVAL", GV_SysNam, Menu_Desc[I], "", TRUE)

Option #	Option Title	Option Description / Procedure or Script Executed
----------	--------------	---

Menu Group: (3) TSD

1	Oper	Maintain Operation Attributes TSDEdit(GV_Oper)
2	Dist_F	Maintain Waste Generator Distribution Fractions TSDEdit(GV_Distf)
3	OperFlow	Maintain Operation Flow (Treatment Streams) TSDEdit(GV_OperFlow)
4	OperCap	Maintain Operation Capacities TSDEdit(GV_Opercap)

Option #	Option Title	Option Description / Procedure or Script Executed
----------	--------------	---

Menu Group: (4) UPLOAD

1	Upload	Upload forecast data to the network Upload()
2	Download	Download - select data, codes or software DnLd()

Table C9.1. (Contd)

<u>Option #</u>	<u>Option Title</u>	<u>Option Description / Procedure or Script Executed</u>
Menu Group: (5) CODES		
1	WG	Maintain Waste Generator Attributes FeaEdit("Waste Generator", GV_WG , "WG Abbrev")
2	WClass	WClass, WCat, TSD_WClass Tables MenuExe("WCLASS", GV_SysNam, "Maintain Waste Class Codes", "", TRUE)
3	Types	PCD, HCD, Cont Type Lists MenuExe("TYPES", GV_SysNam, "Maintain Type Tables", "", TRUE)
4	Groups	WG_Group, WG_Class, PCD, HCD, Cont Group tables MenuExe("GROUPS", GV_SysNam, "Maintain Group Tables", "", TRUE)
5	Scenario	Maintain the Scenario table FeaEdit("Scenarios", GV_SCENARIO, "Scenario Abbrev")
6	Forecast	Maintain the Forecast table (WG+Scenarios) FeaEdit("Forecasts", GV_FORECAST, "WG Abbrev")
7	Dictionary	Maintain SWPM dictionary dictedit()

<u>Option #</u>	<u>Option Title</u>	<u>Option Description / Procedure or Script Executed</u>
Menu Group: (6) DATAVAL		
1	A_Packet	Print Packet A - Low Level Waste Classes play "dv\\DATPUKEA"
2	B_Packet	Print Packet B - Low Level Mixed and Hazardous Waste Classes play "dv\\DATPUKEB"
3	C_Packet	Print Packet C - TRU Waste Class play "dv\\DATPUKEC"
4	D_Packet	Print Packet D - TRU Mixed Waste Class play "dv\\DATPUKED"
5	Every_One	Every last one of the suckers play "dv\\pukeall"

Table C9.1. (Contd)

<u>Option #</u>	<u>Option Title</u>	<u>Option Description / Procedure or Script Executed</u>
---------------------	---------------------	--

Menu Group: (7) WCLASS

1	WClass	Maintain the Waste Class feature table FeaEdit("Waste Class", GV_\$WClass , "WClass Abbrev")
2	WCat	Maintain the Waste Category feature table FeaEdit("Waste Category", GV_\$WCat , "WCat Abbrev")
3	TSD_WClass	Maintain the TSD Waste Class feature table FeaEdit("TSD Waste Class", GV_\$WClass , "WClass Abbrev")

<u>Option #</u>	<u>Option Title</u>	<u>Option Description / Procedure or Script Executed</u>
---------------------	---------------------	--

Menu Group: (8) TYPES

1	PCD	Maintain the PCD Types table FeaEdit("PCD Types" , GV_\$PCD , "PCD Abbrev")
2	HCD	Maintain the HCD Types table FeaEdit("HCD Types" , GV_\$HCD , "HCD Abbrev")
3	Cont	Maintain the Container Types table FeaEdit("Container Types", GV_\$Cont , "Cont Abbrev")

<u>Option #</u>	<u>Option Title</u>	<u>Option Description / Procedure or Script Executed</u>
---------------------	---------------------	--

Menu Group: (9) GROUPS

1	WG_Group	Maintain the Waste Generator Group table FeaEdit("WG Groups" , GV_\$WGGroup, "WG Group Abbrev")
2	WG_Class	Maintain the Waste Generator Class table FeaEdit("WG Classes" , GV_\$WGClass, "WGClass Abbrev")
3	PCD	Maintain the PCD Group table FeaEdit("PCD Groups" , GV_\$PCDgrp, "PCD Group Abbrev")

Table C9.1. (Contd)

Option #	Option Title	Option Description / Procedure or Script Executed
4	HCD	Maintain the HCD Group table FeaEdit("HCD Groups" , GV_\$HCDgrp, "HCD Group Abbrev")
5	Cont	Maintain the Container Group table FeaEdit("Container Groups", GV_\$Contgrp, "Cont Group Abbrev")
6	WCat	Maintain the Waste Category Group table FeaEdit("Waste Category Groups", GV_\$Wcatgrp, "WCat Group")

Option #	Option Title	Option Description / Procedure or Script Executed
-------------	--------------	---

Menu Group: (10) FOREEDMENU

1	Save[F2]	Save updates to database, return to editing retval = "F2" MChoice = "Esc"
2	Leave[Esc]	Leave forecast maintenance, return to previous menu retval = "Esc" MChoice = "Esc"
3	Create[Ins]	Create a new forecast retval = "Ins" MChoice = "Esc"
4	Delete[Del]	Delete the currently displayed forecast retval = "Del" MChoice = "Esc"
5	Report[Alt-F7]	Print the Forecast Inventory report retval = "F37" MChoice = "Esc"

SECTION 10 - SWPM STARTUP SCRIPT

C10.1 DESCRIPTION

To accommodate the three SWPM database applications (Version 1.1 for 1989, Version 1.2 for 1990, and Version 1.3 for 1991), a simple script named SWPM.SC was written to let the user choose which version to run. This script is identical for each application, except for which version serves as the default selection. The subject of this document is the version-specific script that is played by the SWPM.SC when the user selects the 1991 version of the database.

C10.2 NAMES AND LOCATIONS OF FILES

Initial script: J:\SWPMDB91\SWPM.SC

Application startup script: J:\SWPMDB91\PAL\STARTSWP.SC

C10.3 TASKS PERFORMED AT APPLICATION STARTUP

- 2.1 The workspace, variables and procedures are all cleared.
- 2.2 The version of Paradox is checked. Since the 1991 SWPM application contains features not available in previous Paradox versions, release 3.5 is required.
- 2.3 The user is prompted for a password. The response is checked against the volume table in the database to see if it is a valid password. The script RETURNS if it is not.
- 2.4 The identity of the drive on which the application is being run is checked. If it is "J:", then variable **rptsrc** is defined as "Official", otherwise it is set to "Unofficial". Another variable, **GV_where_am_I** is also set at this time to indicate on various screens whether the network database or a local copy is in use.
- 2.5 The notepad hotkey is established by tying procedure **NOTEPAD()** to the Ctrl N key.
- 2.6 Library access is established by defining variable **AutoLib** to contain a list of library files.
- 2.7 A number of other variables are defined that generally name tables so that they need not be hard coded in the application. Due to inconsistent coding, some table name references in the application are literal, however.
- 2.8 The data entry toolkit library is defined via variable **TKLibName**.
- 2.9 The application is executed by invoking the menu procedure **MENUEXE** referencing the MAIN menu group.

SECTION 11 - DEVELOPMENT TOOLS

C11.1 GENERAL DESCRIPTION OF SWPM TOOLS

Tools are software programs, procedures, scripts, etc., that are designed to help the developer perform some task better or quicker. Some of Paradox's features, notably in forms and reports design, require some tedious repetition of actions that can be automated somewhat. Generally, the tools are not polished products with well laid out user interfaces, error checking or recovery, or other refinements. These tools are intended to be used by a developer who has some experience with Paradox and has learned what to expect from each tool procedure. The following sections provide summary descriptions of the tools and show where the files containing the program code are located. It is necessary to study the code to fully understand what to expect when the tools are executed.

C11.2 DETAIL RESIZING TOOL

This tool resizes numeric fields in the table band of a Paradox report. It prompts for the number of digits to add and how many fields in the table band to process. It may be necessary to run the table band column resizing tool, TRSZ.SC, first, to make enough room for wider detail fields.

File name: tools\DETRSZ.SC

C11.3 GROUP SUMMARY FIELD TOOL

This tool adds group total fields to group footers in a report. It requires two blank fields in each group footer. It will process as many group footers as it finds, allowing for multiple subtotal breaks to be defined in one pass. It usually ends without error when it comes to the end of a report, but it will abort when it encounters non-numeric fields. It finds its way to the table band but may not always locate the line with the numeric fields in it. It is best to place the cursor on the right line of the table band before executing. It asks for the number of digits to use in the totals and places an underline of that length over the calculated field it inserts.

File name: tools\GRPSUM.SC

C11.4 PAGE SUMMARY FIELD TOOL

This tool adds page totals to the page footer section of a report. It runs continuously until it generates an error and the script aborts. It requires that the cursor be positioned on the table band line containing the numeric fields it is to total.

File name: tools\PAGESUM.SC

C11.5 REPORT SUMMARY FIELD TOOL

This tool functions identically to the page summary field tool, except that the calculated fields it inserts are placed in the report footer.

File name: tools\RPTSUM.SC

C11.6 TRANSFER KEYS DEFINITION TOOL

This tool defines two keys to serve as cut-and-paste operators to be used while editing tables. After running this script, the F11 key copies the contents of the current field to a variable named XXX and F12 clears the current field and places the contents of XXX into the field. Some Paradox user's initialization scripts also set certain other keys to do this.

File name: tools\TRFKEYS.SC

C11.7 TABLE BAND COLUMN RESIZE TOOL

This tool works similarly to the detail resizing tool, except that it changes the width of columns in a report. It is often necessary to use this tool first before running DETRSZ.SC.

File name: tools\TRSZ.SC

APPENDIX D

REFERENCE DATA LIBRARY PROCESS

APPENDIX D

REFERENCE DATA LIBRARY PROCESS

D.1 DESCRIPTION

This process produces files for input to SWPM. It is written entirely in PAL and can be executed from the SWPM database application menu. It is up to the user to move the output files where they are needed if modeling requirements dictate. Sections D.2 through D.4 that follow describe the process in detail. Section D.5 shows structures of tables used in this process that are not documented elsewhere. The contents of each output file are outlined in Section D.6 and are cross-referenced to process descriptions in Sections D.3 and D.4.

D.2 INITIALIZATION

D.2.1 WriteRDL() (located in library LIB\RDL) called by MenuExe().

2.1.1 A number of constants and switch variables are initialized:

inp, ttl, wrn, msg - used with STYLE command to set colors

delay - value used with SLEEP command to establish delays

CR - carriage return symbol

minyear - first year of simulation period

maxyear - final year of simulation period

metric - logical variable set to True for metric unit data - determines numeric format

2.1.2 Gets user input for output file name to be assigned to variable FNAME. Extensions ".RPS" and ".RPF" are added automatically. If either file exists in directory RDL, the user must okay overwriting or enter a new name. Blank name not accepted. The directory name "RDL" is added to the beginning of the file name.

2.1.3 Other user input is accepted:

tcostunits - Cost units, defaults to 0

tvolunits - Volume units, defaults to 0

2.1.4 The starting time of the process is captured in variable BTIME.

2.1.5 Defines variable OUTFILE as fname + ".RPS".

- 2.1.6 Calls WriteRPS(Outfile) - to produce reference projection summary (RPS) file - see Section D.3 below.
- 2.1.7 Defines variable Outfile as fname + ".RPF".
- 2.1.8 Calls WriteRPF(Outfile) - to produce reference projection summary (RPF) file - see Section D.4 below.
- 2.1.9 Records process completion time as ETIME.
- 2.1.10 Displays end of process message, including beginning time (BTIME) and ending time (ETIME).
- 2.1.11 WriteRDL() terminates, returning control to MenuExe().

D.3 WRITERPS() PROCEDURE - CALLED BY WRITERDL() IN 2.1.6.

Parameters: 1. Type: A
 Name: FileName
 Purpose: file name to write exported data to.

- 3.1 Play query q\RPS_1 - gets WG names and scenarios

Input: work\FVCONVX

Output: work\RPS1 (see Section D.5 for structure)

Fields: 1. Scenario, defined as:
 ' WG, ' + WG Abbrev + ', ' + WG Abbrev + '_ ' + Scenario Abbrev + ', ""

Example:

WG, AMES, AMES FD90, ""

- 2. Tree, defined as:

' ' + WG Abbrev + '_ ' + Scenario Abbrev

Example:

AMES FD90

- 3.2 Play query q\RPS_2 - gets operation data from OPER table

Input: dtsd\OPER

Output: work\RPS2 (see Section 5.0 for structure)

Fields: 1. Tree, defined as:
 ' ' + Oper Abbrev + '_ ' + TSD WC Abbrev + '_ ' + Oper Ref

Example:

DRUM UL CH ALPHA PRELIM2

2. Scenario, defined as:

' ' + TRT/DSP Flag + ', ' + Oper Abbrev + ' _ ' + TSD WC Abbrev + ', ' +
Oper Abbrev + ' _ ' + TSD WC Abbrev + ' _ ' + Oper Ref + ', ' + Oper Name
+ ''

Example:

TRT, DRUM UL CH ALPHA, DRUM UL CH ALPHA PRELIM2,
"UNLOAD DRUMS"

3.3 Play query "q\RPS_3" - gets TSD waste class data

Input: dtsd\OPER

Output: work\RPS3

Fields: 1. CLASSES, defined as:
' ' + TSD WC Abbrev

Example:

CH ALPHA

3.4 Play query "q\RPS_4" - gets operation type data from OPER table

Input: dtsd\OPER

Output: work\RPS4

Fields: 1. OPTYPE, defined as:
' ' + Oper Abbrev

Example:

DRUM UL

3.5 Prepare work\RPS table for TREE records.

3.5.1 Empty it.

3.5.2 Insert 1 row containing ":TREE" in the TEXT field as an identifier for the type of data in this section.

3.6 Play query "q\RPS_5" - inserts TREE column data from work\RPS1 and work\RPS2 data into work\RPS

Input: work\RPS1 - created in 3.1 above
work\RPS2 - created in 3.2 above

Output: work\RPS - receives inserts

Fields: 1. TEXT defined as:
content of TREE field in work\RPS1 - one new row is inserted for every row in work\RPS1, also content of TREE field in work\RPS2 - one new row is inserted for every row in work\RPS2.

Examples:

AMES FD90 - from work\RPS1

DRUM UL CH ALPHA PRELIM2 - from work\RPS2

3.7 Prepare work\RPS table for CLASSES records.

3.7.1 Insert an empty row.

3.7.2 Insert a row containing ":CLASSES" in the TEXT field.

3.8 Add all records from work\RPS3 to work\RPS.

3.9 Prepare work\RPS table for SCENARIO records.

3.9.1 Insert an empty row.

3.9.2 Insert a row containing ":SCENARIO" in the TEXT field.

3.10 Play query q\RPS_6 - inserts SCENARIO column data from work\RPS1 and work\RPS2 data into work\RPS

Input: work\RPS1
work\RPS2

Output: work\RPS - receives inserts

Fields: 1. TEXT defined as:

content of Scenario field in work\RPS1 - one new row is inserted for every row in work\RPS1, also content of SCENARIO field in work\RPS2 - one new row is inserted for every row in work\RPS2.

Examples:

WG, AMES, AMES FD90, "" - from work\RPS1

TRT, DRUM UL CH ALPHA, DRUM UL CH ALPHA PRELIM2, "UNLOAD
DRUMS" - from work\RPS2

3.11 Prepare work\RPS table for OPTYPE records.

3.11.1 Insert a blank line.

3.11.2 Insert a line containing ":OPTYPE" in the TEXT field.

3.12 Add all records from work\RPS4 to work\RPS.

3.13 Export data in work\RPS to file named in parameter FileName.

3.14 Clean up - delete work tables RPS1, RPS2, RPS3, and RPS4 and empty RPS.

D.4 WRITERPF() PROCEDURE - CALLED BY WRITERDL() IN 2.1.8 ABOVE.

Parameters: 1. Type: A
Name: FileName
Purpose: file name to write exported data to.

4.1 Create additional procedures - not stored to libraries, therefore available only for the duration of this procedure.

4.1.1 Procedure CrHead()

Parameters: 1. Type: A
Name: CFile
Purpose: Table name to query

2. Type: A
Name: CField
Purpose: field on query form to contain example

3. Type: A
Name: CType
Purpose: Text to include in HText field of inserted row of Answer table

Description:

This procedure creates a query form on table CFile. The form includes example "_A" in field CField (unselected) and a calculated field HText that contains " " + _A + ", ". After execution of the query, the Answer table is edited as follows:

- A row is inserted at the top of the table with " " + CType + "=" in the HText field.
- In the next row (previously the first, before the above insert), "(" is inserted into the HText field immediately before existing text.
- In the last row, ");" is added to end of the text in the HText field.

4.1.2 Procedure NumAbr()

Parameters: None

Description:

Do_it! is issued followed by a shift to Edit mode in whatever image is current in the workspace - none is specified here. A field called SLG is updated throughout the table via SCAN. In this update process, each row has the record number (converted to a string) plus a space added to the beginning of data in the SLG field. The edit is saved with Do_it!. A query form against Answer is then created. The List

field (unselected) is assigned example _A and SLG (unselected) is assigned _B. A calculated field, Text, is created as _A + " " + _B. After execution, the answer table is added to work\RPF.

4.2 Table work\RPF is emptied.

4.3 A header record is inserted into work\RPF table - "HEADER" is inserted into the Text column

Example:

- see example in Section 4.4.3 below.

4.4 Waste generator names are added to the table work\RPF in these steps:

4.4.1 Procedure CRHEAD() is called with parameters defined as "Work\FVCONVX", "WG Abbrev" and "ALL_WG".

4.4.2 CRHEAD() constructs and executes the query, it adds the section label, "ALL_WG" in this case, to the answer table and encloses the data in parentheses, followed by a semicolon.

4.4.3 The answer table is added to work\RPF.

Example:

```
HEADER
ALL_WG =
( AMES,
  ANL_E,
  .
  .
  WHC_WELL_DRL);
```

4.5 Treatment names are extracted and added to work\RPF in section labeled "TREATMENT":

4.5.1 A query form is created for dtsd\OPER.

4.5.2 Fields Oper Abbrev and TSD WC Abbrev are assigned examples _A and _B respectively, but not checked.

4.5.3 A calculated field, Trt, is defined as _A + "_" + _B.

4.5.4 The query is executed.

4.5.5 Procedure CrHead() is called with parameters defined as "Answer", "TRT" and "TREATMENT".

- 4.5.6 The answer table created by CrHead() is added to work\RPF, creating the treatment section.

Example:

```
TREATMENT =  
( ACID_NEUT_CH_MLIH,  
  ADV_DISP_A_CH_IH,  
  ADV_DISP_B_CH_MLIH,  
  .  
  WIPP_DRUMS_CH_ALPHA);
```

- 4.6 A section labeled "CATEGORY" is created using TSD waste class data:

- 4.6.1 Procedure CrHead() is called with parameters defined as "Dtsd\\Oper", "TSD WC Abbrev" and "CATEGORY".

- 4.6.2 The answer table created by CrHead() is added to work\RPF.

- 4.7 Certain variables are added to work\RPF:

- 4.7.1 Value assignments:

YEARS - range of years to be covered in simulation
COMP_LIST - type of simulation
ABBREV_TYPE - description of certain input data

- 4.7.2 Variable declarations:

ABBREV
LIB_COMMENT
COST_UNITS
VOL_UNITS

- 4.8 Play query q\RPF_1 to process WG variables - this query brings every possible combination of WG Abbrev and the WG variables.

Input: work\FVCONVX
MVD\VARDict

Output: added to work\RPF

Fields: 1. No field name given, defined as:
' ' + RPF Type + ' ' + WG Abbrev + ':' + Var Abbrev +
Var_Parms + ";

Example:

DOUBLE AMES:WG DIST F[CATEGORY,TREATMENT];

- 4.9 Play query q\RPF_2 to process treatment variables - every possible combination of Oper Abbrev and Var Abbrev applicable to treatments is created.
- Input: mvd\VARDICT
dtsd\OPER
- Output: added to work\RPF
- Fields: 1. No field name given, defined as:
' ' + RPF Type + ' ' + Oper Abbrev + ':' + Var Abbrev +
Var_Parms + ";
- Example:
DOUBLE
ACID NEUT CH MLIH:TRT CAPACITY[YEARS];
- 4.10 Add the end of header record to work\RPF:
- 4.10.1 Move to the end of the table and insert a row with "END_HEADER" in the Text field.
- 4.10.2 Move down once more. This will leave a blank row between the header section of the table and the data section.
- 4.11 Add preliminary records at the start of the data section:
- 4.11.1 Move down one row to force an insert and place "DATA" in the Text field. This is the label record showing the start of the data section of the table.
- 4.11.2 Insert three more rows:
- 4.11.2.1 "LIB_COMMENT" row showing current date, time and metric or standard mode.
- 4.11.2.2 "COST_UNITS" row including the value the user entered that was assigned to variable tcostunits.
- 4.11.2.3 "VOL_UNITS" row including the value the user entered that was assigned to variable tvolunits.
- 4.12 Begin the waste generator long and short names phase of RDL generation.
- 4.12.1 Move down twice to insert one blank line and begin another.
- 4.12.2 Enter the beginning of an assignment statement in which array values are defined for ABBREV.
- Example:
ABBREV[COMP_LIST,<RANK,SHORTNAME,LONGNAME,GROUP>]= {

4.13 Play query q\RPF_3 to process WG long and short names.

Input: work\FVCONVX
D\WG
Output: processed with procedure NumAbr() which adds data to work\RPF
Fields: 1. List, defined as:
' ' + WG Abbrev + ' '
2. SLG, defined as:
''' + WG Abbrev + ''' + ' ' + ''' + WG Name + ''' + ' ' +
''' + WGClass Abbrev + '''

Example: (after processing by NumAbr())

AMES 1 "AMES" "Ames Lab" "OFFSITE"

4.14 Play query q\RPF_4 to process treatment long and short names.

Input: dtstd\OPER
Output: processed with procedure NumAbr() which adds data to work\RPF
Fields: 1. List, defined as:
' ' + Oper Abbrev + ' ' + TSD WC Abbrev
2. SLG, defined as:
''' + Oper Abbrev + ' ' + TSD WC Abbrev + ''' + ' ' + '''
+ Oper Abbrev + ' ' + TSD WC Abbrev + ''' + ' ' + ''' +
OP_Cat_Abbrev + '''

Example: (after processing by NumAbr())

ACID NEUT CH MLIH 1 "ACID NEUT CH MLIH"
"ACID NEUT CH MLIH" "WRAP 2 CH M"

4.15 Play query q\RPF_5 to process waste class long and short names.

Input: dtstd\OPER
Output: processed with procedure NumAbr() which adds data to work\RPF
Fields: 1. List, defined as:
' ' + TSD WC Abbrev + ' '
2. SLG, defined as:
''' + TSD WC Abbrev + ''' + ''' + TSD WC Abbrev + '''

Example: (after processing by NumAbr())

CH ALPHA 1 "CH ALPHA" "CH ALPHA" ""

4.16 Finish long and short name section.

4.16.1 Move to the last row in the table and position in Text field.

4.16.2 Add "};" to complete data definition section. Save the table via Do_it! and clear the entire workspace.

4.17 Convert forecast summary data table from standard waste classes to TSD waste classes.

- 4.17.1 Copy table work\FVCONVX to CROSSTAB.
- 4.17.2 Create a query form on CROSSTAB. Define field WClass Abbrev as "_A, changeto _B".
- 4.17.3 Create a query form on table v\SWClass. Define field WClass Abbrev as "_A". Define field TSD WClass Abbrev as "_B".
- 4.17.4 Perform the changeto query using Do_it!.
- 4.18 Perform a group summary operation on table CROSSTAB to collect all like waste class rows.
 - 4.18.1 Create a query form on CROSSTAB. Define fields as:
 - 4.18.1.1 Check WG Abbrev, Scenario Abbrev and WClass Abbrev fields.
 - 4.18.1.2 Define "Calc sum as <field name>" for all year columns. The Held column is excluded at this point.
 - 4.18.1.3 Execute the query by issuing the Do_it! command.
 - 4.18.2 Sort the answer table on WG Abbrev and WClass Abbrev.
- 4.19 Add forecast volume data to work\RPF.
 - 4.19.1 Establish 3 string variables (HString1-3) that contain years separated by spaces. These strings will be inserted into the RPF file as column titles.
 - 4.19.2 View answer table created in 4.18 above.
 - 4.19.3 View work\RPF table and select Edit mode. Position at end of table and then cursor down to start a new row.
 - 4.19.4 Move to the answer table.
 - 4.19.5 Initialize variable OFORE_REF as null. This variable is used to keep track of the last WG Abbrev value. It will be checked against the current one to see if a new WG has been encountered.
 - 4.19.6 Initialize variable CLINE as screen row number. This variable will be used to position cursor on screen relative to its previous position when status messages are displayed.
 - 4.19.7 Begin a scan of the answer table.
 - 4.19.7.1 If OFORE_REF is not the same as the current WG Abbrev in the current row of the answer table:

- 4.19.7.1.1 Assign the current row number to REC1.
- 4.19.7.1.2 Move back to the work\RPF table.
- 4.19.7.1.3 If REC1 is not 1, then data for at least one WG was been written to work\RPF, so
- add "};" to the end of the current field in the current row
 - move the cursor down to create a new row and insert "
#ENDIF" in the current field of that row.
- 4.19.7.1.4 Clear the screen line that is one line before the last cursor position and show the WG we are now processing.
- 4.19.7.1.5 Add three initial rows for the new WG plus insert the three strings defined in 4.19.1 above on three additional rows. Insert one more row with "{" and move the cursor down to start another new row.

Example of 6 lines added in 4.19.7.1.5:

```
#IFDEF WHC_WELL_DRL_FD90
WHC_WELL_DRL:WG_DESCRIPTION = "";
WHC_WELL_DRL:WG_VOL[CATEGORY,
< 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001
2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012
2013 2014 2015 2016 2017 2018 2019 2020 2021 >] =
```

- 4.19.7.2 Move to the answer table. Define three variables, DString1-3, that include volume data from the current row of Answer.
- 4.19.7.3 Move to work\RPF. Define the current field as the content of the WClass Abbrev field in Answer.
- 4.19.7.4 Move the cursor down to start a new row and insert some blank padding and the content of DString1. Repeat this step for DString2 and DString3. This results in all yearly volume data for a given WG and waste class (represented on one row in Answer) to be placed in four rows in work\RPF - one waste class header row and three data rows.

Example for rows created in section 4.19.7.4:

```
CH_L
520 520 520 520 520 520 0 0 ...
0 0 0 0 0 0 0 0 ...
0 0 0 0 0 0 0 0 ...
```

- 4.19.7.5 Move to the answer table. Assign the content of the WG Abbrev field to variable OFORE_REF.
- 4.19.7.6 Steps 4.19.7.1 through 4.19.7.5 are repeated for each row of the answer table.
- 4.19.8 Scanning of the answer table proceeds until end of the table.
- 4.19.9 Move to work\RPF. Insert another row by moving down. Define the current field in this row as " ";". Insert another row and define current field as "#ENDIF".
- 4.19.10 Complete the addition of volume information to work\RPF by saving the table with Do_it!. Clear the workspace.
- 4.20 Insert WG distribution fractions into work\RPF.
 - 4.20.1 View table dtsd\DIST_F.
 - 4.20.2 View and edit table work\RPF. Position at end and move down to begin a new row.
 - 4.20.3 Move to dtsd\DIST_F.
 - 4.20.4 Begin a scan of dtsd\DIST_F.
 - 4.20.4.1 Variable DetString1 is defined as " " + WG Abbrev + "WG:DIST_F[CATEGORY, TREATMENT,<>]={ " + TSD WC Abbrev + " " + Oper Abbrev + " " + TSD WC Abbrev + " " + the string equivalent of DIST_F + "};".
 - 4.20.4.2 Move to work\RPF.
 - 4.20.4.3 Define the current field as the content of variable DetString1.

Example:

WHC SS 272\WA:WG_DIST_F[CATEGORY,TREATMENT,<>]={CH L QA CH L .145};

- 4.20.4.4 Move down to begin a new row.
- 4.20.4.5 Move back to table dtsd\DIST_F.
- 4.20.5 Scanning of dtsd\DIST_F until the end of the table is reached.
- 4.20.6 Table dtsd\DIST_F is saved using the Do_it! command and the workspace is cleared.

- 4.21 Treatment capacity data are added to work\RPF.
- 4.21.1 View table dtstd\OPERCAP.
 - 4.21.2 Edit table work\RPF. Move to the end of the table. Cursor down. to begin a new row.
 - 4.21.3 Move to dtstd\DIST_F
 - 4.21.4 Assign 1 to j. This variable will be used to count the number of years of data retrieved from dtstd\OPERCAP. Data are written to work\RPF in groups of four years per row.
 - 4.21.5 Initialize OOPER as null. This variable will be used to hold the last Oper Abbrev value and will be used to detect when a new Oper_Abbrev is encountered.
 - 4.21.6 Initialize LINE as null. This variable will be used to contain the line of data constructed from multiple dtstd\OPERCAP rows.
 - 4.21.7 Initialize CLINE as the current row position of the display on the screen.
 - 4.21.8 Begin a scan of table dtstd\OPERCAP.
 - 4.21.8.1 If the content of OOPER is not the same as the Oper_Abbrev + WC fields, do the following:
 - 4.21.8.1.1 Set variable OPER_ABBREV equal to field Oper_Abbrev.
 - 4.21.8.1.2 Set variable WC to field WC.
 - 4.21.8.1.3 Set variable REC1 to the current record number of the table.
 - 4.21.8.1.4 If this is not the first line of dtstd\OPERCAP (REC1 is checked) then at least one OPER_ABBREV has already been processed, so finish it off:
 - Insert content of LINE.
 - Move down to make another row and insert " };"
 - Move down two lines, leaving a blank line and beginning a new one.
 - 4.21.8.1.5 Clear the next screen line and show the treatment being processed by displaying variable OPER_ABBREV.
 - 4.21.8.1.6 Define the current field of the new blank row of work\RPF with the following: " " + OPER_ABBREV + " _" + WC + ":TRT_CAPACITY[YEARS,<>]="

- 4.21.8.1.7 Move down to start a new line and insert " {". Move down to begin another new line.
- 4.21.8.1.8 Set variable J to 1.
- 4.21.8.1.9 Move to dtsd\OPERCAP.
- 4.21.8.1.10 Assign " " to LINE.
- 4.21.8.2 Assign LINE + formatted YEAR and CAPACITY fields to LINE.
- 4.21.8.3 If J = 4 then four rows of dtsd\OPERCAP data have been accumulated for the current OPER_ABBREV + WC combination. Write the accumulated data:
 - 4.21.8.3.1 Move to work\RPF.
 - 4.21.8.3.2 Insert the content of LINE in the current field.
 - 4.21.8.3.3 Move down to start a new row.
 - 4.21.8.3.4 Assign " " to LINE.
 - 4.21.8.3.5 Set J to 0.
 - 4.21.8.3.6 Move back to dtsd\OPERCAP.
- 4.21.8.4 Add 1 to J.
- 4.21.8.5 Define variable OOPER as fields OPER_ABBREV + WC.

Example of rows created sections 4.21.8:

```
SPECIAL_HNDL_RH_L:TRT_CAPACITY[YEARS,<>]=
{
  1991 1000000 1992 1000000 1993 1000000 1994 1000000
  1995 1000000 1996 1000000 1997 1000000 1998 1000000
  1999 1000000 2000 1000000 2001 1000000 2002 1000000
  2003 1000000 2004 1000000 2005 1000000 2006 1000000
  2007 1000000 2008 1000000 2009 1000000 2010 1000000
  2011 1000000 2012 1000000 2013 1000000 2014 1000000
  2015 1000000 2016 1000000 2017 1000000 2018 1000000
  2019 1000000 2020 1000000 2021 1000000
};
```

- 4.21.9 End of the scan loop. Repeat above steps for each row of dtsd\OPERCAP.
- 4.21.10 Move to work\RPF.

- 4.21.11 Define the current field with the content of LINE. This reads in whatever happened to be in LINE when the process ran out of rows of dtstd\OPERCAP.
- 4.21.12 Move down to add another row. Define the current field as " };". This finishes up the last section of data.
- 4.21.13 Save work\RPF via Do_it! and clear the workspace.
- 4.22 Treatment distribution fraction data are added to work\RPF.
 - 4.22.1 View table dtstd\OPERFLOW.
 - 4.22.2 Edit table work\RPF. Go to the end of the table and then down to create a new line.
 - 4.22.3 Move to dtstd\OPERFLOW.
 - 4.22.4 Begin a scan of table dtstd\OPERFLOW.
 - 4.22.4.1 Assign [flow fraction] to variable TMPVAL.
 - 4.22.4.2 If the string value of TMPVAL is null, set TMPVAL to "0".
 - 4.22.4.3 Assign " " + [oper abbrev] + "_" + [TSD WC Abbrev] + ":TRT_DIST_F[TREATMENT,<>]={ " + [next oper abbrev] + " " + [next wc abbrev] + " " + strval(TMPVAL) + "};" to variable STRING.
 - 4.22.4.4 Move to work\RPF.
 - 4.22.4.5 Insert the content of variable STRING into the current field.
- Example:
SR METAL BOX CH ALPHA:TRT_DIST_F[TREATMENT,<>]={CERT PKG CH ALPHA .17};
 - 4.22.4.6 Move down to start a new row.
 - 4.22.4.7 Move to dtstd\OPERFLOW.
- 4.22.5 End of scan loop. Perform the above steps for all rows of dtstd\OPERFLOW.
- 4.22.6 Save the updates in work\RPF via the Do_it! command and clear the workspace.
- 4.23 Add treatment rates and other data to work\RPF.
 - 4.23.1 View dtstd\OPER.

- 4.23.2 Edit work\RPF. Go to the end of the table and then move down to begin a new row.
- 4.23.3 Move to dttd\OPER.
- 4.23.4 Began a scan of table dttd\OPER.
 - 4.23.4.1 Assign [TSD WC Abbrev] to variable W'C.
 - 4.23.4.2 Assign [oper abbrev] + "_" + WC to variable TOPER.
 - 4.23.4.3 Assign to variable TSP a number spaces equal to 25 less the length TOPER.
 - 4.23.4.4 Assign to variable TMPRAT the string value of [TRT RATIO].
 - 4.23.4.5 If TMPRAT is null, assign "0" to it.
 - 4.23.4.6 Assign to variable TMPCOS the string value of [STOR COST].
 - 4.23.4.7 If TMPCOS is null, assign "0" to it.
 - 4.23.4.8 Assign to variable TMPOPR the string value of [OPER COST].
 - 4.23.4.9 If TMPOPR is null, assign "0" to it.
 - 4.23.4.10 If [TRT/DSP FLAG] contains "DP", set variable TMPVAL to 1, otherwise set TMPVAL to 0.
 - 4.23.4.11 Move to table work\RPF.
 - 4.23.4.12 Insert in the current field " " + TOPER + ":TRT_WSTCAT " + TSP + WC + ",".

Example:

WIPP DRUMS CH ALPHA:TRT_WSTCAT = CH_ALPHA;

- 4.23.4.13 Move down to begin a new row.
- 4.23.4.14 Insert in the current field " " + TOPER + ":TRT_RATIO " + TSP + TMPRAT + ","

Example:

WIPP DRUMS CH ALPHA:TRT_RATIO = 1;

- 4.23.4.15 Move down to begin a new row.

4.23.4.16 Insert in the current field " " + TOPER + ":TRT_STOR_RATE
" + TSP + TMPCOS + ";".

Example:

WIPP DRUMS CH ALPHA:TRT STOR_RATE = 0;

4.23.4.17 Move down to begin a new row.

4.23.4.18 Insert in the current field " " + TOPER + ":TRT_TREAT_RATE
" + TSP + TMPOPR + ";".

Example:

WIPP DRUMS CH ALPHA:TRT TREAT_RATE = 16;

4.23.4.19 Move down to begin a new row.

4.23.4.20 Insert in the current field " " + TOPER + ":TRT_IS_DISPOSAL"
+ TSP + TMPVAL + ";".

Example:

WIPP DRUMS CH ALPHA:TRT IS DISPOSAL = 1;

4.23.4.21 Move down to begin a new row.

4.23.4.22 Move to table dstd\OPER.

4.23.5 End of scan loop. Perform the above steps for all rows of dstd\OPER.

4.23.6 Move to table work\RPF.

4.23.7 Insert "END_DATA" into the current field.

4.23.8 Save table work\RPF using the Do_it! command.

4.24 Export the work\RPF table as an ASCII text file the name of which is specified by the content of variable FILENAME.

4.25 Cleanup - empty work\RPF.

D.5 WORK TABLE STRUCTURES

work\RPS1:

<u>Field Name</u>	<u>Field Type</u>
Scenario	A50
TREE	A28

work\RPS2:

<u>Field Name</u>	<u>Field Type</u>
TREE	A41
SCENARIO	A107

work\RPS3:

<u>Field Name</u>	<u>Field Type</u>
TREE	A41
SCENARIO	A107

work\RPS:

<u>Field Name</u>	<u>Field Type</u>
Text	A132

work\RPF:

<u>Field Name</u>	<u>Field Type</u>
Text	A132

NOTE: Structures for other tables referenced in this document are found in Table 2.1 of the Technical Reference Manual.

D.6 SUMMARIES OF TEXT FILE STRUCTURES

D6.1 Scenario file - *.RPS - created by procedure WRITERPS() by exporting temporary table work\RPS as ASCII text

6.1.1 TREE section - contents are:

- Waste generator abbreviation + scenario abbreviation name from forecast data table FVCONV
- Operation abbreviation + TSD waste class abbreviation + Operation reference from OPER table

See Sections 3.1, 3.2, 3.5, and 3.6 above.

6.1.2 CLASSES section - contents are:

- TSD Waste Class abbreviations from OPER table

See Sections 3.3, 3.7, and 3.8 above.

6.1.3 SCENARIO section - contents are:

- "WG" + waste generator abbreviation + scenario abbreviation from forecast data table FVCONVX
- Treatment/disposal flag (TRT or DP), operation abbreviation, TSD waste class abbreviation, operation abbreviation + TSD waste class abbreviation + operation reference, operation name - all from OPER table

See Sections 3.1, 3.2, 3.9, and 3.10 above.

6.1.4 OPTYPE section - contents are:

- Operation abbreviations from OPER table

See Sections 3.4, 3.11, and 3.12 above.

6.2 Forecast file - 'filename'.RPF - created by procedure WRITERPF() by exporting temporary table work\RPF as ASCII text

6.2.1 HEADER section - contents are:

- ALL_WG list defined as all waste generator abbreviations appearing in forecast table FVCONVX

See Section 4.4 above.

- TREATMENT list defined as all operation abbreviation + TSD waste class abbreviations appearing in the OPER table

See Section 4.5 above.

- CATEGORY list defined as all TSD waste class abbreviations appearing in the OPER table

See Section 4.6 above.

- Variable value assignments to three variables - hard coded

See Section 4.7.1 above.

- Variable declarations - hard coded

See Section 4.7.2 above.

- Array declarations - names consist of all combinations of waste generator abbreviations from FVCONVX and variable names (including parameters) from VARDICT

See Section 4.8 above.

- Array declarations - names consist of all combinations of operation abbreviations from OPER and variables (including parameters) from VARDICT that are applicable to treatment operations.

See Section 4.9 above.

6.2.2 DATA section - contents are:

- Three miscellaneous variable definitions - hard coded.

See Section 4.11.2 above.

- Waste generator short name/long name array is defined as waste generator abbreviation, a ranking number, the waste generator abbreviation (in quotes), the waste generator name (in quotes) and waste generator class (in quotes) - all from FVCONVX, except ranking number, which is assigned during processing

See Sections 4.12 and 4.13 above.

- Treatment operation short name/long name array is defined as operation abbreviation + TSD waste class abbreviation, a ranking number, operation abbreviation + TSD waste class abbreviation (in quotes, repeated once) and operation category abbreviation (in quotes) - all from OPER, except ranking number, which is assigned during processing

See Section 4.14 above.

- TSD waste class short name/long name array is defined as TSD waste class abbreviation, a ranking number, TSD waste class abbreviation (in quotes, repeated once) and one set of empty quotes) - all from OPER, except ranking number, which is assigned during processing

See Section 4.15 above.

- Forecast volume data - one section for each waste generator with subsections within for each TSD waste class - data for 30 years split into three rows - from FVCONVX

See Sections 4.17 through 4.19 above.

- Distribution fraction data arrays are defined as the waste generator abbreviation, the array name "WG:DIST_F", applicable parameter names, and a data definition consisting of TSD waste class abbreviation, operation abbreviation + TSD waste class abbreviation and the distribution fraction value - all from DIST_F

See Section 4.20 above.

- Treatment capacity data arrays are defined as operation abbreviation + TSD waste class abbreviation, "TRT_CAPACITY", applicable parameter names and capacity data by year with four years per row - from DIST_F and OPERCAP tables

See Section 4.21 above.

- Treatment distribution fraction arrays are defined as operation abbreviation, "TRT_DIST_F", applicable parameter names and data for next operation, waste class and the fraction value - from OPERFLOW table

See Section 4.22 above.

- Treatment rate data are defined in sets of rows each of which begins with an operation abbreviation + TSD waste class abbreviation followed by a variable name and an appropriate data value - from OPER table

See Section 4.23 above.

APPENDIX E

PROCEDURE LIBRARY DICTIONARY

APPENDIX E

PROCEDURE LIBRARY DICTIONARY

LIBRARY: \LIB\DETOOLS.LIB - This library contains Data Entry Toolkit procedures provided by Paradox. The library has been copied to the application library directory for convenience. Individual procedures are documented in the Data Entry Toolkit section of the Paradox PAL manual.

LIBRARY: \LIB\FEAEDIT.LIB - feature edit procedures - used for editing Codes type tables

FeaEdit() **Description:** Provides view and edit facility for table whose name is passed as a parameter. User's rights are checked and special handling is given to operations involving creation, deletion, and changing of key field via other procedures called by this procedure.

Parameters:

1. **Type:** A
Descriptive label of table to be shown as part of a Wait Table prompt
2. **Type:** A
Name of table to be edited
3. **Type:** A
Key field of table

Return: None

Application: SWPM Codes table maintenance

Scripts -

Source: PAL\FEAEDIT.SC
Compile: LIB\FEAEDIT.SC

FeaIns() **Description:** Called by FeaEdit() to handle inserts to the specified table. The user is prompted for a new feature. User's response becomes key to new table row. A check is made for a duplicate. If insert is successful, the cursor is positioned so that the other columns of the new row may be defined.

Parameters: 1. Type: A
Descriptive label of table to be shown as part of prompt for new feature

2. Type: A
Name of table to be edited

3. Type: A
Key field of table

Return: None

Application: SWPM Codes table maintenance

Scripts -

Source: PAL\FEAEDIT.SC

Compile: LIB\FEAEDIT.SC

FeaUpd()

Description: Called by FeaEdit() to handle updates of the key field in the specified table. The user must move to the row to be modified and is prompted for a new feature. A check is made for a duplicate. If the new key definition does not duplicate some existing one, the change is made. The procedure maintains referential integrity by changing other tables using the key value that was modified here.

Parameters: 1. Type: A
Name of table to be edited

2. Type: A
Key field of table

Return: None

Application: SWPM Codes table maintenance

Scripts -

Source: PAL\FEAEDIT.SC

Compile: LIB\FEAEDIT.SC

FeaDel()

Description: Called by FeaEdit() to handle the deletion of a row in the specified table. The user must move to the row to be deleted first. Checks are made for rows in other tables. If the key of the row to be deleted is also a key in certain other tables, the delete is not allowed.

Parameters: 1. Type: A
Name of table to be edited

2. Type: A
Key field of table

Return: None

Application: SWPM Codes table maintenance

Scripts -

Source: PAL\FEAEDIT.SC

Compile: LIB\FEAEDIT.SC

LIBRARY: \LIB\FOREDE.LIB - data entry procedures

CONT_DE()

Description: Extracts container data (if any) from d\CONT for the current WG/Scenario combination into a work table for use as a data entry/update area. Data entry toolkit procedures are called. Certain data validation checks are made before the user may exit. Data are returned to the original table.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -

Source: PAL\CONT.SC

Compile: LIB\FOREDE.SC

CONT_NewFld()

Description: Data entry toolkit procedure invoked whenever the cursor is moved to a new field during data entry. Maintains current row totals, prompts and sets blocking status for fields which cannot accept data.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\CONT.SC
Compile: LIB\FOREDE.SC

DATAVER()

Description: Extracts forecast data and builds report tables from which data verification reports are printed. See Data Verification Reports technical notes and User's Guide for additional documentation.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\DATAVER.SC
Compile: LIB\FOREDE.SC

DENORM()

Description: Normalizes data entry tables in a process that is the inverse of crosstabbing. The receiving table is first purged of all rows containing data for the current WG name and scenario. This process is used to return data to the original table after data entry or update is performed in a work table.

Parameters:

1. Type: A
The name of the table to be normalized.
2. Type: A
The name of an existing normal form table to receive the data.
3. Type: N
The number of "key" fields, i.e., those fields that define the rows.

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\FOREDE.SC
Compile: LIB\FOREDE.SC

DE_REP_INS()	<p>Description: Builds an insert query to add data for the current WG to table work\DE_REP for reporting purposes.</p> <p>Parameters: 1. Type: A The WG to be used as selection criterion in the insert query.</p> <p>Return: None</p> <p>Application: called by FORE_DE_REP()</p> <p>Scripts - Source: PAL\FOREDE.SC Compile: LIB\FOREDE.SC</p>
DV_RPT()	<p>Description: Writes a number of data verification reports to temporary text files and then sends them to the printer in batches.</p> <p>Parameters: 1. None</p> <p>Return: None</p> <p>Application: SWPM data verification reporting</p> <p>Scripts - Source: PAL\DV_RPT.SC Compile: LIB\FOREDE.SC</p>
FOREDE()	<p>Description: Establishes screen messages and invokes menu procedure to get a data entry process selection from the user.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: PAL\FOREDE.SC Compile: LIB\FOREDE.SC</p>

FOREEDIT()	<p>Description: Gets a WG/Scenario selection from the user prior to data entry or verification reporting. This is a mandatory step that defines WG and scenario variables that are used by other processes. Even though the procedure name and code comments imply otherwise, no editing is done within this procedure.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: PAL\FOREEDIT.SC Compile: LIB\FOREDE.SC</p>
FOREVAL()	<p>Description: Verifies the validity of a WG/Scenario combination by looking for it in the d\FORECAST table.</p> <p>Parameters: None</p> <p>Return: "True" if valid</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: PAL\FOREDE.SC Compile: LIB\FOREDE.SC</p>
FOREVOL_DE()	<p>Description: Extracts volume data (if any) from d\FOREVOL for the current WG/Scenario combination into a work table for use as a data entry/update area. Data entry toolkit procedures are called. Certain data validation checks are made before the user may exit. Data are returned to the original table.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: PAL\FOREVOL.SC Compile: LIB\FOREDE.SC</p>

FOREVOL_NewFld()	<p>Description: Data entry toolkit procedure invoked whenever the cursor is moved to a new field during data entry. Maintains current row totals, prompts and sets blocking status for fields which cannot accept data.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: PAL\FOREVOL.SC Compile: LIB\FOREDE.SC</p>
FORE_DE_REP()	<p>Description: Empties and refills forecast report table with current data by calling DE_REP_INS. Sends a report to the printer.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: ?</p> <p>Scripts - Source: PAL\FOREDE.SC Compile: LIB\FOREDE.SC</p>
GET_PERIOD_DATA()	<p>Description: Executes a query to retrieve data for a specified WG, scenario and forecast period.</p> <p>Parameters:</p> <ol style="list-style-type: none"> 1. Type: A Table to run query against. 2. Type: A WG name. 3. Type: A Scenario name. 4. Type: A Period (year, "Held", etc) <p>Return: Number of records in answer table.</p>

Application: ?

Scripts -

Source: PAL\FOREDE.SC

Compile: LIB\FOREDE.SC

HCD_DE()

Description: Extracts HCD data (if any) from d\HCD for the current WG/Scenario combination into a work table for use as a data entry/update area. Data entry toolkit procedures are called. Certain data validation checks are made before the user may exit. Data are returned to the original table.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -

Source: PAL\HCD.SC

Compile: LIB\FOREDE.SC

HCD_NewFld()

Description: Data entry toolkit procedure invoked whenever the cursor is moved to a new field during data entry. Maintains current row totals, prompts and sets blocking status for fields which cannot accept data.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -

Source: PAL\HCD.SC

Compile: LIB\FOREDE.SC

NOTES_A()	<p>Description: Invoked (commonly by ALT N) to capture notes for storage in d\NOTEPAD. This half of the process maintains the notes in an array that must be written to the notepad data table by NOTES_B. Immediate storage to the table was not possible since this procedure is called during data entry toolkit processes. Updating another table while using DET is not worth the coding effort and loss of performance. NOTES_SET() must be used first. See implementation notes in source code.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: UTIL\NOTES_A.SC Compile: LIB\FOREDE.SC</p>
NOTES_B()	<p>Description: This procedure must be called after exiting from a data entry toolkit process to store any notes made during the process via NOTES_A. Implementation notes in source code for NOTES_A include instructions on use of NOTES_B.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p> <p>Scripts - Source: UTIL\NOTES_B.SC Compile: LIB\FOREDE.SC</p>
NOTES_SET()	<p>Description: Establishes arrays for use by NOTES_A and NOTES_B in capturing notepad entries during data entry toolkit processes. See implementation notes in NOTES_A source code.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM data entry</p>

Scripts -
Source: UTIL\NOTES_SET.SC
Compile: LIB\FOREDE.SC

PCD_DE()

Description: Extracts container data (if any) from d\PCD for the current WG/Scenario combination into a work table for use as a data entry/update area. Data entry toolkit procedures are called. Certain data validation checks are made before the user may exit. Data are returned to the original table.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\PCD.SC
Compile: LIB\FOREDE.SC

PCD_NewFld()

Description: Data entry toolkit procedure invoked whenever the cursor is moved to a new field during data entry. Maintains current row totals, prompts and sets blocking status for fields which cannot accept data.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\PCD.SC
Compile: LIB\FOREDE.SC

TKECONT_NONE()

Description: Data entry toolkit procedure that defines arrival, departure and keystroke procedures for container data entry. It also establishes which keys are valid and invalid during data entry.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: WORK\ECNTSC
Compile: LIB\FORDE.SC

TKEFOREVOL_NONE() Description: Data entry toolkit procedure that defines arrival, departure and keystroke procedures for volume data entry. It also establishes which keys are valid and invalid during data entry.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: WORK\EFOREVOL.SC
Compile: LIB\FORDE.SC

TKEHCD_NONE() Description: Data entry toolkit procedure that defines arrival, departure and keystroke procedures for HCD data entry. It also establishes which keys are valid and invalid during data entry.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: WORK\EHCD.SC
Compile: LIB\FORDE.SC

TKEPCD_NONE() Description: Data entry toolkit procedure that defines arrival, departure and keystroke procedures for PCD data entry. It also establishes which keys are valid and invalid during data entry.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: WORK\EPCD.SC
Compile: LIB\FOREDE.SC

TKEWEIGHT_NONE() **Description:** Data entry toolkit procedure that defines arrival, departure and keystroke procedures for weight data entry. It also establishes which keys are valid and invalid during data entry.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: WORK\EWEIGHT.SC
Compile: LIB\FOREDE.SC

WEIGHT_DE() **Description:** Extracts container data (if any) from d\WEIGHT for the current WG/Scenario combination into a work table for use as a data entry/update area. Data entry toolkit procedures are called. Certain data validation checks are made before the user may exit. Data are returned to the original table.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\WEIGHT.SC
Compile: LIB\FOREDE.SC

WEIGHT_NewFld() **Description:** Data entry toolkit procedure invoked whenever the cursor is moved to a new field during data entry. Maintains current row totals, prompts and sets blocking status for fields which cannot accept data.

Parameters: None

Return: None

Application: SWPM data entry

Scripts -
Source: PAL\WEIGHT.SC
Compile: LIB\FOREDE.SC

LIBRARY: \LIB\RDL.LIB - Reference data library procedures - supports production of reference data library files for input to the model. See RDL technical notes in the appendix of the Technical Reference for more information about this process.

WRITERDL() Description: Initiates RDL process, calls WRITERPS() and WRITERPF().

Parameters: None

Return: None

Application: SWPM RDL

Scripts -
Source: PAL\WRITERDL.SC
Compile: LIB\RDL.SC

WRITERPF() Description: Compiles RPF data and exports to a text file.

Parameters: 1. Type: A
Name of file to export to.

Return: None

Application: SWPM RDL

Scripts -
Source: PAL\WRITERPF.SC
Compile: LIB\RDL.SC

WRITERPS() Description: Compiles RPS data and exports to a text file.

Parameters: 1. Type: A
Name of file to export to.

Return: None

Application: SWPM RDL

Scripts -
Source: PAL\WRITERPS.SC
Compile: LIB\RDL.SC

LIBRARY: \LIB\UTIL.LIB - misc procedures for use throughout the SWPM application

ACTION()	<p>Description: Action item list display and edit. See Action Item technical notes and the Action Item section in the User's Guide for additional documentation.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM database application</p> <p>Scripts - Source: UTIL\ACTION.SC Compile: LIB\UTIL.SC</p>
BEEPS()	<p>Description: Beeps three times. Used to notify user of end of a process.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: Various procedures and scripts</p> <p>Scripts - Source: UTIL\BEEPS.SC Compile: LIB\UTIL.SC</p>
BLNKZERO()	<p>Description: Converts zeros or small values to blanks in numeric columns of a specified table. Used for improved report appearance. If a small non-zero value is to be used as the threshold value for conversion to blank, it cannot exceed .1.</p> <p>Parameters: 1. Type: A Table name - including directory path</p> <p>2. Type: N The first column number to be inspected for the threshold value and changed to blank if it is less than or equal.</p>

3. Type: N

The number of columns to be inspected for the threshold value. If the range of columns defined by parameters 2 and 3 includes columns that are not of "N" types, these columns are not changed. They are counted as part of the number of columns to be examined for update, however. The procedure automatically compensates if this number is too large. In situations where all columns after the one specified as parameter 2 are to be processed, a large number (e.g., 100) may be used for convenience.

4. Type: N

The threshold value at or below which a conversion to blank is made. This allows a very small non-zero number to be blanked out as if it were zero. A maximum of .1 is enforced in the procedure, however.

Return: True if no problems were encountered. Returns False if table does not exist or starting column number is too large. On screen error messages are also displayed.

Application: Various table processing scripts

Scripts -

Source: UTIL\BLNKZERO.SC
Compile: UTIL\COMPILE.SC

DICTEDIT()

Description: Provides access to SWPM project dictionary table for editing, viewing and searching. Intended to be called as a result of a menu selection. See Technical Notes, Appendix C, Section 4, for more information.

Parameters: None

Return: None

Application: SWPM database application

Scripts -

Source: UTIL\DICTEDIT.SC
Compile: LIB\UTIL.SC

DNLD()	<p>Description: SWPM database application download process. This procedure allows downloading of data tables, data validation tables (codes) and application software (scripts, procedures and tables) to a local disk drive. See separate Technical Notes, Appendix C, Section 7, and the User's Guide for additional documentation.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM database application</p> <p>Scripts - Source: UTIL\DNLD.SC Compile: LIB\UTIL.SC</p>
DNLD_DRIVE()	<p>Description: Called by DNLD() to provide menu selection of destination drive for download. Also checks space and availability of selected drive. See technical notes for DNLD() for more information.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: SWPM database application</p> <p>Scripts - Source: UTIL\DNLD.SC Compile: LIB\UTIL.SC</p>
FILL_TBL()	<p>Description: Inserts normalized data into spreadsheet style format data entry tables. Similar to crosstab operation.</p> <p>Parameters: 1. Type: A The first field of the source table which is part of the key that defines unique occurrences of rows in the destination table. Additional row keys must appear immediately following the first row key. The column key and table value appear following the row keys.</p>

2. **Type: N**
The number of fields in the source table which uniquely defines records in the destination tables. These fields must appear consecutively after the field named in parameter 1. Acceptable values are 1 or 2 only.
3. A comma delimited list of column names which are valid for data entry. An asterisk means all columns are valid.
4. The name of the spreadsheet style data entry table to receive the data.

Return: None

Applications: Most SWPM data entry processes.

Scripts

Source: UTIL\FILLTBL.SC

Compile: LIB\UTIL.SC

GETSTR_LU()

Description: Accepts a string from the user and checks for its presence as a first field value in a lookup table.

- Parameters:**
1. **Type: A**
Text to be used as a prompt.
 2. **Type: A**
Data type of value to be accepted.
 3. **Type: A**
Name of lookup table.

Return: Value of string entered, of type specified by parameter 2.

Applications: ?

Scripts

Source: UTIL\GETSTR.SC

Compile: LIB\UTIL.SC

GETSTR_YN()

Description: Accepts a string from the user that must be either "Y" or "N".

- Parameters:**
1. **Type: A**
Text to be used as a prompt.

Return: Either a "Y" or "N", depending on user response.

Applications: ?

Scripts

Source: UTIL\GETSTR.SC

Compile: LIB\UTIL.SC

KEYBLK()

Description: Blocks data entry into a field of a table used with the data entry toolkit. Specify as a keystroke procedure for each field on which it may be used. Set the variable ZZDtaOK to FALSE to block entry.

Parameters: None, although this procedure checks value ZZDtaOK.

Return: Sets TKAccept to True or False

Applications: SWPM data entry processes that use the data entry toolkit

Scripts

Source: KEYBLK.SC

Compile: LIB\UTIL.SC

LINECTR

Description: Displays centered text on the screen line specified. Text is truncated if longer than 78 characters. Out-of-range line specification causes function to use line 11 of the display.

Parameters: 1. Type: A, up to 78 characters
Text to be displayed.

2. Type: N
Screen line number (0-23)

LOC_RESTORE()

Description: Restore the workspace location to a previously saved position. LOC_SAVE() must have been used to record data about location.

Parameters: None

Return: None

Applications: ?

Scripts

Source: UTIL\LOOKUP.SC
Compile: LIB\UTIL.SC

LOC_SAVE()

Description: Save the current location relative to the workspace. Assumes recovery will be made with LOC_RESTORE. Allows for multiple linked tables as well as a single table.

Parameters: None

Return: None - defines variables

Applications: ?

Scripts

Source: UTIL\LOOKUP.SC
Compile: LIB\UTIL.SC

LOC_sRESTORE()

Description: Restore the workspace location to a previously saved position. LOC_sSAVE() must have been used to record data about location.

Parameters: None

Return: None

Applications: Notes_b()

Scripts

Source: UTIL\LOC_RES.SC
Compile: LIB\UTIL.SC

LOC_sSAVE()

Description: Save the current location relative to the workspace. Assumes recovery will be made with LOC_sRESTORE. Works for a single table in workspace. Also assigns certain variables that Notepad2() uses to record the current table name, field name and field content.

Parameters: None

Return: None - defines variables

Applications: Notes_b()

Scripts

Source: UTIL\LOC_RES.SC

Compile: LIB\UTIL.SC

LOOKUP()

Description: Simulate the Paradox table lookup feature and allow edits. Begins by calling LOC_SAVE(), allowing a selection via WAIT TABLE and F2, then calls LOC_RESTORE. Returns the value in the second field of the lookup table.

Parameters: 1. **Type:** A
Name of lookup table.

Return: Value of second field of the row that the user selects in the table specified by the parameter.

Applications: Various

Scripts

Source: UTIL\LOOKUP.SC

Compile: LIB\UTIL.SC

MENUEXE()

Description: Provides a data-driven menu facility that allows menu content to be entirely determined by the contents of a table. See Technical Notes, Appendix C, Section 9, for additional documentation.

Parameters:

1. **Type:** A
Menu option name - the text appearing in the MENUOPT field of menu\MENU. This parameter establishes the group of options that are to appear as a single Paradox-style bar menu.
2. **Type:** A
The first title line of the menu screen - appears in central area of the screen.
3. **Type:** A
The second title line of the menu screen.
4. **Type:** A
The third (caption) line of the menu screen.
5. **Type:** logical
Determines whether border is shown - "False" for no border displayed.

Return: None

Application: SWPM database application

Scripts -

Source: MENU\MENU.SC

Compile: LIB\UTIL.SC

MOV_FLDS()

Description: Moves a specified number of fields from the source table to the destination table. Data from all records in the source table are moved to the destination.

- Parameters:**
1. **Type: A**
Name of the field in the current table which will be the first of a specified number of fields in each row to be transferred.
 2. **Type: A**
Name of destination table.
 3. **Type: A**
Name of first field in destination table that will receive data transferred from source.
 4. **Type: N**
Number of consecutive fields to be transferred from source table row to destination table row.

Return: None

Applications: ?

Scripts

Source: UTIL\MOVFLDS.SC

Compile: LIB\UTIL.SC

MSG()

Description: Displays a message at lower right of screen followed by instruction to press ENTER to continue.

- Parameters:**
1. **Type: A**
Text of message.

Return: Message text in lower right of screen, followed by prompt to press ENTER key and a pause induced by an ACCEPT statement. Current colors are overridden with white on red background.

Applications: Various

Scripts

Source: UTIL\MSG.SC

Compile: LIB\UTIL.SC

MSGCTR()

Description: Displays a message at the center of the screen. Unlike MSG(), the process that calls this procedure continues immediately with no user intervention needed. It uses the colors currently in effect.

Parameters: 1. Type: A
Text of message.

Return: Message text in center of screen.

Applications: Various

Scripts

Source: UTIL\MSG.SC

Compile: LIB\UTIL.SC

NOTEPAD()

Description: General purpose note-taking utility that captures information about the current table and field. Not intended to be used within WAIT TABLE function. See Notepad Technical Notes, Appendix C, Section 3, for additional documentation.

Parameters: None

Return: None

Application: Can be invoked as a miniscript or connected to a hotkey via SETKEY. Key 14 [Ctrl N] is recommended.

Scripts -

Source: UTIL\notepad.SC

Compile: LIB\UTIL.SC

Notepad2()	<p>Description: Similar to NOTEPAD() except that it is intended to be used within a WAIT TABLE section of another procedure or script. See Notepad Technical Notes, Appendix C, Section 3, for documentation. Also see source code comments for implementation information.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Application: Available from within certain SWPM table maintenance processes that do not use the data entry toolkit. Maintenance of codes tables is performed with this procedure.</p> <p>Scripts - Source: UTIL\notepad2.SC Compile: LIB\UTIL.SC</p>
PROTKEY()	<p>Description: Provides password protection to the key field of the ANSWER table</p> <p>Parameters: None</p> <p>Return: None</p> <p>Applications: ?</p> <p>Scripts Source: UTIL\PROTKEY.SC Compile: LIB\UTIL.SC</p>
QRYFULL()	<p>Description: Executes a query on a table and returns all rows and columns, duplicating specified table as ANSWER. Query itself is erased.</p> <p>Parameters: 1. Type: A Name of table to query.</p> <p>Return: ANSWER table in workspace</p> <p>Applications: ?</p> <p>Scripts Source: UTIL\QRYFULL.SC Compile: LIB\UTIL.SC</p>

RNDPER()	<p>Description: Rounds percentages to three decimal places. Call as a departure procedure for a field or to update the current field. Uses DE Toolkit features.</p> <p>Parameters: None - works on current field.</p> <p>Return: Replaces current field with rounded data</p> <p>Applications: Data entry processes</p> <p>Scripts</p> <p>Source: UTIL\RNDPER.SC</p> <p>Compile: LIB\UTIL.SC</p>
RPTMGR()	<p>Description: Provides menu selection of available reports. See Report Manager technical notes and the User's Guide for additional documentation.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Applications: Invoked from SWPM database application menu or via hotkey defined with SETKEY. Key -13 (Alt P) is recommended.</p> <p>Scripts</p> <p>Source: UTIL\RPTMGR.SC</p> <p>Compile: LIB\UTIL.SC</p>
RPTMSG()	<p>Description: Invoked by report manager when report processing is chosen for a report that comes directly from the source table rather with various intermediate stages. A message is displayed stating that no processing is required and printing proceeds immediately.</p> <p>Parameters: None</p> <p>Return: None</p> <p>Applications: SWPM database application Report Manager</p>

Scripts

Source: UTIL\RPTMGR.SC
Compile: LIB\UTIL.SC

RPTNA()

Description: Invoked by Report Manager when report processing is chosen for a report that is not yet available. Provides an informational message and avoids aborting the Report Manager when the report has been specified and added to the report table but not yet programmed.

Parameters: None

Return: None

Applications: SWPM database application Report Manager

Scripts

Source: UTIL\RPTMGR.SC
Compile: LIB\UTIL.SC

STORE_RPT()

Description: Prints Paradox report to text file.

- Parameters:
1. Type: A
Name of table to which the report is related
 2. Type: A
Report number of report desired. Values "R" and "R1" through "R14" are valid.
 3. Type: A
Output file to receive report. Extension must be omitted, Paradox default ".RPT" is used. Existing file by this name is written over without warning.

Return: None

Applications: Rptmgr(), Dataver()

Scripts

Source: UTIL\STOR_RPT.SC
Compile: LIB\UTIL.SC

TABDOC()

Description: Adds table and field names to tables in which these are documented. See Technical Notes, Appendix C, Section 6, for documentation of this feature.

Parameters: None

Return: None

Applications: Used in documentation phase only

Scripts

Source: UTIL\TABDOC.SC

Compile: LIB\UTIL.SC

TIMEDIFF()

Description: Calculates difference between times to show elapsed time. Return value format selectable by mode parameter. If either store or end time is null or blank, returned value is "99:99:99" or "999.9", depending on mode. If mode is invalid, "0" is returned.

Parameters:

1. **Type: A**
Starting time of timed period.
2. **Type: A**
Ending time of timed period.
3. **Type: N**
Mode selection. Set to 1 if elapsed time is to be returned in HH:MM:SS format. Set to 2 if MMM.M format is desired.

Return: Difference between times as string in format selected by third parameter. A return of 0 indicates an invalid mode was sent. A return value of all nines indicates a missing start or end time.

Applications: Rptmgr()

Scripts

Source: UTIL\TIMEDIFF.SC

Compile: LIB\UTIL.SC

TRIM()	<p>Description: Strips leading and trailing blanks from a string.</p> <p>Parameters: 1. Type: A The string to be trimmed.</p> <p>Return: Trimmed string sent via parameter</p> <p>Applications: ?</p> <p>Scripts Source: UTIL\TRIM.SC Compile: LIB\UTIL.SC</p>
TSDEdit()	<p>Description: Supports editing of TSD tables. May work for any table specified as parameter 1.</p> <p>Parameters: 1. A Name of table to edit.</p> <p>Return: None</p> <p>Application: Called from SWPM TSD maintenance menu</p> <p>Scripts - Source: PAL\TSDEEDIT.SC Compile: LIB\UTIL.SC</p>
UPDNLOG()	<p>Description: Logs upload and download activity to log table in SWPM database</p> <p>Parameters: None</p> <p>Return: None</p> <p>Applications: SWPM upload and download processes</p> <p>Scripts Source: UTIL\UPLOAD.SC Compile: LIB\UTIL.SC</p>
UPLOAD()	<p>Description: Uploads SWPM user changeable data tables to the network disk upload area. See Technical Notes, Appendix C, Section 7, and User's Guide for additional documentation.</p> <p>Parameters: None</p>

	Return: None
	Applications: SWPM database application
	Scripts
	Source: UTIL\UPLOAD.SC
	Compile: LIB\UTIL.SC
VALEXIST()	Description: Determines whether there are any occurrences of a specified value in a particular column of a table
	Parameters: 1. Type: A Name of table to search.
	2. Type: A Field of table to be searched.
	3. Type: same as type of field specified by parameter 2
	Applications: various
	Return: True or False
	Scripts
	Source: UTIL\VALEXIST.SC
	Compile: LIB\UTIL.SC
VALPDDEL()	Description: Deletes all rows of a table with a Period ID field that contains a specified value
	Parameters: 1. Type: A Name of table in which delete is to take place.
	2. Type: A Dummy parameter.
	3. Type: A Period ID of rows to be deleted.
	Return: None
	Applications: Some SWPM codes table maintenance processes
	Scripts
	Source: UTIL\VALPDDEL.SC
	Compile: LIB\UTIL.SC

VALUPD()

Description: Updates all rows in a designated table containing a specified field value to a new value. A "changeto" query is executed.

- Parameters:**
1. Type: A
Name of table in which update is to take place.
 2. Type: A
Name of field to change.
 3. Type: A
Old value of field.
 4. Type: A
New value of field.

Return: None

Applications: ?

Scripts

Source: UTIL\VALUPD.SC

Compile: LIB\UTIL.SC

VALYRDEL()

Description: Deletes rows from a specified table in which other parameters match certain field values. Uses "delete" query.

- Parameters:**
1. Type: A
Name of field in which deletes are to take place.
 2. Type: A
Name of field containing WG names.
 - 3-5. Dummy parameters
 6. Type: depends on field type of parameter 2
Value contained in field specified by parameter 2.
 7. Type: depends on field one position to the right of that specified in parameter 2
Value of scenario contained in this field.
 8. Type: A
Year value of row(s) to be deleted.
 9. Type: A
Period ID of row(s) to be deleted.

Return: None

Applications: ?

Scripts

Source: UTIL\VALRDEL.SC

Compile: LIB\UTIL.SC

DISTRIBUTION

No. of
Copies

2 DOE/Office of Scientific and
Technical Information

OFFSITE

5 Westinghouse Hanford Company
R. S. Kelley

No. of
Copies

ONSITE

19 Pacific Northwest Laboratory

C. L. Blackburn (2)
G. M. Holter
D. L. Stiles (10)
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

2 / 20 / 92