**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

Received by OSTI

AUG 13 1991

ORNL/ER/Sub/90-KA931/2

Received by OSTI

DEC 03 1991

**Floodplain and Wetlands Assessment
of the White Oak Creek Embayment**

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

ORNL/ER/Sub--90-KA931/2

DE92 003674

Floodplain and Wetlands Assessment of the White Oak Creek Embayment

Environmental Restoration Division
P.O. Box 2003
Oak Ridge, Tennessee 37831-7298

Date Issued—July 1991

Prepared by
CDM Federal Programs Corporation
101 North Rutgers, Suite 202
Oak Ridge, Tennessee 37830
under subcontract 28K-KA931C

Prepared for
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
under budget and reporting code EW 20

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6285
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Author Affiliation

Mary Leslie is an associate with CDM Federal Programs Corporation

ABSTRACT

This report describes the proposed methods for dealing with contaminants that have accumulated in White Oak Creek, White Oak Lake, and the White Oak Creek Embayment as a result of process releases and discharges from the Oak Ridge National Laboratory. Alternative methods of cleaning up the area which were considered in accordance with regulatory guidelines are listed, and information supporting the selected methods is provided. Also included are results of a site survey conducted at the White Oak Creek Embayment and the expected effects of the proposed control structures on the floodplain and wetlands. The appendix contains figures showing the nine cross-sections of the stream channel surveyed during studies of the White Oak Creek area.

PROJECT DESCRIPTION

White Oak Creek is the primary surface water drainage for the Oak Ridge National Laboratory (ORNL) area. Since the early 1940s, process releases and discharges from ORNL have resulted in the accumulation of contaminants in White Oak Creek, White Oak Lake, and the White Oak Creek Embayment (WOCE).

The construction of a sediment retention structure at the mouth of White Oak Creek has been proposed to (1) achieve control of the contaminated sediments in the White Oak Creek Embayment, and (2) prevent their downstream transport into off-site surface waters (the Clinch River and Watts Bar Reservoir).

Floodplain and wetland assessments were performed to assess the potential impacts of the proposed sediment retention structure on the lower White Oak Creek system. These assessments address the potential for alteration of the floodplain of White Oak Creek after the installation of the sediment retention structure, increase in the water surface elevations during flood events, and impacts on nearby properties and the environment. Impacts of concern are increased potential for flooding, sedimentation, erosional alteration of habitat, and overall water quality changes. Benefits include retention of contaminated sediments on-site, minimization of transport of contaminated sediment downstream into off-site surface water environments (Clinch River and Watts Bar Reservoir), and reduction of fish movement into and out of the contaminated area.

The installation of the sediment retention structure at the confluence of White Oak Creek and the Clinch River will alter the existing White Oak Creek Embayment floodplain to a minor extent. The confluence is located at mile 20.8 on the Clinch River. The drainage basin for White Oak Creek is shown in Figure 1.

Based on historic data, a flood frequency curve has been developed by the U.S. Army Corps of Engineering (COE, 1990). From this, a peak flow rate can be determined for any given recurrence interval (Figure 2). The

CDM FEDERAL PROGRAMS CORPORATION
DRAINAGE BASIN OF WHITE OAK CREEK

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

1

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
DISCHARGE-FREQUENCY CURVES

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

2

normal flow elevation varies seasonally and daily due to the operations of the Melton Hill Dam just upstream on the Clinch River and operations of Watts Bar Dam downstream. The normal summer and winter pool elevations in White Oak Creek Embayment are 741.0 ft, and 735.0 ft respectively, at the confluence.

The 100-year and 500-year flood event peak flows were estimated by the COE at 1688 cfs and 2500 cfs, respectively. Based on these peak flows, the COE used their HEC-2 model to determine the elevation of each of the flood events through the reach of the stream under consideration. The stream channel has been surveyed to produce cross-sections at nine locations with Section 0.0 being at the confluence of White Oak Creek and the Clinch River and Section 0.56 being just downstream of White Oak Lake Dam. A figure showing each of the cross-sections is included in the appendix. The HEC-2 model calculates the elevation of each flood event at each cross-section location.

Table 1 gives the summary of the HEC-2 flood routing calculations. The most restrictive section of the stream is at the confluence with the Clinch River where the proposed structure is to be located causing backwater to the White Oak Lake Dam. Hence, the surface water elevation changes very little throughout the reach. A starting water elevation at the mouth of White Oak Creek was assumed to be 741 ft, which is the normal summer pool for the Watts Bar Reservoir. The elevation of the surface water for the 100-year event would range from 741.0 feet at the confluence to 743.1 ft at White Oak Lake Dam. The 500 year-event would range from 741.0 ft at the confluence to 744.3 ft at the dam.

The increased area inundated by the change in the hydrologic system is minimal because the banks on White Oak Creek are very steep. Figure 3 illustrates the 500-year floodplain boundary for the reach under consideration. Because the difference between the 100-year and 500-year floodplain elevation is small (less than 2 feet), the 100-year floodplain is not shown.

Table 1
SUMMARY OF THE 100- and 500-year FLOOD EVENTS
FOR WHITE OAK CREEK BEFORE AND AFTER PROPOSED EMBAYMENT

CROSS-SECTION	EXISTING CONDITIONS		PROPOSED EMBAYMENT	
	100-yr Event*	500-yr Event**	100-yr Event	500-yr Event
0.0	741.0	741.0	748.0	749.3
0.019	741.0	741.0	748.0	749.3
0.038	741.1	741.2	748.0	749.3
0.052	741.2	741.4	748.0	749.3
0.157	741.7	742.4	748.0	749.3
0.246	742.3	743.3	748.0	749.4
0.352	742.8	744.0	748.1	749.5
0.450	742.9	744.2	748.2	749.5
0.560	743.1	744.3	748.2	749.6

* 100-year Event Flow Rate is 1688 cfs

** 500-year Event flow rate is 2500 cfs

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
**PROPOSED FLOODPLAIN BOUNDARY OF THE 500-YEAR
 FLOOD EVENT FOR WHITE OAK CREEK**
WHITE OAK CREEK EMBAYMENT
 OAK RIDGE, TENNESSEE

FIGURE NO.

3

The proposed sediment retention structure design consists of sheet pile coffer cells to an elevation of 738 ft and gabions on top of the cells to an elevation of 743 ft. This allows drainage of White Oak Creek to an elevation of 738 ft when the Clinch River is at lower stages (Figure 4).

The sediment retention structure is designed as a broad crested weir with a crest length of 58 feet. The discharge coefficient was assumed to be 2.7. The sediment control structure as proposed has capacity of 2900 cfs with headwater elevation of 750 ft which is the height of the side walls. Thus, the structure will pass the 100-year and 500-year flood events without overtopping the side walls. Portions of the probable maximum flood (PMF) were also considered by the COE. Thirty-three percent of the PMF would yield a peak flow of 6252 cfs. The hazard ranking of the proposed structure was not considered by the COE due to the small amount of water that would be retained. There are no high hazard areas in the floodplain.

The backwater for the proposed structure was determined by using the starting water elevations at the mouth of White Oak Creek. The starting water elevation was determined from the headwater rating equation for the sediment control structure ($Q = 2.7H^{3/2}$); where Q is the discharge in cfs and H is the height above the crest of the dam. The starting water elevation for the 100-year and 500-year flood events are 748 ft and 749.3 ft, respectively. The resulting water surface elevations from the backwater calculations are summarized in Table 1. There is very little change in water surface elevation between the sediment control structure and White Oak Lake Dam. Backwater from the 500-year event would reach the existing outlet structures at White Oak Lake Dam.

On March 1, 1991 a site survey was conducted at the White Oak Creek Embayment. White Oak Creek Embayment is a significantly disturbed riverine wetland system. High concentrations of radioactive compounds (cesium-137) have been identified and elevated concentrations of mercury and PCBs have been reported in the fish samples collected from White Oak Creek (MMES/DOE, 1990). The dominant flora identified during the site survey adjacent to the White Oak Creek Embayment are black willow Salix nigra (Obligate Wetland) and bamboo Bambusa vulgaris (Facultative Upland) (USFWS, 1988). Other flora identified within the embayment include: dogwood, eastern

ELEVATION
Not to Scale

SECTION
Not to Scale

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
SEDIMENT RETENTION STRUCTURE
WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

4

cottonwood, maple, poison ivy, green ash, sycamore, royal fern, eastern red cedar and a proliferation of vines which line the banks of the river. Fauna observed include: blue heron, mallard, scaup, squirrel, turtle, turkey vulture, and tracks of egret, rabbit, racoon, deer and turkey. It is reported that carp, catfish, largemouth bass, bluegill, gizzard and threadfin shad, and snapping turtle are present in the area. No endangered species have been reported in the embayment (MMES/DOE, 1990). The site has been identified as one of the 90 wetland areas within the Oak Ridge Reservation. The area does not appear to represent a unique wetland system to the area either in size, species diversity, or economic or social value.

FLOODPLAIN/WETLANDS EFFECTS

As a result of construction of the proposed structure over the short-term and long-term, sedimentation within the lower White Oak Creek Embayment will increase in a controlled manner. This is due to the decrease in surface water velocity allowing more time for suspended particles to settle out. This will also reduce the movement of sediments within the channel, which is the specified purpose of the structure. Furthermore, the minimum pool/water level in the embayment will be increased to 738 ft. This increase in water-level elevation at reservoir winter pool will result in retaining water over a larger area of contaminated embayment sediment throughout the year, thereby reducing risks to direct exposure and inhalation of contaminated suspended particles.

Under normal summer pool operations, water will be allowed to drain freely into and out of White Oak Creek Embayment through the gabions. The gabions will reduce the rate at which the water may enter and exit the embayment due to the peaking power operations at the Melton Hill Dam. Melton Hill Dam normally discharges twice daily during peaking power production, which causes a surcharge of approximately two feet at the White Oak Creek Embayment. Thus, normal summer pool elevations (fluctuations) within the embayment will not be effected by the sediment control structure. In addition, there are no existing structures located within the proposed 500-year floodplain. Therefore, the short-term and long-term risks to individuals or property damage will not be increased by construction of the sediment control structure.

The extent to which the backwater from the sediment retention structure affects the discharge from White Oak Lake Dam was also considered. The headwater within White Oak Lake Dam will change very little due to the limited tailwater effect from the proposed structure downstream. The tailwater and headwater curves for the proposed and existing conditions are shown in Figure 5. This increase in headwater in White Oak Lake Dam is estimated to be approximately 0.25 ft for the 500-year flood event, which is a negligible increase (COE, 1990).

Construction of the proposed sediment retention structure at the mouth of WOCE will affect the wetland environment via nutrient and contaminant retention, which may turn create a long-term impact on biota in the embayment. Potential long-term impacts include a decrease in species diversity at the benthic level, and increased levels and retention of radioactive materials which may affect both the terrestrial and aquatic species in the embayment. However, the historically high level of contamination in the embayment has in all probability significantly impacted these populations, and therefore, although difficult to predict and quantify, any additional impacts will likely be marginal.

Containment of contaminants above the proposed structure should serve to inhibit the spread of radioactive contaminants in the Clinch River and Watts Bar Reservoir, therefore minimizing potential long-term impacts to the biota in these aquatic environments. Additionally, construction of the proposed structure will minimize the movement of fish into the embayment and the subsequent movement of contaminated fish from the embayment into off-site surface waters. Long-term monitoring studies would be necessary to quantify the benefits and/or detrimental effects of the sediment control structure.

ALTERNATIVES

The Corps of Engineers performed a detailed analysis of alternatives for sediment control in White Oak Creek Embayment, including the no action alternative, in accordance with the EPA Guidance for Conducting Remedial Investigations and Feasibility Studies Under CERCLA, Interim Final, October 1988.

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
HEADWATER AND TAILWATER RATING CURVES
WHITE OAK LAKE DAM
WHITE OAK CREEK EMBAYMENT
 OAK RIDGE, TENNESSEE

FIGURE NO.

5

The functional requirements/constraints for the proposed interim control measures were as follows:

1. Contain contaminated surface sediments in the lower WOCE to prevent transport off-site into the Clinch River for an interim duration (up to 30 years) consistent with eventual ORNL permanent remedial actions upstream.
2. Minimize the cyclic surging of water in the WOCE which results from hydropower operations at Melton Hill Dam.
3. Minimize potential erosion and subsequent off-site transport of WOCE sediments by local flooding in the watershed and/or in the Clinch River upstream of the mouth of White Oak Creek.
4. Minimize the potential for increased backwater effects in the WOCE due to construction of retention structures in the mouth of the embayment.
5. Ensure that extraordinary measures will be implemented to avoid disturbance of contaminated sediments in WOCE during the construction of the chosen interim corrective measure.
6. Implementability
7. Effectiveness
8. Cost

A complete screening of alternatives was conducted by the COE (COE, 1991). A summary of the findings is illustrated in Figure 6.

Based on the detailed alternatives analysis and site specific constraints of this project, the coffer cell/rock-filled structure was clearly the best alternative for the proposed action. Several aspects of the design and construction of the proposed structure will mitigate adverse effects of actions in the floodplain and wetlands of White Oak Creek Embayment and in downstream surface waters. The height of the structure was designed specifically to minimize the increase in the area of inundation in the floodplain. The construction method selected creates minimal sediment

EVALUATION OF ALTERNATIVES

CERCLA CRITERIA

ALTERNATIVES

RETENTION APPROACHES

IN - SITU APPROACHES

	IMPLEMENTABILITY	LONG - TERM EFFECTIVENESS AND PERMANENCE	OVERALL PROTECTION OF HUMAN HEALTH AND THE ENVIRONMENT	REDUCTION OF TOXICITY, MOBILITY, AND VOLUME THROUGH TREATMENT	SHORT - TERM EFFECTIVENESS	COMPLIANCE WITH ADAR'S	COST
GABION STRUCTURE	N						
ROCKFILL STRUCTURE	N						
ROCKFILL /SHEET PILE STRUCTURE	N						
COFFERCELL /ROCKFILL STRUCTURE	Y	Y	Y	Y	Y	Y	Y
SHEET PILE WALL STRUCTURE	N						
CONCRETE STRUCTURE	N						
SUNKEN CARSSON STRUCTURE	N						
SILT CURTAIN	N						
GABION OVERLAY	N						
MAT OVERLAY	Y	N					
FABRIFORM OVERLAY	Y	N					
EXCAVATE NEW CHANNEL - COVER OLD	Y	N					
INSTALL PIPE CULVERT - COVER OLD	Y	N					
DREDGING /REMOVAL WITHIN CRITICAL REACH	N						
VITRIFICATION	Y	N					
NO ACTION	Y	N	N	N	N	N/A	Y

Y = YES
N = NO

WHITE OAK CREEK EMBAYMENT

OAK RIDGE NATIONAL LABORATORY
OAK RIDGE, TENNESSEE

FIGURE 6

disturbance during construction, and therefore minimizes off-site migration of contaminated sediment. The overall approach minimizes the alteration of the ecosystem and potential off-site impacts associated with contaminated sediment transport downstream.

SUMMARY

Results of the floodplain assessment indicate minimal effects with regard to hydrologic impacts, backwater effects, and increases in floodplain inundation area. Risks to individuals or to property will not be increased by construction of the proposed structure. The wetland assessment indicates that the White Oak Creek Embayment is a significantly disturbed riverine wetland system. The embayment does not constitute a wetland that is unique to the area with regard to size, species diversity, economic or social value, or occurrence of endangered or threatened species.

The results of these assessments indicate that the benefits of the proposed structure (on-site retention of contaminated sediment, prevention of migration of contaminated sediments into off-site public surface waters, reduction on-site risks at winter pool water levels, and reduction of fish movement into and out of the contaminated area) outweigh the potential minimal impacts to the historically disturbed embayment system.

REFERENCES

Department of the Army, Nashville District, Corps of Engineers, 1990. Hydraulic Design and Analyses, Sediment Retention Structure White Oak Creek, Nashville, Tennessee.

Department of the Army, Nashville District, Corps of Engineers, January 1991. Detailed Analysis Report, Evaluation of Alternatives for White Oak Creek Embayment, Nashville, Tennessee.

Martin Marietta Energy Systems, Inc. (MMES) and the Department of Energy (DOE), 1990. Oak Ridge Environmental Report for 1989, ES/ESH-13/V1.

Martin Marietta Energy Systems, Inc. (MMES), 1990. Functional Requirements Documents, White Oak Creek Embayment Report. Environmental Restoration Division.

U.S. Fish and Wildlife Service (USFWS), 1988. Biological Report 88 (24). National List of Plant Species that Occur in Wetlands.

APPENDIX

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .000

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-1

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .019

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-2

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .038

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-3

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .052

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-4

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .157

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-5

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .246

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-6

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .352

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NC

A-7

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .450

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-8

SOURCE: COE, 1990.

CDM FEDERAL PROGRAMS CORPORATION
CROSS-SECTION .560

WHITE OAK CREEK EMBAYMENT
OAK RIDGE, TENNESSEE

FIGURE NO.

A-9

DISTRIBUTION

1. L. D. Bates
2. N. W. Durfee
3. C. D. Goins
4. B. L. Kimmel
5. T. M. Koepf
- 6-7. P. T. Owen
8. J. A. Reafsnyder
9. G. E. Rymer
10. D. W. Swindle
11. R. K. White
12. Central Research Library
- 13-17. ER Document Management Center
18. ORNL Laboratory Records
19. Office of Assistant Manager for Energy Research and Development, DOE Field Office, Oak Ridge, P.O. Box 2001, Oak Ridge, Tennessee 37831-8600
20. P. H. Edmonds, Lee Wan and Associates, 120 South Jefferson Circle, Oak Ridge, TN 37830
- 21-24. W. E. Murphie, Department of Energy, Office of Environmental Restoration, Eastern Area D&D Branch, EM-423 (GTN), Washington, DC 20545
- 25-26. S. S. Perkins, DOE Field Office, Oak Ridge, Information Resource Center, 105 Broadway, Oak Ridge, TN 37830
- 27-28. R. C. Sleeman, DOE Field Office, Oak Ridge, P.O. Box 2001, Oak Ridge, TN 37831-8541
- 29-30. D. G. Page, DOE Field Office, Oak Ridge, P.O. Box 2001, Oak Ridge, TN 37831-8541
31. Mary Leslie, CDM Federal Programs Corporation, 101 North Rutgers, Suite 202, Oak Ridge, Tennessee 37830
- 32-33. Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831

END

**DATE
FILMED**

2/11/92

I