Invited Contribution to the 1981 INS
International Symposium on Nuclear Radiation Detectors
Tokyo, Japan, March 23-26, 1981
(Paper done at CERN-CERN/EF 81-6)

CERN-30196-1-16

Performance of the AFS Vertex Detector at the CERN ISR

O. Botner, V. Burkert, D. Cockerill, C.W. Fabjan, T. Ferbel, P. Frandsen,
A. Hallgren, B. Heck, H.J. Hilke, R. Hogue*, P. Jeffreys, H.B. Jensen, T.
Killian, M. Kreisler, J. Lindsay, H. Lubatti, T. Ludlam, W. Molzon, B.S.
Nielsen, Y. Oren, P. Queru, L. Rosselet, E. Rosso, A. Rudge, R. Schindler,
M. Schire, D.W. Wang, Ch.J. Wang, W.J. Willis and M. Winik*

CERN, European Organization for Nuclear Research, Geneva, Switzerland

H. Bøggild, E. Dahl-Jensen, I. Dahl-Jensen, Ph. Dam, G. Damgaard, K.H. Hansen,
J. Hooper, R. Møller, S.Ø. Nielsen, L. Olssen and B. Schistad

Niels Bohr Institute, Copenhagen, Denmark

T. Akesson, S. Almed, G. von Dardel, S. Henning, G. Jarlskog, B. Lorstad,
A. Melin, U. Mjornmark and A. Nilsson

University of Lund, Lund, Sweden

M.G. Albrow, N.A. McCubbin and W.M. Evans
Rutherford Laboratory, Chilton, Didcot, UK

O. Benary, S. Dagan and D. Lissauer
Tel Aviv University, Tel Aviv, Israel

DISCLAIMER

*Brookhaven National Laboratory, Upton, NY 11973

The submitted manuscript has been authored under contract DE-AC02-76CH00016 with the U.S. Department of Energy. Accordingly, the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U.S. Government purposes.

PERFORMANCE OF THE AFS VERTEX DETECTOR AT THE CERN ISR

O. Botner, V. Burkert, D. Cockerill, C.W. Fabjan, T. Ferbel, P. Frandsen,
A. Hallgren, B. Heck, H.J. Hilke, R. Hogue, P. Jeffreys, H.B. Jensen,
T. Killian, M. Kreisler, J. Lindsay, H. Lubatti, T. Ludlam, W. Molzon,
B.S. Nielsen, Y. Oren, P. Quéru, L. Rosselet, E. Rosso, A. Rudge, R. Schindler,
M. Sciré, D.W. Wang, Ch.J. Wang, W.J. Willis and M. Winik

CERN, European Organization for Nuclear Research, Geneva, Switzerland

H. Bøggild, E. Dahl-Jensen, I. Dahl-Jensen, Ph. Dam, G. Damgaard,
K.H. Hansen, J. Hooper, R. Møller, S.Ø. Nielsen, L. Olssen and B. Schistad
Niels Bohr Institute, Copenhagen, Denmark

T. Akesson, S. Almehed, G. von Dardel, S. Henning, G. Jarlskog, B. Lörstad,
A. Melin, U. Mjörnmark and A. Nilsson
University of Lund, Lund, Sweden

M.G. Albrow, N.A. McCubbin and W.M. Evans
Rutherford Laboratory, Chilton, Didcot, U.K.

O. Benary, S. Dagan and D. Lissaver
Tel Aviv University, Tel Aviv, Israel

ABSTRACT

The central detector of the Axial Field Spectrometer (AFS) is a cylindrical drift chamber using a "bicycle-wheel" geometry. Its design has been optimized for jet-like events with high track densities. This is accomplished through a high degree of azimuthal segmentation (4° sectors) with up to 42 space points per track, using measurements of drift time and charge division. Particle identification in the non-relativistic region is obtained by (dE/dx) sampling. The detector is operated in an inhomogeneous magnetic field at event rates of typically 5×10^5 collisions per second. Preliminary results will be presented on the detector performance achieved after one year of operation at the ISR.

Invited Contribution to the
1981 INS International Symposium on Nuclear Radiation Detectors
Tokyo, Japan, March 1981

Presented by H.J. Hilke

1. INTRODUCTION

The Axial Field Spectrometer (AFS) at the CERN ISR was designed to study events characterized by large transverse momenta. It required a low mass vertex detector providing good momentum resolution in a magnetic field of 0.5 T, powerful pattern recognition for high event rates and particle densities and particle identification in the non-relativistic region [1].

2. CHAMBER DESIGN AND OPERATION

A cylindrical drift chamber with 4° azimuthal segmentation was constructed [2], combining drift time measurement for the azimuthal coordinate with charge division read out for the coordinate along the wires (fig. 1). The chamber is 1.4 m long and extends from a radius of 0.2 m to 0.8 m. Each 4° sector contains 42 resistive sense wires (30 μ m diameter, 8 mm spacing), arranged radially into three crowns. The sense wires are staggered by ± 0.4 mm to resolve the left-right ambiguity. Sector boundaries consist of grids of 100 μ m wires. Particle identification in the non-relativistic region is obtained from multiple ionization sampling (dE/dx). The drift chamber was built in two half-cylinders to permit rapid retraction from the magnet. The outer section of the chamber experiences magnetic field inhomogeneities of more than 30%, due to the open magnet structure.

The chamber is operated with an argon/ethane mixture (50/50 vol.%) at atmospheric pressure. A gas amplification of $(3-6) \times 10^4$ is chosen as compromise between acceptable chamber lifetime and dE/dx resolution on the one side and good space resolution on the other.

3. PERFORMANCE

3.1 Drift time measurements

The CERN DTR units are used for drift time digitization, contributing $\sigma = 60$ μ m to the space resolution. For all tracks, visible radially over > 50 cm, we obtain a point resolution with $\text{FWHM}/2.35 = 200$ μ m, averaged over the full azimuth and all points with valid z information. The residue distribution is well approximated by a Gaussian in the central part, contains, however, stronger tails. Near the sense wires and the sector boundaries the resolution is worse, in between these zones it is better.

Corrections are applied for electrostatic wire deflections, magnetic field inhomogeneities, drift velocity variations and also for time slewing and crosstalk (-4 to -6%). A substantial improvement was gained by the introduction of the last two corrections: a general time slewing term, similar for all wires, and an additional crosstalk term only for the "far wires". These wires, because of staggering, receive their avalanche signal only some 16 ns after the crosstalk signal from the adjacent wires and, therefore, experience additional time slewing.

3.2 Charge division

As expected, a strong correlation is observed between the resolution from charge division and pulseheight (PH): $\text{FWHM (cm)} = A + B \cdot \text{noise/PH}$. For a gas amplification of 5×10^4 , the average resolution for all reconstructed tracks is $\text{FWHM} = 3.4 \text{ cm}$.

3.3 Particle identification by dE/dx

Averaging over all tracks containing > 30 time digitizations and z -measurements, we obtain for the truncated mean of the 60% lowest pulse heights: $\text{FWHM/mean} = 24\%$, a value very close to that predicted by Monte-Carlo estimation. As fig. 2 shows, protons may be identified up to 1.0 GeV/c , pions and kaons up to 0.6 GeV/c . For high particle densities, the superior granularity of this system offers a substantial advantage over a standard time-of-flight system. As an illustration of the performance in complex events, the preliminary spectrum of the total charged transverse energy E_T is shown in fig. 3, for pp and $\alpha\alpha$ collisions. It was obtained with minimum bias trigger and uses only particle identification in the drift chamber, assuming the pion mass, whenever no identification is obtained. A simple Monte-Carlo fit is added, based on measured multiplicity distributions and inclusive spectra, which well reproduce data from other experiments.

3.4 Diverse

The track reconstruction efficiency of the analysis program is greater than 95%, even at high multiplicities ($N_{ch} > 20$). An example of an event containing 45 reconstructed tracks from an $\alpha\alpha$ collision is shown in fig. 4. Data from cosmic rays are being actively studied for surveying purposes and for obtaining better knowledge of systematic errors, e.g. for momentum measurements.

In parallel, a laser beam was set up to produce ionization tracks in one sector of the drift chamber, with magnet on and off conditions. The preliminary results are very encouraging. Clean tracks were observed all through the sector, although the beam had to cross field shaping wires. For the central crown - containing 18 sense wires - the resolution from drift time measurements was $\sigma \sim 100 \mu\text{m}$ (2σ containing 2/3 of the hits). This includes $\sigma = 60 \mu\text{m}$ from the electronics and indicates that the wire positions and electronic delays are well corrected. Due to the high pulse amplitudes, also a good z resolution was obtained with $\text{FWHM} \sim 2 \text{ cm}$.

The advantages of the laser beam for calibration and monitoring are: no magnetic deflection, no production of δ electrons, narrow amplitude spectrum and precise and reproducible localization in space and time [3]. Some systematic effects - not recognized before - became obvious from the first few events. From a detailed study of these measurements we expect a substantial improvement of the detector performance through better knowledge of various parameters as drift velocity and drift angle variations, time slewing and other systematic effects.

This research supported in part by the US Department of Energy.

REFERENCES

- [1] (a) S. Almeded et al., A study of large transverse momentum phenomena
CERN/ISRC/76-36/P95 (1977).
- (b) H. Gordon et al., these proceedings: The AFS at the ISR,
presented by C.W. Fabjan
- [2] (a) D. Cockerill et al., Operation of a drift chamber vertex detector
at the ISR, Nucl. Instr. & Meth. 176 (1980) 159.
- (b) J.C. Berset et al., The drift time and charge division electronics
system for the AFS vertex detector, Nucl. Instr. 6 Meth. 176
(1980) 251.
- (c) D. Cockerill et al., Performance of the AFS Vertex Detector at the
CERN ISR, Physic Scripta 23 (1981) 649.
- [3] See contribution to these proceedings: On the use of laser induced
ionization tracks in drift chambers, H.J. Hilke.

Fig. 1

Schematic view of the drift chamber geometry and one sector.

Fig. 2

dE/dx : truncated mean vs. momentum. Clear $\pi/k/p$ separation is achieved in the non-relativistic region.

Fig. 3

Total charged transverse energy (E_T) spectrum, obtained from momentum measurement and particle identification by dE/dx in the drift chamber. Curve from Monte-Carlo fit, based on inclusive spectra and multiplicity distributions.

Fig. 4

High multiplicity event with 45 tracks reconstructed. Minimal calorimeter trigger on an $\alpha\alpha$ interaction at $\sqrt{s} = 126$ GeV.