Received by

MAY 30 1989

Engineering Design of the Interaction Waveguide for High-Power Accelerator-Driven Microwave Free-Electron Lasers

D. B. Hopkins and H. W. Clay
Lawrence Berkeley Laboratory

B. W. Stallard and A. L. Throop
Lawrence Livermore
National Laboratory

G. Listvinsky and M. A. Makowski
TRW, Inc.

Prepared for presentation at the
1989 Particle Accelerator Conference
Chicago, Illinois
March 20-23, 1989

March 16, 1989

Beam Research Program

Lawrence Livermore National Laboratory

MASTER

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be used for other than personal use.

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government or the University of California nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

ENGINEERING DESIGN OF THE INTERACTION WAVEGUIDE FOR
HIGH-POWER ACCELERATOR-DRIVEN MICROWAVE FREE-ELECTRON LASERS

D.B. Hopkins and H.W. Clay
Lawrence Berkeley Laboratory*, University of California
Berkeley, CA 94720

B.W. Stallard and A.L. Throop
Lawrence Livermore National Laboratory†, University of California
P.O. Box 808, Livermore, CA 94550

G. Listvinsky and M.A. Makowski
TRW Space and Technology Group
One Space Park, Redondo Beach, CA 90278

Abstract

Linear induction accelerators (LIAs) operating at beam energies of a few million electron volts and currents of a few thousand amperes are suitable drivers for free-electron lasers (FELs). Such lasers are capable of producing gigawatts of peak power and megawatts of average power at microwave frequencies. Such devices are being studied as possible power sources for future high-gradient accelerators and are being constructed for plasma heating applications. At high power levels, the engineering design of the interaction waveguide presents a challenge. This paper discusses several concerns, including electrical breakdown and metal fatigue limits, choice of material, and choice of operating propagation mode.

*Work supported by the office of Energy Research, High Energy Physics Division of the U.S. DOE under contract DE-AC03-75SG00098.

†Performed jointly under the auspices of the U.S. DOE under contract W-7405-ENG-48.

Introduction

In recent years, much work has gone on at Lawrence Berkeley Laboratory (LBL) and at Lawrence Livermore National Laboratory (LLNL) directed at using LIA-driven FEL amplifiers as high-power microwave sources for future high-energy accelerators¹⁻³ and for plasma heating applications.⁴⁻⁶ One design for a 17-GHz, 1-TeV electron-positron linear collider³ requires from each of 553 FEL sections a peak output power level of 5.0 GW and an average power level of 54 kW. The Intense Microwave Prototype (IMP) FEL at LLNL, nearing completion, is designed to produce a few gigawatts of peak power at 140 GHz. The IMP will be used for electron cyclotron resonance (ECR) heating in the Microwave Tokamak Experiment (MTX). Also under construction for MTX ECR heating is the wiggler and other hardware for upgrading IMP to a 250-GHz, 8.0-GW (peak), 2.0-MW (average) capability. For ECR heating in the Compact Ignition Tokamak (CIT) and the International Thermonuclear Experimental Reactor (ITER), FEL designs call for driving-beam parameters of 13-15 MeV, 3.0 kA, 70 ns, and 10 kHz. For CIT and ITER, such devices are to generate about 14 GW (peak), 10 MW (average) at 280 GHz and 10 GW (peak), 7.0 MW (average) at 560 GHz, respectively.

The FEL interaction waveguide (IW) is the pipe through which the wiggled electron beam and the growing microwave field propagate. It is an oversized waveguide, typically with a size of a few centimeters. At the high peak and average power levels mentioned above, many questions arise regarding the performance limitations, reliability, lifetime, and mechanical design of this key system component. Several of these issues are examined below.

Interaction Waveguide Concerns

Figure 1 shows the electron beam, electric field pattern, and mode commonly used in single-pass FELs with linear wigglers using circular-, elliptical-, or rectangular-shaped IWs. These are shown oriented for the usual horizontal wiggle motion of the electron beam. A 3 x 10-cm rectangular IW used in LLNL's ELF experiments produced ~1.5-GW peak power at 35 GHz. The same size of guide is being studied for use in a 17-GHz two-beam accelerator that will produce ~5.0 GW of peak power.¹ For the 140/250 GHz IMP FEL discussed a 3.25-cm-diam circular IW must reliably propagate 8.0 GW of peak power and up to 2.0 MW of average power for 0.5 s.

Figure 1. Commonly-used IW cross sections, modes, and E-field intensity.

The threshold power level for electrical breakdown is a natural first concern when dealing with high power waveguides. For the modes shown in Fig. 1, the peak power is related to the electric field in vacuum by

$$P_{P(GW)} \approx 5.0 \times 10^{-5} d_{(cm)}^2 \frac{\lambda}{\lambda_g} E_P^2 \text{ [circular]}$$

and

$$P_{P(GW)} \approx 6.6 \times 10^{-5} a \times b_{(cm)} \frac{\lambda}{\lambda_g} E_P^2 \text{ [rectangular]}$$

where λ is the operating wavelength, λ_g is the guide wavelength,

$\lambda/\lambda_g = [1 - (\lambda/\lambda_c)^2]^{1/2}$, and λ_c is the cutoff wavelength.

For the usual case of operation in a highly oversized waveguide,

$\lambda/\lambda_g \approx 1.0$ and the peak electric field, now independent of frequency,

is given by

$$E_{P(MV/m)} \approx 142 \frac{P_{P(GW)}^{1/2}}{d_{(cm)}} \text{ [circular]}$$

and

$$E_{P(MV/m)} \approx 123 \frac{P_{P(GW)}^{1/2}}{a \times b_{(cm)}} \text{ [rectangular]}$$

For an FEL propagating 5.0 GW in the TE_{01}^0 mode in a 3 x 10-cm rectangular waveguide, $E_p \approx 50$ MV/m. In a 3.25-cm-diam circular waveguide propagating 8.0 GW in the TE_{11}^0 mode, $E_p \approx 123$ MV/m.

To judge whether or not the foregoing peak field values are excessive, we present Fig. 2, which plots E_p versus frequency and shows limits based on electrical breakdown and surface fatigue. Pertinent scaling factors are also included. Note the plot is for a fixed rf pulse width of 60 ns, a common value in induction accelerator designs. Starting with the SLAC electrical breakdown data point of ~ 312 MV/m at 2.856 GHz and an rf pulse width of $T_p = 2.5 \mu s$,⁷ the limit line for annealed oxygen-free high-conductivity

Figure 2. Electrical breakdown and metal fatigue limits on surface electric field for copper.

(OFHC) copper has been scaled⁸ as $f^{1/2} T_p^{-1/4}$. As can be seen, the peak E-field values calculated in the previous paragraph fall well below the electrical breakdown limit. The more stringent limit lines shown on the figure, however, are governed by surface metal fatigue, which we now address.

During each pulse of any rf structure designed to operate at a high repetition rate, such as an FEL, the surface temperature is briefly increased over the average bulk temperature by an amount, ΔT , dependent on the operating mode, the material electrical and thermal properties, the dimensions of the structure, the peak pulsed power level, the pulse width, and any active cooling that is effective during the pulse. This last factor is negligible in the short-pulsed devices under consideration. Because of thermal expansion, this temperature change puts metal surfaces under significant compressive stress. This situation is analyzed in detail elsewhere.⁹ The stress and temperature change are related as

$$|\sigma| = \frac{E \alpha_{ex} \Delta T}{1 - \nu} \quad ,$$

where σ is the stress, E is Young's modulus, α_{ex} is the coefficient of thermal expansion, ΔT is the surface temperature rise, and ν is Poisson's ratio.

A common engineering convention is to design for $\sigma \leq \sigma_{pr}$, where $\sigma_{pr} \approx 80\%$ of the yield stress. Copper is the best commonly available metal for these applications because of its superior electrical and thermal conductivity. A value of $\sigma_{pr} = 40 \text{ N/mm}^2 (= 5.8 \times 10^3 \text{ psi})$ may be taken for annealed OFHC copper. With $E = 17 \times 10^6 \text{ psi}$, $\alpha_{ex} = 17 \times 10^{-6}/^\circ\text{C}$, and $\nu = 0.3$, the corresponding maximum allowable temperature change produced by skin effect and beam interception heating is $\Delta T = 14^\circ\text{C}$.

Modern metal-fatigue theory states that when the yield stress is not exceeded, there is only elastic strain (i.e., no plastic strain) and therefore the cyclic life is essentially infinite.¹⁰ Whereas this may be true regarding overall sample failure, no data known to us offers assurance that surface damage such as micro-cracking has not occurred. Such cracks with depths on the order of a skin depth (typically $<1.0\ \mu\text{m}$) would noticeably increase the surface resistance and pulsed ΔT , leading to runaway failure. A reasonable definition of surface lifetime would therefore be the number of cycles to the onset of micro-cracking. To our knowledge, no relationship has been established between this newly-defined lifetime and sample-rupture lifetime shown in fatigue-test summaries.

Figure 3 shows sample-rupture lifetime curves for various types of copper.¹¹ Typically, the sample stress is cyclically alternated between compression and tension. Since such a test is much more severe than a cyclic compression-only test, the allowable stress is likely to be higher than the results of a compression-tension test would show, perhaps by 20-50%. However, high average power devices will probably operate with a mean bulk temperature in the 100-150°C range, where the yield stress is 15-20% lower than at room temperature. Higher yield-strength copper (e.g., electrolytic tough pitch, or cold worked) can permit higher stresses and ΔT values. However, any annealing step during fabrication will, of course, lower these values. Also, stress softening of such "hard" copper is known to occur and must be examined. The curves plotted in Figure 3 are representative examples only. Copper's strength and other properties are known to be extremely sensitive to the details of the method of its preparation.

Figure 3 Rupture stress vs cycles to failure.
A,B Annealed OFHC copper; C Annealed electrolytic tough pitch copper;
D Annealed copper; E Drawn copper; F C15715 dispersion-strengthened
copper (GildCop); G C17510 $\text{Cu}_{0.4}\text{BeNi}$

For some FELs, e.g., IMP, a 10^8 cycle lifetime for the IW may be acceptable. For others, a lifetime exceeding 10^{11} or more may be required. Figure 3 indicates the large uncertainty in lifetime beyond $\sim 10^7$ cycles. One is therefore faced with the necessity of choosing a stress safety factor with no hard data upon which to base the choice. Obviously, it would be very desirable to have near stress-cycle lifetime data based on, say, a 10% increase in surface resistance, or microwave attenuation.

We are investigating the possibility of correlating data from studies of laser damage to metal mirrors with our present requirements. For example, the peak energy density/pulse in the IMP IW is $0.07 \text{ J/cm}^2/\text{pulse}$. This is below the measured threshold for damage to an uncoated copper mirror ($\sim 0.5 \text{ J/cm}^2/\text{pulse}$) at the $10.6\text{-}\mu\text{m}$ wavelength of a CO_2 laser.

Information pertaining to a promising, relatively new material is included in Figs. 2 and 3. This is type C15715¹² dispersion-strengthened copper, called "GlidCop" by the manufacturer. It permits an operating stress and ΔT several times OFHC values, has a resistivity only $\sim 9\%$ higher than that of OFHC, and has a cost ~ 3 times that of OFHC. Made with $50\text{--}60 \mu\text{m}$ particles of Al_2O_3 dispersed throughout the copper, it is not likely to have an electrical break-down threshold as high as that of OFHC. As indicated by Fig. 2, however, the surface fatigue limit rather than the breakdown limit will be dominant for many applications. The C17510 alloy shown in Fig. 3, incidentally, has a resistivity $\sim 39\%$ higher than that of copper and so is not as interesting as GlidCop.

Completing the explanation of Fig. 2, two reference fatigue limit lines are included for room-temperature OFHC and GlidCop with ΔT values of 10°C

and 68°C, respectively. At frequencies above ~25 GHz, experimental data indicates that surface resistance values (and therefore ΔT values) are higher than theoretical predictions. Empirically, in this frequency range, the fatigue-limited maximum surface electric field is seen to scale as $\sim f^{-0.7}$ for this constant pulse-width case. These limit lines may be considered infinite lifetime limits if one is somewhat optimistic. In that case, if a lifetime of only 10^8 cycles is satisfactory, the lines may be located higher on the figure. Apparently, no relevant experimental data exists to provide guidance for doing so. However, some guidance is provided by pressure vessel codes which indicate that the stress need only be scaled as the square root of the safety factor chosen for cycle lifetime.

Fortunately, for the highest-power FELs where the uncertainties just discussed are intolerable, operation with a certain less common but desirable mode results in a large margin of safety.⁶ This is the hybrid HE_{11} mode.¹³ In a circular waveguide it is similar to the TE_{11}^0 mode except that it has a Gaussian-like distribution of field intensity over the cross section. In the 140-250-GHz range in a 3.25-cm-diam waveguide, the wall-heating power density for the hybrid HE_{11} mode is nearly three orders of magnitude lower than for the TE_{11}^0 mode. This makes possible the CIT and ITER FELs mentioned earlier in the paper. An additional bonus occurs because the beam wiggle motion couples more strongly to this mode than to the TE_{11}^0 mode, resulting in higher FEL gain per unit length. The penalty to

be paid for this performance is a more complex and expensive waveguide. An inner corrugated wall is required with circumferential grooves on the order of $\lambda/4$ deep with a $\lambda/3$ axial spacing. Such a penalty is not prohibitive, however. Lengthy corrugated waveguides operating at 300 GHz have been demonstrated.

The limited space available here prohibits discussing a number of additional interesting topics such as multipactor, surface preparation, oxidation, and mechanical specifications. These have been examined in depth with regard to the IMP/MTX IW requirements and will, perhaps, be the subject of a future paper.

Acknowledgment

The authors are grateful for useful discussions with I. Wilson of the CERN LEP Division, R.S. DiGennaro and K.D. Kennedy of LBL, and R.R. Stone of LLNL.

References

1. D.B. Hopkins and A.M. Sessler, "Status of LBL/LLNL FEL Research for Two-Beam Accelerator Applications," Paper No. D-56, these proceedings.
2. A.M. Sessler, E. Sternbach and J.S. Wurtele, "A New Version of a Free-Electron Laser Two-Beam Accelerator," presented at the Tenth Int. Conf. on the Applications of Accelerators in Research and Industry, Denton, TX., November 7-9, 1988.
3. D.B. Hopkins et al, "An FEL Power Source for a TeV Linear Collider," presented at the 1988 Linear Accelerator Conf., Williamsburg, VA., October 2-7, 1988.
4. A.L. Throop, "High Average Power Millimeter-Wave Source for Plasma Heating (ETA-II)," Invited Paper KA1, these proceedings.

5. R.A. Jong et al, "IMP, A Free-Electron Laser Amplifier for Plasma Heating in the Microwave Tokamak Experiment," presented at the Tenth International Free-Electron Laser Conf., Jerusalem, Israel, August 28-September 2, 1988.
6. R.A. Jong and R.R. Stone, "Induction-Linac Based Free-Electron Laser Amplifier for Fusion Applications," presented at the Tenth International Free-Electron Laser Conf., Jerusalem, Israel, August 28-September 2, 1988.
7. J.W. Wang and G.A. Loew, "Progress Report on New RF Breakdown Studies in an S-Band Structure at SLAC," presented at the 1987 Particle Accelerator Conf., IEEE Cat. No. 87CH2387-9, Washington D.C., March 16-19, 1987.
8. P.B. Wilson, "Linear Accelerators for TeV Colliders," in Laser Acceleration of Particles, C. Joshi and T. Katsouleas, editors, AIP Conf. Proc. 130, 575, Am. Inst. Phys. (1985).
9. M. Makowski and G. Listvinsky, "Engineering Analysis of FEL Waveguides Under High Average Power Pulsed Loads," TRW Internal Note, June 1, 1988.
10. R.R. Stone, LLNL, private communication (1989).
11. A Survey of Properties (OFHC Brand Copper), AMAX Copper, Inc., New York, NY, date unknown.
12. A. Nadkarui and J. Syure, "Dispersion Strengthened Copper C15715," presented at the Workshop on Copper and Copper Alloys for Fusion Reactor Applications, Washington, D. C., April, 1983, pp 151-177.
13. J.L. Doane, "Propagation and Mode Coupling in Corrugated and Smooth-Wall Circular Waveguides," in Infrared and Millimeter Waves, K.J. Button, Ed., Academic Press, 1985, Vol. 13, pp. 123-170.