TECHNOLOGY '90

■ Accomplishments In Technology Transfer
From DOE And Its Laboratories

U.S. Department of Energy
R&D Laboratory Technology Transfer Program

Washington, D.C. 20585
January 1991

T Preface

Technology transfer has become increasingly important in recent years as a result of the perception that U.S. industrial competitiveness is eroding, and that Federal investments in research and development could be better utilized in addressing this issue. As an agency that supports a wide range of research and development activities and has a network of dedicated, world-class laboratories, the Department of Energy (DOE) plays a key role in improving technology transfer.

The DOE laboratories are extremely important in the Department's technology transfer effort. Most of these laboratories were established more than 40 years ago with an initial focus on nuclear research. They have evolved into premier research institutions whose staff are involved in a broad range of research and development areas, including the materials, chemical, environmental, biological, physical, and nuclear sciences. The technical know-how available at the DOE laboratories provides benefits beyond the scope of specific research and development programs. For example, "spin-off" technologies with different applications from those originally envisioned at the beginning of a research program frequently result from laboratory efforts.

A variety of opportunities exists for individuals or organizations to work with the DOE laboratories in the technology transfer process: performing research in scientific user facilities; licensing of laboratory technologies; obtaining technical assistance from laboratory staff through consulting or Work-For-Others agreements; and participating in personnel exchanges and cooperative research and development projects. Laboratory staff also play a major role in transferring knowledge and information by publishing articles in scientific journals, making presentations at technical meetings, participating in professional organizations, and serving as teachers and advisors at educational institutions. I believe it is important to maintain these traditional methods of technology transfer, while strengthening efforts to interact with and assist U.S. industry in nontraditional ways, such as those provided for by the National Competitiveness Technology Transfer Act of 1989.

Technology '90 provides a glimpse of the many research and development and technology transfer activities conducted by the DOE program offices and laboratories. I hope that this document can provide a better understanding of efforts being undertaken by the DOE to facilitate technology transfer and serve as a springboard for further efforts to enhance DOE laboratory contributions to U.S. competitiveness.

James F. Decker
Acting Director
Office of Energy Research
U.S. Department of Energy

CONTENTS

1

OVERVIEW 1

- 3 ■ Introduction
- 5 ■ Transfer Highlights from Research and Development Programs

2

TECHNOLOGIES 53

- 55 ■ Introduction
- 56 ■ Energy Technologies
- 72 ■ Environment and Waste Management
- 88 ■ Biology and Medicine
- 102 ■ Materials Science and Manufacturing Processes
- 122 ■ Analysis and Instrumentation
- 142 ■ Computers and Communications

3

LABORATORIES 153

- 155 ■ Introduction
- 157 ■ Access to the Laboratories
- 165 ■ Multiprogram Laboratories
- 174 ■ Major Single-Program Laboratories
- 185 ■ Other DOE Laboratories
- 189 ■ OFFICE OF SCIENTIFIC AND TECHNICAL INFORMATION

CONTENTS

3 ■ Introduction

5 ■ Transfer Highlights from Research and Development Programs

5 ■ ENERGY RESEARCH

- 5 Basic Energy Sciences
- 10 High Energy and Nuclear Physics
- 12 Fusion Energy
- 13 Health and Environmental Research
- 19 Small Business Innovation Research Program
- 21 R&D Laboratory Technology Transfer Program

24 ■ DEFENSE PROGRAMS

27 ■ NUCLEAR ENERGY

29 ■ CONSERVATION AND RENEWABLE ENERGY

- 29 Utility Technologies
- 33 Industrial Technologies
- 35 Transportation Technologies
- 40 Building Technologies

41 ■ FOSSIL ENERGY

- 42 The Clean Coal Technology Program
- 43 The Fossil Energy R&D Program
- 47 Federal/State Partnership Programs
- 48 International Fossil Energy Technology Transfer

49 ■ ENVIRONMENTAL RESTORATION AND WASTE MANAGEMENT

1 OVERVIEW

Photo at left: In this photograph of the vapor axial deposition technology developed at Sandia National Laboratories (SNL), a laser is focused into a methane/oxygen flame that is being used to produce high-purity silica for optical fibers. The two bright dots locate the points at which the laser intersects the concentrated stream of submicron silica particles produced by the flame. The white streak along the center of the flame is caused by a chemiluminescent reaction of oxygen with the silica precursor. Inelastically scattered light from the laser is used to measure flame temperatures.

[illegible]

9

Introduction

The U.S. Department of Energy (DOE) laboratories are home to over 23,000 scientists and engineers who perform over \$6 billion of research and development annually. The laboratories have a long history of excellence in performing research and development in a number of areas, including the basic sciences, applied-energy technology, and weapons-related technology.

The excellence of the laboratories is of little value unless the results of their research and development programs are utilized. As noted in the *Interim Report of the National Energy Strategy*, which was published in April 1990, technology in a vacuum is of little value. The knowledge gained from basic scientific research must be shared widely so that practical applications for the new knowledge can be found. The results of applied research must be proven through further development and demonstration to ensure that a new technology meets user needs. The resulting new technology must ultimately be adopted by industry, consumers, or other end-users.

Although technology transfer has always been an element of DOE and laboratory activities, it has received increasing emphasis in recent years as U.S. industrial competitiveness has eroded and efforts have increased to better utilize the research and development resources the laboratories provide. The National Competitiveness Technology Transfer Act (NCTTA), which was passed in late 1989, made technology transfer a full mission of the Federal laboratories.

"The scientists and engineers supported by DOE, in its National Laboratories and in universities, are truly a National treasure in terms of their unparalleled capabilities and achievements. I am committed to seeing that these incredible resources are used more effectively to enhance the competitiveness of U.S. industry and the quality of life for U.S. citizens."

*Admiral James D. Watkins, U.S. Navy (Retired),
Secretary of Energy*

Admiral James Watkins, Secretary of Energy, and Dr. James Decker, Acting Director, DOE Office of Energy Research (right), review an exhibit of DOE-laboratory-developed technologies that have won R&D-100 Awards. R&D-100 Awards, which are presented annually by R&D magazine, acknowledge the 100 most significant products, processes, and materials developed worldwide in a given year. As a group, the DOE laboratories have won more R&D-100 Awards than any other organization.

The DOE moved swiftly in 1990 to implement the provisions of the NCTTA, including the successful negotiation of new contract clauses regarding technology transfer responsibilities of the contractors that manage the laboratories. New DOE programs were initiated to help facilitate technology transfer, including "spin-off" transfer from defense-related and basic research programs where a technology is applied for a purpose or in an industry different from that for which it was originally developed.

The NCTTA gave the the laboratories authority to directly enter into Cooperative Research and Development Agreements (CRADA) with private industry. CRADAs, which represent a departure from traditional Federal technology transfer mechanisms, are attractive to industry because the agreements allow proprietary data or information brought into or developed during a research program to be held confidential for 5 years. In addition, DOE is initiating a variety of efforts to support CRADAs on a cost-sharing basis with industrial firms.

The DOE laboratories have also moved to increase the priority attached to technology transfer within their overall programs and missions. They have established royalty-sharing and awards programs for excellence in technology transfer on the part of their scientists and engineers. They have sought increased U.S. industrial input and involvement in planning and establishing new scientific user facilities. They issued over 90 exclusive and nonexclusive licenses for the application of laboratory-developed technologies in Fiscal Year (FY) 1990—an increase of over 50 percent from the previous year. Efforts have already begun to work more closely with U.S. industry in collaborative research and development efforts in generic technology areas, such as high-temperature superconductivity and advanced manufacturing techniques.

This document, *Technology '90*, is the latest in a series that is intended to communicate some of the many opportunities available for U.S. industry and universities to work with the DOE and its laboratories in the vital activity of improving technology transfer to meet national needs. *Technology '90* is divided into three sections: Overview, Technologies, and Laboratories. The Overview section describes the activities and accomplishments of the DOE research and development program offices. The Technologies section provides descriptions of new technologies developed at the DOE laboratories. The Laboratories section presents information on the missions, programs, and facilities of each laboratory, along with a name and telephone number of a technology transfer contact for additional information.

Transfer Highlights from Research and Development Programs

The Office of Energy Research (ER) manages fundamental science and basic energy research programs in several areas: high-energy physics; nuclear physics; the physical, biological, and mathematical sciences; magnetic-fusion energy; and environmental and health effects. ER also supports many scientific user facilities that are used by universities and private-sector researchers, and manages the DOE Small Business Innovation Research (SBIR) Program and the R&D Laboratory Technology Transfer Program. Following are brief descriptions of technology transfer accomplishments in each of these areas.

Basic Energy Sciences

Basic Energy Sciences (BES) has conducted basic research programs in the physical and related sciences and managed complex national experimental research facilities since the 1940s. Responsiveness to the energy mission of the DOE, support of research in the physical and engineering sciences at universities and the DOE laboratories, and construction and operation of large, complex scientific facilities are key aspects of the BES program.

BES activities also support continuing U.S. leadership in science through scientific achievements and the training of young scientists. BES supports close to 1,200 individual research projects, approximately 600 of them at universities and colleges. The following program trends have recently emerged:

- An increased importance to U.S. science of major BES-supported scientific user facilities at DOE laboratories as national assets available to industrial and university researchers
- An urgency for communicating scientific results to technologists, for increasing awareness among BES-supported researchers of scientific issues facing technologists, and for facilitating rapid technology transfer to the private sector
- An immediate need for additional advanced scientific facilities at DOE laboratories with technical capabilities or expertise that are particularly important to the Nation.

BES research support is organized primarily by scientific discipline, and is administered through the Scientific Computing staff and five divisions: Materials Sciences, Chemical Sciences,

■ ENERGY RESEARCH

Admiral James Watkins, Secretary of Energy, shown here with Argonne National Laboratory (ANL) Associate Director David Moncton (left), studies some of the instruments and components destined for use in the Advanced Photon Source (APS), which is under construction at ANL.

Engineering and Geosciences, Biological Energy Research, and Advanced Energy Projects. This structure helps members of the research community identify programs with which they have common interests. At the same time, the structure allows interdivisional activities to occur in areas of mutual interest.

BES maintains close links to industry. For example, industrial scientists serve on advisory panels for several of the BES subprograms, and experts from industry participate in the review of proposals for research to be funded by BES. Industrial researchers use the specialized facilities supported by BES, participate in program advisory committees at the DOE laboratories, and attend topical conferences and workshops held under BES auspices. Outreach workshops and working groups also bring together investigators in related areas to share information and discuss problem areas. Recently, a new focus has been placed on identifying research areas suitable for coordination with industry, and interactions are ongoing with various industrial sectors.

Interagency information exchanges, committee interactions, and workshops provide useful liaison between BES and research groups from universities, industry, or other government agencies. At the government level, BES routinely exchanges information and coordinates program activities in areas of common interest with other agencies.

The DOE laboratories play an essential role in U.S. science and technology by employing expert scientific and engineering personnel, building and operating complex scientific facilities, and undertaking large interdisciplinary projects. Much of the BES budget that goes to the DOE laboratories is used to operate these complex facilities and support research dependent on them, as well as provide services uniquely available at the laboratories. The nature of these facilities and the character of BES programs have made BES a major participant in the national goal of enhancing economic competitiveness through increased, more rapid use of scientific results for technology applications with near-term potential.

BES supports the use of its scientific user facilities by qualified scientists from industry and universities. Most qualified users of these facilities are from outside the DOE laboratory complex. The research typically involves extremes—extremely short reaction times, vanishingly small concentrations, species with only fleeting lifetimes, and measurements made under extreme conditions of temperature and pressure. To carry out such experiments requires constantly improving equipment and facilities. In addition to supporting the operation of current facilities, BES is involved in efforts to meet such needs, including the increasing efforts to exploit synchrotron radiation and advanced neutron sources to understand the atomic structure of materials.

Seven BES facilities have been designated by DOE as major scientific user facilities: 1) the High Flux Beam Reactor at Brookhaven National Laboratory (BNL); 2) the High Flux Isotope Reactor at Oak Ridge National Laboratory (ORNL); 3) the National Synchrotron Light Source at BNL; 4) the Stanford Synchrotron Radiation Laboratory; 5) the Intense Pulsed Neutron Source at Argonne National Laboratory (ANL); 6) the Los Alamos Neutron Scattering Center at Los Alamos National Laboratory (LANL); and 7) the Combustion Research Facility at the Sandia National Laboratories (SNL) facility in Livermore, California. High-voltage electron microscopes at several DOE laboratories also are available to users. A complete guide to BES User Facilities can be obtained by contacting BES program officials.

Significant success stories are common in BES-supported research and development. Some selected examples are described below.

A new method for forming chemically and physically uniform submicron particles of many materials directly from a vapor has been developed at the Pacific Northwest Laboratory (PNL). The process, which is called Rapid Expansion of Supercritical Fluid Solutions (RESS), uses supercritical fluids as solvents for the material to be deposited. The material released after the solution is rapidly expanded from a supercritical liquid to a low-pressure gas forms fine particles that can be collected on a surface. The process lends itself to the formation of thin films and fibers and uniform mixtures of substances that cannot ordinarily be combined. Because many supercritical fluids form at room temperature, heat-sensitive materials like biological molecules and organic polymers can be processed by this method. This technology resulted from research supported by the Chemical Sciences Division of BES and has been awarded several patents and an R&D-100 Award.

Researchers at LBL received a 1990 R&D-100 Award for the development of the soft-X-ray small-angle scattering apparatus (SXSA-447). The SXSA-447 is used for determining the sizes and structures of submicron objects in a controllable or natural environment where changes in size or structure can be observed directly. This capability has a multitude of immediate applications wherever such objects must be sized (for example, in emulsions and abrasives). In addition to determining particle size, the SXSA-447 can reveal other aspects of particle structure, such as ellipticity and shell thickness. It can also be used for nonparticulate small-angle scattering measurements, such as muscle or tendon striations, fiber size and orientation in polymers and plastics, and crystalline structure in thin materials.

With support from the BES Chemical Sciences Division, an investigator at the Georgia Institute of Technology has developed

Researchers at Lawrence Berkeley Laboratory (LBL) received a 1990 R&D-100 Award for the soft X-ray small-angle scattering apparatus (SXSA-447), which is shown here. The key to the performance of the SXSA-447 is the use of multilayer mirrors to collect and focus soft X-rays to a small spot. This unique feature allows the use of dilute samples. Exposure times for obtaining meaningful interference patterns with soft X-rays are reduced from more than 1,000 hours to a matter of tens of minutes.

This figure describes Z-Contrast Imaging with a Scanning Transmission Electron Microscope. This fundamentally new approach to electron microscopy, which was developed at Oak Ridge National Laboratory (ORNL), provides a direct view of the atomic-scale structure and composition of materials.

a new liquid chromatography/mass spectrometry (LC/MS) interface, which is called MAGIC for Monodisperse Aerosol Generation Interface for liquid Chromatography. Results obtained using MAGIC are compatible with the results from traditional electron-bombardment ionization techniques, so the mass spectra produced can be directly compared to spectra stored in extensive libraries of fragmentation patterns. This information can then be used for unambiguous molecular identification. This system has been commercialized by Hewlett-Packard Corporation as the "Particle Beam Interface" under an exclusive license. MAGIC made an immediate and major impact on the LC/MS market upon its introduction in July 1988 and is expected to achieve a sales volume of \$40 million in 1990.

An ion optics computer program that has found wide acceptance by both users and manufacturers of mass spectrometers has been developed at the Idaho National Engineering Laboratory (INEL). The ion optics simulation program, called SIMION, was originally developed to support BES-sponsored research in gas-phase analytical chemistry at INEL. It has subsequently become a standard tool used by scientists interested in understanding and using charged particle beams. The program enables the user to understand ion trajectories through complex potential fields with user-defined boundary conditions. Over 200 organizations and individuals have requested copies of the software, including IBM, Hewlett-Packard, and most DOE laboratories. Use of SIMION allowed instrument designers at Hewlett-Packard to increase the sensitivity of a commercial mass spectrometer by a factor of 100. Staff from INEL presented information on SIMION in a course and in papers presented at a recent meeting of the American Society for Mass Spectrometry.

Researchers at ORNL have developed a new electron microscopy technique that represents a significant advance over conventional high-resolution transmission electron microscopy. In this fundamentally new approach, which is called Z-Contrast Imaging, an electron beam of atomic dimensions is scanned across a sample and electrons that are scattered at higher angles are detected. The resulting images provide, for the first time, a direct view of the atomic-scale structure and composition of materials. This improved performance is accomplished at much lower cost than conventional high-resolution electron microscopy.

Geoscientists at Lawrence Livermore National Laboratory (LLNL) have developed a computational tool that is helping to find more oil and gas. The reflectance of light by vitrinite, a major constituent of coal, is used extensively as a geothermometer in petroleum exploration. The coal particles formed at higher temperatures are shinier. The LLNL researchers derived a chemical kinetic model for the effect of time and temperature on vitrinite composition, from which its reflectance can be estimated. This model makes it possible to better estimate paleothermal

histories in sediments where the presence of petroleum is suspected. When combined with other information in a process called integrated basin analysis, the risks of drilling a dry well can be reduced. Under a software-sharing agreement with Platte River Associates of Denver, Colorado, this model has been incorporated into a commercial basin-analysis software package that is used worldwide by hundreds of petroleum geologists.

Synchrotron radiation produced at the BNL National Synchrotron Light Source (NSLS) is finding extensive use in the investigation of surface properties of materials. X-ray studies at synchrotron sources provide a detailed microscopic picture of the properties of surfaces because they are easier to interpret, and are sensitive to order changes at length scales ranging from angstroms to microns. As a result, studies of surfaces are being performed at over a dozen beamlines at the NSLS. These studies are being performed by university-based participating research teams, such as Harvard, MIT, SUNY, and the University of Chicago; industrial participating research teams, such as AT&T Bell Laboratories, EXXON, and IBM; and government laboratories, such as BNL and ORNL. A much more detailed understanding of the nature of surfaces is emerging from these studies, and the NSLS has become a major center for the study of surface physics that has applications in many areas, including corrosion, catalysis, electronics, tribology, and electrochemistry.

Synchrotron radiation sources from the NSLS at BNL are also ideal for use in different imaging techniques. Absorption coefficients for atoms change abruptly as a function of photon energy, and this change leads to contrast variations that are element specific. Also, the contrast varies with the oxidation states of the constituent elements. This element and oxidation-state contrast can be used in a wide variety of imaging experiments ranging from lithography to coronary angiography.

Pumping heavy crude oil and slurries through pipelines is energy intensive because these viscous fluids tend to stick to the pipe walls and dissipate energy in the bulk of the fluid. Recent studies of the stability of fluids that do not mix well, such as water and oil, has shown that water will take the form of a sheath that hugs the pipe wall, while the heavy viscous oil flows freely and well separated from the solid pipe wall. In effect, a lubricated pipeline is created that requires far less pumping power. Because pipeline lubrication is effective regardless of the pipe orientation (i.e., horizontal or vertical), the method has clear commercial potential, and a major oil company is now supporting a full-scale test of the concept. This work was supported by the BES Division of Engineering and Geosciences and performed at the University of Minnesota.

Facilities for high-energy and nuclear-physics research, such as Fermi National Accelerator Laboratory (Fermilab), pictured above, are built to facilitate fundamental studies of nature and matter. They also produce spin-off technologies with the potential for more immediate industrial and research applications.

High Energy and Nuclear Physics

The knowledge gained from high-energy physics research is used not only in other scientific fields but increasingly in advanced technology and engineering. Because the principal aim of this basic research is to understand the fundamental nature of matter and energy, it often takes years for the results to find mass applications. Nevertheless, money invested in high-energy physics research also can produce more immediate ancillary benefits to society. In the course of their work, researchers develop spin-off devices, instruments, and technologies that can be used for practical purposes outside the domain of pure research. By working with various industries to develop state-of-the-art equipment, research physicists help them improve their processes and speed new technology to the marketplace. The Office of High Energy and Nuclear Physics supports research and development for both long-range and short-term deployment, as can be seen by the research accomplishments described below.

The proposed Superconducting Super Collider (SSC) is intended to be a national resource through which U.S. and international scientists can better understand the universe. As the largest scientific instrument in the world, the SSC will use about 10,000 superconducting magnets and will be 53 miles in circumference. Because of the enormous scale of the SSC, the SSC Program includes a magnet-industrialization program. The 16 industrial participants selected for Phase I of this program were provided detailed, onsite information on the possible design requirements for the magnets by SSC-associated DOE laboratories, which include BNL, Fermilab, and LBL, and the Universities Research Association, Inc. As a result of this program, significant progress continues to be made in magnet analysis, design, materials processing, fabrication, and testing.

A technology developed for the Continuous Electron Beam Accelerator Facility (CEBAF), a major new scientific user facility supported by the Nuclear Physics Division, was transferred to industry. This technology is capable of producing reliably maintained superconducting acceleration gradients of greater than 5 million electron volts (MeV) per meter. Potential applications in other areas include construction of compact accelerators for defense or industry.

In addition, software developed for accelerator control at CEBAF is finding applications in other research accelerators and is drawing interest from industry. This software increases the versatility and user-friendliness of computer-based control of particle accelerators and other complex systems. The new approach used in the CEBAF software lets scientists and engineers operating the accelerator develop control procedures and control-system applications, and to modify control databases or run-time displays without having to call on computer programmers for customized

updates of software. The CEBAF control system software will enable operators to manage approximately 20,000 input/output data points in an accelerator.

The National Nuclear Data Center, maintained at BNL for the Nuclear Physics Division, continues to provide technical publications and data tapes to users in the private sector and at universities. The predominant users of this information are from the private sector. Information categories include fission reactors, fusion reactors, heavy elements, nuclear fuel cycle and waste management, radiation dosimetry and damage, biomedical applications, and astrophysics. Input to and support for this database are provided from seven DOE laboratories, the National Institute of Standards and Technology, and 10 universities.

The side-coupled radio frequency structure for linear accelerators (LINAC) was developed at the Clinton R. Anderson Meson Physics Facility at LANL in the mid-1960s. This research was supported by the Nuclear Physics Division. As a result of information published in technical journals and at various professional meetings, Varian Associates Inc. of Palo Alto, California, became interested in designing an improved LINAC for medical use based on the new coupling principles used in the technology.

The first product developed by Varian that embodied the new technology was the Clinical Linear Accelerator 4 (CLINAC 4), which was an 80-centimeter electron LINAC generating 4-MeV X-rays. The principle that was developed at LANL and used in the CLINAC 4 resulted in a compact, efficient unit that was useful for both diagnosis and cancer therapy. It was also suitable for installation in both community hospitals and large metropolitan hospitals. Almost 400 of the CLINAC 4 units, and the 6-MeV version, were sold between 1968 and 1978. Since the introduction of the original CLINAC 4, Varian has introduced improved models and continued production. NEC in Japan has produced machines under license to Varian, and Siemens manufactures versions for the European market. Altogether, through March 1990, about 2,000 machines using the LANL-developed technology had been built for cancer treatment. In addition, machines are in use worldwide for nondestructive testing and inspection of such things as rocket motors, pressure valves, and airline jet engines. To date, the direct dollar value of the Varian sales alone is on the order of a billion dollars.

At LBL, a group of researchers supported by the Nuclear Physics Division has developed an entirely new family of ion sources called MEVVA (MEtal Vapor Vacuum Arc). This technology meets a longstanding need for high-current beams of heavy-metal ions for accelerators that power atomic and subatomic particles to enormous energies, or as the dopants that turn non-conductors into semiconductors and conductors into superconductors.

This photograph shows the MEVVA IV ion source, which was developed at Lawrence Berkeley Laboratory (LBL). The body of the source, including the vacuum arc region and the ion extraction grids, is shown on the right. The center section is the rotatable cathode assembly, which allows the cathode to be changed while maintaining the source vacuum. This enables one to use multiple cathodes of the same material, or to use cathodes of up to 16 different materials, thus allowing rapid ion changes. The cover on the left side allows the source to operate at high voltages.

MEVVA is an award-winning concept that makes possible the production of ion beams from any solid conductor, or from any nonconducting material that is part of a conducting alloy, at currents up to 1,000 times higher than those obtained from previous types of metal ion sources. There are now several members of the MEVVA family, including two that are more than a foot long and two miniaturized versions that can sit in the palm of a person's hand.

Originally, MEVVA sources were built to provide beams of uranium ions for injection into the Bevelac accelerator at LBL for experiments in nuclear physics. Most recently, MEVVA sources have been used to fine-tune the composition of high-temperature superconducting thin films in order to optimize their properties. In the future, MEVVA sources may play a role in the coating of material surfaces with diamond-like films.

Fusion Energy

The goal of the Fusion Energy Program is to demonstrate the feasibility of magnetic fusion energy as a potential long-term, environmentally desirable energy source. The ultimate technology transfer objective of the program is the commercial application of fusion energy production, probably in the generation of electric power. Other applications also being studied include the generation of alternate fuels such as hydrogen, and breeding of fissile fuels and tritium.

Because development of magnetic fusion energy (MFE) is a high-technology endeavor and covers a wide range of scientific and engineering disciplines, useful inventions and technology spin-offs have resulted. The training of talented people has also been a key ingredient of the fusion development process. Many DOE laboratory researchers, university staff members, and graduate students working in fusion-energy research extend their expertise to benefit other endeavors.

The MFE Program uses industry to provide as many systems and components as possible. If there is an option to buy a compo-

nent rather than make it in-house, it is purchased. This practice provides a base of industrial expertise in relevant technologies and a direct increase in industrial capability.

The MFE Program also provides development funding to the industrial sector when program needs are ahead of the commercial availability of a technology. The development of millimeter wave tubes is one example. U.S. industrial firms have led the effort to develop the gyrotron millimeter wave tube, and are now the leading providers of these tubes. Similarly, very high-power shortwave broadcast tubes have been improved through development efforts sponsored by the Office of Fusion Energy (OFE). OFE has also worked with industrial concerns in developing technology for the Compact Ignition Tokamak Fusion experiment. Collaborative efforts have focused on developing techniques for the explosive bonding of large plates of high-strength materials.

The Fusion Engineering Design Center has effectively used industrial staff members as part of direct industry personnel exchange activities in the MFE Program. Participation by industrial personnel in the line organizations has proven very effective, and this practice is expected to be continued and enhanced.

Health and Environmental Research

DOE-supported research in medical applications, which is managed by the Office of Health and Environmental Research (OHER), has contributed significant developments in instrumentation, radiopharmaceutical development, and new clinical nuclear medicine procedures. Most of the nuclear medicine imaging instrumentation now in use was developed under the auspices of DOE and its predecessor organization.

The early work of the Atomic Energy Commission in producing and distributing radioisotopes and later developments in radiation detection instrumentation and modern computers have been major factors in the development of nuclear medicine as a clinical specialty. Recent emphasis has been on improving the spatial and temporal resolution ability of imaging devices for positron emission tomography (PET), and on the more widely available single photon emission computed tomography (SPECT). The radiopharmaceutical industry relies heavily on DOE laboratories as sources of stable and radioactive nuclides, and many of the production methods used by the industry originated in those laboratories. Also, technologies for instrumentation, computers, and nuclear chemistry that have been developed at some DOE laboratories are used in biomedical applications at other DOE laboratories.

The development of new radiopharmaceuticals has contributed improved agents for the study of body functions and the diagnosis of diseases of the brain and heart, particularly in

This 140-gigahertz gyrotron tube, which was tested to 400 kilowatts, is manufactured by Varian Associates of Palo Alto, California. Similar gyrotrons, which represent spin-offs from fusion energy research, have been used for plasma heating applications and as sources in heat treating complex ceramic components.

These micrographs, which were taken at Lawrence Berkeley Laboratory (LBL), demonstrate binding of monoclonal antibodies to cultured human breast carcinoma cells. A. Electronmicrograph demonstrating apical binding of LBL2 to subconfluent cultures as well as heterogeneity of binding. B and C. Light micrographs of peroxidase-stained 734B cultures labeled with LBL3 (B) and LBL1 (C). The arrows in B indicate extensive staining of edge cells in subconfluent cultures stained with LBL3. This effect was not apparent with LBL1, nor with any of the other antibodies. D and E. Paired phase and fluorescence micrographs demonstrating LBL3 antibody-binding to edge cells.

conjunction with PET and SPECT procedures. These technologies are made available to researchers working in clinical nuclear medicine and biomedicine.

At LBL, a high-resolution PET instrument has been constructed and put into use for brain and heart studies. The higher resolution of this instrument makes it possible to pinpoint the location of radioactive tracers in those organs. In the heart studies, this precise imaging is important for distinguishing viable areas of the organ that will benefit from bypass surgery. In the brain, the identification of small structures provides insight into the role of these structures in brain function.

At BNL, several studies are focusing on the effects of the most frequently abused drugs, alcohol and cocaine, and the mechanisms by which these effects are produced. A better understanding of the changes in the brain that occur with drug dependency and the neurological process that may predispose an individual to drug addiction could lead to more effective pharmacological interventions. Thus far, a correlation has been found between the subjective effect (i.e., the "high") and the concentration of labeled cocaine in the corpus striatum of the brain.

Another area of research with technology transfer potential for clinical applications is the use of labeled monoclonal antibodies in diagnosing and treating disease. For example, monoclonal antibodies that concentrate in lymph nodes may prove to be useful in diagnosing fevers of unknown origin. Other monoclonal antibodies are being developed for use in therapy of certain lymphomas and inaccessible cancers. At ORNL, a generating system for producing tungsten/rhenium-188 has been developed. Rhenium-188 is an excellent radionuclide for therapy, and there is an interest in using it to label chelating agents for monoclonal antibodies.

Researchers in the LBL Cell and Molecular Biology (CMB) Division are studying the characteristics of the surface glycoproteins of normal breast epithelial cells and breast tumor cells to detect how monoclonal antibodies react with human breast cancer cells. Over the past few years LBL scientists have generated several monoclonal antibodies that react with human breast tumor cells and have used them to study various aspects of tumor biology. Members of CMB have entered into a collaborative project with scientists from Triton BioSciences of Alameda, California. The collaborative effort examines the value of these antibodies as tools to monitor tumor-derived glycoproteins in the serum of breast cancer patients. Screening blood samples of approximately 50 cancer patients demonstrated that the monoclonal antibodies did indeed detect shed tumor glycoproteins in the serum. Ongoing experiments are directed towards determining the sensitivity of these antibodies and in assessing whether the antibodies offer advantages over other similar monoclonal antibodies that have been generated at other laboratories.

A new technique called synchrotron radiation-based transvenous angiography, combined with electronic X-ray detectors and computers, makes possible an attractive alternative to conventional angiography. Researchers at Stanford University have demonstrated the principles of iodine K-edge dichromography in phantoms, excised pig hearts, anesthetized dogs, and human subjects. These studies, which are supported by OHER, confirm that transvenous-dichromographic-coronary angiography is feasible with synchrotron radiation as the illuminating source. The studies also indicate that the increased X-ray fluence and improved spatial resolution possible from this technology should provide images of coronary circulation that could be useful in clinical situations.

The use of heavy particle beams for treatment of arteriovenous malformations and for treatment of tumors in the eye is well established. However, the use of neutron beams in a technique called boron neutron capture therapy is also being investigated for the potential treatment of brain tumors and melanomas. This treatment modality depends upon the selective concentration of a boron compound in the tumor being treated. A method called inductively coupled plasma spectrometry was developed at INEL for analysis of boron concentrations in tissues. This method allows boron research programs to use the less-expensive, natural-isotopic-ratio boron and to significantly reduce the required sample size. The new technique has become the standard method for analysis of boron concentrations in tissues.

At LBL, the structural biology of a cancer causing protein called *ras Oncoprotein* is being studied. Radiation, chemical, and environmental carcinogens damage deoxyribonucleic acid (DNA), thereby causing altered proteins to be produced in human cells. When the alteration occurs in *ras Oncoprotein*, the altered protein acts as a molecular switch for human cell growth. In cancer cells, this switch is stuck in the "on" position. Researchers at LBL have recently determined the three-dimensional structures of this molecular switch in both the "on" and "off" states. This precise structural information will now allow researchers to focus their efforts on designing drugs that could shut off this molecular switch in cancer cells. Many major pharmaceutical companies are interested in this effort.

Nuclear medicine also benefits from other DOE-supported research in radiation detection, nuclear instrumentation, and accelerator technology. For example, magnetoencephalography, a new technique for noninvasive study of brain function, relies on ultrasensitive superconducting sensor arrays and advanced computer data acquisition and analysis systems. Clinical applications are being evaluated in collaboration with the U.S. Department of Veterans Affairs and the University of New Mexico.

The Human Genome Project, which is focusing on the molecular-level characterization of the human genome, is one of

several Presidential initiatives to strengthen U.S. economic and technological competitiveness. The activity supports the traditional missions of the DOE to evaluate the health effects of energy-related agents, and to use DOE resources for beneficial applications in biology and medicine. The project represents a new approach, based on modern biology and technology, to evaluate the effects of low doses of radiation and chemicals on human populations.

The objective of this project is to provide the multidisciplinary scientific capabilities needed to both reduce the cost and increase the efficiency of DNA analysis. In recognition of these requirements and to facilitate technology transfer, the DOE established centers at LANL and LBL in September 1987 to study the human genome. The project also includes a major program of research and development at LLNL. These three Human Genome Centers are developing new resources and technologies required for the project, including research on innovative sequencing technologies, computerized data analysis capabilities, and the construction of physical maps of each of the 24 different human chromosomes.

The Human Genome Centers have entered into numerous collaborative agreements to develop and evaluate new instruments and biological resources. At LANL, a cooperative agreement and license with Life Technologies, Inc., of Gaithersburg, Maryland, is being negotiated to jointly develop a technique for sequencing DNA with a fluorescent, base-specific tag. At LLNL, the hardware and software for a Macintosh-based chromosome karyotyping system was jointly developed with Amoco and Delft University in the Netherlands. LLNL is working closely with Amoco to develop user-friendly application programs for karyotype analysis and to transfer the application to clinical and research laboratories. LBL has a formal collaborative research agreement with Cruachem of Herndon, Virginia, to develop an advanced instrument for low-cost, high-volume DNA synthesis.

A new X-ray imaging detector system has been developed for use in life-sciences research at synchrotron facilities. The system, which is based on a charge-coupled device detector, functions well at very high X-ray fluxes and can record two-dimensional diffraction patterns with high spatial resolution. Data can be acquired in times shorter than a millisecond so that fast, dynamic biological processes can be studied.

New imaging X-ray optical techniques are being developed to image biological structures at spatial resolutions far beyond the capability of optical microscopes. Intracellular structures as small as 0.1 micrometer can now be imaged in their native states by soft X-ray microscopy, with a potential for even better resolution as new synchrotron light sources are completed. With the advent of high coherent power insertion devices at synchrotron sources and

Surface roughness measurement being made on a cylindrical metal mirror with the WYKO NCP-1000 Digital Optical Profiler at Brookhaven National Laboratory (BNL). Large mirrors, 1 meter or more in length, can be accommodated easily on this system. Since the system noise level is below 1 angstrom RMS, extremely smooth surfaces are routinely measured with this instrument.

X-ray lasers, X-ray holography of microscopic structures is now feasible. Holograms with resolution of less than 1 micrometer have been recorded. By combining data from different views of a sample, a true three-dimensional image can be obtained.

The DOE also supports environmental research at both the national and international levels. One important effort supported by the DOE is the operation of National Environmental Research Parks at various DOE sites. The National Environmental Research Parks serve as outdoor laboratories where scientists and others conduct research on important environmental issues. The parks are unique because they provide opportunities for researchers to study the compatibility of the environment with energy technology options. Typical topics that are studied at the parks include wetlands protection, soil development, prairie restoration, climatic trends, waste cleanup, nutrient cycling, habitat reclamation, biodiversity, and ecosystem dynamics. Currently, National Environmental Research Parks are located at Savannah River, Oak Ridge, Fermilab, Los Alamos, the Nevada Test Site, Idaho Falls, and the Hanford Site.

In the 1970s, the DOE funded ANL to conduct a multiyear, multidisciplinary effort to perform research on how to restore lands degraded by mining. The legacy of that effort, the Land Reclamation Program, continues today as three projects. In one project for the U.S. Army, methods to rehabilitate lands impacted by military training are being developed. In the second project, in its eighth year of funding by the Gas Research Institute, techniques and methods to reduce the environmental impacts and costs of installing and maintaining pipelines continue to be developed. The third project is the Nepal Forestry Initiative, a multi-year effort funded by the U.S. Agency for International Development to introduce more efficient methods of producing fuelwood and fodder.

Scientists and government agencies in countries with extensive arid or semiarid lands are concerned with establishing policies and practices that will forestall or reverse desertification. At the same time, there is enormous pressure in these countries to manage the semiarid land to increase food production. Fundamental research on the physiological ecology of arid-land plants, which has been carried on at UCLA for more than a decade under DOE sponsorship, is attracting the increasing attention of scientists dealing with these problems. Much of this work has focused on the study of water relations and carbon fixation in Crassulacean acid-metabolism (CAM) plants. These plants, many of them succulents and often prominent components of plant populations in the desert, are remarkable for their water-use efficiency, heat tolerance, and surprisingly high productivity in arid environments.

Deserts characteristically have low plant productivities—about 1 metric ton dry weight per hectare per year. Agronomic crops, such as corn, rice, and soybeans, have productivities about 10 times higher than desert plants. The DOE-supported research at UCLA has shown that many agaves and cacti, which are native to New World deserts but are cultivated worldwide, often achieve productivities in desert environments approaching those of crops like rice and corn grown in nondesert areas.

The Ocean Sciences Division at BNL has modified, tested, and used an acoustic doppler current profile to count and determine the size of zooplankton in the ocean. The BNL system can provide profiles at approximately 50 depth intervals in the water column and at intervals of 5 minutes. This capability means that marine biological measurements can be made at the same frequency as physical measurements, thereby making it possible to couple physical and biological dynamics in the ocean in ways not previously possible. This technology is expected to revolutionize the way biological oceanography is conducted, especially when coupled with other new high-frequency biological measurement instruments.

The BNL acoustic doppler current profiler has been used in the DOE/Shelf Edge Exchange Process Program (SEEP) and the Biosynop and Coastal Transition Zone Programs of the Office of Naval Research. The instrument is one of five key instrument packages to be deployed on ships by the U.S. Coast Guard, the U.S. Navy, and the National Oceanic and Atmospheric Administration (NOAA) for monitoring ocean systems. Computer software developed for the instrument has been given to North Carolina State University, the University of Washington, and NOAA for use in their research programs.

In 1989, the DOE supported development of technologies to meet the pressing need for collecting ocean data in support of the World Ocean Circulation Experiment (WOCE). A major thrust of

WOCE is the ocean-wide survey of hydrography (i.e., characteristics such as temperature, salinity, density). Oceanographers at Battelle Marine Sciences Laboratory in Sequim, Washington, successfully tested a microcomputer-controlled, aircraft-deployed, expendable-conductivity, temperature, density (AXCTD) sensor in the Pacific Ocean off San Diego and in the Puget Sound in Washington. The AXCTD sensor represents a potentially significant contribution from DOE to the WOCE program. The instrument is deployed in a shockproof container so it can be dropped from either airplanes or ships. The sensor takes a profile as it descends, and then can be programmed to return to the surface obtaining a second profile, with a time delay of up to 2 years. It can also be put into an inactive mode that will allow an oceanographic event to trigger its return to the surface. Once at the surface, the AXCTD sensor uses a satellite link to transmit data, including surface data collected as it drifts. At the Oceans '89 and Marine Instrumentation '90 meetings, the sensor package was enthusiastically received. Two invention disclosures have been filed on the sensor.

Small Business Innovation Research Program

The Small Business Innovation Research (SBIR) Program is now in its ninth year, and it shows increasing success. The program continues to strengthen the role that small, innovative firms play in meeting the Nation's research and development needs, and in stimulating technological innovation and commercialization of ideas developed through federally funded research and development. The participating agencies in the SBIR Program all have extramural research and development budgets of over \$100 million, and are required to set aside 1.25 percent of their budgets to fund SBIR projects. The General Accounting Office (GAO) is preparing a report, due next year, that will summarize the successes achieved by small companies in commercializing the products and processes developed under the SBIR Program. The GAO has already determined that the program has had favorable effects on agency research in most of the 11 participating agencies.

In the DOE SBIR Program, competitive Phase I awards of up to \$50,000 for about 6 months are made annually to 150 or more recipients to explore the feasibility of their ideas. Nearly half of those recipients receive Phase II funding of up to \$500,000 for 2 years. The Phase II funding is used to conduct research and development that advances knowledge to meet particular program needs. The DOE SBIR Program has the unique feature of providing for optional early submission and rapid evaluation of Phase II proposals, so that Phase II can be started without a lapse in funding. For Phase III of the program, contractors completing Phase II can seek non-Federal funding to pursue commercial applications, or non-SBIR Federal funds to support further work of interest to an agency.

Improved sensors for monitoring the oceans will provide the tools to quantify ocean structure and heat uptake. The AXCTD sensor, which was developed at the Battelle Marine Science Laboratory under DOE support, is an example of such a new tool.

This gas purifier, developed by Advanced Technology Materials Inc., with SBIR Program support, is used to remove water, oxygen, and other contaminants from the gases commonly used in the manufacture of solar cells and semiconductors. The resulting solar cells showed a 30 percent or more increase in photocurrent, and the microcontamination of the semiconductors was greatly reduced. The gas purifier received a 1988 R&D-100 Award.

As mandated by the legislation enabling SBIR, the entire DOE program, except for Defense Programs, contributes to the annual SBIR Program budget of nearly \$40 million. An annual solicitation for proposals with about 30 technical topics is issued, and awards are made solely on the basis of scientific and technical merit, regardless of topic. Staff members from the DOE laboratories provide help in topic preparation and in reviewing proposals. Other members of the laboratory staff (with due regard for possible conflicts of interest) sometimes assist proposers as consultants or through agreements to do "work for others" at cost. In several instances, a DOE laboratory has provided facilities and equipment at no cost to support an SBIR Program contract.

In response to the 1990 solicitation, 1,172 proposals were received for Phase I awards, and 170 grants were awarded. From the previous year's 161 Phase I projects, 66 were selected for Phase II awards.

The DOE continues to receive reports of Phase II projects that are achieving success in Phase III. For example, a Phase II award was made in 1988 to Advanced Technology Materials, a high-technology firm based in New Milford, Connecticut. This award has already resulted in the development of a device for removing key contaminants from gases used in the chemical vapor deposition of solar cells and semiconductors. The device earned the company a 1988 R&D-100 Award, and has already become an industry standard. For 1990, sales of this product amounted to \$7 million. Investments in the company to develop the product have reached about \$6 million.

In another recently reported success, a new metal-ceramic composite material with excellent abrasion and impact resistance was developed by Waste Energy Technology Corporation of Bedford, Massachusetts, under a Phase II award made in 1985. Under Phase III, \$4 million in investment has been received for commercializing the product, which will be used in the hammers that shred trash in municipal solid waste processors, and for the cutters used in mining coal and rock.

An on-line optical probe for particle counting was developed by Insitex of San Ramon, California, under a Phase II award made in 1986. In Phase III, sales of over \$1 million have already been achieved for the device, which makes in situ measurements of absolute particle concentration, size, and velocity in large-scale combustors and materials processing plants. These measurements are used for process monitoring and control.

In 1990, successful Phase II contractors from the past four DOE competitions were invited to participate in a training workshop where they were given assistance in developing business plans and in meeting with potential partners, investors, or licensees. As a result of this project, one SBIR company has

obtained commitments of \$1.2 million from private-sector funding sources to be applied to commercialization activities, and several other companies are involved in serious negotiations with funding sources.

The SBIR Program enables the DOE to obtain effective, innovative solutions to important problems through the private sector, which has an incentive to pursue the resulting technology and bring it to the marketplace. The growing number of contractors, many of whom started in business in response to SBIR solicitations, is becoming a significant resource for the solution of additional high-risk, high-technology problems for the DOE.

R&D Laboratory Technology Transfer Program

The R&D Laboratory Technology Transfer Program conducts and supports a variety of technology transfer activities that cross-cut the laboratories and the DOE research programs. The program is linked with the Institutional Planning Process established by DOE to guide the current and future activities of its laboratories. The program also sponsors technical personnel exchanges and technology transfer initiatives at the laboratories.

The program provides DOE-wide coordination and communication of laboratory opportunities and accomplishments. Activities in this area include:

- Recommendations for laboratory policies
- Participation in DOE and interagency reviews of laboratory technology transfer efforts
- Development of database systems on laboratory technology transfer efforts, accomplishments, and opportunities
- Development of this *Technology '90* report
- Development of an annual report to the Congress on plans and activities of the laboratories in technology transfer as required by the National Competitiveness Technology Transfer Act (NCTTA)
- Sponsorship of a traveling exhibit of the technologies that won R&D-100 Awards
- Evaluations of technology transfer effectiveness
- Coordination of the laboratory Offices of Research and Technology Applications (ORTA) through meetings and workshops.

Transferring technology to small business. Director of Laboratory Development at SNL, Gerry Yonos, and Ioana McNamara, President of Perma Charge, which is located in Albuquerque, New Mexico, sign an agreement that provides Perma Charge exclusive rights to manufacture an SNL-developed foam in exchange for royalty payments.

University engineering faculty attended a 1990 Summer Institute where they used DOE-developed computer software for analyzing energy-efficiency improvements for buildings. This hands-on approach allows professors to utilize the software prior to introducing it to their students.

The R&D Laboratory Technology Transfer Program has sponsored technical personnel exchanges involving the DOE laboratories since 1987. The purpose of these exchanges is to provide an opportunity for representatives of private industry and the laboratories to become personally acquainted with each other's facilities and personnel. This occurs by 1) staff from private industry coming to the laboratories to work directly with laboratory personnel and facilities, or 2) laboratory staff going to a private industrial laboratory or site. The costs of the exchanges are generally shared between the participating companies and laboratories. Support from the R&D Laboratory Technology Transfer Program is provided to help defray the costs of the exchanges to both parties. Exchanges typically last from 3 to 6 months, although opportunities for longer exchanges are also available.

In FY 1990, the program supported 18 technical personnel exchanges, involving 28 industrial staff and 11 laboratory staff. Six of the 18 exchanges were two-way exchanges involving both the temporary assignment of industrial staff to a laboratory and assignment of laboratory staff to an industrial site. Topics addressed in the FY 1990 exchanges ranged from the properties of high-temperature superconducting materials to new process technologies for making paper more efficiently. Reports on the results of the exchanges are submitted by the laboratories, but are not yet available for FY 1990. Example highlights of exchanges conducted in FY 1989 include:

- Staff from Micro Surface Company of Morris, Illinois, and ANL collaborated to determine whether a coating process developed by Micro Surface could extend the performance of cutting tools coated by a titanium nitride process that was developed in part under a DOE tribology research program. A series of tests performed at ANL found that the coating process reduced the wear rate for high-speed steel inserts, but generally did not decrease the wear rate for cemented-carbide inserts.
- Staff from Ultra Tool Inc. in Mokena, Illinois, and ANL investigated several methods for depositing diamond and diamond-like carbon coatings on cutting and slitting blades. Preliminary results of the work indicate that it is possible to deposit diamond and diamond-like carbon films using chemical vapor deposition methods. The successful development of commercial processes to deposit such films on substrates could have significant benefits for many industries.
- Staff from Mobil Research and Development Company utilized facilities and staff at LBL to study the synthesis of a zeolite catalyst developed by Mobil. The picture of zeolite processing that emerged from the collaboration offers the potential for guiding the selection of organic templating agents for the synthesis of other zeolites.

- Staff from LANL and AMTECH Company of Albuquerque, New Mexico, collaborated to develop microwave interrogation "Read-Write Tags" for equipment identification and tracking. Development of the two-way, encrypted tags is expected to benefit LANL missions in weapons treaty verification and AMTECH efforts to better serve its customers in the transportation industry.

- An employee of Fisher Barton, Watertown, Wisconsin, used knowledge gained through an exchange at SNL to improve the quality of agricultural tools and knives manufactured by his company through the application of plasma-spray applied coatings. Technology gained through the exchange was used in developing a new corn-harvesting cutter with improved wear and fracture-resistance compared to currently-used cutters, many of which are manufactured in Europe.

- ORNL successfully transferred to General Electric and other industrial participants a plasma-assisted laser deposition process for forming high-temperature oxide superconductor thin films on substrates.

The initiatives supported by the R&D Technology Transfer Program are aimed at demonstrating new and innovative methods of technology transfer. In FY 1990, three initiatives were funded. One is aimed at transferring advanced materials-related technology developed at DOE laboratories to small, high-technology businesses in Michigan. Faculty from 2-year community and technical colleges in Michigan are playing a key intermediary role in the transfer and dissemination process. Another initiative is being conducted through ANL to make available to small- and medium-size Illinois businesses the resources and expertise in advanced scientific computing. The third initiative is directed towards developing partnerships between several DOE laboratories and private companies within the ANL High-Temperature Superconductivity Pilot Center.

Highlights of the FY 1989 initiatives include the conceptual development and preliminary design of a computer-based, interactive-information kiosk on energy efficiency by LBL. Based on this effort, LBL received a contract from Southern California Edison to develop an interactive kiosk for its new Customer Technology Application Center. Initiatives supported by the program in FY 1989 also resulted in the formation of several technical and information-sharing alliances between DOE laboratories, National Science Foundation research centers, National Institute of Science and Technology laboratories, universities, and private companies related to high-temperature superconductivity research.

■ DEFENSE PROGRAMS

Defense Programs (DP) manages the nuclear weapons program for the DOE and conducts a broad range of activities integral to national security. This vital mission encompasses weapons development, production, and testing; nuclear nonproliferation policy formulation and related activities; special nuclear materials production and transportation; hazardous waste and remedial actions; arms control and verification; nuclear safeguards and security; classification, export control, and technology security; and intelligence analysis and liaison.

The United States continues to devote more Federal funds to support essential research and development activities than any other nation; however, almost 70 percent of that effort supports military research and development, which in the past decade yielded relatively few commercial spin-off technologies. Furthermore, when technology commercialization did occur, it did so incidentally. Clearly, improving commercial sector use of Federal research and development resources will not only require modification of existing practices, but also increased awareness among Federal researchers of the technology requirements of industry. It will also entail forging new linkages among government, academia, and industry to facilitate technology transfer. Recent congressional actions have brought this goal closer to reality.

The National Competitiveness Technology Transfer Act (NCTTA) creates an opportunity to more fully utilize the resources resident in the nuclear weapons complex to simultaneously foster technology transfer of unclassified research and development and comply with the primary mission of DP, which is national security. In addition, Section 91 of the Atomic Energy Act was amended to emphasize the importance of transferring "federally owned or originated technology to state and local governments, private industry, and universities or other nonprofit organizations" by making these activities a mission of DP.

The Precision Manufacturing Technology Program at Oak Ridge National Laboratory (ORNL) will allow researchers and industrial representatives to work with state-of-the-art precision manufacturing equipment and processes.

The DOE defense complex spans 13 states and consists of four major laboratories, as well as a number of smaller laboratories, production facilities, and test sites. With facility assets of over \$100 billion, an annual budget of about \$7 billion (of which more than \$3 billion is for research and development activities), and a highly skilled work force that includes more than 6,000 scientists and 11,000 engineers, the DP complex has much to offer U.S. industry in terms of resources, technical expertise, and technologies. DP facilities possess capabilities in a broad range of advanced technologies, ranging from basic research to precision production techniques. In addition, personnel participating in these activities have problem-solving capabilities that can be put to work through new types of public and private collaborations to enhance U.S. economic advancement. DP is one of the few Federal programs that advances technologies from basic research completely through to product application.

The Defense Programs Technology Transfer Initiative, which originated in 1988, facilitates the integration of DP technologies and capabilities into the mainstream of the U.S. economy. In general, this initiative involves the transfer of unclassified technology and is governed by four principal goals: 1) to make available the total resources of the complex to maximize the impact on the U.S. industrial economy; 2) to work with industry to create a favorable business climate and foster confidence that DOE can establish speedy and equitable business arrangements; 3) to make available the technical skills of the complex to simultaneously benefit U.S. industry, the U.S. labor force, and the U.S. educational system; and 4) to work with industry to develop methods of cooperation that are mutually beneficial.

The Advanced Manufacturing Initiative (AMI) is a pivotal element of the DP program. This initiative forges an alliance between DP, the defense complex, and the U.S. manufacturing industry that will advance the manufacturing capabilities of both DP and U.S. industry. The first effort under this initiative involves the National Center for Manufacturing Sciences (NCMS), the largest research and development consortium in the United States with over 100 member firms. The AMI encompasses all manufacturing related activities within DP and the defense complex, ranging from machine tools to advanced quality control methods. Additionally, the collaborative framework and management structure of the AMI encourages complex-wide involvement and promotes enhanced relationships with industry in areas of common interest.

Another part of this plan is the Precision Manufacturing Technology (PMT) Program, which is designed to transfer technologies developed by the DP complex of production and design facilities to U.S. industry and help improve the strategic position of U.S. manufacturing firms. The mission of the PMT Program, which is managed by ORNL, is to assist U.S. manufacturers and

Methods used in the Precision Manufacturing Technology Program at Oak Ridge National Laboratory (ORNL) to transfer advanced manufacturing technologies developed under DP sponsorship to U.S. industry.

machine-tool builders to better respond to the emerging markets for precision flexible manufacturing systems by transferring existing technology through validating demonstrations, licensing, training, and the conduct of applications development.

In its planning phase, the PMT Program developed a specific strategy to effectively reach and respond to U.S. manufacturing companies. Members of the PMT Program have traveled across the United States to research existing technology transfer sites in order to establish a networking relationship with current State and Federal extension services. The program is also actively pursuing relationships with universities and technical schools throughout the Nation. These academic institutions can make use of the resources of the PMT Program and act as brokers for their industrial affiliates.

The program is currently working with the National Center for Manufacturing Sciences (NCMS) and other leading national manufacturing organizations to effectively identify targeted industrial firms. On June 13, in cooperation with the NCMS, the PMT Program hosted its first national conference to inform U.S. manufacturers of its objectives. This conference inspired a great deal of interest from some of the Nation's leading manufacturers. Plans for the future include establishing user centers designed to deploy the best available manufacturing practices through demonstrations, training, and applications development.

Recently, DOE established the Specialty Metals Processing Program at SNL to perform unclassified research to advance the state of the art in this critical field where the United States, for the past several years, has lost considerable ground to foreign competition. The research will be primarily conducted at various facilities within the Melting and Solidification Laboratory complex at SNL. In particular, researchers will have access to a new 310 kilowatt-electric (kWe) electron beam melting furnace, the only one of its size available in the United States solely for research purposes. This program will allow industry interns and/or university graduate students to gain hands-on experience by participating in research projects. Information generated by the program will be made available to all participants; however, external release of the information will be withheld until 3 years after the date it is distributed to program participants, unless all parties agree to release the information earlier.

Recently, representatives from the specialty metals industry approached DOE to propose the formation of a consortium under the auspices of the National Cooperative Research Act. Following several consultations, 10 companies agreed to participate in the Specialty Metals Processing Consortium (SMPC). Each participant has agreed to pledge \$50,000 per year for the next 5 years to partially fund SMPC activities. In turn, the consortium is entering into a contract with the DOE Albuquerque

Operations Office to administer the program. Any proposed research program must be mutually agreed to by SMPC, SNL, and DOE. The research programs will be implemented through Project Letter Agreements.

DP is engaged in a number of activities that may ultimately strengthen the U.S. industrial base. Towards this goal, an objective of DP over the next year is to begin testing and utilizing new technology transfer mechanisms and collaborating extensively with new industry partners in areas of precompetitive research and development to provide mutual benefit to the defense complex and U.S. industry.

The Office of Nuclear Energy (NE) is responsible for administering advanced technology programs and projects for nuclear fission power generation and fuel technology; the evaluation of alternate reactor fuel cycle concepts; and the development of space nuclear generator systems, naval nuclear propulsion plants and reactor cores, and nuclear waste technology.

Although initial atomic research was necessarily focused on the development of an effective weapon for use in World War II, scientists speculated that reactors could be developed that would actually breed nuclear fuel, producing more fissionable material as a byproduct of the chain reaction than would be consumed by the fission process itself. After the war, the U.S. Government began to encourage the development of nuclear energy for peaceful civilian applications. The AEC, which was created in 1946, authorized the construction of the Experimental Breeder Reactor I, which generated the first electricity from nuclear energy on December 20, 1951.

In addition to the generation of electricity, nuclear technology plays an important role in medicine, industry, science, food processing, and agriculture. Radioisotopes, for example, are used to identify and investigate the cellular and molecular bases of diseases, as well as to complement traditional medical treatment and therapy. In industry, radioisotopes are used for measuring microscopic thicknesses, detecting irregularities or "voids" in metal castings, and testing welds. Nuclear irradiation is used in the preservation of food, a process that causes less vitamin loss than canning, freezing, or drying, without danger that the food will be made radioactive.

In addition to its mission of transferring nuclear power technology to the U.S. commercial market, NE is committed to transferring spin-off technologies to industries that will strengthen the U.S. national economy. Westinghouse Hanford Company (WHC) operates the Hanford Site Fast Flux Test Facility (FFTF), which is a

■ NUCLEAR ENERGY

world-class irradiation and test facility. The FFTF operational experience and the technology developed in its design and construction form a technology base that can have widespread economic impacts. WHC is using several communication techniques to enhance the technology transfer process: videotapes, feasibility demonstrations of available technologies, and specialized technology seminars have been effective in communicating information about available technologies to interested parties.

The FFTF, which established a record for nuclear reactor operating performance, uses a 12-hour operator shift. A study about FFTF operations, which is described in a report entitled *Operator Efficiency and Safety During Transition From 8-Hour to 12-Hour Shift Schedules*, is recognized by the industry as being the most comprehensive of its kind, and is recommended as background information for anyone contemplating changing to 12-hour shifts at their facilities. This operational experience is being made available to industry and was shared with representatives of utilities, power plants, and pipeline operations at a workshop on "Shiftwork Management in the 1990s." An FFTF work scheduling program, called "Plan of the Day Scheduling Program," is also being made available to commercial nuclear plant operators. This software provides a convenient way for scheduling and controlling staff resources in the operation of a complex facility.

The increased sensitivity to the environmental impact of buried wastes has opened up opportunity for the commercial use of disposal technologies that were developed for radioactively contaminated wastes. One of these technologies, which was developed under NE sponsorship, provides a way to dispose of combustible solid waste material, such as neoprene rubber, polyethylene, latex, polyvinyl chloride, plastic vials and tape, soft plastic tubing, and spent ion exchange resins. This process, which uses acid digestion, reduces waste volumes by a factor of up to 160. The degree of volume reduction experienced for a specific waste will depend on the amount of inorganic constituents present. The final residue or "ash" is inactive and suitable for shipping, storage, or recovery of the inorganic constituent. This technology is being made available for licensing.

The continuing progress in technology transfer experienced by NE illustrates that a progression of hands-on communication and personal interaction with a prospective technology user are key elements in the technology transfer process. Site visits and personnel exchanges are also being encouraged as a means of transferring technology.

The Office of Conservation and Renewable Energy (CE) is responsible for programs that increase the efficiency of energy utilization and the amount of energy produced from renewable sources. Research programs funded by CE are organized by end-use sectors and are managed under the Offices of Utility Technologies, Industrial Technologies, Transportation Technologies, and Building Technologies. Descriptions of technology transfer accomplishments for these programs follow.

■ CONSERVATION AND RENEWABLE ENERGY

Utility Technologies

In recent years, advances in photovoltaic (PV) technology have been made both in research and in the development of industrial capabilities, products, applications, and markets. The National Photovoltaics Program is directed toward providing industry with the technology base to produce high-performance, low-cost photovoltaic products for terrestrial power applications. The success of the program is due primarily to the good working relationships developed among industry, universities, and the DOE laboratories.

One of the major projects undertaken to date has been the Photovoltaics for Utility-Scale Applications (PVUSA) Project for which SNL has served as the focal point for DOE. PVUSA, a public/private-sector partnership, assesses promising PV technologies in a utility setting, looking toward cost-effective commercialization by the mid-1990s. When completed in 1991 in Davis, California, PVUSA will consist of 11 systems ranging from 20 to 400 kilowatts. Information generated from these systems will greatly assist the PV industry.

The Amorphous Silicon Program, a government/industry cost-sharing effort administered by the Solar Energy Research Institute (SERI), continues to make progress and serve as a model for technology transfer at SERI and throughout the DOE laboratory network. Another example of technology transfer within the PV Program, the Design Assistance Center (DAC) at SNL, provides technical assistance to a wide range of interested companies and individuals, primarily in the area of PV systems design and engineering. Over the past 2 years, the DAC has assisted over 75 separate organizations.

In 1989, the PV Program continued to achieve success, particularly in thin-film and concentrator technologies. An important step in thin-film technology was the development of a cadmium telluride cell with an efficiency of 12 percent by Photon Energy of El Paso, Texas. The first commercial-size, cadmium-telluride system (20 kilowatts) was scheduled to be installed at the PVUSA project site by the end of 1990. This was an additional milestone marking DOE support of a new, industry-generated idea that resulted in a viable commercial project.

These geothermal power plants at Coso Hot Springs are operated by California Energy Company. These plants, which are located on the China Lake Naval Weapons Center, are part of a 240 megawatt-electric (MWe) development.

In the area of solar energy concentrators, Alpha Solarco Inc. and Solelectric Corporation, both of Cincinnati, Ohio, completed installation of a demonstration station for their first Modular Solar Electric Power Generator in Pharrup, Nevada. The steel-structured unit, which is the world's largest single photovoltaic concentrator, houses 100 modules designed to produce 9.2 kilowatts of power. These companies combined a significant amount of the module technology developed at SNL, especially in cell assembly and housing design, with their own engineering technology to produce a low-cost, high-concentration module. The system is intended to be a supplemental source of energy for utility power plants during peak-load hours.

DOE research in the concentration of solar energy and its conversion to electricity has resulted in the development of technology that is being increasingly used. Luz International Ltd. is operating eight parabolic trough solar thermal plants that feed 274 megawatts of electric power into the Southern California Edison grid. An additional 80-megawatt plant is under construction. By the mid-1990s, under current contracts, Luz will have over 650 megawatts of solar-to-electric capacity in place. Another company, Industrial Solar Technology Corporation, operates a solar thermal cogeneration plant in Colorado, also using parabolic troughs, and is constructing a second plant in California. Technologies developed and demonstrated under the DOE program for the parabolic trough system include advanced mirrors, advanced heat transfer fluids, evacuated tube receivers, selective absorber coatings, and advanced drive control systems.

Solar thermal systems using Stirling dish technology are still in the developmental stage, but several companies view the technology as promising and are actively working with both DOE and NASA in building commercial prototypes. These companies include Cummins Engine, Westinghouse, and Stirling Technology. Applications envisioned include both connected systems for utility grids and stand-alone systems for remote operation on earth or in

space. Already, Stirling dish systems developed with DOE support by McDonnell Douglas and Advanco/Vanguard have demonstrated 29 percent net solar-to-electric system efficiency, the highest in the world for solar technologies.

Geothermal research has made great strides in assisting the utility sector in reducing both the risk and cost of geothermal power generation projects. Confidence in the accuracy of reservoir production predictions is vital to further cost-effective geothermal energy development. Advanced technologies are, therefore, under development to predict the size of a reservoir, how much power it can produce and for how long, and to characterize its physical and chemical properties. Accomplishments in well-testing techniques promise to expand the understanding of reservoir behavior. New methods of computer analysis are being successfully applied to the interpretation of borehole geophysical measurements and are yielding a 10-fold improvement in determining reservoir performance. A field test of several exciting new organic chemical tracers successfully demonstrated the interaction between injection and production wells. This accomplishment provided an improved means for avoiding premature breakthrough of the cooler injected fluid into the hot producing zone, significantly improving reservoir performance.

Drilling and completing geothermal wells are major cost components in power projects, accounting for 30 to 50 percent of the total cost. A major factor in geothermal drilling is the loss of costly drilling fluids when a borehole encounters open fractures in the rock formation. Researchers are developing methods of analyzing these fluid loss situations and developing systems for emplacing special materials to control the losses. In addition, research continues on a technology that will facilitate directional drilling from nonproductive wells near the fluid-filled fractures. This technology will improve production and prevent the loss of production wells during drilling.

Another significant milestone in reducing drilling costs is the development and patenting of a downhole cement that will withstand high-temperature geothermal environments. This material will reduce the costs and extend the lives of geothermal wells.

A major highlight of FY 1989-90 geothermal research and development is the first successful use of experimental geopressured brines for power generation. In the pilot unit (1 MWe), methane separated from the brine was burned in a gas engine to generate electricity directly. Exhaust heat from the engine was then combined with the thermal energy in the brine to generate additional electricity. This type of system is capable of producing 20 percent more power than units utilizing each energy source separately.

Wind turbines built by U.S. industry may soon be operating with new high-performance blades. Special airfoil shapes are being developed by scientists at SERI. By making subtle changes in the airfoil shape, size, and structural properties, the turbine blades are tailored specifically for operation in the highly turbulent conditions in which wind turbines must perform.

Following a series of airfoil tests in wind tunnels, it was determined that gains in energy capture could be achieved by departing from the conventional principles of aircraft propeller design upon which earlier wind-turbine rotors had been based. The two applications have very different requirements. For aircraft propellers, a very high lift coefficient is desirable to prevent stalling under heavy loads. Wind-turbine rotors, however, need to stall in high winds to prevent damage to generator components. The new airfoils are designed to stall, thereby limiting peak power produced and reducing structural loads. As a result, longer and more efficient blades that capture more energy without increasing turbine structure can be used. The result is increased energy production, with little increase in turbine cost and reduced operation and maintenance costs.

To encourage technology transfer, field testing of the new blades was accomplished under a cooperative research agreement with industry. A commercial 100-kilowatt turbine was equipped with the new lightweight blades. In side-by-side tests with turbines with conventional-design blades, energy output increased 20 to 25 percent at wind speeds from 10 to 25 mph.

SERI's 7.9-meter fiberglass blades are designed to replace smaller, foreign-built blades now being used on about 3,600 wind turbines in California. Industry experts predict that most, if not all, of these blades will need to be replaced in the next decade, creating a potential market in excess of \$30 million for American manufacturers who can offer superior blade designs. SERI is also developing 9-meter blades with potential for \$15 million in sales during the next decade. These projected markets do not include blades for new wind turbines, which are being installed at the rate of about 300 to 500 machines a year in California alone.

Throughout the development and verification effort of the new airfoils, technology transfer has been a primary concern. Transferring the technology to a still-developing U.S. wind industry indicated that SERI should enter into joint ventures with both the manufacturers and users. Substantial effort by SERI had to be devoted to the structural design and quality control of the blades. This effort was followed by performance verification on a candidate machine at a user's site, a process for which SERI recently received a Federal Laboratory Consortium Award.

Industrial Technologies

Technology transfer plays a pivotal role in enabling the Office of Industrial Technologies (OIT) to accomplish its primary objectives of improving industrial energy efficiency and fuel flexibility, and reducing industrial wastes. Success in these objectives will help to enhance U.S. industrial productivity and competitiveness and to mitigate negative environmental impacts. Toward this end, OIT has developed a set of effective mechanisms for communicating information on new conservation-related advances and for making the results of its research and development promptly available to industry.

OIT regards technology transfer as an integral facet of its overall planning and development efforts performed through a continuum of activities from the inception of a concept through the final commercialization by industry of the process or technology. In order to be responsive to the needs of the industrial sector and to maximize acceptance of new technologies when they are ready for commercial application, OIT works closely with appropriate industry representatives.

The variety of technologies and markets being pursued by OIT creates the need for a wide range of technology transfer mechanisms. These mechanisms reflect the different ways in which new technologies are adopted by industry. The selection of techniques to transfer a particular technology is based on the particular research, the comparative risk of the technology, the capabilities and resources of the research partners, and the segment of the economy most likely to benefit. The major technology transfer mechanisms employed by OIT are cooperative efforts with industry; technical assistance; scientific user facilities; licensing agreements; spin-off companies; research and development working groups; educational activities; and publications, presentations, and other outreach activities. Examples of new, energy-saving technologies that have recently been commercialized are described below.

Concentration of liquids, particularly concentration of fruit and vegetable juices, is one of the most energy-intensive steps in the food-processing industry. Almost all concentrated juice made in the United States is produced using some type of evaporation process during which water is removed from single-strength juice to yield a product consisting of 50 to 70 percent solid material. Semipermeable membranes are also used to concentrate juices by separating water from the solution. Expanded application of this technology offers good potential for saving energy.

OIT funded an investigation by the National Food Processors Association into the application of high-temperature hyperfiltration to food processing. The study focused on the use of thin-film composites, a new class of membranes with several

The toughness of ceramic materials can be substantially increased by the addition of ceramic fibers. In this picture, the sizes of a typical ceramic fiber (NICALON) and a silicon carbide (SiC) whisker are contrasted with a human hair. Research conducted at ORNL is developing know-how to help optimize the placement of fibers into ceramic matrices. This process is known as "fiber architecture."

This diagram describes the process developed at the Solar Energy Research Institute (SERI) for producing adhesives from wood waste and bark. In this process, wood waste is converted to a complex pyrolysis oil that contains a phenolic-rich fraction. The phenols from this fraction are extracted and then used to produce phenol/formaldehyde (PF) thermosetting resins that are used in the manufacture of composite wood products, such as plywood and particle board. The phenols from this process can be used as substitutes for the petroleum-derived phenols that are conventionally used to produce PF thermosetting resins. SERI was awarded a 1990 R&D-100 Award for this technology.

advantages over standard cellulose acetate membranes. The membranes tested in this effort were found to withstand higher temperatures, to operate within a wider pH range, and to have increased resistance to biological degradation. The tests were conducted using several configurations in selected high-temperature food-processing streams in order to characterize membrane performance as a function of time. As a result of this effort, a prototype unit for concentrating tomato juice was built and tested successfully at a commercial site.

The increased use of plastics in recent decades has resulted in increased levels of plastic wastes at both the consumer level and the producer/fabricator level. Recycling efforts are complicated because different types of plastic wastes must be separated from one another before further processing can occur. The nature of plastics makes such separation a difficult procedure. For example, selective incineration is hampered by the thermal degradation of plastics at high temperatures, and flotation techniques cannot be employed because of the narrow range of densities in plastics.

As part of a larger project to convert waste plastics to fuel oil, DOE and the Proceadyne Corporation developed an innovative combination of separation processes that assist in recycling polyethylene terephthalate (PET) beverage bottles. At a demonstration plant, approximately 20 million pounds of bottles and cans were sorted for recycling according to those made of PET, high-density polyethylene, or aluminum. The separator is currently being used at a Pepsi Cola plant, where it is recycling 12 to 18 million pounds of PET annually.

Drying operations represent approximately 5 percent of the total energy requirements for the U.S. industrial sector, and this energy is lost mainly through dryer exhaust gas. Dryer energy consumption can be reduced through use of sensors and control systems to accurately and continuously monitor the humidity and temperature of the exhaust gas. However, existing sensors are often unsuitable for continuous use in many common industrial drying processes due to the high temperatures and contamination encountered.

One sensor capable of withstanding these types of conditions is the heat flux dew-point hygrometer, developed by Trans-Met Engineering with funding from DOE. This hygrometer is insensitive to dust and grease and can operate in temperatures up to 500°F and in relative humidities between 50 and 100 percent. A prototype unit of the new sensor was successfully tested at a textile mill. The hygrometer was subsequently commercialized and is being used in the food processing, pulp and paper, chemical, textile, and cement industries.

The pulp and paper industry has long recognized the value of accurate humidity measurements during drying operations to optimize process control and minimize energy consumption. Although many types of humidity sensors have been developed, they have experienced reliability problems in mill environments. With DOE support, two firms have developed a new hygrometer that determines humidity by measuring the absorption of ultraviolet (UV) light. Because the absorption of UV light is a property of the water vapor in the medium (air or process gas), the optical elements of the sensor can be kept from direct contact with the medium, protecting the sensor from contamination. The primary applications of the hygrometer in the pulp and paper industry are in controlling the drying of paper and paperboard. The new hygrometer can be used as a feedback device in the control of a dryer loop, helping to maximize drying efficiency by optimizing the balance of exhausted air and makeup air. Achieving this balance results in energy savings and improved product quality. After successful field testing, the hygrometer was commercialized and has been installed in several pulp and paper mills. The sensor also has applications in the textile, food, and other industries.

Transportation Technologies

The transportation sector is the largest single user of imported fossil fuels and also contributes significantly to air pollution and urban congestion. The Office of Transportation Technologies (OTT) supports a number of programs aimed at reducing and/or providing alternatives to the use of fossil fuels in the transportation sector. Selected highlights of these programs are described below.

The Electric and Hybrid Vehicles Program within OTT has supported development of a full-scale, sodium-sulfur battery by Chloride Silent Power Ltd. (CSPL) of the United Kingdom. This battery demonstrated a range of 150 miles for an electric van tested over a simulated Federal Urban Driving Cycle. A 64-volt version of the CSPL sodium-sulfur battery successfully completed 200 deep-discharge cycles in laboratory testing at ANL.

The proof-of-feasibility phase of the phosphoric acid fuel cell/battery propulsion system for a bus was successfully completed. Two 25-kilowatt fuel cell/battery "brassboard" systems were

The ETX-II electric vehicle was developed by the Ford Motor Company and General Electric under contract to the DOE. The vehicle was tested with sodium-sulfur batteries developed by the Power Plex/ASEA Brown Boveri consortium, and Chloride Silent Power Limited (CSPL). Using the CSPL battery in a dynamometer test, the vehicle demonstrated a range of 150 miles over the Federal Urban Driving Cycle.

built and evaluated in a laboratory. This is the first step in the integration of a phosphoric acid fuel cell/battery power source in a test-bed bus. The brassboard system verified the feasibility of this concept as a near-term energy-efficient, low-emission, and cost-competitive propulsion system for bus applications. The California South Coast Air Quality Management District is sharing in the cost of the development program, and other metropolitan areas experiencing air quality problems are interested in participating in subsequent phases.

Three new field test sites have been added to the OTT Site Operator Program: Southern California Edison, Los Angeles Department of Water and Power, and York Technical College in North Carolina. Several other utility companies and local government agencies, primarily in regions experiencing air quality problems, are also interested in participating in the cost-sharing program to field test new vehicle technologies as they become available.

The automotive gas turbine holds the promise of improving automotive efficiency by over 30 percent compared to conventional piston engines. However, in order to achieve this improvement, cycle temperatures must be elevated to the 2,500°F range. The Advanced Turbine Technology Application Program (ATTAP), currently being pursued by the Office of Propulsion Systems, Allied-Signal Aerospace Company, and General Motors Corporation, addresses this requirement by supporting component design, fabrication, and testing of advanced high-temperature structural ceramics. Recently, improved ceramic materials and processing procedures have resulted in the fabrication of turbine rotors that have operated at full rotor speeds in gas generator test rigs at turbine inlet temperatures in excess of 2,500°F. This result brings the automotive gas turbine and its attendant benefits a step closer to practical reality.

The diesel engine is the workhorse of the heavy duty transport industry, because its fuel economy is higher than any other engine and its reliability and durability are also better. The diesel engine has achieved these advantages with relatively modest use of advanced materials. Incorporation of advanced metal alloys, monolithic ceramics, and metal matrix and ceramic matrix composite materials could further extend the advantages of diesel engines in performance and durability. The Heavy Duty Transport Program is evolving advanced fuel-efficient and low-emission diesel engines from low-heat-rejection (LHR) diesel engine concepts. High-temperature synthetic liquid lubricants under development in the program should considerably extend the engine design and reduce particulate emissions.

The Cummins Engine Company and the Caterpillar Company have completed their Phase I design and analysis work identifying the engine technology necessary to achieve the

program goal of a 0.25 pound per horsepower-hour specific fuel consumption engine. Both engine companies recognized that currently used engines are overcooled. The new designs eliminated the engine block water-cooling system and used a single synthetic liquid for cooling and lubrication. Coolant passages would be directed at only critical hot-spot locations in the cylinder or head in a concept referred to as "precision cooling." Both engine designs involve increasing peak cylinder pressures by 50 percent or more, and consequently, companies are designing advanced pistons with this capability. To reduce emissions, the Detroit Diesel Corporation is developing improved fuel injection systems with 25 percent higher injection pressure, rate shaping of the fuel injection pattern, and computerized electronic control.

Thick thermal barrier coating development has been supported at Caterpillar, Cummins and Detroit Diesel. These ceramic coatings are designed to reduce thermal mechanical fatigue effects on the piston crown as well as reduce in-cylinder heat loss. The requirements of EPA emission regulations are stimulating better understanding of the combustion phenomena and justifying more sophisticated materials, including ceramics, which contribute to emission reductions. These include reductions in carbon dioxide gas thought to be a major contributor to the hypothesized "greenhouse effect." Other trends are toward greater computer control of fuel introduction and improved air management based on power demand and emission measurements.

The Office of Transportation Materials in OTT is sponsoring the development of materials and tribology systems for transportation applications. An industrial technology base in ceramics, ceramic composites, and ceramic coatings for heat engines is being developed in the Ceramics Technology for Advanced Heat Engines (CTAHE) Program. Significant progress has been made by industry, universities, and DOE laboratories in the three areas of the project: materials and processing, design methodology and database, and life prediction.

An engine using lightweight, durable ceramic valves powered this race car to numerous wins and two championships in 1989.

In this photograph, a youngster inspects a silicon nitride automobile engine valve. The dark valve, shown just to the right of center, was used for over 3,000 laps in a championship-winning race car. Other ceramic engine components are also shown.

Recent CTAHE Program technical accomplishments include 1) development of ceramic-to-metal braze systems and analytical tools for designing high-temperature silicon nitride and silicon carbide applications; 2) development of an environmentally sound aqueous powder milling process at Norton Company that contributes to the production of reliable silicon nitride components; 3) completion of attrition powder milling studies with silicon nitride powders at the National Institute for Science and Technology; 4) development of silicon nitride matrix whisker-toughened composites with three companies; 5) establishment of X-ray microfocus detectability limits for all specimen shapes used by GTE Laboratories in processing ceramics; and 6) optimization of strength in layered oxide-ceramic composites at Ceramtec.

Two new user centers for ceramic specimen preparation and residual stress measurements are being installed at the High-Temperature Materials Laboratory (HTML) at ORNL. The centers at HTML are used by industry, university, and government researchers to help solve high-temperature structural ceramics and other materials problems. Since the user program began in 1987, 100 user agreements have been executed (18 proprietary, 46 industry nonproprietary, and 36 university nonproprietary).

Materials developed under OTT support were used to make ceramic components for a racing car that won many races and set track records on the stock car circuit. The engine, with its ceramic components, was so lightweight that 200-pound handicaps were imposed on the car to eliminate its advantage over competitors. After completing more than 3,000 racing laps, analysis revealed no measurable wear (down to the tenth of a micron) on the ceramic valve stems and wear of less than a micron on the valve seat area. These and other ceramic components (e.g., fuel pump push rods and lifters) continue to be used in vehicles raced by top national teams.

OTT sponsors student vehicle competitions in concert with the Society of Automotive Engineers and others. These competitions have been very successful in stimulating student efforts and interest in alternative fuels. The 15 General Motors vehicles that competed in the successful 1989 Methanol Marathon competed again in the 1990 Methanol Challenge. The University of Tennessee repeated its success by converting a car to run on M-85 fuel (a blend of 85 percent methanol and 15 percent gasoline), and scoring the best in both fuel economy and emissions. EPA reports that it is the cleanest car ever tested.

OTT is establishing a Data Center on Alternative Fuels (DCAF) at SERI. This facility will be the only central data collection facility for alternative fuels. DCAF will provide data on emissions, performance, and durability obtained from alternative fuels demonstration programs, as well as abstracts on alternative fuels research and development. Information will be made available

through desktop computer interfaces. The center is expected to be operational in 1991.

Progress was made in converting the xylose fraction of cellulosic biomass to ethanol. Using genetically engineered *E. coli* bacteria, researchers were able to increase the yields from 70 percent to about 85 percent of the theoretically expected yield. Progress in this area could reduce the projected ethanol cost by about 7 cents per gallon.

Research has also shown that the enzymes used to ferment cellulose can be successfully stabilized. Stabilization allows the enzyme, B-glucosidase, to be recycled and, thus, reduces costs. Researchers at SERI successfully stabilized B-glucosidase on ion exchange resins. The enzyme maintained 95 percent of its activity on the resin, an improvement that could reduce the cost of ethanol by approximately 5 cents per gallon.

Researchers participating in the DOE-funded Short Rotation Woody Crops (SRWC) Program in the Pacific Northwest report that several major paper companies are interested in developing the concept. Scott Paper Company is looking for up to 8,000 hectares for a short rotation hybrid poplar plantation while Georgia Pacific and Boise Cascade are establishing hybrid poplar clone testing. These companies have contacted SRWC staff to obtain hybrid poplar clones developed by the program. Although the primary interest in hybrid poplar is as a source of kraft pulp, the additional testing of hybrid poplar clones will benefit the SRWC program by providing energy researchers with information on which silvicultural approaches are most cost effective and which clones are most stable.

DOE-sponsored research at Purdue University compared potential ethanol yields per acre for corn and sorghum. Corn grown at the best Purdue site averaged 142 bushels per acre, which is well above the 1989 U.S. average of 101 bushels. Conversion of both grain and stalk has the potential to yield 601 gallons of ethanol per acre. Yields of sorghum averaged 13 dry tons per acre at the same site. This equates to an ethanol yield of 874 gallons, a 45 percent improvement when compared to corn. Researchers are confident that with improved management practices and genetic engineering, ethanol yields from an acre of sorghum could surpass 1,200 gallons per acre.

The largest microalgae experimental ponds were operated for the second year at the microalgae outdoor test facility in Roswell, New Mexico. The yield and operational data collected thus far represent the first large-scale yield data on the cultivation of microalgae for fuel production. While yields as high as 40 grams per square meter per day were obtained during the summer months, monthly summer average yields were 23 grams per square meter per day. The goal of the fuels from microalgae

The solar-power car entered by a team from Western Michigan University and Jordan College is shown during pre-race trials at an OTT-sponsored student vehicle race.

Ballasts

These fluorescent-light ballasts, which were developed through DOE funding, are 20 to 25 percent more efficient than standard ballasts.

research is to obtain 50 grams per square meter per day with 50 percent lipid content on a consistent basis.

Building Technologies

The goal of the Office of Building Technologies (OBT) is to achieve cost-effective reductions in energy use in new and existing buildings. Technology transfer is essential to achieving this goal. Energy use in buildings will only be reduced when building owners and other energy consumers in the buildings sector become aware of, and adopt, energy-efficient technologies such as those being developed by OBT.

The OBT technology transfer program is largely driven by the character of the U.S. building industry. The industry is diverse and fragmented, with over 28,000 homebuilders, more than 1,000 commercial builders, and thousands of architectural and engineering firms and trade contractors. Firms that manufacture building materials and components also number in the thousands. New commercial buildings commonly require products and services from over 50 separate industries.

To reach this diverse industry, OBT uses a technology transfer strategy that emphasizes close private-public sector interactions (e.g., contracting to industrial partners), strong working relationships with key intermediaries and broker organizations (e.g., trade organizations and professional societies) and tailored information outreach. This strategy is supported by an office-wide technology transfer program, as well as activities conducted by individual research and development programs.

Most technology transfer activities occur in individual research programs. The flexibility and responsiveness allowed by this decentralized approach are important because of the diversity of research and development supported by OBT and the variety of audiences served.

To supplement program-level technology transfer, OBT supports office-wide activities that are crosscutting, benefit from standardized formatting, or have significant economies of scale. In recent years, OBT has spent about 10 percent of its budget on centralized technology transfer activities, indicating a strong commitment to promoting full use of its research and development results. Meetings, workshops, and industrial review and coordination committees were given significant support.

Long-term OBT research and development focuses on technologies, tools, and practices that will directly or indirectly result in decreased energy use in buildings without decreasing the level of energy services. The program concentrates on a few high-risk technologies, because the needed research is time consuming and

expensive. Thermally activated heat pumps and advanced lighting are examples of technologies requiring long-term development. The transfer of such technology, as it is developed, occurs through the early awareness and involvement of a small number of product manufacturers.

The shorter-term research and development, software development, and other products of the OBT program have broader audiences. To be effective in reducing building energy use, OBT has to disseminate these products widely to a variety of audiences. Dissemination of this information occurs both at the project/program level and through office-wide activities.

A common element throughout the programs funded by the Office of Fossil Energy (FE) is to develop advanced coal, oil, and gas technologies with the involvement of industry as a research partner. In many cases, private participants in FE-initiated projects share in the financial cost of the project, in addition to performing the actual research and development or engineering scaleup.

More than 90 percent of the technology-development projects funded by FE are carried out by industrial or university researchers rather than at DOE laboratories. This approach is consistent with the applied nature of FE-sponsored technology development activities, and expedites the transfer of new technologies to potential private sector users and vendors. By playing an active role in the earliest stages of development, private sector participants are able to assess the potential market for new technologies and, ultimately, make well-informed commercialization decisions.

In 1990, FE administered more than 486 active research and development contracts. The nearly \$400 million in 1990 funding for these contracts was supplemented by almost \$80 million in private-sector financing, representing an average ratio of 80/20 public-to-private-sector cost sharing (although certain technology development projects have private cost sharing as high as 40 to 50 percent). With increased emphasis being placed on leveraging Federal dollars, FE has established a goal of boosting private cost sharing to an average of 30 percent of total project financing by 1992.

Prototype of a lamp system for using compact fluorescent lamps to replace incandescent lamps in recessed fixtures. This system incorporates external fins that cool the lamp to achieve maximum efficiency.

■ FOSSIL ENERGY

A technician at the Pittsburgh Energy Technology Center (PETC) cleans recovered magnetite from a small-scale test apparatus. The magnetite, having been separated from the coal, will be reused in the PETC-developed Micro-Mag coal cleaning process.

The Clean Coal Technology Program

The sizable investment in research and development sponsored by FE has been augmented in recent years by the addition of a government/industry joint program intended specifically to transfer new coal-based technologies into commercial markets. This program, called the Clean Coal Technology Program, provides government cost sharing for new, environmentally clean, highly efficient coal concepts that are ready to be demonstrated at the commercial or near-commercial scale.

A primary feature of the program is its emphasis on technology transfer leading to the commercialization of advanced coal technologies. When the program is completed in the 1990s, it is expected to have financed the construction and testing of 50 to 75 "showcase" projects, each demonstrating an advanced method for controlling pollutants from coal, for generating electricity more cleanly and economically than currently used technologies, or for producing new, cleaner fuel forms from coal.

In each project, a wide range of incentives are provided to the industrial participant to encourage maximum efforts to demonstrate and deploy the technology being demonstrated, either through licensing of the technology or through its manufacture and sale. In addition to requiring the industrial participant to fund at least 50 percent of the total costs of the project, advance patent waivers, protection of proprietary data, and ownership of operational data are some of the features of the negotiated Clean Coal Technology Cooperative Agreements. A participant is required to submit a commercialization plan as part of the proposal, further indicating the proposer's interest in the ultimate commercial use of the technology. In the absence of a demonstrated commercialization effort on the part of a participant, the DOE can make the information generated during the project available to other interested parties who would continue the process.

In December 1989, Energy Secretary Watkins announced the selection of 13 new projects in the third round of nationwide competition under the Clean Coal Technology Program. The projects, which were valued at more than \$1.3 billion, were added to 25 active projects selected in the first two rounds of the program (in 1986 and 1988). If agreements can be negotiated with all of the proposers selected in Round 3, the Federal government would contribute \$540 million to the new projects. Private proposers, in many cases joined by State governments, would add more than \$770 million. The nearly 60 percent private cost sharing would substantially exceed the legal 50 percent minimum requirement.

Included in the project selections from Round 3 were a variety of ways to improve the environmental cleanliness of coal use.

Several of the projects would demonstrate ways to remove sulfur and/or nitrogen pollutants inside coal-burning boilers as part of the combustion process. Others would test advanced methods for cleaning the flue gases released from coal combustion. Still others would convert coal into liquid or gaseous forms that could be burned to produce electricity or used as feedstocks. One project would use a technique called "mild gasification" to convert coal into a combination of fuels suitable for several markets. Another would demonstrate a new, cleaner alternative for using coal in the production of steel.

The Fossil Energy R&D Program

The FE Research and Development Program includes a variety of research areas encompassing new technologies for coal use, systems that can use either coal or natural gas, advanced processes for extracting hard-to-recover petroleum, and methods for recovering bypassed natural gas and natural gas that cannot be recovered by conventional methods.

At the earliest stages of research, the Federal government provides all or most of the project funding. As individual technologies mature through applied engineering and proof-of-concept or field testing, financial participation by the private sector is expected to increase. Cost sharing, therefore, becomes one indicator of the private sector's commitment to a new technology and one measure of its commercial potential.

Many of these projects are conducted cooperatively with industry-led organizations. For example, several methods for cleaning impurities from finely ground coal have been tested jointly with the Electric Power Research Institute (EPRI), the research arm of the electric utility industry, at the EPRI Coal Quality Development Center near Homer City, Pennsylvania. Research in the "secondary recovery" of natural gas is being jointly sponsored with the Gas Research Institute (GRI), which is the research organization of the natural gas industry. GRI was also a cosponsor of the field demonstration tests of underground coal gasification processes. Both EPRI and GRI have been involved in the DOE program to develop fuel cell systems, the first generation of which is now being readied for market application.

Most of the fossil energy research projects are carried out by private contractors, often working in combination with each other. For example, to ensure that technology transfer occurs for the duct-injection concept, a potentially low-cost way of lowering pollution from coal plants by injecting sulfur-absorbing chemicals into the plant's ductwork, FE contracted with two organizations for research and testing and a third organization to compile the data into a set of technical guidelines, computer models, and a design handbook for electric utilities.

In thermodynamic studies undertaken at the National Institute for Petroleum and Energy Research (NIPER), this rotating bomb calorimeter is used to measure precisely the enthalpy of formation of organic and organometallic compounds. This instrument, which for years was the only one of its kind in the Western Hemisphere, was developed at NIPER.

The availability of large-scale project sites in the Clean Coal Technology Program offered the opportunity to conduct related research. For example, in 1989-90, DOE joined with the American Electric Power Corporation to use the Tidd Clean Coal Technology Project in Brilliant, Ohio, as a testing station for advanced devices for cleaning particulate matter from the gas stream of pressurized fluidized-bed coal combustors.

Economic viability is obviously a key to the success of technology transfer. Some technologies have been successfully developed in DOE programs, only to remain unused in commercial markets due to noncompetitive costs. The conversion of coal to synthetic liquid fuel is an example of a technology that is technically feasible. In the past, however, synthetic liquid fuel produced from coal has not been an economically viable alternative to conventional fuels produced from petroleum. That situation could change, however, as dramatic improvements have been made in recent years to the costs of coal-to-liquid fuel conversion processes. Today, advanced conversion processes are estimated to produce high-quality liquid fuels at equivalent costs of \$33 barrel—a significant improvement over the \$52 per barrel projections of a decade ago and the nearly \$80 per barrel estimates of the mid-1970s. In 1990, the DOE began a new effort to reduce the costs of producing synthetic liquid fuel from coal even further, perhaps below \$30 per barrel. In a recent report entitled *Fuels to Drive Our Future*, the National Research Council affirmed the realistic possibility of achieving this goal.

Technology transfer can also occur by adapting processes developed for other purposes and at other scales. For example, in 1989-90, FE completed a feasibility study for scaling down a circulating fluidized-bed boiler to serve as a combination cogeneration/waste incineration system that could be installed at hospitals. Such a spin-off application would address both energy needs and growing concerns over the problem of transporting and disposing of infectious medical waste. In 1990, the DOE began working with the U.S. Department of Veterans Affairs on a test program that could expedite the transfer of this technology into commercial use.

The successful commercialization of many advanced coal processes could depend upon the durability of materials in withstanding hostile high-pressure, high-temperature environments. To ensure the availability of such materials, FE supports a generic research program to develop better ceramics and alloys for fossil-fueled systems. Emphasis is given to technology transfer in this program through joint efforts with industry and the DOE laboratories.

For example, metallurgists at the Oak Ridge National Laboratory (ORNL) developed a new series of ductile iron-aluminide alloys that retain their strength and corrosion resistance at

high temperatures. The alloys may find uses not only in coal processes, but also in such diverse applications as structures and automobiles. In another materials advance, the Pacific Northwest Laboratory (PNL) developed a new, low-cost process for making high-quality oxide ceramic powders for solid-state electrolyte systems, such as those used in advanced fuel cells. This glycine nitrate process is expected to enhance U.S. industrial competitiveness in the manufacture of ceramics. Materials related technology transfer can also take the form of computer software. A computer program for modeling thermomechanical stresses in refractory linings of coal combustors is now being made available to industry through ORNL.

In FY 1990, DOE decided to reconfigure its oil and gas research programs to focus on much nearer-term objectives than in the past. The restructuring of the Federal program was prompted in large measure by the alarming increase in the rate of oil field abandonments occurring in the latter half of the 1980s. Under current conditions, the possibility exists that as much as 70 percent of the Nation's onshore oil resource in the 48 contiguous states could be abandoned by early in the next century. Even with elevated oil prices, which would increase value of this resource, the abandonment figure could still approach 60 percent of the total resource.

To counter this disturbing trend, FE announced in early 1990 that it would concentrate much of its oil-related research efforts during the next 5 years on methods for maintaining access to reservoirs with large future production potential. An aggressive technology transfer effort is an inherent part of this refocused, near-term effort. Special attention will be given to acquainting smaller producers with recovery technologies that are not familiar to them.

In carrying out the newly structured program, the DOE is encouraging the formation of consortia that would include groups of companies, service organizations, State and Federal agencies, universities, and oil field consultants. Attendance at these consortia provides a means for participants to leverage their resources and offers a mechanism for immediate transfer of technical know-how to participants. Much of the current effort is taking place through the Interstate Oil Compact Commission and has included a series of meetings to familiarize producers with current technological developments.

At the core of the refocused oil program is the use of the Tertiary Oil Recovery Information System (TORIS), maintained at the Bartlesville Project Office, which is supported by FE. TORIS provides the analytical basis for identifying oil fields with high production potential that face imminent abandonment and for classifying oil reservoirs into categories that can be related to

Computerized diesel and automotive test laboratories, such as this one at the National Institute for Petroleum and Energy Research (NIPER) in Bartlesville, Oklahoma, provide for repetitive and accurate duplication of engine cycles, data collection, and emissions sampling. In this photograph, a NIPER scientist is performing an engine test from the control room of the new six-stand automotive engine test facility.

The performance of oil wells that have been treated for microbially enhanced oil recovery is continuously monitored by staff at the National Institute for Petroleum and Energy Research (NIPER) in Bartlesville, Oklahoma. This photograph shows plate counts being made to determine microbial concentrations in brine samples taken from a producing well.

optimal recovery processes. Much of this analytical work is being done cooperatively with oil-producing States, again working through the Interstate Oil Compact Commission. The results of this analytical work have formed the basis for tax and other incentives provided by some States to encourage the transfer of new technology into commercial use.

Another technology transfer mechanism is the Oil Recovery Technology Partnership, a program in which DOE laboratories are making relevant technologies that have been developed under other Federal programs available to the oil and gas industries (e.g., underground imaging methods originally developed for defense programs). In 1990, four cooperative projects continued in this effort. LANL and Murphy Operating Company, a New Mexico-based independent oil producer, completed their initial seismic wave detection tests to map fractures in the Chaveroo oil field in New Mexico and selected a site for a more extensive field experiment in the Permian Basin Tomahawk oil field, also in New Mexico. SNL and another independent oil producer, Harvey Yates Company, completed their third well for examining natural fractures using well cores and sonic and imaging techniques in the Bone Spring Formation in New Mexico. In an ongoing effort to develop seismic methods for producing three-dimensional images of rock strata between wells, SNL completed an early design of a small, lightweight multistation seismic receiver and signed a cost-sharing contract with a private firm to fabricate and test the instrument.

In the fourth project, LANL, working jointly with Texaco and Chevron, completed seismic signal tests at Texaco's McKittrick field in California. The data from these tests are being analyzed to determine the ability of the system to map subsurface faulting.

Additional technology transfer approaches will include providing user-friendly computer software to independent operators and small production companies. FE is using technical conferences and symposia to provide independent operators with hands-on training in the use of "Predictive Models" and "BOAST II" personal computer programs. These programs can be used to evaluate reservoirs for applicable enhanced recovery processes and to simulate the flow of oil, gas, and water through a reservoir. A third software program for simulating production from horizontally drilled wells is currently being converted to personal computer format for transfer to industry.

The FE natural gas research program has also been restructured to emphasize more near-term objectives, particularly the collection of data that can serve as the basis for analytical models of the Nation's gas resource base and the deliverability of this resource. Much of this work has already been initiated by GRI. The involvement by DOE will expand and complement the GRI effort.

Other near-term research efforts will include the development of methods and strategies, using existing technology, for extracting a greater percentage of the natural gas remaining in the mature fields of the 48 contiguous States. As much as 25 percent of the gas present in some conventional reservoirs cannot be recovered by traditional production methods. A second objective of this project is to develop techniques for restoring production from the thousands of stripper gas wells that face abandonment.

Horizontal or inclined drilling has the potential to dramatically improve the recovery of gas from certain types of reservoirs. The refocused natural gas program will place emphasis on improving these innovations in technology. Another element of the near-term program will involve research on techniques that can upgrade "low quality" gas that is unrecovered because current techniques for removing impurities are too costly.

In the latter half of the 1990s, the principal objectives of the natural gas research program will be oriented toward "unconventional gas resources," the next major source of natural gas available to complement conventional production. Unconventional gas resources are found in sandstone, shale, and coal formations (often interlayered) that lack the natural pathways for gas to flow to a borehole. Longer-term objectives beyond the year 2000 include developing techniques to recover so-called "speculative gas resources," such as natural gas from deep sediments, gas hydrates, and zones that remain opaque to conventional seismic techniques.

As in the oil research program, technology transfer is an inherent part of the FE natural gas research program. And in a similar fashion, consortia of private, State, Federal, and academic organizations will conduct the actual research under cost-sharing arrangements and participate in the technology transfer efforts.

Federal/State Partnership Programs

Crosscutting all of the FE research and development programs is an activity that leverages both Federal and State funding for research and engineering development in fossil fuel technology areas. The Federal/State Partnership Program is a jointly financed effort between the DOE and State governments. Under this program, States identify specific research efforts that can meet regional or State needs. If a proposed project is selected, the State provides at least 50 percent of the funding. The program thus serves as a conduit for technology transfer by identifying regional and State commercialization opportunities and supporting projects that can assist the private sector in meeting those opportunities.

Prior to 1990, 19 separate DOE/State activities were underway with nine States. Four additional States had signed

This state-of-the-art computed tomography (CT) instrument is used to measure spatial distributions in rock samples from petroleum reservoirs. The reservoir characterization capabilities at the National Institute for Petroleum and Energy Research (NIPER) in Bartlesville, Oklahoma, have attracted the attention of the petroleum-production industry worldwide. NIPER and DOE also cosponsored International Technical Conferences on Reservoir Characterization in 1987 and 1989.

Memoranda of Understanding but had not started specific projects. In 1990, the program was restructured to encourage competition among States and to permit the formation of consortia of States for cofinancing regionally significant projects. Following orientation conferences with States in the Spring of 1990, 24 governors had responded positively to the new program. Suggested research topics received from the States were assessed to determine areas that could be the bases for competitive solicitations to be issued in 1991. Funds were not appropriated by the Congress to match State dollars for the 1991 solicitation. However, FE was encouraged to continue its dialogue with States, keep them informed of upcoming competitive solicitations, and seek input to FE programs and activities.

International Fossil Energy Technology Transfer

Technology transfer activities conducted by FE do not focus solely on domestic markets. Changes taking place in the world's economic structure, particularly the industrial initiatives of developing nations and those in Eastern Europe, offer significant opportunities for U.S. technology to be marketed abroad.

To assist private firms in developing overseas marketing opportunities, FE has signed several technical exchange agreements designed to familiarize other countries with U.S. fossil fuel technology. Two agreements, for example, were signed in 1989 and 1990 to convey technical information on U.S. clean coal technologies to Costa Rica and Chile.

Another international clean coal technology project involves the construction and testing of pollution control hardware in Poland. An outgrowth of a Presidential initiative, DOE is coordinating an effort to install advanced clean coal technology in a power plant near Krakow. The project could be instrumental in conveying the benefits of U.S. technology for use in the environmental cleanup of former Soviet Bloc nations.

In the coal research and development program, FE is cooperating with Italy to demonstrate that "superclean" coal-water slurries can be burned in oil-fired furnaces without sacrificing efficiency or environmental performance. The project could open up additional export opportunities for both coal and coal technologies as Italy looks increasingly to coal to supply its energy needs.

International cooperative efforts are also taking place in the oil research program. In 1990, a 9-year cooperative effort concluded between the Bartlesville Project Office, the National Institute for Petroleum and Energy Research, and INTEVER, the Venezuelan central petroleum research facility. During this effort, new processes were developed for separating heavy oil into fractions and assessing problem compounds in each fraction. These

new methods will assist both U.S. and Venezuelan producers in solving problems of conventional petroleum refining and in the development of new refining processes that can handle lower-quality heavy crude oil in their feedstocks.

In November 1989, Energy Secretary Watkins established the Office of Environmental Restoration and Waste Management (EM) to coordinate and manage DOE activities to return the DOE weapons-complex sites to an environmentally sound state and reduce environmental contaminants generated from current operations. EM consolidates DOE management of environmental cleanup efforts. It is the goal of EM to ensure that risks to human health and safety and to the environment, from past, present, and future operations, are either eliminated or reduced to prescribed, safe levels by the year 2019. This program is intended to develop better, faster, and more cost-effective solutions to environmental restoration and waste management problems.

A principal focus of the DOE and the agencies that preceded it has been the manufacture of components for maintaining and upgrading U.S. strategic defenses. The waste generated during these manufacturing processes represents a unique technical challenge. Techniques used in the past to dispose of process waste have been less than ideal, and the remaining wastes currently pose environmental problems that the DOE is actively seeking to rectify.

To address this challenge, new technology is needed. To this end, the EM Office of Technology Development (OTD) was established in 1990 to "carry out a program of research for the development of technologies useful for 1) the reduction of environmental hazards and contamination resulting from defense waste, and 2) environmental restoration of inactive defense waste disposal sites."

The mission of the OTD is to establish a national program for applied research and development that will resolve major technical issues and rapidly advance technology beyond the state now available for environmental restoration and waste management operations. In fulfilling its mission, OTD is organized into the following divisions: Research and Development; Demonstration, Test, and Evaluation; Transportation; Program Support; and Technology Integration and Environmental Education Development. Within the Technology Integration and Environmental Education Development Division are the Environmental Programs Education and Technology Integration Branches.

The Technology Integration Branch functions as the technology transfer and integration arm of the EM organization. The mission of the Technology Integration Program is to facilitate

■ ENVIRONMENTAL RESTORATION AND WASTE MANAGEMENT

***Targeted Synergism
To Address National Issues***

The EM Technology Integration Program (TIP). This figure illustrates the interrelationships that must exist to promote timely and cost-effective environmental restoration of DOE sites. The availability of new or previously unidentified technology that is relevant to restoration effort is important, but the relationships among the respective sectors that must be fostered to locate sources of technology are even more important.

timely and effective applications of technologies to meet the environmental restoration needs of the DOE through collaborative partnerships with U.S. industry, the DOE laboratories, other Federal agencies, universities, and appropriate international participants. In general, the mission is to facilitate technology transfer both "into" and "out of" the EM program.

The networking integral to the Technology Integration Program is accomplished through three specific program areas: Technology Coordination, Technology Transfer, and Industrial Integration. Through its Technology Coordination Program, the Technology Integration Branch is working with other DOE programs, such as DP and CE. The DP collaboration is advancing DP-developed, restoration-relevant technologies that might not otherwise be pursued, for ultimate transfer to the private sector. Through the Innovative Concepts Program, the existing CE infrastructure is being used to assist individuals with unique waste minimization concepts that might not be sufficiently developed.

The EM Technology Integration Program also works closely with the DOE laboratories. In 1990, cooperation between EM, the DOE General Counsel, and the ORTA at Savannah River Laboratory (SRL) led to the transfer of the first EM technology, a horizontal well technology, to two separate commercial entities. EM is planning increased collaboration with DOE laboratory ORTAs in targeted areas. Close internal working relationships and an identifiable DOE Headquarters hub for field interactions are expected to speed the transfer process.

The last program area, Industrial Integration, will be the most critical to the short-term goal of applying available industry technology to the restoration program. In 1990, the Technology Integration Program provided a needs assessment guide to industry. This guide is intended to characterize general restoration needs and to provide a description of technologies in those areas currently being funded at DOE laboratories. From this guide, industry is providing input on three questions: 1) For the given stated problem, is the current research and development the best approach? 2) Does the solution to the stated problem already exist in industry? 3) If the solution does not exist in industry, will industry collaborate in the needed research and development?

Through the Industrial Integration Program, contacts are being established with industry-sponsored working groups that focus on the environment. Many of the DOE environmental problems are the same as those of industry. Collaborations seem the most effective way to reach common restoration goals.

In 1990, the DOE environmental restoration effort initiated the Integrated Demonstration Program. This program is directed towards simultaneous demonstration, test, and evaluation of multiple technologies focused on a single effort. The Technology

Integration Program will introduce restoration-relevant technology that can be either basic or field-ready for subsequent testing and evaluation. In addition, in areas where technologies are not yet ready, collaborative research agreements may be facilitated between an industry source and a Federal facility through the ORTAs.

The location of the Technology Integration Branch in the Technology Integration and Environmental Education Development Division also serves another well-defined purpose. The transfer of knowledge and strategic goals to the educational community is imperative to the overall environmental restoration effort. A new generation of scientists and engineers must be familiar with the impact of their disciplines and inventions on the environment.

The need for technicians and technical support staff also requires good communication with vocational/technical institutions and 2-year colleges. Educational partnerships in New Mexico with the Waste Management Education Research Center, and in South Carolina with the South Carolina Universities Research Education Foundation have already been fruitful in involving educational institutions in the EM technology transfer process.

In South Carolina, a Technology Transfer Summer Institute has been formed in conjunction with the ORTA at SRL. This 10-week program involved 15 students and 4 professors in a review of 133 invention disclosures from SRL for potential licensing opportunities. The goal of the program is to determine interest by the business community in South Carolina in innovations related to environmental restoration and waste management.

Efforts in New Mexico, similarly, have moved to promote better communications and understanding between researchers and commercial counterparts using the Waste Management Education Research Center as a hub around which common interests can be pursued.

EM has adopted the philosophy that it will take a coordinated and integrated effort to effectively address DOE's environmental problems. Commitment to the transfer of technology resulting from federally funded research and development programs and an intimate involvement with industry are considered cornerstones to timely and cost-effective fulfillment of the EM mission.

CONTENTS

- 55 ■ **Introduction**
- 56 ■ **Energy Technologies**
- 72 ■ **Environment and Waste Management**
- 88 ■ **Biology and Medicine**
- 102 ■ **Materials Science and Manufacturing Processes**
- 122 ■ **Analysis and Instrumentation**
- 142 ■ **Computers and Communications**

Photo at left: Scientists at Argonne National Laboratory (ANL) have developed a new method of monitoring cadmium concentrations in the human body. The Blood Cadmium Assay Kit provides a highly sensitive procedure for analyzing blood, plasma, or urine. The procedure concentrates the cadmium into a small volume and separates it from nearly all other elements in the sample. Shown in this photograph is an ANL scientist examining a sample. Monitoring of cadmium in the body is important because adverse responses are being demonstrated at low levels of exposure to this heavy metal.

2TECHNOLOGIES

2TECHNOLOGIES

Technicians inspect SERI blades installed on a Micon 65 wind turbine. The innovative blades, which use specially designed airfoils that govern airflow around the blades, boosted the energy produced by the wind turbine by 15 to 20 percent over that produced by conventional blades.

Introduction

"It is not enough to make it easier for industry to work with the Federal government. We have to make matches between what industry wants and needs and what the Federal researchers can contribute."

Admiral James D. Watkins, U.S. Navy (Retired), Secretary of Energy

The technologies and know-how available at the DOE laboratories span a wide range and represent the fundamental elements of all technology transfer efforts. Accelerating the application of these technologies and know-how into practical use is a major priority of both the DOE and its laboratories. In this section, brief summaries of some of the major technologies that have been developed at the laboratories are presented. The featured technologies are organized into the following six categories:

- Energy Technologies
- Environment and Waste Management
- Biology and Medicine
- Materials Science and Manufacturing Processes
- Analysis and Instrumentation
- Computers and Communications.

The wide range of available laboratory technologies illustrates the breadth and depth of both the capabilities and the research and development activities supported by DOE at its laboratories. Further information on the technologies in any of the categories can be obtained by contacting the laboratory or laboratories mentioned in each technology summary. To facilitate such contacts, names and telephone numbers of technology transfer contacts at each of the laboratories are provided in the *Laboratories* section of this report.

Researchers from Lawrence Berkeley Laboratories (LBL) teamed up with Extrion, a division of Varian Associates, to develop a better method of delivering electrons to silicon or semiconductor wafers. The system neutralizes the positive charge that builds up during ion implantation.

This photograph shows the LBL/Extrion charge-neutralization apparatus in operation. The electron beam comes from the source, goes through a curved solenoid with Helmholtz coils above and below, and merges with the ion beam. One of the bucking coils is visible in the foreground of this photograph.

CONTENTS

- 57 ■ HEAT-DRIVEN CRYOGENIC REFRIGERATOR WITH NO MOVING PARTS (LANL)
The Coolahoop
- 58 ■ NEW AIRFOILS FOR WIND INDUSTRY (SERI)
Improves Longevity and Performance
- 59 ■ IMPROVED COAL CONVERSION (METC)
Acoustically Enhanced Processes
- 60 ■ PREPARING CLEAN COAL (PETC)
The Micro-Mag Process
- 62 ■ SOLID-STATE LITHIUM BATTERIES (LBL)
Nontoxic, Inexpensive, and Biodegradable Components
- 63 ■ BACTERIA REMOVE POLLUTANTS FROM COAL (PETC)
Depyritization Process
- 63 ■ CONVERSION OF COAL TO NEW LIQUID AND SOLID FUEL FORMS (METC)
Mild Gasification Demonstration
- 65 ■ CASCADE PHOTOVOLTAIC CELL SETS EFFICIENCY RECORD (SERI)
New Design and Fabrication
- 67 ■ ADVANCED CERAMIC HEAT EXCHANGER FOR HIGH-EFFICIENCY, COAL-BURNING GAS TURBINES (METC)
Ceramic Heat Exchanger for Indirect Coal Firing
- 68 ■ SATELLITE BATTERY REDESIGNED FOR TERRESTRIAL USE (SNL)
Bringing Space Technology Down to Earth
- 70 ■ SECONDARY RECOVERY OF NATURAL GAS RESERVES (METC)
Characterization of Internal Reservoir Geometries

Lawrence Berkeley Laboratory (LBL) ■ Los Alamos National Laboratory (LANL) ■ Morgantown Energy Technology Center (METC) ■ Pittsburgh Energy Technology Center (PETC) ■ Sandia National Laboratories (SNL) ■ Solar Energy Research Institute (SERI)

Energy Technologies

A new type of cooling system that produces very low temperatures, contains no moving parts, and has an apparently unlimited lifetime will be invaluable for use in remote locations ranging from isolated ranches or natural gas wells to satellites in outer space. The Coolahoop, which was developed by a team of researchers from Los Alamos National Laboratory (LANL) and the National Institute of Standards and Technology (NIST), represents a major breakthrough in cryogenic (ultralow-temperature) cooler technology.

The Coolahoop is remarkably simple, consisting only of assorted tubes and heat exchangers, and contains no exotic materials—only brass, copper, stainless steel, and helium gas. Basically, it is a thermoacoustic engine—a device in which acoustic resonance converts heat to oscillatory pressure—coupled to and driving a pulse-tube refrigerator, which is a variant of the Stirling-cycle refrigerator.

To eliminate all moving parts in the Coolahoop, the cold piston of the Stirling-cycle refrigerator was replaced with a passive dissipative structure consisting of a flow impedance and a ballast tank. Both the flow impedance and the ballast tank operate at ambient temperature and absorb energy from the high-pressure helium gas with which the system is filled. The hot piston was replaced with a thermoacoustic engine in which a self-sustaining, standing sound wave carries the gas back and forth between the high-temperature heat source and the ambient-temperature heat sink. The sound wave pressurizes and depressurizes the gas in phase with the attendant thermal expansion and contraction, thereby producing energy.

The prototype system, which requires 2,000 watts of input power, reaches a low temperature of -300°F and has 5 watts of cooling power at -244°F. Thus, its efficiency is comparable to that of the best mechanical cryocoolers. Mechanical cryocoolers, however, require maintenance about every 2 years because of wear on moving parts, plugging of low-temperature orifices, or both. This short lifetime is intolerable for satellite cooling and is a serious flaw in earthbound commercial and industrial cryogenic pumps. The Coolahoop requires no maintenance, and its reliability is unequalled. Further, the cost of manufacturing the Coolahoop is expected to be one-fifth to one-tenth that of producing conventional cryocoolers because the new system is made of ordinary materials, and since it has no pistons or cylinder walls, it requires no close-tolerance fabrication techniques.

■ HEAT-DRIVEN CRYOGENIC REFRIGERATOR WITH NO MOVING PARTS

The Coolahoop

The Coolahoop, a 1990 R&D-100 Award-winning ultralow-temperature cooler developed at LANL, is made of inexpensive ordinary materials, contains no moving parts, and requires no maintenance. In this thermoacoustic engine, a sound wave pressurizes and depressurizes helium gas, thereby producing energy. The Coolahoop will be particularly useful for such applications as cooling the satellite-based infrared detectors that monitor the earth's climate and survey its resources.

The Coolahoop can be used to cool satellite-based detectors, such as the infrared sensors used for monitoring climate and surveying resources on earth. It can also produce small quantities of liquid nitrogen economically and onsite (since gaseous nitrogen is readily available from the air) for applications such as in medical procedures or in the livestock breeding industry. Currently, liquid nitrogen must be produced at large central facilities and then trucked to wherever it is needed—to ranches, for example, where it is used to preserve stored livestock semen.

When larger Coolahoops are developed, they could be used to liquefy large quantities of natural gas at remote wells where it is not economical to build a pipeline to transport the gas to market. A large Coolahoop could burn a fraction of the gas produced at the well in order to liquefy the rest, and tank trucks could periodically carry the liquefied gas to market.

The Coolahoop is a 1990 R&D-100 Award winner. A patent on this unique system is pending, and the Coolahoop is available for licensing.

■ NEW AIRFOILS FOR WIND INDUSTRY

Improves Longevity and Performance

The U.S. wind industry may soon take flight on new wings—the world's first blades designed specifically to meet the special operating requirements of horizontal-axis wind turbines. Developed by the Solar Energy Research Institute (SERI) and several of its subcontractors in an award-winning technology transfer program, the uniquely shaped blades could reduce wind energy costs by as much as 20 percent, from the current 7¢ to 13¢ per kilowatt-hour to a record low of 6¢ to 10¢ per kilowatt-hour. These low costs would benefit the U.S. wind industry by making wind power more attractive to investors throughout the world.

A commercial wind turbine equipped with the lightweight blades recently experienced a 15 to 20 percent increase in energy output at wind speeds ranging from 10 to 25 miles per hour. The turbine is located in the heart of a huge wind power plant near Palm Springs, California, where turbulent winds often lead to blade damage and failure.

Blades have been one of the biggest problems for the wind industry, both in terms of performance and longevity. Until now, wind turbine blades were designed using conventional aircraft airfoils; however, the use of these airfoils creates problems for the wind industry. Because blades with conventional airfoils produce excessive power at high wind speeds, they cause generators and transmissions to burn out. To limit excessive peak power, wind turbine operators often change the pitch of standard blades. This practice can result in greater blade stress, which leads to early structural failure.

At medium wind speeds, however, blades designed with conventional airfoils produce insufficient energy. Also, when the leading edge becomes soiled, primarily from a buildup of dead insects, the energy output decreases. The new SERI blades help eliminate these problems because their specially designed, cross-sectional shapes govern the air flow around the blade.

The SERI 7.9-meter fiberglass blades were designed to replace Danish AeroStar blades, which are now used on about 3,600 wind turbines in California alone. The AeroStar blades are failing at a high rate and, according to most industry experts, will need to be replaced in the next decade. This demand for replacement blades will create a potential market of about \$36 million for those U.S. manufacturers who can offer superior blade designs. SERI is also developing 9-meter blades with a potential for \$15 million in sales during the next decade. These sales projections do not include blades for new wind turbines, which are being installed at a rate of 600 to 1,000 machines per year in California and Hawaii. Sales on the international market also are not included.

The new airfoils were designed to SERI specifications by Airfoils Inc. of Hampton, Virginia. Another subcontractor, WestWind Industries Inc. of Davis, California, used the airfoils to design blades that limit excessive power, produce more energy, resist the effects of dirt and insect buildup, and have a long operational lifetime. Phoenix Industries Ltd. of Crookston, Minnesota, fabricated the blades and helped conduct initial vibrational tests. Phoenix Industries is applying for a State grant to prepare for mass production and sales.

This closely integrated partnership between government and industry won the design team a 1990 Federal Laboratory Consortium Award.

Morgantown Energy Technology Center (METC) is supporting studies to develop coal-fired pulse combustors and to investigate the effects of acoustics on direct coal firing in turbine systems.

Pulsating and acoustic energy conversion processes have received considerable attention in recent years, with the most visible example being the pulse combustors that have entered the residential heating market. The advantages of such combustors have been well acclaimed: improved heat transfer, reduced nitrogen oxides (NO_x) output, and higher combustion efficiency. The basic phenomenon that provides these benefits is linked to unsteady fluid motion, which improves mixing and heat transfer. There is also a potential benefit in operating the gas-turbine cycle

■ IMPROVED COAL CONVERSION

Acoustically Enhanced Processes

on a pulse combustor directly. Because of the self-aspirating nature of pulse combustors, such an approach could eliminate pressure losses associated with aspirating conventional combustors, which would lead to improved system efficiency. In addition, METC-sponsored research has shown that acoustic energy from the pulse combustor may serve to agglomerate fine coal ash for easier removal and, therefore, reduced particulate pollution.

There are currently two areas of research concerning pulse combustion for direct coal firing of gas turbines. The first area is to determine if the acoustic output of coal-fired pulse combustors can serve as a highly efficient and reliable acoustic source to enhance burning efficiency, agglomeration potential, and sulfur capture by a calcium-based sorbent. Ongoing tests seek to validate this concept, and the prospects of acoustically enhanced processes appear promising.

The second research area is fuel atomization in coal-slurry combustion. Excellent atomization is a prerequisite for the development of coal-fired gas turbines. In proposed systems, slurry atomization is accomplished by using considerable quantities of high-pressure air to shear fuel jets into a fine mist. This air must be externally pumped, thus representing a parasitic energy loss in the turbine system. As an alternative, pulse combustors may be effective atomizers and dryers for viscous slurries. Consequently, an effort to assess the ability of a small pulse combustor to atomize fuel has been completed.

Initial work has demonstrated successful atomization and combustion of the coal-water slurry using a gas-fired pulse combustor. The process of atomization with a pulse combustor is called pulse atomization and is promising for applications outside the original research scope, such as the spray drying of food, minerals, and slurries. METC is seeking commercial development of the "pulse atomization" process. In addition, a new mode of pulse combustion, known as "thermal pulse combustion," may affect the design and operation of more conventional pulse combustors.

■ PREPARING CLEAN COAL

The Micro-Mag Process

Described by *Coal* magazine as one of the emerging technologies for the 1990s, a process called micronized-magnetite cycloning, or the Micro-Mag Process, provides the potential to clean fine coal in a technically feasible and cost-effective manner. This process is being developed by researchers at the Pittsburgh Energy Technology Center (PETC).

PETC has demonstrated that a mixture of finely ground (micronized) magnetite and water can be used in a cyclone sepa-

rator to clean coal as fine as 38 microns (the consistency of flour). In various coal preparation processes, the goal is to work with as fine a coal particle as possible to assist in the removal of impurities, particularly those associated with acid rain. Tests of coal ground to 38 microns and then cleaned with the Micro-Mag Process have shown an overall pyritic sulfur reduction of 93 percent.

Previous research at PETC demonstrated the technical feasibility of cleaning coal as fine as 38 microns using a heavy-liquid medium in a cyclone, which proved to be very effective in rejecting pyritic sulfur. The cyclones use centrifugal float-sink forces to spin the liquid mixture, thereby acting on the differences in density to separate the impurities from the medium.

Some heavy liquids such as methylene chloride, freon, and perchloroethylene worked as media, but created problems with environmental acceptability, toxicity, corrosiveness, and cost.

Schematic of the Micro-Mag Process developed at PETC for removing impurities from coal to yield a cleaner burning product.

A medium was needed that could clean coal to the same fine size, while eliminating the problems associated with some heavy liquids. To find that medium, a literature search and a telephone survey were conducted to identify the best ferromagnetic material that could be used in the process. The survey indicated that finely ground natural magnetite has the advantages of lower cost, rheology, flexibility, and stability over other ferromagnetic materials. Natural magnetite not only is more likely to occur in a size more appropriate for the process, but it is also more plentiful for industrial use than other materials such as ferrosilicon or chemically prepared magnetite.

Current work at PETC is focusing on recovery of the micronized magnetite so it can be recycled in the process.

■ SOLID-STATE LITHIUM BATTERIES

Nontoxic, Inexpensive, and Biodegradable Components

LBL scientists consult about the new class of polymer cathodes used in the solid-state lithium battery. This new battery, which has been shown to deliver 30 percent more capacity than most conventional batteries, could have commercial applications ranging from watches to electric vehicles.

Researchers from the Materials and Chemical Sciences Division at Lawrence Berkeley Laboratory (LBL) have developed a new kind of solid-state rechargeable battery. Based on the principle of redox polymerization and depolymerization, the new battery has been shown to deliver 30 percent more capacity than most commercial batteries and at half the weight.

The battery works the same as commercial batteries. The positive electrode materials, however, are unique and much lighter than those used in commercial batteries. The negative electrode is solid lithium, the separator is a solid polymer electrolyte, and the positive electrode is made of a lightweight plastic material consisting mainly of disulfide polymer chains. The monomer units in the positive electrode are linked by chemical bonds between their sulfur atoms. On discharge, electrons are released from the lithium negative electrode and flow in the external circuit to the polydisulfide positive electrode. These electrons break the sulfur-sulfur bonds of the positive electrode, thus unlinking the chains (depolymerizing) and creating monomer units. The current continues to flow until all of the sulfur bonds are broken and the chains are unlinked. The fully depolymerized positive electrode then consists of a lithium salt.

During recharge, a current is applied from an external source and the electrons begin to flow in the opposite direction. The sulfur atoms rebond to each other and reform the polymers (repolymerization). During testing, the batteries retained their staying power and performed like new with virtually no loss of capacity after many cycles or recharges. More than 350 cycles have been demonstrated so far.

The batteries can be made for many uses, from coin-shaped cells used to power watches to cylindrical cells for flashlights or portable computers. Batteries that operate at room temperature could be commercially available within a few years. It is anticipated that other versions of the cells, operating at 80° to 100°C, could provide enough energy to power electric vehicles.

The solid-state battery components are nontoxic, inexpensive, and biodegradable. They have an indefinite shelf-life with no possibility of corrosive electrolyte leakage and/or catastrophic cell failure.

The solid-state lithium battery technology has been licensed to a U.S. company.

Pyrrite is one of the major polluting components of coal. Many processes, including breaking, shaking, washing, and floating, have been used in attempts to physically remove dense crystalline pyrite from the burnable portion of coal. Some processes attempt to chemically remove the pyrite from the coal, which can be very expensive. In a joint venture, the Pittsburgh Energy Technology Center (PETC) and the U.S. Bureau of Mines have teamed up with nature to develop an unsophisticated and relatively inexpensive process for pyrite removal based on the chemistry of coal.

Heap leaching, which is a microbial process, uses iron- and sulfur-metabolizing bacteria to help increase the oxidation of pyrite. Pyrite oxidizes slowly and naturally when coal is stored in stockpiles. However, when bacteria, such as *Thiobacillus ferrooxidans*, are introduced to the coal, the bacteria consumes the pyrite, and the oxidation process, which normally takes about a year, is accelerated by factor of about 6. The oxidized pyrite dissolves and forms rhomboclase, a soluble iron sulfate salt. The rhomboclase then can be washed away from the coal heap when the pile is properly irrigated. The wash water can be reused on the heap. This recycled water will build up acidity that can later be neutralized in a water treatment device. Roughly 50 percent of the pyrite in the coal can be removed using this leaching process.

Testing of the process for removing pyrites (depyritization) took place in the Bureau of Mines Heap Leaching Test Facility on the site shared by the Bureau of Mines and PETC. The process was tested on a 20- to 30-ton heap of stoker-sized coal lumps that were about 1/4 to 3/4 inches in diameter. The heap was monitored by a 48-channel data acquisition computer linked to a main-frame computer. Compressed-air-powered fluid circulation pumps and liquid storage tanks (two 500 gallon and one 1,500 gallon) handled the fluid flows. A water treatment device renewed the leaching fluid.

The future focus of the heap-leaching process will determine its potential for removing pyrite from storage stockpiles of coal at power plants. This process could be especially beneficial for older power plants that need to reduce sulfur emissions but would like to avoid the retrofits necessary for other desulfurization technologies.

ENCOAL Corporation, a subsidiary of Shell Mining Company of Houston, Texas, is working with the DOE to build a plant that will convert low-Btu, subbituminous coal into low-sulfur, high-Btu liquid and solid fuels. Both fuels should be usable in existing power plants, and the liquid fuel has potential as a refinery feedstock for petrochemicals and transportation fuels. ENCOAL Corporation predicts that the fuels from one

■ BACTERIA REMOVE POLLUTANTS FROM COAL

Depyritization Process

■ CONVERSION OF COAL TO NEW LIQUID AND SOLID FUEL FORMS

Mild Gasification Demonstration

commercial-size plant could reduce sulfur dioxide emissions from power plants using the fuels by about 160,000 tons per year. ENCOAL will provide half of the \$72.5 million cost for the project, which is part of the DOE Clean Coal Technology Program. The facility, which is designed to convert 1,000 tons of coal per day, will begin operating in the third quarter of 1992.

The plant will use the Liquids From Coal Process, which Shell Mining Company and SGI International of La Jolla, California, have been developing since 1983. This process involves mild gasification, which is low-pressure pyrolysis of coal to produce liquid and solid products. The coal is heated to moderate temperatures at near-atmospheric pressure, driving off a gas and leaving a solid residue. A low-sulfur, heavy oil called coal-derived liquid, which resembles Number 6 heating oil, condenses from the gas. The remaining low-Btu gas is burned to dry and pyrolyze incoming coal. The solid is further processed to form a stable, high-heating-value, low-sulfur solid called process-derived fuel, which is similar to Eastern bituminous coal.

The Liquids From Coal Process converts 60 percent of the coal by weight and 90 percent of its heating value into the two new fuels. The process also removes most of the moisture and some of the sulfur present in the coal.

The process control system adjusts variables such as coal heating rate and pyrolysis temperature to accommodate variations

ENCOAL Corporation's mild gasification process converts low-Btu, subbituminous coal to high-Btu, low-sulfur fuels. First, the coal is ground, sized, and dried. Next, the coal is pyrolyzed, producing a coal-derived liquid and a solid fuel called process-derived fuel. The simple process will provide low-cost, environmentally benign fuels for power plants and possibly vehicles. The project is part of the DOE Clean Coal Technology Demonstration Program, which is a major mission responsibility of METC.

in coal feed properties and to produce fuel characteristics requested by purchasers. State-of-the-art technology will be used to control emissions of sulfur dioxide, nitrogen oxides, carbon monoxide, hydrocarbons, and particulates in the conversion plant. The process will produce no wastewater or solid wastes.

The demonstration facility will be built by the M.W. Kellogg Company at the Buckskin Mine near Gillette, Wyoming. During the project operating period, the demonstration facility will produce enough of the two fuels for full-scale test burns in industrial and utility boilers. Triton Coal Company, a subsidiary of Shell Mining Company that owns the Buckskin Mine, will provide the feed coal. Other U.S. coals may also be shipped to the demonstration facility for test processing.

As part of the project, data will be collected from the industrial and utility users who will test the fuels in their commercial-size boilers. Once this information is available, rapid commercialization is expected, because industry needs low-cost, high-energy, low-sulfur fuels to meet an ever-increasing demand for electricity while adhering to stringent environmental standards.

A study written for the National Energy Strategy by several DOE laboratories suggests that photovoltaic systems could provide the United States with between 1.8 and 9.4 quads of electricity annually by the year 2030 (an amount of energy equivalent to that contained in 310 million to 1.64 billion barrels of oil). Photovoltaic cells are layered semiconductor devices that directly convert sunlight into electricity without using moving parts. This technology would help meet the growing demand for electricity. It would also displace some of our need for fossil fuels and, thus, help mitigate some environmental concerns, such as acid rain and the buildup of greenhouse gases.

The major impediment keeping photovoltaics from vying for large electricity markets is cost. Today, electricity generated using photovoltaic systems costs between 25¢ and 35¢ per kilowatt-hour, which is nearly 20 times lower than 15 years ago. Even with this improvement, the cost of photovoltaic-generated electricity is still high for many major markets. The DOE strategy for making photovoltaics competitive with conventional methods of generating electricity is three-fold: 1) increase the conversion efficiency of devices, 2) make them more cheaply, and 3) make them stable.

A new device made by researchers at the Solar Energy Research Institute (SERI) advances photovoltaic technology in ways that are consistent with the first two parts of the DOE strategy. First, under unconcentrated sunlight, the new device converts

■ CASCADE PHOTOVOLTAIC CELL SETS EFFICIENCY RECORD

New Design and Fabrication

The record-breaking cascade cell developed by SERI uses a top cell of gallium indium phosphide with a window layer of aluminum indium phosphide, a bottom cell of gallium arsenide, and a tunnel junction of gallium arsenide. The top cell captures and converts high-energy photons while the bottom cell does the same for the low-energy photons. The tunnel junction allows charge carriers to move between the top cell and the bottom cell through a very thin insulating layer.

27 percent of the incident sunlight into electricity, which is a world record for this type of device. Second, it is made monolithically (i.e., fabricated as a single unit), a method that promises to be cheaper than other fabrication methods for devices of this kind.

A big reason that this device converts so much sunlight into electricity is that it uses a cascade structure. Most current photovoltaic devices rely on single-cell (single-junction) technology, and hence on a single absorber material. A device made with a single junction responds well only to a small portion of the solar spectrum, which limits the efficiency of the device. Cascade devices, however, stack two or more dissimilar cells on top of each other. The different absorber materials respond well to different portions of the spectrum, enabling the device to capture and convert a larger amount of sunlight, thus increasing conversion efficiency.

Other reasons the device is so efficient are the design of the device and the choice of materials. The top cell is made of gallium indium phosphide (GaInP_2), which efficiently absorbs and converts the high-energy photons of sunlight into electricity and passes the rest of the sunlight to the bottom cell in the stack. The bottom cell, which absorbs and converts the lower energy photons, is made of gallium arsenide (GaAs), one of the best photovoltaic materials available.

The construction of the cascade cell is also a coup for the SERI researchers. Until recently, it had been extremely difficult to successfully make cascade devices monolithically (i.e., to grow the entire device as a single unit with one cell on top of the other). This problem existed primarily because the atomic spacings of materials often chosen for the top and bottom cells of cascade devices did not match well. Growing one cell on the other would cause stress fractures in the finished device. However, the atomic spacings of the materials used by SERI researchers match quite well, so this problem is avoided.

To make the device, SERI researchers relied on metal organic chemical vapor deposition, which gave them control over deposition of the constituent cell materials. The researchers also thoroughly characterized the fundamental properties of the GaInP_2 material grown under a variety of deposition conditions and developed a computer code for modeling the photocurrent response of the cell.

The 27 percent efficiency attained by the SERI researchers is simply the latest plateau attained. The patented cascade structure has a theoretical efficiency of 34 percent under unconcentrated sunlight, and higher under concentrated sunlight. With further refinement and exploration of other semiconductor alloys, researchers at SERI expect to push cell efficiencies to 30 percent and beyond.

Novel ceramic tube designs and deposition-control features could allow a pressurized ceramic heat exchanger to operate successfully in high-temperature coal-combustion gases. Use of this technology could allow more electricity to be generated per ton of coal, and a reduction in carbon dioxide emissions.

A \$4.2 million project is currently being conducted by Hague International and Stone & Webster Engineering Corporation to investigate the applicability of this approach. The Morgantown Energy Technology Center (METC) and the organizations comprising the Externally Fired Combined Cycle (EFCC) Consortium are providing guidance and financial support for the project. The project funding consists of a \$2.2 million government share and a private industry share of \$2.0 million.

The team from the EFCC Consortium is developing and testing a ceramic heat exchanger for an indirect, exhaust-fired cycle. This cycle will provide a power-generation alternative that can burn coal with considerably higher cycle efficiency than is attainable with other currently available, fossil-fuel technologies. Use of a heat exchanger with ceramic tubes is required for this cycle to be feasible.

In contrast to the direct coal-fired turbine systems being developed in other DOE projects, indirect firing means that only hot air, rather than hot combustion gases, expands in the turbine to produce power. This practice prevents the exposure of the turbine internal parts to combustion gases, thus eliminating potential fouling, erosion, and corrosion problems caused by coal combustion products. Combustion takes place at atmospheric pressure in a conventional pulverized-coal-fired furnace, which provides hot gases to the ceramic heat exchanger. Emissions are controlled with conventional flue gas cleanup systems.

With this concept, the hot air leaving the turbine is used as a source of preheated combustion air, so efficiency is high. When a heat-recovery steam plant is added to a gas turbine power system based on this concept, up to 50 percent more electricity can be generated per ton of coal than with a conventional coal-fired steam plant. Therefore, this concept could reduce carbon dioxide emissions per kilowatt hour by up to one-third from the present levels for coal-fired plants.

The key to the concept is a ceramic heat exchanger that can transfer heat at high temperature. This heat exchanger will transfer energy from the combustion of coal or other ash-bearing fuels to provide thermal energy to the gas turbine. The energy for the combustion process will be transferred through the heat exchanger to the gas turbine, which will use clean air as the working fluid. The result is a system that converts coal to electricity with high efficiency. The system will consist of modular subassemblies that

■ ADVANCED CERAMIC HEAT EXCHANGER FOR HIGH-EFFICIENCY, COAL-BURNING GAS TURBINES

**Ceramic Heat Exchanger for Indirect
Coal Firing**

Coal-fired steam power plants using this indirect-cycle gas turbine system, which was developed with METC and EFCC guidance and funding, could generate up to 50 percent more electricity per ton of coal than conventional coal-fired steam plants. Indirect firing means that only hot air, rather than hot combustion gases, expands in the turbine to produce power.

can be factory assembled for low initial cost, thus allowing a short lead time from order to initial operation with minimum field erection cost.

An atmospheric-pressure version of the ceramic heat exchanger is currently marketed under the trade name of CerHx. The CerHx heat exchanger, when combined with a suitable atmospheric pressure combustor and with suitable modifications for high-pressure operation, will replace the combustion system in an open-cycle gas turbine. The heat exchanger accepts air from the gas turbine compressor and heats this air to the turbine inlet temperature for expansion in the turbine section. The clean air delivered to the turbine replaces the products of combustion in the conventional open cycle, thereby appreciably extending the service life of the turbine section. Only the ceramic tubes in the heat exchanger are exposed to the high-temperature corrosive effects of the impurities in the fuel.

This concept offers an attractive alternative to other coal-based combined-cycle systems under development, primarily because of its high efficiency, flexible design, and suitability for both large-scale and small-scale plants.

■ SATELLITE BATTERY REDESIGNED FOR TERRESTRIAL USE

Bringing Space Technology Down to Earth

Since October 1957, when Sputnik I announced the dawn of the space age, more than 3,500 payloads—most of them military, commercial, and scientific satellites—have been successfully rocketed beyond the earth's atmosphere. Billions of dollars and years of research have gone into developing reliable space hardware.

Sandia National Laboratories (SNL) is now working with industry to bring one of those proven space components—the

nickel/hydrogen battery—back to earth for use in terrestrial applications. Developed in the early 1970s by Comsat Laboratories of Clarksburg, Maryland, and used for more than a decade for energy storage in communications satellites, nickel/hydrogen batteries may find valuable uses on earth.

The characteristics that make these batteries ideal for space vehicles, such as long life, high reliability, and low maintenance, make them particularly attractive for use at remote sites on earth. The major drawback to using them in terrestrial applications has been their high initial cost. SNL has teamed up through a cost-sharing contract with Johnson Controls Inc. of Milwaukee, Wisconsin, to reduce the cost of these batteries. The cost has already been reduced dramatically from the \$25,000-per-kilowatt-hour (kWh) space version down to \$823 per kWh. The goal is to reduce the cost to about \$375 per kWh, and to develop a version of the aerospace battery that will operate at costs that are economically feasible for terrestrial applications.

The aerospace version is expensive primarily because its cells are housed individually in separate pressure vessels, and because of the large amounts of platinum and nickel used in each cell. Working with Johnson Controls Inc., which did the developmental work, SNL provided technical guidance to redesign the battery so that a number of cells are housed in a common pressure vessel. To reduce costs further, the terrestrial version was designed with thicker positive electrodes, which reduces the number of cell components needed. Additional cost reductions were achieved by using negative electrodes that contain less platinum/carbon catalyst. Other strategies for further reducing costs include using negative electrodes that contain even less platinum or some other material less costly than platinum and housing the battery in a less-expensive pressure vessel.

The challenge is to make the modifications necessary to reduce the cost of the battery without unduly compromising its performance. The latest redesign of the aerospace battery by Johnson Controls—a 7-kWh unit believed to be the largest nickel/hydrogen battery ever assembled—has already been successfully tested in an experiment at SNL that linked the battery to a small refrigerator, four 3-watt fluorescent lights, and a photovoltaic array to simulate a remote-site photovoltaic system. Two prototype batteries have been built and are currently being tested at separate locations.

■ SECONDARY RECOVERY OF NATURAL GAS RESERVES

Characterization of Internal Reservoir Geometries

This schematic shows the research targets of the Secondary Gas Recovery Project: by-passed reservoirs, untapped compartments, and deeper pools. These targets are located within existing conventional reservoirs, but efficient strategies to detect them are needed. Funding for the Secondary Gas Recovery Project is provided under a cost-sharing arrangement among METC, the Gas Research Institute, the State of Texas, and private industry.

A 3-year multimillion dollar project is currently underway to develop, test, and verify technologies and methodologies used to recover natural gas from conventional reservoirs in known fields. This gas may be present in by-passed reservoirs, untapped compartments, and deeper, untouched pools.

The \$22.25 million project, known as the Secondary Gas Recovery Project, is being jointly funded by the Morgantown Energy Technology Center (METC), the Gas Research Institute, the State of Texas, and industry. The lead technical contractor is the Bureau of Economic Geology at the University of Texas in Austin.

Increased drilling in existing oil reservoirs has been a major source of additions to known reservoirs in recent years. This reserve growth has come in large part from a better understanding of the internal geometry of these reservoirs and incorporating this understanding into improved field development approaches. The group working on the Secondary Gas Recovery Project hopes to duplicate the results already obtained for oil recovery.

A recent DOE report identified a total reserve growth potential of 119 trillion cubic feet of gas in the onshore lower 48 states. At present, the project focuses on Texas reservoirs in both sandstone and carbonate formations. The project is also field oriented with operators who are drilling current development wells cooperating in the data collection. This approach is a cost-effective means of acquiring data and performing interim tests on research results. Best of all, the eventual users of the technology are directly involved in its development. Integrated geological,

engineering, petrophysical, and geophysical assessments will help producers economically recover known, but undeveloped, natural gas resources.

Characterization of the internal geometry of reservoirs has demonstrated a higher degree of compartmentalization than was previously recognized. Compartmentalization, which is caused by reservoir heterogeneity or nonhomogeneous flow in different directions, is the primary reason that areas within a reservoir can remain untapped or be bypassed during normal recovery processes. Analysis of data obtained has already led to several important interim conclusions and results. A reservoir engineering model for compartmentalized flow has been designed and configured to investigate and characterize flow in compartmented, partially drained reservoirs. Several conceptual models have been developed, including 1) a model that shows the relationship between depositional and diagenetic heterogeneity and hydraulic fracture geometry, and 2) a model that incorporates both vertical and lateral stacking of lithologic units. Pressure differences of 400 to 1,000 pounds per square inch have been observed within individual sandstones, suggesting heterogeneity and nonuniform drainage. Pressures averaging 71 percent of the original reservoir pressure have been encountered in in-fill wells and recompletions, indicating that a significant volume of natural gas still remains in the reservoir.

According to present plans, a joint-venture, field-experiment well (or wells) will be planned and drilled during 1990 and early 1991. Further field experiments at commercial sites are also planned, as well as a continuation of the cooperative data-gathering program. It is hoped that the final result of the project will be a comprehensive strategy or strategies for detecting previously unrecognized pockets of natural gas within existing fields.

CONTENTS

- 73 ■ **FOOD-PROCESSING BYPRODUCTS YIELD
COMMERCIAL PRODUCTS (PNL)**
Fermentable-Carbohydrate Conversion Process
- 74 ■ **FLUIDIZED-BED TECHNOLOGY FOR DISPOSAL OF
HOSPITAL WASTE (METC)**
Meets State and EPA Regulations
- 76 ■ **CONCENTRATED SOLAR ENERGY DETOXIFIES
ORGANIC POLLUTANTS (SNL)**
Purifying Water with Solar Energy
- 77 ■ **GROUNDWATER CLEANUP (INEL)**
Biosorption
- 77 ■ **STUDYING BIOCHEMISTRY OF MICROBIAL
PROCESSES IN EXTREME ENVIRONMENTS (BNL)**
Biotechnological Applications
- 78 ■ **IMPROVING THE CLEANUP OF STUBBORN
HAZARDOUS WASTES (PNL)**
CEPOD
- 79 ■ **REBURNING TO REMOVE NO_x (PETC)**
Demonstration At Ohio Edison's Niles Plant
- 81 ■ **CONVERTING HIGH-CARBOHYDRATE FOOD WASTES
INTO DEGRADABLE PLASTICS (ANL)**
Biolac Bioconversion Process
- 82 ■ **A NEW APPROACH TO SOLVENT EXTRACTION
(ORNL)**
Electronic Pulses Shatter Water Droplets
- 83 ■ **TUNG FLUE GAS DESULFURIZATION PROCESS
(PETC)**
Three Major Steps
- 85 ■ **REMOVING TRANSURANIC WASTE FROM WATER
(LANL)**
The TRU/Clear Process System
- 86 ■ **DIFFERENTIAL ATMOSPHERIC TRITIUM SAMPLER
(PPPL)**
Portable, Efficient, and Reliable
- 87 ■ **REMOVAL OF CESIUM FROM WASTEWATER (SRL)**
A Cesium-Specific Ion Exchange Resin

Argonne National Laboratory (ANL) ■ Brookhaven National Laboratory (BNL) ■ Idaho National Engineering Laboratory (INEL) ■ Los Alamos National Laboratory (LANL) ■ Morgantown Energy Technology Center (METC) ■ Oak Ridge National Laboratory (ORNL) ■ Pacific Northwest Laboratory (PNL) ■ Pittsburgh Energy Technology Center (PETC) ■ Princeton Plasma Physics Laboratory (PPPL) ■ Sandia National Laboratories (SNL) ■ Savannah River Laboratory (SRL)

Environment and Waste Management

A process that converts sugar byproducts to lactates and then to acrylates could result in major savings to manufacturers of acrylate products. Researchers at Pacific Northwest Laboratory (PNL) have worked with the cane sugar industry to develop and commercialize the technology, which has potential for using the byproducts from a wide variety of industries, including beef and cane sugar production, corn wet milling, and potato processing. PNL received a Federal Laboratory Consortium Award in 1990 for transferring this technology to industry.

FOOD-PROCESSING BYPRODUCTS YIELD COMMERCIAL PRODUCTS

Fermentable-Carbohydrate Conversion Process

In the process, carbohydrate materials such as blackstrap molasses (a byproduct of sugar manufacture) or potato-processing wastes are fermented with a lactic-acid-forming organism in the presence of ammonia to produce ammonium lactate, which is combined with alcohol and then with gaseous carbon dioxide. The result of this processing is a solution containing lactic acid esters, which are purified, recovered, vaporized, and then passed through a bed composed of crystalline hydrated and partially calcined calcium sulfate. The calcium sulfate acts as a catalyst to convert the lactic acid esters into acrylic acid esters.

Flow diagram of the process by which byproducts of sugar manufacturing can be converted to acrylate esters. Products made from the acrylates and lactates that result from the conversion process have many valuable applications, such as surface coatings, adhesives, sealants, textiles, detergents or sorbents, animal feed, and biodegradable plastics. This process, which was developed by PNL, received a Federal Laboratory Consortium Award in 1990.

The carbohydrate conversion technology was derived from the work of PNL researchers in the DOE Fuels-From-Biomass Program. Application of the concept exceeded the DOE scope of interest; consequently, PNL sought a nontraditional client to help advance the technology. The Hamakua Sugar Company of Hawaii agreed to support development. Hamakua was interested because

it produces large quantities of low-value blackstrap molasses as part of its sugar cane conversion process.

The carbohydrate conversion technology is needed and is economically attractive to industry. Through its many valuable applications and its cost-saving potential, the process offers significant benefits to all manufacturers and users of carbohydrate-based products. Demand for acrylate materials has historically been great, and prices have been high for final products such as surface coatings, adhesives, sealants, textiles, and detergents or sorbents. Currently, commercial acrylate materials are derived from petroleum-based propylene, which is an expensive feedstock whose supply is subject to petroleum production cycles. The use of low-cost carbohydrates for the production of acrylates could result in raw-material costs that are lower than when propylene is used.

In addition, several products can be manufactured from the lactate materials that are also produced during the conversion process. These lactate materials could be used for animal feed, or they could be used as a low-cost raw material for a biodegradable plastic that would solve an acute solid waste disposal problem.

After several years of laboratory development culminating in successful demonstration of the carbohydrate conversion process at the bench scale and filing of a broad patent application, PNL and Hamakua Sugar Company have developed a strong and mutually beneficial business relationship. Hamakua is pursuing implementation of the initial process steps on a commercial scale, thus advancing the process and speeding transfer of the technology to other companies through licensing. The technology is available from PNL for applications outside the State of Hawaii. In addition, PNL will share future improvements with Hamakua Sugar Company.

■ FLUIDIZED-BED TECHNOLOGY FOR DISPOSAL OF HOSPITAL WASTE

Meets State and EPA Regulations

Disposing of hospital waste in an environmentally responsible way is becoming increasingly complex and expensive. Hospital incinerators undergo corrosion and other deterioration because of intermittent use and because the combustion products themselves are corrosive. Older incinerators often cannot maintain stable temperatures for the long residence times needed to destroy pathogens and toxic matter. Also, because of advances in medical technology, the nature of the wastes is becoming more complex, and fewer municipalities are accepting such waste in their landfills.

To remedy this situation, the Morgantown Energy Technology Center (METC) and the Good Samaritan Hospital in Lebanon, Pennsylvania, will be using the contaminant control

characteristics of coal-fired, fluidized-bed combustors to provide safe incineration of hospital wastes. The combination of limestone and coal ash in the fluidized-bed combustor traps and destroys pollutants inside the furnace. Thus, this combination maintains a clean environment while using coal for fuel rather than natural gas or imported oil.

This technological linkage offers three advantages. First, the temperature at which the fluidized-bed combustor operates is ideal for destroying the components of hospital waste. Second, a fluidized-bed combustor uses limestone to absorb the sulfur emitted from the coal. This limestone, along with ash, reacts with and neutralizes the chlorine that the incineration process liberates from certain plastics. Capturing the chlorine and sulfur in the combustor converts these potentially noxious gases to a nontoxic state. Finally, the combustor provides heat and steam for the hospital.

Early in the program the theoretical aspects of cocombustion were evaluated. Researchers at Pennsylvania State University used thermodynamic calculations to determine that combustion of coal and hospital waste is a valid technology; these calculations showed that fluidized-bed combustors do capture chlorine from the plastics and liquids in the waste stream. The researchers concluded that this technology will meet the stringent permit requirements of the EPA (i.e., 99.99 percent destruction of hazardous chemicals and 99 percent retention of acid-producing gases). Reviews of State and EPA regulations did not identify any barriers that would prevent this technology from being used.

A project team assembled by Good Samaritan Hospital developed a materials-handling system for feeding the hospital waste into the fluidized-bed combustor. The system was designed to minimize the potential threat for contaminating the boiler room or threatening the health of operators.

A boiler manufacturer, who is a METC subcontractor, conducted pilot-scale tests and confirmed the feasibility of the concept at the pilot scale. To protect the environment while simulating the waste that an actual system would use, a "surrogate waste" that is a mixture of plastics and other noninfectious materials was used in those tests. An analysis of ash products and stack emissions from those tests is currently underway. Preliminary results indicate that chlorine capture exceeds 50 percent and that the ash from the surrogate waste tests meets the requirements of the Pennsylvania Department of Environmental Resources for disposing of ash in a sanitary landfill. To date, the analysis has not revealed any negative results. Researchers are confident that this technology for waste disposal will be successful in a proof-of-concept plant, which is currently being designed.

■ CONCENTRATED SOLAR ENERGY DETOXIFIES ORGANIC POLLUTANTS

Purifying Water with Solar Energy

A scientist from SNL adjusts a glass tube containing polluted water and titanium dioxide. Trough-shaped parabolic mirrors surrounding the tube focus concentrated sunlight on the contaminated mixture. With the titanium dioxide as a catalyst, the sunlight breaks down the toxic materials in the polluted water into nontoxic substances.

Mirrors that seem to stretch to the New Mexico horizon may also brighten the horizons of a world in search of solutions to water pollution. With more than 200 million tons of water contaminated yearly in the United States and the demand for pure water continuing to increase, researchers at Sandia National Laboratories (SNL) are demonstrating that solar energy can destroy organic pollutants in water.

The results, achieved by testing the breakdown of an organic acid with a titanium dioxide catalyst, are considered validation of the concept that solar energy can be used to detoxify contaminated surface water or groundwater. Using concentrated solar power to speed up reaction times makes the process more commercially attractive.

Photocatalytic reactions to degrade or break down hazardous contaminants have been under study in a number of countries for more than a decade. Recent DOE-funded work by SNL represents the first time such a process has been brought out of the laboratory for engineering experiments of this size. Compared with laboratory work, these engineering-scale experiments provide a practical measure of the ability of the process to work with large volumes of water.

Working with the Solar Energy Research Institute in Golden, Colorado, where laboratory studies are underway, SNL investigators began a series of tests on the process in late 1988. By increasing the concentration of sunlight, adding small quantities of hydrogen peroxide, and varying the amount of catalyst, they achieved a sharp reduction in the time required to break down the test acid. Salicylic acid at a concentration of 30 parts per million was used initially because the acid is easy to detect and measure, and is known to have properties similar to those of most hazardous chemicals. Beginning with exposure times of almost 30 minutes under normal or "one-sun" light, the team has demonstrated that organic compounds can be reduced to extremely low levels in a matter of seconds using sunlight concentrated to the level of 30 or 60 suns (equivalent to about 500,000 watts of thermal energy on a 10-foot-square surface).

Two systems were used in the proof-of-concept testing at the SNL Solar Thermal Test Facility. In the first system, a parabolic trough was used to focus energy on a long glass tube. The salicylic acid, water, and the titanium catalyst were then pumped through the illuminated tube and into a measuring tank. In the second system, called a falling-film reactor, the mixture of acid, water, and catalyst was pumped over an 11-foot waterfall in a thin film. The reactor was placed 120 feet above the ground on a tower at the SNL Central Receiver Test Facility. Sunlight was focused on the 3-foot-wide flow by up to twenty 20- by 20-foot sun-tracking glass mirrors, called heliostats. Flow rates through both systems ranged from 20 to 70 gallons per minute depending on the system and the test.

In a commercial detoxification system, many heliostats or troughs would be used to provide the necessary solar energy. The systems would be designed to allow processing onsite. After purification, the water would be suitable for drinking, discharge into surface waters, or injection into underground aquifers.

There are frequently a number of contaminants, including uranium, vanadium, strontium, and cadmium, in the groundwater and soil under mining sites. These metals are frequently present at toxic levels and are possibly carcinogenic. The hazardous metals that contaminate the groundwater come from mine tailings, waste rock, and chemicals left from mining and milling operations. Mine tailings are now stored in clay-lined beds; however, in the past, tailings were usually dumped into pits near the mine. Rainwater trickling down through the tailings in the pits carried the metals to the subsoil and eventually to the groundwater.

A team of biotechnologists at the Idaho National Engineering Laboratory (INEL) are working on ways to use microorganisms to clean up groundwater contaminated by wastes from old uranium mines. INEL researchers know that microorganisms are found naturally in wastes from uranium mines, and that the microorganisms affect the rate at which uranium and other metals are dissolved into water. These microorganisms can also be used to separate metals out of solutions in a process known as "biosorption." INEL researchers are now looking for ways to treat aquifers below old mines around the United States.

INEL is studying water and soil samples from mine sites to see which contaminants need to be removed at each location. The cleanup is a twofold process: metals must be taken out of the groundwater, and the remaining contamination must be removed from the subsurface soil.

Selectd groups of microorganisms capable of living in harsh environments are a subject of systematic studies at Brookhaven National Laboratory (BNL). Some of these organisms are capable of solubilizing natural metal salts, while others can live in acidic, high-temperature, and high-pressure environments. Such acidophilic and thermophilic organisms possess properties that make them suitable candidates for industrial processes.

■ GROUNDWATER CLEANUP

Biosorption

■ STUDYING BIOCHEMISTRY OF MICROBIAL PROCESSES IN EXTREME ENVIRONMENTS

Biotechnological Applications

In this photograph, a BNL technician is monitoring the activities of subsurface soil microorganisms that may be useful for biotechnological applications in extreme environments.

Studies of detoxification and recovery of metals by means of acidophilic microorganisms are focusing on removal of metals from byproducts and wastes produced by geothermal power plants. The feasibility of developing a detoxification biotechnology based on microbial processes has already been demonstrated.

This new biotechnology is also applicable to other residues of geological origin with comparable geochemistry. Concurrent exploratory studies are aimed at concentration and recovery of metals from dilute aqueous solutions. In this area, combinations of chemical and biochemical processes serve as the basis of new biotechnologies.

■ IMPROVING THE CLEANUP OF STUBBORN HAZARDOUS WASTES CEPOD

One of the major waste management issues facing the modern world is that of cleaning up hazardous chemical and nuclear waste sites. An innovative chemical processing technology developed at Pacific Northwest Laboratory (PNL) could significantly advance the ability to clean up waste sites. The system, a catalyzed electrochemical production device (CEPOD), uses a powerful, regenerated oxidative catalyst to dissolve, destroy, or decontaminate organic and inorganic materials that cannot be treated by other processes. CEPOD allows highly toxic, nearly insoluble substances to be either eliminated or converted to manageable forms.

CEPOD was designed to prepare electrochemically generated oxidants for use in dissolving essentially insoluble materials. Some materials are almost impossible to dissolve with current processes.

The presence of these materials leads to the accumulation of essentially untreatable wastes. Existing methods for leaching toxic or radioactive materials from scrap, soils, or ashes have used hydrogen fluoride and nitric acid in repeated cycles without complete dissolution. In these cases, only dissolution in hot, concentrated nitric acid containing the very corrosive fluoride ion is considered effective. In addition, the use of nitric acid containing fluoride ions for ashes containing a high silica content has caused off-gas plugging by condensed fluorosilicic acid solids and severe corrosion to plant equipment and downstream processes. The inability of other, less-effective processes to destroy or dissolve these materials has resulted in a large inventory of contaminated scrap residues and many unremediated hazardous waste sites.

The oxidant dissolver used in the CEPOD is produced in a two-compartment electrochemical cell that employs a porous separator between the compartments. Electrodes of specialized design and materials are placed in each compartment, and direct current is passed through the cell at a low voltage. The oxidant attacks resistant organic and inorganic materials, such as plutonium oxide, and completely destroys or renders them soluble in simple acid media.

The electrochemical device can also be used to destroy hazardous organic wastes or gases at ambient temperatures. Traditional destruction methods require high temperatures and result in hazardous byproducts. The CEPOD process usually yields benign elemental products such as carbon dioxide.

CEPOD is currently being used to decontaminate the large national inventory of plutonium-bearing wastes and residues and to remove or reduce the actinide content in soils, ashes, and other stored residues. Plutonium is recovered in this process, which has been hailed as a major breakthrough. Full-scale production equipment installations are now being considered for the Hanford Site in Washington, the Savannah River Plant in South Carolina, the Rocky Flats Plant in Colorado, and the Idaho National Engineering Laboratory.

The technology is available from PNL for other applications and commercial licensing.

Nitrogen oxides (NO_x) play an important role in the formation of acid rain. A large source of this NO_x are the electric utility boilers that burn coal. In particular, cyclone-fired boilers emit the highest levels of NO_x when compared with other types of boilers. Cyclone-fired boilers are used in only 9 percent of the total coal-fired generating capacity in the United States, but they emit 14 percent of the NO_x produced by utility boilers.

■ **REBURNING TO
REMOVE NO_x**
**Demonstration At Ohio Edison's
Niles Plant**

Schematic of the reburn process for removing NO_x from coal-burning electric utility boilers. A reburn system based on the concept will be installed and tested at Ohio Edison's power plant in Niles, Ohio.

Pollutants can be removed from the fuel before it is burned, in the furnace itself, and from the flue gases produced after burning is completed. In-furnace removal has been shown to be a commercially attractive method for removing NO_x. Reburning is viewed as the most promising in-furnace NO_x reduction technique for cyclone-fired boilers. The Pittsburgh Energy Technology Center (PETC) is participating in a full-scale demonstration of this technology at Ohio Edison's power plant in Niles, Ohio, which uses a coal-fired cyclone boiler of the type that traditionally produces high levels of NO_x emissions.

Reburning is essentially a process in which nitrogen oxides generated in the main combustion zone are passed through a slightly fuel-rich or "reburn" zone that causes the nitrogen oxides to be reduced to molecular nitrogen, which is a naturally occurring element in our atmosphere. The fuel-rich gases flow from the reburn zone to the next part of the boiler, the burnout zone, where additional air is added to complete combustion.

Natural gas will replace up to 20 percent of the total fuel heat input to the boiler, which is presently fired solely with crushed coal. Installation of the natural gas reburning equipment on the unit was completed in mid-1990 and long-term testing is expected to be completed during the first quarter of 1992. The goal of the program is to show that NO_x can be reduced by 50 percent with no adverse effects on the boiler operation. The number and location of reburn fuel and additional air injectors to achieve effective mixing have been determined from extensive cold-flow modeling tests with special attention paid to minimizing the impact on boiler/plant modifications. Mathematical modeling has determined that there will be a slight shift in heat absorption patterns in the boiler when the reburn system is operated, but that the changes are well within the framework of the boiler operational tolerances for satisfactory and reliable boiler performance. Pilot tests have shown that boiler tube life has not been significantly changed by operating either with reburn systems using oil as the reburn fuel or with staged, low-NO_x systems. Boiler tube wastage will be carefully monitored.

The project was initiated in 1987 by the EPA when Combustion Engineering was awarded a contract to demonstrate the reburning technology. Since then, the project has attracted participation by the DOE, the Electric Power Research Institute, the Gas Research Institute, Consolidated Natural Gas, the Ohio Coal Development Office, and Ohio Edison. DOE is funding its share of the project through a \$2.5 million interagency agreement with EPA. This project is expected to be completed in the Spring of 1992.

Agricultural and industrial waste streams have become an economic burden as well as a serious environmental problem. Every year in the United States, billions of pounds of cheese whey and potato processing waste are discarded or sold as cattle feed at \$3 to \$6 per ton, sometimes requiring expensive transportation. Argonne National Laboratory (ANL) is developing a potential solution to this economic and environmental problem—a technology that bioconverts existing food-processing waste streams into lactic acid, which is used for making environmentally safe, degradable plastics. This process, called the Biolac process, will not only help to solve a waste problem for the food industry but will also save energy and be economically attractive.

Although the ANL process uses potato waste, the process can be adapted to convert other food wastes or raw materials such as corn starch to lactic acid. Proprietary technology for bioconverting more than 90 percent of the starch in potato wastes to glucose has been developed. The new process substantially reduces the processing time from more than 100 hours (for conventional processes) to less than 10 hours. That means the entire process of converting potato wastes to glucose can be completed daily. Dextrose and other products of starch hydrolysis are subsequently fermented by bacteria that produce lactic acid. The lactic acid is continuously recovered, concentrated, and further purified to a polymer-grade product. Although plastics containing lactic acid have been made elsewhere, ANL has designed and is constructing polymers and copolymers that will be environmentally safe because they are degradable.

Interest in environmentally degradable plastics is expanding rapidly. Major environmental concerns such as litter, waste materials on beaches and in the ocean, and burgeoning landfills are directly affected by plastics, which can remain undegraded for hundreds of years. Stimulated by public demand, strong State and Federal legislation is forcing industry to explore degradable and recyclable plastics. These plastics should be able to degrade to innocuous compounds, have suitable physical and mechanical properties, and be cost effective. Few of the degradable plastics currently available, including plastics containing starch, meet these criteria. However, polymers and copolymers made with lactic acid can have excellent mechanical properties and degradability characteristics.

Potential uses for lactic-acid-based, water-sensitive plastics are agricultural applications, such as time-release coatings for fertilizers and pesticides, and degradable mulch films, which could have the degradation programmed to coincide with the end of its useful life, for example, at harvest time. Other possible applications include degradable coatings for paper-based products such as drinking cups, as well as a wide range of plastics for marine applications.

■ CONVERTING HIGH-CARBOHYDRATE FOOD WASTES INTO DEGRADABLE PLASTICS

Biolac Bioconversion Process

ANL is developing a technology that bioconverts existing food processing waste streams into lactic acid, which is used to make degradable plastics. Potential uses for the plastics include agricultural applications, degradable coatings, and marine plastic applications. In this photograph, a chemist from ANL is checking a sheet of biodegradable plastic for ultraviolet transmission.

■ A NEW APPROACH TO SOLVENT EXTRACTION

Electronic Pulses Shatter Water Droplets

The availability of low-cost feedstock (starch from potato waste and lactose from cheese whey) and cost-effective bioconversion and recovery processes should stimulate the development of lactic acid as a commodity compound, and its use in producing biodegradable and photodegradable plastics. Two patent applications have been filed (one for the Biolac process and one for the degradable plastic).

A workshop for industry on the bioconversion of food processing waste streams into lactic acid was held at ANL in late June 1990. The meeting was attended by representatives from 66 companies with a wide range of industrial interests: food processors, chemical manufacturers, dairy associations, oil companies, and venture capitalists. The purpose of the meeting was to introduce the technology to industry and to find cost-sharing partners for commercialization of the efforts. The industrial response to the workshop was favorable and enthusiastic. Follow-up discussions and possible joint arrangements are developing.

Researchers in the Chemical Technology Division of Oak Ridge National Laboratory (ORNL) have invented a device that represents a significant improvement in the area of solvent extraction, which is a widely used technique to recover valuable materials from a liquid stream.

Known as the Emulsion Phase Contactor (EPC), the technology uses a pulsed electrical field to enhance recovery of chemicals (either valuable products or pollutants) that are dissolved in water. Because of its higher efficiency, the recovery method can be accomplished in much smaller vessels than those used in conventional solvent extractors, which use mechanical processes to recover chemicals.

When water droplets carrying the substance to be extracted are introduced into the EPC, they are shattered by electronic pulses that produce water particles in the 1- to 5- micron size range. These water particles are up to 100 times smaller than those created by mechanical agitation. These tiny particles produce a much greater surface area than can be achieved using chemical agitators, enabling the chemical solvent to extract more material from the water base. In addition, the EPC uses much less power than mechanical methods and has no moving parts; therefore, servicing requirements for the extraction apparatus are expected to be significantly reduced.

ORNL researchers initially tested the technology at a very small scale, and evaluated its capabilities in extracting high-value substances such as isotopes, pharmaceuticals, and precious metals. Further work has indicated that the EPC can be applied on a much larger scale to handle more common chemical substances.

Schematic of the experimental concept for the Emulsion Phase Contactor, which was developed at ORNL. This process will greatly enhance the efficiencies of solvent extraction operations. The four regions of fluid behavior in the process—organic disengagement, emulsification and coalescence, aqueous disengagement, and aqueous phase—are illustrated in this drawing.

Two licenses for the EPC technology have been granted by ORNL. Analytical Bio-Chemistry Laboratories of Columbia, Missouri, will develop the technology for use in analytical laboratory equipment, and National Tank Company of Tulsa, Oklahoma, will incorporate it into large-scale processing systems for the metals and petroleum industries.

The Tung Flue Gas Desulfurization (FGD) Process, a Raycon Research and Development Inc. project funded by the Pittsburgh Energy Technology Center (PETC), can remove 98 percent of the sulfur dioxide from flue gases with most of the solutions in the process being regenerable.

The Tung FGD process consists of three major steps: wet scrubbing of flue gas, liquid-liquid extraction of bisulfite ions into an organic solvent, and steam stripping the organic solvent to produce a concentrated stream of sulfur dioxide gas. Particulates are removed from the flue gas using conventional particulate control devices before the process begins.

The flue gas is scrubbed in two stages. In the first stage, the prescrubber cools and saturates the flue gas with water while washing out most of the remaining particulates and water-soluble impurities such as chlorides and fluorides. The second stage contacts the cooled, water-saturated flue gas with an aqueous solution

■ TUNG FLUE GAS DESULFURIZATION PROCESS

Three Major Steps

that is rich in sodium sulfite. This solution captures the sulfur dioxide and produces a solution containing a bisulfite ion. Some oxidation of the bisulfite ions yields sodium sulfate, which is subsequently removed from the system.

The bisulfite ions are transferred from the aqueous scrubber solution to an organic mixture using a series of mixers/stirrers to perform the countercurrent liquid-liquid extraction step at room temperature. This step includes mixing the aqueous solution with the organic solvent and allowing it to settle and separate several times. The aqueous solution is regenerated to sodium sulfite and returned to the scrubber, and the bisulfite-bearing organic solvent then proceeds to the steam-stripping step.

In the steam-stripping step, the sulfur dioxide and water are removed from the bisulfite-loaded organic solvent, and the organic solvent is regenerated for reuse in the liquid-liquid extraction step. The loaded organic solvent is preheated and contacted with steam in a multistage column. As the organic solvent progresses down the 20 trays in the column, steam bubbles flow up through the solvent at each tray and cause a reaction that releases gaseous sulfur dioxide. The recovered gaseous sulfur dioxide can then be processed further to produce elemental sulfur, sulfuric acid, or liquid sulfur dioxide, all of which can be sold commercially.

This diagram shows the three major steps used in the Tung Gas Desulfurization Process: wet scrubbing of the flue gases, liquid-liquid extraction, and steam stripping to remove sulfur dioxide, which can be converted to useful products.

The Tung FGD process has been successfully demonstrated in bench-scale testing. Proof-of-concept testing will take place at the Niagara Mohawk Power Corporation Dunkirk Station Unit Number 4. Early results suggest that the process is inexpensive and is suitable for installation at both existing power plants and at new plants. Full-scale application is aimed at retrofit cleanup on 500-MWe units. Commercial use of this process is expected because of its retrofit ability and low operating costs.

A major advance toward solving some of the most intractable problems of environmental cleanup is the TRU/Clear Process System invented by a team of researchers at the Los Alamos National Laboratory (LANL). This process was developed to extract and remove the final trace amounts of the radioactive elements called transuranic (TRU) elements from wastewater streams produced by nuclear facilities. The system, which is completely compatible with existing wastewater treatment technologies, is potentially capable of removing other toxic heavy metals, such as arsenic, mercury, and cadmium, as well as hazardous organic contaminants from wastewater. Future users of the LANL system might include electronics manufacturers and chemical production plants as well as the nuclear industry. The process defines a new chemistry and chemical technology for wastewater treatment that makes a near-zero discharge of pollutants feasible in the near future, while reducing overall waste management costs.

The unprecedented effectiveness of the TRU/Clear Process System for removing TRUs from solution resides in an innovative chemical formulation containing potassium ferrate and some proprietary additives that enhance the polishing step. The iron in the potassium ferrate salt is degraded at a user-controlled rate to an insoluble form. The insoluble material becomes a micro-crystalline precipitate that, as it forms and grows, removes TRUs from solution by binding both soluble and insoluble TRUs to its surface. This slow, controllable precipitation allows the chemical to sweep over every molecule in the wastewater. Thus, the LANL chemical formulation is far more effective in polishing the last traces of TRUs from the solution than are conventional coagulants, which form precipitates so quickly that large portions of the wastewater remain relatively unaffected.

The water discharged to the environment by the TRU/Clear Process System exceeds the drinking water standards established by the EPA. Further important advantages involve cost savings. The process requires only one-tenth of the chemical dose employed in standard wastewater treatment methods: one pound of the relatively inexpensive substance can treat from 25,000 to 50,000 gallons of water. In addition, the volume of radioactive

■ REMOVING TRANSURANIC WASTE FROM WATER

The TRU/Clear Process System

sludge remaining after the treatment is only one-third to one-twentieth of that remaining after conventional water treatment. This volume reduction alone could save tens of millions of dollars in the cost of storing radioactive waste.

The TRU/Clear Process System, used by LANL in its own wastewater treatment plants, has been licensed to Analytical Development Corporation, a 20-year-old analytical chemical firm that hopes to market the system as an important new contribution to solving environmental problems.

■ DIFFERENTIAL ATMOSPHERIC TRITIUM SAMPLER

Portable, Efficient, and Reliable

Schematic of the Differential Atmospheric Tritium Sampler developed at PPPL. This system is sensitive enough for environmental sampling, and also can be used for stack sampling or health physics purposes.

The Differential Atmospheric Tritium Sampler (DATS) developed at the Princeton Plasma Physics Laboratory (PPPL) samples air for tritium in either its molecular form (HT) or as water vapor (HTO). The DATS can be used on a continuous duty cycle or an interim basis. It is sensitive enough for environmental sampling and can also be used for stack sampling or health physics purposes. By operating on either alternating or direct current and by using various trap materials, DATS may be left unattended for up to a few weeks at a remote site.

During operation, air is passed through a series of three traps (e.g., a molecular sieve or a water trap) to remove moisture and any HTO. HTO is removed in the first trap. A palladium catalyst combusts any hydrogen or HT present and deposits it in the third trap, which may be a molecular sieve or a water trap. The second trap consists of a molecular sieve and is placed between

the first and third traps to prevent cross-over and to ensure high differentiation between HT and HTO.

The sampler, which typically runs at 0.1 liters per minute, will sample 1 cubic meter of air in a week, with a sensitivity of better than 10 picocuries. The efficiency of the sampler is 100 percent for HTO and from 60 to 90 percent for HT. A nonexplosive carrier gas is used for operation and as a calibration of the HT section of the sampler. A unique application of the catalyst allows the DATS to be portable, to have a high sensitivity for differential tritium detection, and to be reliable. The DATS can yield frequent results and still be sensitive enough for health physics purposes.

Researchers at the Savannah River Laboratory (SRL) have applied for a patent for an ion exchange resin that will remove cesium from water. Radioactive cesium-137 is a fission product of nuclear reactor operations. Cesium may enter the water of spent fuel holding basins through defects in fuel cladding. Control of cesium in these basins is desirable to keep personnel exposure to a minimum.

Cesium is also present in the waste from reprocessing of defense nuclear reactor fuel. Research has been underway at SRL for over a decade to improve management of high-level reprocessing waste. The current technology separates the waste into soluble and insoluble components. Radioactive constituents are removed from the soluble component stream and combined with the insoluble components, which are then converted to a glass for long-term storage. Cesium is the most radioactive constituent of the soluble components stream.

The SRL resin is a resorcinol-formaldehyde condensation polymer highly specific for cesium and is about 10 times more effective in removal of cesium than other ion exchange resins evaluated for use in processing defense nuclear waste. Tests have been run at SRL using both simulated and actual waste streams. In both cases, the ratio of the cesium concentration in the effluent to that in the feed was determined as a function of the number of column volumes. The resin supports a throughput of about 200 column volumes of feed containing 6 molar sodium ions. The license for manufacturing this resin is available through DOE.

■ REMOVAL OF CESIUM FROM WASTEWATER

A Cesium-Specific Ion Exchange Resin

CONTENTS

- 89 ■ NEW VISTAS IN MOLECULAR BIOLOGY RESEARCH (LANL)
Fast Agarose Gel Electrophoresis
- 90 ■ NEW ASSAY KIT CAN MEASURE VERY LOW LEVELS OF CADMIUM (ANL)
Blood Cadmium Assay Kit
- 91 ■ NEW DIAGNOSTIC PROCEDURE TO DETECT Q FEVER (PNL)
Q-Endoscreen
- 92 ■ SAMARIUM-145 USED FOR CANCER TREATMENT (BNL)
Photon Activation Therapy
- 94 ■ HUMAN MAMMARY EPITHELIAL CELLS (LBL)
A Valuable Cancer Research Tool
- 95 ■ YTTRIUM-90 USED TO TREAT COLON CANCER (ORAU)
Awaiting "Investigational New Drug" Approval
- 96 ■ LUNG MONITOR ALLOWS DIRECT MEASUREMENT OF PLUTONIUM (ANL)
Supersensitive Lung Monitor
- 97 ■ RADIONUCLIDE GENERATOR FOR HEART STUDIES (ORNL)
Iridium-191m
- 97 ■ NEW TOOLS FOR CANCER RESEARCH (LLNL)
Monoclonal Antibodies Measure Tumor Growth
- 99 ■ PROTON ACCELERATOR FOR CANCER TREATMENT SHIPPED (Fermilab)
National Laboratory/University Medical Center/Industrial Cooperation
- 100 ■ IMPROVED TECHNOLOGY FOR AIDS AND LEUKEMIA RESEARCH (LLNL)
High-Speed Electronics Improves Cell Sorter
- 100 ■ DEVELOPING POWERFUL TRITIDE TECHNIQUE (LBL)
Organic and Biological Molecule Labeling

Argonne National Laboratory (ANL) ■ Brookhaven National Laboratory (BNL) ■ Fermi National Accelerator Laboratory (Fermilab) ■ Lawrence Berkeley Laboratory (LBL) ■ Lawrence Livermore National Laboratory (LLNL) ■ Los Alamos National Laboratory (LANL) ■ Oak Ridge Associated Universities (ORAU) ■ Oak Ridge National Laboratory (ORNL) ■ Pacific Northwest Laboratory (PNL)

Biology and Medicine

The human genome, the coded chemical instructions for the production of the thousands of proteins that guide the body's development and maintain its biological systems, is carried by each human being in the molecules of deoxyribonucleic acid (DNA). Researchers in the field of molecular biology examine DNA samples for a wide variety of purposes including genetic screening and mapping, forensic medicine, and studying genetic diseases ranging from cancer to manic depression.

The one step that is common to most molecular biology projects is the separation of DNA molecules by gel electrophoresis, a process in which electrically charged particles or molecules migrate through a gel under the influence of an applied electrical current. When using conventional techniques, this process was time consuming—sometimes taking as long as 36 hours. The Fast Agarose Gel Electrophoresis (FAGE) system, developed at Los Alamos National Laboratory (LANL) and the University of Tennessee, shortens the process so dramatically that it will be a valuable research tool for scientific laboratories worldwide.

The FAGE system separates DNA molecules or DNA complexes by size, which can be used to distinguish one type of DNA from another. The system is inexpensive and highly reliable, but its primary advantage is speed. The FAGE system can separate the molecules ranging in length from 200 base pairs (the chemical building blocks of the molecules) to 400,000 base pairs in 4 to 60 minutes.

In aqueous solution, the movement of the DNA does not depend on the size of the DNA molecules. When agarose is used to gel the solution, however, the DNA fragments have to move around the filaments of solidified agarose. The larger molecules have difficulty skirting the filaments, which slows their migration in the gel. In conventional systems, increasing the voltage in the gel makes all the fragments move at the same speed regardless of their size. But in the FAGE apparatus, the mobility of the DNA is determined by molecular weight even at high voltages. Because this result contradicts established theory and the results of previous experiments, LANL researchers are working to develop a new theory.

The degree to which the FAGE system is an improvement over conventional systems depends on the area in which the apparatus is used. For example, molecular biologists who clone DNA typically work with small molecular fragments. These researchers will find that the FAGE system is 10 times faster than existing systems for their purposes. Biologists who investigate chromosome structure and the human genome use larger DNA fragments; for them, the processing time will be cut from 36 hours to about 2

■ NEW VISTAS IN MOLECULAR BIOLOGY RESEARCH

Fast Agarose Gel Electrophoresis

The Fast Agarose Gel Electrophoresis system, a dramatically faster method of separating DNA molecules by gel electrophoresis, will be a valuable research tool for molecular biologists. Developed by LANL and the University of Tennessee, the system is inexpensive and highly reliable, but its primary advantage is speed. It can separate the molecules in DNA fragments ranging in length from 200 base pairs to 400,000 base pairs in 4 to 60 minutes. The system is a 1990 R&D-100 Award winner.

■ NEW ASSAY KIT CAN MEASURE VERY LOW LEVELS OF CADMIUM

Blood Cadmium Assay Kit

hours. Biochemists who study protein/DNA complexes can work more rapidly but will also be able to characterize, for the first time, mixtures in which individual complexes exist for only a few minutes. Thus, the impact of the FAGE system on molecular biology—from mapping the human genome to studying human diseases—will be significant.

The FAGE system includes the apparatus in which the electrophoresis is performed, the method for preparing the DNA and the gel, and the method for running the electrophoresis. A patent on this 1990 R&D-100 Award-winning invention is pending.

Researchers believe that monitoring cadmium concentrations in the body is critically important because adverse responses are being observed at low levels of exposure to that heavy metal. The body retains cadmium for a long time, and its toxic effects are cumulative.

Existing monitoring processes use an extraction, or wet-ashing, step that removes cadmium from its organic environment but does not dramatically change its inorganic environment (i.e., the other salts associated with blood). Normal human blood has elements at concentrations 1 to 2 million times greater than that of cadmium.

Scientists at Argonne National Laboratory (ANL) have developed a method of monitoring cadmium by removing the unwanted salt background and concentrating the cadmium. The Blood Cadmium Assay Kit is a highly sensitive procedure for analyzing blood, plasma, or urine. The new procedure concentrates the cadmium in body fluids into a very small volume, and separates cadmium, zinc, and possibly mercury from nearly all other elements that make the analysis of cadmium extremely difficult. Concentrating cadmium allows an accurate and precise measurement to be made at concentrations less than 0.5 parts per billion.

The kit is at least 10 times more sensitive than the best assay procedure currently available. This increased sensitivity is important because current procedures are not sensitive enough to reliably measure cadmium concentrations in either the blood, plasma, or urine of persons exposed to low, but toxic, levels of cadmium.

In addition to measuring blood cadmium, other applications for the kit include determining cadmium concentrations in seawater at levels that previously could not be measured, but which may affect fish, and measuring the amount of cadmium in blood serum and the amount bound to protein in the blood serum. Bound cadmium is more toxic to kidneys than other chemical forms.

Industries involved in cadmium production include cadmium/zinc smelting and refining, metal plating, and the manufacturing of paints and pigments, nickel/cadmium batteries, and plastics. The patenting procedure has been initiated, and there has been commercial interest in the kit, which won a 1990 R&D-100 Award.

Q fever, highly infectious and sometimes fatal, annually afflicts thousands of people worldwide. Yet, until now, it has proved nearly impossible to diagnose. Q-Endoscreen, a new detection method developed by researchers at the Pacific Northwest Laboratory (PNL), Washington State University, and the University of New Mexico will enable fast, accurate, and inexpensive identification of the elusive disease.

■ NEW DIAGNOSTIC PROCEDURE TO DETECT Q FEVER

Q-Endoscreen

PROBE: QpH1/pHK17				
TOTAL DNA ON FILTER				
"S"	1000ng		1000ng	NINE MILE PHASE 2
	100		100	
	10		10	
	1		1	
	0.1		0.1	
	0.01		0.01	
QpH1/ pHK17	100		1000	PRISCILLA
	10		100	
	1		10	
NINE MILE PHASE 1	100		1	
	10		0.1	
	1		0.01	

*This photograph illustrates the ability of the Q-Endoscreen procedure, which was developed at PNL, to detect different strains of the *Coxiella burnetii* bacterium at levels down to one nanogram. The "S" and "Priscilla" strains can cause chronic endocarditis, which is usually fatal. The "Nine-Mile" phases 1 and 2 cause the acute variety of Q fever. PNL won a 1990 R&D-100 Award for this technology.*

Q-Endoscreen is a simple procedure, but is potentially so valuable that it received a 1990 R&D-100 Award. The procedure detects *Coxiella burnetii*, a very specialized bacterium that, depending on the strain present, can cause either the acute febrile illness known as Q fever or a chronic endocarditis. Endocarditis, which is an inflammation of the membrane lining the cavities of the heart, is usually fatal to humans. The Q-Endoscreen test also determines which strain is present.

The Q-Endoscreen procedure is based on the observation that the different strains of *Coxiella burnetii* contain different plasmid sequences. Genetic probes are used to identify DNA from the parasitic microorganisms in blood, tissue, or urine samples. The

organism need not be grown or isolated in the laboratory; rather, Q-Endoscreen can specifically amplify any *Coxiella burnetii* DNA that may be present in a biological sample. Moreover, the procedure is remarkably fast—test results are available in only 12 to 16 hours. Q-Endoscreen is also a sensitive method for monitoring efficiency of treatment regimens, detecting as few as two organisms in a biological sample.

Q-Endoscreen occupies a unique position in the market. There is currently no other clinical method for differentiating between the strains of *Coxiella burnetii*. Alternative methods take 2 to 3 weeks to perform; thus, they are too slow to be of any value in treating the diseases. Furthermore, they can only confirm exposure to the organism, and merely serve as epidemiological tools to confirm that an outbreak has occurred.

Physicians should find Q-Endoscreen a valuable tool for fast diagnosis. Although there is currently no known cure for chronic infections, the symptoms can be treated. Fast diagnosis would enable doctors to administer rapid and appropriate treatments and to monitor the efficacy of treatments—perhaps leading to eventual discovery of a cure for this insidious disease.

This fast and accurate procedure for diagnosis should also be extremely valuable to veterinarians. While Q fever is not transmitted between humans, it originates in animals. Q-Endoscreen provides the ability to determine on short notice which animals harbor *Coxiella burnetii* and whether certain species, or herds, are serving as natural reservoirs for chronic disease-causing strains that infect humans.

The award-winning Q-Endoscreen technology is available for transfer from PNL.

■ SAMARIUM-145 USED FOR CANCER TREATMENT

Photon Activation Therapy

A new radiation source for treating malignant tumors—samarium-145—has been developed by three researchers from the Medical Department at the Brookhaven National Laboratory (BNL). The work was performed in collaboration with the Ophthalmology Department at North Shore University Hospital on Long Island.

Samarium-145 is a source of X-rays, or photons. Recently two events—experiments at the National Synchrotron Light Source (NSLS) and clinical tests at Ohio State University—have produced evidence that samarium-145 has a promising future as a source of photons for a new type of cancer therapy called photon activation therapy (PAT). Clinical tests using samarium-145 in PAT are expected to begin within a year.

PAT uses a double-component attack on malignant tumors. The first component is iodine incorporated in the DNA of tumor cells. The second component is a photon with an energy suitable for activating the iodine. Neither agent is effective alone; however, when combined, they can destroy tumors.

As a cancer therapy, PAT overcomes many of the limitations of surgery, chemotherapy, and conventional radiation therapy. With PAT it should be possible to leave normal tissue unharmed, while causing far more destruction to the microscopic extensions of the cancer than is possible with conventional therapy.

In PAT, the patient is given nonradioactive iodine in a form known as IdUrd. The IdUrd molecule is structurally similar to thymidine, a base used by cells to make DNA when they replicate. Because such cell division occurs quite rapidly in malignant tumors, IdUrd is efficiently incorporated in the tumor.

IdUrd has two advantages. It makes the tumor more sensitive to the destructive effects of X-rays, and when the iodine in IdUrd is activated by photons of a specific energy, it produces tumor-destroying cascades of electrons—called Auger cascades—within the tumor cells.

In an Auger cascade, at an energy of 33,200 electron volts (33.2 KeV), a photon ejects an electron from its position within one of the innermost shells of the iodine atom. In order to stabilize the atom, an electron from an outer shell drops down to fill up the "hole" in the inner shell. As the electron drops down, it gives off an X-ray, which knocks out another electron, and so on. In an IdUrd molecule, one photon can cause an Auger cascade of approximately 11 electrons.

The new samarium-145 source, which is made in the High Flux Beam Reactor (HFBR) at BNL, has many advantages. First, it has a half-life of about a year, which is about 6 times longer than other radiation sources of this type. This longer half-life means that it can be sent to distant places and stored without difficulty. Second, the BNL researchers have been able to make samarium-145 in very small 4 x 0.8-millimeter seed-like capsules. These capsules can be surgically implanted directly in tumors, a technique referred to as brachytherapy. For example, arrays of these seeds can be attached to the back of the eye for the treatment of ocular cancer. Even more important, samarium-145 emits photons of the correct energy to activate Auger cascades.

Great interest in the production of samarium as a source for PAT has been demonstrated by the Medical Device Division of the 3M Company in Minnesota. 3M assisted in research and development by encapsulating and sealing the enriched samarium oxide (samarium-144) in titanium capsules, which are then activated at the HFBR to become the radioactive sources of samarium-145.

BNL scientists at beam line X17B1 at the National Synchrotron Light Source. Samarium-145 for use in photon activation therapy for cancer is produced at this beam line.

■ HUMAN MAMMARY EPITHELIAL CELLS

A Valuable Cancer Research Tool

Normal and immortalized cultures of human mammary epithelial cell specimen 184 grown in the serum-free medium MCDB170: A, untreated normal cell strain, 9th passage; B, immortalized cell line 184A1, 15th passage; C, immortalized cell line 184A1, 42nd passage; and D, immortalized cell line 184B5, 11th passage. These cells, which are produced at LBL, are valuable cancer research tools.

Because samarium-145 has a reasonably long shelf life and the ability to activate Augur cascades, 3M is interested in its commercial potential as a possible replacement for implantable iodine-125 brachytherapy sources that are currently used to treat malignant brain tumors.

A large percentage of human cancers (85 to 90 percent) originate in epithelial cells, which are the closely packed functional cells that line the body cavities and ducts. In the past the difficulty of growing normal, healthy human epithelial cells in culture presented a barrier to cancer research.

Cancers of epithelial cells are carcinomas, and tumor cells taken from a person with carcinoma are easier to grow because some of them spontaneously develop into continuous, "immortal" cell lines. Immortal cells are continuous cell lines that can be expected to live indefinitely in culture. The problem with these cells, however, is that they represent very abnormal cell types.

In order to understand cancer-causing mechanisms, researchers needed to study normal, healthy human cells. Scientists at the Lawrence Berkeley Laboratory (LBL) Cell and Molecular Biology (CMB) Division succeeded in promoting the long-term growth of normal human mammary epithelial cells in a culture. This breakthrough meant that large cell populations could be generated and stored frozen, permitting multiple experiments over a period of time with cells from a single donor. LBL researchers have also successfully established two immortal cell lines from the tissue. Normal cell strains grown in culture were made immortal after exposure to benzo(a)pyrene. These immortal cell lines were transformed to malignant cell lines after exposure to oncogenes and oncogenic viruses.

Scientists engaged in carcinoma research now have a virtually unlimited supply of normal parent cells grown from healthy human epithelial mammary tissue, carcinogen-treated "extended life" cultures, and the immortal cell lines, all from the same individual. Researchers use these lines to study normal and abnormal human cell physiology and biochemistry, immunology, growth factor and oncogene action, genetics, and mechanisms of carcinogenesis.

LBL provides investigators across the country with human mammary epithelial cell cultures to help stimulate research in human epithelial cell carcinogenesis and differentiation. Patented and nonpatented cells are available from LBL.

A new radiation treatment, which was developed by researchers at Oak Ridge Associated Universities (ORAU) and takes just 14 to 21 days to shrink colorectal tumors in laboratory mice, is under review for clinical trials with human cancer patients. The treatment, which was developed with the support of the DOE and a grant from the National Cancer Institute, has succeeded in reducing the size of tumors by up to 95 percent. Colon cancer, the second leading cause of cancer deaths in the United States, is extremely difficult to treat unless it is detected early enough for surgical procedures.

In laboratory tests over the last 5 years, a team of researchers from the Medical Sciences Division at ORAU has developed the treatment using yttrium-90, a decay product of radioactive strontium-90. The yttrium-90 is transported to the tumors by attaching it to monoclonal antibodies that seek out the cancer cells. Once the radioisotope has been targeted to the tumor, the radiation destroys many of the cells, dramatically reducing the size of the tumor. Since this treatment usually does not completely eliminate all the cancer cells, it cannot be called a cure, but it does seem to be an effective method of shrinking colorectal tumors.

Clinical trials of this new radiopharmaceutical agent in colon cancer patients at the Thompson Cancer Survival Center in Knoxville, Tennessee, will begin after approval for use of an "investigational new drug" is received from the U.S. Food and Drug Administration. The application was submitted in early July 1990.

In tests at ORAU, human colon cancer cells were implanted under the skin on the backs of special laboratory mice. The tumors were allowed to grow to a certain size before some mice were injected with CO17-1A, a monoclonal antibody developed and supplied by the Wistar Institute in Philadelphia. The CO17-1A antibody had been labeled with yttrium-90. Other mice, left untreated, served as controls. After 2 weeks, tumors in the treated mice were barely visible, while tumors in the untreated control mice were still growing at a rapid rate.

Researchers caution that an agent's ability to treat tumor-bearing laboratory mice does not always mean that it will be effective in treating humans with colon cancer. It will take time to expand these study results to determine the safest effective doses of yttrium-90-labeled CO17-1A on humans.

■ YTTRIUM-90 USED TO TREAT COLON CANCER

Awaiting "Investigational New Drug" Approval

■ LUNG MONITOR ALLOWS DIRECT MEASUREMENT OF PLUTONIUM

Supersensitive Lung Monitor

This drawing depicts the mounting method for the Silicon X-Ray Detector developed at ANL. An array of silicon [Si(Li)] detectors, which are mounted in a cryostat and cooled by liquid nitrogen (LN), faces the lungs. The array is surrounded by a large sodium iodide [NaI(Tl)] scintillation detector, joined on top by an array of photomultiplier tubes. Plutonium from the lungs of a contaminated subject emits X-rays that impinge on the silicon detectors and are recorded in a computer. Unwanted gamma rays penetrate the detector and are absorbed by the sodium iodide scintillator, which prevents them from being recorded. Thus, the sodium iodide detector acts as an active shield against the undesirable gamma-ray background.

Scientists at ANL have developed a supersensitive monitor that can measure plutonium directly in the lungs. Innovations include using silicon to minimize background noise and a novel mounting method to make both sides of the silicon detector usable. The detector is mounted on a motor-driven gantry inside a radiation shield. This mounting enables accurate detector positioning over the subject's lungs.

The ability to measure radioactive contaminants, such as plutonium, in human lungs is beneficial to the health of workers in the nuclear industry. Until recently, however, no devices were available that were sensitive enough to measure plutonium directly in the human body. Plutonium levels have been inferred from the level of americium-241, which is usually present as well. Such indirect measurement involves many uncertainties, which could be detrimental to the health of a contaminated subject.

Scientists at Argonne National Laboratory (ANL) have developed a supersensitive monitor, the Silicon X-Ray Detector, that can measure plutonium directly in lungs. The plutonium is measured by counting the weak X-rays resulting from the decay of plutonium. The new device can measure very low levels of plutonium because the detector is made of silicon, instead of the commonly used germanium, to minimize background noise. The monitor uses a novel mounting method that makes both sides of the detector usable, thereby providing active background suppression. One side of the detector faces the lungs, and the other side faces a large sodium iodide scintillation detector that serves as an active shield to further reject undesirable gamma-ray background. The combination of high resolution and low gamma-ray background results in an ultra-high detector sensitivity that approaches the maximum achievable sensitivity in lung monitoring.

Personnel at weapons production facilities, nuclear power plants, and research laboratories could benefit from the ability of the Silicon X-Ray Detector to provide direct, accurate measurements of trace-level quantities of plutonium in the lungs. The lung monitor is not patented.

Researchers at Oak Ridge National Laboratory (ORNL) have developed a new generator system that produces the medical isotope iridium-191m, which is useful for imaging the human heart. Pending approval by the U.S. Food and Drug Administration, clinical studies in the United States using isotopes produced by the generator were expected to commence in late 1990. The isotope has been successfully used in over 600 patient studies performed by ORNL collaborators in Europe. The DOE Office of Health and Environmental Research funded this research, which led to development of the generator by the Nuclear Medicine Group at ORNL.

Because of its extremely short half-life (4.9 seconds), iridium-191m, which is a decay product of osmium-191, is uniquely suited for performing a series of studies on the same patient to evaluate the efficiency of the heart muscle. In addition, studies using iridium-191 require a much lower radiation dose than those that use other isotopes to image the heart. For this reason, iridium-191m is expected to be useful for the evaluation of thousands of infants born each year with congenital heart defects.

The patented generator has been licensed to Scintillation Technologies Corporation of Maryville, Tennessee, which manufactures state-of-the-art gamma cameras that are used to image medical isotopes. The company plans to market the ORNL invention in conjunction with a new "high-speed" camera that can take full advantage of the unique properties of iridium-191m.

Dozens of cancer researchers and physicians in the United States and other countries are now using two monoclonal antibodies developed by biomedical scientists at Lawrence Livermore National Laboratory (LLNL). These two antibodies, called IU-4 and Br-3, are being used to measure the effectiveness of cancer treatment and in basic research to understand the dynamics of tumor growth. The antibodies are produced and sold under a technology transfer licensing agreement with Caltag Laboratories, a California biotechnology company.

This transfer of technology means that commercial quantities of iododeoxyuridine (IU-4) and bromodeoxyuridine (Br-3) can now be produced, something that had previously been impossible. LLNL researchers had previously provided small amounts of the antibodies on request, but LLNL was not set up for large-scale production. Since the antibodies went on the market in April 1990, they have been purchased by cancer researchers and other biomedical researchers at over 25 institutions in the United States, including the medical centers at UCLA, Duke University, and the University of Virginia; the National Institutes of Health; the

■ RADIONUCLIDE GENERATOR FOR HEART STUDIES

Iridium-191m

This photograph shows a prototype of the ORNL-developed iridium-191m generator, which allows bedside injection of the isotope directly into a patient's bloodstream. The iridium-191m is used for evaluating the efficiency of the heart muscle.

■ NEW TOOLS FOR CANCER RESEARCH

Monoclonal Antibodies Measure Tumor Growth

Harvard School of Public Health and the Harvard Medical School; and the M.D. Andersen Cancer Center in Houston. Scientists in Japan, France, West Germany, Sweden, Australia, England, and Canada have also purchased the IU-4 and Br-3 antibodies.

The monoclonal antibodies were developed by a six-person team of LLNL biomedical scientists during the period from 1985 to 1989. While the LLNL-developed antibodies do not specifically detect cancer cells, they do pick out proliferating cells, which are particularly characteristic of tumors. IU-4, the older and more versatile of the two antibodies, has been used for several years in various types of cancer research at the Medical Center, University of California-San-Francisco (UCSF).

The IU-4 and Br-3 antibodies work by fluorescing, or "lighting up," cells that are proliferating. The process starts when a person or a section of a tumor is given IU-4 or Br-3. Cells that are actively dividing will incorporate these chemicals into their DNA. The fluorescently tagged monoclonal antibodies then bind to the incorporated chemical, allowing easy identification of cells that are growing. If the cells are not growing, the chemical does not incorporate into the DNA, and the antibodies do not bind. Researchers are thus able to identify cells or clusters of cells that have the characteristics of tumor growth.

At UCSF, researchers are using the IU-4 antibody to measure the growth of brain tumors, the goal being the development of a more accurate prediction of the spread of these dangerous tumors. The effectiveness of various treatment for eye tumors is also being determined. Studies of breast and bladder cancer are also underway. By measuring the proportion of proliferating cells, scientists can tell whether a tumor is progressing or receding. This helps physicians choose more effective treatments for their patients. In other research not related to cancer, scientists at LLNL have used the IU-4 antibody to determine when cells replicate their DNA, to study chromosome damage due to chemicals and radiation, and to help understand the basic mechanisms of biology and genetics. This technology transfer will undoubtedly make an important contribution to many types of research involving important problems of health care and basic biological science.

Late in 1989, Fermi National Accelerator Laboratory (Fermilab) completed the operational checkout and testing of the first proton accelerator built specifically for the treatment of cancer. After checkout, the new accelerator was disassembled and shipped to California. The proton therapy accelerator was designed and built at Fermilab for the Loma Linda University Medical Center (LLUMC), Loma Linda, California. Science Applications International Corporation, a Fermilab industrial affiliate, was selected to work with LLUMC during the project. This technology transfer was made possible, in part, by a \$19.6 million congressional appropriation administered as a DOE grant. Fermilab also received some assistance for the program from the State of Illinois.

Shipment of the proton therapy accelerator was one of the last important tasks under a 1986 agreement between LLUMC and Fermilab to develop and build the device. LLUMC had a new facility designed and built specifically to house the accelerator and the clinical facilities required for the treatment of patients. Included in these facilities are four treatment rooms—three with gantries to bring the proton beam to the disease site from any desired angle, and one specifically equipped for treatment of tumors in the head and neck.

The new treatment facility at LLUMC has been designed to serve up to 100 patients per 10-hour day, and can treat more patients if a longer shift is used. For some tumors, proton treatment times will be shorter than conventional treatment times. In addition to the technological innovations at the Proton Beam Cancer Treatment Center, LLUMC physicians, working in concert with scientists at Lawrence Berkeley Laboratory and Harvard University/Massachusetts General Hospital, will generate data on the value of proton therapy for disease control.

The intellectual property rights to technologies developed under this project belong to LLUMC.

■ PROTON ACCELERATOR FOR CANCER TREATMENT SHIPPED

**National Laboratory/University
Medical Center/Industrial
Cooperation**

This accelerator was built at Fermilab as a joint project between Fermilab and the Loma Linda University Medical Center (LLUMC). LLUMC was joined in the project by Science Applications International Corporation. The proton beam is injected into a synchrotron from a so-called RFQ (radio-frequency quadrupole). It is then extracted from the accelerator for patient treatment. The first patient was scheduled to be treated at LLUMC in late 1990.

■ IMPROVED TECHNOLOGY FOR AIDS AND LEUKEMIA RESEARCH

High-Speed Electronics Improves Cell Sorter

A chromosome sample is prepared for measurement in a cell sorter developed at LLNL. The new cell sorter's electronics technology will soon be used by SyStemix, a California biotechnology firm, for AIDS and leukemia research.

■ DEVELOPING POWERFUL TRITIDE TECHNIQUE

Organic and Biological Molecule Labeling

Biochemical instrumentation technology developed at the Lawrence Livermore National Laboratory (LLNL) has been transferred to a California biotechnology firm for use in research to combat leukemia and Acquired Immune Deficiency Syndrome (AIDS). LLNL and SyStemix of Palo Alto, California, have concluded an agreement that will permit SyStemix to replicate the electronics of the third-generation, high-speed biological cell sorter. SyStemix plans to combine the LLNL electronic system with laser and optics systems from an existing commercial device to improve cell-sorting and analytical capabilities. With this technology transfer, SyStemix has a vital and previously unavailable methodology that will speed up research on AIDS and bone-marrow transplantation. The present cell sorter is a third-generation device that evolved from machines first designed at LLNL in the mid-1970s.

Current commercial cell sorters permit researchers to study only a limited number of cell properties. However, the LLNL cell sorter allows more than 200 cell properties to be examined at one time. Cell characteristics that might be determined by this automated sorter could include pH, calcium content, and cell size. With its advanced electronics, the LLNL cell sorter can analyze about 50,000 cells or chromosomes per second, which is approximately 5 to 10 times the speed of comparable commercial instrumentation.

When the technology transfer is complete, SyStemix will use the new cell sorter to analyze cells from mice that have been biologically engineered to carry the virus that causes AIDS. This use of LLNL technology in a cell sorter is important because it will permit scientists to explore one of the very few AIDS disease models in existence outside of humans or primates. The research program planned at SyStemix will offer researchers an opportunity to study the entire life cycle of the AIDS virus.

LLNL and SyStemix will both benefit from the licensing agreement. LLNL will gain the services of a software developer to improve the capabilities of its cell sorter, and SyStemix will get the high-speed processing technology that it did not have previously.

Complex hydrides are very important reagents in organic synthesis due to the range of reducing powers and selectivities available from different agents. Unfortunately, the availability of these compounds for radiosynthesis has been extremely limited due to the difficulty of making them with adequate levels of tritium.

Investigators at the Lawrence Berkeley Laboratory (LBL) National Tritium Labeling Facility have developed a new addition

to the repertoire of the tritium-labeling chemist. The new method allows site-specific incorporation of tritium into organic and biological molecules by efficient reduction processes. Exceptionally reactive and selective reducing agents are prepared and used for labeling in a "one-pot" process. Three new tritide reagents—Supertritide (lithium triethyl borotritide), LiAlT_4 (lithium aluminum tritide), and L-Selectride (sterically hindered lithium tri-sec-butyl borotritide)—have been synthesized at carrier-free levels, and have been demonstrated to be fully reactive. The availability of these versatile and reactive reagents gives the tritium radiochemist great control over chemoselectivity and stereoselectivity.

The LBL tritide reagents can drive numerous conventional chemical reactions, and have been used to reduce p-toluene sulphonates, amides, lactones, esters, and aldehydes. These reactions produce good yields and result in products with maximum specific activities. The reagents clearly exhibit superior reactivity and may be used in many more synthetic processes than sodium borohydride, which is the currently used reagent. In addition, tritide reagents such as L-selectride have been shown to give greater control over stereochemistry and selectivity than sodium borohydride.

Scientists expect the new reagents to create a completely new area of tritium labeling with a market size similar to that serviced by the current techniques of tritiation and tritio-dehalogenation.

Preparation of tritiated borane (BT_3) has also been accomplished and been shown to give products of maximum specific activity. Within a year, this reagent could be as routinely available as the other LBL tritide reagents. Many other useful hydride reagents, such as NaBT_3CN and the sodium and potassium analogs of the LBL reagents are expected to be readily produced with similar chemical characteristics.

The tritide project was the result of a collaboration between Sandoz Research Inc. and members of National Tritium Labeling Facility at LBL. LBL has a patent pending on the preparation of selective reducing agents for tritium labeling.

CONTENTS

- 103 ■ USING THERMITE REDUCTION PROCESS FOR
RARE-EARTH/IRON ALLOYS (Ames)
Process Cuts Cost of Materials for Permanent Magnets
- 104 ■ ULTRALIGHT AEROGELS (LLNL)
Silica-Based "Solid Foams" Are the Lightest Known Solids
- 105 ■ A NEW HIGH-TEMPERATURE STRUCTURAL
MATERIAL (LANL)
Molybdenum Disilicide/Silicon Carbide Composites
- 106 ■ DUCTILE IRON ALUMINIDES (ORNL)
High-Temperature Strength and Corrosion Resistance
- 107 ■ MATERIALS PROCESSING BY DESIGN (SNL)
Industry/Laboratory Collaboration
- 108 ■ BIOPROCESS FOR PHOSPHATE SOLUBILIZATION
(INEL)
Economical Recovery and Upgrade
- 109 ■ CONVERTING METHANE TO HIGHER
HYDROCARBONS (PETC)
Multistep, High-Yield Process
- 111 ■ SUPERPLASTIC STEEL (LLNL)
High-Carbon Alloy Enables Easy, Accurate Fabrication
- 112 ■ NEW NONDESTRUCTIVE EVALUATION METHOD
QUANTIFIES CHEMICAL/PHYSICAL PROPERTIES (ANL)
Solid-State NMR Imaging Accessory
- 113 ■ MAKING SILICON-CARBIDE CERAMIC FIBERS (Ames)
Novel Polymer Precursor Shortcuts Existing Process
- 114 ■ SUPERCONDUCTING SUPER COLLIDER DIPOLE
MAGNETS (Fermilab)
New High-Precision Tooling System
- 115 ■ ASSEMBLY TEST CHIPS MEET CRUCIAL NEED IN
SEMICONDUCTOR INDUSTRY (SNL)
Test Chips Monitor Packaging of Semiconductors
- 117 ■ PLASMA AND NEUTRAL SOURCES FOR ETCHING
(PPPL)
The Oxygen Beam Source
- 119 ■ INORGANIC MEMBRANE TECHNOLOGY (ORNL)
Separating Product and Waste Streams
- 120 ■ FULL-SCALE HORIZONTAL CABLE-TRAY TESTS
(Fermilab)
Fire-Propagation Characteristics

Ames Laboratory (Ames) ■ Argonne National Laboratory (ANL) ■ Fermi
National Accelerator Laboratory (Fermilab) ■ Idaho National Engineering
Laboratory (INEL) ■ Lawrence Livermore National Laboratory (LLNL) ■
Los Alamos National Laboratory (LANL) ■ Oak Ridge National Laboratory
(ORNL) ■ Pittsburgh Energy Technology Center (PETC) ■ Princeton
Plasma Physics Laboratory (PPPL) ■ Sandia National Laboratories (SNL)

Materials Science and Manufacturing Processes

Ames Laboratory (Ames) metallurgists have developed a thermite reduction process for making rare-earth/iron alloys. The process provides a faster and more cost-effective way to produce neodymium iron alloys that are used for making super-powerful permanent magnets. These magnets are twice as strong as the commonly used ferrite magnets and account for \$90 million in annual U.S. sales. This sales figure is projected to increase to as much as \$2.5 billion by 1995.

In this process, at least one rare-earth fluoride and ferric fluoride are reduced with calcium in a sealed steel vessel. The addition of ferric fluoride serves as a thermal booster for the reduction process by providing a source of chemical energy that increases the temperature of the reaction. The conventional process, which reduces the rare-earth fluoride with only calcium, does not generate enough heat to separate the calcium from the fluoride slag. However, the ferric fluoride reaction generates sufficient heat to melt both the slag and the metal alloy. Because the heat comes from the chemical reaction, no furnace is needed; therefore, this method requires a much lower capital investment and consumes much less energy than conventional processes.

In addition to its inherent cost advantage, the Ames process also has the unique capability of utilizing lower quality feedstock materials. These materials can even be of certain types of rare-earth scrap or effluent waste that are produced during magnet production. This feature could have a significant additional effect on reducing overall cost of end-use products and could also assist manufacturers in their problems related to environmental control and waste disposal.

By cutting costs, this process will allow U.S. industry to compete with European and Japanese industry, which have dominated the supermagnet market. The process will also reduce U.S. dependence on imported samarium and cobalt, which are needed for permanent magnets.

Basic research work on the thermite reduction process began in 1983 under DOE funding and resulted in a process that could be carried out on a 1-kilogram scale. The project received subsequent support from industry and the U.S. Department of Commerce for additional work needed to scale-up the process. The Iowa State University Center for Advanced Technology Development conducted a market research study and concluded that the thermite reduction process could make an almost immediate entry into the market. The inventors of the technology

■ USING THERMITE REDUCTION PROCESS FOR RARE EARTH/IRON ALLOYS

Process Cuts Cost of Materials for Permanent Magnets

A laboratory technician monitors the hydrofluorination equipment used in the thermite reduction process for preparing rare-earth/iron alloys. This equipment is part of a process developed at Ames for producing neodymium/iron alloys used in super-powerful permanent magnets.

■ ULTRALIGHT AEROGELS

Silica-Based "Solid Foams" Are the Lightest Known Solids

Easily supported by a puff of shaving cream, this piece of aerogel is many times lighter than the soapy foam. The aerogel sample shown here is only two to three times heavier than air, with a density of 4 milligrams per cubic centimeter.

received a 1990 R&D-100 Award and a 1990 Federal Laboratory Consortium Special Award for their exceptional initiative and effort in transferring the process to industry.

Last year, Edge Technologies, Inc., an Ames, Iowa, company specializing in advanced technologies, was issued an exclusive license to produce the material for magnet manufacturers. The addition of this new division complements Edge Technology's ongoing production of a powerful magnetostrictive rare-earth alloy, Terfenol-D, that was also an outgrowth of Ames research.

Aerogels are a class of extremely lightweight, very porous, and chemically inert materials. Silica aerogels, the world's lightest known solids, are virtually transparent, having the appearance of "frozen smoke." They provide high thermal and acoustic insulation along with unique optical properties.

Since 1985, a research team at the Lawrence Livermore National Laboratory (LLNL) has been making aerogels in a very wide range of densities, including one whose density is one-tenth that of the lightest aerogel previously made. LLNL researchers anticipate that with wider availability, aerogels may find application in many products and industries, including insulation, sonic detectors and acoustic delay lines, acoustic and thermal insulation, gas filters, rocket fuel storage media, and even a gossamer net to collect and store cosmic dust in outer space.

Aerogels are water gels dried in such a way that the solid matter in the gel remains intact. The resulting solid has an amorphous (noncrystalline) structure. Samples with as little as 1 to 5 percent solid matter have been made. Abundant nanometer-sized pores throughout the aerogel comprise most of its volume. Silica aerogels can weigh as little as 5 milligrams per cubic centimeter. Although a wide variety of metallic and organic substances can be made into aerogels, the best studied aerogels are those made of pure silica (silicon dioxide). With the chemical composition of sand or pure glass, silica aerogels are inert and innocuous. When broken, aerogels crumble into a sand-like powder rather than shattering into sharp pieces like glass does. Aerogels can be produced in sheets, slabs, bricks, tiles, or pellets, and can be machined, coated, joined, and finished. They can also be molded into complex shapes, doped with chemicals, or colored with pigments during manufacture.

The superlight aerogels produced at LLNL were made with a special technique. The key to their production is an intermediate stage of fabrication that maintains the open structure in the solid phase. The resulting aerogel can be extremely light. Unlike normal solid materials, the atoms in an aerogel are only

weakly connected to each other. As a consequence, aerogels transmit light and sound poorly. Also, because the pores in an aerogel are much smaller than the wavelengths of visible light, an aerogel is almost transparent. The pores do refract light, however, which gives aerogels their characteristic bluish, smoky appearance.

Aerogels with a density as small as 3 milligrams per cubic centimeter have been produced at LLNL. Despite their light weight, these materials can support the weight of an ordinary coin. The University of California, which manages LLNL, has applied for a patent covering the special processes used to make the ultralight silica aerogels. Since the original announcement describing the LLNL work with ultralight aerogels, more than 300 inquiries have been received from companies interested in learning more about these materials and their potential usefulness in a variety of products, including thermal insulation in windows, furnace thermometer mounts, electronics packaging, and special effects for the entertainment industry.

LLNL won an 1990 R&D-100 Award for its ultralight aerogel technology.

A new family of composite materials developed at Los Alamos National Laboratory (LANL) is the most significant innovation in high-temperature structural materials since silicon-based structural ceramics were introduced two decades ago. The LANL materials—molybdenum disilicide/silicon carbide composites (MD/SCC)—will benefit a variety of industries including commercial aircraft and automobile manufacturers and those associated with electric power generation and pollution control.

The MD/SCCs are stronger and more ductile (i.e., capable of changing shape without breaking) than are other available materials at the extreme temperatures of 1,200° to 1,800°C found in industrial furnaces, incinerators, gas turbines, and such automobile components as glow plugs, piston faces, valves, and turbocharger rotors. They are also more resistant to oxidation than are the best commercially available high-temperature metals; consequently, they are far more reliable.

The composites can be used to provide advanced, very high-temperature heating elements with improved temperature capabilities and extended lifetimes for industrial furnace and waste incineration applications. They can also be used to improve the quality of aircraft components—an improvement that will lead to safer and more reliable aircraft. Better high-temperature components, such as seals, vanes, and nozzles, in the gas turbine engines of advanced aircraft would make it possible to increase

■ A NEW HIGH-TEMPERATURE STRUCTURAL MATERIAL

Molybdenum Disilicide/Silicon Carbide Composites

■ DUCTILE IRON ALUMINIDES

High-Temperature Strength and Corrosion Resistance

Specimens of commercially melted ingots of the ductile iron aluminides developed at ORNL.

the turbine inlet temperatures, which ultimately would improve engine performance and fuel efficiency. The MD/SCCs may make such increased temperatures possible in gas turbines and in a variety of other important industrial and environmental applications.

One patent on these materials has been issued, and a second patent has been allowed. The invention is available for licensing. For the development of these composites, LANL won an R&D-100 Award in 1990.

Researchers at Oak Ridge National Laboratory (ORNL) have developed low-cost iron aluminide (Fe₃Al) alloys that are ductile at room temperature. These alloys have excellent high-temperature strength and corrosion-resistance properties. They are designed to be used as a structural material at temperatures ranging from room temperature to 800°C and in both oxidizing and sulfidizing environments.

Previously, one of the major problems with iron aluminides was their low ductility (less than 5 percent) at room temperature. ORNL researchers have dramatically improved room-temperature ductility to 10 to 20 percent by controlling the alloy composition and processing conditions. This advancement allows these alloys to be fabricated by essentially conventional methods into sheet, rod, bar, and other forms.

The ORNL iron aluminide alloys possess excellent corrosion resistance to temperatures as high as 1,000°C. They form a protective aluminum oxide film at high temperatures, and this coating protects the underlying material. The ORNL alloys have also overcome previous problems with low tensile and creep strength at high temperatures, and they retain excellent strength ratings at temperatures above 600°C.

Iron aluminides have a wide range of potential applications, including structural materials such as I-beams, piping and tubing in energy conversion systems, automobile exhaust system parts, molten salt systems for oxygen generation, and in other applications where ferritic steels have traditionally dominated. In some cases, ductile iron aluminides may be used as a low-cost substitute for austenitic stainless steels.

This technology, which won an 1990 R&D-100 Award, is now available for licensing from ORNL.

Materials synthesis techniques employing high temperatures and gas-phase reactants are in use or are being developed by a variety of industries for the rapid production of ceramic components with improved properties and reliability. Examples of these techniques include gas-phase synthesis of ceramic powders, flame formation of submicron silica particles for optical fiber production, diffusion-barrier coating of nuclear fuel particles using fluidized-bed reactors, and chemical-vapor infiltration techniques for production of composites.

Significant problems exist, however, before some of these complex techniques can be applied in full-scale manufacturing situations. Results obtained in small laboratory reactors may not be extendable to larger manufacturing facilities, making the scaleup process difficult and time consuming. The full potential of these processes is often unknown; higher production rates may be attainable than are currently possible; and extension of the technology to new materials may also be feasible.

To provide industry with technical assistance in the optimization of high-temperature materials processes, Sandia National Laboratories (SNL) initiated the Materials Processing by Design (MPBD) Program. Collaborative research with industrial partners, using experimental and computational facilities at the SNL Combustion Research Facility, is structured to bring new materials manufacturing processes on-line more quickly and efficiently.

The large variety of physical and chemical processes that may occur within the high-temperature (sometimes particulate-laden) gas flows used by these new synthesis technologies, and the correspondingly large number of process variables, makes the determination of general reactor design guidelines for a specific process a formidable task. To develop a general understanding of a specific technique, and thus avoid having to optimize individual reactor designs, a two-pronged approach is taken in the MPBD Program. The approach combines sophisticated laboratory experiments using laser diagnostics with powerful computer software packages that simulate the fluid mechanics and chemistry present in complex reactor environments. Coupling these research technologies leads to verified computational models that can guide engineers involved in process development.

The MPBD Program began with a collaboration with AT&T. Researchers from SNL and AT&T performed joint research to develop laser diagnostic techniques applicable to the vapor axial deposition process. This technique for the rapid production of high-purity silica for communications-grade optical fibers uses very hot flames (with temperatures as high as 3,000°K) to form large numbers of submicron silica particles (as many as 100 billion per cubic centimeter). The presence of so many small particles in the laser probe volume presented substantial problems (such as

■ MATERIALS PROCESSING BY DESIGN

Industry/Laboratory Collaboration

intense Mie-scattering from the particles and reduced laser breakdown thresholds) that had to be overcome to obtain meaningful data. The research led to the development of laser diagnostic techniques for measuring gas temperature, particle size, and particle number density. These techniques are now assisting AT&T researchers in the development of new fiber-synthesis processes.

Currently, research in the MPBD Program is focused on understanding and optimizing a process developed by the Thermo Electron Technologies Corporation of Waltham, Massachusetts, for the manufacture of high-strength, high-toughness silicon carbide composites. Production rates are 10 to 20 times higher than those found in standard chemical vapor infiltration techniques. Using a new software package developed at SNL for the simulation of elementary gas-surface reactions, researchers compiled a unique chemical-reaction mechanism for silicon carbide formation that incorporates both gas-phase and surface reactions. The mechanism successfully predicts silicon carbide deposition rates obtained during high-pressure chemical vapor deposition and is currently being applied to the Thermo Electron process for producing composites.

■ BIOPROCESS FOR PHOSPHATE SOLUBILIZATION

Economical Recovery and Upgrade

The demand for phosphate is expected to remain high into the foreseeable future. Because there are no substitutes for phosphate, over 35 million metric tons of ore will have to be processed yearly to meet the expected demand. However, a large fraction of the phosphate ore currently being mined is considered uneconomical to process, and is left at the mine site where it is treated as waste. A large amount of phosphate can be contained in these "waste" ores.

For the first time, low-grade phosphate ore can be economically recovered and upgraded to a usable product. A process developed by Idaho National Engineering Laboratory (INEL) scientists separates insoluble phosphate from phosphate ore body using biocatalysis. FMC Corporation, a phosphate mining corporation located in Pocatello, Idaho, recognized the need for an innovative phosphate separation technique and cosponsored development of this process.

In the bioprocess, microorganisms that have phosphate solubilizing properties aggressively attack the ore matrix resulting in a release of the bound phosphate. This bound phosphate is then solubilized and separated from the unwanted rock matrix.

Existing phosphate separation techniques employ large quantities of energy or concentrated acids. Abiotic tests have shown that partial phosphate solubilization can be achieved using acid and chelators. The bioprocess developed at INEL will not use concentrated acids, and it is expected to consume only moderate

quantities of energy. When the results from abiotic and biotic tests are compared, the bioprocess yields twice as much phosphate as the abiotic process. Therefore, the microorganisms appear to play an even larger role in solubilization than merely increasing acidity and producing active metabolites such as chelators.

Use of the bioprocess could allow the phosphate industry to recover phosphate from the various layers of ores that now cannot be processed by electric furnace or wet acid techniques. This means at least 50 percent more phosphate could be produced from a given mining operation. The bioprocess system could prove to be a worthwhile step to upgrade processing of these ores. This technique can also be applied to other mineral ore matrices that contain recalcitrant trace amounts of phosphate as a contaminant.

The major restraints on the universal use of methane as a fuel are its transportation and storage costs. Methane as a vehicular fuel would require pressurized or cryogenic fuel tanks, and would pose a greater hazard in accidents, equipment failure, and refueling operations. A likely solution to these problems would be to convert the methane to liquid fuels, such as methyl alcohol or gasoline. Liquid fuels are easier to transport, handle, and store, and facilities and procedures for their use are already in place. Methane conversion to gasoline has long been a goal of the fuels industry; however, the many processes developed to achieve this difficult goal have met with little commercial success.

In 1985, researchers at Pittsburgh Energy Technology Center (PETC) discovered a process that has distinct advantages over other processes for the conversion of methane to gasoline in reasonably high yields. The process, for which a patent was granted in 1988, consists of two sequential reactions, each of which is followed by a separation step. In the first stage, the methane is fractionalized; that is, it is converted to intermediate compounds in a controlled fashion. The mixture of intermediate compounds then reacts over a "shape-selective" catalyst to give gasoline and a recyclable byproduct. The intermediate compounds are chlorinated methanes, mainly monochloromethane, that are produced using a catalyst developed by Allied Chemical Company for production of carbon tetrachloride.

The ability of the Allied Chemical catalyst to produce monochloromethane by altering the proportions of the methane-oxygen-hydrogen chloride feed dictated its use in the overall scheme. The most important aspect of the catalyst is that it allows the use of hydrogen chloride in the first stage as the methane-chlorinating agent instead of chlorine. The second-stage catalyst produces hydrogen chloride as a byproduct of gasoline formation.

CONVERTING METHANE TO HIGHER HYDROCARBONS

Multistep, High-Yield Process

Schematic representation of the high-yield, methane-to-gasoline conversion process developed at PETC. This process can be used to upgrade second-stage hydrocarbon products, such as ethane and propane, to gasoline.

An advantage of this process over existing processes is its ability to upgrade low-molecular-weight, second-stage hydrocarbon products (ethane and propane), which are unsuitable for inclusion in liquid fuels, to gasoline by recycling through the first stage with the hydrogen chloride.

Another important aspect of the process is that water, formed in the first stage, is removed before the second-stage reaction. Water allowed to remain in the stream would have several detrimental effects: irreversible damage would be done to the catalyst, and the hydrogen chloride formed in the second stage would dissolve in the water, making hydrogen chloride recovery more difficult and introducing a serious reactor corrosion problem.

This conversion process was originally conceived as an alternative to steam reforming of the methane produced as a by-product in coal conversion reactions. Other applications may also be of importance, such as remote, onsite, gas well conversion, followed by product storage to await bulk transport to a distributor. The relatively mild reaction conditions and the absence of large, expensive reformers make remote fuel conversion installations more feasible.

Current work emphasizes optimization of reaction conditions for both stages, with special attention directed toward the oxyhydrochlorination reaction of the first stage. The Allegheny Power System, a consortium of Monongahela Power Company, the Potomac Edison Company, and West Penn Power Company, has recently expressed a strong interest in the process. The consortium holds extensive coal reserves containing significant amounts of trapped methane. Also, Amoco is interested in investigating other catalyst systems and in testing the process at the pilot-plant scale.

A research team at the Lawrence Livermore National Laboratory (LLNL) has joined with three U.S. industrial firms to develop a commercial production process for a new family of superplastic steels that has the potential for dramatically improving the ability to form complex shapes and reducing the need for machining. The new ultrahigh-carbon steels, which have superplastic-forming properties, flow so freely that this type of metal may be able to perfectly fill a complex die form. The availability of such steels will radically expand the freedom of the industrial designer to produce complex components while reducing the requirements for machining and joining, which typically represent one-third to one-half of the cost of a finished part.

If these new steels can be produced on a high-tonnage commercial basis, the reduction in the need for machining and joining process could make steel produced in the United States more favorably priced, thus regaining lost markets overseas. The principal factor in the ductility of the new steel is its fine grain size (about 2 microns), which is 25 times smaller than the typical 50-micron grain size for the high-carbon steels currently produced. The new steel is very hard because of the high carbon content, but it retains its ductility because temperature-controlled processing breaks up the coarse network of iron carbides that normally contributes to brittleness.

The superplastic steel program is a result of 1985 legislation adopted by Congress that directed the DOE to use the technical strengths of the DOE laboratories to assist the U.S. steel industry. There was concern that domestic manufacturing industries were falling behind in research on process technologies. The aim of the steel research program is to help develop technologies that produce "leapfrog" advances in the production and processing of raw materials and finished parts, while simultaneously reducing energy costs.

The industrial partners participating in this study are interested in results that will improve their production and processing capabilities. North Star Steel Company of Minneapolis wants to develop the capability to continuously cast the high-carbon steel in cross sections as large as 6 inches square. Ladish Company, Inc. of Cudahay, Wisconsin, wants to produce intricate shapes such as precision gears with minimal machining and heat treating. Caterpillar, Inc. of Peoria, Illinois, wants to produce extremely complex shapes of tough, hard steel that can replace large assemblies of parts that are now joined or machined.

■ SUPERPLASTIC STEEL

**High-Carbon Alloy Enables Easy,
Accurate Fabrication**

NEW NONDESTRUCTIVE EVALUATION METHOD QUANTIFIES CHEMICAL/PHYSICAL PROPERTIES

Solid-State NMR Imaging Accessory

The Solid-State NMR Imaging Accessory developed at Ames provides the capability for imaging solid materials by spatially mapping the internal chemical and physical properties of solids. This noninvasive/nondestructive method will be useful for materials research, process development, and fuels research. Basic components of the imaging accessory are the imaging probe, shown in this diagram, an IBM-PC based pulse program, and a versatile image reconstruction software package.

Despite advances in medical applications, the use of nuclear magnetic resonance (NMR) techniques for analyzing solid materials has been hampered by their inherently broad spectral line widths. A new instrument developed by scientists at Argonne National Laboratory (ANL) combines the use of high-gradient fields with spectral line narrowing techniques to overcome this limitation. The new Solid-State NMR Imaging Accessory provides the capability of imaging solid materials with a conventional NMR spectrometer. The instrument provides a noninvasive/nondestructive means of spatially mapping the internal chemical and physical properties of solids for materials research.

The main components of the imaging accessory include a special imaging probe, an IBM-PC-based pulse programmer, and a versatile imaging reconstruction software package. A variety of specialized techniques for solid-state imaging can be implemented conveniently on any existing wide-bore, wide-bandwidth NMR spectrometer. The modular design provides the flexibility to change or upgrade components.

The new imaging accessory will be useful for materials research, process development, and nondestructive evaluation. Although there are other nondestructive techniques, such as those that use ultrasonics and X-rays for physical property evaluation, NMR is the only known technique that provides quantitative chemical information.

Current uses of the system are in imaging and characterizing green-state (presintered) ceramics and nondestructively obtaining the spatial distributions of binders, plasticizers, and other organics in injection-molded and slip-cast ceramics. Other applications vary widely and include imaging of polymeric and bioengineering materials, and fuels research.

Industrial interest is evidenced by collaborative efforts between ANL and several companies that are working on characterizing and improving the process reliability of their ceramic and polymeric products. Patenting of the imaging accessory has been initiated.

Ames Laboratory (Ames) chemists have developed a new process for making silicon-carbide fibers from polymers. This process may provide industry with an alternative to importing these materials from Japan, at the cost of \$300 to \$500 per pound.

A demand exists for these fibers because they can be mixed with ceramic powder to form lightweight composite materials with superior heat resistance and strength. They are also resistant to chemical breakdown. These properties make them well suited for a wide variety of applications in such areas as the aerospace, automobile, medical, and sports equipment industries. Currently, the market demand for composite materials is about \$100 million a year. Market researchers predict that demand for products made of composite materials will reach \$800 million by the year 2000.

Although silicon carbide can be easily and cheaply made from sand and carbon, the only way to make silicon-carbide fibers is from polymers. Until now, only the Japanese have been able to make commercial-grade continuous silicon-carbide fibers from polymers, namely polysilane. Efforts by U.S. industry to reproduce the Japanese process have failed, mainly because of the complexity of transforming polysilane into an intermediate form and then into ceramic fiber. Another problem has been knowing how to keep the main chain of the polymer intact, while heating or subjecting it to other treatments to eliminate unwanted "side groups" and then converting it to a ceramic.

The Ames chemists started with the same monomer materials that the Japanese use, but instead of reacting the monomers with sodium, they reacted them with dilithium acetylene ($\text{LiC}\equiv\text{LiC}$). The yield of the resulting polymer was extremely good, about 90 percent. The polymer could be melted and pulled into a fiber that was extremely fine, on the order of 5 to 20 micrometers. But most important, the Ames researchers found they could take this polymer fiber and heat it directly to high temperatures to make ceramic fiber. This direct step was a significant improvement over the Japanese method, where the polymer needed to go through a polycarbosilane form before a ceramic fiber could be made. The Ames process solved the problem of keeping the main polymer chain intact and also avoided the complex intermediate step of the Japanese method. The only thing researchers needed to do to prepare the Ames polymer fiber for high-temperature heating was to expose it to ultraviolet light to form a protective layer that would keep the fibers together throughout heating.

The basic research for this process received a 1989 Award for Outstanding Scientific Accomplishment from the DOE Basic Energy Sciences-Material Science Division, and the process for making these fibers is being patented. Ames chemists collaborated with staff at the Iowa State University Materials Science and Engineering Department to develop the fiber processing techniques. The Iowa State University Center for Advanced

■ MAKING SILICON-CARBIDE CERAMIC FIBERS

Novel Polymer Precursor Shortcuts Existing Process

Technology Development is funding additional studies and testing to determine optimal processing conditions, which will be major factors in large-scale manufacturing operations.

The properties of these high-performance fibers will give them a competitive advantage over existing metals and ceramics; manufacturers will be able to produce products that are lighter and more durable than basic materials such as steel and aluminum. The flexible, heat-resistant fibers have many uses, such as ceramic-reinforced furnace curtains, wire and cable insulators, heat-resistant clothing, and metal-matrix composites for sports and medical equipment. These silicon-carbide ceramic materials could displace metals in many industrial applications.

■ SUPERCONDUCTING SUPER COLLIDER DIPOLE MAGNETS

New High-Precision Tooling System

The 20 trillion-electron-volt (TeV) Superconducting Super Collider (SSC) represents an important national commitment for research in particle physics. The success of the SSC program hinges on the development and operation of dipole magnets, which are the largest single subsystem of the SSC. The performance demands of the SSC dipole magnets require extreme precision, consistency, and quality in the manufacturing process. Since nearly 10,000 of these 15-meter-long magnets are required, they must be capable of being economically mass-produced. The Fermi National Accelerator Laboratory (Fermilab), working with the Superconducting Super Collider Laboratory (SSCL), has designed and built a tooling system that provides a means of mass-producing superconducting magnets and their components while meeting stringent precision requirements. The initial use of this tooling has been to build special quadrupole magnets for the TEVATRON, which is the 1,000 giga-electron-volt (GeV) Superconducting Collider at Fermilab. The tooling has been adapted to build 15-meter dipole magnets for the SSCL. The cost of building this tooling was shared by Fermilab and the SSCL.

The 20 TeV Superconducting Super Collider (SSC) represents an important national commitment for research in particle physics. Nearly 10,000 dipole magnets will be required in the SSC. Fermilab, working with the Superconducting Super Collider Laboratory, has designed and built a tooling system that provides a means of mass-producing superconducting magnets and their components. Shown in the photograph is a mockup of a tunnel section containing a string of these dipole magnets.

The tooling system is divided into two areas: generic tooling and design-specific tooling. Generic tooling, such as coil-winding machines and large coil-molding presses, can be used to produce essentially any accelerator magnet design. Design-specific tooling fixtures are tailored to a specific magnet design. These fixtures include such devices as coil-winding mandrels and coil-forming molds that match specific geometries of a particular magnet design.

The capital costs associated with the tooling are very significant for the complex generic tooling. The cost for producing design-specific tooling is a fraction of the cost for generic tooling. If design changes are required as a result of developmental advances, the design-specific tooling can be economically and easily changed. In mass production, many sets of design-specific tooling can be applied to a singular generic tooling set. This segregation of design-specific and generic tooling can lead to millions of dollars in savings.

The design-specific tooling uses and improves on laminated tooling techniques developed at Fermilab for the Tevatron accelerator project. Laminated tooling provides a means for obtaining extremely high precision in coil dimensions. Laminated tooling also allows multiple sets of tooling to be made identically, thereby eliminating systematic errors due to tooling variations. The cost for laminated tooling is concentrated in the fabrication of dies to stamp the laminations and lamination assembly. Once the dies are produced, subsequent sets of essentially identical tooling can be produced at low cost.

The Fermilab generic press for molding coils incorporates improvements over earlier Fermilab press designs. To minimize human intervention and, therefore, possible errors in the operation of the press, all press functions are computer controlled.

It is expected that this technology will be used to produce magnets for the SSC, technology transfer program and ultimately to build thousands of superconducting magnets needed for the SSC.

In the semiconductor industry, the packaging of semiconductor chips is as competitively important as the initial design and fabrication of a semiconductor component. Packaging, which takes place after the individual chips are cut from the "wafer" on which they are fabricated, includes mounting the chip on a metal or ceramic substrate, making electrical connections, attaching a covering, and finally encapsulating or sealing the package for protection. During these processes, chips can suffer various kinds of damage, and pinpointing the cause of the damage is extremely difficult.

■ ASSEMBLY TEST CHIPS MEET CRUCIAL NEED IN SEMICONDUCTOR INDUSTRY

Test Chips Monitor Packaging of Semiconductors

Chip producers currently establish new packaging techniques by testing large numbers of costly finished products [random-access memory (RAM) chips, for example], and inferring from these tests what the stresses, temperatures, and corrosion conditions may have been during the packaging processes. As many as 500,000 chips may be used each year for these tests.

Now, a series of increasingly elaborate assembly test chips developed by Sandia National Laboratories (SNL) could provide an alternative to this expensive method of testing, dramatically reducing the number of chips lost to destructive testing methods. These test chips can be used to monitor circuits in the field for possible failure, or to monitor or evaluate the assembly and packaging process itself. They can also reveal the origin of problems even after packaging and assembly have made the microcircuits inaccessible to direct observation.

Developed initially for use by SNL and the DOE, the design of the assembly test chips will be made available to U.S. microelectronics companies for fabrication and use in their own assembly and packaging operations. The assembly test chips are based on state-of-the-art CMOS (complementary metal oxide semiconductor) technology to ensure that they can be fabricated in facilities typically used by semiconductor manufactures. Sample quantities of the chip may also be provided on an as-available basis.

The assembly test chips contain a variety of sensors that can determine whether the assembly and packaging has damaged or degraded the ability of the semiconductor to function properly. Corrosion of aluminum circuit lines, for example, can cause a chip to fail. The first-generation assembly test chip, which is already in use, contains sensors that can detect corrosion, help identify the chemical reactions responsible for the corrosion, and provide information about the rate of corrosion. This chip also has conductor lines around its perimeter that can detect edge and surface damage.

A second-generation chip, now being fabricated, includes a self-heater that helps assess how well the package gets rid of heat generated by its circuits. It also has an integrated moisture sensor to measure unwanted humidity inside the package. The moisture sensor uses a porous anodized region of aluminum oxide as part of a capacitor—the capacitance changes with the amount of moisture present.

The third-generation chip will have 13 different transducers, including arrays of temperature and mechanical-stress sensors; electrostatic-discharge sensors; several fine-line, corrosion-detecting geometries; and monitors to detect cratering in the bond pads that connect the chip electrically to the rest of the circuits.

By focusing on the design of an evolving series of test chips, SNL is trying to move manufacturing technology in a new direction. The largest U.S. microelectronics companies have made and used assembly test chips, but those chips usually had only one or two types of sensors and were used in the development of a single product. Demand for those test chips was too small to justify development and refinement of a multipurpose test chip. Efforts at SNL could encourage wider manufacture and use of assembly test chips.

One of the goals of the developmental work at SNL is to transfer test-chip and sensor technologies to U.S. industry. A consortium of semiconductor manufacturers is teaming with a university in hope of using inexpensive plastic to replace the expensive ceramic packages that hermetically seal microelectronics in military systems. Because plastic packages do not exclude water as well as ceramic packages, the development of acceptable plastic packages would rely on assembly test chips for evaluation.

Plasma ions are the basis of much semiconductor processing, and superthermal atomic oxygen beams are needed to test erosion resistance of materials for use on spacecraft in low earth orbit. For these purposes, the Oxygen Beam Source (OBS) Project at the Princeton Plasma Physics Laboratory (PPPL) has designed and built new plasma (ion) and low-energy neutral-beam (reactive atom) sources that have advantages when compared to other devices. These developments were based on knowledge gained in plasma-surface and radio-frequency heating studies in fusion devices. These new sources should find applications in industrial microfabrication and materials modification.

The method used to produce a low-energy neutral beam of reactive atoms utilizes a metal surface (a neutralizing plate) in contact with a magnetically confined plasma to accelerate and neutralize plasma ions. The neutralizing plate is biased negative with respect to the plasma potential, and the ions are accelerated on the surface, attaining an energy determined by the bias voltage. If the atoms comprising the metal surface of the neutralizing plate are more massive than the incoming ions, the neutralized ions reflect with high efficiency, retaining most of their energy and forming a beam of reactive atoms. This reactive beam can be used to etch or modify surfaces. Wafers or materials to be etched or eroded by reactive atoms are placed in the target position about 10 centimeters from the neutralizing plate.

■ PLASMA AND NEUTRAL SOURCES FOR ETCHING

The Oxygen Beam Source

The Oxygen Beam Source (OBS) developed at PPPL can be used to etch materials for use in semiconductors or to test the erosion resistance of materials. To produce a low-energy neutral beam of reactive atoms, a metal neutralizer plate is contacted with a magnetically confined plasma to accelerate and neutralize plasma ions. This drawing illustrates how reactive atoms produced with the neutralizer plate in place are directed to a sample target. By removing the neutralizer plate and placing the sample (in this case, a wafer) at the opposite end of the plasma chamber, ions, rather than reactive atoms, can be used for etching.

In this apparatus, the magnetically confined coaxial plasma is sustained by radio-frequency energy input in the form of a lower-hybrid wave. A cylindrical tube surrounding the coaxial electrode acts as a cutoff waveguide, preventing the propagation of electromagnetic waves through the plasma. The operating conditions of the plasma source are determined by the magnetic field strength and the radio frequency at which the lower-hybrid waves exist. For etching semiconductor wafers with the lower-hybrid plasma, or ions, the neutralizing plate is removed, and the sample is placed at the far end of the plasma chamber (upstream from the plasma source). The lower-hybrid plasma etcher is within the category of devices known as "upstream etchers" because it separates the wafer from the region of aggressive plasma production, helping to protect it from high-energy electron bombardment.

The OBS device has a number of properties that makes it an attractive alternative to existing plasma etching devices. First, the lower-hybrid source can be used as a remote plasma source located upstream from the wafer. Second, there is nearly independent

control over two key parameters required for ion etching: ion flux and energy. Third, the plasma ions are produced with low energy, the accelerated plasma is highly anisotropic, and the source can be pulsed for use in intense etching without heating of sensitive components. Finally, the plasma can be flared out upstream by shaping the magnetic field and may be steered to aid in providing higher uniformity.

Application of the OBS to the production of semiconductors was demonstrated by anisotropic etching of photoresist. Energetic neutral atoms are selectively reactive with different materials and may have application in microfabrication to eliminate electric charge buildup where deleterious to the surface. Furthermore, little is known at present of the relative merits of neutral etching compared to ion etching for selectivity problems, primarily due to the lack of high-intensity sources of neutrals with beam-like characteristics.

For over 40 years, the DOE and its predecessor Federal agencies have worked to perfect membrane (i.e., barrier) technology to separate isotopes of uranium. In 1990, DOE and Oak Ridge National Laboratory (ORNL) commenced work with industry to commercialize the technology that resulted from that effort. The commercialization program includes design and development of a research laboratory to work with industry in applying the technology to specific chemical-separation processes. The effort is sponsored and funded by the DOE Office of Uranium Enrichment.

Membranes are thin materials with extremely fine pore structures that selectively allow or block passage of fluid (gas or liquid) components, thereby separating mixtures into product and waste streams. Presently, membranes made from organic materials, such as polysulfone, cellulose acetate, and nylon, dominate the commercial market. A number of inorganic (ceramic, glass, and metal) membranes are now being used by industry, but the application of these products has been limited by their relatively high costs, and in many cases, low separation factors.

Membranes are used in such applications as food processing (especially for dairy products), beverage clarification, process gas production (for producing nitrogen, oxygen, argon), biotechnology purifications (for protein, yeast, and other microorganism separations), and other chemical and water-purification processes.

The ORNL membrane technology offers a number of significant advantages over existing technologies. When compared with organic membranes, the DOE inorganic technology (like other inorganic materials) provides a longer operating life (up to 30-fold), and a tolerance of harsh environments (high temperature

■ INORGANIC MEMBRANE TECHNOLOGY

**Separating Product and
Waste Streams**

and corrosive). In comparison with other inorganics, the DOE technology has demonstrated even more remarkable benefits. Based on extensive production experience of membranes for uranium enrichment, researchers have estimated that this technology can reduce production costs by a factor of 4 or more compared with present state-of-the-art inorganics.

Membranes based on this technology are expected to show flux improvements of 5 times or better when compared to other inorganic membranes, while maintaining an excellent separation factor. Flux is a measure of the permeability of the membrane, which determines the volume throughput of a system. The separation factor is a measure of how completely the membrane separates the product and waste process streams. The bottom line is that the technology is expected to compete on a cost basis with low-cost organic membranes in many applications, while offering the desired durability of an inorganic material. The technology is also expected to be applicable in new situations, particularly in harsh environments where large-volume throughput is necessary.

■ FULL-SCALE HORIZONTAL CABLE- TRAY TESTS

Fire-Propagation Characteristics

At the Fermi National Accelerator Center (Fermilab), as at any high-energy physics laboratory, the experimental program depends on complex arrays of equipment that require years to assemble and place in service. These equipment arrays are typically located in enclosed tunnels or experimental halls and could be destroyed by rapidly propagating, uncontrolled fire. Cable trays, both vertical and horizontal, are an integral and ubiquitous component of these installations. Concurrently, throughout industry and within the professional fire-fighting community, there has been concern over the flammability and fire propagation characteristics of electrical cables in open cable trays. While some information was available concerning fire propagation in vertical cable trays, little was known about fires in horizontal cable trays.

In view of the potential for loss of equipment and facilities, not to mention the programmatic impact of a fire, Fermilab initiated a program of full-scale, horizontal cable-tray fire tests to determine the flammability and rate of horizontal fire propagation in cable-tray configurations and cable mixes typical of those existing in underground tunnel enclosures and support buildings at Fermilab. This series of tests addressed the effects of ventilation rates and cable-tray fill, fire-fighting techniques, and the effectiveness and value of automatic sprinklers, smoke detection, and cable-coating fire barriers in detecting, controlling, or extinguishing a cable-tray fire.

A fire-test facility was constructed utilizing 10-foot-long by 12-foot-diameter precast concrete Main Ring enclosure sections set on a concrete slab to form a 65-foot-long tunnel. These enclosure sections were made from spares for the original tunnel sections. Single-, double-, or multiple-stacked 24-foot-long cable trays with various cable quantities and mixes were supported along one wall near the center of the tunnel. A propane burner with a gravel diffuser was placed 6 inches below the cable tray to be burned. Preburn and postburn photographs, video camera recordings from inside the tunnel during each burn, and temperature readings from thermocouples, which were both surface mounted and imbedded in the cable bundles, provided documentation for each test.

These tests clearly indicate that there is a low probability of high-intensity fires with fast flame propagation in horizontal cable-tray installations in underground enclosures at Fermilab. Only certain polyethylene cables supported horizontal flame propagation, and even these did so at an extremely slow rate.

It is important to realize that the results of these tests are indicative of the fire-propagation characteristics of horizontal cable trays only. Other studies have covered vertical cable trays.

Detailed descriptions of each fire test, including sketches of cable-tray configuration and contents, instrumentation, ventilation rates, Fermilab Fire Department personnel observations, photographs, and graphs of thermocouple readings are available in a report of these tests prepared by the Fermilab Safety Section.

CONTENTS

- 123 ■ FIBEROPTIC MOIRE INTERFEROMETRY (INEL)
FMI 1700 System
- 123 ■ NEW TOOL FOR LAW ENFORCEMENT (LANL)
Universal Process for Fingerprint Detection
- 125 ■ MEASURING OPTICAL SURFACE ROUGHNESS (BNL)
Digital Optical Profiler
- 126 ■ SUBDUCTION ZONES AS EXPLORATION TARGETS IN
THE PACIFIC NORTHWEST (METC)
Seismic Reflection Studies
- 127 ■ DESIGN TOOL FOR ENERGY-EFFICIENT BUILDINGS
(LBL)
DOE-2 Computer Program for Analyzing Building Energy Use
- 129 ■ NEW TOOL FOR WASTE MANAGEMENT, FARMING,
AND ENVIRONMENTAL RESEARCH (PNL)
Electro-Optic Liquid Sensor
- 130 ■ COOLING POND PERFORMANCE SOFTWARE
(Fermilab)
POND
- 131 ■ PREDICTING DRAWABILITY OF SHEET METAL (Ames)
Commercial-Grade, Texture-Measuring Instrument Developed
- 133 ■ ANALYZING SURFACE COATINGS "IN SITU" (ANL)
High-Temperature Surface Film Analyzer Developed
- 134 ■ POWER PLANT FUEL BURNER MONITOR (PPPL)
Two-Color Pyrometer
- 135 ■ MEASURING OXIDATION PROCESSES (SLAC)
Atomic Oxygen Flux Monitor
- 136 ■ MONITORING WATER CONTAMINATION (Ames)
Remote Sensing Module
- 137 ■ UNISOR'S NUCLEAR ORIENTATION FACILITY
(ORAU)
The "Fridge"
- 138 ■ A COMPUTER CODE FOR THREE-DIMENSIONAL
TRANSIENT HYDROTHERMAL ANALYSIS (PNL)
TEMPEST
- 140 ■ NEW INSTRUMENT AIDS IN TITANIUM PROCESSING
(INEL)
Noncontacting Ultrasonic Material and Super Alloy Process
Monitor

Ames Laboratory (Ames) ■ Argonne National Laboratory (ANL) ■
Brookhaven National Laboratory (BNL) ■ Fermi National Accelerator
Laboratory (Fermilab) ■ Idaho National Engineering Laboratory
(INEL) ■ Lawrence Berkeley Laboratory (LBL) ■ Los Alamos National
Laboratory (LANL) ■ Morgantown Energy Technology Center (METC) ■
Oak Ridge Associated Universities (ORAU) ■ Pacific Northwest
Laboratory (PNL) ■ Princeton Plasma Physics Laboratory (PPPL) ■
Stanford Linear Accelerator Center (SLAC)

Analysis and Instrumentation

The technique of diffraction moire interferometry, which is used for the study and measurement of distortion, stress, and fracture, has been an important development in material-properties studies during the past decade. However, the traditional diffraction moire apparatus is complex and difficult to set up and operate, which limits the use of the technique to a small number of experienced operators.

The FiberOptic Moire Interferometry (FMI 1700) System, developed at the Idaho National Engineering Laboratory (INEL), is a major advance in this analytical technique. Developed in response to serious failings of the existing diffraction moire apparatus, this new system uses advanced fiber optic components in a compact, portable unit to replace a table full of standard optical devices. The fiber optic components used in the FMI 1700 System are smaller, lighter, and more stable than the discrete components normally used.

The FMI 1700 System eliminates most of the difficulty and tedium of preparing for diffraction moire measurements. This new system produces better data, requires little experience or knowledge of optics, and is convenient to set up, use, and store. Compared to the several hours required for an experienced operator to prepare for measurement using the older system, the new equipment can be set up, aligned, and operating within 20 minutes. The convenience of the FMI 1700 System will greatly increase the use of this important new measurement technique.

A patent has been issued on the FMI 1700 System. The technology, which won a 1990 R&D-100 Award, has been licensed and is being marketed by a company in Pennsylvania.

Law enforcement agencies throughout the world have gained a valuable new tool in the Universal Process for Fingerprint Detection, which was developed at Los Alamos National Laboratory (LANL). The technique, which is simple, inexpensive, and highly sensitive, can be used to detect fingerprints on a large variety of surfaces where conventional methods fail. As a result, investigators can be more effective and thorough in the collection of evidence. A representative of the U.S. Secret Service has called the invention one of the top five developments in the fingerprinting field in the past 100 years. Both the Secret Service and the Federal Bureau of Investigation have already identified several sus-

■ FIBEROPTIC MOIRE INTERFEROMETRY

FMI 1700 System

This internal view of the FiberOptic Moire Interferometer (FMI 1700) System, which was developed at INEL, reveals some of the optical components of the system.

■ NEW TOOL FOR LAW ENFORCEMENT

Universal Process for Fingerprint Detection

pects—and in at least one case obtained a conviction—by applying the technique to evidence on which other methods had failed to detect fingerprints.

In this sensitive chemical process, fingerprints become visible when gold particles adhere to the proteins in secretions left on an object by the touch of a finger. The object to be examined is first washed for about 30 minutes in a colloidal suspension containing a buffer solution of citric acid and minute gold particles. During that incubation period, the gold binds to the protein in the latent prints. A rinse in distilled water removes any unbound particles, and the object is then bathed in a silver solution. The silver enhances the image by filling in around the gold and highlighting the fingerprint features, producing a permanent, well-defined print. The color of the object does not affect the process—prints developed on a dark surface appear light; prints developed on a light surface appear dark.

The technique can be used to bring up visible prints on porous and nonporous surfaces such as wet or dry paper; metals; glass and ceramics; smooth, rough, soft, and hard plastics; and either the smooth or the adhesive side of all tapes. It has been tested successfully on such objects as computer floppy disks, credit cards, and bullet cartridges. Currency, however, is among the few objects the method cannot be used on because genuine bills contain a large amount of protein-bearing flax and cotton.

The process reveals palm and footprints as well as fingerprints. In fact, the first arrest of a criminal suspect resulting from the use of the Universal Process came after palm prints were developed on a blank government check that had been stolen from a military facility in Pennsylvania.

The Universal Process is so sensitive—it can detect less than a trillionth of a gram of protein—that it can develop faint prints that defy conventional methods. It can be used successfully even after other fingerprinting substances, such as sprays or glues, have been applied to a surface, and it generates no toxic vapors as those substances do. Unlike other methods, it requires no expensive readout instrumentation.

Components of the process also promise to be useful in molecular biology. For example, the extreme sensitivity of the technique may facilitate the staining of protein bands obtained by electrophoresis, which is the migration of molecules in a solution under the influence of an electric current. Thus, the Universal Process may become a tool for researchers trying to identify the protein gene products responsible for the expression of genetic diseases such as Huntington's chorea and cystic fibrosis.

The Universal Process won a 1990 R&D-100 Award. LANL has applied for a patent on the invention, and the transfer of the technology to private industry is currently underway.

Mirrors used to reflect and focus X-rays produced by high-brightness synchrotron-radiation sources, such as the National Synchrotron Light Source (NSLS) at Brookhaven National Laboratory (BNL), need to be made with extremely smooth surface finishes and with very precise overall shapes in order not to degrade the quality of the source. The fabrication problem is compounded by the fact that most of these mirrors are in the shape of segments of cylinders, toroids, and ellipsoids, which are used at extreme grazing incidence angles to reflect X-rays. When the NSLS became operational in the mid-1980s, researchers found that they were prevented from reaching the theoretical resolution of their optical systems by the poor quality of their optics—mirror surfaces were either too rough or they were figured poorly, resulting in large amounts of scattered X-rays at short wavelengths or poor image quality in the focal spot. Workers at BNL quickly realized that manufacturers were having difficulty making grazing-incidence aspheric optics because the metrology instrumentation used to measure conventional sphericity was totally inadequate to characterize aspheric optics.

A program was established to develop measurement techniques and instrumentation better suited for characterizing the figure and finish of X-ray mirror surfaces. A recently developed commercial microinterferometer system was adapted to measure the small-scale roughness on smooth surfaces with a precision and accuracy of better than 1 angstrom RMS. A collaborative effort with a researcher from the U.S. Army Research, Development, and Engineering Center resulted in the development of a surface profile analysis code and a method to specify roughness in terms of the average power spectral density function of the surface. Manufacturers have been able to significantly improve the finish quality of their mirrors based on the feedback provided to them by the BNL workers, and synchrotron-radiation researchers now have a meaningful way to specify the desired properties of their surfaces. An International Standards Organization drawing standard is now in preparation for the specification of optical surface finish based upon the analytical technique developed at BNL. Work continues in the BNL Optical Metrology Laboratory on the development of a long trace-profiling instrument to measure the figure of cylindrical aspheric surfaces up to 1 meter in length. This kind of measurement cannot currently be made with commercially available measuring instruments.

This technology transfer effort received a 1989 Federal Laboratory Consortium Award.

■ MEASURING OPTICAL SURFACE ROUGHNESS Digital Optical Profiler

■ SUBDUCTION ZONES AS EXPLORATION TARGETS IN THE PACIFIC NORTHWEST

Seismic Reflection Studies

A series of seismic surveys indicates the presence of a fossil subduction zone in the Pacific Northwest. Geophysical Systems Corporation of Pasadena, California, is performing these seismic surveys under contract with the Morgantown Energy Technology Center (METC).

Geologists say that subduction zones are good potential sources of natural gas. Central to all current research on subduction zones is the hypothesis that natural gas is generated in sediments carried to great depths, providing a deep gas source that may migrate upward to shallower, drillable traps through deep fracture systems. Subduction zones can be active (modern) or inactive (fossil).

Assessment of Deep Gas Potential from Subducted Sediments

This diagram shows the general geology of the area covered by the seismic reflection surveys conducted by Geophysical Systems Corporation and METC in western Washington State. The geological features of interest are the fossil subduction zone and the early Eocene-Paleocene marine sediments within the Morton Anticline.

Subduction zones are created through plate tectonics: a heavy oceanic crust is forced beneath a lighter continental crust when the two crustal plates converge. Ocean sediments containing organic matter are frequently carried into subduction zones through processes now under study by scientists. Thick accumulations of deeply emplaced sediments are thought to be the result of collisions between extra thick oceanic crust and the continental margin. This process forces sediments deeply into the crust of the earth and terminates further subduction at that location. A new subduction zone eventually forms on the seaward margin of the now inactive zone.

Seismic reflection studies help reveal the subsurface structure of the earth by measuring the time interval for a series of vibrations to bounce off a rock unit and be reflected back to recording stations. Different rock units have different densities and thus sound waves pass through them at different rates.

Seismic data have been acquired in six surveys totaling 247 linear kilometers (154 miles) in Washington State, from the Chehalis Basin on the west to the east flank of the Cascade Range near Mt. Rainier. Multiple vibrator sources and a 1,024-channel, sign-bit recording system were used to obtain data on penetration through variable thicknesses of volcanic rocks.

The seismic data indicate the presence of a prominent eastward-dipping reflector. This reflector has been interpreted as the top of the trapped oceanic crust of a fossil subduction zone at the base of early Eocene-Paleocene marine sedimentary rocks. The subduction zone appears to be as much as 10 kilometers thick, offering a rich potential source of natural gas.

The Morton Anticline (really an anticlinorium or group of anticlines) is a prominent structural feature along the route of the seismic surveys. Geologists also postulate that the Morton Anticline, which overlies the fossil subduction zone, may have the potential to trap hydrocarbons in the marine sediments.

Field work is underway to establish the reservoir rock quality and the degree of structural closure in the vicinity of the Morton Anticline. Two of the six deep seismic surveys have recently been completed and will extend interpretation of these features northward. This work could lead to new estimates of natural gas reserves in this unconventional resource.

DOE-2 is a comprehensive computer program for simulating energy use in buildings. Developed and supported by Lawrence Berkeley Laboratory (LBL), DOE-2 is now used throughout the United States and in 36 other countries.

Given information on a building's location, construction, operation, and heating/cooling systems, DOE-2 does an hour-by-hour calculation of annual thermal performance. The Building Description Language used in the program allows users to easily describe buildings ranging from simple houses to complex, multi-story office buildings. Output reports show hourly, monthly, and annual calculation results for energy use, energy cost, and level of thermal comfort in the building.

The program is used by architecture/engineering firms, corporate design departments, and government agencies for the

■ DESIGN TOOL FOR ENERGY-EFFICIENT BUILDINGS

DOE-2 Computer Program for Analyzing Building Energy Use

The DOE-2 building energy analysis computer program developed by LBL was used to design energy-efficient heating and cooling systems for the One Magnificent Mile in Chicago. In that project, waste heat from commercial spaces is reclaimed to offset the heating demand of perimeter offices.

design of energy-efficient buildings; by equipment manufacturers and industrial organizations (such as the Gas Research Institute and the Electric Power Research Institute) for impact analysis of new heating, cooling, and lighting technologies; by utilities as a key element in demand-side management programs to encourage conservation as an alternative to building new power plants; by the DOE laboratories for building-science research; and by more than 60 universities for research and teaching. Numerous guides used by architects/engineers for energy-efficient design have been developed with DOE-2, including the *Small Commercial Building Design Handbook* and the *Skylight Design Handbook*.

DOE-2 is the basis of new national building-energy-efficiency standards (ASHRAE-90.1 and 90.2) that are mandatory for Federal buildings and are expected to be adopted by most states for non-Federal buildings. This standard is based on thousands of DOE-2 analyses for different building types and climates. The direct use of DOE-2 and the standards developed from it lead to buildings that use 20 to 40 percent less energy than traditional designs, which translates into significant societal benefits, including energy cost savings and reduction in atmospheric pollutants from burning fossil fuels.

DOE-2 is distributed by the National Energy Software Center and the National Technical Information Center. It is available for a wide range of computers, including mainframes, engineering workstations, and personal computers. Documentation includes user's manuals, a sample run book showing input and output for different building configurations, and an engineers manual that describes the scientific basis of the program. The *DOE-2 User News*, published quarterly by LBL, contains articles on the effective use of the program, answers to commonly asked questions, and a directory of DOE-2 related software and analysis services available from the private sector. The developers give an annual 3-day course on the use of DOE-2 through the University of California Extension Service.

LBL maintains an active research effort to add new features to the program in response to industry needs. LBL is also involved in continuing efforts to improve the program and to provide user assistance. The latest version of the program, DOE-2.1D, was released in 1989; among its new features is the ability to simulate the latest gas-fired cooling technologies, including engine-driven chillers, direct-fired absorption chillers, and desiccant cooling systems. Future work on DOE-2 includes development of an interactive, component-based simulation that will allow users to easily model advanced heating and cooling systems.

In 1989, the developers of DOE-2 received a Federal Laboratory Consortium Award for excellence in technology transfer.

A small, inexpensive device that detects and measures liquid present in soil, sand, cement, or other porous materials can help protect the groundwater used for drinking and irrigation by enabling environmental researchers and managers of waste storage sites to detect the onset of underground leaks or monitor the severity of existing spills, leaks, and the progress of remediation measures. Data provided by the electro-optic liquid sensor developed at Pacific Northwest Laboratory (PNL) can also help farmers optimize the application of irrigation water to crops.

■ NEW TOOL FOR WASTE MANAGEMENT, FARMING, AND ENVIRONMENTAL RESEARCH

Electro-optic Liquid Sensor

The electro-optic sensor technology developed at PNL can be used to detect leaks of liquid hazardous waste materials or other organic liquids that could pollute groundwater.

The electro-optic sensor has two functions: it can serve as a meter of water content or as a leak detector for fuel oil, gasoline, solvents, or other organic liquids. The device consists of an optical disk containing an infrared or light-emitting diode and an appropriate detector, joined to a porous disk made of ceramic, fritted glass, Teflon, or various carbon-based materials. When the sensor is buried in the ground or embedded in a porous material such as concrete, the disk absorbs liquid by capillary action.

The PNL electro-optic liquid sensor consists of an optical switch containing a solid-state, light-emitting device joined to a porous disk made of a ceramic material, fritted glass, Teflon, or various carbon-based materials. By detecting and measuring liquid present in soil, this technology could help farmers determine when to irrigate and how much water needs to be applied to crops.

The amount of light passing from the light-emitting diode through the disk to a light detection cell increases in proportion to the amount of liquid held in the pores of the disk. The capillary pressure of the liquid that enters the disk also equals the capillary pressure of the liquid in the porous material surrounding the sensor. For this reason, the electrical signal generated by the sensor can be calibrated to detect not only the presence of a liquid phase, but also the amount of liquid.

Insulated copper leads run from the sensor to the surface of the ground, so measurements can be taken with a standard ohmmeter or voltmeter while the disk remains in place. Sensors could be connected to a data logger or radio transmission system with output to a central collection point.

The electro-optic liquid sensor costs less, lasts longer, and is more accurate than gypsum blocks traditionally used to measure soil water content for agricultural purposes. The PNL sensor is also simpler and less expensive than comparable technologies. Furthermore, no commercially available in-situ sensor can detect immiscible organic liquids in unsaturated ground between the soil surface and the aquifer. By detecting organics in the liquid phase, the PNL sensor can help identify long-term sources of groundwater pollution that must be located and monitored to ensure that remediation has been complete.

The PNL sensor is currently being used by researchers studying the migration of organic fluids in the subsurface environment and developing methods to reduce or remediate the ecological effects. The new technology will also be used in a space science project currently scheduled for early 1991. Researchers will use electro-optic liquid sensors to monitor the rise of liquid up a capillary wick and determine how far the flow is driven past a particular material. The information will be used to design improved heat rejection radiators for satellites and for other space applications.

The electro-optic sensor is available at PNL for licensing by the commercial sector.

■ COOLING POND PERFORMANCE SOFTWARE POND

Cooling ponds are widely used as a means of disposing of excess heat from industrial processes and building air conditioning. In many cases, the use of a cooling pond is a more aesthetically pleasing and environmentally benign approach to waste heat disposal than using massive cooling towers.

An analytical tool, which was initially developed at the Fermi National Accelerator Laboratory (Fermilab) as a manual to guide engineering calculations and now exists as computer software.

brings cooling pond design and performance analysis to a new level of sophistication. Using these tools, cooling ponds can be designed and managed under strategies that take into account daily and seasonal weather variations while conserving energy.

POND is a menu-driven, LOTUS 1-2-3 template for the evaluation and design of cooling ponds, pools, and hydrothermal heat sources. The POND package consists of an instruction/documentation manual and magnetic disk media that contains the software. In order to run POND, the user must already have LOTUS 1-2-3 loaded.

POND contains over 2,000 interactive engineering formulae used in generating four types of thermal performance analyses for ponds or pools: 1) a Daily Equilibrium Performance Profile, which calculates hour-by-hour performance at equilibrium under user-defined conditions; 2) a Daily Dynamic Performance Profile, which calculates hour-by-hour performance under user-defined conditions beginning from a user-defined initial state; 3) Annual Mean Performance Profiles, which are 12 monthly, "typical day," hour-by-hour performance profiles calculated under user-defined conditions; and 4) Annual Extreme Performance Profiles, which are 12 monthly, "typical day," hour-by-hour performance profiles calculated under exact values for user-defined conditions.

POND allows the user to input the following variables: monthly hour-by-hour patterns of heat flow to or from the pond or pool; the temperature differential associated with variable flow pumping, or the flow rate associated with constant flow pumping; submerged depth of the effluent; distance between inlet and outlet; average width and depth of the flow area; total surface area; and relevant environmental conditions such as wind-speed patterns, outdoor air temperature and humidity, percent cloud cover, and the latitude and hemisphere of the pond location.

Typical processing times for computers using 286-chip technology range from less than a minute for simple dynamic pond profiles to about 15 minutes for annual profiles (these may involve 250,000 mathematical solutions). POND is expected to be useful to engineering professionals associated with small and medium-size firms that design or operate cooling ponds, pools, or hydrothermal heat sources.

Ames Laboratory (Ames) basic research on how to measure the texture of materials has led to the development of an instrument that could result in significant savings for the sheet metal industry. Industry needs to know the texture (i.e., the preferred grain orientation) of a material in order to predict how successfully a flat sheet of metal can be formed into complex shapes

■ PREDICTING DRAWABILITY OF SHEET METAL

**Commercial-Grade, Texture-
Measuring Instrument Developed**

Ultraform, a menu-driven, automated instrument that was developed at Ames, measures the texture of materials. The texture of a material determines its formability, which is an important consideration in the sheet metal industry. Its ease of operation, non-destructive nature, speed, and versatility make Ultraform a practical tool for industrial use.

without tearing, wrinkling, or buckling. Beverage cans, automobile oil pans and door panels, and aircraft components are all formed by such "deep drawing" processes.

Current methods of analyzing material texture are time consuming, require periodic sampling that is destructive to the material, and cannot be done on-line during production. It is estimated that the beverage-can industry loses about \$40 million a year due to lack of texture control.

The Ames-developed instrument, called Ultraform, overcomes the limitations of existing techniques by providing a nondestructive method that will allow industry to immediately change or correct production processes. Ironically, the basic research work that led to the development of the instrument was focused on studying stress, not texture. Ames researchers developed a theory for the relationship between stress and anisotropy of ultrasonic wave velocities, and then built a device to test their theories. The researchers realized, however, that in order to measure stress, they had to learn how to suppress the effects of an interfering source of wave speed anisotropies (i.e., the texture) so they could, in effect, eliminate it. The knowledge they gained about the effects of texture on wave speeds was applicable to the needs of the sheet metal-forming industry and led to the development of the instrument.

When Ultraform is in use, three sets of electromagnetic transducers (probes) are positioned on the material. Each set of probes contains radio frequency coils and magnets that allow the probe to generate an ultrasonic wave in the sheet. The three probes measure how fast this wave propagates at 0, 45, and 90 degrees with respect to the rolling directions in the sheet; the texture is determined from this information. The formability parameters (i.e., how well the material can be formed into different shapes without tearing) are then deduced.

The Iowa State University Center for Nondestructive Evaluation recognized the potential for such a device and developed a "breadboard" instrument to test and evaluate both the arrangement of components and a technique for making automatic measurements. The Center for Advanced Technology Development at Iowa State conducted preliminary market studies of steel and aluminum manufacturers and end users. Those studies revealed the existence of significant interest in the development of the technology, so work on a prototype began. The design of the digital components and computer software development was a team effort between the Center for Nondestructive Evaluation and the Laboratory Engineering Services group at Ames, with Magnasonics Inc. of Albuquerque, New Mexico, supplying customized parts for the analog ultrasonics subsystem of the device.

Simultaneous to the development of the hardware and software for a field instrument, the National Institute of Standards and Technology (NIST), through their office of nondestructive evaluation, initiated a collaborative research effort with Ames to further explore how well these texture measurement techniques could be used to predict properties in a range of applications. This work is continuing and has played an important role in defining practical configurations.

Ultraform is now being field tested at several sites. One company has already expressed interest in licensing this instrument as one of a series of nondestructive evaluation products.

Scientists at Argonne National Laboratory (ANL) have devised a new instrument that can analyze surface coatings under operating conditions. The High-Temperature Surface Film Analyzer is the first such instrument to analyze the molecular composition and structure of surface coatings on metals and solids under conditions of high temperature and pressure in liquid environments. Corrosion layers, oxide coatings, polymers or paint films, or adsorbed molecules are examples of conditions that can be analyzed using this instrument. Film thicknesses may vary from a few molecular layers to several microns or thicker.

The process involves shining a laser beam (one wavelength) on a surface film and analyzing the resultant light, which consists of several wavelengths due to interaction with the sample. Analysis of the outgoing beam is then related to the molecular and phase composition of the surface film. The occurrence of characteristic and unique vibrational motions of atoms in the sample is reflected in the wavelengths of the outgoing beam, which constitute a "fingerprint" of the material. The diameter of the probing laser beam can be made as small as several microns so that variation in local surface composition of the sample can be determined.

The instrument was originally developed to study metal corrosion in aqueous solutions similar to the cooling water systems of light-water nuclear reactors. The instrument may have use for the nuclear power industry where coolant pipes degrade due to stress corrosion cracking, which often leads to plant shutdown. Key determinants in the occurrence of stress corrosion cracking are the properties and composition of corrosion scales that form inside pipes. The High-Temperature Surface Analyzer can analyze these coatings under laboratory conditions that simulate the same hostile environment of high temperature, pressure, and solution that exist during plant operations. The ability to analyze these scales in hostile liquid environments is unique to the instrument.

■ ANALYZING SURFACE COATINGS "IN SITU"

High-Temperature Surface Film Analyzer Developed

The High-Temperature Surface Film Analyzer developed by researchers at ANL can analyze surface coatings under actual operating conditions. In this photograph, researchers are looking at the analyzer cell that holds the sample and solution. The sample is analyzed by shining a laser through sapphire windows in the cell, which has previously been heated to 500°C under high pressure.

■ POWER PLANT FUEL BURNER MONITOR

Two-Color Pyrometer

Schematic of the two-color, boiler-imaging pyrometer system developed at PPPL.

Other applications include analyzing paint composition, corrosion of materials in geothermal power systems, integrity of canisters for radioactive waste storage, corrosion inhibitor films on piping and drilling systems, and surface scales on condenser tubes in industrial hot water heat exchangers. The device is not patented.

Currently, power plants monitor fuel burners with black-and-white television cameras. These cameras have a logarithmic response that compresses the dynamic range of the actual optical image. This compression results in a television picture on the monitor that shows only small brightness differences when, in actuality, there are large differences in the radiated light from the flame.

A two-color imaging pyrometer that provides nearly real-time thermal imaging is under development at the Princeton Plasma Physics Laboratory (PPPL) to serve as a research tool to study burning inside boilers. The final goal of such an instrument will be to identify and quantify thermal gradients, to provide tem-

perature trending information, and to simplify operator decisions, and thereby improve the performance of fossil fuel power plants.

The PPPL system uses a telescope that contains a remotely-controlled iris, so light received by the camera can be adjusted to below the saturation point and well above the readout noise. The light is separated by a beam splitter and passes through two different narrow-band filters before it is converted into a television video signal by two charge-coupled-device (CCD) cameras. The video signals are then transmitted to a remotely located dedicated computer.

The computer receives the signals and processes the raw data to obtain the ratio of intensity of any point in the optical image at the two selected optical wavelengths. Each image is composed of approximately 250,000 picture elements. The ratio is then compared to the ratio of intensity of blackbodies at the same wavelengths to determine the temperature of the burner flame. The processed image is converted to eight bands of colors and displayed on a color monitor as a thermal image where each color represents approximately a 200°F change. A typical operating range for this instrument is between 2,000° and 4,000°F. A new thermal image is then processed and displayed approximately every 10 seconds. The images can be recorded on videotape and selectively recorded on the hard disk of the computer. More quantitative results can be obtained by freezing an image of interest, then plotting temperature on the rows and columns of interest.

This work was supported by the Public Service Electric and Gas Company of New Jersey.

Of the existing 95 high-energy accelerators in the world, the Stanford Linear Collider (SLC) at the Stanford Linear Accelerator Center (SLAC) is the only one of the linear-collider type, where electrons and positrons are smashed together at energies of 50 GeV using linear beams instead of beam rings for achieving interactions. Use of a collider eliminates energy losses in the form of X-rays due to the curved trajectory of the rings, a phenomena known as "bremsstrahlung." Because these losses are eliminated, higher interaction energies are reached. Consequently the SLC produced the first Z particle in quantities large enough to allow measurement of its physical properties with some accuracy.

SLAC intends to probe still deeper into the structure of matter by next polarizing the electrons in the beam. The surface of the source for these polarized particles, typically gallium arsenide, must be kept clean of contaminants. One method for accomplishing this task requires the oxidation of the surface, from which the

■ MEASURING OXIDATION PROCESSES

Atomic Oxygen Flux Monitor

oxidized contaminants are later boiled off. The technique requires careful measurement of the oxidation process.

SLAC researchers have developed a technique for measuring the atomic oxygen flux in this process. The method uses a silver film on a quartz-crystal, deposition-rate monitor. Measuring the initial oxidation rate of the silver, which is proportional to the atomic oxygen flux, determines a lower limit on that flux in the range of 10^{13} to 10^{17} atoms per square centimeter per second. Furthermore, the deposition is reversible by exposing the sensor to atomic hydrogen.

This technique has wider applications to processes in solid-state and surface physics as well as surface chemistry. In semiconductor manufacturing where a precise thickness of oxide must be deposited, this technique could be used to monitor the critical flux of atomic oxygen in the process. Also, preparation of the recently discovered high-temperature superconductors, such as YBaCuO, can benefit by employing the technique in the "in situ" growth of the films in reactive electron-beam, coevaporation deposition chambers. This technique, which was developed for the DOE Office of High Energy and Nuclear Physics, is available from SLAC for applications in other fields.

■ MONITORING WATER CONTAMINATION

Remote-Sensing Module

Ames Laboratory (Ames) chemists have developed a portable pH-measuring device that detects hydrogen ions 10 times faster than most other systems. Based on solid-state components that measure changes in an optical sensor, the device incorporates the use of fiber optics, which makes it useful for remote applications. These features give the Ames instrument significant advantages in environmental and biomedical applications. It is especially well suited for testing water quality, studying acid rain, and monitoring illegal discharges of wastes.

The optical sensor consists of a transparent base (glass or fiber optic) that is coated with a polymer film to which a dye has been affixed. When the sensor is immersed in a sample, the dye changes color in response to pH changes. Visible light from a spectrometer is passed through the sensor to measure the intensity of the color change, which gives a quantitative measure of the hydrogen ion concentration.

Although scientists have been developing optical sensors for about 10 years, the response time of most systems is still somewhat slow (from several seconds to 10 minutes). Through basic research studies, Ames scientists developed a polymer and dye combination that gave an extremely fast response time—on the order of a few seconds. By attaching the polymer/dye to the end

of fiber optics, they created a sensor that could also be used for remote analyses.

With support from the Iowa State University Center for Advanced Technology Development, work began on designing the instrumentation for a prototype device. The optical components are interfaced with a computer data acquisition system and a radio transmitter that sends data from the remote sensor in the field to a central receiving station. The design also eliminates the need for periodic recalibration so the device can be left unattended in the field. The central receiving station is capable of collecting data from multiple sensor units simultaneously. This capability will allow the device to distinguish between point-source and nonpoint-source contamination; for example, illegal discharges versus pollution from rain or groundwater runoff.

A patent application has been filed for the sensor, and Ames researchers are continuing their work in this area by creating new sensor films that will measure broader pH ranges and also other types of ions. The fast response time of the sensor also makes it a promising analytical device for various industrial processes, where acidity affects the quality of feedstocks, and in clinical work, where the pH of blood may indicate the presence of certain gases.

This pH sensor, which was developed at Ames, responds 10 times faster than most other sensors. The analytical device that was designed around this sensor fills an important need for instrumentation that can provide on-line monitoring of water contamination.

Final tests of a new nuclear orientation facility, known as the "Fridge," have proven even more successful than expected at the University Isotope Separator at Oak Ridge (UNISOR). As a result of recent design modifications, the Fridge has reached temperatures as low as 4.4 milli-Kelvin.

UNISOR is a consortium of 11 universities, Oak Ridge Associated Universities, Oak Ridge National Laboratory, and the State of Tennessee. One of the first scientific user facilities of its kind in the Nation, UNISOR carries out fundamental investigations into the structures and decay mechanisms of rare, short-lived atomic nuclei.

The Fridge facility is made up of three sections: 1) an isotope separator and beam line, 2) a helium dilution refrigerator, and 3) a detector and data acquisition system. During experiments, a beam from the isotope separator embeds unstable nuclei in a cold metal foil inside the Fridge, where they are cooled to just above absolute zero and aligned in a magnetic field.

■ UNISOR'S NUCLEAR ORIENTATION FACILITY

The "Fridge"

Once the nuclei are aligned, the radiation released as decay occurs can be measured from three different angles with as many as eight detectors. This range of measurement abilities, combined with the exceptionally low on-line temperatures reached by the Fridge, makes the facility unique in the field of nuclear structure research and allows UNISOR researchers to make highly accurate measurements not possible with other systems.

The latest modifications made to the Fridge allow the beam line to run continuously, so nuclei can be implanted and measurements taken simultaneously. This allows researchers to study nuclei with much shorter half-lives and to test models of nuclear structure in new and improved ways.

On-line experiments began with an examination of the structure of gold-184, a short-lived isotope of gold. While results of those tests are still being analyzed, UNISOR researchers have moved into a "production mode" in order to conduct a number of tests of nuclear models.

■ A COMPUTER CODE FOR THREE- DIMENSIONAL TRANSIENT HYDROTHERMAL ANALYSIS TEMPEST

Computer graphics that visualize processes inside an ordinary teapot may be the key to solving complex problems, such as accurately mapping air and fluid movement inside buildings, geologic formations, and even the human body. Researchers at Pacific Northwest Laboratory (PNL) have merged a computer code used in the nuclear industry, a teapot, and three-dimensional, stereo computer graphics to illustrate temperature change and fluid flow as water is heated inside a closed environment.

The TEMPEST code is the result of 12 years of research and application that was initially funded through the DOE Division of Reactor Technology. TEMPEST stands for Transient Energy Momentum and Pressure Equations Solution in Three Dimensions. The code was designed to provide data about fluid movement within the cooling system of a nuclear reactor. However, TEMPEST is versatile; its many useful features support a broad range of applications by enabling users to select the modeling capabilities that meet specific analysis requirements. This versatility accommodates extensive engineering applications and concept analyses.

The computer program parameters are selected by the operator; thus, the code can be adapted for maximum analysis efficiency. Options include hydrodynamics, heat and mass transfer, or hydrodynamics coupled with heat transfer or with viscous or nonviscous flow and steady-state heat transfer. In addition, TEMPEST offers automatically controlled time-stepping for numerical stability and maximum computational efficiency. The operator can select computation in English Units or Standard International Units. The operator also controls printout options to print coordinate planes and inspect selected data, to monitor a specific region or cell and focus on areas of interest, or to receive input and intermediate problem-solving information.

The graphics technology for TEMPEST was unveiled at the Association for Computing Machinery SIGGRAPH '89 conference in Boston. From more than 325 submissions, the technique was one of about 40 entries selected for showing at the conference, where it was viewed by more than 20,000 attendees. The teapot has traditionally been used by the computer graphics industry to test graphics techniques. However, its use with TEMPEST illustrated the ability to simulate basic fluid movements and temperatures accurately in a commonly understood geometric shape.

Computational hydrothermal analysis is an invaluable tool for the nuclear, waste-processing, and chemical-processing industries and for environmental and medical studies. The technique

The TEMPEST computer code, which was developed at PNL, enables the graphic computer representation of water movement and temperature changes inside a container, such as this ordinary teapot, a building, or a geologic formation. The small particles and contorted lines in this graphic are used to trace water as it moves throughout the teapot. The warped plane at the top of the kettle shows temperature variations. A unique combination of code features and analysis capabilities makes TEMPEST a valuable tool for many engineering problems.

could aid in designs for more energy-efficient buildings through improved use of heating and cooling systems. Geologists and hydrologists could use TEMPEST to monitor the flow of groundwater, underground contaminants, and oil. The medical industry could apply the code to improve images of flow through intricate parts of the human body or to produce more detailed CAT scans.

During its long process of development and refinement, TEMPEST has amply demonstrated its usefulness. More than 75 copies of the code have been provided to universities and other organizations by PNL and through the DOE National Energy Software Center at ANL. The latest version of TEMPEST, which can be used on computers from PCs to CRAYs, is now being licensed by PNL to the commercial sector.

■ NEW INSTRUMENT AIDS IN TITANIUM PROCESSING

Noncontacting Ultrasonic Material and Super Alloy Process Monitor

There is a critical need in titanium processing to know the liquid-metal melt depth so that the liquid residence time can be controlled to dissolve, settle, or float out impurities. Impurities in critical airplane engine components can result in catastrophic failures like the fan blade failure that resulted in the loss of life in the 1989 DC-10 airplane crash in Sioux City, Iowa.

A noncontacting sensing technique and apparatus have been developed at the Idaho National Engineering Laboratory (INEL) to determine various elastic, acoustic, and ultrasonic properties of materials in real-time during processing. For example, both the density and shrinkage of a material can be determined during the sintering process. This technology provides a real-time monitoring technique, because the only time needed for the measurement is the time for ultrasonic wave passage through the material, which is usually on the order of microseconds. The monitoring technique requires optical access to the sample surface and uses lasers for both generating ultrasonic waves at the surface of a material and detecting the displacement these waves cause. The technique can be applied to materials processes such as sintering of ceramics; determining melt depth of liquid metals; annealing of metals; and monitoring melting, solidification, joining, welding, and bonding, where optical access is available.

The Fabry-Perot interferometer, which is used in the apparatus developed at INEL, detects ultrasonic motion from materials with rough and/or diffusely reflecting surfaces like those found on most materials during the processing stage. These unique qualities make this apparatus useful in the materials processing environment as a real-time material microstructure diagnostic tool. The interferometer detects ultrasonic motion through the Doppler shift of light scattered from the moving surface and is insensitive to the phase of the light. Therefore, many speckles can be collected to obtain a sufficient signal-to-noise ratio. This

approach is different from other phase-sensitive, optical-detection systems (i.e., homodyne and heterodyne), which require mirror-like reflecting surfaces or focusing to a single speckle.

The sensing process also provides a critical capability that has been unavailable for determining materials properties during processing. Using this technique, the sintering process in ceramics can be monitored and controlled in real time because the density and shrinkage of a ceramic can be determined during processing. Knowledge of the melt depth in liquid-metal processing will enable process control of hearth melting, which will result in higher quality, defect-free ingots. The ability to control these and other processes will result in increased productivity and product reliability coupled with optimum energy consumption in energy-demanding processes.

A consortium with industry is being formed to move this sensing technology into hearth-melting applications. A patent disclosure has been filed with the DOE-Chicago Patent Office.

CONTENTS

- 143 ■ SOFTWARE ENABLES ROBOT TO PROGRAM ITSELF
TO ASSEMBLE PARTS (SNL)
Opening New Territory for Economical Use of Robots
- 144 ■ ALPHA ENERGY ANALYSIS SOFTWARE (WHC)
Improved Isotope Identification and Activation Calculations
- 145 ■ LARGE-SCALE INFORMATION MANAGEMENT
SOFTWARE CONTROLS HUGE DATABASES (LLNL)
UniTree
- 147 ■ LARGE DATABASES MANIPULATED ON SMALL
COMPUTERS (SLAC)
REASON
- 148 ■ SMART CRATE CONTROLLER FOR FAST READOUT
(Fermilab)
Improves Existing Data Collection
- 149 ■ ACCELERATING HIGH-SPEED COMPUTING (LANL)
High-Performance Parallel Interface Tester
- 150 ■ NEW GENERATION OF SUPERCOMPUTERS (LLNL)
Massively Parallel Computing with Hundreds of Linked
Microprocessors

Fermi National Accelerator Laboratory (Fermilab) ■ Lawrence
Livermore National Laboratory (LLNL) ■ Los Alamos National
Laboratory (LANL) ■ Sandia National Laboratories (SNL) ■ Stanford
Linear Accelerator Center (SLAC) ■ Westinghouse Hanford Company
(WHC)

Computers and Communications

Researchers at Sandia National Laboratories (SNL) have developed a prototype computer software that for the first time enables a robot to "program itself" to assemble mechanical components. Getting robots to program themselves automatically is not a new concept, but getting them to do so in the complicated area of mechanical assembly had not been done until now. The ability to quickly and cheaply program robots will allow the use of robots in the production of small batches—an area in which the use of robots has not previously been economical or practical. Designed for use in the U.S. nuclear weapons production complex, the program could have far-reaching implications for design and manufacturing in U.S. industry.

The new software program—called Archimedes—includes routines by which the system "reasons" which steps are necessary to accomplish a given task. In this way it automatically generates assembly plans and the robotic programs that are needed to carry them out. It also "models" the assembly process, enabling engineers to quickly see the effects of design changes on ease of manufacture—opening the way for radical changes in how products are designed and manufactured.

The computer program begins with a three-dimensional Computer-Aided Design (CAD) model of a product. From this model, a generic assembly plan is automatically produced that satisfies the constraints of geometry, stability, and accessibility that were deduced from the model. In the next step, a plan compiler converts the generic plan into robot-specific code.

A crucial part of the work was to create routines in which mathematical descriptions of each part are manipulated in three-dimensional space. Within the computer, the spatial relationships of the parts are analyzed to determine how the parts can be brought together and secured in the correct configuration.

Typically, Archimedes will analyze a number of ways of accomplishing each assembly function, noting which way is not feasible (for example, one part blocking the path of another part) until it finds a solution. It then continues to another function until the assembly is complete in the computer. Sometimes the assembly cannot be accomplished with the robot's single "hand." In these cases, the system will design the necessary fixtures to hold parts during the otherwise nonfeasible operations. A compiler takes the assembly plan and develops the instructions that are followed by a specific robot type. The plan can be re-targeted to a different robot by making small changes in the compiler.

■ SOFTWARE ENABLES ROBOT TO PROGRAM ITSELF TO ASSEMBLE PARTS

Opening New 'Territory' for Economical Use of Robots

Researcher from SNL places parts in a "parts kit" that a robot (arm shown) picks up and assembles into a component part. The robot uses an assembly plan developed by a new software program, called Archimedes, that for the first time allows a robot to program itself automatically to do mechanical assembly.

■ ALPHA ENERGY ANALYSIS SOFTWARE

Improved Isotope Identification and Activation Calculations

The Westinghouse Hanford Company (WHC) has developed a computer software program with improved accuracy for identifying isotopic species and calculating isotope activation levels. This general alpha energy analysis software program was developed to enhance the ability to identify alpha peaks and activity levels from laboratory analysis of samples from high-efficiency particulate air filters used in nuclear facilities. This specialized software is being transferred to commercial industries on a nonexclusive basis where the basic principles are being incorporated into commercial alpha energy analysis products.

Alpha energy analysis is dependent on a number of factors, particularly the analytical environment and physical aspects of the sample during the counting operation. The goal of sample preparation is to produce a virtually weightless source (a weightless source is a sample with no physical or environmental factors that affect the detected alpha energy) for counting, using a vacuum chamber and a spectroscopy-grade, solid-state-detector system for data collection. In most cases, producing this ideal counting environment is either not possible or, at best, is very difficult to achieve, especially with air filters for particulates, high-salt solutions, and biological samples. When these samples are analyzed for alpha energy, the spectra are usually degraded to a point that most manual calculational methods are of questionable value or credibility.

The alpha energy analysis program developed by WHC accepts computer-stored, multichannel-analyzer spectral data; improves the quality of spectral data; determines spectral energy peaks; models the peaks; and using these peak models, provides both qualitative and quantitative results. In its operation, the spectra are first compressed and smoothed to reduce statistical noise found in counting systems, a particular problem with low-count-rate alpha energy detector systems. The program then searches for alpha peaks by examining the first derivative of the conditioned spectra. This method of peak detection is highly sensitive and, depending on the counting noise embedded in the spectra, will initially find too many false peaks to begin the identification and analysis process. The analysis program eliminates most of the false peaks by further testing the derivative slope in the region surrounding a suspected energy peak. This procedure is repeated until the sensed peaks are of a reasonable number or the spectra have been compressed to 128 channels.

The software then successively models the conditioned peaks, starting at the highest energy peak. Sufficient peak data are then introduced, while avoiding near-peak interference, to a simplex-fitting algorithm that provides a smoothed peak. The resulting fit for the peak is subtracted from the original spectrum, and the next lower energy peak is processed with this same procedure. The process is repeated until all of the detected peaks have been processed. The calculated peak energies are compared to a

table of valid isotope energies, and when a match is found within an energy window, a quantitative activity is calculated. Assigning quantitative values is dependent on the alpha-decay branching ratios, yield, and counting geometry or counting efficiency of the alpha energy detection system.

This figure illustrates the curve-modeling steps that the alpha energy analysis program developed by WHC uses to improve the analysis of alpha energy spectra.

Detector-counting efficiencies or geometry factors must be determined before quantitative results are produced. Automatic energy and efficiency calibration is supported by collecting spectra from traceable calibration sources. The program uses predefined or user-specified calibration peak energy definitions to fit an energy calibration curve for the geometry of the sample being analyzed. Matching the observed energy to the proper isotope is dependent on this calibration of the counting system. The program uses externally defined calibration source activity to calculate the efficiency from the results of the calibration spectral analysis. The counting efficiency is maintained in a calibration file for use in sample analysis.

This software was originally designed to run on a minicomputer. It was customized for use in an embedded process stack gas monitoring system and has operated unattended for over 4 years. A general version has been developed that runs on an IBM-PC or compatibles. The calculation times range from 1 to 20 minutes, depending on the system hardware (speed is enhanced with a coprocessor in the PC).

An information storage system developed for supercomputers at Lawrence Livermore National Laboratory (LLNL) was being readied for the commercial market in mid-1990. The LLNL system is capable of managing an enormous amount of information, and for all practical purposes is limited only by the scale of the associated hardware, such as tape libraries or vaults. This system is now being used to manage information equivalent to 5 million novels, approximately 20 times the size of the database

■ **LARGE-SCALE
INFORMATION
MANAGEMENT
SOFTWARE CONTROLS
HUGE DATABASES**

UniTree

previously managed at LLNL. The system will be called UniTree when it is commercially released by Distributed Computing Solutions (DISCOS), a division of General Atomics.

The agreement with General Atomics is an example of how valuable technology developed at a DOE laboratory can be transferred to U.S. industry on a preferential basis. By licensing the system to DISCOS rather than to the manufacturer of a specific brand of hardware, UniTree will receive the widest possible distribution.

Viewed as a further step toward a fully automated information storage and retrieval system, the UniTree file and storage system was developed between 1984 and 1988 by computer scientists in the LLNL Network Systems Division to replace a system that had been used since the 1960s. Now LLNL scientists and engineers receive requested information in a few minutes, rather than in a half hour, or in some cases longer. In the past, many information storage tapes had to be manually retrieved from vaults in other buildings before requests for information could be satisfied.

The UniTree system handles file management using four media that, in the order listed, have increasing amounts of storage space but slower access to information. These media are the disks of Cray supercomputers, 50 to 100 billion bytes (or characters) of storage with millisecond access; the magnetic disks of the central system, controlled by an Amdahl computer, 200 billion bytes with access in a few seconds; an automated tape library, 5,000 billion bytes with access in 30 seconds to several minutes; and a vault, with 16,000 billion bytes, offering manual access within 10 to 15 minutes.

DISCOS was attracted to the UniTree software because it can be easily transferred between different computers and can function as part of a network in which several computers can work on the same problem at the same time. The architecture of UniTree provides an attractive growth path into the 1990s for dynamic, rapidly expanding computer systems with large data-storage requirements. Data storage is becoming more critical because of a geometric rise in information with faster computers and the increasing use of analytical programs involving two and three dimensions.

UniTree is a set of software programs totaling about 150,000 lines of code. It automatically retains frequently used files on magnetic disks and sends rarely used files to other storage media, such as automated tape libraries or vaults, that are more cost effective for storing data with limited access requirements. The implementation of UniTree at LLNL has significantly cut the costs for managing its information storage system. In the past, two or three computer operators were required to manage the system, but no full time operators are needed with UniTree.

Under the terms of the licensing agreement, DISCOS will support the UniTree software. LLNL, in turn, will receive all product upgrades as well as royalties on software sales.

REASON is a software package recently developed at Stanford Linear Accelerator Center (SLAC) to do physics analysis on large databases using the local power of a workstation computer. Today's researcher in most scientific disciplines is faced with the task of analyzing large amounts of data. For example, in the high-energy physics work done at SLAC, raw data from accelerator experiments are initially collected and preprocessed. The computing power required for storage and manipulation of incoming data and the storage of the output data is enormous, so these operations must be done off-line. The task is daunting and is intractable on a small, stand-alone computer or workstation. Even after preprocessing, the data sets are still too large for easy analysis, and further processing is required to reduce them to manageable size for study. Once this stage is reached, analysis usually proceeds on a mainframe computer in batch mode. REASON was created to allow analysis at this level to be done locally and interactively on a workstation.

The workstation chosen for the development of REASON was the NeXT computer. It was chosen for its adequate CPU performance, sufficient RAM and disk space to hold programs and copious amounts of data, high throughput, good networking capabilities, megapixel graphics capability, and a good programming environment to develop the graphic user-interface.

The result of the REASON project at SLAC is a software package that permits local, interactive statistical analysis on amounts of data that heretofore could only be efficiently processed on a mainframe computer. Tasks too long to be interactive can use the multitasking operating system of the workstation. The networking capabilities or the optical disc feature of the NeXT computer can offer collaborators at remote sites access to data at a cost that is affordable by virtually any small research budget. The use of object-oriented programming techniques enables the user to achieve flexibility, modularity, simplicity of coding, and reusability of code. All aspects of the analysis are performed in a graphical and intuitive way, thus reducing the possibility of program bugs and syntactical errors. Analysis chains are easily constructed by using a mouse rather than by writing code.

Care was taken in the development of REASON to separate the physics-related aspects of the software from the general data analysis utilities. Hence, REASON can be applied to statistical analysis in many other fields as well. Users can customize the application by selecting from a palette of objects that input files,

■ LARGE DATABASES MANIPULATED ON SMALL COMPUTERS REASON

■ SMART CRATE CONTROLLER FOR FAST READOUT

Improves Existing Data Collection

make cuts, create loops, construct arbitrary logical and numerical expressions, generate histograms, and plot curves. These operations can be done interactively so that preliminary ideas and theories can be validated or eliminated quickly. Such versatility was designed to make the job of the analyst in whatever discipline much easier.

In the past, event sizes and rates in high-energy physics experiments at scientific research centers like Fermi National Accelerator Center (Fermilab) were such that the data readout time was small enough to keep experiment dead time down within the 10 to 20 percent range. With present higher intensity and larger event-size experiments, existing CAMAC and FASTBUS system read-times have become too large.

The Fermilab Smart Crate Controller (SCC) solves both of these problems. First, in a CAMAC system, the minimum readout time per 24-bit word from a single CAMAC crate is almost halved. Typically the time per word is 1 microsecond, the time for a normal CAMAC cycle. Second, several separate electronic crates can be read in parallel using a microprocessor-based Crate Controller in each readout crate. Data from each crate goes into either VME-based or FASTBUS-based memories. CAMAC, VME, and FASTBUS are widely used electronic data collection standards.

The SCC system provides impressive improvements. For example, if 1,000 words are to be read at 100 words per crate from 10 CAMAC crates, the data readout time using the SCC CAMAC Readout System is shortened by a factor of about 30 over a normal parallel CAMAC system. Another reason for employing the SCC CAMAC Readout System is to provide a fast, efficient, and highly parallel method for transferring CAMAC readout data into either VME-based or FASTBUS-based on-line processing farms.

The SCC stores readout lists of CAMAC or FASTBUS commands. Upon receipt of a front panel trigger, the SCC microprocessor executes the readout list at a 1-microsecond rate for CAMAC or 150 nanoseconds per 32-bit word for FASTBUS. Data being read are transferred out of the controller, 16 bits at a time, via a front panel connector using RS-485 differential drivers and receivers. SCC circuitry is centered around a Motorola 68020 microprocessor. Software running on the microprocessor controls communication with the host computer, initializes the SCC control registers, supervises operation of the module during data taking, and handles errors. In a typical SCC configuration the microprocessor is connected to 16K 16-bit words of EPROM, 32K 16-bit words of RAM, an RS-232 serial port controller, and Trigger-In and Trigger-Out ports. The microprocessor is also connected to 8K 32-bit words of Readout List Memory, which specifies the

sequences of CAMAC operations to be performed for each type of trigger. For normal CAMAC readout, control is transferred to the Readout List Processor, a Signetics PLS168 sequencer programmed as a State Machine.

Software has been developed for both the CAMAC and the FASTBUS versions of the SSC. Some parts of this software have been created by commercial and public-sector software developers (Software Components Group Inc. of Santa Clara, California, and the University of California at Berkeley). Typically, some user software must be developed for each installation.

A commercial version of the CAMAC-based SSC is available from BiRa Systems in Albuquerque, New Mexico. The FASTBUS version is presently being commercialized.

For complex research areas such as superconductivity, earthquake prediction, global warming trends, and environmental modeling and monitoring, high-speed computers are increasingly invaluable tools. As these supercomputers become faster and faster, however, a unique problem has developed: their processing power has significantly outpaced their input/output capability. Consequently, users of high-performance computers have awaited the arrival of an input/output channel that can handle the speed required for visualizing data (in movie-quality video images) and for transferring information to and from storage devices and other computers.

With the recent development of the High-Performance Parallel Interface (HIPPI), a new standard from the American National Standards Institute, the input/output speed of a high-speed computer can be increased so that it is compatible with the processing speed of the computer. But at 800 million bits per second, the sheer speed of the new interface called for a means of testing and diagnosing failures in the channel. The HIPPI Tester, developed at Los Alamos National Laboratory (LANL), ensures that users will get the performance they require.

Because many companies have announced that they will support the HIPPI channel for their next generation of high-speed computers and peripherals, the HIPPI Tester is crucial to the rapid growth of the high-performance computer industry. While the HIPPI channel will pave the way for researchers to make the best use of high-speed computers, the tester is expected to expedite significantly the availability of this channel for a broad variety of research applications.

The HIPPI Tester was developed in time for the arrival of the first HIPPI prototypes so that the availability of the new chan-

■ ACCELERATING HIGH-SPEED COMPUTING

**High-Performance Parallel
Interface Tester**

nel would not be delayed. The tester attaches to any computer equipped with the new interface to evaluate compliance with specifications, to diagnose failed hardware, and to help measure performance and reliability. The tester can also be used to troubleshoot new product designs at engineering laboratories, to aid in the manufacture of each copy of new hardware on commercial production lines, and to enable field-service personnel to repair the channel at remote computer sites.

The LANL device consists of two parts: a custom-printed circuit assembly (custom hardware) and an attached personal computer that runs the HIPPI Tester software. Packaged in a standard briefcase, the system is portable and inexpensive; in fact, the direct equipment cost is only 30 percent of the cost of conventional test equipment, and the tester can save even more money indirectly because it is so easy to use that any technician or engineer can operate it with only a minimal of training.

The DOE holds copyrights on the tester technology for seven programmable devices, two large software programs, and five test suites comprising 38 individual tests of the HIPPI channel. Industry has expressed a great deal of interest in the tester, and the LANL Industrial Applications Office is pursuing licensing of the technology for production and marketing by one or more commercial firms.

■ NEW GENERATION OF SUPERCOMPUTERS

**Massively Parallel Computing with
Hundreds of Linked Microprocessors**

For the past 15 years, supercomputers have relied on eight or fewer processors per machine. However, scientists at Lawrence Livermore National Laboratory (LLNL) are now researching methods to effectively use computers that have hundreds of processors. To evaluate this idea, LLNL is launching one of the largest research efforts ever undertaken in the field of massively parallel computing. The \$10 million project will span 3 years and will involve at least 50 scientists on a full-time or part-time basis.

The design concept called massive parallelism enables computers to use a very large number of processors by dividing a problem into small pieces and then solving the pieces at the same time, in parallel. This approach is proving faster for many kinds of jobs than the approach used by conventional supercomputers, in which just one or a handful of processors attack the problem serially, or one step at a time. The promise of improved performance through massive parallelism comes at a critical time for the U.S. supercomputer industry and the Nation, because supercomputers are widely used for national defense and high-level scientific research. Japanese companies now make serial supercomputers that rival the performance of computers made by Cray Research Inc., the Minneapolis-based supercomputer pioneer that presently controls about 60 percent of the market.

The LLNL program will focus on writing production codes for a TC-2000 126-processor computer that LLNL has agreed to purchase for \$4.5 million from BBN Advanced Computers Inc., a subsidiary of Bolt Beranek and Newman of Cambridge, Massachusetts. LLNL and the computer manufacturer have agreed to collaboratively study massively parallel computing. This move is seen by LLNL researchers as an important step toward bringing the promise of massively parallel computing to real-world computing problems. It will also enhance the manufacturer's ability to develop its next generation of hardware and software. The software developed at LLNL will be provided to BBN Advanced Computers for distribution and development in an ongoing technology transfer program.

The decision by LLNL to investigate massively parallel computing was fueled by the revolutionary improvements in microprocessor chips that have been made in the last few years, during which the floating point computing power has doubled nearly every 12 months, rapidly narrowing the power gap that separates the microprocessor from the supercomputer. Leading microprocessor chips can now run scalar computer codes faster than supercomputer processors. Another key factor is cost. Microprocessor-based computers now cost \$20,000 to \$40,000 per processing unit, or \$2 to \$4 million for 100 processors, while supercomputer processors are about \$3.75 million each, or \$30 million for the eight units required for a typical supercomputer.

Codes that may be adapted by LLNL for the 126-processor massively parallel computer include those for models of atmospheric and oceanic circulation, radiation transport through the sun, magnetic confinement fusion, turbulent flow around hypersonic aircraft, and the mechanical properties of gases. This approach may also be useful for applications in speech and image processing, in which the demand for computer power is seemingly inexhaustible. Massively parallel computers may be from 10 to 100 times more powerful for many jobs than conventional supercomputers.

There are now dozens of startup companies exploring new computer designs based on linking microprocessors. One company has made a computer using up to 64,000 microprocessors, and these efforts have established that the innovative approach of massively parallel supercomputing can compete and often surpass conventional designs. LLNL, through a program of ongoing technology transfer, is helping private enterprise move ahead rapidly in its exploration of this new and extremely promising computer technology.

CONTENTS

155 ■ Introduction

157 ■ Access to the Laboratories

158 ■ COLLABORATIVE PROJECTS WITH INDUSTRY

159 ■ TECHNOLOGY AND SOFTWARE LICENSING

160 ■ SCIENTIFIC USER FACILITIES

160 ■ INDUSTRIAL INTERACTIONS

161 ■ TECHNICAL PERSONNEL EXCHANGES

162 ■ REIMBURSABLE WORK FOR OTHERS

162 ■ CONSULTING ARRANGEMENTS

162 ■ UNIVERSITY INTERACTIONS

164 ■ CONTRACTING ARRANGEMENTS

164 ■ TECHNICAL DOCUMENTS AND SOFTWARE

165 ■ Multiprogram Laboratories

165 ■ ARGONNE NATIONAL LABORATORY

166 ■ BROOKHAVEN NATIONAL LABORATORY

167 ■ IDAHO NATIONAL ENGINEERING LABORATORY

168 ■ LAWRENCE BERKELEY LABORATORY

169 ■ LAWRENCE LIVERMORE NATIONAL LABORATORY

170 ■ LOS ALAMOS NATIONAL LABORATORY

171 ■ OAK RIDGE NATIONAL LABORATORY

172 ■ PACIFIC NORTHWEST LABORATORY

173 ■ SANDIA NATIONAL LABORATORIES

174 ■ Major Single-Program Laboratories

174 ■ AMES LABORATORY

175 ■ CONTINUOUS ELECTRON BEAM ACCELERATOR
FACILITY

176 ■ FERMI NATIONAL ACCELERATOR LABORATORY

177 ■ MORGANTOWN ENERGY TECHNOLOGY CENTER

178 ■ OAK RIDGE ASSOCIATED UNIVERSITIES

179 ■ PITTSBURGH ENERGY TECHNOLOGY CENTER

180 ■ PRINCETON PLASMA PHYSICS LABORATORY

181 ■ SAVANNAH RIVER LABORATORY

182 ■ SOLAR ENERGY RESEARCH INSTITUTE

183 ■ STANFORD LINEAR ACCELERATOR CENTER

184 ■ WESTINGHOUSE HANFORD COMPANY

185 ■ Other DOE Laboratories

185 ■ BATES LINEAR ACCELERATOR CENTER

185 ■ ENERGY TECHNOLOGY ENGINEERING CENTER

185 ■ ENVIRONMENTAL MEASUREMENTS LABORATORY

186 ■ INHALATION TOXICOLOGY RESEARCH INSTITUTE

186 ■ LABORATORY OF RADIOBIOLOGY AND
ENVIRONMENTAL HEALTH

187 ■ MICHIGAN STATE UNIVERSITY - DOE PLANT
RESEARCH LABORATORY

187 ■ NATIONAL INSTITUTE FOR PETROLEUM AND
ENERGY RESEARCH

187 ■ NEW BRUNSWICK LABORATORY

188 ■ NOTRE DAME RADIATION LABORATORY

188 ■ SAVANNAH RIVER ECOLOGY LABORATORY

188 ■ STANFORD SYNCHROTRON RADIATION
LABORATORY

3 LABORATORIES

LABORATORIES

The steel-making industry may get a boost with Magneco/Metrel's development of new castable refractory materials. In this photograph, researchers from Magneco/Metrel and Argonne National Laboratory (ANL) prepare to test a sample of refractory brick using ANL's 30 kilovolt-ampere (kVA) induction furnace. The new materials last longer and perform better than conventional refractories. Magneco/Metrel is using grants from the Illinois Department of Commerce and Community Affairs to fund tests at ANL of the new refractory, which can be pumped into place to form vessels for molten metal.

Introduction

"I believe that one of the most powerful ways for the government to help [U.S. competitiveness] is to make it easier for U.S. industry to obtain the results of federally sponsored R&D, both through licensing and through collaborative research."

Admiral James D. Watkins, U.S. Navy (Retired), Secretary of Energy

The DOE laboratories form a network composed of 9 multi-program laboratories, 11 major single-program laboratories, and 11 smaller laboratories. Collectively, the laboratories are a significant national resource, and their diversity encompasses all of the major scientific and engineering disciplines. Research activities at the laboratories span a broad range of scientific and technical areas, including materials science, chemical science, environmental science, biology, physics, fusion energy, defense-related research, waste management, nuclear energy, conservation, renewable energy, and fossil energy. Overall, the DOE laboratories perform over \$6 billion of research and development annually.

This network of DOE laboratories is a national resource for new technologies that can be accessed through the Offices of Research and Technology Applications (ORTA) at the laboratories.

President George Bush presents the 1989 National Medal of Technology to Dr. J. Ritchie Orr of Fermilab. Four Fermilab scientists—Dr. Helen Edwards (now at the Superconducting Super Collider Laboratory), Dr. Richard Lundy (retired), Dr. Alvin Tollestrup, and Dr. Orr—received the award for their contributions to the design, construction, and initial operation of the superconducting TEVATRON accelerator at Fermilab.

The excellence of the research and development performed by the DOE laboratories is indicated by the high standing of their personnel within the scientific and technical community and their successes in receiving various awards within this community. For example, 16 Nobel prizes in science have been awarded for work performed at the laboratories. The laboratories have also received over 325 R&D-100 Awards. These awards are selected annually by *R&D* magazine in an international competition and represent the 100 most significant new products, processes, and materials developed in a given year. DOE laboratory scientists and engineers have won more of these awards than any other organization and continued this tradition of excellence in 1990 by receiving 27 R&D-100 Awards. Some of these award-winning technologies are described in *Technology '90*. A recent study revealed that about 45 percent of the technologies that received R&D-100 Awards had been commercially applied.

New technologies from the DOE laboratories can be accessed through the Offices of Research and Technology Applications (ORTA), which are responsible for technology transfer. Information on specific technology transfer contacts and descriptions of each laboratory are included later in this section. The laboratories emphasized in this document are the major DOE laboratories that have comprehensive technology transfer programs; however, all DOE laboratories perform technology transfer activities.

For licensing information on DOE-owned technology, the contact is:

Mr. Robert J. Marchick
Assistant for Licensing
Assistant General Counsel for Patents, GC-42
U.S. Department of Energy
1000 Independence Ave., S.W.
Washington, D.C. 20585
(202) 586-2802
FTS 896-2802

For additional information about the DOE's R&D Laboratory Technology Transfer Program, the contact is:

**Office of Energy Research, Laboratory
Management Division, ER-42**
U.S. Department of Energy
1000 Independence Ave., S.W.
Washington, D.C. 20585
(202) 586-9740
FTS 896-9740

Access to the Laboratories

The DOE has made significant efforts to provide opportunities for U.S. industry and universities to access technology in the DOE laboratories. As the accompanying illustration shows, many different mechanisms are available for working with the laboratories. Companies of all sizes and university scientists and engineers in various technical disciplines interact and collaborate with DOE laboratories through these mechanisms. The following discussion briefly describes the various means of accessing the laboratories.

Opportunities to work with DOE laboratories are many and varied. Each arrow in this diagram represents a means of access to the laboratories for U.S. industry, universities, and agencies of State and local governments.

■ COLLABORATIVE PROJECTS WITH INDUSTRY

Increasing the number and scope of collaborative research and development projects with U.S. industry is one of the most important goals of current DOE and laboratory technology transfer efforts. This emphasis results from the fact that neither the laboratories nor industry can be successful in the technology transfer process by working in isolation. A team effort, with joint participation from both parties, is required. Laboratory participation is necessary to provide a technical perspective required for successful technology application, while participation by industry is needed to lend a market-oriented and production perspective to the transfer process.

A major goal of the National Competitiveness Technology Transfer Act (NCTTA) was to encourage and facilitate the development of collaborative relationships between the DOE laboratories and U.S. industry. The NCTTA provided laboratory Directors or their designees with authority to enter directly into Cooperative Research and Development Agreements (CRADA) with industrial partners, and required swift reviews of these agreements by DOE. The NCTTA also stipulated that laboratory contracts be modified to appropriately reflect the new emphases and authorities granted by the Act. The DOE moved rapidly to implement these provisions, and significant progress has been made in negotiating the new contract terms. As of November 1990, negotiations had been successfully completed on the new contract terms with several laboratory contractors and most of the other negotiations were in the final stages. In addition, the first CRADA was signed between the Idaho National Engineering Laboratory (INEL) and industrial partners.

Under a CRADA, the Federal government (through its laboratories) may provide personnel, facilities, equipment, or other resources (but not funds to non-Federal parties). Non-Federal participants may provide funds, personnel services, facilities, equipment, or other resources to conduct specified research and development efforts that are consistent with the mission of a laboratory. Proprietary data brought into or generated in a CRADA can be withheld from public release for up to 5 years. Both the laboratories and the DOE program offices are placing a high priority on the establishment of CRADAs that can mutually benefit their missions and the objectives of the industrial partners. Interested parties are encouraged to contact either laboratory or DOE representatives for more information on CRADAs.

Nonprofit laboratory contractors automatically can retain patent titles and license technology in all technical areas except defense and other sensitive programs. The for-profit laboratory contractors should soon have a similar broad capability through class patent waiver agreements that are currently under negotiation. Currently, these contractors retain title and license technology on a case-by-case basis.

Each laboratory contractor licenses its own patents; government-owned patents are licensed from DOE Headquarters. The number of patents awarded for laboratory inventions is steadily increasing. Licenses and income earned from licensing also are on a significant upswing with 57 licenses issued in FY 1989 (a 30 percent increase over the previous year) and nearly \$1.5 million earned (a 190 percent increase compared to FY 1988). Within broad guidelines governing such areas as conflict-of-interest and fairness-of-opportunity, laboratory contractors are free to negotiate a variety of terms and conditions for their technology licenses. These terms and conditions are aimed at protecting the investment of the Federal government and/or the contractor in the technology, providing an incentive for the firm licensing the technology (i.e., the licensee) to make additional investments, and, most important, providing the best possible assurance for the eventual commercialization of the technology.

A DOE policy established in 1988 allows computer software to be copyrighted and licensed by laboratory contractors. To ensure public availability of the basic information, abstracts of source codes are provided to the National Energy Software Center, which is maintained at Argonne National Laboratory by the Office of Scientific and Technical Information (OSTI). The licensing of DOE-developed computer software by the laboratory contractors is steadily increasing with 13 licenses issued in FY 1989.

Technologies may be licensed from the laboratories on a fully exclusive basis, exclusive for a particular application or field-of-use, or on a nonexclusive basis. In selected cases, up-front investments by the licensee may be negotiated. However, a characteristic common to nearly all licensing agreements is that most of the licensing costs to the licensee are not incurred until product sales are realized. Thus, licensing is a relatively low-risk method of accessing potential new products.

The laboratories widely advertise licensing opportunities through press releases, attendance at trade and technical conferences, and information mailings. Additional information on laboratory licensing programs and opportunities can be obtained by contacting the laboratory technology transfer contact identified in the laboratory descriptions that follow.

■ TECHNOLOGY AND SOFTWARE LICENSING

■ SCIENTIFIC USER FACILITIES

■ INDUSTRIAL INTERACTIONS

David Moncton, Associate Laboratory Director for the Advanced Photon Source at ANL, demonstrates to Marilyn Lloyd (D-Tenn.) the path a beam of positrons would follow in the Advanced Photon Source beam line. Congresswoman Lloyd is Chairman of the U.S. House Subcommittee on Energy Research and Development that held a hearing at ANL.

DOE laboratories provide valuable, often unique, experimental facilities for use by university and industrial scientists in many fields. Potential user research proposals are peer reviewed for appropriateness and quality, and access to a facility is granted based on the scientific merit of the proposal. If users publish the results of their work, there is traditionally no charge to work at the facility; if the work is proprietary, users pay full costs of using the facility. Patent rights to any resulting inventions are generally given in advance to users paying full costs.

The DOE and its laboratories use a variety of methods for interacting with private industry. Some of these interactions occur on a program-specific basis through Advisory Committees that provide guidance in specific research and development areas. Others occur through workshops and conferences sponsored by the laboratories. The laboratories conducted over 300 such workshops and conferences in FY 1989. Other interactions occur at the senior management level through efforts such as the Technology Transfer Roundtable convened by Energy Secretary Watkins in March 1990 in conjunction with the development of the National Energy Strategy.

The DOE and its laboratories are major participants and supporters of the Federal Laboratory Consortium, which is an organization that focuses on facilitating increased interactions between U.S. industry and Federal laboratories. The DOE laboratories are

also frequent participants in events sponsored by the Industrial Research Institute. They also conduct various activities with State and local government organizations and are in the process of formulating methods for strengthening interactions with such organizations, particularly as a means of improving outreach to small businesses. Increasing the amount of industrial interactions at all levels of DOE and laboratory activities, and throughout all phases of research and development programs, is a major goal of current technology transfer efforts.

Personnel exchanges with U.S. industries and universities are an important component of the technology transfer efforts of the DOE. These exchanges may be conducted through specific research and development programs or arranged on an informal basis with the laboratories. In addition, a separate technical personnel exchange program may be conducted with a focus on technology transfer between private-sector companies and the laboratories. This program will support travel, living, and other costs for personnel participating in exchanges. To encourage participation, the rights to any resulting patents go to the participant's organization. The exchanges, which typically last about 6 months, are opportunities for the laboratories and industry to develop improved relations and are ideal for updating the technical skills of the participants. Additional information on this exchange program for FY 1990 was presented previously in the R&D Laboratory Technology Transfer Program subsection of the *Overview*.

■ TECHNICAL PERSONNEL EXCHANGES

Superconductive Components Inc. and ANL are collaborating in the development of high-temperature ceramic superconductors. In this photograph, staff from Superconductive Components and ANL are shown preparing a sample of yttrium-barium-copper oxide with a hydraulic press in the ceramics laboratory at ANL. This collaborative work is funded through the ANL Center for Superconductivity Commercialization, a DOE program aimed at hastening commercial applications of superconductivity technology.

■ REIMBURSABLE WORK FOR OTHERS

DOE laboratories are available to perform work for industry or for other Federal agencies as long as the work pertains to the mission of the respective laboratory, does not impact on the achievement of DOE program requirements, and does not directly compete with capabilities available in the private sector. In 1989, the laboratories performed about \$60 million worth of this fully reimbursed work for non-Federal organizations. An advance patent waiver can be obtained to give ownership of any inventions resulting from the research to a participating company from the private sector.

■ CONSULTING ARRANGEMENTS

Scientists and engineers at the DOE laboratories are available to consult in their areas of technical expertise, and their involvement in consulting activities is increasing. Each laboratory contractor has its own consulting practices that comply with DOE consulting guidelines. Laboratory staff are generally free to consult for pay, and many laboratories also have programs that allow their employees to provide free technical assistance to outside organizations on a limited and selected basis. Laboratory employees who are involved in consulting activities are allowed to sign nondisclosure arrangements. In FY 1989, over 1,575 DOE laboratory employees performed consulting services.

■ UNIVERSITY INTERACTIONS

The DOE and its laboratories support the training of the next generation of U.S. scientific and technical leaders in several ways. DOE supports 3,500 to 4,000 graduate students and 950 postdoctoral research fellows at universities and the laboratories. All laboratories and research programs incorporate an education mission. Ongoing laboratory research education programs involve faculty, undergraduate students, and precollege science teachers and students onsite at the laboratories. Increasing emphasis is being placed on reaching minority and female students through educational outreach and training programs.

This map shows the locations of the National Environmental Research Parks within ecoregions in the United States.

Research collaboration among university, private-sector, and Federal scientists is ongoing in various research and development programs and at laboratory scientific user facilities. Most of the laboratories have formal collaborative agreements with universities that cover matters such as staff/faculty exchanges, joint instructional programs, university agreements for joint research, administrative procedures for large-scale scientific computing systems, and joint appointments of affiliate scientists. In addition to university interactions, the laboratories are playing a pivotal role in the implementation of Secretary Watkins' new initiatives to promote and improve science and mathematics education at the pre-college grade levels.

■ CONTRACTING ARRANGEMENTS

Subcontracts, procurements, and, less frequently, grants are used by the DOE laboratories to work with industry and universities and are often overlooked as technology transfer mechanisms. However, such contracting arrangements can offer an opportunity for the private sector to be integral in developing new technology, can provide access by the laboratories to needed capabilities available from private industry and universities, and can provide an automatic vehicle for communication between the various participants. Total subcontracts and procurements from the laboratories exceed \$1 billion in value, and a significant number of these arrangements can be shown to facilitate technology transfer.

■ TECHNICAL DOCUMENTS AND SOFTWARE

Technical documents and database software are a traditional means of disseminating information on research results and technologies available at the laboratories. Every author of a technical program report written at a DOE laboratory must submit copies of the report to the Office of Scientific and Technical Information (OSTI) in Oak Ridge, Tennessee, as long as the contents of the report are considered to be in the public domain. OSTI also compiles and manages various types of databases and computer software programs to assist individuals in determining the types of technical activities being performed at the laboratories and the technologies that are available. Further information on OSTI's capabilities is provided at the end of this document.

Multiprogram Laboratories

■ ARGONNE NATIONAL LABORATORY

Argonne, Illinois

*Operated by The University of Chicago
FY 1990 Operating Budget \$325M
FY 1990 Staff 3,800*

Argonne National Laboratory (ANL) conducts applied research and engineering-based development in nuclear fission and other energy technologies and scientific research in basic physical and life sciences. Research and development at ANL links technology-based research with engineering development, from concept stages to application. Primary research and development program areas at ANL are nuclear energy, basic energy sciences, conservation and renewable energy, biological and environmental research, and superconductivity.

ANL is one of three high-temperature superconductivity research centers and is also one of the three Pilot Centers designated by DOE to collaborate with industry in advancing high-temperature superconductivity technologies.

Designated Scientific User Facilities

Biological-Materials Growth Facility
4 MV Dynamitron Facility
Facility for High Resolution Atomic Spectroscopy
JANUS Biomedical Research Reactor
Argonne Tandem Linac Accelerator Facility
Intense Pulsed Neutron Source
High Voltage Electron Microscope Tandem Facility
Users Support Center
Advanced Photon Source (under construction)

Technology Transfer Contact

Dr. Paul Betten
Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439-4841
(708) 972-5361
FIS 972-5361

BROOKHAVEN NATIONAL LABORATORY

Upton, New York

*Operated by Associated Universities, Inc.
FY 1990 Operating Budget \$260M
FY 1990 Staff 3,325*

Designated Scientific User Facilities

Alternating Gradient Synchrotron
National Synchrotron Light Source
Double MP-Type Tandem Accelerator Facility
60-Inch Cyclotron
Scanning Transmission Electron Microscopy Facility
JSW168 Small Cyclotron
High Flux Beam Reactor
Relativistic Heavy Ion Collider (under construction)

Technology Transfer Contact

Dr. Margaret C. Bogosian
Brookhaven National Laboratory
Building 902C
Upton, NY 11973
(516) 282-7338
FTS 666-7338

The Brookhaven National Laboratory (BNL) conceives, develops, constructs, and operates complex research facilities for the study of fundamental properties of matter. BNL conducts basic and applied research in technology base areas, supports research facilities, and establishes important new directions for research. Major disciplinary strengths at BNL are high-energy, nuclear, and solid-state physics; chemistry; and biology. The primary program areas at BNL are high-energy physics, basic energy sciences, biological and environmental research, and nuclear physics.

■ IDAHO NATIONAL ENGINEERING LABORATORY

Idaho Falls, Idaho

*Operated by EG&G Idaho, Inc.
Westinghouse Idaho Nuclear Company, Inc.
Rockwell-INEL
FY 1990 Operating Budget \$541M
FY 1990 Staff 6,540*

INEL

The Idaho National Engineering Laboratory (INEL) is a multiprogram laboratory. Historically a leader in the DOE reactor technology programs and engineering projects, INEL conducts applied research and development to support the mission of DOE and other government agencies. INEL provides independent scientific advice and technical verification and validation in areas of its expertise for the Federal Government. INEL offers use of its unique facilities for the benefit of members of the technical community, cooperates with personnel in universities and industry to educate scientists and engineers, and provides technology transfer to the public and private sectors. Major INEL facilities are located in Idaho Falls, Idaho, and on an 890-square-mile tract west of Idaho Falls.

In addition to the three primary operating contractors identified above, Westinghouse Electric Corporation operates the Naval Reactor Facility for the DOE and the U.S. Navy, and Argonne National Laboratory-West operates the Experimental Breeder Reactor-II and maintains research facilities.

Designated Scientific User Facilities

INEL Environmental Research Park

Technology Transfer Contact

Mr. Richard D. Holman
Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P.O. Box 1625
Idaho Falls, ID 83415-3561
(208) 526-1571
FTS 583-1571

■ LAWRENCE BERKELEY LABORATORY

Berkeley, California

*Operated by the University of California
FY 1990 Operating Budget \$180M
FY 1990 Staff 3,420*

Designated Scientific User Facilities

Bevalac
National Center for Electron Microscopy
National Tritium Labeling Facility
88 Inch Cyclotron
Advanced Light Source (under construction)

Technology Transfer Contact

Dr. Pepi Ross
Lawrence Berkeley Laboratory
University of California
Building 90-1070
Berkeley, CA 94720
(415) 486-6467
FTS 451-6467

Lawrence Berkeley Laboratory (LBL) is a multiprogram DOE laboratory. The oldest of the DOE laboratories, LBL is the only one located next to one of the world's great universities—the University of California, Berkeley.

LBL supports a wide range of research activities in fields ranging from astrophysics to energy conservation. LBL's role is to serve the Nation and its scientific and educational communities through energy-related research performed in its unique facilities. LBL's role forms a four-part mission: 1) perform leading multidisciplinary research in energy sciences, general sciences, and life sciences; 2) develop and operate unique national experimental facilities for use by qualified investigators; 3) educate and train future generations of scientists and engineers; and 4) foster productive relationships between LBL research programs and industry.

Current programs encompass all the natural sciences, as well as engineering, mathematics, and computer science. Basic studies of the nature of the atom and the cell, research on new treatments for cancer patients, and the development of advanced materials, instruments, facilities, and new energy sources are typical examples of LBL research.

■ LAWRENCE LIVERMORE NATIONAL LABORATORY

Livermore, California

*Operated by the University of California
FY 1990 Operating Budget \$1.1B
FY 1990 Staff 8,200*

Lawrence Livermore National Laboratory (LLNL) was established in 1952 to perform research on nuclear weapons and magnetic fusion energy. Since then, the mission has expanded to include research in other areas, including laser fusion and laser isotope separation, biomedical and environmental sciences, applied energy technology, and a broad range of beam technology issues. These programs, in turn, are supported by research in basic scientific disciplines, computer science and technology, engineering, materials science, and physics.

The laboratory has particular strengths in fields that industry may find valuable, such as scientific and engineering software, biotechnology, advanced materials, precision engineering, laser and electro-optic technology, microelectronics and instrumentation, and measurement technology.

Designated Scientific User Facilities

National Gene Library Project
National Magnetic Fusion Energy Computation
Center

Technology Transfer Contact

Mr. Gordon T. Longerbeam
Lawrence Livermore National Laboratory
P.O. Box 808, L795
Livermore, CA 94551
(415) 422-6416
FTS 532-6416

■ LOS ALAMOS NATIONAL LABORATORY

Los Alamos, New Mexico

*Operated by the University of California
FY 1990 Operating Budget \$950M
FY 1990 Staff 7,820*

Los Alamos

Los Alamos National Laboratory
Los Alamos, New Mexico 87545

Designated Scientific User Facilities

National Genetic Sequence Data Bank (GenBank)
National Flow Cytometry and Sorting Research
Resource
Clinton P. Anderson Meson Physics Facility
(LAMPF) (linear accelerator, biomedical electronics,
electrosurgery, implants, medical instrumentation,
and cancer therapy)
Weapons Neutron Research (WNR) Facility
Los Alamos National Environmental Research Park
National Stable Isotopes Research
Manuel Lujan Jr. Neutron Scattering Center

Technology Transfer Contact

Dr. Ronald E. Barks
Los Alamos National Laboratory
P.O. Box 1663, MS M-899
Los Alamos, NM 87545
(505) 667-3839
FTS 843-3839

Los Alamos National Laboratory's (LANL) primary mission is the application of science and technology to problems of national security, including the maintenance of a strong defense, the fulfillment of arms control commitments, and the guarantee of a secure energy supply for the future. LANL also undertakes multidisciplinary fundamental and applied research. Primary program areas are weapons, nuclear physics, nuclear materials production, magnetic fusion, human genome studies, environmental studies, oil recovery technology, and superconductivity.

Los Alamos has been designated one of three Superconductivity Pilot Centers to collaborate with industry in advancing high-temperature superconductivity technologies.

■ OAK RIDGE NATIONAL LABORATORY

Oak Ridge, Tennessee

Managed by Martin Marietta Energy Systems, Inc.

FY 1990 Operating Budget \$489M

FY 1990 Staff 4,527

ornl

The Oak Ridge National Laboratory (ORNL) is a large, multi-disciplinary research and development center whose primary mission is to carry out applied research and engineering development in fusion, fission, and other energy technologies and scientific research in basic physical and life sciences to underpin work in the energy technologies. A secondary mission of the ORNL is to use its resources to address other nationally important issues, such as hazardous and chemical wastes and nonnuclear defense technologies, when such work is closely related to the primary mission.

ORNL also designs and provides research facilities for the benefit of members of the scientific and technical community and is the site of 11 major user facilities and other unique resources for academic and industrial research. In addition, ORNL is a national and regional resource for the education and training of technical personnel and is one of the Southeast's major employers of technically trained graduates.

Designated Scientific User Facilities

Holifield Heavy Ion Research Facility
Oak Ridge Electron Linear Accelerator (ORELA)
Neutron Scattering Facility
Surface Modification and Characterization Laboratory
National Center for Small-Angle Scattering Research
Shared Research Equipment (SIRE)
Microanalysis Facility
Oak Ridge National Environmental Research Park
Roof Research Center
High-Temperature Materials Laboratory
Low-Temperature Neutron Irradiation Facility
High Flux Isotope Reactor

Technology Transfer Contact

Mr. Glen A. Prosser
Martin Marietta Energy Systems, Inc.
Oak Ridge National Laboratory
P.O. Box 2009
Oak Ridge, TN 37831-8218
(615) 574-4552
FTS 624-4552

■ PACIFIC NORTHWEST LABORATORY

Richland, Washington

*Operated by Battelle Memorial Institute
FY 1990 Operating Budget \$266M
FY 1990 Staff 3,340*

Designated Scientific User Facilities

Hanford National Environmental Research Park

Technology Transfer Contact

Mr. Mary Clement
Pacific Northwest Laboratory
P.O. Box 999
Richland, WA 99352
(509) 375-2789
FIS (509) 375-2789

The missions of the Pacific Northwest Laboratory (PNL) are the advancement of science and the rapid development and deployment of technology. As a DOE multiprogram laboratory, PNL has the staff and the facilities to carry out research and development activities in the physical, biological, chemical, environmental, materials, and computational sciences. Engineering capabilities at PNL are currently being applied in the development of technologies for waste management, environmental restoration, efficient energy usage, nuclear energy utilization, and national security. Transferring technology to users in the public and private sectors, developing and operating scientific user facilities for researchers from these sectors, and contributing to the enhancement of science and mathematics education are integral parts of PNL programmatic activities.

Current research and development activities at PNL focus on gaining scientific understanding of phenomena at the molecular level; improving the scientific understanding of subsurface contaminant transport and global environmental processes; characterizing and remediating hazardous waste sites; increasing energy efficiency in buildings and industrial processes; modernizing the Federal infrastructure, including the nuclear weapons complex; and linking research and development activities at universities, DOE laboratories, and industry to leverage Federal investments and enhance technology transfer.

PNL also provides technical support for activities at the DOE Hanford Site, including independent environmental surveillance and oversight.

■ SANDIA NATIONAL LABORATORIES

**Albuquerque, New Mexico
Livermore, California
Tonopah, Nevada**

*Operated by AT&T Technologies, Inc.
FY 1990 Operating Budget \$678M
FY 1990 Staff 9,019*

Sandia National Laboratories (SNL) applies its engineering and scientific capabilities to areas of national importance, including nuclear-weapons technology, energy research, and other programs that are in the national interest. In its nuclear-weapons programs, SNL performs research, development, engineering for production, and stockpile surveillance with particular emphases on nuclear-weapons safety and command and control. In the energy area, SNL performs research and development leading to improved concepts for recovering and using energy resources, for generating electricity, and for understanding the energy sciences. SNL is committed to enhancing the economic competitiveness of the United States by creating, developing, and transferring commercially valuable technology through cooperative arrangements with industry, universities, and other research institutions.

Designated Scientific User Facilities

Solar Thermal Test Center - Albuquerque
Combustion Research Facility - Livermore

Technology Transfer Contacts

Albuquerque:
Dr. Dan E. Arvizu
Technology Transfer & Industrial Relations
Department
Sandia National Laboratories
P.O. Box 5800
Albuquerque, NM 87185
(505) 845-8759
FTS 845-8759

Livermore:
Dr. T. Michael (Mike) Dyer
Technology Transfer Liaison
Division 8300A
Sandia National Laboratories
P.O. Box 969
Livermore, CA 94550
(415) 294-2678
FTS 234-2678

Major Single-Program Laboratories

■ AMES LABORATORY

Ames, Iowa

*Operated by Iowa State University
FY 1990 Operating Budget \$22M
FY 1990 Staff 400*

Designated User Facilities and Scientific Information Services

Materials Preparation Center
Coal Preparation and Characterization Facility

Technology Transfer and General Contact

Mr. Daniel E. Williams
Associate Director for Planning and Technology Application
Ames Laboratory
119 O & L Building
Iowa State University
Ames, IA 50011-3020
(515) 294-2635
FTS (515) 294-2635

High T_c Update

Dr. Ellen O. Feinberg
Ames Laboratory
12 Physics
Iowa State University
Ames, IA 50011-3020
(515) 294-3877
FTS (515) 294-3877

Ames Laboratory (Ames) conducts basic research in physical, chemical, materials, mathematical, and engineering sciences. Ames performs related studies in materials synthesis and processing, materials reliability, and nondestructive evaluation. This fundamental research program is maintained to provide solutions to energy production and utilization problems in the medium- to long-term regimes and to address other problems of national importance.

Primary program areas at Ames are basic energy sciences, fossil energy, high-energy physics, nuclear physics, environmental sciences, environmental restoration and waste management, nuclear energy research, and nuclear safeguards and security. Extensive interaction with Iowa State University is achieved through faculty appointments, graduate student training, science education, facility sharing, and technology transfer programs.

■ CONTINUOUS ELECTRON BEAM ACCELERATOR FACILITY

Newport News, Virginia

*Operated by the Southeastern Universities
Research Association (SURA)*

FY 1990 Construction Budget \$62.6M

FY 1990 Operating & Equipment

Budget \$18.8M

FY 1990 Staff 330

CEBAF
The Continuous Electron Beam Accelerator Facility

The Continuous Electron Beam Accelerator Facility (CEBAF) is being built as a national designated scientific user facility for nuclear physics research. When operational in 1994, CEBAF will enable scientists to study the structure of atomic nuclei with unprecedented precision. The technology for the superconducting radio-frequency accelerating cavity, which is the heart of the accelerator, has been successfully transferred to industry, where it is being produced in quantity. Some 338 cavities will be used in the machine. The computer-based accelerator control system, already operational on a small scale, has been adopted at other laboratories and is attracting the attention of industry.

Designated Scientific User Facilities

Entire Facility (under construction)

Technology Transfer Contact

Mr. Steven T. Corneliussen

CEBAF Project Management Office

Continuous Electron Beam Accelerator Facility

12000 Jefferson Avenue

Newport News, VA 23606

(804) 249-7782

FTS (804) 249-7582

■ FERMI NATIONAL ACCELERATOR LABORATORY

Batavia, Illinois

Operated by Universities Research Associates, Inc.

FY 1990 Operating Budget \$164M

FY 1990 Staff 2,185

Designated Scientific User Facilities

Entire facility including:

1,000 GeV Superconducting Accelerator System

Meson Experimental Area

Proton Experimental Area

Neutrino Experimental Area

Colliding Beam Areas

Antiproton Source

National Environmental Research Park

Technology Transfer Contact

Dr. Richard A. Carrigan, Jr.

Fermilab, MS-200

Box 500

Batavia, IL 60510

(708) 840-3333

FTS 370-3333

The primary research and development program area at Fermi National Accelerator Laboratory (Fermilab) is high-energy physics. In this program area, elementary particle physics is explored to broaden the understanding of the basic structure of matter. Improvement of accelerator design at Fermilab has resulted in numerous technical spin-offs: the development of superconductivity on an industrial scale, fast electronics and particle detector technology, and special computers and computer programs. The linear accelerator at Fermilab is used in cancer therapy, and the laboratory has become heavily involved in medical radiation therapy.

■ MORGANTOWN ENERGY TECHNOLOGY CENTER

Morgantown, West Virginia

*Operated by the U.S. Department of Energy
FY 1990 Operating Budget \$340M
FY 1990 Staff 276*

METC

The Morgantown Energy Technology Center (METC) conducts and manages research and development to enhance the use of U.S. fossil energy resources. Activities at METC focus on developing technologies to increase coal utilization in an environmentally acceptable manner, to extend the reserve base of natural gas and oil, and to provide economically and environmentally improved techniques for extracting energy from oil shales and tar sands. The goal of these activities is to expand the technology base for fossil energy production, conversion, and utilization. In addition to in-house research and development, other projects at METC are executed through contracts with industry and academia. METC has major mission responsibilities for the following fossil energy technologies: surface coal gasification, fluidized-bed combustion, gas stream cleanup, heat engines, fuel cells, instrumentation, components, waste management, underground coal gasification, Arctic and offshore research, unconventional gas recovery, oil shale, and tar sands. METC also shares major mission responsibilities for enhanced oil recovery, clean coal technology, and environmental protection.

Technology Transfer Contact

Ms. L. Carol Roberson
Morgantown Energy Technology Center
3610 Collins Ferry Road, MS-A05
Morgantown, WV 26507-0660
(304) 291-4308
FTS 923-4308

■ OAK RIDGE ASSOCIATED UNIVERSITIES

Oak Ridge, Tennessee

*Operated by Oak Ridge Associated
Universities*

FY 1990 Operating Budget \$46M

FY 1990 Staff 600

Technology Transfer Contact

Ms. Mary M. Loges

Office of General Counsel

Oak Ridge Associated Universities

P.O. Box 117

Oak Ridge, TN 37831-0117

(615) 576-3756

FIS 626-3756

Oak Ridge Associated Universities (ORAU) conducts research, development, and implementation to ensure that energy technologies are effectively used to meet our national energy challenges. ORAU's current emphases are to understand the positive and negative health impacts to individuals and societies resulting from man-made and natural substances, especially from energy and energy-related systems; to ensure that our educational systems produce the scientists, engineers, and technologists needed by society and a public that is literate about science and technology; to upgrade the knowledge base of the scientific, engineering, and technical work force that is vital to our economic health and national well-being; and to provide an integrated understanding of the interactions of our energy system and our environment.

Work at ORAU is concentrated in four major areas: science/engineering education, training and management systems, medical sciences, and energy/environmental systems.

■ PITTSBURGH ENERGY TECHNOLOGY CENTER

Pittsburgh, Pennsylvania

*Operated by the U.S. Department of Energy
FY 1990 Operating Budget \$162M
FY 1990 Staff 306*

The Pittsburgh Energy Technology Center (PETC) is responsible for the technical and administrative management of 12 primary mission research and development programs within the DOE Office of Fossil Energy. In addition to the Pittsburgh facility, PETC has administrative responsibilities for the petroleum and natural gas research and development programs at the National Institute of Petroleum and Energy Resources (NIPER) through the DOE Bartlesville, Oklahoma, Project Office. In conjunction with these program responsibilities, PETC has established a National Coal Technology Data Center where users may have access to government databases on coal research in PETC's lead laboratory areas. PETC's responsibilities are grouped within the following areas: environmental concerns (coal preparation, advanced combustion, flue gas cleanup, and alternative fuels), energy conversion (magnetohydrodynamics, coal liquefaction, and advanced research in liquefaction), and fundamental research (University Coal Research, solids transport, and direct utilization). PETC manages projects under the congressionally mandated Clean Coal Technology Program. In FY 1990, 28 projects worth approximately \$1.3 billion were assigned to PETC in its cognizant research and development areas.

Technology Transfer Contact

Ms. Kay Downey
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236
(412) 892-3029
FTS 723-6029

■ PRINCETON PLASMA PHYSICS LABORATORY

Princeton, New Jersey

*Operated by Princeton University
FY 1990 Operating Budget \$91M
FY 1990 Staff 800*

PPPL

Technology Transfer Contact

Dr. Joseph Eile
Princeton Plasma Physics Laboratory
P.O. Box 451
Princeton, NJ 08543
(609) 243-3009
FTS 340-3009

The primary mission of the Princeton Plasma Physics Laboratory (PPPL) is research in magnetic fusion, which is conducted using a Tokamak Fusion Test Reactor and associated experimental equipment. PPPL is a world leader in research and development aimed primarily at the use of magnetic fusion energy as a safe, economical, and environmentally acceptable method of generating electricity for the long term.

In support of the primary mission, extensive research and development is done in the following disciplines:

- Neutral Beam Technology
- Remote Handling of Nuclear Systems
- Plasma Engineering
- Plasma Diagnostics
- Surface Modification Technology
- Magnetic Field Systems
- RF Heating and Current Drive
- Tritium Handling and Storage/Delivery Systems
- Computer Systems
- Diagnostic Systems
- Theoretical and Applied Physics
- Soft X-Ray Development
- Space Glow and Erosion Experiment.

■ SAVANNAH RIVER LABORATORY

Aiken, South Carolina

*Operated by Westinghouse Savannah
River Company*

FY 1990 Operating Budget \$190M

FY 1990 Staff 1,365

SRL

The Savannah River Laboratory (SRL) provides development and technical assistance in all areas of nuclear reactor technology and the nuclear fuel cycle, including fuel fabrication, robotics technology, isotope production, reactor physics and engineering, fuel reprocessing, waste management, and environmental monitoring. The primary program areas at SRL are nuclear materials production and defense waste management.

Technology Transfer Contact

Dr. John C. Corey
Savannah River Laboratory
Westinghouse Savannah River Company
P.O. Box 616
Aiken, SC 29808
(803) 725-3020
FTS 239-3020

■ SOLAR ENERGY RESEARCH INSTITUTE

Golden, Colorado

*Operated by Midwest Research Institute
FY 1990 Operating Budget \$69M
FY 1990 Staff 487*

Technology Transfer Contact

Mr. H. Dana Moran
Solar Energy Research Institute
1617 Cole Boulevard
Golden, CO 80401
(303) 231-7115
FTS 327-7115

The Solar Energy Research Institute (SERI) conducts basic and applied research in the physical, chemical, biological, and engineering sciences pertinent to solar and renewable energy resources. Research activities are carried out in three divisions. The Solar Electric Division is responsible for studies in photovoltaics, wind energy conversion, and resource assessment. The Solar Fuels Division conducts and manages research in aquatic species, biochemical conversion, alcohol fuels, and energy from municipal waste. The Solar Heat Division performs research in solar thermal processes, buildings energy management, conservation, ocean thermal energy, thermal energy storage, and advanced materials systems.

■ STANFORD LINEAR ACCELERATOR CENTER

Stanford, California

*Operated by Stanford University
FY 1990 Operating Budget \$119M
FY 1990 Staff 1,565*

The Stanford Linear Accelerator Center (SLAC) is dedicated to experimental and theoretical research in elementary-particle physics and to the development of new technologies for high-energy accelerators and elementary-particle detectors.

Designated Scientific User Facilities

SLC: a 100-GeV (center of mass) linear electron/positron collider
SPEAR: an 8-GeV colliding beam, storage-ring facility, 80 meters in diameter
PEP: a 32-GeV colliding-beam, storage-ring facility, 800 meters in diameter

Technology Transfer Contact

Mr. James E. Simpson
Stanford Linear Accelerator Center
P.O. Box 4349
Stanford, CA 94309
(415) 926-2213
FTS 462-2213

■ WESTINGHOUSE HANFORD COMPANY

Richland, Washington

*Operated by Westinghouse Electric
Corporation*

FY 1990 Operating Budget \$720M

FY 1990 Staff 9,400

**Westinghouse
Hanford Company**

Technology Transfer Contact

Mr. Fred R. Reich
Westinghouse Hanford Company
P.O. Box 1970
Richland, WA 99352
(509) 376-4063
FYS 444-4063

Westinghouse Hanford Company (WHC) is the operations and engineering contractor for the DOE Hanford Site. WHC carries out national missions of the site, including energy research and technology, defense materials production, management and disposal of radioactive waste, and environmental, health, and safety studies. The Fast Flux Test Facility (FFTF), which is operated by WHC, is a 400-megawatt, sodium-cooled, fast-neutron-flux reactor providing a full-scale irradiation test environment for advanced reactors and space applications and operating experience that is relevant to the commercial nuclear power industry. Testing in the FFTF includes the irradiation of materials for the SP-100 Space Reactor System, advanced fusion concepts, and isotope production. The fast spectrum of the FFTF is ideal for the generation of special isotopes that can be used with monoclonal antibodies in the diagnosis and treatment of cancer. Experience gained at the FFTF with 12-hour operator shifts and computerized maintenance scheduling is relevant to commercial industries, including non-nuclear facilities. Scientists and engineers are also developing ways, using the transmutation capabilities of high-energy neutrons, to permanently dispose of nuclear waste generated by defense materials production and research activities. The waste surveillance, disposal, and cleanup activities ongoing at Hanford are generating a whole new technology base at the site. The waste cleanup activities and the technologies of the FFTF are being made available to other government agencies and the U.S. private business sector through the DOE Technology Transfer Program.

Other DOE Laboratories

The William H. Bates Linear Accelerator Center, which is operated by the Massachusetts Institute of Technology for the DOE, has two primary objectives: 1) production of experimental data in medium-energy nuclear physics and 2) the education of highly trained scientists for employment at universities, DOE laboratories, and industry.

A high-intensity, high-resolution electron beam (1 GeV) is used to study nuclear properties. Programs are currently underway to measure charge, current, and magnetization distributions; photoreactions; coincidence reactions; and polarized beam interactions.

There are about 200 active participants from over 50 institutions in the research program. The center has produced 5 to 10 percent of the Nation's PhDs in nuclear physics over the past few years.

The Energy Technology Engineering Center (ETEC) tests components being developed for the U.S. liquid-metal reactor program. ETEC maintains and operates liquid-metal test facilities for evaluating components, such as heat exchangers, steam generators, pumps, valves, piping, vessels, and instrumentation. Primary program areas at ETEC are nuclear energy, conservation, and renewable energy.

The mission of the Environmental Measurements Laboratory (EML) is to conduct environmental research concerning pollutants associated with energy technologies and related national security activities, principally for the purpose of providing the scientific information required to determine the consequent effects on human health and the environment.

■ BATES LINEAR ACCELERATOR CENTER

*FY 1990 Operating Budget \$10.3M
FY 1990 Staff 91*

Technology Transfer Contact

Mr. William Lobar
Bates Linear Accelerator Center
P.O. Box 846
Middleton, MA 01949
(617) 245-6600

■ ENERGY TECHNOLOGY ENGINEERING CENTER

*FY 1990 Operating Budget \$24M
FY 1990 Staff 140*

Technology Transfer Contact

Mr. Guy Ervin III
Energy Technology Engineering Center
P.O. Box 1449
Canoga Park, CA 91304
(818) 586-5532

■ ENVIRONMENTAL MEASUREMENTS LABORATORY

*FY 1990 Operating Budget \$8.5M
FY 1990 Staff 90*

Technology Transfer Contact

Dr. Gail de Planque
U. S. Department of Energy
Environmental Measurements Laboratory
376 Hudson Street
New York, NY 10014-3621
(212) 620-3616
FTS 660-3619

■ INHALATION TOXICOLOGY RESEARCH INSTITUTE

FY 1990 Operating Budget \$13.9M
FY 1990 Staff 208

Technology Transfer Contact

Dr. Robert K. Jones
Inhalation Toxicology Research Institute
P.O. Box 5890
Albuquerque, NM 87185
(505) 844-2502
FTS 844-2502

■ LABORATORY OF RADIOBIOLOGY AND ENVIRONMENTAL HEALTH

FY 1990 Operating Budget \$3.3M
FY 1990 Staff 44

Technology Transfer Contact

Ms. Penelope Tucker
Laboratory of Radiobiology and Environmental
Health
University of California, San Francisco
Box 0750
San Francisco, CA 94143-0750
(415) 476-1639

The mission of the Inhalation Toxicology Research Institute (ITRI) is to conduct basic and applied research to improve understanding of the nature and magnitude of the human health impacts of inhaling airborne materials in the home, workplace, and general environment. Research programs at ITRI have a strong basic science orientation with emphasis on the nature and behavior of airborne materials, the fundamental mechanisms by which they cause disease, and the means by which data produced in the laboratory can be used to estimate risks to human health. As the largest laboratory dedicated to the study of basic inhalation toxicology, ITRI provides a national resource of specialized facilities, personnel, and educational activities serving the needs of government, academia, and industry.

The Laboratory of Radiobiology and Environmental Health is a basic research institute in cell biology dedicated to gaining fundamental information that can be used to gain insights into how radiation and other energy-related biomedical insults affect normal cellular processes and lead to detrimental genetic and somatic biomedical effects. At present the Laboratory has five separate but interrelated groups studying cell biology starting from the point of view of DNA replication and progressing through DNA repair, chromosomal effects and cytogenetics, the cellular structure, and physiology of the macrophage system, to developmental biology. The purpose of these studies is to gain a fundamental understanding of the mechanisms by which perturbation and repair of these cellular systems can affect the whole organism, lead to damage that affects future generations, or even lead to cancer in the present generation, and especially how the organism can cope with such insults.

The mission of the Michigan State University-DOE Plant Research Laboratory is to conduct interdisciplinary research and provide training to graduate students and postdoctoral research associates in the plant sciences based on technology from molecular genetics, biophysics, biochemistry, and physiology.

The primary mission of the National Institute for Petroleum and Energy Research (NIPER) is to support the DOE Office of Fossil Energy Research programs in areas of enhanced oil recovery and advanced extraction and process technology. The operating agreement with DOE has been very effective in merging DOE-supported research with the needs of other government agencies and industry. It also ensures timely transfer and rapid dissemination of newly acquired technical information to the private sector.

New Brunswick Laboratory is a government-owned, government-operated laboratory. Its mission is to provide and maintain a Nuclear Material Measurement and Standards Laboratory as a technical response to DOE's statutory responsibility for assuring the safeguarding of nuclear materials.

■ **MICHIGAN STATE
UNIVERSITY-DOE
PLANT RESEARCH
LABORATORY**

*FY 1990 Operating Budget \$2.4M
FY 1990 Staff 30*

Technology Transfer Contact

Ms. Alice J. Albin
MSU-DOE Plant Research Laboratory
Room 106 Plant Biology
Michigan State University
East Lansing, MI 48824-1312
(517) 353-2270
FTS 353-2270

■ **NATIONAL INSTITUTE
FOR PETROLEUM AND
ENERGY RESEARCH**

*FY 1990 Operating Budget \$4.8M
FY 1990 Staff 175*

Technology Transfer Contact

Mr. Herb A. Tiedemann
U.S. Department of Energy
Bartlesville Project Office
P.O. Box 1398
Bartlesville, OK 74005
(918) 337-4293

■ **NEW BRUNSWICK
LABORATORY**

*FY 1990 Operating Budget \$4.3M
FY 1990 Staff 46*

Technology Transfer Contact

Dr. Carleton D. Bingham
U.S. Department of Energy
New Brunswick Laboratory
9800 South Cass Avenue
Argonne, IL 60439
(708) 972-2446
FTS 972-2446

■ NOTRE DAME RADIATION LABORATORY

FY 1990 Operating Budget \$3.2M

FY 1990 Staff 54

Technology Transfer Contact

Dr. John Bentley
Notre Dame Radiation Laboratory
Notre Dame, IN 46556-0768
(219) 239-6117

■ SAVANNAH RIVER ECOLOGY LABORATORY

FY 1990 Operating Budget \$8.0M

FY 1990 Staff 150

Technology Transfer Contact

Mr. Robert L. Nestor
Savannah River Ecology Laboratory
The University of Georgia
Drawer E
Aiken, SC 29802
(803) 725-2472
FTS 239-2472

■ STANFORD SYNCHROTRON RADIATION LABORATORY

FY 1990 Operating Budget \$10.6M

FY 1990 Staff 100

Technology Transfer Contact

Ms. Katherine Cantwell
Stanford Synchrotron Radiation Laboratory
P.O. Box 4349, Bin 69
Stanford, CA 94309
(415) 926-3191
FTS 462-3191

The Notre Dame Radiation Laboratory conducts fundamental research on the chemical processes that result from bombarding matter with ionizing radiation or light. Its particular emphasis is on the kinetics and mechanisms of reactions involving short-lived molecular species (e.g., free radicals or excited molecules), with emphasis on reactions in solution or on surfaces.

The mission of the Savannah River Ecology Laboratory (SREL) is to acquire and communicate knowledge of ecological processes and principles. The cornerstones of the SREL program are research, education, and service.

The mission of Stanford Synchrotron Radiation Laboratory is to perform research with synchrotron radiation; to develop, implement, maintain, and operate existing, new, and improved sources of synchrotron radiation; and to develop and advance new techniques for the use of synchrotron radiation in scientific and technological experimentation.

OFFICE OF SCIENTIFIC AND TECHNICAL INFORMATION

The DOE Office of Scientific and Technical Information (OSTI) collects, organizes, and disseminates the results of DOE's \$6 billion-per-year research and development program and combines these data with domestic and foreign information necessary for DOE researchers to conduct their work. This information is stored in the world's most comprehensive group of databases on energy. DOE scientific and technical information is available in the form of technical reports, on-line retrieval systems, and announcement publications. This information is shared with other government agencies and is made available to the private sector.

Application Assessments

(New Technology from DOE)
U.S. Department of Energy
Office of Scientific and Technical Information
Information Analysis and Management Division
P.O. Box 62
Oak Ridge, TN 37831
(615) 576-1223
FTS 626-1223

Energy Science and Technology Database

DIALOG Information Services
3460 Hillview Avenue
Palo Alto, CA 93404
(800) 334-2564

STN International

2540 Olentangy River Road
P.O. Box 02228
Columbus, OH 43202
(800) 848-6533

Superconductivity Information Service

Office of Scientific and Technical Information
Technical Services
P.O. Box 62
Oak Ridge, TN 37831
(615) 576-1222
FTS 626-1222

Documents - DOE and DOE Contractors

Office of Scientific and Technical
Information
P.O. Box 62
Oak Ridge, TN 37831
(615) 576-8401
FTS 626-8401

Documents - Industry, Academia, Others

National Technical Information Service
U.S. Department of Energy
5285 Port Royal Road
Springfield, VA 22161
(703) 487-4650

Software - National Energy Software Center

Argonne National Laboratory
9700 S. Cass Avenue
Argonne, IL 60439
(312) 972-7250
FTS 972-7250

END

DATE FILMED

06 / 04 / 91