RECEIVED BY OSTI

JUN 18 1985

MAGNUM-2D Computer Code: Users Guide

January 1985

Richard L. England
Niall W. Kline
BCS Richland, Inc.

Karen J. Ekblad
BCS Seattle, Inc.

Robert G. Baca
Rockwell Hanford Operations

Prepared for Rockwell Hanford Operations,
a Prime Contractor to the U.S. Department of Energy
under Contract DE-AC06-77RL01030

Rockwell International

Rockwell Hanford Operations
Richland, Washington

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United States of America

DO NOT MICROFILM
COVER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RHO-BW-CR-143

MAGNUM-2D Computer Code: Users Guide

Date Manuscript Completed: January 1985

Richard L. England
Niall W. Kline
BSC Richland, Inc.

RHO-BW-CR--143P

Karen J. Ekblad
BSC Seattle, Inc.

DE85 013315

Robert G. Baca
Rockwell Hanford Operations

Prepared for Rockwell Hanford Operations,
a Prime Contractor to the U.S. Department of Energy
under Contract DE-AC06-77RL01030

Rockwell International

Rockwell Hanford Operations
P.O. Box 800
Richland, Washington 99352

MASTER

jsu

ABSTRACT

In this report, information relevant to the general use of the MAGNUM-2D computer code is presented. This computer code was developed for the purpose of modeling (i.e., simulating) the thermal and hydraulic conditions in the vicinity of a waste package emplaced in a deep geologic repository. The MAGNUM-2D code computes (1) the temperature field surrounding the waste package as a function of the heat generation rate of the nuclear waste and thermal properties of the basalt and (2) the hydraulic head distribution and associated groundwater flow fields as a function of the temperature gradients and hydraulic properties of the basalt.

MAGNUM-2D is a two-dimensional numerical model for transient or steady-state analysis of coupled heat transfer and groundwater flow in a fractured porous medium. The governing equations consist of a set of coupled, quasi-linear partial differential equations that are solved using a Galerkin finite-element technique. A Newton-Raphson algorithm is embedded in the Galerkin functional to formulate the problem in terms of the incremental changes in the dependent variables. Both triangular and quadrilateral finite elements are used to represent the continuum portions of the spatial domain. Line elements may be used to represent discrete conduits.

CONTENTS

1.0	Introduction	1
1.1	Background	1
1.2	Purpose and Scope	2
2.0	Mathematical Framework	2
2.1	Governing Equations	2
2.2	Spatial Discretization	6
2.3	Initial Conditions	9
2.4	Boundary Conditions	9
2.5	Numerical Solution Method	10
3.0	General Input Considerations	12
3.1	Model Generation	12
3.2	Element Types	13
3.3	Initial Conditions	14
3.4	Boundary Conditions	15
3.5	Heat Sources	15
3.6	Time Stepping	17
3.7	Simulation Restart	19
3.8	Execution Control	20
3.9	Data Input Records	20
4.0	Input Preparation	23
4.1	Introduction	23
4.2	Input Data Description and Discussion	23
4.3	Input Data Format Summary	35
5.0	Output	41
5.1	Introduction	41
5.2	Printed Report	41
5.2.1	Banner Page	41
5.2.2	Input Verification	42
5.2.3	Simulation Results	43
5.2.4	Gauss Point Locations	43
5.3	Other Output Files	43
6.0	Nomenclature	45
7.0	References	47
Appendixes:		
A.	Program Internals	A-1
B.	Preprocessors	B-1
C.	Postprocessors	C-1
D.	Example Cases	D-1
E.	Diagnostic Messages	E-1

FIGURES:

1. Locations of Nodes and Gauss Points for
Quadratic-Shape Functions 7
2. Locations of Nodes and Gauss Points for
Linear-Shape Functions. 8
3. Typical Volumetric Heat Generation Profile 16
4. Gauss Points in Local Coordinates for Quadratic Elements . . 44

TABLES:

1. Coefficients of Relative Heat Generation 17

1.0 INTRODUCTION

1.1 BACKGROUND

A suite of numerical models (i.e., computer codes) has been developed and interfaced for use in assessing the long-term isolation performance of a repository in basalt (DOE 1982). These models are based primarily on deterministic approaches (Estey et al. 1985; Kline et al. 1983); however, certain codes are formulated on a probabilistic framework (Baca et al. 1984b; Sagar and Clifton 1983; Clifton et al. 1983). The numerical models are grouped by space scale into three categories:

1. Waste package scale (very near-field) models
2. Repository scale (near-field) models
3. Regional scale (far-field) models.

The waste package scale models provide predictions of the temperature and flow field around the waste package and radionuclide release rates from the waste package and/or emplacement horizon. The repository scale models are designed to calculate groundwater flow paths and traveltimes, the large-scale temperature field around the repository, and radionuclide concentrations and releases. Results from the repository scale analysis provide boundary conditions for regional scale predictions of groundwater traveltimes to and cumulative releases at the boundary of the accessible environment.

This report focuses on one of the deterministic waste package scale models designated as MAGNUM-2D. The MAGNUM-2D code is a two-dimensional finite-element code applicable to a fractured porous medium. This computer code is capable of simulating the coupled or uncoupled processes of heat transfer in a water/rock system and groundwater flow in an inhomogeneous anisotropic medium. In addition, it provides the capability of simulating flow in discrete conduits or fractures (macroscale discontinuities). The conceptual modeling approach is based on representing the physical system by a two-dimensional cross section. Three-dimensional systems with axial symmetry can also be modeled with MAGNUM-2D. A set of support codes and graphics software has been developed and interfaced with the MAGNUM-2D code to (1) generate, manipulate, and display the finite-element grid; (2) compute and plot pathlines/streamlines and traveltimes; and (3) plot contours, spatial cross sections, and time histories for temperature and hydraulic head. In addition, the data files generated by MAGNUM-2D are arranged to be used directly by the CHAINT computer code (Baca et al. 1984a), which simulates the transport of dissolved radionuclides.

This users guide provides detailed instructions regarding the use of the MAGNUM-2D computer code for waste package scale analysis of coupled groundwater flow and heat transfer. It also contains descriptions of input data requirements, as well as sample input and output for test cases.

1.2 PURPOSE AND SCOPE

The MAGNUM-2D computer code was developed by the Basalt Waste Isolation Project (BWIP) at Rockwell Hanford Operations (Rockwell) for use in studies of nuclear waste disposal in deep geologic repositories (Baca et al. 1984a, 1984b; Baca et al. 1981). Subsequent enhancements as well as ongoing maintenance are provided by Boeing Computer Services Richland, Inc., Richland, Washington. This document is intended to serve as a users guide for version 3.1 of the code as it exists at the BWIP computing facility. It is noteworthy that earlier versions of MAGNUM-2D have been implemented on a UNIVAC 1100/44 and a CRAY 1, as well as PRIME minicomputers. The current version is installed on a PRIME 750 minicomputer network. Although the BWIP version of MAGNUM-2D is maintained and used in a PRIME operating environment, transportability of the code has been given high priority. Features of the current version of the MAGNUM-2D computer code as described herein are machine independent except for the isolated service subroutines noted in Appendix A.

The format and content of this users guide are with respect to guidance given by the U.S. Nuclear Regulatory Commission (Silling 1983). The partial differential equations solved by MAGNUM-2D and the numerical method are discussed in Section 2.0. The general usage considerations and capabilities are discussed in Section 3.0, while detailed instructions for inputting a given problem are given in Section 4.0. The output obtainable from MAGNUM-2D is described in Section 5.0. The possible machine/environment dependencies are discussed in Appendix A. Included as Appendixes B and C are descriptions and short discussions of several preprocessors and postprocessors that may be used to assist in preparation of the input data for MAGNUM-2D and the interpretation of the output data. The input data and output listings for some example problems, along with examples of plots generated by preprocessor and postprocessor graphics programs, are given in Appendix D. Diagnostic messages generated by MAGNUM-2D are tabulated in Appendix E.

2.0 MATHEMATICAL FRAMEWORK

2.1 GOVERNING EQUATIONS

The MAGNUM-2D computer code is designed to simulate steady-state and time-dependent coupled processes of buoyancy-driven fluid flow in a fractured porous medium and advective and conductive heat transfer in a porous continuum. The code is applicable to problems that can be formulated in two dimensions over rectangular or axially symmetric cylindrical domains. The mathematical model is founded on the physical laws of fluid continuity and conservation of momentum and energy (Fahien 1983; Malvern 1969). Discussions on the theoretical bases may be found in Baca et al. (1984a); however, for completeness, the governing equations are also given here.

The equation governing nonisothermal flow balance in a porous continuum as written in indicial notation for a Cartesian coordinate system is.

$$S_s \frac{\partial h}{\partial t} = \frac{\partial}{\partial x_i} \left[K_{ij} \left(\frac{\partial h}{\partial x_j} + \delta_b \delta_{i2} \right) \right] + \gamma \frac{\partial T}{\partial t} \quad (1)$$

where

S_s = specific storage of the porous rock matrix

h = hydraulic head

t = the time coordinate

x_i = space coordinates (x,y)

K_{ij} = principal hydraulic conductivities of the rock matrix
(K_{xx} and K_{yy})

δ_b = density disparity

δ_{i2} = the Kronecker delta

γ = thermal coupling coefficient

T = temperature of the water/rock system.

Note that the principal axes of the hydraulic conductivity tensor are assumed to coincide with the coordinate axes and, hence, only components of flow in the principal directions are considered. Furthermore, the density disparity and thermal coupling coefficient are given by

$$\delta_b = \frac{\rho - \rho_0}{\rho^*} \quad (2)$$

and

$$\gamma = \phi \beta, \text{ respectively} \quad (3)$$

where

ρ = fluid density as a function of location (x,y) and time

ρ_0 = initial fluid density as a function of vertical location (y)

ρ^* = reference fluid density

ϕ = effective porosity

β = bulk modulus of fluid.

The equation governing nonisothermal flow balance in a fracture as written for a local one-dimensional coordinate system is

$$S_f \frac{\partial h}{\partial t} = \frac{\partial}{\partial L} \left[K_f \left(\frac{\partial h}{\partial L} + \delta_b' \right) \right] + \gamma \frac{\partial T}{\partial t} \quad (4)$$

where

S_f = specific storage in the fracture

L = local space coordinate

K_f = hydraulic conductivity of (filled or unfilled) fracture

δ_b' = component of the density disparity along L .

For an unfilled fracture, the hydraulic conductivity is determined by (Snow 1969)

$$K_f = \frac{ge^2}{12\nu} \quad (5)$$

where

g = acceleration due to gravity

e = fracture aperture

ν = kinematic viscosity of the fluid.

Under the assumption that the fluid and rock mass are in thermal equilibrium at all times (Combarous and Bories 1975), the governing thermal energy balance equation written for Cartesian coordinates using indicial notation is

$$S_t \frac{\partial T}{\partial t} + \rho c_f q_i \frac{\partial T}{\partial x_i} = \frac{\partial}{\partial x_i} \left(D_{ti} \frac{\partial T}{\partial x_j} \right) + Q \quad (6)$$

where

S_t = heat capacity of the fluid/rock system

c_f = specific heat of the fluid

q_i = component of the Darcy velocity vector $\left(-K_{ij} \frac{\partial h}{\partial x_j}\right)$

D_{ti} = effective thermal conductivity

Q = volumetric rate of heat generation.

Moreover,

$$S_t = \phi \rho c_f + (1-\phi) \rho_s c_s \quad (7)$$

where

ρ_s = bulk density of the rock

c_s = specific heat of the rock,

and

$$D_{tx} = \phi D_f + (1-\phi) D_{sx} + \left(\alpha_L q_x^2 + \alpha_T q_y^2 \right) \frac{\rho c_f}{\bar{q}} \quad (8)$$

and

$$D_{ty} = \phi D_f + (1-\phi) D_{sy} + \left(\alpha_T q_x^2 + \alpha_L q_y^2 \right) \frac{\rho c_f}{\bar{q}} \quad (9)$$

where

D_f = thermal conductivity of the fluid

D_s = thermal conductivity of the rock

α_L = longitudinal dispersivity

α_T = transverse dispersivity

$\bar{q} = (q_x^2 + q_y^2)^{1/2}$, the groundwater speed.

Again, as with the flow equation, cross-product terms are assumed to be negligible. Heat transfer along a fracture is handled analogously to flow in the fracture (i.e., in one dimension).

The MAGNUM-2D computer code is programmed to solve the governing equations in Cartesian or radial coordinates (Eq. 1, 4, and 6) subject to initial and boundary conditions using a Galerkin finite-element method. The flow equations are solved simultaneously. The flow and heat transfer equations are solved in alternating sequence. The units of the constants, coefficients, and state variables are given in the nomenclature list comprising Section 6.0.

2.2 SPATIAL DISCRETIZATION

The finite-element method employed by MAGNUM-2D in solution of the governing equations (Eq. 1, 4, and 6) is implemented in a fashion that affords substantial flexibility in discretization of the spatial domain. An arbitrarily shaped planar domain may be discretized over a Cartesian global coordinate system as long as it is topologically connected and has a continuous boundary. A bounded disk, cylinder, or annulus may be discretized over a radial global coordinate system. In practice, this latter case amounts to representation of a vertical cross section in Cartesian coordinates and specification of an appropriate angle of revolution. Note that in a radial coordinate system, a line element superimposed on a vertical cross section of a cylinder defines a surface intersecting the cylinder.

Linear or quadratic Lagrangian one-dimensional elements (Huyakorn and Pinder 1983) may be used to represent a one-dimensional domain. Isoparametric triangular and/or serendipity elements (Huyakorn and Pinder 1983) may be used in combination with line elements for discretization of a two-dimensional domain. Both linear and quadratic Lagrangian shape functions may be used with the two-dimensional elements as well.

Typical one- and two-dimensional elements show the placement of nodes (denoted by Roman numerals) and Gauss points (denoted by Arabic numerals) for quadratic-shape functions in Figure 1 and the same for linear-shape functions in Figure 2. Note that the transport variables, h and T , are defined at the nodes, and the Darcy velocities, U and V , are defined at the Gauss points.

Guidance for selection of element types and shape functions is provided in Sections 3.1 and 3.2. Detailed descriptions of MAGNUM-2D input options and formats are given in Section 4.0. Automated procedures for construction of a complete finite-element grid system is outlined in Appendix B. Two-dimensional plots of a grid system used for an example problem may be found in Appendix D.

(a)

(b)

(c)

PS84-2131-1

FIGURE 1. Locations of Nodes and Gauss Points for Quadratic-Shape Functions (a) Quadrilateral Element, (b) Triangular Element, and (c) Line Element.

(a)

(b)

(c)

PS84-2131-2

FIGURE 2. Locations of Nodes and Gauss Points for Linear-Shape Functions (a) Quadrilateral Element, (b) Triangular Element, and (c) Line Element.

2.3 INITIAL CONDITIONS

Solutions of the governing equations (Eq. 1, 4, and 6) are dependent upon the initial conditions of the state variables h and T . To facilitate the present as well as later discussions, let F denote a generalized state variable (i.e., either h or T) and let F_k^0 denote the value of F at the k^{th} node at the 0^{th} time step. Then, a global initial condition may be written

$$F_k^0 = \text{constant}, \quad 1 \leq k \leq \text{NP} \quad (10)$$

where NP denotes the total number of nodes in the spatial domain. If no initial conditions are specified for F , then Equation 10 is assumed where the constant is taken to be zero. Explicit specification of the above form (Eq. 10) is easily accomplished according to instructions given in Section 4.0. Alternately, a spatially varying initial condition may be written

$$F_k^0 = F(x_k, y_k, t^0), \quad 1 \leq k \leq \text{NP}. \quad (11)$$

Use of this form requires specification of the initial value of F at each node. Manual setup of the input corresponding to this form (Eq. 11) can be tedious if NP is large, and hence there exists a preprocessor that provides automated generation of an initial condition file as described in Appendix B.

The foregoing description of initial conditions is germane to transient analysis of fluid flow and/or heat transfer. However, MAGNUM-2D is also equipped to perform steady-state solution of the governing equations. In this case, starting values for solution of the steady-state distribution of F may be specified in the same manner as initial conditions.

2.4 BOUNDARY CONDITIONS

The MAGNUM-2D computer code is generally applicable to problems involving solution of Equations 1, 4, and 6 over a domain meeting the requirements given in Section 2.2. However, MAGNUM-2D is utilized primarily in the analysis of waste package scale phenomena. At this scale differentials (i.e., gradients) are typically small, and hence the default boundary condition for F is taken from

$$\left. \frac{\partial F}{\partial z} \right|_{x=x_B, y=y_B} = 0 \quad (12)$$

where (x_B, y_B) denotes a boundary node and z is a coordinate normal to the boundary. Optionally, one may specify a Dirichlet boundary condition for F at any boundary node.

Formatting of input for optional boundary conditions can prove to be tedious. To further facilitate the setup of a MAGNUM-2D simulation, a preprocessor is available to generate a boundary condition file as described in Appendix B.

2.5 NUMERICAL SOLUTION METHOD

The finite-element method employed by MAGNUM-2D in solution of the governing equations (Eq. 1, 4, and 6) is based on a Galerkin approach (Huyakorn and Pinder 1983). A substantial derivation of the method is given by Baca et al. (1984a). A summary, along with complementary details, is provided in the following paragraphs.

Consider an arbitrarily selected element containing m nodes. Then an approximation to F over the element is written

$$F \doteq \sum_{k=1}^m \omega_k F_k \quad (13)$$

where ω denotes a shape function. Let ϵ denote the error due to the approximation (Eq. 13). Then the Galerkin approach to weighted residuals is based on minimization of the error, ϵ , through the functional

$$\chi = \int_E \omega_k \epsilon dE \quad (14)$$

where E is the current element. The finite-element equations are formulated in terms of incremental change in F by using a Newton-Raphson algorithm for ϵ in Equation 14 (Baca et al. 1978, 1984a). Communication between fractures and the porous continuum is achieved by superposition which amounts to summing the functionals for hydraulic head in a continuum element and hydraulic head in an adjacent fracture.

Expansion of terms for the system of finite-element equations derived for a single element is illustrated by Baca et al. (1984a). Derivatives of F with respect to time as occur in the element equations are approximated by linear combinations of differences over incremental times written

$$\left. \frac{\partial F^{l+1}}{\partial t} \right|_{t=t^{l+1}} \doteq \theta \frac{F^{l+1} - F^l}{t^{l+1} - t^l} + (1-\theta) \frac{\partial F^l}{\partial t}. \quad (15)$$

The value of F^{l+1} as used in Equation 15 is calculated from a non-iterated Hermite-Milne predictor-corrector method characterized by the two stages

$$F^{l+1} = -4F^l + 5F^{l-1} + (t^{l+1} - t^l) \left(4 \frac{\partial F^l}{\partial t} + 2 \frac{\partial F^{l-1}}{\partial t} \right) \quad (16)$$

and

$$F^{l+1*} = F^{l-1} + \frac{t^{l+1} - t^l}{3} \left(\frac{\partial F^{l+1}}{\partial t} + 4 \frac{\partial F^l}{\partial t} + \frac{\partial F^{l-1}}{\partial t} \right) \quad (17)$$

where F^{l+1*} is the corrected value of F^{l+1} .

The weighting factor, θ , in Equation 15 may be specified by the user. Suggested values range between one and two; a value of one corresponds to a first order backward difference approximation, whereas a value of two corresponds to a second order backward difference approximation.

Assembly of the blocks of element equations yields a banded system of linear algebraic equations that is solved using a Gaussian frontal-solution technique. The frontwidth of the system is a factor in the amount of memory and processing time needed to solve the system of equations (Irons and Ahmad 1980). In turn, the frontwidth is dependent upon element numbering. Hence, as described in Appendix B, there is a preprocessor available to optimize the element numbering in the respect that the frontwidth is minimized.

3.0 GENERAL INPUT CONSIDERATIONS

3.1 MODEL GENERATION

The generation of a finite-element model requires careful consideration of the processes being simulated and the limitations of the finite-element technique. Detailed consideration of these points is outside the scope of this document. It is assumed that the user is versed in finite-element applications and thus needs only a discussion of the use of this particular code.

In general, the majority of the time required in formulation and generation of a finite-element model is spent in developing the grid that represents the physical domain. This consists of determination of the points that define the corners of the elements and specification of the connectivity that defines the set of nodes describing each element.

One of the advantages of the finite-element approach used in MAGNUM-2D is that it permits the use of a "graded" mesh. A graded mesh is a variable computational grid that is coarse in areas of low gradients and is fine in areas of high gradients. The significance of the graded mesh is that it permits accurate representation of the spatial domain and its boundaries, and it minimizes the space truncation error, thus optimizing the computational problem. Selection of the mesh layout is, therefore, one of the most important steps in applying the code.

Mesh generation for a practical simulation problem is generally an iterative process. For problems of coupled heat and flow, the numerical solution of the flow equations (Eq. 1 and 4) usually requires the finer mesh layout (i.e., greater spatial resolution). The generation process begins with a trial mesh layout that is selected to conform with the anticipated solution field(s) and system boundaries. A test simulation is performed with MAGNUM-2D, and the results are analyzed. For cases involving fluid flow, the pathlines are calculated, plotted, and checked. From these initial results, the grid is refined as needed. This process is repeated until the simulation results show convergence to a reasonable solution.

Time may be saved in the geometry definition phase of the problem formulation by making use of the preprocessing utilities described in the appendixes, specifically, GEN and FEMESH to generate the mesh, MESHER to optimize it, PURGE to verify it, and BCGEN to identify the boundary nodes. In addition, there is a processor called PLT that displays the geometry on a graphics terminal and a family of postprocessors that assist in the analysis of the output data.

The following guidelines should be considered in generating a two-dimensional finite-element mesh.

- Quadrilateral elements should be used for most of the mesh, and if necessary, triangular elements should be used for transition regions; line elements are used for discrete fractures.
- Element aspect ratios should not exceed roughly 100.
- Midside nodes should be located in the middle third of the element side or length.
- The element numbering sequence should be continuous and should begin along the side of the grid with the fewest elements.

The MAGNUM-2D computer code uses a frontal solution algorithm developed by Hood (1976) to solve unsymmetric finite-element matrix equations. This technique is an implementation of Gaussian elimination in which the assembly of equations alternates with their solution. With respect to accuracy, the algorithm is insensitive to node numbering and independent of matrix bandwidth. The numbering of the elements, however, must be assigned in a contiguous and optimal sequence to assure computational efficiency. In general, the optimal element numbering begins along the side of the mesh with the fewest elements. A preprocessor program, designated as MESHER, has been developed that reads a finite-element mesh (element-node table and nodal coordinate list), reorders the element numbering sequence, and outputs the optimized mesh layout.

3.2 ELEMENT TYPES

The MAGNUM-2D computer code uses a grid system composed of quadratic and linear elements such as those depicted in Figures 1 and 2. The grid layout is defined by an element-node table (connectivity definition) and a list of nodal coordinates (geometry definition). Node numbers for any element must be entered in a counterclockwise manner starting at any corner node. The finite-element grid consists of any combination of quadrilateral and triangular elements with line elements superimposed along element boundaries as needed.

By default, quadratic-shape functions are used to approximate the state variables, h and T , over each finite element. This default may be overridden by specifying a "zone" as part of the input data. The state variables are approximated within the zone using quadratic-shape functions as normal, but all elements outside the zone are approximated with linear-shape functions. Midside nodes are automatically averaged by MAGNUM-2D for any linear zone elements, thus reducing the number of unknowns. The elements and the node numbering used for linear-shape function elements are shown in Figure 2. Using linear-shape functions in domain areas with gradually varying-state variables can save substantial computer run time.

In addition to the zone definition technique mentioned above, the user may also specify elements with linear-shape functions directly. During input, the user enters zero or blank for all midside nodes. The MAGNUM-2D computer code will detect these "zero" nodes and use the linear-shape function.

Although the shapes and sizes of the continuum elements are arbitrary, it should be noted that the aspect ratio, roughly the ratio between the height and width of the element, can be a determining factor in the accuracy of the final results of a simulation. It has been found through experience that if the user maintains an aspect ratio of less than 100, the results will be reasonable.

The modeling of macrofeatures such as fractures will at times require a tradeoff between the best fracture geometry representation and the number and location of the continuum elements. One fracture width is allowed per material type. Several material types may be defined with their fracture widths being the only difference in the rock properties. The line element representing the fracture is treated as isotropic. Regardless of the fracture orientation in the domain, the x-direction conductivity value is used along the fracture length, and a zero-conductivity value is used across the fracture width. The specified fracture permeabilities must be greater than the permeability of the surrounding medium. Moreover, a line element and a continuum element cannot be assigned the same material type index.

In addition to the modeling considerations, care should be exercised in placing the continuum elements so that the various material types are in their proper orientation and location. Material types may only be specified on an element-by-element basis, so material boundaries must coincide with element boundaries.

3.3 INITIAL CONDITIONS

A global or local initial value of a state variable, F , may be specified as summarized by Equations 10 and 11, respectively. The role of initial conditions in a simulation of transient phenomena is obvious. For a steady-state simulation, the initial conditions are taken as starting values in that the steady-state value of F is

$$F_k = F_k^0 + \Delta F_k \quad (18)$$

where ΔF_k represents the incremental change in F after a single iteration.

For steady-state applications the default value of zero for starting values may be as good as any other starting value in that the steady-state value, F_k , and the amount of computer time needed to obtain it are independent of the starting value, F_k^0 . As an exception, starting values

of temperature may be important in steady-state flow if the user wishes to account for temperature dependence of hydraulic conductivity. A tacit assumption in this exceptional case is that the initial temperatures are actually steady-state temperatures. Of importance though is merely acquainting the user with the capability of specifying starting values for steady-state applications.

3.4 BOUNDARY CONDITIONS

The MAGNUM-2D computer code is designed principally for simulation of nonisothermal fluid flow and heat transfer in the vicinity of a waste container under saturated groundwater conditions. Hence aquifer leakage, recharge, and pumping are not considered in the model. Heat sources are accommodated as described in the following section. At the outer boundary of the simulation domain, as well as along the axis of symmetry for a radial coordinate system, a zero flux boundary condition is taken by default for both state variables h and T .

Optional Dirichlet boundary conditions may be specified for either or both h and T at any boundary node. Note that specification of fixed temperature or head along the axis of symmetry for a radial coordinate system may be used to simulate a point, line, or cylindrical source of constant strength. No provision is made to allow any time dependent boundary conditions (except for internal heating as described in the next section).

3.5 HEAT SOURCES

Heat sources may be specified throughout the discretized spatial domain on an elemental basis. Use of this feature requires specification of the total number of elements to which a time-dependent heat load is applied, the numbers of the individual elements that bear the heat load uniformly, and the temporal profile of the common heat generation rate. As an option, one may also supply a scale factor that magnifies the thermal source strength. Provision of this scaling option is intended to facilitate user transition between simulations for which the heat loads are identical up to magnitude of source strength.

Zero heat loading is set by default. Alternately, for a transient simulation involving heat transfer processes, one may specify a heat generation rate through either of two methods. The more general of the two available source strength options allows the user to input the pairs of points of the form (t^i, Q^i) that define a piecewise-linear heat generation profile. An example of such a profile is depicted in Figure 3. The shaded area in this figure indicates the amount of thermal energy released per unit volume, ΔQ , over a time step of size Δt . Attainment of a constant source

strength requires a single pair of points. A step-change profile may be approximated by three pairs of points (i.e., four total points taken pairwise in increasing time). In general, a continuous piecewise-linear profile consisting of n segments requires $n+1$ points.

FIGURE 3. Typical Volumetric Heat Generation Profile.

The other source strength option is specially tailored to simulation of heat transfer around a waste package. In particular, under this option the source strength is the product of an initial volumetric heat load and a relative heat generation rate for 10-yr old unprocessed spent fuel (Hardy and Hocking 1978). Use of this option requires entry of the initial heat load, Q^0 , after which successive loads decay according to the empirical relation

$$Q^{\ell} = Q^0 \sum_{i=1}^6 b_{i1} e^{-b_{i2} t^{\ell}} \quad (19)$$

where the coefficients b_{ij} are given in Table 1.

TABLE 1. Coefficients of Relative Heat Generation.

i	b_{i1}	b_{i2}
1	0.00756	2.3×10^{-5}
2	0.0151	9.95×10^{-5}
3	0.1404	1.75×10^{-3}
4	0.677	2.166×10^{-2}
5	0.0504	4.03×10^{-2}
6	0.1093	2.912×10^{-1}

Both of the foregoing heat source strength options are programmed only for use in a transient simulation mode. To obtain a steady-state temperature distribution around a constant heat source, one must run a transient simulation covering at least one step of strictly positive duration. This is due to the nature of the piecewise-linear profile that is used to specify a constant heat source. Alternately for steady-state heat transfer around a constant source, it may be reasonable to assume a line of symmetry across the source and run a steady-state simulation in which an appropriate Dirichlet boundary condition is specified along a segment of the axis of symmetry.

3.6 TIME STEPPING

The time steps for a transient simulation may be subdivided into groups of equally sized steps. The number of steps of any given size is arbitrary. The user need only specify the step size and number of steps for each group of time steps as described in Section 4.0.

Apart from the procedural task of inputting time-step data is the need for criteria to gage step sizes. As a rule of thumb, a beginning time-step size should not be greater than the characteristic time

$$\Delta t_{ch} \equiv \min \frac{S(\Delta x)^2}{T} \quad (20)$$

where

S = generalized storage coefficient (S_s or S_t)

Γ = generalized conductivity (K or D_t)

Δx = internodal distance

and the minimum is taken over all pairs of adjacent nodes aligned in the principal direction of the gradient of F . A solution of the flow equations (Eq. 1 and 4) at the ℓ^{th} time step is generally stable as long as

$$\max_{1 \leq k \leq NP} \left\{ \frac{h_k^\ell - h_k^{\ell-1}}{h_k^{\ell-1}} \right\} \leq 10^{-4} \quad (21)$$

is maintained for the current step as well as all previous steps. Moreover, an empirical guideline for assessing the effectiveness of time steps during solution of the temperature equation (Eq. 6) is

$$\max_{1 \leq k \leq NP} \left\{ \frac{T_k^\ell - T_k^{\ell-1}}{t^\ell - t^{\ell-1}} \right\} \leq 10^{-2}. \quad (22)$$

Time steps chosen so that temporal changes of state variables are within the suggested limits (Eq. 21 and 22) will generally lead to stable results. However, gross undershoot of both criteria (Eq. 21 and 22) may be indicative of computational inefficiency.

Further considerations regarding computational efficiency stem from the need to update the stiffness matrix and load vector during time-stepping. The load vector must be updated at each time step. In the stiffness matrix, the temporal and spatial gradients of the dependent variables are differentiated with respect to themselves. The time derivative reduces to the weighting factor divided by the time-step size, while the spatial derivatives of the dependent variables reduce to spatial derivatives of the weighting function.

For two special cases, all the coefficients of the stiffness matrix are constant. These two cases are isothermal flow and uncoupled heat conduction. The stiffness matrix will change only when the time-step size is altered. Limiting the frequency of time-step size changes in these cases will significantly improve the efficiency of the simulations.

In contrast, when both the heat and flow equations are solved, the stiffness matrix must be reformed and inverted at each time step. Moreover, fluid density is thermally dependent, and hydraulic conductivity exhibits a weak temperature dependence due to viscosity changes. Conductivity and density values in the flow equations are updated based on temperatures from the previous time step, a technique known as "quasi-linearization." The diffusion term in the heat equation is linearized by assuming a constant diffusion coefficient, D_t , throughout the temperature range of interest, but the advection term must still be updated at each time step. Other coefficients are constant over time.

Run-time options described in Section 4.0 determine whether the flow and thermal equations are both being solved and whether they are coupled or uncoupled. The uncoupled solution uses thermal data from the first time step to solve the flow equation at all subsequent times. Groundwater systems vary slowly over time, so the error incurred is usually minimal if the time step is small. Computational savings are great. A parametric study of the domain should be implemented, however, before assuming uncoupled simulations are valid.

The simulation time in a transient run can be divided into several time intervals with different time-step sizes. Small time steps may be used when a thermal load is applied or after other abrupt changes in aquifer properties. At each time step, the incremental change in the dependent variables is found for each node. These incremental values are added to the previous time-step results to give the head and temperature values throughout the domain. State variables and their gradients are then updated based on these new data; thermally dependent coefficients are recalculated; the new matrix and load vector are formed; and the system of equations is solved. This procedure is repeated until the final simulation time is reached.

3.7 SIMULATION RESTART

Restart capabilities are particularly useful in simulations that span long time periods relative to the time-step size. The first interval of time steps can be checked for errors before continuing an extensive run. After a given time period, perturbations in the system can be simulated by changing values in the input data file and restarting the run. For instance, changes in fracture permeabilities and apertures could be used to account for other factors such as stress coupling effects.

The user flags the initial run to generate the restart output file by using parameter ICF to specify a logical unit number (LUN). The file so generated will contain data from the last time step completed. When the restart run is started, the LUN entered as ICF is specified as the input file using parameter IRS.

Note that the data file used as the initial input must be provided in its entirety, but modifications may be made to material properties or other parameters. No modifications may be made to the geometry.

3.8 EXECUTION CONTROL

Execution control parameters make up most of the parameters on the second and third input records. These two cards specify items such as the simulation mode, temperature options, moisture (fluid flow) options, type of initial conditions, output specifiers, and all of the LUNs used for files. In several cases, values entered in these records are used later during input to control the number of values to be entered (e.g., the number of nodes or elements). Note that not all the controlling parameters are located in these records. In some cases, they may immediately precede the table of values to be entered.

The LUN or file numbers entered on the third card often serve a dual capacity, e.g., the parameter IRS for restart. If this value is blank or zero, no restart is performed. When IRS is a positive number, it specifies the LUN to be read for restart and simultaneously indicates that a restart run is being made.

Details of all the input data may be found in Section 4.0 broken down by card type and parameter. Any interaction between control values and input data is fully explained in context.

3.9 DATA INPUT RECORDS

The input for MAGNUM-2D consists of a sequence of 80-character "card images." All the input is entered in fixed-length fields as defined in the following sections and consists of numeric or alphanumeric (character) data. It is entered in a manner consistent with the conventions of the FORTRAN programming language, of which an abbreviated description will be found in this section.

The input records are divided into a series of fields, each field being a fixed, predetermined number of characters in length. These fields may be used to enter either numeric or alphanumeric data. In the case of numeric data, there are two types: integer and real.

Integer numbers are entered as a string of numerals (0 through 9) with no decimal points. They may be preceded by an algebraic sign (+ or -), if required, and should not have any commas or blanks embedded in them. Examples are as follows:

- 100
- -53

- 0
- +1025.

In the descriptions that follow, an integer value is specified by using the FORTRAN editing code of Ixx, where the I stands for integer, and the xx is a number indicating the length of the field that will contain the integer number. Examples are as follows:

- I5 - Integer field 5 digits long
- I10 - Integer field 10 digits long.

All integers entered must fit within the field specified, or erroneous results will occur.

Real numbers can be entered in two forms. The first is called a real fixed-point number and is entered as a string of numerals with a decimal point. If required, they may be preceded by an algebraic sign and should not have any commas or blanks embedded in them. Examples are as follows:

- 3.14159
- 2034.
- -1.0
- +2.57.

In the descriptions that follow, a real fixed-point value is specified by using the FORTRAN editing code of Fxx.xx, where the F stands for real fixed, and the xx is a number indicating the length of the field that will contain the real number. The xx that follows the decimal point indicates the number of decimal places that will be assumed if no decimal point is entered. Examples are as follows.

- F10.2 - Real number in a field 10 digits long with an assumed decimal point two places to the left of the last digit. A number entered as 1024 will be interpreted as the value 10.24.
- F10.0 - Real number in a field 10 digits long with no assumed decimal point. A number entered as 1024 will be interpreted as the value 1024.

All numbers entered must fit within the field specified, or erroneous results will occur.

A real floating-point number consists of a string of numerals with a decimal point and may be preceded by a sign (as in the real fixed point number). However, the real floating-point number is followed by an E and up

to a two-digit number (three digits on some machines) which indicate the power of 10 by which the preceding real fixed-point number should be multiplied to produce the correct order of magnitude. The power of 10 value, called the exponent, may be a signed number as well. Examples are as follows:

- 1.24E2 = 124.0
- -10.45E4 = -104500.0
- -45.63E-4 = -0.004563
- 3141592E-6 = 3.141592.

In the descriptions that follow, a real floating-point value is specified by using the FORTRAN editing code of Exx.xx, where the E stands for floating point, and the xx is a number indicating the length of the field that will contain the number. The xx that follows the decimal point indicates the number of decimal places that will be assumed if no decimal point is entered as follows.

- E10.2 - Real number in a field 10 digits long with an assumed decimal point two places from the right of the last digit. A number entered as 1024 or as 1.024E1 will be interpreted as the value 10.24.
- E10.0 - Real number in a field 10 digits long with no assumed decimal point. A number entered as 1024 will be interpreted as the value 1024.

All numbers entered must fit within the field specified, or erroneous results will occur.

Alphanumeric (character) data are often entered for titling purposes. These data consist of a string of characters of the users choice, not exceeding the input field length in number. Examples are as follows:

- THIS IS AN EXAMPLE TITLE 24 character string
- ANOTHER LINE 12 character string.

In the descriptions that follow, an alphanumeric value is specified by using the FORTRAN editing code of Axx, where the A stands for alphanumeric, and the xx is a number indicating the length of the field that will contain the characters. Examples are as follows:

- A10 - A field of 10 is available for character input. The characters may be entered anywhere within the field.

All characters entered must fit within the field specified, or erroneous results will occur.

4.0 INPUT PREPARATION

4.1 INTRODUCTION

Preparation of input for a MAGNUM-2D simulation consists of a series of interrelated but identifiable steps. These steps are as follows:

1. Construction of a suitably discretized geometric model that takes into account the materials comprising the various regions of the model
2. Definition of the initial and boundary conditions
3. Definition of the material properties
4. Definition of the program control parameters and time-step sequences.

While the following discussion will not follow these points in the order given, each item should be kept in mind to ensure that a complete data set representing the problem is developed.

The actual input data for MAGNUM-2D are entered in a very definite, controlled order. In some cases, data entered early in a data set control the type and quantity of data entered later. Care should be taken to ensure that the values entered in these cases are consistent, since errors of this nature can be difficult to pinpoint.

All the card types available to the user for input are presented and the parameters that are entered on each card are described in Section 4.2. A summary is given in Section 4.3 of the card types giving FORTRAN variable names, short definitions, field lengths, and input editing codes for easy reference during setup of simulation input. In both sections, the card types are given in order of their occurrence in an input stream.

4.2 INPUT DATA DESCRIPTION AND DISCUSSION

A detailed, in-depth description of each input parameter is given in this section. Numbers that appear in parentheses represent allowable values for some parameters that only have a limited number of choices.

Card Type A

Title Card

TITLE - This parameter is a string of up to 80 characters that may be input to describe the analysis. It is limited to one card. This parameter will be output as part of the header on the MAGNUM-2D printout.

Card Type B

Control Parameters

IMODE - This parameter flags whether the simulation being performed is time dependent (0) or steady-state (1). If steady state is indicated, the input for the dynamic control data below is still required but is ignored in the simulation. No convergence criteria are required.

Data files for transient runs can be used for steady-state runs without modifications. Reset variable IMODE from 0 to 1, and only one iteration will be taken. Time steps and thermal loads in the input file will be ignored.

ITEMP - This parameter indicates how the temperatures are handled or used. The options are to ignore heat flow calculations (0), to simulate heat flow (1), to uncouple the heat flow/fluid flow calculations (2), and to utilize temperature input without performing the heat flow analysis (-1).

If ITEMP = 0, the hydrodynamic flow equation is solved without any heat transfer. An initial run of the flow at steady state can be used to determine the initial conditions for transient runs.

If ITEMP = 1, a coupled thermal-flow simulation is performed. Incremental changes in the dependent variables, head and temperature, are solved by a system of simultaneous equations. The calculated thermal values are used to update the temperature-dependent coefficients in the conductivity matrix and in the load vector at each time step. The coupled simulation requires the most computer time because the matrix to be inverted is large, and it must be updated at each time step.

If ITEMP = 2, the thermal equation is uncoupled from the flow equation. This can save computer time. The flow equations are solved alone, and the head values are used to solve the thermal equations. At the next time step, the new temperature values are used to update the conductivity matrix and the load vector in the flow equation. The large matrix in the coupled simulation has been broken into two smaller matrices that are solved alternately, thus reducing the computation time.

If ITEMP = -1, MAGNUM-2D uses temperature results from a previous run. While thermal fields strongly affect the groundwater flow patterns, the thermal regime is only slightly influenced by the flow. Therefore thermal output from a previous simulation can be used repeatedly in a flow simulation sensitivity analysis.

IMOIST - This parameter indicates how fluid flow will be handled. The options are to simulate fluid flow (1), to ignore fluid flow (0), and to assume steady flow (2) at each time step.

If IMOIST = 0, the thermal equation is solved without fluid flow. All the thermal transport is by conduction through the rock with no advection.

If IMOIST = 1, a hydrodynamic simulation is invoked. The values of IMODE and ITEMP together determine the nature of the hydrodynamic simulation.

If IMOIST = 2, steady-state flow is computed at each time step, regardless of whether or not the temperature equation is being solved.

NP - This parameter indicates the number of node points needed to define the model used for the current simulation. It is used to control the geometry input later. This value should be entered properly even if the geometry is to be entered from an external geometry file. The nodal point count on the file is checked against it.

NE - This parameter indicates the number of elements needed to define the model used for the current simulation. Later, it is used to control the geometry input. This value should be entered properly even if the geometry is to be entered from a geometry file. The element count on the binary file is checked against it.

NMAT - This parameter indicates the number of different material or rock types that will be used in the model. Later, it is used to control the material data input.

ICND - This parameter indicates the type of initial conditions to be used for this simulation. Two choices are available. The first is to read one input record to define the initial conditions for all node points (0). The second is to read one record for each node (1). This parameter is used to control the type of input needed later.

If the initial conditions are unknown, one card can be used to define all nodes with the same initial value estimate, i.e., ICND = 0. In steady-state flow problems, the initial head values are unimportant because the algorithm calculates head values at the unknown nodes based on known boundary values. The first few time steps of a transient flow simulation, however, can be influenced by the initial head conditions, so a reasonable estimate is needed. A steady-state, flow only run, with variable ICND = 0 and file unit ICSV specified, can be used to generate and save head values. The ICSV file may then be used for initial condition input in a subsequent transient run.

In contrast, initial temperature values are important in both steady-state and transient heat problems. The density and viscosity are based on these reference values. One initial condition card can be used, but the temperature chosen should be representative of the system (alternatively, see TREF). If file unit ICSV is specified, the data from a steady-state, heat flow only simulation can be used as the initial conditions in a transient run.

Initial condition files can also be created by a preprocessor program ICGEN. The ICGEN or ICSV initial condition file must be inserted into the data deck at the appropriate location (see card type J). To signal that there is one initial condition card per node, set ICND = 1.

IECH - This parameter controls the echoing or parroting of the input data. The choices are to echo only part of the data (0) or all the data (1).

If IECH = 0, the principal problem specifications, specified boundary conditions, rock hydraulic properties, and heat generation history will be printed in tabular form. If IECH = 1, the input geometry, initial conditions, and element connectivity will be printed in addition to the above default output.

IALL - This parameter controls the diagnostic printout available during the simulation. Either no printout is available (0) or a listing of data showing convergence may be obtained (1).

If IALL = 1, the maximum change in head or temperature is printed at each time step. Extremely large changes might indicate instability in the solution. The maximum change in state variables may also be used as a convergence criteria. If the value is close to zero for several time steps, the transient problem has probably reached steady state. This information is useful, e.g., in convection cell simulations with a constant heat source. The default of IALL = 0 provides none of the above output.

IVELP - This parameter controls the printout of the velocities at each Gauss point. The user may choose no printout (0) or printout for all the nodes (1). Regardless of the choice, the data will still be written to the binary velocity output file specified as IVEL.

IPRT - This parameter controls the frequency of output to the binary results file specified as ISV. The output may be generated at each time step (0), or at the print frequency specified below (1). A choice of (0) may result in a very large file being produced, since many time steps may occur for a simulation to finish and the data for each node will be written each time step. A choice of (1) will cause the output to the binary file to correspond to the printed output.

NSYS - This parameter controls the type of coordinate system to be used in defining the simulation model. The choices are Cartesian (0) or radial about the y axis (1).

Card Type C

File Assignments

The MAGNUM-2D computer code is designed to allow data to be read from or written to a mass storage device. To tell the program where to read or write, the user must provide the LUNs of the files that are being used.

Each system will have a slightly different way of associating LUNs with files so the system documentation should be consulted for advice on how to accomplish this. The default input unit (defined internally) is IC = 5, and the output unit is IOUT = 6.

IRS - This logical unit is used as the input file for restarting a simulation. The file should be the one specified as ICF (see below) in the previous run. Note that for restarting a simulation, all the data must be re-input, but some may not be used.

ISV - This logical unit is used to save the results of the simulation for later processing. It contains the heads and/or temperatures generated and is designed to be used by the various postprocessors available for MAGNUM-2D. The data is saved on this file at the time-step frequency specified by parameter IPRT discussed previously.

ICF - This logical unit is used to save the data necessary to restart the simulation at a later time. It is the file that is used as IRS when restarting.

IGI - This logical unit is used as input for the geometry that has been created using a preprocessor or has been saved (see below) from a previous simulation using the same model. This file may be a binary or coded file. If the initial attempt to read as a coded file fails, a binary read is used. Binary files are recommended to reduce I/O time.

IG - This logical unit is used to save the geometry defined in the current simulation for later use. It could be used as IGI (see above) when needed.

IVEL - This logical unit is used to save the data necessary for computing the velocity field. Its intended use is for the PATH program, but other postprocessors may also utilize it. The contents of this file are material properties (with corrections due to temperatures), density disparity, and head values at each time step.

The Darcy velocities can be calculated by interpolation at any interior point of an element. The sister program CHAINT uses this file as input to the solute transport simulation. Several postprocessor graphics programs use the IVEL file; e.g., the VELPLT program plots the velocity vector field, and the program PATH can be used to plot the streamlines or the pathlines of the flow field.

INPT - This logical unit is used as input for the temperature field generated by another simulation. Its format is the same as the ISV file (see above) allowing the results of an earlier temperature simulation to be used as input. MAGNUM-2D will use the precalculated temperatures in the INPT file for the current flow simulation. IMOIST must equal one when this option is used.

ICSV - This logical unit is used to save the final conditions of temperature and head calculated at the end of the current simulation as a coded file so that they can be edited into data for a later simulation. Refer to the parameter ICND when this data is to be used in a later run.

Card Type D

Constants Definition

SSF - This parameter specifies the starting time for the simulation. It is typically set to 0.0. Restarted simulations will automatically start at the ending time of the previous run.

ALFA - This parameter specifies the weighting factor, θ , to be used in the simulation. It should be a value between 1 and 2, i.e., $1 < \theta < 2$. The time derivatives of the dependent variables are approximated by the difference expression (Eq. 15). When $\theta = 1$, the expression is a backward difference of the fully implicit kind with maximum damping. The Crank-Nicolson approximation is invoked when $\theta = 2$. A commonly used value for θ is 1.8.

TREF - This parameter specifies the reference temperature to be used when calculating the initial densities and viscosities from the reference density and viscosity respectively (as long as $TREF > 0.05$).

Using this parameter, the user may specify a reference temperature that is different than the starting temperature and correctly model the buoyancy/viscosity effects. The properties of viscosity and density are modeled as a one-dimensional Hermitian expansion as are the coupling coefficients. The temperature range is from 0.0-300.0 °C

Card Type E

Dynamic Control Card

This card type is used to specify the time-step information for the simulation. The total time for the simulation is broken into intervals that are arbitrary in length and are in turn further broken into equally sized time steps. This scheme for variation of time step size allows the user to tailor MAGNUM-2D to each problem. After perturbations occur in the model, small time steps allow adaptation to rapid changes. Larger time steps are adequate when the model response is slow.

NTS - This parameter specifies the number of time steps to be used in a specific time interval. Typically, the user would specify more time steps of shorter duration for those time intervals suspected of having more variation in the heads and/or temperatures.

NTSG - This parameter specifies the frequency at which the results of the simulation will be printed; i.e., every NTSG time steps a printout of the current results will be created. As an example, consider NTS = 25 and NTSG = 4. The results will be six printouts corresponding to the time steps 4, 8, 12, 16, 20, and 24.

DLT - This parameter specifies the actual time allotted to each time step. It is specified in years. As an example, consider the previous example of NTS = 25 and NTSG = 4. If DLT = 10.0, then the time interval will be 250 yr long (25 time steps of 10.0 yr each) and will have printout corresponding to 40, 80, 120, 160, 200, and 240 yr.

Card Type F

Control Factors

SCALEX - This parameter allows the user to apply a uniform scale factor to the x-dimensions of a model without having to modify the input data.

SCALEY - This parameter allows the user to apply a uniform scale factor to the y-dimensions of a model without having to modify the input data.

In order to decrease the amount of time needed to complete the simulation but maintain accuracy in the region of greatest variation, the elements in the mesh may be split into two groups by using the following parameters to define a zone. Within this zone, the elements will use a quadratic-shape function, while outside it, the elements will use a linear-shape function.

ZONEL - This parameter specifies the left boundary for the quadratic zone and is given in meters.

ZONER - This parameter specifies the right boundary for the quadratic zone and is given in meters.

ZONE T - This parameter specifies the top boundary for the quadratic zone and is given in meters.

ZONEB - This parameter specifies the bottom boundary for the quadratic zone and is given in meters.

If these four parameters are entered as zeros or are left blank, the state variables will be approximated with quadratic-shape functions over all elements.

Card Type G

Element (connectivity) Definition

This card type should be omitted if a data file is being used for geometry input, i.e., if IGI is nonzero on card type C. The number of sets of the following parameters should correspond to the value entered for NE (number of elements) on card type B.

J - This parameter specifies the element number being entered. The element numbers are used as indices to arrays, so they must be contiguous starting with one, but need not be entered in any specific order.

NOP - This parameter specifies the node numbers that define the element. There may be up to eight nodes per element, and they must be entered counterclockwise starting from any corner node. If a quadratic-shape function element is being specified, all eight nodes must be entered. If only the four corner nodes are entered (with the midside node entries being blank or zero), then a linear-shape function element is assumed. If a triangular element is needed, it may be specified in a similar manner by entering six nodes for a triangular quadratic element or the three corner nodes (with blank or zero midside nodes) for a linear quadratic element. Line elements are entered in a similar fashion; the choices being either three nodes for a quadratic-shape function or two nodes for a linear-shape function. (See Section 3.2.)

IMAT - This parameter specifies the material type used for this element. It must correspond to one of the material types defined on the following type M cards.

NFIXH - This parameter specifies the order in which this element will be considered during the solution phase of the simulation. These values may be input by the user but are typically modified by one of the preprocessors which optimizes the model geometry.

Card Type H

Coordinate (Geometry) Definition

This card type should be omitted if a data file is being used for geometry input, i.e., if IGI is nonzero on card type C. The number of sets of the following parameters should correspond to the value entered for NP (number of node points) on card type B.

N - This parameter specifies the number of the node being entered. Like the elements, the nodes need not be entered sequentially; but node numbers must be contiguous and start with one.

CORD(N,1) - This parameter specifies the x-coordinate of the node in global coordinates.

CORD(N,2) - This parameter specifies the y-coordinate of the node in global coordinates.

Card Type J

Initial Condition Definition

The use of this card type is controlled by the variable ICND, which was entered on card type B. Two modes of use exist. If ICND = 0, a single card of this type is used to define the initial conditions for head and/or

temperature for every node in the model. If ICND = 1, MAGNUM-2D expects to find one initial condition card, as described here, for each node in the model.

Note that if a restart simulation is being performed, the initial condition specification must be present for the restart run to be valid.

N - This parameter specifies the node for which the initial condition is being entered. This parameter is ignored if ICND = 0.

T1 - This parameter specifies the temperature to be used initially for the node(s) in question. It is entered in degrees Celsius.

T2 - This parameter specifies the hydraulic head to be used initially for the node(s) in question. It is entered in meters.

Card Type K1

Dirichlet Boundary Condition Nodes

A zero flux Neumann condition is assumed at all unspecified boundary nodes.

KSPEC - This parameter specifies the number of nodes at which constant head and/or temperature boundary conditions will be specified.

Card Type K2

Dirichlet Boundary Condition Values

The number of sets of the following parameters is controlled by the value entered for KSPEC above. One set is entered for each node at which a boundary condition is to be specified.

N - This parameter specifies the node number at which the boundary condition is being specified.

NFIX - This parameter specifies the type of boundary conditions being specified. It consists of a two-digit integer number that may have a one entered in either place. A one entered in the tens place indicates that a temperature value is being entered while a one in the ones place indicates that a hydraulic head value is being entered.

BVAL(1) - This parameter specifies the actual boundary condition value to be used for temperature at the node in question. It is specified in degrees Celsius.

BVAL(2) - This parameter specifies the actual boundary condition value to be used for hydraulic head at the node in question. It is specified in meters.

As an example of the boundary condition specifications, consider the following example card images:

13	10	103.	11.
28	01		5.7
57	11	95.	10.6

The first entry specifies the boundary condition for Node 13 as temperature only (10), indicating a value of 103.0 °C. The second entry specifies the boundary condition for Node 28 as head only (01) with a value of 5.7 m. The last entry specifies the boundary conditions for Node 57 as temperature and head (11), 95.0 °C and 10.6 m, respectively.

Note that in the first entry, even though a value is entered for head or temperature (in this case head), unless the appropriate flag is set, that value will be ignored.

Card Type M

Material Properties

This card type set defines the properties of the materials comprising the model^(a). The number of material properties to be specified was entered on card type B as NMAT. Each entry must consist of two cards, so the number of material property definition cards must be NMAT*2. Note that some of the properties are anisotropic. If this capability is not required, specify the property to be the same in both directions.

The Card 1 parameters are as follows.

L - This parameter specifies the material type number. This is the number referred to in the element definition as IMAT.

CVM - This parameter specifies the specific heat of the rock, C_s , for this material type in joules per kilogram-degree Celsius [J/(kg·°C)].

TKK(L,1) - This parameter specifies the thermal conductivity of the rock in the x-direction, D_{sx} , for this material type in joules per second-meter-degree Celsius [J/(s·m·°C)].

TKK(L,2) - This parameter specifies the thermal conductivity of the rock in the y-direction, D_{sy} , for this material type in joules per second-meter-degree Celsius [J/(s·m·°C)].

^(a)In this context material properties are synonymous to rock properties in that the saturating fluid is assumed to be water and the reference water properties are hard coded with the following values: $\rho^* = 985 \text{ kg/m}^3$, $c_f = 4174 \text{ J/(kg·°C)}$, $D_f = 2.008 \times 10^7 \text{ J/(m·yr·°C)}$, and the compressibility of water is 4.6×10^{-10} Pascals.

POROS(L) - This parameter specifies the effective porosity, ϕ , of the rock for this material type. It is a dimensionless number.

HKAX - This parameter specifies the hydraulic conductivity in the x-direction, K_{xx} , for this material type in meters per second (m/s).

HKAY - This parameter specifies the hydraulic conductivity in the y-direction, K_{yy} , for this material type in meters per second (m/s).

NME - This parameter may be used to assign a name to this rock type. It is optional and may be up to eight characters in length. It is printed with the echoed data.

The Card 2 parameters are as follows.

SP1 - This parameter specifies the specific storage, S_s , of this material type. Its units are 1/m.

RHOM - This parameter specifies the bulk density, ρ_s , of this material in kilograms per cubic meter (kg/m^3).

ALPAL - This parameter specifies the longitudinal dispersivity, α_L , of this material in meters (m).

ALPAT - This parameter specifies the transverse dispersivity, α_T , of this material in meters (m).

WIDTH - This parameter specifies the thickness or width of fractures, e , used in the model. It is used only for fracture elements and must be zero for continuum elements. It is specified in meters (m).

Card Type P

Thermal Loading Control

This card type must exist for every simulation. If no thermal loads are applied, this is indicated using the parameter NLD as described below. Flow only simulations automatically ignore any thermal data.

Note also that no thermal loads are allowed for a steady-state run. An ill-formed problem may result if this is attempted.

NLD - This parameter specifies the number of elements in the model that will be considered as heat source elements. If no thermal loads are to be applied to the model, this parameter should be entered as a zero or a blank card.

NLT - This parameter specifies the number of thermal load data points, i.e., the number of times and corresponding loads that will be input. This parameter is ignored if NLD = 0 above. For a transient problem, if NLT = 0, a piecewise exponential decay will be applied to the single initial thermal load defined on card type R1 below. The decay function is given in Equation 19. In this case FORTRAN variable QT contains the current source strength.

SCF - This parameter specifies a scale factor that is applied to the thermal load values. This parameter is ignored if NLD = 0 above.

Card Type Q

Heat Source Elements

This card type is ignored if NLD = 0 on card type P.

NLE(I) - This parameter specifies the element numbers of the elements that are to be considered as the heat sources in the model. The number of these elements is controlled by the parameter NLD on card type P above. Each record (or line) may contain at most 16 fields, and the records may be repeated as many times as needed.

Card Type R1

Initial Thermal Load Definition for Exponential Decay

This card type is ignored if NLD = 0 on card type P, and is only used if NLT = 0 and NLD $\neq$ 0.

Q0 - This parameter specifies the initial thermal load, Q^0 , to be used for the exponential decay for all the elements entered in card type Q. It is given as joules per year-cubic meter [$J/(yr \cdot m^3)$].

Card Type R2

Thermal Load Definition

This card type is ignored if NLD = 0 on card type P, and is only used if NLT $\neq$ 0 and NLD $\neq$ 0.

The loading is specified by defining a set of points in time at which the thermal load is known. The range of times input must bracket or coincide with the range covered by the simulation. Any times used by the simulation but not input are interpolated as long as the input times bracket the time required. Thus, this interpolation requires that a minimum of two time/load pairs be input.

TLE(I) - This parameter specifies the time of the thermal load being entered for the next parameter. It is given in years (yr).

OLE(I) - This parameter specifies the thermal load for the time entered above in joules per year-cubic meter [$J/(yr \cdot m^3)$].

These time and load values are input in pairs, up to four per card, until NLT values have been entered. Recall that NLT was defined as the number of thermal loads on card type P above. Repeat this card type as many times as needed.

4.3 INPUT DATA FORMAT SUMMARY

Card Type A

Title Card

1-80	TITLE	20A4	Title or description of this analysis, up to 80 characters.
------	-------	------	---

Card Type B

Control Parameters

01-05	IMODE	I5	Simulation Mode = 0 Time-dependent analysis. = 1 Steady-state analysis.
06-10	ITEMP	I5	Temperature Option = 0 No heat flow in this analysis. = 1 Temperature simulation. = 2 Temperature simulation uncoupled from fluid flow (i.e., $q_i \frac{\partial T}{\partial x_i} = 0$). = -1 Temperature input from external file.
11-15	IMOIST	I5	Fluid Flow Option = 0 No fluid flow simulation. = 1 Fluid flow simulation. = 2 Steady-state flow simulation at each time step.
16-20	NP	I5	Number of Nodes in the Model
21-25	NE	I5	Number of Elements in the Model
26-30	NMAT	I5	Number of Rock Types in the Model (Number of Material Types)
31-35	ICND	I5	Initial Condition Type = 0 Read only one card to define ICs. = 1 Read one card per node to define ICs.
36-40	IECH	I5	Input Data Echo Switch = 0 Echo selected portion of the input data. = 1 Echo all the input data.
41-45	IALL	I5	Diagnostic Printout = 0 Display no diagnostics. = 1 Print diagnostics regarding convergence.

46-50	IVELP	I5	Velocity Print Control (IMOIST $\neq$ 0 only) = 0 Do not print velocities. = 1 Print velocities.
51-55	IPRT	I5	Binary Results File (ISV) Creation Flag = 0 Write at each time step. = 1 Write at the print frequency requested by the user (NTSG below).
56-60	NSYS	I5	Coordinate System Control = 0 Cartesian coordinate system used. = 1 Radial coordinate system used (radial about the X = 0 line: Y axis).

Card Type C

File Assignments

01-05	IRS	I5	Restart input data file (generated by an earlier MAGNUM-2D run).
06-10	ISV	I5	Binary results file (contains head and temperature results for each node in the model).
11-15	ICF	I5	Restart output data file (to be generated for use by a later MAGNUM-2D run).
16-20	IGI	I5	Geometry input file (optional and supersedes the geometry input parameters requested later).
21-25	IG	I5	Geometry output file. The input geometry data is written to this binary file for subsequent use.
26-30	IVEL	I5	Velocity output file. This binary file may be used as input for the PATHLINE program (see the appendixes for more information) or other postprocessing.
31-35	INPT	I5	Temperature input file.
36-40	ICSV	I5	Initial condition output file. The state of the simulation is written (in coded form) to this file for subsequent use as an initial condition file.

Card Type D

Constants Definition

01-10	SSF	F10.1	Initial time, t^0 (in yr).
11-20	ALFA	F10.1	Weighting factor ($1 < \theta < 2$).
21-30	TREF	F10.1	Temperature for computing reference densities and viscosities. Set TREF = 0.0 to use initial temperature distribution, instead of TREF.

Card Type E

Dynamic Control Card

(This card is repeated as needed. Terminate this card type set with NTS=9999.)

01-05	NTS(I)	I5	Number of time steps.
06-10	NTSG(I)	I5	Printout frequency.
11-20	DLT(I)	F10.1	Time steps in years.

Card Type F

Control Factors

01-10	SCALEX	F10.1	Scale factor for the x-coordinates.
11-20	SCALEY	F10.1	Scale factor for the y-coordinates.
21-30	ZONEL	F10.1	Left boundary for quadratic element generation zone.
31-40	ZONER	F10.1	Right boundary for quadratic element generation zone.
41-50	ZONET	F10.1	Top boundary for quadratic element generation zone.
51-60	ZONEB	F10.1	Bottom boundary for quadratic element generation zone.

Card Type G

Element (connectivity) Definition

The number of cards for this card type set is controlled by the parameter NE defined earlier. OMIT this card type set if a geometry input file is used, i.e., if IGI is NOT equal to zero.

01-05	J	I5	Element number.
06-45	NOP(J,K)	8I5	Up to eight node numbers for elements listed counterclockwise.
46-50	IMAT(J)	I5	Element type (material type). The number entered must correspond to one of the parameters specified as L under card type M below.
51-55	NFIXH(J)	I5	Element ordering array. This parameter is the number of the J th element to process and may be used to optimize the solution of the matrix equations by modifying the bandwidth.

Card Type H

Coordinate (Geometry) Definition

The number of cards for this card type set is controlled by the parameter NP defined earlier. OMIT this card type set if a geometry input file is used, i.e., if IGI is NOT equal to zero.

01-05	N	I5	Node number.
06-17	CORD(N,1)	F12.3	x-coordinate (in m).
18-29	CORD(N,2)	F12.3	y-coordinate (in m).

Card Type J

Initial Condition Definition

01-10	N	I10	Node number (not used if ICND = 0 as discussed earlier on card type B).
11-20	T1	F10.1	Temperature (in °C)).
21-30	T2	F10.1	Hydraulic head (in m).

Note that if ICND = 0, only one card of this type is required. It will define the initial head and temperature at all nodes. If ICND = 1, then, NP cards of this type must be supplied (one for each node).

Card Type K1

Dirichlet Boundary Condition Nodes

01-05	KSPEC	I5	Number of nodes at which boundary conditions will be specified.
-------	-------	----	---

Card Type K2

Dirichlet Boundary Condition Values

01-10	N	I10	Node number.
19-20	NFIX	I2	Specified value node type indicator. This is a two-digit number, where the tens place represents temperature, and ones place represents hydraulic head. 0 = >unspecified, 1 = >specified.
21-30	BVAL(1)	F10.1	Specified temperature (in °C).
31-40	BVAL(2)	F10.1	Specified hydraulic head (in m).

Card Type M

Material Properties.

There will be twice NMAT cards in this card type set where NMAT was defined earlier on card Type A as the number of material types.

01-10	L	I10	Material type number.
11-20	CVM	F10.1	Specific heat, C [in J/(kg·°C)].
21-30	TKK(L,1)	F10.1	Thermal conductivity in the x-direction, D _{sx} [in J/(s·m·°C)].
31-40	TKK(L,2)	F10.1	Thermal conductivity in the y-direction, D _{sy} [in J/(s·m·°C)].
41-50	POROS(L)	F10.1	Effective porosity, ϕ (fraction).
51-60	HKAX	F10.1	Hydraulic conductivity in the x-direction, K _{xx} (in m/s).
61-70	HKAY	F10.1	Hydraulic conductivity in the y-direction, K _{yy} (in m/s).
73-80	NME	A8	Material type name identifier (optional).

Begin the Second Card

11-20	SP1	F10.1	Specific storage, S _s (1/m).
21-30	RHOM	F10.1	Bulk density, ρ_s (in kg/m ³).
31-40	ALPAL	F10.1	Longitudinal dispersivity, α_L (in m).

41-50	ALPAT	F10.1	Transverse dispersivity, α_T (in m).
51-60	WIDTH	F10.1	Fracture thickness (in m).

Card Type P

Thermal Loading Control

This card type must be entered whether thermal loading is being specified or not.

01-05	NLD	I5	Number of heat source elements. NLD = 0 indicates that no loading will occur.
06-10	NLT	I5	Number of thermal load points to be specified. Ignore if NLD = 0.
11-20	SCF	F10.2	Scale factor. Ignore if NLD = 0.

Card Type Q

Heat Source Elements

Omit this card type if parameter NLD = 0 on card type P.

01-80	NLE	I5	Element number to which heat sources are applied (16 values may be entered on a single card). There must be NLD values entered where NLD was defined on the previous card. This card type may be repeated as many times as needed.
-------	-----	----	--

Card Type R1

Thermal Load Definition

Omit this card type if parameter NLD = 0 on card type P.

01-10	Q0	F10.0	Initial thermal load, Q^0 [$J/(yr \cdot m^3)$].
-------	----	-------	---

Card Type R2

Thermal Load Definition

Omit this card type if parameter NLD = 0 on card type P.

01-10	TLE(1)	F10.0	Time of thermal load, t^1 (yr).
11-20	QLE(1)	F10.0	Thermal load at this time, Q^1 [$J/(yr \cdot m^3)$].

21-30	TLE(2)	F10.0	Time of second thermal load point, t^2 .
31-40	QLE(2)	F10.0	Thermal load, Q^2 , at the time t^2 .
41-80			Continue entering time and load input in pairs, up to four per card, until NLT values have been entered. Repeat this card type as many times as needed. NLT was defined as the number of thermal loads on card type P above.

5.0 OUTPUT

5.1 INTRODUCTION

The output from the MAGNUM-2D program is available in two forms. The first is the printed output that reports on the input data, the parameters that were set, the events that took place during execution, the heads and temperatures calculated at the various time steps, the duration of the run (in model time), and so on. The second form of output is composed of the various binary data files that are created for use by postprocessing programs and further analysis by other simulation programs such as CHAINT. This section will give an overview and some explanation of the printed report and the possible use of each of the binary files.

5.2 PRINTED REPORT

The MAGNUM-2D program generates one printed report file. The contents of this report may be modified by the input data using the parameters IECH, IALL, and IVELP, which appear on card type B. These parameters are described in Sections 4.2 and 4.3. Their effects will be pointed out in the following discussion.

For examples of the output report, see Appendix D.

5.2.1 Banner Page

The formatted report begins with a banner page that announces (1) the version and revision of MAGNUM-2D, (2) the day, date, and time of the run that generated the printout, and (3) the unique identifier assigned to the run. This identifier is placed on all the mass storage files and is displayed by the graphics postprocessors. It acts as an "audit" trail, allowing the user to ensure a match between printout and graphic results.

5.2.2 Input Verification

The next section of the output is the input verification section, which is divided into output "Tables." Note that in the output tables, temperature and head values are given in degrees Celsius and meters, respectively. As a reminder, column headers are T(C) for temperature and H(M) for head.

The "PRINCIPAL PROBLEM SPECIFICATIONS" are printed in output Table 1. This is an echo of the parameters input on card types B, C, F, D, and E. The card types are echoed in the order just given, and the parameters on each card type are echoed in the input order (see Section 4.2).

The "NODE POINT COORDINATES" are printed in output Table 2. This is an echo of the node point locations as defined for the problem. It is simply a table of node numbers and the corresponding x- and y-coordinates. This table is not produced if IECH = 0.

The "ELEMENT/NODE CONNECTIVITY" is printed in output Table 3. This is an echo of the connectivity defined for the problem, e.g., the node numbers that define the corner and midside nodes of the elements defining the model. It is simply a table of element numbers and the corresponding node numbers that define the element (up to the maximum of eight nodes). These are given in the order that MAGNUM-2D encountered them. Note that the table also includes the rock type and the order used in solving the matrix equations. (This may be modified or defined manually or by using a geometry preprocessor such as MESHER.) This table is not produced if IECH = 0.

The "INITIAL CONDITIONS" are printed in output Table 4. This is an echo of the initial conditions defined by the user or generated by MAGNUM-2D at the request of the user on card type J. It consists of a list of the node numbers at which the initial conditions are defined, and the temperature and head values are specified at those nodes. This table is not produced if IECH = 0.

The "SPECIFIED BOUNDARY CONDITIONS" are printed in output Table 5. This is an echo of the Dirichlet boundary conditions input on card type K1 and K2. It contains the node at which the boundary condition is applied, the type (using the same code as specified on input for temperature, head, or both), and the temperature and head input.

The "ROCK PROPERTIES" are printed in output Table 6. This is an echo of the properties input on card type M. The entries in this table are arranged in a two-dimensional array. The rows represent the actual properties (identified by name and units), and the columns represent the various rock or material types (identified by number and by user defined name).

The "HEAT GENERATION HISTORY" is printed in output Table 7. This is an echo of the thermal loading and heat source information input on card types P, Q, and R. The card types are echoed in the order just given, and the parameters on each card type are echoed in the input order (as described in Section 4.2).

5.2.3 Simulation Results

The title entered by the user on card type A is printed in the upper left corner of each page of simulation results. The next line announces the results time in years, or that the results are for steady state. The table that follows gives the head and/or temperature values for each node point in the model. The user will note asterisks occurring beside some of the head/temperature values. These mark the specified boundary conditions.

If the user specified IALL = 1 diagnostic output will be printed. This consists of some convergence criteria, namely, the iteration number, the maximum change in the temperature/head value, and the maximum relative correction made.

When MAGNUM-2D reaches a time step for which velocity output has been requested and IVELP = 1, the velocity results are printed. This output takes the form of a two-dimensional matrix with the rows representing the elements (with the x and y velocities as subdivisions) and the columns representing the Gauss points.

5.2.4 Gauss Point Locations

Occasionally, it is necessary to consider the velocity distribution within a single element. Because the velocities are computed from heads interpolated to the Gauss points, the Gauss point locations are of interest. The location of the points in the three element types and their numbering relative to the node point numbering order are shown in Figures 1 and 2.

The actual location of each of the Gauss points is given in Figure 4 for the case of quadratic-shape functions.

5.3 OTHER OUTPUT FILES

The input/output file LUNs are all specified on card type C, "File Assignments." The parameters associated with output files are ISV, ICF, IG, IVEL, AND ICSV. The use of some of these files may be clarified by the data flow diagrams in Appendix A. Each of the above files is a binary file, except as noted otherwise.

ISV MAGNUM-2D Flow and Temperature File. It contains both the head and temperature values at each node for each user-specified time step. This data may be used to generate contours, time-histories, and spatial cross sections.

PS84-2131-4

FIGURE 4. Gauss Points in Local Coordinates η, ψ for (a) Quadratic Quadrilateral, (b) Quadratic Triangle, and (c) Quadratic Line Elements.

- ICF MAGNUM-2D Restart Data File. It contains all the necessary data needed to restart the simulation from the time step at which the file was produced. When MAGNUM-2D is flagged to produce this file, it will indicate that the restart file was generated by printing a message to that effect after the head and temperature printout. The time step at which this message is printed is the time step at which the restarted run will commence.
- IG MAGNUM-2D Geometry File. This file is a convenience only. It allows the user to save the geometry on a mass storage file for later use if, for instance, the original input was on cards or some other media. This file is simply a geometry file and may be used in the same fashion as any file that had been created using preprocessors.
- IVEL MAGNUM-2D Velocity File. It contains the velocity data in binary form. This file may be utilized by the CHAINT program for radionuclide solute transport. It may also be used by the postprocessor programs VELPLT to plot the velocity vectors, or PATH to plot pathlines or streamlines.
- ICSV MAGNUM-2D Initial Condition File. It contains the information necessary to define, as initial conditions, the state of every node in the model at the end of the current simulation. This file is a coded or ASCII file and may be used in an editing session to generate the input data for a later simulation.

6.0 NOMENCLATURE

<u>Symbol</u>	<u>Interpretation</u>	<u>Units</u>
S_s	Specific storage of rock	1/m
h	Hydraulic head	m
t	Time coordinate	yr
K	Hydraulic conductivity of rock	m/s
x,y	Global space coordinates	m
δ_b	Density disparity in rock	--
δ_{ij}	Kronecker delta	--
γ	Thermal coupling coefficient	1/°C
T	Temperature	°C

<u>Symbol</u>	<u>Interpretation</u>	<u>Units</u>
ρ	Fluid density	kg/m ³
ρ_0	Initial density	kg/m ³
ρ^*	Reference density	kg/m ³
ϕ	Effective porosity	--
β	Bulk modulus of fluid	1/°C
S_f	Specific storage of fracture	1/m
K_f	Hydraulic conductivity of fracture	m/s
L	Local coordinate of fracture	m
δ_b	Density disparity in fracture	--
g	Acceleration due to gravity	m/s ²
e	Fracture aperture	m
ν	Viscosity	m ² /s
S_t	Bulk heat capacity	J/(kg·°C)
c_f	Specific heat of fluid	J/(kg·°C)
q	Component of specific discharge	m/s
D_t	Effective thermal diffusivity	J/(m·s·°C)
Q	Thermal source	J/(kg·s)
ρ_s	Density of rock	kg/m ³
c_s	Specific heat of rock	J/(kg·°C)
D_f	Thermal conductivity of fluid	J/(m·s·°C)
D_s	Thermal conductivity of rock	J/(m·s·°C)
α	Dispersivity	m
$\bar{q}$	Groundwater speed	m/s

<u>Symbol</u>	<u>Interpretation</u>	<u>Units</u>
F	Generalized state variable	--
NP	Total number of nodes	--
z	Normal coordinate	m
ω	Shape function	--
ϵ	Residual	--
X	Galerkin functional	--
E	Finite element	--
θ	Weighting factor	--
ΔF	Incremental change in F	--
b	Heat generation coefficients	--
S	Generalized storage coefficient	--
Γ	Generalized conductivity	--
Δx	Internodal distance	--
Δt_{ch}	Characteristic time	--
η, ψ	Local coordinates	m

7.0 REFERENCES

- Baca, R. G., I. P. King, and W. R. Norton (1978), "Finite Element Models for Simultaneous Heat and Moisture Transport in Unsaturated Soils," in Proceedings of Second International Conference on Finite Elements in Water Resources, Pentech Press, London, England; also RHO-SA-31, Rockwell Hanford Operations, Richland, Washington.
- Baca, R. G., D. W. Langford, and R. E. England (1981), "Analysis of Host Performance for a Nuclear Waste Repository Using Coupled Flow and Transport Models," in Proceedings of the Workshop on Near-Field Phenomena in Geologic Repositories for Radioactive Waste, OECD/NEA, Paris, France; also RHO-BWI-SA-140, Rockwell Hanford Operations, Richland, Washington.

- Baca, R. G., R. C. Arnett, and D. W. Langford (1984a), "Modeling Fluid Flow in Fractured-Porous Rock Masses by Finite-Element Techniques," International Journal for Numerical Methods in Fluids, Vol. 4, pp. 337-348; also RHO-BW-SA-297 P.
- Baca, R. G., J. C. Sonnichsen, M. K. Altenhoffen, and D. W. Langford (1984b), "Application of Finite Element Models on the Evaluation of Engineered Barriers for a Mined Geologic Repository," in Proceedings of the Fifth International Conference on Finite Elements in Water Resources, University of Connecticut; also RHO-BW-SA-312 P, Rockwell Hanford Operations, Richland, Washington.
- Clifton, P. M., R. G. Baca, and R. C. Arnett (1983), "Stochastic Analysis of Groundwater Traveltimes for Long-Term Repository Performance Assessment," in the proceeding of symposium on Scientific Basis for Nuclear Waste Management; also RHO-BW-SA-323A P, Rockwell Hanford Operations, Richland, Washington.
- Combarous, M. A. and S. A. Bories (1975), "Hydrothermal Convections in Saturated Porous Media," Advanced Hydrosciences, 10.
- DOE (1982), Site Characterization Report for the Basalt Waste Isolation Project, DOE/RL 82-3, 3 Vol., Rockwell Hanford Operations for the U.S. Department of Energy, Washington, D.C.
- Estey, S. A., R. C. Arnett, D. R. Aichele (1985), Users Guide for MAGNUM 3D: A Three-Dimensional Groundwater Flow Numerical Model, RHO-BW-ST-67 P, Rockwell Hanford Operations, Richland, Washington.
- Fahien, R. W. (1983), Fundamentals of Transport Phenomena, McGraw-Hill Book Company, New York, New York.
- Hardy, M. P. and G. Hocking (1978), Numerical Modelling of Rock Stresses Within a Basaltic Nuclear Waste Repository: Phase II - Parametric Design Studies, RHO-BWI-C-23, Department of Civil and Mineral Engineering, University of Minnesota, Minneapolis, Minnesota.
- Hood, P. (1976), "Frontal Solution Program for Unsymmetric Matrices," International Journal for Numerical Methods in Engineering, Vol. 10.
- Huyakorn, P. S. and G. F. Pinder (1983), Computational Methods in Subsurface Flow, Academic Press, New York, New York.
- Irons, B. M. and S. Ahmad (1980), Techniques of Finite Elements, John Wiley and Sons, Inc., New York, New York.
- Kline, N. W., A. K. Runchal, and R. G. Baca (1983), PORFLO Computer Code: Users Guide, RHO-BW-CR-138 P, Rockwell Hanford Operations, Richland, Washington.
- Malvern, L. E. (1969), Introductions to the Mechanics of a Continuous Medium, Prentice-Hall, Inc., Englewood Cliffs, New Jersey.

- Sagar, B. and P. M. Clifton (1983), Numerical Modeling of Parametric Uncertainties in Flow Through Porous Media: Development of PORSTAT, RHO-BW-CR-140P, Rockwell Hanford Operations, Richland, Washington.
- Silling, S. A. (1983), Final Technical Position on Documentation of Computer Codes for High-Level Waste Management, NUREG-0856, U.S. Nuclear Regulatory Commission, Washington, D.C.
- Snow, D. T. (1969), "Anisotropic Permeability of Fractured Media," Water Resources, 5 (6).

This page intentionally left blank.

APPENDIX A

PROGRAM INTERNALS

INTRODUCTION

MAGNUM-2D is written in FORTRAN 77 and is currently operational on the Basalt Waste Isolation Project PRIME 750 computer system. Earlier development work was performed on a UNIVAC 1100/40, and an early version was converted to a CRAY 1. Attempts were made to use standard FORTRAN 77, but some PRIME specific functions were used in isolated incidents. These will be pointed out in the following sections.

SUBROUTINES: FUNCTIONAL DESCRIPTIONS

This subsection lists the modules comprising the MAGNUM-2D program and gives a brief explanation of the function of each.

MAGNUM-2D	The main program that controls the simulation by calling the appropriate subroutines. The MAGNUM-2D program initiates the solution for each time interval. For transient solutions, the dependent variables and their gradients are predicted for the next time step. The flow and temperature file, the initial condition file, and the restart data file are written in this module.
BANNER	Prints a banner page including the date and time at which the run is initiated. This subroutine also generates the unique run identifier.
INPUTS	Reads control option parameters, file unit assignments, time step parameters, scale factors, geometry data, initial and boundary conditions, and material properties.
ZONE	Determines the pointer array which designates midside nodes that are to be eliminated from computation. Mixed-order triangular or quadrilateral elements are constructed in transition zones.
LOADQ	Reads and/or computes the thermal loading rate for the source elements.
HEADR	Writes file headers to external files and reads the header record from the temperature input file, if specified.
SETUP	Sets up a pointer array for the element matrix and computes the total array storage requirement.
FPROP	A one-dimensional Hermitian polynomial expansion is used to approximate values of the viscosity, density, and coupling coefficient as functions of temperature.
VPROP	Computes density disparity and temperature correction to hydraulic conductivity.

FRONT Performs a Gauss elimination procedure with partial pivoting using a frontal solution method for unsymmetric matrices.

STIFF Forms the coefficient matrices for each finite element. Gaussian quadrature is used to numerically integrate the element equations.

RESOL Performs the back substitution for the updated right-hand sides. The algorithm is based on the frontal solution approach.

RIGHTSD Forms the right-hand side load vectors which take into account updated coefficients and source terms.

VEL Computes the Darcian velocity at the Gauss points from the hydraulic head and conductivity values. The velocities are written to the velocity file by this subroutine.

WRT Performs mass transfer of pivotal rows to the scratch file according to a flag. Calls subroutine RWND (rewind file), POSIT (position file), and BINOUT (write file).

RED Reads pivotal row from scratch file for back substitution with mass transfer of data. Calls subroutines POSIT (position file) and BININ (read file).

RWND A subroutine using PRIMOS calls to rewind the scratch file.

POSIT A subroutine using PRIMOS calls to position the file pointer relative to the current location.

BININ A subroutine using PRIMOS calls to read variable length binary records from disk.

BINOUT A subroutine using PRIMOS calls to write variable length binary records to disk.

PRINT Prints out the tabular results for temperature and hydraulic head at each nodal point. Specific boundary values are indicated in the output by an asterisk. If required, this subroutine also prints out the velocities.

BLKDAT A block data routine that contains shape function and derivative evaluations at the Gauss points within the elements. The data statements contain evaluations specific to Gaussian quadrature formulas based on 2×2 Gauss points for linear-shape functions and 3×3 Gauss points for quadratic-shape functions.

PARA This is an insert file containing the parameter statements used to define the program limits. See the next section for details.

PROGRAM LIMITS

All arrays that would need to be changed due to a need to increase the model size are dimensioned using "PARAMETER" statements. If required, the maximum limits can be increased or decreased by changing these parameters within the insert file PARA and recompiling the program. Note that PARA contains images that are included or inserted in a subroutine at compilation time. Most systems have such a facility. In PRIMOS, it is the FORTRAN "INSERT" directive.

The following parameters are used in MAGNUM-2D:

MAXE	Maximum number of elements
MAXP	Maximum number of node points
MAXMAT	Maximum number of material types
MAXH	Maximum number of heat source elements
MAXT	Maximum number of points used to define a heat generation profile
NMAX	Maximum front width of equation network array
NTT	Maximum number of time intervals
MAXP2 = (MAXP * 2)	Maximum number of unknown dependent variables in R1 array, i.e., change in hydraulic head and temperature at each node.

The arrays affected by the PARAMETERS listed are given below with the names of the COMMON blocks in which they reside:

COMMON /BLK1/	
DLT(NTT)	Time-step size for each time interval
NTS(NTT)	Number of time steps in each time interval
NTSG(NTT)	Print frequency within each time interval
TIME(NTT)	Time at the end of each time interval

COMMON /BLK2/

CORD(MAXP,2)	x- and y-coordinates for each node
IMAT(MAXE)	Material type of each element
NBC(MAXP2)	Equation number for computational nodes
NFIXH(MAXP)	Element ordering array
NOP(MAXE,8)	List of element - node connectivity

COMMON /BLK3/

R1(MAXP2)	The change in state variables solved for at each node
-----------	---

COMMON /BLK5/

ALPAL(MAXMAT)	Longitudinal dispersivity (m)
ALPAT(MAXMAT)	Transverse dispersivity (m)
BETA(MAXP)	Thermal coupling coefficient
CVM(MAXMAT)	Specific heat of the rock [J/(kg·°C)]
HKAX(MAXMAT)	Hydraulic conductivity in the x-direction (m/s)
HKAY(MAXMAT)	Hydraulic conductivity in the y-direction (m/s)
POROS(MAXMAT)	Effective porosity
Q(MAXE)	Thermal loads in the domain [J/(yr·m ³)]
RHOM(MAXMAT)	Rock density (kg/m ³)
SP1(MAXMAT)	Rock specific storage (1/m)
ST(MAXMAT)	Heat capacity of the water-rock system [J/(m ³ ·°C)]
THETA(MAXE)	Conductivity corrections based on the change in viscosity
TKK(MAXMAT,2)	Thermal conductivity in the x- and y-directions [J/(s·m·°C)]
VISCO(MAXP)	Viscosity at the previous step

VISCA(MAXP)	Viscosity at the current step
WIDTH(MAXMAT)	Fracture aperture (m)
BOUY(MAXP)	Density disparity term
RHOO	Water density at previous time step
RHOA(MAXP)	Current water density

COMMON /BLK10/

KIND(MAXE,4)	Element type: quadrilateral, triangle, or line
MIDB(MAXP)	Midside or corner node flag

COMMON /BLK17/

TDOT1(MAXP,2)	Head and temperature derivatives two time steps back
TNXT(MAXP)	Temperature input values from a separate run file
TOLD1(MAXP,2)	Head and temperature values two time steps back

COMMON /BLK18/

TDOT(MAXP,2)	Head and temperature derivatives for the current time step
TDOTO(MAXP,2)	Head and temperature derivatives for the previous time step
TNEW(MAXP,2)	Head and temperature values for the current time step
TOLD(MAXP,2)	Head and temperature values for the previous time step.

FILE MANIPULATION

All mass storage files used by MAGNUM-2D are referenced internally by their logical unit numbers (LUN). Each operating system has its own way of associating the LUN with the files needed or being created by an application

program. For this reason, the user is asked to consult the operating system reference publications for the machine being used. The remainder of this section will be aimed at the PRIME operating system (PRIMOS).

PREASSIGNED LOGICAL UNIT NUMBERS

All the files except three are associated with, or may be associated with, a file previously generated, or that will be generated, by MAGNUM-2D. The first exception is LUN 16, which is used as the "out-of-core" solution scratch file. This file must be opened but is for scratch purposes only. The second and third exceptions are LUN 5 and LUN 6 (internal variables IC=5 and IOUT=6), which are used for the main input file and printed output file, respectively. That is, all the information discussed in Section 4.2 enters MAGNUM-2D via LUN 5, and all reports of the results of the analyses are printed via LUN 6. Variables IC and IOUT are set in the main program and are passed through common block INOUT where needed.

THE PRIMOS FILES

In PRIMOS the LUNs are associated with the appropriate files by using the OPEN command. It should be noted that the PRIME version OF MAGNUM-2D requires special attention to the assignment and use of LUNs. The numbers used in Section 4.2 for card type B are the FORTRAN LUNs. These have a range starting with one and going to some maximum value (consult the current PRIME FORTRAN manual). These numbers are decimal numbers. The PRIMOS LUNs, however, are octal numbers and have an offset of four relative to their FORTRAN counterparts. The following table shows the arrangement.

FORTRAN (decimal)	PRIMOS (octal)
1	user terminal
2	paper tape
3	card reader
4	serial printer
5	1
6	2
7	3
8	4
9	5
10	6
11	7
12	10
13	11
.	.
.	.
.	.

Note that the arrangement shown means that the FORTRAN LUNs 5 and 6, for example, correspond to the PRIMOS LUNs 1 and 2, respectively.

SUBROUTINES: CONTROL AND HIERARCHY

A top level flowchart for the MAGNUM-2D program is shown in Figure A-1. In this figure the rectangular boxes denote subroutines, and the triangular boxes denote decisions. The flowchart depicts iteration in the solution at each time step; however, since applications of the code have never required more than a single iteration, the iteration limit is currently set to one. The full module hierarchy for the MAGNUM-2D program is depicted in Figure A-2.

CODE AVAILABILITY

The FORTRAN source code for MAGNUM-2D is not duplicated here for the sake of compactness, but it is available in the form of a paper listing and/or magnetic tape. Inquiries regarding MAGNUM-2D and requests for copies of the code should be directed to:

Mr. R. G. Baca
Rockwell Hanford Operations
Basalt Waste Isolation Project
Performance Assessment Group
P.O. Box 800
Richland, Washington 99352

PS84-2131 A-1

FIGURE A-1. Control Flow for MAGNUM-2D.

*PRIMOS (OPERATING SYSTEM SUBROUTINES)

PS84-213-9

FIGURE A-2. Subroutine Hierarchy for MAGNUM 2-D.

This page intentionally left blank.

APPENDIX B

PREPROCESSORS

INTRODUCTION

A finite-element code such as MAGNUM-2D requires an extensive input data set, including a geometry, initial conditions, and boundary conditions. The creation of this data set can be automated to some extent by providing software "tools" to help the modeler develop and handle the requisite data. The tools used to create the data, known collectively as "preprocessors," deal mostly with the input geometry data. Geometries may be created, refined, modified, optimized, verified, and plotted. Two other preprocessors exist for creating initial and boundary condition data.

This appendix lists the preprocessors available for use with MAGNUM-2D and gives a brief description of each. A brief discussion is provided of the steps that must be followed to use the preprocessors to generate a data set describing a model to be used for a simulation.

Note that this section is not intended to be an instruction manual for any of the preprocessors described herein. At present, the preprocessors are self-help interactive FORTRAN programs.

MAGNUM-2D PREPROCESSORS

The FEMESH code is used to generate arbitrarily shaped, finite-element geometries. The input for FEMESH is a coarse finite-element geometry of quadrilateral elements followed by some refinement specifications telling FEMESH how the coarse mesh is to be subdivided. This input must be in literal ASCII form. The input format for the coarse geometry is exactly like that required for the MAGNUM-2D geometry. This allows the user to generate the coarse mesh "by hand" using a standard text editor program. The user may also generate the coarse mesh using GEN and later add the refinement data by hand using an editor. The FEMESH code will generate triangular, as well as quadrilateral elements, but the input is restricted to quadrilaterals.

The GEN code is a simple processor for generating regular, rectangular finite-element geometries of quadrilateral or line elements. No prior preparation of input data is required. The program prompts the user for all required input. The output geometry may be chosen as a set of quadrilaterals or a network of line elements. The lower left-hand corner of the rectangular area generated may start at (0.0, 0.0), or at whatever coordinates the user requests. All the elements will have a common, user-specified material type. The data generated by GEN is written to a formatted file and may be suitably modified for use by the FEMESH code by adding the refinement data required (see FEMESH).

The MERGE code is a processor that combines two model geometries into a single geometry. This allows the creation of large, finite-element geometries in smaller parts. The two geometries to be combined must be compatible along the sides that will become common. No overlap in the geometries being combined is allowed except in the case of line elements where the line element nodes will be merged if they coincide with the two-dimensional element nodes. One of the geometries being merged may have an offset defined for the node locations during the merge. This often simplifies generation of the subgeometries.

The MESHER code reorders the elements and/or nodes of a finite-element geometry. Reordering of element numbers is performed to minimize the bandwidth for MAGNUM-2D or CHAINT during the solution phase of the programs. The technique used is not a true optimization. Instead, MESHER requires an input starting list of nodes from which a near-optimum order is generated. Several different starting lists may be compared in one MESHER run, and the best of these will be automatically retained. The starting list of nodes is best chosen as the nodes along the shortest side of the mesh. A feature of MESHER is the ability to list all the boundary nodes and to indicate the corner nodes, allowing the user to try various sides and to make comparisons.

The MOD code allows the user to make simple modifications to a geometry including node position, geometry scaling, rotating, mirroring, or translating; to change the slope, angle, material type, or connectivity; to recalculate the midside node positions; or to create new elements. This program will allow changes to be made to a binary file where an editor would be ineffectual.

The PLT code is used for plotting two-dimensional finite-element geometries. All three element types (quadrilaterals, triangles, and lines) are recognized. The plots produced are the mesh alone; the mesh with node, element, or material types numbered; single elements; and subregions of the entire mesh with all the above options. (Note: This program makes use of the DISSPLA graphics system by ISSCO. This library of FORTRAN graphics routines is necessary to run PLT on any computer system.)

The PURGE code is used to verify a geometry. Checks are made for some of the more common errors. These include errors in element connectivity specification, midside node placement, unused nodes and elements, duplicate nodes, node rotation, free elements, ill-defined elements, aspect ratios that are potentially unacceptable, elements that overlap or are distorted, and correctness of the ordering array. Obvious errors, such as unused nodes and elements, are corrected while more subtle errors are noted for the user to correct.

The REFINE code allows single elements to be divided into two smaller elements or two smaller elements to be combined into one larger element.

The TRGEN code will generate a finite-element transition geometry using triangular elements to go from a region of smaller elements to a region of larger elements.

The BCGEN code is used to generate a boundary condition data file for input to MAGNUM-2D or CHAINT. A geometry is read from a geometry file, and a search is made for all boundary nodes. These nodes are then listed in counterclockwise order, and two user-supplied subroutines, BCHEAD and BCTEMP, are called to generate the boundary conditions for head and temperature, respectively.

The ICGEN code is used to generate an initial condition data file for input to MAGNUM-2D or CHAINT. A geometry is read from a geometry file, and the initial conditions are calculated based on position (or other appropriate variable) by a user-supplied function.

The ICMOD code is more of a utility than a preprocessor. It allows the user to convert an initial condition file to a file that looks like a binary results file. This file may be gridded and contoured for inspection. Alternately, a binary results file may be converted for use as a formatted initial condition file.

DATA GENERATION WALK THROUGH

The first step in the generation of any finite-element representation is the determination of the exact geometric definition of the physical system. This should include dimensions and locations of all features associated with the region being modeled, such as voids, varying material types, heat and fluid sources, etc. Once this data is collected, the modeler must determine the optimum form of the model to ensure accurate mathematical representation of the region and, therefore, accurate results. If the area of highest gradient can be identified beforehand, the modeling effort is often simplified and the model size is limited since this allows the element density to be restricted to those high-gradient regions.

A typical method for the creation of the model is for the modeler to start with a sketch of the region to be modeled. Any identifiable subregions are then indicated (i.e., subregions composed of a single material, voids, etc.), and a plan is determined, such as modeling these subregions and merging them into a whole model. This technique will be assumed in the following discussion.

A data flow diagram for the preprocessors and files discussed in this section is shown in Figure B-1. It is recommended that the reader follow this diagram while reading the remainder of this appendix.

Often the first program to be used, and perhaps the only one needed depending on the complexity of the model, is GEN. If it is convenient to produce the entire model or complete subregions with GEN, the task is simplified; however, GEN may also be used to generate a preliminary coarse mesh to which the refinement data is added using an editor, and this file is then run through FEMESH to refine and enhance the mesh.

Note that in creating the mesh for subregions, care should be exercised to ensure that the boundary nodes are located at common geometric points so that merging the meshes is possible. If the points do not coincide or at least vary with a constant x- or y-dimension offset, it will be necessary to modify a potentially large number of coordinates before merging is feasible.

If a transition zone is necessary between regions of varying element densities (i.e., between regions of suspected high and low gradients), then TRGEN may be used to produce the zone as a separate region.

The various "pieces" of the model may be combined or merged using MERGE. This program will take any two geometry files and attempt to merge them at their common node points; thus, the user may have to use this program several times depending on the number of subregions being combined. The MERGE code (like MESHER, MOD, and REFINER) has the ability to write the new geometry back into an old file or onto a new file, thus preserving the subregion data files for future use. A precaution is to maintain all the component geometries until the model generation, or some phase of it, has been verified to be correct. This allows the user to redo a portion of the geometry from the last correct phase in case a mistake is made.

At any point in the model generation procedure, the program PLT may be used to view the model. It is helpful to have hard copies of the element and node number plots at hand when merging geometries.

Often the automatically generated finite-element geometry is not sufficiently accurate or the region is too intricate to attempt defining adequate constraints for automatic generation. In these cases it is up to the modeler to amend and modify the geometry with a text editor to produce the desired results. The MOD program will allow the user to change node locations or connectivity. This is convenient when the material boundaries require specific location of elements or midside nodes do not fall where they should when generated automatically. In addition, MOD will allow the user to mirror or translate geometries so the modeler may use any symmetry in the model. The REFINER program is useful in "fine tuning" a geometry because it will allow the user to produce a fine mesh in just a few elements without defining a subregion. Both MOD and REFINER provide flexibility in "refitting" a model, that is, modifying it after it is complete for sensitivity analyses or because of features uncovered by the initial analysis.

After the model parts have been assembled and the actual node locations have been fine tuned, it is wise to run PURGE on the geometry. This ensures that many of the innocuous errors that propagate from the creation process are removed. These errors may not be large in themselves, but they may create great variations in the final simulation results if they occur in a critical location. It is probably a good idea to make at least one PLT run on the final geometry file for a final visual check. A hard copy of the node number, material type, and element number plots is essential in order to analyze the results of a simulation in detail.

When the geometry file has been created, it may be in one of two forms: either binary or formatted (ASCII, BCD, etc.). Either of these is readable from MAGNUM-2D or CHAINT. It may be utilized by reading the file directly from mass storage (in coded or binary form) or, in the case of a coded file, it may be edited into an input file that contains all the other data necessary for the simulation (boundary conditions, material properties, and other data as contained in card types A through R).

Using an editor program, the remainder of the data required for simulation as described in card types A through R is usually entered into a mass storage file, the MAGNUM-2D data input file. Card types G and H, which describe the geometry, may be entered from the coded form of the geometry file or may be omitted and read from a binary or formatted mass storage file at execution time by specifying the logical unit number on card type C. The initial and boundary conditions, however, must be included in the MAGNUM-2D data input file. If they are few or straightforward, they may be entered directly by using the editor. If they are numerous, the two programs ICGEN and BCGEN may be used to produce files of initial and boundary conditions, respectively, which are edited into the data input file.

A data flow diagram for the MAGNUM-2D and CHAINT environment and the data files involved is shown in Figure B-2. Note that for a nonrestart job, only two input files are needed: the MAGNUM-2D data input file and the geometry file. (Only one input file is needed if the geometry input is included directly on the MAGNUM-2D data input file.)

PS84-2131-8

FIGURE B-1. Preprocessor Data Flow.

FIGURE B-2. MAGNUM/CHAINT Data Flow.

This page intentionally left blank.

APPENDIX C

POSTPROCESSORS

INTRODUCTION

A finite-element code, such as MAGNUM-2D or CHAINT, creates a large amount of output data that are often difficult to interpret in their raw form. Postprocessors provide a means of graphically displaying output data in a variety of modes. These may be two-dimensional contour plots of the results, cross-sectional plots of the data versus position, or time history plots for the data at a given location. In addition, pathlines, streamlines, velocity vectors, and mass flux data may be plotted.

This appendix lists the most commonly used postprocessors for MAGNUM-2D and gives a brief description of each.

Note that this section is not intended to be an instruction manual for any of the postprocessors described herein. Each of the graphics postprocessors is a self-help interactive FORTRAN program.

All of the graphics postprocessors utilize subroutines from the ISSCO DISSPLA graphics system. The DISSPLA graphics system is mandatory for utilization of these programs.

MAGNUM-2D POSTPROCESSORS

A data flow diagram for the postprocessors and files discussed in this section is shown in Figure C-1. Note from Figure B-2 that there are five files output from MAGNUM-2D but that only three are shown in Figure C-1. These are the only files that are used in postprocessing. They are the geometry file, the MAGNUM-2D groundwater velocity file, and the MAGNUM-2D flow and temperature file.

First and probably foremost is the program CHAINT. While not strictly a postprocessor, it may utilize the MAGNUM-2D groundwater velocity file as input to define the flow field to be used in solving the mass transport equations. No manipulation or modification of the file is required before its use by CHAINT.

The GRIDDER postprocessor interpolates nonregularly spaced nodal data onto a regular rectangular grid to allow contouring. The GRIDDER postprocessor ignores data associated with line elements. The sister program LEGRID will grid line elements only. They accept the MAGNUM-2D flow and temperature file as input and place the output data in an output file that may be used by CONTOUR, HISTORY, AND PARAM.

The CONTOUR postprocessor is used to draw contour line plots from data given as a function of two space variables. The MAGNUM-2D flow and temperature data must be interpolated onto a regular, rectangular grid using

GRIDDER prior to using CONTOUR. This program is totally interactive, and the user is prompted to enter commands to set the desired plotting options, such as contour levels, background, and time plane of interest.

The HISTORY postprocessor is used to plot results as a function of time. The data histories corresponding to chosen locations in a finite-element geometry are plotted. The histories of several points may be plotted on a single graph. The MAGNUM-2D flow and temperature data must be interpolated onto a regular, rectangular grid using GRIDDER prior to using HISTORY.

The PARAM postprocessor is used to plot data cross sections. Data are plotted as a function of x or y, with either y, x, or t being varied as a parameter. Several curves may be plotted on a single graph. The MAGNUM-2D flow and temperature data must be interpolated onto a regular, rectangular grid using GRIDDER prior to using PARAM.

The VELPLT postprocessor is used to plot velocity vectors from the groundwater velocity file. The vectors can be scaled or plotted at uniform lengths and may be generated with a background of the geometry boundaries. The vectors may also be drawn in their true directions or relative to the geometry background. The VELPLT postprocessor also requires the geometry file as input. The user is prompted for both file names and all directives.

The PATH postprocessor generates plots of flow paths through a two-dimensional finite-element geometry. Both pathlines (time varying flow fields) and streamlines (flow at a single time plane) can be created. The path length and traveltime for each pathline or streamline are computed and printed to the terminal after each plot is complete. The user is prompted both for file names and for all directives to select subplots, time markers, background, and pathline and streamline starting points. Input data for PATH include the groundwater velocity file and the corresponding geometry file.

The PLOT1 postprocessor is used to plot the flow and temperature file on an element by element basis. A three-dimensional surface of the data is plotted along with a two-dimensional sketch of the element with written node values at each node. This program is useful as a diagnostic tool in the analysis of data anomalies. An error of insufficient geometry resolution often can be determined by examining the surface plot for data corresponding to a single element. The PLOT1 postprocessor also requires the geometry file as input.

PS84-2131-6

FIGURE C-1. Postprocessor Data Flow.

This page intentionally left blank.

APPENDIX D

EXAMPLE CASES

Reproduced listings of the PRIMOS commands, input, and printed output for two example problems are contained in this appendix.

The first example is a one-dimensional coupled flow and heat transfer problem with a thermal load. A single column of elements with a linear head gradient is defined from bottom to top with a single heat source specified in the element at the bottom end (element 1). The resulting head and temperature cross sections at selected times are shown in graphic form in Figures D-1 and D-2 as produced from the postprocessor PARAM. The geometry in this example is specified in the data input file, Listing D-1. The PRIMOS commands used to run this example are shown in Listing D-2. The resulting output is shown in Listing D-3.

The second example is a two-dimensional flow problem with heat transfer and a thermal load. The model is shown in Figures D-3 and D-4. Note that Figure D-3 is only the mesh; the node numbering option in the PLT program was not used. Also, Figure D-4 is a close-up of a specific detail on the model and includes element numbers. The model is typical of the type that might be used for a repository simulation (although much simplified) showing perhaps a bored repository with provisions for modeling the host rock, the grout or backfill, and the waste container. The semicircular area containing elements 70, 71, 84, etc., are heat source elements, and both the top and bottom boundaries are specified to be at 50 °C. The top boundary is also specified to have a 1.0-m hydraulic head while the bottom is 1.2 m. The simulation is set to run for 10 yr. Figures D-5 through D-10 show the head and temperature distributions at selected times ranging from 0-10 yr. All these plots were generated using CONTOUR. Figures D-11 and D-12 show the head and temperature histories of five specific points in the model, all of which lie along the horizontal plane of symmetry. The data input file is shown in Listing D-4. Note that the geometry in this case has been defined on an external mass storage file and has been specified as LUN 11. The PRIMOS commands used to run this example are shown in Listing D-5. Note also the specification of Unit 11 to correspond to the filename VEL. The resulting report file is shown in Listing D-6.

FIGURE D-1. Hydraulic Head Profiles for Test Case One.

1-D VERTICAL FLOW WITH A HEAT SOURCE

1206041129

FIGURE D-2. Temperature Profiles for Test Case One.

FIGURE D-3. Finite-Element Grid for Test Case Two.

FIGURE D-4. Closeup View of Heat Source Gridding with Element Numbers for Test Case Two.

FIGURE D-5. Initial Hydraulic Head Contours for Test Case Two.

FIGURE D-6. Hydraulic Head Contours at 0.6 Year for Test Case Two.

FIGURE D-7. Hydraulic Head Contours at Two Years for Test Case Two.

FIGURE D-8. Hydraulic Head Contours at 10 Years for Test Case Two.

FIGURE D-9. Temperature Contours at 0.2 Year for Test Case Two.

FIGURE D-10. Temperature Contours at 10 Years for Test Case Two.

FIGURE D-11. Time History of Hydraulic Head at Selected Points for Test Case Two.

FIGURE D-12. Time History of Temperature at Selected Points for Test Case Two.

LISTING D-1. Input Data File for Test Case One. (Sheet 1 of 3)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

```

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION
0 1 1 53 10 1 1 1 1 1 0 0 /*CNTRL
0 8 0 0 11 12 0 0.0 0.0 0.0 0.0 /*FILE UNITS
4 4 1.8 0.0 0.0 0.0 /*STRT TIME
3 3 0.5
6 6 1.0
6 6 2.5
6 6 3.0
9999
1.0 1.0 0.0 0.0 0.0 0.0 /*SCALE
1 1 2 3 5 8 7 6 4 1 1 /*GEOM
2 6 7 8 10 13 12 11 9 1 2
3 11 12 13 15 18 17 16 14 1 3
4 16 17 18 20 23 22 21 19 1 4
5 21 22 23 25 28 27 26 24 1 5
6 26 27 28 30 33 32 31 29 1 6
7 31 32 33 35 38 37 36 34 1 7
8 36 37 38 40 43 42 41 39 1 8
9 41 42 43 45 48 47 46 44 1 9
10 46 47 48 50 53 52 51 49 1 10
1 -5.000 0.000 0.00 0.00
2 0.000 0.000 0.00 0.00
3 5.000 0.000 0.00 0.00
4 -5.000 7.500 0.00 0.00
5 5.000 7.500 0.00 0.00
6 -5.000 15.000 0.00 0.00
7 0.000 15.000 0.00 0.00
8 5.000 15.000 0.00 0.00
9 -5.000 20.000 0.00 0.00
10 5.000 20.000 0.00 0.00
11 -5.000 25.000 0.00 0.00
12 0.000 25.000 0.00 0.00
13 5.000 25.000 0.00 0.00
14 -5.000 27.500 0.00 0.00
15 5.000 27.500 0.00 0.00
16 -5.000 30.000 0.00 0.00
17 0.000 30.000 0.00 0.00
18 5.000 30.000 0.00 0.00
19 -5.000 32.500 0.00 0.00
20 5.000 32.500 0.00 0.00
21 -5.000 35.000 0.00 0.00
22 0.000 35.000 0.00 0.00
23 5.000 35.000 0.00 0.00
24 -5.000 37.500 0.00 0.00
25 5.000 37.500 0.00 0.00
26 -5.000 40.000 0.00 0.00
27 0.000 40.000 0.00 0.00
28 5.000 40.000 0.00 0.00
29 -5.000 45.000 0.00 0.00
30 5.000 45.000 0.00 0.00
31 -5.000 50.000 0.00 0.00
32 0.000 50.000 0.00 0.00
33 5.000 50.000 0.00 0.00

```

LISTING D-1. Input Data File for Test Case One. (Sheet 2 of 3)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

34	-5.000	56.000	0.00	0.00
35	5.000	56.000	0.00	0.00
36	-5.000	62.000	0.00	0.00
37	0.000	62.000	0.00	0.00
38	5.000	62.000	0.00	0.00
39	-5.000	68.500	0.00	0.00
40	5.000	68.500	0.00	0.00
41	-5.000	75.000	0.00	0.00
42	0.000	75.000	0.00	0.00
43	5.000	75.000	0.00	0.00
44	-5.000	80.000	0.00	0.00
45	5.000	80.000	0.00	0.00
46	-5.000	85.000	0.00	0.00
47	0.000	85.000	0.00	0.00
48	5.000	85.000	0.00	0.00
49	-5.000	92.500	0.00	0.00
50	5.000	92.500	0.00	0.00
51	-5.000	100.000	0.00	0.00
52	0.000	100.000	0.00	0.00
53	5.000	100.000	0.00	0.00

1	52.00	1.00E+00
2	52.00	1.00E+00
3	52.00	1.00E+00
4	52.00	9.25E-01
5	52.00	9.25E-01
6	52.00	8.50E-01
7	52.00	8.50E-01
8	52.00	8.50E-01
9	52.00	8.00E-01
10	52.00	8.00E-01
11	52.00	7.50E-01
12	52.00	7.50E-01
13	52.00	7.50E-01
14	52.00	7.25E-01
15	52.00	7.25E-01
16	52.00	7.00E-01
17	52.00	7.00E-01
18	52.00	7.00E-01
19	52.00	6.75E-01
20	52.00	6.75E-01
21	52.00	6.50E-01
22	52.00	6.50E-01
23	52.00	6.50E-01
24	52.00	6.25E-01
25	52.00	6.25E-01
26	52.00	6.00E-01
27	52.00	6.00E-01
28	52.00	6.00E-01
29	52.00	5.50E-01
30	52.00	5.50E-01
31	52.00	5.00E-01
32	52.00	5.00E-01
33	52.00	5.00E-01

/*IC

LISTING D-1. Input Data File for Test Case One. (Sheet 3 of 3)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

34	52.00	4.40E-01						
35	52.00	4.40E-01						
36	52.00	3.80E-01						
37	52.00	3.80E-01						
38	52.00	3.80E-01						
39	52.00	3.15E-01						
40	52.00	3.15E-01						
41	52.00	2.50E-01						
42	52.00	2.50E-01						
43	52.00	2.50E-01						
44	52.00	2.00E-01						
45	52.00	2.00E-01						
46	52.00	1.50E-01						
47	52.00	1.50E-01						
48	52.00	1.50E-01						
49	52.00	7.50E-02						
50	52.00	7.50E-02						
51	52.00	0.00E+01						
52	52.00	0.00E+01						
53	52.00	0.00E+01						
6								/*B. C.
1	01	52.0	1.0					
2	01	52.0	1.0					
3	01	52.0	1.0					
51	11	52.0	0.0					
52	11	52.0	0.0					
53	11	52.0	0.0					
1	1000.0	0.200	0.200	1.0E-1	5.00E-7	5.00E-7	ROCK	
	1.0E-2	1800.	1.E-02	1.E-02	0.0			
1	2	1.0					/* LOAD	
1								
0.0	1.00E+6	10000.	1.00E+6					

LISTING D-2. The PRIMOS Command File for Test Case One.

EAT SEERUN

```

EAT SEERUN
EAT PRT
EAT RLT
COMO SEERUN
DATE
DELSEQ ALL
TIME
OPEN DATA 1 1
OPEN PRT 2 3
OPEN WORKSPACE 14 3
OPEN RLT 4 3
OPEN GEDM 7 3
OPEN VEL 10 3
SEQ SYSTEMS>FEM>MAGNUM>#MAGNUM
TIME
CLOSE WORKSPACE
EAT WORKSPACE
COMO -END
CLOSE ALL
COMO -TTY
    
```

LISTING D-3. Output Report File for Test Case One. (Sheet 1 of 13)

```
###      ###      ###      ####      ###      *      *      *      ###      ###
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *      *
```

VERSION 3.0 (Revision 1.)

THU, JUL 12 1984

11:13:09

ID= 712841113

LISTING D-3. Output Report File for Test Case One. (Sheet 2 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

TABLE 1. - PRINCIPAL PROBLEM SPECIFICATIONS

SIMULATION MODE (0-TIME VARYING, .NE. 0-STEADY STATE).....	0
HEAT TRANSPORT (0-ISOTHERMAL, .NE. 0-NONISOTHERMAL).....	1
GROUNDWATER FLOW (0-HYDROSTATIC, .NE. 0-FLUID FLOW).....	1
NUMBER OF NODES.....	53
NUMBER OF ELEMENTS.....	10
NUMBER OF ROCK TYPES.....	1
INITIAL CONDITION INPUTS (0-UNIFORM, 1-SPATIALLY VARYING)	1
INPUT DATA PRINT CONTROL (0-PARTIAL ECHO, 1-TOTAL ECHO...	1
DIAGNOSTIC PRINTOUT (0-NO ACTION, 1-CONVERGENCE INFO).....	1
VELOCITY PRINT CONTROL (0-SUPPRESS PRINT, 1-PRINT VEL)...	1
RESULTS FILE WRITE CONTROL (0-AT TIME STEP, 1-AT PRT FREQ)	0
COORD SYSTEM (0-CARTESIAN, 1-AXISYMMETRIC ABOUT X=0.)....	0
INPUT RESTART FILE (LU).....	0
RESULTS FILE (LU).....	8
OUTPUT RESTART FILE (LU).....	0
INPUT GEOMETRY FILE (LU).....	0
OUTPUT GEOMETRY FILE (LU).....	11
STREAM/PATHLINE DATA FILE (LU).....	12
TEMPERATURE INPUT FILE (TEMPERATURE INACTIVE).....	0
INITIAL CONDITION OUTPUT FILE (FORMATTED).....	0
SCALE FACTOR FOR X COORDINATES.....	1.00
SCALE FACTOR FOR Y COORDINATES.....	1.00
LEFT BOUNDARY FOR QUAD ELEMENTS.....	0.00
RIGHT BOUNDARY FOR QUAD ELEMENTS.....	0.00
TOP BOUNDARY FOR QUAD ELEMENTS.....	0.00
BOTTOM BOUNDARY FOR QUAD ELEMENTS.....	0.00
START TIME (YEARS).....	0.00
WEIGHTING FACTOR.....	1.8
DENSITY/VISCOUSITY REFERENCE TEMP (>0.05 TO IMPLEMENT)...	0.0

TIME CONTROL AND RUN SPECIFICATIONS

NUMBER OF TIME STEPS	PRINT INTERVAL	TIME STEP	TIME(YEARS)
4	4	0.5000	2.000
3	3	1.000	5.000
6	6	2.500	20.00
6	6	5.000	50.00

LISTING D-3. Output Report File for Test Case One. (Sheet 3 of 13)

TABLE 2. - NODE POINT COORDINATES

0

NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD
1	-5.00	0.00	15	5.00	27.50	29	-5.00	45.00	43	5.00	75.00
2	0.00	0.00	16	-5.00	30.00	30	5.00	45.00	44	-5.00	80.00
3	5.00	0.00	17	0.00	30.00	31	-5.00	50.00	45	5.00	80.00
4	-5.00	7.50	18	5.00	30.00	32	0.00	50.00	46	-5.00	85.00
5	5.00	7.50	19	-5.00	32.50	33	5.00	50.00	47	0.00	85.00
6	-5.00	15.00	20	5.00	32.50	34	-5.00	56.00	48	5.00	85.00
7	0.00	15.00	21	-5.00	35.00	35	5.00	56.00	49	-5.00	92.50
8	5.00	15.00	22	0.00	35.00	36	-5.00	62.00	50	5.00	92.50
9	-5.00	20.00	23	5.00	35.00	37	0.00	62.00	51	-5.00	100.00
10	5.00	20.00	24	-5.00	37.50	38	5.00	62.00	52	0.00	100.00
11	-5.00	25.00	25	5.00	37.50	39	-5.00	68.50	53	5.00	100.00
12	0.00	25.00	26	-5.00	40.00	40	5.00	68.50			
13	5.00	25.00	27	0.00	40.00	41	-5.00	75.00			
14	-5.00	27.50	28	5.00	40.00	42	0.00	75.00			

TABLE 3. - ELEMENT/NODE CONNECTIVITY

ELEMENT	CONNECTIONS								TYPE	ORDER	ELEMENT	CONNECTIONS								TYPE	ORDER
M	N1	N2	N3	N4	N5	N6	N7	N8			M	N1	N2	N3	N4	N5	N6	N7	N8		
1	1	2	3	5	9	17	4	4	1	2	6	26	27	28	30	33	32	31	29	1	6
2	6	7	8	10	13	12	11	9	1	2	7	31	32	33	35	38	37	36	34	1	7
3	11	12	13	15	18	17	16	14	1	3	8	36	37	38	40	43	42	41	39	1	8
4	16	17	18	20	23	22	21	19	1	4	9	41	42	43	45	48	47	46	44	1	9
5	21	22	23	25	28	27	26	24	1	5	10	46	47	48	50	53	52	51	49	1	10

LISTING D-3. Output Report File for Test Case One. (Sheet 4 of 13)

TABLE 4. - INITIAL CONDITIONS

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	52.00	1.00	19	52.00	0.67	37	52.00	0.38
2	52.00	1.00	20	52.00	0.67	38	52.00	0.38
3	52.00	1.00	21	52.00	0.65	39	52.00	0.31
4	52.00	0.92	22	52.00	0.65	40	52.00	0.31
5	52.00	0.92	23	52.00	0.65	41	52.00	0.25
6	52.00	0.85	24	52.00	0.63	42	52.00	0.25
7	52.00	0.85	25	52.00	0.63	43	52.00	0.25
8	52.00	0.85	26	52.00	0.60	44	52.00	0.20
9	52.00	0.80	27	52.00	0.60	45	52.00	0.20
10	52.00	0.80	28	52.00	0.60	46	52.00	0.15
11	52.00	0.75	29	52.00	0.55	47	52.00	0.15
12	52.00	0.75	30	52.00	0.55	48	52.00	0.15
13	52.00	0.75	31	52.00	0.50	49	52.00	0.07
14	52.00	0.72	32	52.00	0.50	50	52.00	0.07
15	52.00	0.72	33	52.00	0.50	51	52.00	0.00
16	52.00	0.70	34	52.00	0.44	52	52.00	0.00
17	52.00	0.70	35	52.00	0.44	53	52.00	0.00
18	52.00	0.70	36	52.00	0.38			

TABLE 5. - SPECIFIED BOUNDARY CONDITIONS

NUMBER OF SPECIFIED BOUNDARY NODES

6

NODE	TYPE	T(C)	H(M)
1	(01)	52.000	1.000
2	(01)	52.000	1.000
3	(01)	52.000	1.000
51	(11)	52.000	0.000
52	(11)	52.000	0.000
53	(11)	52.000	0.000

LISTING D-3. Output Report File for Test Case One. (Sheet 5 of 13)

TABLE 6. - ROCK PROPERTIES

PARAMETER	ROCK TYPES
	1 ROCK
1. SPECIFIC HEAT (J/KG-C)	1.000E+03
2. THERMAL CONDUCTIVITY IN X (J/SEC-M-C)	2.000E-01
3. THERMAL CONDUCTIVITY IN Y (J/SEC-M-C)	2.000E-01
4. EFFECTIVE POROSITY (FRACTION)	1.000E-01
5. HYDRAULIC CONDUCTIVITY (KXX-M/SEC)	5.000E-07
6. HYDRAULIC CONDUCTIVITY (KZZ-M/SEC)	5.000E-07
7. SPECIFIC STORAGE (1/M)	1.000E-02
8. ROCK DENSITY (KG/M**3)	1.800E+03
9. LONGITUDINAL DISPERSIVITY (M)	1.000E-02
10. LATERAL DISPERSIVITY (M)	1.000E-02
11. FRACTURE/FAULT THICKNESS (M)	0.000E-01

LISTING D-3. Output Report File for Test Case One. (Sheet 6 of 13)

TABLE 7. - HEAT GENERATION HISTORY

NUMBER OF HEAT SOURCE ELEMENTS..... 1
 NUMBER OF TIME POINTS..... 2
 SCALE FACTOR FOR HEAT LOAD..... 1.00

HEAT SOURCE ELEMENT NUMBER

1

TIME (YR)	THERMAL LOAD (J/YR-M**3)
0.000	0.100E+07
0.100E+05	0.100E+07

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS ON YEAR 2.000

NODE	T(C)	H(M)		NODE	T(C)	H(M)		NODE	T(C)	H(M)
1	52.80	1.000	*	19	52.00	0.6793		37	52.00	0.3818
2	52.80	1.000	*	20	52.00	0.6793		38	52.00	0.3818
3	52.80	1.000	*	21	52.00	0.6540		39	52.00	0.3164
4	52.90	0.9281		22	52.00	0.6540		40	52.00	0.3164
5	52.90	0.9281		23	52.00	0.6540		41	52.00	0.2511
6	52.49	0.8556		24	52.00	0.6288		42	52.00	0.2511
7	52.49	0.8556		25	52.00	0.6288		43	52.00	0.2511
8	52.49	0.8556		26	52.00	0.6035		44	52.00	0.2008
9	52.04	0.8036		27	52.00	0.6035		45	52.00	0.2008
10	52.04	0.8036		28	52.00	0.6035		46	52.00	0.1506
11	52.01	0.7551		29	52.00	0.5531		47	52.00	0.1506
12	52.01	0.7551		30	52.00	0.5531		48	52.00	0.1506
13	52.01	0.7551		31	52.00	0.5027		49	52.00	0.7530E-01
14	52.01	0.7298		32	52.00	0.5027		50	52.00	0.7530E-01
15	52.01	0.7298		33	52.00	0.5027		51	52.00	* 0.0000 *
16	52.00	0.7046		34	52.00	0.4422		52	52.00	* 0.0000 *
17	52.00	0.7046		35	52.00	0.4422		53	52.00	* 0.0000 *
18	52.00	0.7046		36	52.00	0.3818				

ITERATION NUMBER 1, MAX REL CHANGE (TEMP) = 4.6735E-03, MAX REL CORRECTION = 4.6107E-05
 ITERATION NUMBER 1, MAX REL CHANGE (HEAD) = 2.4432E-03, MAX REL CORRECTION = 1.2964E-03

LISTING D-3. Output Report File for Test Case One. (Sheet 7 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS FOR VELOCITY (M/YR) OF YEAR 2.000

ELEMENT		QSS PNT 1	QSS PNT 2	QSS PNT 3	QSS PNT 4	QSS PNT 5	QSS PNT 6	QSS PNT 7	QSS PNT 8	QSS PNT 9
1	VEL X	-4.3931E-13	1.1337E-13	3.1177E-13	-2.1257E-13	2.8342E-14	2.5508E-13	-2.5508E-13	-1.4171E-14	-1.4171E-13
	VEL Y	1.5954E-01	1.5954E-01	1.5954E-01	1.6076E-01	1.6076E-01	1.6076E-01	1.5954E-01	1.5954E-01	1.5954E-01
2	VEL X	-1.4122E-12	6.3233E-14	1.2366E-12	-1.0117E-12	-4.2156E-14	9.4147E-13	-5.4100E-13	8.4311E-14	3.8643E-13
	VEL Y	1.6016E-01	1.6016E-01	1.6016E-01	1.5930E-01	1.5930E-01	1.5930E-01	1.6045E-01	1.6045E-01	1.6045E-01
3	VEL X	3.5016E-15	5.2524E-14	-1.8559E-13	-5.6026E-13	4.2019E-14	6.8632E-13	-1.2746E-12	1.0855E-13	1.2081E-12
	VEL Y	1.5949E-01	1.5949E-01	1.5949E-01	1.5956E-01	1.5956E-01	1.5956E-01	1.5964E-01	1.5964E-01	1.5964E-01
4	VEL X	-1.4005E-14	6.6524E-14	-1.5055E-13	1.2605E-13	2.8010E-14	-8.4030E-14	1.8907E-13	3.1511E-14	-3.4663E-13
	VEL Y	1.5934E-01	1.5934E-01	1.5934E-01	1.5940E-01	1.5940E-01	1.5940E-01	1.5946E-01	1.5946E-01	1.5946E-01
5	VEL X	1.7506E-14	1.0504E-13	-2.8010E-14	2.8010E-14	4.2014E-14	8.4029E-14	-4.5516E-14	4.2014E-14	-9.4532E-14
	VEL Y	1.5919E-01	1.5919E-01	1.5919E-01	1.5925E-01	1.5925E-01	1.5925E-01	1.5930E-01	1.5930E-01	1.5930E-01
6	VEL X	-7.0024E-15	6.6523E-14	-2.1007E-14	-3.5012E-14	-1.4005E-14	2.8010E-14	-1.0504E-14	6.6523E-14	-6.3022E-14
	VEL Y	1.5895E-01	1.5895E-01	1.5895E-01	1.5905E-01	1.5905E-01	1.5905E-01	1.5915E-01	1.5915E-01	1.5915E-01
7	VEL X	-4.5516E-14	5.6019E-14	-5.6019E-14	-2.8010E-14	-6.3022E-14	2.8010E-14	-1.7506E-14	5.2518E-14	2.8010E-14
	VEL Y	1.5869E-01	1.5869E-01	1.5869E-01	1.5879E-01	1.5879E-01	1.5879E-01	1.5889E-01	1.5889E-01	1.5889E-01
8	VEL X	-1.4005E-14	3.3261E-14	-1.7506E-14	-2.1007E-14	-2.1007E-14	-1.4005E-14	1.7506E-14	6.6523E-14	1.9257E-14
	VEL Y	1.5848E-01	1.5848E-01	1.5848E-01	1.5856E-01	1.5856E-01	1.5856E-01	1.5864E-01	1.5864E-01	1.5864E-01
9	VEL X	-1.5755E-14	2.4508E-14	-2.4508E-14	-1.0504E-14	-1.4005E-14	3.5012E-15	7.0024E-15	4.5516E-14	1.7506E-15
	VEL Y	1.5837E-01	1.5837E-01	1.5837E-01	1.5841E-01	1.5841E-01	1.5841E-01	1.5845E-01	1.5845E-01	1.5845E-01
10	VEL X	-3.0635E-14	-6.1271E-15	-2.5384E-14	-8.7530E-16	8.7530E-16	6.1271E-15	1.6193E-14	3.7200E-14	8.3153E-15
	VEL Y	1.5831E-01	1.5831E-01	1.5831E-01	1.5833E-01	1.5833E-01	1.5833E-01	1.5835E-01	1.5835E-01	1.5835E-01

LISTING D-3. Output Report File for Test Case One. (Sheet 8 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS ON YEAR 5.000

NODE	T(C)	H(M)		NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	54.24	1.000	*	19	52.00	0.6899	37	52.00	0.3877
2	54.24	1.000	*	20	52.00	0.6899	38	52.00	0.3877
3	54.24	1.000	*	21	52.00	0.6642	39	52.00	0.3213
4	54.31	0.9341		22	52.00	0.6642	40	52.00	0.3213
5	54.31	0.9341		23	52.00	0.6642	41	52.00	0.2549
6	53.35	0.8665		24	52.00	0.6385	42	52.00	0.2549
7	53.35	0.8665		25	52.00	0.6385	43	52.00	0.2549
8	53.35	0.8665		26	52.00	0.6129	44	52.00	0.2039
9	52.37	0.8175		27	52.00	0.6129	45	52.00	0.2039
10	52.37	0.8175		28	52.00	0.6129	46	52.00	0.1529
11	52.06	0.7669		29	52.00	0.5616	47	52.00	0.1529
12	52.06	0.7669		30	52.00	0.5616	48	52.00	0.1529
13	52.06	0.7669		31	52.00	0.5104	49	52.00	0.7646E-01
14	52.03	0.7412		32	52.00	0.5104	50	52.00	0.7646E-01
15	52.03	0.7412		33	52.00	0.5104	51	52.00	* 0.0000 *
16	52.01	0.7155		34	52.00	0.4490	52	52.00	* 0.0000 *
17	52.01	0.7155		35	52.00	0.4490	53	52.00	* 0.0000 *
18	52.01	0.7155		36	52.00	0.3877			

ITERATION NUMBER 1, MAX REL CHANGE (TEMP) = 9.0616E-03, MAX REL CORRECTION = 1.0331E-04
 ITERATION NUMBER 1, MAX REL CHANGE (HEAD) = 5.3353E-03, MAX REL CORRECTION = 5.7984E-04

LISTING D-3. Output Report File for Test Case One. (Sheet 9 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS FOR VELOCITY (M/YR) OF YEAR 5.000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
1	VEL X	-3.4673E-13	1.3002E-13	2.4560E-13	-1.4447E-13	5.7788E-14	2.1670E-13	-2.5282E-13	-2.1671E-14	-1.5169E-13
	VEL Y	1.6149E-01	1.6149E-01	1.6149E-01	1.6407E-01	1.6407E-01	1.6407E-01	1.6143E-01	1.6143E-01	1.6143E-01
2	VEL X	-7.7825E-14	1.2735E-13	1.4150E-14	-2.1225E-13	-4.2450E-14	1.5565E-13	-3.6082E-13	9.1974E-14	1.8395E-13
	VEL Y	1.6314E-01	1.6314E-01	1.6314E-01	1.6158E-01	1.6158E-01	1.6158E-01	1.6337E-01	1.6337E-01	1.6337E-01
3	VEL X	-1.2612E-13	3.5032E-15	-1.7516E-13	-7.0065E-14	-2.8026E-14	-1.4013E-14	-7.0065E-15	1.2962E-13	3.5032E-15
	VEL Y	1.6216E-01	1.6216E-01	1.6216E-01	1.6219E-01	1.6219E-01	1.6219E-01	1.6233E-01	1.6233E-01	1.6233E-01
4	VEL X	3.1164E-13	1.2606E-13	-2.6962E-13	2.1009E-13	8.4037E-14	-5.6025E-14	-1.4006E-14	3.5016E-14	-1.2606E-13
	VEL Y	1.6192E-01	1.6192E-01	1.6192E-01	1.6199E-01	1.6199E-01	1.6199E-01	1.6208E-01	1.6208E-01	1.6208E-01
5	VEL X	3.5013E-15	9.8035E-14	2.1008E-14	1.4005E-14	-7.0025E-14	-1.6806E-13	2.1358E-13	3.8514E-14	-3.8514E-13
	VEL Y	1.6174E-01	1.6174E-01	1.6174E-01	1.6181E-01	1.6181E-01	1.6181E-01	1.6188E-01	1.6188E-01	1.6188E-01
6	VEL X	-3.5012E-14	4.2014E-14	-6.6523E-14	-7.0024E-14	-2.1007E-14	4.2014E-14	-3.5012E-14	1.2954E-13	6.3022E-14
	VEL Y	1.6145E-01	1.6145E-01	1.6145E-01	1.6157E-01	1.6157E-01	1.6157E-01	1.6168E-01	1.6168E-01	1.6168E-01
7	VEL X	-4.9017E-14	4.9017E-14	-6.3022E-14	2.1007E-14	-2.8010E-14	3.5012E-14	-1.0504E-14	4.5516E-14	2.1007E-14
	VEL Y	1.6116E-01	1.6116E-01	1.6116E-01	1.6127E-01	1.6127E-01	1.6127E-01	1.6138E-01	1.6138E-01	1.6138E-01
8	VEL X	-1.7506E-14	3.3261E-14	-3.1511E-14	-7.0024E-15	-7.0024E-15	7.0024E-15	-7.0024E-15	4.5516E-14	-3.5012E-15
	VEL Y	1.6093E-01	1.6093E-01	1.6093E-01	1.6101E-01	1.6101E-01	1.6101E-01	1.6110E-01	1.6110E-01	1.6110E-01
9	VEL X	-7.0024E-15	2.2758E-14	-3.6763E-14	-1.4005E-14	-1.4005E-14	0.0000E-01	0.0000E-01	3.6763E-14	-2.4508E-14
	VEL Y	1.6081E-01	1.6081E-01	1.6081E-01	1.6085E-01	1.6085E-01	1.6085E-01	1.6089E-01	1.6089E-01	1.6089E-01
10	VEL X	-2.9323E-14	-4.8141E-15	-2.5384E-14	0.0000E-01	1.7506E-15	5.2518E-15	1.7068E-14	3.2824E-14	-1.3129E-15
	VEL Y	1.6074E-01	1.6074E-01	1.6074E-01	1.6076E-01	1.6076E-01	1.6076E-01	1.6078E-01	1.6078E-01	1.6078E-01

LISTING D-3. Output Report File for Test Case One. (Sheet 10 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS ON YEAR 20.00

NODE	T(C)	H(M)		NODE	T(C)	H(M)		NODE	T(C)	H(M)
1	61.22	1.000	*	19	52.67	0.7547		37	52.00	0.4253
2	61.22	1.000	*	20	52.67	0.7547		38	52.00	0.4253
3	61.22	1.000	*	21	52.44	0.7275		39	52.00	0.3525
4	60.82	0.9630		22	52.44	0.7275		40	52.00	0.3525
5	60.82	0.9630		23	52.44	0.7275		41	52.00	0.2797
6	58.24	0.9193		24	52.28	0.6998		42	52.00	0.2797
7	58.24	0.9193		25	52.28	0.6998		43	52.00	0.2797
8	58.24	0.9193		26	52.17	0.6721		44	52.00	0.2237
9	55.71	0.8792		27	52.17	0.6721		45	52.00	0.2237
10	55.71	0.8792		28	52.17	0.6721		46	52.00	0.1677
11	54.01	0.8331		29	52.06	0.6161		47	52.00	0.1677
12	54.01	0.8331		30	52.06	0.6161		48	52.00	0.1677
13	54.01	0.8331		31	52.02	0.5600		49	52.00	0.8386E-01
14	53.43	0.8077		32	52.02	0.5600		50	52.00	0.8386E-01
15	53.43	0.8077		33	52.02	0.5600		51	52.00	* 0.0000 *
16	52.99	0.7816		34	52.01	0.4926		52	52.00	* 0.0000 *
17	52.99	0.7816		35	52.01	0.4926		53	52.00	* 0.0000 *
18	52.99	0.7816		36	52.00	0.4253				

ITERATION NUMBER 1, MAX REL CHANGE (TEMP) = 1.8530E-02, MAX REL CORRECTION = 2.8225E-04
 ITERATION NUMBER 1, MAX REL CHANGE (HEAD) = 1.7283E-02, MAX REL CORRECTION = 2.7608E-04

LISTING D-3. Output Report File for Test Case One. (Sheet 11 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS FOR VELOCITY (M/YR) OF YEAR 20.00

ELEMENT		QSS PNT 1	QSS PNT 2	QSS PNT 3	QSS PNT 4	QSS PNT 5	QSS PNT 6	QSS PNT 7	QSS PNT 8	QSS PNT 9
1	VEL X	6.2666E-14	1.4883E-13	-1.1750E-13	0.0000E-01	1.5667E-14	-6.2666E-14	-2.5067E-13	-4.7000E-14	-2.3500E-13
	VEL Y	1.7559E-01	1.7559E-01	1.7559E-01	1.8245E-01	1.8245E-01	1.8245E-01	1.7547E-01	1.7547E-01	1.7547E-01
2	VEL X	-2.0087E-13	5.2076E-14	2.2318E-14	-5.9516E-14	-2.9758E-14	7.4394E-14	1.2647E-13	1.3391E-13	-8.9273E-14
	VEL Y	1.7974E-01	1.7974E-01	1.7974E-01	1.7713E-01	1.7713E-01	1.7713E-01	1.7990E-01	1.7990E-01	1.7990E-01
3	VEL X	0.0000E-01	1.4348E-13	-1.4348E-14	-7.1740E-14	-1.4348E-14	1.0044E-13	-2.1522E-13	5.7392E-14	2.1522E-14
	VEL Y	1.7849E-01	1.7849E-01	1.7849E-01	1.7819E-01	1.7819E-01	1.7819E-01	1.7844E-01	1.7844E-01	1.7844E-01
4	VEL X	0.0000E-01	1.0981E-13	-4.9594E-14	-5.6678E-14	-5.6678E-14	-2.8339E-14	-7.0848E-15	1.0627E-13	-1.1336E-13
	VEL Y	1.7819E-01	1.7819E-01	1.7819E-01	1.7805E-01	1.7805E-01	1.7805E-01	1.7837E-01	1.7837E-01	1.7837E-01
5	VEL X	-4.5746E-14	5.9822E-14	-9.5011E-14	2.8151E-14	2.8151E-14	4.2227E-14	5.6303E-14	1.4780E-13	-7.0379E-15
	VEL Y	1.7788E-01	1.7788E-01	1.7788E-01	1.7785E-01	1.7785E-01	1.7785E-01	1.7807E-01	1.7807E-01	1.7807E-01
6	VEL X	-4.9091E-14	4.9091E-14	-1.1221E-13	-1.4026E-14	-7.0130E-15	1.4026E-14	-6.3117E-14	4.5584E-14	-1.0169E-13
	VEL Y	1.7743E-01	1.7743E-01	1.7743E-01	1.7745E-01	1.7745E-01	1.7745E-01	1.7779E-01	1.7779E-01	1.7779E-01
7	VEL X	-3.1516E-14	7.0035E-14	-4.9025E-14	7.0035E-15	-2.8014E-14	4.2021E-14	-2.8014E-14	3.5018E-14	-3.1516E-14
	VEL Y	1.7692E-01	1.7692E-01	1.7692E-01	1.7705E-01	1.7705E-01	1.7705E-01	1.7725E-01	1.7725E-01	1.7725E-01
8	VEL X	-7.0025E-15	5.6020E-14	-1.0504E-14	-4.2015E-14	-2.8010E-14	-1.4005E-14	-7.0025E-15	5.9521E-14	-1.7506E-15
	VEL Y	1.7657E-01	1.7657E-01	1.7657E-01	1.7669E-01	1.7669E-01	1.7669E-01	1.7682E-01	1.7682E-01	1.7682E-01
9	VEL X	3.5012E-15	4.3765E-14	-1.0504E-14	-5.2518E-14	-4.9017E-14	-3.8513E-14	1.4005E-14	5.0767E-14	-3.5012E-15
	VEL Y	1.7640E-01	1.7640E-01	1.7640E-01	1.7646E-01	1.7646E-01	1.7646E-01	1.7652E-01	1.7652E-01	1.7652E-01
10	VEL X	-4.5078E-14	-1.6631E-14	-3.8513E-14	-1.2254E-14	-1.2254E-14	-8.7530E-15	5.4269E-14	7.0024E-14	3.3699E-14
	VEL Y	1.7630E-01	1.7630E-01	1.7630E-01	1.7633E-01	1.7633E-01	1.7633E-01	1.7636E-01	1.7636E-01	1.7636E-01

LISTING D-3. Output Report File for Test Case One. (Sheet 12 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS ON YEAR 50.00

NODE	T(C)	H(M)		NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	73.97	1.000	*	19	58.66	0.9188	37	52.42	0.5458
2	73.97	1.000	*	20	58.66	0.9188	38	52.42	0.5458
3	73.97	1.000	*	21	57.58	0.8940	39	52.19	0.4531
4	73.39	1.014		22	57.58	0.8940	40	52.19	0.4531
5	73.39	1.014		23	57.58	0.8940	41	52.08	0.3599
6	69.84	1.018		24	56.63	0.8668	42	52.08	0.3599
7	69.84	1.018		25	56.63	0.8668	43	52.08	0.3599
8	69.84	1.018		26	55.80	0.8384	44	52.04	0.2880
9	66.06	1.005		27	55.80	0.8384	45	52.04	0.2880
10	66.06	1.005		28	55.80	0.8384	46	52.02	0.2160
11	62.72	0.9800		29	54.48	0.7766	47	52.02	0.2160
12	62.72	0.9800		30	54.48	0.7766	48	52.02	0.2160
13	62.72	0.9800		31	53.55	0.7119	49	52.01	0.1080
14	61.23	0.9621		32	53.55	0.7119	50	52.01	0.1080
15	61.23	0.9621		33	53.55	0.7119	51	52.00	* 0.0000 *
16	59.88	0.9419		34	52.84	0.6296	52	52.00	* 0.0000 *
17	59.88	0.9419		35	52.84	0.6296	53	52.00	* 0.0000 *
18	59.88	0.9419		36	52.42	0.5458			

ITERATION NUMBER 1, MAX REL CHANGE (TEMP) = 3.0525E-02, MAX REL CORRECTION = 9.7269E-04
 ITERATION NUMBER 1, MAX REL CHANGE (HEAD) = 4.9591E-02, MAX REL CORRECTION = 1.1191E-03

LISTING D-3. Output Report File for Test Case One. (Sheet 13 of 13)

ONE DIMENSION VERTICAL FLOW WITH HEAT GENERATION

RESULTS FOR VELOCITY (M/YR) OF YEAR 50.00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
1	VEL X	8.9203E-11	-6.6104E-13	-9.0892E-11	4.9302E-11	-1.3404E-12	-5.2057E-11	1.0622E-11	-5.4168E-13	-1.2192E-11
	VEL Y	2.2526E-01	2.2526E-01	2.2526E-01	2.3646E-01	2.3646E-01	2.3646E-01	2.2501E-01	2.2501E-01	2.2501E-01
2	VEL X	3.0979E-11	-1.1300E-12	-3.3587E-11	5.7029E-11	-2.0732E-12	-6.1141E-11	8.5017E-11	-8.9214E-13	-8.7183E-11
	VEL Y	2.3104E-01	2.3104E-01	2.3104E-01	2.2952E-01	2.2952E-01	2.2952E-01	2.3105E-01	2.3105E-01	2.3105E-01
3	VEL X	-1.5065E-10	-1.9102E-13	1.4992E-10	-7.4993E-11	-2.3878E-13	7.4579E-11	3.9797E-13	-3.7409E-13	-1.4804E-12
	VEL Y	2.3053E-01	2.3053E-01	2.3053E-01	2.3008E-01	2.3008E-01	2.3008E-01	2.3057E-01	2.3057E-01	2.3057E-01
4	VEL X	-4.9946E-12	-5.3934E-14	4.5090E-12	-7.5674E-11	-1.0791E-13	7.5504E-11	-1.4660E-10	-1.7728E-13	1.4588E-10
	VEL Y	2.3040E-01	2.3040E-01	2.3040E-01	2.2999E-01	2.2999E-01	2.2999E-01	2.3052E-01	2.3052E-01	2.3052E-01
5	VEL X	1.3907E-11	-1.3892E-12	-1.7061E-11	1.4177E-11	-1.2165E-12	-1.6625E-11	1.4861E-11	-3.9798E-13	-1.6024E-11
	VEL Y	2.3015E-01	2.3015E-01	2.3015E-01	2.2984E-01	2.2984E-01	2.2984E-01	2.3034E-01	2.3034E-01	2.3034E-01
6	VEL X	-2.5398E-12	4.0140E-14	2.2880E-12	4.8898E-12	-2.7733E-13	-5.4299E-12	1.1666E-11	-1.0108E-12	-1.3991E-11
	VEL Y	2.2989E-01	2.2989E-01	2.2989E-01	2.2899E-01	2.2899E-01	2.2899E-01	2.3039E-01	2.3039E-01	2.3039E-01
7	VEL X	6.1173E-13	3.9123E-14	-7.5755E-13	-1.5791E-12	-4.2679E-14	1.6645E-12	-3.9549E-12	3.5566E-15	3.8411E-12
	VEL Y	2.2886E-01	2.2886E-01	2.2886E-01	2.2842E-01	2.2842E-01	2.2842E-01	2.2949E-01	2.2949E-01	2.2949E-01
8	VEL X	-2.2849E-13	5.6243E-14	1.9334E-13	4.4291E-13	-1.4061E-14	-4.4291E-13	1.1003E-12	5.2728E-14	-1.1284E-12
	VEL Y	2.2785E-01	2.2785E-01	2.2785E-01	2.2783E-01	2.2783E-01	2.2783E-01	2.2839E-01	2.2839E-01	2.2839E-01
9	VEL X	5.2560E-15	3.1536E-14	-7.0080E-14	-1.9622E-13	-1.7520E-14	1.6118E-13	-3.5741E-13	5.6064E-14	3.6441E-13
	VEL Y	2.2734E-01	2.2734E-01	2.2734E-01	2.2742E-01	2.2742E-01	2.2742E-01	2.2760E-01	2.2760E-01	2.2760E-01
10	VEL X	-3.7643E-14	-1.1381E-14	-4.8148E-14	3.3266E-14	-5.2525E-15	-3.6768E-14	9.1044E-14	4.6397E-14	-7.6162E-14
	VEL Y	2.2710E-01	2.2710E-01	2.2710E-01	2.2715E-01	2.2715E-01	2.2715E-01	2.2724E-01	2.2724E-01	2.2724E-01

LISTING D-4. Input Data File for Test Case Two. (Sheet 1 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER
0 1 1 445 136 3 1 1 1 1 0 0 /*CNTRL
0 8 0 11 0 13 0 /*FILE UNITS
0 0 1 5 50 0 /*STRT TME
5 5 0 20
4 4 1 00
2 2 2 50
9999
1 0 1 0 /*SCALE
1 5 00E+01 1 20E+00 /*IC
2 5 000E+01 1 200E+00
3 5 000E+01 1 200E+00
4 5 000E+01 1 200E+00
5 5 000E+01 1 200E+00
6 5 000E+01 1 200E+00
7 5 000E+01 1 200E+00
8 5 000E+01 1 200E+00
9 5 000E+01 1 200E+00
10 5 000E+01 1 200E+00
11 5 000E+01 1 200E+00
12 5 000E+01 1 200E+00
13 5 000E+01 1 200E+00
14 5 000E+01 1 200E+00
15 5 000E+01 1 200E+00
16 5 000E+01 1 190E+00
17 5 000E+01 1 179E+00
18 5 000E+01 1 179E+00
19 5 000E+01 1 179E+00
20 5 000E+01 1 190E+00
21 5 000E+01 1 190E+00
22 5 000E+01 1 179E+00
23 5 000E+01 1 179E+00
24 5 000E+01 1 190E+00
25 5 000E+01 1 179E+00
26 5 000E+01 1 179E+00
27 5 000E+01 1 190E+00
28 5 000E+01 1 180E+00
29 5 000E+01 1 179E+00
30 5 000E+01 1 190E+00
31 5 000E+01 1 180E+00
32 5 000E+01 1 180E+00
33 5 000E+01 1 190E+00
34 5 000E+01 1 180E+00
35 5 000E+01 1 180E+00
36 5 000E+01 1 190E+00
37 5 000E+01 1 180E+00
38 5 000E+01 1 180E+00
39 5 000E+01 1 169E+00
40 5 000E+01 1 158E+00
41 5 000E+01 1 158E+00
42 5 000E+01 1 158E+00
43 5 000E+01 1 169E+00
44 5 000E+01 1 169E+00

```


LISTING D-4. Input Data File for Test Case Two. (Sheet 2 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

45 5 000E+01 1 159E+00
46 5 000E+01 1 158E+00
47 5 000E+01 1 169E+00
48 5 000E+01 1 159E+00
49 5 000E+01 1 159E+00
50 5 000E+01 1 169E+00
51 5 000E+01 1 159E+00
52 5 000E+01 1 159E+00
53 5 000E+01 1 170E+00
54 5 000E+01 1 160E+00
55 5 000E+01 1 159E+00
56 5 000E+01 1 170E+00
57 5 000E+01 1 160E+00
58 5 000E+01 1 160E+00
59 5 000E+01 1 170E+00
60 5 000E+01 1 160E+00
61 5 000E+01 1 160E+00
62 5 000E+01 1 148E+00
63 5 000E+01 1 137E+00
64 5 000E+01 1 137E+00
65 5 000E+01 1 137E+00
66 5 000E+01 1 148E+00
67 5 000E+01 1 148E+00
68 5 000E+01 1 137E+00
69 5 000E+01 1 137E+00
70 5 000E+01 1 148E+00
71 5 000E+01 1 138E+00
72 5 000E+01 1 138E+00
73 5 000E+01 1 149E+00
74 5 000E+01 1 139E+00
75 5 000E+01 1 138E+00
76 5 000E+01 1 150E+00
77 5 000E+01 1 140E+00
78 5 000E+01 1 139E+00
79 5 000E+01 1 150E+00
80 5 000E+01 1 140E+00
81 5 000E+01 1 140E+00
82 5 000E+01 1 150E+00
83 5 000E+01 1 140E+00
84 5 000E+01 1 140E+00
85 5 000E+01 1 130E+00
86 5 000E+01 1 122E+00
87 5 000E+01 1 129E+00
88 5 000E+01 1 129E+00
89 5 000E+01 1 121E+00
90 5 000E+01 1 122E+00
91 5 000E+01 1 129E+00
92 5 000E+01 1 122E+00
93 5 000E+01 1 122E+00
94 5 000E+01 1 122E+00
95 5 000E+01 1 122E+00
96 5 000E+01 1 129E+00
97 5 000E+01 1 130E+00

```

```

98 5 000E+01 1 123E+00
99 5 000E+01 1 123E+00
100 5 000E+01 1 131E+00
101 5 000E+01 1 124E+00
102 5 000E+01 1 124E+00
103 5 000E+01 1 132E+00
104 5 000E+01 1 125E+00
105 5 000E+01 1 125E+00
106 5 000E+01 1 132E+00
107 5 000E+01 1 126E+00
108 5 000E+01 1 126E+00
109 5 000E+01 1 132E+00
110 5 000E+01 1 126E+00
111 5 000E+01 1 126E+00
112 5 000E+01 1 109E+00
113 5 000E+01 1 115E+00
114 5 000E+01 1 115E+00
115 5 000E+01 1 109E+00
116 5 000E+01 1 109E+00
117 5 000E+01 1 114E+00
118 5 000E+01 1 108E+00
119 5 000E+01 1 108E+00
120 5 000E+01 1 116E+00
121 5 000E+01 1 111E+00
122 5 000E+01 1 109E+00
123 5 000E+01 1 118E+00
124 5 000E+01 1 113E+00
125 5 000E+01 1 112E+00
126 5 000E+01 1 119E+00
127 5 000E+01 1 114E+00
128 5 000E+01 1 114E+00
129 5 000E+01 1 120E+00
130 5 000E+01 1 115E+00
131 5 000E+01 1 115E+00
132 5 000E+01 1 120E+00
133 5 000E+01 1 115E+00
134 5 000E+01 1 115E+00
135 5 000E+01 1 120E+00
136 5 000E+01 1 115E+00
137 5 000E+01 1 115E+00
138 5 000E+01 1 097E+00
139 5 000E+01 1 102E+00
140 5 000E+01 1 103E+00
141 5 000E+01 1 097E+00
142 5 000E+01 1 097E+00
143 5 000E+01 1 102E+00
144 5 000E+01 1 098E+00
145 5 000E+01 1 097E+00
146 5 000E+01 1 106E+00
147 5 000E+01 1 104E+00
148 5 000E+01 1 101E+00
149 5 000E+01 1 109E+00
150 5 000E+01 1 106E+00

```

LISTING D-4. Input Data File for Test Case Two. (Sheet 3 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

151 5 000E+01 1 105E+00
152 5 000E+01 1 110E+00
153 5 000E+01 1 107E+00
154 5 000E+01 1 107E+00
155 5 000E+01 1 111E+00
156 5 000E+01 1 108E+00
157 5 000E+01 1 108E+00
158 5 000E+01 1 111E+00
159 5 000E+01 1 108E+00
160 5 000E+01 1 108E+00
161 5 000E+01 1 111E+00
162 5 000E+01 1 108E+00
163 5 000E+01 1 108E+00
164 5 000E+01 1 097E+00
165 5 000E+01 1 097E+00
166 5 000E+01 1 097E+00
167 5 000E+01 1 097E+00
168 5 000E+01 1 097E+00
169 5 000E+01 1 098E+00
170 5 000E+01 1 098E+00
171 5 000E+01 1 098E+00
172 5 000E+01 1 099E+00
173 5 000E+01 1 098E+00
174 5 000E+01 1 103E+00
175 5 000E+01 1 102E+00
176 5 000E+01 1 101E+00
177 5 000E+01 1 099E+00
178 5 000E+01 1 098E+00
179 5 000E+01 1 099E+00
180 5 000E+01 1 105E+00
181 5 000E+01 1 104E+00
182 5 000E+01 1 103E+00
183 5 000E+01 1 105E+00
184 5 000E+01 1 100E+00
185 5 000E+01 1 102E+00
186 5 000E+01 1 105E+00
187 5 000E+01 1 105E+00
188 5 000E+01 1 100E+00
189 5 000E+01 1 100E+00
190 5 000E+01 1 105E+00
191 5 000E+01 1 100E+00
192 5 000E+01 1 100E+00
193 5 000E+01 1 105E+00
194 5 000E+01 1 100E+00
195 5 000E+01 1 100E+00
196 5 000E+01 1 098E+00
197 5 000E+01 1 097E+00
198 5 000E+01 1 098E+00
199 5 000E+01 1 098E+00
200 5 000E+01 1 098E+00
201 5 000E+01 1 098E+00
202 5 000E+01 1 098E+00
203 5 000E+01 1 098E+00

```

```

204 5 000E+01 1 099E+00
205 5 000E+01 1 099E+00
206 5 000E+01 1 099E+00
207 5 000E+01 1 100E+00
208 5 000E+01 1 099E+00
209 5 000E+01 1 101E+00
210 5 000E+01 1 100E+00
211 5 000E+01 1 100E+00
212 5 000E+01 1 100E+00
213 5 000E+01 1 099E+00
214 5 000E+01 1 100E+00
215 5 000E+01 1 102E+00
216 5 000E+01 1 100E+00
217 5 000E+01 1 100E+00
218 5 000E+01 1 100E+00
219 5 000E+01 1 099E+00
220 5 000E+01 1 100E+00
221 5 000E+01 1 100E+00
222 5 000E+01 1 098E+00
223 5 000E+01 1 096E+00
224 5 000E+01 1 098E+00
225 5 000E+01 1 095E+00
226 5 000E+01 1 093E+00
227 5 000E+01 1 095E+00
228 5 000E+01 1 095E+00
229 5 000E+01 1 092E+00
230 5 000E+01 1 092E+00
231 5 000E+01 1 095E+00
232 5 000E+01 1 092E+00
233 5 000E+01 1 092E+00
234 5 000E+01 1 095E+00
235 5 000E+01 1 092E+00
236 5 000E+01 1 092E+00
237 5 000E+01 1 099E+00
238 5 000E+01 1 098E+00
239 5 000E+01 1 098E+00
240 5 000E+01 1 099E+00
241 5 000E+01 1 099E+00
242 5 000E+01 1 099E+00
243 5 000E+01 1 100E+00
244 5 000E+01 1 099E+00
245 5 000E+01 1 100E+00
246 5 000E+01 1 099E+00
247 5 000E+01 1 098E+00
248 5 000E+01 1 099E+00
249 5 000E+01 1 101E+00
250 5 000E+01 1 101E+00
251 5 000E+01 1 101E+00
252 5 000E+01 1 101E+00
253 5 000E+01 1 101E+00
254 5 000E+01 1 097E+00
255 5 000E+01 1 101E+00
256 5 000E+01 1 101E+00

```

LISTING D-4. Input Data File for Test Case Two. (Sheet 4 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

257 5 000E+01 1 101E+00
258 5 000E+01 1 101E+00
259 5 000E+01 1 101E+00
260 5 000E+01 1 101E+00
261 5 000E+01 1 093E+00
262 5 000E+01 1 094E+00
263 5 000E+01 1 095E+00
264 5 000E+01 1 095E+00
265 5 000E+01 1 096E+00
266 5 000E+01 1 097E+00
267 5 000E+01 1 090E+00
268 5 000E+01 1 086E+00
269 5 000E+01 1 086E+00
270 5 000E+01 1 087E+00
271 5 000E+01 1 091E+00
272 5 000E+01 1 089E+00
273 5 000E+01 1 085E+00
274 5 000E+01 1 085E+00
275 5 000E+01 1 089E+00
276 5 000E+01 1 085E+00
277 5 000E+01 1 085E+00
278 5 000E+01 1 089E+00
279 5 000E+01 1 085E+00
280 5 000E+01 1 085E+00
281 5 000E+01 1 100E+00
282 5 000E+01 1 099E+00
283 5 000E+01 1 100E+00
284 5 000E+01 1 101E+00
285 5 000E+01 1 101E+00
286 5 000E+01 1 101E+00
287 5 000E+01 1 099E+00
288 5 000E+01 1 102E+00
289 5 000E+01 1 102E+00
290 5 000E+01 1 102E+00
291 5 000E+01 1 102E+00
292 5 000E+01 1 102E+00
293 5 000E+01 1 102E+00
294 5 000E+01 1 102E+00
295 5 000E+01 1 101E+00
296 5 000E+01 1 102E+00
297 5 000E+01 1 102E+00
298 5 000E+01 1 102E+00
299 5 000E+01 1 102E+00
300 5 000E+01 1 102E+00
301 5 000E+01 1 102E+00
302 5 000E+01 1 088E+00
303 5 000E+01 1 089E+00
304 5 000E+01 1 094E+00
305 5 000E+01 1 091E+00
306 5 000E+01 1 092E+00
307 5 000E+01 1 098E+00
308 5 000E+01 1 081E+00
309 5 000E+01 1 076E+00

```

```

310 5 000E+01 1 076E+00
311 5 000E+01 1 077E+00
312 5 000E+01 1 082E+00
313 5 000E+01 1 080E+00
314 5 000E+01 1 075E+00
315 5 000E+01 1 075E+00
316 5 000E+01 1 077E+00
317 5 000E+01 1 078E+00
318 5 000E+01 1 084E+00
319 5 000E+01 1 080E+00
320 5 000E+01 1 074E+00
321 5 000E+01 1 074E+00
322 5 000E+01 1 080E+00
323 5 000E+01 1 074E+00
324 5 000E+01 1 074E+00
325 5 000E+01 1 103E+00
326 5 000E+01 1 103E+00
327 5 000E+01 1 092E+00
328 5 000E+01 1 091E+00
329 5 000E+01 1 097E+00
330 5 000E+01 1 103E+00
331 5 000E+01 1 102E+00
332 5 000E+01 1 103E+00
333 5 000E+01 1 102E+00
334 5 000E+01 1 103E+00
335 5 000E+01 1 103E+00
336 5 000E+01 1 103E+00
337 5 000E+01 1 078E+00
338 5 000E+01 1 079E+00
339 5 000E+01 1 086E+00
340 5 000E+01 1 078E+00
341 5 000E+01 1 078E+00
342 5 000E+01 1 085E+00
343 5 000E+01 1 069E+00
344 5 000E+01 1 061E+00
345 5 000E+01 1 062E+00
346 5 000E+01 1 062E+00
347 5 000E+01 1 070E+00
348 5 000E+01 1 068E+00
349 5 000E+01 1 060E+00
350 5 000E+01 1 061E+00
351 5 000E+01 1 062E+00
352 5 000E+01 1 063E+00
353 5 000E+01 1 071E+00
354 5 000E+01 1 068E+00
355 5 000E+01 1 060E+00
356 5 000E+01 1 060E+00
357 5 000E+01 1 063E+00
358 5 000E+01 1 063E+00
359 5 000E+01 1 071E+00
360 5 000E+01 1 068E+00
361 5 000E+01 1 060E+00
362 5 000E+01 1 060E+00

```

LISTING D-4. Input Data File for Test Case Two. (Sheet 5 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

363 5 000E+01 1 103E+00
364 5 000E+01 1 103E+00
365 5 000E+01 1 091E+00
366 5 000E+01 1 091E+00
367 5 000E+01 1 098E+00
368 5 000E+01 1 103E+00
369 5 000E+01 1 078E+00
370 5 000E+01 1 078E+00
371 5 000E+01 1 085E+00
372 5 000E+01 1 070E+00
373 5 000E+01 1 063E+00
374 5 000E+01 1 071E+00
375 5 000E+01 1 063E+00
376 5 000E+01 1 071E+00
377 5 000E+01 1 051E+00
378 5 000E+01 1 041E+00
379 5 000E+01 1 041E+00
380 5 000E+01 1 041E+00
381 5 000E+01 1 052E+00
382 5 000E+01 1 050E+00
383 5 000E+01 1 040E+00
384 5 000E+01 1 041E+00
385 5 000E+01 1 041E+00
386 5 000E+01 1 041E+00
387 5 000E+01 1 052E+00
388 5 000E+01 1 050E+00
389 5 000E+01 1 040E+00
390 5 000E+01 1 040E+00
391 5 000E+01 1 042E+00
392 5 000E+01 1 042E+00
393 5 000E+01 1 052E+00
394 5 000E+01 1 050E+00
395 5 000E+01 1 040E+00
396 5 000E+01 1 040E+00
397 5 000E+01 1 042E+00
398 5 000E+01 1 052E+00
399 5 000E+01 1 042E+00
400 5 000E+01 1 031E+00
401 5 000E+01 1 020E+00
402 5 000E+01 1 021E+00
403 5 000E+01 1 021E+00
404 5 000E+01 1 031E+00
405 5 000E+01 1 030E+00
406 5 000E+01 1 020E+00
407 5 000E+01 1 020E+00
408 5 000E+01 1 021E+00
409 5 000E+01 1 021E+00
410 5 000E+01 1 031E+00
411 5 000E+01 1 030E+00
412 5 000E+01 1 020E+00
413 5 000E+01 1 020E+00
414 5 000E+01 1 021E+00
415 5 000E+01 1 021E+00

```

```

416 5 000E+01 1 031E+00
417 5 000E+01 1 030E+00
418 5 000E+01 1 020E+00
419 5 000E+01 1 020E+00
420 5 000E+01 1 021E+00
421 5 000E+01 1 031E+00
422 5 000E+01 1 021E+00
423 5 000E+01 1 010E+00
424 5 000E+01 1 000E+00
425 5 000E+01 1 000E+00
426 5 000E+01 1 000E+00
427 5 000E+01 1 010E+00
428 5 000E+01 1 010E+00
429 5 000E+01 1 000E+00
430 5 000E+01 1 000E+00
431 5 000E+01 1 000E+00
432 5 000E+01 1 000E+00
433 5 000E+01 1 010E+00
434 5 000E+01 1 010E+00
435 5 000E+01 1 000E+00
436 5 000E+01 1 000E+00
437 5 000E+01 1 000E+00
438 5 000E+01 1 000E+00
439 5 000E+01 1 010E+00
440 5 000E+01 1 010E+00
441 5 000E+01 1 000E+00
442 5 000E+01 1 000E+00
443 5 000E+01 1 000E+00
444 5 000E+01 1 010E+00
445 5 000E+01 1 000E+00

```

30

/*BC

```

1 11 5 000E+01 1 200E+00
2 11 5 000E+01 1 200E+00
3 11 5 000E+01 1 200E+00
4 11 5 000E+01 1 200E+00
5 11 5 000E+01 1 200E+00
6 11 5 000E+01 1 200E+00
7 11 5 000E+01 1 200E+00
8 11 5 000E+01 1 200E+00
9 11 5 000E+01 1 200E+00
10 11 5 000E+01 1 200E+00
11 11 5 000E+01 1 200E+00
12 11 5 000E+01 1 200E+00
13 11 5 000E+01 1 200E+00
14 11 5 000E+01 1 200E+00
15 11 5 000E+01 1 200E+00
441 11 5 000E+01 1 000E+00
442 11 5 000E+01 1 000E+00
435 11 5 000E+01 1 000E+00
436 11 5 000E+01 1 000E+00
429 11 5 000E+01 1 000E+00
430 11 5 000E+01 1 000E+00
424 11 5 000E+01 1 000E+00

```

LISTING D-4. Input Data File for Test Case Two. (Sheet 6 of 6)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

```

425      11 5.000E+01 1.000E+00
426      11 5.000E+01 1.000E+00
431      11 5.000E+01 1.000E+00
432      11 5.000E+01 1.000E+00
437      11 5.000E+01 1.000E+00
438      11 5.000E+01 1.000E+00
445      11 5.000E+01 1.000E+00
443      11 5.000E+01 1.000E+00
  1      1500.0      1.500      1.500      1.0E-2      1.00E-8      1.00E-8      CANST
        1.0E-3      2500.      1.E-10      1.E-10      0.0
  2      930.0      0.800      0.800      3.0E-1      1.00E-9      1.00E-9      PCKNG
        1.0E-3      1800.      1.E-10      1.E-10      0.0
  3      930.0      1.000      1.000      2.2E-4      1.0E-12      1.0E-12      STRESS
        1.0E-5      2780.      1.E-10      1.E-10      0.0
  8      2      1.0
70 71 72 77 84 85 89 90
0.0 1.0E+10 1000. 1.0E+10

```

/* LOAD

LISTING D-5. The PRIMOS Command File for Test Case Two.

EAT SEERUN

EAT SEERUN
EAT PRT
EAT RLT
COMO SEERUN
DATE
DELSEQ ALL
TIME
OPEN DATA 1 1
OPEN PRT 2 3
OPEN WORKSPACE 14 3
OPEN RLT 4 3
OPEN GEOM 7 1
OPEN VEL 11 3
SEQ SYSTEMS>FEND>MAGNUM>#MAGNUM
TIME
CLOSE WORKSPACE
EAT WORKSPACE
CLOSE ALL
COMO -END
COMO -TTY

LISTING D-6. Output Report File for Test Case Two. (Sheet 1 of 48)

```
***      ***      ***      ****      ***      *      *      *      ***      ***
*      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *
*      *      *      *      *      *      *      *      *      *      *
```

VERSION 3.0 (Revision 1.)

FRI, JUL 20 1984

10:21:29

ID= 720841021

LISTING D-6. Output Report File for Test Case Two. (Sheet 2 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

TABLE 1. - PRINCIPAL PROBLEM SPECIFICATIONS

SIMULATION MODE (0-TIME VARYING, .NE.0-STEADY STATE).....	0
HEAT TRANSPORT (0-ISOTHERMAL, .NE.0-NONISOTHERMAL).....	1
GROUNDWATER FLOW (0-HYDROSTATIC, .NE.0-FLUID FLOW).....	1
NUMBER OF NODES.....	445
NUMBER OF ELEMENTS.....	136
NUMBER OF ROCK TYPES.....	3
INITIAL CONDITION INPUTS (0-UNIFORM, 1-SPATIALLY VARYING)	1
INPUT DATA PRINT CONTROL (0-PARTIAL ECHO, 1-TOTAL ECHO...	1
DIAGNOSTIC PRINTOUT (0-NO ACTION, 1-CONVERGENCE INFO)....	1
VELOCITY PRINT CONTROL (0-SUPPRESS PRINT, 1-PRINT VELS)...	1
RESULTS FILE WRITE CONTROL (0-AT TIME STEP, 1-AT PRT FREQ)	0
COORD SYSTEM (0-CARTESIAN, 1-AXISYMMETRIC ABOUT X=0.)....	0
INPUT RESTART FILE (LU).....	0
RESULTS FILE (LU).....	8
OUTPUT RESTART FILE (LU).....	0
INPUT GEOMETRY FILE (LU).....	11
OUTPUT GEOMETRY FILE (LU).....	0
STREAM/PATHLINE DATA FILE (LU).....	13
TEMPERATURE INPUT FILE (TEMPERATURE INACTIVE).....	0
INITIAL CONDITION OUTPUT FILE (FORMATTED).....	0
SCALE FACTOR FOR X COORDINATES.....	1.00
SCALE FACTOR FOR Y COORDINATES.....	1.00
LEFT BOUNDARY FOR QUAD ELEMENTS.....	0.00
RIGHT BOUNDARY FOR QUAD ELEMENTS.....	0.00
TOP BOUNDARY FOR QUAD ELEMENTS.....	0.00
BOTTOM BOUNDARY FOR QUAD ELEMENTS.....	0.00
START TIME (YEARS).....	0.00
WEIGHTING FACTOR.....	1.5
DENSITY/VISCOUSITY REFERENCE TEMP (>0.05 TO IMPLEMENT)...	50.0

TIME CONTROL AND RUN SPECIFICATIONS

NUMBER OF TIME STEPS	PRINT INTERVAL	TIME STEP	TIME(YEARS)
5	5	0.2000	1.000
4	4	1.000	5.000
2	2	2.500	10.00

LISTING D-6. Output Report File for Test Case Two. (Sheet 3 of 48)

TABLE 2 - NODE POINT COORDINATES

NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD
1	0 00	-2 50	51	1 00	-1 50	101	1 00	-0 64	151	0 50	-0 19
2	0 12	-2 50	52	0 81	-1 50	102	0 81	-0 65	152	1 00	-0 27
3	0 20	-2 50	53	1 89	-1 75	103	1 89	-0 81	153	1 00	-0 19
4	0 28	-2 50	54	1 89	-1 50	104	1 89	-0 64	154	0 81	-0 19
5	0 38	-2 50	55	1 39	-1 50	105	1 39	-0 64	155	1 89	-0 28
6	0 50	-2 50	56	3 22	-1 75	106	3 22	-0 81	156	1 89	-0 20
7	0 64	-2 50	57	3 22	-1 50	107	3 22	-0 64	157	1 39	-0 20
8	0 81	-2 50	58	2 50	-1 50	108	2 50	-0 64	158	3 22	-0 28
9	1 00	-2 50	59	5 00	-1 75	109	5 00	-0 81	159	3 22	-0 20
10	1 39	-2 50	60	5 00	-1 50	110	5 00	-0 64	160	2 50	-0 20
11	1 89	-2 50	61	4 06	-1 50	111	4 06	-0 64	161	5 00	-0 28
12	2 50	-2 50	62	0 20	-1 25	112	0 00	-0 42	162	5 00	-0 20
13	3 22	-2 50	63	0 19	-1 00	113	0 00	-0 53	163	4 06	-0 20
14	4 06	-2 50	64	0 12	-1 00	114	0 11	-0 52	164	0 00	-0 22
15	5 00	-2 50	65	0 00	-1 00	115	0 11	-0 41	165	0 00	-0 24
16	0 20	-2 25	66	0 00	-1 25	116	0 06	-0 42	166	0 10	-0 23
17	0 20	-2 00	67	0 38	-1 25	117	0 19	-0 50	167	0 10	-0 21
18	0 12	-2 00	68	0 38	-1 00	118	0 19	-0 37	168	0 05	-0 22
19	0 00	-2 00	69	0 27	-1 00	119	0 15	-0 39	169	0 18	-0 18
20	0 00	-2 25	70	0 64	-1 25	120	0 38	-0 50	170	0 17	-0 17
21	0 38	-2 25	71	0 64	-1 00	121	0 38	-0 38	171	0 13	-0 20
22	0 38	-2 00	72	0 50	-1 00	122	0 27	-0 37	172	0 24	-0 10
23	0 28	-2 00	73	1 00	-1 25	123	0 65	-0 50	173	0 22	-0 14
24	0 64	-2 25	74	1 00	-1 00	124	0 65	-0 38	174	0 39	-0 15
25	0 64	-2 00	75	0 81	-1 00	125	0 50	-0 38	175	0 41	-0 11
26	0 50	-2 00	76	1 89	-1 25	126	1 00	-0 50	176	0 31	-0 10
27	1 00	-2 25	77	1 89	-1 00	127	1 00	-0 38	177	0 21	-0 10
28	1 00	-2 00	78	1 39	-1 00	128	0 81	-0 38	178	0 20	-0 13
29	0 81	-2 00	79	3 22	-1 25	129	1 89	-0 50	179	0 23	-0 10
30	1 89	-2 25	80	3 22	-1 00	130	1 89	-0 38	180	0 66	-0 16
31	1 89	-2 00	81	2 50	-1 00	131	1 39	-0 38	181	0 66	-0 11
32	1 39	-2 00	82	5 00	-1 25	132	3 22	-0 50	182	0 52	-0 11
33	3 22	-2 25	83	5 00	-1 00	133	3 22	-0 38	183	0 83	-0 15
34	3 22	-2 00	84	4 06	-1 00	134	2 50	-0 38	184	1 00	0 00
35	2 50	-2 00	85	0 15	-0 83	135	5 00	-0 50	185	0 83	-0 06
36	5 00	-2 25	86	0 11	-0 66	136	5 00	-0 38	186	1 00	-0 12
37	5 00	-2 00	87	0 06	-0 83	137	4 06	-0 38	187	1 89	-0 12
38	4 06	-2 00	88	0 19	-0 81	138	0 00	-0 25	188	1 89	0 00
39	0 20	-1 75	89	0 19	-0 65	139	0 00	-0 32	189	1 39	0 00
40	0 20	-1 50	90	0 16	-0 66	140	0 10	-0 31	190	3 22	-0 12
41	0 12	-1 50	91	0 38	-0 81	141	0 10	-0 24	191	3 22	0 00
42	0 00	-1 50	92	0 38	-0 65	142	0 05	-0 25	192	2 50	0 00
43	0 00	-1 75	93	0 27	-0 65	143	0 19	-0 27	193	5 00	-0 12
44	0 38	-1 75	94	0 06	-0 67	144	0 19	-0 19	194	5 00	0 00
45	0 38	-1 50	95	0 00	-0 67	145	0 14	-0 22	195	4 06	0 00
46	0 28	-1 50	96	0 00	-0 82	146	0 37	-0 27	196	0 00	-0 20
47	0 64	-1 75	97	0 65	-0 81	147	0 37	-0 19	197	0 00	-0 21
48	0 64	-1 50	98	0 65	-0 65	148	0 27	-0 19	198	0 09	-0 20
49	0 50	-1 50	99	0 50	-0 65	149	0 65	-0 27	199	0 09	-0 19
50	1 00	-1 75	100	1 00	-0 81	150	0 65	-0 19	200	0 05	-0 20

LISTING D-6. Output Report File for Test Case Two. (Sheet 4 of 48)

TABLE 2 - NODE POINT COORDINATES

NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD
201	0 16	-0 16	251	0 23	0 10	301	0 00	0 15	351	0 50	1 00
202	0 15	-0 15	252	0 21	0 10	302	0 50	0 38	352	0 38	1 00
203	0 12	-0 17	253	0 22	0 05	303	0 38	0 38	353	0 38	0 81
204	0 19	-0 09	254	0 52	0 11	304	0 37	0 27	354	3 22	0 81
205	0 17	-0 12	255	0 20	0 09	305	0 27	0 37	355	3 22	1 00
206	0 20	-0 09	256	0 19	0 09	306	0 19	0 37	356	2 50	1 00
207	0 25	0 00	257	0 20	0 05	307	0 19	0 27	357	0 27	1 00
208	0 25	-0 05	258	0 15	0 10	308	1 00	0 50	358	0 19	1 00
209	0 42	-0 06	259	0 10	0 10	309	1 00	0 64	359	0 19	0 81
210	0 42	0 00	260	0 10	0 05	310	0 81	0 65	360	5 00	0 81
211	0 32	0 00	261	0 81	0 19	311	0 65	0 65	361	5 00	1 00
212	0 22	0 00	262	0 65	0 19	312	0 65	0 50	362	4 06	1 00
213	0 22	-0 05	263	0 66	0 16	313	1 89	0 50	363	0 00	0 25
214	0 24	0 00	264	0 50	0 19	314	1 89	0 64	364	0 05	0 25
215	0 67	-0 06	265	0 37	0 19	315	1 39	0 64	365	0 06	0 42
216	0 67	0 00	266	0 39	0 15	316	0 50	0 65	366	0 00	0 42
217	0 53	0 00	267	1 00	0 27	317	0 38	0 65	367	0 00	0 32
218	0 20	0 00	268	1 00	0 38	318	0 38	0 50	368	0 00	0 24
219	0 20	-0 05	269	0 81	0 38	319	3 22	0 50	369	0 06	0 67
220	0 21	0 00	270	0 65	0 38	320	3 22	0 64	370	0 00	0 67
221	0 82	0 00	271	0 65	0 27	321	2 50	0 64	371	0 00	0 53
222	0 83	0 06	272	1 89	0 28	322	5 00	0 50	372	0 15	0 83
223	0 66	0 11	273	1 89	0 38	323	5 00	0 64	373	0 00	1 00
224	0 67	0 06	274	1 39	0 38	324	4 06	0 64	374	0 06	0 83
225	1 00	0 12	275	3 22	0 28	325	0 10	0 24	375	0 12	1 00
226	1 00	0 19	276	3 22	0 38	326	0 14	0 22	376	0 00	0 82
227	0 83	0 15	277	2 50	0 38	327	0 15	0 39	377	1 00	1 25
228	1 89	0 12	278	5 00	0 28	328	0 11	0 41	378	1 00	1 50
229	1 89	0 20	279	5 00	0 38	329	0 10	0 31	379	0 81	1 50
230	1 39	0 20	280	4 06	0 38	330	0 10	0 21	380	0 64	1 50
231	3 22	0 12	281	0 00	0 00	331	0 13	0 20	381	0 64	1 25
232	3 22	0 20	282	0 00	-0 05	332	0 10	0 23	382	1 89	1 25
233	2 50	0 20	283	0 05	0 00	333	0 09	0 20	383	1 89	1 50
234	5 00	0 12	284	0 05	0 10	334	0 05	0 22	384	1 39	1 50
235	5 00	0 20	285	0 00	0 10	335	0 00	0 22	385	0 50	1 50
236	4 06	0 20	286	0 00	0 05	336	0 00	0 21	386	0 38	1 50
237	0 00	-0 10	287	0 27	0 19	337	0 27	0 65	387	0 38	1 25
238	0 00	-0 15	288	0 19	0 19	338	0 19	0 65	388	3 22	1 25
239	0 10	-0 15	289	0 22	0 14	339	0 19	0 50	389	3 22	1 50
240	0 10	-0 10	290	0 18	0 18	340	0 16	0 66	390	2 50	1 50
241	0 05	-0 10	291	0 17	0 17	341	0 11	0 66	391	0 28	1 50
242	0 15	-0 10	292	0 20	0 13	342	0 11	0 52	392	0 20	1 50
243	0 10	0 00	293	0 16	0 16	343	1 00	0 81	393	0 20	1 25
244	0 10	-0 05	294	0 15	0 15	344	1 00	1 00	394	5 00	1 25
245	0 15	0 00	295	0 17	0 12	345	0 81	1 00	395	5 00	1 50
246	0 42	0 06	296	0 12	0 17	346	0 64	1 00	396	4 06	1 50
247	0 41	0 11	297	0 09	0 19	347	0 65	0 81	397	0 00	1 50
248	0 31	0 10	298	0 10	0 15	348	1 89	0 81	398	0 00	1 25
249	0 24	0 10	299	0 05	0 20	349	1 89	1 00	399	0 12	1 50
250	0 25	0 05	300	0 00	0 20	350	1 39	1 00	400	1 00	1 75

LISTING D-6. Output Report File for Test Case Two. (Sheet 5 of 48)

TABLE 2. - NODE POINT COORDINATES

NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD	NODE	XCORD	YCORD
401	1.00	2.00	413	2.50	2.00	425	0.81	2.50	437	0.28	2.50
402	0.81	2.00	414	0.28	2.00	426	0.64	2.50	438	0.20	2.50
403	0.64	2.00	415	0.20	2.00	427	0.64	2.25	439	0.20	2.25
404	0.64	1.75	416	0.20	1.75	428	1.89	2.25	440	5.00	2.25
405	1.89	1.75	417	5.00	1.75	429	1.89	2.50	441	5.00	2.50
406	1.89	2.00	418	5.00	2.00	430	1.39	2.50	442	4.06	2.50
407	1.39	2.00	419	4.06	2.00	431	0.50	2.50	443	0.00	2.50
408	0.50	2.00	420	0.00	2.00	432	0.38	2.50	444	0.00	2.25
409	0.38	2.00	421	0.00	1.75	433	0.38	2.25	445	0.12	2.50
410	0.38	1.75	422	0.12	2.00	434	3.22	2.25			
411	3.22	1.75	423	1.00	2.25	435	3.22	2.50			
412	3.22	2.00	424	1.00	2.50	436	2.50	2.50			

LISTING D-6. Output Report File for Test Case Two. (Sheet 6 of 48)

TABLE 3. - ELEMENT/NODE CONNECTIVITY

ELEMENT	CONNECTIONS								TYPE	ORDER	ELEMENT	CONNECTIONS								TYPE	ORDER
M	N1	N2	N3	N4	N5	N6	N7	N8			M	N1	N2	N3	N4	N5	N6	N7	N8		
1	1	2	3	16	17	18	19	20	3	1	51	175	174	147	151	150	180	181	182	3	51
2	17	16	3	4	5	21	22	23	3	2	52	153	183	181	180	150	154	0	0	3	52
3	22	21	5	6	7	24	25	26	3	3	53	184	185	181	183	153	186	0	0	3	53
4	25	24	7	8	9	27	28	29	3	4	54	184	186	153	157	156	187	188	189	3	54
5	28	27	9	10	11	30	31	32	3	5	55	188	187	156	160	159	190	191	192	3	55
6	31	30	11	12	13	33	34	35	3	6	56	191	190	159	163	162	193	194	195	3	56
7	34	33	13	14	15	36	37	38	3	7	57	196	197	164	168	167	198	199	200	2	57
8	19	18	17	39	40	41	42	43	3	8	58	199	198	167	171	170	201	202	203	2	58
9	40	39	17	23	22	44	45	46	3	9	59	204	205	202	201	170	178	177	206	2	59
10	45	44	22	26	25	47	48	49	3	10	60	207	208	172	176	175	209	210	211	3	60
11	48	47	25	29	28	50	51	52	3	11	61	212	213	177	179	172	208	207	214	2	61
12	51	50	28	32	31	53	54	55	3	12	62	210	209	175	182	181	215	216	217	3	62
13	54	53	31	35	34	56	57	58	3	13	63	218	219	204	206	177	213	212	220	2	63
14	57	56	34	38	37	59	60	61	3	14	64	216	215	181	185	184	221	0	0	3	64
15	42	41	40	62	63	64	65	66	3	15	65	216	221	184	222	223	224	0	0	3	65
16	63	62	40	46	45	67	68	69	3	16	66	184	225	226	227	223	222	0	0	3	66
17	68	67	45	49	48	70	71	72	3	17	67	184	189	188	228	229	230	226	225	3	67
18	71	70	48	52	51	73	74	75	3	18	68	188	192	191	231	232	233	229	228	3	68
19	74	73	51	55	54	76	77	78	3	19	69	191	195	194	234	235	236	232	231	3	69
20	77	76	54	58	57	79	80	81	3	20	70	237	238	196	200	199	239	240	241	1	70
21	80	79	57	61	60	82	83	84	3	21	71	240	239	199	203	202	205	204	242	1	71
22	65	64	63	85	86	87	0	0	3	22	72	243	244	240	242	204	219	218	245	1	72
23	86	85	63	88	89	90	0	0	3	23	73	207	211	210	246	247	248	249	250	3	73
24	89	88	63	69	68	91	92	93	3	24	74	212	214	207	250	249	251	252	253	2	74
25	65	87	86	94	95	96	0	0	3	25	75	210	217	216	224	223	254	247	246	3	75
26	92	91	68	72	71	97	98	99	3	26	76	218	220	212	253	252	255	256	257	2	76
27	98	97	71	75	74	100	101	102	3	27	77	243	245	218	257	256	258	259	260	1	77
28	101	100	74	78	77	103	104	105	3	28	78	226	261	262	263	223	227	0	0	3	78
29	104	103	77	81	80	106	107	108	3	29	79	247	254	223	263	262	264	265	266	3	79
30	107	106	80	84	83	109	110	111	3	30	80	262	261	226	267	268	269	270	271	3	80
31	112	113	95	94	86	114	115	116	3	31	81	226	230	229	272	273	274	268	267	3	81
32	115	114	86	90	89	117	118	119	3	32	82	229	233	232	275	276	277	273	272	3	82
33	118	117	89	93	92	120	121	122	3	33	83	232	236	235	278	279	280	276	275	3	83
34	121	120	92	99	98	123	124	125	3	34	84	281	282	237	241	240	244	243	283	1	84
35	124	123	98	102	101	126	127	128	3	35	85	281	283	243	260	259	284	285	286	1	85
36	127	126	101	105	104	129	130	131	3	36	86	249	248	247	266	265	287	288	289	3	86
37	130	129	104	108	107	132	133	134	3	37	87	252	251	249	289	288	290	291	292	2	87
38	133	132	107	111	110	135	136	137	3	38	88	256	255	252	292	291	293	294	295	2	88
39	138	139	112	116	115	140	141	142	3	39	89	259	258	256	295	294	296	297	298	1	89
40	141	140	115	119	118	143	144	145	3	40	90	285	284	259	298	297	299	300	301	1	90
41	144	143	118	122	121	146	147	148	3	41	91	265	264	262	271	270	302	303	304	3	91
42	147	146	121	125	124	149	150	151	3	42	92	288	287	265	304	303	305	306	307	3	92
43	150	149	124	128	127	152	153	154	3	43	93	270	269	268	308	309	310	311	312	3	93
44	153	152	127	131	130	155	156	157	3	44	94	268	274	273	313	314	315	309	308	3	94
45	156	155	130	134	133	158	159	160	3	45	95	303	302	270	312	311	316	317	318	3	95
46	159	158	133	137	136	161	162	163	3	46	96	273	277	276	319	320	321	314	313	3	96
47	164	165	138	142	141	166	167	168	2	47	97	276	280	279	322	323	324	320	319	3	97
48	167	166	141	145	144	169	170	171	2	48	98	325	326	288	307	306	327	328	329	3	98
49	172	173	144	148	147	174	175	176	3	49	99	330	331	291	290	288	326	325	332	2	99
50	177	178	170	169	144	173	172	179	2	50	100	297	296	294	293	291	331	330	333	2	100

D-43

RHO-BM-CR-143 P

LISTING D-6. Output Report File for Test Case Two. (Sheet 7 of 48)

TABLE 3. - ELEMENT/NODE CONNECTIVITY

ELEMENT	CONNECTIONS								TYPE	ORDER	ELEMENT	CONNECTIONS								TYPE	ORDER
M	N1	N2	N3	N4	N5	N6	N7	N8			M	N1	N2	N3	N4	N5	N6	N7	N8		
101	300	299	297	333	330	334	335	336	2	101	119	349	356	355	388	389	390	383	382	3	119
102	306	305	303	318	317	337	338	339	3	102	120	358	357	352	387	386	391	392	393	3	120
103	328	327	306	339	338	340	341	342	3	103	121	355	362	361	394	395	396	389	388	3	121
104	311	310	309	343	344	345	346	347	3	104	122	397	398	373	375	358	393	392	399	3	122
105	309	315	314	348	349	350	344	343	3	105	123	380	379	378	400	401	402	403	404	3	123
106	317	316	311	347	346	351	352	353	3	106	124	378	384	383	405	406	407	401	400	3	124
107	314	321	320	354	355	356	349	348	3	107	125	386	385	380	404	403	408	409	410	3	125
108	338	337	317	353	352	357	358	359	3	108	126	383	390	389	411	412	413	406	405	3	126
109	320	324	323	360	361	362	355	354	3	109	127	392	391	386	410	409	414	415	416	3	127
110	363	364	325	329	328	365	366	367	3	110	128	389	396	395	417	418	419	412	411	3	128
111	335	334	330	332	325	364	363	368	2	111	129	420	421	397	399	392	416	415	422	3	129
112	366	365	328	342	341	369	370	371	3	112	130	403	402	401	423	424	425	426	427	3	130
113	341	340	338	359	358	372	0	0	3	113	131	401	407	406	428	429	430	424	423	3	131
114	373	374	341	372	358	375	0	0	3	114	132	409	408	403	427	426	431	432	433	3	132
115	373	376	370	369	341	374	0	0	3	115	133	406	413	412	434	435	436	429	428	3	133
116	346	345	344	377	378	379	380	381	3	116	134	415	414	409	433	432	437	438	439	3	134
117	344	350	349	382	383	384	378	377	3	117	135	412	419	418	440	441	442	435	434	3	135
118	352	351	346	381	380	385	386	387	3	118	136	443	444	420	422	415	439	438	445	3	136

LISTING D-6. Output Report File for Test Case Two. (Sheet 8 of 48)

TABLE 4. - INITIAL CONDITIONS

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	50.00	1.20	51	50.00	1.16	101	50.00	1.12
2	50.00	1.20	52	50.00	1.16	102	50.00	1.12
3	50.00	1.20	53	50.00	1.17	103	50.00	1.13
4	50.00	1.20	54	50.00	1.16	104	50.00	1.13
5	50.00	1.20	55	50.00	1.16	105	50.00	1.13
6	50.00	1.20	56	50.00	1.17	106	50.00	1.13
7	50.00	1.20	57	50.00	1.16	107	50.00	1.13
8	50.00	1.20	58	50.00	1.16	108	50.00	1.13
9	50.00	1.20	59	50.00	1.17	109	50.00	1.13
10	50.00	1.20	60	50.00	1.16	110	50.00	1.13
11	50.00	1.20	61	50.00	1.16	111	50.00	1.13
12	50.00	1.20	62	50.00	1.15	112	50.00	1.11
13	50.00	1.20	63	50.00	1.14	113	50.00	1.11
14	50.00	1.20	64	50.00	1.14	114	50.00	1.11
15	50.00	1.20	65	50.00	1.14	115	50.00	1.11
16	50.00	1.19	66	50.00	1.15	116	50.00	1.11
17	50.00	1.18	67	50.00	1.15	117	50.00	1.11
18	50.00	1.18	68	50.00	1.14	118	50.00	1.11
19	50.00	1.18	69	50.00	1.14	119	50.00	1.11
20	50.00	1.19	70	50.00	1.15	120	50.00	1.12
21	50.00	1.19	71	50.00	1.14	121	50.00	1.11
22	50.00	1.18	72	50.00	1.14	122	50.00	1.11
23	50.00	1.18	73	50.00	1.15	123	50.00	1.12
24	50.00	1.19	74	50.00	1.14	124	50.00	1.11
25	50.00	1.18	75	50.00	1.14	125	50.00	1.11
26	50.00	1.18	76	50.00	1.15	126	50.00	1.12
27	50.00	1.19	77	50.00	1.14	127	50.00	1.11
28	50.00	1.18	78	50.00	1.14	128	50.00	1.11
29	50.00	1.18	79	50.00	1.15	129	50.00	1.12
30	50.00	1.19	80	50.00	1.14	130	50.00	1.11
31	50.00	1.18	81	50.00	1.14	131	50.00	1.11
32	50.00	1.18	82	50.00	1.15	132	50.00	1.12
33	50.00	1.19	83	50.00	1.14	133	50.00	1.11
34	50.00	1.18	84	50.00	1.14	134	50.00	1.11
35	50.00	1.18	85	50.00	1.13	135	50.00	1.12
36	50.00	1.19	86	50.00	1.12	136	50.00	1.11
37	50.00	1.18	87	50.00	1.13	137	50.00	1.11
38	50.00	1.18	88	50.00	1.13	138	50.00	1.10
39	50.00	1.17	89	50.00	1.12	139	50.00	1.10
40	50.00	1.16	90	50.00	1.12	140	50.00	1.10
41	50.00	1.16	91	50.00	1.13	141	50.00	1.10
42	50.00	1.16	92	50.00	1.12	142	50.00	1.10
43	50.00	1.17	93	50.00	1.12	143	50.00	1.10
44	50.00	1.17	94	50.00	1.12	144	50.00	1.10
45	50.00	1.16	95	50.00	1.12	145	50.00	1.10
46	50.00	1.16	96	50.00	1.13	146	50.00	1.11
47	50.00	1.17	97	50.00	1.13	147	50.00	1.10
48	50.00	1.16	98	50.00	1.12	148	50.00	1.10
49	50.00	1.16	99	50.00	1.12	149	50.00	1.11
50	50.00	1.17	100	50.00	1.13	150	50.00	1.11

LISTING D-6. Output Report File for Test Case Two. (Sheet 9 of 48)

TABLE 4. - INITIAL CONDITIONS

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
151	50.00	1.10	201	50.00	1.10	251	50.00	1.10
152	50.00	1.11	202	50.00	1.10	252	50.00	1.10
153	50.00	1.11	203	50.00	1.10	253	50.00	1.10
154	50.00	1.11	204	50.00	1.10	254	50.00	1.10
155	50.00	1.11	205	50.00	1.10	255	50.00	1.10
156	50.00	1.11	206	50.00	1.10	256	50.00	1.10
157	50.00	1.11	207	50.00	1.10	257	50.00	1.10
158	50.00	1.11	208	50.00	1.10	258	50.00	1.10
159	50.00	1.11	209	50.00	1.10	259	50.00	1.10
160	50.00	1.11	210	50.00	1.10	260	50.00	1.10
161	50.00	1.11	211	50.00	1.10	261	50.00	1.09
162	50.00	1.11	212	50.00	1.10	262	50.00	1.09
163	50.00	1.11	213	50.00	1.10	263	50.00	1.09
164	50.00	1.10	214	50.00	1.10	264	50.00	1.09
165	50.00	1.10	215	50.00	1.10	265	50.00	1.10
166	50.00	1.10	216	50.00	1.10	266	50.00	1.10
167	50.00	1.10	217	50.00	1.10	267	50.00	1.09
168	50.00	1.10	218	50.00	1.10	268	50.00	1.09
169	50.00	1.10	219	50.00	1.10	269	50.00	1.09
170	50.00	1.10	220	50.00	1.10	270	50.00	1.09
171	50.00	1.10	221	50.00	1.10	271	50.00	1.09
172	50.00	1.10	222	50.00	1.10	272	50.00	1.09
173	50.00	1.10	223	50.00	1.10	273	50.00	1.08
174	50.00	1.10	224	50.00	1.10	274	50.00	1.08
175	50.00	1.10	225	50.00	1.09	275	50.00	1.09
176	50.00	1.10	226	50.00	1.09	276	50.00	1.08
177	50.00	1.10	227	50.00	1.09	277	50.00	1.08
178	50.00	1.10	228	50.00	1.09	278	50.00	1.09
179	50.00	1.10	229	50.00	1.09	279	50.00	1.08
180	50.00	1.10	230	50.00	1.09	280	50.00	1.08
181	50.00	1.10	231	50.00	1.09	281	50.00	1.10
182	50.00	1.10	232	50.00	1.09	282	50.00	1.10
183	50.00	1.10	233	50.00	1.09	283	50.00	1.10
184	50.00	1.10	234	50.00	1.09	284	50.00	1.10
185	50.00	1.10	235	50.00	1.09	285	50.00	1.10
186	50.00	1.10	236	50.00	1.09	286	50.00	1.10
187	50.00	1.10	237	50.00	1.10	287	50.00	1.10
188	50.00	1.10	238	50.00	1.10	288	50.00	1.10
189	50.00	1.10	239	50.00	1.10	289	50.00	1.10
190	50.00	1.10	240	50.00	1.10	290	50.00	1.10
191	50.00	1.10	241	50.00	1.10	291	50.00	1.10
192	50.00	1.10	242	50.00	1.10	292	50.00	1.10
193	50.00	1.10	243	50.00	1.10	293	50.00	1.10
194	50.00	1.10	244	50.00	1.10	294	50.00	1.10
195	50.00	1.10	245	50.00	1.10	295	50.00	1.10
196	50.00	1.10	246	50.00	1.10	296	50.00	1.10
197	50.00	1.10	247	50.00	1.10	297	50.00	1.10
198	50.00	1.10	248	50.00	1.10	298	50.00	1.10
199	50.00	1.10	249	50.00	1.10	299	50.00	1.10
200	50.00	1.10	250	50.00	1.10	300	50.00	1.10

LISTING D-6. Output Report File for Test Case Two. (Sheet 10 of 48)

TABLE 4. - INITIAL CONDITIONS

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
301	50.00	1.10	350	50.00	1.06	399	50.00	1.04
302	50.00	1.09	351	50.00	1.06	400	50.00	1.03
303	50.00	1.09	352	50.00	1.06	401	50.00	1.02
304	50.00	1.09	353	50.00	1.07	402	50.00	1.02
305	50.00	1.09	354	50.00	1.07	403	50.00	1.02
306	50.00	1.09	355	50.00	1.06	404	50.00	1.03
307	50.00	1.10	356	50.00	1.06	405	50.00	1.03
308	50.00	1.08	357	50.00	1.06	406	50.00	1.02
309	50.00	1.08	358	50.00	1.06	407	50.00	1.02
310	50.00	1.08	359	50.00	1.07	408	50.00	1.02
311	50.00	1.08	360	50.00	1.07	409	50.00	1.02
312	50.00	1.08	361	50.00	1.06	410	50.00	1.03
313	50.00	1.08	362	50.00	1.06	411	50.00	1.03
314	50.00	1.07	363	50.00	1.10	412	50.00	1.02
315	50.00	1.07	364	50.00	1.10	413	50.00	1.02
316	50.00	1.08	365	50.00	1.09	414	50.00	1.02
317	50.00	1.08	366	50.00	1.09	415	50.00	1.02
318	50.00	1.08	367	50.00	1.10	416	50.00	1.03
319	50.00	1.08	368	50.00	1.10	417	50.00	1.03
320	50.00	1.07	369	50.00	1.08	418	50.00	1.02
321	50.00	1.07	370	50.00	1.08	419	50.00	1.02
322	50.00	1.08	371	50.00	1.08	420	50.00	1.02
323	50.00	1.07	372	50.00	1.07	421	50.00	1.03
324	50.00	1.07	373	50.00	1.06	422	50.00	1.02
325	50.00	1.10	374	50.00	1.07	423	50.00	1.01
326	50.00	1.10	375	50.00	1.06	424	50.00	1.00
327	50.00	1.09	376	50.00	1.07	425	50.00	1.00
328	50.00	1.09	377	50.00	1.05	426	50.00	1.00
329	50.00	1.10	378	50.00	1.04	427	50.00	1.01
330	50.00	1.10	379	50.00	1.04	428	50.00	1.01
331	50.00	1.10	380	50.00	1.04	429	50.00	1.00
332	50.00	1.10	381	50.00	1.05	430	50.00	1.00
333	50.00	1.10	382	50.00	1.05	431	50.00	1.00
334	50.00	1.10	383	50.00	1.04	432	50.00	1.00
335	50.00	1.10	384	50.00	1.04	433	50.00	1.01
336	50.00	1.10	385	50.00	1.04	434	50.00	1.01
337	50.00	1.08	386	50.00	1.04	435	50.00	1.00
338	50.00	1.08	387	50.00	1.05	436	50.00	1.00
339	50.00	1.09	388	50.00	1.05	437	50.00	1.00
340	50.00	1.08	389	50.00	1.04	438	50.00	1.00
341	50.00	1.08	390	50.00	1.04	439	50.00	1.01
342	50.00	1.08	391	50.00	1.04	440	50.00	1.01
343	50.00	1.07	392	50.00	1.04	441	50.00	1.00
344	50.00	1.06	393	50.00	1.05	442	50.00	1.00
345	50.00	1.06	394	50.00	1.05	443	50.00	1.00
346	50.00	1.06	395	50.00	1.04	444	50.00	1.01
347	50.00	1.07	396	50.00	1.04	445	50.00	1.00
348	50.00	1.07	397	50.00	1.04			
349	50.00	1.06	398	50.00	1.05			

LISTING D-6. Output Report File for Test Case Two. (Sheet 11 of 48)

TABLE 5. - SPECIFIED BOUNDARY CONDITIONS

NUMBER OF SPECIFIED BOUNDARY NODES 30

NODE	TYPE	T(C)	H(M)
1	(11)	50.000	1.200
2	(11)	50.000	1.200
3	(11)	50.000	1.200
4	(11)	50.000	1.200
5	(11)	50.000	1.200
6	(11)	50.000	1.200
7	(11)	50.000	1.200
8	(11)	50.000	1.200
9	(11)	50.000	1.200
10	(11)	50.000	1.200
11	(11)	50.000	1.200
12	(11)	50.000	1.200
13	(11)	50.000	1.200
14	(11)	50.000	1.200
15	(11)	50.000	1.200
441	(11)	50.000	1.000
442	(11)	50.000	1.000
435	(11)	50.000	1.000
436	(11)	50.000	1.000
429	(11)	50.000	1.000
430	(11)	50.000	1.000
424	(11)	50.000	1.000
425	(11)	50.000	1.000
426	(11)	50.000	1.000
431	(11)	50.000	1.000
432	(11)	50.000	1.000
437	(11)	50.000	1.000
438	(11)	50.000	1.000
445	(11)	50.000	1.000
443	(11)	50.000	1.000

LISTING D-6. Output Report File for Test Case Two. (Sheet 12 of 48)

TABLE 6. - ROCK PROPERTIES

PARAMETER	ROCK TYPES		
	1 CANST	2 PCKNG	3 STRESS
1. SPECIFIC HEAT (J/KG-C)	1.500E+03	9.300E+02	9.300E+02
2. THERMAL CONDUCTIVITY IN X (J/SEC-M-C)	1.500E+00	8.000E-01	1.000E+00
3. THERMAL CONDUCTIVITY IN Y (J/SEC-M-C)	1.500E+00	8.000E-01	1.000E+00
4. EFFECTIVE POROSITY (FRACTION)	1.000E-02	3.000E-01	2.200E-04
5. HYDRAULIC CONDUCTIVITY (KXX-M/SEC)	1.000E-08	1.000E-09	1.000E-12
6. HYDRAULIC CONDUCTIVITY (KZZ-M/SEC)	1.000E-08	1.000E-09	1.000E-12
7. SPECIFIC STORAGE (1/M)	1.000E-03	1.000E-03	1.000E-05
8. ROCK DENSITY (KG/M**3)	2.500E+03	1.800E+03	2.780E+03
9. LONGITUDINAL DISPERSIVITY (M)	1.000E-10	1.000E-10	1.000E-10
10. LATERAL DISPERSIVITY (M)	1.000E-10	1.000E-10	1.000E-10
11. FRACTURE/FAULT THICKNESS (M)	0.000E-01	0.000E-01	0.000E-01

TABLE 7. - HEAT GENERATION HISTORY

NUMBER OF HEAT SOURCE ELEMENTS.....	8
NUMBER OF TIME POINTS.....	2
SCALE FACTOR FOR HEAT LOAD.....	1.00

HEAT SOURCE ELEMENT NUMBER							
70	71	72	77	84	85	89	90
TIME (YR)				THERMAL LOAD (J/YR-M**3)			
0.000				0.100E+11			
0.100E+04				0.100E+11			

LISTING D-6. Output Report File for Test Case Two. (Sheet 13 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 1.000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	50.00	*	51	53.62	1.358	101	56.82	1.483
2	50.00	*	52	53.90	1.371	102	57.68	1.520
3	50.00	*	53	51.77	1.272	103	53.64	1.338
4	50.00	*	54	52.33	1.293	104	53.87	1.345
5	50.00	*	55	53.03	1.329	105	53.32	1.414
6	50.00	*	56	50.86	1.221	106	51.67	1.233
7	50.00	*	57	51.12	1.227	107	51.77	1.232
8	50.00	*	58	51.65	1.257	108	52.66	1.282
9	50.00	*	59	50.50	1.200	109	50.96	1.190
10	50.00	*	60	50.65	1.198	110	51.01	1.187
11	50.00	*	61	50.77	1.206	111	51.21	1.199
12	50.00	*	62	55.91	1.456	112	63.79	1.754
13	50.00	*	63	57.52	1.521	113	62.11	1.694
14	50.00	*	64	57.59	1.524	114	62.03	1.691
15	50.00	*	65	57.63	1.526	115	63.68	1.751
16	51.06	1.248	66	55.98	1.459	116	63.73	1.752
17	52.15	1.297	67	55.73	1.448	117	62.07	1.692
18	52.16	1.298	68	57.22	1.508	118	63.74	1.753
19	52.17	1.298	69	57.40	1.516	119	63.68	1.751
20	51.07	1.249	70	55.30	1.429	120	61.04	1.653
21	51.04	1.247	71	56.56	1.480	121	62.17	1.695
22	52.10	1.295	72	56.94	1.496	122	63.10	1.729
23	52.13	1.297	73	54.58	1.396	123	59.29	1.583
24	50.99	1.244	74	55.53	1.434	124	59.91	1.606
25	51.99	1.290	75	56.08	1.459	125	61.09	1.652
26	52.06	1.293	76	52.85	1.313	126	57.28	1.499
27	50.89	1.239	77	53.32	1.329	127	57.61	1.510
28	51.78	1.279	78	54.47	1.384	128	58.74	1.557
29	51.90	1.285	79	51.35	1.231	129	54.04	1.348
30	50.60	1.225	80	51.55	1.233	130	54.15	1.350
31	51.19	1.249	81	52.32	1.276	131	55.79	1.428
32	51.52	1.266	82	50.78	1.196	132	51.83	1.230
33	50.29	1.208	83	50.89	1.193	133	51.87	1.228
34	50.58	1.215	84	51.06	1.204	134	52.83	1.281
35	50.86	1.231	85	58.85	1.572	135	51.05	1.183
36	50.17	1.200	86	60.46	1.634	136	51.07	1.180
37	50.34	1.200	87	58.93	1.576	137	51.28	1.192
38	50.40	1.204	88	58.94	1.576	138	67.25	1.868
39	53.29	1.347	89	60.46	1.633	139	65.53	1.813
40	54.53	1.400	90	60.45	1.633	140	65.39	1.810
41	54.56	1.401	91	58.50	1.558	141	67.06	1.869
42	54.58	1.402	92	59.78	1.607	142	67.14	1.868
43	53.32	1.348	93	60.20	1.623	143	65.43	1.813
44	53.22	1.343	94	60.50	1.635	144	66.96	1.870
45	54.41	1.395	95	60.53	1.636	145	67.00	1.869
46	54.49	1.398	96	59.04	1.580	146	63.13	1.729
47	53.03	1.335	97	57.57	1.519	147	63.79	1.753
48	54.13	1.381	98	58.49	1.554	148	65.45	1.814
49	54.29	1.389	99	59.21	1.583	149	60.35	1.621
50	52.69	1.318	100	56.24	1.461	150	60.63	1.631

LISTING D-6. Output Report File for Test Case Two. (Sheet 14 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 1 000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
151	62 16	1 691	201	68 42	1 870	251	67 52	1 876
152	57 82	1 516	202	68 99	1 871	252	67 98	1 876
153	57 95	1 520	203	68 94	1 870	253	68 09	1 875
154	59 22	1 573	204	69 00	1 872	254	62 15	1 684
155	54 22	1 350	205	68 94	1 871	255	68 47	1 876
156	54 26	1 349	206	68 47	1 872	256	69 00	1 876
157	55 98	1 431	207	67 27	1 874	257	69 12	1 875
158	51 90	1 225	208	67 17	1 873	258	69 67	1 876
159	51 91	1 223	209	63 81	1 752	259	70 22	1 876
160	52 90	1 278	210	63 87	1 753	260	70 62	1 875
161	51 09	1 177	211	65 58	1 816	261	59 22	1 562
162	51 09	1 174	212	68 21	1 874	262	60 63	1 621
163	51 31	1 187	213	68 09	1 873	263	60 63	1 622
164	68 19	1 869	214	67 73	1 874	264	62 16	1 683
165	67 71	1 869	215	60 70	1 630	265	63 79	1 749
166	67 50	1 869	216	60 73	1 630	266	63 74	1 747
167	67 96	1 869	217	62 24	1 690	267	57 82	1 499
168	68 07	1 869	218	69 21	1 874	268	57 61	1 486
169	67 41	1 870	219	69 12	1 873	269	58 74	1 535
170	67 89	1 870	220	68 70	1 874	270	59 91	1 586
171	67 89	1 869	221	59 35	1 573	271	60 35	1 607
172	67 09	1 872	222	59 26	1 567	272	54 22	1 330
173	67 02	1 871	223	60 65	1 624	273	54 15	1 322
174	63 74	1 750	224	60 70	1 627	274	55 79	1 401
175	63 75	1 751	225	58 03	1 513	275	51 90	1 204
176	65 43	1 811	226	57 95	1 507	276	51 87	1 199
177	67 98	1 872	227	59 15	1 560	277	52 83	1 252
178	67 90	1 871	228	54 29	1 339	278	51 09	1 155
179	67 52	1 872	229	54 26	1 335	279	51 07	1 150
180	60 63	1 630	230	55 98	1 417	280	51 28	1 163
181	60 65	1 630	231	51 92	1 212	281	71 32	1 874
182	62 15	1 689	232	51 91	1 208	282	71 20	1 873
183	59 15	1 569	233	52 90	1 263	283	71 20	1 874
184	58 09	1 519	234	51 10	1 162	284	70 62	1 877
185	59 26	1 571	235	51 09	1 158	285	70 79	1 876
186	58 03	1 521	236	51 31	1 171	286	71 20	1 875
187	54 29	1 348	237	70 79	1 872	287	65 45	1 815
188	54 31	1 344	238	70 13	1 871	288	66 96	1 878
189	56 06	1 427	239	69 66	1 871	289	67 02	1 877
190	51 92	1 221	240	70 22	1 872	290	67 41	1 878
191	51 93	1 217	241	70 62	1 872	291	67 89	1 878
192	52 92	1 272	242	69 67	1 872	292	67 90	1 877
193	51 10	1 171	243	70 79	1 874	293	68 41	1 878
194	51 10	1 167	244	70 62	1 873	294	68 99	1 878
195	51 32	1 180	245	70 14	1 874	295	68 94	1 877
196	69 20	1 869	246	63 81	1 750	296	68 94	1 878
197	68 68	1 869	247	63 75	1 748	297	68 99	1 879
198	68 46	1 869	248	65 43	1 812	298	69 66	1 878
199	68 99	1 870	249	67 08	1 876	299	69 11	1 879
200	69 11	1 869	250	67 17	1 875	300	69 20	1 879

LISTING D-6. Output Report File for Test Case Two. (Sheet 15 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 1 000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
301	70 13	1 878	350	54 47	1 312	399	54 56	1 294
302	61 09	1 635	351	56 94	1 431	400	52 69	1 186
303	62 17	1 680	352	57 22	1 444	401	51 78	1 125
304	63 13	1 721	353	58 50	1 509	402	51 90	1 132
305	63 09	1 718	354	51 67	1 170	403	51 99	1 137
306	63 74	1 745	355	51 55	1 155	404	53 03	1 204
307	65 43	1 815	356	52 32	1 199	405	51 77	1 137
308	57 28	1 466	357	57 40	1 452	406	51 19	1 093
309	56 82	1 440	358	57 52	1 457	407	51 52	1 111
310	57 68	1 479	359	58 94	1 528	408	52 06	1 140
311	58 49	1 515	360	50 96	1 126	409	52 10	1 143
312	59 29	1 555	361	50 89	1 115	410	53 22	1 213
313	54 04	1 312	362	51 06	1 126	411	50 86	1 084
314	53 87	1 298	363	67 25	1 880	412	50 58	1 057
315	55 32	1 369	364	67 14	1 880	413	50 86	1 073
316	59 21	1 546	365	63 73	1 743	414	52 13	1 144
317	59 78	1 571	366	63 79	1 745	415	52 15	1 145
318	61 04	1 629	367	65 53	1 815	416	53 29	1 217
319	51 83	1 191	368	67 71	1 880	417	50 50	1 061
320	51 77	1 182	369	60 50	1 601	418	50 34	1 041
321	52 66	1 233	370	60 53	1 603	419	50 40	1 045
322	51 05	1 144	371	62 11	1 673	420	52 17	1 146
323	51 01	1 136	372	58 85	1 523	421	53 32	1 219
324	51 21	1 148	373	57 63	1 463	422	52 16	1 146
325	67 06	1 880	374	58 95	1 528	423	50 89	1 063
326	67 00	1 879	375	57 59	1 460	424	50 00	* 1 000 *
327	63 68	1 741	376	59 04	1 532	425	50 00	* 1 000 *
328	63 68	1 742	377	54 58	1 307	426	50 00	* 1 000 *
329	65 39	1 811	378	53 62	1 247	427	50 99	1 068
330	67 96	1 879	379	53 90	1 261	428	50 60	1 047
331	67 89	1 879	380	54 13	1 273	429	50 00	* 1 000 *
332	67 50	1 879	381	55 30	1 342	430	50 00	* 1 000 *
333	68 46	1 879	382	52 85	1 218	431	50 00	* 1 000 *
334	68 07	1 879	383	52 33	1 179	432	50 00	* 1 000 *
335	68 19	1 879	384	53 03	1 217	433	51 04	1 071
336	68 68	1 879	385	54 29	1 281	434	50 29	1 029
337	60 20	1 589	386	54 41	1 287	435	50 00	* 1 000 *
338	60 46	1 601	387	55 73	1 362	436	50 00	* 1 000 *
339	62 07	1 672	388	51 35	1 133	437	50 00	* 1 000 *
340	60 45	1 600	389	51 12	1 110	438	50 00	* 1 000 *
341	60 46	1 600	390	51 65	1 141	439	51 06	1 072
342	62 03	1 670	391	54 49	1 291	440	50 17	1 021
343	56 24	1 406	392	54 53	1 293	441	50 00	* 1 000 *
344	55 53	1 365	393	55 91	1 371	442	50 00	* 1 000 *
345	56 08	1 391	394	50 78	1 098	443	50 00	* 1 000 *
346	56 56	1 413	395	50 65	1 080	444	51 07	1 072
347	57 57	1 467	396	50 77	1 088	445	50 00	* 1 000 *
348	53 64	1 279	397	54 58	1 295			
349	53 32	1 254	398	55 98	1 374			

ITERATION NUMBER 1, MAX CHANGE (TEMP) = 2 1629E-03, MAX REL CORRECTION = 4 2879E-03
 ITERATION NUMBER 1, MAX CHANGE (HEAD) = 7 6922E-02, MAX REL CORRECTION = 2 9814E-02

LISTING D-6. Output Report File for Test Case Two. (Sheet 16 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
1	VEL X	1 7048E-07	3 5943E-07	7 2765E-07	9 2613E-08	1 9638E-07	3 9330E-07	2 0105E-08	4 2863E-08	8 4953E-08
	VEL Y	-1 7252E-05	-1 7197E-05	-1 7116E-05	-1 6977E-05	-1 6925E-05	-1 6848E-05	-1 6701E-05	-1 6652E-05	-1 6579E-05
2	VEL X	1 1890E-06	6 5240E-07	1 4304E-07	1 0124E-06	5 4966E-07	1 1918E-07	7 4884E-07	3 9562E-07	8 3232E-08
	VEL Y	-1 6717E-05	-1 6479E-05	-1 6239E-05	-1 6917E-05	-1 6667E-05	-1 6415E-05	-1 7054E-05	-1 6792E-05	-1 6528E-05
3	VEL X	1 9186E-06	1 0501E-06	2 2969E-07	1 6786E-06	9 1141E-07	1 9764E-07	1 3662E-06	7 3060E-07	1 5577E-07
	VEL Y	-1 5710E-05	-1 5540E-05	-1 5369E-05	-1 6187E-05	-1 5989E-05	-1 5790E-05	-1 6551E-05	-1 6325E-05	-1 6097E-05
4	VEL X	2 5867E-06	1 4148E-06	3 0921E-07	2 3749E-06	1 2922E-06	2 8087E-07	2 1171E-06	1 1428E-06	2 4632E-07
	VEL Y	-1 3761E-05	-1 3712E-05	-1 3662E-05	-1 4626E-05	-1 4527E-05	-1 4428E-05	-1 5346E-05	-1 5199E-05	-1 5050E-05
5	VEL X	2 7972E-06	1 5549E-06	3 4567E-07	2 7800E-06	1 5411E-06	3 4162E-07	2 7544E-06	1 5206E-06	3 3562E-07
	VEL Y	-8 4737E-06	-8 5906E-06	-8 7073E-06	-1 0918E-05	-1 0970E-05	-1 1020E-05	-1 2931E-05	-1 2916E-05	-1 2900E-05
6	VEL X	1 6199E-06	9 1389E-07	2 0623E-07	2 0561E-06	1 1598E-06	2 6170E-07	2 6216E-06	1 4787E-06	3 3361E-07
	VEL Y	-2 1025E-06	-2 2170E-06	-2 3315E-06	-4 3496E-06	-4 4727E-06	-4 5958E-06	-6 8596E-06	-6 9920E-06	-7 1242E-06
7	VEL X	1 7952E-07	1 0418E-07	2 4165E-08	6 7210E-07	3 8205E-07	8 6864E-08	1 2703E-06	7 1950E-07	1 6301E-07
	VEL Y	1 0864E-06	1 0205E-06	9 5463E-07	4 3522E-07	3 5013E-07	2 6497E-07	-9 5083E-07	-1 0563E-06	-1 1619E-06
8	VEL X	4 8666E-07	9 4404E-07	1 9007E-06	3 3969E-07	6 8455E-07	1 3860E-06	2 2763E-07	4 7583E-07	9 6709E-07
	VEL Y	-1 9630E-05	-1 9531E-05	-1 9401E-05	-1 8596E-05	-1 8515E-05	-1 8407E-05	-1 7557E-05	-1 7495E-05	-1 7408E-05
9	VEL X	3 0888E-06	2 2696E-06	1 5784E-06	2 6532E-06	1 9192E-06	1 3372E-06	2 0115E-06	1 4005E-06	9 7844E-07
	VEL Y	-1 8707E-05	-1 7846E-05	-1 6982E-05	-1 9038E-05	-1 8123E-05	-1 7203E-05	-1 9286E-05	-1 8315E-05	-1 7340E-05
10	VEL X	4 9064E-06	3 6198E-06	2 5368E-06	4 3364E-06	3 1610E-06	2 2140E-06	3 5989E-06	2 5663E-06	1 7947E-06
	VEL Y	-1 7036E-05	-1 6471E-05	-1 5903E-05	-1 7793E-05	-1 7107E-05	-1 6417E-05	-1 8404E-05	-1 7596E-05	-1 6785E-05
11	VEL X	6 3310E-06	4 7330E-06	3 3842E-06	5 8891E-06	4 3628E-06	3 1079E-06	5 3532E-06	3 9132E-06	2 7719E-06
	VEL Y	-1 4083E-05	-1 3991E-05	-1 3897E-05	-1 5335E-05	-1 5052E-05	-1 4768E-05	-1 6428E-05	-1 5955E-05	-1 5480E-05
12	VEL X	6 2221E-06	4 8619E-06	3 5976E-06	6 3770E-06	4 9297E-06	3 5966E-06	6 6064E-06	5 0299E-06	3 5952E-06
	VEL Y	-7 5728E-06	-7 9890E-06	-8 4055E-06	-1 0380E-05	-1 0599E-05	-1 0818E-05	-1 2877E-05	-1 2899E-05	-1 2918E-05
13	VEL X	3 3645E-06	2 7148E-06	2 0494E-06	4 3689E-06	3 4998E-06	2 6132E-06	5 6710E-06	4 5177E-06	3 3441E-06
	VEL Y	-1 2617E-06	-1 6100E-06	-1 9588E-06	-3 3570E-06	-3 7561E-06	-4 1556E-06	-5 8096E-06	-6 2604E-06	-6 7116E-06
14	VEL X	3 6741E-07	3 0478E-07	2 2740E-07	1 3871E-06	1 1244E-06	8 4557E-07	2 6253E-06	2 1198E-06	1 5963E-06
	VEL Y	1 5735E-06	1 3790E-06	1 1843E-06	1 0179E-06	7 6503E-07	5 1181E-07	-2 2182E-07	-5 3424E-07	-8 4707E-07
15	VEL X	1 1926E-06	2 2599E-06	4 6667E-06	8 1373E-07	1 5956E-06	3 3070E-06	5 9219E-07	1 1566E-06	2 3567E-06
	VEL Y	-2 5849E-05	-2 5576E-05	-2 5234E-05	-2 3140E-05	-2 2953E-05	-2 2703E-05	-2 0422E-05	-2 0320E-05	-2 0159E-05
16	VEL X	7 3130E-06	5 3126E-06	3 8201E-06	6 2657E-06	4 4548E-06	3 2456E-06	4 7415E-06	3 2007E-06	2 4016E-06
	VEL Y	-2 3393E-05	-2 1395E-05	-1 9387E-05	-2 4255E-05	-2 2039E-05	-1 9812E-05	-2 4921E-05	-2 2486E-05	-2 0038E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 17 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1.000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
17	VEL X	1.0697E-05	7.9920E-06	5.9726E-06	9.6360E-06	7.0696E-06	5.2722E-06	8.2708E-06	5.8804E-06	4.3672E-06
	VEL Y	-1.9489E-05	-1.8501E-05	-1.7508E-05	-2.1185E-05	-1.9787E-05	-1.8384E-05	-2.2628E-05	-2.0821E-05	-1.9006E-05
18	VEL X	1.2180E-05	9.5584E-06	7.5390E-06	1.1767E-05	9.0839E-06	7.0573E-06	1.1268E-05	8.5093E-06	6.4734E-06
	VEL Y	-1.3978E-05	-1.4172E-05	-1.4364E-05	-1.6162E-05	-1.5895E-05	-1.5625E-05	-1.8215E-05	-1.7487E-05	-1.6756E-05
19	VEL X	9.9379E-06	8.4865E-06	7.1582E-06	1.0887E-05	9.0884E-06	7.4362E-06	1.2293E-05	9.9794E-06	7.8478E-06
	VEL Y	-5.5016E-06	-6.4027E-06	-7.3050E-06	-8.7287E-06	-9.3764E-06	-1.0024E-05	-1.2076E-05	-1.2471E-05	-1.2865E-05
20	VEL X	4.8654E-06	4.3459E-06	3.7738E-06	6.5481E-06	5.7707E-06	4.9339E-06	8.7297E-06	7.6179E-06	6.4380E-06
	VEL Y	1.9931E-07	-3.7731E-07	-9.5478E-07	-1.5124E-06	-2.2508E-06	-2.9903E-06	-3.7258E-06	-4.6274E-06	-5.5303E-06
21	VEL X	5.1939E-07	4.7584E-07	4.0913E-07	1.9930E-06	1.7811E-06	1.5438E-06	3.7827E-06	3.3663E-06	2.9218E-06
	VEL Y	2.3820E-06	2.0715E-06	1.7606E-06	1.9723E-06	1.5709E-06	1.1688E-06	9.8723E-07	4.9378E-07	-4.0647E-10
22	VEL X	3.6104E-06	5.5274E-06	3.0515E-06	2.7628E-06	1.6983E-06	5.3690E-06	5.0480E-06		
	VEL Y	-2.9921E-05	-3.0980E-05	-3.1776E-05	-2.7040E-05	-2.8189E-05	-2.6655E-05	-3.4950E-05		
23	VEL X	7.8850E-06	7.8811E-06	8.6322E-06	6.6132E-06	7.1700E-06	4.7852E-06	1.0536E-05		
	VEL Y	-3.3340E-05	-3.1666E-05	-3.6746E-05	-3.1853E-05	-3.6192E-05	-2.8328E-05	-3.6160E-05		
24	VEL X	1.5802E-05	1.1956E-05	8.9889E-06	1.3850E-05	1.0263E-05	7.7107E-06	1.1040E-05	7.8147E-06	5.8550E-06
	VEL Y	-3.0503E-05	-2.7564E-05	-2.5127E-05	-3.3101E-05	-2.9389E-05	-2.6303E-05	-3.5172E-05	-3.0736E-05	-2.7038E-05
25	VEL X	1.5711E-06	3.0733E-06	1.5414E-08	2.2476E-06	4.0744E-07	5.3086E-06	7.7587E-07		
	VEL Y	-3.4426E-05	-3.7868E-05	-3.3002E-05	-3.2740E-05	-2.9437E-05	-3.7033E-05	-3.7734E-05		
26	VEL X	1.9959E-05	1.6004E-05	1.2792E-05	1.8799E-05	1.4805E-05	1.1640E-05	1.7315E-05	1.3267E-05	1.0159E-05
	VEL Y	-2.1118E-05	-2.0636E-05	-2.0248E-05	-2.4962E-05	-2.3495E-05	-2.2288E-05	-2.8435E-05	-2.6023E-05	-2.4027E-05
27	VEL X	1.8848E-05	1.6334E-05	1.4032E-05	1.9367E-05	1.6443E-05	1.3749E-05	1.9995E-05	1.6576E-05	1.3406E-05
	VEL Y	-1.1968E-05	-1.3022E-05	-1.3903E-05	-1.5191E-05	-1.5712E-05	-1.6154E-05	-1.8604E-05	-1.8581E-05	-1.8572E-05
28	VEL X	1.2646E-05	1.1812E-05	1.0865E-05	1.4871E-05	1.3550E-05	1.2092E-05	1.8165E-05	1.6122E-05	1.3908E-05
	VEL Y	-2.6608E-06	-3.8245E-06	-4.7890E-06	-5.6210E-06	-6.8404E-06	-7.8534E-06	-9.4783E-06	-1.0674E-05	-1.1670E-05
29	VEL X	5.7319E-06	5.4928E-06	5.1641E-06	7.9320E-06	7.5137E-06	6.9941E-06	1.0785E-05	1.0134E-05	9.3667E-06
	VEL Y	1.7134E-06	1.1376E-06	6.6229E-07	5.2688E-07	-3.1102E-07	-1.0035E-06	-1.2646E-06	-2.3082E-06	-3.1721E-06
30	VEL X	6.0301E-07	5.8698E-07	5.4641E-07	2.3370E-06	2.2330E-06	2.1020E-06	4.4429E-06	4.2320E-06	3.9911E-06
	VEL Y	3.1792E-06	2.8824E-06	2.6382E-06	2.9244E-06	2.5190E-06	2.1851E-06	2.2004E-06	1.7323E-06	1.3461E-06
31	VEL X	1.2363E-05	9.2098E-06	7.1037E-06	6.9243E-06	5.1363E-06	3.8828E-06	2.2928E-06	1.7933E-06	1.3287E-06
	VEL Y	-5.6787E-05	-4.7694E-05	-4.0658E-05	-5.7767E-05	-4.8344E-05	-4.1095E-05	-5.8426E-05	-4.8805E-05	-4.1424E-05
32	VEL X	2.4079E-05	1.6887E-05	1.2051E-05	1.9897E-05	1.3873E-05	9.7235E-06	1.6468E-05	1.1564E-05	8.0651E-06
	VEL Y	-5.3362E-05	-4.5429E-05	-3.9177E-05	-5.4555E-05	-4.6205E-05	-3.9666E-05	-5.5958E-05	-4.7151E-05	-4.0305E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 18 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
33	VEL X	3 4073E-05	2 5694E-05	1 9220E-05	3 0615E-05	2 2638E-05	1 6878E-05	2 5703E-05	1 8271E-05	1 3514E-05
	VEL Y	-3 7009E-05	-3 4612E-05	-3 2745E-05	-4 4808E-05	-3 9939E-05	-3 6118E-05	-5 1165E-05	-4 4016E-05	-3 8377E-05
34	VEL X	3 1613E-05	2 7009E-05	2 2911E-05	3 2680E-05	2 7073E-05	2 2017E-05	3 4045E-05	2 7159E-05	2 0876E-05
	VEL Y	-1 8445E-05	-1 9963E-05	-2 1166E-05	-2 4852E-05	-2 5027E-05	-2 5181E-05	-3 1746E-05	-3 0540E-05	-2 9613E-05
35	VEL X	2 4590E-05	2 2750E-05	2 0633E-05	2 7128E-05	2 4484E-05	2 1533E-05	3 0181E-05	2 6573E-05	2 2620E-05
	VEL Y	-7 5119E-06	-9 5218E-06	-1 1094E-05	-1 0733E-05	-1 2746E-05	-1 4326E-05	-1 4896E-05	-1 6803E-05	-1 8306E-05
36	VEL X	1 4196E-05	1 3785E-05	1 3199E-05	1 7627E-05	1 6782E-05	1 5728E-05	2 2704E-05	2 1219E-05	1 9472E-05
	VEL Y	1 8914E-07	-9 9535E-07	-1 9152E-06	-1 8836E-06	-3 4943E-06	-4 7484E-06	-5 2851E-06	-7 1585E-06	-8 6214E-06
37	VEL X	6 1575E-06	6 0465E-06	5 8730E-06	8 6718E-06	8 4550E-06	8 1679E-06	1 1931E-05	1 1578E-05	1 1143E-05
	VEL Y	2 9739E-06	2 4682E-06	2 0778E-06	2 2306E-06	1 4723E-06	8 8574E-07	9 7869E-07	3 3319E-08	-6 9978E-07
38	VEL X	6 4235E-07	6 3606E-07	6 1382E-07	2 5076E-06	2 4576E-06	2 3902E-06	4 7726E-06	4 6697E-06	4 5474E-06
	VEL Y	3 8187E-06	3 5692E-06	3 3777E-06	3 6757E-06	3 3288E-06	3 0620E-06	3 2125E-06	2 8112E-06	2 5018E-06
39	VEL X	2 6730E-05	2 1229E-05	1 5602E-05	1 1711E-05	1 0978E-05	8 7996E-06	-1 5662E-06	1 9427E-06	2 7786E-06
	VEL Y	-9 1932E-05	-7 4819E-05	-6 3245E-05	-9 1923E-05	-7 5860E-05	-6 5120E-05	-8 9739E-05	-7 5524E-05	-6 6047E-05
40	VEL X	6 1668E-05	4 3047E-05	3 0616E-05	4 8129E-05	3 3099E-05	2 4504E-05	3 3948E-05	2 3497E-05	1 9000E-05
	VEL Y	-7 8120E-05	-6 7818E-05	-6 0497E-05	-8 4560E-05	-7 1360E-05	-6 2057E-05	-9 0224E-05	-7 3903E-05	-6 2578E-05
41	VEL X	5 8872E-05	4 8463E-05	4 0163E-05	6 3322E-05	4 9224E-05	3 7477E-05	6 9607E-05	5 0308E-05	3 3667E-05
	VEL Y	-3 2053E-05	-3 5466E-05	-3 7896E-05	-4 9391E-05	-4 7365E-05	-4 5963E-05	-6 8885E-05	-6 1205E-05	-5 5790E-05
42	VEL X	4 1061E-05	3 8515E-05	3 4931E-05	4 6943E-05	4 2524E-05	3 6935E-05	5 4382E-05	4 7611E-05	3 9486E-05
	VEL Y	-1 0378E-05	-1 4076E-05	-1 6663E-05	-1 5693E-05	-2 0156E-05	-2 3296E-05	-2 3706E-05	-2 8479E-05	-3 1859E-05
43	VEL X	2 7885E-05	2 7073E-05	2 5792E-05	3 2267E-05	3 0789E-05	2 8801E-05	3 7512E-05	3 5246E-05	3 2417E-05
	VEL Y	-2 2379E-06	-4 4657E-06	-6 0059E-06	-4 3339E-06	-7 1768E-06	-9 1508E-06	-7 7955E-06	-1 1005E-05	-1 3245E-05
44	VEL X	1 4884E-05	1 4738E-05	1 4460E-05	1 9016E-05	1 8641E-05	1 8108E-05	2 5128E-05	2 4415E-05	2 3506E-05
	VEL Y	2 4396E-06	1 4877E-06	8 3797E-07	1 3439E-06	-1 7493E-07	-1 2166E-06	-9 3558E-07	-2 7973E-06	-4 0810E-06
45	VEL X	6 3337E-06	6 2923E-06	6 2184E-06	8 9928E-06	8 9057E-06	8 7823E-06	1 2439E-05	1 2294E-05	1 2106E-05
	VEL Y	3 8755E-06	3 4976E-06	3 2430E-06	3 4685E-06	2 8999E-06	2 5149E-06	2 7092E-06	2 0205E-06	1 5517E-06
46	VEL X	6 5827E-07	6 5657E-07	6 4639E-07	2 5785E-06	2 5594E-06	2 5312E-06	4 9100E-06	4 8701E-06	4 8199E-06
	VEL Y	4 2652E-06	4 0885E-06	3 9709E-06	4 2044E-06	3 9460E-06	3 7734E-06	3 9400E-06	3 6429E-06	3 4434E-06
47	VEL X	-2 1876E-05	-2 4482E-05	-2 7196E-05	-1 1984E-05	-1 1896E-05	-1 1840E-05	-2 3036E-06	5 2846E-07	3 5064E-06
	VEL Y	-7 8169E-05	-9 2052E-05	-1 0454E-04	-6 7419E-05	-8 1542E-05	-9 4539E-05	-5 2952E-05	-6 6961E-05	-8 0090E-05
48	VEL X	-5 9221E-06	-7 3533E-06	-9 0241E-06	-1 6321E-05	-1 7760E-05	-1 9357E-05	-1 9833E-05	-2 1152E-05	-2 2483E-05
	VEL Y	-1 1438E-04	-1 3105E-04	-1 4595E-04	-1 0003E-04	-1 1471E-04	-1 2772E-04	-8 4124E-05	-9 7697E-05	-1 0974E-04

LISTING D-6. Output Report File for Test Case Two. (Sheet 19 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
49	VEL X	6 6953E-05	6 6013E-05	6 4019E-05	7 8252E-05	7 4803E-05	7 0396E-05	9 4453E-05	8 7199E-05	7 9310E-05
	VEL Y	-1 7077E-05	-2 2801E-05	-2 9051E-05	-2 2741E-05	-3 2514E-05	-4 2386E-05	-3 5136E-05	-4 9226E-05	-6 2180E-05
50	VEL X	3 8256E-05	1 8376E-05	-1 4569E-07	3 5053E-05	1 7660E-05	7 6511E-07	3 1994E-05	1 6976E-05	1 4094E-06
	VEL Y	-1 7787E-04	-1 7136E-04	-1 5594E-04	-1 5792E-04	-1 5399E-04	-1 4044E-04	-1 3606E-04	-1 3482E-04	-1 2327E-04
51	VEL X	4 3329E-05	4 2576E-05	4 2008E-05	5 0665E-05	4 9500E-05	4 8552E-05	6 0075E-05	5 8316E-05	5 6831E-05
	VEL Y	-4 4312E-06	-6 2747E-06	-8 8588E-06	-8 4468E-06	-1 0925E-05	-1 4140E-05	-1 4175E-05	-1 7776E-05	-2 2118E-05
52	VEL X	3 5262E-05	3 9272E-05	3 3297E-05	3 3503E-05	2 9356E-05	3 8617E-05	3 8590E-05		
	VEL Y	-4 3700E-06	-5 1982E-06	-4 3325E-06	-2 9550E-06	-8 3142E-07	-3 5720E-06	-7 3235E-06		
53	VEL X	3 1320E-05	3 2559E-05	2 7926E-05	3 3518E-05	2 9297E-05	3 7260E-05	2 7449E-05		
	VEL Y	5 5265E-07	-1 7532E-06	1 5269E-06	1 2663E-06	2 8407E-06	-1 0877E-06	-1 6550E-06		
54	VEL X	1 5159E-05	1 5074E-05	1 4966E-05	1 9622E-05	1 9427E-05	1 9202E-05	2 6228E-05	2 5871E-05	2 5471E-05
	VEL Y	4 3922E-06	3 7817E-06	2 4840E-06	4 0158E-06	3 1346E-06	1 2067E-06	3 3504E-06	2 0691E-06	-8 1823E-07
55	VEL X	6 4089E-06	6 3848E-06	6 3544E-06	9 1342E-06	9 0884E-06	9 0349E-06	1 2667E-05	1 2594E-05	1 2510E-05
	VEL Y	4 6616E-06	4 4075E-06	3 9046E-06	4 5328E-06	4 1820E-06	3 4688E-06	4 3264E-06	3 8423E-06	2 8303E-06
56	VEL X	6 6357E-07	6 6230E-07	6 5880E-07	2 6097E-06	2 5997E-06	2 5872E-06	4 9731E-06	4 9525E-06	4 9288E-06
	VEL Y	4 6816E-06	4 5474E-06	4 2994E-06	4 6592E-06	4 4974E-06	4 1903E-06	4 5907E-06	4 3819E-06	3 9751E-06
57	VEL X	-1 8130E-05	-1 9362E-05	-2 1244E-05	-1 1820E-05	-1 1938E-05	-1 2410E-05	-4 7520E-06	-3 9988E-06	-3 3397E-06
	VEL Y	-4 5616E-05	-5 8769E-05	-7 0123E-05	-2 9401E-05	-4 3740E-05	-5 6662E-05	-1 9066E-05	-3 3609E-05	-4 7149E-05
58	VEL X	3 5753E-06	-1 3424E-06	-5 9837E-06	-5 9091E-06	-1 0571E-05	-1 4927E-05	-1 1454E-05	-1 5212E-05	-1 8608E-05
	VEL Y	-6 4693E-05	-8 5733E-05	-1 0402E-04	-6 1692E-05	-7 8568E-05	-9 2961E-05	-5 3090E-05	-6 6859E-05	-7 8406E-05
59	VEL X	3 5429E-05	1 7657E-05	1 7840E-07	3 5200E-05	1 9387E-05	2 2952E-06	3 5112E-05	2 1063E-05	3 7964E-06
	VEL Y	-1 2636E-04	-1 2533E-04	-1 1290E-04	-1 0322E-04	-1 0543E-04	-9 5528E-05	-7 7497E-05	-8 3261E-05	-7 6337E-05
60	VEL X	7 2005E-05	7 0475E-05	6 7947E-05	8 2307E-05	8 1725E-05	7 9721E-05	9 7702E-05	9 8488E-05	9 7069E-05
	VEL Y	1 1662E-07	-6 3472E-06	-1 3533E-05	-5 4083E-08	-9 7926E-06	-2 0602E-05	2 1182E-06	-1 2168E-05	-2 7875E-05
61	VEL X	9 1053E-05	8 2043E-05	5 6833E-05	8 5053E-05	7 6881E-05	5 1804E-05	7 9064E-05	7 1734E-05	4 6676E-05
	VEL Y	-1 8500E-04	-1 8172E-04	-1 6852E-04	-1 5999E-04	-1 6084E-04	-1 5254E-04	-1 3382E-04	-1 3884E-04	-1 3571E-04
62	VEL X	4 4828E-05	4 4326E-05	4 3757E-05	5 3034E-05	5 2265E-05	5 1357E-05	6 3708E-05	6 2558E-05	6 1149E-05
	VEL Y	3 0580E-06	1 8848E-07	-3 4200E-06	2 1460E-06	-1 5033E-06	-5 9168E-06	9 5682E-07	-4 0192E-06	-9 7878E-06
63	VEL X	7 6609E-05	6 0912E-05	4 4793E-05	6 9587E-05	5 6594E-05	4 2883E-05	6 2577E-05	5 2321E-05	4 1027E-05
	VEL Y	-1 2091E-04	-1 2609E-04	-1 2580E-04	-9 6694E-05	-1 0148E-04	-1 0226E-04	-7 0762E-05	-7 4937E-05	-7 6546E-05
64	VEL X	3 6664E-05	3 4613E-05	3 5011E-05	4 0764E-05	4 0675E-05	3 9696E-05	3 0721E-05		
	VEL Y	2 8680E-06	2 1760E-06	4 6778E-06	1 0325E-06	3 6595E-06	-1 4724E-06	4 3670E-06		

LISTING D-6. Output Report File for Test Case Two. (Sheet 20 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
65	VEL X	3 6842E-05	3 4860E-05	4 1020E-05	3 5044E-05	4 0732E-05	3 0774E-05	4 0116E-05		
	VEL Y	6 4818E-06	7 3677E-06	8 0356E-06	4 7879E-06	5 4224E-06	5 5114E-06	1 0634E-05		
66	VEL X	3 1690E-05	3 3097E-05	3 3854E-05	2 8149E-05	2 9377E-05	2 7863E-05	3 7838E-05		
	VEL Y	9 1498E-06	1 1299E-05	8 4225E-06	8 3262E-06	6 9948E-06	1 1477E-05	1 0559E-05		
67	VEL X	2 5791E-05	1 9402E-05	1 5084E-05	2 6079E-05	1 9562E-05	1 5160E-05	2 6281E-05	1 9657E-05	1 5183E-05
	VEL Y	1 0514E-05	8 7491E-06	7 5576E-06	7 5631E-06	6 7511E-06	6 2640E-06	6 2556E-06	5 8388E-06	5 6560E-06
68	VEL X	1 2597E-05	9 0914E-06	6 3871E-06	1 2648E-05	9 1249E-06	6 4074E-06	1 2681E-05	9 1434E-06	6 4150E-06
	VEL Y	6 8115E-06	6 2854E-06	5 8937E-06	5 8210E-06	5 5654E-06	5 3913E-06	5 3477E-06	5 2116E-06	5 1376E-06
69	VEL X	4 9542E-06	2 6000E-06	6 6131E-07	4 9681E-06	2 6081E-06	6 6477E-07	4 9769E-06	2 6118E-06	6 6437E-07
	VEL Y	5 5862E-06	5 4062E-06	5 2962E-06	5 1812E-06	5 0925E-06	5 0518E-06	4 9734E-06	4 9272E-06	4 9197E-06
70	VEL X	-1 5282E-04	-2 0021E-04	-2 6993E-04	-8 1818E-05	-1 1443E-04	-1 4331E-04	-2 5505E-05	-4 7079E-05	-4 9980E-05
	VEL Y	2 2603E-04	1 3795E-04	3 2503E-05	3 8703E-04	2 7367E-04	9 3343E-05	4 4666E-04	3 5343E-04	1 5087E-04
71	VEL X	-2 1587E-04	-2 8682E-04	-3 2433E-04	-1 8917E-04	-2 5778E-04	-3 1164E-04	-1 7804E-04	-2 3763E-04	-2 7114E-04
	VEL Y	-3 8977E-04	-3 6860E-04	-2 7500E-04	-1 3109E-04	-1 7073E-04	-1 5904E-04	1 0014E-04	3 1392E-05	-3 5598E-05
72	VEL X	4 1620E-05	-4 0283E-05	-1 4052E-04	2 9165E-05	-4 9107E-05	-1 3003E-04	1 5909E-05	-6 1643E-05	-1 3083E-04
	VEL Y	-4 9498E-04	-4 8218E-04	-4 4359E-04	-6 6315E-05	-8 7467E-05	-1 3318E-04	2 4785E-04	2 2635E-04	1 3710E-04
73	VEL X	1 0386E-04	8 3876E-05	7 0332E-05	1 0255E-04	8 4189E-05	7 1888E-05	9 8654E-05	8 2882E-05	7 2336E-05
	VEL Y	3 0628E-05	2 5806E-05	2 0578E-05	1 3474E-05	1 4187E-05	1 2904E-05	-1 3198E-06	4 1520E-06	6 2204E-06
74	VEL X	1 3836E-04	1 4356E-04	1 4899E-04	1 1686E-04	1 2245E-04	1 2815E-04	8 7365E-05	9 3504E-05	9 9668E-05
	VEL Y	-7 3771E-05	-9 1602E-05	-1 0853E-04	-1 0327E-04	-1 2120E-04	-1 3838E-04	-1 2078E-04	-1 3920E-04	-1 5698E-04
75	VEL X	6 2999E-05	5 2549E-05	4 4448E-05	6 3682E-05	5 2994E-05	4 4758E-05	6 3978E-05	5 3210E-05	4 4935E-05
	VEL Y	1 7325E-05	1 4494E-05	1 2652E-05	1 1183E-05	9 8667E-06	8 9530E-06	6 0237E-06	6 1071E-06	6 0374E-06
76	VEL X	1 2175E-04	1 2730E-04	1 3314E-04	1 0058E-04	1 0711E-04	1 1379E-04	7 3742E-05	8 1306E-05	8 8898E-05
	VEL Y	-2 4165E-05	-4 5061E-05	-6 4859E-05	-5 1601E-05	-7 3001E-05	-9 3527E-05	-6 7613E-05	-8 9529E-05	-1 1082E-04
77	VEL X	2 2337E-04	2 4729E-04	2 8695E-04	1 5206E-04	1 6222E-04	1 7783E-04	6 9952E-05	7 9859E-05	9 0929E-05
	VEL Y	2 1716E-04	-5 0784E-05	-3 5315E-04	2 6998E-04	-4 1715E-05	-4 3261E-04	2 6000E-04	-5 0373E-05	-4 7554E-04
78	VEL X	3 6003E-05	4 0164E-05	3 4114E-05	3 4026E-05	2 9862E-05	3 9587E-05	3 9364E-05		
	VEL Y	1 3910E-05	1 4447E-05	1 2533E-05	1 4131E-05	1 0800E-05	1 6740E-05	1 2796E-05		
79	VEL X	6 0058E-05	5 0619E-05	4 3165E-05	6 1044E-05	5 1259E-05	4 3567E-05	6 2277E-05	5 2077E-05	4 4137E-05
	VEL Y	3 0578E-05	2 3163E-05	1 8299E-05	2 5843E-05	1 9761E-05	1 5624E-05	2 2028E-05	1 7194E-05	1 3739E-05
80	VEL X	3 3808E-05	2 9828E-05	2 6515E-05	3 6476E-05	3 1684E-05	2 7689E-05	3 8577E-05	3 3027E-05	2 8390E-05
	VEL Y	2 3183E-05	1 9198E-05	1 6143E-05	2 0789E-05	1 7109E-05	1 4527E-05	1 7330E-05	1 4080E-05	1 2174E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 21 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
81	VEL X	2 4074E-05	1 8460E-05	1 4666E-05	2 4880E-05	1 8927E-05	1 4905E-05	2 5498E-05	1 9244E-05	1 5015E-05
	VEL Y	1 3900E-05	1 1192E-05	9 2404E-06	1 2564E-05	1 0125E-05	8 5807E-06	1 0613E-05	8 5595E-06	7 6090E-06
82	VEL X	1 2270E-05	8 8871E-06	6 2775E-06	1 2425E-05	8 9890E-06	6 3385E-06	1 2542E-05	9 0582E-06	6 3703E-06
	VEL Y	8 1379E-06	7 2431E-06	6 5641E-06	7 6645E-06	6 8579E-06	6 3059E-06	6 9654E-06	6 2863E-06	5 9211E-06
83	VEL X	4 8681E-06	2 5547E-06	6 4972E-07	4 9088E-06	2 5782E-06	6 5898E-07	4 9402E-06	2 5933E-06	6 6042E-07
	VEL Y	6 1300E-06	5 8202E-06	5 6326E-06	5 9268E-06	5 6479E-06	5 5133E-06	5 6231E-06	5 3890E-06	5 3332E-06
84	VEL X	1 6799E-05	-4 4225E-05	-1 1458E-04	8 3314E-06	-2 5098E-05	-5 8905E-05	-2 5578E-07	-8 1833E-06	-1 1775E-05
	VEL Y	3 9020E-04	3 7263E-04	2 6762E-04	5 6052E-04	5 4689E-04	4 2747E-04	6 3037E-04	6 3380E-04	5 1637E-04
85	VEL X	2 2692E-05	1 0131E-04	1 9225E-04	1 9014E-05	6 5718E-05	1 1651E-04	9 3572E-06	3 0797E-05	5 2790E-05
	VEL Y	5 8664E-04	5 0045E-04	3 4600E-04	6 7327E-04	5 8787E-04	4 1540E-04	6 3950E-04	5 7140E-04	4 0119E-04
86	VEL X	9 0514E-05	7 7675E-05	6 8515E-05	9 7083E-05	8 1118E-05	6 9840E-05	1 0256E-04	8 3291E-05	6 9893E-05
	VEL Y	7 1932E-05	5 1190E-05	3 7712E-05	5 5690E-05	3 9498E-05	3 0686E-05	3 8998E-05	2 8385E-05	2 4449E-05
87	VEL X	1 5325E-04	1 6150E-04	1 7052E-04	1 5466E-04	1 6205E-04	1 6984E-04	1 4511E-04	1 5088E-04	1 5678E-04
	VEL Y	2 1438E-05	1 0098E-05	4 6288E-07	-1 8954E-05	-3 1855E-05	-4 3064E-05	-5 3380E-05	-6 9833E-05	-8 4494E-05
88	VEL X	1 2121E-04	1 3369E-04	1 4662E-04	1 3254E-04	1 4256E-04	1 5277E-04	1 2856E-04	1 3512E-04	1 4170E-04
	VEL Y	5 5131E-05	3 9412E-05	2 6341E-05	2 1736E-05	4 2258E-06	-1 0562E-05	-7 0005E-06	-2 7399E-05	-4 4988E-05
89	VEL X	3 6755E-04	4 2369E-04	4 4230E-04	3 3307E-04	3 7318E-04	4 2641E-04	2 7149E-04	3 0697E-04	3 6224E-04
	VEL Y	1 1312E-04	-1 7147E-05	-1 5516E-04	1 5081E-04	-5 3841E-05	-2 5545E-04	1 9461E-04	-3 4667E-05	-2 9252E-04
90	VEL X	6 9460E-05	1 9270E-04	3 5986E-04	6 3000E-05	1 5988E-04	2 8195E-04	3 7599E-05	1 2510E-04	2 3217E-04
	VEL Y	2 8566E-04	2 3323E-04	1 8136E-04	4 6401E-04	3 8842E-04	2 5686E-04	5 3343E-04	4 7844E-04	3 1959E-04
91	VEL X	4 2619E-05	3 9283E-05	3 6663E-05	5 1012E-05	4 4942E-05	4 0158E-05	5 7771E-05	4 9181E-05	4 2388E-05
	VEL Y	4 2855E-05	3 3830E-05	2 6935E-05	3 8576E-05	3 0080E-05	2 4071E-05	3 2466E-05	2 4700E-05	1 9942E-05
92	VEL X	3 8234E-05	4 1617E-05	4 4003E-05	5 7870E-05	5 4804E-05	5 2639E-05	8 0089E-05	7 0306E-05	6 3365E-05
	VEL Y	7 0077E-05	5 8493E-05	4 9533E-05	7 4878E-05	5 9021E-05	4 6104E-05	8 1614E-05	5 9738E-05	4 1207E-05
93	VEL X	2 3938E-05	2 2624E-05	2 1535E-05	2 7978E-05	2 5596E-05	2 3618E-05	3 1608E-05	2 8203E-05	2 5371E-05
	VEL Y	2 9091E-05	2 4938E-05	2 1598E-05	2 7357E-05	2 3178E-05	1 9908E-05	2 5122E-05	2 0907E-05	1 7726E-05
94	VEL X	2 0216E-05	1 6222E-05	1 3525E-05	2 1904E-05	1 7227E-05	1 4068E-05	2 3323E-05	1 8015E-05	1 4429E-05
	VEL Y	1 8746E-05	1 4872E-05	1 2053E-05	1 7197E-05	1 3560E-05	1 1109E-05	1 5195E-05	1 1863E-05	9 8855E-06
95	VEL X	2 2612E-05	2 3613E-05	2 4398E-05	2 9450E-05	2 8972E-05	2 8601E-05	3 6847E-05	3 4845E-05	3 3278E-05
	VEL Y	4 1484E-05	3 6619E-05	3 2327E-05	4 2188E-05	3 6217E-05	3 0871E-05	4 3071E-05	3 5690E-05	2 8995E-05
96	VEL X	1 1397E-05	8 3332E-06	5 9700E-06	1 1795E-05	8 5956E-06	6 1277E-06	1 2115E-05	8 7895E-06	6 2245E-06
	VEL Y	1 0452E-05	8 9050E-06	7 7418E-06	9 7075E-06	8 3106E-06	7 3446E-06	8 7414E-06	7 5878E-06	6 8272E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 22 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
97	VEL X	4 6252E-06	2 4282E-06	6 1918E-07	4 7355E-06	2 4897E-06	6 4047E-07	4 8268E-06	2 5342E-06	6 4617E-07
	VEL Y	7 0888E-06	6 5432E-06	6 2328E-06	6 7741E-06	6 2740E-06	6 0387E-06	6 3635E-06	5 9222E-06	5 7843E-06
98	VEL X	2 1731E-05	2 8024E-05	3 4846E-05	2 7338E-05	3 8595E-05	4 9907E-05	4 1027E-05	5 7544E-05	7 2645E-05
	VEL Y	7 8608E-05	7 7960E-05	7 5897E-05	9 1618E-05	8 7958E-05	8 2967E-05	1 1021E-04	1 0199E-04	9 2795E-05
99	VEL X	1 1580E-04	1 4714E-04	1 6394E-04	1 0930E-04	1 3960E-04	1 5668E-04	1 0270E-04	1 3215E-04	1 4973E-04
	VEL Y	8 8889E-05	6 3428E-05	2 6474E-05	9 1753E-05	6 7784E-05	3 3026E-05	9 6429E-05	7 4229E-05	4 1807E-05
100	VEL X	1 0035E-04	1 2975E-04	1 4445E-04	9 1743E-05	1 2068E-04	1 3587E-04	8 3047E-05	1 1183E-04	1 2792E-04
	VEL Y	1 0230E-04	7 9883E-05	4 4100E-05	1 0700E-04	8 5633E-05	5 1267E-05	1 1406E-04	9 3941E-05	6 0955E-05
101	VEL X	1 3573E-05	4 5304E-05	8 2562E-05	1 1242E-05	4 0843E-05	7 7220E-05	7 9140E-06	3 5681E-05	7 1490E-05
	VEL Y	1 2313E-04	1 2281E-04	1 1197E-04	1 2216E-04	1 2481E-04	1 1559E-04	1 2223E-04	1 2842E-04	1 2135E-04
102	VEL X	1 4891E-05	1 8445E-05	2 0919E-05	2 0354E-05	2 4883E-05	2 8052E-05	2 8873E-05	3 3855E-05	3 7362E-05
	VEL Y	5 1455E-05	4 8878E-05	4 5117E-05	5 7507E-05	5 2847E-05	4 6852E-05	6 5140E-05	5 7861E-05	4 9040E-05
103	VEL X	8 8747E-06	1 0692E-05	1 3239E-05	1 2950E-05	1 5479E-05	1 8754E-05	1 8890E-05	2 2643E-05	2 7156E-05
	VEL Y	5 3719E-05	5 2993E-05	5 2435E-05	6 1374E-05	6 0195E-05	5 9215E-05	7 1171E-05	6 9343E-05	6 7774E-05
104	VEL X	1 4303E-05	1 4592E-05	1 4831E-05	1 7640E-05	1 7387E-05	1 7178E-05	2 1212E-05	2 0399E-05	1 9726E-05
	VEL Y	2 9679E-05	2 7093E-05	2 4716E-05	2 9612E-05	2 6566E-05	2 3744E-05	2 9522E-05	2 5919E-05	2 2559E-05
105	VEL X	1 4624E-05	1 2625E-05	1 1275E-05	1 6866E-05	1 4079E-05	1 2198E-05	1 8918E-05	1 5382E-05	1 2994E-05
	VEL Y	2 2115E-05	1 8165E-05	1 5026E-05	2 1034E-05	1 7086E-05	1 4024E-05	1 9716E-05	1 5772E-05	1 2804E-05
106	VEL X	1 0961E-05	1 2497E-05	1 3693E-05	1 4334E-05	1 5881E-05	1 7087E-05	1 8726E-05	2 0164E-05	2 1288E-05
	VEL Y	3 5724E-05	3 3824E-05	3 1625E-05	3 7822E-05	3 5058E-05	3 1963E-05	4 0334E-05	3 6533E-05	3 2361E-05
107	VEL X	9 6864E-06	7 2090E-06	5 2982E-06	1 0431E-05	7 7112E-06	5 6136E-06	1 1056E-05	8 1101E-06	5 8380E-06
	VEL Y	1 3038E-05	1 0855E-05	9 1826E-06	1 2149E-05	1 0144E-05	8 6952E-06	1 1066E-05	9 2761E-06	8 1005E-06
108	VEL X	6 3568E-06	8 3440E-06	9 7130E-06	8 5242E-06	1 1142E-05	1 2953E-05	1 2109E-05	1 5100E-05	1 7178E-05
	VEL Y	3 9137E-05	3 8321E-05	3 7023E-05	4 3144E-05	4 1639E-05	3 9610E-05	4 7930E-05	4 5608E-05	4 2707E-05
109	VEL X	4 0973E-06	2 1539E-06	5 5362E-07	4 3274E-06	2 2797E-06	5 9364E-07	4 5274E-06	2 3784E-06	6 0895E-07
	VEL Y	8 2803E-06	7 4431E-06	6 9881E-06	7 8853E-06	7 1026E-06	6 7385E-06	7 4032E-06	6 6865E-06	6 4330E-06
110	VEL X	3 2623E-06	1 0139E-05	1 7854E-05	2 0976E-06	1 2978E-05	2 5234E-05	-2 0430E-06	1 4315E-05	3 2624E-05
	VEL Y	8 2974E-05	8 1907E-05	7 9479E-05	9 4333E-05	9 4626E-05	9 3002E-05	1 1127E-04	1 1354E-04	1 1289E-04
111	VEL X	2 5294E-05	5 5396E-05	8 6595E-05	2 0768E-05	5 1785E-05	8 5182E-05	1 5595E-05	4 7857E-05	8 3966E-05
	VEL Y	1 1501E-04	1 2056E-04	1 0554E-04	1 1606E-04	1 2272E-04	1 0749E-04	1 1804E-04	1 2613E-04	1 1095E-04
112	VEL X	1 4590E-06	4 2735E-06	7 8193E-06	2 0405E-06	5 7586E-06	1 0280E-05	2 7208E-06	7 9001E-06	1 3964E-05
	VEL Y	5 5039E-05	5 4649E-05	5 4131E-05	6 3395E-05	6 2828E-05	6 2043E-05	7 4245E-05	7 3415E-05	7 2223E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 23 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		QSS PNT 1	QSS PNT 2	QSS PNT 3	QSS PNT 4	QSS PNT 5	QSS PNT 6	QSS PNT 7	QSS PNT 8	QSS PNT 9
113	VEL X	8 6461E-06	8 6274E-06	7 2195E-06	9 5387E-06	7 9015E-06	1 1634E-05	5 1998E-06		
	VEL Y	4 6090E-05	4 4253E-05	4 4484E-05	4 9795E-05	4 9230E-05	4 9118E-05	4 0632E-05		
114	VEL X	3 9425E-06	6 0344E-06	3 0004E-06	3 3472E-06	1 8562E-06	5 5406E-06	5 8162E-06		
	VEL Y	4 2279E-05	4 3421E-05	3 9145E-05	4 4314E-05	4 0415E-05	4 7775E-05	3 8706E-05		
115	VEL X	1 7288E-06	3 3786E-06	2 4775E-06	-2 1834E-09	3 9770E-07	8 4117E-07	5 8561E-06		
	VEL Y	4 7344E-05	5 1102E-05	4 5498E-05	4 5793E-05	4 1888E-05	5 0954E-05	5 0193E-05		
116	VEL X	6 9528E-06	7 5573E-06	8 0561E-06	9 1107E-06	9 6851E-06	1 0160E-05	1 2035E-05	1 2509E-05	1 2902E-05
	VEL Y	2 7827E-05	2 6615E-05	2 5275E-05	2 8590E-05	2 6881E-05	2 5043E-05	2 9359E-05	2 7151E-05	2 4813E-05
117	VEL X	8 3531E-06	7 8666E-06	7 5379E-06	1 0572E-05	9 5640E-06	8 8827E-06	1 2964E-05	1 1400E-05	1 0344E-05
	VEL Y	2 3499E-05	2 0498E-05	1 7658E-05	2 3055E-05	1 9799E-05	1 6705E-05	2 2611E-05	1 9100E-05	1 5751E-05
118	VEL X	4 7115E-06	5 6760E-06	6 4223E-06	6 3348E-06	7 5924E-06	8 5678E-06	8 9161E-06	1 0349E-05	1 1462E-05
	VEL Y	3 0333E-05	2 9661E-05	2 8721E-05	3 2292E-05	3 1165E-05	2 9770E-05	3 4257E-05	3 2676E-05	3 0824E-05
119	VEL X	6 7492E-06	5 1522E-06	3 9204E-06	7 9402E-06	5 9938E-06	4 4925E-06	9 0539E-06	6 7682E-06	5 0051E-06
	VEL Y	1 5556E-05	1 2936E-05	1 0843E-05	1 4607E-05	1 2161E-05	1 0243E-05	1 3657E-05	1 1386E-05	9 6432E-06
120	VEL X	2 5958E-06	3 5049E-06	4 1236E-06	3 4549E-06	4 8041E-06	5 7268E-06	5 1381E-06	6 7717E-06	7 8943E-06
	VEL Y	3 1492E-05	3 1249E-05	3 0790E-05	3 4160E-05	3 3669E-05	3 2962E-05	3 6833E-05	3 6095E-05	3 5142E-05
121	VEL X	3 0374E-06	1 6001E-06	4 1658E-07	3 4801E-06	1 8371E-06	4 8421E-07	3 8928E-06	2 0470E-06	5 2715E-07
	VEL Y	9 6924E-06	8 5006E-06	7 8940E-06	9 1814E-06	8 0841E-06	7 5728E-06	8 6697E-06	7 6669E-06	7 2512E-06
122	VEL X	2 5491E-06	3 5683E-06	5 0387E-06	1 2501E-06	1 7246E-06	2 4482E-06	6 3933E-07	8 8238E-07	1 2994E-06
	VEL Y	3 1641E-05	3 4415E-05	3 7196E-05	3 1816E-05	3 4689E-05	3 7573E-05	3 1927E-05	3 4896E-05	3 7876E-05
123	VEL X	3 0021E-06	3 3606E-06	3 6555E-06	4 2171E-06	4 6919E-06	5 0829E-06	5 7571E-06	6 3186E-06	6 7815E-06
	VEL Y	2 6443E-05	2 5681E-05	2 4751E-05	2 6964E-05	2 5990E-05	2 4848E-05	2 7487E-05	2 6302E-05	2 4947E-05
124	VEL X	3 8651E-06	3 8481E-06	3 8367E-06	5 3852E-06	5 2482E-06	5 1556E-06	7 0480E-06	6 7632E-06	6 5708E-06
	VEL Y	2 3599E-05	2 1357E-05	1 8802E-05	2 3574E-05	2 1122E-05	1 8358E-05	2 3549E-05	2 0888E-05	1 7913E-05
125	VEL X	1 9484E-06	2 4011E-06	2 7495E-06	2 7759E-06	3 4144E-06	3 9069E-06	3 8875E-06	4 6763E-06	5 2860E-06
	VEL Y	2 7892E-05	2 7495E-05	2 6941E-05	2 8785E-05	2 8253E-05	2 7564E-05	2 9682E-05	2 9015E-05	2 8191E-05
126	VEL X	3 5490E-06	2 7612E-06	2 1535E-06	4 7691E-06	3 6795E-06	2 8391E-06	5 9627E-06	4 5748E-06	3 5043E-06
	VEL Y	1 6859E-05	1 4174E-05	1 1877E-05	1 6378E-05	1 3750E-05	1 1510E-05	1 5896E-05	1 3325E-05	1 1142E-05
127	VEL X	1 0635E-06	1 4529E-06	1 7148E-06	1 5165E-06	2 0773E-06	2 4562E-06	2 1784E-06	2 8698E-06	3 3391E-06
	VEL Y	2 8511E-05	2 8364E-05	2 8125E-05	2 9589E-05	2 9379E-05	2 9078E-05	3 0670E-05	3 0397E-05	3 0034E-05
128	VEL X	1 6809E-06	8 8590E-07	2 3124E-07	2 2189E-06	1 1726E-06	3 1098E-07	2 7370E-06	1 4413E-06	3 7435E-07
	VEL Y	1 0609E-05	9 1979E-06	8 4980E-06	1 0281E-05	8 9313E-06	8 2943E-06	9 9523E-06	8 6644E-06	8 0903E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 24 of 48)

SAMPLE PROBLEM. FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 1 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
129	VEL X	1 0511E-06	1 5028E-06	2 0594E-06	5 1729E-07	7 4142E-07	1 0214E-06	2 4760E-07	3 6713E-07	5 2513E-07
	VEL Y	2 8593E-05	2 9697E-05	3 0805E-05	2 8688E-05	2 9815E-05	3 0947E-05	2 8755E-05	2 9903E-05	3 1056E-05
130	VEL X	2 6755E-07	3 0456E-07	3 3492E-07	1 2409E-06	1 4010E-06	1 5324E-06	2 2985E-06	2 5747E-06	2 8017E-06
	VEL Y	2 5975E-05	2 5299E-05	2 4467E-05	2 6140E-05	2 5409E-05	2 4521E-05	2 6307E-05	2 5520E-05	2 4576E-05
131	VEL X	3 6318E-07	3 6762E-07	3 7062E-07	1 6416E-06	1 6554E-06	1 6648E-06	2 9671E-06	2 9812E-06	2 9907E-06
	VEL Y	2 3608E-05	2 1580E-05	1 9095E-05	2 3625E-05	2 1526E-05	1 8969E-05	2 3643E-05	2 1472E-05	1 8843E-05
132	VEL X	1 6998E-07	2 1522E-07	2 4986E-07	7 9598E-07	9 9150E-07	1 1415E-06	1 4864E-06	1 8243E-06	2 0841E-06
	VEL Y	2 7128E-05	2 6793E-05	2 6335E-05	2 7382E-05	2 7016E-05	2 6526E-05	2 7638E-05	2 7240E-05	2 6718E-05
133	VEL X	3 5609E-07	2 7818E-07	2 1809E-07	1 5758E-06	1 2307E-06	9 6447E-07	2 7892E-06	2 1777E-06	1 7060E-06
	VEL Y	1 7347E-05	1 4653E-05	1 2251E-05	1 7204E-05	1 4520E-05	1 2129E-05	1 7061E-05	1 4387E-05	1 2007E-05
134	VEL X	9 0831E-08	1 2987E-07	1 5577E-07	4 3130E-07	5 9872E-07	7 1038E-07	8 1600E-07	1 1025E-06	1 2945E-06
	VEL Y	2 7604E-05	2 7481E-05	2 7289E-05	2 7899E-05	2 7762E-05	2 7557E-05	2 8196E-05	2 8045E-05	2 7826E-05
135	VEL X	1 7244E-07	9 1511E-08	2 4870E-08	7 6041E-07	4 0184E-07	1 0657E-07	1 3413E-06	7 0574E-07	1 8241E-07
	VEL Y	1 0976E-05	9 4678E-06	8 7450E-06	1 0863E-05	9 3760E-06	8 6751E-06	1 0750E-05	9 2841E-06	8 6052E-06
136	VEL X	9 2514E-08	4 2829E-07	7 9198E-07	4 6761E-08	2 1412E-07	3 9162E-07	2 2023E-08	1 0127E-07	1 8616E-07
	VEL Y	2 7662E-05	2 7963E-05	2 8266E-05	2 7742E-05	2 8048E-05	2 8356E-05	2 7795E-05	2 8105E-05	2 8416E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 25 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 5 000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	50 00	* 1 200 *	51	53 67	1 160	101	56 89	1 129
2	50 00	* 1 200 *	52	53 95	1 159	102	57 75	1 129
3	50 00	* 1 200 *	53	51 81	1 170	103	53 71	1 135
4	50 00	* 1 200 *	54	52 37	1 160	104	53 94	1 129
5	50 00	* 1 200 *	55	53 08	1 160	105	55 40	1 129
6	50 00	* 1 200 *	56	50 89	1 170	106	51 74	1 134
7	50 00	* 1 200 *	57	51 16	1 160	107	51 84	1 128
8	50 00	* 1 200 *	58	51 70	1 160	108	52 73	1 128
9	50 00	* 1 200 *	59	50 53	1 170	109	51 03	1 134
10	50 00	* 1 200 *	60	50 69	1 160	110	51 08	1 127
11	50 00	* 1 200 *	61	50 82	1 160	111	51 28	1 127
12	50 00	* 1 200 *	62	55 97	1 149	112	63 87	1 118
13	50 00	* 1 200 *	63	57 58	1 140	113	62 19	1 123
14	50 00	* 1 200 *	64	57 65	1 140	114	62 11	1 123
15	50 00	* 1 200 *	65	57 70	1 140	115	63 77	1 118
16	51 07	1 189	66	56 04	1 149	116	63 81	1 118
17	52 17	1 179	67	55 78	1 150	117	62 15	1 122
18	52 18	1 179	68	57 28	1 140	118	63 82	1 118
19	52 19	1 179	69	57 47	1 140	119	63 76	1 118
20	51 08	1 189	70	55 35	1 150	120	61 11	1 123
21	51 05	1 189	71	56 62	1 141	121	62 25	1 120
22	52 13	1 179	72	57 00	1 141	122	63 18	1 119
23	52 16	1 179	73	54 63	1 150	123	59 36	1 124
24	51 00	1 189	74	55 59	1 141	124	59 99	1 121
25	52 02	1 179	75	56 15	1 141	125	61 17	1 120
26	52 08	1 179	76	52 91	1 151	126	57 35	1 124
27	50 90	1 190	77	53 39	1 141	127	57 69	1 121
28	51 81	1 179	78	54 53	1 141	128	58 81	1 121
29	51 92	1 179	79	51 40	1 151	129	54 11	1 123
30	50 61	1 190	80	51 61	1 141	130	54 23	1 119
31	51 21	1 180	81	52 38	1 141	131	55 87	1 120
32	51 55	1 179	82	50 83	1 151	132	51 90	1 122
33	50 31	1 190	83	50 95	1 141	133	51 95	1 117
34	50 61	1 180	84	51 13	1 141	134	52 91	1 118
35	50 88	1 180	85	58 92	1 134	135	51 12	1 121
36	50 18	1 190	86	60 54	1 128	136	51 15	1 117
37	50 36	1 180	87	59 02	1 134	137	51 35	1 117
38	50 43	1 180	88	59 01	1 133	138	67 34	1 110
39	53 33	1 169	89	60 54	1 127	139	65 62	1 114
40	54 58	1 159	90	60 52	1 128	140	65 47	1 114
41	54 60	1 159	91	58 57	1 134	141	67 15	1 111
42	54 62	1 159	92	59 86	1 128	142	67 23	1 110
43	53 36	1 169	93	60 27	1 128	143	65 52	1 114
44	53 25	1 169	94	60 57	1 128	144	67 05	1 112
45	54 46	1 159	95	60 60	1 128	145	67 09	1 111
46	54 53	1 159	96	59 11	1 134	146	63 21	1 117
47	53 07	1 169	97	57 64	1 134	147	63 87	1 116
48	54 17	1 159	98	58 56	1 129	148	65 54	1 114
49	54 34	1 159	99	59 28	1 128	149	60 43	1 118
50	52 73	1 169	100	56 31	1 135	150	60 72	1 116

LISTING D-6. Output Report File for Test Case Two. (Sheet 26 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 5 000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
151	62 25	1 116	201	68 51	1 112	251	67 61	1 118
152	57 90	1 117	202	69 08	1 113	252	68 07	1 118
153	58 03	1 115	203	69 03	1 112	253	68 18	1 117
154	59 30	1 116	204	69 09	1 114	254	62 24	1 110
155	54 30	1 115	205	69 03	1 113	255	68 56	1 118
156	54 34	1 113	206	68 56	1 114	256	69 09	1 118
157	56 06	1 114	207	67 36	1 116	257	69 21	1 117
158	51 97	1 114	208	67 25	1 115	258	69 76	1 119
159	51 99	1 111	209	63 89	1 114	259	70 31	1 119
160	52 97	1 112	210	63 95	1 114	260	70 71	1 117
161	51 16	1 113	211	65 67	1 115	261	59 30	1 104
162	51 17	1 110	212	68 30	1 116	262	60 72	1 106
163	51 38	1 110	213	68 18	1 115	263	60 71	1 107
164	68 28	1 111	214	67 82	1 116	264	62 25	1 109
165	67 80	1 111	215	60 78	1 113	265	63 87	1 112
166	67 59	1 111	216	60 81	1 111	266	63 82	1 112
167	68 05	1 111	217	62 32	1 112	267	57 90	1 100
168	68 16	1 111	218	69 30	1 116	268	57 69	1 096
169	67 50	1 112	219	69 21	1 115	269	58 81	1 098
170	67 98	1 112	220	68 79	1 116	270	59 99	1 100
171	67 98	1 112	221	59 42	1 110	271	60 43	1 104
172	67 17	1 114	222	59 34	1 108	272	54 30	1 095
173	67 11	1 113	223	60 73	1 108	273	54 23	1 092
174	63 82	1 115	224	60 78	1 110	274	55 87	1 094
175	63 84	1 115	225	58 11	1 105	275	51 97	1 092
176	65 52	1 115	226	58 03	1 103	276	51 95	1 088
177	68 07	1 114	227	59 23	1 105	277	52 91	1 090
178	67 99	1 113	228	54 37	1 101	278	51 16	1 091
179	67 61	1 114	229	54 34	1 098	279	51 15	1 087
180	60 71	1 115	230	56 06	1 100	280	51 35	1 087
181	60 73	1 114	231	52 00	1 098	281	71 41	1 116
182	62 24	1 115	232	51 99	1 095	282	71 29	1 115
183	59 23	1 114	233	52 97	1 096	283	71 29	1 116
184	58 17	1 109	234	51 18	1 097	284	70 71	1 119
185	59 34	1 112	235	51 17	1 094	285	70 88	1 119
186	58 11	1 113	236	51 38	1 094	286	71 29	1 117
187	54 37	1 110	237	70 88	1 114	287	65 54	1 116
188	54 39	1 105	238	70 22	1 113	288	67 05	1 121
189	56 14	1 107	239	69 75	1 113	289	67 10	1 120
190	52 00	1 108	240	70 31	1 114	290	67 50	1 120
191	52 01	1 103	241	70 71	1 114	291	67 98	1 120
192	53 00	1 104	242	69 76	1 114	292	67 99	1 119
193	51 18	1 107	243	70 89	1 116	293	68 50	1 120
194	51 18	1 102	244	70 71	1 115	294	69 08	1 120
195	51 39	1 102	245	70 23	1 116	295	69 03	1 119
196	69 29	1 111	246	63 89	1 113	296	69 03	1 120
197	68 77	1 111	247	63 84	1 112	297	69 08	1 121
198	68 55	1 111	248	65 52	1 115	298	69 75	1 120
199	69 08	1 112	249	67 17	1 119	299	69 20	1 121
200	69 20	1 111	250	67 25	1 117	300	69 29	1 121

LISTING D-6. Output Report File for Test Case Two. (Sheet 27 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 5 000

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
301	70 22	1 120	350	54 53	1 069	399	54 60	1 052
302	61 17	1 103	351	57 00	1 075	400	52 73	1 037
303	62 25	1 105	352	57 28	1 076	401	51 81	1 025
304	63 21	1 109	353	58 57	1 085	402	51 92	1 026
305	63 18	1 108	354	51 74	1 071	403	52 02	1 026
306	63 82	1 109	355	51 61	1 064	404	53 07	1 038
307	65 52	1 116	356	52 38	1 065	405	51 81	1 035
308	57 35	1 092	357	57 47	1 076	406	51 21	1 024
309	56 89	1 086	358	57 58	1 076	407	51 55	1 024
310	57 75	1 088	359	59 01	1 086	408	52 08	1 026
311	58 56	1 090	360	51 03	1 070	409	52 13	1 026
312	59 36	1 096	361	50 95	1 062	410	53 25	1 039
313	54 11	1 087	362	51 13	1 063	411	50 89	1 033
314	53 94	1 081	363	67 34	1 122	412	50 61	1 022
315	55 40	1 084	364	67 23	1 122	413	50 88	1 023
316	59 28	1 091	365	63 81	1 109	414	52 16	1 026
317	59 86	1 093	366	63 87	1 109	415	52 17	1 026
318	61 11	1 099	367	65 62	1 116	416	53 33	1 039
319	51 90	1 084	368	67 80	1 122	417	50 53	1 032
320	51 84	1 078	369	60 57	1 094	418	50 36	1 021
321	52 73	1 079	370	60 60	1 094	419	50 43	1 021
322	51 12	1 082	371	62 19	1 102	420	52 19	1 026
323	51 08	1 077	372	58 92	1 085	421	53 36	1 039
324	51 28	1 077	373	57 70	1 077	422	52 18	1 026
325	67 15	1 122	374	59 02	1 085	423	50 90	1 013
326	67 09	1 121	375	57 65	1 077	424	50 00	* 1 000
327	63 76	1 109	376	59 11	1 086	425	50 00	* 1 000
328	63 77	1 109	377	54 63	1 060	426	50 00	* 1 000
329	65 47	1 115	378	53 67	1 049	427	51 00	1 013
330	68 05	1 121	379	53 95	1 050	428	50 61	1 012
331	67 98	1 121	380	54 17	1 050	429	50 00	* 1 000
332	67 59	1 121	381	55 35	1 062	430	50 00	* 1 000
333	68 55	1 121	382	52 91	1 057	431	50 00	* 1 000
334	68 16	1 121	383	52 37	1 046	432	50 00	* 1 000
335	68 27	1 121	384	53 08	1 048	433	51 05	1 013
336	68 77	1 121	385	54 34	1 051	434	50 31	1 011
337	60 27	1 094	386	54 46	1 051	435	50 00	* 1 000
338	60 54	1 094	387	55 78	1 063	436	50 00	* 1 000
339	62 15	1 102	388	51 40	1 053	437	50 00	* 1 000
340	60 52	1 094	389	51 16	1 043	438	50 00	* 1 000
341	60 54	1 094	390	51 70	1 044	439	51 07	1 013
342	62 11	1 102	391	54 53	1 051	440	50 18	1 011
343	56 31	1 080	392	54 58	1 052	441	50 00	* 1 000
344	55 59	1 072	393	55 97	1 064	442	50 00	* 1 000
345	56 15	1 073	394	50 83	1 052	443	50 00	* 1 000
346	56 62	1 074	395	50 69	1 042	444	51 08	1 013
347	57 64	1 082	396	50 82	1 042	445	50 00	* 1 000
348	53 71	1 075	397	54 62	1 052			
349	53 39	1 067	398	56 04	1 064			

ITERATION NUMBER 1, MAX CHANGE (TEMP) = 3 5411E-05, MAX REL CORRECTION = 1 9037E-03
 ITERATION NUMBER 1, MAX CHANGE (HEAD) = 2 3423E-02, MAX REL CORRECTION = 3 4447E-02

LISTING D-6. Output Report File for Test Case Two. (Sheet 28 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
1	VEL X	-4 2346E-09	-8 5105E-09	-1 6843E-08	-2 3803E-09	-4 7429E-09	-9 2267E-09	-5 3783E-10	-1 0511E-09	-2 0003E-09
	VEL Y	5 0943E-06	5 0928E-06	5 0906E-06	5 0820E-06	5 0806E-06	5 0786E-06	5 0715E-06	5 0703E-06	5 0685E-06
2	VEL X	-2 7724E-08	-1 5295E-08	-3 3697E-09	-2 3727E-08	-1 2991E-08	-2 8491E-09	-1 7764E-08	-9 5368E-09	-2 0645E-09
	VEL Y	5 0785E-06	5 0679E-06	5 0590E-06	5 0840E-06	5 0727E-06	5 0632E-06	5 0877E-06	5 0760E-06	5 0660E-06
3	VEL X	-4 2535E-08	-2 3744E-08	-5 3011E-09	-3 7657E-08	-2 0981E-08	-4 6751E-09	-3 1312E-08	-1 7380E-08	-3 8573E-09
	VEL Y	5 0497E-06	5 0416E-06	5 0349E-06	5 0619E-06	5 0526E-06	5 0449E-06	5 0711E-06	5 0609E-06	5 0524E-06
4	VEL X	-5 3494E-08	-2 9391E-08	-6 4454E-09	-5 0256E-08	-2 7519E-08	-6 0223E-09	-4 6316E-08	-2 5238E-08	-5 5065E-09
	VEL Y	4 9944E-06	4 9920E-06	4 9907E-06	5 0158E-06	5 0110E-06	5 0073E-06	5 0340E-06	5 0269E-06	5 0211E-06
5	VEL X	-4 0190E-08	-2 3539E-08	-5 5066E-09	-4 3875E-08	-2 5787E-08	-6 0524E-09	-4 9329E-08	-2 9116E-08	-6 8603E-09
	VEL Y	4 8812E-06	4 8821E-06	4 8833E-06	4 9232E-06	4 9226E-06	4 9226E-06	4 9605E-06	4 9590E-06	4 9585E-06
6	VEL X	-1 1417E-08	-7 4313E-09	-1 8999E-09	-2 0111E-08	-1 2459E-08	-3 0623E-09	-3 1383E-08	-1 8978E-08	-4 5693E-09
	VEL Y	4 7763E-06	4 7765E-06	4 7766E-06	4 7985E-06	4 7997E-06	4 8008E-06	4 8305E-06	4 8320E-06	4 8336E-06
7	VEL X	1 9071E-09	7 6658E-10	1 0521E-10	-3 7865E-09	-2 4729E-09	-6 3387E-10	-1 0701E-08	-6 4071E-09	-1 5314E-09
	VEL Y	4 7325E-06	4 7319E-06	4 7313E-06	4 7339E-06	4 7343E-06	4 7345E-06	4 7471E-06	4 7472E-06	4 7472E-06
8	VEL X	-8 8904E-09	-1 8579E-08	-3 8844E-08	-6 5479E-09	-1 3952E-08	-2 9013E-08	-5 1768E-09	-1 0692E-08	-2 1608E-08
	VEL Y	5 1771E-06	5 1745E-06	5 1711E-06	5 1402E-06	5 1385E-06	5 1359E-06	5 1078E-06	5 1068E-06	5 1049E-06
9	VEL X	-5 9459E-08	-4 5264E-08	-3 4920E-08	-5 1810E-08	-3 8454E-08	-2 9677E-08	-4 0542E-08	-2 8373E-08	-2 1878E-08
	VEL Y	5 1484E-06	5 1188E-06	5 0930E-06	5 1572E-06	5 1251E-06	5 0971E-06	5 1639E-06	5 1296E-06	5 0995E-06
10	VEL X	-8 6262E-08	-6 7499E-08	-5 3173E-08	-7 8239E-08	-6 0138E-08	-4 7024E-08	-6 7859E-08	-5 0596E-08	-3 9035E-08
	VEL Y	5 0986E-06	5 0794E-06	5 0631E-06	5 1162E-06	5 0926E-06	5 0723E-06	5 1308E-06	5 1031E-06	5 0791E-06
11	VEL X	-9 3081E-08	-7 6448E-08	-6 5092E-08	-9 1341E-08	-7 3515E-08	-6 1459E-08	-8 9231E-08	-6 9953E-08	-5 7042E-08
	VEL Y	5 0172E-06	5 0147E-06	5 0137E-06	5 0417E-06	5 0324E-06	5 0251E-06	5 0645E-06	5 0486E-06	5 0353E-06
12	VEL X	-4 8481E-08	-4 8568E-08	-4 6818E-08	-6 2682E-08	-5 8616E-08	-5 2357E-08	-8 3704E-08	-7 3489E-08	-6 0555E-08
	VEL Y	4 8925E-06	4 8960E-06	4 8992E-06	4 9180E-06	4 9194E-06	4 9214E-06	4 9479E-06	4 9479E-06	4 9490E-06
13	VEL X	-4 6400E-09	-9 4072E-09	-1 2090E-08	-1 6881E-08	-2 0790E-08	-2 2344E-08	-3 2752E-08	-3 5547E-08	-3 5639E-08
	VEL Y	4 7905E-06	4 7903E-06	4 7895E-06	4 7932E-06	4 7954E-06	4 7972E-06	4 8035E-06	4 8073E-06	4 8107E-06
14	VEL X	3 3911E-09	2 6117E-09	2 3344E-09	-4 5221E-10	-2 4012E-09	-3 7997E-09	-5 1195E-09	-8 4890E-09	-1 1249E-08
	VEL Y	4 7377E-06	4 7358E-06	4 7336E-06	4 7365E-06	4 7356E-06	4 7344E-06	4 7369E-06	4 7360E-06	4 7346E-06
15	VEL X	-2 7745E-08	-4 5665E-08	-8 6074E-08	-1 6887E-08	-3 0411E-08	-6 0017E-08	-1 0945E-08	-2 2123E-08	-4 5892E-08
	VEL Y	5 3511E-06	5 3418E-06	5 3315E-06	5 2720E-06	5 2661E-06	5 2595E-06	5 2033E-06	5 2005E-06	5 1972E-06
16	VEL X	-1 3417E-07	-9 3658E-08	-7 0355E-08	-1 1891E-07	-7 9475E-08	-6 0431E-08	-9 6698E-08	-5 8739E-08	-4 5851E-08
	VEL Y	5 2653E-06	5 2158E-06	5 1745E-06	5 2920E-06	5 2328E-06	5 1825E-06	5 3133E-06	5 2451E-06	5 1863E-06

D-65

RHO-BW-CR-143 P

LISTING D-6. Output Report File for Test Case Two. (Sheet 29 of 48)

SAMPLE PROBLEM. FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
17	VEL X	-1 5532E-07	-1 1862E-07	-9 8635E-08	-1 5113E-07	-1 1125E-07	-9 0152E-08	-1 4574E-07	-1 0176E-07	-7 9190E-08
	VEL Y	5 1434E-06	5 1292E-06	5 1201E-06	5 1850E-06	5 1564E-06	5 1340E-06	5 2227E-06	5 1803E-06	5 1454E-06
18	VEL X	-1 0541E-07	-1 0056E-07	-1 0101E-07	-1 2321E-07	-1 0968E-07	-1 0195E-07	-1 4473E-07	-1 2071E-07	-1 0309E-07
	VEL Y	5 0124E-06	5 0244E-06	5 0378E-06	5 0427E-06	5 0451E-06	5 0502E-06	5 0766E-06	5 0695E-06	5 0667E-06
19	VEL X	-2 3752E-09	-2 6635E-08	-4 5026E-08	-3 3447E-08	-5 1736E-08	-6 3022E-08	-7 9443E-08	-8 8895E-08	-8 9661E-08
	VEL Y	4 8990E-06	4 9038E-06	4 9075E-06	4 8934E-06	4 9030E-06	4 9123E-06	4 9053E-06	4 9190E-06	4 9332E-06
20	VEL X	2 3762E-08	1 0562E-08	-2 1749E-10	1 8473E-08	1 8765E-09	-1 1987E-08	1 1615E-08	-9 3845E-09	-2 7247E-08
	VEL Y	4 8122E-06	4 8085E-06	4 8040E-06	4 7943E-06	4 7946E-06	4 7937E-06	4 7791E-06	4 7818E-06	4 7832E-06
21	VEL X	5 7386E-09	4 6673E-09	3 9026E-09	1 0948E-08	6 0483E-09	1 4847E-09	1 7275E-08	7 7254E-09	-1 4517E-09
	VEL Y	4 7505E-06	4 7460E-06	4 7409E-06	4 7460E-06	4 7419E-06	4 7372E-06	4 7364E-06	4 7318E-06	4 7265E-06
22	VEL X	-8 8428E-08	-1 3464E-07	-8 2045E-08	-5 9445E-08	-4 2334E-08	-1 0852E-07	-1 3759E-07		
	VEL Y	5 4370E-06	5 4578E-06	5 4891E-06	5 3690E-06	5 4043E-06	5 3509E-06	5 5688E-06		
23	VEL X	-2 1164E-07	-2 0411E-07	-2 6756E-07	-1 6152E-07	-2 1157E-07	-1 0338E-07	-3 2300E-07		
	VEL Y	5 5634E-06	5 5166E-06	5 6445E-06	5 5341E-06	5 6493E-06	5 4421E-06	5 6118E-06		
24	VEL X	-3 5032E-07	-2 4269E-07	-1 6958E-07	-3 2890E-07	-2 1987E-07	-1 5145E-07	-2 9810E-07	-1 8688E-07	-1 2514E-07
	VEL Y	5 3559E-06	5 3340E-06	5 3064E-06	5 4524E-06	5 3972E-06	5 3423E-06	5 5336E-06	5 4472E-06	5 3669E-06
25	VEL X	-4 4731E-08	-8 6889E-08	9 2467E-09	-6 6201E-08	1 2843E-08	-1 5981E-07	-1 6038E-08		
	VEL Y	5 6240E-06	5 7122E-06	5 5889E-06	5 5777E-06	5 4911E-06	5 6923E-06	5 7081E-06		
26	VEL X	-2 4184E-07	-2 0223E-07	-1 7863E-07	-2 8323E-07	-2 2305E-07	-1 8074E-07	-3 3626E-07	-2 4979E-07	-1 8346E-07
	VEL Y	5 0760E-06	5 1235E-06	5 1526E-06	5 1585E-06	5 1804E-06	5 1886E-06	5 2489E-06	5 2448E-06	5 2319E-06
27	VEL X	-4 5524E-08	-8 0289E-08	-1 0527E-07	-1 0922E-07	-1 2590E-07	-1 3192E-07	-1 8604E-07	-1 8098E-07	-1 6414E-07
	VEL Y	4 9434E-06	4 9830E-06	5 0069E-06	4 9445E-06	4 9921E-06	5 0222E-06	4 9677E-06	5 0207E-06	5 0547E-06
28	VEL X	8 0492E-08	4 5367E-08	1 4210E-08	4 8352E-08	1 2286E-08	-1 9058E-08	7 6637E-10	-3 6691E-08	-6 8307E-08
	VEL Y	4 9130E-06	4 9143E-06	4 9109E-06	4 8575E-06	4 8762E-06	4 8856E-06	4 8217E-06	4 8541E-06	4 8731E-06
29	VEL X	5 6653E-08	4 4897E-08	3 2191E-08	6 6060E-08	4 8414E-08	2 9686E-08	7 8261E-08	5 2979E-08	2 6441E-08
	VEL Y	4 8382E-06	4 8326E-06	4 8262E-06	4 8102E-06	4 8047E-06	4 7976E-06	4 7740E-06	4 7693E-06	4 7619E-06
30	VEL X	8 1071E-09	7 4845E-09	6 4934E-09	2 3493E-08	1 8954E-08	1 4009E-08	4 2183E-08	3 2887E-08	2 3137E-08
	VEL Y	4 7666E-06	4 7613E-06	4 7560E-06	4 7614E-06	4 7550E-06	4 7486E-06	4 7445E-06	4 7386E-06	4 7323E-06
31	VEL X	-5 3513E-07	-3 3758E-07	-2 0603E-07	-3 3863E-07	-2 0075E-07	-1 1244E-07	-1 6365E-07	-8 4832E-08	-3 6844E-08
	VEL Y	6 4256E-06	6 0690E-06	5 7763E-06	6 5101E-06	6 1223E-06	5 8071E-06	6 5804E-06	6 1653E-06	5 8304E-06
32	VEL X	-1 0226E-06	-5 7169E-07	-3 3638E-07	-9 4531E-07	-5 0554E-07	-2 7610E-07	-8 5551E-07	-4 4427E-07	-2 3172E-07
	VEL Y	5 9923E-06	5 8393E-06	5 7015E-06	6 1521E-06	5 9233E-06	5 7252E-06	6 3331E-06	6 0187E-06	5 7546E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 30 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
33	VEL X	-9 1980E-07	-6 3178E-07	-4 3966E-07	-9 6667E-07	-6 3905E-07	-4 2286E-07	-1 0339E-06	-6 4964E-07	-3 9879E-07
	VEL Y	5 1521E-06	5 2988E-06	5 3972E-06	5 4972E-06	5 5189E-06	5 5196E-06	5 8218E-06	5 7233E-06	5 6297E-06
34	VEL X	-1 6937E-07	-2 2695E-07	-2 5875E-07	-3 9401E-07	-3 7696E-07	-3 3093E-07	-6 8005E-07	-5 6848E-07	-4 2336E-07
	VEL Y	4 8006E-06	4 9416E-06	5 0382E-06	4 8118E-06	4 9776E-06	5 0927E-06	4 9117E-06	5 0904E-06	5 2146E-06
35	VEL X	1 1916E-07	3 9078E-08	-2 0611E-08	2 7837E-08	-4 4004E-08	-9 3810E-08	-8 1839E-08	-1 4396E-07	-1 8201E-07
	VEL Y	4 8572E-06	4 8980E-06	4 9213E-06	4 7724E-06	4 8545E-06	4 9083E-06	4 7134E-06	4 8320E-06	4 9123E-06
36	VEL X	1 6738E-07	1 3503E-07	1 0209E-07	1 6419E-07	1 1935E-07	7 3755E-08	1 5944E-07	9 6141E-08	3 1823E-08
	VEL Y	4 9434E-06	4 9364E-06	4 9278E-06	4 8557E-06	4 8631E-06	4 8640E-06	4 7532E-06	4 7757E-06	4 7861E-06
37	VEL X	8 3891E-08	7 4833E-08	6 3771E-08	1 1007E-07	9 4624E-08	7 6907E-08	1 4399E-07	1 2028E-07	9 3944E-08
	VEL Y	4 8639E-06	4 8569E-06	4 8504E-06	4 8337E-06	4 8232E-06	4 8134E-06	4 7856E-06	4 7746E-06	4 7637E-06
38	VEL X	9 8114E-09	9 4271E-09	8 5749E-09	3 3877E-08	3 0245E-08	2 6098E-08	6 3093E-08	5 5525E-08	4 7382E-08
	VEL Y	4 7822E-06	4 7767E-06	4 7720E-06	4 7772E-06	4 7700E-06	4 7637E-06	4 7581E-06	4 7520E-06	4 7464E-06
39	VEL X	-2 3560E-06	-1 5374E-06	-7 8931E-07	-1 0434E-06	-7 6012E-07	-4 7915E-07	2 0238E-07	-3 6669E-08	-1 8135E-07
	VEL Y	8 4358E-06	7 4128E-06	6 6865E-06	8 7614E-06	7 6787E-06	6 9193E-06	8 7603E-06	7 7068E-06	6 9698E-06
40	VEL X	-4 1459E-06	-2 4968E-06	-1 4556E-06	-3 6534E-06	-2 0289E-06	-1 2308E-06	-2 7925E-06	-1 4108E-06	-9 5549E-07
	VEL Y	5 6251E-06	6 0633E-06	6 3335E-06	6 8507E-06	6 7039E-06	6 5479E-06	7 9917E-06	7 2017E-06	6 5998E-06
41	VEL X	-1 0077E-06	-1 0635E-06	-1 0671E-06	-2 1440E-06	-1 7400E-06	-1 2708E-06	-3 7395E-06	-2 6947E-06	-1 5596E-06
	VEL Y	3 8457E-06	4 5028E-06	4 9418E-06	4 0796E-06	4 7609E-06	5 2169E-06	4 8554E-06	5 4716E-06	5 8816E-06
42	VEL X	1 8855E-07	-1 8020E-08	-1 3428E-07	-1 3995E-07	-3 1817E-07	-3 9739E-07	-5 5494E-07	-6 9877E-07	-7 3201E-07
	VEL Y	4 4872E-06	4 6210E-06	4 7020E-06	4 1060E-06	4 4627E-06	4 6961E-06	3 8215E-06	4 3785E-06	4 7490E-06
43	VEL X	3 2059E-07	2 5006E-07	1 7186E-07	2 8645E-07	1 9024E-07	8 5380E-08	2 4531E-07	1 1837E-07	-1 8522E-08
	VEL Y	4 8336E-06	4 8479E-06	4 8523E-06	4 6985E-06	4 7300E-06	4 7443E-06	4 5252E-06	4 5796E-06	4 6076E-06
44	VEL X	2 3076E-07	2 1068E-07	1 8573E-07	2 7058E-07	2 3393E-07	1 9143E-07	3 2921E-07	2 6819E-07	1 9979E-07
	VEL Y	4 9802E-06	4 9690E-06	4 9596E-06	4 8883E-06	4 8784E-06	4 8688E-06	4 7327E-06	4 7366E-06	4 7350E-06
45	VEL X	1 0214E-07	9 6623E-08	8 8961E-08	1 4192E-07	1 3146E-07	1 1857E-07	1 9339E-07	1 7657E-07	1 5694E-07
	VEL Y	4 8844E-06	4 8783E-06	4 8736E-06	4 8563E-06	4 8446E-06	4 8358E-06	4 8024E-06	4 7920E-06	4 7837E-06
46	VEL X	1 0882E-08	1 0736E-08	1 0115E-08	4 0928E-08	3 8618E-08	3 5790E-08	7 7366E-08	7 2454E-08	6 6959E-08
	VEL Y	4 7939E-06	4 7899E-06	4 7870E-06	4 7906E-06	4 7836E-06	4 7787E-06	4 7711E-06	4 7665E-06	4 7630E-06
47	VEL X	-5 4731E-05	-5 6736E-05	-5 8898E-05	-3 0929E-05	-3 2881E-05	-3 4688E-05	-9 2122E-06	-1 0332E-05	-1 1043E-05
	VEL Y	1 3335E-05	5 2139E-06	-1 4461E-06	2 6604E-05	1 8401E-05	1 1395E-05	2 9950E-05	2 2557E-05	1 6063E-05
48	VEL X	-7 9924E-05	-8 4222E-05	-8 8813E-05	-7 6458E-05	-8 1015E-05	-8 5702E-05	-6 3238E-05	-6 7293E-05	-7 1307E-05
	VEL Y	-4 1154E-05	-5 3441E-05	-6 3716E-05	-1 6905E-05	-2 6979E-05	-3 5156E-05	2 8481E-06	-5 7413E-06	-1 2647E-05

LISTING D-6. Output Report File for Test Case Two. (Sheet 31 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
49	VEL X	-7 8294E-08	-5 3398E-07	-9 0414E-07	-8 8271E-07	-1 5809E-06	-2 1457E-06	-2 0666E-06	-3 0870E-06	-3 8976E-06
	VEL Y	3 2753E-06	3 4097E-06	3 6637E-06	2 3082E-06	2 7683E-06	3 4626E-06	1 1785E-06	2 1721E-06	3 5268E-06
50	VEL X	-5 9961E-05	-7 7241E-05	-8 7454E-05	-5 8643E-05	-7 3644E-05	-8 2370E-05	-5 7321E-05	-7 0237E-05	-7 7821E-05
	VEL Y	-1 3788E-04	-1 1302E-04	-8 2375E-05	-1 2075E-04	-9 9027E-05	-7 0209E-05	-1 0175E-04	-8 3278E-05	-5 6350E-05
51	VEL X	4 8985E-07	3 8473E-07	2 9180E-07	3 4222E-07	1 4801E-07	-2 3223E-08	1 4543E-07	-1 5981E-07	-4 2522E-07
	VEL Y	4 4846E-06	4 4671E-06	4 4581E-06	4 1276E-06	4 1199E-06	4 1454E-06	3 5706E-06	3 6016E-06	3 7055E-06
52	VEL X	3 5679E-07	3 6556E-07	3 2257E-07	3 8473E-07	3 5045E-07	4 2325E-07	3 0039E-07		
	VEL Y	4 5982E-06	4 4388E-06	4 7247E-06	4 6454E-06	4 8797E-06	4 4604E-06	4 4769E-06		
53	VEL X	4 5705E-07	4 0094E-07	4 5878E-07	5 1859E-07	5 5718E-07	4 7807E-07	3 5585E-07		
	VEL Y	4 7788E-06	4 6545E-06	4 8720E-06	4 7873E-06	4 8910E-06	4 6328E-06	4 7903E-06		
54	VEL X	2 8851E-07	2 5641E-07	2 3860E-07	3 7602E-07	3 2361E-07	2 8796E-07	5 0557E-07	4 2309E-07	3 6067E-07
	VEL Y	5 0225E-06	5 0080E-06	4 9779E-06	4 9216E-06	4 9180E-06	4 9111E-06	4 7881E-06	4 7739E-06	4 7442E-06
55	VEL X	1 1858E-07	1 0998E-07	1 0445E-07	1 7218E-07	1 5798E-07	1 4713E-07	2 4168E-07	2 2020E-07	2 0237E-07
	VEL Y	4 9051E-06	4 8987E-06	4 8860E-06	4 8759E-06	4 8694E-06	4 8562E-06	4 8378E-06	4 8219E-06	4 7891E-06
56	VEL X	1 1609E-08	1 0785E-08	1 0713E-08	4 7666E-08	4 4455E-08	4 2058E-08	9 1457E-08	8 5344E-08	8 0080E-08
	VEL Y	4 8078E-06	4 8028E-06	4 7935E-06	4 8003E-06	4 7974E-06	4 7921E-06	4 7884E-06	4 7825E-06	4 7711E-06
57	VEL X	-4 6336E-05	-4 9931E-05	-5 3675E-05	-2 4612E-05	-2 7318E-05	-2 9855E-05	-6 6003E-06	-7 8991E-06	-8 7365E-06
	VEL Y	3 2717E-05	2 4091E-05	1 7444E-05	4 4740E-05	3 6581E-05	2 9938E-05	4 6872E-05	4 0382E-05	3 4917E-05
58	VEL X	-6 3635E-05	-7 0358E-05	-7 7254E-05	-6 0458E-05	-6 7499E-05	-7 4492E-05	-4 8681E-05	-5 5149E-05	-6 1382E-05
	VEL Y	-8 2392E-06	-2 3043E-05	-3 5170E-05	1 0341E-05	-1 5736E-06	-1 0934E-05	2 5145E-05	1 5514E-05	8 1977E-06
59	VEL X	-5 3720E-05	-6 8889E-05	-7 5078E-05	-5 0430E-05	-6 2705E-05	-6 7300E-05	-4 7076E-05	-5 6642E-05	-6 0086E-05
	VEL Y	-9 2981E-05	-7 4620E-05	-4 9027E-05	-7 2855E-05	-5 7682E-05	-3 4367E-05	-4 9990E-05	-3 8226E-05	-1 7468E-05
60	VEL X	1 3096E-06	7 4554E-07	2 1522E-07	1 3985E-06	4 5617E-07	-4 1687E-07	1 5265E-06	1 0744E-08	-1 3622E-06
	VEL Y	3 1187E-06	3 0940E-06	3 1862E-06	2 0119E-06	1 9588E-06	2 1363E-06	4 2998E-07	3 8880E-07	7 8112E-07
61	VEL X	-2 5433E-06	-2 1942E-05	-4 6063E-05	-2 5337E-06	-2 1743E-05	-4 5953E-05	-2 5305E-06	-2 1598E-05	-4 6014E-05
	VEL Y	-1 7946E-04	-1 6787E-04	-1 4529E-04	-1 5811E-04	-1 4902E-04	-1 2915E-04	-1 3585E-04	-1 2924E-04	-1 1215E-04
62	VEL X	8 6459E-07	6 9446E-07	5 5592E-07	9 9860E-07	7 1092E-07	4 6495E-07	1 1715E-06	7 2713E-07	3 4047E-07
	VEL Y	4 5361E-06	4 4992E-06	4 4690E-06	4 1036E-06	4 0824E-06	4 0962E-06	3 4528E-06	3 4402E-06	3 5050E-06
63	VEL X	-4 6043E-06	-2 5782E-05	-4 4325E-05	-4 3890E-06	-2 4609E-05	-4 2308E-05	-4 1816E-06	-2 3483E-05	-4 0410E-05
	VEL Y	-1 2459E-04	-1 1817E-04	-1 0301E-04	-1 0199E-04	-9 5781E-05	-8 1547E-05	-7 8206E-05	-7 1970E-05	-5 8444E-05
64	VEL X	6 6085E-07	5 8524E-07	6 9814E-07	7 0805E-07	8 0356E-07	6 0600E-07	5 9894E-07		
	VEL Y	4 6555E-06	4 7359E-06	4 7497E-06	4 4798E-06	4 5410E-06	4 4734E-06	4 9449E-06		

D-68

RHO-BW-CR-143 P

LISTING D-6. Output Report File for Test Case Two. (Sheet 32 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
65	VEL X	8 3943E-07	8 3140E-07	9 6396E-07	7 3048E-07	8 6059E-07	6 5211E-07	1 0252E-06		
	VEL Y	4 7306E-06	4 8438E-06	4 6251E-06	4 7522E-06	4 5776E-06	4 9692E-06	4 7245E-06		
66	VEL X	8 2596E-07	9 3710E-07	8 5483E-07	6 8031E-07	6 3570E-07	7 6752E-07	1 0558E-06		
	VEL Y	4 9581E-06	4 9266E-06	4 9363E-06	5 0143E-06	4 9778E-06	5 0651E-06	4 8750E-06		
67	VEL X	6 7747E-07	4 8567E-07	3 5628E-07	6 2919E-07	4 5789E-07	3 4216E-07	5 5820E-07	4 1140E-07	3 1222E-07
	VEL Y	4 9823E-06	5 0714E-06	5 0881E-06	4 8893E-06	4 9948E-06	5 0619E-06	4 8491E-06	4 9604E-06	5 0499E-06
68	VEL X	2 8956E-07	2 0350E-07	1 3719E-07	2 7440E-07	1 9436E-07	1 3262E-07	2 5504E-07	1 8142E-07	1 2462E-07
	VEL Y	4 8771E-06	4 9213E-06	4 9351E-06	4 8656E-06	4 9013E-06	4 9229E-06	4 8603E-06	4 8916E-06	4 9168E-06
69	VEL X	1 0533E-07	5 4757E-08	1 3146E-08	1 0077E-07	5 2745E-08	1 3201E-08	9 5204E-08	4 9789E-08	1 2390E-08
	VEL Y	4 8128E-06	4 8264E-06	4 8237E-06	4 8032E-06	4 8143E-06	4 8180E-06	4 7983E-06	4 8080E-06	4 8149E-06
70	VEL X	-2 0096E-04	-2 5182E-04	-3 2907E-04	-1 0800E-04	-1 4328E-04	-1 7555E-04	-3 2953E-05	-5 7523E-05	-6 2370E-05
	VEL Y	1 8957E-04	1 2618E-04	4 9690E-05	3 4779E-04	2 5893E-04	1 0479E-04	4 0258E-04	3 3556E-04	1 5937E-04
71	VEL X	-3 0152E-04	-3 7246E-04	-4 0071E-04	-2 5887E-04	-3 2957E-04	-3 8430E-04	-2 3471E-04	-2 9818E-04	-3 3375E-04
	VEL Y	-4 1706E-04	-3 8334E-04	-2 7989E-04	-1 6186E-04	-1 8341E-04	-1 4861E-04	6 5868E-05	2 0559E-05	-1 8788E-05
72	VEL X	-2 4256E-05	-1 1277E-04	-2 2253E-04	-2 5308E-05	-1 0953E-04	-1 9657E-04	-2 7386E-05	-1 1108E-04	-1 8474E-04
	VEL Y	-5 7813E-04	-5 4589E-04	-4 7998E-04	-1 5401E-04	-1 5578E-04	-1 7714E-04	1 5517E-04	1 5438E-04	8 9323E-05
73	VEL X	5 4685E-06	3 7612E-06	2 6125E-06	4 0966E-06	2 9349E-06	2 1653E-06	2 4844E-06	1 9774E-06	1 6416E-06
	VEL Y	1 9772E-06	3 0872E-06	3 8872E-06	9 1304E-07	2 4502E-06	3 4896E-06	3 5998E-07	2 0985E-06	3 2441E-06
74	VEL X	5 0026E-05	5 0079E-05	5 0302E-05	2 5679E-05	2 5941E-05	2 6257E-05	6 1669E-06	6 3095E-06	6 4591E-06
	VEL Y	-1 1097E-04	-1 2801E-04	-1 4420E-04	-1 2856E-04	-1 4828E-04	-1 6706E-04	-1 3560E-04	-1 5770E-04	-1 7890E-04
75	VEL X	2 2011E-06	1 6612E-06	1 2481E-06	1 8572E-06	1 4429E-06	1 1275E-06	1 4422E-06	1 1753E-06	9 7124E-07
	VEL Y	4 0636E-06	4 5179E-06	4 8021E-06	3 7532E-06	4 3171E-06	4 6808E-06	3 5568E-06	4 1853E-06	4 5978E-06
76	VEL X	4 4318E-05	4 6225E-05	4 8257E-05	2 7192E-05	2 8397E-05	2 9653E-05	7 5483E-06	7 9132E-06	8 2864E-06
	VEL Y	-5 7357E-05	-8 0403E-05	-1 0183E-04	-7 1500E-05	-9 5223E-05	-1 1755E-04	-7 8167E-05	-1 0187E-04	-1 2440E-04
77	VEL X	1 8694E-04	1 9941E-04	2 2614E-04	1 1315E-04	1 1223E-04	1 1615E-04	2 9309E-05	2 7882E-05	2 7491E-05
	VEL Y	8 9256E-05	-1 7701E-04	-4 7951E-04	1 5431E-04	-1 5572E-04	-5 4564E-04	1 5513E-04	-1 5397E-04	-5 7799E-04
78	VEL X	1 0976E-06	1 2584E-06	9 9384E-07	1 0501E-06	8 5392E-07	1 2976E-06	1 1703E-06		
	VEL Y	4 9783E-06	4 8465E-06	4 9679E-06	5 1090E-06	5 1231E-06	4 9763E-06	4 8003E-06		
79	VEL X	2 8186E-06	2 0527E-06	1 4503E-06	2 6040E-06	1 9139E-06	1 3772E-06	2 3595E-06	1 7602E-06	1 2991E-06
	VEL Y	4 7913E-06	4 9159E-06	5 0209E-06	4 5000E-06	4 7536E-06	4 9210E-06	4 3160E-06	4 6570E-06	4 8612E-06
80	VEL X	1 3712E-06	1 1086E-06	8 9016E-07	1 3472E-06	1 0828E-06	8 6243E-07	1 3099E-06	1 0445E-06	8 2299E-07
	VEL Y	5 3650E-06	5 3357E-06	5 3162E-06	5 2402E-06	5 2364E-06	5 2456E-06	5 0466E-06	5 0821E-06	5 1350E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 33 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
81	VEL X	7 6280E-07	5 4065E-07	3 9060E-07	7 2954E-07	5 1856E-07	3 7608E-07	6 9587E-07	4 9604E-07	3 6113E-07
	VEL Y	5 1130E-06	5 1328E-06	5 1423E-06	5 0594E-06	5 0976E-06	5 1231E-06	4 9752E-06	5 0418E-06	5 0924E-06
82	VEL X	3 2048E-07	2 2312E-07	1 4803E-07	3 0762E-07	2 1463E-07	1 4293E-07	2 9604E-07	2 0724E-07	1 3879E-07
	VEL Y	4 9294E-06	4 9450E-06	4 9557E-06	4 9167E-06	4 9361E-06	4 9476E-06	4 8962E-06	4 9215E-06	4 9347E-06
83	VEL X	1 1479E-07	5 9134E-08	1 3312E-08	1 1099E-07	5 7270E-08	1 3045E-08	1 0742E-07	5 5599E-08	1 2954E-08
	VEL Y	4 8326E-06	4 8364E-06	4 8375E-06	4 8256E-06	4 8319E-06	4 8330E-06	4 8144E-06	4 8246E-06	4 8258E-06
84	VEL X	-1 8110E-05	-8 3466E-05	-1 6000E-04	-1 1347E-05	-4 7162E-05	-8 3527E-05	-4 9314E-06	-1 4140E-05	-1 7952E-05
	VEL Y	2 9402E-04	2 9749E-04	2 1610E-04	4 6250E-04	4 6898E-04	3 7078E-04	5 3041E-04	5 5425E-04	4 5726E-04
85	VEL X	1 8196E-05	8 4518E-05	1 6183E-04	1 4355E-05	4 8074E-05	8 5117E-05	5 1345E-06	1 2207E-05	1 9635E-05
	VEL Y	4 5686E-04	3 7043E-04	2 1591E-04	5 5400E-04	4 6875E-04	2 9734E-04	5 3031E-04	4 6239E-04	2 9393E-04
86	VEL X	7 3727E-06	5 1749E-06	3 6150E-06	6 8558E-06	4 7697E-06	3 3124E-06	6 0939E-06	4 1856E-06	2 8768E-06
	VEL Y	6 2720E-06	5 3812E-06	5 0355E-06	4 3186E-06	4 2446E-06	4 5087E-06	2 6947E-06	3 3567E-06	4 1288E-06
87	VEL X	8 1188E-05	8 5823E-05	9 0997E-05	7 3966E-05	7 7453E-05	8 1135E-05	6 1172E-05	6 2580E-05	6 3988E-05
	VEL Y	-5 3458E-05	-6 7262E-05	-7 9372E-05	-8 0979E-05	-9 6654E-05	-1 1057E-04	-1 0014E-04	-1 1907E-04	-1 3612E-04
88	VEL X	6 3078E-05	7 0431E-05	7 8333E-05	6 0305E-05	6 6420E-05	7 2651E-05	5 0991E-05	5 4343E-05	5 7630E-05
	VEL Y	-1 4586E-05	-3 1525E-05	-4 6201E-05	-3 5944E-05	-5 5391E-05	-7 2309E-05	-4 8496E-05	-7 1308E-05	-9 1376E-05
89	VEL X	3 3628E-04	3 8716E-04	4 0378E-04	3 0062E-04	3 3251E-04	3 7608E-04	2 3700E-04	2 6176E-04	3 0517E-04
	VEL Y	-1 8028E-05	-1 4789E-04	-2 7950E-04	2 0896E-05	-1 8297E-04	-3 8275E-04	6 5860E-05	-1 6167E-04	-4 1666E-04
90	VEL X	6 2858E-05	1 7681E-04	3 3139E-04	5 7928E-05	1 4442E-04	2 5388E-04	3 3250E-05	1 0904E-04	2 0286E-04
	VEL Y	1 5961E-04	1 0515E-04	5 0348E-05	3 3546E-04	2 5895E-04	1 2639E-04	4 0216E-04	3 4751E-04	1 8944E-04
91	VEL X	2 4138E-06	1 9570E-06	1 5980E-06	2 7185E-06	2 1081E-06	1 6268E-06	2 8514E-06	2 1071E-06	1 5182E-06
	VEL Y	6 2911E-06	5 8781E-06	5 6069E-06	5 7615E-06	5 5016E-06	5 4123E-06	4 9785E-06	4 9403E-06	5 1154E-06
92	VEL X	3 0331E-06	2 8910E-06	2 7907E-06	4 9102E-06	3 8698E-06	3 1329E-06	6 8035E-06	4 8783E-06	3 5084E-06
	VEL Y	8 4703E-06	7 3676E-06	6 7445E-06	8 2654E-06	6 9478E-06	6 1830E-06	7 9386E-06	6 3179E-06	5 3520E-06
93	VEL X	1 1305E-06	9 9048E-07	8 7435E-07	1 2567E-06	1 0624E-06	9 0099E-07	1 3434E-06	1 0985E-06	8 9471E-07
	VEL Y	5 9012E-06	5 7299E-06	5 6079E-06	5 7523E-06	5 6055E-06	5 5155E-06	5 5458E-06	5 4326E-06	5 3859E-06
94	VEL X	7 6894E-07	5 6430E-07	4 2606E-07	7 7500E-07	5 6062E-07	4 1579E-07	7 7136E-07	5 4908E-07	3 9891E-07
	VEL Y	5 3630E-06	5 2827E-06	5 2321E-06	5 2886E-06	5 2268E-06	5 1998E-06	5 1838E-06	5 1484E-06	5 1540E-06
95	VEL X	1 3129E-06	1 2628E-06	1 2238E-06	1 7274E-06	1 5227E-06	1 3625E-06	2 1320E-06	1 7754E-06	1 4955E-06
	VEL Y	6 6909E-06	6 3780E-06	6 1527E-06	6 5976E-06	6 2491E-06	5 9993E-06	6 4586E-06	6 0658E-06	5 7857E-06
96	VEL X	3 4707E-07	2 4195E-07	1 6086E-07	3 3720E-07	2 3495E-07	1 5609E-07	3 2686E-07	2 2755E-07	1 5095E-07
	VEL Y	5 0108E-06	4 9990E-06	4 9905E-06	4 9888E-06	4 9815E-06	4 9773E-06	4 9571E-06	4 9566E-06	4 9587E-06

D-70

RHO-BW-CR-143 P

LISTING D-6. Output Report File for Test Case Two. (Sheet 34 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
97	VEL X	1 2469E-07	6 3828E-08	1 3713E-08	1 2090E-07	6 2084E-08	1 3652E-08	1 1698E-07	6 0217E-08	1 3478E-08
	VEL Y	4 8654E-06	4 8620E-06	4 8587E-06	4 8546E-06	4 8535E-06	4 8514E-06	4 8393E-06	4 8415E-06	4 8412E-06
98	VEL X	1 7899E-06	2 3068E-06	2 7960E-06	2 4524E-06	3 4978E-06	4 4006E-06	4 3294E-06	5 8186E-06	6 8963E-06
	VEL Y	9 5038E-06	9 4277E-06	9 1383E-06	1 0601E-05	9 9753E-06	9 1585E-06	1 2102E-05	1 0675E-05	9 1265E-06
99	VEL X	7 3275E-05	8 8379E-05	9 2051E-05	6 9194E-05	8 3625E-05	8 7411E-05	6 5069E-05	7 8999E-05	8 3065E-05
	VEL Y	-8 7910E-06	-3 1455E-05	-6 0398E-05	-1 9785E-06	-2 3367E-05	-5 0219E-05	6 5210E-06	-1 3378E-05	-3 8024E-05
100	VEL X	6 3214E-05	7 7049E-05	8 0333E-05	5 6932E-05	7 0043E-05	7 3460E-05	5 0419E-05	6 3002E-05	6 6785E-05
	VEL Y	1 1929E-05	-7 3838E-06	-3 2161E-05	1 9244E-05	1 9248E-06	-2 0163E-05	2 8875E-05	1 3782E-05	-5 5053E-06
101	VEL X	8 9590E-06	3 0592E-05	5 5051E-05	8 0575E-06	2 7992E-05	5 1282E-05	6 6727E-06	2 5199E-05	4 7638E-05
	VEL Y	3 8468E-05	3 3675E-05	2 1218E-05	4 3773E-05	4 0235E-05	2 7848E-05	5 0104E-05	4 8313E-05	3 6463E-05
102	VEL X	9 8054E-07	1 1458E-06	1 2609E-06	1 4413E-06	1 6123E-06	1 7321E-06	2 1525E-06	2 2873E-06	2 3826E-06
	VEL Y	7 4911E-06	7 2816E-06	7 0128E-06	7 8214E-06	7 4378E-06	6 9855E-06	8 2190E-06	7 6150E-06	6 9295E-06
103	VEL X	5 7862E-07	6 9415E-07	8 5413E-07	9 4646E-07	1 1070E-06	1 3021E-06	1 5806E-06	1 8177E-06	2 0730E-06
	VEL Y	7 7026E-06	7 6451E-06	7 5997E-06	8 2615E-06	8 1222E-06	8 0017E-06	8 9541E-06	8 7061E-06	8 4889E-06
104	VEL X	7 2518E-07	7 0393E-07	6 8636E-07	8 7572E-07	8 1053E-07	7 5656E-07	1 0245E-06	9 1577E-07	8 2563E-07
	VEL Y	6 0675E-06	5 9324E-06	5 8223E-06	6 0301E-06	5 8800E-06	5 7578E-06	5 9730E-06	5 8055E-06	5 6692E-06
105	VEL X	6 4103E-07	5 1046E-07	4 2226E-07	7 0035E-07	5 3807E-07	4 2846E-07	7 4672E-07	5 5526E-07	4 2594E-07
	VEL Y	5 5891E-06	5 4439E-06	5 3444E-06	5 5249E-06	5 3885E-06	5 3041E-06	5 4377E-06	5 3142E-06	5 2499E-06
106	VEL X	6 1292E-07	6 7063E-07	7 1554E-07	8 1258E-07	8 4761E-07	8 7495E-07	1 0727E-06	1 0780E-06	1 0823E-06
	VEL Y	6 4814E-06	6 3634E-06	6 2402E-06	6 5764E-06	6 4031E-06	6 2237E-06	6 6791E-06	6 4390E-06	6 1916E-06
107	VEL X	3 4565E-07	2 4439E-07	1 6629E-07	3 4891E-07	2 4554E-07	1 6581E-07	3 4889E-07	2 4383E-07	1 6279E-07
	VEL Y	5 1226E-06	5 0732E-06	5 0374E-06	5 0906E-06	5 0475E-06	5 0195E-06	5 0475E-06	5 0131E-06	4 9957E-06
108	VEL X	3 7389E-07	4 7814E-07	5 4995E-07	5 2056E-07	6 5669E-07	7 5085E-07	7 7176E-07	9 2088E-07	1 0245E-06
	VEL Y	6 7490E-06	6 6924E-06	6 6055E-06	6 9854E-06	6 8767E-06	6 7342E-06	7 2586E-06	7 0872E-06	6 8775E-06
109	VEL X	1 2858E-07	6 5413E-08	1 3397E-08	1 2765E-07	6 5251E-08	1 3867E-08	1 2607E-07	6 4501E-08	1 3801E-08
	VEL Y	4 9126E-06	4 8976E-06	4 8882E-06	4 8982E-06	4 8852E-06	4 8780E-06	4 8790E-06	4 8688E-06	4 8646E-06
110	VEL X	3 0526E-07	8 6718E-07	1 4746E-06	1 1925E-07	1 2511E-06	2 4899E-06	-2 7653E-07	1 5771E-06	3 5731E-06
	VEL Y	1 0035E-05	9 9436E-06	9 6223E-06	1 1196E-05	1 1181E-05	1 0860E-05	1 2884E-05	1 2977E-05	1 2637E-05
111	VEL X	1 1649E-05	3 5609E-05	6 0157E-05	1 0782E-05	3 3739E-05	5 8050E-05	9 4976E-06	3 1718E-05	5 6103E-05
	VEL Y	1 9850E-05	1 5592E-05	2 6474E-06	2 6203E-05	2 2478E-05	9 1892E-06	3 3456E-05	3 0562E-05	1 7193E-05
112	VEL X	9 3925E-08	2 7939E-07	5 1142E-07	1 6342E-07	4 2406E-07	7 3703E-07	2 6649E-07	6 4258E-07	1 0748E-06
	VEL Y	7 8287E-06	7 7906E-06	7 7400E-06	8 4838E-06	8 4197E-06	8 3368E-06	9 3155E-06	9 2146E-06	9 0854E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 35 of 48)

SAMPLE PROBLEM. FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
113	VEL X	5 4956E-07	5 4127E-07	4 4406E-07	6 3970E-07	5 2019E-07	7 7677E-07	3 0687E-07		
	VEL Y	7 2150E-06	7 0967E-06	7 1231E-06	7 4405E-06	7 4229E-06	7 3817E-06	6 8812E-06		
114	VEL X	2 4256E-07	3 7068E-07	1 7678E-07	2 1280E-07	1 1479E-07	3 5415E-07	3 3622E-07		
	VEL Y	6 9417E-06	7 0071E-06	6 7516E-06	7 0730E-06	6 8365E-06	7 2873E-06	6 7165E-06		
115	VEL X	1 1230E-07	2 1892E-07	1 6292E-07	-9 0180E-09	3 3019E-09	4 9151E-08	3 8831E-07		
	VEL Y	7 3239E-06	7 5583E-06	7 2058E-06	7 2285E-06	6 9790E-06	7 5485E-06	7 5029E-06		
116	VEL X	3 7213E-07	3 9406E-07	4 1215E-07	4 7516E-07	4 8615E-07	4 9523E-07	6 1551E-07	6 1215E-07	6 0937E-07
	VEL Y	6 0116E-06	5 9477E-06	5 8828E-06	6 0422E-06	5 9504E-06	5 8573E-06	6 0770E-06	5 9559E-06	5 8331E-06
117	VEL X	4 1227E-07	3 6528E-07	3 3354E-07	4 9947E-07	4 2103E-07	3 6803E-07	5 8555E-07	4 7587E-07	4 0177E-07
	VEL Y	5 7113E-06	5 5732E-06	5 4581E-06	5 6763E-06	5 5323E-06	5 4120E-06	5 6420E-06	5 4911E-06	5 3648E-06
118	VEL X	2 6168E-07	3 0988E-07	3 4718E-07	3 4831E-07	4 0679E-07	4 5214E-07	4 9442E-07	5 5583E-07	6 0355E-07
	VEL Y	6 1873E-06	6 1496E-06	6 0988E-06	6 2972E-06	6 2290E-06	6 1470E-06	6 4146E-06	6 3147E-06	6 2002E-06
119	VEL X	2 8409E-07	2 0625E-07	1 4620E-07	3 1270E-07	2 2485E-07	1 5709E-07	3 3544E-07	2 3834E-07	1 6345E-07
	VEL Y	5 2561E-06	5 1662E-06	5 0975E-06	5 2122E-06	5 1309E-06	5 0721E-06	5 1669E-06	5 0944E-06	5 0459E-06
120	VEL X	1 4643E-07	1 9617E-07	2 3003E-07	1 9321E-07	2 6654E-07	3 1669E-07	2 9747E-07	3 8358E-07	4 4275E-07
	VEL Y	6 2730E-06	6 2596E-06	6 2337E-06	6 4346E-06	6 4030E-06	6 3583E-06	6 6054E-06	6 5551E-06	6 4911E-06
121	VEL X	1 1325E-07	5 7191E-08	1 1026E-08	1 2069E-07	6 1465E-08	1 2699E-08	1 2668E-07	6 4434E-08	1 3182E-08
	VEL Y	4 9791E-06	4 9458E-06	4 9273E-06	4 9579E-06	4 9274E-06	4 9127E-06	4 9360E-06	4 9083E-06	4 8975E-06
122	VEL X	1 4460E-07	1 9905E-07	2 8321E-07	7 0553E-08	9 7548E-08	1 4132E-07	3 5735E-08	5 1182E-08	7 8400E-08
	VEL Y	6 2894E-06	6 4586E-06	6 6375E-06	6 2996E-06	6 4760E-06	6 6626E-06	6 3067E-06	6 4900E-06	6 6837E-06
123	VEL X	1 7185E-07	1 8984E-07	2 0463E-07	2 3196E-07	2 5359E-07	2 7139E-07	3 1140E-07	3 3489E-07	3 5424E-07
	VEL Y	5 9314E-06	5 8918E-06	5 8446E-06	5 9629E-06	5 9089E-06	5 8470E-06	5 9969E-06	5 9281E-06	5 8510E-06
124	VEL X	2 0822E-07	1 9873E-07	1 9233E-07	2 8002E-07	2 5898E-07	2 4476E-07	3 5509E-07	3 2185E-07	2 9940E-07
	VEL Y	5 7370E-06	5 6235E-06	5 5038E-06	5 7324E-06	5 6094E-06	5 4799E-06	5 7289E-06	5 5959E-06	5 4558E-06
125	VEL X	1 1362E-07	1 3889E-07	1 5833E-07	1 5732E-07	1 9137E-07	2 1763E-07	2 1805E-07	2 5875E-07	2 9020E-07
	VEL Y	6 0305E-06	6 0084E-06	5 9779E-06	6 0874E-06	6 0562E-06	6 0163E-06	6 1479E-06	6 1074E-06	6 0577E-06
126	VEL X	1 6965E-07	1 2573E-07	9 1850E-08	2 1616E-07	1 5891E-07	1 1475E-07	2 5916E-07	1 8903E-07	1 3493E-07
	VEL Y	5 3431E-06	5 2283E-06	5 1348E-06	5 3175E-06	5 2062E-06	5 1171E-06	5 2915E-06	5 1836E-06	5 0989E-06
127	VEL X	6 2596E-08	8 5292E-08	1 0055E-07	8 6698E-08	1 1834E-07	1 3972E-07	1 2475E-07	1 6263E-07	1 8834E-07
	VEL Y	6 0745E-06	6 0664E-06	6 0531E-06	6 1447E-06	6 1321E-06	6 1141E-06	6 2191E-06	6 2018E-06	6 1789E-06
128	VEL X	7 2787E-08	3 6128E-08	5 9409E-09	8 9905E-08	4 5271E-08	8 5175E-09	1 0571E-07	5 3229E-08	1 0013E-08
	VEL Y	5 0342E-06	4 9822E-06	4 9560E-06	5 0186E-06	4 9687E-06	4 9457E-06	5 0025E-06	4 9548E-06	4 9351E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 36 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 5 000

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
129	VEL X	6 1853E-08	8 6799E-08	1 1832E-07	3 0498E-08	4 2476E-08	5 8040E-08	1 4656E-08	2 0686E-08	2 9219E-08
	VEL Y	6 0829E-06	6 1550E-06	6 2313E-06	6 0884E-06	6 1622E-06	6 2403E-06	6 0921E-06	6 1674E-06	6 2471E-06
130	VEL X	1 5672E-08	1 7591E-08	1 9164E-08	7 2499E-08	8 0832E-08	8 7673E-08	1 3404E-07	1 4840E-07	1 6021E-07
	VEL Y	5 9012E-06	5 8616E-06	5 8135E-06	5 9125E-06	5 8687E-06	5 8160E-06	5 9252E-06	5 8769E-06	5 8195E-06
131	VEL X	2 0645E-08	1 9958E-08	1 9494E-08	9 1568E-08	8 8525E-08	8 6470E-08	1 6246E-07	1 5706E-07	1 5342E-07
	VEL Y	5 7490E-06	5 6362E-06	5 5030E-06	5 7493E-06	5 6331E-06	5 4958E-06	5 7504E-06	5 6305E-06	5 4889E-06
132	VEL X	1 0311E-08	1 2856E-08	1 4804E-08	4 7701E-08	5 8754E-08	6 7233E-08	8 8104E-08	1 0731E-07	1 2207E-07
	VEL Y	5 9761E-06	5 9559E-06	5 9285E-06	5 9937E-06	5 9714E-06	5 9417E-06	6 0129E-06	5 9885E-06	5 9564E-06
133	VEL X	1 7961E-08	1 3435E-08	9 9446E-09	7 8306E-08	5 8406E-08	4 3057E-08	1 3652E-07	1 0152E-07	7 4526E-08
	VEL Y	5 3881E-06	5 2543E-06	5 1410E-06	5 3797E-06	5 2467E-06	5 1347E-06	5 3714E-06	5 2391E-06	5 1284E-06
134	VEL X	5 5107E-09	7 7891E-09	9 3011E-09	2 5965E-08	3 5814E-08	4 2383E-08	4 8947E-08	6 5834E-08	7 7152E-08
	VEL Y	6 0077E-06	6 0003E-06	5 9888E-06	6 0284E-06	6 0199E-06	6 0072E-06	6 0508E-06	6 0413E-06	6 0274E-06
135	VEL X	7 8295E-09	3 9637E-09	7 8046E-10	3 4193E-08	1 7106E-08	3 0360E-09	5 9735E-08	2 9507E-08	4 6153E-09
	VEL Y	5 0651E-06	4 9975E-06	4 9681E-06	5 0593E-06	4 9922E-06	4 9645E-06	5 0534E-06	4 9868E-06	4 9607E-06
136	VEL X	5 5247E-09	2 5567E-08	4 7104E-08	2 8297E-09	1 2905E-08	2 3470E-08	1 3725E-09	6 2333E-09	1 1342E-08
	VEL Y	6 0124E-06	6 0334E-06	6 0563E-06	6 0172E-06	6 0386E-06	6 0619E-06	6 0205E-06	6 0422E-06	6 0657E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 37 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 10 00

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
1	50 00	* 1 200 *	51	53 67	1 155	101	56 89	1 122
2	50 00	* 1 200 *	52	53 95	1 155	102	57 75	1 121
3	50 00	* 1 200 *	53	51 81	1 168	103	53 71	1 130
4	50 00	* 1 200 *	54	52 37	1 157	104	53 94	1 124
5	50 00	* 1 200 *	55	53 08	1 156	105	55 40	1 123
6	50 00	* 1 200 *	56	50 89	1 169	106	51 74	1 131
7	50 00	* 1 200 *	57	51 16	1 159	107	51 84	1 125
8	50 00	* 1 200 *	58	51 70	1 158	108	52 73	1 124
9	50 00	* 1 200 *	59	50 53	1 169	109	51 03	1 132
10	50 00	* 1 200 *	60	50 69	1 159	110	51 08	1 125
11	50 00	* 1 200 *	61	50 82	1 159	111	51 28	1 125
12	50 00	* 1 200 *	62	55 97	1 143	112	63 87	1 105
13	50 00	* 1 200 *	63	57 58	1 132	113	62 19	1 111
14	50 00	* 1 200 *	64	57 65	1 132	114	62 11	1 111
15	50 00	* 1 200 *	65	57 70	1 132	115	63 77	1 105
16	51 07	1 188	66	56 04	1 143	116	63 81	1 105
17	52 17	1 176	67	55 78	1 143	117	62 15	1 110
18	52 18	1 176	68	57 28	1 132	118	63 82	1 104
19	52 19	1 176	69	57 47	1 132	119	63 76	1 105
20	51 08	1 188	70	55 35	1 144	120	61 11	1 112
21	51 05	1 188	71	56 62	1 133	121	62 25	1 107
22	52 13	1 176	72	57 00	1 133	122	63 18	1 106
23	52 16	1 176	73	54 63	1 145	123	59 36	1 114
24	51 00	1 188	74	55 59	1 135	124	59 99	1 110
25	52 02	1 177	75	56 15	1 134	125	61 17	1 109
26	52 08	1 176	76	52 91	1 147	126	57 35	1 116
27	50 90	1 188	77	53 39	1 137	127	57 69	1 112
28	51 81	1 177	78	54 53	1 136	128	58 81	1 111
29	51 92	1 177	79	51 40	1 149	129	54 11	1 118
30	50 61	1 189	80	51 61	1 139	130	54 23	1 114
31	51 21	1 178	81	52 38	1 138	131	55 87	1 113
32	51 55	1 177	82	50 83	1 149	132	51 90	1 119
33	50 31	1 190	83	50 95	1 139	133	51 95	1 115
34	50 61	1 179	84	51 13	1 139	134	52 91	1 114
35	50 88	1 179	85	58 92	1 125	135	51 12	1 120
36	50 18	1 190	86	60 54	1 117	136	51 15	1 115
37	50 36	1 179	87	59 02	1 124	137	51 35	1 115
38	50 43	1 179	88	59 01	1 124	138	67 34	1 094
39	53 33	1 165	89	60 54	1 117	139	65 62	1 099
40	54 58	1 154	90	60 52	1 117	140	65 48	1 100
41	54 60	1 154	91	58 57	1 125	141	67 15	1 095
42	54 62	1 154	92	59 86	1 118	142	67 23	1 094
43	53 36	1 165	93	60 27	1 117	143	65 52	1 099
44	53 25	1 165	94	60 57	1 117	144	67 05	1 096
45	54 46	1 154	95	60 60	1 117	145	67 09	1 095
46	54 53	1 154	96	59 11	1 124	146	63 21	1 104
47	53 07	1 165	97	57 64	1 126	147	63 87	1 102
48	54 17	1 154	98	58 56	1 120	148	65 54	1 100
49	54 34	1 154	99	59 28	1 119	149	60 43	1 107
50	52 73	1 166	100	56 31	1 128	150	60 72	1 105

LISTING D-6. Output Report File for Test Case Two. (Sheet 38 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 10 00

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
151	62 25	1 104	201	68 51	1 096	251	67 61	1 102
152	57 90	1 109	202	69 08	1 097	252	68 07	1 102
153	58 03	1 106	203	69 03	1 096	253	68 18	1 101
154	59 30	1 106	204	69 09	1 098	254	62 24	1 098
155	54 30	1 110	205	69 03	1 097	255	68 56	1 102
156	54 34	1 107	206	68 56	1 098	256	69 09	1 102
157	56 06	1 107	207	67 36	1 100	257	69 21	1 101
158	51 97	1 111	208	67 26	1 099	258	69 76	1 102
159	51 99	1 108	209	63 89	1 101	259	70 31	1 103
160	52 97	1 108	210	63 95	1 100	260	70 71	1 101
161	51 16	1 111	211	65 67	1 100	261	59 30	1 095
162	51 17	1 108	212	68 30	1 100	262	60 72	1 095
163	51 38	1 108	213	68 18	1 099	263	60 71	1 096
164	68 28	1 095	214	67 82	1 100	264	62 25	1 096
165	67 80	1 095	215	60 78	1 102	265	63 87	1 098
166	67 59	1 095	216	60 81	1 100	266	63 82	1 098
167	68 05	1 095	217	62 32	1 100	267	57 90	1 091
168	68 16	1 095	218	67 30	1 100	268	57 69	1 088
169	67 50	1 096	219	69 21	1 099	269	58 81	1 089
170	67 98	1 096	220	68 79	1 100	270	59 99	1 090
171	67 98	1 096	221	59 42	1 100	271	60 43	1 093
172	67 17	1 098	222	59 34	1 098	272	54 30	1 090
173	67 11	1 097	223	60 73	1 097	273	54 23	1 086
174	63 82	1 102	224	60 78	1 099	274	55 87	1 087
175	63 84	1 101	225	58 11	1 096	275	51 97	1 089
176	65 52	1 100	226	58 03	1 094	276	51 95	1 086
177	68 07	1 098	227	59 23	1 096	277	52 91	1 086
178	67 99	1 097	228	54 37	1 096	278	51 16	1 089
179	67 61	1 098	229	54 34	1 093	279	51 15	1 085
180	60 71	1 104	230	56 06	1 093	280	51 35	1 085
181	60 73	1 103	231	52 00	1 095	281	71 41	1 100
182	62 24	1 102	232	51 99	1 092	282	71 29	1 099
183	59 23	1 105	233	52 97	1 093	283	71 29	1 100
184	58 17	1 100	234	51 18	1 095	284	70 71	1 103
185	59 34	1 102	235	51 17	1 092	285	70 88	1 102
186	58 11	1 104	236	51 38	1 092	286	71 29	1 101
187	54 37	1 105	237	70 88	1 098	287	65 54	1 101
188	54 39	1 100	238	70 22	1 097	288	67 05	1 104
189	56 14	1 100	239	69 75	1 097	289	67 11	1 103
190	52 00	1 105	240	70 31	1 098	290	67 50	1 104
191	52 01	1 100	241	70 71	1 098	291	67 98	1 104
192	53 00	1 100	242	69 76	1 098	292	67 99	1 103
193	51 18	1 105	243	70 89	1 100	293	68 51	1 104
194	51 18	1 100	244	70 71	1 099	294	69 08	1 104
195	51 39	1 100	245	70 23	1 100	295	69 03	1 103
196	69 29	1 095	246	63 89	1 100	296	69 03	1 104
197	68 77	1 095	247	63 84	1 099	297	69 08	1 105
198	68 55	1 095	248	65 52	1 100	298	69 75	1 104
199	69 08	1 096	249	67 17	1 102	299	69 20	1 105
200	69 20	1 095	250	67 26	1 101	300	69 29	1 105

LISTING D-6. Output Report File for Test Case Two. (Sheet 39 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS ON YEAR 10 00

NODE	T(C)	H(M)	NODE	T(C)	H(M)	NODE	T(C)	H(M)
301	70 22	1 104	350	54 53	1 064	399	54 60	1 046
302	61 17	1 091	351	57 00	1 067	400	52 73	1 034
303	62 25	1 093	352	57 28	1 068	401	51 81	1 023
304	63 21	1 096	353	58 57	1 076	402	51 92	1 023
305	63 18	1 095	354	51 74	1 069	403	52 02	1 023
306	63 82	1 096	355	51 61	1 061	404	53 07	1 035
307	65 52	1 101	356	52 38	1 062	405	51 81	1 033
308	57 35	1 084	357	57 47	1 068	406	51 21	1 022
309	56 89	1 079	358	57 58	1 068	407	51 55	1 023
310	57 75	1 080	359	59 01	1 076	408	52 08	1 024
311	58 56	1 081	360	51 03	1 068	409	52 13	1 024
312	59 36	1 086	361	50 95	1 061	410	53 25	1 035
313	54 11	1 082	362	51 13	1 061	411	50 89	1 031
314	53 94	1 076	363	67 34	1 106	412	50 61	1 021
315	55 40	1 077	364	67 23	1 106	413	50 88	1 021
316	59 28	1 082	365	63 81	1 095	414	52 16	1 024
317	59 86	1 082	366	63 87	1 096	415	52 17	1 024
318	61 11	1 088	367	65 62	1 101	416	53 33	1 035
319	51 90	1 081	368	67 80	1 106	417	50 53	1 031
320	51 84	1 075	369	60 57	1 083	418	50 36	1 021
321	52 73	1 076	370	60 60	1 083	419	50 43	1 021
322	51 12	1 080	371	62 19	1 090	420	52 19	1 024
323	51 08	1 075	372	58 92	1 076	421	53 36	1 035
324	51 28	1 075	373	57 70	1 068	422	52 18	1 024
325	67 15	1 106	374	59 02	1 076	423	50 90	1 012
326	67 09	1 105	375	57 65	1 068	424	50 00	* 1 000 *
327	63 76	1 096	376	59 11	1 076	425	50 00	* 1 000 *
328	63 77	1 095	377	54 63	1 055	426	50 00	* 1 000 *
329	65 48	1 101	378	53 67	1 045	427	51 00	1 012
330	68 05	1 105	379	53 95	1 045	428	50 61	1 011
331	67 98	1 105	380	54 17	1 046	429	50 00	* 1 000 *
332	67 59	1 105	381	55 35	1 056	430	50 00	* 1 000 *
333	68 55	1 105	382	52 91	1 053	431	50 00	* 1 000 *
334	68 16	1 105	383	52 37	1 043	432	50 00	* 1 000 *
335	68 28	1 105	384	53 08	1 044	433	51 05	1 012
336	68 77	1 105	385	54 34	1 046	434	50 31	1 011
337	60 27	1 083	386	54 46	1 046	435	50 00	* 1 000 *
338	60 54	1 084	387	55 78	1 057	436	50 00	* 1 000 *
339	62 15	1 090	388	51 40	1 051	437	50 00	* 1 000 *
340	60 52	1 083	389	51 16	1 041	438	50 00	* 1 000 *
341	60 54	1 083	390	51 70	1 042	439	51 07	1 012
342	62 11	1 090	391	54 53	1 046	440	50 18	1 010
343	56 31	1 072	392	54 58	1 046	441	50 00	* 1 000 *
344	55 59	1 065	393	55 97	1 057	442	50 00	* 1 000 *
345	56 15	1 066	394	50 83	1 051	443	50 00	* 1 000 *
346	56 62	1 067	395	50 69	1 041	444	51 08	1 012
347	57 64	1 074	396	50 82	1 041	445	50 00	* 1 000 *
348	53 71	1 070	397	54 62	1 047			
349	53 39	1 063	398	56 04	1 057			

ITERATION NUMBER 1, MAX CHANGE (TEMP) = 1 1606E-05, MAX REL CORRECTION = 2 3840E-03
 ITERATION NUMBER 1, MAX CHANGE (HEAD) = 2 3516E-03, MAX REL CORRECTION = 7 9769E-03

LISTING D-6. Output Report File for Test Case Two. (Sheet 40 of 48)

SAMPLE PROBLEM. FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
1	VEL X	-7 7625E-09	-1 5937E-08	-3 1866E-08	-4 2930E-09	-8 7949E-09	-1 7339E-08	-9 5220E-10	-1 9341E-09	-3 7501E-09
	VEL Y	5 5734E-06	5 5708E-06	5 5669E-06	5 5555E-06	5 5530E-06	5 5494E-06	5 5393E-06	5 5371E-06	5 5338E-06
2	VEL X	-5 2262E-08	-2 8743E-08	-6 3145E-09	-4 4630E-08	-2 4322E-08	-5 3017E-09	-3 3244E-08	-1 7693E-08	-3 7756E-09
	VEL Y	5 5465E-06	5 5310E-06	5 5173E-06	5 5561E-06	5 5397E-06	5 5251E-06	5 5627E-06	5 5456E-06	5 5302E-06
3	VEL X	-8 2015E-08	-4 5333E-08	-1 0019E-08	-7 2231E-08	-3 9733E-08	-8 7365E-09	-5 9504E-08	-3 2433E-08	-7 0615E-09
	VEL Y	5 4967E-06	5 4853E-06	5 4752E-06	5 5188E-06	5 5056E-06	5 4939E-06	5 5356E-06	5 5208E-06	5 5077E-06
4	VEL X	-1 0644E-07	-5 8310E-08	-1 2756E-08	-9 8963E-08	-5 3977E-08	-1 1764E-08	-8 9861E-08	-4 8699E-08	-1 0553E-08
	VEL Y	5 4009E-06	5 3979E-06	5 3959E-06	5 4403E-06	5 4336E-06	5 4281E-06	5 4733E-06	5 4633E-06	5 4547E-06
5	VEL X	-9 6322E-08	-5 4734E-08	-1 2440E-08	-1 0001E-07	-5 6900E-08	-1 2948E-08	-1 0547E-07	-6 0107E-08	-1 3700E-08
	VEL Y	5 1799E-06	5 1837E-06	5 1878E-06	5 2713E-06	5 2722E-06	5 2736E-06	5 3496E-06	5 3482E-06	5 3476E-06
6	VEL X	-4 2629E-08	-2 5049E-08	-5 8778E-09	-6 0414E-08	-3 5204E-08	-8 1966E-09	-8 3472E-08	-4 8369E-08	-1 1203E-08
	VEL Y	4 9484E-06	4 9516E-06	4 9547E-06	5 0145E-06	5 0187E-06	5 0230E-06	5 0961E-06	5 1009E-06	5 1058E-06
7	VEL X	-1 3203E-09	-1 1146E-09	-3 3284E-10	-1 6504E-08	-9 7081E-09	-2 2802E-09	-3 4944E-08	-2 0144E-08	-4 6451E-09
	VEL Y	4 8434E-06	4 8449E-06	4 8463E-06	4 8570E-06	4 8598E-06	4 8624E-06	4 8966E-06	4 8995E-06	4 9023E-06
8	VEL X	-1 8979E-08	-3 8162E-08	-7 8287E-08	-1 3565E-08	-2 8110E-08	-5 7694E-08	-9 8825E-09	-2 0524E-08	-4 1587E-08
	VEL Y	5 7059E-06	5 7012E-06	5 6950E-06	5 6475E-06	5 6440E-06	5 6391E-06	5 5935E-06	5 5911E-06	5 5875E-06
9	VEL X	-1 2342E-07	-9 2141E-08	-6 7498E-08	-1 0680E-07	-7 8103E-08	-5 7284E-08	-8 2335E-08	-5 7324E-08	-4 2090E-08
	VEL Y	5 6576E-06	5 6102E-06	5 5667E-06	5 6734E-06	5 6223E-06	5 5753E-06	5 6853E-06	5 6309E-06	5 5806E-06
10	VEL X	-1 8748E-07	-1 4201E-07	-1 0537E-07	-1 6783E-07	-1 2527E-07	-9 2621E-08	-1 4240E-07	-1 0356E-07	-7 6055E-08
	VEL Y	5 5724E-06	5 5419E-06	5 5143E-06	5 6059E-06	5 5683E-06	5 5340E-06	5 6334E-06	5 5891E-06	5 5485E-06
11	VEL X	-2 2270E-07	-1 7320E-07	-1 3433E-07	-2 1222E-07	-1 6289E-07	-1 2517E-07	-1 9951E-07	-1 5037E-07	-1 1403E-07
	VEL Y	5 4287E-06	5 4252E-06	5 4233E-06	5 4794E-06	5 4649E-06	5 4524E-06	5 5250E-06	5 4998E-06	5 4773E-06
12	VEL X	-1 7291E-07	-1 4585E-07	-1 1896E-07	-1 9125E-07	-1 5800E-07	-1 2495E-07	-2 1840E-07	-1 7599E-07	-1 3383E-07
	VEL Y	5 1698E-06	5 1833E-06	5 1966E-06	5 2522E-06	5 2594E-06	5 2671E-06	5 3333E-06	5 3347E-06	5 3373E-06
13	VEL X	-6 9098E-08	-6 1514E-08	-5 1539E-08	-1 0214E-07	-8 9182E-08	-7 3529E-08	-1 4497E-07	-1 2505E-07	-1 0204E-07
	VEL Y	4 9415E-06	4 9502E-06	4 9584E-06	4 9848E-06	4 9969E-06	5 0086E-06	5 0435E-06	5 0581E-06	5 0723E-06
14	VEL X	-3 2406E-09	-2 8941E-09	-1 7602E-09	-2 6556E-08	-2 3603E-08	-1 9786E-08	-5 4871E-08	-4 8752E-08	-4 1677E-08
	VEL Y	4 8337E-06	4 8379E-06	4 8417E-06	4 8429E-06	4 8492E-06	4 8551E-06	4 8667E-06	4 8740E-06	4 8809E-06
15	VEL X	-5 2897E-08	-9 3160E-08	-1 8395E-07	-3 3908E-08	-6 3735E-08	-1 2903E-07	-2 3247E-08	-4 6156E-08	-9 4875E-08
	VEL Y	6 0116E-06	5 9964E-06	5 9788E-06	5 8750E-06	5 8650E-06	5 8531E-06	5 7487E-06	5 7438E-06	5 7371E-06
16	VEL X	-2 8739E-07	-2 0436E-07	-1 4959E-07	-2 5033E-07	-1 7232E-07	-1 2779E-07	-1 9641E-07	-1 2548E-07	-9 5761E-08
	VEL Y	5 8727E-06	5 7813E-06	5 6980E-06	5 9179E-06	5 8121E-06	5 7149E-06	5 9537E-06	5 8339E-06	5 7235E-06

D-77

RHO-BW-CR-143 P

LISTING D-6. Output Report File for Test Case Two. (Sheet 41 of 48)

SAMPLE PROBLEM. FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10.00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
17	VEL X	-3.7788E-07	-2.8417E-07	-2.2199E-07	-3.5208E-07	-2.5795E-07	-1.9920E-07	-3.1887E-07	-2.2413E-07	-1.6975E-07
	VEL Y	5.6668E-06	5.6327E-06	5.6037E-06	5.7446E-06	5.6871E-06	5.6359E-06	5.8133E-06	5.7331E-06	5.6604E-06
18	VEL X	-3.5562E-07	-2.9646E-07	-2.5544E-07	-3.6597E-07	-2.9654E-07	-2.4693E-07	-3.7848E-07	-2.9665E-07	-2.3662E-07
	VEL Y	5.4184E-06	5.4361E-06	5.4551E-06	5.4947E-06	5.4927E-06	5.4935E-06	5.5719E-06	5.5507E-06	5.5336E-06
19	VEL X	-2.0052E-07	-1.9597E-07	-1.8811E-07	-2.5301E-07	-2.3497E-07	-2.1298E-07	-3.3072E-07	-2.9271E-07	-2.4979E-07
	VEL Y	5.1287E-06	5.1543E-06	5.1787E-06	5.1887E-06	5.2136E-06	5.2382E-06	5.2696E-06	5.2932E-06	5.3173E-06
20	VEL X	-6.8879E-08	-7.2393E-08	-7.2446E-08	-1.0876E-07	-1.1044E-07	-1.0820E-07	-1.6046E-07	-1.5976E-07	-1.5456E-07
	VEL Y	4.9268E-06	4.9377E-06	4.9478E-06	4.9419E-06	4.9598E-06	4.9766E-06	4.9701E-06	4.9937E-06	5.0159E-06
21	VEL X	-3.6227E-09	-3.9243E-09	-3.4833E-09	-2.6347E-08	-2.7350E-08	-2.7539E-08	-5.3944E-08	-5.5799E-08	-5.6752E-08
	VEL Y	4.8222E-06	4.8272E-06	4.8317E-06	4.8253E-06	4.8324E-06	4.8390E-06	4.8341E-06	4.8424E-06	4.8500E-06
22	VEL X	-1.6503E-07	-2.5197E-07	-1.4705E-07	-1.1772E-07	-7.8330E-08	-2.2162E-07	-2.4528E-07		
	VEL Y	6.1841E-06	6.2275E-06	6.2760E-06	6.0546E-06	6.1147E-06	6.0281E-06	6.4235E-06		
23	VEL X	-3.7981E-07	-3.7184E-07	-4.5271E-07	-3.0208E-07	-3.6508E-07	-2.0426E-07	-5.4889E-07		
	VEL Y	6.3846E-06	6.3018E-06	6.5384E-06	6.3236E-06	6.5318E-06	6.1562E-06	6.4927E-06		
24	VEL X	-6.8575E-07	-4.9528E-07	-3.5850E-07	-6.2349E-07	-4.3701E-07	-3.1371E-07	-5.3390E-07	-3.5276E-07	-2.4869E-07
	VEL Y	6.1128E-06	6.0294E-06	5.9507E-06	6.2658E-06	6.1322E-06	6.0119E-06	6.3921E-06	6.2114E-06	6.0524E-06
25	VEL X	-7.8272E-08	-1.5263E-07	9.2103E-09	-1.1423E-07	4.7521E-09	-2.7357E-07	-3.2488E-08		
	VEL Y	6.4692E-06	6.6311E-06	6.4037E-06	6.3867E-06	6.2295E-06	6.5932E-06	6.6241E-06		
26	VEL X	-6.5976E-07	-5.3651E-07	-4.4527E-07	-6.7852E-07	-5.3343E-07	-4.2404E-07	-7.0262E-07	-5.2951E-07	-3.9676E-07
	VEL Y	5.6303E-06	5.6694E-06	5.6917E-06	5.7951E-06	5.7873E-06	5.7710E-06	5.9602E-06	5.9060E-06	5.8515E-06
27	VEL X	-4.3314E-07	-4.1618E-07	-3.9381E-07	-5.1007E-07	-4.6600E-07	-4.1597E-07	-6.0287E-07	-5.2617E-07	-4.4276E-07
	VEL Y	5.3033E-06	5.3668E-06	5.4106E-06	5.3719E-06	5.4323E-06	5.4730E-06	5.4670E-06	5.5214E-06	5.5565E-06
28	VEL X	-1.7082E-07	-1.8974E-07	-2.0234E-07	-2.5135E-07	-2.6092E-07	-2.6296E-07	-3.7057E-07	-3.6631E-07	-3.5269E-07
	VEL Y	5.0794E-06	5.1067E-06	5.1247E-06	5.0835E-06	5.1295E-06	5.1615E-06	5.1270E-06	5.1862E-06	5.2274E-06
29	VEL X	-5.1953E-08	-5.9382E-08	-6.6033E-08	-8.7498E-08	-9.7241E-08	-1.0611E-07	-1.3358E-07	-1.4632E-07	-1.5806E-07
	VEL Y	4.9156E-06	4.9244E-06	4.9298E-06	4.9101E-06	4.9242E-06	4.9331E-06	4.9089E-06	4.9277E-06	4.9396E-06
30	VEL X	-2.7330E-09	-3.0801E-09	-3.3479E-09	-2.0049E-08	-2.2711E-08	-2.5287E-08	-4.1074E-08	-4.6548E-08	-5.1928E-08
	VEL Y	4.8145E-06	4.8183E-06	4.8205E-06	4.8140E-06	4.8187E-06	4.8214E-06	4.8105E-06	4.8168E-06	4.8206E-06
31	VEL X	-8.0458E-07	-5.3675E-07	-3.5821E-07	-4.9041E-07	-3.1212E-07	-1.9564E-07	-2.1505E-07	-1.2406E-07	-6.5292E-08
	VEL Y	7.7550E-06	7.2008E-06	6.7548E-06	7.8619E-06	7.2689E-06	6.7955E-06	7.9475E-06	7.3224E-06	6.8261E-06
32	VEL X	-1.5471E-06	-9.3592E-07	-5.9425E-07	-1.3809E-06	-8.0554E-07	-4.8427E-07	-1.2176E-06	-6.9482E-07	-4.0443E-07
	VEL Y	7.2406E-06	6.9187E-06	6.6474E-06	7.4289E-06	7.0208E-06	6.6818E-06	7.6432E-06	7.1381E-06	6.7253E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 42 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
33	VEL X	-1 6500E-06	-1 1803E-06	-8 4853E-07	-1 6260E-06	-1 1243E-06	-7 8283E-07	-1 5925E-06	-1 0444E-06	-6 8856E-07
	VEL Y	6 0399E-06	6 1400E-06	6 2018E-06	6 5556E-06	6 4764E-06	6 3974E-06	7 0203E-06	6 7705E-06	6 5572E-06
34	VEL X	-8 2999E-07	-7 9223E-07	-7 3879E-07	-1 0826E-06	-9 4760E-07	-7 9460E-07	-1 4043E-06	-1 1460E-06	-8 6615E-07
	VEL Y	5 2917E-06	5 4681E-06	5 5924E-06	5 4375E-06	5 6110E-06	5 7322E-06	5 6841E-06	5 8418E-06	5 9496E-06
35	VEL X	-3 8506E-07	-4 2828E-07	-4 4491E-07	-5 3264E-07	-5 5055E-07	-5 3958E-07	-7 0996E-07	-6 9770E-07	-6 5369E-07
	VEL Y	5 1200E-06	5 2047E-06	5 2620E-06	5 1010E-06	5 2278E-06	5 3163E-06	5 1281E-06	5 2899E-06	5 4038E-06
36	VEL X	-1 1368E-07	-1 3834E-07	-1 6002E-07	-1 9013E-07	-2 1836E-07	-2 4308E-07	-3 0328E-07	-3 3681E-07	-3 6605E-07
	VEL Y	5 0476E-06	5 0666E-06	5 0781E-06	5 0008E-06	5 0432E-06	5 0712E-06	4 9671E-06	5 0302E-06	5 0722E-06
37	VEL X	-3 2332E-08	-3 9456E-08	-4 7403E-08	-5 7247E-08	-6 8703E-08	-8 1099E-08	-8 9558E-08	-1 0662E-07	-1 2478E-07
	VEL Y	4 9106E-06	4 9161E-06	4 9193E-06	4 8943E-06	4 9012E-06	4 9048E-06	4 8704E-06	4 8804E-06	4 8857E-06
38	VEL X	-1 7138E-09	-1 9938E-09	-2 4539E-09	-1 2687E-08	-1 5445E-08	-1 8401E-08	-2 6020E-08	-3 1779E-08	-3 7764E-08
	VEL Y	4 8112E-06	4 8133E-06	4 8144E-06	4 8088E-06	4 8110E-06	4 8119E-06	4 7981E-06	4 8024E-06	4 8048E-06
39	VEL X	-2 9658E-06	-2 0142E-06	-1 1320E-06	-1 3108E-06	-1 0059E-06	-6 7317E-07	2 3964E-07	-7 7944E-08	-2 4329E-07
	VEL Y	1 0543E-05	9 1402E-06	8 1562E-06	1 0876E-05	9 4337E-06	8 4333E-06	1 0829E-05	9 4554E-06	8 5043E-06
40	VEL X	-5 5242E-06	-3 4498E-06	-2 1261E-06	-4 7384E-06	-2 7641E-06	-1 7689E-06	-3 5626E-06	-1 9320E-06	-1 3727E-06
	VEL Y	7 3817E-06	7 6146E-06	7 7380E-06	8 7689E-06	8 3433E-06	7 9898E-06	1 0053E-05	8 9052E-06	8 0537E-06
41	VEL X	-2 2586E-06	-2 0979E-06	-1 9279E-06	-3 5128E-06	-2 8053E-06	-2 0803E-06	-5 2746E-06	-3 8039E-06	-2 2962E-06
	VEL Y	4 6008E-06	5 3439E-06	5 8434E-06	5 2022E-06	5 8563E-06	6 2932E-06	6 4022E-06	6 8717E-06	7 1778E-06
42	VEL X	-6 6275E-07	-8 2021E-07	-8 6372E-07	-1 1222E-06	-1 2115E-06	-1 1752E-06	-1 7027E-06	-1 7077E-06	-1 5714E-06
	VEL Y	4 8016E-06	5 0162E-06	5 1535E-06	4 5238E-06	4 9820E-06	5 2866E-06	4 4013E-06	5 0705E-06	5 5200E-06
43	VEL X	-2 4849E-07	-3 0345E-07	-3 5641E-07	-3 7647E-07	-4 4363E-07	-5 0894E-07	-5 2993E-07	-6 1190E-07	-6 9222E-07
	VEL Y	4 9839E-06	5 0459E-06	5 0830E-06	4 8901E-06	4 9824E-06	5 0388E-06	4 7860E-06	4 9093E-06	4 9853E-06
44	VEL X	-6 3030E-08	-8 0566E-08	-1 0032E-07	-1 1036E-07	-1 3995E-07	-1 7226E-07	-1 8063E-07	-2 2796E-07	-2 7879E-07
	VEL Y	5 0359E-06	5 0453E-06	5 0500E-06	4 9645E-06	4 9871E-06	4 9997E-06	4 8535E-06	4 8972E-06	4 9228E-06
45	VEL X	-1 7093E-08	-2 1934E-08	-2 8327E-08	-3 1117E-08	-4 0060E-08	-5 0765E-08	-4 9380E-08	-6 3602E-08	-7 9872E-08
	VEL Y	4 9093E-06	4 9125E-06	4 9141E-06	4 8886E-06	4 8898E-06	4 8897E-06	4 8489E-06	4 8537E-06	4 8557E-06
46	VEL X	-9 1469E-10	-1 0336E-09	-1 4786E-09	-6 8417E-09	-8 8349E-09	-1 1186E-08	-1 4083E-08	-1 8330E-08	-2 2983E-08
	VEL Y	4 8097E-06	4 8112E-06	4 8118E-06	4 8074E-06	4 8074E-06	4 8071E-06	4 7926E-06	4 7957E-06	4 7973E-06
47	VEL X	-5 5119E-05	-5 7090E-05	-5 9220E-05	-3 1157E-05	-3 3138E-05	-3 4970E-05	-9 3075E-06	-1 0506E-05	-1 1294E-05
	VEL Y	1 6676E-05	8 5498E-06	1 8844E-06	2 9958E-05	2 1750E-05	1 4738E-05	3 3085E-05	2 5693E-05	1 9200E-05
48	VEL X	-8 1054E-05	-8 5368E-05	-8 9974E-05	-7 7312E-05	-8 1893E-05	-8 6602E-05	-6 3805E-05	-6 7884E-05	-7 1921E-05
	VEL Y	-3 7954E-05	-5 0245E-05	-6 0523E-05	-1 3617E-05	-2 3703E-05	-3 1892E-05	6 1299E-06	-2 4749E-06	-9 3960E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 43 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
49	VEL X	-1 4784E-06	-1 9241E-06	-2 2604E-06	-2 5364E-06	-3 1775E-06	-3 6624E-06	-4 0846E-06	-4 9755E-06	-5 6390E-06
	VEL Y	3 7042E-06	3 9614E-06	4 3518E-06	2 8351E-06	3 5094E-06	4 4252E-06	1 9402E-06	3 2497E-06	4 9044E-06
50	VEL X	-6 1670E-05	-7 8798E-05	-8 8779E-05	-6 0291E-05	-7 5156E-05	-8 3658E-05	-5 8911E-05	-7 1707E-05	-7 9073E-05
	VEL Y	-1 3513E-04	-1 1004E-04	-7 9259E-05	-1 1802E-04	-9 6054E-05	-6 7077E-05	-9 9038E-05	-8 0310E-05	-5 3202E-05
51	VEL X	-4 0273E-07	-4 9423E-07	-5 7720E-07	-7 0785E-07	-8 8171E-07	-1 0367E-06	-1 1068E-06	-1 3816E-06	-1 6215E-06
	VEL Y	4 6736E-06	4 6946E-06	4 7398E-06	4 3935E-06	4 4378E-06	4 5314E-06	3 9450E-06	4 0524E-06	4 2498E-06
52	VEL X	-3 6797E-07	-4 4413E-07	-3 6125E-07	-3 0206E-07	-2 4906E-07	-3 7124E-07	-4 9630E-07		
	VEL Y	4 7883E-06	4 6429E-06	4 9167E-06	4 8067E-06	5 0010E-06	4 6307E-06	4 7267E-06		
53	VEL X	-1 8194E-07	-2 6559E-07	-1 0812E-07	-1 6572E-07	-3 6696E-08	-2 8657E-07	-2 0316E-07		
	VEL Y	4 8687E-06	4 7907E-06	4 9433E-06	4 8622E-06	4 9348E-06	4 7543E-06	4 9275E-06		
54	VEL X	-9 6798E-09	-4 0698E-08	-5 6673E-08	-1 5355E-08	-6 4772E-08	-9 6479E-08	-2 3739E-08	-1 0041E-07	-1 5572E-07
	VEL Y	5 0363E-06	5 0348E-06	5 0325E-06	4 9411E-06	4 9563E-06	4 9907E-06	4 8189E-06	4 8317E-06	4 8628E-06
55	VEL X	-1 7732E-09	-1 0075E-08	-1 5132E-08	-3 0550E-09	-1 6634E-08	-2 6638E-08	-4 7116E-09	-2 5137E-08	-4 1648E-08
	VEL Y	4 9111E-06	4 9108E-06	4 9103E-06	4 8839E-06	4 8853E-06	4 8885E-06	4 8491E-06	4 8436E-06	4 8327E-06
56	VEL X	-2 7009E-10	-1 0871E-09	-1 0957E-09	-5 6361E-10	-3 6483E-09	-5 8544E-09	-9 1743E-10	-6 7587E-09	-1 1674E-08
	VEL Y	4 8115E-06	4 8104E-06	4 8085E-06	4 8043E-06	4 8060E-06	4 8091E-06	4 7935E-06	4 7929E-06	4 7918E-06
57	VEL X	-4 6703E-05	-5 0316E-05	-5 4066E-05	-2 4757E-05	-2 7498E-05	-3 0059E-05	-6 6006E-06	-7 9363E-06	-8 8017E-06
	VEL Y	3 6201E-05	2 7512E-05	2 0804E-05	4 8106E-05	3 9917E-05	3 3245E-05	5 0081E-05	4 3596E-05	3 8136E-05
58	VEL X	-6 4787E-05	-7 1479E-05	-7 8355E-05	-6 1344E-05	-6 8371E-05	-7 5356E-05	-4 9240E-05	-5 5713E-05	-6 1954E-05
	VEL Y	-5 0739E-06	-1 9858E-05	-3 1975E-05	1 3754E-05	1 8113E-06	-7 5815E-06	2 8640E-05	1 8946E-05	1 1566E-05
59	VEL X	-5 5342E-05	-7 0369E-05	-7 6276E-05	-5 2030E-05	-6 4157E-05	-6 8448E-05	-4 8653E-05	-5 8065E-05	-6 1178E-05
	VEL Y	-9 0226E-05	-7 1603E-05	-4 5863E-05	-7 0110E-05	-5 4647E-05	-3 1153E-05	-4 7259E-05	-3 5171E-05	-1 4197E-05
60	VEL X	-1 6711E-07	-7 1089E-07	-1 1995E-06	-2 9176E-07	-1 2417E-06	-2 0914E-06	-4 8309E-07	-2 0473E-06	-3 4197E-06
	VEL Y	3 1836E-06	3 2940E-06	3 5389E-06	2 0574E-06	2 2069E-06	2 6144E-06	3 9691E-07	6 5344E-07	1 3824E-06
61	VEL X	-4 4813E-06	-2 3987E-05	-4 7949E-05	-4 3730E-06	-2 3705E-05	-4 7760E-05	-4 2715E-06	-2 3476E-05	-4 7740E-05
	VEL Y	-1 7716E-04	-1 6549E-04	-1 4285E-04	-1 5587E-04	-1 4665E-04	-1 2666E-04	-1 3367E-04	-1 2687E-04	-1 0960E-04
62	VEL X	-5 1731E-08	-2 1481E-07	-3 4427E-07	-8 7563E-08	-3 6504E-07	-5 9706E-07	-1 3557E-07	-5 6504E-07	-9 3019E-07
	VEL Y	4 5682E-06	4 5912E-06	4 6364E-06	4 1461E-06	4 2012E-06	4 3083E-06	3 5068E-06	3 5986E-06	3 7860E-06
63	VEL X	-6 3377E-06	-2 7513E-05	-4 6002E-05	-5 9958E-06	-2 6258E-05	-4 3944E-05	-5 6620E-06	-2 5052E-05	-4 2009E-05
	VEL Y	-1 2240E-04	-1 1579E-04	-1 0042E-04	-9 9807E-05	-9 3413E-05	-7 8951E-05	-7 6042E-05	-6 9626E-05	-5 5860E-05
64	VEL X	-8 7085E-08	-1 2073E-07	-1 3947E-08	-1 2593E-07	-2 6575E-08	-2 0742E-07	-2 4124E-08		
	VEL Y	4 6939E-06	4 7905E-06	4 7518E-06	4 5534E-06	4 5605E-06	4 5996E-06	4 9577E-06		

LISTING D-6. Output Report File for Test Case Two. (Sheet 44 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
65	VEL X	9 1318E-08	1 2518E-07	1 2973E-07	1 8365E-08	3 0397E-08	2 8989E-08	2 1135E-07		
	VEL Y	4 6943E-06	4 7910E-06	4 5539E-06	4 7520E-06	4 5606E-06	4 9578E-06	4 6005E-06		
66	VEL X	1 8659E-07	2 7003E-07	1 7022E-07	1 1315E-07	4 1740E-08	2 0802E-07	2 9061E-07		
	VEL Y	4 8697E-06	4 7922E-06	4 8630E-06	4 9442E-06	4 9353E-06	4 9293E-06	4 7555E-06		
67	VEL X	1 6075E-07	1 0108E-07	6 0982E-08	1 0548E-07	6 9400E-08	4 5026E-08	2 8840E-08	2 0003E-08	1 4022E-08
	VEL Y	4 8646E-06	4 9923E-06	5 0339E-06	4 8326E-06	4 9571E-06	5 0355E-06	4 8193E-06	4 9415E-06	5 0366E-06
68	VEL X	4 5565E-08	2 9749E-08	1 7620E-08	2 9069E-08	1 9756E-08	1 2572E-08	8 6549E-09	6 1851E-09	4 2761E-09
	VEL Y	4 8339E-06	4 8895E-06	4 9113E-06	4 8442E-06	4 8858E-06	4 9113E-06	4 8494E-06	4 8842E-06	4 9114E-06
69	VEL X	1 3574E-08	6 8434E-09	1 3347E-09	8 6651E-09	4 6409E-09	1 3273E-09	2 8290E-09	1 5586E-09	5 1036E-10
	VEL Y	4 7927E-06	4 8099E-06	4 8093E-06	4 7934E-06	4 8064E-06	4 8108E-06	4 7937E-06	4 8045E-06	4 8117E-06
70	VEL X	-2 0083E-04	-2 5143E-04	-3 2837E-04	-1 0794E-04	-1 4305E-04	-1 7520E-04	-3 2918E-05	-5 7404E-05	-6 2265E-05
	VEL Y	2 1210E-04	1 4765E-04	6 9930E-05	3 7057E-04	2 8053E-04	1 2513E-04	4 2563E-04	3 5728E-04	1 7973E-04
71	VEL X	-3 0158E-04	-3 7205E-04	-3 9992E-04	-2 5885E-04	-3 2914E-04	-3 8355E-04	-2 3455E-04	-2 9769E-04	-3 3308E-04
	VEL Y	-3 9573E-04	-3 6230E-04	-2 5938E-04	-1 4005E-04	-1 6222E-04	-1 2827E-04	8 8061E-05	4 1814E-05	1 3522E-06
72	VEL X	-2 5612E-05	-1 1372E-04	-2 2300E-04	-2 6411E-05	-1 1025E-04	-1 9687E-04	-2 8235E-05	-1 1155E-04	-1 8484E-04
	VEL Y	-5 5606E-04	-5 2384E-04	-4 5807E-04	-1 3154E-04	-1 3333E-04	-1 5477E-04	1 7803E-04	1 7722E-04	1 1209E-04
73	VEL X	3 4119E-06	2 0870E-06	1 1975E-06	2 0391E-06	1 2372E-06	7 0872E-07	4 7496E-07	2 8713E-07	1 6483E-07
	VEL Y	1 3800E-06	2 6133E-06	3 5388E-06	6 5239E-07	2 2064E-06	3 2939E-06	3 9709E-07	2 0573E-06	3 1835E-06
74	VEL X	4 7868E-05	4 7836E-05	4 7973E-05	2 3591E-05	2 3765E-05	2 3993E-05	4 3884E-06	4 4313E-06	4 4810E-06
	VEL Y	-1 0979E-04	-1 2686E-04	-1 4307E-04	-1 2698E-04	-1 4676E-04	-1 6561E-04	-1 3370E-04	-1 5590E-04	-1 7720E-04
75	VEL X	9 2984E-07	5 9866E-07	3 4738E-07	5 6461E-07	3 6662E-07	2 1793E-07	1 3503E-07	8 9095E-08	5 4850E-08
	VEL Y	3 7864E-06	4 3091E-06	4 6374E-06	3 5988E-06	4 2016E-06	4 5917E-06	3 5067E-06	4 1462E-06	4 5684E-06
76	VEL X	4 2369E-05	4 4208E-05	4 6168E-05	2 5410E-05	2 6518E-05	2 7674E-05	6 0186E-06	6 2529E-06	6 4952E-06
	VEL Y	-5 5992E-05	-7 9110E-05	-1 0060E-04	-6 9708E-05	-9 3507E-05	-1 1590E-04	-7 6083E-05	-9 9847E-05	-1 2244E-04
77	VEL X	1 8500E-04	1 9714E-04	2 2343E-04	1 1157E-04	1 1042E-04	1 1406E-04	2 8181E-05	2 6516E-05	2 5879E-05
	VEL Y	1 0925E-04	-1 5738E-04	-4 6041E-04	1 7563E-04	-1 3478E-04	-5 2512E-04	1 7755E-04	-1 3201E-04	-5 5650E-04
78	VEL X	3 7218E-07	4 4793E-07	3 0649E-07	3 6563E-07	2 5389E-07	5 0011E-07	3 7516E-07		
	VEL Y	4 7900E-06	4 6445E-06	4 8083E-06	4 9185E-06	5 0029E-06	4 7286E-06	4 6321E-06		
79	VEL X	1 6213E-06	1 0383E-06	5 8029E-07	1 3813E-06	8 8335E-07	4 9736E-07	1 1065E-06	7 0947E-07	4 0584E-07
	VEL Y	4 2504E-06	4 5328E-06	4 7416E-06	4 0528E-06	4 4389E-06	4 6961E-06	3 9453E-06	4 3943E-06	4 6748E-06
80	VEL X	6 9613E-07	5 1329E-07	3 6113E-07	6 1577E-07	4 4801E-07	3 0825E-07	5 3373E-07	3 8085E-07	2 5336E-07
	VEL Y	4 9887E-06	5 0423E-06	5 0863E-06	4 9122E-06	4 9853E-06	5 0486E-06	4 7879E-06	4 8922E-06	4 9859E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 45 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
81	VEL X	2 8363E-07	1 7671E-07	1 0452E-07	2 3289E-07	1 4447E-07	8 4819E-08	1 8563E-07	1 1493E-07	6 7319E-08
	VEL Y	4 9258E-06	5 0024E-06	5 0523E-06	4 8997E-06	4 9894E-06	5 0473E-06	4 8553E-06	4 9661E-06	5 0373E-06
82	VEL X	8 3708E-08	5 3815E-08	3 0772E-08	6 7478E-08	4 3141E-08	2 4401E-08	5 3283E-08	3 4218E-08	1 9574E-08
	VEL Y	4 8578E-06	4 8915E-06	4 9157E-06	4 8554E-06	4 8913E-06	4 9139E-06	4 8501E-06	4 8897E-06	4 9103E-06
83	VEL X	2 4849E-08	1 2157E-08	1 7128E-09	2 0212E-08	9 8152E-09	1 2714E-09	1 5977E-08	7 8280E-09	1 1534E-09
	VEL Y	4 7988E-06	4 8085E-06	4 8132E-06	4 7969E-06	4 8086E-06	4 8123E-06	4 7935E-06	4 8082E-06	4 8105E-06
84	VEL X	-1 8826E-05	-8 3871E-05	-1 6007E-04	-1 1743E-05	-4 7394E-05	-8 3586E-05	-5 0115E-06	-1 4203E-05	-1 7987E-05
	VEL Y	3 1739E-04	3 2084E-04	2 3738E-04	4 8612E-04	4 9258E-04	3 9434E-04	5 5414E-04	5 7796E-04	4 8094E-04
85	VEL X	1 7985E-05	8 3633E-05	1 6018E-04	1 4156E-05	4 7376E-05	8 3884E-05	5 0068E-06	1 1696E-05	1 8734E-05
	VEL Y	4 7791E-04	3 9131E-04	2 3642E-04	5 7622E-04	4 9082E-04	3 1915E-04	5 5367E-04	4 8558E-04	3 1688E-04
86	VEL X	5 6331E-06	3 6588E-06	2 2584E-06	4 9688E-06	3 1736E-06	1 9221E-06	4 0771E-06	2 5322E-06	1 4765E-06
	VEL Y	4 8996E-06	4 4232E-06	4 3515E-06	3 2457E-06	3 5079E-06	3 9611E-06	1 9373E-06	2 8341E-06	3 7041E-06
87	VEL X	7 9217E-05	8 3768E-05	8 8852E-05	7 1846E-05	7 5252E-05	7 8849E-05	5 9047E-05	6 0378E-05	6 1707E-05
	VEL Y	-5 3463E-05	-6 7370E-05	-7 9584E-05	-8 0545E-05	-9 6317E-05	-1 1033E-04	-9 9250E-05	-1 1825E-04	-1 3538E-04
88	VEL X	6 1470E-05	6 8684E-05	7 6449E-05	5 8401E-05	6 4414E-05	7 0543E-05	4 9011E-05	5 2295E-05	5 5513E-05
	VEL Y	-1 4291E-05	-3 1320E-05	-4 6099E-05	-3 5273E-05	-5 4807E-05	-7 1820E-05	-4 7389E-05	-7 0277E-05	-9 0429E-05
89	VEL X	3 3364E-04	3 8407E-04	4 0053E-04	2 9813E-04	3 2964E-04	3 7274E-04	2 3481E-04	2 5919E-04	3 0208E-04
	VEL Y	-2 6025E-06	-1 3205E-04	-2 6288E-04	3 8232E-05	-1 6554E-04	-3 6525E-04	8 4821E-05	-1 4303E-04	-3 9840E-04
90	VEL X	6 2359E-05	1 7545E-04	3 2886E-04	5 7481E-05	1 4324E-04	2 5178E-04	3 2956E-05	1 0804E-04	2 0100E-04
	VEL Y	1 7539E-04	1 2083E-04	6 5801E-05	3 5329E-04	2 7660E-04	1 4389E-04	4 2200E-04	3 6700E-04	2 0869E-04
91	VEL X	1 5727E-06	1 1777E-06	8 6705E-07	1 7083E-06	1 2135E-06	8 2339E-07	1 7026E-06	1 1238E-06	6 6582E-07
	VEL Y	5 5224E-06	5 2896E-06	5 1570E-06	5 0722E-06	4 9845E-06	5 0190E-06	4 4019E-06	4 5253E-06	4 8034E-06
92	VEL X	2 2957E-06	2 0804E-06	1 9285E-06	3 8014E-06	2 8041E-06	2 0976E-06	5 2698E-06	3 5099E-06	2 2570E-06
	VEL Y	7 1778E-06	6 2943E-06	5 8454E-06	6 8697E-06	5 8560E-06	5 3449E-06	6 3974E-06	5 1998E-06	4 6005E-06
93	VEL X	6 5740E-07	5 4358E-07	4 4915E-07	7 0153E-07	5 5471E-07	4 3273E-07	7 1383E-07	5 3691E-07	3 8966E-07
	VEL Y	5 4098E-06	5 3221E-06	5 2675E-06	5 2950E-06	5 2328E-06	5 2094E-06	5 1321E-06	5 1049E-06	5 1238E-06
94	VEL X	3 7039E-07	2 4717E-07	1 6394E-07	3 4138E-07	2 2261E-07	1 4238E-07	3 0802E-07	1 9450E-07	1 1782E-07
	VEL Y	5 0772E-06	5 0757E-06	5 0821E-06	5 0346E-06	5 0471E-06	5 0700E-06	4 9706E-06	5 0038E-06	5 0502E-06
95	VEL X	8 6851E-07	7 9755E-07	7 4220E-07	1 1481E-06	9 5047E-07	7 9569E-07	1 4060E-06	1 0852E-06	8 3337E-07
	VEL Y	5 9558E-06	5 7385E-06	5 5986E-06	5 8467E-06	5 6162E-06	5 4734E-06	5 6875E-06	5 4413E-06	5 2957E-06
96	VEL X	1 2840E-07	8 3991E-08	4 9730E-08	1 1034E-07	7 1670E-08	4 1840E-08	9 3355E-08	6 0268E-08	3 4755E-08
	VEL Y	4 8892E-06	4 9080E-06	4 9221E-06	4 8834E-06	4 9039E-06	4 9185E-06	4 8728E-06	4 8964E-06	4 9125E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 46 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
97	VEL X	3 9541E-08	1 9325E-08	2 6757E-09	3 3597E-08	1 6392E-08	2 2240E-09	2 7871E-08	1 3651E-08	1 9465E-09
	VEL Y	4 8074E-06	4 8143E-06	4 8167E-06	4 8046E-06	4 8130E-06	4 8153E-06	4 7998E-06	4 8104E-06	4 8127E-06
98	VEL X	1 3724E-06	1 7685E-06	2 1254E-06	1 9312E-06	2 7628E-06	3 4479E-06	3 5605E-06	4 7352E-06	5 5199E-06
	VEL Y	8 0537E-06	7 9896E-06	7 7377E-06	8 9028E-06	8 3408E-06	7 6121E-06	1 0047E-05	8 7631E-06	7 3760E-06
99	VEL X	7 1998E-05	8 6681E-05	9 0060E-05	6 7980E-05	8 1998E-05	8 5484E-05	6 3919E-05	7 7443E-05	8 1201E-05
	VEL Y	-9 7474E-06	-3 2239E-05	-6 0864E-05	-2 7784E-06	-2 4005E-05	-5 0548E-05	5 8732E-06	-1 3878E-05	-3 8222E-05
100	VEL X	6 2081E-05	7 5508E-05	7 8529E-05	5 5878E-05	6 8577E-05	7 1719E-05	4 9442E-05	6 1605E-05	6 5097E-05
	VEL Y	1 1339E-05	-7 8142E-06	-3 2220E-05	1 8812E-05	1 6618E-06	-2 0037E-05	2 8597E-05	1 3683E-05	-5 1946E-06
101	VEL X	8 8138E-06	3 0113E-05	5 4167E-05	7 9461E-06	2 7563E-05	5 0447E-05	6 6089E-06	2 4833E-05	4 6863E-05
	VEL Y	3 7926E-05	3 3036E-05	2 0585E-05	4 3481E-05	3 9803E-05	2 7388E-05	5 0061E-05	4 8086E-05	3 6170E-05
102	VEL X	6 8970E-07	7 8451E-07	8 5057E-07	1 0453E-06	1 1257E-06	1 1820E-06	1 5927E-06	1 6267E-06	1 6510E-06
	VEL Y	6 5633E-06	6 4035E-06	6 2080E-06	6 7747E-06	6 4809E-06	6 1448E-06	7 0221E-06	6 5580E-06	6 0430E-06
103	VEL X	4 0523E-07	4 8519E-07	5 9532E-07	6 9528E-07	8 0618E-07	9 3675E-07	1 2177E-06	1 3811E-06	1 5473E-06
	VEL Y	6 7315E-06	6 6880E-06	6 6535E-06	7 1425E-06	7 0251E-06	6 9229E-06	7 6452E-06	7 4307E-06	7 2423E-06
104	VEL X	4 4568E-07	4 1914E-07	3 9718E-07	5 2941E-07	4 6950E-07	4 1989E-07	6 0640E-07	5 1387E-07	4 3715E-07
	VEL Y	5 5650E-06	5 4812E-06	5 4184E-06	5 5290E-06	5 4396E-06	5 3739E-06	5 4737E-06	5 3782E-06	5 3094E-06
105	VEL X	3 5617E-07	2 6637E-07	2 0572E-07	3 7015E-07	2 6462E-07	1 9334E-07	3 7472E-07	2 5528E-07	1 7461E-07
	VEL Y	5 2347E-06	5 1681E-06	5 1307E-06	5 1928E-06	5 1354E-06	5 1119E-06	5 1326E-06	5 0885E-06	5 0838E-06
106	VEL X	3 9875E-07	4 2644E-07	4 4799E-07	5 3171E-07	5 3609E-07	5 3952E-07	7 0494E-07	6 8135E-07	6 6299E-07
	VEL Y	5 8607E-06	5 7800E-06	5 7004E-06	5 9143E-06	5 7955E-06	5 6773E-06	5 9673E-06	5 8021E-06	5 6372E-06
107	VEL X	1 6125E-07	1 0867E-07	6 8110E-08	1 4970E-07	9 9949E-08	6 1574E-08	1 3711E-07	9 0323E-08	5 4230E-08
	VEL Y	4 9450E-06	4 9379E-06	4 9340E-06	4 9325E-06	4 9284E-06	4 9281E-06	4 9129E-06	4 9136E-06	4 9187E-06
108	VEL X	2 4979E-07	3 1520E-07	3 6025E-07	3 5395E-07	4 3864E-07	4 9722E-07	5 3504E-07	6 2515E-07	6 8777E-07
	VEL Y	6 0620E-06	6 0214E-06	5 9600E-06	6 2199E-06	6 1406E-06	6 0378E-06	6 3992E-06	6 2730E-06	6 1200E-06
109	VEL X	5 3512E-08	2 6109E-08	3 5442E-09	4 8216E-08	2 3580E-08	3 2921E-09	4 2814E-08	2 0954E-08	2 9508E-09
	VEL Y	4 8245E-06	4 8250E-06	4 8239E-06	4 8203E-06	4 8218E-06	4 8213E-06	4 8134E-06	4 8166E-06	4 8170E-06
110	VEL X	2 4325E-07	6 7302E-07	1 1317E-06	7 7874E-08	1 0054E-06	2 0134E-06	-2 3950E-07	1 3101E-06	2 9642E-06
	VEL Y	8 5042E-06	8 4333E-06	8 1562E-06	9 4529E-06	9 4312E-06	9 1377E-06	1 0823E-05	1 0870E-05	1 0537E-05
111	VEL X	1 1308E-05	3 5006E-05	5 9280E-05	1 0519E-05	3 3179E-05	5 7164E-05	9 3199E-06	3 1205E-05	5 5207E-05
	VEL Y	1 8846E-05	1 4386E-05	1 5333E-06	2 5395E-05	2 1450E-05	8 2484E-06	3 2842E-05	2 9711E-05	1 6424E-05
112	VEL X	6 5372E-08	1 9590E-07	3 5871E-07	1 2411E-07	3 1236E-07	5 3722E-07	2 1506E-07	4 9048E-07	8 0473E-07
	VEL Y	6 8324E-06	6 8018E-06	6 7610E-06	7 3269E-06	7 2733E-06	7 2052E-06	7 9495E-06	7 8639E-06	7 7570E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 47 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10 00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
113	VEL X	3 8072E-07	3 7288E-07	3 0293E-07	4 5373E-07	3 6597E-07	5 4998E-07	2 0547E-07		
	VEL Y	6 3927E-06	6 3103E-06	6 3322E-06	6 5456E-06	6 5393E-06	6 4999E-06	6 1656E-06		
114	VEL X	1 6562E-07	2 5283E-07	1 1824E-07	1 4751E-07	7 8638E-08	2 4597E-07	2 2262E-07		
	VEL Y	6 1932E-06	6 2361E-06	6 0644E-06	6 2847E-06	6 1245E-06	6 4313E-06	6 0377E-06		
115	VEL X	7 8571E-08	1 5291E-07	1 1463E-07	-9 1043E-09	-4 7939E-09	3 2604E-08	2 7410E-07		
	VEL Y	6 4774E-06	6 6384E-06	6 3954E-06	6 4123E-06	6 2390E-06	6 6314E-06	6 6007E-06		
116	VEL X	2 3837E-07	2 4889E-07	2 5757E-07	2 9878E-07	2 9891E-07	2 9901E-07	3 8107E-07	3 6880E-07	3 5865E-07
	VEL Y	5 5442E-06	5 5039E-06	5 4651E-06	5 5605E-06	5 5023E-06	5 4453E-06	5 5810E-06	5 5034E-06	5 4268E-06
117	VEL X	2 5204E-07	2 1533E-07	1 9053E-07	2 9542E-07	2 3773E-07	1 9875E-07	3 3389E-07	2 5616E-07	2 0366E-07
	VEL Y	5 3269E-06	5 2471E-06	5 1869E-06	5 3019E-06	5 2217E-06	5 1616E-06	5 2776E-06	5 1959E-06	5 1352E-06
118	VEL X	1 7089E-07	2 0060E-07	2 2359E-07	2 2554E-07	2 5968E-07	2 8615E-07	3 2062E-07	3 5419E-07	3 8028E-07
	VEL Y	5 6715E-06	5 6469E-06	5 6145E-06	5 7435E-06	5 6974E-06	5 6428E-06	5 8230E-06	5 7542E-06	5 6761E-06
119	VEL X	1 5691E-07	1 1011E-07	7 4007E-08	1 6245E-07	1 1261E-07	7 4171E-08	1 6347E-07	1 1118E-07	7 0848E-08
	VEL Y	5 0234E-06	4 9833E-06	4 9537E-06	5 0004E-06	4 9658E-06	4 9430E-06	4 9760E-06	4 9471E-06	4 9315E-06
120	VEL X	9 6383E-08	1 2864E-07	1 5059E-07	1 2624E-07	1 7337E-07	2 0561E-07	1 9735E-07	2 5162E-07	2 8892E-07
	VEL Y	5 7349E-06	5 7263E-06	5 7093E-06	5 8446E-06	5 8227E-06	5 7919E-06	5 9638E-06	5 9279E-06	5 8826E-06
121	VEL X	5 7941E-08	2 8155E-08	3 6283E-09	5 7153E-08	2 8055E-08	4 0947E-09	5 5451E-08	2 7130E-08	3 8089E-09
	VEL Y	4 8555E-06	4 8440E-06	4 8365E-06	4 8473E-06	4 8369E-06	4 8315E-06	4 8384E-06	4 8292E-06	4 8260E-06
122	VEL X	9 5487E-08	1 2979E-07	1 8491E-07	4 6455E-08	6 4107E-08	9 3625E-08	2 3399E-08	3 4102E-08	5 3144E-08
	VEL Y	5 7485E-06	5 8638E-06	5 9889E-06	5 7553E-06	5 8759E-06	6 0066E-06	5 7602E-06	5 8858E-06	6 0218E-06
123	VEL X	1 1487E-07	1 2614E-07	1 3541E-07	1 5151E-07	1 6419E-07	1 7463E-07	2 0099E-07	2 1390E-07	2 2454E-07
	VEL Y	5 4892E-06	5 4641E-06	5 4347E-06	5 5112E-06	5 4760E-06	5 4362E-06	5 5360E-06	5 4901E-06	5 4391E-06
124	VEL X	1 3498E-07	1 2620E-07	1 2027E-07	1 7753E-07	1 5965E-07	1 4757E-07	2 2035E-07	1 9332E-07	1 7505E-07
	VEL Y	5 3484E-06	5 2775E-06	5 2062E-06	5 3453E-06	5 2693E-06	5 1924E-06	5 3433E-06	5 2615E-06	5 1784E-06
125	VEL X	7 6589E-08	9 3288E-08	1 0614E-07	1 0429E-07	1 2618E-07	1 4306E-07	1 4336E-07	1 6901E-07	1 8884E-07
	VEL Y	5 5607E-06	5 5462E-06	5 5263E-06	5 6009E-06	5 5800E-06	5 5534E-06	5 6448E-06	5 6172E-06	5 5835E-06
126	VEL X	1 0334E-07	7 4586E-08	5 2411E-08	1 2676E-07	9 0573E-08	6 2659E-08	1 4707E-07	1 0384E-07	7 0499E-08
	VEL Y	5 0812E-06	5 0166E-06	4 9655E-06	5 0665E-06	5 0044E-06	4 9569E-06	5 0514E-06	4 9919E-06	4 9478E-06
127	VEL X	4 2379E-08	5 7681E-08	6 7967E-08	5 7716E-08	7 8645E-08	9 2783E-08	8 2858E-08	1 0751E-07	1 2425E-07
	VEL Y	5 5930E-06	5 5877E-06	5 5790E-06	5 6429E-06	5 6343E-06	5 6221E-06	5 6970E-06	5 6850E-06	5 6691E-06
128	VEL X	4 2343E-08	2 0130E-08	1 8389E-09	4 9626E-08	2 4057E-08	3 0014E-09	5 5945E-08	2 7112E-08	3 3702E-09
	VEL Y	4 8875E-06	4 8611E-06	4 8475E-06	4 8802E-06	4 8548E-06	4 8433E-06	4 8725E-06	4 8482E-06	4 8388E-06

LISTING D-6. Output Report File for Test Case Two. (Sheet 48 of 48)

SAMPLE PROBLEM, FLOW AROUND A HEATED CANNISTER

RESULTS FOR VELOCITY (M/YR) OF YEAR 10.00

ELEMENT		GSS PNT 1	GSS PNT 2	GSS PNT 3	GSS PNT 4	GSS PNT 5	GSS PNT 6	GSS PNT 7	GSS PNT 8	GSS PNT 9
129	VEL X	4.1871E-08	5.8084E-08	7.8800E-08	2.0664E-08	2.8301E-08	3.8414E-08	9.9494E-09	1.3659E-08	1.9106E-08
	VEL Y	5.5999E-06	5.6512E-06	5.7067E-06	5.6036E-06	5.6561E-06	5.7129E-06	5.6060E-06	5.6596E-06	5.7176E-06
130	VEL X	1.0633E-08	1.1856E-08	1.2859E-08	4.9058E-08	5.4393E-08	5.8772E-08	9.0513E-08	9.9714E-08	1.0728E-07
	VEL Y	5.4672E-06	5.4404E-06	5.4079E-06	5.4756E-06	5.4456E-06	5.4097E-06	5.4854E-06	5.4521E-06	5.4126E-06
131	VEL X	1.3813E-08	1.3072E-08	1.2572E-08	6.0608E-08	5.7451E-08	5.5317E-08	1.0636E-07	1.0099E-07	9.7357E-08
	VEL Y	5.3594E-06	5.2847E-06	5.1980E-06	5.3597E-06	5.2831E-06	5.1937E-06	5.3609E-06	5.2820E-06	5.1897E-06
132	VEL X	7.1111E-09	8.7994E-09	1.0092E-08	3.2659E-08	4.0017E-08	4.5661E-08	5.9915E-08	7.2743E-08	8.2605E-08
	VEL Y	5.5205E-06	5.5066E-06	5.4878E-06	5.5334E-06	5.5181E-06	5.4976E-06	5.5480E-06	5.5312E-06	5.5090E-06
133	VEL X	1.1336E-08	8.3051E-09	5.9674E-09	4.8954E-08	3.5681E-08	2.5443E-08	8.4501E-08	6.1252E-08	4.3320E-08
	VEL Y	5.1153E-06	5.0315E-06	4.9622E-06	5.1102E-06	5.0271E-06	4.9590E-06	5.1053E-06	5.0226E-06	4.9557E-06
134	VEL X	3.8021E-09	5.3389E-09	6.3587E-09	1.7815E-08	2.4490E-08	2.8942E-08	3.3468E-08	4.4934E-08	5.2620E-08
	VEL Y	5.5431E-06	5.5380E-06	5.5301E-06	5.5583E-06	5.5525E-06	5.5437E-06	5.5753E-06	5.5687E-06	5.5590E-06
135	VEL X	4.7136E-09	2.3158E-09	3.4133E-10	2.0447E-08	9.8645E-09	1.1508E-09	3.5477E-08	1.6779E-08	1.3819E-09
	VEL Y	4.9093E-06	4.8689E-06	4.8525E-06	4.9064E-06	4.8661E-06	4.8509E-06	4.9033E-06	4.8632E-06	4.8493E-06
136	VEL X	3.7762E-09	1.7458E-08	3.2083E-08	1.9475E-09	8.8549E-09	1.6045E-08	9.5869E-10	4.3218E-09	7.8138E-09
	VEL Y	5.5467E-06	5.5622E-06	5.5795E-06	5.5500E-06	5.5658E-06	5.5834E-06	5.5523E-06	5.5683E-06	5.5861E-06

This page intentionally left blank.

APPENDIX E

DIAGNOSTIC MESSAGES

The MAGNUM-2D computer code has evolved to the current version (3.1) over a number of years and has been tested with a variety of problems. It is therefore expected to provide trouble-free operation. However, for a computer program of such complexity, it is possible that difficulties may be encountered in its application. Moreover, any such problems are likely to arise from a lack of familiarity with the various features and input formats. Hence, MAGNUM-2D has the additional capability of diagnosing some possible input errors and a few run-time errors and generating appropriate warning/error messages.

The possible diagnostic messages as printed by MAGNUM-2D are reproduced in Table E-1 along with possible causes and/or corrective user action. Furthermore, since the input to MAGNUM-2D is in fixed format, the foremost remedial action is simply an exhaustive search of the inputs for incorrect data formatting. If unresolvable difficulties are encountered in the application of MAGNUM-2D to a well-posed problem, please contact the authors.

TABLE E-1: MAGNUM-2D Diagnostics. (Sheet 1 of 4)

MESSAGE	CAUSE/CORRECTIVE ACTION
<p>I) PROGRAM CONTROL (CARD TYPES B, C, D)</p> <p>THE TEMPERATURE INPUT OPTION REQUIRES THAT A TEMPERATURE INPUT FILE BE SPECIFIED. ERROR STOP IN ROUTINE INPUTS.</p> <p>BOTH TEMPERATURE AND MOISTURE ARE INACTIVE. ERROR STOP IN ROUTINE INPUTS.</p> <p>TOO MANY NODES REQUESTED. LIMIT IS n. ERROR STOP IN ROUTINE INPUTS.</p> <p>TOO MANY ELEMENTS REQUESTED. LIMIT IS n. ERROR STOP IN ROUTINE INPUTS.</p> <p>TOO MANY MATERIAL TYPES REQUESTED. LIMIT IS n. ERROR STOP IN ROUTINE INPUTS.</p> <p>**WARNING: THE INTEGRATION CONSTANT ** * IS OUT OF THE SUGGESTED RANGE (1 TO 2)*</p>	<p>The temperature input file option has been selected, but no logical unit for the temperature input file has been specified.</p> <p>Neither heat transfer nor fluid flow has been selected.</p> <p>Either decrease the problem size or increase the node limit (MAXP).</p> <p>Either decrease the problem size or increase the element limit (MAXE).</p> <p>Either decrease the problem size or increase the material type limit (MAXMAT).</p> <p>Check the value of the integration constant echoed in the report file.</p>
<p>II) TIME STEPS (CARD TYPE E)</p> <p>TOO MANY TIME STEPPING DEFINITION CARDS ARE PRESENT IN THE INPUT DATA FILE. THE PROGRAM LIMIT IS n. ERROR STOP IN ROUTINE INPUTS.</p>	<p>Decrease the number of time step cards or increase the limit (NTT). Terminator card may have been omitted.</p>
<p>III) GEOMETRY INPUT (CARD TYPES G, H, OR EXTERNAL FILE)</p> <p>GEOMETRY HAS n NODES. THIS DOES NOT EQUAL THE NUMBER GIVEN IN THE PROBLEM SPECIFICATIONS DATA. ERROR STOP IN ROUTINE INPUTS.</p> <p>GEOMETRY HAS n ELEMENTS. THIS DOES NOT EQUAL THE NUMBER GIVEN IN THE PROBLEM SPECIFICATION DATA. ERROR STOP IN ROUTINE INPUTS.</p> <p>THE CHOICE OF AXISYMMETRIC COORDINATES IS INCOMPATIBLE WITH THE GEOMETRY. MINIMUM $x < 0$. ERROR STOP IN ROUTINE INPUTS.</p> <p>ERROR AT ELEMENT m MATERIAL TYPE n IS OUT OF RANGE. ERROR STOP IN ROUTINE INPUTS.</p> <p>ERROR IN THE ORDERING ARRAY, ELEMENT n DOES NOT APPEAR. ERROR STOP IN ROUTINE INPUTS.</p>	<p>The number of nodes, n, in the geometry input does not equal the number specified on card type B.</p> <p>The number of elements, n, in the geometry input does not equal the number specified on card type B.</p> <p>For an axisymmetric radial coordinate system the axis of symmetry is the line $x = 0$, and hence, all x-coordinates should be nonnegative.</p> <p>For element number m the material type index n is greater than the number of material types specified in card type B.</p> <p>Element number n is not assigned an ordering index in card type G.</p>

TABLE E-1: MAGNUM-2D Diagnostics. (Sheet 2 of 4)

MESSAGE	CAUSE/CORRECTIVE ACTION
<p>IV) INITIAL CONDITIONS (CARD TYPES J1, J2, AND EXTERNAL FILE)</p> <p>THE RESTART FILE HAS m1 NODES AND n1 RECORDS THE CURRENT PROBLEM HAS m2 NODES AND n2 RECORDS CHANGING THESE NUMBERS IS NOT PERMITTED ON RESTART ERROR STOP IN ROUTINE INPUTS</p> <p>ERROR IN THE INITIAL CONDITION INPUT, NODE n IS OUT OF RANGE * ERROR STOP IN ROUTINE INPUTS</p> <p>ERROR IN THE INITIAL CONDITION INPUT, NODE n DOES NOT GET INITIALIZED ERROR STOP IN ROUTINE INPUTS</p>	<p>The restart file contains problem size specifications that are incompatible with those contained in card type B</p> <p>Node number n is assigned initial values, but does not exist in the problem geometry</p> <p>Initial conditions are being input on a nodal basis (Eq 11), but no initial values are assigned to node number n</p>
<p>V) BOUNDARY CONDITIONS (CARD TYPES K1, K2)</p> <p>TOO MANY BOUNDARY NODES, m REQUESTED, PROBLEM ONLY HAS n NODES ERROR STOP IN ROUTINE INPUTS</p> <p>ERROR IN BOUNDARY CONDITIONS, NODE n IS OUT OF RANGE ERROR STOP IN ROUTINE INPUTS</p> <p>ERROR IN BOUNDARY CONDITIONS, NODE m IS A DUPLICATE, LINE n OF BOUNDARY NODE LIST ERROR STOP IN ROUTINE INPUTS</p> <p>** WARNING ELEMENT n CONSISTS SOLELY ** * OF SPECIFIED NODES *</p>	<p>The number, m, of specified boundary conditions exceeds the total number, n, of nodes</p> <p>Node number n is assigned a boundary value, but does not exist in the problem geometry</p> <p>Node number m is twice assigned a boundary value for one transport variable</p> <p>All nodal values in element n are fixed and will not change during the simulation</p>
<p>VI) MATERIAL PROPERTIES (CARD TYPE M)</p> <p>ERROR IN ROCK PROPERTIES INPUT, MATERIAL TYPE n IS OUT OF RANGE ERROR STOP IN ROUTINE INPUTS</p> <p>ERROR IN ROCK PROPERTIES INPUT, ELEMENT m, MATERIAL TYPE n NO MATERIAL PROPERTY DATA HAS BEEN READ FOR THIS MATERIAL TYPE ERROR STOP IN ROUTINE INPUTS</p> <p>**WARNING LINE ELEMENTS OF ZERO FRACTURE WIDTH HAVE BEEN FOUND THESE ** **ELEMENT WIDTHS WILL BE SET TO UNITY **</p> <p>ERROR IN ROCK PROPERTIES INPUT CONTINUUM ELEMENT NUMBER m HAS NON-ZERO FRACTURE WIDTH ERROR STOP IN ROUTINE INPUTS</p>	<p>Material type number n is greater than the number of material types specified on card type B</p> <p>Element number m is assigned a nonexistent material type</p> <p>The default fracture aperture for a line element is one length unit</p> <p>Fracture aperture has no meaning for a two-dimensional element (cf card type M)</p>

TABLE E-1: MAGNUM-2D Diagnostics. (Sheet 3 of 4)

MESSAGE	CAUSE/CORRECTIVE ACTION
<p>VII) GEOMETRY FILE READ ERRORS</p> <p>ERROR READING GEOMETRY FILE HEADER RECORD. ERROR STOP IN ROUTINE INPUTS.</p> <p>ERROR READING GEOMETRY ELEMENT RECORDS. ERROR STOP IN ROUTINE INPUTS.</p> <p>ERROR READING GEOMETRY NODE COORDINATES. ERROR STOP IN ROUTINE INPUTS.</p>	<p>A read error or EOF occurred while reading the geometry file header record.</p> <p>A read error or EOF occurred while reading the geometry file connectivity records.</p> <p>A read error or EOF occurred while reading the geometry file nodal coordinate records.</p>
<p>VIII) HEAT SOURCE (CARD TYPE P, R1, R2)</p> <p>ERROR, m HEAT SOURCE ELEMENTS EXCEEDS PROGRAM MAXIMUM OF n. ERROR STOP IN ROUTINE LOADQ.</p> <p>ERROR, m THERMAL LOAD POINTS EXCEED THE PROGRAM MAXIMUM OF n. ERROR STOP IN ROUTINE LOADQ.</p> <p>** WARNING: THERMAL LOADS ARE SET TO ** * ZERO FOR STEADY STATE RUNS. *</p>	<p>Either decrease the number of heat source elements or increase the program limit (MAXH).</p> <p>Either decrease the number of points defining the source profile or increase the program limit (MAXT).</p> <p>Heat source options may not be used with steady-state runs. (cf. Section 3.5).</p>
<p>IX) TEMPERATURE INPUT FILE ERRORS</p> <p>ERROR, n COMPONENTS ON TEMPERATURE INPUT FILE. INPUT REQUIRES ONLY ONE COMPONENT ON THIS FILE. ERROR STOP IN ROUTINE HEADR.</p> <p>ERROR, m DATA POINTS ON TEMPERATURE INPUT FILE. INPUT REQUIRES n NODES TO MATCH CURRENT GEOMETRY SIZE. ERROR STOP IN ROUTINE HEADR.</p> <p>**WARNING: TEMPERATURE INPUT FILE HAS ** * MOISTURE DATA ON IT, OR WAS NOT GENER-* **ATED BY MAGNUM-2D **</p> <p>ERROR OR END OF FILE ENCOUNTERED AT TEMPERATURE INPUT FILE HEADER READ. ERROR STOP IN ROUTINE HEADR.</p> <p>THE INPUT TEMPERATURE FILE BEGINS AT TIME x, WHICH EXCEEDS THE SIMULATION INITIAL TIME. ERROR STOP IN MAIN ROUTINE.</p> <p>THE INPUT TEMPERATURE FILE ENDS AT TIME x, AFTER READING n RECORDS. ERROR STOP IN MAIN ROUTINE.</p> <p>ERROR READING TEMPERATURE FILE AT TIME x, AFTER READING n RECORDS. ERROR STOP IN MAIN ROUTINE.</p>	<p>The temperature input file must contain temperature data only.</p> <p>There must be a one-to-one correspondence between the number of nodal temperatures in the temperature input file and the number of nodes in the current geometry.</p> <p>The temperature input file header does not correspond to the expected format.</p> <p>A read error or EOF occurred while reading the temperature input file header record.</p> <p>The temperature input file contains data for times that do not correspond to current simulation times.</p> <p>The temperature file ends prematurely.</p> <p>Read error occurred while reading data records from the temperature input file.</p>

TABLE E-1: MAGNUM-2D Diagnostics. (Sheet 4 of 4)

MESSAGE	CAUSE/CORRECTIVE ACTION
<p>X) EXECUTION ERRORS</p> <p>NO ACTIVE ELEMENTS FOUND IN GEOMETRY. ERROR STOP IN ROUTINE SETUP.</p> <p>ERROR IN NODE SEQUENCING. m NODES PERMITTED. TWICE THAT NUMBER OF EQUATIONS ARE PERMITTED. n EQUATIONS HAVE BEEN SET UP FOR THIS PROBLEM. ERROR STOP IN ROUTINE SETUP.</p> <p>TEMPERATURE INPUT TO FPROP IS OUT OF RANGE AT NODE m, TEMPERATURE IS x. ALLOWABLE RANGE IS FROM y TO z. SIMULATION TIME IS t. ERROR STOP IN ROUTINE FPROP.</p> <p>NELL = m IS GREATER THAN MAXE (= n). ERROR STOP IN ROUTINE FRONT.</p> <p>LCOL = m, NELL = n. THE DIFFERENCE (NMAX-NCRIT) IS NOT SUFFICIENTLY LARGE TO PERMIT THE ASSEMBLY OF THE NEXT ELEMENT. EITHER INCREASE NMAX OR LOWER NCRIT. (POSSIBLE GEOMETRY BANDWIDTH/ORDERING ERROR). ERROR STOP IN ROUTINE FRONT.</p> <p>END OF FILE ENCOUNTERED ON FILE n. ERROR STOP IN ROUTINE RED.</p> <p>WARNING: MATRIX SINGULAR OR ILL-CONDITIONED, x IS LESS THAN y, EQUATION NUMBER m. ERROR IN FRONT AT LOCATION n. ERROR STOP IN ROUTINE FRONT.</p> <p>BINARY READ SIZE ERROR. ROUTINE BININ MUST BE MODIFIED SO THAT m OR MORE RECORDS CAN BE READ AT ONCE. ERROR STOP IN ROUTINE BININ.</p> <p>BINARY WRITE ERROR. ROUTINE BINOUT MUST BE MODIFIED SO THAT m OR MORE RECORDS CAN BE WRITTEN AT ONCE. ERROR STOP IN ROUTINE BINOUT.</p>	<p>Every node is a boundary node.</p> <p>Array storage is overutilized by the solver. Check geometry and especially the element ordering.</p> <p>Empirical relations employed in updating temperature-dependent material properties are only valid in the indicated range.</p> <p>Possible incompatibility between element connectivity and element ordering.</p> <p>The frontwidth requires adjustment to arrange storage as indicated, or optimization of element ordering.</p> <p>An EOF occurred while reading the scratch file used by the solver.</p> <p>Either the material properties are zero or highly contrasting.</p> <p>Direct I/O block size is not large enough for scratch file.</p> <p>Direct I/O block size is not large enough for scratch file.</p>

This page intentionally left blank.

DISTRIBUTION

Number of copies

OFFSITE

1	<u>Analytical and Computational Research, Inc.</u> A. K. Runchal
1	<u>Analytical Sciences Corporation</u> J. W. Bartlett
3	<u>Atomic Energy of Canada Research Company</u> R. B. Lyon E. L. J. Rosinger B. J. S. Wilkins
7	<u>Battelle-Office of Nuclear Waste Isolation</u> S. Gupta P. L. Hofmann Library (5)
1	<u>BCS Seattle, Inc.</u> K. J. Ekblad
1	<u>Commissariat a l'Energie Atomique</u> A. Barbreau
1	<u>Confederated Tribes of the Umatilla Indian Reservation</u> E. H. Patawa
1	<u>D'Appolonia Consulting Engineers, Inc.</u> J. B. Case
1	<u>Envirosphere, Inc.</u> R. Mahan
1	<u>GeoTrans, Inc.</u> P. Huyakorn

Number of copies

1	<u>Holcomb Research Institute</u> P. K. M. van der Heijde
1	<u>Institut fur Kerntechnik</u> R. Storck
1	<u>Institut fur Tieflagerung</u> E. Uerpmann
1	<u>Institute for Geological Sciences</u> N. A. Chapman
3	<u>Lawrence Berkeley Laboratory</u> T. N. Narasimhan M. Shimo Library
1	<u>Lawrence Livermore Laboratory</u> Library
3	<u>Los Alamos Scientific Laboratory</u> B. Crowe B. J. Travis Library
1	<u>Massachusetts Institute of Technology</u> L. W. Gelhar
2	<u>Montana College of Mineral Science and Technology</u> V. W. Daniel E. Van Eeckhout
1	<u>NAGRA-National Cooperative for the Storage of Radioactive Waste</u> C. McCombie
2	<u>National Radiological Protection Board</u> P. D. Grimwood M. D. Hill

Number of copies

1	<u>New Mexico Institute of Mining and Technology</u> D. B. Stephens
1	<u>Nez Perce Tribal Executive Committee of the Nez Perce Tribal Council</u> A. Pinkham
1	<u>Nuclear Energy Agency</u> P. Johnston
1	<u>Nuclear Waste Policy and Review Board</u> W. Bishop
2	<u>Office of Crystalline Repository Development</u> A. Brandstetter W. F. Ubbes
1	<u>Ontario Hydro</u> K. K. Tsui
1	<u>OTHA, Inc.</u> J. A. Lieberman
1	<u>Principia Recherche Developpement</u> P. Bardey
2	<u>Princeton University</u> G. F. Pinder Library
1	<u>Purdue University</u> D. Gray
1	<u>Resource Management Associates</u> I. P. King
1	<u>Royal Institute of Technology</u> R. Thunvik

Number of copies

2	<u>SKBF/KBS</u> F. D. B. Karlsson T. Tarandi
6	<u>Sandia Laboratories</u> R. M. Cranwell N. Ortiz R. L. Hunter L. D. Tyler J. W. Nuciato Library
2	<u>Siting/Licensing Overview Committee</u> P. Domenico F. Parker
2	<u>Stanford University</u> I. Remson Library
1	<u>State of Texas Attorney General's Office</u> M. Plaster
1	<u>Swedish Geological Company</u> A. Winberg
6	<u>U.S. Department of Energy-Headquarters</u> D. Alexander J. J. Fiore E. S. Burton M. W. Frei C. R. Cooley R. Stein
1	<u>U.S. Department of Energy- Nevada Operations Office</u> D. L. Vieth
1	<u>U.S. Department of Energy-Public Reading Room</u> Seattle, Washington
2	<u>U.S. Environmental Protection Agency</u> Headquarters Librarian Region X Librarian

Number of copies

2	<u>U.S. Geological Survey</u> D. B. Grove K. L. Kipp
11	<u>U.S. Nuclear Regulatory Commission</u> Branch Chief, High-Level Waste Technical Development Branch Branch Chief, High-Level Waste Licensing Management Branch Director, Division of Waste Management Docket Control Center-Division of Waste Management (4) M. Dunkelman D. Goode M. Gordon Library
5	<u>University of Arizona</u> D. R. Davis S. N. Davis L. S. Leonhart S. P. Neuman Library
1	<u>University of California, Berkeley</u> T. H. Pigford
1	<u>University of Waterloo</u> E. O. Frind
4	<u>Washington State Department of Ecology</u> A. Beatty Riniker D. O. Provost J. Rensel D. W. Stevens
2	<u>Washington State Department of Natural Resources</u> B. J. Boyle Library

Number of copies

1	<u>Washington State Department of Social & Health Services</u> K. Rahm
1	<u>Washington State Energy Facility Site Evaluation Council</u> C. Eschels
1	<u>Washington State Energy Office</u> R. H. Watson
1	<u>Washington State House of Representatives Energy and Utilities Committee</u>
1	<u>Washington State Joint Legislative Committee on Science and Technology</u>
1	<u>Washington State Library</u> Documents Section
1	<u>Washington State Senate Energy and Utilities Committee</u>
5	<u>Washington State University</u> L. C. Chow W. H. Funk A. H. Marcus E. P. Poeter Science and Engineering Library
2	<u>Weston Designer Consultants</u> W. L. Lee L. Rickertsen
4	<u>Yakima Indian Nation</u> J. B. Hovis L. Lehman Tribal Council (2)

Number of copies

ONSITE

18	<u>BCS Richland, Inc.</u> D. R. Aichele N. W. Kline (10) C. Bromley D. W. Langford R. B. Doggett J. J. Ratcliffe R. L. England RLSEC S. A. Estey
1	<u>Joint Center for Graduate Study</u> W. Kinsel
11	<u>Pacific Northwest Laboratory</u> M. K. Altenhoffen B. Kuhn M. J. Budden R. W. Nelson H. C. Burkholder A. E. Reisenauer C. R. Cole S. C. Sneider F. H. Dove Library L. L. Eyler
2	<u>U.S. Department of Energy-Public Reading Room</u> Richland, Washington
3	<u>U.S. Department of Energy-</u> <u>Richland Operations Office</u> A. J. Knepp P. E. Lamont O. L. Olson
40	<u>Rockwell Hanford Operations</u> E. B. Ash A. H. Lu R. C. Arnett J. Ludwick (2) R. G. Baca S. P. Luttrell M. S. Bensky C. F. McLane Y. Chien D. L. Oliver P. M. Clifton B. Sagar E. A. Fredenburg D. H. Sandoz R. E. Gephart J. C. Sonnichsen J. Graham S. C. Yung Basalt Waste Isolation Project Library (15) Document Control (2) Publications Services Department-Station 2 (2) Records Retention (2)

Number of copies

1

UNC

W. D. Wittekind