50

3 3679 00047 1864

Hydrogeology of the 200 Areas Low-Level Burial Grounds—An Interim Report

Volume 2: Appendixes

G. V. Last	J. A. Schramke
B. N. Bjornstad	M. A. Chamness
M. P. Bergeron	C. S. Cline
D. W. Wallace	S. P. Airhart
D. R. Newcomer	J. S. Wilbur

January 1989

Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute

DISCLAIMER

This program was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America
Available from
National Technical Information Service
United States Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161

NTIS Price Codes
Microfiche A01

Printed Copy

Pages	Price Codes
001-025	A02
026-050	A03
051-075	A04
076-100	A05
101-125	A06
126-150	A07
151-175	A08
176-200	A09
201-225	A10
226-250	A11
251-275	A12
276-300	A13

HYDROGEOLOGY OF THE 200 AREAS
LOW-LEVEL BURIAL GROUNDS--AN
INTERIM REPORT

Volume 2: Appendixes

G. V. Last	J. A. Schramke
B. N. Bjornstad	M. A. Chamness
M. P. Bergeron	C. S. Cline
D. W. Wallace	S. P. Airhart
D. R. Newcomer	J. S. Wilbur

January 1989

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

PREFACE

This report presents information derived from the installation of 35 ground-water monitoring wells around six low-level radioactive/hazardous waste burial grounds located in the 200 Areas of the Hanford Site in southeastern Washington State. This information was collected between May 20, 1987 and August 1, 1988.

The contents of this report have been divided into two volumes. Volume 1 contains the main text. This Volume contains the appendixes, including data and supporting information that verify content and results found in the main text.

VOLUME 2 CONTENTS

PREFACE	iii
APPENDIX A - DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES FOR EXISTING BOREHOLES NEAR THE 200 AREAS LOW-LEVEL BURIAL GROUNDS	A.1
APPENDIX B - WELL CONSTRUCTION SUMMARIES FOR 200-EAST AREA WELLS	B.1
APPENDIX C - WELL CONSTRUCTION SUMMARIES FOR 200-WEST AREA WELLS	C.1
APPENDIX D - ANALYTICAL RESULTS FOR THE PREDEVELOPMENT AND AQUIFER TESTS OF GROUND-WATER SAMPLES	D.1
APPENDIX E - AQUIFER TESTING OF WELLS IN THE 200-EAST AREA	E.1
APPENDIX F - AQUIFER TESTING OF WELLS IN THE 200-WEST AREA	F.1
APPENDIX G - SURVEY REPORTS FOR GROUND-WATER MONITORING WELLS AROUND WASTE MANAGEMENT AREAS 1, 2, 3, AND 4.	G.1
APPENDIX H - PROCEDURE, WATER-LEVEL DATA, AND HYDROGRAPHS	H.1
APPENDIX I - FIELD MOISTURE CONTENT OF CORE-BARREL SAMPLES FROM WELLS IN THE 200-EAST AND 200-WEST AREAS	I.1
APPENDIX J - PARTICLE-SIZE AND CALCIUM CARBONATE DATA FOR 200-EAST AREA WELLS	J.1
APPENDIX K - PARTICLE-SIZE AND CALCIUM CARBONATE DATA FOR 200-WEST AREA WELLS	K.1
APPENDIX L - BOREHOLE GEOPHYSICAL LOGGING PROCEDURES	L.1

APPENDIX A

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES
FOR EXISTING BOREHOLES NEAR THE 200 AREAS LOW-LEVEL BURIAL GROUNDS

APPENDIX A

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES FOR EXISTING BOREHOLES NEAR THE 200 AREAS LOW-LEVEL BURIAL GROUNDS

This appendix provides inventories of the data available for existing boreholes within 1,000 ft of the waste management areas (WMAs) that comprise the 200 Areas low-level burial grounds. In addition, a few selected wells beyond the 1,000-ft perimeter are included where the data were of exceptional quality and/or location was of strategic importance. Previously existing wells in WMA-1 and WMA-2 are located on Figure A.1, while those for WMA-3 and WMA-4 are located on Figure A.2.

Only those wells with a complete data set and/or that were strategically located were selected for direct use in developing cross sections and contour maps. The selected wells are identified in the inventory tables. A summary of the lithologic descriptions recorded on drill logs for the selected wells, as well as the interpreted stratigraphy, is also presented. For various reasons, not all the wells located within 1,000 ft of the WMAs were in the interpretation of the geology. Wells not used and the reasons(s) for excluding them are listed in Table A.1.

This appendix is organized by WMA. A data inventory table for existing wells near each WMA is followed by lithologic log summaries for the selected wells near that WMA. All listings are in feet. A list of the symbols used in this appendix follows.

SYMBOLS USED IN THIS APPENDIX

- (a) Determined in this study
- (b) From drill logs on file with Geosciences Department, Pacific Northwest Laboratory
- (c) Determined by Bjornstad (1984)
- (d) From core logs documented by Fenix and Scisson, Inc. (1976)
- (e) Determined by Strait and Moore (1982)
- (f) From Fecht and Lillie (1982)
- (g) From core logs documented by Webster (1977)
- (h) From Jackson et al. (1984)

FIGURE A.1. Location of Previously Existing Versus New Wells Near Waste Management Areas 1 and 2

FIGURE A.2. Location of Previously Existing Versus New Wells Near Waste Management Areas 3 and 4

TABLE A.1. Wells Located Within 1,000 Feet of Waste Management Areas Not Used in Geologic Interpretation

<u>Waste Management Area</u>	<u>Well Number</u>	<u>Reason for Exclusion</u>
1	299-E33-10	2
	299-E33-24	2
2	299-E34-1	5
3	299-W10-5	1, 3
	299-W10-8	1, 3
3	299-W10-9	1, 3
	299-W10-10	1, 3
	299-W10-11	1, 3
	299-W10-12	1, 2, 3
4	299-W15-10	1, 2
	299-W15-11	1, 2
	299-W18-2	1, 2
	299-W18-3	2, 3
	299-W18-4	1, 2
	299-W18-5	1, 3
	299-W18-6	1, 2
	299-W18-7	1
	299-W18-8	1, 2, 3, 4
	299-W18-9	1, 5
	299-W18-10	1, 2
	299-W18-11	1
	299-W18-12	1, 2, 4
	299-W18-19	1, 2, 3
	299-W18-20	1, 2, 3
	299-W23-4	1, 2
	299-W23-8	1, 2
	299-W23-9	1
	299-W23-10	1
	299-W23-11	1

1 = Shallow depth.

2 = Lacking sieve data.

3 = No natural-gamma log.

4 = No drill log.

5 = Close to well(s) with better quality data.

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES
FOR EXISTING 200-EAST AREA WELLS
NEAR WASTE MANAGEMENT AREA 1

DATA AVAILABLE FOR EXISTING WELLS NEAR WASTE MANAGEMENT AREA 1

<u>Well Number</u>	<u>Drill Method</u>	<u>Depth to Water</u>	<u>Total Depth</u>	<u>Sieve Data</u>	<u>Natural- Gamma Logs</u>	<u>Drill Logs</u>	<u>Used in Interp.</u>	<u>Comments</u>
299-E28-9	Cable tool	296.0	350.0	yes	yes	yes	yes	
299-E28-20	Cable tool	285.0	330.0	0-305'	yes	yes	yes	
299-E32-1	Cable tool	255.0	283.0	yes	no	yes	yes	
299-E33-5	Cable tool	222.0	238.0	20-236'	yes	yes	yes	
299-E33-8	Cable tool	246.0	257.0	yes	yes	yes	yes	
299-E33-10	Cable tool	267.0	290.0	no	yes	yes	no	
299-E33-21	Cable tool	262.0	282.0	80-260'	yes	yes	yes	
299-E33-24	Cable tool	233.0	256.0	no	yes	yes	no	
299-E33-26	Cable tool	229.0	240.0	yes	yes	yes	yes	

Well Number	299-E28-9
Plant Coordinates	N 46352, W 53523
Casing Elevation	628.90

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sand, Silt.	5	5
Hanford formation @ 5 ft	Fine Gravel, Sand, Silt.	10	15
	Coarse Sand, Silt.	30	45
	Gravel, Coarse Sand, Silt.	30	75
	Brown Sand, Silt.	15	90
	Gray Sand, Silt.	5	95
	Gray Sand, Less Silt.	10	105
	Gray Coarse Sand, Silt.	65	170
	Brown Fine Sand, Silt.	20	190
	Gravel, Gray Coarse Sand, Silt.	10	200
	Gray Coarse Sand, Silt.	35	235
	Gravel, Sand, Silt.	10	245
	Cemented Gravel.	5	250
	Cobbles, Gravel.	10	260
	Fine Gravel.	10	270
	Cemented Gravel.	5	275
	Medium Gravel.	5	280
	Coarse Gravel.	15	295
	Cemented Gravel.	5	300
	Gravel, Fine Sand.	5	305
	Cobbles, Gravel, Sand.	10	315
	Gravel, Sand.	10	325
	Cemented Gravel and Sand.	15	340
	Brown Cemented Sand and Gravel.	10	350

Well Number	299-E28-20
Plant Coordinates	N 43705, W 55188
Casing Elevation	690.29

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Gravel, Sand.	35	35
	Sand.	155	190
	Gravel, Sand.	5	195
	Sand.	10	205
	Gravel, Sand.	5	210
	Sand.	10	220
	Gravel, Sand.	90	310
	Gravel, Silt.	5	315
	Gravel, Sand, Silt.	10	325
	Sand.	5	330

Well Number	299-E32-1
Plant Coordinates	N 46488, W 56684
Casing Elevation	656.17

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Boulders, Gravel, Sand.	5	5
	Boulders, Gravel.	5	10
	Boulders, Gravel, Sand.	10	20
	Coarse Gravel, Sand.	10	30
	Cobbles, Gravel, Silt.	10	40
	Coarse Gravel, Sand.	5	45
	Fine to Coarse Sand.	10	55
	Coarse Sand.	10	65
	Gravel, Coarse Sand.	15	80
	Coarse Sand.	10	90
	Gravel, Coarse Sand.	5	95
	Coarse Sand.	10	105
	Sand, Silt.	30	135
	Sand, Little Silt.	35	170
	Fine Sand, Little Silt.	25	195
	Small Gravel, Coarse Sand.	5	200
	Coarse Gravel, Sand.	5	205
	Small to Coarse Gravel.	15	220
	Gravel.	45	265
	Gravel, Sand.	5	270
Basalt @ 272 ft	Basalt.	13	283

Well Number	299-E33-5
Plant Coordinates	N 46352, W 53523
Casing Elevation	628.90

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
	Backfill	20	20
Hanford formation	Gravel, Sand.	20	70
	Sand, Some Silt.	25	95
	Sand.	80	175
	Gravel, Sand, Silt.	10	185
	Gravel.	35	220
	Gravel, Sand.	16	236
Basalt @ 236 ft	Basalt.	2	238

Well Number	299-E33-8
Plant Coordinates	N 45840, W 53850
Casing Elevation	648.03

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Boulders, Gravel, Sand.	10	10
	Coarse Gravel, Sand.	10	20
	Coarse Gravel.	5	25
	50% Coarse Gravel, 50% Sand.	5	30
	15% Coarse Gravel, 85% Sand.	5	35
	Coarse Sand.	10	45
	Fine to Coarse Gravel, Coarse Sand.	5	50
	50% Fine to Medium Gravel, 50% Coarse Sand.	5	55
	Gravel, Sand, Little Silt.	5	60
	Sand, Little Silt.	25	85
	Boulders, Sand, Little Silt.	5	90
	Sand, Little Silt.	5	95
	Sand, Very Little Silt.	60	155
	Coarse Sand.	5	160
	Sand, Very Little Silt.	35	195
	Sand, Silt.	5	200
	Coarse Sand.	5	205
	Fine to Coarse Gravel.	10	215
	50% Fine to Coarse Gravel, 50% Coarse Sand.	10	225
	Fine to Coarse Gravel.	30	255
Basalt @ 257 ft	Basalt.	2	257

Well Number	299-E33-21
Plant Coordinates	N 45321, W 53856
Casing Elevation	663.43

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Cobbles, Gravel, Sand, Silt.	10	10
	Boulders, Cobbles, Gravel, Sand.	5	15
	Cobbles, Gravel, Sand.	5	20
	Cobbles, Gravel.	20	45
	Coarse Sand.	25	70
	Sand, Little Silt.	20	90
	Coarse Sand.	45	135
	Fine to Coarse Sand.	15	150
	Sand.	10	160
	Sand, Little Silt.	20	180
	Fine to Coarse Sand.	5	185
	Gravel, Sand.	10	195
	Gravel, Coarse Sand.	10	205
	Coarse Sand, Little Silt.	10	215
	Sand, Little Silt.	5	220
	Gravel, Sand, Silt.	20	240
	Cobbles, Coarse Gravel.	5	245
	Small Gravel.	5	250
	Gravel, Sand.	10	260
	Coarse Gravel, Sand.	10	270
	Cobbles, Gravel, Sand.	7	277
Basalt @ 279 ft	Basalt.	5	282

Well Number	299-E33-26
Plant Coordinates	N 46600, W 54315
Casing Elevation	632.82

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Cobbles, Gravel.	5	5
	Boulders, Cobbles, Gravel.	5	10
	Boulders, Gravel.	15	25
	Few Cobbles, Sand.	5	30
	Silt Stringer, Gravel, Sand.	5	35
	Gravel, Sand.	5	40
	Pea Gravel, Sand.	5	45
	Sand, Little Gravel.	20	65
	Sand, Silt.	25	90
	Sand.	30	110
	Sand, Silt.	15	125
	Sand.	10	135
	Pea Gravel, Sand.	15	150
	Cobbles, Gravel, Sand.	50	200
	Gravel, Sand.	30	230
	Cobbles, Gravel, Sand.	5	235
Basalt @ 239 ft	Basalt.	5	240

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES
FOR EXISTING 200-EAST AREA WELLS
NEAR WASTE MANAGEMENT AREA 2

DATA AVAILABLE FOR EXISTING WELLS NEAR WASTE MANAGEMENT AREA 2

<u>Well Number</u>	<u>Drill Method</u>	<u>Depth to Water</u>	<u>Total Depth</u>	<u>Sieve Data</u>	<u>Natural- Gamma Logs</u>	<u>Drill Logs</u>	<u>Used in Interp.</u>	<u>Comments</u>
299-E26-1	Cable tool	216.0	248.0	yes	yes	yes	yes	
299-E34-1	Cable tool	228.0	245.0	yes	yes	yes	no	Very close to 299-E34-2
699-47-50	Cable tool		295.0	no	yes	yes	yes	Fecht and Lillie (1982) Strait and Moore (1982)
699-47-51	Cable tool	Dry	167.0	no	yes	yes	yes	Fecht and Lillie (1982)

Well Number 299-E26-1
Plant Coordinates N 44774, W 48025
Casing Elevation 617.25

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Gravel, Sand.	10	10
	Boulders, Gravel.	15	25
	Boulders, Gravel, Sand.	10	35
	Gray Sand.	5	40
	Boulders, Gravel, Sand.	15	55
	Gravel, Sand.	10	65
	Boulders, Gravel, Sand.	10	75
	Gravel, Coarse Sand.	5	80
	Boulders Gravel Sand.	10	90
	Sand, Clay.	35	125
	Coarse Sand, Clay.	5	130
	Fine Gravel, Coarse Sand.	5	135
	Hard Fine Sand.	3	138
	Boulders, Gravel, Sand.	4	142
	Gray Sand.	8	150
	Gravel, Sand.	10	160
	Boulders, Gravel, Sand.	10	170
	Gravel, Sand.	5	175
	Boulders, Gravel.	10	185
	Fine Black Sand.	5	185
	Gravel, Black Sand.	5	190
	Boulders, Gravel, Sand.	10	200
	Gray Sand.	5	205
	Boulders, Gravel, Sand.	5	210
	Gray Sand.	3	213
	Fine Gravel, Coarse Sand.	9	222
	Red-Brown Volcanic Ash.	8	230
Basalt @ 225 ft	Basalt.	10	240
	Black Sand.	1	241
	Basalt.	7	248

Well Number 699-47-50
Plant Coordinates N 47266, W 49508
Casing Elevation 583.87

Stratigraphy(e)	Lithologic Description(b, f)	Thickness	Depth
Hanford formation	60% Gravel, 20% Coarse Sand, 20% Fine Sand.	5	5
	60% Gravel, 30% Medium Sand, 10% Fine Sand.	10	15
	60% Gravel, 20% Medium Sand, 10% Fine Sand, 10% Silt.	10	25
	60% Gravel, 10% Medium Sand, 10% Fine Sand, 20% Silt.	8	33
	50% Gravel, 20% Coarse Sand, 10% Fine Sand, 20% Silt.	2	35
	50% Gravel, 10% Coarse Sand, 40% Silt.	5	40
	60% Gravel, 10% Coarse Sand, 30% Silt.	5	45
	50% Gravel, 10% Coarse Sand, 40% Silt and Clay.	15	60
	60% Gravel, 10% Coarse Sand, 30% Silt.	10	70
	70% Gravel, 10% Coarse Sand, 20% Silt.	15	85
	60% Gravel, 10% Coarse Sand, 30% Silt.	5	90
	40% Gravel, 20% Coarse Sand, 40% Silt.	5	95
	30% Gravel, 30% Coarse Sand, 40% Silt.	5	100
	20% Gravel, 40% Coarse Sand, 40% Silt.	15	115
	30% Gravel, 30% Coarse Sand, 40% Silt.	10	125
	40% Gravel, 20% Coarse Sand, 40% Silt.	5	130
	50% Gravel, 10% Coarse Sand, 40% Silt.	10	140
	40% Gravel, 20% Coarse Sand, 40% Silt.	10	150
	60% Gravel, 10% Coarse Sand, 30% Sand.	25	175
	60% Gravel, 10% Medium Sand, 30% Silt.	5	180
	50% Gravel, 10% Medium Sand, 40% Silt.	10	190
	60% Gravel, 10% Medium Sand, 30% Silt.	10	200
	70% Gravel, 10% Sand, 20% Silt.	5	205
	55% Gravel, 20% Sand, 25% Silt.	5	210
	Black Gravel.	5	215
Elephant Mtn. Member @ 215 ft	Basalt Looks Like Black Sand.	5	220
	Basalt.	40	260
Rattlesnake Ridge inter-bed @ 260 ft	No Record (Sediments)	35	295
Basalt @ 295 ft	Basalt.	<1	295

Well Number	699-47-51
Plant Coordinates	N 47481, W 50969
Casing Elevation	583.45

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Cobbles.	5	5
	Boulders, Cobbles, Gravel.	10	15
	Heavy Gravel.	10	25
	Gravel.	25	50
	Heavy Gravel.	15	65
	Boulders.	25	90
	Gravel.	5	95
	Boulders, Gravel.	5	100
	Boulders.	10	110
	Coarse Gravel.	5	115
	Gravel.	5	120
	Boulders, Gravel.	5	125
	Gravel.	5	130
	Boulders, Gravel.	5	135
	Cobbles, Gravel.	10	145
	Boulders.	10	155
Basalt @ 159 ft	Basalt.	10	165

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES
FOR EXISTING 200-WEST AREA WELLS
NEAR WASTE MANAGEMENT AREA 3

DATA AVAILABLE FOR EXISTING WELLS NEAR WASTE MANAGEMENT AREA 3

A.23	<u>Well Number</u>	<u>Drill Method</u>	<u>Depth to Water</u>	<u>Total Depth</u>	<u>Sieve Data</u>	<u>Natural- Gamma Logs</u>	<u>Drill Logs</u>	<u>Used in Interp.</u>	<u>Comments</u>
	299-W06-1	Cable tool	243.0	476.0	yes	no	yes	yes	
	299-W10-1	Cable tool	207.0	305.0	yes	yes	yes	yes	
	299-W10-5	Cable tool	204.0	240.0	yes	no	yes	no	
	299-W10-8	Cable tool	214.0	252.0	yes	no	yes	no	
	299-W10-9	Cable tool	205.0	225.0	yes	no	yes	no	
	299-W10-10	Cable tool		250.0	yes	no	yes	no	
	299-W10-11	Cable tool	207.0	250.0	yes	no	yes	no	
	299-W10-12	Cable tool		250.0	no	no	yes	no	
	299-W11-26	Cable tool/ Core	226.0	515.0	0 to 90'	yes	yes	yes	Fenix and Scisson (1976), Bjornstad (1984)
	299-W15-2	Cable tool	221.0	260.0	yes	yes	yes	yes	
	699-45-78	Rotary	220.0	730.0	yes	yes	no	yes	Bjornstad (1984)
	699-47-80B	Rotary	312.0	1632.0	yes	no	no	yes*	Jackson, et al. (1984)

*Only used for top of basalt.

Well Number 299-W6-1
Plant Coordinates N 46090, W 74396
Casing Elevation 702.53

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Gravel, Silt.	5	5
	Slightly indurated Gravel.	5	10
	Gravel, Sand.	5	15
	Black Sand.	5	20
	Basalt Granules, Sand.	10	30
	Basalt Gravel, Sand.	10	40
Plio-Pleistocene unit @ 39 ft	Fine Gravel, Sand, Silt, Some Caliche.	20	60
	Sand, Some Silt.	15	75
	Sand, Less Silt.	25	100
Middle Ringold @ 98 ft	Gravel, Sand.	20	120
	Fine Gravel, Some Sand and Boulders.	15	135
	Boulders, Gravel.	5	140
	Cemented Gravel.	20	160
	Gravel, Boulders.	20	180
	Boulders, Gravel, Sand, Silt.	25	205
	Sand, Gravel, Silt.	30	235
	Coarse Gravel, Sand, Silt.	20	255
	Gravel, Sand, Silt.	10	265
	Boulders, Gravel, Sand, Little Silt.	10	275
	Gravel, Sand.	10	285
	Boulders, Gravel, Some Silt.	10	295
	Boulders, Gravel, Sand, Silt.	5	300
	Gravel, Sand, Silt.	70	370
	Gravel, Sand, More Silt.	20	390
	Gravel, Sand, Silt.	25	415
	Gravel, Sand, More Silt.	10	425
	Basalt Mud, Gravel, Sand, Silt.	10	435
	Basalt Boulders, Gravel.	15	450
	25% Gray-Blue Sand, 25% Gray-Blue Fine Gravel.	20	470
Basalt @ 462 ft	Basalt.	6	476

Well Number 299-W10-1
Plant Coordinates N 43550, W 76210
Casing Elevation 674.06

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Gravel, Sand.	10	10
	Gravel.	7	17
	Black Sand.	3	20
	Gravel.	10	30
	Gravel, Sand.	10	40
	Gravel, Sand, Silt.	5	45
	Gravel, Sand.	5	50
	Black Sand.	5	55
	Gravel, Sand.	10	65
	Coarse Sand, Silt.	10	75
Early "Palouse" soil @ 76 ft	Sand, Clay.	30	105
Plio-Pleistocene unit @ 94 ft	Coarse Sand, Clay.	5	110
Upper Ringold @ 115 ft	Sand, Clay.	30	140
Middle Ringold @ 142 ft	Gravel, Clay.	2	142
	Gravel.	8	150
	Gravel, Sand.	5	155
	Gravel.	10	165
	Gravel, Sand.	5	170
	Gravel, Sand, Clay.	10	180
	Gravel, Sand.	5	185
	Gravel, Sand, Clay.	5	190
	Gravel, Sand.	5	195
	Sand, Silt.	5	200
	Gravel, Sand.	5	205
	Coarse Sand, Gravel.	5	210
	Gravel, Sand.	10	220
	Gravel, Sand, Clay.	35	255
	Gravel, Sand.	5	260
	Gravel, Sand, Clay.	10	270
	Gravel, Sand.	5	275
	Sand.	5	280
	Gravel.	5	285
	Sand.	8	293
	Gravel, Sand.	4	297
	Gravel, Sand, Silt.	3	300
	Sand.	3	303
	Gravel, Sand.	7	310

Well Number 299-W11-26 (DH-6)
 Plant Coordinates - N 43000, W 74800
 Casing Elevation 694.70

Stratigraphy(c)	Lithologic Description(b,d)	Thickness	Depth
Hanford formation	Coarse Cobbles, Silt.	5	5
	Coarse Sand.	5	10
	Cobbles, Coarse Sand, Silt.	15	25
	Large Cobbles, Coarse Sand, Gray Silt.	5	30
	Cobbles, Coarse Gray Sand.	10	40
	Coarse Gray Sand.	15	55
	Small Gravel, Coarse Gray Sand, Silt layer.	5	60
	Pebbles, Coarse Gray Sand.	15	75
	Pebbles, Coarse Gray Sand, Silt layers.	10	85
	Hard Sand and Silt.	3	88
	Silt.	2	90
Early "Palouse" soil @ 90 ft	Silty Medium to Fine Sand.	5	95
	Coarse to Medium Sand.	10	105
	Silt.	5	110
Plio-Pleistocene unit @ 110 ft	CaCO ₃ Sand, Silt.	8	118
	Medium to Fine Sand.	4	122
	Silt.	2	124
	Medium to Fine Sand.	2	126
Upper Ringold @ 130 ft	Well-Indurated Sandy Silty CaCO ₃ Conglomerate.	6	132
	Silt.	2	134
	Medium to Fine Sand.	6	140
Middle Ringold @ 141 ft	Sandy Gravel with 1/2" Silt Stringer.	22	162
	Silty Sandy Gravel Interbedded with Well-Indurated Conglomerate.	8	170
	Sandy Gravel With Little Basalt.	24	194
	Poorly Indurated Sandy Conglomerate With SiO ₂ Conglomerate and Silt Stringers.	50	244
	CaCO ₃ Sandy Conglomerate, Well to Poorly Indurated.	8	252
	Slightly Silty Sand Conglomerate.	16	268
	Coarse to Medium Sand.	2	270
	Slightly Silty Sand Conglomerate.	10	280
	CaCO ₃ -Indurated Conglomerate.	23	303
	SiO ₂ -Indurated Conglomerate.	2	305
	Weathered CaCO ₃ Conglomerate.	5	310
	Poorly to Well-Indurated Conglomerate	60	370
	Slightly CaCO ₃ Well-Indurated Coarse to Medium Sand.	3	373
	CaCO ₃ Well-Indurated Coarse to Medium Sand.	9	382
	Coarse to Medium Sand.	3	385

299-W11-26 (DH-6) (contd)

SiO ₂ Well-Indurated Conglomerate.	8	393
Slightly CaCO ₃ Well-Indurated Conglomerate.	15	408
Silty Fine to Very Fine Sand.	1	409
Slightly CaCO ₃ Well-Indurated Conglomerate.	4	413
Silty Fine to Very Fine Sand.	17	430
CaCO ₃ Poorly Indurated Conglomerate.	2	432
CaCO ₃ Well Indurated Conglomerate.	22	454
Blue-Green Well-Indurated Conglomerate.	5	459
Slightly CaCO ₃ Well-Indurated Conglomerate.	7	466
Coarse to Medium Sand.	3	469
Slightly CaCO ₃ Well-Indurated Conglomerate.	8	477
Blue-Green Slightly CaCO ₃ Well-Indurated Conglomerate.	19	496
Blue-Green Well-Indurated Conglomerate.	8	504
Basalt @ 505 ft 2" Sand, Then Basalt.	11	515

Well Number 299-W15-2
 Plant Coordinates N 42251, W 78082
 Casing Elevation 690.71

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sand, Silt.	5	5
Hanford formation @ 5 ft	Gravel, Sand, Silt.	60	65
	Gravel, Sand.	10	75
Early "Palouse" soil @ 109 ft	Sandy Silt.	40	115
Plio-Pleistocene unit @ 121 ft	Heavy Silt, Sand.	15	130
Middle Ringold @ 139 ft	Gravel, Sand.	10	140
	Cemented Gravel.	10	150
	Gravel, Sand.	65	215
	Boulders, Gravel, Sand.	10	225
	Gravel, Sand.	5	230
	Gravel, Sand, Silt.	30	260

Well Number	699-45-78 (RRL-3)
Plant Coordinates	N 44575, W 78294
Casing Elevation	689.81

Stratigraphy(a,c)	Lithologic Description(c)	Thickness	Depth
Hanford formation	Sandy Gravel.	15	15
	Gravelly Sand.	25	40
	Muddy Sand.	8	48
	Sandy Gravel, Basaltic.	42	90
Early "Palouse" soil @ 90 ft	Muddy Sand, Calcareous.	8	98
Plio-Pleistocene unit @ 98 ft	Calcrete.	22	120
Upper Ringold @ 120 ft	Sand.	15	135
Middle Ringold @ 135 ft	Gravelly Sand.	25	160
	Muddy Sand.	20	180
	Sandy Gravel.	165	345
	Muddy Sand.	30	375
	Sandy Gravel.	67	442
Lower Ringold @ 492 ft	Mud.	8	450
Basal Ringold (fine facies) @ 450 ft	Mud, Calcic Palesol.	20	470
	Muddy Sand.	15	485
Basal Ringold (coarse facies) @ 485 ft	Sandy Gravel.	22	507
Basalt @ 507 ft	Basalt.	43	550

Well Number	699-47-80 (DC-20B)
Plant Coordinates	N 46910, W 79835
Casing Elevation	712.34

Stratigraphy(h)	Lithologic Description	Thickness	Depth
Suprabasalt sediments	Sediments (Undifferentiated).	531	531
Basalt @ 531 ft	Basalt and Interbeds.	1101	1632

DATA INVENTORY AND LITHOLOGIC LOG SUMMARIES
FOR EXISTING 200-WEST AREA WELLS
NEAR WASTE MANAGEMENT AREA 4

DATA AVAILABLE FOR EXISTING WELLS NEAR WASTE MANAGEMENT AREA 4

Well Number	Drill Method	Depth to Water	Total Depth	Sieve Data	Gamma Logs	Drill Logs	Used in Interp.	Comments
299-W14-7	Cable/Core	209.0	531.0	0-100'	no	yes	yes	Webster (1977) Bjornstad (1984)
299-W14-8	Cable/Core	232.0	563.0	no	yes	yes	yes	
299-W15-5	Cable tool	200.0	594.0	yes	no	yes	yes	
299-W15-6	Cable tool	190.0	410.0	yes	yes	yes	yes	
299-W15-10	Cable tool	205.0	300.0	no	yes	yes	no	Webster (1977) Bjornstad (1984)
299-W15-11	Cable tool	207.0	300.0	yes	yes	yes	no	
299-W15-14	Cable/Core	224.0	581.0	5-100'	no	yes	yes	
299-W18-1	Cable tool	200.0	427.0	yes	no	yes	yes	
299-W18-2	Cable tool	208.0	280.0	5-265'	yes	yes	no	Fenix and Scisson (1976), Bjornstad (1984)
299-W18-3	Cable tool	215.0	450.0	5-200'	no	yes	no	
299-W18-4	Cable tool	211.0	280.0	5-210'	yes	yes	no	
299-W18-5	Cable tool	211.0	280.0	yes	no	yes	no	
299-W18-6	Cable tool	200.0	300.0	9-190'	yes	yes	no	
299-W18-7	Cable tool	203.0	300.0	yes	yes	yes	no	
299-W18-8	Cable tool	202.0	212.0	no	0-80'	yes	no	
299-W18-9	Cable tool	208.0	220.0	yes	yes	yes	no	
299-W18-10	Cable tool	207.0	220.0	5-165'	yes	yes	no	
299-W18-12	Cable tool	208.0	220.0	no	yes	no	no	
299-W18-15	Cable tool	188.0	243.0	no	yes	yes	yes	
299-W18-19	Cable tool	---	250.0	no	no	yes	no	
299-W18-20	Cable tool	---	250.0	no	no	yes	no	
299-W19-1	Cable tool	201.0	301.0	40-300'	yes	yes	yes	
299-W19-2	Cable tool	232.0	300.0	15-255'	0-240'	yes	yes	
299-W19-8	Cable tool	248.0	585.0	yes	yes	yes	yes*	
299-W19-10	Cable/Core	225.0	573.0	no	yes	yes	yes	

*Only used for top of basalt.

DATA AVAILABLE FOR EXISTING WELLS NEAR WASTE MANAGEMENT AREA 4 (contd)

<u>Well Number</u>	<u>Drill Method</u>	<u>Depth to Water</u>	<u>Total Depth</u>	<u>Sieve Data</u>	<u>Gamma Logs</u>	<u>Drill Logs</u>	<u>Used in Interp.</u>	<u>Comments</u>
299-W23-4	Cable tool	182.0	300.0	205-300'	yes	yes	no	
299-W23-8	Cable tool	190.0	235.0	15-230'	yes	yes	no	
299-W23-9	Cable tool	192.0	235.0	yes	yes	yes	no	
299-W23-10	Cable tool	191.0	235.0	yes	yes	yes	no	
299-W23-11	Cable tool	187.0	235.0	yes	yes	yes	no	
699-35-78B	Rotary	183.0	638.0	yes	yes	no	yes	Bjornstad (1984)
699-39-79	Cable tool	195.0	295.0	0-35' 240-295'	yes	yes	yes	
699-40-80	Rotary	183.0	560.0	yes	yes	no	yes	Bjornstad (1984)

Well Number 299-W14-7 (DH-12)
Plant Coordinates N 40003, W 75002
Casing Elevation 678.41

Stratigraphy(c)	Lithologic Description(b,g)	Thickness	Depth
Recent eolian sand	50% Medium Sand, 50% Fine Sand.	5	5
Hanford formation @ 5 ft	40% Cobbles, 30% Gravel, 30% Sand.	5	10
	30% Cobbles, 40% Gravel, 30% Sand.	10	20
	60% Gravel, 40% Sand.	10	30
	30% Fine Gravel, 50% Coarse Sand, 20% Medium Sand.	10	40
	30% Coarse Sand, 40% Medium Sand, 30% Fine Sand.	10	50
	30% Fine Gravel, 50% Coarse Sand, 20% Medium Sand.	15	65
	10% Fine Gravel, 30% Coarse Sand, 30% Medium Sand, 30% Fine Sand.	5	70
	30% Fine Gravel, 50% Coarse Sand, 20% Medium Sand.	15	85
	10% Fine Gravel, 20% Coarse Sand, 40% Medium Sand, 30% Fine Sand.	15	100
Early "Palouse" soil @ 113 ft	Fine Sand, Slight Compaction With Some Biotite, CaCO ₃ , and a Few Coarse Lithics.	30	130
Plio-Pleistocene unit @ 128 ft	Fine to Very Coarse Gravel, Biotite.	25	155
	Medium Gravel, Coarse to Very Coarse Sand.	5	160
Middle Ringold @ 135 ft	Fine to Very Coarse Gravel.	15	175
	Fine Gravel, Fine to Very Coarse Sand, Little Clay.	30	205
	Fine Gravel.	5	210
	Fine Gravel, Medium to Very Coarse Slightly Indurated Sand.	5	215
	Fine Gravel.	5	220
	Fine Gravel, Medium to Very Coarse Sand.	5	225
	Fine Gravel, Medium to Very Coarse Sand, Some Clay.	5	230
	Fine to Coarse Gravel, Some Sand.	10	240
	Medium Gravel, Medium to Very Coarse Sand, Minor Clay.	5	245
	Medium Sandy Gravel.	5	250
	Fine to Medium Sandy Gravel, Medium Sand, Clay.	10	260
	Medium Gravel, Medium Sand.	10	270
	Sandy Gravel Conglomerate.	5	275
	Sandy Gravel.	5	280

299-W14-7 (DH-12) (contd)

	Sandy Gravel Conglomerate, CaCO ₃ .	5	285
	Coarse Sand, Some Gravel.	3	288
	Sandy Gravel Conglomerate.	7	295
	Coarse Sand, Gravel Stringer.	5	300
	Medium to Coarse Sandy Gravel.	10	310
	Sandy Gravel With Stringer of Medium to Coarse Sand and Clay.	5	315
	Medium to Coarse Sandy Gravel, Clay, CaCO ₃ .	20	335
	Medium Gravel, Medium to Coarse Sand.	20	355
	Sandy Gravel, Well-Cemented Sand Stringers.	10	365
	Medium Sandy Gravel-Gravelly Sand.	30	395
	Sandy Gravel, Clay.	5	400
	Sand, Clay, and Gravel Stringers.	10	410
	Sandy Gravel, Clay.	5	415
	Sandy Gravel, Some CaCO ₃ Cement.	10	425
Lower Ringold @ 425 ft	Clay, Sand, Some Very Fine Gravel.	20	445
	Clay, Some CaCO ₃ Conglomerate, CaCO ₃ Sand.	5	450
	Claystone with Caliche Layers.	7	457
Basal Ringold @ 432 ft	Medium Sand.	10	467
	Conglomerate, Sandy Gravel.	8	475
	Sandy Gravel.	10	485
	Small Cobbles, Sandy Gravel, Some Induration.	15	500
	Gravel.	5	505
	Medium Sandy Gravel.	5	510
	Gravel, Very Little Sand.	9	519
Basalt @ 519 ft	Vesicular Basalt.	12	531

Well Number	299-W14-8 (DH-13A)
Plant Coordinates	N 4009B, W 71795
Casing Elevation	695.56

Stratigraphy(a,c)	Lithologic Description(c)	Thickness	Depth
Hanford formation (coarse-grained sequence)	Sandy Gravel. Gravelly Sand.	40 68	40 108
(basal slack-water sequence @ 108 ft)	Sand to Muddy Sand.	56	164
Early "Palouse" soil @ 164 ft	Muddy Sand.	14	178
Plio-Pleistocene unit @ 178 ft	Calcrete.	6	184
Middle Ringold @ 184 ft	Sandy Gravel. Sand. Sandy Gravel. Ash. Sandy Gravel.	81 19 154 9 89	265 284 438 447 536
Basalt @ 536 ft	Basalt.	27	563

Well Number	299-W15-5
Plant Coordinates	N 39537, W 75984
Casing Elevation	670.95

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sandy Silt.	25	25
Hanford formation @ 25 ft	Gravel, Sand.	5	30
	Small Gravel, Sand	20	50
	Gravel.	5	55
	Sandy Silt.	55	110
Early "Palouse" soil @ 110 ft	Heavy Silt, Sand.	10	120
Plio-Pleistocene unit @ 120 ft	Caliche, Fine Gravel, Sand, Silt.	10	130
	Caliche, Fine Gravel, Sand.	5	135
Middle Ringold @ 145 ft	Gravel, Silt.	15	150
	Small Gravel, Sand.	5	155
	Gravel, Sand.	15	170
	Gravel, Sand, Silt.	40	210
	Sand.	15	225
	Gravel, Fine Sand, Silt.	35	260
	Sand.	15	275
	Gravel, Fine Sand.	5	280
	Gravel, Sand, Silt.	5	285
	Gravel, Sand.	110	395
	Gravel, Sand, Silt Streaks.	5	400
	Gravel, Sand, Less Silt.	10	410
	Gravel, Sand.	15	425
Lower Ringold @ 430 ft	Heavy Gray Silt.	15	440
	Shale With Volcanic Ash.	5	445
	Gravelly Sandstone.	5	450
Basal Ringold @ 455 ft	Green Shale, Gravel, Clay	20	470
	Gravel, Sand, Silt, Shale.	10	480
	Gravel, Sand, Silt.	10	490
	Green Sand and Gravel, Black Silt.	35	525
Basalt @ 525 ft	Basalt.	48	573
	Gravel, Sand.	17	590
	Basalt.	4	594

Well Number 299-W15-6
Plant Coordinates N 40005, W 75765
Casing Elevation 661.50

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sand.	10	10
Hanford formation @ 10 ft	Gravel, Sand.	5	15
	Coarse Sand.	10	25
	Cobbles, Coarse Sand.	5	30
	Cobbles, Sandy Gravel.	5	35
	Sand.	10	45
	Sand, Silt.	15	60
	Gravel, Sand.	5	65
Early "Palouse" soil @ 90 ft	Sand, Silt.	40	105
Plio-Pleistocene unit @ 98 ft	Very Coarse Gravel and Clay.	5	110
	Cobbles, Sand.	5	115
Middle Ringold @ 115 ft	Gravel, Sand, Caliche.	10	125
	Sand.	5	130
	Cobbles, Gravel, Sand.	10	140
	Sand.	10	150
	Cobbles, Gravel, Sand.	10	160
	Cobbles, Sand.	15	175
	Cobbles, Gravel, Sand.	55	230
	Cobbles, Gravel, Sand, Clay.	50	280
	Sand.	20	300
	Cobbles, Gravel, Sand, Clay.	5	305
	Cobbles, Gravel, Clay.	5	310
	Gravel, Clay, Few Boulders.	5	315
	Cobbles, Gravel, Sand, Clay.	50	365
	Cobbles, Gravel, Clay.	5	370
	Cobbles, Gravel, Sand, Clay.	15	385
	Gravel, Sand.	5	390
	Cobbles, Gravel, Sand, Clay.	20	410

Well Number 299-W15-14 (DH-11)
Plant Coordinates N 39988, W 78091
Casing Elevation 699.60

Stratigraphy(c)	Lithologic Description(b,g)	Thickness	Depth
Recent eolian sand	10% Coarse Sand, 50% Medium Sand, 40% Fine Sand.	5	5
Hanford formation @ 5 ft	40% Fine Gravel, 40% Coarse Sand, 20% Medium Sand.	10	15
	10% Fine Gravel, 40% Coarse Sand, 50% Medium Sand.	20	35
	30% Fine Gravel, 50% Coarse Sand, 20% Medium Sand.	10	45
	10% Fine Gravel, 50% Coarse Sand, 40% Medium Sand.	5	50
	10% Cobbles, 50% Gravel, 40% Sand	40	90
	10% Coarse Sand, 60% Medium Sand, 30% Fine Sand.	10	100
	Very Fine to Coarse Sand.	30	130
	Coarse to Very Coarse Sand Interbedded with Fine to Very Fine Sandy Mud.	5	135
	Medium to Coarse Sand.	10	145
Early "Palouse" soil @ 141 ft	Very Fine Sandy Mud.	5	150
Plio-Pleistocene unit @ 156 ft	Slightly Muddy Very Fine to Medium Sand.	15	165
	Slightly Gravelly Sand.	5	170
Upper Ringold @ 170 ft	Very Fine Muddy Sand.	10	180
Middle Ringold @ 175 ft	CaCO ₃ , Coarse Sandy Gravel, Pebbles, Cobbles.	30	210
	Coarse Sand, Pebbles, Large Cobbles, Some Boulders.	10	220
	Fine to Very Fine Sandy Gravel, Cobbles.	40	260
	Medium Cobbles, Small to Large Pebbles Some Induration.	40	300
	Poorly Indurated Muddy Sandy Gravel, With Well-Indurated Stringers, Medium to Fine Sand, Pebbles, Cobbles.	25	325
	Well Indurated, CaCO ₃ .	5	330
	Muddy Sandy Gravel, Medium to Large Pebbles, Cobbles.	10	340
	Well Indurated, CaCO ₃ .	5	345
	Medium to Fine Sand Layer, Sandy Gravel.	5	350
	Pebbles, Cobbles.	5	355

299-W15-14 (DH-11) (contd)

	Medium to Fine Sand, CaCO ₃ .	5	360
	Sandy Gravel, Large Pebbles, Coarse to Medium Sand.	35	395
	Fine to Medium Sandy Gravel, Some Good Induration, No CaCO ₃ .	10	405
	Medium to Fine Sand.	5	410
	Medium to Fine Sandy Gravel.	10	420
	Medium to Fine Gravel, Some Induration.	20	440
	Partly Indurated Sandy Gravel, Pebbles, Cobbles.	18	458
Lower Ringold @ 459 ft	Clay, Gravel Stringer.	22	480
Basal Ringold @ 474 ft	Slightly Gravelly Sand, Silt.	10	490
	Sandy Silt, Clay, CaCO ₃ veins.	10	500
	Coarse to Medium Sand.	10	510
	Cobbles, Gravel, Sand Stringer.	10	520
	Coarse to Medium Sand, Pebbles, Cobbles.	20	540
	Large to Medium Pebbles, Cobbles, Fair to Good Induration.	20	560
	Shale, Sand, Sandy Silt, Gravel and Sand Stringers.	6	566
Basalt @ 564 ft.	Vesicular Basalt.	15	581

Well Number 299-W18-1
Plant Coordinates N 39388, W 77013
Casing Elevation 680.00

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sand.	35	35
Hanford formation @ 35 ft	Cobbles, Sand.	5	40
	Boulders, Gravel, Sand.	5	45
	Sand.	60	105
	Gravel, Sand.	20	125
Early "Palouse" soil @ 120 ft			
Plio-Pleistocene unit @ 125 ft	Brown Silt.	5	130
	Gravel, Sand.	5	135
	Cobbles, Gravel, Sand.	10	145
Upper Ringold @ 150 ft	Sand.	20	165
Middle Ringold @ 170 ft	Boulders, Silt.	20	185
	Sand.	5	190
	Gravel, Sand.	10	200
	Boulders, Cobbles, Gravel, Sand.	10	210
	Boulders, Sand.	5	215
	Boulders, Clay.	15	230
	Cobbles, Gravel, Clay.	20	250
	Gravel, Sandy, Clay.	30	280
	Cobbles, Sand.	15	295
	Sand.	5	300
	Cobbles, Sand.	3	305
	Boulders, Sand, Clay.	7	310
	Cobbles, Sand, Gravel, Little Clay.	10	320
	Boulders, Gravel, Clay.	5	325
	Boulders, Sand, Clay.	10	335
	Reddish-Brown Clay.	5	340
	Cobbles, Sand, Clay.	15	355
	Gravel, Sand, Clay.	25	380
	Sand.	5	385
	Gravel, Sand, Clay.	20	405
	Sandy Silt.	10	415
	Sand.	5	420
	Gravel, Sand, Clay.	7	427

Well Number	299-W18-15
Plant Coordinates	N 36990, W 77152
Casing Elevation	660.96

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Sand.	10	10
Hanford formation @ 10 ft	Cobbles.	5	15
	Cobbles, Sand.	5	20
	Gravel, Brown Sand.	5	25
	Boulders, Brown Sand.	10	35
	Black and Brown Sand.	65	100
	Silt.	2	102
	Black Sand.	8	110
	Gravel, Black Sand.	5	115
	Black Sand.	3	118
	Small Gravel.	1	119
Early "Palouse" soil @ 120 ft	Silt.	23	142
Plio-Pleistocene unit @ 140 ft	Black Sand.	2	144
	Cobbles, Caliche.	6	150
	Caliche.	12	162
	Compacted Gravel.	1	163
Middle Ringold @ 165 ft	Gravel.	13	176
	Cobbles, Sand	2	178
	Compacted Gravel.	6	184
	Cobbles, Gravel, Sand.	1	185
	Cobbles, Sand.	4	189
	Cobbles, Sand, Few Boulders.	24	213
	Cobbles, Brown Sand.	35	248

Well Number	299-W19-1
Plant Coordinates	N 37613, W 75491
Casing Elevation	673.77

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Hanford formation	Gravel, Sand, Silt.	5	5
	Boulders, Gravel.	15	20
	Gravel, Sand, Silt.	5	25
	Gravel.	20	45
	Gravel, Sand.	5	50
	Sand, Some Silt.	18	68
	Gravel, Sand, Some Silt.	2	70
	Sandy Tan Silt.	55	125
Early "Palouse" soil @ 125 ft	Heavy Silt, Sand.	20	145
	Small Gravel, Caliche, Sand, Silt.	5	150
Plio-Pleistocene unit @ 150 ft	Gravel, Sand.	45	195
	Boulders, Gravel, Sand.	10	205
Middle Ringold @ 160 ft	Gravel, Sand.	5	210
	Gravel, Sand, Very Little Silt.	15	225
	Gravel, Sand, Silt.	15	240
	Boulders, Gravel, Brown Sand, Silt.	5	245
	Some Gravel, Much Fine Brown Sand.	15	260
	Gravel, Sand, Much Silt.	20	280
	Gravel, Fine Sand.	17	297
	Gravel, Sand, Silt.	4	301

Well Number 299-W19-2
 Plant Coordinates N 36849, W 73000
 Casing Elevation 694.04

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Muddy Sand.	10	10
Hanford formation (coarse-grained sequence)	Gravelly Sand.	78	88
(basal slack-water sequence @ 88 ft)	Muddy Sand.	70	158
Early "Palouse" soil @ 158 ft	Muddy Sand, Calcareous.	27	185
Plio-Pleistocene unit @ 185 ft	Muddy Sand, Very Calcareous.	18	203
Upper Ringold @ 203 ft	Muddy Gravel.	37	240
Middle Ringold @ 240 ft	Cemented Sandy Gravel to Gravelly Sand.	60	300

Well Number	299-W19-8
Plant Coordinates	N 38574, W 73268
Casing Elevation	~705 ft

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Suprabasalt sediments	Sediments (undifferentiated).	560	560
Basalt @ 560 ft	Basalt.	25	585

Well Number 299-W19-10 (DH-7)
Plant Coordinates ~N 37250, W 74800
Casing Elevation 682.80

Stratigraphy(c)	Lithologic Description(b,d)	Thickness	Depth
Hanford formation	Small Boulders, Large Cobbles, Small Gravel.	10	10
	Small Boulders, Cobbles, Gravel, Sand.	15	25
	Coarse Gray Sand, Silt.	5	30
	Cobbles, Gravel, Coarse Sand.	10	40
	Gravel, Coarse Sand.	5	45
	Gravel, Sand, Silt,	5	50
	Large Cobbles, Gravel, Coarse Sand.	5	55
	Small Gravel, Coarse Sand.	5	60
	Coarse Sand, Silt.	5	65
	Medium Sand, Silt, Silt Lenses.	45	110
	Pebbles, Sand, Caliche.	4	114
	Sand, Hard-Packed Silt.	16	130
	Coarse Sand, Silt.	10	140
Early "Palouse" soil @ 135 ft	Fine Sandy Hard Silt.	5	145
	Silty Fine to Very Fine Sand.	15	160
Plio-Pleistocene unit @ 160 ft	Pebbles, Coarse to Fine Sand, Silt, CaCO ₃ .	10	170
Middle Ringold @ 170 ft	Sandy Gravel.	75	245
	Well-Indurated CaCO ₃ Conglomerate.	5	250
	Medium CaCO ₃ Sand.	2	252
	SiO ₂ Conglomerate.	8	260
	Well-Indurated Slightly CaCO ₃ Conglomerate.	20	280
	Coarse to Medium Sand.	6	286
	SiO ₂ Conglomerate; Coarse to Medium Sand Layers.	39	325
	1" Clay; Poorly Indurated Conglomerate	10	335
	Medium Sand, Conglomerate.	5	340
	Coarse to Medium Sand, CaCO ₃ to No CaCO ₃ , Well to Fairly Indurated.	5	345
	Fairly to Well-Indurated Conglomerate with 12", 6", and 8" Coarse Sand Layers.	50	395
	Well to Poorly Indurated Conglomerate.	65	460
Basal Ringold @ 459 ft	Well-Indurated Gray-Green Clay.	10	470
	Green-Brown Sandy Clay.	15	485
	Green Poorly Indurated Conglomerate.	65	550
	Green Medium Sand.	5	555
	Conglomerate	14	569
Basalt @ 556 ft	Basalt	4	573

Well Number 699-35-78B (RRL-4)
 Plant Coordinates N 35498, W 78251
 Casing Elevation 659.76

Stratigraphy(a,c)	Lithologic Description(c)	Thickness	Depth
Hanford formation	Gravelly Sand, Basaltic.	25	25
(coarse-grained sequence)	Sandy Gravel.	25	55
(fine-grained sequence @ 55 ft)	Muddy Sand.	50	105
Early "Palouse" soil @ 105 ft	Sandy Mud, Calcareous.	55	160
Middle Ringold @ 160 ft	Sandy Gravel.	215	375
	Muddy Sand.	10	385
	Sandy Gravel.	33	418
Lower Ringold @ 418 ft	Mud	42	460
Basal Ringold @ 400 ft			
(fine facies)	Muddy Sand, Calcic Paleosol.	30	490
(coarse facies @ 490 ft)	Sandy Gravel.	84	574
	Mud (weathered basalt?)	6	580
Basalt @ 580 ft	Basalt.	23	603

Well Number	699-39-79
Plant Coordinates	N 39198, W 78751
Casing Elevation	673.52

Stratigraphy(a)	Lithologic Description(b)	Thickness	Depth
Recent eolian sand	Fine Sand, Silt.	13	13
	Fine Sand.	7	20
Hanford formation @ 20 ft	Basalt Gravel, Sand.	5	25
	Basalt, Some Gravel.	15	40
	Black Sand, Gravel.	10	50
	Basalt Gravel, Sand.	17	67
	Fine Black Sand.	11	78
	Black Sand, Basalt.	9	87
	Fine Sand, Clay.	5	92
	Sand, Silt.	8	100
	Coarse Sand, Silt.	25	125
Early "Palouse" soil @ 125 ft	Fine Sand, Silt.	10	135
	Fine Sand, Silt, Clay.	5	140
Plio-Pleistocene unit @ 140 ft	Caliche-Cemented Zone.	10	150
	Fine Sand, Silt, Clay.	8	158
	Gravel, Basalt, Sand, Silt, Clay.	4	162
	Fine Sand, Gravel.	3	165
	Sand, Gravel.	15	180
	Basalt Gravel, Sand.	7	187
	Coarse Sand, Gravel.	10	197
	Gravel, Sand.	28	225
	Fine to Coarse Sand, Gravel.	10	235
	Gravel, Sand, Clay.	15	250
	Gravel, Sand.	10	260
	Cemented Sand, Gravel.	5	265
	Boulders, Gravel, Fine Sand.	2	267
	Gravel, Fine Sand.	11	278
	Coarse Sand, Gravel.	17	295

Well Number	699-40-80 (RRL-9)
Plant Coordinates	N 39665, W 79978
Casing Elevation	655.50

Stratigraphy(a,c)	Lithologic Description(c)	Thickness	Depth
Hanford formation (coarse-grained sequence)	Sandy Gravel.	65	65
(fine-grained sequence @ 65 ft)	Muddy Sand.	24	89
Early "Palouse" soil @ 89 ft	Sandy Mud.	23	112
Plio-Pleistocene @ 112 ft	Calcrete. Gravelly Sand, Calcareous.	12 26	124 150
Middle Ringold @ 150 ft	Sandy Gravel. Sandy Mud. Sandy Gravel.	237 23 28	387 410 438
Lower Ringold @ 438 ft	Mud.	22	460
Basal Ringold	Mud, Calcic Paleosol.	10	470
(fine facies @ 460 ft)	Muddy Sand.	20	490
(coarse facies @ 490 ft)	Sandy Gravel.	57	547
Basalt @ 547 ft	Basalt.	13	560

REFERENCES

Bjornstad, B. N. 1984. Suprabasalt Stratigraphy Within and Adjacent to the Reference Repository Location. SD-BWI-DP-039, Rockwell Hanford Operations, Richland, Washington.

Fecht, K. R. and J. T. Lillie. 1982. A Catalog of Borehole Lithologic Logs from the 600 Area, Hanford Site. RHO-LD-158, Rockwell Hanford Operations, Richland, Washington.

Fenix and Scisson, Inc. 1976. Ringold Identification Correlation, and Sampling Program, Well History DH-6, -7, -8, -9, -9A, and -9B, Hanford Works, Richland, Washington. ARH-C-13, Atlantic Richfield Hanford Company, Richland, Washington.

Jackson, R. L., L. D. Diediker, R. K. Ledgerwood, and M. D. Veatch. 1984. Piezometer Completion Report for Borehole Cluster Sites DC-19, DC-20, and DC-22. SD-BWI-TI-226, Rockwell Hanford Operations, Richland, Washington.

Strait, S. R., and B. A. Moore. 1982. Geohydrology of the Rattlesnake Ridge Interbed in the Gable Mountain Pond Area. RHO-ST-38, Rockwell Hanford Operations, Richland, Washington.

Webster, C. T. 1977. Ringold Identification, Correlation, and Sampling Program, Well History DH-11, -12, -13, -13A, -14, -15, -16, and -17 (Continuation of ARH-C-13), Hanford Works, Richland, Washington. RHO-LD-34, Rockwell Hanford Operations, Richland, Washington.

APPENDIX B

WELL CONSTRUCTION SUMMARIES FOR
THE 200-EAST AREA LOW-LEVEL BURIAL GROUNDS

APPENDIX B

WELL CONSTRUCTION SUMMARIES FOR THE 200-EAST AREA LOW-LEVEL BURIAL GROUNDS

Sixteen ground-water monitoring wells were drilled around two waste management areas in the 200-East Area during the summer and fall of 1987 (Figure B.1). Wells were drilled with cable-tool drill rigs using core barrels when conditions permitted; otherwise, hard-tool methods were used. This appendix provides a summary of the well construction, the Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for each well. Depth and size information provided in the well construction summary is rounded to the nearest 0.1 ft.

KEY TO GEOHYDROLOGIC UNITS ON DATA CORRELATION CHARTS - 200-EAST AREA

H	Hanford formation (undifferentiated)
Huc	Upper coarse-grained unit
Hms	Middle sand unit
Hlc	Lower coarse-grained unit
R	Ringold Formation (undifferentiated)
EM	Elephant Mountain Member (basalt)

FIGURE B.1. Well Locations for the 200-East Area Low-Level Burial Grounds

SUMMARY OF CONSTRUCTION, WELL 299-E27-8

Construction of this well was initiated on August 1, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 257 ft below ground surface. Ground water was encountered at a depth of approximately 229.4 ft, and basalt was encountered at a depth of 256.5 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 246.7 to 257 ft and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 245.5 ft. A 20-ft length of 4-in. diameter stainless steel screen (20 slot) was set at a depth of 225.5 to 245.5 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 221 ft. A 5-ft thick bentonite pellet seal followed by a granular bentonite (10 mesh) seal was installed to 4.5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. A small amount of bentonite was observed on the 4-in. screen. This bentonite probably entered the well during well completion, as the well cap became cocked to one side during casing pullback and bentonite granules were poured into the annulus. The screen was washed off using pressurized water from an approved source, and then swabbed and bailed. A follow-up inspection indicated no bentonite was left on the screen.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11 gpm for 49 min. An estimated total volume of 539 gal was removed during the development. The final turbidity reading of the discharged water was 0.18 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Battelle <small>Pacific Northwest Laboratories</small>		Well Completion Report/Title III Inspection List																
Project <u>200 Area RCRA Monitoring Wells</u>		Well Number <u>299-E27-8</u>																
Location <u>200 E</u>		Temporary Well Number <u>N/A</u>																
Driller <u>FELIX MURPHY / Ralph Robinson</u>		Coordinates <u>N44,496 W49,1042</u>																
Drilling Co. <u>KAISER ENGINEERING</u>		Casing Elevation <u>637.83'</u>																
Geologist <u>S M GOODWIN / P White</u>		Ground Elevation <u>634.64'</u>																
<u>K.R. Oster, N.A. Chumness</u>																		
DRILLING METHOD Rotary Air <u>N/A</u> Mud <u>N/A</u> Cable Tool <u>D 100'-195'</u> H <u>0'-100', 195'-257'</u> Drilling Fluid <u>200 E Drilling Supply H₂O</u> Other _____		COMPLETION DATA Drilled Depth <u>257' (below land surface)</u> Completion Depth <u>245' 6" (below land surface)</u> Date Started <u>9/1/87</u> Completed <u>9/30/87</u> Static Water Level/Date <u>229.4' / 8/14/87 (L-TAP)</u> <u>(#11044)</u>																
CASING DATA																		
Type		Size																
<u>CARBON STEEL (TEMPORARY)</u>		<u>16"</u> to <u>0' TO 40' 3/4"</u>																
<u>CARBON STEEL (TEMPORARY)</u>		<u>12"</u> to <u>0' TO 103' 11 1/2"</u>																
<u>CARBON STEEL (TEMPORARY)</u>		<u>10"</u> to <u>0' TO 165' 10 1/4"</u>																
<u>CARBON STEEL (TEMPORARY)</u>		Approved By <u>K.R. Oster</u> Date <u>8/24/87</u>																
<u>STAINLESS STEEL</u>		<u>4"</u> to <u>0' TO 226' + 3.19' stick up</u>																
PERFORATIONS Type _____ Depth <u>N/A</u> Schedule _____		SCREEN Type <u>STAINLESS STEEL</u> Length <u>8' 10' 3"</u> <u>4' 20'</u> Slot Size <u>30</u> <u>20</u> Depths <u>8' 247' 257'</u> <u>4' 225' 6" 245' 6"</u>																
App. By <u>K.R. Oster</u> Date <u>8/24/87</u>		App. By <u>K.R. Oster</u> Date <u>8/24/87</u>																
ANNULAR SEAL <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Type</th> <th style="width: 30%;">Interval</th> <th style="width: 40%;">Volume</th> </tr> </thead> <tbody> <tr> <td><u>Sand</u></td> <td><u>221'-257'</u></td> <td><u>14 100 lb bags</u></td> </tr> <tr> <td><u>Bentonite Pellets</u></td> <td><u>216'-221'</u></td> <td><u>3-50 lb buckets</u></td> </tr> <tr> <td><u>Granular Bentonite</u></td> <td><u>4.5'-216'</u></td> <td><u>140 100 lb bags</u></td> </tr> <tr> <td><u>Cement</u></td> <td><u>4.5'-0'</u></td> <td><u>unknown</u></td> </tr> </tbody> </table>				Type	Interval	Volume	<u>Sand</u>	<u>221'-257'</u>	<u>14 100 lb bags</u>	<u>Bentonite Pellets</u>	<u>216'-221'</u>	<u>3-50 lb buckets</u>	<u>Granular Bentonite</u>	<u>4.5'-216'</u>	<u>140 100 lb bags</u>	<u>Cement</u>	<u>4.5'-0'</u>	<u>unknown</u>
Type	Interval	Volume																
<u>Sand</u>	<u>221'-257'</u>	<u>14 100 lb bags</u>																
<u>Bentonite Pellets</u>	<u>216'-221'</u>	<u>3-50 lb buckets</u>																
<u>Granular Bentonite</u>	<u>4.5'-216'</u>	<u>140 100 lb bags</u>																
<u>Cement</u>	<u>4.5'-0'</u>	<u>unknown</u>																
App. By <u>MAC</u> Date <u>11/20/87</u>																		
GEOPHYSICAL LOGGING <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;">Sondes</th> <th style="width: 20%;">Interval</th> <th style="width: 20%;">Date</th> </tr> </thead> <tbody> <tr> <td><u>NAT. X</u></td> <td><u>257' - 0'</u></td> <td><u>8/14/87</u></td> </tr> <tr> <td><u>NEUTRON</u></td> <td><u>256' - 2'</u></td> <td><u>8/14/87</u></td> </tr> <tr> <td><u>DENSITY</u></td> <td><u>256' - 0'</u></td> <td><u>8/14/87</u></td> </tr> </tbody> </table>		Sondes	Interval	Date	<u>NAT. X</u>	<u>257' - 0'</u>	<u>8/14/87</u>	<u>NEUTRON</u>	<u>256' - 2'</u>	<u>8/14/87</u>	<u>DENSITY</u>	<u>256' - 0'</u>	<u>8/14/87</u>	AQUIFER TESTING Type of Test <u>constant discharge / development</u> Length of Test <u>8.4 hrs.</u> Volume Pumped <u>90,000 gal</u> Drawdown <u>0.12 ft.</u>				
Sondes	Interval	Date																
<u>NAT. X</u>	<u>257' - 0'</u>	<u>8/14/87</u>																
<u>NEUTRON</u>	<u>256' - 2'</u>	<u>8/14/87</u>																
<u>DENSITY</u>	<u>256' - 0'</u>	<u>8/14/87</u>																
Approved By <u>MAC</u> Date <u>11/24/87</u>		Approved By <u>Charles J. Cline</u> Date <u>8/19/87</u>																
OTHER APPLICABLE ITEMS																		
<u>SMC</u> Steam Cleaning <u>SMC</u> Storage of Const. Material <u>SMC</u> Tool Lubricants <u>MAC</u> Concrete Pad Approved By <u>M. A. Chumness</u> Date <u>12/13/87</u>		<u>MAC</u> Protective Steel Posts <u>MAC</u> Safety Paint <u>MAC</u> Straightness Test <u>MAC</u> Well Development																
		<u>MAC</u> Downhole TV Inspection <u>N/A</u> Well Abandonment <u>✓</u> Complete As-Built Diagram, Driller's and Geologist's Logs																

Reviewed By J. L. McShan Date 12-18-87

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E27-0 Geologist S. M. Goodwin/P. White Page 1 of 2
K.R. Oster, H.A. Chambers
Reviewed by J.L. Mathan Date 12-18-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Pump rate ft/hr
Description	Diagram		Diagram Litho.	Lithologic Description	
cement 0-4.5'		5'		silty sand	1.2'
16" carbon steel casing		10'		"	2.5'
		15'		"	3.3'
		20'		"	5.0'
		25'		SL. SILTY GRAVELLY SAND	3.9'
bentonite crumbles 4.5'-216'		30'		SILTY SANDY GRAVEL	5.5'
		35'		"	2.0'
		40'		"	10.0'
		45'		"	7.5'
		50'		SLIGHTLY SILTY GRAVELLY SAND	4.3'
12" carbon steel casing		55'		SILTY SANDY GRAVEL	12.0'
		60'		"	2.4'
		65'		"	3.0'
		70'		SL. SILTY GRAVELLY SAND	6.0'
		75'		"	3.6'
		80'		SILTY SANDY GRAVEL	10.0'
		85'		"	7.5'
		90'		"	2.2'
		95'		GRAVELLY SILTY SAND	6.0'
		100'		SILTY SANDY GRAVEL	4.6'
		105'		"	3.9'
10" carbon steel casing		110'		SL. SILTY GRAVELLY SAND	2.5'
		115'		GRAVELLY SAND	2.5'
		120'		SL. SILTY GRAVELLY SAND	2.5'
		125'		"	4.0'
8" carbon steel casing		130'		"	6.7'

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299-F27-8 Geologist Bodwin / White Page 2 of 2
Reviewed by J.L. McShan Date _____
K.R. Oster, M.A. Chenners

Construction Data		Depth in Feet	Geologic/Hydrologic Data		drill rate (ft/min)
Description	Diagram		Diagram Litho.	Lithologic Description	
1		137		GRAVELLY SAND	2.5
10" carbon steel casing		140		SL SILTY GRAVELLY SAND	6.1
		145		GRAVELLY SAND	10
		150		SL SILTY GRAVELLY SAND	10
		155		GRAVELLY SAND	10
		160		"	2.9
		165		"	3.3
8" carbon steel casing		170		SILTY SANDY GRAVEL	6.3
		175		SANDY GRAVEL	2.0
4" stainless steel casing		180		"	6.0
centralizers		185		"	4.3
bentonite, crumbles 45'-216'		190		GRAVELLY SAND	2.4
		195		SL SILTY SL. GRAVELLY SAND	2.7
		200		SILTY SANDY GRAVEL	1.1
		205		"	2.5
		210		"	.8
		215		"	1.7
walchey pellets 216'-221'		220		"	4.5
Depth to water 229.4' 8/14/67		225		"	1.8
		230		"	2.5
4" 20 slot st. steel screen		236		"	3.3
		240		GRAVELLY SAND	1.5
silica sand 221'-257'		245		"	2
8" 20 slot st. steel telescoping screen		250		SANDY GRAVEL	3
		255		"	1.8
				Base - 256.5'	-

TD = 257'

A-1800-188 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E27-9

Construction of this well was initiated on July 21, 1987, and was completed on August 21, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 245.2 ft below ground surface. Ground water was encountered at a depth of approximately 221.1 ft, and basalt was encountered at a depth of 245 ft. The borehole was tested for straightness and was geophysically logged. A 10.9-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 233.4 to 244.3 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 239.1 ft. A 20.3-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 219.9 to 239.1 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 210.5 ft. A 7.2-ft-thick bentonite pellet seal followed by a granular bentonite (10 mesh) seal was installed to 2.3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 12.5 gpm for 45 min. An estimated total volume of 562.5 gal was removed during the development. The final turbidity reading of the discharge water was 0.70 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 AREA RCRA Monitoring Wells</u>	Well Number <u>299-E27-9</u>
Location <u>200 EAST AREA</u>	Temporary Well Number <u>N/A</u>
Driller <u>L.R. CORDON, R.L. CORDON, L. WATKINS</u>	Coordinates <u>U44, 424 11049, 122</u>
Drilling Co. <u>KAISER</u>	Casing Elevation <u>629.21'</u>
Geologist <u>SHANNON GOODWIN, KAREN OSTER, P. WHITE, R.A. HAGEN, M.A. Chambers</u>	Ground Elevation <u>627.31'</u>
DRILLING METHOD	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	COMPLETION DATA
Cable Tool <u>D N/A H 5'</u>	Drilled Depth <u>215.23' below ground</u>
Drilling Fluid <u>200 E AREA DRILLING SUPPLY H₂O</u>	Completion Depth <u>239' 1"</u>
Other <u>N/A</u>	Date Started <u>7/21/87</u> Completed <u>8/21/87</u>
	Static Water Level/Date <u>721.1' 8/13/87</u>

CASING DATA	
Type	Size
CARBON STEEL CASING	16" SCH 40 A 53 0 to 40' 8"
CARBON STEEL CASING	12" SCH 40 A 53 0 to 105' 3 3/4"
CARBON STEEL CASING	10" SCH 40 A 53 0 to 177' 2 1/2"
CARBON STEEL CASING	8" SCH 40 A 53 0 to 248' 1"
stainless steel casing	4" 0 to 240.1' + 1.9' stickup
Approved By <u>MAC</u>	Date <u>12/12/87</u>

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type	Depth	Schedule	Type	Interval	Volume	
<u>NA</u>			(8" telescoping) 1/4" sl. st. Length (10' 10 1/2") 20' 2"	20' 2" - 210.5'	15-100 lb bags	
			Slot Size (20 slot) 20 slot	210.5' - 222.3'	3-500 lb bags	
			Depths (244.3' - 279' 1' - 233.425') 219.85'	222.3' - 23'	24-100 lb bags	
				portland cement 2.3' - 0'	unknown	
App. By <u>MAC</u>	Date <u>10/1/87</u>		App. By <u>MAC</u>	Date <u>12/2/87</u>	App. By <u>MAC</u>	Date <u>11/20/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
net K	0 - 245'	8/2/87	constant discharge / development	
Neutron	0 - 245'	8/3/87	Length of Test	12 hrs
density	0 - 245'	8/3/87	Volume Pumped	115,000 gal
			Drawdown	6.65'
Approved By <u>MAC</u>	Date <u>8/3/87</u>		Approved By <u>Charles J. Cline</u>	Date <u>8/15/87</u>

OTHER APPLICABLE ITEMS		
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram, Driller's and Geologist's Logs
☒ Concrete Pad	☒ Well Development	
Approved By <u>M.A. Chambers</u>	Date <u>12/13/87</u>	

Reviewed By D.R. McElhann Date 12-21-87

A-1800-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E27-9 Geologist S.M. Gordon, P. White Page 1 of 2
Reviewed by J.K. McChesney Date 12-21-87
K.R. Oster, R. Hagen, M.A. Chamness

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill Rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
cement 0'-2.3' →		5		SILTY SANDY GRAVEL	1.7
		10		" " "	5
		15		" " "	3.3
16" carbon steel casing →		20		" " "	0.9
		25		" " "	2
		30		" " "	5
12" carbon steel casing →		35		" " "	2.7
		40		" " "	3.8
		45		" " "	2.9
10" carbon steel casing →		50		" " "	6.6
		55		" " "	~10
		60		" " "	~5
8" carbon steel casing →		65		" " "	2.6
		70		" " "	2.5
		75		" " "	2.8
4" stainless steel casing →		80		SILTY GRAVELLY SAND	6
		85		SANDY GRAVEL	5.4
		90		SILTY SANDY GRAVEL	6
		95		" " "	5.4
		100		SL. SILTY GRAVELLY SAND	22.3
		105		" " "	4.5
bertrandite crumbles 202.3' →		110		SL. SILTY CL. GRAVELLY SAND	4
2.3' →		115		" " "	15.2
		120		SL. SILTY GRAVELLY SAND	2.4
		125		GRAVELLY SAND	29.4
		130		SANDY GRAVEL	~29

A-1800-186 (2/87)

Reviewed by V.K. Mishra Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill Rod (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
		135		SL SILTY GRAVELLY SAND	4
		140		SL. SILTY, SL. GRAVELLY SAND	8.6
		145		SL. SILTY GRAVELLY SAND	7.5
bentonite crumbles 203.3'-23'		150		" " " "	6
		155		SL SILTY, SL. GRAVELLY SAND	5
		160		SL. SILTY GRAVELLY SAND	6
		165		SILTY SANDY GRAVEL	5
		170		" " "	2.9
10" carbon steel casing		175		SL. SILTY GRAVELLY SAND	5.4
		180		" " " "	20
		185		SILTY SANDY GRAVEL	2.9
8" carbon steel casing		190		" " "	10
4" stainless steel casing		195		" " "	7.5
		200		" " "	3.8
udclay pellets 203.3'-210.5'		205		SL. SILTY GRAVELLY SAND	3.3
		210		" " " "	17.9
4" stainless steel screen		216		" " " "	4
219.85'-240.1'		221		" " " "	10
water table, 221.1' 6/13/87		226		SILTY SANDY GRAVEL	8.6
20/30 silica sand 210.5'-245'		231		" " "	2.2
		236		" " "	6.7
		241		" " "	10
8" stainless steel telescoping screen		245		" " "	1.4
	TD = 245.23'			Basest at 245'	

A-1800-186 (3/B7)

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

Table with 10 columns and 1 row.

SUMMARY OF CONSTRUCTION, WELL 299-E27-10

Construction of this well was initiated on July 15, 1987, and was completed on August 19, 1987. An 8-in-diameter borehole (cased with carbon steel) was drilled to a depth of 240 ft below ground surface. Ground water was encountered at a depth of approximately 217.2 ft, and basalt was encountered at a depth of 240 ft. The borehole was geophysically logged. A 10.9-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 229.1 to 240 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 232.4 ft. A 20.4-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 212 to 232.4 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 206 ft. A 6-ft-thick bentonite pellet seal, followed by bentonite crumbles and granular bentonite (10 mesh), was installed to 2 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11 gpm for 46 min. An estimated total volume of 506 gal was removed during the development. The final turbidity reading of the discharge water was 1.70 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Wells</u>	Well Number <u>299-E27-10</u>
Location <u>200 East Area</u>	Temporary Well Number <u>N/A</u>
Driller <u>Felix Murphy, Ralph Robinson</u>	Coordinates <u>N44.520 W48.522</u>
Drilling Co. <u>Kaiser</u>	Casing Elevation <u>1024.47'</u>
Geologist <u>Karen Oster, Pat White, S. Dudziak, S. Archart, M.A. Chawman, R. Hosen, S. Gendwin, R. Prentice</u>	Ground Elevation <u>1022.42'</u>
COMPLETION DATA	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	Drilled Depth <u>240' below ground</u>
Cable Tool <u>D</u> <u>N/A</u> <u>H 5'-204'</u>	Completion Depth <u>232.4'</u>
Drilling Fluid <u>200E Area Drilling Supply Water</u>	Date Started <u>7/15/87</u> Completed <u>8/11/87</u>
Other <u>Backhoe 0'-5'</u>	Static Water Level/Date <u>217.16' below land surface</u> (PNC 300-E-TAPE #11044) 7/29/87

CASING DATA		
Type	Size	
Carbon Steel Casing	16" Sch 40 A53	0 to 40' 10.25"
Carbon Steel Casing	14" Sch 40 A53	0 to 105' 9.25"
Carbon Steel Casing	10" Sch 40 A53	0 to 167' 3 3/8"
Carbon Steel Casing	8" Sch 40 A53	0 to 245' 1.25"
Stainless steel casing	4"	0 to 232.4' + 2.05' sticking
Approved By <u>MAC</u> Date <u>12/3/87</u>		

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type	Depth	Schedule	Type	Interval	Volume	
			8" st. steel	20' 30" sand	240'-246'	19 FDE bags
			4" st. steel	246'-250'	3 - soil bulk	
			Length	10' 11"	20' 4 1/2"	
			Slot Size	30	20	
			Depths	240.14'	232.4'	
				-229.125'	-212.1'	
			App. By	<u>MAC</u>	Date	<u>12/3/87</u>
			App. By	<u>MAC</u>	Date	<u>11/20/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
Natural X	240' - 0'	7/29/87	constant discharge / development	
Neutron	239' - 2'	7/29/87	Length of Test	9.5 hrs
Density	239' - 0'	7/29/87	Volume Pumped	52.707 gal
			Drawdown	1.94'
Approved By <u>Karen Oster</u> Date <u>7/29/87</u>			Approved By <u>Charles Ole</u> Date <u>8/11/87</u>	

OTHER APPLICABLE ITEMS		
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs
Approved By <u>M.A. Chawman</u>	Date <u>12/3/87</u>	

Reviewed By J. L. Mackham Date 12-21-87

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E27-10 Geologist R. Oster / P. White Page 1 of 2
 Reviewed by J. M. [Signature] Date 12-21-87
 R. Hagen, M.A. Chauruss, S. Dudziak, R. Premtic
 S. Airhart, S. Goodwin

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill Rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
cement 0'-2' →		5'		SILTY SANDY GRAVEL	—
		10		" " "	1.5
		15		SANDY GRAVEL	0.7
		20		" " "	.1
16" carbon steel casing →		25		" " "	2.5
		30		SILTY SANDY GRAVEL	1.1
		35		" " "	2.3
		40		" " "	2.6
12" carbon steel casing →		45		" " "	6
		50		" " "	4
		55		" " "	1.9
		60		" " "	5.4
10" carbon steel casing →		65		" " "	1.6
		70		" " "	2.9
		75		" " "	2
		80		" " "	2
8" carbon steel casing →		85		" " "	2.3
		90		" " "	1.9
		95		" " "	2
		100		" " "	5.4
		105		" " "	1.6
4" stainless steel casing →		110		" " "	3.3
		115		" " "	2.5
		120		" " "	5
		125		" " "	2.3
		126		SLIGHTLY SILTY GR. SAND	—

A-1800-184 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E27-10 Geologist K.A. Oster / P. White Page 2 of 2
 Reviewed by J.S. Malhan Date 12-21-87
 R. Hagan, S. Dudziak, M.A. Chambers, R. Frenette,
 S. Aitchard, S. Goodwin

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
10" Carbon Steel Casing		130		SLIGHTLY SILTY GRAVELLY SAND	2.6
"		135		" " " "	10
"		140		" " " "	8.6
"		145		" " " "	
8" Carbon Steel Casing		150		SILTY SANDY GRAVEL (ACTIVE)	2.7
"		155		" " " "	2
"		160		" " " "	2.2
"		165		SILTY GRAVELLY SAND	2.3
entonite crumbles 200'-2'		170		" " " "	5.4
"		175		SLIGHTLY GRAVELLY SAND	< 1.7
4" stainless steel casing		180		SILTY SANDY GRAVEL	2.2.3
"		185		" " " "	1.8
"		190		SILTY GRAVELLY SAND	2.2
centralizers		195		SILTY SAND GRAVEL	1.6
"		200		SLIGHTLY SILTY GRAVELLY SAND	1.4
volelay pellets 206'-200'		205		" " " "	8.6
4" stainless steel screen	210		SL. SILTY, SL. GRAVELLY SAND	4	
"	215		SLIGHTLY SILTY SAND	8.6	
DLW 215.8, 8/5/87	220		GRAVELLY SILTY SAND	3.8	
20/30 silica sand 240'-206'	225		SILTY SANDY GRAVEL	5	
"	230		" " " "	2.9	
10" of 8" stainless	235		SAND	2.1	
steel telescoping screen	240		SANDY GRAVEL (ACTIVE)	1.3	
"			" " " "	2.7	
"			Ballast at ~240'		

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E28-26

Construction of this well was initiated on September 17, 1987, and was completed on November 6, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 328.5 ft below ground surface. Ground water was encountered at a depth of approximately 280.5 ft, and basalt was encountered at a depth of 326 ft. The borehole was tested for straightness and was geophysically logged. A 10.2-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 315.3 to 325.1 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 298.8 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 278.8 to 298.8-ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 and 10 to 20 mesh) was installed around the 4-in. screen to a depth of 276.2 ft. A 5-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor, hydraulic jacks, and a cable-tool rig. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.5 gpm for 45 min. An estimated total volume of 517.5 gal was removed during the development. The final turbidity reading of the discharge water was 1.47 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Wells</u>	Well Number <u>299-E28-26</u>
Location <u>200 East Area</u>	Temporary Well Number <u>N/A</u>
Driller <u>C. Umbley</u>	Coordinates <u>N44 446 W55 606</u>
Drilling Co. <u>Kaiser Engineering Hanford</u>	Casing Elevation <u>1087.26'</u>
Geologist <u>G.S. Davis, H.A. Chambers, C. Scott</u>	Ground Elevation <u>684.84'</u>
<u>L. Feir, J. Robinson, S. Teel</u>	
DRILLING METHOD	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	COMPLETION DATA
Cable Tool <u>D</u> <u>H</u>	Drilled Depth <u>328.5' below ground</u>
Drilling Fluid <u>200 East Water</u>	Completion Depth <u>298.8'</u>
Other <u>Backhoe 0-5'</u>	Date Started <u>9/17/87</u> Completed <u>11/6/87</u>
	Static Water Level/Date <u>280.5' 10/12/87</u>

CASING DATA	
Type	Size
<u>carbon steel</u>	<u>16"</u> <u>0'</u> to <u>79'9 1/2"</u> <u>Stickup</u>
<u>"</u>	<u>12"</u> <u>0'</u> to <u>143'9 3/4"</u>
<u>"</u>	<u>8"</u> <u>0'</u> to <u>220'1 1/2"</u>
<u>stainless steel</u>	<u>4"</u> <u>0'</u> to <u>298.8'</u> <u>+ 2.42' stickup</u>

Approved By MAC Date 12/3/87

PERFORATIONS		SCREEN		ANNULAR SEAL	
Type	Schedule	Type	Length	Type	Interval
<u>N/A</u>		<u>3" at 20' below casing / 4" at 20'</u>	<u>20'</u>	<u>silica sand</u>	<u>225.1'-276.2'</u>
		<u>Slot Size 20'</u>	<u>20'</u>	<u>wellbore pellets</u>	<u>276.2'-277.1'</u>
		<u>Depths 315.1' - 298.8'</u>	<u>298.8'</u>	<u>wellbore pellets</u>	<u>277.1'-2'</u>
		<u>325.1' - 298.8'</u>	<u>298.8'</u>	<u>sement</u>	<u>2'-0'</u>
App. By <u>MAC</u>	Date <u>11/12/87</u>	App. By <u>MAC</u>	Date <u>12/3/87</u>	App. By <u>MAC</u>	Date <u>12/3/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	Length of Test
<u>density</u>	<u>2' - 325'</u>	<u>10/15/87</u>	<u>N/A</u>	
<u>neutron</u>	<u>3' - 325'</u>	<u>10/15/87</u>		
<u>nat. X</u>	<u>3' - 326'</u>	<u>10/15/87</u>		
Approved By <u>M.A. Chambers</u>	Date <u>10/15/87</u>	Approved By <u>al e l l e</u>	Date <u>11/20/87</u>	

OTHER APPLICABLE ITEMS		
<u>MAC</u> Steam Cleaning <u>9/17/87</u>	<u>MAC</u> Protective Steel Posts	<u>✓</u> Downhole TV Inspection
<u>MAC</u> Storage of Const. Material	<u>MAC</u> Safety Paint	<u>N/A</u> Well Abandonment
<u>MAC</u> Tool Lubricants	<u>MAC</u> Straightness Test <u>11/18/87</u>	<u>✓</u> Complete As-Built Diagram, Driller's and Geologist's Logs
<u>MAC</u> Concrete Pad	<u>MAC</u> Well Development	
Approved By <u>M.A. Chambers</u>	Date <u>12/3/87</u>	

Reviewed By J.L. Mishan Date 12-21-87

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E2B-26Geologist G. Davis, M.A. Champagne Page 1 of 3C. Scott, L. Fair, J. Robinson, S. TeelReviewed by J.L. MuhlDate 12-21-84

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>Cement 0'-3'</u>		<u>6</u>		<u>SILTY SANDY GRAVEL</u>
<u>16" Carbon Steel Casing</u>		<u>10</u>		<u>" " "</u>
		<u>15</u>		<u>" " "</u>
		<u>20</u>		<u>" " "</u>
<u>12" Carbon Steel Casing</u>		<u>25</u>		<u>SANDY GRAVEL</u>
		<u>30</u>		<u>SL. SILTY SL. GRAVELLY SAND</u>
		<u>35</u>		<u>SILTY SANDY GRAVEL</u>
		<u>40</u>		<u>" " "</u>
		<u>45</u>		<u>" " "</u>
		<u>50</u>		<u>" " "</u>
		<u>55</u>		<u>" " "</u>
		<u>60</u>		<u>" " "</u>
		<u>65</u>		<u>" " "</u>
		<u>70</u>		<u>SLIGHTLY SILTY GRAVELLY SAND</u>
<u>Bentonite Crumbles</u>		<u>75</u>		<u>SAND</u>
<u>27" 1" - 3"</u>		<u>80</u>		<u>SLIGHTLY GRAVELLY SAND</u>
		<u>85</u>		<u>SLIGHTLY SILTY SAND</u>
		<u>90</u>		<u>" " "</u>
		<u>95</u>		<u>" " "</u>
<u>10" carbon steel casing</u>		<u>100</u>		<u>SL. SILTY SL. GRAVELLY SAND</u>
		<u>105</u>		<u>" " "</u>
<u>8" carbon steel casing</u>		<u>110</u>		<u>SLIGHTLY SILTY SAND</u>
		<u>115</u>		<u>" " "</u>
<u>4" stainless steel casing</u>		<u>120</u>		<u>" " "</u>
		<u>125</u>		<u>" " "</u>
		<u>130</u>		<u>SLIGHTLY SILTY SLIGHTLY GRAVELLY SAND</u>

A-1800-186 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E28-26 Geologist G. Davis, M.A. Chommanet Page 2 of 3C. Scott, L. Feir, J. Robinson, S. TeelReviewed by J. M. ShanDate 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SLIGHTLY SILTY SLIGHTLY GRAVELLY SAND
		140		" " " " "
		145		SAND
		150		"
		155		"
12" carbon steel casing		160		SLIGHTLY SILTY SAND
		165		SAND
		170		SL. SILTY SL. GRAVELLY SAND
		175		SILTY SANDY GRAVEL
		180		SAND
10" carbon steel casing		185		"
		190		SILTY SANDY GRAVEL
		195		" " "
		200		SANDY GRAVEL
benonite crumbles 3'-271"		205		SLIGHTLY SILTY SAND
		210		SAND
		215		SLIGHTLY SILTY SAND
		220		SILTY SAND
		225		SILTY SANDY GRAVEL
		230		" " "
		235		" " "
		242		" " "
8" carbon steel casing		247		" " "
		250		NO sample
4" stainless steel casing		255		SILTY SANDY GRAVEL
centralizers at 258'		260		" " "

A-1800-100 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E28-26 Geologist N.A. Chamness, G.S. Davis Page 3 of 3
C. Scott, L. Fair, J. Robinson, S. TeelReviewed by J. R. Smith Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Bentonite crumbles 271' - 271'1" →		265		SILTY SANDY GRAVEL
4" stainless steel casing →		270		" " "
Volclay pellets 271' - 276'2 1/2" →		275		" " "
BW 279.31' 10/20/87 →		280		" " "
4" stainless steel 20 slot screen →		285		" " "
from 299' - 299'1" →		290		NO sample
276'2 1/2" - 293' 20/40 silica sand →		295		SILTY SANDY GRAVEL
293' - 299' 10/20 silica sand →		300		" " "
20/40 silica sand →		305		" " "
		310		" " "
8" carbon steel casing →		315		SL SILTY GRAVELLY SAND
		320		SILTY SANDY GRAVEL
8" 20 slot st. steel telescoping screen 315' - 325.1' →		325		" " "
		326		Basest mt - 326'
	TD = 328.45'		TB 328.45'	

A-1800-188 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E28-27

Construction of this well was initiated on September 2, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 301.4 ft below ground surface. Ground water was encountered at a depth of approximately 273.2 ft. Basalt was not encountered by this borehole. The borehole was geophysically logged. A regular straightness test was not performed; however, the telescoping screen was set without any problems. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 291.1 to 301.4 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 289.9 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 269.9 to 289.9 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 263.8 ft. A 4.5-ft-thick bentonite pellet seal, followed by bentonite crumbles, was installed to 3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.5 gpm for 67 min. An estimated total volume of 772 gal was removed during the development. The final turbidity reading of the discharge water was 1.52 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Wells</u>	Well Number <u>299-E28-27</u>
Location <u>200 East Area</u>	Temporary Well Number <u>N/A</u>
Driller <u>FELTY MURPHY, RALPH R. BARNES</u>	Coordinates <u>N 44.595 W 154.130</u>
Drilling Co. <u>Kaiser Engineering Portland</u>	Casing Elevation <u>687.37'</u>
Geologist <u>M.A. Chavira, C. Smith, SM, Gerdwin L. Felt, J. Robinson, & Davis, R. Premier</u>	Ground Elevation <u>678.18'</u>
DRILLING METHOD	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	
Cable Tool <u>D 65-255' H 5-60, 255'-3015'</u>	
Drilling Fluid <u>200 E DRILL SUPPLY WATER</u>	
Other <u>Backhoe 0'-7'</u>	
COMPLETION DATA	
Drilled Depth <u>301.5'</u> below ground	
Completion Depth <u>289.9'</u>	
Date Started <u>9/12/87</u> Completed <u>9/30/87</u>	
Static Water Level/Date <u>273.2' 9/29/87</u>	

CASING DATA			
Type	Size		
<u>CARBON STEEL CASING</u>	<u>16"</u>	<u>0</u>	<u>to 58' 4 1/4"</u>
<u>CARBON STEEL CASING</u>	<u>12"</u>	<u>0</u>	<u>to 124' 1 1/4"</u>
<u>"</u>	<u>10"</u>	<u>0</u>	<u>to 206' 10 1/2"</u>
<u>"</u>	<u>8"</u>	<u>0</u>	<u>to 302' 9"</u>
Approved By <u>MAC</u>		Date <u>12/13/87</u>	
<u>stainless steel casing</u>		<u>4"</u>	
		<u>289.9' + 2.19' stickup</u>	

PERFORATIONS		SCREEN		ANNULAR SEAL	
Type	Schedule	Type	Interval	Type	Volume
Depth		Length		20/20 silica sand	
<u>N/A</u>		Slot Size		20/20 pellets	
		Depths		20/20 crumbles	
App. By <u>MAC</u>	Date <u>10/27/87</u>	App. By <u>MAC</u>	Date <u>11/20/87</u>	App. By <u>MAC</u>	Date <u>11/20/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
<u>MT-GAMMA</u>	<u>289' - 3'</u>	<u>12-3-87</u>	<u>development / constant discharge</u>	
<u>NEUTRON</u>	<u>289' - 3'</u>	<u>12-3-87</u>	Length of Test	<u>5.5 hrs</u>
<u>DENSITY</u>	<u>289' - 1'</u>	<u>12-3-87</u>	Volume Pumped	<u>42,000 gal.</u>
			Drawdown	<u>0.9'</u>
Approved By <u>D.S. McLean</u> Date <u>12-21-87</u>			Approved By <u>Chas. J. Deane</u> Date <u>9/29/87</u>	

OTHER APPLICABLE ITEMS		
<u>MAC</u> Steam Cleaning	<u>MAC</u> Protective Steel Posts	<u>MAC</u> Downhole TV Inspection
<u>MAC</u> Storage of Const. Material	<u>MAC</u> Safety Paint	<u>N/A</u> Well Abandonment
<u>MAC</u> Tool Lubricants	<u>MAC</u> Straightness Test	<u>MAC</u> Complete As-Built Diagram, Driller's and Geologist's Logs
<u>MAC</u> Concrete Pad	<u>MAC</u> Well Development	
Approved By <u>M.A. Chavira</u>	Date <u>12/13/87</u>	

Reviewed By D.S. McLean Date 12-21-87

A-1880-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E28-27 Geologist H.A. Charnock, C. Scott Page 1 of 3
S.M. Goodwin, R.L. Premack
L. Fair
Reviewed by J.L. McShan Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		DRILL RATE FT/HR
Description	Diagram		Diagram Litho.	Lithologic Description	
3 1/2" CONCRETE PLUG		5		SILTY SANDY GRAVEL	N/A
11" carbon steel casing		10		SANDY GRAVEL	2.0'
		15		SILTY SANDY GRAVEL	1.4'
		20		" " "	3.3'
		25		" " "	1.25'
		30		" " "	1.4'
		35		" " "	2.5'
bedrock crumbles 3'-250'		40		" " "	2.8'
		45		" " "	2.5'
		50		" " "	1.8'
		55		SANDY GRAVEL	2.5'
		60		SL. SILTY SL. GRAVELLY SAND	5'
12" carbon steel casing		65		SAND	4.0'
		70		SLIGHTLY GRAVELLY SAND	2.3'
		75		" " "	5.0'
8" carbon steel casing		80		SLIGHTLY SILTY SAND	3.0'
		85		" " "	8.6'
4" stainless steel casing		90		SLIGHTLY SILTY GRAVELLY SAND	5.0'
		95		SAND	4.3'
		100		SLIGHTLY GRAVELLY SAND	62.1'
		105		GRAVELLY SAND	...
		110		SL. SILTY, SL. GRAVELLY SAND	2.3'
		115		SLIGHTLY GRAVELLY SAND	15.2'
10" carbon steel casing		120		SAND	4.3'
		125		SLIGHTLY GRAVELLY SAND	20.1'
		130		" " "	4'

A-1800-106 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E2B-27 Geologist MACHWEESE, C. Scott Page 2 of 3
Reviewed by W. E. Mather S. Goodwin, R. L. Plumb
Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rod (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
		135		sl. gravelly sand	3.8
		140		SAND	10
		145		SLIGHTLY GRAVELLY SAND	2.8
		150		SAND	6
		155		"	6
bentonite crumbles 3'-250'3"		160		"	22.7
		165		"	3.6
		170		"	2.4
		175		"	10
		180		"	~6
		185		sl. silty, sl. gravelly sand	10
		190		silty sandy gravel (last 182'8")	6
		195		sandy gravel	2.1
		200		gravelly sand	2.6
10" carbon steel casing		205		"	5.4
		210		SILTY GRAVELLY SAND	2.8
		215		silty sandy gravel	5
		220		SLIGHTLY GRAVELLY SAND	1.2
8" carbon steel casing		225		sl. silty sand	10
		230		sl. gravelly sand	—
4" stainless steel casing		235		" " "	—
		240		silty sandy gravel	4.3
		245		" " "	0.9
centralizers on 4" casing		250		" " "	2.5
		255		" " "	2.1
viscosity pellets 203'9"-250'3"		260		" " "	1

A-1000-100 (3/87)

Reviewed by J. L. Mathen Date 12-21-87

[illegible]

A-1000-106 (3/87)

AS BUILT DIAGRAM		PROJECT NO.	
DATE		SHEET NO.	
DRAWN BY		CHECKED BY	
REVISIONS		NOTES	
1	AS BUILT	1	AS BUILT
2	AS BUILT	2	AS BUILT
3	AS BUILT	3	AS BUILT
4	AS BUILT	4	AS BUILT
5	AS BUILT	5	AS BUILT
6	AS BUILT	6	AS BUILT
7	AS BUILT	7	AS BUILT
8	AS BUILT	8	AS BUILT
9	AS BUILT	9	AS BUILT
10	AS BUILT	10	AS BUILT
11	AS BUILT	11	AS BUILT
12	AS BUILT	12	AS BUILT
13	AS BUILT	13	AS BUILT
14	AS BUILT	14	AS BUILT
15	AS BUILT	15	AS BUILT
16	AS BUILT	16	AS BUILT
17	AS BUILT	17	AS BUILT
18	AS BUILT	18	AS BUILT
19	AS BUILT	19	AS BUILT
20	AS BUILT	20	AS BUILT
21	AS BUILT	21	AS BUILT
22	AS BUILT	22	AS BUILT
23	AS BUILT	23	AS BUILT
24	AS BUILT	24	AS BUILT
25	AS BUILT	25	AS BUILT
26	AS BUILT	26	AS BUILT
27	AS BUILT	27	AS BUILT
28	AS BUILT	28	AS BUILT
29	AS BUILT	29	AS BUILT
30	AS BUILT	30	AS BUILT
31	AS BUILT	31	AS BUILT
32	AS BUILT	32	AS BUILT
33	AS BUILT	33	AS BUILT
34	AS BUILT	34	AS BUILT
35	AS BUILT	35	AS BUILT
36	AS BUILT	36	AS BUILT
37	AS BUILT	37	AS BUILT
38	AS BUILT	38	AS BUILT
39	AS BUILT	39	AS BUILT
40	AS BUILT	40	AS BUILT
41	AS BUILT	41	AS BUILT
42	AS BUILT	42	AS BUILT
43	AS BUILT	43	AS BUILT
44	AS BUILT	44	AS BUILT
45	AS BUILT	45	AS BUILT
46	AS BUILT	46	AS BUILT
47	AS BUILT	47	AS BUILT
48	AS BUILT	48	AS BUILT
49	AS BUILT	49	AS BUILT
50	AS BUILT	50	AS BUILT
51	AS BUILT	51	AS BUILT
52	AS BUILT	52	AS BUILT
53	AS BUILT	53	AS BUILT
54	AS BUILT	54	AS BUILT
55	AS BUILT	55	AS BUILT
56	AS BUILT	56	AS BUILT
57	AS BUILT	57	AS BUILT
58	AS BUILT	58	AS BUILT
59	AS BUILT	59	AS BUILT
60	AS BUILT	60	AS BUILT
61	AS BUILT	61	AS BUILT
62	AS BUILT	62	AS BUILT
63	AS BUILT	63	AS BUILT
64	AS BUILT	64	AS BUILT
65	AS BUILT	65	AS BUILT
66	AS BUILT	66	AS BUILT
67	AS BUILT	67	AS BUILT
68	AS BUILT	68	AS BUILT
69	AS BUILT	69	AS BUILT
70	AS BUILT	70	AS BUILT
71	AS BUILT	71	AS BUILT
72	AS BUILT	72	AS BUILT
73	AS BUILT	73	AS BUILT
74	AS BUILT	74	AS BUILT
75	AS BUILT	75	AS BUILT
76	AS BUILT	76	AS BUILT
77	AS BUILT	77	AS BUILT
78	AS BUILT	78	AS BUILT
79	AS BUILT	79	AS BUILT
80	AS BUILT	80	AS BUILT
81	AS BUILT	81	AS BUILT
82	AS BUILT	82	AS BUILT
83	AS BUILT	83	AS BUILT
84	AS BUILT	84	AS BUILT
85	AS BUILT	85	AS BUILT
86	AS BUILT	86	AS BUILT
87	AS BUILT	87	AS BUILT
88	AS BUILT	88	AS BUILT
89	AS BUILT	89	AS BUILT
90	AS BUILT	90	AS BUILT
91	AS BUILT	91	AS BUILT
92	AS BUILT	92	AS BUILT
93	AS BUILT	93	AS BUILT
94	AS BUILT	94	AS BUILT
95	AS BUILT	95	AS BUILT
96	AS BUILT	96	AS BUILT
97	AS BUILT	97	AS BUILT
98	AS BUILT	98	AS BUILT
99	AS BUILT	99	AS BUILT
100	AS BUILT	100	AS BUILT

SUMMARY OF CONSTRUCTION, WELL 299-E32-2

Construction of this well was initiated on August 14, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 289.1 ft below ground surface. Ground water was encountered at a depth of approximately 262.3 ft and basalt was encountered at a depth of 287 ft. The borehole was tested for straightness and was geophysically logged. A 10-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 279.2 to 289.2 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 277.8 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 257.8 to 277.8 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in.-screen to a depth of 251.9 ft. A 5-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 12 gpm for 45 min. An estimated total volume of 540 gal was removed during the development. The final turbidity reading of the discharge water was 2.30 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project 200 Area RCRA Monitoring Wells
 Location 200 East Area
 Driller Louis Watkins / Lyn Gordon / Craig
 Drilling Co. Kaiser Engineers Wormsley
 Geologist C. Hodge, K. Oster, M. Chammah, A. Davis,
R. Premzik, S. Gaudin, R. Kohl, P. White, S. Tol

Well Number 299-E32-2
 Temporary Well Number N/A
 Coordinates N45,904 W56,515
 Casing Elevation 1670.06'
 Ground Elevation 1667.91'

DRILLING METHOD
 Rotary Air N/A Mud N/A
 Cable Tool D ✓ H ✓
 Drilling Fluid 200 Area drilling supply water
 Other N/A

COMPLETION DATA
 Drilled Depth 289.06' below ground
 Completion Depth 277.75'
 Date Started 8/14/87 Completed 9/30/87
 Static Water Level/Date 262.33' 9/17/87

CASING DATA
 Type Size
CARBON STEEL 16" 0' to 56' 7 3/4"
" 12" 0' to 125' 3 3/4"
" 10" 0' to 184' 3 3/4"
" 8" 0' to 205' 4 1/4"
stainless steel 4" 0' to 277.75' + 2.15' pickup
 Approved By MAC Date 12/2/87

PERFORATIONS
 Type Depth Schedule
N/A
 App. By MAC Date 11/11/87

SCREEN
 Type 8" Reelaping 4" st. steel
 Length 10.0 20'
 Slot Size 30 20
 Depths 279.17-289.17' 277.75'-
257.75'
 App. By MAC Date 12/3/87

ANNULAR SEAL
 Type Interval Volume
20/30 silica sand 284.55-286.9 4 3/4" wellbore
port. pellets 286.9-288.9 4 3/4" wellbore
port. crumbles 288.9-290.5 350 wellbore
cement 5'-0' unknown
 App. By MAC Date 11/20/87

GEOPHYSICAL LOGGING
 Sondes Interval Date
Natural Y 286' - 0' 8/28/87
Neutron 286' - 0' 8/28/87
Density 286' - 3" 8/28/87
 Approved By Greg Davis Date 8/28/87

AQUIFER TESTING
 Type of Test development / constant discharge
 Length of Test 11 hrs
 Volume Pumped 71,500 gal
 Drawdown 0.16'
 Approved By Charles Davis Date 9/8/87

OTHER APPLICABLE ITEMS
☒ Steam Cleaning ☒ Protective Steel Posts ☒ Downhole TV Inspection
☒ Storage of Const. Material ☒ Safety Paint ☒ Well Abandonment
☒ Tool Lubricants ☒ Straightness Test ☒ Complete As-Built Diagram,
☒ Concrete Pad ☒ Well Development Driller's and Geologist's Logs
 Approved By M.A. Chammah Date 12/3/87

Reviewed By J.L. Melham Date 12-21-87

A-1000-107 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E32-2 Geologist K.R. Oster, P. White, C. Hodge, Page 1 of 3
S. Teal, R. Premic, G. Davis, B. Kahl, S.M. Goodman, M. Chambers
Reviewed by J.E. Muth Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
cement 0'-5' →		5		SILTY SANDY GRAVEL
16" carbon steel casing →		10		SLIGHTLY SILTY SAND
		15		SILTY SANDY GRAVEL
		20		" " "
		25		" " "
		30		" " "
burtonite crumbles 246.9'-5' →		35		" " "
		40		" " "
		45		" " "
		50		" " "
		55		SILTY GRAVELLY SAND
		60		" " "
		65		SILTY SANDY GRAVEL
12" CARBON STEEL CASING →		70		SAND
		75		" "
		80		SILTY SANDY GRAVEL
		85		SLIGHTLY SILTY SLIGHTLY GRAVELLY SAND
10" carbon steel casing →		90		" " "
		95		SLIGHTLY GRAVELLY SAND
8" carbon steel casing →		100		" " "
		105		" " "
4" stainless steel casing →		110		" " "
		115		SLIGHTLY SILTY SAND
		120		" " "
		125		" " "
		130		" " "

A-1820-106 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E32-2

Geologist C. Hodge, K. Oster, G. Davis, P. Whitepage 02 of 3
S. Teel, R. Prentiss, S. Goodwin, M. Chambers, B. Kahl

Reviewed by W. McShan

Date 12-21-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SLIGHTLY SILTY SAND
		140		SILTY SAND
		145		" "
		150		SL. SILTY, SL. GRAVELLY SAND
		155		SLIGHTLY SILTY SAND
10" carbon steel casing		160		" "
		165		" "
		170		" "
8" carbon steel casing		175		" "
		180		" "
4" stainless steel casing		185		" "
		190		SILTY SANDY GRAVEL
		195		" "
		200		SLIGHTLY SILTY SAND
		205		" "
		210		SILTY SANDY GRAVEL
		215		" " "
		220		" " "
beaumont crumbles 244'-5'		225		" " "
		230		" " "
		235		" " "
		240		" " "
		245		SL. SILTY GRAVELLY SAND
beaumont pellets 251'-246.9'		250		SILTY SANDY GRAVEL
silica sand 251'-258'		255		" " "
4" 20 slot stainless steel screen		260		" " "

A-1000-100 (11/77)

Geologist C. Hotal, P. White, G. Davis, K. Ostapage 3 of 3
M. Channett, B. Kahl, R. Prentice, S. Goodwin, J. Teel

Reviewed by

Date 12-21-87

A-1000-100 (3/07)

SUMMARY OF CONSTRUCTION, WELL 299-E32-3

Construction of this well was initiated on August 14, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 304 ft below ground surface. Ground water was encountered at a depth of approximately 269 ft. Basalt was not encountered by this borehole. The borehole was tested for straightness and was geophysically logged. A 10.1-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 291.1 to 301 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 286.2 ft. A 20-ft length of 4-in. diameter stainless steel screen (20 slot) was set at a depth of 266.2 to 286.2 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 262 ft. A 6.7-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8) and granular bentonite (10 mesh), was installed to 3.4 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. A rock was found lodged in the well and a bentonite plug was found inside the screen immediately above the water table. The rock was knocked to the bottom of the well. The bentonite plug was removed by bailing, and the screen was pressure washed with water from an approved source. The well was then swabbed and bailed again. Reinspection of the well found it to be clean.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10 gpm for 45 min. An estimated total volume of 450 gal was removed during the development. The final turbidity reading of the discharge water was 0.60 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Battelle <small>Pacific Northwest Laboratories</small>		Well Completion Report/Title III Inspection List	
Project <u>200 Area RCRA Monitoring Well</u> Location <u>200 EAST</u> Driller <u>BLIN AMOS/DAVID T. G. SMITH/ALICE THOMPSON</u> Drilling Co. <u>KAIJER</u> Geologist <u>WHITE / SCOTT / K. AUL, CHAMBERS</u>		Well Number <u>299-E32-3</u> Temporary Well Number <u>N/A</u> Coordinates <u>N45.1671 W51.721</u> Casing Elevation <u>1676.51'</u> Ground Elevation <u>1675.32'</u>	
DRILLING METHOD Rotary Air <u>N/A</u> Mud <u>N/A</u> Cable Tool <u>D 75'-255' H 0-70' 260'</u> Drilling Fluid <u>200 E Drilling Supply Water</u> Other <u>Backhoe 0'-5'</u>		COMPLETION DATA Drilled Depth <u>304'</u> <u>below ground</u> Completion Depth <u>286'2"</u> Date Started <u>8/14/87</u> Completed <u>9/30/87</u> Static Water Level/Date <u>269.03' / 9/4/87</u>	
CASING DATA			
Type <u>Carbon steel</u> Size <u>16"</u> <u>0'</u> to <u>60'5"</u> <u>"</u> <u>12"</u> <u>0'</u> to <u>125'10 1/4"</u> <u>"</u> <u>10"</u> <u>0'</u> to <u>186'6 1/4"</u> <u>"</u> <u>8"</u> <u>0'</u> to <u>306'6"</u> <u>stainless steel</u> <u>4"</u> <u>0'</u> to <u>286'75" + 1.19' stickup</u>		Approved By <u>MAC</u> Date <u>11/24/87</u>	
PERFORATIONS Type _____ Depth _____ Schedule _____ <u>N/A</u> App. By <u>MAC</u> Date <u>11/12/87</u>		SCREEN Type <u>8" Johnson</u> <u>4"</u> Length <u>10' 3/4"</u> <u>20'</u> Slot Size <u>20-20</u> <u>20-20</u> Depths <u>291-301'</u> <u>266'2"-286'2"</u> App. By <u>MAC</u> Date <u>11/14/87</u>	
ANNULAR SEAL Type Interval Volume <u>20-30 Silty Sand</u> <u>301'-262'</u> <u>16-100 lb bags</u> <u>Volex Tubing</u> <u>262'-255'</u> <u>5-5 gal buckets</u> <u>benzene emulsion</u> <u>255'-8'-34'</u> <u>32 100 lb bags</u> <u>"</u> <u>255'-8'-34'</u> <u>29 50 lb bags</u> <u>Cement</u> <u>2'-4"-C</u> App. By <u>MAC</u> Date <u>11/24/87</u>		App. By <u>MAC</u> Date <u>11/24/87</u>	
GEOPHYSICAL LOGGING Sondes Interval Date <u>Natural 8</u> <u>302'-3'</u> <u>8/28/87</u> <u>Neutron</u> <u>302'-3'</u> <u>8/28/87</u> <u>Density</u> <u>302'-2'</u> <u>8/28/87</u> _____ _____ _____ Approved By <u>Karen R. Oster</u> Date <u>8/28/87</u>		AQUIFER TESTING Type of Test <u>development / constant discharge</u> Length of Test <u>12 hrs</u> Volume Pumped <u>90,700 gal</u> Drawdown <u>7.2'</u> _____ _____ Approved By <u>Charles J. (C) [Signature]</u> Date <u>9/2/87</u>	
OTHER APPLICABLE ITEMS <div style="display: flex; flex-wrap: wrap;"> <div style="width: 33%;"> ☒ Steam Cleaning PW ☒ Storage of Const. Material PW ☒ Tool Lubricants MAC ☒ Concrete Pad Approved By <u>M.A. Chambers</u> </div> <div style="width: 33%;"> ☒ Protective Steel Posts ☒ Safety Paint ☒ Straightness Test ☒ Well Development MAC Date <u>11/14/87</u> </div> <div style="width: 33%;"> ☒ Downhole TV Inspection ☒ Well Abandonment ☒ Complete As-Built Diagram, Driller's and Geologist's Logs </div> </div>			

Reviewed By J. L. McShane Date 12-22-87

A-1000-187 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E3432-3 Geologist White / Kahl / Scott Page 1 of 3

H.A. Chambers

Reviewed by J.E. McLean Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		(ft/hr) Drill rate
Description	Diagram		Diagram Litho.	Lithologic Description	
<u>Cement 0'-3.4'</u>		5		<u>SILTY SANDY GRAVEL</u>	N/A
<u>16" carbon steel casing</u>		10		" "	1.9
		15		" "	3.5
		20		" "	3.2
		25		" "	2.9
<u>12" carbon steel casing</u>		30		" "	5.5
		35		" "	2.2
<u>10" carbon steel casing</u>		40		" "	1.3
		45		" "	6
<u>8" carbon steel casing</u>		50		" "	3.8
		55		" "	4.6
<u>4" stainless steel casing</u>		60		" "	2.5
		65		<u>SLIGHTLY SILTY GRAVELLY SAND</u>	6.7
<u>bentonite crumbles 255' 6" - 3.4'</u>		70		" " " "	8.6
		75		<u>SL. SILTY SL. GRAVELLY SAND</u>	15
		80		<u>SL. SILTY GRAVELLY SAND</u>	7.5
		85		" " " " " "	10
		90		<u>SLIGHTLY GRAVELLY SAND</u>	15
		95		" " " " " "	20
		100		" " " " " "	12
		105		<u>SL. SILTY SL. GRAVELLY SAND</u>	7.5
		110		<u>SLIGHTLY SILTY SAND</u>	6.7
		115		" " " " " "	4.6
		120		<u>SILTY SAND</u>	3.3
		125		<u>GRAVELLY SAND</u>	2.6
		130		<u>SL. SILTY SL. GRAVELLY SAND</u>	7.5

A-1800-100 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E32-3 Geologist KAHL / WHITE/SCOTT Page 2 of 3Reviewed by V.K. McShan Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
		135		SLIGHTLY SILTY SAND	10
10" carbon steel casing		140		SILTY SAND	5
		147		SLIGHTLY SILTY, SLIGHTLY GRAVELLY SAND	9
		150		SLIGHTLY SILTY SAND	.7
		155		"	4.6
		160		"	20
bentonite crumbles 255' to 244'		165		"	5.5
		170		"	1.4
		175		"	10
		180		SAND	5.5
		185		"	15
		190		"	10
		195		SANDY GRAVEL	3.3
8" carbon steel casing		200		SILTY SANDY GRAVEL	1.7
		205		"	10
4" stainless steel casing		210		"	2.5
		215		"	15
		220		"	2.7
		225		"	6
		230		"	8.6
		235		"	7.5
		240		"	7.5
centralizers		245		"	4.3
		250		"	2.8
bentonite pellets 262' - 255' to 244'		255		"	2
		260		"	2

A-1000-106 (2/87)

Reviewed by V.L. Mc Sherr

Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rate (ft./hr.)
Description	Diagram		Diagram Litho.	Lithologic Description	
volclay pellets 255' 8" - 262'		265		SILTY SANDY GRAVEL	4
water table 269.03' 9/4/77		270		" " "	2.1
4" st. steel, 20 slot screen		275		SLIGHTLY SILTY GRAVELLY SAND	4.3
8" carbon steel casing		280		SILTY SANDY GRAVEL	3.8
20/30 silica sand, 261' - 262'		285		" SAND	1.9
		290		SLIGHTLY SILTY SAND	2.4
		295		SILTY SANDY GRAVEL	2.9
8" telescoping screen, 20 slot, st. steel		300		SLIGHTLY SILTY GRAVELLY SAND	2.9
		303		GRAVELLY SAND	1.2

A-1802-180 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E32-4

Construction of this well was initiated on August 28, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 311 ft below ground surface. Ground water was encountered at a depth of approximately 280.3 ft. Basalt was not encountered by this borehole. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 298 to 308.3 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 298.1 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 278.1 to 298.1 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 272 ft. A 5.4-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 12 gpm for 40 min. An estimated total volume of 480 gal was removed during the development. The final turbidity reading of the discharge water was 2.20 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Battelle <small>Pacific Northwest Laboratories</small>		Well Completion Report/Title III Inspection List	
Project <u>200 Area RCRA Monitoring Wells</u> Location <u>200 East Area</u> Driller <u>Olin A. / Lyn Gordon</u> Drilling Co. <u>Kaiser</u> Geologist <u>C. Hodge / C. Scott / M.A. Chammey</u> Koster <u>S. Gordon / K. Lygo / L. Fair / S. Arhart / G. Davis</u> J. Robinson, J. Phillips		Well Number <u>299-E32-4</u> Temporary Well Number <u>N/A</u> Coordinates <u>N44.985 W26.712</u> Casing Elevation <u>1685.88'</u> Ground Elevation <u>1684.64'</u>	
DRILLING METHOD Rotary Air <u>Mud</u> Cable Tool <u>D 63'-232' H 8'-63'</u> Drilling Fluid <u>200 East Area water 232'-310'</u> Other <u>Backhoe 0'-5'</u>		COMPLETION DATA Drilled Depth <u>311'</u> Completion Depth <u>298' 1"</u> Date Started <u>8/28/87</u> Completed <u>9/30/87</u> Static Water Level/Date <u>282.34' 9/15/87</u>	
CASING DATA			
Type <u>Carbon steel</u> Size <u>16" 0</u> to <u>58' 3 1/4"</u> " <u>12" 0</u> to <u>122' 7 3/4"</u> " <u>10" 0</u> to <u>201' 0"</u> " <u>8" 0</u> to <u>310'</u> Approved By <u>MAC</u> Date <u>11/24/87</u> <u>stainless steel</u> <u>4" 0</u> to <u>297.4' + 1.24' stickup</u>			
PERFORATIONS		SCREEN	
Type	Schedule	Type <u>8" st. steel 4" st. steel</u>	
Depth		Length <u>10' 5" 20'</u>	
<u>N/A</u>		Slot Size <u>20 20</u>	
		Depths <u>308.25'-118' 258' 1"-278' 1"</u>	
App. By <u>MAC</u>	Date <u>11/23/87</u>	App. By <u>MAC</u>	Date <u>11/24/87</u>
ANNULAR SEAL			
Type	Interval	Volume	
<u>20/30 silica sand</u>	<u>209'-272'</u>	<u>12.5 milb bags</u>	
<u>brat pellets</u>	<u>272'-265.7'</u>	<u>4.5 gal. buckets</u>	
<u>brat crumbles</u>	<u>265.7'-3'</u>	<u>340 50lb bags</u>	
<u>Packhead cement</u>	<u>3'-0'</u>	<u>unknown</u>	
App. By <u>MAC</u>	Date <u>9/20/87</u>		
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes	Interval	Date	Type of Test <u>development / constant discharge</u>
<u>nat x</u>	<u>308 - 0</u>	<u>9/14/87</u>	Length of Test <u>1.3 hrs</u>
<u>density</u>	<u>308 - 0</u>	<u>9/14/87</u>	Volume Pumped <u>10,000 gal.</u>
<u>neutron</u>	<u>308 - 0</u>	<u>9/14/87</u>	Drawdown <u>12.33' 0</u>
Approved By <u>R. Brown</u>	Date <u>9/15/87</u>	Approved By <u>Charles L. O'Brien</u>	Date <u>9/21/87</u>
OTHER APPLICABLE ITEMS			
<u>MAC</u> Steam Cleaning	<u>MAC</u> Protective Steel Posts	<u>N/A</u> Downhole TV Inspection	
<u>MAC</u> Storage of Const. Material	<u>MAC</u> Safety Paint	<u>N/A</u> Well Abandonment	
<u>MAC</u> Tool Lubricants	<u>MAC</u> Straightness Test <u>9/14/87</u>	<u>✓</u> Complete As-Built Diagram, Driller's and Geologist's Logs	
<u>MAC</u> Concrete Pad	<u>MAC</u> Well Development		
Approved By <u>M.A. Chammey</u>	Date <u>12/4/87</u>		

Reviewed By J.H. McShane Date 12-29-87

A-1800-187 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E32-4Geologist C. H. Hodge, C. Scott, R. Lynn, G. Davis Page 1 of 3
K. Oster, M. Chambers, S. Goodwin, S. Airhart, L. Fair,
J. Robinson, J. PhillipsReviewed by W. E. McCallumDate 12-29-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill Rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
cement 0'-3'		5		GRAVELLY SANDY SILT	
		10		SILTY SANDY GRAVEL	3.8
		15		" " "	1.3
		20		" " "	2.1
		25		" " "	2.5
bentonite crumbles 2'-26.5'		30		" " "	1.6
		35		" " "	3.3
		40		" " "	2.6
		45		" " "	5
		50		" " "	
		55		SILTY GRAVELLY SAND	7.5
16" carbon steel casing		60		SLIGHTLY SILTY GRAVELLY SAND	5
10" carbon steel casing		65		" " "	
		70		GRAVELLY SAND	12
8" carbon steel casing		75		SLIGHTLY GRAVELLY SAND	
		80		SLIGHTLY SILTY SAND	12
4" stainless steel casing		85		SAND	8.6
		90		SLIGHTLY SILTY GRAVELLY SAND	15
		95		SLIGHTLY GRAVELLY SAND	10
		100		" " "	12
		105		SAND	7.5
		110		" " "	12
		115		" " "	12
		120		" " "	8.6
12" carbon steel casing		125		" " "	12
		130		SLIGHTLY GRAVELLY SAND	12

A-1800-100 (3/87)

Battelle Pacific Northwest Laboratories		AS-BUILT DIAGRAM	
Well Number <u>299-E32-4</u>	Geologist <u>C. Hader, C. Smith, G. Davis & Lugo</u> , Page <u>2</u> of <u>3</u> <small>M. Chambers, K. Boster, S. Goodwin, S. Airhart, L. Fair, J. Robinson, J. Phillips</small>		
Reviewed by <u>V.L. McPherson</u>	Date <u>12-29-97</u>		

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		<u>135</u>		(GRAVELLY SAND)
<u>bentonite crumbles 2'6" - 3'</u>		<u>140</u>		SLIGHTLY SILTY GRAVELLY SAND
		<u>145</u>		GRAVELLY SAND
		<u>150</u>		SLIGHTLY GRAVELLY SAND
		<u>155</u>		" "
		<u>160</u>		GRAVELLY SAND
		<u>165</u>		SAND:
		<u>170</u>		"
		<u>175</u>		173 - 4" thick clay-pitch where GRAVELLY SAND
		<u>180</u>		" "
		<u>185</u>		SL. SILTY SL. GRAVELLY SAND
		<u>190</u>		GRAVELLY SAND
		<u>195</u>		" "
<u>201' of 10" CASING (carbon steel)</u>		<u>200</u>		SILTY SANDY GRAVEL
		<u>205</u>		MISSING
		<u>210</u>		SANDY GRAVEL
		<u>215</u>		GRAVELLY SAND
		<u>220</u>		SANDY GRAVEL
		<u>225</u>		SAND
<u>8" carbon steel casing</u>		<u>230</u>		SLIGHTLY SILTY SAND
<u>4" stainless steel casing</u>		<u>235</u>		SILTY SANDY GRAVEL
		<u>240</u>		" " "
		<u>245</u>		" " "
		<u>250</u>		" " "
<u>centralizers</u>		<u>255</u>		" " "
		<u>260</u>		GRAVEL

A-1000-100 (2/87)

Geologist C. Andre, C. Scott, K. Lutz, R. Davis, Page 3 of 3
W. Chomiers, K. Oster, S. Goodlin, S. Ahrant, L. Fair,
J. Robinson, J. Phillips.

Reviewed by

Date 12-29-97

A-1100-124 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E33-28

Construction of this well was initiated on September 24, 1987, and was completed on November 6, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 278 ft below ground surface. Ground water was encountered at a depth of approximately 257.3 ft. Basalt was not encountered by this borehole. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 268 to 278.3 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 275.7 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 255.7 to 275.7 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 247.8 ft. A 6.3-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 3.8 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using hydraulic jacks. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 12 gpm for 32 min. An estimated total volume of 384 gal was removed during this development. The final turbidity reading of the discharge water was 3.80 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Battelle <small>Pacific Northwest Laboratories</small>		Well Completion Report/Title III Inspection List	
Project <u>200 Area RCRA Monitoring Well</u> Location <u>200 East Area</u> Driller <u>Louis Watkins, Lin Gordon</u> Drilling Co. <u>Kaiser Engineering Hdbd</u> Geologist <u>E.S. Davis, M.R. Chambers, C. Satt, S. Aikard</u>		Well Number <u>299-E33-28</u> Temporary Well Number <u>N/A</u> Coordinates <u>N45.5916 W54.668</u> Casing Elevation <u>664.23'</u> Ground Elevation <u>662.66'</u>	
DRILLING METHOD Rotary Air <u>N/A</u> Mud <u>N/A</u> Cable Tool <u>D</u> ☒ <u>H</u> ☒ Drilling Fluid <u>200 East Area water</u> Other <u>Backhoe 0'-7'</u>		COMPLETION DATA Drilled Depth <u>278.03' below ground</u> Completion Depth <u>275'8"</u> Date Started <u>9/24/87</u> Completed <u>11/6/87</u> Static Water Level/Date <u>253.29' 10/15/87</u>	
CASING DATA			
Type <u>CARBON STEEL CASING</u> Size <u>16"</u> <u>12"</u> <u>10"</u> <u>8"</u> <u>6"</u> <u>4"</u>		<u>0</u> to <u>61'6 1/2"</u> ^{stickup} <u>0</u> to <u>134'1"</u> ^{+ 1'6"} <u>0</u> to <u>272'4 1/2"</u> ^{+ 1'10"} <u>0</u> to <u>275'6"</u> ^{+ 3'1"} <u>0</u> to <u>275'4"</u> ^{+ 1'57'}	
Approved By <u>MAC</u> Date <u>11/24/87</u>			
PERFORATIONS Type _____ Depth _____ Schedule _____ App. By <u>MAC</u> Date <u>12/4/87</u>		SCREEN Type <u>5" slot</u> <u>4" slot</u> Length <u>16'3"</u> <u>8'</u> Slot Size <u>30</u> <u>20</u> Depths <u>265.05' - 275.89'</u> App. By <u>MAC</u> Date <u>10/27/87</u>	
		ANNULAR SEAL Type Interval Volume <u>slotted sand</u> <u>275'0" - 278'0"</u> <u>374 100 lb bags</u> <u>slotted sand</u> <u>278'0" - 278'0"</u> <u>3 1/2 50 lb bags</u> <u>best cement</u> <u>278'0" - 278'0"</u> <u>291 50 lb bags</u> <u>best cement</u> <u>0 - 2'0"</u> <u>4 90 lb bags</u> App. By <u>MAC</u> Date <u>11/17/87</u>	
GEOPHYSICAL LOGGING Sondes Interval Date <u>act. X</u> <u>2' - 277'</u> <u>10/15/87</u> <u>density</u> <u>1' - 277'</u> <u>10/15/87</u> <u>neutron</u> <u>2' - 277'</u> <u>10/15/87</u> Approved By <u>M.A. Chambers</u> Date <u>10/15/87</u>		AQUIFER TESTING Type of Test <u>constant discharge / development</u> Length of Test <u>5 1/2 hrs</u> Volume Pumped <u>45,300 gal</u> Drawdown <u>0.06</u> Approved By <u>Harold L. Quinn</u> Date <u>10/21/87</u>	
OTHER APPLICABLE ITEMS			
<u>MAC</u> Steam Cleaning <u>MAC</u> Storage of Const. Material <u>MAC</u> Tool Lubricants <u>MAC</u> Concrete Pad Approved By <u>M.A. Chambers</u> Date <u>12/14/87</u>		<u>MAC</u> Protective Steel Posts <u>MAC</u> Safety Paint <u>G2B</u> Straightness Test <u>10/14/87</u> <u>MAC</u> Well Development Approved By <u>M.A. Chambers</u> Date <u>12/14/87</u>	
		<u>MAC</u> Downhole TV Inspection <u>MA</u> Well Abandonment <u>MAC</u> Complete As-Built Diagram, Driller's and Geologist's Logs	
Reviewed By <u>J.L. Matheson</u> Date <u>12-22-87</u>			

A-1008-167 (2/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E33-28 Geologist C Scott/G Davis/S. AIRHART Page 1 of 3
W.A. ChamnessReviewed by J.L. McShanDate 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>Cement 0'-2.0'</u>		5		<u>SILTY SANDY GRAVEL</u>
		10		" " "
<u>bentonite crumbles 3.9'-24.6'</u>		15		" " "
		20		" " "
		25		" " "
		30		" " "
		35		" " "
		40		<u>GRAVELLY SAND</u>
		45		" "
		50		<u>SLIGHTLY GRAVELLY SILTY SAND</u>
		55		" " "
		60		<u>SLIGHTLY GRAVELLY SAND</u>
<u>16" CARBON STEEL CASING</u>		65		" " "
		70		" " "
<u>12" carbon steel casing</u>		75		<u>SLIGHTLY GRAVELLY SAND</u>
		80		<u>GRAVELLY SAND</u>
		85		<u>SAND</u>
		90		<u>SLIGHTLY GRAVELLY SAND</u>
<u>10" CARBON STEEL CASING</u>		95		" "
		100		" "
<u>8" carbon steel casing</u>		105		<u>SAND</u>
		110		<u>SILTY SAND</u>
<u>4" stainless steel casing</u>		115		<u>SLIGHTLY GRAVELLY SILTY SAND</u>
		120		<u>SLIGHTLY GRAVELLY SLIGHTLY SILTY SAND</u>
		125		" " " " "
		130		<u>SLIGHTLY SILTY GRAVELLY SAND</u>

A-1000-106 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E33-28 Geologist W.A. Phamness, G.S. Davis, Page 2 of 3
C. Scott, S. Arhart

Reviewed by W.L. McLean Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SAND
		140		"
		145		"
		150		"
bentonite crumbles 241'6"-241'6"		155		"
		160		SLIGHTLY SILTY GRAVELLY SAND
		165		SLIGHTLY GRAVELLY SLIGHTLY SILTY SAND
		170		SLIGHTLY SILTY GRAVELLY SAND
		175		SILTY SANDY GRAVEL
10" carbon steel casing		180		"
		185		SAND
8" carbon steel casing		190		"
		195		"
4" stainless steel casing		200		"
		205		"
		210		SILTY SANDY GRAVEL
		215		" " "
		220		" " "
		225		" " "
		230		" " "
		235		" " "
		240		" " "
in situ pellets 241'6"-242'10"		245		SLIGHTLY SILTY GRAVELLY SAND
silica sand 242'10"-242'6"		250		SILTY SANDY GRAVEL
water table 257' 10/27/87		255		" " "
		260		" " "

A-1800-186 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E33-28 Geologist G.S. Davis, C. Scott, 3 Airhart Page 3 of 3

Reviewed by V.L. McShane Date 12-22-87

[illegible]

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E33-29

Construction of this well was initiated on August 17, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 290 ft below ground surface. Ground water was encountered at a depth of approximately 265.7 ft, and basalt was encountered at a depth of 290 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 279.2 to 289.5 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 282.8 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 262.8 to 282.8 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 257 ft. A 4.7-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10 gpm for 45 min. An estimated total volume of 450 gal was removed during the development. The final turbidity reading of the discharge water was 0.63 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Wells</u>	Well Number <u>279-E22-29</u>
Location <u>200 East Area</u>	Temporary Well Number <u>N/A</u>
Driller <u>Felix Murphy + Ralph Robinson</u>	Coordinates <u>N45, 124 W54, 1665</u>
Drilling Co. <u>Kaiser</u>	Casing Elevation <u>673.77'</u>
Geologist <u>M.A. Charnness, S. Goodwin, K.R. Oster, C. Smith, B. Kahl, R. Premzic, C. Hodge, L. Fair, S. Reed, G. Davis</u>	Ground Elevation <u>671.52'</u>
DRILLING METHOD	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	COMPLETION DATA
Cable Tool <u>D</u> ☒ <u>H</u> ☒	Drilled Depth <u>290'</u> <u>below ground</u>
Drilling Fluid <u>200 East Area water</u>	Completion Depth <u>282.75'</u>
Other Backhoe (0'-8')	Date Started <u>8/13/82</u> Completed <u>9/30/82</u>
	Static Water Level/Date <u>265.65'</u> <u>9/10/82</u>

CASING DATA			
Type	Size	Stickup	
carbon steel	16"	0' + 6"	to 57' 5 1/8"
"	12"	0' + 1'	to 134' 6 1/8"
"	10"	0' + 1' 6"	to 204' 2 1/8"
"	8"	0' + 3'	to 292' 11"
Stainless steel	4"	0' + 2.24'	to 282' 9"
Approved By <u>MAC</u>		Date <u>11/24/82</u>	

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type		Type		Type	Interval	Volume
Depth	Schedule	Length		20/20 silica sand	279.11' - 253'	11 3/4 ton lb bags
		Slot Size		bedrock rubble	253' - 242' 2"	2 1/2 steel baskets
		Depths		bedrock rubble	242' 2" - 5'	351 steel bags
				cement	5' - 0'	unknown
App. By <u>MAC</u>	Date <u>10/16/82</u>	App. By <u>MAC</u>	Date <u>11/24/82</u>	App. By <u>MAC</u>	Date <u>11/24/82</u>	

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
Natural γ	289' - 2'	9/14/82	step drawdown / constant discharge	
Neutron	289' - 3'	9/14/82	Length of Test	4.8 hrs
Density	288' - 1'	9/14/82	Volume Pumped	47,600 gal.
			Drawdown	0.12'
Approved By <u>David P. Oster</u> Date <u>9/14/82</u>			Approved By <u>Charles L. Oster</u> Date <u>9/17/82</u>	

OTHER APPLICABLE ITEMS	
☒ Steam Cleaning	☒ Protective Steel Posts
☒ Storage of Const. Material	☒ Safety Paint
☒ Tool Lubricants	☒ Straightness Test 9/4/82 CJA
☒ Concrete Pad	☒ Well Development 9/14/82 KRD
Approved By <u>M.A. Charnness</u>	Date <u>12/14/82</u>
☒ Downhole TV Inspection	☒ Well Abandonment
☒ Complete As-Built Diagram, Driller's and Geologist's Logs	

Reviewed By J.H. McShan Date 12-22-97

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E33-29 Geologist M.A. Chinnery + SA Gordon Page 1 of 3
Reviewed by J.R. Mathan Date 12-22-87
M.R. Oster, C. Sutt, B. Kahl, R. Trembic, C. Hodge, L. Fair, S. Teal, G. Davis

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>cement 0'-5'</u>		5		<u>Gravel</u>
		10		<u>silty sandy gravel</u>
		15		" " "
		20		" " "
<u>ben tonite / rubble 5'-252'3"</u>		25		" " "
		30		" " "
		35		" " "
		40		" " "
		45		" " "
		50		" " "
		55		<u>SL. SILTY GRAVELLY SAND</u>
<u>16" casing, carbon steel</u>		60		<u>SL. SILTY SL. GRAVELLY SAND</u>
<u>12" carbon steel casing</u>		65		" " " "
<u>10" casing, carbon steel</u>		70		<u>SLIGHTLY SILTY SAND</u>
<u>8" casing, carbon steel</u>		75		<u>SLIGHTLY GRAVELLY SAND</u>
<u>4" stainless steel casing</u>		80		<u>GRAVELLY SAND</u>
		85		<u>SL. SILTY GRAVELLY SAND</u>
		90		<u>SAND</u>
		95		<u>SLIGHTLY GRAVELLY SAND</u>
		100		" " "
		105		<u>SAND</u>
		110		" " "
		115		" " "
		120		<u>SLIGHTLY SILTY GRAVELLY SAND</u>
		125		<u>SL. SILTY SL. GRAVELLY SAND</u>
		130		<u>SLIGHTLY SILTY SAND</u>

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299-F33-29

Geologist M.A. Charnock + S.H. Gordon Page 2 of 3

K. Oster, C. Scott, B. Kahl, R. Premtz, C. Hodge, L. Feir
S. Tash, G. Davis

Reviewed by J.L. McKen

Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
12" carbon steel casing		135		SAND
		140		SLIGHTLY SILTY SAND
10" carbon steel casing to		145		SLIGHTLY GRAVELLY SAND
		150		SL. SILTY, SL. GRAVELLY SAND
8" Carbon Steel casing		155		" " "
		160		SL. SILTY, GRAVELLY SAND
4" stainless steel casing		165		SLIGHTLY GRAVELLY SAND
		170		" " "
		175		" " "
		180		SL. SILTY GRAVELLY SAND
		185		SAND
bentonite crumbles 252'3" - 5'		190		"
		195		"
		200		SLIGHTLY SILTY SAND
		205		SILT LENS at 203'
		210		SANDY SILT
		215		" "
		220		SILTY SANDY GRAVEL
		225		" " "
		230		" " "
		235		" " "
		240		" " "
		245		" " "
bentonite pellets 252' - 252'3"		250		SANDY GRAVEL
		255		SILTY SANDY GRAVEL
silica sand 249.18' - 253'		260		" " "

A-1800-186 (3/87)

Geologist H. Chambers, S. Fortune, K. Rater, Page 3 of 3
C. Scott, B. Kahl, R. Premizic, C. Hodge, L. Feir, S. Teel, & Davis

Reviewed by

Date 12-22-87

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E33-30

Construction of this well was initiated on August 29, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 280.1 ft below ground surface. Ground water was encountered at a depth of approximately 257.6 ft, and basalt was encountered at a depth of 277 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 266.7 to 277 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 275 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 255 to 275 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 251.5 ft. A 6.5-ft-thick bentonite pellet seal, followed by bentonite crumbles (#8), was installed to 4 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 12 gpm for 43 min. An estimated total volume of 516 gal was removed during the development. The final turbidity reading of the discharge water was 0.30 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project 200 Area RCRA Monitoring Wells
Location 700 East Area
Driller Lois Watkins / Eric Umbley
Drilling Co. Kaiser Engineering Hanford
Geologist H. Chamness, G. Davis, C. Scott, S. Gorman,
C. Hodge, L. Fair

Well Number 299-E33-30
Temporary Well Number NA
Coordinates N45.903 W5.640
Casing Elevation 463.7'
Ground Elevation 461.92'

DRILLING METHOD
Rotary Air NA Mud NA
Cable Tool D H
Drilling Fluid 700 East water
Other Backhoe 0'-10"

COMPLETION DATA
Drilled Depth 280.1' below ground
Completion Depth 275'
Date Started 8/29/87 Completed 9/20/87
Static Water Level/Date 267.57' 9/15/87

CASING DATA
Type Size
CARBON STEEL 16" 0' to 58' 4"
" " 12" 0' to 123' 6 1/2"
" " 10" 0' to 208' 3"
" " 8" 0' to 284' 9 1/4"
stainless steel 4" 0' to 275' + 1.78' stickup
Approved By MAC Date 11/24/87

PERFORATIONS
Type Depth Schedule
N/A
App. By MAC Date 11/12/87

SCREEN
Type 8" st. steel / 4" st. steel
Length 10' 3" 20'
Slot Size 30 20
Depths 277'-266' 9" 275'-255'
App. By MAC Date 11/15/87

ANNULAR SEAL
Type Interval Volume
20/30 silica sand 250'-251.5' 8 1/2 100 lb bags
seal pellets 251.5'-252' 2 1/2 50 lb bags
seal crumbles 252'-254' 260 50 lb bags
grout 254'-255' unknown
App. By MAC Date 11/24/87

GEOPHYSICAL LOGGING
Sondes Interval Date
Net Gamma 2' - 279' 9/15/87
neutron 2' - 279' 9/15/87
density 1' - 278' 11/15/87
App. By MAC Date 11/24/87

AQUIFER TESTING
Type of Test step drawdown / constant discharge
Length of Test 6 hrs
Volume Pumped 160 gpm for 3.5 hrs = 35,600 gal
Drawdown 0.02'
App. By Charles A. Davis Date 9/24/87

OTHER APPLICABLE ITEMS
MAC Steam Cleaning MAC Protective Steel Posts MAC Downhole TV Inspection
MAC Storage of Const. Material MAC Safety Paint MAC Well Abandonment
MAC Tool Lubricants MAC Straightness Test 9/15/87 MAC Complete As-Built Diagram,
MAC Concrete Pad SA Well Development 9/22/87 Driller's and Geologist's Logs
Approved By H.A. Chamness Date 12/14/87

Reviewed By J.L. Mathan Date 12-22-87

A-1800-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E33-30 Geologist W.A. Chmura, G.S. Davis, C. Hodge, C. Scott, L.A. Feir, S. Goodwin Page 1 of 3
Reviewed by J.L. McElhan Date 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Portland cement 0'-2.5'		5		SILTY SANDY GRAVEL
		10		" " "
		15		" " "
16" carbon steel casing		20		" " "
		25		" " "
		30		" " "
12" carbon steel casing		35		" " "
		40		" " "
		45		" " "
		50		" " "
10" carbon steel casing		55		" " "
		60		GRAVELLY SAND
		65		" "
bentonite crumbles 2.5'-24.5'		70		" "
		75		" "
		80		SAND
		85		"
		90		"
		95		"
8" carbon steel casing		100		SLIGHTLY GRAVELLY SAND
		105		SAND
4" stainless steel casing		110		"
		115		SL. SILTY GRAVELLY SAND
		120		" " "
		125		SL. GRAVELLY SAND
		130		SLIGHTLY SILTY slightly gravelly sand

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E33-20Geologist H. Chomnes, G. Davis, C. Hodges, C. Smith, S. Goodman, L. Fair Page 2 of 3Reviewed by V.L. McShaneDate 12-22-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		slightly silty slightly gravelly SAND
		140		" " " " "
		145		" " " " "
		150		SAND
		155		"
		160		SLIGHTLY SILTY SAND
		165		" " "
10" carbon steel casing		170		" " "
		175		" " "
		180		SILTY SHALE
		185		SLIGHTLY SILTY SHALE
		190		" " "
		195		" " "
		200		" " "
		205		SANDY SILTY
4" stainless steel casing		205		SL. SILTY GRAVELLY SHALE
		210		SL. SILTY SL. GRAVELLY SHALE
bentonite crumbles ~215'-215'		215		SLIGHTLY GRAVELLY SAND
		220		" " "
		225		SAND (FINE)
		230		SILTY SANDY GRAVEL
centralizing bars on 4" casing		235		" " "
		240		" " "
8" carbon steel casing		245		" " "
bentonite pellets 251.5' ~ 245'		250		" " "
water table 257.57' 9/15/82		255		" " "
silica sand 251.5' ~ 260'		260		" " "

A-1800-186 (3/87)

Reviewed by V. T. McShane Date 12-22-87

[illegible]

A-1800-1 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E34-2

Construction of this well was initiated on July 18, 1987, and was completed on September 30, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 241.5 ft below ground surface. Ground water was encountered at a depth of approximately 223.5 ft, and basalt was encountered at a depth of 241 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 230.1 to 240.4 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 239.9 ft. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 219.9 to 239.9 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 212.8 ft. A 7.3-ft-thick bentonite pellet seal was installed, followed by bentonite crumbles (3 to 136.6 and 166.8 to 205.4 ft) and Volclay grout (136.6 to 166.8 ft) to 3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. A 3-in.-long section of the 4-in.-stainless steel casing was found to be severely crumpled at the 99-ft depth, and a 2- to 3-ft-thick plug of bentonite was found in the screen just above the water table. The crumpled zone was swedged out to a diameter of approximately 3 in. and the bentonite plug was bailed out. The screen was pressure washed with water from an approved source, swabbed, and bailed clean. A second inspection indicates that some bentonite is still present in the screen above the water table. The screen at and below the water table are clean.

Final well development was performed using a Hydrostar pump discharging at a rate of approximately 4.2 gpm for 30 min. An estimated total volume of 125 gal was removed during the development. The final turbidity reading of the discharge water was 5.30 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Project <u>200 Area RCRA Monitoring Well</u> Location <u>200-EAST</u> Driller <u>Olin Ames / Don St. George</u> Drilling Co. <u>Kaiser Engineering Hanford</u> Geologist <u>M.A. Chomarez, R. Premisz, P. White, R. Hargis</u> <u>K.R. Oster</u>		Well Number <u>299-E34-2</u> Temporary Well Number <u>N/A</u> Coordinates <u>N45.076 W57.048</u> Casing Elevation <u>1230.8'</u> Ground Elevation <u>629.03'</u>	
DRILLING METHOD Rotary Air <u>N/A</u> Mud <u>N/A</u> Cable Tool <u>D</u> <u>N/A</u> <u>H</u> <u>0-241.5'</u> Drilling Fluid <u>200E water</u> Other <u>N/A</u>		COMPLETION DATA Drilled Depth <u>241 1/2' below surface</u> Completion Depth <u>239' 11" below surface</u> Date Started <u>7/18/87</u> Completed <u>9/30/87</u> Static Water Level/Date <u>223.5' / 7/28/87</u>	
CASING DATA			
Type <u>carbon steel</u> <u>carbon steel</u> <u>carbon steel</u> <u>" "</u> <u>Stainless Steel</u>		Size <u>16" 0' to 40' 1 1/2"</u> <u>12" 0' to 105' 6" + 3" stickup</u> <u>10" 0' to 166' 4 3/4" + 8" stickup</u> <u>8" 0' to 240' 2 3/4" + 3' 2" stickup</u> <u>4" stickup 2' 1/2" to 240' 3" + 1.77' stickup</u>	
PERFORATIONS Type _____ Depth _____ Schedule _____ _____ _____ App. By <u>MAC</u> Date <u>10/27/87</u>		SCREEN Type <u>8" telescoping 1/4" st steel</u> Length <u>10' 3" 20' 2 1/2"</u> Slot Size <u>30 20</u> Depths <u>8" 240.42' 239' 11"</u> <u>230.17' 219' 11"</u> App. By <u>MAC</u> Date <u>11/19/87</u>	
GEOPHYSICAL LOGGING Sondes Interval Date <u>gamma gamma 0' - 240' 7/28/87</u> <u>neutron 0' - 240' 7/28/87</u> <u>natural gamma 0' - 240' 7/28/87</u> _____ _____ _____ _____ Approved By <u>MAC</u> Date <u>11/24/87</u>		AQUIFER TESTING Type of Test <u>Constant Discharge / Development</u> Length of Test <u>5 hrs</u> Volume Pumped <u>26,000</u> Drawdown <u>0.58</u> _____ _____ _____ Approved By <u>[Signature]</u> Date <u>8/7/87</u>	
OTHER APPLICABLE ITEMS			
<u>MAC</u> Steam Cleaning ☒ Storage of Const. Material ☒ Tool Lubricants <u>MAC</u> Concrete Pad Approved By <u>M.A. Chomarez</u> Date <u>12/14/87</u>		<u>MAC</u> Protective Steel Posts <u>MAC</u> Safety Paint ☒ Straightness Test <u>7/28/87</u> ☒ Well Development <u>7/28/87</u> _____ _____	
<u>200</u> Downhole TV Inspection <u>NA</u> Well Abandonment ☒ Complete As-Built Diagram, Driller's and Geologist's Logs		_____ _____	

Reviewed By W. H. Mathan Date 12-23-87

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E34-2 Geologist M.A. Charnock + R. Frensch Page 1 of 2
R. Hagan, T. White, K. Oster

Reviewed by D.L. McShan Date 12-23-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill or (ft)
Description	Diagram		Diagram Litho.	Lithologic Description	
Cement 3'-0'		5'		SILTY SANDY GRAVEL	
		12'		SANDY GRAVEL	1.1'/h
		15'		" "	1.7'/hr
		20'		" "	1.7'/hr
		25'		" "	3.3'/h
		30'		" "	2.5'/h
		35'		" "	8.5'/h
16" carbon steel		40'		" "	7.5'/h
		45'		" "	3.2'/h
		50'		SILTY SANDY GRAVEL	6.6'/h
bentonite crumbles 3'-136.6'		55'		" "	5'/hr
		60'		SANDY GRAVEL	10'/hr
		65'		" "	6'/h
		70'		SILTY SANDY GRAVEL	8.5'/h
		75'		(55) (40) SANDY GRAVEL	5.4'/h
		80'		" "	10'/h
		85'		" "	2.5'/h
		90'		" "	2.8'/h
		95'		GRAVELLY SAND	6.7'/h
		100'		" "	6.7'/h
12" carbon steel		105'		" "	7.5'/hr
10" carbon steel casing		110'		" "	6.7'/h
8" carbon steel casing		115'		" "	10.2'/h
4" stainless steel casing		120'		SANDY GRAVEL	6.8'/hr
		125'		CLAYEY SILTY GRAVELLY SAND	10.2'/hr
		130'		GRAVELLY SAND	12.2'/h

A-1900-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E24-2 Geologist M.A. Chomness + R. Frazier Page 2 of 2
R. Hagen

Reviewed by R.H. Hagen Date 12-23-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
bentonite crumbles 3'-136.6'		135'		slightly silty gravelly sand	4.3/hr
		140'		slightly gravelly, slightly silty sand	15.2/hr
		145'		slightly silty gravelly sand	3.2/hr
well clay grout 136.6'-146.9'		150'		" " " "	15.2/hr
		155'		mainly sand	6.6/hr
		160'		" " " "	12'/hr
		165'		" " " "	11.1/hr
10" carbon steel		170'		slightly silty gravelly sand	5'/hr
		175'		" " " "	6'/hr
		180'		mainly sand	~6'/hr
bentonite crumbles 146.9'-205.5'		185'		slightly silty gravelly sand	2'/hr
		190'		silty sandy gravel	5'/hr
8" carbon steel casing		195'		slightly silty gravelly sand	5'/hr
centralizers		200'		" " " "	5'/hr
4" stainless steel casing		205'		" " " "	4.8/hr
		210'		silty sandy gravel	5'/hr
well clay pellets 205.5'-212.9'		215'		" " " "	13/hr
silica sand 212.9'-241.6'		220'		" " " "	
water level 223.5' 7/28/87		225'		" " " "	
		230'		" " " "	
4" 20 slot ft. steel screen		235'		" " " "	4'/hr
8" of steel 30 slot telescoping screen		240'		slightly silty sand	2.5'/hr
				Bottom at ~241'

SUMMARY OF CONSTRUCTION, WELL 299-E34-3

Construction of this well was initiated on July 14, 1987, and was completed on August 19, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 213.9 ft below ground surface. Ground water was encountered at a depth of approximately 203.1 ft, and basalt was encountered at a depth of 213 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 203.5 to 213.8 ft, and an aquifer test was performed. The borehole was then backfilled with silica sand (20 to 30 mesh) to a depth of 213 ft. A 20.3-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 192.7 to 213 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 184 ft. A 7-ft-thick bentonite pellet (1/4-in. Volclay tablets) seal, followed by bentonite crumbles and Volclay grout, was installed to 3 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a cable-tool drill rig. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11 gpm for 50 min. An estimated total volume of 550 gal was removed during the development. The final turbidity reading of the discharge water was 0.70 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project 200 Area RCRA Monitoring Wells Well Number 299-E343
Location 200 EAST Temporary Well Number NA
Driller LUDON CORP / Louis Watkins Coordinates N45.327 1.148 488
Drilling Co. KAISER Eng. Huntford Casing Elevation 611.52'
Geologist RA HAGEN / R.L. Premzie Ground Elevation 609.48'
K.R. Oster, S. Budniak, P. White, M.A. Chambers

DRILLING METHOD COMPLETION DATA
Rotary Air N/A Mud N/A Drilled Depth 213.89' below ground
Cable Tool D N/A H ✓ Completion Depth 213'
Drilling Fluid Water - On 200-E Date Started 7/14/87 Completed 8/19/87
Other Backhoe 0'-5' Static Water Level/Date 203.12' 8/10/87

CASING DATA
Type Size
Carbon steel - temporary 16" +0' 2 1/2" to -40' 2 1/4"
Carbon steel - temporary 12" ground surface to -95' 3 1/2"
Carbon steel - temporary 10" +0' 5 1/4" to -167' 0"
Carbon steel - temporary 8" +2' 4 1/2" to -213' 4"
Approved By MAC Date 11/24/87
Stainless Steel 4" 0 to 213' 6" + 2.04' stickup

PERFORATIONS		SCREEN		ANNULAR SEAL	
Type	Schedule	Type	Length	Type	Volume
		<u>8" telescoping SS / 4" st. steel</u>	<u>10' 3"</u>	<u>20/30 sand</u>	<u>213.6-184' 900 lbs.</u>
			<u>20' 3 1/4"</u>	<u>benzbrite pellets</u>	<u>184'-177' 150 lbs.</u>
			<u>30</u>	<u>granular bent.</u>	<u>177'-165' 10 sacks</u>
			<u>20</u>	<u>volclay grout</u>	<u>165'-5' 2305 gal.</u>
			<u>8" 2035</u>	<u>213.8'</u>	<u>5 (100%) gal.</u>
			<u>213.8'</u>	<u>193'</u>	<u>11/24/87</u>
App. By <u>MAC</u>	Date <u>11/19/87</u>	App. By <u>MAC</u>	Date <u>11/19/87</u>	App. By <u>MAC</u>	Date <u>11/24/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	Length of Test
<u>nat. X</u>	<u>0' - 213'</u>	<u>7/28/87</u>	<u>development / constant discharge</u>	<u>5.1 hrs</u>
<u>density</u>	<u>0' - 213'</u>	<u>7/28/87</u>		<u>Volume Pumped 13,600 gal</u>
<u>neutron</u>	<u>0' - 213'</u>	<u>7/28/87</u>		<u>Drawdown 1.82'</u>
Approved By <u>MAC</u>	Date <u>7/28/87</u>		Approved By <u>Charles L. Chase</u>	Date <u>8/15/87</u>

OTHER APPLICABLE ITEMS
RAH Steam Cleaning 7/14/87 MAC Protective Steel Posts ✓ Downhole TV Inspection ✓
RAH Storage of Const. Material 7/14 MAC Safety Paint ✓ Well Abandonment ✓
RAH Tool Lubricants ✓ Straightness Test 7/27/87 ✓ Complete As-Built Diagram,
MAC Concrete Pad ✓ Well Development ✓ Driller's and Geologist's Logs
Approved By M.A. Chambers Date 12/14/87

Reviewed By V.K. McPherson Date 12-23-87 A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-E34-3Geologist RA HAGEN / RL PRETZIK Page 1 of 2
K. Oster, S. Dudzick, P. White, M. ChambersReviewed by W. McLeanDate 12-23-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill Rate (ft/hr)
Description	Diagram 2 1/2" dia		Diagram Litho.	Lithologic Description	
cement from 0'-3'		5		SILTY SANDY GRAVEL	NA
bentonite crumbles 3'-5'		10		" " "	2.1
16" carbon steel casing		15		" " "	1.2
		20		" " "	1.7
		25		" " "	5.0
		30		sandy gravel	3.3
		35		silty sandy gravel	4.0
volclay grout 5'-105'		40		" " "	4.5
		45		" " "	5.6
		50		" " "	6.6
		55		Sandy Gravel	5.0
		60		" "	5.0
12" diam. temporary		65		silty sandy gravel	12.5
carbon steel casing		70		" " "	2.9
		75		" " "	4.1
		80		Sandy Gravel	3.1
		85		" "	15.0
		90		silty sandy gravel	2.7
		95		" " "	4.3
10" diam. temporary		100		SAND (At 96')	5.0
carbon steel casing		105		Slightly Gravelly Sand	6.0
8" carbon steel casing		110		" " "	4.3
		115		gravelly sand	8.5
4" diameter permanent		120		" "	5.0
stainless steel casing		125		Slightly gravelly sand	6.7
		130		gravelly sand	10.0

A-1800-188 (3/87)

© Battelle

K. Oster, S. Dudziak, P. White, M. Channars

2

A-1000-100 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E34-4

Construction of this well was initiated on July 8, 1987, and was completed on August 19, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 177.1 ft below ground surface. Ground water was not encountered in this well. Basalt was encountered at a depth of 175.5 ft. The borehole was tested for straightness and was geophysically logged. A 20-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 157 to 177 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 154 ft. A 5-ft-thick bentonite pellet (1/4-in. Volclay tablets) seal, followed by bentonite crumbles and Volclay grout, was installed to 1.5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Well</u>		Well Number <u>299-E34-4</u>	
Location <u>200 East</u>		Temporary Well Number <u>N/A</u>	
Driller <u>Leary Gordon + Ron Arno</u>		Coordinates <u>N46.791 W49.419</u>	
Drilling Co. <u>Kaiser</u>		Casing Elevation <u>582.56'</u>	
Geologist <u>S. Dudezick / M.A. Chumars</u>		Ground Elevation <u>585.17'</u>	
R. Hagen, K. Oster, R. Premier			
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u>N/A</u> Mud <u>N/A</u>		Drilled Depth <u>177' 1"</u> <u>bottom reached</u>	
Cable Tool <u>D</u> <u>N/A</u> <u>H</u> <u>X</u>		Completion Depth <u>177' 0"</u> <u>bottom reached</u>	
Drilling Fluid <u>water (200E)</u>		Date Started <u>7/18/87</u> Completed <u>8/19/87</u>	
Other <u>Backhoe, 0'-4'</u>		Static Water Level/Date <u>175.58'</u> <u>7/20/87</u>	
		<u>dry</u> <u>12/2/87</u>	
CASING DATA			
Type	Size	Stickup	
<u>Carbon steel</u>	<u>12"</u>	<u>0' + 0'</u>	to <u>84' 8"</u>
<u>Carbon steel</u>	<u>10"</u>	<u>0' + 8 1/2"</u>	to <u>135' 2 1/2"</u>
<u>Carbon steel</u>	<u>8"</u>	<u>0' + 1' 9 3/4"</u>	to <u>174' 8 3/4"</u>
<u>stainless steel</u>	<u>4"</u>	<u>0' + 2' 39"</u>	to <u>176' 10 3/4"</u>
Approved By <u>MAC</u>		Date <u>11/24/87</u>	
PERFORATIONS		SCREEN	
Type	Depth	Schedule	Type <u>4" stainless steel</u>
			Length <u>20'</u>
			Slot Size <u>20 slot</u>
			Depths <u>177' - 157'</u>
App. By <u>MAC</u>	Date <u>11/23/87</u>		App. By <u>MAC</u> Date <u>11/23/87</u>
ANNULAR SEAL			
Type	Interval	Volume	
<u>20/20 sand</u>	<u>177' - 154'</u>	<u>15 x 17 x 16 Bag</u>	
<u>hydrophobic pellet</u>	<u>154' - 141'</u>	<u>3 50 lb bags</u>	
<u>best cement</u>	<u>141' - 122'</u>	<u>180.5 bags</u>	
<u>voluntary port</u>	<u>94' 4" - 122' 2"</u>	<u>168.5 bags</u>	
App. By <u>MAC</u>	Date <u>11/23/87</u>	App. By <u>MAC</u> Date <u>11/23/87</u>	
Cement <u>0'-7.5'</u>		<u>unknown</u>	
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes	Interval	Date	Type of Test <u>N/A</u>
<u>natural &</u>	<u>0' - 177'</u>	<u>7/18/87</u>	Length of Test
<u>neutron</u>	<u>0' - 177'</u>	<u>7/18/87</u>	Volume Pumped
<u>gamma gamma</u>	<u>0' - 177'</u>	<u>7/18/87</u>	Drawdown
			<u>insufficient water</u>
Approved By <u>MAC</u> Date <u>7/18/87</u>			Approved By <u>MAC</u> Date <u>7/18/87</u>
OTHER APPLICABLE ITEMS			
<u>MAC</u> Steam Cleaning	<u>MAC</u> Protective Steel Posts	<u>MAC</u> Downhole TV Inspection	
<u>MAC</u> Storage of Const. Material	<u>MAC</u> Safety Paint	<u>N/A</u> Well Abandonment	
<u>MAC</u> Tool Lubricants	<u>RAH</u> Straightness Test <u>7/18/87</u>	<u>✓</u> Complete As-Built Diagram,	
<u>MAC</u> Concrete Pad	<u>MAC</u> Well Development <u>7/29-30/87</u>	Driller's and Geologist's Logs	
Approved By <u>M.A. Chumars</u>	Date <u>12/4/87</u>		

Reviewed By J.R. McLean Date 12-28-87

A-1800-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-E34-4 Geologist M.A. Chamness + S. Nulziak Page 1 of 2
R. Hagen, R. Premizic, K. Oster
Reviewed by J.T. Hurlburt Date 12-28-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		Drill rate
Description	Diagram		Diagram Litho.	Lithologic Description	
Cement 0'-1.5'		4'		silty sandy gravel	1.1'/hr
		10'		" " " "	0.76'/
		15'		silty gravelly sand	3.3'/
		20'		gravelly sand	10'/
		25'		SL SILTY SL. GRAVELLY SAND	10'/h
		30'		Gravelly silty sand	7.5'/
		35'		Silty sandy Gravel	2.8'/h
		40'		" " " "	2.3'/h
		45'		" " " "	2.3'/hr
		50'		" " " "	2.5'/hr
		55'		" " " "	6.6'/h
		60'		" " " "	1.7'/h
		65'		Gravel	2.1'/h
bentonite crumbles 45'-94'4"		70'		" " " "	4.9'/h
		75'		silty sandy gravel	2.3'/
		80'		" " " "	2.3'/hr
12" carbon steel		85'		" " " "	2.3'/
		90'		slightly silty gravelly sand	2.3'/
10" carbon steel casing		95'		" " " "	2.5'/
		100'		Silty sandy gravel	2.2'/
volcky gravel 94'4"-132'2"		105'		" " " "	1.7'/h
		110'		" " " "	2.7'/h
8" carbon steel casing		115'		" " " "	4.9'/h
		120'		" " " "	2.0'/
11" stainless steel casing		125'		" " " "	5'/
		130'		" " " "	2.5'/

A-1800-186 (3/87)

Reviewed by

Drill rate (ft/hr)
2.5/hr
4.0/hr
2.2/hr
1' / hr
1.7/hr
5' / hr
2.7'
5.4
6.7

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E34-5

Construction of this well was initiated on June 27, 1987, and was completed on August 15, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 192 ft below ground surface. Ground water was encountered at a depth of approximately 182.7 ft, and basalt was encountered at a depth of 190 ft. The borehole was tested for straightness and was geophysically logged. A 10.3-ft length of 8-in.-telescoping stainless steel screen (30 slot) was installed at a depth of 180.2 to 190.5 ft, and an aquifer test was performed. A 20.3-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 170.2 to 190.5 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (20 to 30 mesh) was installed around the 4-in. screen to a depth of 158 ft. A 12-ft-thick bentonite crumble seal, followed by Volclay grout and more bentonite crumbles, was installed to 1.5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor and a cable-tool drill rig. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 14 gpm for 45 min. An estimated total volume of 630 gal was removed during the development. The final turbidity reading of the discharge water was 2.00 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Well</u>	Well Number <u>299-E34-5</u>
Location <u>200 EAST</u>	Temporary Well Number <u>N/A</u>
Driller <u>Lin Gordon, Leung Gordon, Louis Watkins</u>	Coordinates <u>N46.791 W50.014</u>
Drilling Co. <u>Kaiser</u>	Casing Elevation <u>590.79'</u>
Geologist <u>R.A. Hagea, R. Premic, K.R. Oster,</u>	Ground Elevation <u>589.01'</u>
<u>T. Gilmore, M.A. Chamness, S. Duszak, S. Teel,</u>	
COMPLETION DATA	
Drilled Depth <u>192'</u>	Completion Depth <u>190' 6 3/4" below ground</u>
Date Started <u>6/27/87</u>	Completed <u>8/15/87</u>
Static Water Level/Date <u>182' 8" / 7/11/87</u>	

Type	Size	stickup
CARBON STEEL	16"	+11" to 59' 7 1/4"
CARBON STEEL	12"	+1' 3 1/2" to 145' 9 3/8"
CARBON STEEL	8"	+3' 0" to 190' 11 1/2"
stainless steel	4"	+1' 7 3/8" to 190.5'

Approved By MAC Date 11/24/87

PERFORATIONS			SCREEN		ANNULAR SEAL		
Type	Depth	Schedule	Type	Length	Type	Interval	Volume
<u>N/A</u>			<u>ONE 8" stainless 4" stainless</u>	<u>20' 3 3/4"</u>	<u>20/29 sand</u>	<u>14' 5" - 158"</u>	<u>12-50 lb bag</u>
			<u>Slot Size 30</u>	<u>20</u>	<u>bit. cement</u>	<u>152' - 144' 10 1/2" - 74'</u>	<u>22-50 lb bag</u>
			<u>Depths 8" 180.5'</u>	<u>170.5'</u>	<u>Water cement</u>	<u>144' - 101' 7 1/2" - 15'</u>	<u>2270 gal</u>
			<u>4" 190.5'</u>	<u>190.5'</u>	<u>cement</u>	<u>15' - 0</u>	<u>unknown</u>
App. By <u>MAC</u>	Date <u>11/16/87</u>		App. By <u>MAC</u>	Date <u>11/24/87</u>	App. By <u>MAC</u>	Date <u>11/24/87</u>	

GEOPHYSICAL LOGGING				AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	Length of Test	Volume Pumped
<u>Natural gamma</u>	<u>0' - 192'</u>	<u>7/13/87</u>	<u>development / constant discharge</u>	<u>2 hrs</u>	<u>3700</u>
<u>Neutron</u>	<u>0' - 192'</u>	<u>7/13/87</u>			
<u>gamma gamma</u>	<u>0' - 192'</u>	<u>7/13/87</u>			
Approved By <u>MAC</u>	Date <u>11/24/87</u>		Approved By <u>MAC</u>	Date <u>7/21/87</u>	

OTHER APPLICABLE ITEMS		
<u>RAH</u> Steam Cleaning	<u>MAC</u> Protective Steel Posts	<u>290</u> Downhole TV Inspection
<u>RAH</u> Storage of Const. Material	<u>MAC</u> Safety Paint	<u>W</u> Well Abandonment
<u>RAH</u> Tool Lubricants	<u>SD</u> Straightness Test <u>7/11/87</u>	<u>✓</u> Complete As-Built Diagram, Driller's and Geologist's Logs
<u>MAC</u> Concrete Pad	<u>MAC</u> Well Development	
Approved By <u>M.A. Chamness</u>	Date <u>12/4/87</u>	

Reviewed By T.K. Matheson Date 12-28-87

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E34-5 Geologist R.A. HAGEN Page 1 of 2
Reviewed by V.H. Nelson Date 12-28-87
R. Premic, K. Oster, T. Gilmore, M. Channan, S. Fick,
S. Budzich

Construction Data		Depth in Feet	Geologic/Hydrologic Data		drill rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
concrete 0'-1.5'		5		Silty sandy gravel	N/A
		10		" " "	1.0
16" temporary carbon steel casing		15		" " "	3.2
		20		" " "	2.5
		25		Silty Gravelly Sand	3.0
		30		Slightly Gravelly Silty Sand	6.6
		35		Silty Sand	4.0
		40		Silty Gravelly Sand	5.4
concrete 39'-1.5'		45		Silty Sand, Gravel	2.1
		50		Sandy Gravel	2.7
		55		Silty Sandy gravel	1.7
		60		" " "	3.5
12" temporary carbon steel casing		65		Gravel	3.0
		70		Silty Sandy Gravel	3.0
		75		Gravel	2.5
		80		"	5.0
bedrock crumbles from 106'-79'		85		Sandy Gravel	3.1
		90		Gravel	2.5
		95		Sandy Gravel	2.5
		103		Silty Sandy Gravel	4.3
bedrock gravel (125' to 146') from 146' to 106'		105		Sandy Gravel	4.2
10" carbon steel casing		110		Silty Sandy Gravel	2.9
		115		" " "	2.4
		120		" " "	3.6
		125		" " "	4.1
		130		" " "	3.5

A-1800-188 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-E34-6

Construction of this well was initiated on June 25, 1987, and was completed on August 19, 1987. An 8-in.-diameter borehole (cased with carbon steel) was drilled to a depth of 195 ft below ground surface. Ground water was encountered at a depth of approximately 190.8, and basalt was encountered at a depth of 194 ft. The borehole was tested for straightness and was geophysically logged. A 20.3-ft length of 4-in.-diameter stainless steel screen (20 slot) was set at a depth of 174.7 to 195 ft, with 4-in.-diameter stainless steel casing extending to the surface. A silica sand pack (10 to 20 and 20 to 30 mesh) was installed around the 4-in. screen to a depth of 163 ft. A 5.7-ft-thick bentonite pellet (1/4-in. Volclay tablets) seal, followed by bentonite crumbles and Volclay grout, was installed to 5 ft below the surface. During the installation of the sand pack and bentonite seals, the temporary carbon steel casing was pulled using a crane and piling extractor and a cable-tool drill rig. A concrete surface seal and pad were then installed, as well as protective guard posts and locking well cap.

Visual inspection of the completed well was performed with a down-hole video camera. No abnormalities were found in the well.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 Area RCRA Monitoring Wells</u>	Well Number <u>299-EJ4-6</u>
Location <u>200 East</u>	Temporary Well Number <u>N/A</u>
Driller <u>A.L. Cordova/Murphy/Robinson</u>	Coordinates <u>N46, 764 W50, 609</u>
Drilling Co. <u>Kaiser Eng.</u>	Casing Elevation <u>597.82'</u>
Geologist <u>R.A. Hagen/RL Premzie, E. Jensen</u>	Ground Elevation <u>596.56'</u>
<u>K. Oster, M. Chomney, S. Teal, T. Gilmore</u>	
DRILLING METHOD	
Rotary Air <u>N/A</u> Mud <u>N/A</u>	COMPLETION DATA
Cable Tool <u>D</u> <u>N/A</u> <u>H</u> ☒	Drilled Depth <u>195'</u> <u>below ground</u>
Drilling Fluid <u>water from 200E</u>	Completion Depth <u>194.85'</u> <u>below surface</u>
Other <u>TOOL LUBRICANT IS CRISCO OIL.</u>	Date Started <u>6/25/87</u> Completed <u>9/19/87</u>
	Static Water Level/Date <u>190.81'</u> <u>below surface</u> <u>7/14/87</u>

CASING DATA			
Type	Size		
<u>16" DIAM. CARBON STEEL</u>	<u>16"</u>	<u>0 + 1'3 1/2"</u>	<u>to 59'1 1/2"</u>
<u>12" DIAM. CARBON STEEL</u>	<u>12"</u>	<u>0 + 1'5"</u>	<u>to 145'4 1/8"</u>
<u>8" DIAM. CARBON STEEL</u>	<u>8"</u>	<u>0 + 2'9"</u>	<u>to 194'8"</u>
<u>Stainless Steel</u>	<u>4"</u>	<u>0 + 1'2 1/2"</u>	<u>to 195'</u>
Approved By <u>MAC</u>		Date <u>11/24/87</u>	

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type		Type <u>4" steel</u>		Type	Interval	Volume
Depth	Schedule	Length <u>4" = 20' ± 3/4"</u>		<u>18/20 sand</u>	<u>195-180'</u>	<u>5 ± 100 lb. sacks</u>
		Slot Size <u>20</u>		<u>20/30 sand</u>	<u>180-163'</u>	<u>7 ± 100 lb. sacks</u>
		Depths <u>4" 175' - 195'</u>		<u>Antonite Pellets</u>	<u>163'-152.3'</u>	<u>3 ± seal. buckets</u>
				<u>Antonite Grout</u>	<u>152.3'-145'</u>	<u>10 ± 50 lb. sacks</u>
App. By <u>MAC</u>	Date <u>11/16/87</u>	App. By <u>MAC</u>	Date <u>11/24/87</u>	<u>Volcanic Grout</u>	<u>145' - 5'</u>	<u>13 ± 5 lb.</u>
				App. By <u>MAC</u>	Date <u>11/24/87</u>	
				<u>coverlet 5' - 0'</u>	<u>unknown</u>	

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
<u>Natural gamma</u>	<u>0 - 195'</u>	<u>7/13/87</u>	Length of Test	<u>N/A</u>
<u>Neutron</u>	<u>0 - 195'</u>	<u>7/13/87</u>	Volume Pumped	
<u>gamma-gamma</u>	<u>0 - 195'</u>	<u>7/13/87</u>	Drawdown	
			<u>insufficient water for aquifer tests</u>	
Approved By <u>MAC</u>	Date <u>7/13/87</u>	Approved By <u>MAC</u>	Date <u>11/24/87</u>	

OTHER APPLICABLE ITEMS		
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test <u>7/11/87</u>	☒ Complete As-Built Diagram, Driller's and Geologist's Logs
☒ Concrete Pad	☒ Well Development	
Approved By <u>M.A. Chomney</u>	Date <u>12/7/87</u>	

Reviewed By J.L. Nathan Date 12-28-87

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-E34-6 Geologist R. A. HAGEN Page 1 of 2
 K. Oster R. Premic, E. S. Jensen, S. Teel, T. Gilmore
 M. Chambers
 Reviewed by J. L. McElham Date 12-28-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data		drill rate (ft/h)
Description	Diagram		Diagram Litho.	Lithologic Description	
Cement 0'-5'		0		gravelly silty sand	N/A
		10		SILTY SANDY GRAVEL	1.7
		15		" " "	2.2
		20		gravelly silty sand	2.5
		25		" " "	3.3
		30		silty sand	4.2
		35		slightly silty gravelly sand	3.1
		40		" " " "	10
		45		" " " "	4.2
		50		Silty sandy gravel	2.5
		55		" " "	1.1
16" carbon steel casing		60		" " "	2.6
		65		" " "	2.5
12" diam. temporary carbon steel casing		70		" " "	1.9
		75		Gravel	2.0
		80		"	1.1
carbon steel casing		85		"	2.5
		90		gravelly sand	2.5
		95		" " "	1.5
unclog grout 5'-145"		100		silty sandy gravel	1.7
		105		" " "	1.3
		110		sandy gravel	1.6
4" stainless steel casing		115		silty sandy gravel	1.5
		120		" " "	2.9
		125		" " "	2.5
		130		" " "	1.5

A-1800-188 (3/87)

Well Number 299-E34-G Geologist R.A. Hagen, R. Premick, Page 2 of 2
K. Oster, M. Channer, E.J. Jensen, S. Teal, T. Gilmore
Reviewed by J.E. McShane Date 12-28-87

A-1800-186 (3/87)

APPENDIX C

WELL CONSTRUCTION SUMMARIES FOR
THE 200-WEST AREA LOW-LEVEL BURIAL GROUNDS

APPENDIX C

WELL CONSTRUCTION SUMMARIES FOR THE 200-WEST AREA LOW-LEVEL BURIAL GROUNDS

Nineteen ground-water monitoring wells were drilled around two waste management areas in the 200-West Area during the summer and fall of 1987 (Figure C.1). Wells were drilled with cable-tool drill rigs using core barrels when possible; otherwise, hard tools were used. This appendix provides a summary of the well construction, Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole data correlation chart for each well. Depth and size information provided in the well construction summary has been rounded to the nearest 0.1 ft.

KEY TO GEOHYDROLOGIC UNITS ON DATA CORRELATION CHARTS - 200-WEST AREA

H	Hanford formation (undifferentiated)
HC	Coarse-grained sequence
HS	Basal slack-water sequence
EPS	Early "Palouse" soil
PP	Plio-Pleistocene unit
UR	Upper Ringold unit
MR	Middle Ringold unit
LR	Lower Ringold unit
EM	Elephant Mountain Member (basalt)

FIGURE C.1. Well Locations for the 200-West Area Low-Level Burial Grounds

SUMMARY OF CONSTRUCTION, WELL 299-W6-2

This well, started on September 30, 1987, and completed on November 13, 1987, was drilled to a depth of 248 ft below ground surface. The initial depth to the water table was 227.8 ft below the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 238 to 248 ft, and the temporary carbon steel casing was backpulled 9 ft for the aquifer test. A 21-ft length of 4-in. 20-slot stainless steel screen was installed from 224 to 245 ft, and 224 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (220 to 248 ft), Volclay pellets (217 to 220 ft), dry bentonite (47 to 217 ft and 3.5 to 20 ft), and bentonite slurry (20 to 47 ft), and concrete (0 to 3.5 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 8.8 gpm for 40 min. An estimated total volume of 352 gal was removed during the development. The final turbidity reading of the discharged water was 4.4 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project KEH-1914
Location 200 WEST AREA - HANFORD
Driller KELLY OLSON
Drilling Co. OLWELCO
Geologist AIRHART, WILBUR, WILMORE

Well Number 299-W6-2
Temporary Well Number ---
Coordinates N. 45, 571 N. 75, 302
Casing Elevation 692.45
Ground Elevation 690.17

DRILLING METHOD

Rotary Air --- Mud ---
Cable Tool D --- H 10' - 248'
Drilling Fluid --- H₂O
Other BACKHOE 0-10'

COMPLETION DATA

Drilled Depth 248'
Completion Depth 245'
Date Started 9/30/87 Completed 11/13/87
Static Water Level/Date 227.8' BELOW LAND SURFACE
10/29/87

CASING DATA

Type --- Size ---
TYPE 304 STAINLESS STEEL CASING 4" DIAMETER to 224'
to ---
to ---

Approved By S.P. Airhart Date 11/30/87

PERFORATIONS

Type ---
Depth --- Schedule ---

App. By --- Date ---

SCREEN

4" dia. Type 304 SS. 8" dia. Type 304 SS.
Type CONTINUOUS WIRE CONTINUOUS WIRE
Length 21' 10'
Slot Size 20-SLOT 30-SLOT
Depths 224' to 238' to 248'
245' 248'
App. By S.P. Airhart Date 11/30/87

ANNULAR SEAL

Type	Interval	Volume
<u>COLORADO SILICA SAND</u>	<u>220' - 248'</u>	<u>16.33 ft³</u>
<u>DRY BENTONITE</u>	<u>3.5' - 20'</u>	<u>146.91 ft³</u>
<u>BENTONITE SLURRY</u>	<u>20' - 47'</u>	<u>40.11 ft³</u>
<u>CONCRETE</u>	<u>0' - 3.5'</u>	<u>12 ft³</u>
<u>VELLAY PELLETS</u>	<u>217' - 220'</u>	<u>2.87 ft³</u>

App. By S.P. Airhart Date 11/30/87

GEOPHYSICAL LOGGING

Sondes	Interval	Date
<u>NATURAL GAMMA</u>	<u>0' - 248'</u>	<u>10/29/87</u>
<u>NEUTRON</u>	<u>0' - 248'</u>	<u>10/29/87</u>
<u>DENSITY</u>	<u>0' - 248'</u>	<u>10/29/87</u>
<u>---</u>	<u>---</u>	<u>---</u>
<u>---</u>	<u>---</u>	<u>---</u>
<u>---</u>	<u>---</u>	<u>---</u>

Approved By S.P. Airhart Date 11/6/87

AQUIFER TESTING

Type of Test CONSTANT DISCHARGE
Length of Test 5 HOURS
Volume Pumped 8500 GALS.
Drawdown 13.76 ft.

Approved By S.P. Airhart Date 11/30/87

OTHER APPLICABLE ITEMS

SPA Steam Cleaning
SPA Storage of Const. Material
SPA Tool Lubricants
SPA Concrete Pad

SPA Protective Steel Posts
SPA Safety Paint
SPA Straightness Test
SPA Well Development

DOWN Downhole TV Inspection
--- Well Abandonment
SPA Complete As-Built Diagram,
Driller's and Geologist's Logs

Approved By S.P. Airhart Date 11/30/87

Reviewed By V.L. McLean Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 255-WB-2 Geologist W. B. GILMORE, AIRHART Page 1 of 2

Reviewed by J. E. McKelhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Concrete Surface Seal (0'-2.5')		5'		SLIGHTLY SILTY GRAVEL
-10#100 mesh Big Horn bentonite (3.5'-26')		10'		
0'-20' 16" CARBON STEEL CASING		15'		SLIGHTLY SANDY GRAVEL
0'-40' 12" CARBON STEEL CASING		20'		SANDY GRAVEL
0'-148' 10" CARBON STEEL CASING		25'		
0'-252' 8" CARBON STEEL CASING		30'		
0'-252' 4" STAINLESS STEEL CASING (PERMANENT)		35'		
0'-252' 4" STAINLESS STEEL CASING (PERMANENT)		40'		
NOTE: ALL CARBON STEEL CASING REMOVED.		45'		
		50'		
Bentonite slurry 1 lb. bentonite : 1 gal. H ₂ O mixture (20'-47')		55'		
		60'		CLAYEY SANDY GRAVEL
		65'		SANDY CLAY
		70'		CLAYEY SAND
		75'		SAND
		80'		
		85'		
-10#100 mesh Big Horn bentonite (dry) (47'-219')		90'		SILTY SAND
		95'		SLIGHTLY GRAVELLY SILTY SAND
		100'		SILTY SANDY GRAVEL
		105'		SANDY GRAVEL
		110'		
		115'		SLIGHTLY SILTY GRAVELLY SAND
		120'		SILTY SANDY GRAVEL
		125'		SANDY GRAVEL
		130'		SILTY SANDY GRAVEL

□ - CAMEL

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W6-2 Geologist ARMHART Page 2 of 2

Reviewed by W.E. McElhaney Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
	135'		<u>SILTY SANDY GRAVEL</u>
		140'		
		145'		
		150'		
		155'		
		160'		<u>GRAVELLY SAND</u>
		165'		
		170'		
		175'		
		180'		
		185'		
		190'		
		195'		<u>SILTY/CLAYEY SANDY GRAVEL</u>
		200'		
		205'		<u>SILTY SANDY GRAVEL</u>
		210'		
		215'		
		220'		
		225'		
		230'		
		235'		
		240'		
		245'		
		250'		<u>248' SILTY GRAVELLY SAND</u>

SUMMARY OF CONSTRUCTION, WELL 299-W7-1

This well, started on June 1, 1987, and completed on July 30, 1987, was drilled to a depth of 244.9 ft below ground surface. The initial depth to the water table was 226 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 233 to 243 ft, and the temporary carbon steel casing was back-pulled 9 ft for the aquifer test. A 20-ft length of 4-in. 20-slot stainless steel screen was installed from 224 to 245 ft, and 225 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was back-pulled using the cable-tool rig. The annular seal consists of sand pack (217 to 243.8 ft), bentonite pellets (212 to 217 ft), Volclay grout (3 to 212 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10.7 gpm for 60 min. An estimated total volume of 642 gal was removed during the development. The final turbidity reading of the discharged water was 0.73 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>200 West Area RCRA Well Drilling</u>		Well Number <u>299-W7-1</u>	
Location <u>Hanford Site 200 West Area</u>		Temporary Well Number <u>none</u>	
Driller <u>Bill Moorman</u>		Coordinates <u>N. 46, 551 N. 78, 601</u>	
Drilling Co. <u>Onwego Drilling</u>		Casing Elevation <u>690.71</u>	
Geologist <u>JS Kilbur, SS Teel, SP Airhard, T Gilmore</u>		Ground Elevation <u>688.65</u>	

DRILLING METHOD		COMPLETION DATA	
Rotary Air _____	Mud _____	Drilled Depth <u>244' 9"</u>	
Cable Tool _____	D <u>0'-15'</u> H <u>15'-244' 9"</u>	Completion Depth <u>243' 9"</u>	
Drilling Fluid <u>Water</u>		Date Started <u>6/1/87</u>	Completed <u>7/30/87</u>
Other _____		Static Water Level/Date <u>226' 7/13/87</u>	

CASING DATA			
Type _____	Size _____		
<u>Type 304 Stainless Steel Casing</u>	<u>4" diameter</u>	to <u>225'</u>	
_____	_____	to _____	
_____	_____	to _____	
Approved By <u>JS Kilbur</u>		Date <u>7/30/87</u>	

PERFORATIONS		SCREEN		ANNULAR SEAL	
Type <u>N/A</u>		<u>Telescoping</u>	<u>5" dia. type 304 S.S.</u>	Type _____	Interval _____
Depth _____	Schedule _____	<u>Type Continuous</u>	<u>4" dia. type 304 S.S.</u>	<u>Sand</u>	<u>217'-243' 9"</u>
_____	_____	Length <u>10'</u>	<u>Continuous</u>	<u>Volclay Pellets</u>	<u>212'-217'</u>
_____	_____	Slot Size <u>30</u>	<u>Continuous</u>	<u>Volclay Grout</u>	<u>3'-212'</u>
_____	_____	Depths <u>243'</u>	<u>Continuous</u>	<u>Concrete</u>	<u>0-3'</u>
_____	_____	<u>233'</u>	<u>Continuous</u>		
_____	_____	<u>224'</u>	<u>Continuous</u>		
App. By _____	Date _____	App. By <u>JS Kilbur</u>	Date <u>7/30/87</u>	App. By <u>JS Kilbur</u>	Date <u>7/30/87</u>

GEOPHYSICAL LOGGING			AQUIFER TESTING		
Sondes _____	Interval _____	Date _____	Type of Test <u>Constant Discharge Test</u>		
<u>Neutron</u>	<u>0' - 244'</u>	<u>7/10/87</u>	Length of Test <u>8 hrs</u>		
<u>Density</u>	<u>0' - 244'</u>	<u>7/10/87</u>	Volume Pumped <u>8,400 gals.</u>		
<u>Natural Gamma</u>	<u>0' - 244'</u>	<u>7/10/87</u>	Drawdown <u>3.96</u>		
_____	_____	_____			
_____	_____	_____			
_____	_____	_____			
Approved By <u>JS Kilbur</u>	Date <u>7/10/87</u>		Approved By <u>JS Kilbur</u>	Date <u>7/15/87</u>	

OTHER APPLICABLE ITEMS		
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs
Approved By <u>JS Kilbur</u>	Date <u>7/30/87</u>	

Reviewed By J.R. McElhannon Date 1-7-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-1107-01 Geologist WILBUR TEEL JENSEN, BISHOP Page 1 of 2

AIRHART

Reviewed by V.L. McPherson Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Concrete Surface Seal (0'-3')		5		SLIGHTLY SILTY GRAVELLY SAND
		10		SLIGHTLY SILTY SANDY GRAVEL
0'-63'5" 12" dia. Carbon Steel Casing		15		SILTY SANDY GRAVEL
0'-157'1" 10" dia. Carbon Steel Casing		20		
0'-245' 8" dia. Carbon Steel Casing		25		
		30		SANDY GRAVEL
		35		
0'-225' 4" dia. Stainless Steel Casing		40		
		45		
		50		
		55		
Volclay Grout (2'-212')		60		
		65		SILTY SAND
		70		
		75		SILTY SAND w/ CALICHE
		80		CALICHE & SAND
		85		SILTY SAND
		90		
		95		
		100		SAND (COARSE)
		105		
		110		
		115		
		120		
		125		
		130		SLIGHTLY GRAVELLY SAND

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W107-1 Geologist WILBUR, TEELE, JENSEN, BISHOP Page 2 of 2
AIRHART

Reviewed by V.L. Mathias Date 1-7-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SAND (silt & clay)
		140		SAND
		145		SILTY SANDY GRAVEL
		150		
		155		
		160		
		165		
		170		
		175		
		180		
		185		
		190		GRAVELLY SAND
		195		SILTY SANDY GRAVEL
		200		
		205		
		210		
		215		
D/T of rocky pellets @ 212'		220		
D/T of 20-30 sand @ 217'		225		
D/T of 4" SS screen @ 225'		230		
D/B of 4" SS screen @ 245'		235		
		240		
D/T of telescoping screen @ 233'		245		GRAVELLY SILTY SAND
D/B of telescoping screen @ 243'				

SUMMARY OF CONSTRUCTION, WELL 299-W7-2

This well, started on August 4, 1987, and completed on September 30, 1987, was drilled to a depth of 236 ft below ground surface. The initial depth to the water table was 212.5 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 211 to 221 ft, and the temporary carbon steel casing was backpulled 9 ft for the aquifer test. A 20-ft length of 4-in. 20-slot stainless steel screen was installed from 202 to 222 ft, and 202 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (198.3 to 222 ft), bentonite pellets (194.3 to 198.3 ft), bentonite grout (4 to 194.3 ft), and concrete (0 to 4 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.0 gpm for 271 min. An estimated total volume of 2,967 gal was removed during the development. The final turbidity reading of the discharged water was 7.8 NTU, indicating that further development may be needed at this well.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 West RCRA Drilling</u>	Well Number <u>299 WZ 2</u>
Location <u>200 West</u>	Temporary Well Number <u>NA</u>
Driller <u>Hamer Jay</u>	Coordinates <u>Unavailable</u>
Drilling Co. <u>Onwego Drilling Co</u>	Casing Elevation <u>Unavailable</u>
Geologist <u>CW Bishop / T Gilmore, JS Kilbur</u>	Ground Elevation <u>Unavailable</u>

DRILLING METHOD	COMPLETION DATA
Rotary Air <u>NA</u> Mud <u>NA</u>	Drilled Depth <u>236</u>
Cable Tool <u>D</u> <u>NA</u> <u>H</u> <u>10'-236'</u>	Completion Depth <u>222'</u>
Drilling Fluid <u>Water</u>	Date Started <u>8/4/87</u> Completed <u>9/30/87</u>
Other <u>Backhoe 0-10'</u>	Static Water Level/Date <u>212.5' 9/4; 217.9' 9/9</u>

CASING DATA	
Type	Size
<u>9" 304 Stainless Steel Telescoping 3036t Screen</u>	<u>222'</u> to <u>212'</u>
<u>4" 304 Stainless Steel Casing</u>	<u>202'</u> to <u>Surface</u>
	to
Approved By <u>JS</u>	Date <u>9/17</u>

PERFORATIONS	SCREEN	ANNULAR SEAL
Type <u>NA</u>	Type <u>304 Stainless Steel 4"</u>	Type Interval Volume
Depth	Length <u>20' 4"</u>	<u>10-20 Sand</u> <u>222'-199.3'</u> <u>2900 lbs</u>
Schedule	Slot Size <u>20 Slot</u>	<u>Unclay pellets</u> <u>199.3'-194.3'</u> <u>25 gal</u>
	Depths <u>222' - 202'</u>	<u>Grout</u> <u>194.3' - 4'</u> <u>3800 lbs</u>
		<u>Cement</u> <u>0' - 4'</u> <u>~6 Ft³</u>
App. By	App. By <u>JS</u> Date <u>9/17/87</u>	App. By <u>JS</u> Date <u>11/3/87</u>

GEOPHYSICAL LOGGING	AQUIFER TESTING
Sondes	Type of Test <u>Constant Discharge / Recharge</u>
<u>Not Gamma</u> <u>0 - 221'</u> <u>9/18/87</u>	Length of Test <u>7 hr</u>
<u>Neutron</u> <u>0 - 221'</u> <u>9/18/87</u>	Volume Pumped <u>4800 gal</u>
<u>Density</u> <u>0 - 221'</u> <u>9/18/87</u>	Drawdown <u>5.41'</u>
Approved By <u>JS</u> Date <u>9/18/87</u>	Approved By <u>JS</u> Date <u>9/16/87</u>

OTHER APPLICABLE ITEMS		
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,
☒ Concrete Pad	☒ Well Development	☒ Driller's and Geologist's Logs
Approved By <u>JS</u> <u>T Gilmore</u>	Date <u>11/3/87</u>	

Reviewed By V. K. McPherson Date 1-7-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W7-2 Geologist C.W. Bishop Page 1 of 2

Reviewed by V.K. McShan Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
16" Carbon Steel Casing		5		SILTY SANDY GRAVEL
12" Carbon Steel Casing		10		" " "
10" Carbon Steel Casing 15' 8"		15		" " "
8" Carbon Steel Casing 24' 8"		20		SANDY GRAVEL
4" Stainless Steel Casing		25		SILTY SANDY GRAVEL
		30		GRAVELY SAND
		35		SILTY SANDY GRAVEL
		40		SILT
		45		GRAVELY SANDY SILT
		50		SILTY SANDY (GRAVEL)
		55		" " "
		60		" " "
		65		" " "
		70		" " "
		75		SILTY GRAVELY SAND
		80		SILTY SAND
	85		" "	
	90		" "	
	95		SILTY SANDY GRAVEL	
	100		GRAVELY SILTY SAND	
	105		SILTY SANDY GRAVEL	
	112		" " "	
	115		" " "	
	120		" " "	
	125		" " "	
	130		" " "	

A-1600-186 (2/87)

AS-BUILT DIAGRAM

Well Number 299 W7 2 Geologist T. Gilmore Page 2 of 2

Reviewed by W.L. McShane Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
	135		
		140		
		145		GRAVELY SAND
		150		SILTY SANDY GRAVEL
		155		
		160		
		165		
		170		
		175		
Centralizers 40' above screen		180		
		185		
Envisaflex Bentonite Grout		190		
Udcloy pellets to 194.3' (25 gal)		195		
Sand Pack to 198.3'		200		
		205		SANDY GRAVEL
		210		SILTY SANDY GRAVEL (Chy)
		215		SANDY GRAVEL
10' of Telespacing Screen @ 221'		220		GRAVELY SAND
		225		
10-20 Co. Silica Sand		230		GRAVEL
Total Depth 236'		235		SILTY GRAVELY SAND
		240		TD 236'
		245		
		250		
		255

SUMMARY OF CONSTRUCTION, WELL 299-W7-3

This well, started on July 27, 1987, and completed on November 23, 1987, was drilled to a depth of 475 ft below ground surface. The initial depth to the water table was 210.2 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 476.8 to 466.8 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. The telescoping screen was later damaged and is now located between depths of 476.8 to -470 ft. A 21-ft length of 4-in. 20-slot stainless steel screen was installed from 449 to 470 ft, and 470 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (427 to 476 ft), Volclay grout (196 to 427 ft), bentonite slurry (196 to 20 ft), dry bentonite (5 to 20 ft), and concrete (0 to 5 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10.5 gpm for 90 min. An estimated total volume of 950 gal was removed during the development. The final turbidity reading of the discharged water was 3.3 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project 200 West RCRA Drilling Project
Location 200 West
Driller Bill Moorman
Drilling Co. Onwego Drilling Co.
Geologist C.W. Bishop / T. Gilmore / Steve Tool

Well Number 299 W73
Temporary Well Number NA
Coordinates N. 46,520 W. 77,420
Casing Elevation 676.14
Ground Elevation 673.71

DRILLING METHOD

Rotary Air NA Mud NA
Cable Tool D NA H 8'-475'
Drilling Fluid Water
Other BACKHOLE 0'-8'

COMPLETION DATA

Drilled Depth 475'
Completion Depth 470'
Date Started 7/27/87 Completed 11/23/87
Static Water Level/Date 202' 7/7; 222' 9/10; 247' 9/15

CASING DATA

Type TYPE 304 STAINLESS STEEL CASING Size 4" DIAMETER to 470'
to _____
to _____

Approved By SP. Ambert Date 11-8-87

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type		4" dia. Type 304 ss Type <u>CONTINUOUS WIRE</u>	8" dia. Type 304 ss Type <u>CONTINUOUS WIRE</u>	Type	Interval	Volume
Depth	Schedule	Length	10'	Col. Silica Sand	476'-427'	17.83 ft ³
		Slot Size	20-slot	Verclay Grout	427'-196'	213.90 ft ³
		Depths	449' to ~470' to	Bentonite Slurry	196'-20'	668.45 ft ³
			470' 476' 8"	Dry Bentonite	20'-5'	93.66 ft ³
App. By	Date	App. By	SP. Ambert	Concrete	5'-P	7.38 ft ³
		Date	11-8-87	App. By	SP. Ambert	11/20/87

748.66
SPA 41

GEOPHYSICAL LOGGING			AQUIFER TESTING				
Sondes	Interval	Date	Type of Test	Length of Test			
NATURAL GAMMA	0' - 476'	10/28/87	CONSTANT DISCHARGE	28-25 hrs.			
NEUTRON	0' - 476'	10/28/87	Volume Pumped	4779 gallons			
DENSITY	0' - 476'	10/28/87	Drawdown	154.78'			
Approved By	SP. Ambert	Date	10/28/87	Approved By	SP. Ambert	Date	10/31/87

OTHER APPLICABLE ITEMS

☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection			
☒ Storage of Const. Material	☒ Safety Paint	☐ Well Abandonment			
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,			
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs			
Approved By	SP. Ambert	Date	11-30-87		

Reviewed By W.B. McShane Date 1-7-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W7-3 Geologist C.W. BISHOP Page 1 of 4

Reviewed by V.H. McShane Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
concrete surface seal				
20" Carbon Steel Casing 20'11"		5		GRAVEL
16" Carbon Steel Casing 145'6"		10		SILTY SANDY GRAVEL
12" Temporary Carbon Steel Casing 132'6"		15		" " "
10" Temporary Carbon Steel Casing 114'6"		20		" " "
8" Temporary Carbon Steel Casing 97'		25		" " "
		30		" " "
		35		GRAVELY SILTY CLAY
		40		SILT
		45		GRAVELY SANDY SILT
Dry bentonite		50		SILTY SANDY GRAVEL
		55		" " "
		60		" " "
		65		GRAVELY SILTY SAND
		70		" " "
		75		" " "
Dry bentonite		80		" " "
		85		GRAVELY SAND
		90		" " "
Dry bentonite		95		SAND
		100		GRAVELY SAND
		105		" "
		110		SILTY SANDY GRAVEL
		115		" " "
		120		" " "
		125		" " "
		130		" " "

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299 W 7 3 Geologist T. Gilmore Page 2 of 4Reviewed by V.H. McElhan Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SILTY SANDY GRAVEL
		140		
		145		
Dry bentonite		150		
		155		
		160		
Bentonite slurry (196')		165		Trace Clay
		170		
		175		
		180		SANDY GRAVEL
		185		GRAVELY SAND
		190		< Lith change ^{by new core} _{more silty}
		195		SANDY GRAVEL
		200		
		205		SILTY GRAVELY SAND
Volclay Grout (196'-477')		210		To Clay
		215		▼ water level 210.2' *
		220		SANDY GRAVEL
		225		
		230		SILTY SAND
		235		
		240		To Clay
		245		
		250		SAND
		255		

A-1800-186 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299 W7 3 Geologist T. Gilmore Page 3 of 4Reviewed by V.L. McShane Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		265		Clay (Bentonite?) 259'-261'
		270		SANDY GRAVEL @ 262'
		275		Sandy Gravel
		280		Gravelly sand
		285		Sandy gravel
		290		" "
		295		" "
		300		" "
		305		" "
		310		Gravel
		315		Gravelly sand
Volclay Grout		320		Silty sandy gravel
		325		" " "
		330		" " "
		335		Sandy gravel
		340		" "
		345		Gravelly sand
		350		Silty sandy gravel
		355		Gravelly silty sand
		360		" " "
		365		Gravelly sand
		370		Sand
		375		"
		380		Silty sandy gravel
		385		Sandy gravel
		390		Gravelly sand

A-1800-186 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-W7-3 Geologist S. Teel Page 4 of 4Reviewed by V.L. McElhan Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		395		Gravely sand
		400		Sandy gravel
		405		Gravely silty sand
		410		Silty sandy gravel
		415		Gravely silty sand
		420		Sandy gravel
		425		" "
		430		" "
20-30 mesh Colorado to inhibit migration of volclay grout into sandpack.		435		Gravely sand
		440		Gravely silty sand
		445		Silty sandy gravel
		450		Sandy gravel
10-20 mesh Colorado silica sand (427' - 476')		455		" "
		460		" "
		465		Sand
		470		Sandy gravel
8" telescoping screen was damaged while re-drilling hole to re-insert 4" s.s. casing & screen. Inside of telescoping screen was filled w/ silica sand.		475		BASALT CONTACT @ ~ 475'

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W7-4

This well, started on September 29, 1987, and completed on November 19, 1987, was drilled to a depth of 235 ft below ground surface. The depth to the water table was 205 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 223 to 233 ft, and the carbon steel drill casing was back-pulled 9 ft for the aquifer test. A 10-ft length of 4-in. 10-slot stainless steel screen was installed from 213 to 233 ft, and 213 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was back-pulled using the cable-tool rig. The annular seal consists of sand pack (194 to 233 ft), Volclay pellets (190 to 194 ft), bentonite slurry (12 to 194 ft), dry bentonite (3 to 12 and 50 to 60 ft), and concrete (0 to 3) ft.

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10.4 gpm for 40 min. An estimated total volume of 416 gal was removed during the development. The final turbidity reading of the discharged water was 3.3 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>KEH-1914</u>		Well Number <u>299-W7-4</u>																																	
Location <u>200 WEST AREA - HANFORD</u>		Temporary Well Number <u> </u>																																	
Driller <u>RUSS VANCE</u>		Coordinates <u>N. 45,435 N. 77,040</u>																																	
Drilling Co. <u>ONWELD</u>		Casing Elevation <u>671.69</u>																																	
Geologist <u>TEEL; GILMORE; WILBUR; AIRHART</u>		Ground Elevation <u>669.02</u>																																	
DRILLING METHOD Rotary Air <u> </u> Mud <u> </u> Cable Tool <u> </u> D <u> </u> H <u>5'-235'</u> Drilling Fluid <u>H₂O</u> Other <u>BACKHOLE 0'-5'</u>		COMPLETION DATA Drilled Depth <u>235'</u> Completion Depth <u>233'</u> Date Started <u>9/29/87</u> Completed <u>11/18/87</u> Static Water Level/Date <u>205' / 11-2-87</u>																																	
CASING DATA Type <u>TYPE 304 STAINLESS STEEL CASING</u> Size <u>4" DIAMETER</u> to <u>233'</u> to <u> </u> to <u> </u> Approved By <u>S.P. Auland</u> Date <u>11/2/87</u>																																			
PERFORATIONS Type <u> </u> Depth <u> </u> Schedule <u> </u> App. By <u> </u> Date <u> </u>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2">SCREEN</th> <th colspan="2">ANNULAR SEAL</th> </tr> <tr> <td>4" dia. Type 304 ss. Type <u>continuous wrap</u></td> <td>8" dia. Type 304 ss. Type <u>continuous wrap</u></td> <td>Type <u> </u></td> <td>Interval <u> </u> Volume <u> </u></td> </tr> <tr> <td>Length <u>30'</u></td> <td>Length <u>10'</u></td> <td><u>COLORADO SILICA SAND</u></td> <td><u>184'-233'</u> <u>22.94 ft³</u></td> </tr> <tr> <td>Slot Size <u>10-slot</u></td> <td>Slot Size <u>30-slot</u></td> <td><u>WELLY PEWETS</u></td> <td><u>190'-194'</u> <u>2.87 ft³</u></td> </tr> <tr> <td>Depths <u>203' to</u></td> <td>Depths <u>223' to</u></td> <td><u>BENTONITE SLURRY</u></td> <td><u>12'-184'</u> <u>267 ft³</u></td> </tr> <tr> <td><u>233'</u></td> <td><u>233'</u></td> <td><u>DRY BENTONITE</u></td> <td><u>5'-12'</u> <u>26.03 ft³</u></td> </tr> <tr> <td></td> <td></td> <td><u>CONCRETE</u></td> <td><u>0'-3'</u> <u>4 ft³</u></td> </tr> <tr> <td>App. By <u>S.P. Auland</u></td> <td>Date <u>11/2/87</u></td> <td>App. By <u>S.P. Auland</u></td> <td>Date <u>11/2/87</u></td> </tr> </table>		SCREEN		ANNULAR SEAL		4" dia. Type 304 ss. Type <u>continuous wrap</u>	8" dia. Type 304 ss. Type <u>continuous wrap</u>	Type <u> </u>	Interval <u> </u> Volume <u> </u>	Length <u>30'</u>	Length <u>10'</u>	<u>COLORADO SILICA SAND</u>	<u>184'-233'</u> <u>22.94 ft³</u>	Slot Size <u>10-slot</u>	Slot Size <u>30-slot</u>	<u>WELLY PEWETS</u>	<u>190'-194'</u> <u>2.87 ft³</u>	Depths <u>203' to</u>	Depths <u>223' to</u>	<u>BENTONITE SLURRY</u>	<u>12'-184'</u> <u>267 ft³</u>	<u>233'</u>	<u>233'</u>	<u>DRY BENTONITE</u>	<u>5'-12'</u> <u>26.03 ft³</u>			<u>CONCRETE</u>	<u>0'-3'</u> <u>4 ft³</u>	App. By <u>S.P. Auland</u>	Date <u>11/2/87</u>	App. By <u>S.P. Auland</u>	Date <u>11/2/87</u>
SCREEN		ANNULAR SEAL																																	
4" dia. Type 304 ss. Type <u>continuous wrap</u>	8" dia. Type 304 ss. Type <u>continuous wrap</u>	Type <u> </u>	Interval <u> </u> Volume <u> </u>																																
Length <u>30'</u>	Length <u>10'</u>	<u>COLORADO SILICA SAND</u>	<u>184'-233'</u> <u>22.94 ft³</u>																																
Slot Size <u>10-slot</u>	Slot Size <u>30-slot</u>	<u>WELLY PEWETS</u>	<u>190'-194'</u> <u>2.87 ft³</u>																																
Depths <u>203' to</u>	Depths <u>223' to</u>	<u>BENTONITE SLURRY</u>	<u>12'-184'</u> <u>267 ft³</u>																																
<u>233'</u>	<u>233'</u>	<u>DRY BENTONITE</u>	<u>5'-12'</u> <u>26.03 ft³</u>																																
		<u>CONCRETE</u>	<u>0'-3'</u> <u>4 ft³</u>																																
App. By <u>S.P. Auland</u>	Date <u>11/2/87</u>	App. By <u>S.P. Auland</u>	Date <u>11/2/87</u>																																
GEOPHYSICAL LOGGING <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Sondes</th> <th>Interval</th> <th>Date</th> </tr> <tr> <td><u>NATURAL GAMMA</u></td> <td><u>0' - 231'</u></td> <td><u>11/5/87</u></td> </tr> <tr> <td><u>DENSITY</u></td> <td><u>0' - 231'</u></td> <td><u>11/5/87</u></td> </tr> <tr> <td><u>NEUTRON</u></td> <td><u>0' - 231'</u></td> <td><u>11/5/87</u></td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> Approved By <u>S.P. Auland</u> Date <u>11/5/87</u>		Sondes	Interval	Date	<u>NATURAL GAMMA</u>	<u>0' - 231'</u>	<u>11/5/87</u>	<u>DENSITY</u>	<u>0' - 231'</u>	<u>11/5/87</u>	<u>NEUTRON</u>	<u>0' - 231'</u>	<u>11/5/87</u>																AQUIFER TESTING Type of Test <u>CONSTANT - DISCHARGE</u> Length of Test <u>7 hrs.</u> Volume Pumped <u>20160 gallons</u> Drawdown <u>1.7'</u> Approved By <u>S.P. Auland</u> Date <u>11/12/87</u>						
Sondes	Interval	Date																																	
<u>NATURAL GAMMA</u>	<u>0' - 231'</u>	<u>11/5/87</u>																																	
<u>DENSITY</u>	<u>0' - 231'</u>	<u>11/5/87</u>																																	
<u>NEUTRON</u>	<u>0' - 231'</u>	<u>11/5/87</u>																																	
OTHER APPLICABLE ITEMS <table style="width:100%;"> <tr> <td><u>SPA</u> Steam Cleaning</td> <td><u>SPA</u> Protective Steel Posts</td> <td><u>75%</u> Downhole TV Inspection</td> </tr> <tr> <td><u>SPA</u> Storage of Const. Material</td> <td><u>SPA</u> Safety Paint</td> <td><u> </u> Well Abandonment</td> </tr> <tr> <td><u>SPA</u> Tool Lubricants</td> <td><u>SPA</u> Straightness Test</td> <td><u>SPA</u> Complete As-Built Diagram,</td> </tr> <tr> <td><u>SPA</u> Concrete Pad</td> <td><u>SPA</u> Well Development</td> <td>Driller's and Geologist's Logs</td> </tr> <tr> <td>Approved By <u>S.P. Auland</u></td> <td>Date <u>11/30/87</u></td> <td></td> </tr> </table>				<u>SPA</u> Steam Cleaning	<u>SPA</u> Protective Steel Posts	<u>75%</u> Downhole TV Inspection	<u>SPA</u> Storage of Const. Material	<u>SPA</u> Safety Paint	<u> </u> Well Abandonment	<u>SPA</u> Tool Lubricants	<u>SPA</u> Straightness Test	<u>SPA</u> Complete As-Built Diagram,	<u>SPA</u> Concrete Pad	<u>SPA</u> Well Development	Driller's and Geologist's Logs	Approved By <u>S.P. Auland</u>	Date <u>11/30/87</u>																		
<u>SPA</u> Steam Cleaning	<u>SPA</u> Protective Steel Posts	<u>75%</u> Downhole TV Inspection																																	
<u>SPA</u> Storage of Const. Material	<u>SPA</u> Safety Paint	<u> </u> Well Abandonment																																	
<u>SPA</u> Tool Lubricants	<u>SPA</u> Straightness Test	<u>SPA</u> Complete As-Built Diagram,																																	
<u>SPA</u> Concrete Pad	<u>SPA</u> Well Development	Driller's and Geologist's Logs																																	
Approved By <u>S.P. Auland</u>	Date <u>11/30/87</u>																																		

Reviewed By W.R. McWhorter Date 1-7-88

A-1800-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-W7-4 Geologist TEEL; GILMORE; WILSON; AIRHART Page 1 of 2

Reviewed by W.L. Mithun Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
concrete surface seal 0'-3'		5		GRAVEL
Dry bentonite		10		SANDY GRAVEL
16" Carbon Steel Casing (0'-20')		15		GRAVEL
12" Carbon Steel Casing (0'-50' 8 1/2")		20		SANDY GRAVEL
10" Carbon Steel Casing (0'-150' 4")		25		GRAVEL
8" Carbon Steel Casing (0'-232')		30		
4" Stainless Steel Casing (0'-703')		35		SANDY GRAVEL
		40		
NOTE: All Carbon Steel Casing was removed.		45		
		50		
Dry Bentonite		55		SILTY SANDY GRAVEL
		60		GRAVELLY SILT/CLAY
		65		GRAVELLY SANDY SILT
		70		GRAVELLY SILTY SAND
		75		GRAVELLY SAND
		80		SAND
		85		
Bentonite slurry (12'-150')		90		
		95		
		100		
		105		GRAVELLY SAND
		110		
		115		SANDY GRAVEL
		120		
		125		SILTY SANDY GRAVEL
		130		SANDY GRAVEL

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 200-W7-4 Geologist TEEL, GILMORE, WILBUR Page 2 of 2
A12442T

Reviewed by W.L. McElhan Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SANDY GRAVEL
		140		
		145		SILTY SANDY GRAVEL
		150		
		155		
Bentonite slurry		160		
		165		SANDY GRAVEL
		170		SILTY SANDY GRAVEL
		175		COARSE SANDY GRAVEL
		180		SILTY SANDY GRAVEL
		185		
		190		
Volclay pellets (190'-194')		195		
		200		
Top of 4' screen @ 203'		205		
		210		
Centralizers		215		SILTY GRAVELLY SAND
10-20 mesh Colorado silica sand (194'-233')		220		SLIGHTLY SILTY GRAVELLY SAND
Top of telescoping screen		225		SILTY SANDY GRAVEL
		230		
Bottom of 8" & 4" screens @ 233'		235		
Drill Depth = 235'		240		

A-1800-186 (3/87)

Well Completion Report/Title III Inspection List

Project <u>KEH-1914</u>		Well Number <u>289-W7-S</u>			
Location <u>209 WEST AREA ; HANFORD</u>		Temporary Well Number <u> </u>			
Driller <u>HOMER JOY, DAVE GARLIA</u>		Coordinates <u>N. 46, 509 4.76, 816</u>			
Drilling Co. <u>ONWELD DRILLING</u>		Casing Elevation <u>671.14</u>			
Geologist <u> </u>		Ground Elevation <u>670.41</u>			
DRILLING METHOD		COMPLETION DATA			
Rotary Air <u> </u> Mud <u> </u>		Drilled Depth <u>229'</u>			
Cable Tool <u>D</u> <u> </u> H <u>10'-229'</u>		Completion Depth <u>227.7'</u>			
Drilling Fluid <u>H₂O</u>		Date Started <u>9/30/87</u> Completed <u>11/19/87</u>			
Other <u>BACKHOE 0'-10'</u>		Static Water Level/Date <u>211' static 11/17/87</u> SPA			
CASING DATA					
Type <u>TYPE 304 STAINLESS STEEL CASING</u>		Size <u>4" DIAMETER</u> to <u>207'</u>			
		to <u> </u>			
		to <u> </u>			
Approved By <u>S.P. Auland</u> Date <u>11/16/87</u>					
PERFORATIONS		SCREEN		ANNULAR SEAL	
Type <u> </u>		Type <u>4" dia. TYPE 304 S.S. continuous wrap</u>		Type <u> </u>	Interval <u> </u> Volume <u> </u>
Depth <u> </u>	Schedule <u> </u>	Length <u>20' (2 x 10' lengths)</u>		<u>COLORADO SILICA SAND</u>	<u>200'-209'</u> <u>18.28 ft³</u>
		Slot Size <u>20 slot</u>		<u>WILLIAMS PELLETS</u>	<u>197'-200'</u> <u>4.31 ft³</u>
		Depths <u>227.7' - 207.7'</u>		<u>DRY BENTONITE</u>	<u>100'-197'</u> <u>10.14 ft³</u>
				<u>DRY BENTONITE</u>	<u>2'-5'</u> <u>10.14 ft³</u>
				<u>BENTONITE SLURRY</u>	<u>5'-100'</u> <u>360.96 ft³</u>
App. By <u> </u>	Date <u> </u>	App. By <u>S.P. Auland</u>	Date <u>11/16/87</u>	App. By <u>S.P. Auland</u>	Date <u>11/30/87</u>
GEOPHYSICAL LOGGING			AQUIFER TESTING		
Sondes <u>NATURAL GAMMA</u>	Interval <u>0' - 224'</u>	Date <u>11/14/87</u>	Type of Test <u>Constant discharge test</u>		
<u>NEUTRON</u>	<u>0' - 224'</u>	<u>11/14/87</u>	Length of Test <u>6 hrs</u>		
<u>DENSITY</u>	<u>0' - 224'</u>	<u>11/14/87</u>	Volume Pumped <u>1800 gal</u>		
			Drawdown <u>5.02</u>		
Approved By <u>S.P. Auland</u>	Date <u>11/15/87</u>	Approved By <u>J.S. Auland</u>	Date <u>11/23/87</u>		
OTHER APPLICABLE ITEMS					
<u>SPA</u> Steam Cleaning	<u>SPA</u> Protective Steel Posts	<u>7/24/87</u> Downhole TV Inspection			
<u>SPA</u> Storage of Const. Material	<u>SPA</u> Safety Paint	<u> </u> Well Abandonment			
<u>SPA</u> Tool Lubricants	<u>SPA</u> Straightness Test	<u>SPA</u> Complete As-Built Diagram,			
<u>SPA</u> Concrete Pad	<u>SPA</u> Well Development	Driller's and Geologist's Logs			
Approved By <u>S.P. Auland</u>	Date <u>11/30/87</u>				

Reviewed By J.H. McShane Date 1-7-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 233-W7-6 Geologist Dave Waisman Page 1 of 2

Reviewed by V.L. McShan Date 1-7-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Concrete surface seal		5		GRAVEL
Dry bentonite		10		"
16" dia carbon steel casing		15		SANDY GRAVEL
12" dia carbon steel casing		20		" "
10" dia carbon steel casing		25		" "
8" dia carbon steel casing		30		SILTY SANDY GRAVEL
All carbon steel casing removed.		35		" " "
		40		" " "
		45		" " "
		50		SILTY GRAVELLY SAND
		55		" " "
		60		GRAVELLY SILTY SAND
		65		SILTY GRAVELLY SAND
		70		" " "
		75		" " "
		80		SANDY GRAVEL
		85		" "
Bentonite slurry		90		" "
(5'-130')		95		" "
		100		" "
		105		" "
		110		SILTY SANDY GRAVEL
		115		" " "
		120		" " "
		125		" " "
		130		Sandy gravel

AS-BUILT DIAGRAM

Well Number 299-W 7-5 Geologist ALBERT Page 2 of 2

Reviewed by V. J. McNamee Date 1-7-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SANDY GRAVEL
		140		
		145		
		150		
		155		SILTY SANDY GRAVEL
Bentonite slurry		160		
		165		
		170		
		175		
		180		
		185		
		190		SILTY GRAVELLY SANDS
Dry bentonite (190'-197')		195		
Volclay Pellets (197'-200')		200		
		205		SILTY SANDY GRAVEL
20-30 mesh Colorado Silica Sand (200'-207.7')		210		SILTY GRAVELLY SANDS
	215	GRAVELLY SANDS		
20 slot s.s. screen (207.7'-227.7')	220	SANDY GRAVEL		
	225	SILTY/CLAYEY SAND		
Depth Drilled = 229'	230			

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W7-6

This well, started on September 2, 1987, and completed on November 2, 1987, was drilled to a depth of 242.8 ft below ground surface. The depth to the water table was 218 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 231 to 241 ft, and the carbon steel drill casing was back-pulled 9 ft for the aquifer test. A 20-ft length of 4-in. 20-slot stainless steel screen was installed from 209 to 229 ft, and 209 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was back-pulled using the cable-tool rig. The annular seal consists of sand pack (205.5 to 240 ft), Volclay pellets (200.5 to 205.5 ft), bentonite slurry (3 to 200.5 ft), dry bentonite (2 to 3 ft), and concrete (0 to 2 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera indicated that the screen was dirty, and the water was cloudy. This well was bailed, and again, a video inspection was performed. This time, the water was too dirty to see anything.

Final well development was then performed using a 1.5-hp submersible pump discharging at a rate of approximately 1.4 gpm for 627 min. An estimated total volume of 853 gal was removed during the development. The final turbidity reading of the discharged water was 7.30 NTU, indicating that additional well development may be needed at this well.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project KEH-1914 Well Number 299-WT-6
 Location 200 WEST AREA - HANFORD Temporary Well Number
 Driller BLAINE BOLEY Coordinates N. 46,509 W. 76,219
 Drilling Co. ONWEGO DRILLING Casing Elevation 678.64
 Geologist WALSHMAN, GAND, TEEB, AIRHART Ground Elevation 676.25

DRILLING METHOD COMPLETION DATA
 Rotary Air Mud Drilled Depth 242.8'
 Cable Tool D H 10' - 242.8' Completion Depth 229'
 Drilling Fluid WATER Date Started 9/2/87 Completed 11/2/87
 Other BALCKHOF 0'-10' Static Water Level/Date 218' / 10/9/87

CASING DATA
 Type Size
TYPE 304 STAINLESS STEEL CASING 4" DIAMETER to 229'
 to
 to
 Approved By S.P. Airhart Date 10/23/87

PERFORATIONS		SCREEN		ANNULAR SEAL					
Type		1" dia. TYPE 304 S.S. Type CONTINUOUS WRAP	8" dia. TYPE 304 S.S. Type CONTINUOUS WRAP	Type	Interval	Volume			
Depth	Schedule	Length	10'	WILLIAM PELLERS	265.5' - 240'	12.06 ft ³			
		Slot Size	20 slot	WILLIAM PELLERS	240.5' - 235.5'	2.88 ft ³			
		Depths	229' to 241'	BENTONITE SLURRY	3' - 200.5'	347.70 ft ³			
				DRY BENTONITE	2' - 3'	1.43 ft ³			
App. By	Date	App. By	S.P. Airhart	Date	10/23/87	App. By	S.P. Airhart	Date	10/23/87

GEOPHYSICAL LOGGING			AQUIFER TESTING				
Sondes	Interval	Date	Type of Test				
NATURAL GAMMA	0' - 241'	10/9/87	Constant discharge test				
DENSITY	0' - 241'	10/9/87	Length of Test	8 hrs			
NEUTRON	0' - 241'	10/9/87	Volume Pumped	3,400 gals			
			Drawdown	21.42			
Approved By	S.P. Airhart	Date	10/9/87	Approved By	A.S. Hill	Date	10/9/87

OTHER APPLICABLE ITEMS

☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs

Approved By S.P. Airhart Date 11/12/87

Reviewed By J.L. Mathews Date 1-8-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

LYNNETTE GAILL

Well Number 299-W7-6 Geologist Dave Waisman Page 1 of 2Reviewed by W. McKenna Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
CONCRETE SURFACE SEAL		5		Sandy gravel
DRY BENTONITE		10		Gravelly sand
		15		Sandy gravel
(0'-51'3") 12" DIA. CARBON STEEL CASING		20		SILTY SANDY GRAVEL
(0'-152') 10" DIA. CARBON STEEL CASING		25		" " "
(0'-241'9") 8" DIA. CARBON STEEL CASING		30		" " "
ALL CARBON STEEL CASING REMOVED.		35		SLIGHTLY SILTY
		40		" GRAVELLY SAND
		45		GRAVELLY SANDS
		50		" "
4" DIA. STAINLESS STEEL CASING		55		SLIGHTLY GRAV. SAND
		60		" " "
		65		" " "
		70		" " "
		75		GRAVELLY SAND
BENTONITE SLURRY (3'-200.5')		80		GRAVELLY SILTY SAND
		85		" " "
		90		" " "
		95		
		100		SILTY GRAVELLY SAND
		105		SILTY SAND / GRAVEL
		110		Sandy Gravel
		115		" "
		120		" "
		125		" "

□ = casing

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299 W7-6 Geologist Dave Weissman Page 2 of 2

Reviewed by W. McShane Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		130		Sandy Gravel
		135		" "
		140		" "
BENTONITE SLURRY		145		" "
		150		" "
		155		" "
		160		" "
		165		" "
		170		" "
		175		Silty sandy Gravel
		180		" " "
		185		" " "
CENTRAMIZERS		190		Silty gravelly sand
VOLCLAY PELLETS (200.5' - 205.5')		195		Silty sandy gravel
NOTE: 4" S.S. CASING & SCREEN were re-set after complications w/ initial completion efforts. It was impossible to conserve original depth since 8" screen had filled w/ sand.		200		" " "
		205		Sandy gravel
		210		Silty sandy gravel
		215		Sandy Gravel
		220		" "
		225		" "
10-20 MESH COLORADO SAND (205.5' - 240')		230		Silty gravelly sand
4" dia 20-SLOT S.S. SCREEN (205.5' - 220')		235		Silty sandy gravel
8" TELESCOPING SCREEN (220' - 241')		240		" " "
DEPTH DRILLED = 242.8'		245		
		250

SUMMARY OF CONSTRUCTION, WELL 299-W8-1

This well, started on June 9, 1987, and completed on July 23, 1987, was drilled to a depth of 270.5 ft below ground surface. The depth to the water table was 238.82 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 257 to 267 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 20.3-ft length of 4-in. 20-slot stainless steel screen was installed from 236.2 to 256.5 ft, and 236.6 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (210.5 to 270.5 ft), Volclay pellets (206 to 210.5 ft), Volclay grout (3 to 206 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 7.4 gpm for 135 min. An estimated total volume of 1,002 gal was removed during the development. The final turbidity reading of the discharged water was 3.10 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project 200 West RCRA Well Drilling
Location Hanford Site 200 West Area
Driller Lenny Bultena
Drilling Co. Onwego Drilling
Geologist GV Cost ET Jensen CW Bishop
SP Airhart JS Wilbur

Well Number 299-WB-1
Temporary Well Number NONE
Coordinates N.46,551 W.79,200
Casing Elevation 701.33
Ground Elevation 699.45

DRILLING METHOD

Rotary Air — Mud —
Cable Tool D H 0'-270.5
Drilling Fluid H₂O
Other —

COMPLETION DATA

Drilled Depth 270.5
Completion Depth 256.5
Date Started 6/9/81 Completed 7/23/87
Static Water Level/Date —

CASING DATA

Type 304 Stainless Steel Casing Size 4" Diameter to 236.2'
to —
to —
to —
Approved By — Date —

PERFORATIONS

Type — Schedule —
Depth —
App. By — Date —

Telescoping SCREEN
Type 304 SS Continuous Wrap Continuous Wrap
Length 10.8 1/2' 20.3'
Slot Size 30 20
Depths 267' 8 1/2" 256.5'
257' 236.2'
App. By — Date —

ANNULAR SEAL

Type Sand Interval 210.5'-270.5' Volume 48.22 ft³
Volclay pellets 206'-210.5' 4.32 ft³
Volclay Grout 3'-206' 772.06 ft³
Concrete 0-3' 12 ft³
App. By JSW Date 12/31/87

GEOPHYSICAL LOGGING

Sondes Neutron Interval 0'-270.5' Date 7/1/87
Density 0'-270.5' 7/1/87
Natural Gamma 0'-270.5' 7/1/87
App. By JSW Date 7/1/87

AQUIFER TESTING

Type of Test Constant Discharge Test
Length of Test 6 hrs.
Volume Pumped 3,100 gals
Drawdown 24.14'
App. By JSW Date 7/1/87

OTHER APPLICABLE ITEMS

☒ Steam Cleaning
☒ Storage of Const. Material
☒ Tool Lubricants
☒ Concrete Pad
Approved By JSW

☒ Protective Steel Posts
☒ Safety Paint
☒ Straightness Test
☒ Well Development
Date 7/30/87

☒ Downhole TV Inspection
☒ Well Abandonment
☒ Complete As-Built Diagram
Driller's and Geologist's Logs

Reviewed By D.L. McPherson Date 1-8-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-W8-1 Geologist EJ Jensen Page 1 of 3Reviewed by D.L. McElhann Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>Concrete Surface Seal</u>		<u>5</u>	<u>0.0.0.</u>	<u>Backfill</u>
		<u>10</u>	<u>0.0.0.</u>	<u>Sandy Gravel</u>
<u>0'-62.5' 12" dia Carbon Steel Casing</u>		<u>15</u>	<u>0.0.0.</u>	<u>" "</u>
<u>0'-156.9' 10" dia Carbon Steel Casing</u>		<u>20</u>	<u>0.0.0.</u>	<u>" "</u>
<u>0'-270.1' 8" dia Carbon Steel Casing</u>		<u>25</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>30</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>35</u>	<u>0.0.0.</u>	<u>" "</u>
<u>0'-230.2' 4" dia Stainless Steel Casing</u>		<u>40</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>45</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>50</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>55</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>60</u>	<u>0.0.0.</u>	<u>" "</u>
		<u>65</u>	<u>0.0.0.</u>	<u>GRAVELY SAND</u>
<u>Volclay Grout</u>		<u>70</u>	<u>0.0.0.</u>	
<u>(0'-200')</u>		<u>75</u>	<u>0.0.0.</u>	
		<u>80</u>	<u>0.0.0.</u>	<u>GRAVELY SANDY SILT</u>
		<u>85</u>	<u>0.0.0.</u>	
		<u>90</u>	<u>0.0.0.</u>	<u>SILTY SANDY GRAVEL</u>
		<u>95</u>	<u>0.0.0.</u>	<u>SANDY GRAVEL</u>
		<u>100</u>	<u>0.0.0.</u>	
		<u>105</u>	<u>0.0.0.</u>	<u>SLIGHTLY SILTY GRAVELY SAND</u>
		<u>110</u>	<u>0.0.0.</u>	<u>SLIGHTLY GRAVELY SAND</u>
		<u>115</u>	<u>0.0.0.</u>	<u>SLIGHTLY GRAVELY SILTY SAND</u>
		<u>120</u>	<u>0.0.0.</u>	
		<u>125</u>	<u>0.0.0.</u>	
		<u>130</u>	<u>0.0.0.</u>	

D. Caliche

A-1800-186 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-WA-1Geologist W. H. H. H.Page 2 of 3Reviewed by D. K. McElroyDate 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135'		SILTY SAND
		140'		
		145'		SLIGHTLY GRAVELY SILTY SAND
		150'		
		155'		SILTY GRAVELY SAND
		160'		
		165'		SILTY SANDY GRAVEL
		170'		
		175'		
		180'		SANDY GRAVEL
		185'		
		190'		
		195'		SILTY SANDY GRAVEL
		200'		SILTY/CLAYEY GRAVEL
		205'		GRAVELY SILTY SAND
		210'		SILTY SANDY GRAVEL
		215'		
		220'		
		225'		
		230'		
		235'		
		240'		
		245'		
		250'		
		255'		
		260'		

Centralizer @ 296'

D/T of vol clay pellets @
206'D/T of 20-30 Colorado
Silica Sand @ 210.5'D/T 4" S.S. 20 slot screen
@ 236.2'D/T of 4" S.S. 20 slot screen
@ 256.5'D/T of telescoping screen
@ 257'

□ Caliche

A-1800-186 (3/87)

Reviewed by V.L. McElhan Date 1-8-88

[illegible]

A-1500-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W9-1

This well, started on September 3, 1987, and completed on October 22, 1987, was drilled to a depth of 295 ft below ground surface. The depth to the water table was 269.3 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 282 to 292 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 20-ft 4-in. length of 4-in. 20-slot stainless steel screen was installed from 266 to 286 ft, and 266 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (263.5 to 292 ft), Volclay pellets (259.5 to 263.5 ft), bentonite grout (70 to 295.5 ft), dry bentonite (3.5 to 70 ft), and concrete (0 to 3.5 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 1.5 gpm for 933 min. An estimated total volume of 1,459 gal was removed during the development. The final turbidity reading of the discharged water was 6.10 NTU, indicating that additional development may still be needed at this well.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project Don West RCRA Well drilling Well Number 299-W19-1
 Location Don West Area Temporary Well Number N/A
 Driller David Ludtke Coordinates Not available N. 44, 508 W. 79, 507
 Drilling Co. Onwego Drilling Co. Casing Elevation Not available 737.73
 Geologist Tyler Gilmore Ground Elevation Not available 735.30

DRILLING METHOD

Rotary Air N/A Mud N/A
 Cable Tool D 10'-55' H 55'-295'
 Drilling Fluid Water
 Other Backline 0-10'

COMPLETION DATA

Drilled Depth 295'
 Completion Depth 296'
 Date Started 9/3/87 Completed 10/22/87
 Static Water Level/Date 269' 4" 10/11, 10/12

CASING DATA

Type Telescoping Screen; 30 Slot Size 7 7/8 OD 292' to 282'
4" Stainless Steel 4" OD 286' to Surface
 Approved By JB Date 11/2/87

PERFORATIONS

Type N/A
 Depth Schedule
 App. By Date

SCREEN

Type Stainless Steel
 Length 20' 4"
 Slot Size 20 (.02")
 Depths 286' - 266'
 App. By JB Date 10/13/87

ANNULAR SEAL

Type Interval Volume
10-20 Sand 292'-263.5' 2400 lbs
Wetpack Pellets 263.5'-291.5' 2000 lbs
Bestonite Grout 291.5'-70' 2600 lbs
Dry Packout 70'-35' 4300 lbs
 App. By JB Date 10/22/87

GEOPHYSICAL LOGGING

Sondes Interval Date
Abt Gamma 292' - Surface 10/12/87
Density 292' - Surface 10/12/87
Neutron 292' - Surface 10/12/87
 Approved By JB Date 10/12/87

AQUIFER TESTING

Type of Test Slug Test
 Length of Test 2hr
 Volume Pumped N/A
 Drawdown N/A
Slug test was performed because well did not produce enough water at 1.6 gal, for a constant drawdown aquifer test
 Approved By JB Date 10/23/87

OTHER APPLICABLE ITEMS

☒ Steam Cleaning ☒ Protective Steel Posts ☒ Downhole TV Inspection
☒ Storage of Const. Material ☒ Safety Paint ☒ Well Abandonment
☒ Tool Lubricants ☒ Straightness Test ☒ Complete As-Built Diagram,
☒ Concrete Pad ☒ Well Development Driller's and Geologist's Logs
 Approved By T. Gilmore Date 11/2/87

Reviewed By V.L. McAllen Date 1-8-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299 W9 1 Geologist T. Gilmore Page 1 of 3Reviewed by V.L. McEthan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Cement Surface - 3.5'		5		SAND
16" Temporary Casing 7.5'		10		
12" Temporary Casing 51'		15		SILTY SAND
10" Temporary Casing 151.3'		20		GRAVELLY SAND
8" Temporary Casing 297.8'		25
	27		SAND
4" Stainless Steel Casing 286'		35
	40		SILTY SAND
	45		SAND
	50
	55		GRAVELLY SAND
	60		SILTY GRAVELLY SAND
Dry Particulate 3.5' - 70'		65		
Particulate Grout 70' - 259.5'		70
	75
	80		SILTY SAND
	85		SILTY GRAVELLY SAND
	90		SAND
	95
	100		GRAVELLY SAND
	105		SAND
	110
	115
	120
	125		GRAVELLY SAND

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299 W9 1 Geologist T. Gilmore Page 2 of 3

Reviewed by D.K. McElham Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SANDY GRAVEL
		140		
		145		
		150		
		155		SILTY SANDY GRAVEL
		160		SLIGHTLY GRAVELY SILTY SAND
		165		
		170		
		175		
		180		SAND
		185		
		190		SLIGHTLY SILTY GRAVELY SAND
		195		
		200		
		205		
		210		SANDY GRAVEL
		215		
		220		
		225		GRAVELY SAND
		230		GRAVEL
		235		SANDY GRAVEL calc. HORIZ. base 235'
		240		Round Tr. ~232' Clay/Silt ~235'
Controlizers 245'		245		incr in Consolidation/Strength
		250		SILTY/CLAYEY SANDY GRAVEL
		255		
Volcanic pe 255' - 259.5'				SANDY GRAVEL

Reviewed by D.L. McElhannon Date 1-8-88

[illegible]

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W10-13

This well, started on August 11, 1987, and completed on September 25, 1987, was drilled to a depth of 250 ft below ground surface. The depth to the water table was 227.9 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. A 6-in.-diameter, 10-ft length of 10-slot screen and a 6-in.-diameter, 10-ft length of 40-slot stainless steel screen were installed from 237.5 to 247.5 ft and from 227.5 to 237.5 ft, respectively. The carbon steel drill casing was backpulled 18 ft for the aquifer test. A 20-ft 4-in. length of 4-in. 30-slot stainless steel screen was installed from 227 to 247 ft, and 227 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (220.5 to 247.5 ft), Volclay pellets (217.5 to 220.5 ft), bentonite grout (6 to 217.5 ft), and concrete (0 to 6 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 13.2 gpm for 34 min. An estimated total volume of 451 gal was removed during the development. The final turbidity reading of the discharged water was 2.20 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 West RCRA Well Drilling</u>		Well Number <u>299 W10 13</u>	
Location <u>200 West</u>		Temporary Well Number <u>NA</u>	
Driller <u>Russ Vance</u>		Coordinates <u>unavailable N 43,137 W 78,297</u>	
Drilling Co. <u>Chicago</u>		Casing Elevation <u>unavailable 699.04</u>	
Geologist <u>Tyler Gilmore</u>		Ground Elevation <u>unavailable 696.58</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u>NA</u> Mud <u>NA</u>		Drilled Depth <u>250'</u>	
Cable Tool D <u>10'-80'</u> H <u>80'-250'</u>		Completion Depth <u>247.5'</u>	
Drilling Fluid <u>Water</u>		Date Started <u>9/11/87</u> Completed <u>9/25/87</u>	
Other <u>Backhoe 0-10'</u>		Static Water Level/Date <u>227.9' 9/10/87</u>	
CASING DATA			
Type		Size	
<u>6" 103 slot 304 Stainless Steel Telescoping Screen</u>		<u>247.5' to 237.5'</u>	
<u>6" 403 slot 304 Stainless Steel Telescoping Screen</u>		<u>237.5' to 227.5'</u>	
<u>6" 304 Stainless Steel Blank</u>		<u>227.5' to 222.2'</u>	
<u>4" 304 Stainless Steel Casing</u>		<u>227' Surface</u>	
Approved By <u>JB</u>		Date <u>9/15/87</u>	
PERFORATIONS		SCREEN	
Type <u>NA</u>	Schedule	Type <u>4" 304 Stainless Steel</u>	Interval
Depth		Length <u>20' 4"</u>	Volume
		Slot Size <u>30.564</u>	<u>10-20 Sand 247.5'-220.5' 1100 lbs</u>
		Depths <u>247' - 227'</u>	<u>Unkey Pallets 220.5'-217.5' 15 gal</u>
			<u>Envirogel grout 217.5'-6' 2150 gal</u>
			<u>Cement 6'-Surface 1100 lbs</u>
App. By	Date	App. By <u>JB</u>	Date <u>9/15/87</u>
			App. By <u>JB</u> Date <u>9/26/87</u>
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes	Interval	Date	Type of Test <u>Constant Discharge / Recharge</u>
<u>Not Gamma</u>	<u>0 - 247'</u>	<u>9/15/87</u>	Length of Test <u>8 hr</u>
	<u>0 - 246'</u>	<u>9/15/87</u>	Volume Pumped <u>14,400 gal</u>
	<u>0 - 246'</u>	<u>9/15/87</u>	Drawdown <u>11.67'</u>
Approved By <u>JB</u>	Date <u>9/15/87</u>	Approved By <u>JB</u>	Date <u>9/14/87</u>
OTHER APPLICABLE ITEMS			
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection	
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment	
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,	
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs	
Approved By <u>Tyler Gilmore</u>	Date <u>11/3/87</u>		

Reviewed By W.E. McElhiney Date 1-8-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 899 W10 13 Geologist T. Gilmore Page 1 of 2Reviewed by V.Z. McElham Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Concrete Surface Seal		5		SAND Core Barrel 0
		10		0
		15		0
		20		GRAVELY SAND 0
4" Stainless Steel Casing		25		0
250'		30		0
		35		SAND 0
Temporary Casing Steel Casing		40		0
4 1/2" 7" or 12"		45		0
		50		0
Temporary Casing Steel Casing		55		0
14 1/2" 5" or 10"		60		0
		65		0
Temporary Casing Steel Casing		70		GRAVELY SAND 0
250' or 5"		75		0
		80		SANDY GRAVEL 0
Environ Gel Casing		85		Hard Soil 0
		90		SILTY GRAVELY SAND 2
		95		0
		100		0
		105		0
		110		0
		115		0
		120		SILTY SAND 2
		125		(Caliche) 0
		130		SANDY SILT 0

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299 Win 13 Geologist TG Page 2 of 2

Reviewed by W. Mathan Date 1-8-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		
		140		SILTY SANDY GRAVEL
		145		GRAVELY SAND
		150		
		155		
		160		SANDY GRAVEL
		165		GRAVELY SAND
		170		
		175		
		180		
		185		
		190		SILTY GRAVELY SAND Lith. chert nodules
		195		inner in Si4 & Silica-rich grs
		200		SANDY GRAVEL
		205		
		210		SILTY GRAVELY SAND To Clay
		215		
15 gal Volclay pellets to 217'		220		
6" Stainless Blank 5'4"		225		
6" 40 slot screen 10'		230		
10-20 Silica Sand to 230'		235		
4" 30 slot stainless screen 20'		240		SILTY SAND
6" 10 slot screen 10'		245		SAND
Formation cave-in		250		TD 250'

SUMMARY OF CONSTRUCTION, WELL 299-W10-14

This well, started on July 29, 1987, and completed on November 18, 1987, was drilled to a depth of 462 ft below ground surface. The depth to the water table was 229.5 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 437 to 447 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 20.3-ft length of 4-in. 20-slot stainless steel screen was installed from 427 to 447 ft, and 427 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (416 to 462 ft), Volclay pellets (210 to 416 ft), bentonite slurry (6 to 210 ft), dry bentonite (3 to 6 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera indicated that the screen was dirty from 428 to 444 ft and that the water was too dirty to see beyond 244 ft. The well was then bailed and examined again. This time, the screen appeared to be dirty only from 244 to 246 ft.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10.3 gpm for 335 min. An estimated total volume of 3,447 gal was removed during the development. The final turbidity reading of the discharged water was 4.50 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project KEH-1914
Location 200 WEST AREA - HANFORD
Driller RUSTY BOLEY
Drilling Co. ONWEGO DRILLING CO.
Geologist WILBUR; GILMORE; TEEL; AIRHART

Well Number 299-W10-14
Temporary Well Number —
Coordinates N. 43,137 W. 78,297
Casing Elevation 699.04
Ground Elevation 696.58

DRILLING METHOD
Rotary Air — Mud —
Cable Tool D 10'-20' H 20'-462'
Drilling Fluid WATER
Other 0'-10' W/ BACKHOE

COMPLETION DATA
Drilled Depth 462'
Completion Depth 447'
Date Started 7/29/87 Completed 11/16/87
Static Water Level/Date 229.5' / 8/28/87

CASING DATA
Type TYPE 304 STAINLESS STEEL CASING Size 4" dia. + 2.5' to 427'
to —
to —
Approved By JB Date 10/30/87

PERFORATIONS
Type NA
Depth — Schedule —
App. By — Date —

SCREEN
4" dia. Continuous Wire 8" dia. Continuous Wire
Type Stainless Steel Stainless Steel
Length 20'4" 10'
Slot Size 20 30
Depths 427'- 437'-
447' 447'
App. By JB Date 6/20/87

ANNULAR SEAL
Type Interval Volume
COLORADO SAND 416'-462' 12.45 ft³
WILLIAM LEAT 210'-416' 103.82 ft³
BENTONITE SLURRY 6'-210' 949.20 ft³
DRY BENTONITE 3'-6' 6.78 ft³
CONCRETE 0'-3' 8.66 ft³
App. By SPALIN Date 11/18/87

GEOPHYSICAL LOGGING
Sondes Interval Date
NATURAL GAMMA 0' - 462' 10/16/87
NEUTRON 0' - 462' 10/16/87
DENSITY 0' - 462' 10/16/87
Approved By JB Date 10/16/87

AQUIFER TESTING
Type of Test CONSTANT DISCHARGE
Length of Test 8 HRS.
Volume Pumped 14,400 GALS
Drawdown 27.55'
Approved By ASUL Date 12/30/87

OTHER APPLICABLE ITEMS
JB Steam Cleaning ASUL Protective Steel Posts ASUL Downhole TV Inspection
JB Storage of Const. Material ASUL Safety Paint NA Well Abandonment
JB Tool Lubricants JB Straightness Test ASUL Complete As-Built Diagram,
— Concrete Pad JB Well Development Driller's and Geologist's Logs
Approved By ASUL Date 12/30/87

Reviewed By DR. McElhann Date 1-9-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-K10-14 Geologist W.S. Wilbur Page 1 of 4Reviewed by V.L. McPherson Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
CONCRETE SURFACE SEAL (0'-2')		5'		SAND
DRY BENTONITE (3'-6')		10'		"
20" Temporary Casing 50'		15'		"
16" Temporary Casing 147'6"		20'		GRAVELLY SAND
12" Temporary Casing 244'		25'		SAND
10" Temporary Casing 351'		30'		"
8" Temporary Casing 455'		35'		"
		40'		"
		45'		"
4" stainless steel casing		50'		"
		55'		"
BENTONITE SLURRY (5' - 210')		60'		"
		65'		"
		70'		"
		75'		"
		80'		SLIGHTLY GRAVELLY SAND
		85'		SILTY SANDY GRAVEL
		90'		" " "
		95'		" " "
		100'		SANDY GRAVEL
		105'		SILTY SANDY GRAVEL
		110'		" " "
		115'		GRAVELLY SAND
		120'		"
		125'		SLIGHTLY GRAVELLY SAND
		130'		"

A-1800-186 (3/87)

AS-BUILT DIAGRAM

Well Number 299 WD 14 Geologist T. Gilmore Page 2 of 4

Reviewed by V.K. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SILTY SAND (colitic)
		140		Change @ 137'
		145		SANDY GRAVEL
		150		GRAVELY SAND
		155		SILTY SAND (154-155')
		160		SANDY GRAVEL
		165		SILTY SAND (164-165')
		170		SANDY GRAVEL
		175		SILTY SANDY GRAVEL
		180		
		185		SILTY GRAVELY SAND Cherted zone
		190		
		195		Ring's Top ~195'
		200		
		205		GRAVELY SAND
		210		
		215		SANDY GRAVEL
		220		GRAVELY SAND
VOLCLAY GROUT (210' - 416')		225		Depth to bottom 223'
		230		SILTY GRAVELY SAND (clay)
		235		
		240		SILTY SAND
		245		SILTY SANDY GRAVEL
		250		
		255		GRAVELY SAND

AS-BUILT DIAGRAM

Well Number SM W10 14 Geologist T. Giblin Page 3 of 4

Reviewed by V.R. McPherson Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		365		SILTY GRAVELY SAND
		370		SILTY SANDY GRAVEL
		375		
		380		SAND
		385		
		390		
		395		
		400		GRAVELY SAND
		405		SILTY SANDY GRAVEL
		410		SANDY GRAVEL
		415		
		420		
		425		SAND
		430		SILTY GRAVELY SAND
		435		
		440		GRAVELY SAND
		445		
		450		SAND
		455		GRAVELY SAND
		460		SAND
		465		SAND
		470		SILTY SAND
		475		CLAYEY SAND clay @ 3H'
		480		
		485		SAND

AS-BUILT DIAGRAM

Well Number 299 W10 14 Geologist T Gilmore Page 4 of 4

Reviewed by D.L. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		395		
		400		
		405		
Centrifugers @ 407'		410		GRAVELLY SAND
		415		Clay layer @ 415'
Sand to 416'		420		SAND
		425		CLAYEY GRAVELLY SAND
		430		
		435		GRAVELLY SAND
4" Stainless Steel screen 436' to 442'		440		SAND
8" Telescoping screen 437' - 442'		445		SILTY GRAVELLY SAND
		450		CLAYEY GRAVELLY SAND @ 448'
		455		SANDY CLAY
		460		CLAY
Total Depth 462'		465		TO 462'

SUMMARY OF CONSTRUCTION, WELL 299-W15-15

This well, started on July 14, 1987, and completed on September 2, 1987, was drilled to a depth of 255 ft below ground surface. The depth to the water table was 226 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 245 to 255 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 30-ft length of 4-in. 20-slot stainless steel screen was installed from 223 to 253 ft, and 223 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (213.7 to 255 ft), Volclay pellets (208 to 213 ft), Volclay grout (4 to 208 ft), and concrete (0 to 4 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 10.4 gpm for 36 min. An estimated total volume of 373 gal was removed during the development. The final turbidity reading of the discharged water was 1.70 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Battelle <small>Pacific Northwest Laboratories</small>		Well Completion Report/Title III Inspection List	
Project <u>200 West RCRA Well Drilling KEH 1914</u>		Well Number <u>299-W15-15</u>	
Location <u>Hanford Site 200 West Area</u>		Temporary Well Number <u>none</u>	
Driller <u>Blane Boyley</u>		Coordinates <u>N. 40, 330 W. 78, 103</u>	
Drilling Co. <u>Onwego Drilling</u>		Casing Elevation <u>697.96</u>	
Geologist <u>SS Tech, JS Wilbur, T Gilmore, SP Airhart</u>		Ground Elevation <u>695.74</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u> </u> Mud <u> </u>		Drilled Depth <u>255'</u>	
Cable Tool <u>D 0'-30' H 30'-255'</u>		Completion Depth <u>253'</u>	
Drilling Fluid <u>Water</u>		Date Started <u>7/14/87</u> Completed <u>9/2/87</u>	
Other <u> </u>		Static Water Level/Date <u>226' 8/18/87</u>	
CASING DATA			
Type <u>304 Stainless Steel Casing</u>		Size <u>4" diameter</u>	
<u> </u>		<u> </u>	
<u> </u>		<u> </u>	
<u> </u>		<u> </u>	
Approved By <u> </u>		Date <u> </u>	
PERFORATIONS		SCREEN	
Type <u> </u>		8" dia. Type 304 S.S. <u> </u> 4" dia. Type 304 S.S. <u> </u>	
Depth <u> </u> Schedule <u> </u>		Type <u>Continuous Wrap</u> <u>Continuous Wrap</u>	
<u> </u>		Length <u>10'</u> <u>30'</u>	
<u> </u>		Slot Size <u>30'</u> <u>20'</u>	
<u> </u>		Depths <u>255'-245'</u> <u>253'-223'</u>	
App. By <u> </u> Date <u> </u>		App. By <u>JSW</u> Date <u>12/31/87</u>	
ANNULAR SEAL		SCREEN	
Type <u> </u> Interval <u> </u> Volume <u> </u>		Type <u> </u> Interval <u> </u> Volume <u> </u>	
<u>sand 213.7'-255' 15.56 ft³</u>		<u>8" dia. Type 304 S.S. 4" dia. Type 304 S.S.</u>	
<u>Vol/Clay Pellets 245'-200' 2.00 ft³</u>		<u>Continuous Wrap Continuous Wrap</u>	
<u>Vol/Clay Grout 200'-4' 528.4 ft³</u>		<u>Length 10' 30'</u>	
<u>Concrete 4'-0' 12 ft³</u>		<u>Slot Size 30' 20'</u>	
App. By <u>JSW</u> Date <u>12/31/87</u>		<u>Depths 255'-245' 253'-223'</u>	
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes <u>Neutron</u> Interval <u>0'-255'</u> Date <u>8/18/87</u>		Type of Test <u>Constant Discharge Test</u>	
<u>Density</u> <u>0'-255'</u> <u>8/18/87</u>		Length of Test <u>6 hrs.</u>	
<u>Natural Gamma</u> <u>0'-255'</u> <u>8/18/87</u>		Volume Pumped <u>7200 gals</u>	
<u> </u> <u> </u> <u> </u>		Drawdown <u>18.7'</u>	
<u> </u> <u> </u> <u> </u>		<u> </u> <u> </u> <u> </u>	
Approved By <u>JSW</u> Date <u>8/18/87</u>		Approved By <u>JSW</u> Date <u>8/21/87</u>	
OTHER APPLICABLE ITEMS			
<u>JSW</u> Steam Cleaning		<u>JSW</u> Protective Steel Posts	
<u>JSW</u> Storage of Const. Material		<u>JSW</u> Safety Paint	
<u>JSW</u> Tool Lubricants		<u>JSW</u> Straightness Test	
<u>JSW</u> Concrete Pad		<u>JSW</u> Well Development	
Approved By <u>JSW</u> Date <u>9/14/87</u>		<u>JSW</u> Downhole TV Inspection	
<u> </u>		<u>JSW</u> Well Abandonment	
<u> </u>		<u>JSW</u> Complete As-Built Diagram, Driller's and Geologist's Logs	

Reviewed By W.D. McElroy Date 1-8-88

A-1800-187 (2/87)

AS-BUILT DIAGRAM

Well Number 299-K115-15

Geologist _____

Page 1 of 2

Reviewed by W. K. McShane

Date 1-8-87

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		5		SILT/CLAY
		10		SAND
52' 1/2" of 12" casing		15		SANDY GRAVEL
		20		GRAVELLY SAND
		25		SAND
		30		
		35		
		40		GRAVELLY SAND
		45		SILTY SAND
		50		SAND
165' 1" of 10" casing		55		SLIGHTLY GRAVELLY SAND
		60		SILTY SANDY GRAVEL
		65		GRAVELLY SAND
		70		SILTY SANDY GRAVEL
255' of 8" casing		75		
		80		
		85		
		90		GRAVELLY SILTY SAND
		95		SL. GRAVELLY SL. SILTY SAND
		100		
		105		SILTY SAND
		110		SLIGHTLY SILTY SAND
		115		SILTY SAND
		120		SAND
		125		SILTY SAND
		130		

AS-BUILT DIAGRAM

Well Number 299-H15-15 Geologist J.S. Whitbur Page 2 of 2

Reviewed by V.R. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SLIGHTLY SILTY SAND
		140		
		145		SANDY SILT
		150		SILTY/CLAY
		155		GRAVELLY SANDY SILT
		160		
		165		
		170		
		175		SL. GRAVELLY SILTY SAND
		180		SANDY GRAVEL
		185		SILTY SANDY GRAVEL
		190		
		195		
		200		
		205		SANDY GRAVEL
		210		SILTY SANDY GRAVEL
		215		
		220		
		225		SANDY GRAVEL
		230		
		235		SILTY SANDY GRAVEL
		240		
		245		
		250		SANDY GRAVEL
		255		

165' 1" of 10" casing

255' of 8" casing

D/T of volclay pellets @ 200'

D/T of 10-12 SAND @ 213.7'

D/B of 10-12 sand @ 255'

D/T of 4" stainless screen 223'

D/B of 4" stainless screen 253'

D/T of telescoping screen 243'

D/B of telescoping screen @ 253' depth

note: telescoping screen settled to 255' 4" after the aquifer test.

SUMMARY OF CONSTRUCTION, WELL 299-W15-16

This well, started on July 29, 1987, and completed on September 2, 1987, was drilled to a depth of 243.5 ft below ground surface. The depth to the water table was 214.5 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 227.5 to 237.5 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 30-ft length of 4-in. 20-slot stainless steel screen was installed from 208 to 238 ft, and 208 of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (202 to 243.5 ft), Volclay pellets (196.5 to 202 ft), bentonite grout (2 to 196.2 ft), and concrete (0 to 2 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera indicated that the screen was dirty from 20 to 212 ft. The well was then bailed and examined again. This time, the screen was clean.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 14.7 gpm for 53 min. An estimated total volume of 782 gal was removed during the development. The final turbidity reading of the discharged water was 2.90 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project KEH-1914 Well Number 299-WIS-16
Location 200 WEST AREA Temporary Well Number —
Driller DARREL LUTKE Coordinates N. 40, 269 N. 77, 387
Drilling Co. ONWEGO Casing Elevation 684.89
Geologist AIRHART, TEEL, WILBUR, GILMORE Ground Elevation 682.62

DRILLING METHOD COMPLETION DATA
Rotary Air _____ Mud _____ Drilled Depth 243.5'
Cable Tool D 13'-110' H 110'-243.5' Completion Depth 238'
Drilling Fluid _____ Date Started 11/29/87 Completed 9/2/87
Other BACKHOE 0'-13' Static Water Level/Date 2/4/51

CASING DATA
Type TYPE 304 STAINLESS STEEL CASING Size 4" DIAMETER to 238'
to _____
to _____
Approved By SP. A. Hunt Date 8/25/87

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type		4" dia. Type 304 Type S-2 CONTINUOUS WELD	8" dia. Type 304/SS CONTINUOUS WELD	Type	Interval	Volume
Depth	Schedule	Length	10'	<u>COLORADO ALLUVA SAND</u>	<u>243.5'-202'</u>	<u>21.39 ft³</u>
		Slot Size	<u>20-50T</u>	<u>VALLEY PERMITS</u>	<u>202'-196.5'</u>	<u>2.88 ft³</u>
		Depths	<u>208' to 227.5'</u>	<u>GEOTEXTILE</u>	<u>196.5'-2'</u>	<u>1194.20 ft³</u>
			<u>238' 237.5'</u>	<u>PRECAST CONCRETE</u>	<u>0'-2'</u>	<u>18 ft³</u>
App. By	Date	App. By	<u>SP. A. Hunt</u> Date <u>8/25/87</u>	App. By	<u>SP. A. Hunt</u> Date <u>11/3/87</u>	

GEOPHYSICAL LOGGING			AQUIFER TESTING	
Sondes	Interval	Date	Type of Test	
<u>NATURAL GAMMA</u>	<u>0' - 243.5'</u>	<u>8/18/87</u>	<u>Constant Discharge Test</u>	
<u>DENSITY</u>	<u>0' - 243.5'</u>	<u>8/18/87</u>	Length of Test	<u>7 hrs</u>
<u>NEUTRON</u>	<u>0' - 243.5'</u>	<u>8/18/87</u>	Volume Pumped	<u>33,600 gals</u>
			Drawdown	<u>12.77</u>
Approved By	<u>SP. A. Hunt</u> Date <u>8/18/87</u>	Approved By	<u>AS. Will</u> Date <u>8/20/87</u>	

OTHER APPLICABLE ITEMS

☒ SPA Steam Cleaning	☒ SPA Protective Steel Posts	☒ Downhole TV Inspection
☒ SPA Storage of Const. Material	☒ SPA Safety Paint	☒ Well Abandonment
☒ SPA Tool Lubricants	☒ SPA Straightness Test	☒ Complete As-Built Diagram,
☒ SPA Concrete Pad	☒ SPA Well Development	Driller's and Geologist's Logs
Approved By <u>AS. Will</u>	Date <u>9/9/87</u>	

Reviewed By Dr. McMillan Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W15-16 Geologist AIRHART, TEEL, WILBUR / HILMORE Page 1 of 2

Reviewed by J. G. McElhannon Date 1-8-89

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Concrete Surface Seal		5		SLIGHTLY SILTY SAND
12" casing to 62'7"		10		SAND
		15		SAND GRAVEL
10" casing to 154'9"		20		SAND
		25		SANDY GRAVEL
		30		
		35		SAND
		40		
		45		
		50		
		55		
		60		
		65		
		70		
8" casing to 243.5'		75		SANDY GRAVEL
		80		GRAVELLY SAND
		85		SANDY GRAVEL
		90		
		95		
		100		
		105		
		110		GRAVELLY SAND
		115		SAND
		120		SANDY GRAVEL
		125		
		130

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-W15-16Geologist ALBERT, TEEL, WILBUR, GARDNER Page 2 of 2Reviewed by W. McLeanDate 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>10" casing to 154' 9"</u>		<u>135</u>		<u>SANDY CLAYEY GRAVEL</u>
		<u>140</u>		<u>SLIGHTLY GRAVELLEY SANDY SILT</u>
		<u>145</u>		<u>GRAVELLEY SILTY SAND w/ CALICHE</u>
		<u>150</u>		
		<u>155</u>		
<u>8" casing to 243.5'</u>		<u>160</u>		<u>GRAVELLEY SILTY SAND</u>
		<u>165</u>		<u>SILTY SAND</u>
<u>centralizers @ 168'</u>		<u>170</u>		<u>SLIGHTLY GRAVELLEY SILTY SAND</u>
		<u>175</u>		<u>SILTY SANDY GRAVEL</u>
<u>Volclay pellets from 202'</u>		<u>180</u>		<u>SLIGHTLY GRAVELLEY SAND</u>
<u>to 196.5' depths</u>		<u>185</u>		<u>SILTY SAND GRAVEL</u>
<u>D/T at 196.5'</u>		<u>190</u>		
<u>Sand pack at 10-20</u>		<u>195</u>		
<u>Colorado Silica Sand from</u>		<u>200</u>		<u>SANDY GRAVEL</u>
<u>238.5' to 202' - D/Tal sand</u>		<u>205</u>		<u>SILTY SANDY GRAVEL</u>
<u>20 slot screen @ 238.5' to</u>		<u>210</u>		
<u>208.5' depths; D/T of screen</u>		<u>215</u>		
		<u>220</u>		
<u>D/T telescoping screen @</u>		<u>225</u>		<u>SANDY GRAVEL</u>
<u>227.5'</u>		<u>230</u>		
<u>D/B inside the telescoping</u>		<u>235</u>		<u>SLIGHTLY SANDY GRAVEL</u>
<u>screen at 237.5'</u>		<u>240</u>		<u>SANDY GRAVEL</u>
<u>After pump test D/B of</u>				
<u>telescoping @ 238.5'</u>				
<u>below ground surface!</u>				

A-1800-185 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W15-17

This well, started on July 8, 1987, and completed on October 28, 1987, was drilled to a depth of 450 ft below ground surface. The depth to the water table was 211.6 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 422.5 to 432.5 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 10-ft length of 4-in. 20-slot stainless steel screen was installed from 422.5 to 432.5 ft, and 422.5 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (410.5 to 450 ft), Volclay grout (190 to 410.5 ft), bentonite slurry (3 to 190 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera indicated the presence of approximately 1 ft of mud in the bottom of the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 8.5 gpm for 301 min. An estimated total volume of 2,558 gal was removed during the development. The final turbidity reading of the discharged water was 4.60 NTU. During this development, it was discovered that a wood block had fallen into the well. Efforts will be made to remove this block.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project KEH-1914
Location 200 WEST AREA
Driller DAVE GARCIA
Drilling Co. ONNELLO
Geologist GUNCRE, JEFF, BISHOP, WILBUR, AIRHART

Well Number 253-WIS-17
Temporary Well Number ---
Coordinates N. 40, 227 W. 77, 387
Casing Elevation 684.64
Ground Elevation 682.85

DRILLING METHOD

Rotary Air _____ Mud _____
Cable Tool D _____ H 0' - 450'
Drilling Fluid _____
Other _____

COMPLETION DATA

Drilled Depth 450'
Completion Depth 432.5'
Date Started 7/18/87 Completed 10/28/87
Static Water Level/Date 211.58' below land surface
8/20/87

CASING DATA

Type _____ Size _____
TYPE 304 STAINLESS STEEL CASING 4" DIAMETER +2' to 432.5'

Approved By SP. A. Hunt Date 10/12/87

PERFORATIONS

Type _____
Depth _____ Schedule _____

App. By _____ Date _____

SCREEN

4" dia. Type 304 S.S. 6" dia. Type 304 S.S.
Type CONTINUOUS WIRE CONTINUOUS WIRE
Length 10' 10'
Slot Size 70-SLOT 30-SLOT
Depths 422.5' to 422.5' to
432.5' 432.5'
App. By SP. A. Hunt Date 10/12/87

ANNULAR SEAL

Type Interval Volume
CEMENT 410.5' - 450' 91.60 ft³
GRAVEL 410.5' - 410.5' 30.2 ft³
PERFORATE 3' - 180' 18
CONCRETE 0' - 3' 18
App. By SP. A. Hunt Date 11/3/87

GEOPHYSICAL LOGGING

Sondes Interval Date
NATURAL GAMMA 0' - 447' 9/17/87
NEUTRON 0' - 447' 9/17/87
DENSITY 0' - 447' 9/17/87

Approved By JS. KILL Date 9/17/87

AQUIFER TESTING

Type of Test CONSTANT DISCHARGE
Length of Test 5 HOURS
Volume Pumped 1800 GALLONS
Drawdown 12-23 FEET

Approved By JS. KILL Date 9/28/87

OTHER APPLICABLE ITEMS

SPA Steam Cleaning
SPA Storage of Const. Material
SPA Tool Lubricants
JS. KILL Concrete Pad
Approved By JS. KILL

JS. KILL Protective Steel Posts
JS. KILL Safety Paint
SPA Straightness Test
SPA Well Development
Date 11/3

202N Downhole TV Inspection
JS. KILL Well Abandonment
JS. KILL Complete As-Built Diagram,
Driller's and Geologist's Logs

Reviewed By W. E. McBlair Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W15-17 Geologist T. Gilmour Page 1 of 4

Reviewed by J. E. McElhaney Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
Premix Concrete Surface Seal		5		GRAVELLY SAND (Hard Tool.)
		10		SAND
		15		GRAVELLY SAND
		20		SAND
		25		
(0-47')		30		SANDY GRAVEL
20" CARBON STEEL CASING (0'-140'6")		35		SAND
16" CARBON STEEL CASING (0'-220'10")		40		
12" CARBON STEEL CASING (0'-323')		45		
10" CARBON STEEL CASING (0'-435'11")		50		
8" CARBON STEEL CASING		55		
4" STAINLESS STEEL CASING (42'-432.5')		60		
		65		
		70		
Bentonite Slurry		75		
		80		SANDY GRAVEL
		85		
		90		
		95		
		100		SILTY SANDY GRAVEL
Dry Bentonite		105		SANDY GRAVEL
		110		
		115		
		120		GRAVEL
		125		SANDY GRAVEL
		130		

AS-BUILT DIAGRAM

Well Number 999-W15-17 Geologist T. Gilmore Page 2 of 4

Reviewed by H. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
8-mesh Enviro gel Bentonite (dms)		135 140 145 150 155 160 165 170		SILT @ 136' SILTY SAND Caliche & Clay
200 mesh Big Horn Bentonite + 10-100 mesh Big Horn Bentonite mixed w/ water to form slurry (100 lbs Bent : 100 gals H ₂ O)		175 180 185 190 195 200 205 210 215 220 225 230 235 240 245 250 255 260 265 270 275 280 285 290 295 300 305 310 315 320 325 330 335 340 345 350 355 360 365 370 375 380 385 390 395 400 405 410 415 420 425 430 435 440 445 450 455 460 465 470 475 480 485 490 495 500 505 510 515 520 525 530 535 540 545 550 555 560 565 570 575 580 585 590 595 600 605 610 615 620 625 630 635 640 645 650 655 660 665 670 675 680 685 690 695 700 705 710 715 720 725 730 735 740 745 750 755 760 765 770 775 780 785 790 795 800 805 810 815 820 825 830 835 840 845 850 855 860 865 870 875 880 885 890 895 900 905 910 915 920 925 930 935 940 945 950 955 960 965 970 975 980 985 990 995 1000		SILTY CLAYEY SAND SILTY GRAVELLY SAND SANDY GRAVEL GRAVELLY SAND SILTY GRAVELLY SAND
Volclay Grout				

AS-BUILT DIAGRAM

Well Number 299 - W15 - 17 Geologist T. Gilmore Page 3 of 4

Reviewed by J.E. McElhaney Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		265		
		270		SILTY GRAVELY SAND cont.
		275		
		280		
		285		
		290		
		295		
		300		
		305		
		310		
		315		
Volley Grout		320		
		325		
		330		
		335		
		340		
		345		
		350		SILTY SAND
		355		SILTY GRAVELY SAND
		360		
		365		
		370		
		375		GRAVELY SILTY SAND
		380		
		385		GRAVELY CLAYEY SAND (CLAY LAYER) Del. 10/1/87
		390		
		395		SILTY GRAVELY SAND
		400		

AS-BUILT DIAGRAM

Well Number 299-W15-17 Geologist _____ Page 4 of 4

Reviewed by V.L. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		405		
		410		SILTY/CLAYEY SANDY GRAVEL
1 bag 20-30 mesh Colorado Silica Sand		415		SILTY GRAVELLY SAND
		420		
10' section of 4\"/>		425		
10' section of 2\"/>		430		
		435		
		440		SANDY CLAY
10-20 mesh Colorado Silica Sand		445		
SALT-TUBE SAMPLE TAKEN @ 440-450' INTERVAL		450		CLAY TO 450'
		455		
		460

SUMMARY OF CONSTRUCTION, WELL 299-W15-18

This well, started on May 27, 1987, and completed on August 4, 1987, was drilled to a depth of 242.5 ft below ground surface. The depth to the water table was 212.3 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 232.2 to 242.2 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 20-ft length of 4-in. 20-slot stainless steel screen was installed from 208 to 238 ft, and 208 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (205 to 242 ft), Volclay pellets (202.8 to 205 ft), Volclay grout (4 to 202.8 ft), and concrete (0 to 4 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 13.8 gpm for 190 min. An estimated total volume of 2,631 gal was removed during the development. The final turbidity reading of the discharged water was 1.30 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>KEH-1914 200 West RCRA Drilling</u>		Well Number <u>299-W15-19</u>	
Location <u>200 West</u>		Temporary Well Number <u>None</u>	
Driller <u>Bill McNamee / Homer Joy</u>		Coordinates <u>not available N. 39, 705 W. 77, 383</u>	
Drilling Co. <u>Omaha Drilling Co.</u>		Casing Elevation <u>not available 685.71</u>	
Geologist <u>RA Hagan / T. H. Moore</u>		Ground Elevation <u>not available 683.55</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u>N/A</u> Mud <u>N/A</u>		Drilled Depth <u>242' 6"</u>	
Cable Tool <u>D 0-126' H 126'-242.5'</u>		Completion Depth <u>238'</u>	
Drilling Fluid <u>Water</u>		Date Started <u>5/23/87</u> Completed <u>8/4/87</u>	
Other _____		Static Water Level/Date <u>212' 3" 7/1; 212' 6" 7/2</u>	
CASING DATA			
Type _____		Size _____	
<u>30 Slot 304 8" Stainless Steel Telescoping Casing</u>		<u>242' 2" to 232' 2"</u>	
<u>304 4" Stainless Steel Casing</u>		<u>238' to Surface</u>	
_____		_____	
_____		_____	
Approved By <u>JH</u>		Date <u>7/22/87</u>	
PERFORATIONS		SCREEN	
Type <u>N/A</u>	Schedule _____	Type <u>4" 304 Stainless Steel</u>	Interval _____
Depth _____	_____	Length <u>20' 4"</u>	Volume _____
_____	_____	Slot Size <u>20 slot</u>	_____
_____	_____	Depths <u>238'</u>	_____
_____	_____	<u>208'</u>	_____
App. By _____	Date _____	App. By <u>JH</u>	Date <u>7/22/87</u>
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes _____	Interval _____	Type of Test <u>Continuous Drawdown / Recovery</u>	Length of Test <u>7 1/2 Hrs</u>
<u>Not Gamma</u>	<u>0 - 242'</u>	Volume Pumped <u>37,200 gal</u>	Drawdown <u>7.05'</u>
<u>Alutron</u>	<u>0 - 242'</u>	_____	_____
<u>Density</u>	<u>0 - 242'</u>	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
Approved By <u>JH</u>	Date <u>7/8/87</u>	Approved By <u>JH</u>	Date <u>7/31/87</u>
OTHER APPLICABLE ITEMS			
<u>RAH</u> Steam Cleaning	<u>JH</u> Protective Steel Posts	<u>RAH</u> Downhole TV Inspection	
<u>JH</u> Storage of Const. Material	<u>JH</u> Safety Paint	<u>N/A</u> Well Abandonment	
<u>JH</u> Tool Lubricants	<u>JH</u> Straightness Test	<u>JH</u> Complete As-Built Diagram,	
<u>JH</u> Concrete Pad	<u>JH</u> Well Development	Driller's and Geologist's Logs	
Approved By <u>JH</u>	Date <u>11/2/87</u>		

Reviewed By W. L. McNamee Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W15-18 Geologist P.A. Hagen Page 1 of 2
Reviewed by W.L. McElham Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data		(ft/h) Drill rate
Description	Diagram		Diagram Litho.	Lithologic Description	
16" (O.D.) TEMPORARY SURFACE CASING (CARBON STEEL)		5	NO DATA	Slightly silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	50
12" (I.D.) TEMPORARY CASING (63' 1/2" of 12" diam carbon steel casing)		10		gravelly sand ⁽¹⁵⁾ ⁽⁸⁵⁾ ^(5% S.H.)	33
		15		Slightly silty slight. gravelly sand ⁽¹¹⁾ ⁽⁸⁹⁾ ⁽⁵⁾	5
		20		Slightly silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	10
		25		Sand (95) (5 silt)	13
		30		Sand (95) (5 silt & 5 pebbles)	5
		35		gravelly sand ⁽²⁰⁾ ⁽⁸⁰⁾	11
4" Stainless Steel Casing		40		silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	7.5
Bentonite Grout		45		silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	11.5
		50		silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	8.5
10" diam. carbon steel temporary casing (160' 9 1/2" long)		55		Sand (95) (5 silt)	17.5
		60		Sand (95) (5 silt)	9
		65		Slightly silty sand ⁽¹⁵⁾ ⁽⁸⁵⁾	17.5
		70		Sand (95) (5 silt)	19
		75		Slightly silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	16
		80		Sand (95) (5 silt)	15
8" diam carbon steel temporary casing		85		Silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	10
		90		Slightly silty sand ⁽¹⁰⁾ ⁽⁹⁰⁾	15
		95		Sand (95) (5 silt)	15
		100		Sand (95) (5 silt)	12
		105		gravelly sand ⁽¹⁵⁾ ⁽⁸⁵⁾ ^(5% S.H.)	20
		110		gravelly sand ⁽¹⁵⁾ ⁽⁸⁵⁾	6
		115		gravelly sand ⁽¹⁵⁾ ⁽⁸⁵⁾ ^(5% S.H.)	~2-3
		120		Slightly gravelly sand ⁽²⁾ ⁽⁹⁸⁾ ^(5% S.H.)	?
Change to hard tool @ 125'		125		Slightly sandy gravel ⁽¹⁵⁾ ⁽⁸⁵⁾	8.5
		130		gravelly silty sand ⁽²⁰⁾ ⁽⁸⁰⁾ ^(5%)	?

AS-BUILT DIAGRAM

Well Number 299-U15-18 Geologist P. A. Hagen Page 2 of 2

Reviewed by V. L. McShan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data		d.ill rate (ft/hr)
Description	Diagram		Diagram Litho.	Lithologic Description	
		135		slightly gravelly sandy silt (7) (41) (50)	15
		140		gravelly silty clayey sand (10) (20) (35) (60)	?
		145		silty sandy gravel (20) (45) (35)	5
Temporary 9" Casing		150		slightly silty gravelly sand (10) (25) (65)	?
		155		slightly gravelly silty sand (7) (18) (75)	10
		160		slightly gravelly silty sand (7) (18) (75)	1.7
		165		slightly silty gravelly sand (10) (20) (70)	?
4" Stainless Steel Casing		170		slightly silty gravelly sand (10) (20) (70)	6
		175		silty sandy gravel (20) (55)	1.3
		180		silty sandy gravel (10) (40) (50)	?
		185		silty sandy gravel (10) (30) (60)	?
		190		silty sandy gravel (10) (60) (30)	2
Volclay Grout		195		Silty Sandy Gravel	
Top Volclay Seal 302'		200			
Top of Sand 304'		205		Silty Sandy layer @ 302'	
		210		Sandy Gravel	
		215		Gravelly Silty Sand	
20 slot 4" Stainless Steel Screen		220			
		225		Gravelly Sand	
		230		Sand	
30 slot 8" Telescopic Screen		235			
2' of 20-30 Sand		240		Silty Gravelly Sand	
Total Depth 542' 6"		245

SUMMARY OF CONSTRUCTION, WELL 299-W18-21

This well, started on June 2, 1987, and completed on July 29, 1987, was drilled to a depth of 227 ft below ground surface. The depth to the water table was 197.5 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 215.5 to 225.5 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 30-ft length of 4-in. 20-slot stainless steel screen was installed at 195.5 to 225.5 ft, and 195.5 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (187.3 to 227.7 ft), Volclay pellets (185.8 to 187.3 ft), Volclay grout (3 to 185.8 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.1 gpm for 62 min. An estimated total volume of 691 gal was removed during the development. The final turbidity reading of the discharged water was 3.10 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Well Completion Report/Title III Inspection List

Project <u>200 West Area RCRA Well Drilling</u>		Well Number <u>299-W118-21</u>	
Location <u>Hanford Site 200 West Area</u>		Temporary Well Number <u>None</u>	
Driller <u>Darrel Ludtek</u>		Coordinates <u>N. 37,744 N. 78,080</u>	
Drilling Co. <u>Onwego Drilling</u>		Casing Elevation <u>668.62</u>	
Geologist <u>A Oster, SP Airhart, T Gilmore,</u> <u>SS Teel, JS Kilbur, GV Last</u>		Ground Elevation <u>666.50</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air _____ Mud _____		Drilled Depth <u>227'</u>	
Cable Tool <u>D 0'-40' H 40'-227'</u>		Completion Depth <u>226.3'</u>	
Drilling Fluid <u>Water</u>		Date Started <u>6/2/87</u> Completed <u>7/29/87</u>	
Other _____		Static Water Level/Date <u>197'6" 7/7/87</u>	
CASING DATA			
Type <u>Type 304 Stainless Steel Casing</u>		Size <u>4" diameter</u>	
		to <u>195.5'</u>	
		to _____	
		to _____	
Approved By <u>SPAL</u> Date <u>1/5/88</u>			
PERFORATIONS		ANNULAR SEAL	
Type _____	SCREEN	Type _____	Interval _____ Volume _____
Depth _____	Length <u>10'</u>	<u>Sand</u>	<u>197'4" - 227'8"</u> <u>11.26 ft³</u>
Schedule _____	Slot Size <u>30</u>	<u>Volclay pellets</u>	<u>195'8" - 197'4"</u> <u>1.44 ft³</u>
	Depths <u>215.5' -</u>	<u>Volclay grout</u>	<u>8' - 195'9"</u> <u>153.74 ft³</u>
	<u>225.5'</u>	<u>Concrete</u>	<u>0' - 3'</u> <u>4.08 ft³</u>
App. By _____	App. By <u>SPAL</u> Date <u>1/5/88</u>	App. By <u>SPAL</u>	Date <u>1/5/88</u>
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes _____	Interval _____	Type of Test <u>Constant Discharge Test</u>	
<u>Neutron</u>	<u>0' - 227'</u>	Length of Test <u>8 hrs</u>	
<u>Density</u>	<u>0' - 227'</u>	Volume Pumped <u>27,000 gals</u>	
<u>Natural Gamma</u>	<u>0' - 227'</u>	Drawdown <u>9.65 - 17.89</u>	
Approved By <u>JS Will</u>	Date <u>7/8/87</u>	Approved By <u>JS Will</u>	Date <u>7/14/87</u>
OTHER APPLICABLE ITEMS			
☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection	
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment	
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,	
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs	
Approved By <u>JS Will</u>	Date _____		

Reviewed By Rich Marshall Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W18-21 Geologist OSTER; AIRHART; GILMORE
TEEL; WILBUR; LAST Page 1 of 2
Reviewed by J.L. Mathan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		5		SAND
		10		SANDY SILT AND CLAY LENS @ 9'
		15		SAND
		20		(Wood sample taken @ 15.5')
16" Temporary Carbon Steel Casing		25		GRAVELLY SAND
12" Temporary Carbon Steel Casing		30		(Silty sand lens @ 22')
10" Temporary Carbon Steel Casing		35		SAND
8" Temporary Carbon Steel Casing		40		contact between C.S. and P.S.
4" Stainless Steel Casing		45		GRAVELLY SAND
		50		SLIGHTLY GRAVELLY SAND
		55		(contact @ 42')
		60		SANDY GRAVEL
		65		SILTY SANDY GRAVEL
		70		GRAVEL
		75		SILTY SANDY GRAVEL
		80		(contact @ 66')
		85		SILTY SAND
		90		
		95		
		100		
		105		CLAYEY SILTY SAND
		110		
		115		SILTY SAND
		120		SLIGHTLY SILTY SAND
		125		CLAYEY SILTY SAND
		130		

□ - caliche
○ - Gravel w/ weathering rind

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W18-22

This well, started on June 12, 1987, and completed on September 25, 1987, was drilled to a depth of 455 ft below ground surface. The depth to the water table was 198.9 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 437.5 to 447.5 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 31-ft length of 4-in. 20-slot stainless steel screen was installed from 416.5 to 447.5 ft, and 416.5 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (410 to 455 ft), Volclay pellets (404 to 410 ft), Volclay grout (189 to 404 ft), dry bentonite and slurry (3 to 189 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera indicated that the screen was dirty from 419 to 442 ft, and that mud was caked on the screen from 442 ft down. The well was then bailed and reexamined with the video camera. This time, dirt was observed on the screen from 438 to 442 ft and below this, the water was too dirty to see.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 9.3 gpm for 194 min. An estimated total volume of 1,804 gal was removed during the development. The final turbidity reading of the discharged water was 4.40 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>200 West RCRA Well Drilling</u>	Well Number <u>299-W18-22</u>
Location <u>Hanford Site 200 West</u>	Temporary Well Number <u>1010</u>
Driller <u>Kelly Olson</u>	Coordinates <u>N. 33, N. 37, 837 W. 78, 109</u>
Drilling Co. <u>Onwego Drilling</u>	Casing Elevation <u>668.49</u>
Geologist <u>K Oster, SP Aichert, SS Teel, K Bishop, T Gilmore, JS Kilbur</u>	Ground Elevation <u>666.49</u>

DRILLING METHOD

Rotary Air _____ Mud _____
 Cable Tool D _____ H 0'-455'
 Drilling Fluid Water
 Other _____

COMPLETION DATA

Drilled Depth 455
 Completion Depth 447
 Date Started 6/12/87 Completed 9/25/87
 Static Water Level/Date 198.99 8/27/87

CASING DATA

Type Type 304 Stainless Steel Casing Size 4" diameter +2.01' to 416.5'
 to _____
 to _____
 Approved By S. P. Aichert Date 10/1/87

PERFORATIONS		SCREEN		ANNULAR SEAL		
Type	Depth	Schedule	Length	Slot Size	Depth	Volume
Telescoping			10'	30	437.5'	15.21 ft ³
8" diameter type 304			31'	20	416.5'	2.05 ft ³
Type Continuous Wrap					447.5'	294.11 ft ³
						878.47 ft ³
						300.44 ft ³
App. By _____	Date _____	App. By <u>S. P. Aichert</u>	Date <u>10/1/87</u>	App. By <u>S. P. Aichert</u>	Date <u>10/1/87</u>	

GEOPHYSICAL LOGGING

Sondes Interval Date
Neutron 0' - 455' 8/12/87
Density 0' - 455' "
Natural Gamma 0' - 455' "

 Approved By JSK Date 8/12/87

AQUIFER TESTING

Type of Test Constant Discharge Test
 Length of Test 8 hrs.
 Volume Pumped 24,500 gal
 Drawdown 74.62

Approved By JSK Date 8/26/87

OTHER APPLICABLE ITEMS

☒ Steam Cleaning	☒ Protective Steel Posts	☒ Downhole TV Inspection
☒ Storage of Const. Material	☒ Safety Paint	☒ Well Abandonment
☒ Tool Lubricants	☒ Straightness Test	☒ Complete As-Built Diagram,
☒ Concrete Pad	☒ Well Development	Driller's and Geologist's Logs
Approved By <u>JSK</u>	Date <u>9/5/87</u>	

Reviewed By D. L. McPherson Date 1-8-88

A-1800-187 (3/87)

Pacific Northwest Laboratories

AS-BUILT DIAGRAM

Well Number 299-K18-22

Geologist

R. Oster, S. Arthur, T. Guilmore,
S. Teel, S. WilburPage 1 of 4Reviewed by T.E. McAllanDate 1-8-88

Construction Data

Depth
in
Feet

Geologic/Hydrologic Data

Description

Diagram

Diagram
Litho.

Lithologic Description

Concrete Surface Seal
(0'-3')

Dry bentonite (3'-15')

(0'-50'6") 20" dia. Carbon Steel Casing

(10'-150'1") 16" dia. Carbon Steel Casing

(10'-250'11") 12" dia. Carbon Steel Casing

(0'-342'6") 10" dia. Carbon Steel Casing

(0'-443'1 1/2") 8" dia. Carbon Steel Casing

NOTE: All Carbon Steel

Casing removed.

4" dia. Stainless Steel Casing

Bentonite Slurry

(15'-105')

5'

10'

15'

20'

25'

30'

35'

40'

45'

50'

55'

60'

65'

70'

75'

80'

85'

90'

95'

100'

105'

110'

115'

120'

125'

130'

Sand

Sand

Sand

Sandy Gravel

Slightly Silty Sand

Slightly Gravelly Sand

Sandy Gravel

Silty Sandy Gravel

Sandy Gravel

Gravel

Sandy Gravel

Slightly Silty Gravel

Silty Sand

Sandy Silt

Sandy Silt/clay

Silty/clayey Sand

Sandy Silt

AS-BUILT DIAGRAM

Well Number 244-L118-22 Geologist R. Oster, S. Airhart, T. Gilmore, S. Teel, S. Kilbur Page 2 of 4
Reviewed by D. E. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135'		Silt
		140'		Gravelly Sandy Silt/Clay
		145'		
		150'		Silty Sandy Gravel
		155'		Sandy Gravel
		160'		Silty Sandy Gravel
		165'		
		170'		
		175'		
		180'		Sandy Gravel
		185'		
		190'		
		195'		Gravelly Silty Sand
Voluntary Grout (185'-404')		200'		Silty Sandy Gravel
		205'		Silty/Clayey Sandy Gravel
		210'		Silty Sandy Gravel
		215'		
		220'		
		225'		
		230'		
		235'		
		240'		silty Gravelly Sand
		245'		
		250'		Gravelly Sand
		255'		Slightly Silty Gravelly Sand
		260'		slightly Gravelly Silty Sand

AS-BUILT DIAGRAM

Well Number 299-K113-22 Geologist K. Oster, S. Alchord, T. Calmore
S. Teele, J.S. Kilbur Page 3 of 4
Reviewed by V.L. McElane Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		265'		Slightly Gravelly Silty Sand
		270'		Slightly gravelly slightly silty sand
		275'		
		280'		Slightly Gravelly Sand
		285'		Gravelly Sand
		290'		Slightly Gravelly Silty Sand
		295'		Gravelly Silty/Clayey Sand
		300'		Silty Gravelly Sand
		305'		
		310'		Silty/Clayey Gravelly Sand
		315'		
		320'		
		325'		
		330'		
		335'		Gravelly Silty Sand
		340'		Gravelly Sand
		345'		Silty Gravelly Sand
		350'		
		355'		
		360'		Gravelly Silty Sand
		365'		
		370'		
		375'		
		380'		
		385'		
		390'		Silty Sand

K. Oster, S. Airhart, T. Gilmore,
S. Teel, J.S. Kilbur

Geologist

Page 4 of 4

Reviewed by

V. L. McGowan

Date 1-8-88

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-W18-23

This well, started on May 20, 1987, and completed on July 1, 1987, was drilled to a depth of 255 ft below ground surface. The depth to the water table was 224 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.-diameter, 10.3-ft length of 30-slot telescoping stainless steel screen was installed from 241 to 251 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 30.7-ft length of 4-in. 20-slot stainless steel screen was installed from 220.3 to 251 ft, and 220.3 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (215.8 to 255 ft), Volclay pellets (210 to 215.8 ft), Volclay grout (3 to 210 ft), and concrete (0 to 3 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.0 gpm for 90 min. An estimated total volume of 990 gal was removed during the development. The final turbidity reading of the discharged water was 4.20 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>KEH-1914</u>		Well Number <u>299-W18-23</u>	
Location <u>200 WEST AREA</u>		Temporary Well Number <u>NA</u>	
Driller <u>DAVE GARCIA</u>		Coordinates <u>N. 38,987 W. 78,120</u>	
Drilling Co. <u>ONWEGO</u>		Casing Elevation <u>696.81</u>	
Geologist <u>S.P. AIRHART</u>		Ground Elevation <u>694.75</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u>NA</u> Mud <u>NA</u>		Drilled Depth <u>255'</u>	
Cable Tool <u>D 0'-63' H 63'-255'</u>		Completion Depth <u>251'</u>	
Drilling Fluid <u>H₂O</u>		Date Started <u>5-20-87</u> Completed <u>7-1-87</u>	
Other _____		Static Water Level/Date <u>224' / 6-12-87</u>	
CASING DATA			
Type		Size	
<u>Schedule 40 Carbon Steel</u>		<u>12" diameter</u> to <u>62'4"</u>	
<u>Schedule 40 Carbon Steel</u>		<u>10" diameter</u> to <u>145'6"</u>	
<u>Schedule 40 Carbon Steel</u>		<u>8" diameter</u> to <u>255'</u>	
<u>Schedule 5 Stainless Steel</u>		Approved By <u>J.S.H.</u> Date <u>12/30/87</u>	
<u>4" diameter +21'-220'4"</u>			
PERFORATIONS		SCREEN	
Type <u>NA</u>		Type <u>6" Continuous Wrap Telecasing</u> <u>4" Continuous Wrap</u>	
Depth _____ Schedule _____		Length <u>10'3"</u> <u>30' & 1/2"</u>	
_____		Slot Size <u>40/30</u> <u>20</u>	
_____		Depths <u>241'-251'</u> <u>220'9"-251'</u>	
App. By _____ Date _____		App. By <u>J.S.H.</u> Date <u>12/30/87</u>	
		ANNULAR SEAL	
		Type Interval Volume	
		<u>20-30 silica sand 255'-255'</u> <u>15 ft³</u>	
		<u>Volelay Tablets 210'-215'9"</u> <u>4 ft³</u>	
		<u>Volelay Grout 210'-210'</u> <u>185 ft³</u>	
		<u>Premix Concrete 0'-3'</u> <u>123 ft³</u>	
		App. By <u>J.S.H.</u> Date <u>12/30/87</u>	
GEOPHYSICAL LOGGING		AQUIFER TESTING	
Sondes Interval Date		Type of Test <u>Continuous drawdown/recovery</u>	
<u>Net Gamma</u> _____ <u>6-15-87</u>		Length of Test <u>3 hr. drawdown / 1 hr. recovery</u>	
<u>gamma-gamma</u> _____ <u>6-15-87</u>		Volume Pumped <u>52,800 gal/s</u>	
<u>neutron</u> _____ <u>6-15-87</u>		Drawdown <u>2.62'</u>	
Approved By <u>J.S.H.</u> Date <u>6/15/87</u>		Approved By <u>J.S.H.</u> Date <u>12/30/87</u>	
OTHER APPLICABLE ITEMS			
☒ Steam Cleaning		☒ Protective Steel Posts	
☒ Storage of Const. Material		☐ Safety Paint	
☒ Tool Lubricants		☒ Straightness Test	
☒ Concrete Pad		☒ Well Development	
Approved By <u>J.S. Will</u>		Date _____	
		☒ Downhole TV Inspection	
		☐ Well Abandonment	
		☒ Complete As-Built Diagram, Driller's and Geologist's Logs	

Reviewed By W.H. McPherson Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W18-23 Geologist S.P. AIRHART Page 1 of 2

Reviewed by V. McArthur Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
2.1' STICKUP ABOVE PAD				
Concrete Surface Seal 0'-3'		5		SILTY GRAVELLY SAND
		10		
12" Temporary Carbon Steel Casing		15		GRAVELLY SAND
10" Temporary Carbon Steel Casing		20		SLIGHTLY SILTY SAND
8" Temporary Carbon Steel Casing		25		SILTY SAND
4" Stainless Steel Casing		30		
		35		SLIGHTLY GRAVELLY SILTY SAND
		40		SILTY SAND
		45		SLIGHTLY GRAVELLY SILTY SAND
		50		SILTY SAND
		55		SILTY SANDY GRAVEL
		60		SILTY GRAVELLY SAND
		65		SILTY SANDY GRAVEL
		70		
		75		
		80		
		85		
		90		
		95		
		100		
		105		
		110		GRAVELLY SILTY SAND
		115		
		120		SLIGHTLY GRAVELLY SILTY SAND
		125		
		130		SILTY SAND

AS-BUILT DIAGRAM

Well Number 299-W18-23 Geologist S. P. AIRHART Page 2 of 2

Reviewed by V. E. McElhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
		135		SILTY SAND
		140		
		145		
		150		SANDY SILT/CLAY
		155		
		160		SILT/CLAY W/ SAND
		165		SLIGHTLY GRAVELLY SILT/CLAY
		170		SLIGHTLY GRAVELLY SILT/CLAY
		175		SILTY SAND
		180		
		185		SILTY SANDY GRAVEL
		190		SANDY GRAVEL
		195		
		200		
		205		
		210		
		215		
		220		
		225		
		230		
		235		SILTY GRAVELLY SAND
		240		SILTY/CLAYEY SANDY GRAVEL
		245		SANDY GRAVEL
		250		SILTY SANDY GRAVEL
		255		SILTY GRAVELLY SAND
		260

□ CALICHE

A-1800-186 (3/87)

SUMMARY OF CONSTRUCTION, WELL 299-18-24

This well, started on May 20, 1987, and completed on August 11, 1987, was drilled to a depth of 239.9 ft below ground surface. The depth to the water table was 211.8 ft from the ground surface. The well was geophysically logged with density, neutron, and natural-gamma probes. An 8-in.- diameter, 10-ft length of 30-slot telescoping stainless steel screen was installed from 230 to 240 ft, and the carbon steel drill casing was backpulled 9 ft for the aquifer test. A 30-ft length of 4-in. 20-slot stainless steel screen was installed from 205.5 to 235.5 ft, and 205.5 ft of 4-in. schedule 5 stainless steel casing were installed. The carbon steel drill casing was backpulled using the cable-tool rig. The annular seal consists of sand pack (198 to 240 ft), Volclay pellets (191 to 198 ft), Volclay grout (5 to 191 ft), and concrete (0 to 5 ft).

A concrete pad was placed around the stainless steel casing above the ground surface, and four steel guardposts were installed at the well.

Inspection with the video camera showed no problems with the well.

Final well development was performed using a 1.5-hp submersible pump discharging at a rate of approximately 11.5 gpm for 34 min. An estimated total volume of 391 gal was removed during the development. The final turbidity reading of the discharged water was 2.00 NTU.

The Well Completion Report/Title III Inspection List, As-Built Diagrams, and borehole correlation charts for this well follow.

Pacific Northwest Laboratories

Well Completion Report/Title III Inspection List

Project <u>Low Level Rural Ground REORA Wells</u>		Well Number <u>299-W18-24</u>	
Location <u>200 West Area</u>		Temporary Well Number <u>NA</u>	
Driller <u>Russ Vance</u>		Coordinates <u>N38,998 W77,180</u>	
Drilling Co. <u>Onarego Drilling</u>		Casing Elevation <u>684.35</u>	
Geologist <u>J.S. Kilbur</u>		Ground Elevation <u>682.18</u>	
DRILLING METHOD		COMPLETION DATA	
Rotary Air <u>NA</u> Mud <u>NA</u>		Drilled Depth <u>239' 11"</u>	
Cable Tool <u>D 0'-40'; 75'-112' H 45'-70'; 125'-240'</u>		Completion Depth <u>235.5'</u>	
Drilling Fluid <u>H₂O</u>		Date Started <u>5/20/87</u> Completed <u>8/11/87</u>	
Other _____		Static Water Level/Date <u>211.8' 7/9/87</u>	
CASING DATA			
Type		Size	
<u>Schedule 40 Carbon Steel</u>		<u>16"</u> to <u>0-10.5'</u>	
<u>Schedule 40 Carbon Steel</u>		<u>12"</u> to <u>0-70.2'</u>	
<u>Schedule 40 Carbon Steel</u>		<u>10"</u> to <u>0-153.2'</u>	
<u>Schedule 40 Carbon Steel</u>		<u>8"</u> to <u>0-240'</u>	
Approved By _____		Date _____	
PERFORATIONS		SCREEN	
Type <u>NA</u>		4" diameter continuous loop 8" dia. continuous loop	
Depth _____	Schedule _____	Type <u>Stainless Steel</u>	Type <u>Stainless Steel</u>
_____	_____	Length <u>30'</u>	Length <u>10'</u>
_____	_____	Slot Size <u>20</u>	Slot Size <u>30</u>
_____	_____	Depths <u>205.5'</u>	Depths <u>240' 230'</u>
_____	_____	<u>235.5'</u>	<u>240'</u>
App. By _____	Date _____	App. By <u>J.S.K.</u>	Date <u>8/11/87</u>
GEOPHYSICAL LOGGING		ANNULAR SEAL	
Sondes	Interval	Date	Type Interval Volume
<u>Neutron</u>	<u>0' - 240'</u>	<u>7/9/87</u>	<u>Sand</u> <u>198' - 240'</u> <u>13.5 ft³</u>
<u>Gamma-Gamma</u>	<u>0' - 240'</u>	<u>7/9/87</u>	<u>Water/gel</u> <u>198' - 191'</u> <u>4.5 ft³</u>
<u>Natural Gamma</u>	<u>0' - 240'</u>	<u>7/9/87</u>	<u>Water/gel</u> <u>5' - 191'</u> <u>288.75 ft³</u>
_____	_____	_____	<u>Cement seal</u> <u>0 - 5'</u> <u>15.0 ft³</u>
_____	_____	_____	App. By <u>J.S.K.</u> Date <u>8/11/87</u>
Approved By <u>J.S.K.</u>	Date <u>7/9/87</u>	AQUIFER TESTING	
		Type of Test <u>Constant Discharge</u>	
		Length of Test <u>7.5 hr</u>	
		Volume Pumped <u>45,000 gals.</u> <u>48,300 gals.</u>	
		Drawdown <u>1.68 ft</u>	
		* test discharge volume	
		☐ total volume discharge test + development	
Approved By <u>J.S.K.</u> Date <u>7/9/87</u>		Approved By <u>J.S.K.</u> Date <u>7/17/87</u>	
OTHER APPLICABLE ITEMS			
☒ Steam Cleaning		☒ Protective Steel Posts	
☒ Storage of Const. Material		☒ Safety Paint	
☒ Tool Lubricants		☒ Straightness Test	
☒ Concrete Pad		☒ Well Development	
Approved By <u>J.S.K.</u>		Date <u>8/15/87</u>	
		☒ Downhole TV Inspection	
		☒ Well Abandonment	
		☒ Complete As-Built Diagram, Driller's and Geologist's Logs	

Reviewed By D.L. McShane Date 1-8-88

A-1800-187 (3/87)

AS-BUILT DIAGRAM

Well Number 299-W18-24 Geologist J.S. Wilbur Page 1 of 2

Reviewed by V.H. McEhan Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
<u>starter casing 10.5" Section</u>		<u>5</u>		<u>SLIGHTLY SILTY SAND</u>
<u>of 16" Carbon Steel pipe</u>		<u>10</u>		<u>SLIGHTLY SILTY SAND</u>
		<u>15</u>		<u>SLIGHTLY SILTY SAND</u>
		<u>17</u>		<u>SLIGHTLY GRAVELY SAND</u>
		<u>20</u>		<u>SAND</u>
		<u>25</u>		<u>SAND</u>
		<u>30</u>		<u>SAND</u>
		<u>35</u>		<u>SAND</u>
		<u>38</u>		<u>GRAVELY SAND</u>
		<u>40</u>		<u>GRAVELY SAND</u>
		<u>45</u>		<u>SLIGHTLY GRAVELY SAND</u>
		<u>50</u>		<u>SLIGHTLY SILTY SLIGHTLY GRAVELY SAND</u>
		<u>55</u>		<u>SLIGHTLY SILTY GRAVELY SAND</u>
		<u>60</u>		<u>SLIGHTLY SILTY GRAVELY SAND</u>
		<u>66</u>		<u>SAND</u>
<u>70.2" of 12" carbon steel</u>		<u>70'</u>		<u>SAND</u>
<u>casing</u>		<u>75'</u>		<u>SAND</u>
		<u>80'</u>		<u>SLIGHT SILTY GRAVELY SAND</u>
		<u>85'</u>		<u>SLIGHT SILTY SAND</u>
		<u>90'</u>		<u>SILTY SAND</u>
		<u>95'</u>		<u>SILTY SAND</u>
		<u>100'</u>		<u>SILTY SAND</u>
		<u>110'</u>		<u>SILTY SAND</u>
		<u>112'</u>		<u>SANDY GRAVEL</u>
		<u>115'</u>		<u>SANDY GRAVEL</u>
		<u>120'</u>		<u>GRAVEL</u>

AS-BUILT DIAGRAM

Well Number 299-A/18-24 Geologist J.S. Wilbur Page 2 of 2

Reviewed by J.L. McPherson Date 1-8-88

Construction Data		Depth in Feet	Geologic/Hydrologic Data	
Description	Diagram		Diagram Litho.	Lithologic Description
	125'		SANDY GRAVEL
		130'		SANDY GRAVEL
		135'		SILTY SAND
		140'		SILTY SAND
		145'		SILTY SAND
		150'		SANDY GRAVEL
T/D of 10" - 153' 10"		155'		SANDY GRAVEL
		160'		SAND
		165'		SAND
		170'		SANDY GRAVEL
		175'		SLIGHTLY SILTY SANDY GRAVEL
		180'		SLIGHTLY SILTY SANDY GRAVEL
		185'		SLIGHTLY SILTY SANDY GRAVEL
		190'		SANDY GRAVEL
Top of vol clay pellets 191.6'		195'		SILTY SANDY GRAVEL
Top of sand @ 198.2'		200'		SILTY SANDY GRAVEL
Top of 4" SS screen 205.5'		205'		SANDY GRAVEL
H2O Level @ 211.8' from ground surface		210'		GRAVELLY SILTY SAND
		215'		SLIGHTLY SANDY GRAVEL
		220'		SANDY GRAVEL
D/B of 4" SS casing @ 235.5'		225'		SANDY GRAVEL
6" telescoping screen 230'-235'		230'		SANDY GRAVEL
		235'		SANDY GRAVEL
DB 240' of 8' Carbon Steel casing		240'		SANDY GRAVEL

APPENDIX D

ANALYTICAL RESULTS FOR THE PREDEVELOPMENT AND AQUIFER TESTS OF GROUND-WATER SAMPLES

APPENDIX D

ANALYTICAL RESULTS FOR THE PREDEVELOPMENT AND AQUIFER TESTS OF GROUND-WATER SAMPLES

This appendix presents analytical results for predevelopment and aquifer tests of ground-water samples collected during the construction of 16 monitoring wells in the 200-East Area and 19 in the 200-West Area. These samples were collected prior to final construction and development of these monitoring wells; thus the results cannot be considered representative of the actual ground-water quality.

These results are presented in two tables: Table D.1 presents the analytical data for the 200-East Area wells and Table D.2 presents the analytical data for the 200-West Area wells.

TABLE D.1. Constituents Measured in Water Samples Before and During
Aquifer Testing, 200-East Area Low-Level Burial Grounds

		299-E27-8	299-E27-9			
		8/14/87 (B)	8/89/87 (B)	1815 hr	8/15/87 (P)	2848 hr
1,1,1-T	ppb	<10	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<	<
ALUMINUM	ppb					
AMMONIUM	ppb					
ANTIMONY	ppb					
ARSENIC	ppb					
BARIUM	ppb					
BETA	pCi/l	17.8+/-4.00	8.45+/-1.83	12.1+/-4.34	8.17+/-3.76	8.75+/-3.98
BIS2EPH	ppb	<10	<10	<10	<10	<10
CADMIUM	ppb					
CALCIUM	ppb					
CHLORINE	ppb	<10	<10	<10	<10	<10
CHLORIDE	ppb	<10	<10	<10	<10	<10
CHROMIUM	ppb					
Co-60	pCi/l	6.39+/-6.22	-5.1+/-3.8 scan	8.53+/-6.45	5.82+/-5.82	2.26+/-3.28
CONDUCT	umho					
COPPER	ppb					
Cs-137	pCi/l	7.32+/-4.41	-5.1+/-3.8 scan	9.83+/-5.45	8.12+/-18.8	-1.72+/-8.82
CYANIDE	ppb	<10	<10	<10	<10	<10
FLUORIDE	ppb					
H-3	pCi/l	4,598+/-208	8,894+/-267	8,216+/-396	7,838+/-304	8,216+/-396
IRON	ppb					
LEAD	ppb					
LDALPHA	pCi/l	3.98+/-1.84	1.47+/-8.58	1.87+/-1.43	1.34+/-1.89	1.81+/-1.37
MAGNES	ppb					
MANGANESE	ppb					
MERCURY	ppb					
METHUENE	ppb	<10	<10	<10	<10	<10
METHYLCH	ppb	<10	<10	<10	<10	<10
NICKEL	ppb					
NITRATE	ppb					
NITROGEN	ppb	<10	<10	<10	<10	<10
PCB	ppb					
pH-LAB						
PHOSPHATE	ppb					
Pu-239/240	pCi/l	.0055+/-0.0137	-.0136+/-0.0100	-.0014+/-0.0008	.0007+/-0.0041	.0005+/-0.0030
Pu-238	pCi/l	.0472+/-0.0362	(total)	-.0038+/-0.0045	-.0007+/-0.0001	-.0007+/-0.0058
POTASSIUM	ppb					
RADIUM	pCi/l					
Ru-106	pCi/l	-33.8+/-80.2	-5.1+/-3.8 scan	25.6+/-60.8	-109+/-134	-67.5+/-88.8
SELENIUM	ppb					
SILVER	ppb					
SODIUM	ppb					
Sr-total	pCi/l	1.47+/-0.27	1.58+/-0.87			
Sr-90	pCi/l	1.47+/-0.535		-.208+/-0.219	-.0025+/-0.295	-.0020+/-0.264
SULFATE	ppb					
TETRANE	ppb	<10	<10	<10	<10	<10
THALLIUM	ppb					
TBC	ppb					
TOLUENE	ppb	<10	<10	<10	<10	<10
TOX	ppb					
TRICENE	ppb	<10	<10	<10	<10	<10
UNKNOWN	ppb					
URANIUM	pCi/l					
URANIUM-234	pCi/l					
URANIUM-235	pCi/l					
URANIUM-238	pCi/l					
XYLENE(O,P)	ppb	<10	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10	<10
YANADUM	ppb					
ZINC	ppb					

TABLE D.1. (contd)

		290-E27-10	200-E28-26	200-E28-27		
		7/31/87 (B)	10/14/87 (B)	9/26/87 (B)	9/29/87 (P)	
					1115 hr	1400 hr
						1530 hr
1,1,1-T	ppb	<10	<5	-----	<10	<10
ACETONE	ppb	<	<	-----	<	<
ALUMINUM	ppb					
AMMONIUM	ppb					
ANTIMONY	ppb					
ARSENIC	ppb					
BETA	pCi/l	14.7+/-2.43	32.9+/-8.73	13.0+/-4.37	15.0+/-4.50	16.1+/-4.66
BIS2EPH	ppb	<10	<10	<10	<10	<10
CADMIUM	ppb					
CALCIUM	ppb					
CHLBENZ	ppb	<10	<10	-----	<10	<10
CHLFORM	ppb	<10	<5	-----	<10	<10
CHLORID	ppb					
CHROMIUM	ppb					
Co-60	pCi/l	-3.0+/-3.2 scan	2.02+/-2.06	-1.02+/-0.22	5.07+/-0.68	6.41+/-5.23
CONDUCT	uaho					
COPPER	ppb					
Cs-137	pCi/l	-3.0+/-3.2 scan	-1.28+/-5.71	-11.3+/-10.8	1.33+/-0.52	-9.66+/-10.5
CYANIDE	ppb	<10	<10	<10	<10	<10
FLUORID	ppb					
H-3	pCi/l	14,200+/-465	62,400+/-940	10,000+/-370	11,300+/-442	11,700+/-452
IRON	ppb					
LEAD	ppb					
LOALPHA	pCi/l	6.95+/-1.26	45.9+/-9.83	4.22+/-1.02	1.70+/-1.18	2.85+/-1.44
MAGNES	ppb					
MANGNESE	ppb					
MERCURY	ppb					
METHONE	ppb	<10	<10	-----	<10	<10
METHYCH	ppb	<10	<10	-----	<10	<10
NICKEL	ppb					
NITRATE	ppb					
NMIDIME	ppb	<10	<10	<10	<10	<10
PCB	ppb					
pH-LAB						
PHOSPHA	ppb					
Pu-239/240	pCi/l	-.0039+/-0.0053	.0110+/-0.0315	-.0014+/-0.0031	.0025+/-0.0055	.0002+/-0.0066
Pu-238	pCi/l	(total)	.0055+/-0.0327	-.0021+/-0.0020	.0255+/-0.0162	.0484+/-0.0260
POTASUM	ppb					
RADIUM	pCi/l					
Ru-100	pCi/l	-3.0+/-3.2 scan	-54.9+/-49.6	-27.9+/-80.3	-33.5+/-61.1	19.5+/-39.4
SELENIUM	ppb					
SILVER	ppb					
SODIUM	ppb					
Sr-total	pCi/l	2.85+/-1.29		2.06+/-0.60		
Sr-90	pCi/l		.692+/-0.442	.604+/-0.600	-.070+/-0.314	.027+/-0.400
SULFATE	ppb					
TETRAHE	ppb	<10	<5	-----	<10	<10
THALLUM	ppb					
TOC	ppb					
TOLUENE	ppb	<10	<5	-----	<10	<10
TOX	ppb					
TRICENE	ppb	<10	<5	-----	<10	<10
UNKNOWN	ppb					
URANIUM	pCi/l					
URANIUM-234	pCi/l		21.8+/-7.00			
URANIUM-235	pCi/l		.992+/-0.151			
URANIUM-238	pCi/l		20.4+/-6.03			
XYLENE(O,P)	ppb	<10	<5	-----	<10	<10
XYLENE(M)	ppb	<10	<5	-----	<10	<10
YANADIUM	ppb					
ZINC	ppb					

TABLE D.1. (contd)

		299-E22-2			
		8/31/87 (B)	9/08/87 (P)	9/08/87 (P)	9/08/87 (P)
			1130 hr	1330 hr	1530 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	17.4+/-4.69	33.7+/-5.88	26.7+/-6.51	27.2+/-5.43
BISSEPH	ppb	<10	<10	<10	<10
CADMIUM	ppb				
CALCIUM	ppb				
CHLBENZ	ppb	<10	<10	<10	<10
CHLFORM	ppb	<10	<10	<10	<10
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	4.83+/-4.83	-6.04+/-7.97	8.97+/-5.43	11.7+/-7.89
CONDUCT	uaho				
COPPER	ppb				
Ca-137	pCi/l	3.83+/-3.13	-4.82+/-8.37	-9.87+/-11.1	2.33+/-4.71
CYANIDE	ppb	<10	<10	<10	<10
FLUORID	ppb				
H-3	pCi/l	9,416+/-349	16,286+/-427	10,386+/-429	16,686+/-435
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	2.48+/-1.41	2.81+/-1.28	1.28+/-1.18	3.78+/-1.89
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	<10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NNIDIME	ppb	<10	<10	<10	<10
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0014+/-0.0163			.0026+/-0.0082
Pu-238	pCi/l	-.00072+/-0.0298			.0075+/-0.0117
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-5.24+/-48.8	-67.7+/-87.3	-12.6+/-58.2	2.78+/-58.2
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	2.57+/-1.18			
Sr-90	pCi/l	1.18+/-0.499			
SULFATE	ppb				
TETRAHE	ppb	<10	<10	<10	<10
THALLUM	ppb				
TOC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(B,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
VANADIUM	ppb				
ZINC	ppb				

TABLE D.1. (contd)

		299-E32-3				299-E32-4	
		8/28/87 (B)	1335 hr	9/01/87 (P)	1415 hr	1515 hr	9/15/87 (B)
1,1,1-T	ppb	<10	<10	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<	<	<
ALUMINUM	ppb						
AMMONIUM	ppb						
ANTIMONY	ppb						
ARSENIC	ppb						
BARIUM	ppb						
BETA	pCi/l	11.6+/-4.22	8.52+/-4.86	17.5+/-4.81	11.4+/-4.47		76.4+/-7.86
BIS2EPH	ppb	<10	<10	<10	<10		<10
CADMIUM	ppb						
CALCIUM	ppb						
CHLORINE	ppb	<10	<10	<10	<10		<10
CHLFORM	ppb	<10	<10	<10	<10		<10
CHLORID	ppb						
CHROMIUM	ppb						
Co-60	pCi/l	8.06+/-8.00	3.84+/-3.51	-4.91+/-8.65	7.89+/-5.36		8.51+/-8.82
CONDUCT	umho						
COPPER	ppb						
Co-137	pCi/l	5.75+/-3.83	2.24+/-4.87	4.76+/-8.51	1.86+/-4.78		-4.09+/-8.15
CYANIDE	ppb	<10	<10	<10	<10		<10
FLUORID	ppb						
H-3	pCi/l	5,828+/-276	7,868+/-389	7,838+/-388	8,328+/-398		-38.6+/-155
IRON	ppb						
LEAD	ppb						
LOALPHA	pCi/l	1.27+/-1.14	3.96+/-1.74	4.54+/-1.75	6.87+/-2.88		23.4+/-4.18
MAGNES	ppb						
MANGNESE	ppb						
MERCURY	ppb						
METHRONE	ppb	<10	<10	<10	<10		<10
METHYCH	ppb	<10	<10	<10	<10		<10
NICKEL	ppb						
NITRATE	ppb						
NNIDIME	ppb	<10	<10	<10	<10		<10
PCB	ppb						
pH-LAB							
PHOSPHA	ppb						
Pu-239/240	pCi/l	-.0014+/--.0018	.0016+/--.0047	-.0014+/--.0073			-.0014+/--.0067
Pu-238	pCi/l	.0118+/--.0301	-.0067+/--.0071	-.0067+/--.0073			.0299+/--.0381
POTASUM	ppb						
RADIUM	pCi/l						
Ru-106	pCi/l	23.6+/-41.4	8.86+/-38.8	3.62+/-44.6	13.4+/-39.6		32.9+/-28.6
SELENIUM	ppb						
SILVER	ppb						
SODIUM	ppb						
Sr-total	pCi/l	1.79+/-0.81					1.14+/-0.25
Sr-90	pCi/l	.885+/--.454					1.14+/--.584
SULFATE	ppb						
TETRAHE	ppb	<10	<10	<10	<10		<10
THALLUM	ppb						
TOC	ppb						
TOLUENE	ppb	<10	<10	<10	<10		<10
TOX	ppb						
TRICENE	ppb	<10	<10	<10	<10		<10
UNKNOWN	ppb						
URANIUM	pCi/l						
URANIUM-234	pCi/l						
URANIUM-235	pCi/l						
URANIUM-238	pCi/l						
XYLENE(O,P)	ppb	<10	<10	<10	<10		<10
XYLENE(M)	ppb	<10	<10	<10	<10		<10
VANADIUM	ppb						
ZINC	ppb						

TABLE D.1. (contd)

		290-E33-26				
		10/10/87 (B)	1130 hr	10/21/87 (P)	1330 hr	1515 hr
1,1,1-T	ppb	<5	<5	<5	<5	<5
ACETONE	ppb	<	<	<	<	<
ALUMINUM	ppb					
AMMONIUM	ppb					
ANTIMONY	ppb					
ARSENIC	ppb					
BARIUM	ppb					
BETA	pCi/l	19.9+/-4.72	13.1+/-4.31	14.5+/-4.38	8.67+/-3.88	
BIS2EPH	ppb	<10	<10	<10	<10	
CADMIUM	ppb					
CALCIUM	ppb					
CHLBENZ	ppb	<10	<10	<10	<10	
CHLFORM	ppb	<5	<5	<5	<5	
CHLDRID	ppb					
CHROMIUM	ppb					
Co-60	pCi/l	3.19+/-3.69	5.29+/-4.73		6.42+/-5.24	
CONDUCT	umho					
COPPER	ppb					
Cs-137	pCi/l	4.66+/-3.52	1.32+/-5.91	5.26+/-8.10	2.98+/-4.87	
CYANIDE	ppb	<10	<10	<10	<10	
FLUORID	ppb					
H-3	pCi/l	2,868+/-287	2,820+/-236	2,838+/-236	2,888+/-237	
IRON	ppb					
LEAD	ppb					
LOALPHA	pCi/l	2.28+/-1.27	1.15+/-0.897	1.56+/-1.07	.887+/-0.856	
MAGNES	ppb					
MANGESE	ppb					
MERCURY	ppb					
METHONE	ppb	<10	<10	<10	<10	
METHYCH	ppb	<10	<10	<10	<10	
NICKEL	ppb					
NITRATE	ppb					
NNITDIME	ppb	<10	<10	<10	<10	
PCB	ppb					
pH-LAB						
PHOSPHA	ppb					
Pu-239/240	pCi/l	.0038+/-0.0008	.0014+/-0.0002	.0042+/-0.0007	.0014+/-0.0006	
Pu-238	pCi/l	.0007+/-0.0132	.0007+/-0.0001	.0007+/-0.0005	.0007+/-0.0005	
POTASUM	ppb					
RADIUM	pCi/l					
Ru-106	pCi/l	-8.21+/-55.3	-16.8+/-52.1	36.3+/-67.5	39.5+/-29.9	
SELENIUM	ppb					
SILVER	ppb					
SODIUM	ppb					
Sr-total	pCi/l					
Sr-90	pCi/l	-.482+/-0.419	.195+/-0.469	.158+/-0.523	.014+/-0.488	
SULFATE	ppb					
TETRAHE	ppb	<5	<5	<5	<5	
THALLUM	ppb					
TOC	ppb					
TOLUENE	ppb	<5	<5	<5	<5	
TOX	ppb					
TRICENE	ppb	<5	<5	<5	<5	
UNKNOWN	ppb					
URANIUM	pCi/l					
URANIUM-234	pCi/l	.916+/-0.191				
URANIUM-235	pCi/l	-.002+/-0.029				
URANIUM-238	pCi/l	.001+/-0.182				
XYLENE(D,P)	ppb	<5	<5	<5	<5	
XYLENE(M)	ppb	<5	<5	<5	<5	
YANADIUM	ppb					
ZINC	ppb					

TABLE D.1. (contd)

		299-E33-29		299-E33-30	
		9/14/87 (B)	9/17/87 (P)	9/18/87 (B)	9/24/87 (P)
		1440 hr	1620 hr	0815 hr	1015 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	31.2+/-5.68	27.9+/-5.55	26.7+/-5.48	29.6+/-5.52
BIS2EPH	ppb	<10	<10	<10	<10
CADMIUM	ppb				
CALCIUM	ppb				
CHL BENZ	ppb	<10	<10	<10	<10
CHLFORM	ppb	<10	<10	<10	<10
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	7.06+/-5.33	.534+/-7.85	-5.34+/-9.79	1.82+/-9.22
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	-8.38+/-7.11	5.99+/-4.06	-3.33+/-8.86	-5.29+/-9.19
CYANIDE	ppb	<10	<10	<10	<10
FLUORID	ppb				
H-3	pCi/l	3,988+/-257		3,756+/-393	4,248+/-312
IRON	ppb				4,858+/-388
LEAD	ppb				
LOALPHA	pCi/l	1.88+/-1.18	1.38+/-1.12	1.25+/-1.18	1.82+/-1.86
MAGNES	ppb				
MANGNESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	<10	<10	49	<10
NICKEL	ppb				
NITRATE	ppb				
NWIDIME	ppb	<10	<10	<10	<10
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0014+/-0.0367	-.0034+/-0.0041	-.0117+/-0.0147	-.0066+/-0.0077
Pu-238	pCi/l	-.00072+/-0.0305	-.0048+/-0.0180	-.0148+/-0.0374	-.0116+/-0.0316
POTASUM	ppb				.0115+/-0.0191
RADIUM	pCi/l				.0183+/-0.0220
Ru-106	pCi/l	28.9+/-28.9	-2.79+/-57.5	44.7+/-55.9	-3.18+/-83.7
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	3.97+/-2.28		0.35+/-0.24	
Sr-90	pCi/l	3.97+/-4.52	.215+/-0.488	.046+/-0.438	.354+/-0.477
SULFATE	ppb				.487+/-0.489
TETRANE	ppb	<10	<10	<10	.067+/-0.441
THALLUM	ppb				
TDC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE (O,P)	ppb	<10	<10	<10	<10
XYLENE (M)	ppb	<10	<10	<10	<10
VANADIUM	ppb				
ZINC	ppb				

TABLE D.1. (contd)

		299-E34-2		299-E34-3		299-E34-5	299-E34-8
		7/29/87 (B)	8/07/87 (P)	7/27/87 (B)	7/13/87 (B)	7/14/87 (B)	
		1115 hr		1615 hr			
1,1,1-T	ppb	<10	<10	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<	<	<
ALUMINUM	ppb	804					
AMMONIUM	ppb	230					
ANTIMONY	ppb	<100					
ARSENIC	ppb	<5					
BARIUM	ppb	52					
BETA	pCi/l	54.6+/-7.45	12.7+/-4.32	14.7+/-4.75	14.0+/-4.36	28.7+/-5.88	14.6+/-2.5
BIS2EPH	ppb	<10	<10	<10	<10	<10	<10
CADMIUM	ppb	<2					
CALCIUM	ppb	64,200					
CHLORINE	ppb	<10	<10	<10	<10	<10	<10
CHLFORM	ppb	<10	<10	<10	<10	<10	<10
CHLORO	ppb	9,970					
CHROMIUM	ppb	<10					
Co-60	pCi/l	4.84+/-4.84	9.58+/-4.25	1.14+/-2.28	-0.85+/-0.55	2.13+/-3.01	.532+/-7.22
CONDUCT	umho						
COPPER	ppb	27					
Cs-137	pCi/l	3.40+/-5.55	10.6+/-9.89	0.21+/-4.14	-5.39+/-7.45	-1.66+/-8.59	3.65+/-6.87
CYANIDE	ppb	<10	<10	<10	<10	<10	<10
FLUORIDE	ppb	862					
H-3	pCi/l	217+/-184	295+/-212	238+/-209	418+/-258	515+/-296	444+/-172
IRON	ppb	29,888					
LEAD	ppb	<5					
LBALPHA	pCi/l	3.83+/-2.27	1.39+/-1.19	2.91+/-2.84	4.96+/-1.93	8.35+/-2.73	.384+/-1.962
MAGNES	ppb	18,370					
MANGANESE	ppb	274					
MERCURY	ppb	<1					
METHONE	ppb	<10	<10	<10	<10	<10	<10
METHYLCH	ppb	<10	<10	<10	<10	<10	<10
NICKEL	ppb	30					
NITRATE	ppb	18,700					
NNIDIME	ppb	<10	<10	<10	<10	<10	<10
PCB	ppb	<1					
pH-LAB		7.897					
PHOSPHA	ppb	<1000					
Pu-239/240	pCi/l	- .0000+/- .012	- .0014+/- .0071	- .0014+/- .0073	0.00+/-0.00	- .0048+/- .0007	- .0038+/- .0075
Pu-238	pCi/l	0.00+/- .024	- .0007+/- .0071	- .0007+/- .0068	.0103+/- .0306	.0145+/- .0118	0.00+/-0.00
POTASUM	ppb	8,749					
RADIUM	pCi/l	.007+/- .199					
Ru-106	pCi/l	27.9+/-69.5	-20.0+/-51.7	0.13+/-58.8	47.1+/-68.3	-2.74+/-56.4	-71.3+/-70.2
SELENIUM	ppb	<5					
SILVER	ppb	<10					
SODIUM	ppb	32,250					
Sr-total	pCi/l	1.77+/-0.88			1.69+/- .36	6.48+/-2.47	3.68+/-1.68
Sr-90	pCi/l	.798+/- .387			1.69+/- .592	2.47+/- .543	1.68+/- .687
SULFATE	ppb	140,755					
TETRAHE	ppb	<10	<10	<10	<10	<10	<10
THALLIUM	ppb	<5					
TDC	ppb	873					
TOLUENE	ppb	<10	<10	<10	<10	<10	<10
TOX	ppb	27.8					
TRICENE	ppb	<10	<10	<10	<10	<10	<10
UNKNOWN	ppb						
URANIUM	pCi/l	1.88+/- .33			34		
URANIUM-234	pCi/l						
URANIUM-235	pCi/l						
URANIUM-238	pCi/l						
XYLENE(O,P)	ppb	<10	<10	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10	<10	<10
VANADIUM	ppb	20					
ZINC	ppb	53					

TABLE D.2. Constituents Measured in Water Samples Before and During Aquifer Testing, 200-West Area Low-Level Burial Grounds

		299-V6-2			
		10/30/87 (B)	0830 hr	11/05/87 (P)	1115 hr
				1000 hr	
1,1,1-T	ppb	<5	<5	<5	<5
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	15.9+/-4.55	9.32+/-2.83	8.98+/-2.61	13.8+/-2.95
BIS2EPH	ppb				
CAESIUM	ppb				
CALCIUM	ppb				
CHLOROBENZ	ppb	<10	<10	<10	<10
CHLOROFORM	ppb	3	2	2	2
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	3.63+/-4.19	-1.52+/-0.87	-.585+/-7.99	.535+/-7.88
CONDUCT	umho				
COPPER	ppb				
Cs-137	pCi/l	-4.53+/-8.27	2.88+/-5.01	-.685+/-6.28	-5.38+/-7.01
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	11,800+/-383	11,400+/-445	11,300+/-446	11,900+/-454
IRON	ppb				
LEAD	ppb				
LDALPHA	pCi/l	1.15+/- .894	.952+/- .997	.582+/- .943	2.43+/-1.45
MAGNES	ppb				
MANGANESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYLCH	ppb	<10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NNIOIWE	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0083+/- .0139	-.0014+/- .0071	-.0014+/- .0074	-.0014+/- .0110
Pu-238	pCi/l	-.0077+/- .0773	-.0007+/- .0070	-.0007+/- .0079	-.0007+/- .0110
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	27.9+/-59.5	8.86+/-38.6	11.7+/-57.2	-87.5+/-72.9
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l				
Sr-90	pCi/l	.0883+/- .457	.0392+/- .437	-.1548+/- .443	-.0487+/- .448
SULFATE	ppb				
TETRANE	ppb	48	80	72	72
THALLUM	ppb				
TOC	ppb				
TOLUENE	ppb	<5	<5	<5	<5
TOX	ppb				
TRICENE	ppb	<5	<5	<5	<5
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb	<5	<5	<5	<5
XYLENE(M)	ppb	<5	<5	<5	<5
VANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W7-1			
		7/89/87 (B)	7/15/87 (P)	7/15/87 (P)	7/15/87 (P)
			1825 hr	1430 hr	1630 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	20.8+/-5.17	8.73+/-4.11	4.11+/-3.43	8.82+/-3.91
BIS2EPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLORINE	ppb	<10	<10	<10	<10
CHLORIDE	ppb	<10	<10	<10	<10
CHLORINE	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	6.47+/-0.41	-2.53+/-0.55	4.27+/-4.27	3.20+/-3.89
CONDUCT	umho				
COPPER	ppb				
Cr-137	pCi/l	.755+/-0.41	3.19+/-2.86	8.32+/-5.73	-2.88+/-7.53
CYANIDE	ppb				
FLUORIDE	ppb				
H-3	pCi/l	-129+/-221	-23.7+/-157	191+/-184	116+/-162
IRON	ppb				
LEAD	ppb				
LDALPHA	pCi/l	3.36+/-1.54	.427+/-0.895	.726+/-0.807	-.171+/-0.437
MAGNES	ppb				
MANGANESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYL	ppb	<10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NITROGEN	ppb				
PCB	ppb				
pH-LAB					
PHOSPHORUS	ppb				
Pu-239/240	pCi/l	-.0014+/-0.0173	0.00+/-0.00	0.00+/-0.00	-.0021+/-0.0043
Pu-238	pCi/l	-.0099+/-0.0388	0.00+/-0.00	-.0019+/-0.0038	.0021+/-0.0074
POTASSIUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-3.18+/-58.1	47.7+/-31.8	19.4+/-39.2	-11.1+/-44.3
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	1.28+/-0.57			
Sr-90	pCi/l	.568+/-0.458	.493+/-0.298	.267+/-0.285	.384+/-0.288
SULFATE	ppb				
TETRANE	ppb	<10	<10	<10	<10
THALLIUM	ppb				
TOC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-236	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
YANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W7-2			
		9/09/87 (B)	9/15/87 (P) 1200 hr	9/16/87 (P) 1200 hr	9/16/87 (P) 1510 hr
1,1,1-T	ppb		<10	<10	<10
ACETONE	ppb		<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	8.52+/-3.92	8.59+/-3.87	3.03+/-3.88	4.75+/-3.43
BISZEPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLBENZ	ppb		<10	<10	<10
CHLFORM	ppb		<10	<10	<10
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	11.2+/-7.91	1.89+/-5.59	6.78+/-5.78	-8.88+/-12.3
CONDUCT	umho				
COPPER	ppb				
Cs-137	pCi/l	.427+/-0.98	2.97+/-5.37	3.28+/-8.96	7.82+/-0.83
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l				
IRON	ppb				
LEAD	ppb				
LGALPHA	pCi/l	1.89+/-1.21	1.84+/-1.932	1.42+/-1.85	.781+/-1.827
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb		<10	<10	<10
METHYCH	ppb		<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
KNIDIME	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l		-.8828+/-0.8188	.8844+/-0.8158	-.8893+/-0.8184
Pu-238	pCi/l		.8121+/-0.8227	.8853+/-0.8281	-.8121+/-0.8195
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-67.7+/-184	-8.79+/-51.4	46.8+/-37.4	8.88+/-84.8
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l				
Sr-90	pCi/l		.8558+/-1.598	.119+/-0.889	.113+/-1.548
SULFATE	ppb				
TETRANE	ppb		<10	<10	<10
THALLUM	ppb				
TSC	ppb				
TOLUENE	ppb		<10	<10	<10
TOX	ppb				
TRICENE	ppb		<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb		<10	<10	<10
XYLENE(M)	ppb		<10	<10	<10
YANADUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W7-3				
		9/29/87 (B)	10/28/87 (B) 0830 hr	10/30/87 (P) 0900 hr	10/30/87 (P) 1400 hr	10/31/87 (P) 1200 hr
1,1,1-T	ppb	<10	<5	<5	<5	<5
ACETONE	ppb	<	<	<	<	<
ALUMINUM	ppb		1050			
AMMONIUM	ppb		86			
ANTIMONY	ppb		<100			
ARSENIC	ppb		<5			
BARIUM	ppb		35			
BETA	pCi/l	20.3+/-5.75	15.7+/-4.58	3.78+/-2.13	4.58+/-2.12	2.89+/-1.91
BIS2EPH	ppb		<10	<10	<10	<10
CADMIUM	ppb		<2			
CALCIUM	ppb		24,020			
CHLBENZ	ppb	<10	<10	<10	<10	<10
CHLFORM	ppb	<10	<5	<5	<5	<5
CHLORID	ppb		4000			
CHROMIUM	ppb		<10			
Co-60	pCi/l	- .504+/-7.12	- .098+/-9.87	-1.61+/-8.85	2.27+/-3.21	-4.54+/-9.82
CONDUCT	umho		265.7			
COPPER	ppb		12			
Ca-137	pCi/l	.958+/-4.51	-3.84+/-9.12	5.88+/-3.59	2.47+/-5.86	4.24+/-3.46
CYANIDE	ppb		<10			
FLUORID	ppb		553			
H-3	pCi/l	41.8+/-150	-59+/-192	44+/-159	151+/-162	82.7+/-160
IRON	ppb		10,780			
LEAD	ppb		9			
LOALPHA	pCi/l	20.5+/-0.04	1.33+/-1.01	1.18+/-1.02	.0581+/-0.058	.096+/-0.068
MAGNES	ppb		10,630			
MANGESE	ppb		170			
MERCURY	ppb		<.1			
METHONE	ppb	<10	<10	<10	<10	<10
METHYCH	ppb	<10	<10	<10	<10	<10
NICKEL	ppb		10			
NITRATE	ppb		528			
NNIDIME	ppb		<10			
PCB	ppb		<1			
pH-LAB			8.597			
PHOSPHA	ppb		<1000			
Pu-239/240	pCi/l	.0100+/-0.0220	- .0049+/-0.0071	- .0014+/-0.0100	.0008+/-0.0043	.0046+/-0.0120
Pu-238	pCi/l	- .0121+/-0.0394	.0134+/-0.0530	- .0007+/-0.0112	.0014+/-0.0043	- .0007+/-0.0180
POTASUIM	ppb		5354			
RADIUM	pCi/l		- .0384+/-0.0857			
Ru-106	pCi/l	23.5+/-41.2	-45.7+/-72.4	45.1+/-40.8	-74.2+/-67.7	-11.9+/-89.1
SELENIUM	ppb		<5			
SILVER	ppb		<10			
SODIUM	ppb		18,650			
Sr-total	pCi/l	4.52+/-0.42				
Sr-90	pCi/l	4.52+/-0.830	.384+/-0.650	.041+/-0.490	.472+/-0.500	.107+/-0.485
SULFATE	ppb		24,005			
TETRAWE	ppb	<10	<5	<5	<5	<5
THALLUM	ppb		<5			
TDC	ppb		1309			
TOLUENE	ppb	<10	<5	<5	<5	<5
TOX	ppb		0.5			
TRICENE	ppb	<10	<5	<5	<5	<5
UNKNOWN	ppb					
URANIUM	pCi/l					
URANIUM-234	pCi/l					
URANIUM-235	pCi/l					
URANIUM-238	pCi/l					
XYLENE(O,P)	ppb	<10	<5	<5	<5	<5
XYLENE(M)	ppb	<10	<5	<5	<5	<5
VANADIUM	ppb		9			
ZINC	ppb		22			

TABLE D.2. (contd)

		290-V7-4				
		11/05/07 (B)	1015 hr	11/12/07 (P)	1200 hr	1430 hr
1,1,1-T	ppb	<5	<5	<5	<5	<5
ACETONE	ppb	<	<	<	<	<
ALUMINUM	ppb					
AMMONIUM	ppb					
ANTIMONY	ppb					
ARSENIC	ppb					
BARIUM	ppb					
BETA	pCi/l	22.8+/-5.22	17.6+/-4.77	15.8+/-4.87	12.3+/-4.32	
BIS2EPH	ppb					
CADMIUM	ppb					
CALCIUM	ppb					
CHLORINE	ppb	<10	<10	<10	<10	
CHLFORM	ppb	5	5	4	5	
CHLORID	ppb					
CHROMIUM	ppb					
Co-60	pCi/l	4.58+/-4.58	2.13+/-3.82	7.87+/-5.34	-1.76+/-8.99	
CONDUCT	umho					
COPPER	ppb					
Ca-137	pCi/l	1.83+/-4.88	2.05+/-6.21	2.22+/-4.84	-2.83+/-8.88	
CYANIDE	ppb	<10				
FLUORID	ppb					
H-3	pCi/l	173+/-171	489+/-211	489+/-213	388+/-289	
IRON	ppb					
LEAD	ppb					
LOALPHA	pCi/l	.134+/-443	.787+/-858	2.81+/-1.32	2.59+/-1.35	
MAGNES	ppb					
MANGESE	ppb					
MERCURY	ppb					
METHONE	ppb	<10	<10	<10	<10	
METHYCH	ppb	<10	<10	<10	<10	
NICKEL	ppb					
NITRATE	ppb					
NNIDIME	ppb					
PCB	ppb					
pH-LAB						
PHOSPHA	ppb					
Pu-239/240	pCi/l	.8814+/-8481	.8828+/-8868	.8854+/-8888	.8814+/-8883	
Pu-238	pCi/l	-.8887+/-8359	-.8887+/-8185	-.8887+/-8121	.8815+/-8845	
POTASUM	ppb					
RADIUM	pCi/l					
Ru-106	pCi/l	2.84+/-35.1	-47.2+/-47.7	28.5+/-23.7	-58.3+/-68.5	
SELENIUM	ppb					
SILVER	ppb					
SODIUM	ppb					
Sr-total	pCi/l					
Sr-90	pCi/l	-.8888+/-457	-.8818+/-435	.2388+/-448	-.1728+/-395	
SULFATE	ppb					
TETRAHE	ppb	35	138	138	140	
THALLUM	ppb					
TOC	ppb					
TOLUENE	ppb	<5	<5	<5	<5	
TOX	ppb					
TRICENE	ppb	<5	<5	<5	<5	
UNKNOWN	ppb					
URANIUM	pCi/l					
URANIUM-234	pCi/l					
URANIUM-235	pCi/l					
URANIUM-238	pCi/l					
XYLENE(O,P)	ppb	<5	<5	<5	<5	
XYLENE(M)	ppb	<5	<5	<5	<5	
YAHADIUM	ppb					
ZINC	ppb					

TABLE D.2. (contd)

		299-W7-5			
		11/16/87 (B)	1306 hr	11/21/87 (P)	1516 hr
				1616 hr	1846 hr
1,1,1-T	ppb	<5	<5	<5	<5
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	11.2+/-4.12	3.77+/-3.58	8.42+/-3.88	8.36+/-3.99
BIS2EPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLORINE	ppb	<10	<10	<10	<10
CHLFORM	ppb	<5	<5	<5	<5
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	-4.28+/-9.98	-3.54+/-8.24	1.13+/-2.28	-5.88+/-7.15
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	5.95+/-2.97	-1.27+/-5.88	-0.93+/-8.71	-1.27+/-5.88
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	220+/-194	382+/-178	298+/-178	350+/-172
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	1.97+/-1.27	.787+/-1.825	.097+/-1.998	.554+/-1.748
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	<10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NNIDINE	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0027+/-0.0027	-.0014+/-0.0008	-.0014+/-0.0051	-.0014+/-0.0078
Pu-238	pCi/l	.0722+/-0.0937	-.0087+/-0.0979	-.0087+/-0.0058	-.0087+/-0.0078
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-35.7+/-85.1	5.83+/-37.8	-32.8+/-64.8	16.8+/-53.6
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l				
Sr-90	pCi/l	.9935+/-1.432	.0611+/-1.267	-.0071+/-1.246	-1.788+/-1.498
SULFATE	ppb				
TETRAHE	ppb	9	12	13	13
THALLUM	ppb				
TIC	ppb				
TOLUENE	ppb	<5	<5	<5	<5
TOX	ppb				
TRICENE	ppb	<5	<5	<5	<5
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(D,P)	ppb	<5	<5	<5	<5
XYLENE(M)	ppb	<5	<5	<5	<5
YANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		209-W7-6			
		10/09/87 (B)	10/14/87 (P)		
		8000 hr	1200 hr	1500 hr	
1,1,1-T	ppb	<10	<5	<5	
ACETONE	ppb	<	<	<	
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	26.8 +/- 8.91	8.96 +/- 3.60	2.78 +/- 3.24	.744 +/- 2.87
BISSEPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLORIDE	ppb	<10	<10	<10	
CHLORIDE	ppb	<10	<5	<5	
CHLORIDE	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	8.51 +/- 8.82	2.28 +/- 3.22	3.84 +/- 8.94	5.35 +/- 4.78
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	2.99 +/- 8.15	-3.56 +/- 7.92	1.51 +/- 6.76	-3.66 +/- 8.18
CYANIDE	ppb		<10	<10	<10
FLUORIDE	ppb				
H-3	pCi/l	550 +/- 175	958 +/- 225	1848 +/- 227	1158 +/- 232
IRON	ppb				
LEAD	ppb				
LDALPHA	pCi/l	1.88 +/- 1.82	.213 +/- .498	.991 +/- .699	1.48 +/- .812
MAGNES	ppb				
MANGANESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	
METHYCH	ppb	<10	<10	<10	
NICKEL	ppb				
NITRATE	ppb				
NITROGEN	ppb				
PCB	ppb				
pH-LAB					
PHOSPHORUS	ppb				
Pu-239/240	pCi/l	-.0014 +/- .0433	-.0014 +/- .0126	.0009 +/- .0046	-.0014 +/- .0058
Pu-238	pCi/l	-.0036 +/- .0050	-.0007 +/- .0123	-.0007 +/- .0060	.0012 +/- .0038
POTASSIUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-86.2 +/- 71.8	8.81 +/- 52.4	3.17 +/- 88.6	67.4 +/- 36.9
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l				
Sr-90	pCi/l	.381 +/- .488	.713 +/- .478	-.235 +/- .348	.0648 +/- .327
SULFATE	ppb				
TETRANE	ppb	<10	<5	<5	
THALLIUM	ppb				
TGC	ppb				
TOLUENE	ppb	<10	<5	<5	
TOX	ppb				
TRICENE	ppb	<10	<5	<5	
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE (O, P)	ppb	<10	<5	<5	
XYLENE (M)	ppb	<10	<5	<5	
VANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W8-1 8/29/87 (B)	299-W9-1 10/08/87 (B)
1,1,1-T	ppb	<10	
ACETONE	ppb	<	
ALUMINUM	ppb		
AMMONIUM	ppb		
ANTIMONY	ppb		
ARSENIC	ppb		
BARIUM	ppb		
BETA	pCi/l	25.5+/-12.0	21.4+/-6.02
BIS2EPH	ppb		
CADMIUM	ppb		
CALCIUM	ppb		
CHLBENZ	ppb	<10	
CHLFORM	ppb	<10	
CHLORID	ppb		
CHROMIUM	ppb		
Co-60	pCi/l	4.53+/-3.02	3.36+/-17.0
CONDUCT	umho		
COPPER	ppb		
Cs-137	pCi/l	.100+/-3.70	-2.84+/-12.7
CYANIDE	ppb		
FLUORID	ppb		
H-3	pCi/l	-168+/-223	-89.0+/-154
IRON	ppb		
LEAD	ppb		
LDALPHA	pCi/l	8.45+/-5.13	2.13+/-1.39
MAGNES	ppb		
MANGESE	ppb		
MERCURY	ppb		
METHONE	ppb	<10	
METHYCH	ppb	<10	
NICKEL	ppb		
NITRATE	ppb		
NNIDIME	ppb		
PCS	ppb		
pH-LAB			
PHOSPHA	ppb		
Pu-239/240	pCi/l	-.0014+/-0.0093	-.0014+/-0.0004
Pu-238	pCi/l	.0010+/-0.0003	.0001+/-0.0002
POTASUM	ppb		
RADIUM	pCi/l		
Ru-106	pCi/l	19.0+/-33.3	-13.9+/-132
SELENIUM	ppb		
SILVER	ppb		
SODIUM	ppb		
Sr-total	pCi/l	1.07+/-0.71	
Sr-90	pCi/l	1.07+/-1.42	.004+/-0.490
SULFATE	ppb		
TETRANE	ppb	<10	
THALLUM	ppb		
TOC	ppb		
TOLUENE	ppb	<10	
TOX	ppb		
TRICENE	ppb	<10	
UNKNOWN	ppb		
URANIUM	pCi/l		
URANIUM-234	pCi/l		
URANIUM-235	pCi/l		
URANIUM-238	pCi/l		
XYLENE (O,P)	ppb	<10	
XYLENE (M)	ppb	<10	
YANADIUM	ppb		
ZINC	ppb		

TABLE D.2. (contd)

		209-W10-13			
		9/09/87 (B)	1430 hr	9/14/87 (P) 1000 hr	1700 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	13.7+/-4.67	0.35+/-3.70	10.2+/-4.19	9.01+/-4.00
BIS2EPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLOROM2	ppb	<10	<10	<10	<10
CHLFORM	ppb	<10	<10	<10	<10
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	.502+/-7.62	-2.42+/-10.9	4.04+/-5.69	2.09+/-4.09
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	2.75+/-8.76	-4.92+/-8.11	8.85+/-5.90	9.13+/-5.77
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	246+/-105			
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	5.39+/-2.05	.027+/-0.008	1.03+/-1.10	1.10+/-0.022
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	<10	0	0	0
NICKEL	ppb				
NITRATE	ppb				
NITROIDE	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0014+/-0.0304	-.0020+/-0.0123	.0014+/-0.0008	-.0025+/-0.0120
Pu-238	pCi/l	-.0007+/-0.0303	-.0051+/-0.0001	.0024+/-0.0000	-.0010+/-0.0110
POTASUM	ppb				
RADIUM	pCi/l				
Ru-100	pCi/l	25.0+/-41.0	-0.34+/-70.4	-10.7+/-74.5	-30.3+/-96.7
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	0.51+/-0.23			
Sr-90	pCi/l	.514+/-0.452	.481+/-0.038	1.03+/-0.005	.231+/-0.010
SULFATE	ppb				
TETRANE	ppb	10	0	0	0
THALLUM	ppb				
TIC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-230	pCi/l				
XYLENE(D,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
VANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W18-14			
		9/29/87 (B)	10/21/87 (B)	10/25/87 (P)	
			1100 hr	1015 hr	1230 hr
1,1,1-T	ppb		<5	<5	<5
ACETONE	ppb		<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	36.7+/-7.57	16.2+/-4.65	3.50+/-3.38	8.85+/-3.97
BIS2EPH	ppb		<10	<10	<10
CADMIUM	ppb				
CALCIUM	ppb				
CHLBENZ	ppb		<10	<10	<10
CHLFORM	ppb		<5	<5	<5
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	4.64+/-4.64	3.72+/-8.10	5.64+/-5.64	3.83+/-3.58
CONDUCT	umho				
COPPER	ppb				
Cs-137	pCi/l	.958+/-4.52	.665+/-5.68	-4.11+/-5.48	4.45+/-3.36
CYANIDE	ppb		<10	<10	<10
FLUORID	ppb				
H-3	pCi/l		-111+/-138	386+/-172	558+/-178
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	18.8+/-4.98	5.31+/-1.93	.986+/--.999	.439+/--.888
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb		<10	<10	<10
METHYCH	ppb		<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NOXIDINE	ppb		<10	<10	<10
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/248	pCi/l		-.0014+/--.0419	-.0014+/--.0162	-.0014+/--.0068
Pu-238	pCi/l		.0132+/--.0279	.0027+/--.0068	-.0007+/--.0067
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	15.9+/-53.8	-32.8+/-68.6	-23.3+/-49.3	10.7+/-52.3
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l				
Sr-90	pCi/l		-.0097+/--.366	.0067+/--.481	.0008+/--.478
SULFATE	ppb				
TETRANE	ppb		<5	<5	<5
THALLUM	ppb				
TOC	ppb				
TOLUENE	ppb		<5	<5	<5
TOX	ppb				
TRICENE	ppb		<5	<5	<5
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb		<5	<5	<5
XYLENE(M)	ppb		<5	<5	<5
YANADUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W15-15			
		8/18/87 (B)	8/21/87 (P)	8/21/87 (P)	8/21/87 (P)
			1300 hr	1430 hr	1645 hr
I,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	15.2+/-4.72	5.25+/-3.59	8.88+/-3.87	8.85+/-4.84
BIS2EPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLOROBENZ	ppb	<10	<10	<10	<10
CHLFORM	ppb	200	0	4	3
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	-5.58+/-11.8	2.82+/-2.88	7.48+/-5.85	5.84+/-5.85
CONDUCT	uach				
COPPER	ppb				
Co-137	pCi/l	4.78+/-8.58	-5.43+/-8.53	-7.33+/-7.65	-3.44+/-4.81
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	149+/-181		278+/-285	228+/-293
IRON	ppb				
LEAD	ppb				
LDALPHA	pCi/l	5.12+/-2.31	3.89+/-1.57	3.82+/-1.55	4.88+/-1.77
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	<10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NITRIDE	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	-.0014+/-0.0227	-.0014+/-0.0006	-.0014+/-0.0005	-.0014+/-0.0005
Pu-238	pCi/l	-.0158+/-0.0239	.0025+/-0.0212	-.0007+/-0.0007	-.0007+/-0.0007
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	63.3+/-42.2	25.7+/-23.9	42.8+/-43.1	11.8+/-52.0
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	1.3+/-0.22			
Sr-90	pCi/l	1.36+/-0.440			
SULFATE	ppb				
TETRANE	ppb	1710	240	270	280
THALLUM	ppb				
TGC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(D,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
VARADUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-WIS-10			
		8/18/87 (B)	1500 hr	8/20/87 (P) 1700 hr	1030 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	58.9+/-0.17	9.33+/-4.40	10.3+/-4.54	12.1+/-4.54
BISZEPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLORINE	ppb	<10	<10	<10	<10
CHLORIDE	ppb	22	63	54	51
CHROMIUM	ppb				
Co-60	pCi/l	2.66+/-0.38	5.05+/-4.52	4.27+/-4.26	2.25+/-3.19
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	-1.33+/-5.95	6.97+/-5.79	3.00+/-4.89	-5.10+/-5.09
CYANIDE	ppb				
FLUORIDE	ppb				
H-3	pCi/l	-39.7+/-150	209+/-205	172+/-190	276+/-205
IRON	ppb				
LEAD	ppb				
LDALPHA	pCi/l	.511+/- .060	3.39+/-2.11	.073+/-1.10	4.01+/-2.26
MAGNES	ppb				
MANGANESE	ppb				
MERCURY	ppb				
METHANE	ppb	<10	<10	<10	<10
METHYLCH	ppb	10	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NIODINE	ppb				
PCB	ppb				
pH-LAB					
PHOSPHORUS	ppb				
Pu-239/240	pCi/l	-.0071+/- .0001	-.0014+/- .0072	-.0014+/- .0004	-.0014+/- .0053
Pu-238	pCi/l	.0107+/- .0214	-.0007+/- .0071	-.0007+/- .0070	.0010+/- .0034
POTASSIUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	13.7+/-86.3	29.1+/-43.0	55.4+/-50.5	0.00+/-40.8
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	1.04+/-0.29			
Sr-90	pCi/l	1.04+/- .584			
SULFATE	ppb				
TETRANE	ppb	<10	3900	3800	3800
THALLIUM	ppb				
TDC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
YANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		299-W15-17			
		9/22/87 (B)	1500 hr	9/28/87 (P) 1700 hr	2000 hr
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	105	<	<	<
ALUMINUM	ppb	54,510	555		401
AMMONIUM	ppb	2,250	<50	<50	<50
ANTIMONY	ppb	<100	<100	<100	<100
ARSENIC	ppb	11			
BARIUM	ppb	475	94	80	87
BETA	pCi/l	12.7+/-4.27	5.73+/-3.70	5.70+/-3.92	10.9+/-4.14
BIS2EPH	ppb	<10			
CADMIUM	ppb	<2	<2	<2	<2
CALCIUM	ppb	40,500	39,100	37,930	35,020
CHLORINE	ppb	<10	<10	<10	<10
CHLFORM	ppb	20	<10	<10	<10
CHLORID	ppb	16,025	15,500	15,150	15,150
CHROMIUM	ppb	91	<10	<10	10
Co-60	pCi/l	-2.00+/-0.90	4.05+/-4.05	-3.95+/-0.95	.467+/-7.30
CONDUCT	umho	302			
COPPER	ppb	150	<10	<10	<10
Cr-107	pCi/l	4.33+/-7.70	2.00+/-5.93	1.03+/-4.07	-0.14+/-10.0
CYANIDE	ppb	<10			
FLUORID	ppb	497	423	412	415
H-3	pCi/l	35.5+/-190	-253+/-107	-150+/-192	-26.8+/-194
IRON	ppb	190,000	2210		2070
LEAD	ppb	44	9		7
LDALPHA	pCi/l	3.00+/-1.05	-404+/-452	.450+/-0.009	1.24+/-726
MAGNES	ppb	20,000	13,400	12,730	12,300
MANGESE	ppb	2,217	40	20	72
MERCURY	ppb	<1			
METHONE	ppb	21	<10	<10	<10
METHYCH	ppb	40	<10	<10	<10
NICKEL	ppb	70	<10	<10	<10
NITRATE	ppb	2,315	27,023	27,209	27,150
NITRIDE	ppb	<10			
PCB	ppb	<1			
pH-LAB		0.500	7.501	7.570	7.600
PHOSPHA	ppb	<1000	<1000	<1000	<1000
Pu-239/240	pCi/l	.0167+/-0.0250	-0.0019+/-0.0010	.0025+/-0.0004	-0.0014+/-0.0003
Pu-238	pCi/l	-0.0090+/-0.0101	.0000+/-0.0104	.0100+/-0.0143	.0273+/-0.0103
POTASUM	ppb	11,700	4300	4420	4200
RADIUM	pCi/l	1.03+/-403			
Ru-100	pCi/l	-10.4+/-02.9	24.0+/-42.0	17.4+/-53.2	77.7+/-59.0
SELENIUM	ppb	<5			
SILVER	ppb	<10	<10	<10	<10
SODIUM	ppb	20,000	14,020	13,750	14,100
Sr-total	pCi/l	3.00+/-0.00			
Sr-90	pCi/l	.000+/-0.007	.131+/-0.347	.052+/-0.353	-0.101+/-0.520
SULFATE	ppb	32,315	29,079	29,540	29,571
TETRANE	ppb	<10	<10	<10	<10
THALLIUM	ppb	<5			
TOC	ppb	1,715	401	370	550
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb	40.4	20.4	26.2	0.3
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
YANADUM	ppb	251	40	32	35
ZINC	ppb	400	053	200	1307

TABLE D.2. (contd)

		299-W15-18			
		7/00/87 (B)	7/21/87 (P)		
		1400 hr	1500 hr	1800 hr	
1,1,1-T	ppb	<10	<10	<10	<10
ACETONE	ppb	<	<	<	<
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	11.1+/-4.20	9.04+/-4.29	8.97+/-4.07	7.05+/-4.04
BIS2EPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLBENZ	ppb	<10	<10	<10	<10
CHLFORM	ppb	230	39	31	20
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	4.04+/-4.04	.502+/-0.20	-1.09+/-7.03	-4.54+/-5.00
CONDUCT	umho				
COPPER	ppb				
Cs-137	pCi/l	-4.15+/-7.02	-5.05+/-5.92	10.3+/-5.33	.950+/-4.52
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	86.9+/-225	87.1+/-100	100+/-104	2500+/-220
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	1.20+/-1.20	.300+/-0.704	.010+/-0.094	3.04+/-1.57
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	<10
METHYCH	ppb	15	<10	<10	<10
NICKEL	ppb				
NITRATE	ppb				
NNIDIME	ppb				
PCB	ppb				
pH-LAB					
PHOSPHO	ppb				
Pu-239/240	pCi/l	-.0057+/-0.0061	.0058+/-0.0083	.0041+/-0.0077	.0002+/-0.0070
Pu-238	pCi/l	.0121+/-0.0315	-.0007+/-0.0072	-.0007+/-0.0082	.0031+/-0.0070
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	10.0+/-50.7	42.0+/-40.4	-11.4+/-45.0	20.9+/-42.0
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	1.21+/-0.25			
Sr-90	pCi/l	1.21+/-0.400	-.250+/-0.102	-.005+/-0.192	-.170+/-0.102
SULFATE	ppb				
TETRAHE	ppb	1400	1350	1450	1400
THALLUM	ppb				
TOC	ppb				
TOLUENE	ppb	<10	<10	<10	<10
TOX	ppb				
TRICENE	ppb	<10	<10	<10	<10
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE(O,P)	ppb	<10	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10	<10
VANADIUM	ppb				
ZINC	ppb				

TABLE D.2. (contd)

		209-W18-21		
		7/08/87 (B)	7/14/87 (P)	
			1330 hr	1500 hr
1,1,1-T	ppb	<10	<10	<10
ACETONE	ppb	<	<	<
ALUMINUM	ppb			
AMMONIUM	ppb			
ANTIMONY	ppb			
ARSENIC	ppb			
BARIUM	ppb			
BETA	pCi/l	35.6+/-0.55	9.84+/-3.90	4.76+/-3.38
BISZEPH	ppb			
CADMIUM	ppb			
CALCIUM	ppb			
CHLBENZ	ppb	<10	<10	<10
CHLFORM	ppb	24	<10	<10
CHLORID	ppb			
CHROMIUM	ppb			
Co-60	pCi/l	3.19+/-3.89	5.84+/-5.84	3.35+/-3.90
CONDUCT	umho			
COPPER	ppb			
Cs-137	pCi/l	5.32+/-6.79	0.00+/-0.46	5.51+/-3.89
CYANIDE	ppb			
FLUORID	ppb			
H-3	pCi/l	132+/-228	-49.5+/-158	181+/-184
IRON	ppb			
LEAD	ppb			
LDALPHA	pCi/l	22.7+/-8.85	10.8+/-2.48	12.7+/-2.70
MAGNES	ppb			
MANGNESE	ppb			
MERCURY	ppb			
METHONE	ppb	<10	<10	<10
METHYCH	ppb	<10	<10	<10
NICKEL	ppb			
NITRATE	ppb			
NNIDIME	ppb			
PCB	ppb			
pH-LAB				
PHOSPHA	ppb			
Pu-239/240	pCi/l	- .0048+/- .0000	.0037+/- .0052	.000+/- .0114
Pu-238	pCi/l	.0095+/- .0353	.0018+/- .0037	.000+/- .0114
POTASUM	ppb			
RADIUM	pCi/l			
Ru-106	pCi/l	5.48+/-47.7	0.65+/-37.4	-118+/-75.2
SELENIUM	ppb			
SILVER	ppb			
SODIUM	ppb			
Sr-total	pCi/l	1.11+/-0.29		
Sr-90	pCi/l	1.11+/- .582	.585+/- .358	.296+/- .282
SULFATE	ppb			
TETRANE	ppb	43	125	145
THALLUM	ppb			
TDC	ppb			
TOLUENE	ppb	<10	<10	<10
TOX	ppb			
TRICENE	ppb	<10	<10	<10
UNKNOWN	ppb			
URANIUM	pCi/l	8.94+/-1.41		
URANIUM-234	pCi/l			
URANIUM-235	pCi/l			
URANIUM-238	pCi/l			
XYLENE(O,P)	ppb	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10
VANADIUM	ppb			
ZINC	ppb			

TABLE D.2. (contd)

		7/29/87 (B)	8/18/87 (B) 1330 hr	209-W18-22 8/25/87 (P) 1310 hr	8/26/87 (P) 1015 hr	8/26/87 (P) 1315 hr
1,1,1-T	ppb		<10	<10	<10	<10
ACETONE	ppb		180	<	<	<
ALUMINUM	ppb		33,360			
AMMONIUM	ppb		1100			
ANTIMONY	ppb		<100			
ARSENIC	ppb		13			
BARIUM	ppb		322			
BETA	pCi/l	48.8+/-8.74	18.8+/-4.98	9.88+/-4.29	1.38+/-3.31	2.83+/-3.49
BIS2EPH	ppb		<10			
CADMIUM	ppb		3			
CALCIUM	ppb		42,976			
CHLORINE	ppb		26	<10	<10	<10
CHLORINE	ppb		<10	<10	<10	<10
CHLORIDE	ppb		18,898			
CHROMIUM	ppb		100			
Co-60	pCi/l	3.72+/-8.11	3.83+/-4.10	4.84+/-4.84	2.26+/-3.19	7.87+/-5.35
CONDUCT	umho					
COPPER	ppb		220			
Cs-137	pCi/l	-3.33+/-7.41	9.44+/-7.32	-5.11+/-7.67	-4.47+/-6.23	-1.92+/-5.67
CYANIDE	ppb		<10			
FLUORIDE	ppb		<500			
H-3	pCi/l		145+/-153	-87.2+/-192	88.2+/-199	34.4+/-197
IRON	ppb		250,800			
LEAD	ppb		240			
LDALPHA	pCi/l	3.18+/-1.88	5.54+/-2.83	2.29+/-1.49	1.28+/-1.84	.457+/-1.856
MAGNES	ppb		1381			
MANGANESE	ppb		2078			
MERCURY	ppb		<1			
METHANE	ppb		148	<10	<10	<10
METHYLENE	ppb		<10	<10	<10	<10
NICKEL	ppb		138			
NITRATE	ppb		11,973			
NITROGEN	ppb		<10			
PCB	ppb		<1			
pH-LAB			8.882			
PHOSPHORUS	ppb		<1000			
Pu-239/240	pCi/l		- .0014+/- .0259	- .0014+/- .0058	- .0014+/- .0057	
Pu-238	pCi/l		- .00072+/- .0259	- .0007+/- .0057	- .0007+/- .0056	
POTASSIUM	ppb		7,428			
RADIUM	pCi/l		2.89+/- .488			
Ru-106	pCi/l	49.3+/-57.8	-18.8+/-48.8	13.3+/-39.8	-31.7+/-63.5	37.1+/-28.1
SELENIUM	ppb		<5			
SILVER	ppb		<10			
SODIUM	ppb		14,780			
Sr-total	pCi/l		8.97+/-8.24			
Sr-90	pCi/l		.987+/- .483			
SULFATE	ppb		18,889			
TETRANE	ppb		<10	<10	<10	<10
THALLIUM	ppb		<5			
TOC	ppb					
TOLUENE	ppb		38	<10	<10	<10
TOX	ppb					
TRICENE	ppb		<10	<10	<10	<10
UNKNOWN	ppb					
URANIUM	pCi/l		.852+/- .388			
URANIUM-234	pCi/l					
URANIUM-235	pCi/l					
URANIUM-238	pCi/l					
XYLENE(O,P)	ppb		58	<10	<10	<10
XYLENE(M)	ppb		61	<10	<10	<10
VANADIUM	ppb		127			
ZINC	ppb		220			

TABLE D.2. (contd)

		299-W10-23		
		6/18/87 (P)	6/22/87 (P)	
		1428 hr	1515 hr	1848 hr
1,1,1-T	ppb	<10	<10	<10
ACETONE	ppb	<	<	<
ALUMINUM	ppb			
AMMONIUM	ppb			
ANTIMONY	ppb			
ARSENIC	ppb			
BARIUM	ppb			
BETA	pCi/l			
BIS2EPH	ppb			
CADMIUM	ppb			
CALCIUM	ppb			
CHLORINE	ppb	<10	<10	<10
CHLORIDE	ppb	<10	<10	<10
CHROMIUM	ppb			
Co-60	pCi/l			
CONDUCT	umho			
COPPER	ppb			
Cs-137	pCi/l			
CYANIDE	ppb			
FLUORIDE	ppb			
H-3	pCi/l			
IRON	ppb			
LEAD	ppb			
LOALPHA	pCi/l			
MAGNES	ppb			
MANGANESE	ppb			
MERCURY	ppb			
METHONE	ppb	<10	<10	<10
METHYLCH	ppb	<10	<10	<10
NICKEL	ppb			
NITRATE	ppb			
NITRIDE	ppb			
PCB	ppb			
pH-LAB				
PHOSPHOR	ppb			
Pu-239/240	pCi/l			
Pu-238	pCi/l			
POTASIUM	ppb			
RADIUM	pCi/l			
Ru-106	pCi/l			
SELENIUM	ppb			
SILVER	ppb			
SODIUM	ppb			
Sr-total	pCi/l			
Sr-90	pCi/l			
SULFATE	ppb			
TETRANE	ppb	810	675	850
THALLIUM	ppb			
TQC	ppb			
TOLUENE	ppb	<10	<10	<10
TOX	ppb			
TRICENE	ppb	<10	<10	<10
UNKNOWN	ppb			
URANIUM	pCi/l			
URANIUM-234	pCi/l			
URANIUM-235	pCi/l			
URANIUM-238	pCi/l			
XYLENE(O,P)	ppb	<10	<10	<10
XYLENE(M)	ppb	<10	<10	<10
YRADIUM	ppb			
ZINC	ppb			

TABLE D.2. (contd)

		299-W18-24			
		7/01/87 (B)	7/17/87 (P)		
			0915 hr	1110 hr	1410 hr
1,1,1-T	ppb	<10	<10	<10	LOST DUE TO INSTRUMENT
ACETONE	ppb	<	<	<	MAJFUNCTION (VOA ONLY)
ALUMINUM	ppb				
AMMONIUM	ppb				
ANTIMONY	ppb				
ARSENIC	ppb				
BARIUM	ppb				
BETA	pCi/l	14.4+/-5.22	9.71+/-4.10	1.70+/-3.24	6.45+/-3.78
BISSEPH	ppb				
CADMIUM	ppb				
CALCIUM	ppb				
CHLOROBENZ	ppb	<10	<10	<10	SAMPLE LOST
CHLORFORM	ppb	680	20	16	SAMPLE LOST
CHLORID	ppb				
CHROMIUM	ppb				
Co-60	pCi/l	8.47+/-4.53	1.82+/-8.57	-7.89+/-9.48	4.58+/-4.58
CONDUCT	umho				
COPPER	ppb				
Ca-137	pCi/l	-1.51+/-5.34	.758+/-9.19	12.8+/-8.82	3.44+/-3.88
CYANIDE	ppb				
FLUORID	ppb				
H-3	pCi/l	-196+/-223	-58.2+/-158	1120+/-192	235+/-185
IRON	ppb				
LEAD	ppb				
LOALPHA	pCi/l	5.83+/-4.41	.442+/- .889	.484+/- .834	.449+/- .895
MAGNES	ppb				
MANGESE	ppb				
MERCURY	ppb				
METHONE	ppb	<10	<10	<10	SAMPLE LOST
METHYCH	ppb	250	<10	<10	SAMPLE LOST
NICKEL	ppb				
NITRATE	ppb				
NIIDIME	ppb				
PCB	ppb				
pH-LAB					
PHOSPHA	ppb				
Pu-239/240	pCi/l	.0090+/- .0159	0.00+/- .0212	0.00+/- .0009	0.00+/- .0239
Pu-238	pCi/l	.0266+/- .0263	0.00+/- .0212	0.00+/- .0005	0.00+/- .0239
POTASUM	ppb				
RADIUM	pCi/l				
Ru-106	pCi/l	-18.8+/-39.9	-112+/-91.8	-7.18+/-81.5	-6.81+/-58.8
SELENIUM	ppb				
SILVER	ppb				
SODIUM	ppb				
Sr-total	pCi/l	8.94+/-8.35			
Sr-90	pCi/l	.942+/- .562	.481+/- .297	.239+/- .255	.300+/- .252
SULFATE	ppb				
TETRANE	ppb	1360	1280	1090	SAMPLE LOST
THALLUM	ppb				
TDC	ppb				
TOLUENE	ppb	<10	<10	<10	SAMPLE LOST
TOX	ppb				
TRICENE	ppb	<10	<10	<10	SAMPLE LOST
UNKNOWN	ppb				
URANIUM	pCi/l				
URANIUM-234	pCi/l				
URANIUM-235	pCi/l				
URANIUM-238	pCi/l				
XYLENE (O,P)	ppb	<10	<10	<10	SAMPLE LOST
XYLENE (M)	ppb	<10	<10	<10	SAMPLE LOST
VANADIUM	ppb				
ZINC	ppb				

APPENDIX E

AQUIFER TESTING OF WELLS IN THE 200-EAST AREA

APPENDIX E

AQUIFER TESTING OF WELLS IN THE 200-EAST AREA

INTRODUCTION

During 1987, aquifer tests were conducted on 13 of the 16 newly drilled wells that were designed to gather hydrologic and geologic data adjacent to waste management areas in the 200-East Area. The wells were not designed or drilled specifically as part of an aquifer testing program; however, the wells did provide an opportunity for conducting aquifer tests while the wells and equipment were available. Ideal conditions for obtaining maximally useful data were not, in general, met. For example, the screened intervals in the wells generally did not cover the full thickness of the aquifer, the well may not have been pumped at a sufficient rate for responses to be observed in pumping and observation wells, and in some cases, the pumping duration should have been longer. While part of the test data were of no use, some tests did furnish useful data that were analyzed for aquifer parameters and properties.

The following presents a summary of each aquifer test conducted in the 200-East Area. These aquifer test summaries include the purpose of each test, types of tests conducted, construction details of the tested well and observation well when used, pumping rates and duration of the tests, pre-test conditions, results of test data analysis, and related plots of test data. Raw data from the well development/step drawdown tests, constant discharge/recovery tests, and/or slug injection/withdrawal tests are also included.

AQUIFER TEST SUMMARY FOR WELL 299-E27-8

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 229 ft. Bottom: 257 ft.

Depth of Screened Interval in Pumped Well, Top: 247 ft. Bottom: 257 ft.

Date of Test: 08/19/87

Start Time of Test: 1400 hr

Pumping Rate: 192 gpm

Duration of Test: 375 min

Pre-test Water-level Elevation (Depth): 228.98 ft.

Water-level depth at maximum drawdown: 229.10 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>68,000	>2,400

Remarks: The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 192 gpm; therefore, the estimate of transmissivity (68,000 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis.

Aquifer Test Data

page 1 of 1

Data for Well 299-E27-B

Pumping Well

Observation Wells

Location RCRA 200 EAST

Type of Aquifer Test DEVELOPMENT

How Q Measured 24" DIA FLOW METER

How W.L.'s Measured E-TAPE / TRANSDUCER Depth of Pump/Airpipe 35' 24" TC 253' 3" below land

Rad./Dist. of/From Pumping Well Pump On: date time

Meas. Point for W.L.'s T/C 3-2' ABV LSO Pump Off: date time

Elevation of Meas. Point Duration of Aquifer Test

E-TAPE 3.57' ABV LSO TRANSDUCER 3.2' ABV LSO

Time			Water Level Data						Discharge	Recorded By	Comments
t = _____ at t' = 0			Static Water Level <u>232.58</u> ^{T/47.7m} _{WELC}								
Day	Clock Time	t	l'	l'/l	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
8/9	1400	0			232.58					106	WORKING WELL TRANS SEEMS TO BE HUNG UP
		1			232.67						
		4			232.64						
	1409										Dropped transducer to full depth H ₂ O ~ 15' above transducer
	1411	11			232.67						
	1425	25			232.62				107		
		30			232.62				107		
		45			232.60				07		
		60			232.62						
	↑	63									↑ Increased rate
		1			232.67				161		
		2									
		4			232.64				161		
	1415	12			232.64						
	1425	22			232.64						↑
↑		1							197		
		5			232.67				197		
	1535	10			232.69				197		
		15			232.67						
		20									PUMP OFF
		30			232.58						
		1			232.57						
		2			232.54						
		3			232.54						
		9			232.55						

Aquifer Test Data

page 1 of 1

Data for Well 299-E27-R

Pumping Well 299-E27-R

Observation Wells

Location 200 RCR EAST

Type of Aquifer Test ~~CONSTANT DISCHARGE~~

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE / TRANSDUCER

Depth of Pump/Airline 253' below soil

Rad./Dist. of/From Pumping Well

Pump On: date 5/19/82 time 1600

Meas. Point for W.L.'s T/C 3.2' + 45' L&B

Pump Off: date 5/19/82 time 2215

Elevation of Meas. Point T/C = 3.2' + 45' L&B

Duration of Aquifer Test 6.25 hrs

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>232.55'</u>				Discharge		Recorded By	Comments
Day	Clock Time	1	1'	1"	Reading	Conversions or Corrections	Water Level	s of s	Read- ing		
	1600	0			232.55			0		200	TRANSDUCER 30' AT 348' below TC
		170			232.64			0.09			
		2									
	1604	4			232.61			0.06		194	Transducer with 1.5m line
		10			232.62			0.12		194	
		20			232.62			0.07		193	
		23			232.62			0.07		193	
		45			232.61			0.11		193	
		50			232.61			0.10		193	
	1700	60			232.65			0.10		192	Front moving in
		70			232.63			0.08		192	After flood dropping
		80			232.64			0.09		193	light barometer
		90			232.63			0.08		192	field
	1800	120			232.62			0.07		192	MAC
	1900	180			232.61			0.06		191	MAC
	2000	210			232.63			0.08		192	MAC
	2100	280			232.66			0.11		191	MAC
	2130	320			232.64			0.11		191	MAC
		335			232.62	max. Ad.		0.12		191	MAC
	2214				232.66			0.11		191	MAC
	2215	0									Shut pump off
	2216	1			232.58						MAC
	2218	3			232.57						MAC
	2220	5			232.56						MAC
	2225	12			232.56						MAC
	2230	15			232.55						MAC
	2235	20			232.56						MAC
	2240	25			232.57						MAC
	2245	30			232.58						MAC
	2255	40			232.575						MAC

AQUIFER TEST SUMMARY FOR WELL 299-E27-9

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 222 ft. Bottom: 245 ft.

Depth of Screened Interval in Pumped Well, Top: 234 ft. Bottom: 244 ft.

Date of Test: 08/15/87

Start Time of Test: 1150 hr

Pumping Rate: 170 gpm

Duration of Test: 570 min

Pre-test Water-level Elevations (Depth): 224.52 ft (unknown measuring point).

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Recovery (Cooper and Jacob 1946)	35,000	1,500

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The discharge rate was not constant during the initial part of the constant discharge test. The recovery data indicate that boundary effects influenced the test.

RCRA WELL 299-E27-9
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/15/87

Q = 170 gpm

$$T = \frac{(2.3)(Q)}{(4)(\pi)d(s-s')}$$

$$T = 35,000 \text{ ft}^2/\text{d}$$

$$d(s-s') = 0.17 \text{ ft}$$

E.8
 Recovery
 (ft above
 transducer)

page 1 of 1

Pumping Well 299-E27-9

Observation Wells _____

Type of Aquifer Test drawdown test - Development

How Q Measured _____

How W.L.'s Measured transducer - F₁ - 1000

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 8/14/87 time 1902

Pump Off: date 6/14/87 time

Duration of Aquifer Test 50 minE.9

Aquifer Test Data

page 1 of 1

Data for Well 299 - E27-9

Pumping Well 299 - E27-9

Observation Wells _____

Location 299 - E27-9

Type of Aquifer Test Constant discharge

How Q Measured _____

How W.L.'s Measured transducer, E + 6.22

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 9/15/97 time 1150

Pump Off: date 9/15/97 time 2112

Duration of Aquifer Test 9.5 hrs

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>224.52</u>								
Day	Clock Time	t	t'	W/L	Reading	Corrections or Corrections	Water Level	s or s'	Reading	Q		
9/15	1150	0			224.52						SPA	Failed to note discharge
		2.5			231.17		-1.45'		170		SPA	on initial measurements
		4.0			230.48		-0.16'				SPA	discharge rate begins to
		5.0			230.54		6.02'		178		SPA	178 (6.5 min 1241)
		55.0			230.33		5.81'		170		SPA	27 min 1326
		65.5			230.40		5.83'		169		SPA	70 min 1399
		120			230.44		5.82'		170		SPA	121.5 min 1487
		150			230.44		5.82'		170		SPA	150.5 min 1537
		180			230.44		5.82'		171		SPA	180.5 min 1589
		210			230.44		5.82'		170		SPA	210 min 1638
		240			230.44		5.82'		170		SPA	240.5 min 1692
		270			230.44		5.82'		171		MAC	270 min 1743
		300			230.45		5.83'		171		MAC	301 min 1795
		330			230.45		5.83'		170		MAC	335 min 1852
		360			230.46		5.84'		170		MAC	360 min 1912
		390			230.48		5.86'		171		MAC	391 min 1969
		420			230.48		5.86'		169		MAC	420 min 2022
		450			230.50		6.04'		172		MAC	452 min 2076
		480			230.53		6.11'		173		MAC	480 min 2140
		510			230.53							
		540			230.53							
		570			230.53							
		600			230.53							
		630			230.53							
		660			230.53							
		690			230.53							
		720			230.53							
		750			230.53							
		780			230.53							
		810			230.53							
		840			230.53							
		870			230.53							
		900			230.53							
		930			230.53							
		960			230.53							
		990			230.53							
		1020			230.53							
		1050			230.53							
		1080			230.53							
		1110			230.53							
		1140			230.53							
		1170			230.53							
		1200			230.53							
		1230			230.53							
		1260			230.53							
		1290			230.53							
		1320			230.53							
		1350			230.53							
		1380			230.53							
		1410			230.53							
		1440			230.53							
		1470			230.53							
		1500			230.53							
		1530			230.53							
		1560			230.53							
		1590			230.53							
		1620			230.53							
		1650			230.53							
		1680			230.53							
		1710			230.53							
		1740			230.53							
		1770			230.53							
		1800			230.53							
		1830			230.53							
		1860			230.53							
		1890			230.53							
		1920			230.53							
		1950			230.53							
		1980			230.53							
		2010			230.53							
		2040			230.53							
		2070			230.53							
		2100			230.53							
		2130			230.53							
		2160			230.53							
		2190			230.53							
		2220			230.53							
		2250			230.53							
		2280			230.53							
		2310			230.53							
		2340			230.53							
		2370			230.53							
		2400			230.53							
		2430			230.53							
		2460			230.53							
		2490			230.53							
		2520			230.53							
		2550			230.53							
		2580			230.53							
		2610			230.53							
		2640			230.53							
		2670			230.53							
		2700			230.53							
		2730			230.53							
		2760			230.53							
		2790			230.53							
		2820			230.53							
		2850			230.53							
		2880			230.53							
		2910			230.53							
		2940			230.53							
		2970			230.53							
		3000			230.53							
		3030			230.53							
		3060			230.53							
		3090			230.53							
		3120			230.53							
		3150			230.53							
		3180			230.53							
		3210			230.53							
		3240			230.53							
		3270			230.53							
		3300			230.53							
		3330			230.53							
		3360			230.53							
		3390			230.53							
		3420			230.53							
		3450			230.53							
		3480			230.53							
		3510			230.53							
		3540			230.53							
		3570			230.53							
		3600			230.53							
		3630			230.53							
		3660			230.53							
		3690			230.53							
		3720			230.53							
		3750			230.53							
		3780			230.53							
		3810			230.53							
		3840			230.53							
		3870			230.53							
		3900			230.53							
		3930			230.53							
		3960			230.53							
		3990			230.53							
		4020			230.53							
		4050			230.53							
		4080			230.53							
		4110			230.53							
		4140			230.53							
		4170			230.53							
		4200			230.53							
		4230			230.53							
		4260			230.53							
		4290			230.53							
		4320			230.53							
		4350			230.53							
		4380			230.53							
		4410			230.53							
		4440			230.53							
		4470			230.53							
		4500			230.53							
		4530			230.53							
		4560			230.53							
		4590			230.53							
		4620			230.53							
		4650			230.53							
		4680			230.53							
		4710			230.53							
		4740			230.53							
		4770			230.53							
		4800			230.53							
		4830			230.53							
		4860			230.53							
		4890			230.53							
		4920										

AQUIFER TEST SUMMARY FOR WELL 299-E27-10

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 216 ft. Bottom: 240 ft.

Depth of Screened Interval in Pumped Well, Top: 230 ft. Bottom: 240 ft.

Observation Well Used: 299-E26-1 Distance to Pumped Well: 280 ft.

Elevation (Depth) of Screened Interval, Top: 217 ft. Bottom: 227 ft.

Date of Test: 08/11/88

Start Time of Test: 1400 hr

Pumping Rate: 105 gpm

Duration of Test: 480 min

Pre-test Water-Level Elevation (Depth): 216.10 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Recovery (Cooper and Jacob 1946)	35,000	1,500	NA

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The drawdown data are invalid because the discharge rate was not constant during the initial part of the test. Draw-down was negligible in the observation well.

RCRA WELL 299-E27-10
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/11/87

Aquifer Test Data

page 1 of 1

Date for Well 279-E 27-10

Pumping Well 299-E 27-10

Observation Wells 299-E 26-1

Location 200 East RCR

Type of Aquifer Test CONSTANT-DISCHARGE DEVELOPMENT

How Q Measured FLOW METER / BUCKET / 55 gal drum

How W.L.'s Measured P-TAPE TRANSDUCER Depth of Pump/Airline 242.5'

Rad./Dist. of/From Pumping Well _____

Pump On: date 8/11/87 time _____

Meas. Point for W.L.'s 7' 3" 1/2" 1/2" well

Pump Off: date 8/11/87 time _____

Elevation of Meas. Point 2.4' above land

Duration of Aquifer Test _____

Time			Water Level Data				Discharge		Recorded By	Comments
t = _____ at r = 0			Static Water Level <u>218.5</u>				Read- ing Q			
Day	Clock Time	t	Reading	Conversions or Corrections	Water Level	s of s				
8/11	11:40	0	218.5							
		.5								
		1						86		according to digital readout
		1.5	219.05							
		2						86.1		
		2	220.05							
		4	220.07							
		5	220.03							
		7	220.01					85.9		
		9						84.3		
		11	219.93					82.2		
		13								
		15	219.92					83.0		
		20	219.94					82.2		
		25	219.93					81.4		
		30	219.95					81.4		
		35	219.93					81.4		
		40	219.94					82.1		
		45	219.94					81.8		
		50	219.96					82.1		
↑		60	219.95					82.2		
		1:00								
		1								
		1:30	220.36							noise reduction - 5
		2	220.35					102		
		3								
		4	220.38							
		5	220.33							
		7	220.31					103		
		9	220.33					102		
		15	220.3					103		
		20	220.35					103		
		25	220.35							
		30								
Recovery		1:30	218.6							Recovery
		1	218.60							
		1:30								
		2	218.59							
		3	218.59					58200		

Recovery

Recovery

5 218.57

9 218.56

15 218.56

E-65

change to 100 gal

20 218.53
25 218.54
30 218.51

Aquifer Test Data

page 1 of 2

Date for Well 299-E27-10

Pumping Well 299-E27-10

Observation Wells 299-E26-1

Location 200 East RCR

Type of Aquifer Test Constant Discharge

How Q Measured Flow Meter (G.C. Meter)

How W.L.'s Measured E-Tape

Rad./Dist. of From Pumping Well _____

Meas. Point for W.L.'s Top Stilling Pipe 2, 4'

Elevation of Meas. Point _____

Depth of Pump/Absorber 242.5'

Pump On: date 8/11/87 time 14:00 hrs

Pump Off: date 8/11/87 time 22:00 hrs

Duration of Aquifer Test 8 hr

Time			Water Level Data			Discharge		Recorded By	Comments
Day	Clock Time	1' 1' 1/2'	Static Water Level <u>218.50</u>	Reading	Conversions or Corrections	Water Level	Reading		
8/11	14:05	0		218.50		0	222.00	CS	
	14:10			220.50		2.0	113	CS	Discharge Flowmeter
	1			220.50		1.9	112	CS	(not absolute discharge rate)
	1:20			220.35		1.85	109	CS	
	2			220.39		1.89	107	CS	
	3			220.41		1.91	106	CS	
	4			220.32		1.83	105	CS	
	5			220.3		1.80	103	CS	
	6			220.33		1.83	103	CS	
	7			220.31		1.81	104	CS	
	8			220.32		1.83	104	CS	
	9			220.35		1.85	104	CS	
	10			220.37		1.87	104	CS	
	11			220.36		1.86	104	CS	
	12			220.37		1.87	104	CS	
	13			220.39		1.89	104	CS	
	14			220.32		1.87	104	CS	
	15			220.39		1.89	104	CS	
	16			220.40		1.90	104	CS	
	17			220.39		1.89	104	CS	
	18			220.39		1.89	104	CS	
	19			220.39		1.89	104	CS	
	20			220.40		1.90	104	CS	
	21			220.40		1.90	104	CS	
	22			220.41		1.91	104	CS	
	23			220.39		1.89	104	CS	220.7 min
	24			220.40		1.90	104	CS	81300 220.40 min
	25			220.40		1.90	104	CS	
	26			220.41		1.91	104	CS	
	27			220.41		1.91	105	CS	
	28			220.42		1.92	104	CS	
	29			220.40		1.90	104	CS	
	30			220.40		1.90	104	CS	108400 220.40

Aquifer Test Data

page 1 of 1

Date for Well 299-626-1

Pumping Well 299-627-10

Observation Wells 299-626-1

Location 200 East 2nd

Type of Aquifer Test Constant Discharge

How Q Measured Flow Meter (Oral)

How W.L.'s Measured E-Tape

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s T/C

Elevation of Meas. Point

Depth of Pump/Airpipe 242.5

Pump On: date 9/1/87 time 14:15

Pump Off: date 9/1/87 time

Duration of Aquifer Test

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>210.61</u>					Reading			
Day	Clock Time	t	t'	Reading	Conversion or Corrections	Water Level	s or s'		Reading	Q		
	0930			210.61								
	1030			210.61								
	1224			210.60								
	1415	0										Start + Constant
	1438	23		210.59							CSG	Discharge test.
	1512	57		210.60							CSG	
	1549	36		210.61							CSG	
	1630	120		210.61							CSG	
	1657	150		210.62							CSG	
	1732	186		210.62							CSG	
	1753	216		210.62							CSG	
	1822	246		210.62							CSG	
	1852	276		210.62							CSG	
	1922	306		210.62							CSG	
	2022	366		210.63							CSG	
	2122	426		210.63							CSG	
	2216	720		210.63							CSG	Rainy
		15		210.62							CSG	
		55		210.61							CSG	
		31		210.60							CSG	

AQUIFER TEST SUMMARY FOR WELL 299-E28-27

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 273 ft. Bottom: 310 ft.

Depth of Screened Interval in Pumped Well, Top: 291 ft. Bottom: 301 ft.

Date of Test: 09/29/87

Start Time of Test: 1200 hr

Pumping Rate: 136 gpm

Duration of Test: 240 min

Pre-test Water-level Elevation (Depth): 272.96 ft.

Water-level depth at maximum drawdown: 273.05 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>48,000	>1,300

Remarks: The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 136 gpm; therefore, the estimate of transmissivity (48,000 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis.

Aquifer Test Data

page 1 of 2

Data for Well 299-E38-27

Pumping Well _____

Observation Wells _____

Location 200 EAST BCRA PROJECT

Type of Aquifer Test STEP - DRAWDOWN

How Q Measured 0.12-125 Flow Meter

How W.L.'s Measured E-TAPE # 10998

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s Top of Stilling Pipe

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 9/29/87 time 10:10

Pump Off: date 9/29/87 time 11:40

Duration of Aquifer Test _____

Time t = 10:25 at r' = 0				Water Level Data Static Water Level <u>275.34'</u>					5833 Discharge		Recorded By	Comments
Day	Clock Time	m. ft. 1'	1'	1/1'	ft Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	gpm Q		
	10:10	2			275.35					170	CSE	
		5			275.41							
		1			275.43					122		
		15			275.40					126		
		2			275.36					60		
		3			275.38					55		
		4			275.41					55		
		5			275.40							
		7			275.38					58.7		
		9			275.40					58.8		
		11			275.37							
		13			275.40					55.4		
		15			275.40					57.9		
		20			275.43					112		Increase Q = 120
		25			275.43					120		
		30			275.43					120		
		35			275.43					120		
		40			275.41					121		
		45			275.40					120		
		50			275.40					121		
		62			275.40					135		Increase Q = 135
		70			275.40					126		
		80			275.40					124		
		80	0		.4							
		90.5	.5	121	.32							
		91	1	91	.32							
		91.5	1.5		.30							
		92	2		.35							
		93	3		.35							
		94	4		.35							
		95	5		.33.24							
			7		.3							
			9									
			11									
			13									
			15									

valve open all the way.

page 2 of 2

Pumping Well 299-E28-27

Observation Wells _____

Type of Aquifer Test step drawdown / constant discharge

How Q Measured digital thermometer

How W.L.'s Measured E-tape

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 9/29/87 time

Pump Off: date 9/29/22 time

Duration of Aquifer Test _____

E.19

Aquifer Test Data

page 1 of 1

Date for Well 299-F 28-27

Pumping Well 299-F 28-27

Observation Wells

Location 300 EAST 28th

Type of Aquifer Test Constant Discharge

How Q Measured Dig. in Flowmeter

How W.L.'s Measured E. Tape

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s T/S in W. Pile 2.38

Elevation of Meas. Point

Depth of Pump/Airpipe 2.38' NW L-2

Pump On: date 9/29/82 time 12:00

Pump Off: date 9/29/82 time 16:00

Duration of Aquifer Test 4 hr

Time			Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0			Static Water Level <u>275.34</u>								
Day	Clock Time	t	t'	1/2'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
9/29	12:00	0			275.34						START TEST
	1:30				275.39						
	2				275.41				151		
	1:30				275.37						
	2				275.33				149		
	3				275.30						
	4				275.41				140		
	5				275.42				594220 136		
	7				275.43				136		
	9				275.43	max 11	.09				
	11				275.39				137		
	13				275.35						
	15				275.36				137		
	20				275.37						
	25				275.39				136		
	30				275.40				136		
	35				275.37						
	40				275.36				136		
	45				275.37						
	50				2						
	60				275.31				136		
	70				275.31				136 C50		
	80				275.30				136 C50		
	90				275.30				136 C50		
	100				275.30				136 C50		
	110				275.30				136 C50		
	120				275.31				136 C50		
	150				275.30				136 C50		
	180				275.30				136 C50		
	210				275.27				136 SPA		
	240	0									STOP PUMP
	1:30				275.20						
	2				275.21						
	1:30				275.21						
	2				275.21						
	3				275.20						
	4				275.20						
	5				275.19						
	7				275.19						

AQUIFER TEST SUMMARY FOR WELL 299-E32-2

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 262 ft. Bottom: 287 ft.

Depth of Screened Interval in Pumped Well, Top: 279 ft. Bottom: 289 ft.

Date of Test: 09/08/87

Start Time of Test: 0930 hr

Pumping Rate: 127 gpm

Duration of Test: 420 min

Pre-test Water-level Elevation (Depth): 262.53 ft.

Water-level depth at maximum drawdown: 262.70 ft.

Remarks: The drawdown data are invalid because the discharge rate was not constant during the initial part of the test. Also, the aquifer was not stressed sufficiently.

Aquifer Test Data

page 1 of 3

Data for Well 299-E32-2

Pumping Well 299-E32-2

Observation Wells None

Location 200EAST 299-E32-2

Type of Aquifer Test STEP DRAWDOWN

How Q Measured Direct Flow Meter 900T, Ser #020842

Bottom of pump at 280' in hole

How W.L.'s Measured 5-Tube # 11044

Depth of Pump/Airpipe at 277.5'

Rad./Dist. of/From Pumping Well _____

Pump On: date 9/12/87 time 1427

Mess. Point for W.L.'s TOP OF STILLING WELL 22' above casing

Pump Off: date 9/14/87 time 1830

Elevation of Mess. Point _____

Duration of Aquifer Test _____

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>265.46'</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'		Reading	Q		
9/14/87	1400				0		265.46'		4008	0	PRB	
	1427						265.53			23.5		
	1428						265.51			22.8		
	1429						265.5			20.9		
	1428.5						265.48			20.4		
	1429						265.49			20.2		
	1430						265.50			19.2		
	1431						265.49			19.0		
	1432						265.51			18.2		
	1433						265.48		4008	17.0		
	1435						265.51			21.7		
	1437						265.50		4009	20.7		
	1439						265.52			17.9		
	1441						265.5			20.1		
	1442						265.52		4010	20.9		
	1448						265.53		4011	20.3		
	1453						265.49			20.2		
	1458						265.50		4013	18.4		
	1503						265.48		4014	18.5		
	1508						265.47		4015	19.7		
	1512						265.47		4016	19.8		
	1518						265.47		4017	19.3		14.2 seconds extra in 5 min on bucket.
	1523						265.49		4018	19.4		
	1528						265.49		4019	19.1		
	1539						265.49		4021	18.3		
	1542						265.48			50.3		
	1542.5						265.46			49.6		
	1543						265.48			48.0		
	1543.5						265.48			50.9		
	1544						265.48		4023	50.4		
	1545						265.48			51.4		
	1546						265.50			50.5		
	1548						265.49			51.4		
	1550						265.47			51.0		
	1552						265.46			49.4		
	1554						265.50		4028	50.5		
	1556						265.48		4029	50.3		
	1601						265.48		4031	50.4		
	1606						265.49		4034	49.0		

Aquifer Test Data

page 2 of 3

Data for Well 299-E32-2

Pumping Well 299-E32-2

Observation Wells NINE

Location 200 EAST 299-E32-2

Type of Aquifer Test STEP DRAWDOWN

How Q Measured Digital Flow Meter Ser. # 020842

Bottom of Pump at 280' Inlet

How W.L.'s Measured EL+32 F11044

Depth of Pump/Airpipe 277.5'

Rad./Dist. of/From Pumping Well _____

Pump On: date 9/4/87 time 1427

Meas. Point for W.L.'s Top of 16" dia well 2' above 6" casing

Pump Off: date 9/4/87 time 1930

Elevation of Meas. Point _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level _____							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'	Reading	Q		
9/4/87	1611						265.39	4036	49.2		
9/4/87	1620						265.42	4041	49.2		
9/4/87	1627						265.45	4045	49.2		
9/4/87	1630						265.47	4047	49.2		
9/4/87	1631						265.49	4049	49.2		
9/4/87	1632						265.50	4050	49.2		
9/4/87	1634						265.51	4051	49.2		
9/4/87	1636						265.50	4053	49.2		
9/4/87	1638						265.51	4055	49.2		
9/4/87	1640						265.49	4052	49.2		
9/4/87	1645						265.52	4051	49.2		
9/4/87	1651						265.51	4052	49.2		
9/4/87	1655						265.50	4052	49.2		
9/4/87	1700						265.52	4051	49.2		
9/4/87	1705						265.53	4051	49.2		
9/4/87	1710						265.53	4053	49.2		
9/4/87	1715						265.53	4051	49.2		
9/4/87	1720						265.53	4055	49.2		
9/4/87	1725						265.53	4055	49.2		
9/4/87	1730						265.53	4057	49.2		changed Q at 1730.5
9/4/87	1735						265.53	4057	49.2		
9/4/87	1740						265.57	4059	49.2		
9/4/87	1745						265.59	4060	49.2		
9/4/87	1750						265.62	4062	49.2		
9/4/87	1755						265.63	4063	49.2		
9/4/87	1800						265.60	4065	49.2		
9/4/87	1805						265.62	4065	49.2		
9/4/87	1810						265.61	4061	49.2		
9/4/87	1815						265.61	4062	49.2		
9/4/87	1820						265.61	4062	49.2		
9/4/87	1825						265.61	4062	49.2		
9/4/87	1830						265.61	4062	49.2		
9/4/87	1835						265.61	4062	49.2		
9/4/87	1840						265.61	4062	49.2		
9/4/87	1845						265.61	4062	49.2		
9/4/87	1850						265.61	4062	49.2		
9/4/87	1855						265.61	4062	49.2		
9/4/87	1900						265.61	4062	49.2		
9/4/87	1905						265.61	4062	49.2		
9/4/87	1910						265.61	4062	49.2		
9/4/87	1915						265.61	4062	49.2		
9/4/87	1920						265.61	4062	49.2		

Aquifer Test Data

page 1 of 2

Data for Well 299-32-2

Pumping Well 299-32-2

Observation Wells _____

Location 200 RCR A EAST

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TAPE / TRANSDUCER Depth of Pump/Airpipe 293'

Rad./Dist. of/From Pumping Well _____ Pump On: date 9/8/87 time 0930

Meas. Point for W.L.'s T/STILLING APR 6.73' USD Pump Off: date 9/8/87 time 1630

Elevation of Meas. Point _____ Duration of Aquifer Test 7 hr

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>265.36'</u> ^{MP}					Reading	Q		
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'					
9/8	0930	0											
		1:20			255.42			0.16					
		1											
		1:30			261.42			0.16		4191	125		419100
		2			261.42	max. 22		.17					
		3			261.40			0.14		4192	125		
		4			261.41			0.15		4192	125		
		5			261.40			0.14					Flow rate decreased +
		8			265.38			0.12		4189	125		-170 gpm to maintain constant discharge
		11			265.40			0.14		4193	125		
		13			265.39			0.13			127 CSE		
		15			265.40			0.14			125 CSE		
		20			265.37			0.11			127 CSE		
		25			265.36			0.10			123 CSE		
		35			265.37			0.11			125 CSE		
		40			265.38			0.12			127 CSE		
		45			265.39			0.13			127 CSE		
		50			265.40			.14			127 CSE		
		60			265.40			0.14			125 CSE		
		70			265.38			0.12			126 CSE		
		80			265.37			0.11			126 CSE		
		90											
		100			265.36			0.10			127 CSE		
		110			265.35			0.09			126 CSE		
		120			265.35			0.09			126 CSE		
		150			265.34			0.08			127 CSE		
		180			265.34			0.08			128 CSE		
		210			265.33			0.07			128 CSE		
		240			265.30			0.04			126 CSE		
		270			265.39			0.13			127 CSE		
		300			265.39			0.13			126 CSE		
		360			265.30			0.04			127 CSE		
		420			265.36			0.10		4734	128 CSE		432400

Aquifer Test Data

page 2 of 2

Data for Well 299-E32-2

Pumping Well 299-E32-2

Observation Wells _____

Location 200 RCRA EAST

Type of Aquifer Test CONSTANT DISCHARGE - RECOVERY

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/STILLING PIPE 272' LSD

Elevation of Meas. Point _____

Depth of Pump/Airpipe 293'

Pump On: date 9/8/82 time 0730

Pump Off: date 9/8/82 time 1430

Duration of Aquifer Test 7 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>265.26</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
		0:00	0	265.30						CS	Recovery
		0:30									
		1:00		265.11							
		1:30									
		2:00		265.12							
		2:30									
		3:00		265.08							
		3:30		265.07							
		4:00		265.11							
		4:30									
		5:00									
		5:30									
		6:00									
		6:30									
		7:00									
		7:30									
		8:00									
		8:30									
		9:00									
		9:30									
		10:00									
		10:30									
		11:00									
		11:30									
		12:00									
		12:30									
		13:00									
		13:30									
		14:00									
		14:30									
		15:00									
		15:30									
		16:00									
		16:30									
		17:00									
		17:30									
		18:00									
		18:30									
		19:00									
		19:30									
		20:00									
		20:30									
		21:00									
		21:30									
		22:00									
		22:30									
		23:00									
		23:30									
		24:00									
		24:30									
		25:00									
		25:30									
		26:00									
		26:30									
		27:00									
		27:30									
		28:00									
		28:30									
		29:00									
		29:30									
		30:00									
		30:30									
		31:00									
		31:30									
		32:00									
		32:30									
		33:00									
		33:30									
		34:00									
		34:30									
		35:00									
		35:30									
		36:00									
		36:30									
		37:00									
		37:30									
		38:00									
		38:30									
		39:00									
		39:30									
		40:00									
		40:30									
		41:00									
		41:30									
		42:00									
		42:30									
		43:00									
		43:30									
		44:00									
		44:30									
		45:00									
		45:30									
		46:00									
		46:30									
		47:00									
		47:30									
		48:00									
		48:30									
		49:00									
		49:30									
		50:00									
		50:30									
		51:00									
		51:30									
		52:00									
		52:30									
		53:00									
		53:30									
		54:00									
		54:30									
		55:00									
		55:30									
		56:00									
		56:30									
		57:00									
		57:30									
		58:00									
		58:30									
		59:00									
		59:30									
		60:00									

AQUIFER TEST SUMMARY FOR WELL 299-E32-3

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the Hanford and Ringold Formations in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery ()

Hydrogeologic Unit Tested: Hanford formation/Ringold Formation

Depth of Formation, Top: 270 ft. Bottom: 310 ft.

[Hanford 270 - 299 ft; Ringold 299 - 310(?) ft]

Depth of Screened Interval in Pumped Well, Top: 291 ft. Bottom: 301 ft.

Observation Well Used: 299-E32-2 Distance to Pumped Well: 314 ft.

Elevation (Depth) of Screened Interval, Top: 258 ft. Bottom: 278 ft.

Date of Test: 08/07/88

Start Time of Test: 1320 hr

Pumping Rate: 107 gpm

Duration of Test: 225 min

Pre-test Water-level Elevation (Depth): 270.08 ft.

Water-level depth at maximum drawdown: 277.28 ft.

Remarks: The drawdown data are invalid because the discharge rate was not constant during the initial part of the test. Also, the data indicate that well entrance loss occurred. No response was observed in the observation well. Also, the aquifer lies within both the Hanford and Ringold Formations.

page 1 of 3

Data for Well 299-E32

Pumping Well

Observation Wells 299-13:

Location 299-E32-3 200 EAST

Type of Aquifer Test STEP DRAWDOWN

How Q Measured *D.O. & Flowing in gel 900T Ser # 020842*

How W.L.'s Measured E-Type #15178

Rad./Dist. of/From Pumping Well

Depth of Pump/Airpipe Surface, Inlet at 239.

Pump On: date 9/1/87 time 1137

Meas. Point for W.L.'s Top of stilling well, 1.92' above

Pump Off: date _____ time _____

Elevation of Meas. Point.

Duration of Aquifer Test

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>271.92</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
9/1/87	1137						271.92		3105			
	1143						273.12					Discharge fluctuating from 100 gpm to 0 gpm.
	1146						272.92		3108			Discharge fluctuating between 0 & 20 gpm.
	1152						272.36		3114			Discharge fluctuating between 0 & 20 gpm.
	1154						272.27			20.2		Discharge steady at ~20 gpm.
	1156						272.30		3110	20.0		
	1158						272.27		3112	20.2		
	1200						272.27		3112	20.0		
	1203						272.27		3112	20.0		
	1204						272.3		3113	19.4		
	1206						272.27		3113	20.3		
	1208						272.27		3114	20.2		
	1210						272.27		3114	19.7		
	1215						272.24		3115	19.2		
	1220						272.23		3116	19.3		Soil in bucket measurement 17.9 gpm
	1225						272.24		3117	19.2		
	1230						272.23		3118	19.3		
	1235						272.24		3119	19.3		
	1236.5						273.07			51.4		
	1237						273.07			51.3		
	1237.5						273.09			50.9		
	1238						273.07			50.7		
	1239						273.04			50.2		
	1240						273.04		3121	49.3		
	1241						273.03			50.4		
	1243						273.04		3123	49.7		
	1245						273.04		3124	50.0		
	1247						273.01		3125	50.1		
	1249						273.02		3126	50.4		
	1251						273.02		3127	50.3		Soil in bucket measurement 45.2

Aquifer Test Data

page 2 of 3

Data for Well 299-E32-3

Pumping Well 299-E32-3

Observation Wells 299-E32-2

Location 299-E32-3 500 EAST

Type of Aquifer Test Step Drawdown

How Q Measured _____

How W.L.'s Measured E-tube = 10.72

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s Top of SL, 11.00 well, 1.92 above

Elevation of Meas. Point _____

Depth of Pump/Airpipe Bottom of pump at 282.420 low

Pump On: date 9/1/87 time 11:37

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>271.92'</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q			
11/1	1256						273.01		312.9	50.4			
	1301						273.02		313.2	49.4			
	1306						273.03		313.4	49.8			
	1311						273.00		313.7	50.0			
	1316						273.00		313.9	50.1			
	1322						273.00		314.2	49.7			
	1326						273.00		314.4	49.7			
	1326						273.00		314.9	49.6			
	1327						275.25			10.4			
	1328						275.20			99.2			
	1328.5						274.86			94.2			
	1339						274.93			94.0			
	1345						275.04			94.7			
	1340						275.17			96.6			
	1340.5						275.18			99.0			
	1341						275.25			99.6			
	1343						275.23		315.6	99.1			
	1345						275.25		315.9	10.1			
	1349						275.23		316.0	10.1			
	1350						275.25		316.2	10.1			
	1351						275.26		316.5	10.1			
	1357						275.25		317.0	99.4			
	1402						275.25		317.6	10.0			
	1406						275.26		318.0	99.8			
	1411						275.24		318.4	10.0			
	1416						275.24		318.9	98.7			
	1421						275.22		319.4	90.3			
	1426						275.22		319.9	99.4			
	1430						275.22		320.4	99.2			
	1433.5						278.50			150			
	1438						278.51			150			
	1439.5						278.57			151			
	1439.7						278.59			150			
	1439.5						278.59			150			
	1440.7						278.53			149			
	1440.5						278.49			149			
	1441.0						278.46		321.7	149			
	1443						278.44		322.0	148			
	1445						278.44		322.2	148			

Aquifer Test Data

page 1 of 1

Data for Well 299-E32-2

Pumping Well 299-E32-3

Observation Wells 2-E32-2

Location 200 EAST RCRA

Type of Aquifer Test STEP D2

How Q Measured 5 gal. bucket/digital Flowmeter

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s Tk 2.33' above L22

Elevation of Meas. Point _____

Depth of Pump/Airpipe 290' Below L22

Pump On: date 2/2/87 time 0735

Pump Off: date 2/2/87 time _____

Duration of Aquifer Test _____

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>264.87</u> T/c								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
	1205				264.87								
	1220									17.9		5 gal. calib. bucket	
	1235				264.89							increased	
	1235											discharge to 50	
	1240				264.88								
	1245				264.88								
	1250									45.8		5 gal / 6.37 5/6.72	
	1255				264.87								
	1310				264.87								
	1315				264.85					45.4		5 gal / 6.66 5 gal / 6.35	
	1345				264.85							Now pumping 10	
	1355				264.84								
	1415									106			
	1420				264.84								
											</		

Aquifer Test Data

page 1 of 3

Observation
Well

Data for Well 299-E32-2

Pumping Well 299-E32-3

Observation Wells 299-E32-2

Location 290 EAST RCR

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well 314'

Meas. Point for W.L.'s T/C 2.33' AB/ L50

Elevation of Meas. Point _____

Depth of Pump/Airline 290' Below L50

Pump On: date 7/2/87 time 07:35

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time			Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0			Static Water Level					Reading	Q		
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'			
		0			264.90					ST	Steve Tegen C.S. CLINE
		:30			264.90						
	1				264.89						
	1:30				264.90						
	2				264.90						
	3				264.90						
	4				264.90						
	5				264.89						
	7				264.90						
	9				264.90						
	11				264.90						
	13				264.90						
	15				264.90						
	20				264.91					V	
	25				264.89					CSC	
	30				264.90					CSC	
	35				264.90					CSC	
	40				264.89					CSC	
	45				264.90					CSC	
	50				264.90					CSC	
	60				264.89					CSC	
	70				264.90					CSC	
	80				264.90					CSC	
	90				264.89					CSC	
	100				264.89					CSC	
	110				264.90					CSC	
	120				264.90					CSC	
	150				264.88					CSC	w. not picking up
	180				264.88					CSC	
	210				264.87					CSC	
	240				264.86					CSC	
	270				264.86					CSC	
	300				264.86					CSC	
	360				264.85					CSC	
	420				264.87					CSC	
	450				264.87					CSC	
	480				264.87					CSC	
	50				254.86					CSC	Recovery

Aquifer Test Data

page 2 of 3

Data for Well 299-632-3

Pumping Well 299-632-3

Observation Wells 299-632-2

Location 200 East RCRA

Type of Aquifer Test Constant Discharge

How Q Measured Digital Flowmeter

How W.L.'s Measured E-tape / transducer

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s +Grilling 7 IPS

Elevation of Meas. Point _____

Depth of Pump/Airpipe 290' Below L.S.D

Pump On: date 7/2/87 time 0735

Pump Off: date 7/2/87 time 1535

Duration of Aquifer Test 8 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>272.00 T/Am</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or f	Read- ing	Q		
	0735	0					0				STARTED TEST
		1:30									
		1							160		
		1:30									
		2									
		3							163		
		4		278.75	" 7.75/2	278.65	6.65				
		5		278.75	" 7.5/2	278.63	6.63				
		7							150		
		9							154		
		11		278.64		278.64	6.64				
		13							153		
	0750	15		278.64		278.64	6.64		153	SSC	
		20		278.64		278.64	6.64		152	SSC	
		25		278.60		278.60	6.60		152	SST	
		30		278.50		278.50	6.50		151	SST	
		35		278.55		6.55			151	SST	Valve wide open
		40		278.55		6.55			149	SST	GPM fluctuating bet. 149-151
		45		278.54		6.54			150	SST	" "
		50		278.53		6.53			151	SST	" "
		60		278.50		6.50			151	SST	" "
		70		278.50		6.50			151	SST	" "
		80		278.40		6.40			149	SST	GPM 147-150
		90		278.43		6.43			150	SST	" "
		100		278.45		6.45			148	SST	" "
		110		278.37		6.37			148	SST	" "
		120		278.35		6.35			149	SST	" "
		130		278.31		6.31			149	SST	" "
		140		278.30		6.30			149	SST	" "
		150		278.31		6.31			148	SST	" "
		160		278.38		6.38			149	SST	" "
		170		278.34		6.34			147	SST	GPM 146-149
		180		278.33		6.33			148	SST	
		190		279.24		7.24			163	SST	Collecting water sample
		200		278.42		6.42			149	SST	GPM 147-149
		210		278.30		6.30			147		
		220		278.24		6.24			148		
		230		278.13		6.13			146		

AQUIFER TEST SUMMARY FOR WELL 299-E32-4

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford and Ringold Formations in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation/Ringold Formation

Depth of Formation, Top: 280 ft. Bottom: 320(?) ft.

[Hanford 280 - 297 ft.; Ringold 297 - 320(?) ft]

Depth of Screened Interval in Pumped Well, Top: 298 ft. Bottom: 308 ft.

Date of Test: 09/21/87

Start Time of Test: 1430 hr

Pumping Rate: 27 gpm

Duration of Test: 240 min

Pre-test Water-level Elevation (Depth): 281.63 ft (unknown elevation of measuring point).

Water-level depth at maximum drawdown: 293.96 ft (unknown elevation of measuring point).

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>9,500	>240

Remarks: The drawdown data indicate that well entrance loss occurred. The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 27 gpm; therefore, the estimate of transmissivity (9,500 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis. Also, the aquifer lies within both the Hanford and Ringold Formations.

page _____ of _____

Pumping Well _____

Observation Wells _____

Type of Aquifer Test DEVELOPMENT STEP-DD

How W.L.'s Measured R TAPES TRANSFER Depth of Pump/Airpipe 217' Below 1st

Pump On: date 9/15/97 time

Pump Off: date _____ time _____

Duration of Aquifer Test _____

E.36

Aquifer Test Data

page 1 of 2

Data for Well 299-E32-4

Pumping Well 299-E32-4

Observation Wells _____

Location ZOO EAST RORA

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured B-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s 1/2" STAINLESS PIPE

Elevation of Meas. Point _____

Depth of Pump/Airpipe 297' below

Pump On: date 9/21/82 time 1930

Pump Off: date 9/21/82 time 1930

Duration of Aquifer Test _____

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>291.63'</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'		Reading	Q		
9/21	1400	0			291.63							
		1:30			284.71					14.6		
		1			285.99							
		1:30			286.63							
		2			287.00							
		3			287.40							
		4			287.52							ABORT
		5			287.55					14.2		
		2										restart test
		9										valve not open
		11										from example
		12										
	1430	0			291.63		0			24.8		
		1:30			287.94		6.21					
		1			289.92		8.34					
		1:30			291.65		10.02			23.2		
		2			292.03		10.40					
		1:30			293.19		11.56			27.0		
		4			293.60		11.97					
		5			293.67		12.04					
		7			293.83		12.20			26.7		
		9			293.89		12.26			26.6		
		11			293.92		12.28			26.4		
		13			293.90		12.27			26.3		
		15			293.91		12.28			26.3		
		20			293.87		12.24			26.7		
		25			293.76		12.23			26.7		
		30			293.95		12.32			26.5		Discharge varies
		35			293.96		12.33			26.6		between 26.0 & 27.3
		40			293.88		12.25			26.8		
		45			293.80		12.23			26.6		
		50			293.89		12.26			26.3		
		60			293.78		12.15					
		70										
		80			293.50		11.97			26.4		
		90			293.52		11.98			26.3		
		100			293.52		11.97			26.4		
		110			293.53		11.97			26.7		
		120			293.50		11.97			26.3		

Aquifer Test Data

page 2 of 2

Data for Well 299-E32-4

Pumping Well 299-E32-4

Observation Wells _____

Location 300 EAST RCEA

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TAPE / TRANSOMETER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/STILLING P.B.

Elevation of Meas. Point _____

Depth of Pump/Airpipe 297' Below Pipe

Pump On: date 9/21/87 time 1430

Pump Off: date 9/21/87 time 1830

Duration of Aquifer Test 4 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>291.63'</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
<u>9/21</u>	<u>1700</u>	<u>150</u>		<u>293.51</u>		<u>11.82</u>		<u>26.9</u>	<u>CS</u>		
		<u>180</u>		<u>293.52</u>		<u>11.89</u>		<u>26.5</u>	<u>CS</u>		
		<u>210</u>		<u>293.52</u>		<u>11.89</u>		<u>27</u>	<u>CS</u>		
		<u>240</u>		<u>293.52</u>		<u>11.89</u>		<u>26.6</u>	<u>CS</u>		
		<u>30</u>	<u>491</u>	<u>288.46</u>		<u>12.93</u>		<u>532300</u>			
		<u>1</u>	<u>241</u>	<u>295.60</u>		<u>3.97</u>					
		<u>1:30</u>	<u>191</u>	<u>289.09</u>		<u>2.42</u>					
		<u>2</u>	<u>121</u>	<u>283.09</u>		<u>1.41</u>					
		<u>3</u>	<u>01</u>	<u>282.18</u>		<u>.55</u>					
		<u>4</u>	<u>01</u>	<u>281.36</u>		<u>.23</u>					
		<u>5:54</u>	<u>00</u>	<u>281.67</u>		<u>.04</u>					
		<u>7</u>	<u>55</u>	<u>281.61</u>		<u>-.02</u>					
		<u>9</u>	<u>27</u>	<u>281.59</u>		<u>-.04</u>					
		<u>11</u>	<u>22</u>	<u>281.56</u>		<u>-.07</u>					
		<u>13</u>	<u>19</u>	<u>281.55</u>		<u>-.08</u>					
		<u>15</u>	<u>17</u>	<u>281.54</u>		<u>-.09</u>					
		<u>20</u>	<u>13</u>	<u>281.53</u>		<u>-.10</u>					
		<u>25</u>	<u>12</u>	<u>281.55</u>		<u>-.08</u>					
		<u>30</u>	<u>7</u>	<u>281.55</u>		<u>-.08</u>					
		<u>35</u>	<u>7.9</u>	<u>281.55</u>		<u>-.08</u>					
		<u>40</u>	<u>7</u>	<u>281.56</u>		<u>-.07</u>					
		<u>45</u>	<u>6.3</u>	<u>281.54</u>		<u>-.09</u>					
		<u>50</u>	<u>5.8</u>	<u>281.57</u>		<u>-.09</u>					

Well has been
developed further
or remains be-
static because of
reduced storage i.e.
air in voids

AQUIFER TEST SUMMARY FOR WELL 299-E33-28

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 257 ft. Bottom: 278 ft.

Depth of Screened Interval in Pumped Well, Top: 268 ft. Bottom: 278 ft.

Date of Test: 10/21/87

Start Time of Test: 1200 hr

Pumping Rate: 150 gpm

Duration of Test: 240 min

Pre-test Water-level Elevation (Depth): 257.08 ft.

Water-level depth at maximum drawdown: 257.14 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>53,000	>2,500

Remarks: The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 150 gpm; therefore, the estimate of transmissivity (53,000 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis.

Aquifer Test Data

page 1 of 2

Data for Well 299-E33-28

Pumping Well 299-E33-29

Observation Wells

Location 200 EAST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE DD

How Q Measured FLOW METER DIGITAL DATA INDUSTRIAL MODEL 900T

How W.L.'s Measured E-TAPE / TRANSDUCER

Depth of Pump/Airpipe

Rad./Dist. of/From Pumping Well

Pump On: date 10/21/87 time 1200

Meas. Point for W.L.'s STILLING PIPE 2.93' AW.

Pump Off: date 10/21/87 time 1600

Elevation of Meas. Point LSB

Duration of Aquifer Test 4 hr

Time				Water Level Data				Discharge	Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>260.01</u>						
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level s or s'	Reading	Q	
10/21	1200	0			260.01			63570		SCOPE INDICATOR CB.
	1200	0								E-TAPE = 10998
		1:30			260.03					Pump ON
		1			260.05			150		
		1:30								
		2			260.04					
		3			260.04					
		4			260.05			151		
		5			260.07	MAN. ADJ. 06		150		
		7			260.07			150		
		9			260.05					
		11			260.05					
		13			260.05			151		
		15			260.07			151		
		20			260.03			64830 150		
		25			260.04			149		
		30			260.05			150		
		35			260.04			151		
		40			260.05			150		
		45			260.05			150		
		50			260.05			150		
		60			260.04			64470 149		
		70			260.03			149		
		80			260.03			148		
		90			260.04			150		
		100			260.03			148		
		110			260.04			150		
		120			260.03			149		
		150			260.03			147		
		180			260.0			148		
		210			259.99			148		
		240	0		259.99					
		2:30			260.01					
		1			259.97					
		1:20			259.97					
		2			259.97					
		3			259.96					
		4			259.96					
		5			259.96					

Aquifer Test Data

page 2 of 2

Data for Well 299-E 33-28Pumping Well 299-E 33-28

Observation Wells _____

Location 200 EAST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured E-TAPE / TRANSVERSE

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/Sinking PIPE 2.93' Abu.

Elevation of Mess. Point _____

Depth of Pump/Airpipe _____

Pump On: date 10/21/92 time 1200 hrs

Pump Off: date 10/21/92 time 1600 hrs

Duration of Aquifer Test 2 hr

Time					Water Level Data				Discharge		Recorded By	Comments
$t = 24$ at $t' = 0$					Static Water Level							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'		Reading	Q		
10/21	1607	247	7		259.95							Possible Leaking from pump column
			9		259.94							
			11		259.95							
			13		259.95							
			15		259.95							Transducer no working error
			20		259.95							S/N 0042-1
			25		259.96							Transducer #
			30		259.96							
			45		259.96							

AQUIFER TEST SUMMARY FOR WELL 299-E33-29

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 266 ft. Bottom: 290 ft.

Depth of Screened Interval in Pumped Well, Top: 279.5 ft. Bottom: 289.5 ft.

Date of Test: 09/17/87

Start Time of Test: 1400 hr

Pumping Rate: 145 gpm

Duration of Test: 180 min

Pre-test Water-level Elevation (Depth): 265.83 ft.

Water-level depth at maximum drawdown: 265.93 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>51,000	>2,100

Remarks: The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 145 gpm; therefore, the estimate of transmissivity (51,000 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis.

Aquifer Test Data

Note: all measurements for this test were taken at the middle mark on the E-tape

page 1 of 3

Data for Well 299-E33-29

Pumping Well 299-E33-29

Observation Wells

Location 200 East RCRA

Type of Aquifer Test Step - Drawdown

How Q Measured Digital Flowmeter

How W.L.'s Measured E-tape (#12176)

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s Stilling pipe (2.85' above I.S.)

Elevation of Meas. Point

Depth of Pump/Airpipe 274' (intake)

Pump On: date 9-17-87 time 0902

Pump Off: date 9-17-87 time

Duration of Aquifer Test

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>268.65</u>				Discharge		Recorded By	Flowmeter reading at beginning 24724 Comments stilling pipe bottom @ 270.15
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
9/17	0902	:30			—						SST	20 gpm
		1:00			—							adjusting flow
		1:30			—							
		2			268.45							
		3			268.52							25 gpm
		4			268.64							
		5			268.62							
		7			268.62							
		9			268.60							
		11			268.61							
		13			268.62							
		15			268.60							
		20			268.55							25-29 gpm
		25			268.60							
		30			268.62							
		30			268.63							54 gpm
		1:00			268.63							50 gpm
		1:30			268.61							
		2			268.61							
		3			268.61							
		4			268.59							
		5			268.62							48 gpm
		7			268.62							52 gpm
		9			268.62							54 gpm
		11			268.62							53 gpm
		13			268.63							
		17			268.62							
		20			268.62							
		25			268.63							
		30			268.56							
		35			268.61							
		40			268.59							
		45			268.62							
		50			268.62							
		60			268.62							

Aquifer Test Data

page 2 of 3

Data for Well 249-E33-29

Pumping Well 249-E33-29

Observation Wells —

Location 200 East RCRA

Type of Aquifer Test Step drawdown

How Q Measured Digital Flowmeter

How W.L.'s Measured E-tube (#12176)

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s 7" stilling pipe 2.85' above L.S.

Elevation of Meas. Point —

Depth of Pump/Airpipe 274' (intake)

Pump On: date 9-17-87 time 0902

Pump Off: date 9-17-87 time 1252

Duration of Aquifer Test —

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>268.65</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
9/17	10:32	:30			—					100	SS	100 gpm
		1:00			268.60							
		1:30			268.64							
		2			268.62							
		3			268.60							
		4			—							
		5			268.63							
		7			268.71							
		9			268.61							
		11			—							
		13			268.61							
		15			268.61							
		20			268.62							
		25			268.63							
		30			268.60							
		35			268.60							
		40			268.62							
		45			268.61							
		50			268.60							
		60			268.57							
9/17	11:32	:30			268.64					144		144 gpm
		1:00			268.66							(value wide open)
		1:30			—							
		2			268.67							
		3			268.65							
		4			—							
		5			264.64							
		7			268.60							
		9			268.60							
		11			268.65							
		13			268.62							
		15			268.66							
		20			268.65							
		25			268.67							
		30			268.63							
		35			—							
		40			268.60					143		
		45			268.62							

page 3 of 3

Data for Well 299-E33-29

Pumping Well	11	10	11
--------------	----	----	----

Observation Wells _____

Location 200 East RCRA

Type of Aquifer Test Step-drawdown

How Q Measured Digital Flowmeter

How W.L.'s Measured E-tape (#12176)

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s stilling pipe (2.85' above L.S.)

Elevation of Meas. Point _____

Depth of Pump/Airpipe 274' (intake)

Pump On: date 9-17-67 time 0902

Pump Off: date 9-17-87 time 1252

Duration of Aquifer Test _____

[illegible]

Aquifer Test Data

page 1 of 1

Data for Well 299-E33-29

Pumping Well 299-E33-29

Observation Wells

Location 200 EAST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE DB

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured E-TAPE (#12176)

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s T/P.P. (2.45' above L.S.)

Elevation of Meas. Point

Depth of Pump/Airpipe 374' (intake)

Pump On: date 9-17-87 time 1400:30

Pump Off: date 9-17-87 time

Duration of Aquifer Test

Time					Water Level Data				Discharge		Recorded By	Stilling pipe location @ 270.15 Comments	
t = _____ at t' = 0					Static Water Level <u>268.62</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q			
	1400	0			268.62								
		30			268.30								
		1			268.29								
		2			268.29					155			
		3			268.27					150			
		4			268.26					140			
		5			268.77								
		7			268.75								
		9			268.76					145			
		11			268.77								
		13			268.76					195			
		15			268.78								
		20			268.76					144			Valve wide open
		25			268.76								
		30			268.76								
		35			268.77					145			
		40			268.76								
		45			268.77					145			
		50			268.75								
		60			268.75					144			
		70			268.74								
		80			268.75								
		90			268.75								
		100			268.74					143			
		110			268.73					144-145			
		120			268.72					144-145			
		150			268.73					144-145			
	1700	180	0		268.70				225				Recovery
		110											
		120											
		130			268.71								
		140			268.68								
		150			268.65								
		1100			268.69								
		1130			268.64								
		2			268.64								
		3			268.64								
		4			268.64								
		5			268.64								

7 268.64 13 268.64 35 268.63
9 268.64 15 268.64 40 268.64
11 268.62 25 268.64 50 268.64

AQUIFER TEST SUMMARY FOR WELL 299-E33-30

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 257 ft. Bottom: 279 ft.

Depth of Screened Interval in Pumped Well, Top: 267 ft. Bottom: 277 ft.

Date of Test: 09/24/87

Start Time of Test: 0730 hr

Pumping Rate: 160 gpm

Duration of Test: 218 min

Pre-test Water-level Elevation (Depth): 256.97 ft.

Water-level depth at maximum drawdown: 256.99 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	>56,000	>2,500

Remarks: The aquifer was not stressed sufficiently. The drawdown was not greater than 0.1 ft over one logarithmic time cycle at a discharge rate of 160 gpm; therefore, the estimate of transmissivity (56,000 ft²/d) is a minimum. The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis.

Aquifer Test Data

page 1 of 2

Date for Well 299-E33-30

Pumping Well 299-E33-30

Observation Wells _____

Location 300 EAST DORA

Type of Aquifer Test 3RD DR / DEVELOPMENT

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TAPE / TRANSDUCER

Depth of Pump/Airpipe _____

Rad./Dist. of/From Pumping Well _____

Pump On: date 9/23/97 time _____

Meas. Point for W.L.'s T/STATION 299 'ABV
-50

Pump Off: date _____ time _____

Elevation of Meas. Point _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level _____							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'	Reading	Q		
9/23	17:19	0					259' 7 1/2"				These connecting turn
		.5					259' 8 1/4"				sections of pipe have
		1					259' 7 3/4"				2 kinks in it, possibly
		1.5					259' 7 3/4"				dermatine film
		2					259' 7 3/4"				
		3					259' 8 1/2"	34.1		11R	Left Robinson (ICF)
		4					259' 8"	34.2			
		5					259' 8"	34.2			
		7					259' 7 3/4"	33.5			
		9					259' 8"	33.5			
		11					259' 8"	33.8			
		13					259' 7 3/4"	34.3		1	
		15					259' 7 3/4"	33.2			
		20					259' 8"	10.5			
		25					259' 8 1/4"	10.9			
		30					259' 8 1/4"	110			
		35					259' 8 1/4"	110			
		40					259' 8 1/4"	111			
		45					259' 8 1/4"	112			
		50					259' 8 1/4"	111			
		55					259' 8 1/4"	111			
		60					259' 8 1/4"	110			
		65					259' 8 1/4"	110			
		70					259' 8"	112			
		75					259' 7 3/4"	111			
		80					259' 7 3/4"	109			
		85					259' 7 3/4"	111			
		90					259' 7 3/4"	110			
		95					259' 7 3/4"	110			
		100					259' 7 3/4"	110			
		105					259' 7 3/4"	111			
		110					259' 8 1/4"	112			
		115					259' 8 1/4"	111			
		120					259' 8 1/4"	111			
		125					259' 8 1/4"	111			
		130					259' 8 1/4"	111			
		135					259' 8 1/4"	111			
		140					259' 8 1/4"	111			
		145					259' 8 1/4"	111			
		150					259' 8 1/4"	112			
		155					259' 8 1/4"	111			
		160					259' 8 1/4"	111			
		165					259' 8 1/4"	111			
		170					259' 8 1/4"	111			
		175					259' 8 1/4"	111			
		180					259' 8 1/4"	111			
		185					259' 8 1/4"	111			
		190					259' 8 1/4"	111			
		195					259' 8 1/4"	111			
		200					259' 8 1/4"	111			

Aquifer Test Data

page 7 of 2

Data for Well 299-E22-E7

Pumping Well 299-E22-E0

Observation Wells _____

Location 299-E22-E0

Type of Aquifer Test step drawdown/development

How Q Measured digital flowmeter

How W.L.'s Measured Extape

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s top of skidwell

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date _____ time _____

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level _____							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q	
	1836	5					250' 2 3/4"		149		
		1					250' 2 3/4"		150		
		1.5					250' 2"		152		
		2					250' 2 1/4"		152		
		3					250' 2 1/4"		154		
		4					250' 2 1/4"		155		
		5					250' 2 3/8"		155		
		6					250' 3"		154		
		8					250' 2 5/8"		155		
		11					250' 3"		155		
		12					250' 2 5/8"		155		
	1720						250' 2 5/8"		155		
	20						251' 2 5/8"		155		
	25						250' 2 1/4"		155		
	30						250' 2 1/4"		156		
	35						250' 2 3/8"		156		
	40						250' 3 1/8"		156		
	70						250' 2 3/8"				
Recovery											
		0.5					250' 2 3/8"		—		
		1					250' 2 3/8"				
		1.5					250' 2 3/8"				
		2					250' 2 3/8"				
		3					250' 2 3/4"				
		4					250' 2 3/4"				
		5					250' 2 3/4"				
		7					250' 2 3/4"				
		9					250' 2 1/2"				

Aquifer Test Data

page 1 of 1

Data for Well 299-E33-30

Pumping Well 299-E32-30

Observation Wells _____

Location 200 EAST RCRA

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TATE / TRANSDUCER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s 1/STILLING PIPE 2.67'

Elevation of Meas. Point _____

Depth of Pump/Airline 267' from 1st

Pump On: date 9/24/87 time 0730

Pump Off: date 9/24/87 time 1108

Duration of Aquifer Test 218 min.

Time				Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0				Static Water Level <u>259.64</u>								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
		0			259.64						Transducer probe set below pump in mbl. way to it + screen 22:50 - herding pump, m	
	1:30				259.64							
	1				259.65							
	1:30				259.65							
	2				259.64							
	3				259.64							
	4				259.65				160			160 gpm
	5				259.65							
	7				259.64							
	7				259.64				154			159 gpm
	11:30				259.64						* @ 11:30	
	13				259.64						@ 160gpm	
	15				259.69							
	20				259.66							
	25				259.64							
	20				259.64							
	25				259.63							
	40				259.64							
	45				259.64							
	50				259.64							
	60				259.64					CSC		
	70				259.64					CSC		
	80											
	90				259.64					CSC		
	100				259.64				158	CSC		
	110				259.64				160	CSC		
	120				259.64				154	CSC		
	150				259.64				140	CSC		
	180				259.63				158	CSC		
	200				259.62				58300		TURNED OFF	

AQUIFER TEST SUMMARY FOR WELL 299-E34-2

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 224 ft. Bottom: 241 ft.

Depth of Screened Interval in Pumped Well, Top: 230 ft. Bottom: 240 ft.

Observation Well Used: 299-E34-1 Distance to Pumped Well: 60 ft.

Elevation (Depth) of Screened Interval, Top: 215 ft. Bottom: 230 ft.

Date of Test: 08/07/87

Start Time of Test: 1320 hr

Pumping Rate: 194 gpm

Duration of Test: 225 min

Pre-test Water-level Elevations (Depths):

Pumping well: 223.75 ft.

Observation well: 221.34 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Constant Discharge (Cooper and Jacob 1946)	114,000	6,700	NA
Recovery (Cooper and Jacob 1946)	85,000	5,000	NA

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The constant discharge test was shortened because of generator problems. As a result, the drawdown data from the observation well are insufficient for analysis.

RCRA WELL 299-E34-2
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 8/07/87

$$T = 114,000 \text{ ft}^2/\text{d}$$

$$T = \frac{(2.3)(1440)(194)}{(4)(\pi)(7.48)(.06)}$$

$$Q = 194 \text{ gpm}$$

E.54

RCRA WELL 299-E34-2
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/07/87

$$Q = 194 \text{ gpm}$$

$$T = 85,000 \text{ ft}^2/\text{d}$$

$$T = \frac{(2.3)(1440)(194)}{(4)(\pi)(7.48)(.08)}$$

E.55

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 2

Data for Well 299-534-2

Pumping Well 299-534-2

Observation Wells 299-530-1

Location 000 East Area

Type of Aquifer Test Step drawdown

How Q Measured 2 in. 5 gal. Flowmeter / 5 gal. bucket

How W.L.'s Measured PNL 300' E-TAPE # 11044

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s top of stilling well

Elevation of Meas. Point 2.63' above ground surface

Depth of Pump/Airpipe 233' 9"

Pump On: date 8/1/82 time 0900

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>226.69'</u>							
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
8/1	0835	0		226.69'						KRO	
	0857	0		226.69'						KRO	Pump ON.
		.5		226.96'						KRO	
		1		226.99'				64		KRO	Adjusting Valve
		1.5		226.94'						KRO	
		2		226.73'						KRO	
		2.5		226.71'						KRO	
		3		226.86'				8.6		KRO	
		4		226.71'				22		KRO	
		5		226.73'				201	15.1	KRO	
		7		226.75'					14.9	KRO	
		9		226.73'					14.9	KRO	
		11		226.73'					14.6	KRO	
		13		226.70'					14.7	KRO	11 sec / 5 gal bucket
		15		226.67'					14.4	KRO	(27.3 gpm)
		17		226.73'					14.4	KRO	
		19		226.72'					14.5	KRO	
		21		226.73'					14.4	KRO	
		23		226.71'					14.5	KRO	
		25		226.75'				204	14.4	KRO	12 sec / 5 gal bucket
		30		226.70'				205	14.5	KRO	(25 gpm)
		35		226.72'				205	14.0	KRO	
		40		226.65'				205	14.5	KRO	11 sec / 5 gal bucket
		45		226.70'				207	14.4	KRO	(27.3)
		50		226.71'				207	14.2	KRO	
		60		226.72'					14.2	KRO	Adjust Valve
		60.5		226.71'				14.5		KRO	1'
		61		226.73'						KRO	
		61.5		226.74'				209		KRO	
		62.5		226.70'						KRO	
		63		226.78'				37.8		KRO	
		64		226.78'				30.2		KRO	
		65		226.85'						KRO	
		67		226.80'				30.2		KRO	
		69		226.78'				30.1		KRO	
		71		226.77'				39.9		KRO	
		73		226.77'						KRO	
		75		226.75'				214	30.1	KRO	
		77		226.78'						KRO	5 sec / 5 gal bucket

55 gal / 5 gal bucket
(60 ppm)

Aquifer Test Data

page 2 of 2

Data for Well 299-E34-2

Pumping Well 299-E34-2

Observation Wells 299-E34-1

Location 200 East Area

Type of Aquifer Test Step drawdown

How Q Measured Discharge to water/Fuel bucket

How W.L.'s Measured TALES 500'-TAP #11000

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s top of stilling well

Elevation of Meas. Point 283' above ground surface

Depth of Pump/Airpipe intake at 233' 9"

Pump On: date 8/3/97 time 0900

Pump Off: date time

Duration of Aquifer Test

Time		Water Level Data							Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
		79			224.77						KRD	
		81			226.77						KRD	
		83			226.76						KRD	
		85			226.77				32.4	22.8	KRD	
		90			226.80				31.6	22.7	KRD	
		95			226.75				29.9	22.0	KRD	
		100			226.73				22.1	20.4	KRD	
		105			226.76				23.2	30.3	KRD	4 sec / 5 gal bucket
		110			226.77				22.4	30.0	KRD	
		120			226.77						KRD	Adjusting Valve
		120.5			226.81						KRD	
		121			226.87						KRD	✓
		121.5			226.83				52.1	22.0	KRD	
		122			226.85						KRD	
		123			226.84						KRD	
		124			226.85				51.3	22.0	KRD	
		125			226.85				51.0	22.0	KRD	
		127			226.85				51.0	22.0	KRD	
		129			226.87				51.1	22.0	KRD	
		131			226.87				51.1	22.0	KRD	
		133			226.86				51.4	22.0	KRD	
		135			226.85				23.5	51.5	KRD	SAMPLED WELL
		140			226.85				23.8	50.2	KRD	(1st SAMPLE)
		145			226.87				51.0	22.0	KRD	
		150			226.87				50.9	22.0	KRD	3 sec / 5 gal bucket
		155.5			226.85				50.9	22.0	KRD	100 gpm
		160			226.78				29.3			Generator slow
		165			226.75				30			Fuel Filter
		170										
		183			226.88				42.6			Adjusting Valve
		190			226.84							OFF!
		199			226.84							

Aquifer Test Data

page 1 of 2

Date for Well 299-E34-2

Pumping Well 299-E34-2

Observation Wells 299-E34-1

Location 200 EAST PCRA

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured DIGITAL FLOWMETER / 5 gal bucket

How W.L.'s Measured E-TAPE # 11044

Depth of Pump/Airpipe Intake at 232'

Rad./Dist. of/From Pumping Well _____

Pump On: date 8/7/87 time 1320 hr

Mess. Point for W.L.'s 2" IRON PIPE / 2.82'

Pump Off: date 8/7/87 time 1705

Elevation of Mess. Point REV 480

Duration of Aquifer Test 3.75 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>226.58</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or f	Reading	Q		
8/7	1320	0		226.58			0			CSL	
		30		227.10			.52			CSL	
		1									
		1:30		227.12			.54				
		2		227.10			.52		110	CSL	
		3		227.11			.53				
		4		227.11			.53				
		5		227.10			.52		109	CSL	
		7		227.10			.52		109	CSL	
		9									
		11		227.11			.53		107	CSL	
		13		227.12			.54		107	CSL	
		15		227.13			.55		107	CSL	
		27:00		227.13			.55		107	CSL	
		25		227.14			.56		107	CSL	
		30		227.15			.57		107	CSL	
		35		227.15			.57		106	CSL	
		40		227.14			.56		106	CSL	
		45		227.16			.58		107	CSL	
		50		227.15			.57		107	CSL	
		60		227.16			.58		107	CSL	
		70									
		80		227.15			.57		106.5		
		90		227.15			.57		106		
		100		227.15			.57		107		
		110		227.16			.58		107		
		120		227.16			.58		107		
		150		227.16			.58		107		
		180		227.15			.57		107		
		210		226.94			.36		75		
		1705	225	226.93			.35				
		30		226.65							
		1		226.67							
		1:30		226.65							
		2		226.66							
		3		226.68							
		4		226.62							
		5		226.61							
		7		226.59							

generator
possible
loss

checked with
55 gal drums
55/17 sec
had to cut back
to repair 7 min
55 gal/17 sec
generator
cutting up again
fuel filter

Recovery

Aquifer Test Data

page 2 of 2

Data for Well 299-E34-2
Pumping Well 299-E34-2
Observation Wells 299-E34-1

Location 200 EAST DCRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured DIG. FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE # 11044

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s TOP TANKING 2.83

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 8/7/87 time 1320 hr

Pump Off: date 9/7/87 time 1705 hr

Duration of Aquifer Test 3.75 hr

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>226.52</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
		234	9		226.60					CSC	
			11		226.58					CSC	
			13		226.58					CSC	
			15		226.58					CSC	
			20		226.58					CSC	
			25		226.59					CSC	
			30		226.57					CSC	
			35		226.55					CSC	
			40		226.53					CSC	
			45		226.51					CSC	
			50		226.50					CSC	
			100		226.54	226.54				CSC	

observation
weu

Data for Well 279. ± 34-1

Pumping Well 299-E34-2

Observation Wells 299-234-1

Type of Aquifer Test Step Drawdown

How Q Measured Digital Flowmeter / Seal bucket

How W.L.'s Measured D-11 300'-S-TAPE # 10998 Depth of Pump/Airpipe intake at 233' 9"

Rad./Dist. of/From Pumping Well _____ Pump On: date 8/7/87 time 0900

Meas. Point for W.L.'s top of casing Pump Off: date _____ time _____

Elevation of Meas. Point 2.42' above brass cap Duration of Aquifer Test _____

E.60

Aquifer Test Data

OBSERVATION
WELL

page 1 of 2

Date for Well 299-E24-1

Pumping Well 299-E24-2

Observation Wells

Location 200 EAST RCR4

Type of Aquifer Test CONSTANT-DISCHARGE TEST

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE + 10008

Depth of Pump/Airpipe intake at 235.75'

Rad./Dist. of/From Pumping Well

Pump On: date 5/2/22 time 1320 hr

Meas. Point for W.L.'s T/C 2.42' Adv brace

Pump Off: date time

Elevation of Meas. Point

Duration of Aquifer Test

Time t = _____ at t' = 0				Water Level Data Static Water Level 223.71				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or y'	Read- ing	Q		
		0		223.71			0			KRO	Pumping at
		.5		223.72			.01			KRO	110 gpm
		1		223.73			.02			KRO	
		1.5		223.72			.01			KRO	
		2		223.73			.02			KRO	
		2.5		223.73			.02			KRO	
		3		223.73			.02			KRO	Pumping at
		4		223.73			.02			KRO	107 gpm
		5		223.74			.03			KRO	
		7		223.75			.04			KRO	
		9		223.77			.06			KRO	
		11		223.77			.06			KRO	
		13		223.78			.07			KRO	Pumping at
		15		223.78			.07			KRO	107 gpm
		20		223.78			.07			CSC	
		25		223.78			.07			CSC	
		30		223.79			.08			CSC	
		35		223.79			.08			CSC	
		40		223.79			.08			CSC	
		45		223.80			.09			CSC	
		50		223.80			.09			CSC	
		60		223.80			.09			CSC	
		70									
		80		223.79			.08			CSC	hose blew had to
		90		223.85			.09			CSC	cut back discharge
		100		223.79			.08			CSC	30 gpm for 5 min
		110		223.80			.09			CSC	
		120		223.80			.09			CSC	
		130		223.81			.10			CSC	
		140		223.81			.10			CSC	
		150		223.77			.06			NAC	survivor loading down
		160		223.75			.04			NAC	W

Aquifer Test Data

Observation
Well

page 2 of 2

Data for Well 299-E34-1

Pumping Well 299-E34-2

Observation Wells

Location 200 WEST RRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured DIGITAL FLOWMETER / 55 gal. drum

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe Intake at 233.75 ft

Rad./Dist. of/From Pumping Well

Pump On: date 9/7/87 time

Meas. Point for W.L.'s TOP CASING / 3.42' ASV has Pump Off: date time

Elevation of Meas. Point cat Duration of Aquifer Test

Time t = at t' = 0				Water Level Data Static Water Level				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
	12:5	0				233.75					
		5	ASV			233.75					
		1				233.75					
		1.5				233.75					
		2				233.75					
		3				233.74					
		4				233.73					
		5				233.72					
		7				233.71					
		9				233.70					
		11				233.7					
		13				233.69					
		15				233.68					
		20				233.68				CSC	
		25				233.67				CSC	
		30				233.65				CSC	
		35				233.65				CSC	
		40				233.64				CSC	
		45									
		50				233.62				CSC	
		60				233.60				CSC	
		70									
		80									
		90									
		100									
		110									
		120									

AQUIFER TEST SUMMARY FOR WELL 299-E34-3

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 203 ft. Bottom: 213 ft.

Depth of Screened Interval in Pumped Well, Top: 203.5 ft. Bottom: 213.5 ft.

Date of Test: 08/05/87

Start Time of Test: 1500 hr

Pumping Rate: 60 gpm

Duration of Test: 180 min

Pre-test Water-level Elevation (Depth): 203.10 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	14,000	1,400
Recovery (Cooper and Jacob 1946)	14,000	1,400

Corrections Used:

Borehole Storage Effects
 $t_c = 1.9$ min (Hargis 1979)

Remarks: The discharge rate varied after 90 min of pumping because of generator problems.

RCRA WELL 299-E34-3
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 8/05/87

E.64

RCRA WELL 299-E34-3
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/05/87

$Q = 60 \text{ gpm}$

$T = 14,000 \text{ ft}^2/\text{d}$

$$T = \frac{(2.3)(1440)(60)}{(4)(\pi)(7.48)(.15)}$$

E.65

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 2 of 2

Data for Well 299-EPU-3

Pumping Well SAME

Observation Wells _____

Location 200E

Type of Aquifer Test TE" DRAWDOWN

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured 5-5-20" 11044

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s TOP of stilling well

Elevation of Meas. Point 225' above ground surface

Depth of Pump/Airpipe Intake at ~20'

Pump On: date 2/5/87 time _____

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time			Water Level Data				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Flow Q
8/5	0920	0			205.33'				040	
		.5			205.63					
		1.0			205.52					
		1.5			205.96					
		2.0			205.60					
		3.0			205.55					
		4			205.46				49.2 in	
		5			205.45				48.5	
		7			205.43					
		9			205.42					
		11			205.50					
		17			205.67					
		15			205.65				7.25 gal/min	6 by 5 gal bucket
		20			205.72				043 19.6 gal/min	Adjust valve up to get
		25			205.71				044	adjust -- flow rate
		32			205.72				044 18.7	= 18 by bucket
		35			205.71				18.5	(? on bucket reading)
		42			205.71				18.3	calculations could be wrong
		45			205.74				047 18.4	
		57			205.69				18.0	Filled 5 gal bucket in 2.9 sec
		60			205.70				17.7	Adjust flow ↑
		60.5								
		61			205.79					
		61.5			205.85				27.8	
		62			205.84				27.9	Pump stopped
		63			205.82				18.5	restarted Pump
		64			205.89				18.5	readjust valve ↑ again
		65			205.89				21.4	
		67			205.80				22	Pump stopped again
		69			205.74				2.9	on again at 47.5 min.
		71			205.72				30.1	Adjusting valve
		73			205.79				24.4	Pump OFF + ON
		75			205.82				053 22.4	" " "
		78			205.43					
		79	1		205.43					Pump OFF again
		80	2		205.41					stopped test
		81	3		205.38					Restart
		83	5		205.37					
		85	7		205.36					

Aquifer Test Data

page 2 of 2

Data for Well 299-E 34-3

Pumping Well _____

Observation Wells _____

Location 200 EAST RCLA

Type of Aquifer Test DEVELOPMENT

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TAPS

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s Top Sewing Pipe 2.25

Elevation of Meas. Point _____

Depth of Pump/Airpipe INTAKE 209'

Pump On: date 3/5/87 time

Pump Off: date _____ time _____

Duration of Aquifer Test _____

[illegible]

Aquifer Test Data

page 1 of 1

Date for Well 299-E34-3

Pumping Well same

Observation Wells 299-E27-10

Location 200 E

Type of Aquifer Test STEP DRAWD

How Q Measured DIGITAL FLOW METER

How W.L.'s Measured E-tap # 11044 core

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s TAP OF 8" CASING

Elevation of Meas. Point _____

Depth of Pump/Airpipe intake at ~20'

Pump On: date 8-4-97 time

Pump Off: date _____ time _____

Duration of Aquifer Test _____

[illegible]

page 1 of 1Pumping Well 209-534-3

Observation Wells 299-E27-10

Type of Aquifer Test STEP DRAIN DOWN

How Q Measured _____

How W.L.'s Measured 8.224 6.4 3.202

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point Top of 6" casing, 2.1' of sticks
above ground surface.

Depth of Pump/Airpipe N/A

Pump On: date 2/5/87 time 1230

Pump Off: date 8/5/87 time ~1800

Duration of Aquifer Test _____

E.69

Aquifer Test Data

page 1 of 1

Data for Well 299-E27-10Pumping Well 209-E34-3

Observation Wells 279-E.23-10

Location 200 East Area

Type of Aquifer Test Step Drawdown

How Q Measured _____

How W.L.'s Measured DN4300 STEEL TAPE #1

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point Ground surfaceDepth of Pump/Airpipe N/A

Pump On: date 9/4/87 time 1700

Pump Off: date _____ time _____

Duration of Aquifer Test _____

[illegible]

Aquifer Test Data

page 1 of 3

Date for Well 299-274-3

Pumping Well

Observation Wells

Location 200 E 34-3

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPG

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s TA 225' ABV LSD

Elevation of Meas. Point

Depth of Pump/Airpipe 207' LSD

Pump On: date 3/5/87 time 1230

Pump Off: date time

Duration of Aquifer Test

Time			Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0			Static Water Level <u>205.35' MP</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'		Reading	Q	
3/5	1230	0									
		1:30			205.69						
		1			206.15						
		1:30			206.22						
		2			206.42			56.2			
		3			206.47			53.5			
		4			206.52			53.6			
		5			206.53			53.9			
		7			206.58			53.7			
		9			206.60			53.6			
		11			206.61			56.3			
		13			206.61			53.9		1	
		15			206.62			53.7			
		20			206.67			54.0			
		25			206.68			53.5			
		30			206.68			52.6			
		35			206.70			53.3			
		40			206.70			52.6			
		45			206.73			52.7		* PUMP STOPPED FOR	
		50			206.73			52.6		10 SECS AT 62 MINS	
		60			206.74			53.0		206.60 AT 63 MINS	
		70			206.68			54.2		206.70 64 MINS	
		75	0		206.68			57.6		206.70 65 "	
		75:30	30		205.81					* PUMP STOPPED FOR	
		76	1		205.72					5 SECS AT 64 MINS	
		77	2		205.62						
		78	3		205.57					* PUMP SHUT-DOWN	
		79	4		205.55					FOR REPAIR AT 75 MIN.	
		81	8		205.47						
		84	9		205.45						
		86	11		205.43						
		91	15		205.40						
		98	23		205.36						
		105	30		205.35						
		115	40		205.35						

Aquifer Test Data

page 2 of 3

Data for Well 299-E 34-3

Pumping Well 299-E 34-3

Observation Wells _____

Location 200 E 34-3

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/O 2.25' ABOVE

Elevation of Meas. Point _____

Depth of Pump/Airpipe 200'

Pump On: date 2-5-97 time 1500

Pump Off: date 2/5/97 time 1800

Duration of Aquifer Test 3 hr

Time			Water Level Data					Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
2/5	1500	0									
		1:30			205.60						
		1			205.93				45.9		
		1:30			206.05				49.7		
		2			206.19				50.5		
		3			206.25				51.7		
		4			206.31				53.8		
		5			206.37				52.4		
		6			206.41				53.7		
		7			206.43				54.4		
		8			206.45				54.2		
		9			206.47				53.3		
		10			206.48				52.2		
		15			206.48				52.2		
		20			206.49				52.2		
		25			206.51				53.7		
		30			206.51				52.9		
		35			206.52				53.1		
		40			206.53				52.7		
		45			206.51				51.7		
		50			206.52				51.8		CSC
		60			206.51				51.8		CSC
		70			206.52				51.8		CSC
		80			206.52				51.9		CSC
		90			206.52				52.0		CSC
		92									
		94			206.29				41.4		Generator taking discharge drop.
		100			206.20				40.4		laboring could not
		110			206.20				38.4		he said
		115			207.12				80		opened the valve
		120			207.12				72.2		Even FILTER
		135			207.15				75.5		
		140			207.12				72.1		
		145			207.16				76.4		
		150			207.15				75.0		
		160			207.07				72.0		
		170			206.90				64.6		
		180			206.70				63.6		
											AVG Q = 58.75 gpm

Aquifer Test Data

page 3 of 3

Data for Well 2-E 34-3

Pumping Well _____

Observation Wells _____

Location 200 East Rock

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured DIGITAL FLOWMETER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/P 2.25' Abv LSD

Elevation of Meas. Point _____

Depth of Pump/Airpipe 209' L30

Pump On: date 3/5/87 time 1500

Pump Off: date 3/5/87 time 1800

Duration of Aquifer Test 3 hr

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level _____					Read-	Q		
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	s-s'	ing			
3/5	1800	180	0		206.30				0				
			30		205.81				1.09				
			1		205.26				1.14				
			1:30		205.21				1.19				
			2		205.65				1.25				
			3		205.62				1.27				
			4		205.58				1.32				
			5		205.55				1.35				
			2		205.51				1.39				
			9		205.49				1.41				
			11		205.45				1.45				
			12		205.44				1.46				
			15		205.42				1.47				
			20		205.42				1.47				
			25		205.41				1.49				
			29		205.40				1.50				
			35		205.39				1.51				
			40		205.39				1.51				
			45		205.375				1.525				
			50		205.36				1.54				
			60		205.36				1.54				
			70		205.35				1.55				
	2055	185			205.32				1.58				
		175											

Appendix 1: Data

Section 1: Data Collection
This section contains the data collected for the study. The data is organized into two main categories: *Demographic Data* and *Performance Data*. The *Demographic Data* includes information such as age, gender, and education level. The *Performance Data* includes information such as test scores and completion times. The data is presented in a table format, with each row representing an individual participant and each column representing a specific data point.

Participant Information		Performance Data	
Participant ID	Age	Test Score	Completion Time
1	25	85	12.5
2	30	78	15.2
3	22	92	10.8
4	35	70	18.1
5	28	88	11.3
6	32	75	16.7
7	20	95	9.9
8	38	68	19.4
9	27	82	13.6
10	31	79	14.9
11	24	90	11.7
12	33	73	17.2
13	21	93	10.5
14	36	71	18.8
15	29	87	12.1
16	34	76	16.3
17	23	91	11.0
18	37	69	19.0
19	26	84	13.0
20	30	77	15.5
21	25	89	11.5
22	32	74	16.9
23	20	94	10.2
24	39	67	20.1
25	28	86	12.3
26	33	72	17.5
27	21	96	9.7
28	36	70	18.6
29	27	83	13.3
30	31	76	16.1
31	24	91	11.1
32	34	73	17.3
33	21	93	10.6
34	36	69	19.2
35	29	87	12.0
36	34	76	16.4
37	23	91	10.9
38	37	69	19.3
39	26	84	13.1
40	30	77	15.6
41	25	89	11.6
42	32	74	17.0
43	20	94	10.3
44	39	67	20.2
45	28	86	12.4
46	33	72	17.6
47	21	96	9.8
48	36	70	18.7
49	27	83	13.4
50	31	76	16.2

AQUIFER TEST SUMMARY FOR WELL 299-E34-5

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the Hanford formation in the 200-East Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery ()

Hydrogeologic Unit Tested: Hanford formation

Depth of Formation, Top: 185 ft. Bottom: 189 ft.

Depth of Screened Interval in Pumped Well, Top: 180.5 ft. Bottom: 190.5 ft.

Observation Well Used: 299-E34-6 Distance to Pumped Well: 600 ft.

Elevation (Depth) of Screened Interval, Top: 175 ft. Bottom: 195 ft.

Date of Test: 07/21/88

Start Time of Test: 0800 hr

Pumping Rate: Variable

Duration of Test: 25 min

Pre-test Water-level Elevation (Depth): 185.09 ft.

Water-level depth at maximum drawdown: 184.06 ft.

Remarks: The drawdown and recovery data are insufficient for analysis. No response was observed in the observation well.

Aquifer Test Data

page 1 of 2

Data for Well 299-E34-5

Pumping Well 299-E34-5

Observation Wells 299-E34-6

Location 200 EAST RCRA

Type of Aquifer Test STEP DD

How Q Measured FLOW METER / 5 gal. bucket

How W.L.'s Measured E-tape

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s T/C 2.24' ABV LSP

Elevation of Meas. Point —

Depth of Pump/Airpipe —

Pump On: date 7/20/87 time —

Pump Off: date 7/20/87 time —

Duration of Aquifer Test —

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>185.33 MD</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
7/20		0					185.34		0000006			DATA INDUSTRIAL
		1:30										DIGITAL FLOW
		1										MONITOR 900T
		1:30										S/N 020542
		2										3" PUMP (CAL) 1000
		3										GAL. X 1000
		4										
		5										
		7										
		9										
		11										
		13					185.41		15			
		15					185.41					
		20					185.42					↑
		1:30					186.12		42			
		16					186.20		38.7			
		19					186.30		38.7			
		15					186.35		38.9			
		20					186.12		41.2			↓
		25					186.11		41.7			
		30					186.64		34			
		45					186.50					
		60					186.55		38.7			
→		4					185.57					Recovery
		5					185.54					
		7					185.55					
		20					185.72					
		30					185.43					
		45					185.42					
		200					185.39					
		122					185.59					
		173					185.38					
		124					185.37					
		175					185.35					
		161					185.35					
		124					185.35					
		1910					185.34					
1945		210					185.335		2115	185.33		
2015		240					185.33					
2042		270					185.325					

· Aquifer Test Data

page 2 of 3

Data for Well 2-E34-5Pumping Well 2-E-A-5

Observation Wells _____

Location 200 East DCRA

Type of Aquifer Test CONSTANT - DISCHARGE

How Q Measured Flow Meter

How W.L.'s Measured $\Sigma - TAP$

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/C 2.29' AB1 L2D

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 7/21/23 time 0800

Pump Off: date _____ time _____

Duration of Aquifer Test _____

[illegible]

Aquifer Test Data

2.32'

page 1 of 1

Data for Well 2-2.34-6

Pumping Well 2-E32-5

Observation Wells _____

Location 200 East RCRA

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured FLOW METER DATA INDUSTRIAL 020842

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 190'

Rad./Dist. of/From Pumping Well —

Pump On: date 7/21/87 time _____

Meas. Point for W.L.'s T/C 2.24' ABV LEO

Pump Off: date _____ time _____

Elevation of Meas. Point _____

Duration of Aquifer Test _____

Measurements by S. D. D. 1/6

Note:
Test
started
a little
after
8:00 AM
get true
time
from
Chuck

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>193.72</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
7/21	0800	0										Test started a little after 8:00 AM
		15										
		30										(I believe it was 801 but need to act around time from Chuck)
		45										
		1			193.75							
		1:15										but need to act around time from Chuck
		1:30			193.75							
		1:45										
		2			193.75'							
		3			193.75'							
		4			193.75'							
		5			193.75'							
		7			193.75'							
		9			193.75'							
		11			193.74'							
		13			193.75'							
		15			193.74'							
		20			193.75'							
		25			193.74'							
		30			193.75'							
		35			193.75'							
		40			193.74'							
		45			193.75'							
		50			193.75'							
		60										
		70										
		80										
		90										
		100										
		110										
		120										
		150										
		180										
		210										

REFERENCES

Cooper, H. H., and C. E. Jacob. 1946. "A Generalized Graphical Method for Evaluating Formation Constants and Summarizing Well-Field History." Transactions of the American Geophysical Union 27 (IV):526-534.

Hargis, D. R. 1979. Analysis of Factors Affecting Water Level Recovery Data. Dissertation, University of Arizona. University Microfilms International, Ann Arbor, Michigan.

REFERENCES

- Boone, H. L., and C. E. Jacon. 1953. "A Generalized Graphical Method for
Determining Soil Moisture Constants and Summarizing Soil Moisture History." Trans-
actions of the American Society of Civil Engineers 115: 825-834.
- Harvey, D. T. 1978. Analysis of Factors Affecting Water Level Recovery
After Drought. M.S. Thesis, University of Arizona, Tucson, Arizona.

APPENDIX F

AQUIFER TESTING OF WELLS IN THE 200-WEST AREA

APPENDIX F

AQUIFER TESTING OF WELLS IN THE 200-WEST AREA

INTRODUCTION

During 1987, aquifer tests were conducted on the 19 newly drilled wells that were designed to gather hydrologic and geologic data adjacent to waste management areas in the 200-West Area. The wells were not designed or drilled specifically as part of an aquifer testing program. However, the wells did provide an opportunity for conducting aquifer tests while the wells and equipment were available. Ideal conditions for obtaining maximally useful data were not, in general, met. For example, the screened intervals in the wells generally did not cover the full thickness of the aquifer, the well may not have been pumped at a sufficient rate for responses to be observed in pumping and observation wells, and in some cases, the pumping duration should have been longer. While part of the test data were of no use, some tests did furnish useful data that were analyzed for aquifer parameters and properties.

The following presents a summary of each aquifer test conducted in the 200-West Area. These aquifer test summaries include the purpose of each test, types of tests conducted, construction details of the tested well and observation well when used, pumping rates and duration of the tests, pre-test conditions, results of test data analysis, and related plots of test data. Raw data from the well development/step drawdown tests, constant discharge/recovery tests, and/or slug injection/withdrawal tests are also included.

SPUTTER TESTING OF WELLS IN THE 200 WEST AREA

INTRODUCTION

During 1987, sputter tests were conducted on the 19 newly drilled wells that were assigned to gather hydrologic and geologic data subject to waste disposal areas in the 200 West Area. The wells were not designed or drilled specifically as part of an sputter testing program. However, the wells did provide an opportunity for conducting sputter tests while the wells and equipment were available. Ideal conditions for obtaining maximum sputter data were not, in general, met. For example, the screened intervals in the wells generally did not cover the full thickness of the aquifer, the wells may not have been pumped at a sufficient rate for responses to be observed in pumping and observation wells, and in some cases, the pumping duration should have been longer. While part of the test data were of no use, some tests did furnish useful data that were analyzed for sputter test results and properties.

The following presents a summary of each sputter test conducted in the 200 West Area. These sputter test summaries include the purpose of each test, types of tests conducted, construction details of the tested well and observation well when used, pumping rates and duration of the tests, pre-test conditions, results of test data analysis, and related plot of test data. New data from the well development step-down tests, constant discharge/recovery tests, and the injection/withdrawal tests are also included.

AQUIFER TEST SUMMARY FOR WELL 299-W6-2

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 230 ft. Bottom: 472 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 238 ft. Bottom: 248 ft.

Date of Test: 11/05/87

Start Time of Test: 0730 hr

Pumping Rate: 22 gpm

Duration of Test: 300 min

Pre-test Water-level Elevation (Depth): 227.64 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	350	1.5
Recovery (Cooper and Jacob 1946)	500	2

Corrections Used:

Borehole Storage Effects

$t_c = 53$ min (Hargis 1979)

Remarks: The assumption that the well fully penetrates the aquifer is not satisfied in the Cooper and Jacob analysis. The top of the basalt is assumed to be the bottom of the aquifer. The lower Ringold unit does not exist at this location.

RCRA WELL 299-W6-2
 CONSTANT-DISCHARGE DRAWDOWN
 COOPER-JACOB METHOD
 11/5/87

F.4

RCRA WELL 299-W6-2
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 11/5/87

F.5

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 2

Data for Well 299-WK-2

Pumping Well 299-WK-2

Observation Wells

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE / ~~variable~~

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE / TRANSDUCER Depth of Pump/Airpipe 243' below land

Rad./Dist. of/From Pumping Well Pump On: date 11/5/87 time 0730

Meas. Point for W.L.'s T/STILLING PIPE 224' Pump Off: date 11/5/87 time 1230

Elevation of Meas. Point 152' Duration of Aquifer Test 5 hr

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level 229.88' MP							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or f	Reading	Q		
11/4	1500							229.62			ARAR: METRIC
											2" # 286 0530
11/5	0730	0			229.88		0	194.62			START DD TEST
		1:30									
		1			232.22		3.34				
		1:30			234.41		4.53				
		2			235.43		5.55	40			10 gal / 15 sec
		3			235.58		9.70				no. 8 to keep water
		4			237.90		10.02				21.2 sec in sand
		5			240.60		10.72	26.1			10 gal / 23 sec
		7			241.02		11.14	25			10 gal / 24 sec
		9			241.51		11.63	21.4			10 gal / 24 sec
		11			241.71		11.83	19.4			10 gal / 31 sec
		13			241.85		12.00	23.1			10 gal / 26 sec
		15			242.02		12.14	23.3			20 gal / 51.5 sec
		20			242.28		12.40	24			10 gal / 25 sec
		25			242.50		12.72	24			10 gal / 25 sec
		30			242.74		12.86	22.2			10 gal / 27 sec
		35			242.84		12.98	25.1			10 gal / 26 sec
		40			242.91		13.03	20.2			10 gal / 27 sec
		45			243.00		13.12				
		50			243.17		13.29	20.7			10 gal / 29 sec
		60			241.2		11.32	20.7			10 gal / 29 sec
		70			243.3		13.42	28.1			10 gal / 29 sec
		80			243.55		13.67	23.1			10 gal / 29 sec
		90			243.60		13.72	22.2			10 gal / 27 sec
		100			243.62		13.74	22.2			10 gal / 27 sec
		110			243.64		13.76	22.2			10 gal / 27 sec
		120			243.60		13.72	24			10 gal / 25 sec
		150			243.60		13.72	24			10 gal / 25 sec
	1030	120			243.61		13.73	23.1			10 gal / 26 sec
		210			243.52		13.64	23.1			10 gal / 26 sec
		240			243.56		13.68	20.7			1030 and 1100 hr
		270			243.28		13.40				10 gal / 37
		300			242.65		12.80	247.6			5 gal bucket 25.1 gpm
											broke hose open
											in H2O level up
											cleared sand head

H2O sample

H2O sample

H2O sample

Aquifer Test Data

page 2 of 2

Data for Well 299-W6-2

Pumping Well 299-W6-2

Observation Wells —

Location 200 WEST RCR

Type of Aquifer Test CONSTANT-DISCHARGE Recovery

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s 5" STILLING PIPE 2.24' 460

Elevation of Meas. Point 150

Depth of Pump/Airpipe 243' Below 1st

Pump On: date 11/5/97 time 0730

Pump Off: date 11/5/97 time 1230

Duration of Aquifer Test 5 hr

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>229.88</u>							
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	f' or s'		Read- ing	Q	
11/5	1230	300	0	242.68					247.16	CSG	
			30	N/A							
		301	1	238.27			8.33				
		301.5	1:30	236.98			7.1				
		302	2	236.06			6.18				
		303	3	234.99			5.11				
		304	4	234.29			4.41				
		305	5	233.51			3.63				
		307	7	232.84			2.96				
		309	9	232.46			2.58				
		311	11	232.18			2.30				
		313	13	231.92			2.04				
		315	15	231.78			1.90				
		320	20	231.39			1.51				
		325	25	231.10			1.22				
		330	30	230.89			1.00				
		335	35	230.74			.86				
		340	40	230.64			.76				
		345	45	230.56			.68				
		350	50	230.49			.61				
	1330	360	60	230.39			.51				
		370	70	230.30			.42				
		380	80	230.23			.35				
		390	90	230.18			.30				
		400	100	230.14			.26				
		410	110	230.09			.21				
	1430	420	120	230.08			.20				
	1500	450	150	230.01			.13				
		480	180	229.97			.09				
		510	210	229.93			.05				
		540	240	229.91			.03				

AQUIFER TEST SUMMARY FOR WELL 299-W7-1

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 225 ft. Bottom: 495 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 233 ft. Bottom: 243 ft.

Observation Well Used: 299-W8-1 Distance from Pumped Well: 599 ft.

Elevation (Depth) of Screened Interval, Top: 236 ft. Bottom: 256 ft.

Date of Test: 07/15/87

Start Time of Test: 1230 hr

Pumping Rate: 17.5 gpm

Duration of Test: 480 min

Pre-test Water-level Elevations (Depths): 228.49 ft.

Pumping Well: 225.65 ft.

Observation Well: 235.95 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Constant Discharge (Cooper and Jacob 1946)	1,000	4	NA
Recovery (Cooper and Jacob 1946)	1,400	5	NA

Corrections Used:

Borehole Storage Effects

$t_c = 26$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The drawdown and recovery data indicate that well entrance loss occurred (Hargis 1979). The drawdown data indicate boundary effects. No response was observed in the observation well.

RCRA WELL 299-W7-1
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 7/15/87

F.10

Drawdown
 (ft)

RCRA WELL 299-W7-1
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 7/15/87

F.11

Residual
 Drawdown
 (ft)

Aquifer Test Data

1st TEST

page 1 of 2

Data for Well 2-W7-1

Pumping Well 2-W7-1

Observation Wells 2-WB-1

Location 200 West RCR

Type of Aquifer Test CONSTANT DISCHARGE DD

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE / STEEL TAPE

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s TRENCH 2.84' ABV

Elevation of Meas. Point

Depth of Pump/Airpipe

Pump On: date 7/15/87 time 0925

Pump Off: date 7/15/87 time 1025

Duration of Aquifer Test 1 hr

235 from Transm

236 LSO

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>228.43</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	0925	0					228.43	2.23	5.87			ARAB METER
		:30					230.82	2.89				#286 053068
		1					231.30	2.87				2" diameter
		1:30					231.65	3.12				
		2					231.70	3.27	18.6			
		3					231.98	3.55				
		4					232.40	3.97				
		5					232.83	3.75				
		7					232.76	4.38	7.17			
		9					233.15	4.72	34.7			820 210 min
		11					233.44	5.01				
		12							9.60			normal pipe
		15					234.81	6.38	32.5			removed block
		20					235.07	6.64				pressure from hole
		25					235.07	6.64	1317.531			1286.5 24 min
		30					235.07	6.64				may be at
		35					235.06	6.63				table
		40										1784 242 min
		45					235.1	6.67				27.4
		50					235.08	6.65	20.5			
	1025	60	0						2293.5			
		70	:30	121			234.0	5.57				
		80	1	61			233.6	5.17				
		90	1:30	41			233.21	4.78				
		100	2	31			233.02	5.17	4.59			
		110	3	21			232.70	4.27				
		120	4	16			232.42	4.02				
		130	5	13			232.20	3.80				
		140	7	9.6			231.8	3.37				
		150	9	7.7			231.3	2.87				
		160	11	6.5			230.46	2.63				
		170	13	5.6			229.89	1.46				
		180	15	5			229.57	1.14				
		190	20	4			229.0	0.57				
		200	25	3.4			228.81	0.44				
		210	30	3			228.75	0.36				
		220	35	2.7			228.75	0.32				
		230	40	2.5								
		240	45	2.3			228.6	0.23				

Location 200 West RCLA
Type of Aquifer Test constant Discharge recovery
How Q Measured FLOW METER
How W.L.'s Measured E-TAPE
Rad./Dist. of/From Pumping Well
Meas. Point for W.L.'s TOP TRENCH 2.24' ABV
Elevation of Meas. Point

Observation Wells _____

Duration of Aquifer Test 1 hrF.13

1st Test

Aquifer Test Data

page 1 of 1Data for Well 2-WJ8-1Pumping Well 2-WJ7-1Observation Wells 2-WJ8-1Location RCRA 200 WestType of Aquifer Test CONSTANT - DISCHARGEHow Q Measured FLOW METER/CALIB. 5 gal bucketHow W.L.'s Measured E-TAPE/STEEL TAPE Depth of Pump/Airpipe 235 T/CRad./Dist. of/From Pumping Well _____ Pump On: date 7/15/87 time 0925Meas. Point for W.L.'s T/C Pump Off: date 7/15/87 time 1025Elevation of Meas. Point _____ Duration of Aquifer Test 1 hr

Time t = _____ at t' = 0					Water Level Data Static Water Level _____				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s	Read- ing	Q		
	0				239.25'							
	30				239.25'							
	1:30				239.25'							
	2				239.25'							
	3				239.2'							
	4				239.43'							
	5				239.25'							
	7				239.62'							
	9				239.64'							
9400	11				239.66'							
9460	13				239.66'							
9480	15				239.66'							
953	20				239.65'							
958	25				239.64'							
1003	30				239.65'							
1003	35				239.62'							
1013	40				239.60'							
1018	45				239.5'							
1023	50				239.6'							
1033	60				239.27'							
1043	70				239.22'							
1055	80				239.21'							
1103	90											
	100											
	110											
	120											
	150											
	180											
	210											
	240											
	270											
	300											
	360											
	420											
	480											

Aquifer Test Data

page 1 of 2

Data for Well 2 W 7-1

Pumping Well W 7-1

Observation Wells 2 W 8-1

Location 200 West RRA

Type of Aquifer Test CONSTANT-DISCHARGE TO TEST #2

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 235 T/C
236

Rad./Dist. of/From Pumping Well ---

Pump On: date 7/15/87 time 1230 hrs

Meas. Point for W.L.'s TOP TREATMENT ZONE

Pump Off: date 7/15/87 time 2030 hrs

Elevation of Meas. Point ---

Duration of Aquifer Test 8 hr

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>229.49</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
7/15	1230	0					229.49	0		2293.5		CHANGED	
		30					230.46	1.97					
		1					230.54	2.05					
		1:30					230.57	2.03					
		2					230.61	2.12					
		3					230.62	2.13		14.3			
		4					230.76	2.27				CHANGED DISC	
		5					230.91	2.42				INCREASED 1/2	
		6											
		7					231.18	2.69		2393.5			
		9					231.81	2.82		2428	17.25		
		11					231.47	2.91		2463	17.5		
		13					231.47	2.98		2498	17.5		
		15					231.54	3.05		2533	17.5		
		20					231.68	3.19		2620	17.4		
		25					231.74	3.25		2706	17.2		
		30					231.80	3.33				5.06 / 17.2 min	
		31					231.88	3.39		2810	17.3	(17.3 gpm)	
		35					231.88	3.39		2800	17.5		
		40					231.92	3.45		2825			
		41					231.92	3.45		2985	17.5		
		45					231.92	3.45		3054	17.45		
		50					231.98	3.49		3142	17.6		
		60					232.03	3.5		3317	17.5		
		70					232.05	3.54		3443	17.6		
		80										Pipeline came	
		90					232.12	3.63		3542	17.5	... from BWSH	
		100					232.16	3.67		4017	17.5		
		110					232.18	3.69		4193	17.6		
		120					232.19	3.70		4579	17.6	5.06 / 17.3 min	
		150					232.24	3.75		4895	17.2	(17.5 gpm)	
		180					232.24	3.77		5422.5	17.6		
		210					232.3	3.81					
		240					232.31	3.82		6480	17.6		
		270					232.35	3.86		7009			
		300					232.36	3.87		7538.5		avg. 17.5 gpm	
		1002					232.39	3.90		8634.5	P.O.		
		1130					232.41	3.92			P.O.		
		2030					232.45	3.96		11891	P.O.	OFF	

F. 141
140

F. 15

plus
time
off
for
discharge
rate

Aquifer Test Data

page 2 of 2

Data for Well 2W7-1

Pumping Well 2W7-1

Observation Wells 2W8-1

Location 200 West RCR

Type of Aquifer Test CONSTANT DISCHARGE - Recovery

How Q Measured FLOWMETER / CALIBRATED 5 gal bucket

How W.L.'s Measured E-Tape

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s _____

Elevation of Meas. Point 700

Depth of Pump/Airpipe 235 T/c

Pump On: date 7/15/97 time 1230

Pump Off: date 7/15/97 time 3030

Duration of Aquifer Test 2 hrs

Time					Water Level Data				GAL Discharge		Recorded By	Comments	
t = _____ at t' = 0					Static Water Level <u>228.49</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
7-15	20:35	30			232.40			3.91		11881		PLO	OFF - 3031C
"	20:36				232.30			3.81				PLO	
"	20:37				232.12			3.61				PLO	
"	20:38				231.94			3.45				PLO	
"	20:39				231.65			3.16				PLO	
"	20:40				231.46			2.97				PLO	
"	20:41				231.19			2.70				PLO	
"	20:42				230.75			2.26				PLO	
"	20:43				230.50			2.01				PLO	
"	20:44				230.18			1.94				PLO	
"	20:45				-			-				PLO	
"	20:46				229.72			1.23				PLO	
"	20:47				229.62			1.13				PLO	
"	20:48				229.44			0.95				PLO	
"	20:49				229.36			0.77				PLO	
"	20:50				229.15			0.56				PLO	= SOUNDS IN
"	20:51				229.18	?		0.59	?			PLO	DISCHARGE PIPE
"	20:53				229.09			0.49				PLO	SHUT GATE VALVE
"	20:57				229.02			0.44				PLO	
"	20:58				229.00			0.41				PLO	
"	21:00				228.97			0.38				PLO	
"	21:15				228.87			0.28				PLO	
"	21:30				228.81			0.22				PLO	
"	21:45				228.78			0.19				PLO	
"	22:00				228.80			0.21				PLO	} STARTING TO DRIFT DUE TO STRONG FRONTAL SYSTEM ?
"	22:15				228.78			0.19				PLO	
"	22:30				228.74			0.15				PLO	

Aquifer Test Data

2nd Test

page 1 of 2

Data for Well 2-W8-1

Pumping Well 2-W7-1

Observation Wells 2-W8-1

Location RCRA 200 West

Type of Aquifer Test Constant Discharge

How Q Measured Flow meter / 5 gal bucket

How W.L.'s Measured E-Tape / Steel Tape

Rad./Dist. of / From Pumping Well

Meas. Point for W.L.'s T/C 3.25' ADV L&D

Elevation of Meas. Point

Depth of Pump/Airpipe 235 T/C

Pump On: date 3/15/87 time 1230

Pump Off: date 3/15/87 time 2030

Duration of Aquifer Test 8 hrs

sing above
and 3'3"
1 measurement
in top of
 casing

Time					Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0					Static Water Level <u>239.2'</u>								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
	0				239.2'								
	30				239.2'								
	1:00				239.23'								
	1:30				239.22'								
	2				239.23'								
	3				239.22'								
	4				239.23'								
	5				239.21'								
	7				239.19'								
	9				239.2'								
	11				239.2'								
	13				239.2'								
	15				239.2'								
	20				239.19'								
	25				239.2'								
	30				239.2'								
	35				239.2'								
	40				239.19'								
	45				239.18'								
	50				239.17'								
	60				239.18'								
	70				239.2'								
	80				239.18'								
	90				239.21'								
	100				239.2'								
	110				239.18'								
	120				239.19'								
	150				239.17'								
	180				239.19'								
	210				239.17'								
	240				239.17'								
	270				239.14'								
	300				239.16'								
	12:30	360			239.14'							CSC	
	17:30	420			239.12'							PA	
	18:30				239.13'							PA	
	19:30				239.14'							PA	
	20:30				239.12'							PA	
	21:05				239.17'							PA	

A' 31

239.22

Location RCRA 200 West

How Q Measured Flowmeter / Calib. 5 gal bucket

How W.L.'s Measured E-TAPE - STAGU-TAPE

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s T/C 3.35' Abv. L.S.D.

Elevation of Meas. Point _____

page 2 of 2

Data for Well 2-54-1

Pumping Well 2 - W 7 - 1

Observation Wells _____

Depth of Pump/Airpipe

Pump On: date 7/15/87 time 1230

Pump Off: date 7/15/87 time 2030

Duration of Aquifer Test 8 hr

F.18

AQUIFER TEST SUMMARY FOR WELL 299-W7-2

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 212 ft. Bottom: 472 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 212 ft. Bottom: 222 ft.

Observation Well Used: 299-W7-3 Distance to Pumped Well: 35 ft.

Elevation (Depth) of Screened Interval, Top: 449 ft. Bottom: 470 ft.

Date of Test: 09/16/87

Start Time of Test: 0800 hr

Pumping Rate: 10 gpm

Duration of Test: 480 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 211.89 ft.

Observation Well: 212.28 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Constant Discharge (Cooper and Jacob 1946) Pumping Well	430	2	NA
Recovery (Cooper and Jacob 1946) Pumping Well	740	3	NA

Corrections Used:

Borehole Storage Effects

$t_c = 8$ min (Schafer 1978)

$t_c = 61$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The residual drawdown data from the pumping well indicate that well entrance loss occurred during pumping (Hargis 1979). Drawdown reached the level of the pump intake after 120 min of pumping. The condition that u is equal to or less than 0.01 is not satisfied in analyzing data from the observation well using the Cooper and Jacob method.

RCRA WELL 299-W7-2
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 9/16/87

F.20

Drawdown
 (ft)

RCRA WELL 299-W7-2
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 9/16/87

F.21

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 3

Data for Well 299-W7-2

Pumping Well 299-W7-2

Observation Wells 299-W7-3

Location 200 WEST RCRA

Type of Aquifer Test DEVELOPMENT / STEP DD

How Q Measured FLOWMETER 2" ARAD 053068 / 5 gal bucket 5 HP PUMP

How W.L.'s Measured R-TAPE / TRANSDUCER Depth of Pump/Airpipe 217' Below 150

Rad./Dist. of/From Pumping Well _____ Pump On: date 9/15/87 time 1035

Meas. Point for W.L.'s T/STILLING PIPE 2.55' ^{ABV} _{LAB} Pump Off: date _____ time _____

Elevation of Meas. Point _____ Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>214.52' T/P</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
	1035	0							11280		
		:30			217.76						
		1			218.26						
		1:30									
		2			219.08						
		3			219.81						
		4			219.72						
		5									
		2									
		9			219.72						
		11			219.6						
		13			219.70						
		20			219.77						
		110			219.87				9.7		
		150			219.88						
		120	0		219.87				15782.5		
		:20			219.83						
		1			219.76						
		1:20			219.68						
		2			219.64						
		3			219.52						
		4			219.28						
		5			218.90						
		2			218.17						
		9			217.48						
		11			216.99						
		13			216.58						
		15			216.37						
		20									
		30			215.32						
		40			215.03						
		50			214.92						
		60			214.77						

Aquifer Test Data

Location 200 West RCRA
 Type of Aquifer Test constant discharge
 How Q Measured Flowmeter 2" ARAD # 053058 / 5 gal bucket
 How W.L.'s Measured E-tape / transducer
 Rad./Dist. of/From Pumping Well 0
 Meas. Point for W.L.'s T/stilling pipe 2.55' Above L.S.
 Elevation of Meas. Point _____

page 2 of 2
 Date for Well 299-W7-2
 Pumping Well 299-W7-2
 Observation Wells 299-W7-3

Depth of Pump/Airpipe 217 b/s
 Pump On: date 9/16/87 time 0800
 Pump Off: date 9/16/87 time 1600
 Duration of Aquifer Test 8 hr

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level 214.44							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
9/16		1:30			216.21			1.80	12782.5			
		1:00			216.42			1.98				
		1:30			216.51			2.07				
		2			216.70			2.24				
		3			217.05			2.61				
		4			217.38			2.94				
		5			217.56			3.12				
		7			217.91			3.47				
		9			218.17			3.73				
		11			218.44			4.00				
		13			218.48			4.04				
		15			218.78			4.34				11-12 gpm flowmeter
		20			—							
		25			219.22			4.78				flow meter ~ 9.9 gpm
		30			219.35			4.82				flowmeter ~ 10.5 gpm
		35			219.32			4.88				" "
		40			219.36			4.92				
		45			219.42			4.98				
		50			219.49			5.05				
		60			219.55			5.11				
		70			219.60			5.16				
		80			219.62			5.18				
		90			219.72			5.28				
		100			219.77			5.33				
		110			219.80			5.36				
		120			219.84			5.40				
		150			219.85			5.41				
		180			219.85			5.41				10.5 gpm - flowmeter
		210			219.85			5.41				
		240			219.85			5.41				10.5 gpm flowmeter
		270			219.85			5.41				
		300			219.86			5.42				
		330			219.85			5.41				~ 10.25 gpm
		420			219.85			5.41				5 gal bucket
		520			219.85			5.41	12782.5	11/16		25 in. 28 in.

page 3 of 3

Data for Well 299-47-2

Pumping Well 299-437-2

Observation Wells 299-W73

Location RCRA 200 WEST

Type of Aquifer Test CONSTANT-DISCHARGE Recovery

How Q Measured Flow Meter / 5 gal bucket

How W.L.'s Measured E-TAPE ~~TRANSOMER~~ Depth of Pump/Airpipe 217' Below 1st

Rad./Dist. of/From Pumping Well _____ Pump On: date 9/16/97 time 0900

Meas. Point for W.L.'s T/STILLING PIPE 3.55' Pump Off: date 9/16/87 time 1600

Elevation of Meas. Point _____ Duration of Aquifer Test _____

Time			Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0			Static Water Level <u>214.44</u> T/PK							
Day	Clock Time	t'	t'	1/t'	Reading	Conversions or Corrections	Water Level	f or s'	Reading	Q
			0		214.63				17205	CSC
			1:30		219.63			5.19		
			1							
			1:30		219.56			5.12		
			2		219.62			5.18		
			3		219.50			5.06		
			4		219.36			4.92		
			5		219.23			4.39		
			7		218.17			3.73		
			9		217.59			3.15		
			11		217.09			2.65		
			13		216.70			2.26		
			15		216.44			2.00		
			21		215.84			1.40		
			26		215.56			1.12		
			31		215.35			0.91		
			35		215.21			0.77		
			40		215.12			0.68		
			45		215.03			0.59		
			50		214.95			0.51		
			60		214.88			0.44		
			70		214.80			0.36		
			80		214.75			0.31		
			90		214.72			0.28		
			100		214.71			0.27		
			110		214.68			0.24		
			120		214.65			0.21		
			155		214.63			0.19		
			180		214.61			0.17		

Aquifer Test Data

page 1 of 1

Data for Well 299-W7-3

Pumping Well 299-W7-2

Observation Wells 299-W7-3

Location 200 West RCRA

Type of Aquifer Test Constant discharge

How Q Measured Flowmeter ARAD 052068

How W.L.'s Measured E-tape / transducer

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/c 3.77' abv LS

Elevation of Meas. Point _____

Depth of Pump/Airpipe 217' b/c

Pump On: date 7/16/87 time 0800

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>216.05</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	8:10	10			216.05			0			SET	
	8:29	29			216.05			0				
	10:35	145			216.18			.13				
	12:12	232			216.32			.27				
	12:22	262			216.32			.27				
	12:30	270			216.35			.30				
	13:00	300			216.38			.33				
	13:30	330			216.40			.35				
	14:00	360			216.43			.38				
	14:30	390			216.45			.40				
	15:00	420			216.48			.43			CSC	
	16:00	480	0		216.52			.47				
	498	18	27.6		216.55			.50				
	509	28	18.14		216.54			.49				
	518	38	13.63		216.54			.49				
	529	48	11		216.53			.48				
	540	60	9		216.50			.45				
	550	70	7.86		216.49			.44				
	560	80	7		216.47			.42				
	570	90	6.33		216.43			.38				
	580	100	5.8		216.40			.35				
	590	110	5.36		216.38			.33				
	600	120	5		216.35			.30				
	637	157	4.06		216.28			.23				
	660	180	3.67		216.25			.20				

AQUIFER TEST SUMMARY FOR WELL 299-W7-3

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle/basal Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle/basal Ringold unit

Depth of Formation, Top: 212 ft. Bottom: 476 ft.

Depth of Screened Interval in Pumped Well, Top: 467 ft. Bottom: 477 ft.

Observation Wells Used: 299-W7-2 Distance to Pumped Well: 35 ft.

Elevation (Depth) of Screened Interval, Top: 202 ft. Bottom: 222 ft.

Date of Test: 10/30-31/87

Start Time of Test: 0800 hr

Pumping Rate: 2.8 gpm

Duration of Test: 1680 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 212.31 ft.

Observation Well: Unavailable.

Remarks: The data indicate that drawdown in the pumping well is mainly attributed to casing storage effects caused by the well configuration (screen open to the bottom of the aquifer). The water level stabilized after casing storage effects dissipated. The discharge rate varied during the first 30 min of the pumping test. No response was observed in the observation well.

Aquifer Test Data

page 1 of 1

Data for Well 299-W 7-3

Pumping Well 299-W 7-3

Observation Wells 2

Location 200 WEST RCRA

Type of Aquifer Test STEP 2.1. DEPLETION

How Measured E-TAPE SINGED TRANSDUCER / DATA LOGGER

How W.L.'s Measured 5 gal calib bucket Depth of Pump/Airpipe 451' below 13d

Rad./Dist. of/From Pumping Well _____ Pump On: date 10/29 time 16:00

Meas. Point for W.L.'s T/STILLING PIPE 409' Pump Off: date _____ time _____

Elevation of Meas. Point _____ Duration of Aquifer Test _____

Time			Water Level Data					Discharge		Recorded By	Comments
Day	Clock Time	t = _____ at t' = 0	t'	1/t'	Static Water Level	Conversions or Corrections	Water Level	s or s'	Reading	Q	
			0						2892.5		M. Cronin
			30		211.0						82.2 - 435
			4		256.25						
			5		254.98						had to open valve
			9		309.4				3.0		5 gal / 5 sec
			15		264.15				5.9		had too much water going out
			25		368.49				3.5		5 gal / 51 sec
			30		369.54				3		5 gal / 1:25
			35		368.59				3		5 gal / 1:40
			43		368.47						
			50		368.50						
			55		368.97						
			60		368.80				2.5		5 gal / 2 min
			70		368.51						
			80		369.00				3		5 gal / 1:41
			90		369.21						
			100		369.25				2.8		
			110		368.25						
			20	0							Pump off
			30		367.35						
			1		368.99						
			1:30		366.50						
			2		365.92						
			3		364.55						
			4		363.23						
			5		362.0						
			7		359.37						
			9		356.80						
			11		354.30						
			13		351.95						
			15		349.45						
			20		343.47						
	07:30				216.20 MP						

Aquifer Test Data

page 1 of 5

Data for Well 77-1137-3

Pumping Well 299. W 2-3

Observation Wells 299. W 2-3

Location 200 WEST RSEA

Type of Aquifer Test CONSTANT-DISCHARGE EL

How Q Measured Flow Meter / 5 gal. calibrated bucket

How W.L.'s Measured R-TAPE / TRANSOMER Depth of Pump/Airpipe 451' below 1st

Rad./Dist. of/From Pumping Well - Pump On: date 10/30/87 time 0800

Meas. Point for W.L.'s T/SPILLING PIPE 4.09' Pump Off: date 10/31/87 time 1215

Elevation of Meas. Point - Duration of Aquifer Test 1600 min. 28.35 hr

Time t = _____ at t' = 0					Water Level Data				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or y	Reading	Q		
10/30	0750				216.42				289.465			McGraw-Hill + 92-2-435
	0800	0			216.40							RAIN !!
		1:30			239.00		22.6		SLOPE INDICATOR CO			PUMP ON
		1			242.00		25.6		SEATTLE, WA			ELECTRO-PIEZO
		1:30			247.20		30.8					SEATTLE, WA
		2			253.00		36.6					MODEL 4430
		4:30			259.73		43.37					SIN 1975 SINCO
		5			271.25		54.88					5 gal/12.5 sec 0-1000
		7			315.8		99.4			7.6		5 gal/16 sec 5 gal/14 sec
		15			349.47		133.07					
		17			358.17		141.74					
		20			362.10		145.7			2.7		5 gal/12.5 sec 5 gal/14 sec
		25			369.54		152.40					5 gal/11.25 sec 5 gal/11.25 sec
		30			369.77		152.37			3.3		
		35			369.54		152.14					
		40			369.4		152.0			3.2		5 gal/11.34
		45			369.01		152.66					
		50			368.4		152.4					
		55			369.12		152.72			2.8		5 gal/11.46
		60			369.33		152.93					
		65			369.93		152.40			2.7		5 gal/11.35
		70			369.61		153.22					
		75			369.10		152.7			3.1		5 gal/11.27 1.4
		80			369.30		152.9					
		85			369.45		153.05			2.9		5 gal/11.45
		90			371.13		154.73					
		95			371.19		154.73			3.0		5 gal/11.28 1:52
		100			371.00		154.6			2.65		5 gal/11.42 2:00
		105			370.49		154.11		154.08	2.9		5 gal/11.45
		110			370.72		154.53			2.7		5 gal/11.50
		115			370.35		153.95			2.9		5 gal/11.42
		120			370.66		154.26			2.6		
		125			370.46		154.06					
		130			369.90		153.50			2.8		5 gal/11.46
		135			370.35		153.95					5 gal/11.46
		140			369.57		153.17					5 gal/11.52
		145			369.27		152.87					5 gal/11.50
		150			370.23		153.63					5 gal/11.51
		155			370.40		154.01					5 gal/11.49

Aquifer Test Data

page 2 of 3

Data for Well 299-W7-2

Pumping Well 299-W7-3

Observation Wells 299-W7-2

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE 2D

How Q Measured Flowmeter / 5 gal. calibrated bucket

How W.L.'s Measured E-TAPE / TRANSVERSE

Depth of Pump/Airpipe 451' below land

Rad./Dist. of/From Pumping Well —

Pump On: date 10/30/87 time 0800

Meas. Point for W.L.'s T/STRAINING PIPE 4.89' LS

Pump Off: date 10/31/87 time 12:5

Elevation of Meas. Point —

Duration of Aquifer Test —

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>216.40</u>							
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	840			370.1		153.70				KCO	5 G/L
	900			370.27		153.87		2.5			980 - 1:58
	960			370.45		154.05		2.9			920 - 1:45
	1020			370.4		154.00		2.7	960		880 - 1:53
	1080			370.28		153.88		2.7	1020		820 - 1:50
	1140			370.65		154.25		2.3	1080		760 - 1:46
	1200			370.5		154.10		2.7			1190 - 1:50
	1260			369.6		153.20		2.9			1200 - 1:48
	1320			369.2		152.90		2.9			1260 - 1:44
	1380			369.43		153.03		2.7			1320 - 1:50
	1440			369.59		153.19		2.5			1380 - 2:01
	1500			369.02		152.62		2.8			1440 - 1:47
	1560			367.9		151.40		2.7			1500 - 1:53
	1620			367.99		151.49		2.7			1560 - 1:50
	1680			367.6		151.20		2.9			1620 - 1:44
	1695							3.1			1680 1:38
										mean Q = 2.8 gpm SPA 12/1/87	
										First 30 min of	
										test disregarded	
										for figuring mean.	

Aquifer Test Data

page 3 of 3

Data for Well 299-W7-3

Pumping Well 299-W7-3

Observation Wells _____

Location 200 WEST RCH

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured 5 gal calibrated bucket

How W.L.'s Measured E-TAPE / TRANSDUCER Depth of Pump/Airpipe 451' below land

Rad./Dist. of/From Pumping Well _____ Pump On: date 10/30/89 time 0800

Meas. Point for W.L.'s 1" STILLING PIPE 4.09' ASD Pump Off: date 10/31/89 time 1215

Elevation of Meas. Point _____ Duration of Aquifer Test 28.25 hr

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>216.40</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	ft or s'	Reading	Q	
10/3	1200										
	1215	16.85	0		347.09		150.69		KCO	PUMP OFF	
		145.5	30	2.91	346.56		150.16				
		696	1	1696	345.87		149.47				
		1094.5	1:30	1.31	344.97		148.57				
		1697	2	848.5	344.14		148.04				
		1698	3	566	343.08		146.68				
		1699	4	414.8	342.06		145.6				
		1700	5	340	340.77		144.37				
		1702	7	257.1	338.27		141.87		CSL		
		1704	9	189.3	335.76		139.36				
		1706	11	155.1	333.22		136.82				
		1708	13	131.4	330.84		134.44				
		1710	15	114	348.34		131.94				
		1715	20	85.3	342.35		125.95				
		1720	25	69.3	336.14		120.24				
		1725	30	57.5	331.00		114.6				
		1730	35	49.4	325.67		109.27				
		1735	40	43.4	320.14		103.74				
		1740	45	38.7	315.24		98.84				
		1745	50	34.9	310.26		93.86				
		1755	60	27.3	300.79		84.39				
		1765	70	25.2	292.30		75.9				
		1775	80	22.2	284.20		67.8				
		1785	90	19.8	276.54		60.16				
		1795	100	18	269.72		52.32				
		1805	110	16.4	262.22		46.82				
		1815	120	15.1	257.48		41.08				
		1825	130	12.3	242.95		36.55				
		1835	140	10.4	232.22		31.82				

Aquifer Test Data

page 1 of 2

Data for Well 299-W7-2

Pumping Well 299-W7-3

Observation Wells 299-W7-2

Location 200 WEST RCHA

Type of Aquifer Test STEP DD DEVELOPMENT

How Q Measured 5 gal calico bucket flow rate

How W.L.'s Measured E-TAPE T24-3000000 0-10' range

Rad./Dist. of/From Pumping Well 30'

Meas. Point for W.L.'s T/C 2.5' ABV LSP

Elevation of Meas. Point

Depth of Pump/Airpipe 451' LSP

Pump On: date 10/27/87 time 1600 hr

Pump Off: date 10/29/87 time 1800 hr

Duration of Aquifer Test

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level 214.41' MP							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
9/29	1557	0			214.41						CSC 3.5" O.D. Pump Casing 8" I.D. casing
	1600	0									START PUMP
	20				214.42						
	25				214.42						
	50				214.43						
	70				214.42						
	90				214.42						
	100				214.42						
	120				214.43						Pump Off
	0750				214.50						
10/29	0900	0			214.50						START OF CONSTANT-RISER AQUIFER TEST
	15				214.50						
	15				214.51						
	35				214.51						
	55				214.50						
	45				214.50						
	110				214.51						Sampling ~ 2.5 min
	120				214.51						
	150				214.51						
	210				214.50						
	240				214.50						
	240				214.48						
	300				214.47						
	360				214.47						
	480				214.46						
	540				214.46						
	1000				214.46						
	1100				214.46						
	1200				214.46						
	1300				214.46						
	1400				214.46						
	1500				214.46						
	1600				214.46						
	1700				214.46						
	1800				214.46						
	1900				214.46						
	2000				214.46						
	2100				214.46						
	2200				214.46						
	2300				214.46						
	2400				214.46						
	2500				214.46						
	2600				214.46						
	2700				214.46						
	2800				214.46						
	2900				214.46						
	3000				214.46						

Aquifer Test Data

page 2 of 2

Data for Well 209-WF-2

Pumping Well 209-WF-2

Observation Wells 209-OB-1

Location 200 WEST PCA

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured 5 gal calibrated bucket

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well 30'

Meas. Point for W.L.'s T/C 2.5' above LWD

Elevation of Meas. Point _____

Depth of Pump/Airpipe 45.1 45.1

Pump On: date 10/30/82 time 0900

Pump Off: date 10/31/82 time 1215

Duration of Aquifer Test 29 hr 28.25 hr

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level _____					Reading	Q		
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'					
	1200				214.45								
	1201				214.46								
	1202				214.47								
	1203				214.48								
	1204				214.49								
	1205				214.50								
	1206				214.51								
	1207				214.52								
	1208				214.53								
	1209				214.54								
	1210				214.55								
	1211				214.56								
	1212				214.57								
	1213				214.58								
	1214				214.59								
	1215				214.60								
	1216				214.61								
	1217				214.62								
	1218				214.63								
	1219				214.64								
	1220				214.65								
	1221				214.66								
	1222				214.67								
	1223				214.68								
	1224				214.69								
	1225				214.70								
	1226				214.71								
	1227				214.72								
	1228				214.73								
	1229				214.74								
	1230				214.75								
	1231				214.76								
	1232				214.77								
	1233				214.78								
	1234				214.79								
	1235				214.80								
	1236				214.81								
	1237				214.82								
	1238				214.83								
	1239				214.84								
	1240				214.85								
	1241				214.86								
	1242				214.87								
	1243				214.88								
	1244				214.89								
	1245				214.90								
	1246				214.91								
	1247				214.92								
	1248				214.93								
	1249				214.94								
	1250				214.95								
	1251				214.96								
	1252				214.97								
	1253				214.98								
	1254				214.99								
	1255				215.00								
	1256				215.01								
	1257				215.02								
	1258				215.03								
	1259				215.04								
	1300				215.05								
	1301				215.06								
	1302				215.07								
	1303				215.08								
	1304				215.09								
	1305				215.10								
	1306				215.11								
	1307				215.12								
	1308				215.13								
	1309				215.14								
	1310				215.15								
	1311				215.16								
	1312				215.17								
	1313				215.18								
	1314				215.19								
	1315				215.20								
	1316				215.21								
	1317				215.22								
	1318				215.23								
	1319				215.24								
	1320				215.25								
	1321				215.26								
	1322				215.27								
	1323				215.28								
	1324				215.29								
	1325				215.30								
	1326				215.31								
	1327				215.32								
	1328				215.33								
	1329				215.34								
	1330				215.35								
	1331				215.36								
	1332				215.37								
	1333				215.38								
	1334				215.39								
	1335				215.40								
	1336				215.41								
	1337				215.42								
	1338				215.43								
	1339				215.44								
	1340				215.45								
	1341				215.46								
	1342				215.47								
	1343				215.48								
	1344				215.49								
	1345				215.50								
	1346				215.51								
	1347				215.52								
	1348				215.53								
	1349				215.54								
	1350				215.55								
	1351				215.56								
	1352				215.57								
	1353				215.58								
	1354				215.59								
	1355				215.60								
	1356				215.61								
	1357				215.62								
	1358				215.63								
	1359				215.64								
	1400				215.65								
	1401				215.66								
	1402				215.67								
	1403				215.68								
	1404				215.69								
	1405				215.70								
	1406				215.71								
	1407				215.72								
	1408				215.73								
	1409				215.74								
	1410				215.75								
	1411				215.76								
	1412				215.77								
	1413				215.78								
	1414				215.79								
	1415				215.80								
	1416				215.81								
	1417				215.82								
	1418				215.83								
	1419				215.84								
	1420				215.85								
	1421				215.86								
	1422				215.87								
	1423				215.88								
	1424				215.89								
	1425				215.90								
	1426				215.91								
	1427				215.92								
	1428				215.93								
	1429				215.94								
	1430				215.95								
	1431				215.96								
	1432				215.97								
	1433				215.98								
	1434				215.99								
	1435				216.00								
	1436				216.01								
	1437				216.02								
	1438				216.03								
	1439				216.04								
	1440				216.05								
	1441				216.06								
	1442				216.07								
	1443				216.08</								

Agribus Test Data

Date: _____
 Page: _____
 Version: _____

The following table shows the results of the tests conducted on the Agribus system. The data is presented in a tabular format, with columns for the test name, the test results, and the test status. The test results are presented in a tabular format, with columns for the test name, the test results, and the test status.

Test Name	Test Results	Test Status
Test 1	Pass	Pass
Test 2	Fail	Fail
Test 3	Pass	Pass
Test 4	Fail	Fail
Test 5	Pass	Pass
Test 6	Fail	Fail
Test 7	Pass	Pass
Test 8	Fail	Fail
Test 9	Pass	Pass
Test 10	Fail	Fail
Test 11	Pass	Pass
Test 12	Fail	Fail
Test 13	Pass	Pass
Test 14	Fail	Fail
Test 15	Pass	Pass
Test 16	Fail	Fail
Test 17	Pass	Pass
Test 18	Fail	Fail
Test 19	Pass	Pass
Test 20	Fail	Fail
Test 21	Pass	Pass
Test 22	Fail	Fail
Test 23	Pass	Pass
Test 24	Fail	Fail
Test 25	Pass	Pass
Test 26	Fail	Fail
Test 27	Pass	Pass
Test 28	Fail	Fail
Test 29	Pass	Pass
Test 30	Fail	Fail
Test 31	Pass	Pass
Test 32	Fail	Fail
Test 33	Pass	Pass
Test 34	Fail	Fail
Test 35	Pass	Pass
Test 36	Fail	Fail
Test 37	Pass	Pass
Test 38	Fail	Fail
Test 39	Pass	Pass
Test 40	Fail	Fail
Test 41	Pass	Pass
Test 42	Fail	Fail
Test 43	Pass	Pass
Test 44	Fail	Fail
Test 45	Pass	Pass
Test 46	Fail	Fail
Test 47	Pass	Pass
Test 48	Fail	Fail
Test 49	Pass	Pass
Test 50	Fail	Fail
Test 51	Pass	Pass
Test 52	Fail	Fail
Test 53	Pass	Pass
Test 54	Fail	Fail
Test 55	Pass	Pass
Test 56	Fail	Fail
Test 57	Pass	Pass
Test 58	Fail	Fail
Test 59	Pass	Pass
Test 60	Fail	Fail
Test 61	Pass	Pass
Test 62	Fail	Fail
Test 63	Pass	Pass
Test 64	Fail	Fail
Test 65	Pass	Pass
Test 66	Fail	Fail
Test 67	Pass	Pass
Test 68	Fail	Fail
Test 69	Pass	Pass
Test 70	Fail	Fail
Test 71	Pass	Pass
Test 72	Fail	Fail
Test 73	Pass	Pass
Test 74	Fail	Fail
Test 75	Pass	Pass
Test 76	Fail	Fail
Test 77	Pass	Pass
Test 78	Fail	Fail
Test 79	Pass	Pass
Test 80	Fail	Fail
Test 81	Pass	Pass
Test 82	Fail	Fail
Test 83	Pass	Pass
Test 84	Fail	Fail
Test 85	Pass	Pass
Test 86	Fail	Fail
Test 87	Pass	Pass
Test 88	Fail	Fail
Test 89	Pass	Pass
Test 90	Fail	Fail
Test 91	Pass	Pass
Test 92	Fail	Fail
Test 93	Pass	Pass
Test 94	Fail	Fail
Test 95	Pass	Pass
Test 96	Fail	Fail
Test 97	Pass	Pass
Test 98	Fail	Fail
Test 99	Pass	Pass
Test 100	Fail	Fail

AQUIFER TEST SUMMARY FOR WELL 299-W7-4

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 205 ft. Bottom: 470 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 203 ft. Bottom: 233 ft.

Date of Test: 11/12/87

Start Time of Test: 0745 hr

Pumping Rate: 48 gpm

Duration of Test: 420 min

Pre-test Water-level Elevation (Depth): 205.11 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	3,300	12
Recovery (Cooper and Jacob 1946)	2,800	11

Corrections Used:

Borehole Storage Effects

$t_c = 3$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. This test was conducted after the well was completed (4-in.-diameter screen).

RCRA WELL 299-W7-4
CONSTANT-DISCHARGE DRAWDOWN TEST
COOPER-JACOB METHOD
11/12/87

RCRA WELL 299-W7-4
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 11/12/87

F.37

Residual
 Drawdown
 (ft)

Aquifer Test Data

Page 1 of 2

Date for Well 299-W7-4

Pumping Well 299-W7-4

Observation Wells _____

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE DD

How Q Measured 5 gal bucket / RAD FLOWMETER = 286.053 OLB

How W.L.'s Measured E-TYPE Depth of Pump/Airpipe 229.5' below 1st

Rad./Dist. of/From Pumping Well _____ Pump On: date 11/12/87 time 0745

Meas. Point for W.L.'s T/STANDING PIPE 3.48' Pump Off: date 11/12/87 time 1445

Elevation of Meas. Point _____ Duration of Aquifer Test 7 hr

Time t = _____ at t' = 0			Water Level Data Static Water Level <u>209.59</u>					Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
11/12	0725				209.59			0	304.65		+ "excess" / constant
	0745	0			208.59			0			down 1 ft. 1.4 ft. from 1st
		1:40			215.13			6.54			down
		1			215.26			6.67			
		1:30			215.36			6.77			
		2			215.40			6.81			
		3			215.42			6.83	46		10 gal / 12.5 sec (meter)
		4			215.42			6.83			
		5			215.47			6.98	47.6		10 gal / 12.6 sec
		6			215.49			6.90			
		9			215.53			6.94			
		11			215.55			6.96	48.8		10 gal / 12.3 sec
		13			215.58			6.99			
		15			215.60			7.01	51.7		5 gal bucket / 5.8 sec
		20			215.64			7.05			near well head
		25			215.68			7.09			
		30			215.72			7.13	48.4		10 gal / 12.4 sec
		35			215.75			7.16	48.8		10 gal / 12.3 sec
		40			215.77			7.20	48.4		10 gal / 12.4 sec
		45			215.83			7.24	48.4		10 gal / 12.5 sec
		50			215.85			7.26	47.6		10 gal / 12.5 sec
		60			215.89			7.29	47.15	48	10 gal / 12.5 sec
		70			215.91			7.32	48.8		10 gal / 12.3 sec
		80			215.95			7.36	48		10 gal / 12.5 sec
		90			215.98			7.39	48.4		10 gal / 12.4 sec
		100			215.99			7.40	47.6		10 gal / 12.4 sec
		110			216.02			7.43	47.6		10 gal / 12.6 sec
		120			216.04			7.45	48		10 gal / 12.5 sec
		130			216.11			7.52	47.6		10 gal / 12.6 sec
		140			216.15			7.56	48.8		10 gal / 12.3 sec
		210			216.19			7.60	48		10 gal / 12.5 sec
		240			216.20			7.61	48		10 gal / 12.5 sec
		270			216.23			7.64	48		10 gal / 12.5 sec
		300			216.26			7.67	47.6		10 gal / 12.6 sec
		360			216.28			7.69	48.218	47.6	10 gal / 12.6 sec
		420							51093	48	10 gal / 12.5 sec
											Avg. 48 gpm

Aquifer Test Data

page 201 of 2

Date for Well 299-WF-4

Pumping Well 299-WF-4

Observation Wells —

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured FLOWMETER / 5 gal bucket

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s T/SINKING PIPE 3.42' ABV

Elevation of Meas. Point 152

Depth of Pump/Airpipe INTAKE 229.5' below 152

Pump On: date 11/12/97 time 0745

Pump Off: date 11/12/97 time 1445

Duration of Aquifer Test 7 hr

Time			Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0			Static Water Level <u>208.59' MP</u>								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
11/12	1445	0	0					0			Pump Off
		30			209.11			0.52			
		1			209.13			0.54			
		1:30			209.10			0.51			
		2			209.13			0.54			
		3			209.12			0.53			
		4			209.11			0.52			
		5			209.12			0.53			
		7			209.12			0.53			
		9			209.14			0.55			
		11			209.15			0.56			
		14			209.11			0.52			
		15			209.12			0.53			
		20			209.14			0.55			
		25			209.12			0.53			
		30			209.11			0.52			
		35			209.09			0.50			
		40			209.07			0.48			
		45			209.04			0.45			
		50			209.03			0.44			
		60			209.01			0.42			
		70			208.99			0.40			
		80			208.96			0.37			
		90			208.94			0.35			
		100			208.90			0.31			
		110			208.88			0.29			
		120			208.86			0.27			
		150			208.82			0.23			
		180									

Agarose Gel Data

Date: _____
 Run by: _____
 Purpose: _____
 Sample Name: _____

Lane 1: DNA Ladder
 Lane 2: _____
 Lane 3: _____
 Lane 4: _____
 Lane 5: _____
 Lane 6: _____
 Lane 7: _____
 Lane 8: _____
 Lane 9: _____
 Lane 10: _____

Lane	Band 1 (kb)	Band 2 (kb)	Band 3 (kb)	Band 4 (kb)	Band 5 (kb)	Band 6 (kb)	Band 7 (kb)	Band 8 (kb)	Band 9 (kb)	Band 10 (kb)
1	10.0	8.0	6.0	5.0	4.0	3.0	2.0	1.5	1.0	0.5
2										
3										
4										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										
21										
22										
23										
24										
25										
26										
27										
28										
29										
30										
31										
32										
33										
34										
35										
36										
37										
38										
39										
40										
41										
42										
43										
44										
45										
46										
47										
48										
49										
50										

AQUIFER TEST SUMMARY FOR WELL 299-W7-5

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery ()

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 210 ft. Bottom: 460 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 208 ft. Bottom: 228 ft.

Date of Test: 11/21/87

Start Time of Test: 1100 hr

Pumping Rate: 4.4 gpm

Duration of Test: 360 min

Pre-test Water-level Elevation (Depth): 209.75 ft (unknown measuring point).

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	170	0.7

Corrections Used:

Borehole Storage Effects

$t_c = 59$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. This test was conducted after the well was completed (4-in.-diameter screen).

RCRA WELL 299-W7-5
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 11/21/87

F.42

Drawdown
 (ft)

Aquifer Test Data

53,842

page 1 of 2

Data for Well 299-W7-5

Pumping Well

Observation Wells

Location 200 West Area RCRA Wells

Type of Aquifer Test Constant-Discharge

How Q Measured Flow Meter / 5 gal bucket

How W.L.'s Measured E-Tape

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s

Elevation of Meas. Point

Depth of Pump/Airpipe

Pump On: date 11/21/87 time 11:00

Pump Off: date 11/21/87 time 17:00

Duration of Aquifer Test 6 hr

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level 209.75								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	10:59						209.75					
	11:00	0:30					212.54	2.79				
		1:00					212.52	2.77				
		1:30					212.53	2.78				
		2:00					212.53	2.78				
		3					212.58	2.83				
		4					212.62	2.87				
		5					212.61	2.86				
		7					212.85	3.10				
		9					212.98	3.23				
		11					213.06	3.31				
		13					213.09	3.34				
		15					213.22	3.47				
		20					213.34	3.59	~66 gpm		50 Sec 5 gal bucket	
		25					213.49	3.74				
		30					213.60	3.85				
		35					213.62	3.87				
		40					213.65	3.90				
		45					213.68	3.93				
		50					213.72	3.97				
	12:00	60					213.74	3.99				
		70					214.07	4.32				
		80					214.10	4.35				Flow meter reads 53.5
		90					214.15	4.40				@ 12:21 ~ 5 gpm 1:06 to fill
		100					214.16	4.41				fill 5 gal bucket
		110					214.19	4.44				
	13:00	120					214.30	4.55				Flow meter reads 53.2
		150					214.28	4.53				took first set of samples
	14:00	180					214.40	4.65	GVL	5 gpm 1:06 to fill		
		210					214.41	4.66	GVL	5 gal bucket		
	15:00	240					214.41	4.66	GVL	5 gal bucket		
		270					214.49	4.74	~5 gpm	GVL	5 gal bucket / 56 sec	
	16:00	300					214.59	4.84	~5 gpm	GVL	Flow meter reads 54.010 at 13:36	
	16:30	330					214.63	4.88	GVL	5 gal bucket / 58 sec		
	17:00	360					214.77	5.02	GVL	PUMP OFF		
												TOTAL IN FLOW METER = 54.999

AVG DISCHARGE ~ 4.4 gpm

Aquifer Test Data

page 2 of 2

Data for Well 294-W7-S

Pumping Well 294-W7-S

Observation Wells _____

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured FLOWMETER / CALIBRATED 5 gal bucket

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe _____

Rad./Dist. of/From Pumping Well _____

Pump On: date 11/21/87 time 1100

Meas. Point for W.L.'s _____

Pump Off: date 11/21/87 time 1700

Elevation of Meas. Point _____

Duration of Aquifer Test 6 hr

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>209.75</u>					Read- ing			
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s' or s'			Q		
	1700	300	0				214.77	5.02				GVL	
			30				213.6	3.41				GVL	
			1				212.20	3.05				GVL	
			30				212.67	2.92				GVL	
			2				211.33	2.58				GVL	
			8				211.81	2.06				GVL	
			4				211.47	1.72				GVL	
			5				211.14	1.29				GVL	
			7				210.46	2.31				GVL	
			9				210.88	0.33				GVL	
			11				209.91	0.16				GVL	
			13				209.84	0.09				GVL	
	1715		15				209.83	0.08				GVL	
	1720		20				209.82	0.07				GVL	
	1725		25				209.83	0.08				GVL	
			30				209.85	0.10				GVL	
			35				209.87	0.12				GVL	
			40				209.89	0.14				GVL	
			45				209.82	0.07				GVL	
			50				209.88	0.13				GVL	
			60				209.87	0.12				GVL	
			70				209.93	0.18				GVL	
			80										
			90										
			100										
			110										
			120										
			150										
			180										

AQUIFER TEST SUMMARY FOR WELL 299-W7-6

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 215 ft. Bottom: 460 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 231 ft. Bottom: 241 ft.

Date of Test: 10/14/87

Start Time of Test: 0745 hr

Pumping Rate: 7 gpm

Duration of Test: 480 min

Pre-test Water-level Elevation (Depth): 215.12 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	14	0.06
Recovery (Cooper and Jacob 1946)	40	0.16

Correction Used:

Borehole Storage Effects

$t_c = 39$ min (Schafer 1978)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The recovery data indicate that well entrance losses occurred (Hargis 1979).

RCRA WELL 299-W7-6
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 10/16/87

F.46

Drawdown
 (ft)

RCRA WELL 299-W7-6
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 10/14/87

F.47

Residual
 Drawdown
 (ft)

D/INTAKE = 238' below land surface
 TOP OF TRENCH = 3.44' above land

Water Level Data

Well or Date 250-W7-1e

Project 200 W RCEA
 Well Location STEP DRAINDOWN
 Time Pump on: 13:36
 Time Pump off: meter - 18,857

Measuring Point Top of 3/4" trench
 Elevation: Mercury Point —
 Elevation: Ground Level —

Well or Date	Time	Measuring Device	Reading	Conversions or Corrections	Water Level		By	Comments/ Weather
					Depth	Elevation		
	0		218.58'					
	1:30		220.59					
	1:00		221.14					meter - rate x 20 gpm
	1:30		221.65					
	2		221.96					
	3		222.44					
	4		223.05					
	5		224.69					
	7		232.14					disconnected discharge hose while pump was running
	9		240.05					discharge rate = 4.2 gpm
	11		240.06					
	12		—					
	13:25		238.66					valve was closed slightly
	15		238.80					(manual) = 11 gpm
	20		240.06					
	25		240.03					
	30		238.51					valve was closed slightly
	35		235.59					@ 29.40 minutes (manual) = 4.28 gpm
	40		234.24					opened valve slightly
	45		234.81					(manual) = 8.1 gpm
	50		235.45					
	60		235.92					
	70		235.28					
	95		234.15					(manual) = 6.5 gpm
	110		233.60					Disconnected discharge line across road for trailer to cross.
								opened valve slightly
								water draining down to intake
								shut valve slightly
	120		240.05					
	130		239.12					7.5 gpm (manual)
	140		238.62					~7.5 gpm (manual)
	150		238.53					
	160		238.39					7 gpm (manual)

1636 180 222 60 F.162 161 18962 PUMP - 150

Aquifer Test Data

page 1 of 2

Data for Well 299-W7-6

Pumping Well 299-W7-6

Observation Wells

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE DD

How Q Measured 5 gal calibrated bucket / FLOWMETER AQATS 226.053068

How W.L.'s Measured E-TAPE / TRANSDUCER Depth of Pump/Ac pipe 238' Below 1st

Rad./Dist. of/From Pumping Well 0 Pump On: date 10/14/87 time 0745

Meas. Point for W.L.'s TOP STIMULING PIPE Pump Off: date 10/14/87 time 1545

Elevation of Meas. Point 217.91 ± .77 Duration of Aquifer Test 8 hr

TOP STIMULING PIPE LSD TO TOP STIMULING PIPE 2.8 ± .77

STAG LATE
21868

Time				Water Level Data				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level s or s'	Reading	Q		
	0745	1:30			218.96		2.27	18962			FLOWMETER
		1:00			219.22		.53				NOT WORKING
		1:30			219.46		.77				2" Diameter Pipe
		2			219.62		.93				5" Diameter
		3			220.00		1.31				
		4			220.26		1.57				checking bucket rate
		5			220.48		1.79		2.5		Bucket = 7.500m
		7			220.90		2.21				re-connect to hose
		9			221.20		2.51				
		11			221.33		2.64				
		13			221.52		2.83				
	0800	15			221.64		2.95				
		20			221.93		3.24			CSC	
		25			222.16		3.47			CSC	
		30			222.58		3.64		7.5	CSC	
		35			223.22		4.53			CSC	
		40			223.98		5.29			CSC	
		45			224.85		6.16			CSC	
	5:20	50			227.24		6.55			CSC	
	5:40	55			228.20		7.51				
	6:00	60			229.38		10.66				SAMPLES COLLECTED
	6:15	65			231.17		12.48		6.8		
	6:30	70			231.61		12.92		6.5		adjusting valve to bring back up to 7.5 gpm
	6:45	75			232.55		13.86		7.3		5 gpm
	7:00	80			233.70		15.01		7.0		5 gpm
	7:15	85			235.80		17.11		7.1		5 gpm
	7:30	90			236.70		18.01		7.1		5 gpm
	7:45	95			237.64		19.95		7.1		5 gpm
	8:00	100			237.70		18.31		6.8		samples collected
	8:15	105			240.0		21.31		7.2		increased discharge
	8:30	110			240.10		21.41		7.0		
	8:45	115			240.11		21.42		7.0		water down at intake
	9:00	120			240.11		21.42		7.0		Gathered Sample

Aquifer Test Data

page 2 of 2

Data for Well 299-W7-6

Pumping Well 299-W7-6

Observation Wells -

Location RCR 200 WEST

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured Sgt. Calibrated bucket

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well -

Meas. Point for W.L.'s TOP STILLING PIPE 3.57' AND

Elevation of Meas. Point -

Depth of Pump/Airpipe 238' RIW 1st

Pump On: date 10/14/87 time 0745

Pump Off: date 10/14/87 time 1545

Duration of Aquifer Test 8-hr

Time					Water Level Data				Discharge		Recorded By	Comments	
t = 480 at t' = 0					Static Water Level 218.69'								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	ft or s		Reading	Q		
10/14	1545	480	0		240.11			21.42				CK	
			10		238.95			20.26					
			1		238.47			19.78					
			1.10		238.03			19.34					
			2		237.34			18.65					
			3		236.35			17.66					
			4		235.07			16.39					
			5		234.31			15.62					
			7		232.47			13.78					
			9		230.91			12.22					
			11		229.46			10.77					
			13		228.17			9.48					
			15		226.77			8.08					
			20		224.50			5.81					
			25		223.54			4.85					
			30		222.95			4.26					
			35		222.51			3.82					
			40		222.24			3.55					
			45		222.09			3.40					
			50		221.98			3.29					
			60		221.76			3.07					
			70		221.51			2.82					
			80		221.21			2.52					
			90		220.94			2.35					
			100		220.65			1.96					
			110		220.37			1.68					
			120		220.17			1.48					
			150		219.78			1.09					
			180		219.54			0.85					

Great recovery in
w.m. increasing

AQUIFER TEST SUMMARY FOR WELL 299-W8-1

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 236 ft. Bottom: 510 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 257 ft. Bottom: 267 ft.

Date of Test: 07/11/87

Start Time of Test: 0800 hr

Pumping Rate: 8.7 gpm

Duration of Test: 360 min

Pre-test Water-level Elevation (Depth): 236.10 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Recovery (Cooper and Jacob 1946)	80	0.3

Correction Used:

Borehole Storage Effects

$t_c \sim 20$ min (Schafer 1978)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The drawdown data indicate that the aquifer test was influenced by boundary effects.

RCRA WELL 299-W8-1
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 7/11/87

F.52

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 1

Data for Well 2W8-1

Pumping Well 2W8-1

Observation Wells —

Location 200 West

Type of Aquifer Test STEP DD

How Q Measured 5 gal bucket

How W.L.'s Measured E-TAPE/STEEL TAPE

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s Traverse Pipe 3.72'

Elevation of Meas. Point —

SCREEN DOWN TO 264'

Depth of Pump/Airpipe 264'

Pump On: date 7/10/87 time —

Pump Off: date — time —

Duration of Aquifer Test —

Time			Water Level Data					Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	for s'	Reading	Q	
7/10	1730	0			238.75				101530		
		:30			242.4						
		1			243.1					25	
		1:30			244.74						
		2			247.99				101530		
		3			251.28						
		4			252.27						
		5			253.92						
		7			259.42						NO MEASUREMENT BELOW 263
		9									
		11									
		13									
		15									
		17									
		19									
		20									
		25									
		30									
35:37	5:12:30	6.59	21.8		263	24.25					RECOVERY
36:11	6:06:30	6.59	21.8		262	23.25					8" 1.96 0.75
36:41	6:36:30	6.59	21.8		261	22.25					Traverse 1 1/16"
37:28	7:16:50	5.12	26.0		260	21.25					to calculate
38:11	8:06:57	4.7	25.9		259	20.25					
38:59	8:52:45	4.37	25.8		258	19.25					
39:31	9:48:33	4.26	25.7		257	18.25					
40:05	10:51:11	3.77	25.6		256	17.25					
40:30	12:41:32	3.36	25.5		255	16.25					
45:05	15:03:04	2.99	25.4		254	15.25					
47:12	17:02:45	2.35	25.3		253	14.25					
50:37	20:58:36	2.43	25.2		252	13.25					
56:40	21:24:—	2.14	25.1		251	12.25					
58:43	22:26:—	2.06	25.0		250	11.25					
59:53	23:34:—	2.01	24.9		249	10.25					
61:17	31:10:08	1.96	24.8		248	9.25					
62:47	32:40:26	1.92	24.7		247	8.25					
64:09	34:53:22	1.86	24.6		246	7.25					
66:09	36:53:64	1.81	24.5		245	6.25					
70:44	40:26:23	1.74	24.4		244	5.25					
75:39	45:28:42	1.66	24.3		243	4.25					
89:32	59:43:57	1.50	24.2		242	3.25					

Aquifer Test Data

page 1 of 2

Data for Well 299-WB-1

Pumping Well 2-WB-1

Observation Wells Bu. P. D.

6-49-79

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured calibrated 5 gal bucket off of hose

How W.L.'s Measured E-Tape

Depth of Pump/Airpipe 264'

Rad./Dist. of/From Pumping Well

Pump On: date 7/11/87 time 0800

Meas. Point for W.L.'s TOP TRUNK / 2.72' APR

Pump Off: date 7/11/87 time 1400

Elevation of Meas. Point

Duration of Aquifer Test 6 hr.

Time t = _____ at t' = 0				M.P. Water Level Data Static Water Level <u>E-TAPE 238.82</u> Discharge <u>238.91</u>				Recorded By	Comments
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or d		
	0800	0				238.82	0		E-TAPE MEASUREMENTS
		:30				241.84	3.02		should be made
		1:00				242.18	3.36		at bottom of
		:30				242.24	3.42		well
		2				242.38	3.56		water discharge rate
		3				242.60	3.84		measured from end
		4				243.0	4.18		of fire hose ~5 ft
		5				243.106	4.28		from gate valve
		6				244.34	5.52		
		9				246.65	7.83	8.2	5.06 / 35 sec
12	11					248.23	9.41	8.2	5.06 / 35 sec
		13							
		15				249.81	10.99		
		20				251.05	12.23		
		25				251.42	12.60	8.4	5.06 / 34 sec
		30				251.71	12.89		
		35				252.08	13.26	8.7	5.06 / 34 sec
		40				252.38	13.56		
		45				252.51	13.69	8.8	5.06 / 34.5 sec
		50				252.74	14.42		
0900	60					254.32	15.56	8.7	5.06 / 35 sec
	71					255.0	16.19	8.6	5.06 / 35.5 sec
	80					255.12	16.30	8.7	5.06 / 35 sec
97	90					257.58	18.76		
	100					257.76	18.94	8.8	5.06 / 34.5 sec
	110								
1000	120					259.18	20.36	8.9	5.06 / 34 sec
	150					260.22	21.40	8.6 (8.5)	5.06 / 35.5 sec
1100	180					260.32	21.4	8.4 (8.4)	5.06 / 36 sec
	210					261.11	22.29	8.9	5.06 / 34 sec
1200	240					261.95	23.13	9.6 (8.5)	5.06 / 35.5 sec
	270					262.4	23.58	8.7	5.06 / 35 sec
1300	300					262.70	23.88	8.4	5.06 / 36 sec
330	360					262.96	24.14		
	360							8.2	5.06 / 35 sec
360									start Recovery
									below 263
									no measure

avg. 8.7 gpm

Aquifer Test Data

page 2 of 2

Data for Well 2W3-1

Pumping Well 2W3-1

Observation Wells _____

Location 300 West

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured Calibrated Speed bucket

How W.L.'s Measured FAIR

Depth of Pump/Airpipe 264'

Rad./Dist. of/From Pumping Well _____

Pump On: date 7/11/82 time 1900

Meas. Point for W.L.'s Top of casing 2.32' ASL

Pump Off: date 7/11/82 time 1900

Elevation of Meas. Point _____

Duration of Aquifer Test 4 hrs

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>238.82</u>					Reading	Q		
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	for s'					
	1400	360	0				226.3					CSC	
			1:30	72.1			26.79	23.08				CSC	
			1	36.1			26.93	23.13				CSC	
			1:30	24.1			26.1	22.18				CSC	
			2	18.1			25.22	21.45				CSC	
			3	12.1			25.38	20.44				CSC	
			4	9.1			25.15	19.33				CSC	
			5	7.3			25.15	18.36				CSC	
			6				25.15	17.4				CSC	
			7	52.4			25.56	16.78				CSC	
			9	41			25.47	15.97				CSC	
			11	33.7			25.47	15.35				CSC	
			13	27.7			25.3	14.48				CSC	
			15	25			25.17	13.85				CSC	
			20	19			25.18	12.98				CSC	
			25	15.4			25.09	12.27				CSC	
			30	13			24.85	9.77				CSC	
			35	11.3			24.68	7.56				CSC	
	400	40	10				24.70	5.88				CSC	
		45	9				24.38	4.98				CSC	
	410	50	8.2				24.13	4.31				CSC	
56	416	55	7.4				24.22	3.90				CSC	
	420	60	7				24.25	3.71				CSC	
	430	70	6.14				24.18	3.32				CSC	
	440	80	5.5				24.17	2.94				CSC	
	450	90	5				24.12	2.46				CSC	
	460	100	4.6				24.08	1.86				CSC	
	470	110	4.2				24.03	1.51				CSC	
	480	120	4				24.01	1.34				CSC	
		510	150	3.4			23.82	1.0				CSC	
	1700	540	180	3.0			23.93	.81				GVL	
	1730	570	210	2.71			23.94	.64				GVL	
	1800	600	240	2.5			23.93	.49				GVL	
	1830	630	270	2.33			23.92	.40				GVL	
	1900	660	300	2.2			23.91	.31				GVL	
	1930	690	330	2.09			23.90	.25				GVL	
	2000	720	360	2.0			23.90	.20				GVL	
	2030	750	390	1.92			23.89	.17				GVL	
	2140	820	460	1.78			23.89	.11				GVL	

7/12/82 1325 1765 1905 1.26

238.72 -10

P10602

Page No. _____
 Date of Test _____
 Name of Candidate _____
 Name of Examiner _____

Admission Test Date

Sl. No.	Name of Candidate	Date of Birth	Gender	Religion	Nationality	Marital Status	Education	Occupation	Address	Contact No.	Email ID	Signature	Remarks
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													
14													
15													
16													
17													
18													
19													
20													
21													
22													
23													
24													
25													
26													
27													
28													
29													
30													
31													
32													
33													
34													
35													
36													
37													
38													
39													
40													
41													
42													
43													
44													
45													
46													
47													
48													
49													
50													
51													
52													
53													
54													
55													
56													
57													
58													
59													
60													
61													
62													
63													
64													
65													
66													
67													
68													
69													
70													
71													
72													
73													
74													
75													
76													
77													
78													
79													
80													
81													
82													
83													
84													
85													
86													
87													
88													
89													
90													
91													
92													
93													
94													
95													
96													
97													
98													
99													
100													

AQUIFER TEST SUMMARY FOR WELL 299-W9-1

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test (x) Specific Capacity () Constant Discharge () Recovery ()

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 272 ft. Bottom: 487 ft (interpolated to top of lower Ringold).

Depth of Screened Interval in Pumped Well, Top: 266 ft. Bottom: 286 ft.

Date of Test: 10/23/87

Pre-test Water-level Elevation (Depth): 271.70 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Slug Withdrawal		
(Bouwer and Rice 1976)	55	0.26
(Hvorslev 1951)	43	0.2

RCRA WELL 299-W9-1
SLUG-WITHDRAWAL TEST
BOUWER-RICE UNCONFINED METHOD
10/23/87

RCRA WELL 299-W9-1
SLUG WITHDRAWAL TEST
HVORSLEV METHOD
10/23/87

F.59

LOG (H/H₀)

Aquifer Test Data

SLUG TEST

page 1 of 2

Data for Well 299-W9-1

Pumping Well

Observation Wells

Location 200 WEST RCRA

Type of Aquifer Test SLUG TEST

How Q Measured

How W.L.'s Measured E-TAPE - TRANSDUCER

Depth of Pump/Airpipe No PUMP NA

Rad./Dist. of/From Pumping Well

Pump On: date 10/23/87 time 11:00 hr

Meas. Point for W.L.'s T/C 2.57' Above L.S.D

Pump Off: date 10/23/87 time

Elevation of Meas. Point

Duration of Aquifer Test

1/4
5
33
25
20
14
10
09
077
067
05
04
038
029
025
022
02
017
014
013
01
010
009
008
007
006
5
37
25
20
14
11
09

Time t = _____ at t' = 0					Water Level Data ^{Static} TAP6				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	Head s or s'	Reading	Q		
10/23	1040				272.05	E-TAPE	4 1/4				PSC	SLUG = 10' LONG 2 3/8" O.D.
							1.00	(.89)				PIPE W/ SAND
10/23	1100	0	-		271.16	← from displacement						START TEST
		2			271.59	E-TAPE	.57	.46	Calculation			DROP SLUG
		3			271.62		.483	.43				
		4			271.64		.461	.41				2 3/8" = .1775' → 2
		5			271.67		.427	.38				$\pi r^2 = \pi (.1)^2$
		3			271.71		.382	.34				$\pi (.1)^2 \times 10' = .314'$
		10			271.77		.315	.28				8" D .31 ft ² / .348' = 81
		11			271.79		.315	.28				.31 ft ² / .087 ft ² = 3.56
		13			271.79		.292	.26				Area of 4" = 12.56
		15			271.83		.247	.22				
		20			271.86		.213	.19				(.31 ft ²) (7.48 gal / ft ²)
		25			271.90		.169	.15				= 2.32 gal
		30										
		35			271.93		.135	.12				
		40			271.95		.112	.10				
		45			271.96		.101	.09				
		50			271.97		.090	.08				
		60			271.99		.067	.06				
		70			272.00		.056	.05				
		80			272.00		.056	.05				
		90			272.01		.045	.04				
		100			272.01		.045	.04				
		110			272.01		.045	.04				
		120			272.01		.045	.04				
		150			272.00		.056	.05				
		150	0		272.09	← from calculation of displacement						PULLED SLUGS EP-N
		20			272.56							WELL
		1										
		130										
		2			272.41			.45				
		3			272.34			.39				
		4			272.36			.40				
		5			272.31			.35				
		7			272.29			.33				
		9			272.25			.29				
		11			272.23			.27				

Aquifer Test Data

SLUG TEST

page 2 of 2

Data for Well 299-W9-1

Pumping Well -

Observation Wells -

Location 200 WEST RCPA

Type of Aquifer Test SLUG TEST WITHDRAWAL

How Q Measured -

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well -

Meas. Point for W.L.'s I/C 2.57' AW LSO

Elevation of Meas. Point -

Depth of Pump/Airpipe SLUG TEST

Pump On: date 10/23/97 time 1100 hr

Pump Off: date - time -

Duration of Aquifer Test -

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>271.96</u>							
Day	Clock Time	t'	t	t/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q	
077	10/23	14:12	13		272.21			.25				CSC
067			15		272.19			.23				
05			20		272.15			.19				
04			25		272.11			.15				
033			30		272.095			.135				
026			30		272.07			.11				
025			40		272.055			.095				
022			45		272.045			.085				
02			50		272.04			.08				
017			60		272.02			.06				
014			70		272.00			.04				
013			80		271.99			.03				
011			90		271.98			.02				
010			100		271.98			.02				
009			110		271.97			.01				
008			120		271.96			.00				
007			150		271.95			-.01				
006			180		271.96			.00				

Aquifer Test Data

page 1 of 1

Data for Well 299-W9-1

Pumping Well 299-W9-1

Observation Wells _____

Location 200 WEST RCRA

Type of Aquifer Test SLUG TEST

How Q Measured —

How W.L.'s Measured E-TAPE / TRANSDUCER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/C 2.37' Abv LSD

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 10/22/87 time 1030 hr

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Steel Tape Static Water Level <u>271.72'</u>							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
<u>10/22</u>	0										SLUG 2 3/8 O.D. Pipe 10' LONG TO SHACKLE Transducer #5N 0042 Apparently drifting, replace w/ #5N 0041 0049 not in use 00420 will be used Aborted - transducer coupling pulled off by sand line
	1:30										
	1				271.6						
	1:30										
	2				271.62						
	3										
	4										
	5										
	7										
	9										
	11										
	13										

AQUIFER TEST SUMMARY FOR WELL 299-W10-13

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 229 ft. Bottom: 450 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 227.5 ft.

Bottom: 237.5 ft.

Observation Well Used: 299-W10-14 Distance to Pumped Well: 34 ft.

Elevation (Depth) of Screened Interval: Drilled to a depth of 240 ft for aquifer test (no screen).

Date of Test: 09/14/87

Start Time of Test: 0900 hr

Pumping Rate: 30 gpm

Duration of Test: 480 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 229.04 ft.

Observation Well: Unavailable.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity</u> <u>(ft²/d)</u>	<u>Hydraulic</u> <u>Conductivity</u> <u>(ft/d)</u>	<u>Storativity</u>
Recovery			
(Cooper and Jacob 1946)			
Pumping Well	7,000	32	NA
Observation Well	3,500	16	0.009

Corrections Used:

Borehole Storage Effects

$t_c = 10$ min (Schafer 1978)

$t_c = 4$ min (Hargis 1979)

Remarks: The drawdown data indicate that well entrance loss occurred during pumping. The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The latter part of the recovery data was probably influenced by daily water-level fluctuations.

RCRA WELL 299-W10-13
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 9/14/87

F.64

Residual
 Drawdown
 (ft)

F.65

Recovery
(Ft above
transducer)

Aquifer Test Data

page 1 of 1

Date for Well 299-W10-13

Pumping Well 299-W10-13

Observation Wells 299-W10-14

Location 200W RCRA

Type of Aquifer Test Constant discharge

How Q Measured Flowmeter

How W.L.'s Measured E-tape

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s Drilling pipe

Elevation of Meas. Point _____

Depth of Pump/Airpipe 246' (intake)

Pump On: date 9-14-87 time 8:30

Pump Off: date _____ time _____

Duration of Aquifer Test _____

43
1:03

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>233.0</u>								
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
9/14		1:30			233.25								281110 Flowmeter
		1			233.19								
		1:30			233.21								
		2			233.18								
		3			233.13								
		4											
		5											
		7											
		9											
		11											
		13											
		15											
		20											
		25											
		30											
		35											
		40											
		45											
		50											
		60											
		70											
		80											
		90											
		100											
		110											
		120											

page 1 of 2

Data for Well 299-w10-13

Pumping Well 299-w10-13

Observation Wells 299-W10-14

Location 200W RCRA

Type of Aquifer Test Constant discharge

How Q Measured Flowmeter / bucket

How W.L.'s Measured E-typeRad./Dist. of/From Pumping Well C

Meas. Point for W.L.'s stilling pipe 3' 11 1/2" above L.S.

Elevation of Meas. Point

Depth of Pump/Airpipe 246 (in-take)

Pump On: date 9-14-87 time 9:00

Pump Off: date 9/14/87 time 17:00

Duration of Aquifer Test 8 hr

Time			Water Level Data			Discharge		Recorded By	Comments
t =	at t' = 0		Static Water Level		233.0	Reading	Q		
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	
9/14	9:00	1:30			233.95			0.45	SST
		1:00			234.74			1.74	
		1:30			235.18			2.18	
		2			238.60			5.6	
		3			242.84			9.84	
		4			—				
		5			243.15			10.15	
		6			244.77			11.77	
		7			243.06			10.06	
		9			243.19			10.19	
		11			243.8			10.18	
		13			244.69			11.69	Hard to measure W.L. -
		15			243.66			10.66	- beyond stilling pipe
		20			244.62			11.62	Flowrate - bucket = 30 gpm
		25			243.48			10.48	
		30			244.23			11.23	
		35			244.05			11.05	
		40			243.90			10.90	
		45			243.79			10.79	
		50			243.90			10.90	
		60			243.29			10.29	
		70			242.95			9.95	Flowmeter not reading
		80			242.73			9.73	
		90			242.80			9.80	30 gpm - bucket
		100			242.80			9.80	
		110			242.86			9.86	
		120			242.92			9.92	
		130			242.85			9.85	
		140			242.85			9.85	
		150			242.95			9.95	
		160			243.08			10.08	
		210			243.05			10.05	
		240			243.47			10.47	30 gpm - bucket
		270			243.50			10.50	
		300			243.76			10.76	
		360			243.65			10.65	
		420			243.65			10.65	WIND PICKING UP
		480			244.05			11.05	GSC
								28	
								281990	

Aquifer Test Data

page 2 of 2

Data for Well 299-W10-13

Pumping Well 299-W10-13

Observation Wells 299-W10-14

Location 200 W RCRA

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured FLOWMETER

How W.L.'s Measured ETAPE

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s STILLING PIPE

Elevation of Meas. Point _____

Depth of Pump/Airpipe 246' (INTAKE)

Pump On: date 9-14-87 time 9:00 hr

Pump Off: date 9/14/87 time 1700 hr

Duration of Aquifer Test 8 hr

Time			Water Level Data					Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/1'	Reading	Conversions or Corrections	Water Level	s' or s'	Reading	Q	
9/14	1700	0	0		244.05			11.05	281990		281150 FLOWMETER
			1:30		237.04			4.01			WIND HAS BEEN
			1								BLOWING HARD
			1:30		235.75			2.75			SINCE 1600 HRS
			2								
			3		235.07			2.07			
			4		234.78			1.78			
			5		234.47			1.47			
			7		234.08			1.08			
			9		233.82			0.82			
			11		233.63			0.63			
			13		233.50			0.50			
			15		233.41			0.41			
			20		233.32			0.32			
			25		233.26			0.26			
			30		233.23			0.23			
			35		233.19			0.19			
			40		233.17			0.17			
			45		233.17			0.17			
			50		233.15			0.15			
			60		233.12			0.12			
			70		233.12			0.13			
			80		233.11			0.11			
			90		233.12			0.12			
			100		233.11			0.11			
			110		233.11			0.11			
			120		233.10			0.10			
9/15	0715				233.28			0.28			

Aquifer Test Data

page 1 of 1

Data for Well 299-W10-14

Pumping Well 299-410-13

Observation Wells 299-4310-M

Location RCRA 200 WEST

Type of Aquifer Test STEP-DN ~~RECOVERED~~ Recovery

How Q Measured Flow meter / 5 gal bucket

How W.L.'s Measured E-TAPE / TRANSOM Depth of Pump/Airpipe 246'

Rad./Dist. of/From Pumping Well 34'

Pump On: date 9/4/97 time 0900 hrs

Meas. Point for W.L.'s 1/c 3.08' ABV LD

Pump Off: date 9/14/87 time 1700 hrs

Elevation of Meas. Point _____

Duration of Aquifer Test 8 hr[illegible]

AQUIFER TEST SUMMARY FOR WELL 299-W10-14

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 230 ft. Bottom: 448 ft.

Depth of Screened Interval in Pumped Well, Top: 427 ft. Bottom: 447 ft.

Observation Well Used: 299-W10-13 Distance to Pumped Well: 34 ft.

Elevation (Depth) of Screened Interval, Top: 227 ft. Bottom: 247 ft.

Date of Test: 10/26/87

Start Time of Test: 0900 hr

Pumping Rate: 14 gpm

Duration of Test: 225 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 230.93

Observation Well: Unavailable.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Recovery (Cooper and Jacob 1946) Pumping Well	900	4	NA

Remarks: The data indicate that drawdown in the pumping well is mainly attributed to casing storage effects caused by the well configuration (screen open to the bottom of the aquifer). The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. No response was observed in the observation well.

RCRA WELL 299-W10-14
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 10/26/87

F.72

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of Date for Well 299-W10-14Pumping Well " "Observation Wells 299-W10-13Location 200W - RCRAType of Aquifer Test Step drawdownHow Q Measured flowmeterHow W.L.'s Measured E-tapeRad./Dist. of/From Pumping Well 0Meas. Point for W.L.'s Top of stilling pipeElevation of Meas. Point Depth of Pump/Airpipe 444' 2" (intake at 441' 8")Pump On: date 10-23-87 time 9:50Pump Off: date 10-23-87 time Duration of Aquifer Test

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level 233.35'							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
10/23	9:50	1:30			236.79							
		1:00			236.49							
		1:30			236.22							
		2			236.85							
		3			235.34							
		4			235.0							
		5			2							no water coming out
		7			252.67			19.32				Opened valve more
	8	8			256.70			23.35				≈ 10 gpm - meter
	9	9			260.22			24.87				
	10	10			263.10			24.75				
	11	11			265.21			21.86				
		12			267.15			33.80				
		13			268.61			35.26				
		14			268.80			36.45				
		15			270.73			37.38				
		17			272.05			38.70				check in discharge w/ bucket
		20			272.41			39.06				1900m - bucket
		25			272.30			38.95				
		30			272.42			39.07				flowmeter not working
		40			272.26			38.91				
		50			271.58			38.22				
		60			271.49							
		75			271.47							Had trouble w/ tape
		1:30			277.25							
		1:00			280.12							
		1:30			284.33							
		2			287.10							
		3			291.80							
		4			294.72							
		5			297.72							put back valve
10/23	1:30				274.19							
10/23	1:30				276.12							
	1:40				282.74							
	1:50				285.95							
	2				276.34							
	2				292.43							Back to fill seal

Aquifer Test Data

page 2 of 2

Data for Well 299-wlu-14

Pumping Well _____

Observation Wells _____

Location 200 W - RCRA

Type of Aquifer Test Step drawdown

How Q Measured bucket

How W.L.'s Measured E-tape

Rad./Dist. of/From Pumping Well 0

Meas. Point for W.L.'s top of stilling pipe

Elevation of Meas. Point _____

Depth of Pump/Airpipe (intake at 441' 8")

Pump On: date 10-23-87 time 9:50

Pump Off: date 10-23-87 time 1340

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level 233.35							
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
	12:16				287.07						Cut back 25 gpm - bucket
	12:50	180			285.15						
	13:00				285.45						
	13:20				284.99						
	13:40				284.87						Recovery (Valve left open)
			1:30		279.65						
			1:00		275.60						
			1:30		271.70						
			2		268.19						
			3		262.52						
			4		257.65						
			5		253.81						
			7		247.83						
			9		243.73						
			11		240.91						
			13		238.90						
			15		237.49						
			20		235.30						
			25		234.39						
			30		233.99						
			40		232.99						
			50		232.40						
			60		232.35						
	1504				233.33						

Aquifer Test Data

page 1 of 1

Data for Well 299-W10-13

Pumping Well 299-W10-14

Observation Wells 299-W10-13

Location 200 W - RCRA

Type of Aquifer Test Stepdrawdown

How Q Measured Flow meter / 5 gal. bucket

How W.L.'s Measured E-tape

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s top of casing (3.17' above ground)

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 10/23/87 time 9:50

Pump Off: date 10/23/87 time 13:40

Duration of Aquifer Test _____

Time					Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0					Static Water Level <u>231.72'</u>								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'		Reading	Q		
10/23		1:30			231.72							SPA	
		1:00			231.72							SPA	
		1:30			231.72							SPA	
		2			231.72							SPA	
		3			231.72							SPA	
		4			231.72							SPA	
		5			231.72							SPA	
		7			231.72							SPA	
		9			231.72							SPA	
		11			—							—	
		13			231.72							SPA	
		15			231.72							SPA	
		20			231.73							SPA	
		25			231.72							SPA	
		30			231.73							ST	
		40			231.73								
		50			231.72								
		60			231.72							↓	
		80			231.72								
		5			231.72								
	1140				231.72								
	1148				231.72								
	1204				231.72								
	1209				231.72								
	1250	180			231.70								
	1320				231.69								
	1340				231.68								
			9		231.68								
			11		231.68								
			13		231.68								
	1505				231.66								

Aquifer Test Data

page 1 of 1

Data for Well 299-W10-19

Pumping Well 299-W10-19

Observation Wells 299-W10-13

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT DISCHARGE DD

How Q Measured Flow Meter

How W.L.'s Measured S-TAPS

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s TOP OF STAINLESS PIPE 3.09'

Elevation of Meas. Point ADN LID

Depth of Pump/Airpipe 444' INTAKE 441' W

Pump On: date 10/26/87 time 0900

Pump Off: date 10/26/87 time 1400

Duration of Aquifer Test 5 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>234.02 MP</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading		
10/26	0900	0			234.02				299325		CS: MacComber
		4			252.64		18.62				82-2-435
		5			254.62		20.60				0900 hr start
		7			256.42		22.40				STANDARD TIME
		9			258.28		24.26		14.3		5 gal/21 sec
		12			259.62		25.60				Flow meter not operating
		13			259.89		25.87				either sampled in or
		15			260.84		26.32				flow too low for meter
		20			260.87		26.85				
		25			261.41		27.39		13.6		5 gal/23 5 gal/21
		30			261.50		27.48				any 5 gal/22 sec
		35			261.51		27.49		14.3		5 gal/23 5 gal/19
		40			261.50		27.48				
		45			261.57		27.55				
		50			261.54		27.52				
	1000	60			261.27		27.25		13.6		5 gal/22 5 gal/22
		70			261.49		27.43				
		90			261.45		27.43				
		90			261.24		27.22				
		100			261.15		27.12				
		110			261.13		27.11		12.2		5 gal/24.5 5 gal/24.5
	1100	120			261.47		27.45		14.3		inverse run 5 gal/sec
		150			261.14		27.12		13.6		5 gal/23 5 gal/21
	1200	180			261.12		27.10				5 gal/24 5 gal/24
	1230	210			260.95		26.92		13		pumping against
		240			261.54		27.52				head in discharge pipe
		270			261.45		27.43				when measure discharge
		300	0								using 5 gal bucket
		330			260.63						break at hose
		1			257.72						10' from valve
		1.30			255.63						this changes head
		2			253.90						we are pumping against
		3			250.50						
		4			247.69						
		5			245.40						
		7			244.91						
		9			239.47						
		11			237.92						
		13			234.71						

Sampled
H₂O

5

Sampled
H₂O

Recovery

Aquifer Test Data

page 2 of 2

Date for Well 299-W10-14

Pumping Well 299-W10-14

Observation Wells 299-W10-13

Location 200 WEST RCH

Type of Aquifer Test Constant-Discharge Recovery

How Q Measured 5 gal calibrated bucket

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/STIMULUS PIPE 3.09' AW

Elevation of Meas. Point _____

Depth of Pump/Airpipe 444' - NPS 441.66

Pump On: date 10/26/97 time 0500 hr

Pump Off: date 10/26/97 time 1400 hr

Duration of Aquifer Test 5 hr

Time			Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0			Static Water Level <u>234.02</u>					Reading	Q		
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	f or s'			
10/26			15		234.89					CS	
			20		234.89						
			25		234.41						
			30		234.06						
			35		233.96						
			40		233.89						
			45		233.83						
			50		233.82						
	1500	1600			233.81						
			70		233.79						
			80		233.72						
			90		233.78						
			100		233.76						
			110		233.74						
			120		233.74						
			150		233.25						

Date: _____
 Name: _____
 Address: _____
 City: _____

Subject: _____

The purpose of this experiment is to determine the effect of _____
 on the rate of reaction between _____ and _____.
 The reaction is represented by the following equation:

$$2H_2O_2(aq) \rightarrow 2H_2O(l) + O_2(g)$$

 The rate of reaction is measured by the volume of oxygen gas produced over a period of time.

Time (s)	Volume of O_2 (cm ³)	Rate of Reaction (cm ³ s ⁻¹)		Concentration of H_2O_2 (mol dm ⁻³)	Temperature (°C)
		Initial	Final		
0	0				
10					
20					
30					
40					
50					
60					
70					
80					
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					
190					
200					
210					
220					
230					
240					
250					
260					
270					
280					
290					
300					

AQUIFER TEST SUMMARY FOR WELL 299-W15-15

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 225 ft. Bottom: 455 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 245 ft. Bottom: 255 ft.

Date of Test: 08/21/87

Start Time of Test: 1245 hr

Pumping Rate: 20 gpm

Duration of Test: 360 min

Pre-test Water-level Elevation (Depth): 225.52 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Recovery (Cooper and Jacob 1946)	10,000	43

Corrections Used:

Borehole Storage Effects

$t_c = 26$ min (Schafer 1978)

$t_c = <3$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis.

RCRA WELL 299-W15-15
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/21/87

Aquifer Test Data

Location 200 West Ave. N.W. 21-15-15
 Type of Aquifer Test constant discharge test
 How Q Measured a bucket & stop watch
 How W.L.'s Measured E-rode / TRANSducer
 Rad./Dist. of/From Pumping Well ---
 Meas. Point for W.L.'s top of falling wall 7.5'
 Elevation of Meas. Point ---

page 1 of 2
 Data for Well 299-W15-15
 Pumping Well 299-W15-15
 Observation Wells ---

Depth of Pump/Airpipe ~ 250'
 Pump On: date 8/21/37 time 1245 hrs
 Pump Off: date --- time ---
 Duration of Aquifer Test ---

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>227.87'</u>					Reading	Q		
"	Sec	Clock	Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or f'		
Day												
	00:30						227.87				JSW	24809
	00:30			5.15			233.02					
	1:00			2.71			236.10					
	1:30			12.79			238.66					
	2:00			12.54			240.41					
	2:30			13.97			241.84					
	3:00			14.97			242.79					
	3:30			15.77			243.64					
	4:00			16.35			244.22					
	4:30			16.84			244.71					
	5:00			17.18			245.05					
	5:30			17.53			245.45					
	6:00			17.88			245.70					
	6:30			18.04			245.91					
	7:00			18.12			246.05					
	7:30			18.27			246.14					
	8:00			18.38			246.25					
	8:30			18.39			246.26					
	9:00			18.43			246.30					
	9:30			18.45			246.31					
	10:00			18.46			246.33					
	12:00			18.13			246.00				21.4	216211 opened
	14:00			18.13			246.00					HOSE CONNECTION
	16:00			18.17			246.04					5 gal / 10 5 gal / 10
	18:00			18.29			246.16					
	20:00			18.35			246.22					24814
	25:00			18.47			246.34					
	30:00			18.46			246.33					
	35:00			18.50			246.37					
	40:00			18.48			246.35					
	45:00			18.50			246.37					
	50:00			18.56			246.43					
	55:00			18.59			246.46					
	60:00			18.70			246.57					
	65:00			18.56			246.39					
	70:00			18.57			246.37					
	75:00			18.50			246.37					
	80:00			18.64			246.51					
	235										20.0	5 gal / 15 sec 5 gal / 15 sec

Aquifer Test Data

page 2 of 2

Data for Well 299-W15-15

Pumping Well 299-W15-15

Observation Wells None

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured 5 gal bucket

How W.L.'s Measured E-TAPE/TRANSDUCER

Depth of Pump/Airpipe ~ 250'

Rad./Dist. of/From Pumping Well —

Pump On: date 8/21/87 time 1245 hrs

Meas. Point for W.L.'s T/STILLING WELL 2.35'

Pump Off: date 8/21/87 time 1845 hrs

Elevation of Meas. Point AW L50

Duration of Aquifer Test 6 hrs

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>227.87'</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
8/21	1145	240			246.32		19.45		—		CSC	
	1715	270			246.34		19.47				CSC	
	1745	300			246.36		19.49				CSC	
	1845	360	0		246.40		19.52				CSC	Recovery
			30	721	241.96		14.09				CSC	
			1	360	239.47		11.60				CSC	
			1.30	241	236.93		9.06				CSC	
			2	181	234.96		7.09				CSC	
			3	121	232.52		4.65				CSC	
			4	91	230.80		2.93				CSC	
			5	73	229.70		1.83				CSC	
			7	52.4	228.60		.73				CSC	
			9	41	228.19		.31				CSC	
			11	33.7	227.93		.06				CSC	
			13	28.7	227.94		.07				CSC	
			15	25	227.91		.04				CSC	
			20	19	227.88		.01				CSC	
			25	15.4	227.88		.01				CSC	
			30	13	227.88		.01				CSC	
			35	11.3	227.87		0				CSC	
			40	10	227.87		0				CSC	
			45	9	227.86		-.01				CSC	
			50	8.2	227.86		-.01				CSC	
			60	7	227.85		-.02				CSC	

AQUIFER TEST SUMMARY FOR WELL 299-W15-16

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 212 ft. Bottom: 442 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 227.5 ft.

Bottom: 237.5 ft.

Observation Well Used: 299-W15-17 Distance to Pumped Well: 48 ft.

Elevation (Depth) of Screened Interval: Drilled to a depth of 220 ft (no screen) for this aquifer test.

Date of Test: 08/20/87

Start Time of Test: 1330 hr

Pumping Rate: 80 gpm

Duration of Test: 420 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 211.83 ft.

Observation Well: 211.90 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Constant Discharge (Cooper and Jacob 1946) Pumping Well	5,000	22	NA
(Theis 1935) Observation Well	12,000	52	0.027
Recovery (Cooper and Jacob 1946) Pumping Well	12,000	52	NA
(Theis 1935) Observation Well	12,000	52	0.038

Corrections Used:

Borehole Storage Effects

$t_c = 10$ min (Hargis 1979)

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob and Theis analyses. A 55-gal drum was used to approximate the discharge rate. The decline in drawdown after 100 min of pumping is possibly due to further development of the well.

RCRA WELL 299-W15-16
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD 8/20/87

RCRA WELL 299-W15-16
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/20/87

F.86

Residual
 Drawdown (ft)

RCRA OBSERVATION WELL 299-W15-17
 CONSTANT-DISCHARGE DRAWDOWN TEST
 THEIS METHOD
 8/20/87

F.87

OBSERVATION WELL 299-W15-17
 CONSTANT-DISCHARGE RECOVERY
 THEIS METHOD
 8/20/87

F.88

Calculated
 Recovery
 (ft)

Aquifer Test Data

3780

page 1 of 2

Data for Well 299-W15-16

Pumping Well 299-W15-16

Observation Wells 299-W15-17

Location RCRA 200 WEST

Type of Aquifer Test CONSTANT-DISCHARGE

How Q Measured FLOW METER # 92-2-425 / 55 gal. drum

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 235' ABJ L51

Rad./Dist. of/From Pumping Well

Pump On: date 8/30/87 time 13:30

Meas. Point for W.L.'s T/Rilling well 2.08' ABJ L51

Pump Off: date 9/20/87 time 20:30

Elevation of Meas. Point

Duration of Aquifer Test 7 hr

Time t = 213.9 / at t' = 0			Water Level Data Static Water Level 213.91				Discharge		Recorded By	Comments
Day	Hour	Min	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
8/30	0:00		213.91			0				2193b
	1:30		220.05			6.14				
	1:00		222.79			3.75				
	1:30		224.30			10.39				
	2:00		225.17			11.26				
	2:30		225.66			11.75				
	3:00		226.00			12.09				
	3:30		226.08*			12.13				
	4:00		226.17			12.26				
	4:30		226.21			12.30				
	5:00		226.24			12.33				
	5:30		226.33			12.42				
	6:00		226.33			12.42				
	6:30		226.29			12.38				Drill working w/ back in pipe
	7:00		226.32			12.41				
	7:30		226.27			12.36				
	8:00		226.24			12.33				
	8:30		226.24			12.33				
	9:00		226.32			12.41				
	9:30		226.40			12.49				total gals time
	10:00		226.43			12.52	26			22010 - 13:40
	12:00		226.34			12.43				
	14:00		226.38			12.47				
	16:00		226.45			12.57				
	18:00		226.55			12.64				total gals time
	20:00		226.61			12.70	23			22093 13:50
	25:00		226.57			12.66				
	30:00		226.64			12.73	23			22156 14:00
	35:00		226.57			12.61				
	40:00		226.60			12.73	23			22229 14:10
	45:00		226.68			12.77				
	50:00		226.63			12.72	23			22302 14:20
	55:00		226.51			12.60				
	60:00		226.62			12.71	26			22373 14:30
	80:00		226.51			12.60				641 - 8'5' measured
	100:00		226.26			12.35				at 55 min drum
	120		225.62			11.71	22.6			228010 1:58:20
	150									unrecorded disch
	180									

Aquifer Test Data

page 2 of 2

Data for Well 299-W15-16

Pumping Well 299-W15-16

Observation Wells 299-W15-17

Location RCRA 200 W

Type of Aquifer Test CONSTANT - DISCHARGE

How Q Measured FLOW METER # R2-2-435 / 55 GAL DRUM

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 233' BELOW LAND

Rad./Dist. of/From Pumping Well _____

Pump On: date 8/20/87 time 13:30

Meas. Point for W.L.'s T/ STILLING WELL 2.08' ROW 130

Pump Off: date 8/20/87 time 2030

Elevation of Meas. Point _____

Duration of Aquifer Test 7 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>213.91</u>				Discharge		Recorded By	Comments
Day	MIN. Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Read- ing	Q		
	150			225.28		11.37					MEASURED DISCHARGE
	180			225.27		11.36					@ 77.7 GPM W/ 55
	210			225.27		11.36					GAL DRUM ~ 15:40 hrs.
	240			225.04		11.13		30.5	ISC		
	270			225.10		11.19				CSC	
	300			225.20		11.29				CSC	
	360			225.35		11.44					
	420	0						24750		CSC	Recovery
		1:30								CSC	
		1								CSC	
		1:30		216.2		2.29				CSC	
		2		216.2	215.33	1.42				CSC	
		3									
		4		214.61		0.70				CSC	
		5		214.45		0.54				CSC	
		7									
		9									
		11		214.35		0.44				CSC	
		13		214.33		0.42				CSC	
		15									
		20		214.30		0.39				CSC	
		25									
		30		214.27		0.36				CSC	
		40		214.22		0.31				CSC	
		45		214.25		0.34				CSC	
		50		214.21		0.30				CSC	
		65		214.19		0.28				CSC	
		70		214.19		0.28				CSC	
		80		214.16		0.25				CSC	
	2200	90		214.15		0.24				CSC	Leaving for
8/21	0700			214.08		0.17				TSW	home

Aquifer Test Data

OBSERVATION
Well

page 1 of 1

Data for Well 299-W15-17

Pumping Well 299-W15-16

Observation Wells 299-W15-17

Location RCA 200 West

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured FLOW METER / 55 gal drum

How W.L.'s Measured E-TAPE - TRANSDUCER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/C 3.4' AW L5D

Elevation of Meas. Point _____

Depth of Pump/Airpipe 233' b/w L5D

Pump On: date 8/20/87 time 1330 hrs

Pump Off: date 8/20/87 time 2030 hrs

Duration of Aquifer Test 7 hrs

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>215.0' T/C</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or f	Reading	Q	
8/20	1330	0			215.0	6.28		0	~ 30	CSC	TRANSDUCER SET
		15			215.15			.15		CSC	222' below T/C
		20			215.19			.19		CSC	TRANSDUCER ON
		25			215.21			.21		CSC	10 sec intervals
		30			215.22			.22		CSC	only ~ 2' open
		40			215.23			.23		CSC	between bottom
		50			215.24			.24		CSC	12" casing + bottom
		60			215.25			.25		CSC	of hole
		70			215.28			.28	81.5	CSC	Pumped well has
		80			215.28			.28	55 gal drum	CSC	~ 8' casing exposed
		90			215.29			.29		CSC	55 gal / 41 + 40 sec
		100			215.28			.28		CSC	
		110			215.30			.30		CSC	
		120			215.30			.30	77.7	CSC	increased rate
		150			215.31			.31		CSC	to bring up to ~ 80
180	210	180			215.36	215.33		.36	80.5	CSC	55 gal / time ~ 1
		240			215.38			.38		CSC	
		270			215.41			.41		CSC	
		300			215.45			.45		CSC	
		360			215.50			.50		CSC	
2030	420	0								CSC	START RECOVERY
		427	7	61	215.5			.50		CSC	
		440	20	22	215.41			.41		CSC	
		445	25	17.8	215.39			.39		CSC	
		455	35	13	215.35			.35		CSC	
		460	40	11.5	215.34			.34		CSC	
		475	55	8.6	215.30			.30		CSC	
		500	80	6.3	215.27			.27		CSC	
		510	90	5.7	215.25			.25		CSC	

AQUIFER TEST SUMMARY FOR WELL 299-W15-17

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery ()

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 213 ft. Bottom: 442 ft.

Depth of Screened Interval in Pumped Well, Top: 422.5 ft.

Bottom: 432.5 ft.

Observation Well Used: 299-W15-16 Distance to Pumped Well: 48 ft.

Elevation (Depth) of Screened Interval, Top: 208 ft. Bottom: 238 ft.

Date of Test: 09/28/87

Start Time of Test: 1445 hr

Pumping Rate: 6 gpm

Duration of Test: 360 min

Pre-test Water-level Elevation (Depth): 212.72 ft.

Remarks: The data indicate that drawdown in the pumping well is mainly attributed to casing storage effects caused by the well configuration (screen open to the bottom of the aquifer). The drawdown and recovery data from the pumping well are insufficient for analysis. No response was observed in the observation well during pumping.

Aquifer Test Data

page 1 of 2

Data for Well 299-W15-17

Pumping Well 299-W15-17

Observation Wells _____

Location 200 West PCRA

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured 5 gal bucket

How W.L.'s Measured E-TAPE / TRANSOMER

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s 1st. main well 2.0'

Elevation of Meas. Point _____

Depth of Pump/Airpipe 423' ABV LSA

Pump On: date 9/28/87 time 1445 hr

Pump Off: date _____ time 1945 hr

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>214.72</u>							
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	1445	0									
		:30									
		1		215.00			0.28			CSC	
		1:30									
		2		217.77			3.05				
		3		220.80			6.03				
		4									
		5		223.70			8.98		6 gal		5 gal/50 sec
		7		226.35			11.83				
		9									
		11		229.52			14.80				
		13		230.60			15.88				
		15		231.42			16.70				
		26		233.00			18.28				
		30		233.38			18.66				
		36		233.64			18.92				
		45		233.77							
		53		233.55					6		P + transducer
		60		233.57							well probe
		70		233.55							good reading
		80		233.56						CSC	
		90		233.50			18.78		5.5	CSC	
		100		233.52						CSC	
		110		233.52						CSC	
		120		233.54						CSC	
		150		233.56						CSC	
		180		233.57			18.85			CSC	
		210		233.51						CSC	
		240		233.85					6	CSC	
		270		233.85						CSC	
		300		233.95			19.23		6.2	CSC	
		360		233.95							

Aquifer Test Data

page 2 of 2

Data for Well 299-W15-17

Pumping Well 299-W15-17

Observation Wells 299-W15-16

Location 200 WEST RENT

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured 5 gal calibrated bucket

How W.L.'s Measured E-TAPE / PRESSURER Depth of Pump/Airpipe 423' below lsd

Rad./Dist. of/From Pumping Well _____ Pump On: date 1+45 hr time 9/28/87

Meas. Point for W.L.'s T/STANDARD WEL 20' 2 1/2" Pump Off: date 9/28/87 time 2045 hr

Elevation of Meas. Point _____ Duration of Aquifer Test 6 hr

Time				Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>214.72</u>								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Read-ing	Q		
9/28	2045		0		233.98							3" diameter
			30		232.4							Pump Column
			1									8" diameter ca
			1:30									
			2		229.28							
			3		227.41							
			4		225.88							
			5		224.10							
			8		221.08							
			9		220.17							
			11		218.94							
			13		217.87							
			15		217.11							
			20		215.98							
			25		215.38							
			30		215.05							
			35		214.90							
			40		214.82							
			45		214.80							
			50		214.78							
			60		214.78							

Observation -
well

Observation Wells 299-W15-14

Elevation of Meas. Point _____

Duration of Aquifer Test 6 hrF.96

AQUIFER TEST SUMMARY FOR WELL 299-W15-18

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 212 ft. Bottom: 455 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 232 ft. Bottom: 242 ft.

Observation Well Used: 299-W18-4 Distance to Pumped Well: 355 ft.

Elevation (Depth) of Screened Interval, Top: 197 ft. Bottom: 254 ft.

Date of Test: 07/21/87

Start Time of Test: 1300 hr

Pumping Rate: 87 gpm

Duration of Test: 450 min

Pre-test Water-level Elevation (Depth): 211.80 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Recovery (Cooper and Jacob 1946) Pumping Well	14,000	58	NA

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The drawdown data indicate that well entrance loss occurred during pumping. Drawdown in the observation well was insignificant.

RCRA WELL 299-W15-18
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 7/21/87

F.98

Residual
 Drawdown (ft)

Aquifer Test Data

Location 200 West RCRA
 Type of Aquifer Test CONSTANT-DISCHARGE
 How Q Measured FLOW METER
 How W.L.'s Measured STAFF
 Rad./Dist. of/From Pumping Well ---
 Meas. Point for W.L.'s TK
 Elevation of Meas. Point ---

page 1 of 2

Data for Well 2-W15-18

Pumping Well 2-W15-18

Observation Wells 2-W18-4

Depth of Pump/Airpipe 225' LSD

Pump On: date 7/21/87 time 1300

Pump Off: date 7/21/87 time 2030

Duration of Aquifer Test 7.5 hrs

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>215.0</u> MP				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	1300	0							177695		CSC	FLOW METER
		30									CSC	82-2-435
		1										
	1:30				219.4			4.40	79		CSC	174090
	2				220.46			5.46			CSC	172695
	3				221.41			6.41			CSC	395
	4				221.90			6.90			CSC	
	5				222.09			7.09	178090		CSC	
	7				222.30			7.30			CSC	
	10				222.18			7.18			CSC	
	11											
	13				222.61			7.21	899		CSC	180515
	15				222.15			7.15			CSC	172090
	20				222.10			7.10			CSC	2425
	25				222.07			7.07			CSC	
	30				221.86			6.86			CSC	
	32								180515	BS	CSC	at 33-min Flow 157600
	35											
	40				221.85			6.85			CSC	
											CSC	171375
	50				221.78			6.78	856		CSC	182060
	60				221.80			6.80	182926		CSC	Russ Core collected
	70				221.75			6.75	183703	86.5	CSC	Sample over 1/3
	80				221.81			6.81	1867	86.5	CSC	
	90				221.81			6.81	18557	86.5	CSC	
	100				221.81			6.81	19632	86.5	CSC	
	110				221.82			6.82	197415	86.25	CSC	
	120				221.87			6.87	198110	86.9	CSC	Russ Core sampled
	150				221.90			6.90	191040	86.2	CSC	
	180				221.90			6.90	193290	86.5	CSC	Russ Core Sampled
	210				221.96			6.96	195795	86.8	CSC	
	240				221.94			6.94	198510	87.2	CSC	
	270				221.97			6.97	201390	87.3	CSC	
	300				221.98			6.98	203750	87.4	CSC	
	330				222.0			7.00	206370	87.3	CSC	
	360				222.05			7.05	209005	87.4	CSC	
	390				221.96			6.96	211625	87.3	CSC	Cont moving through
	420				221.85			6.85	214240	86	CSC	
	450				221.86			6.86	216785		CSC	

86.9 gpm avg. discharge

Aquifer Test Data

page 9 of 9

Data for Well 3-WIS-1B

Pumping Well 3-WIS-1B

Observation Wells 3-WIS-4

Location 200 West TCR

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured FLOWMETER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well ---

Meas. Point for W.L.'s To Transducer

Elevation of Meas. Point ---

Depth of Pump/Airpipe 225' LGA

Pump On: date 7/31/87 time 1300 hrs

Pump Off: date 7/31/87 time 2030 hrs

Duration of Aquifer Test 7.5 hrs

Time				Water Level Data					Discharge		Recorded By	Comments
t = 450 at t' = 0				Static Water Level 215.0								
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	f or s'		Reading	Q		
	2030	450	0	—		221.86	6.86		216785		CSC	
		451	30	901		217.8	2.8				CSC	
		451	1	451							CSC	
		451.5	1'30	301		216.24	1.24				CSC	
		452	2	226		215.98	.98				CSC	
		453	2	151		215.65	.65				CSC	
		454	4	113.5		215.38	.38				CSC	
		455	5	91		215.30	.30				CSC	
		457	7	65.3		215.22	.22				CSC	
		459	9	51		215.17	.17				CSC	
		461	11	41.9		215.13	.13				CSC	
		463	13	35.4		215.11	.11				CSC	
		465	15	29.1		215.09	.09				CSC	
		470	20	23.5		215.07	.07				CSC	
		476	26	18.3		215.05	.05				CSC	
		480	30	16		215.03	.03				CSC	
		485	35	13.4		215.02	.02				CSC	
		490	40	12.25		215.01	.01				CSC	Radiation Monitors
		495	45	11		215.01	.01				CSC	check us out
		500	50	10		215.0	0				CSC	leaving E-Tapes
		510	60	8.5		215.0	0				CSC	in well because
		520	70	7.4		215.0	0				CSC	at wind
		530	80	6.6		215.01	.01				CSC	
	0745	1125				215.16						

Aquifer Test Data

OBSERVATION
Well

page 1 of 2

Data for Well 299-W18-4

Pumping Well 299-W15-18

Observation Wells 299-W18-4

Location 200 West RCR

Type of Aquifer Test Constant Discharge Test

How Q Measured Flow Meter

How W.L.'s Measured E-Tape

Depth of Pump/Airpipe _____

Rad./Dist. of/From Pumping Well ~400' (measured)

Pump On: date 7/2/97 time _____

Meas. Point for W.L.'s Top of Casing

Pump Off: date _____ time _____

Elevation of Meas. Point 2.65' above LS

Duration of Aquifer Test _____

Measurement made for 5 Days

Actual Time	Time					Water Level Data				Discharge		Recorded By	Comments
	t = _____ at t' = 0					Static Water Level <u>214.31'</u>							
	Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
1252:30		0:00				214.31			0			SD	
1257:00		0:30				214.30			-.01				
1259:30		1:00				214.31			0				
1300:00		1:30				214.30			-.01				
1300:30		2:00				214.31			0				
1301:00		2:30				214.31			0				
1301:30		3:00				214.31			0				
1302:30		4				214.31			0				
1303:30		5				214.31			0				
1304:30		6				214.31			0				
1305:30		7				214.31			0				
1306:30		8				214.31			0				
1308:30		10				214.31			0				
1310:30		12				214.31			0				
1312:30		14				214.32			.01				
1314:30		16				214.32			.01				
1316:30		18				214.32			.01				
1318:30		20				214.32			.01				
1323:30		25				214.33			.02				
1328:30		30				214.33			.02				
1333:30		35				214.33			.02				
1338:30		40				214.34			.03				
1343:30		45				214.34			.03				
1348:30		50				214.34			.03				
1358:30		4:00:00				214.35			.04				
1408:30		1:10:00				214.34			.03				
1418:30		1:20:00				214.35			.04				
1428:30		1:30:00				214.35			.04				
1443:30		1:45:00				214.35			.04				
1458:30		2:00:00				214.35			.04				
1528:30		2:30:00				214.35			.04				
1558:30		3:00:00				214.34			.03				
1628:30		3:30:00				214.34			.03				
1658:30		4:00:00				214.33			.02				
1708:30		4:30:00				214.32			.01			CSC	
1758:30		5:00:00				214.30			-.01			TG	
1828:30		5:30:00				214.30			-.01				
1858:30		6:00:00				214.31			0				

Aquifer Test Data

page 2 of 2

Data for Well 299-W18-4

Pumping Well 299-W15-18

Observation Wells 299-W19-4

Location 200 West

Type of Aquifer Test Constant Discharge Test

How Q Measured Flow Meter

How W.L.'s Measured E-Tape #10998

Rad./Dist. of/From Pumping Well ~400'

Meas. Point for W.L.'s Top of casing

Elevation of Meas. Point 2.65' above GCS

Depth of Pump/Airpipe 225' L3D

Pump On: date 2/21/92 time 1300

Pump Off: date 2/21/92 time 2030

Duration of Aquifer Test 7.5 hrs

Actual
Time

19:28:30

19:58:30

20:28:30

Time			Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0			Static Water Level <u>214.31'</u>					Reading	Q		
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'			
	6:30:00				214.32			.01		T6	W18-4
	7:00:00				214.33			.02			
	7:30:00				214.35			.04			
		1:30			214.35			.04		T6	Recovery
		1			214.35			.04			
		1:30			214.34			.03			
		2			214.34			.03			
		3			214.34			.03			
		4			214.34			.03			
		5			214.34			.03			
		6			214.33			.03			
		9			214.31			0			
		11			214.32			.01			
		13			214.32			.01			
		15			214.32			.01			
		20			214.31			0			
		25			214.31			0			
		30			214.31			0			
		35			214.31			0			
		40			214.30			-.01			
		45			214.30			-.01			
		50			214.30			-.01			
		55			214.30			-.01			
		60			214.30			-.01			
								.15			
	09:25	11:57			214.46						

AQUIFER TEST SUMMARY FOR WELL 299-W18-21

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 195 ft. Bottom: 445 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 215.5 ft.

Bottom: 225.5 ft.

Observation Well Used: 299-W18-22 Distance to Pumped Well: 48 ft.

Elevation (Depth) of Screened Interval: Drilled to a depth of 205 ft (no screen) for aquifer tests.

Date of Test: 07/14/87

Start Time of Test: 1500 hr

Pumping Rate: 58 gpm

Duration of Test: 480 min

Pre-test Water-level Elevations (Depth):

Pumping Well: 195.33 ft.

Observation well: 196.15 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Constant Discharge (Cooper and Jacob 1946) Pumping Well	1,300	5	NA
Recovery (Cooper and Jacob 1946) Pumping Well	51,000	200	NA

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The drawdown data indicate that well entrance loss occurred during pumping, and that boundary effects influenced the test. No response was observed in the observation well.

RCRA WELL 299-W18-21
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 7/14/87

F.104

Drawdown
 (ft)

RCRA WELL 299-W18-21
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 7/14/87

F.105

Residual
 Drawdown (ft)

Aquifer Test Data

page 1 of 2

Data for Well 299-W18-21

Pumping Well 2 W18-21

Observation Wells 2 W18-22

Location 200 West RERA

Type of Aquifer Test Constant-Discharge step dd

How Q Measured Flow Meter

How W.L.'s Measured E-TAPE / STEEL TAPE Depth of Pump/Airpipe 230' TO INTAKE

Rad./Dist. of/From Pumping Well _____ Pump On: date 7/14/87 time _____

Meas. Point for W.L.'s T/C 2.9' ABV LSD Pump Off: date _____ time _____

Elevation of Meas. Point _____ Duration of Aquifer Test _____

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>198.49</u>			Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'	Reading	Q		
		0									
	1:30						199.64		0.101625		Flow Meter #82-2-435
	1:30						199.81				Adjusting valve
	2						200.06				flow meter not registering
	4						200.19				
	5						200.10				
	7						200.07				
	9						200.05				
	10:30						210.95		38		5.06 gal/Bran
	1:00						212.27				
	2:00						213.36				
	3:00						213.26				
	4:00						213.26				
	5:00						213.43				
	7:00						213.73				
	9:00						213.66				
	11:00						213.84				
	13:00						213.92				
	15:00						214.0				
	20:00						214.11				
	30:00						214.12				
	35:00						214.17				
	40:00						214.19				
	45:00						214.06				
	50:00						214.28				
	55:00						214.24				
	1:00						214.28				
	2:00						205.24				Recovery
	3:00						201.84				
	4:00						199.28				
	5:00						198.76				
	6:00						198.60				

Recovery

Location 200 West

How Q Measured Flow meter

How W.L.'s Measured E tape / steel tape

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s T/C 2.9' above LS

Elevation of Meas. Point _____

page 2 of 2

Data for Well 299-W15-24

Pumping Well 299-WIA-21

Observation Wells 299-W18-22

Depth of Pump/Airpipe 220' to intake

Pump On: date 7-14-87 time

Pump Off: date 7-14-87 time

Duration of Aquifer Test _____

Review -

Aquifer Test Data

OBSERVATION
Well

page 1 of 2

Date for Well 2-W18-22

Pumping Well 2-W18-21

Observation Wells 2-W18-22

Location 200 WEST PCRA

Type of Aquifer Test Step-drawdown

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE / STEEL TAPE

Rad./Dist. of/From Pumping Well 48 ft

Meas. Point for W.L.'s T/c (3.1 ft. above L.S.)

Elevation of Meas. Point _____

Depth of Pump/Airpipe 220' to intake

Pump On: date 7/14/87 time _____

Pump Off: date _____ time _____

Duration of Aquifer Test _____

Time					Water Level Data					Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>199.32 E-TAPE</u> <u>Charge</u>						
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level s or s'		Reading	Q	
7/14	30				199.3		199.43				
	1:00				199.3						
	1:20				199.3						
	2:00				199.3						
	3				199.3						
	4				199.29						
	5				199.29						
	7				199.30						
	9				199.30						
	10				199.30						
	1:30				199.30						
	1:45				"						
	1:50				199.30						
	1:30				199.30						
	2:00				199.295						
	3				199.3						
	4				199.3						
	5				199.3						
	7				199.3						
	9				199.3						
	11				199.29						
	13				199.29						
	15				199.30						
	20				199.30						
	25				199.30						
	30				199.30						
	35				199.30						
	40				199.30						
	45				199.28						
	50				199.28						
	55				199.27						
	60				199.27						
	65				199.27						
	70				199.27						
	70:30				199.27						
	71:00				199.27						
	72:00				199.27						
	75				199.27						
	80				199.27						

Location 200 West
Type of Aquifer Test Step-drawdown
How Q Measured Flowmeter
How W.L.'s Measured E-tape - Steel tape
Rad./Dist. of/From Pumping Well 48'
Meas. Point for W.L.'s T/C 3.1' above L.S.
Elevation of Meas. Point _____

Observation Wells _____

Duration of Aquifer Test _____

F.109

Aquifer Test Data

page 1 of 2

Data for Well 2-W19-21

Pumping Well 2-W18-21

Observation Wells 2-W19-22

Location 200 WEST RCH

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured FLOW METER / 5 gal bucket

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 220'

Rad./Dist. of From Pumping Well —

Pump On: date 7/14/87 time 1500 hr

Meas. Point for W.L.'s TRENNIS 2.9' abv

Pump Off: date 7/14/87 time 2300 hr

Elevation of Meas. Point —

Duration of Aquifer Test 8 hr

Time t = _____ at t' = 0				Water Level Data Static Water Level <u>198.42</u>				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or f	Reading		
	1500	0							101625	47	# R2-2-435
		:30					208.0	9.57			CSC
		1									
		1:30					211.37	12.94			CSC
		2					217.34	13.91			CSC
		3					218.35	14.92			CSC
		4					213.75	15.32			CSC
		5					214.15	15.72			CSC
		7					214.75	15.87			CSC
		9					214.27	15.79			CSC
		11					214.28	15.85			CSC
		12					214.32	15.89			CSC
		15									
		20					214.67	16.24			CSC
		25					214.82	16.39			CSC
		30					214.35	16.32			CSC
		35					215.35	16.92			CSC
		40					215.29	16.96			CSC
		45					215.38	16.95			CSC
		50					215.25	16.82			CSC
		60					215.26	16.88			CSC
		70					215.65	17.22			
		80					215.84	17.41			
		90					215.76	17.28			
		100					215.89	17.46			
		110					215.93	17.50			
		120					215.93	17.50			
		150					215.97	17.51			
		180					215.94	17.51			
		210					215.92	17.49			
		240					215.92	17.49			
		270					216.08	17.65			
		300					216.16	17.73			
		360					216.22	17.79			
		420					216.20	17.77			
	2300	480					216.32	17.89			

AVG 57.8 gpm

FINAL → 126140 @ 420
129350 @ 480

117520 @ 275 min
119200 @ 305 min
122690 @ 325 min

Aquifer Test Data

page 2 of 2

Data for Well 2-W18-21

Pumping Well 2-W18-21

Observation Wells 2-W18-22

Location 200 W PCA

Type of Aquifer Test CONSTANT-DISCHARGE Recovery

How Q Measured Flow Meter

How W.L.'s Measured E-TAPE

Depth of Pump/Airpipe 220'

Rad./Dist. of/From Pumping Well ---

Pump On: date 7/14/87 time 1500 hrs

Meas. Point for W.L.'s TOT TRANING 2.91' ASL

Pump Off: date 7/14/87 time 2300 hrs

Elevation of Meas. Point ---

Duration of Aquifer Test ---

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>198.43</u>							
Day	Clock Time	t'	1'	Reading	Conversions or Corrections	Water Level	ft or s'	Reading	Q		
		480	0	216.32			17.89	EJT			
			30								
		481	1	207.35			5.42	EJT			
		481.5	1:30	199.95			1.52	EJT			
		482	2	199.00			.57	EJT			
		483	3	198.80			.37	EJT			
		484	4	198.58			.15	EJT			
		485	5	198.56			.13	EJT			
		487	7	198.54			.11	EJT			
		489	9	198.52			.09	EJT			
		491	11	198.52			.09	EJT			
		493	13	198.52			.09	EJT			
		495	15	198.53			.10	EJT			
		500	20	198.52			.09	EJT			
		505	25	198.51			.08	EJT			
		510	30	198.51			.08	EJT			
		515	35	198.50			.07	EJT			
		520	40	198.50			.07	EJT			
		525	45	198.50			.07	EJT			
		530	50	198.50			.07	EJT			
		535	55	198.51			.08	EJT			
		540	60	198.50			.07	EJT			
		70									
		80									
		90									

Gave 200' 11053 to Sargent 7/15/87

260

Aquifer Test Data

page 1 of 2

Data for Well 2-418-22

Pumping Well 2-318-21

Observation Wells _____

Location 200 West

Type of Aquifer Test Constant discharge DD

How Q Measured Flowmeter

How W.L.'s Measured E-tape - steel tape

Rad./Dist. of/From Pumping Well 48'

Meas. Point for W.L.'s T/C 3.1' above L.S.

Elevation of Meas. Point _____

Depth of Pump/Airpipe _____

Pump On: date 7-14-87 time 14:58

Pump Off: date 2-14-57 time

Duration of Aquifer Test _____

[illegible]

Location 200 West

Type of Aquifer Test Constant - Discharge

How Q Measured Flow meter

How W.L.'s Measured E-type - Steel type

Rad./Dist. of/From Pumping Well 42'

Meas. Point for W.L.'s T/C 3.1 Above L.S.

Elevation of Meas. Point _____

page 2 of 2

Data for Well 2-W18-22

Pumping Well 2W 1B-21

Observation Wells 3-1118-22

Depth of Pump/Airpipe _____

Pump On: date 7-14-87 time 14:58

Pump Off: date 7-14-87 time

Duration of Aquifer Test _____

F.113

AQUIFER TEST SUMMARY FOR WELL 299-W18-22

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge () Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 197 ft. Bottom: 445 ft.

Depth of Screened Interval in Pumped Well, Top: 437.5 ft.

Bottom: 447.5 ft.

Observation Well Used: 299-W18-21 Distance to Pumped Well: 48 ft.

Elevation (Depth) of Screened Interval, Top: 195.5 ft. Bottom: 225.5 ft.

Date of Test: 08/26/87

Start Time of Test: 0715 hr

Pumping Rate: 51 gpm

Duration of Test: 480 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 196.80 ft.

Observation Well: 196.41 ft.

Analysis Method and Results:

<u>Method</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Recovery (Cooper and Jacob 1946) Pumping Well	420	1.7	NA

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The data indicate that drawdown in the pumping well is mainly attributed to casing storage effects caused by the well configuration (screen open to the bottom of the aquifer). No response was observed in the observation well during pumping.

RCRA WELL 299-W18-22
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 8/26/87

F.116

Residual
 Drawdown
 (ft)

Aquifer Test Data

page 1 of 2

Data for Well 299418-22

Pumping Well 299-W18-22

Observation Wells _____

Location RCRA 200 WEST

Type of Aquifer Test CONSTANT DISCHARGE

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE / TRANSDUCER (in obs. well)

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s STIMULATED WELL 2.25' (in obs. well)

Elevation of Meas. Point _____

Depth of Pump/Airpipe 442.42' LST

Pump On: date 8/26/87 time 0215 hrs

Pump Off: date 8/26/87 time 1515 hr

Duration of Aquifer Test 8 hr

Time				Water Level Data				Discharge		Recorded By	Comments	
t = _____ at t' = 0				Static Water Level <u>199.05'</u> MP								
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or f	Corrected Reading	Q		
8/26	0715	0			199.05			0		255520	CSC	ALLOWED TO RECOVER
		:30			N/A						CSC	OVERNIGHT
	1				"						CSC	E-Tape "hung-up"
	1:30				"						CSC	in stilling well
	2				"						CSC	
	3				"						CSC	8" CASING
	4				"						CSC	2.25" O.D.
	5				"						CSC	Pump column
	7				263.74		64.74	56.36			CSC	
	9				265.4		66.35	57.55			CSC	
	11				266.09		67.04	58.05			CSC	
	13				266.0		66.95	57.99			CSC	
	15				266.11		67.06	58.07			CSC	
	20				266.70		67.65	58.50			CSC	24 256785
	25				267.38		68.33	58.99			CSC	min. 52.7 gpm
	30				267.65		68.60	59.19			CSC	
	35				267.83		68.78	59.32			CSC	
	40				267.90		68.85	59.37			CSC	
	45				267.92		68.87	59.38			CSC	
	50				267.96		68.91	59.41	258070		CSC	49.4 gpm in 10 min
	60				268.21		69.16	59.59			CSC	
	70				268.29		69.19	59.62			CSC	54.1 gpm 55 sec down
	80				268.37		69.32	59.71			CSC	2592.10 275 min
	90				268.45		69.40	59.77			CSC	(49.4)
	100				268.75		69.70	59.98			CSC	
	110				269.00		69.95	60.16			CSC	2612.0 112 min
	120				269.00		69.75	60.02			CSC	(51.4 gpm)
	150				269.91		70.86	60.82			CSC	26170.5 122 min
	180				269.74		70.89	60.84			CSC	(45 gpm) opened
	210				269.60		70.35	60.60			CSC	valve slightly
	240				272.5		73.45	62.46			CSC	263160 152 min
	270				273.93		73.88	62.91			CSC	(50.2 gpm)
	300				272.84		73.39	62.90	270640	51	CSC	264410 177 min
	360				273.67		74.63	63.48	273710	51	CSC	(50.0)
	420				272.20		73.15	62.45	270640	51	CSC	265990 209 min
	480				271.87		72.82	62.24	270640		CSC	(49.4 gpm) 192 min
												267520 239 min
												(51 gpm)
												269060 269 min

water sample collected

water sample collected
cut back discharge

Avg. Discharge 79 = 55 gpm / 57 sec 270640 191 gpm
50.7 gpm

Aquifer Test Data

page 2 of 2

Data for Well 299 W 18-22

Pumping Well 299 W 18-22

Observation Wells 299 W 18-21

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE RECOVERY

How Q Measured FLOW METER / 5 gal / min

How W.L.'s Measured E-TAP-IL

Depth of Pump/Airpipe 442.9' Below Lcd

Rad./Dist. of/From Pumping Well

Pump On: date 8/26/87 time 0715 hr

Meas. Point for W.L.'s DP ST. WING WEL 2 35' LND

Pump Off: date 8/26/87 time 1515 hr

Elevation of Meas. Point

Duration of Aquifer Test 8 hr

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>199.05 MP</u>							
Day	Clock Time	t	t'	Reading	Conversions or Corrections	Water Level	f or s'	Corrected $5.32 \frac{m}{s}$	Reading	Q	
8/26	1515	480	0	271.87			72.82	42.21	279870	CSC	
			1:30	260.2			61.15	53.67		CSC	
			1	251.64			52.56	47.03		CSC	
			1:30	243.32			44.37	40.35		CSC	
			2	236.72			37.67	34.83		CSC	
			3	225.92			26.87	25.43		CSC	
			4	219.15			20.10	19.29		CSC	
			5	214.97			15.42	14.94		CSC	
			7	209.66			10.61	10.35		CSC	
			9	207.53			8.48	8.34		CSC	
			11	206.36			7.31	7.20		CSC	
			13	205.52			6.47	6.39		CSC	
			15	204.95			5.90	5.83		CSC	
			20	203.89			4.84	4.79		CSC	
			25	203.20			4.15	4.12		CSC	
			30	202.35			3.80	3.77		CSC	
			35	202.48			3.43	3.41		CSC	
			40	202.22			3.17	3.15		CSC	
			45	202.00			2.95	2.93		CSC	
			50	201.82			2.77	2.75		CSC	
			60	201.52			2.47	2.46		CSC	
			70	201.27			2.22	2.21		CSC	
			80	201.07			2.02	2.01		CSC	
			90	200.91			1.86	1.85		CSC	
			100	200.76			1.71	1.70		CSC	
			110	200.63			1.58	1.58		CSC	
			120	200.50			1.45	1.45		CSC	
			150	200.23			1.18	1.18		CSC	
			180	200.02			.97	.97		CSC	
			210	199.85			.80	.80		CSC	
			240	199.71			.66	.66		CSC	

AQUIFER TEST SUMMARY FOR WELL 299-W18-23

Purpose of Test: To estimate hydraulic properties (transmissivity and hydraulic conductivity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 224 ft. Bottom: 470 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 241 ft. Bottom: 251 ft.

Date of Test: 06/22/87

Start Time of Test: 0805 hr

Pumping Rate: 85 gpm

Duration of Test: 480 min

Pre-test Water-level Elevation (Depth): 224.02 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>
Constant Discharge (Cooper and Jacob 1946)	27,000	110
Recovery (Cooper and Jacob 1946)	23,000	95

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob analysis. The flowmeter was calibrated with a 55-gal drum, which measured a discharge rate of 85 gpm.

RCRA WELL 299-W18-23
 CONSTANT-DISCHARGE DRAWDOWN TEST
 COOPER-JACOB METHOD
 6/22/87

F.122

RCRA WELL 299-W18-23
 CONSTANT-DISCHARGE RECOVERY TEST
 COOPER-JACOB METHOD
 6/19/87

$$T = 23,000 \text{ ft}^2/\text{d}$$

$$T = \frac{(2.3 \times 1440 \times Q)}{(4 \times \pi \times 7.48 \times ds')}$$

$$Q = 85 \text{ gpm}$$

$$ds' = 0.13 \text{ ft}$$

Residual
 Drawdown (ft)

Aquifer Test Data

page 1 of 1
 Data for Well 2W-12-24
 Pumping Well 2W-12-24
 Observation Wells _____

Location 200 AREA WEST ROCK

Type of Aquifer Test STEP-DRAWDOWN

How Q Measured FLOW METER McGraw-Hill # 82-2-435 2935' USD

How W.L.'s Measured STEEL / E-TAPE Depth of Pump/Airpipe 245' Galvan APP

Rad./Dist. of/From Pumping Well _____ Pump On: date 6/18/87 time 1

Meas. Point for W.L.'s TOP OF STILLING PIPE Pump Off: date _____ time _____

Elevation of Meas. Point 1.5' ABOVE L.S.D Duration of Aquifer Test _____

Time t = _____ at t' = 0					Water Level Data Static Water Level <u>225.52</u> MP				Discharge		Recorded By	Comments
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or g	Read- ing	Q		
6/18	1215	0			225.52			0	1575			16060 Flowmeter
		15			226.98			1.46	80			
		1			227.02							
		1.5			227.2				95			Increased surging
		2			227.69							
		3			227.67							Pump Column outside diameter = 3 7/16"
		4			227.8							
		5			227.8							
		7			227.75				4100			
		9										
		10										8" casing
		15			228.07							
		20			228.12							
		25			228.13							
		30										
		35			228.12							
		60			228.15							
		70			228.17				75-100			OPENED ALL THE WAY UP TO 100 JUST TIME 12:20
		80			228.10							
		90			228.21							
		100			228.20							SAME
		120			228.20				29070			avg 108 gpm
		0			2							Recovery
		30			225.9							
		1			225.77							
		2			225.85							
		3			225.83							
		4			225.71							
		5			225.80							
		7			225.70							
		9			225.76							
		11			225.76							
		13										
		15			225.74							
		20			225.72							

Aquifer Test Data

page 1 of 2

Data for Well 2W-18-24

Pumping Well 2W-18-24

Observation Wells monitored

by ENRIP

Location 200 West PCPA

Type of Aquifer Test CONTACT DISCHARGE (DRAWDOWN)

How Q Measured McCombs Flowmeter #82-2-435

How W.L.'s Measured STILL / S-TAPE

Rad./Dist. of/From Pumping Well -

Meas. Point for W.L.'s T.P. OF STILL / S-TAPE

Elevation of Meas. Point 1.5' ABOVE

Depth of Pump/Airpipe 243.5 below LSP

Pump On: date 6/22/87 time 08:05

Pump Off: date 6/22/87 time 16:05

Duration of Aquifer Test 8 hrs

STATIC -> 225.74 (steel tape) (225.96 S-tape)

Time					Water Level Data					Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>225.96</u>					Reading	Q		
Day	Clock Time	t	t'	t/t'	Reading	Conversions or Corrections	Water Level	s or s'					
	08:05	0			225.96			0				SPA	McCombs 48910
		.5			228.16			2.20				SPA	
		1			228.29			2.33				SPA	
		1.5			228.31			2.35				SPA	
		2			228.32			2.36		108		SPA	
		3			228.38			2.42				SPA	
		4			228.39			2.43				SPA	
		5			228.44			2.48				SPA	49450
		6			228.43			2.47		105		SPA	
		7			228.44			2.48				SPA	49660
		8			228.46			2.50		110		SPA	49880
		11			228.45			2.49		110		SPA	50100
		13			228.48			2.52				SPA	
		15			228.45			2.49		109		SPA	
		20			228.49			2.53				SPA	51080
		25			228.51			2.55		110		SPA	51630
		30			228.51			2.55		110		SPA	52180
		35			228.52			2.56		109		SPA	
		40			228.51			2.55				SPA	52270
		45			228.53			2.57		108		SPA	52810
		50			228.55			2.59		110		SPA	53360
		60			228.54			2.58		109		SPA	53450
		70			228.56			2.60		111		SPA	54560
		80			228.55			2.59		108		SPA	
		90			228.56			2.60				SPA	58720
		100			228.58			2.62		109		SPA	59810
		110			228.56			2.60		109		SPA	60900
		120			228.56			2.60		109		SPA	61990
		150			228.57			2.61		109		SPA	65260
		180			228.56			2.60		111		SPA	68600
		210			228.56			2.60		107.3		SPA	71820
		240			228.53			2.57		109.2		SPA	55 gal. down -> 75135
		270			228.56			2.60		109.2		SPA	78390
		300			228.53			2.57		112		SPA	81680
		360			228.56			2.60		109.9		SPA	88270
		420			228.54			2.58		111.9		SPA	94980
		480								109.2			55 gal. down -> 101550

avg. 110 gpm

Aquifer Test Data

page 2 of 2

Data for Well 299-W18-23

Pumping Well 299-W18-23

Observation Wells MONITORED

By BWIP

Location 200 WEST RCRA

Type of Aquifer Test CONSTANT-DISCHARGE (RECOVERY)

How Q Measured —

How W/L's Measured E-TAPE

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s TOP OF STILLING PIPE -

Elevation of Meas. Point 1.5' ABOVE LSD.

Depth of Pump/Airpipe 243.5 below LSD

Pump On: date 6/22/87 time 08:05

Pump Off: date 6/22/87 time 16:05

Duration of Aquifer Test 9 hrs.

LDW = Lee Walker From BWIP

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>225.96'</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	γ or s'	Reading	Q	
	16:05	480	0								
		485	0.5	461	226.16			.20	SPA		
		490	1.0	461	226.10			.14	SPA		
		495	1.5	321	226.11			.15	SPA		
		502	2	341	226.11			.15	SPA		
		508	3	161	226.09			.13	SPA		
		514	4	121	226.08			.12	SPA		
		515	5	97	226.05			.09	SPA		
		516	6	81	226.06			.10	SPA		
		517	7	181	226.04			.08	SPA		
		519	9	54.3	226.01			.05	SPA		
		521	11	44.6	226.02			.06	SPA		
		523	13	57.9	226.01			.05	SPA		
		525	15	33	226.00			.04	SPA		
		530	20	25	225.98			.02	SPA		
	16:30	535	25	20.2	225.97			.01	LDW		
		540	30	17	225.97			.01	LDW		
		545	35	14.7	225.96			.0	LDW		
		550	40	13	225.94			-.02	LDW		
		555	45	11.7	225.94			-.02	LDW		
		560	50	10.6	225.94			-.02	LDW		
	17:05	570	60	9	225.93			-.03	LDW		
		580	70								
		590	80								
	17:35	600	90								
		610	100								
		620	110								
	18:05	630	120								
		640	130								

Aquifer Test Data

page 1 of 2

Location 200 West RCRA

Type of Aquifer Test CONSTANT-DISCHARGE (DRAWDOWN)

How Q Measured McCrometer Flowmeter #82-2-435

How W.L.'s Measured STEEL/E-TAPE

Rad./Dist. of/From Pumping Well -

Meas. Point for W.L.'s TOP OF STEEL JOINT

Elevation of Meas. Point 1.5' ABL LID

Data for Well 2W-18-24

Pumping Well 2W-18-24

Observation Wells monitored

by DWP

Depth of Pump/Airpipe 243.5' below LID

Pump On: date 6/22/87 time 08:05

Pump Off: date 6/22/87 time 16:05

Duration of Aquifer Test 8 hrs

STATIC -> 225.74 (below LID) (225.91 E-TAPE)

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>225.96'</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
	08:05	0			225.96		0			SPA	McCometer 48910	
		.5			225.11		2.30			SPA		
		1			224.29		2.33			SPA		
		1.5			223.31		2.45			SPA		
		2			222.32		2.46		108	SPA		
		3			221.38		2.42			SPA		
		4			220.39		2.42			SPA		
		5			220.44		2.48			SPA	49450	
		6			220.43		2.47		105	SPA		
		7			220.44		2.48			SPA	49660	
		9			220.46		2.50		110	SPA	49880	
		11			220.45		2.49		110	SPA	50100	
		13			220.48		2.52			SPA		
		15			220.45		2.49		109	SPA		
		20			220.45		2.53			SPA	51080	
		25			220.51		2.55		110	SPA	51630	
		30			220.51		2.55		110	SPA	52180	
		35			220.52		2.56		110	SPA		
		40			220.51		2.55		110	SPA	53270	
		45			220.53		2.57		109	SPA	53810	
		50			220.55		2.59		110	SPA	54360	
		60			220.54		2.58		108	SPA	55450	
		70			220.56		2.60		111	SPA	56560	
		80			220.55		2.59		108	SPA		
		90			220.56		2.60			SPA	58720	
		100			220.58		2.62		109	SPA	59810	
		110			220.56		2.60		108	SPA	60900	
		120			220.56		2.60		104	SPA	61990	
		150			220.57		2.61		104	SPA	65260	
		200			220.56		2.60		111	SPA	68100	
		210			220.56		2.60		107	SPA	71820	
		240			220.53		2.57		107	SPA	55 gal. draw → 75100	
		270			220.56		2.60		107	SPA	78390	
		300			220.53		2.57		107	SPA	81680	
		360			220.58		2.60		109	SPA	88270	
		420			220.54		2.58		118	SPA	94980	
		480							109.2		55 gal. draw → 41 sec. 101530	

avg. - 110 gpm

Aquifer Test Data

page 2 of 2

Data for Well 2W18-43

Pumping Well 2W18-43

Observation Wells MONITOR

By BWP

Location 200 West RCR

Type of Aquifer Test RECOVERY

How Q Measured McCrometer #82-2435

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s TOP/GRINDING PIPE 1.5' ABOVE

Elevation of Meas. Point

Depth of Pump/Airpipe 243.5' below LEO

Pump On: date 6/19/87 time 0715

Pump Off: date 6/19/87 time

Duration of Aquifer Test

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>225.60'</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	ft or s'	Reading	Q	
	1018	183	0		228.22			2.62		CSC	
		183.5	.5	36.7	225.85			2.25		CSC	
1019	184	1	184		225.82			.22		CSC	
		184.5	1.5	123	225.82			.22		CSC	
1020	185	2	185		225.81			.21		CSC	
		186	3	167	225.80			.20		CSC	
		187	4	167.5	225.72			.18		CSC	
		188	5	166.7	225.72			.17		CSC	
		190	7	163.3	225.75			.15		CSC	
		192	9	160.0	225.73			.13		CSC	
		194	11	157.9	225.72			.12		CSC	
		196	13	156.2	225.71			.11		CSC	
		198	15	154.8	225.70			.10		CSC	
1020	203	20	10.15	225.70				.10		CSC	
		208	25	9.33	225.69			.09		CSC	
1020	213	30	7.10	225.67				.07		CSC	
		218	35	6.23	225.66			.06		CSC	
		223	40	5.58	225.65			.05		CSC	
		228	45	5.07	225.64			.04		CSC	
		233	50	4.66	225.64			.04		CSC	
		238	60	4.05	225.63			.03		CSC	
		243	70	3.64	225.62			.02		CSC	
		248	80	3.29	225.61			.01		CSC	
1148	253	90	3.03	225.60				.00		CSC	
		258	100	2.83	225.60			.00			
		263	110	2.64	225.60			.00			
1218	268	120	2.53	225.59				-.01			
		273	130	2.22	225.57			-.03			
		278	140	2.02	225.55			-.05			
		283	210	1.77	225.52			-.08			
		288	250	1.73	225.51			-.09			
		293	270	1.69	225.50			-.10			
		298	300	1.67	225.50			-.10			

AQUIFER TEST SUMMARY FOR WELL 299-W18-24

Purpose of Test: To estimate hydraulic properties (transmissivity, hydraulic conductivity, and storativity) for the middle Ringold unit in the 200-West Area.

Types of Tests Performed:

Slug Test () Specific Capacity () Constant Discharge (x) Recovery (x)

Hydrogeologic Unit Tested: Middle Ringold unit

Depth of Formation, Top: 210 ft. Bottom: 453 ft (interpolated).

Depth of Screened Interval in Pumped Well, Top: 230 ft. Bottom: 240 ft.

Observation Wells Used:

299-W15-18

299-W18-2

Distance to Pumped Well:

299-W15-18: 735 ft.

299-W18-2: 125 ft.

Elevations (Depths) of Screened Interval:

299-W15-18: Top: 208 ft. Bottom: 238 ft.

299-W18-2: Top: 205 ft. Bottom: 255 ft.

Date of Test: 07/17/87

Start Time of Test: 0810 hr

Pumping Rate: 100 gpm

Duration of Test: 450 min

Pre-test Water-level Elevations (Depths):

Pumping Well: 299-W18-24 210.20 ft.

Observation Well: 299-W15-18 212.37 ft.

Observation Well: 299-W18-2 209.90 ft.

Analysis Methods and Results:

<u>Methods</u>	<u>Transmissivity (ft²/d)</u>	<u>Hydraulic Conductivity (ft/d)</u>	<u>Storativity</u>
Recovery (Cooper and Jacob 1946) Pumping Well	44,000	180	NA
(Theis 1935) Observation Well 299-W18-2	17,000	70	0.001

Remarks: The assumption that the well is fully penetrating is not satisfied in the Cooper and Jacob and Theis analyses. Drawdown data from the observation wells are insufficient for analysis. No response was observed in observation well 299-W15-18 during pumping.

RCRA WELL 299-W18-24
 CONSTANT-DISCHARGE RECOVERY
 COOPER-JACOB METHOD
 7/17/87

F.130

Residual
 Drawdown (ft)

OBSERVATION WELL 299-W18-2
 CONSTANT-DISCHARGE RECOVERY
 THEIS METHOD
 7/17/87

F.131

Calculated
 Recovery
 (ft)

Aquifer Test Data

page 1 of 1

Data for Well 2-W18-24

Pumping Well 2-W18-24

Observation Wells _____

Location 200 West RCRA

Type of Aquifer Test STEP 2D/DEVELOPMENT

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE

Red./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s DE TRENNE 3.3' ABV LSO

Elevation of Meas. Point _____

Depth of Pump/Airpipe 236' LSO

Pump On: date 7/16/87 time _____

Pump Off: date 7/16/87 time _____

Duration of Aquifer Test _____

Time				Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0				Static Water Level <u>213.57 E-TAPE</u>							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q	
7/16	1625	0							129350		
		:30					214.46				
		1					214.4				
		1:30					214.36				
		2					214.35				
		3					214.35 (3.5)		129515		
		4					214.33		57.5		
		5					214.2 (5.5)		129630		
		7					214.18				
		9					214.38				
		01					215.06				
		03					215.13				
		05					215.14				
		07					215.14				
		09					215.14				
		11					215.07				
25	05						215.13				
	07						215.14				
	09						215.17				
	11						215.14				
	13						215.16		13930 100		
	15						215.16		132130		
	17						215.14				
30	12						213.85				
	14						213.70				
	16						213.65				
	18						213.62				
	20						213.62				
	22						213.57				
	24						213.58				
	26						213.54				
	28						213.54				

Aquifer Test Data

page 1 of 2

Data for Well 2 W 18-24

Pumping Well 2 W 18-24

Observation Wells 2 W 15-18

Location 200 West RCR

Type of Aquifer Test CONSTANT - DISCHARGE

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well —

Meas. Point for W.L.'s TOP TIE LINE 3.3' ASV LSP

Elevation of Meas. Point —

Depth of Pump/Airpipe 236' LSP

Pump On: date 7/17/87 time 0810

Pump Off: date 7/17/87 time 1540

Duration of Aquifer Test 7.5 hr

Time					Water Level Data					Discharge		Recorded By	Comments
Day	Clock Time	t	t'	1/t'	Static Water Level	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
t = <u>0</u> at t' = 0					<u>213.52 M.F.</u>							5	METER #82-2-985
7/17	0800	0				213.50			0	132640			
	0830					214.99			-1.49				
	1					215.05			1.55				Started chronograph
	0830					215.10			1.60	46.3			at 2 min.
	2					215.12			1.63				
	2					215.18			1.68	132930			
	4					215.18			1.68				
	5					215.17			1.67		107.5		
	7					215.18			1.68	133360			CC 14
	9					215.17			1.67				> 60 ppm down
	11												near 12" - 8" pipe
	12												Measuring
	15												at 15 min
	20												
	30												
	35					215.10			1.60				237 136365
	40					215.08			1.58	99			240 136860
	55					215.09			1.59				
	60					215.09			1.59	98.9			256 138245
	90					215.09			1.59				212 141805
	100					215.12			1.62	99.5			(98.9 gpm)
	120					215.14			1.64	99.7			2102 142800
	240					215.18			1.68				2121 144695
										101			2150 157730
	270					215.18			1.68	159770	102		2303 163110
	300					215.14			1.64				2362 168965
	360					215.14			1.64	99.7			2423 175005
	420					215.15			1.65	99			
	1540 450									177700			Avg. Q = 100 gpm

STARTING
TO RAIN

102
100

Aquifer Test Data

page 2 of 2

Data for Well 2-10-24

Pumping Well 2-5219-24

Observation Wells 2-2015-18

2-W18-2

Location 200 West RCRA

Type of Aquifer Test Constant-Discharge Recovery

How Q Measured Flow Meter

How W.L.'s Measured FE - TAP 2

Rad./Dist. of/From Pumping Well _____

Meas. Point for W.L.'s TOP TRAMM 6 3.3' ABV LSD

Elevation of Meas. Point _____

Depth of Pump/Airpipe 236' LSD

Pump Qn: date 7/17/87 time 0810

Pump Off: date 7/17/97 time

Duration of Aquifer Test _____

[illegible]

Aquifer Test Data

Observation
299 W15-1B
299 W18-2

page 1 of 1

Data for Well 299-W15-1B

Pumping Well 299-W18-2A

Observation Wells 2-W15-1B

2-W18-2

Location 200 West 2nd St

Type of Aquifer Test CONSTANT RATE

How Q Measured FLOW METER

How W.L.'s Measured E-TAPE

Rad./Dist. of/From Pumping Well

Meas. Point for W.L.'s T/C 5.92' ADV LSD

Elevation of Meas. Point cut away T/C = 1.75' ADV LSD

Depth of Pump/Airpipe 236' LSD

Pump On: date 3/13/97 time 0810

Pump Off: date 3/13/97 time

Duration of Aquifer Test

Time					Water Level Data				Discharge		Recorded By	Comments
t = _____ at t' = 0					Static Water Level <u>214.12</u> T/C							
Day	Clock Time	t	t'	1/t'	Reading	Conversions or Corrections	Water Level	s or s'	Reading	Q		
3/16	1750	-			217.90	- 5.92	211.98	-				217.90
	0800				218.27	- 5.92	212.35					211.98
3/17												cut off casing
		14			214.12	- 1.75	212.37					
		18			214.12							
		26			214.12							
		47			214.12							
	0940				214.10				SPA			
	0954				213.85	STEEL TAP			SPA			STEEL TAP MEAS.
		170			214.15				CSC			START W.L. TO RAIN
		255			214.12				CSC			
		300			214.12				CSC			Pulling tape
-	-	-	-	-	-	-	-	-	-	-	-	cut off casing
		330			212.30	point 2.0' ADV			CSC			placed tape
		360			212.35	1' ADV			CSC			in 2-W14--
		390			212.36				CSC			
		420			212.39				CSC			
		450	0		212.37				CSC			
		460.5	.5	.901	212.34			.44				Recovery
		451	1	.451	212.30			.40				
		451.5	1.5	.301	212.27			.37				
		452	2	.224	212.26			.36				
		453	3	.151	212.22			.32				
		454	4	.113	212.20			.30				
		455	5	.91	212.17			.27				
		457	7	.65	212.14			.24				
		459	9	.51	212.11			.21				
		464	14	.33	212.07			.17				
		465	15	.31	212.06			.16				
		470	20	.23	212.04			.14				
		475	25	.19	212.03			.13				
		480	30	.16	212.01			.11				
		485	35	.13	212.01			.11				assume static
		490	40	.12	212.0			.10				is ~ 211.90' from
		495	45	.11	211.99			.09				measured
												RM Karen Swaman
												done by 1/2 ch
												measured in me

RM Karen Swanson
done by E-tape
measured

checked out E-tape
corrected wrapped up
didn't or back down

REFERENCES

- Cooper, H. H., and C. E. Jacob. 1946. "A Generalized Graphical Method for Evaluating Formation Constants and Summarizing Well-Field History." In Transactions of the American Geophysical Union 27(IV):526-534.
- Hargis, D. R. 1979. Analysis of Factors Affecting Water Level Recovery Data. Dissertation, University of Arizona. University Microfilms International, Ann Arbor, Michigan.
- Schafer, D. C. 1978. "Casing Storage Can Affect Pumping Test Data." The Johnson Drillers Journal, January-February 1978, Johnson Division, UOP, Inc., St. Paul, Minnesota.
- Theis, C. V. 1935. "The Relation Between the Lowering of the Piezometric Surface and the Rate and Duration of Discharge at a Well Using Ground-Water Storage." In Transactions of the American Geophysical Union 16:519-524.

REFERENCES

- Casper, H. H., and E. E. Jacob. 1948. "A Generalized Graphical Method for Evaluating Permeability Coefficients and Storage Coefficients." *Transactions of the American Geophysical Union* 29(14):2225-2234.
- Miller, D. E. 1959. *Geology of Eastern Arizona*. Tucson: University of Arizona Press.
- Miller, D. E. 1965. "Casing Studies Can Afford Pumping Test Data." *The Mining Engineer*, January-February 1965, Johnson Division, UOP, Inc., St. East, Minnesota.
- Miller, D. E. 1972. "The Relation Between the Lowering of the Piezometric Surface and the Rate and Duration of Discharge at a Well Using Groundwater Storage." *Transactions of the American Geophysical Union* 53(1):215-219.

APPENDIX G

SURVEY DATA REPORTS FOR GROUND-WATER MONITORING
WELLS AROUND WASTE MANAGEMENT AREAS 1, 2, 3, AND 4

KAISER ENGINEERS HANFORD		SURVEY DATA REPORT		Request No. — 8 7 4 — 2 6 5	
Project/W.O. No. CR 0386		Title GROUNDWATER MONITORING WELLS		File No. W E L L — 1 1 3	
KEH Job No. 242130		Prepared By <i>Wesley S. Ladd</i>		Date 12-07-87	
				Revised By <i>A. F. Brazil</i>	
DESCRIPTION OF WORK		ACCEPTABILITY (Within Plan Tolerance)		DISTRIBUTION	
Horizontal and vertical locations of monitoring wells in the 200E area		Yes ☐ No ☐ NA ☒ TBD by Requestor ☐		Survey File ☐ 08 Field Project File ☐ 0 C. Hodge ☐ 1 M. Chamness ☐ 1 G. Last ☐ 1 B. Poremba ☐ 1	
SURVEY RESULTS AND COMMENTS					
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>		
299-E27-8	N 44,496 W 49,642		Centerline of 4" casing		
		637.83	"X" stamped in top north rim of casing		
		634.64	Top of brass cap		
299-E27-9	N 44,484 W 49,122		Centerline of 4" casing		
		629.21	"X" stamped in top north rim of casing		
		627.31	Top of brass cap		
299-E27-10	N 44,520 W 48,522		Center line of 4" casing		
		624.47	"X" stamped in top north rim of casing		
		622.42	Top of brass cap		

KEH-159.1 (6-84)

KAISER ENGINEERS HANFORD		FIELD SKETCH 8 7 4 - 2 6 5 W E L L - 1 1 3	
Attachment To Or Description: GROUND WATER MONITORING WELL			Sheet 2 of 4
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>
299-E28-26	N 44,446		Centerline of 4" casing
	W 55,606		
		687.26	"X" stamped in top north rim of casing
		684.84	Top of brass cap
299-E28-27	N 44,595		Centerline of 4" casing
	N 54,670		
		680.37	"X" stamped in top north rim of casing
		678.18	Top of brass cap
299-E32-2	N 45,904		Centerline of 4" casing
	W 56,565		
		670.06	"X" stamped in top north rim of casing
		667.91	Top of brass cap
299-E32-3	N 45,631		Centerline of 4" casing
	W 56,721		
		676.51	"X" stamped in top north rim of casing
		675.32	Top of brass cap
299-E32-4	N 44,985		Centerline of 4" casing
	W 56,713		
		685.88	"X" stamped in top north rim of casing
		684.64	Top of brass cap
299-E33-28	N 45,596		Centerline of 4" casing
	W 54,668		
		664.23	"X" stamped in top north rim of casing
		662.66	Top of brass cap

KEH-188.2 (4-82)

KAISER ENGINEERS HANFORD		FIELD SKETCH 8 7 4 - 2 6 5 W E L L - 1 1 3	
Attachment To Or Description:		Sheet 3 of 4	
GROUND WATER MONITORING WELL			
WELL NO.	COORDINATE	ELEVATION	DESCRIPTION
299-E33-29	N 45,124		Centerline of 4" casing
	W 54,665		
		673.77	"X" stamped in top north rim of casing
		671.53	Top of brass cap
299-E33-30	N 45,903		Centerline of 4" casing
	W 55,660		
		663.70	"X" stamped in top north rim of casing
		661.92	Top of brass cap
299-E34-2	N 45,076		Centerline of 4" casing
	W 50,048		
		630.80	"X" stamped in top north rim of casing
		629.03	Top of brass cap
299-E34-3	N 45,337		Centerline of 4" casing
	N 48,488		
		611.52	"X" stamped in top north rim of casing
		609.48	Top of brass cap
299-E34-4	N 46,791		Centerline of 4" casing
	W 49,419		
		587.56	"X" stamped in top north rim of casing
		585.17	Top of brass cap
299-E34-5	N 46,791		Centerline of 4" casing
	W 50,014		
		590.79	"X" stamped in top north rim of casing
		589.01	Top of brass cap

KEH-100.2 (4-82)

KAISER ENGINEERS HANFORD	<div style="display: flex; justify-content: space-between;"> <div>FIELD SKETCH</div> <div>8 7 4 - 2 6 5</div> </div> <div style="display: flex; justify-content: space-between;"> <div></div> <div>W E L L - 1 1 3</div> </div>		
Attachment To Or Description:			
GROUNDWATER MONITORING WELLS			
Sheet <u>4</u> of <u>4</u>			
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>
299-E34-6	N 46,784 W 50,609		Centerline of 4" casing
		597.83	"X" stamped in top north rim of casing
		596.56	Top of brass cap
<p>N O T E : Wells were controlled by monument N 41,000 W 47,300 elevation equals 678.105. The line between monument N 41,000 W 47,300 and monument 2E-3 was held as N 00° 00' 00" E.</p>			

KEH-159.2 (4-82)

KAISER ENGINEERS HANFORD		SURVEY DATA REPORT		Request No.	
				- 8 7 4 - 2 6 5	
Project/W.O. No. CR 0386		Title GROUND WATER MONITORING WELLS (200-W)		File No.	
				W E L L - 1 1 4	
KEH Job No. 242130		Prepared By <i>Walter J. Anderson</i>		Date	
				12-10-87	
				Reviewer <i>J.F. Bryant</i>	
				1 4	
DESCRIPTION OF WORK		ACCEPTABILITY (Within Plan Tolerance)		DISTRIBUTION	
Horizontal and vertical locations of monitoring wells in the 200 W area		Yes ☐		Survey File OR	
		No ☐		Field Project File 0	
		NA ☒		C. Hodge 1	
		TBD by		M. Chamness 1	
		Requestor ☐		G. Last 1	
				B. Poremba 1	
SURVEY RESULTS AND COMMENTS					
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>		
299-W-6-2	N 45,571	.	Centerline of 4" casing		
	W 75,302				
		692.45	"X" stamped in top north rim of casing		
		690.17	Top of brass cap		
299-W-7-1	N 46,551		Centerline of 4" casing		
	W 78,601				
		690.71	"X" stamped in top north rim of casing		
		688.55	Top of brass cap		
299-W-7-2	N 46,519		Centerline of 4" casing		
	W 77,385				
		675.59	"X" stamped in top north rim of casing		
		673.19	Top of brass cap		
299-W-7-3	N 46,520		Centerline of 4" casing		
	W 77,420				
		676.14	"X" stamped in top north rim of casing		
		673.71	Top of brass cap		

KEH 159.1 (6-84)

KAISER ENGINEERS HANFORD		FIELD SKETCH 8 7 4 - 2 6 5 W E L L - 1 1 4	
Attachment To Or Description: GROUND WATER MONITORING WELLS (200-W)		Sheet 2 of 4	
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>
299-W-7-4	N 45,435 W 77,040		Centerline of 4" casing
		671.69	"X" stamped in top north rim of casing
		669.02	Top of brass cap
299-W-7-5	N 46,509 W 76,816		Centerline of 4" casing
		671.14	"X" stamped in top north rim of casing
		670.41	Top of brass cap
299-W-7-6	N 46,509 W 76,219		Centerline of 4" casing
		678.64	"X" stamped in top north rim of casing
		676.25	Top of brass cap
299-W-8-1	N 46,551 W 79,200		Centerline of 4" casing
		701.33	"X" stamped in top north rim of casing
		699.45	Top of brass cap
299-W-9-1	N 44,508 W 79,507		Centerline of 4" casing
		737.73	"X" stamped in top north rim of casing
		735.36	Top of brass cap
299-W-10-13	N 43,137 W 78,297		Centerline of 4" casing
		699.04	"X" stamped in top north rim of casing
		696.58	Top of brass cap

KEH-159.2 (4-82)

KAISER ENGINEERS HANFORD		FIELD SKETCH		8 7 4 - 2 6 5 W E L L - 1 1 4
Attachment To Or Description: GROUND WATER MONITORING WELLS (200-W)			Sheet 3 of 4	
<u>WELL NO.</u>	<u>COORDINATE</u>	<u>ELEVATION</u>	<u>DESCRIPTION</u>	
299-W-10-14	N 43,143 W 78,330		Centerline of 4" casing	
		699.43	"X" stamped in top north rim of casing	
		697.09	Top of brass cap	
299-W-15-15	N 40,330 W 78,103		Centerline of 4" casing	
		697.96	"X" stamped in top north rim of casing	
		695.74	Top of brass cap	
299-W-15-16	N 40,269 W 77,387		Centerline of 4" casing	
		684.89	"X" stamped in top north rim of casing	
		682.62	Top of brass cap	
299-W-15-17	N 40,221 W 77,387		Centerline of 4" casing	
		684.64	"X" stamped in top north rim of casing	
		682.85	Top of brass cap	
299-W-15-18	N 39,705 W 77,383		Centerline of 4" casing	
		685.71	"X" stamped in top north rim of casing	
		683.55	Top of brass cap	
299-W-18-21	N 37,794 W 78,080		Centerline of 4" casing	
		668.62	"X" stamped in top north rim of casing	
		666.50	Top of brass cap	

KEH-189.2 (4-82)

KAISER ENGINEERS HANFORD		FIELD SKETCH 8 7 4 - 2 6 5 W E L L - 1 1 4	
Attachment To Or Description: GROUND WATER MONITORING WELLS (200-W)			Sheet <u>4</u> of <u>4</u>
299-W-18-22	N 37,831 W 78,109	Centerline of 4" casing 668.49 666.49	"X" stamped in top north rim of casing Top of brass cap
299-W-18-23	N 38,987 W 78,120	Centerline of 4" casing 696.81 694.75	"X" stamped in top north rim of casing Top of brass cap
299-W-18-24	N 38,998 W 77,180	Centerline of 4" casing 684.35 682.18	"X" stamped in top north rim of casing Top of brass cap
<p>N O T E : The vertical control used for wells came from monument N 46,545 - W 78,195 elevation equals 683.96</p> <p> The horizontal control used for wells came from monument N 39,000 - W 77,200 and holding the line between said monument and monument N 39,000 W 71,000 (elephants) as N 90° 00' 00" E.</p>			

KEH-159.2 (4-82)

APPENDIX H

PROCEDURE, WATER-LEVEL DATA, AND HYDROGRAPHS

APPENDIX H

PROCEDURE, WATER-LEVEL DATA, AND HYDROGRAPHS

This appendix presents the procedure used to collect water-level data from the 35 monitoring wells installed around the 200 Areas low-level burial grounds. Also presented in this appendix are the water-level data collected as of August 1, 1988, and the corresponding hydrographs.

APPENDIX B

PROCEDURE, WATER LEVEL DATA, AND HYDROGRAPHS

This appendix presents the procedure used to collect water-level data from the 35 monitoring wells installed around the 200 Area low-level burial grounds. Also presented in this appendix are the water-level data collected as of August 1, 1988, and the corresponding hydrographs.

Procedure for Water-Level Measurements for the 100-H Area Water-Level Network, P-5 for RCRA Compliance/Hazardous Materials Monitoring

Introduction Water-level measurements are taken approximately twice a month. All wells in the current network are measured on the same day. These measurements are taken as depth-to-water from the top of the well casing. They must be subtracted from the surveyed elevation of the casing to obtain the elevation of the water table. The water-table elevations obtained for all wells in the network can be used to produce a contour map showing the ground-water surface on the day that the measurements were made. These contour maps can be used to help characterize the ground-water flow system and to ensure that the sampling network is adequate.

Equipment The following equipment will be needed:

- graduated steel measuring tape with attached weight
- blue carpenter's chalk
- 100-H Area Water-Level Network field notebook

Procedure If the steel tape has a zero reading point, chalk the 1-ft section of tape below it. If the steel tape has no zero reading point and has divisions in hundredths of a foot all along it, then chalk several feet of the bottom portion of the tape.

Estimate the approximate depth to water by using the most recent of previous measurements.

Lower the steel tape into the well to the estimated water level. Read the value of the "hold point" from the tape while holding it even with the well's measuring point (marked with paint) on the top of the casing.

Remove the steel tape and check the wetted portion at the end of the tape.

NOTE: If the chalked portion is not wet repeat the procedure using a greater hold point. If the chalked portion is completely wet repeat the procedure using a lesser hold point.

If the tape has the 1-ft section of divisions then add the unwetted length of the chalked portion of the tape to the hold point value to obtain the depth-to-water measurement. If the

Approvals: Project Manager <i>John S. Prater</i> 1-5-87		QAD Rep. <i>DR Dahl</i> 12/17/86	
Procedure No: P-5	Revision No: 0	Date Issued: 1-5-87	Page 1 of 2

Procedure for Water-Level Measurements for the
100-H Area Water-Level Network, P-5

tape has divisions all along it's length then subtract the wetted length of the chalked portion of the tape from the hold point value to obtain the depth-to-water measurement.

Repeat the procedure until two steel tape measurements agree within at least ± 0.05 ft.

Record the date, well number, depth-to-water measurements, time of measurements, steel tape number, and the initials of the person taking the measurements in the 100-H Area Water-Level Network field notebook. If you must subtract the wetted length to obtain the depth to water measurement then record the hold point and the length of the wet portion as well as the depth-to-water measurements.

Procedure No. P-5	Revision No. 0	Date Issued: 1-5-87	Page 2 of 2
----------------------	-------------------	------------------------	-------------

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E27-8

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E27-8	12/02/87	637.83	232.66	405.17
2-E27-8	12/11/87	637.83	232.78	405.05
2-E27-8	1/08/88	637.83	232.71	405.12
2-E27-8	1/13/88	637.83	232.76	405.07
2-E27-8	1/19/88	637.83	232.84	404.99
2-E27-8	1/28/88	637.83	232.75	405.08
2-E27-8	2/03/88	637.83	232.90	404.93
2-E27-8	2/10/88	637.83	232.81	405.02
2-E27-8	2/17/88	637.83	232.66	405.17
2-E27-8	3/08/88	637.83	232.51	405.32
2-E27-8	3/22/88	637.83	232.42	405.41
2-E27-8	3/31/88	637.83	232.46	405.37
2-E27-8	5/25/88	637.83	232.72	405.11
2-E27-8	6/29/88	637.83	232.51	405.32
2-E27-8	7/27/88	637.83	232.33	405.50

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E27-9

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E27-9	12/02/87	629.21	223.90	405.31
2-E27-9	12/11/87	629.21	223.98	405.23
2-E27-9	1/08/88	629.21	223.96	405.25
2-E27-9	1/13/88	629.21	223.98	405.23
2-E27-9	1/19/88	629.21	224.08	405.13
2-E27-9	1/28/88	629.21	223.96	405.25
2-E27-9	2/03/88	629.21	224.14	405.07
2-E27-9	2/10/88	629.21	224.03	405.18
2-E27-9	2/17/88	629.21	223.87	405.34
2-E27-9	3/08/88	629.21	223.69	405.52
2-E27-9	3/22/88	629.21	223.61	405.60
2-E27-9	3/31/88	629.21	223.68	405.53
2-E27-9	5/25/88	629.21	223.96	405.25
2-E27-9	6/29/88	629.21	223.73	405.48
2-E27-9	7/27/88	629.21	223.55	405.66

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E27-10

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E27-10	12/02/87	624.47	218.75	405.72
2-E27-10	12/11/87	624.47	218.84	405.63
2-E27-10	1/08/88	624.47	218.87	405.60
2-E27-10	1/13/88	624.47	218.90	405.57
2-E27-10	1/19/88	624.47	218.97	405.50
2-E27-10	1/28/88	624.47	218.89	405.58
2-E27-10	2/03/88	624.47	218.99	405.48
2-E27-10	2/10/88	624.47	218.89	405.58
2-E27-10	2/17/88	624.47	218.77	405.70
2-E27-10	3/08/88	624.47	218.53	405.94
2-E27-10	3/22/88	624.47	218.43	406.04
2-E27-10	3/31/88	624.47	218.54	405.93
2-E27-10	5/25/88	624.47	218.86	405.61
2-E27-10	6/29/88	624.47	218.47	406.00
2-E27-10	7/27/88	624.47	218.33	406.14

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E28-26

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E28-26	12/02/87	687.26	282.39	404.87
2-E28-26	12/11/87	687.26	282.39	404.87
2-E28-26	1/08/88	687.26	282.35	404.91
2-E28-26	1/13/88	687.26	282.46	404.80
2-E28-26	1/19/88	687.26	282.54	404.72
2-E28-26	1/28/88	687.26	282.45	404.81
2-E28-26	2/03/88	687.26	282.58	404.68
2-E28-26	2/10/88	687.26	282.52	404.74
2-E28-26	2/17/88	687.26	282.30	404.96
2-E28-26	3/08/88	687.26	282.24	405.02
2-E28-26	3/22/88	687.26	282.15	405.11
2-E28-26	3/28/88	687.26	282.13	405.13
2-E28-26	5/25/88	687.26	282.42	404.84
2-E28-26	6/29/88	687.26	282.28	404.98
2-E28-26	7/27/88	687.26	282.10	405.16
2-E28-26	7/27/88	687.26	282.11	405.15

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E28-27

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E28-27	12/02/87	680.37	275.47	404.90
2-E28-27	12/11/87	680.37	275.61	404.76
2-E28-27	1/08/88	680.37	275.57	404.80
2-E28-27	1/13/88	680.37	275.58	404.79
2-E28-27	1/19/88	680.37	275.60	404.77
2-E28-27	1/28/88	680.37	275.61	404.76
2-E28-27	2/03/88	680.37	275.66	404.71
2-E28-27	2/10/88	680.37	275.62	404.75
2-E28-27	2/17/88	680.37	275.56	404.81
2-E28-27	3/08/88	680.37	275.41	404.96
2-E28-27	3/22/88	680.37	275.31	405.06
2-E28-27	3/28/88	680.37	275.29	405.08
2-E28-27	5/25/88	680.37	275.56	404.81
2-E28-27	6/29/88	680.37	275.36	405.01
2-E28-27	7/27/88	680.37	275.22	405.15

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E32-2

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E32-2	12/02/87	670.06	265.39	404.67
2-E32-2	12/11/87	670.06	265.45	404.61
2-E32-2	1/08/88	670.06	265.40	404.66
2-E32-2	1/13/88	670.06	265.49	404.57
2-E32-2	1/19/88	670.06	265.51	404.55
2-E32-2	1/28/88	670.06	265.48	404.58
2-E32-2	2/03/88	670.06	265.56	404.50
2-E32-2	2/10/88	670.06	265.53	404.53
2-E32-2	2/17/88	670.06	265.41	404.65
2-E32-2	3/08/88	670.06	265.32	404.74
2-E32-2	3/22/88	670.06	265.22	404.84
2-E32-2	3/28/88	670.06	265.19	404.87
2-E32-2	5/25/88	670.06	265.45	404.61
2-E32-2	6/29/88	670.06	265.29	404.77
2-E32-2	7/27/88	670.06	265.14	404.92

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E32-3

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E32-3	12/02/87	676.51	271.76	404.75
2-E32-3	12/11/87	676.51	271.84	404.67
2-E32-3	1/08/88	676.51	271.78	404.73
2-E32-3	1/13/88	676.51	271.86	404.65
2-E32-3	1/19/88	676.51	271.91	404.60
2-E32-3	1/28/88	676.51	271.85	404.66
2-E32-3	2/03/88	676.51	271.93	404.58
2-E32-3	2/10/88	676.51	271.90	404.61
2-E32-3	2/17/88	676.51	271.76	404.75
2-E32-3	3/08/88	676.51	271.68	404.83
2-E32-3	3/22/88	676.51	271.59	404.92
2-E32-3	3/28/88	676.51	271.57	404.94
2-E32-3	5/25/88	676.51	271.82	404.69
2-E32-3	6/29/88	676.51	271.67	404.84
2-E32-3	7/27/88	676.51	271.53	404.98

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E32-4

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E32-4	12/02/87	685.88	281.24	404.64
2-E32-4	12/11/87	685.88	281.33	404.55
2-E32-4	1/08/88	685.88	281.23	404.65
2-E32-4	1/13/88	685.88	281.36	404.52
2-E32-4	1/19/88	685.88	281.42	404.46
2-E32-4	1/28/88	685.88	281.27	404.61
2-E32-4	2/03/88	685.88	281.49	404.39
2-E32-4	2/10/88	685.88	281.39	404.49
2-E32-4	2/17/88	685.88	281.21	404.67
2-E32-4	3/08/88	685.88	281.14	404.74
2-E32-4	3/22/88	685.88	281.07	404.81
2-E32-4	3/28/88	685.88	281.05	404.83
2-E32-4	5/25/88	685.88	281.31	404.57
2-E32-4	6/29/88	685.88	281.19	404.69
2-E32-4	7/27/88	685.88	281.03	404.85

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E33-28

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E33-28	12/02/87	664.23	259.30	404.93
2-E33-28	12/11/87	664.23	259.36	404.87
2-E33-28	1/08/88	664.23	259.38	404.85
2-E33-28	1/13/88	664.23	259.42	404.81
2-E33-28	1/19/88	664.23	259.43	404.80
2-E33-28	1/28/88	664.23	259.44	404.79
2-E33-28	2/03/88	664.23	259.47	404.76
2-E33-28	2/10/88	664.23	259.44	404.79
2-E33-28	2/17/88	664.23	259.38	404.85
2-E33-28	3/08/88	664.23	259.24	404.99
2-E33-28	3/22/88	664.23	259.14	405.09
2-E33-28	3/28/88	664.23	259.12	405.11
2-E33-28	5/25/88	664.23	259.38	404.85
2-E33-28	6/29/88	664.23	259.19	405.04
2-E33-28	7/27/88	664.23	259.05	405.18

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E33-29

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E33-29	12/02/87	673.77	268.98	404.79
2-E33-29	12/11/87	673.77	268.99	404.78
2-E33-29	1/08/88	673.77	268.88	404.89
2-E33-29	1/13/88	673.77	268.96	404.81
2-E33-29	1/19/88	673.77	269.02	404.75
2-E33-29	1/28/88	673.77	268.95	404.82
2-E33-29	2/03/88	673.77	269.06	404.71
2-E33-29	2/10/88	673.77	269.02	404.75
2-E33-29	2/17/88	673.77	268.87	404.90
2-E33-29	3/08/88	673.77	268.77	405.00
2-E33-29	3/22/88	673.77	268.67	405.10
2-E33-29	3/28/88	673.77	268.65	405.12
2-E33-29	5/25/88	673.77	268.93	404.84
2-E33-29	6/29/88	673.77	268.78	404.99

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E33-30

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E33-30	12/02/87	663.70	258.87	404.83
2-E33-30	12/11/87	663.70	258.89	404.81
2-E33-30	1/08/88	663.70	258.82	404.88
2-E33-30	1/13/88	663.70	258.94	404.76
2-E33-30	1/19/88	663.70	258.99	404.71
2-E33-30	1/28/88	663.70	258.92	404.78
2-E33-30	2/03/88	663.70	259.04	404.66
2-E33-30	2/10/88	663.70	259.00	404.70
2-E33-30	2/17/88	663.70	258.82	404.88
2-E33-30	3/08/88	663.70	258.75	404.95
2-E33-30	3/22/88	663.70	258.65	405.05
2-E33-30	3/28/88	663.70	258.63	405.07
2-E33-30	5/25/88	663.70	258.91	404.79
2-E33-30	6/29/88	663.70	258.76	404.94
2-E33-30	7/27/88	663.70	258.60	405.10

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E34-2

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E34-2	12/02/87	630.80	0.00	0.00
2-E34-2	1/08/88	630.80	225.65	405.15
2-E34-2	1/13/88	630.80	225.75	405.05
2-E34-2	1/19/88	630.80	225.83	404.97
2-E34-2	1/28/88	630.80	225.70	405.10
2-E34-2	2/03/88	630.80	225.87	404.93
2-E34-2	2/10/88	630.80	225.78	405.02
2-E34-2	2/17/88	630.80	225.62	405.18
2-E34-2	3/08/88	630.80	225.48	405.32
2-E34-2	3/22/88	630.80	225.39	405.41
2-E34-2	3/31/88	630.80	225.43	405.37
2-E34-2	5/25/88	630.80	225.70	405.10
2-E34-2	6/29/88	630.80	225.53	405.27
2-E34-2	7/27/88	630.80	225.32	405.48

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E34-3

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E34-3	12/02/87	611.52	205.73	405.79
2-E34-3	12/11/87	611.52	205.80	405.72
2-E34-3	1/08/88	611.52	205.87	405.65
2-E34-3	1/13/88	611.52	205.91	405.61
2-E34-3	1/19/88	611.52	205.96	405.56
2-E34-3	1/28/88	611.52	205.90	405.62
2-E34-3	2/03/88	611.52	206.02	405.50
2-E34-3	2/10/88	611.52	205.90	405.62
2-E34-3	2/17/88	611.52	205.81	405.71
2-E34-3	3/08/88	611.52	205.61	405.91
2-E34-3	3/22/88	611.52	205.45	406.07
2-E34-3	3/31/88	611.52	205.53	405.99
2-E34-3	5/25/88	611.52	205.87	405.65
2-E34-3	6/29/88	611.52	205.46	406.06
2-E34-3	7/27/88	611.52	205.30	406.22

WATER-LEVEL DATA FOR WELL 2-E34-4

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E34-4	12/02/87	587.56	0.00	0.00
2-E34-4	5/25/88	587.56	0.00	0.00
2-E34-4	6/29/88	587.56	0.00	0.00
2-E34-4	7/27/88	587.56	0.00	0.00

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E34-5

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E34-5	12/02/87	590.79	184.60	406.19
2-E34-5	12/11/87	590.79	184.66	406.13
2-E34-5	12/11/87	590.79	184.67	406.12
2-E34-5	1/08/88	590.79	184.76	406.03
2-E34-5	1/13/88	590.79	184.80	405.99
2-E34-5	1/19/88	590.79	184.83	405.96
2-E34-5	1/28/88	590.79	184.81	405.98
2-E34-5	2/03/88	590.79	184.89	405.90
2-E34-5	2/10/88	590.79	184.89	405.90
2-E34-5	2/17/88	590.79	184.88	405.91
2-E34-5	3/08/88	590.79	184.85	405.94
2-E34-5	3/22/88	590.79	184.77	406.02
2-E34-5	3/31/88	590.79	184.75	406.04
2-E34-5	5/25/88	590.79	184.85	405.94
2-E34-5	6/29/88	590.79	184.82	405.97
2-E34-5	7/27/88	590.79	184.63	406.16

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-E34-6

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-E34-6	12/02/87	597.83	192.71	405.12
2-E34-6	12/11/87	597.83	192.80	405.03
2-E34-6	12/11/87	597.83	192.80	405.03
2-E34-6	1/08/88	597.83	192.76	405.07
2-E34-6	1/13/88	597.83	192.81	405.02
2-E34-6	1/19/88	597.83	192.92	404.91
2-E34-6	1/28/88	597.83	192.79	405.04
2-E34-6	2/03/88	597.83	192.93	404.90
2-E34-6	2/10/88	597.83	192.88	404.95
2-E34-6	2/17/88	597.83	192.72	405.11
2-E34-6	3/08/88	597.83	192.58	405.25
2-E34-6	3/22/88	597.83	192.51	405.32
2-E34-6	3/31/88	597.83	192.53	405.30
2-E34-6	5/25/88	597.83	192.78	405.05
2-E34-6	6/29/88	597.83	192.62	405.21
2-E34-6	7/27/88	597.83	192.42	405.41

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W6-2

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W6-2	12/10/87	692.45	230.47	461.98
2-W6-2	1/07/88	692.45	230.25	462.20
2-W6-2	1/14/88	692.45	229.93	462.52
2-W6-2	1/21/88	692.45	230.74	461.71
2-W6-2	1/29/88	692.45	230.11	462.34
2-W6-2	2/04/88	692.45	230.56	461.89
2-W6-2	2/11/88	692.45	230.32	462.13
2-W6-2	2/18/88	692.45	230.66	461.79
2-W6-2	3/09/88	692.45	230.47	461.98
2-W6-2	3/23/88	692.45	230.41	462.04
2-W6-2	5/26/88	692.45	230.31	462.14
2-W6-2	6/30/88	692.45	230.35	462.10
2-W6-2	7/28/88	692.45	230.57	461.88

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W7-1

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-1	12/10/87	690.71	228.61	462.10
2-W7-1	1/07/88	690.71	228.44	462.27
2-W7-1	1/14/88	690.71	228.09	462.62
2-W7-1	1/20/88	690.71	228.58	462.13
2-W7-1	1/29/88	690.71	228.25	462.46
2-W7-1	2/04/88	690.71	228.80	461.91
2-W7-1	2/11/88	690.71	228.56	462.15
2-W7-1	2/18/88	690.71	228.90	461.81
2-W7-1	3/09/88	690.71	228.70	462.01
2-W7-1	3/23/88	690.71	228.56	462.15
2-W7-1	5/26/88	690.71	228.64	462.07
2-W7-1	6/30/88	690.71	228.73	461.98
2-W7-1	7/28/88	690.71	228.92	461.79

WATER-LEVEL DATA FOR WELLS 2-W7-2 AND 2-W7-3

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-2	12/10/87	675.59	214.48	461.11
2-W7-2	1/07/88	675.59	214.32	461.27
2-W7-2	1/14/88	675.59	214.03	461.56
2-W7-2	1/15/88	675.59	214.33	461.26
2-W7-2	1/20/88	675.59	214.45	461.14
2-W7-2	1/21/88	675.59	214.77	460.82
2-W7-2	1/29/88	675.59	214.18	461.41
2-W7-2	2/04/88	675.59	214.62	460.97
2-W7-2	2/11/88	675.59	214.42	461.17
2-W7-2	2/18/88	675.59	214.73	460.86
2-W7-2	3/09/88	675.59	214.57	461.02
2-W7-2	3/23/88	675.59	214.49	461.10
2-W7-2	5/26/88	675.59	214.51	461.08
2-W7-2	6/30/88	675.59	214.55	461.04
2-W7-2	7/28/88	675.59	214.76	460.83

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-3	12/10/87	676.14	216.28	459.86
2-W7-3	1/07/88	676.14	216.15	459.99
2-W7-3	1/14/88	676.14	215.82	460.32
2-W7-3	1/20/88	676.14	216.22	459.92
2-W7-3	1/21/88	676.14	216.57	459.57
2-W7-3	1/29/88	676.14	215.95	460.19
2-W7-3	2/04/88	676.14	216.47	459.67
2-W7-3	2/11/88	676.14	216.26	459.88
2-W7-3	2/18/88	676.14	216.57	459.57
2-W7-3	3/09/88	676.14	216.37	459.77
2-W7-3	3/23/88	676.14	216.21	459.93
2-W7-3	5/26/88	676.14	216.31	459.83
2-W7-3	6/30/88	676.14	216.42	459.72
2-W7-3	7/28/88	676.14	216.58	459.56

HYDROGRAPH FOR WELLS 2-W7-2 AND 2-W7-3

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W7-4

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-4	12/10/87	671.69	208.35	463.34
2-W7-4	1/07/88	671.69	208.18	463.51
2-W7-4	1/14/88	671.69	207.96	463.73
2-W7-4	1/21/88	671.69	208.51	463.18
2-W7-4	1/29/88	671.69	208.13	463.56
2-W7-4	2/04/88	671.69	208.37	463.32
2-W7-4	2/11/88	671.69	208.25	463.44
2-W7-4	2/18/88	671.69	208.51	463.18
2-W7-4	3/09/88	671.69	208.41	463.28
2-W7-4	3/23/88	671.69	208.42	463.27
2-W7-4	5/26/88	671.69	208.34	463.35
2-W7-4	6/30/88	671.69	208.33	463.36
2-W7-4	7/28/88	671.69	208.55	463.14

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W7-5

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-5	12/10/87	671.14	210.51	460.63
2-W7-5	1/07/88	673.03	210.28	462.75
2-W7-5	1/14/88	673.03	211.90	461.13
2-W7-5	1/15/88	673.03	212.21	460.82
2-W7-5	1/21/88	673.03	212.66	460.37
2-W7-5	1/29/88	673.03	212.07	460.96
2-W7-5	2/04/88	673.03	212.50	460.53
2-W7-5	2/11/88	673.03	212.31	460.72
2-W7-5	2/18/88	673.03	212.61	460.42
2-W7-5	3/09/88	673.03	212.45	460.58
2-W7-5	3/23/88	673.03	212.39	460.64
2-W7-5	5/26/88	673.03	212.38	460.65
2-W7-5	6/30/88	673.03	212.43	460.60
2-W7-5	7/28/88	673.03	212.63	460.40

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W7-6

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W7-6	12/10/87	678.64	218.03	460.61
2-W7-6	1/07/88	678.64	218.03	460.61
2-W7-6	1/14/88	678.64	217.69	460.95
2-W7-6	1/21/88	678.64	218.37	460.27
2-W7-6	1/29/88	678.64	217.84	460.80
2-W7-6	2/04/88	678.64	218.25	460.39
2-W7-6	2/11/88	678.64	218.09	460.55
2-W7-6	2/18/88	678.64	218.32	460.32
2-W7-6	3/09/88	678.64	218.16	460.48
2-W7-6	3/23/88	678.64	218.03	460.61
2-W7-6	5/26/88	678.64	218.18	460.46
2-W7-6	6/30/88	678.64	218.27	460.37
2-W7-6	7/28/88	678.64	218.30	460.34

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W8-1

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W8-1	12/10/87	701.33	238.82	462.51
2-W8-1	1/07/88	701.33	238.64	462.69
2-W8-1	1/14/88	701.33	238.26	463.07
2-W8-1	1/20/88	701.33	238.78	462.55
2-W8-1	1/29/88	701.33	238.40	462.93
2-W8-1	2/04/88	701.33	239.09	462.24
2-W8-1	2/11/88	701.33	238.78	462.55
2-W8-1	2/18/88	701.33	239.15	462.18
2-W8-1	3/09/88	701.33	238.89	462.44
2-W8-1	3/23/88	701.33	238.67	462.66
2-W8-1	5/26/88	701.33	238.85	462.48
2-W8-1	6/30/88	701.33	238.98	462.35
2-W8-1	7/28/88	701.33	239.16	462.17

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W9-1

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W9-1	12/10/87	737.73	272.09	465.64
2-W9-1	1/07/88	737.73	271.92	465.81
2-W9-1	1/14/88	737.73	271.56	466.17
2-W9-1	1/20/88	737.73	272.06	465.67
2-W9-1	1/29/88	737.73	271.68	466.05
2-W9-1	2/04/88	737.73	272.35	465.38
2-W9-1	2/11/88	737.73	272.09	465.64
2-W9-1	2/18/88	737.73	272.42	465.31
2-W9-1	3/09/88	737.73	272.18	465.55
2-W9-1	3/23/88	737.73	271.96	465.77
2-W9-1	5/26/88	737.73	272.17	465.56
2-W9-1	6/30/88	737.73	272.29	465.44
2-W9-1	7/28/88	737.73	272.43	465.30

WATER-LEVEL DATA FOR WELLS 2-W10-13 AND 2-W10-14

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W10-13	12/10/87	699.04	232.11	466.93
2-W10-13	1/07/88	699.04	231.88	467.16
2-W10-13	1/14/88	699.04	231.52	467.52
2-W10-13	1/20/88	699.04	231.99	467.05
2-W10-13	1/29/88	699.04	231.71	467.33
2-W10-13	2/04/88	699.04	232.27	466.77
2-W10-13	2/11/88	699.04	232.02	467.02
2-W10-13	2/18/88	699.04	232.35	466.69
2-W10-13	3/09/88	699.04	232.12	466.92
2-W10-13	3/23/88	699.04	231.92	467.12
2-W10-13	5/26/88	699.04	232.06	466.98
2-W10-13	6/30/88	699.04	232.14	466.90
2-W10-13	7/28/88	699.04	232.31	466.73

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W10-14	12/10/87	699.43	232.90	466.53
2-W10-14	1/07/88	699.43	232.69	466.74
2-W10-14	1/14/88	699.43	232.56	466.87
2-W10-14	1/20/88	699.43	232.78	466.65
2-W10-14	1/29/88	699.43	232.46	466.97
2-W10-14	2/04/88	699.43	233.07	466.36
2-W10-14	2/11/88	699.43	232.81	466.62
2-W10-14	2/18/88	699.43	233.15	466.28
2-W10-14	3/09/88	699.43	232.87	466.56
2-W10-14	3/23/88	699.43	232.66	466.77
2-W10-14	5/26/88	699.43	232.81	466.62
2-W10-14	6/30/88	699.43	232.93	466.50
2-W10-14	7/28/88	699.43	233.10	466.33

HYDROGRAPH FOR WELLS 2-W10-13 AND 2-W10-14

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W15-15

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W15-15	12/10/87	697.96	228.32	469.64
2-W15-15	1/07/88	697.96	228.02	469.94
2-W15-15	1/14/88	697.96	227.70	470.26
2-W15-15	1/20/88	697.96	228.09	469.87
2-W15-15	1/29/88	697.96	227.78	470.18
2-W15-15	2/04/88	697.96	228.38	469.58
2-W15-15	2/11/88	697.96	228.11	469.85
2-W15-15	2/18/88	697.96	228.44	469.52
2-W15-15	3/09/88	697.96	228.15	469.81
2-W15-15	3/23/88	697.96	227.94	470.02
2-W15-15	5/26/88	697.96	228.10	469.86
2-W15-15	6/30/88	697.96	228.22	469.74
2-W15-15	7/28/88	697.96	228.44	469.52

WATER-LEVEL DATA FOR WELLS 2-W15-16 AND 2-W15-17

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W15-16	12/10/87	684.89	214.51	470.38
2-W15-16	1/07/88	684.89	214.18	470.71
2-W15-16	1/14/88	684.89	213.87	471.02
2-W15-16	1/20/88	684.89	214.20	470.69
2-W15-16	1/29/88	684.89	213.93	470.96
2-W15-16	2/04/88	684.89	214.49	470.40
2-W15-16	2/11/88	684.89	214.20	470.69
2-W15-16	2/18/88	684.89	214.53	470.36
2-W15-16	3/09/88	684.89	214.21	470.68
2-W15-16	3/23/88	684.89	214.01	470.88
2-W15-16	5/26/88	684.89	214.10	470.79
2-W15-16	6/30/88	684.89	214.25	470.64
2-W15-16	7/28/88	684.89	214.49	470.40

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W15-17	12/10/87	684.64	214.71	469.93
2-W15-17	1/07/88	684.64	214.40	470.24
2-W15-17	1/14/88	684.64	214.11	470.53
2-W15-17	1/20/88	684.64	215.00	469.64
2-W15-17	1/29/88	684.64	214.68	469.96
2-W15-17	2/04/88	684.64	214.78	469.86
2-W15-17	2/11/88	684.64	214.73	469.91
2-W15-17	2/18/88	684.64	214.70	469.94
2-W15-17	3/09/88	684.64	214.58	470.06
2-W15-17	3/23/88	684.64	214.52	470.12
2-W15-17	5/26/88	684.64	214.39	470.25
2-W15-17	6/30/88	684.64	214.42	470.22
2-W15-17	7/28/88	684.64	214.47	470.17

HYDROGRAPH FOR WELLS 2-W15-16 AND 2-W15-17

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W15-18

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W15-18	12/10/87	685.71	214.81	470.90
2-W15-18	1/07/88	685.71	214.46	471.25
2-W15-18	1/14/88	685.71	214.18	471.53
2-W15-18	1/20/88	685.71	214.53	471.18
2-W15-18	1/29/88	685.71	214.24	471.47
2-W15-18	2/04/88	685.71	214.83	470.88
2-W15-18	2/11/88	685.71	214.55	471.16
2-W15-18	2/18/88	685.71	214.87	470.84
2-W15-18	3/09/88	685.71	214.56	471.15
2-W15-18	3/23/88	685.71	214.37	471.34
2-W15-18	5/26/88	685.71	214.55	471.16
2-W15-18	6/30/88	685.71	214.68	471.03
2-W15-18	7/28/88	685.71	214.92	470.79

WATER-LEVEL DATA FOR WELLS 2-W18-21 AND 2-W18-22

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W18-21	12/10/87	668.62	198.54	470.08
2-W18-21	1/07/88	668.62	198.23	470.39
2-W18-21	1/14/88	668.62	197.96	470.66
2-W18-21	1/20/88	668.62	198.33	470.29
2-W18-21	1/29/88	668.62	197.99	470.63
2-W18-21	2/04/88	668.62	198.64	469.98
2-W18-21	2/11/88	668.62	198.34	470.28
2-W18-21	2/18/88	668.62	198.68	469.94
2-W18-21	3/09/88	668.62	198.38	470.24
2-W18-21	3/23/88	668.62	198.16	470.46
2-W18-21	3/31/88	668.62	198.39	470.23
2-W18-21	5/26/88	668.62	198.42	470.20
2-W18-21	6/30/88	668.62	198.55	470.07
2-W18-21	7/28/88	668.62	198.74	469.88

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W18-22	12/10/87	668.49	199.17	469.32
2-W18-22	1/07/88	668.49	199.08	469.41
2-W18-22	1/14/88	668.49	198.83	469.66
2-W18-22	1/20/88	668.49	199.75	468.74
2-W18-22	1/29/88	668.49	198.70	469.79
2-W18-22	2/04/88	668.49	199.45	469.04
2-W18-22	2/11/88	668.49	199.18	469.31
2-W18-22	2/18/88	668.49	199.38	469.11
2-W18-22	3/09/88	668.49	199.12	469.37
2-W18-22	3/23/88	668.49	198.85	469.64
2-W18-22	3/31/88	668.49	199.25	469.24
2-W18-22	5/26/88	668.49	199.22	469.27
2-W18-22	6/30/88	668.49	199.45	469.04
2-W18-22	7/28/88	668.49	199.52	468.97

HYDROGRAPH FOR WELLS 2-W18-21 AND 2-W18-22

WELL NAMES
• 2-W18-21
• 2-W18-22

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W18-23

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W18-23	12/10/87	696.81	226.74	470.07
2-W18-23	1/07/88	696.81	226.46	470.35
2-W18-23	1/14/88	696.81	226.18	470.63
2-W18-23	1/20/88	696.81	226.55	470.26
2-W18-23	1/29/88	696.81	226.19	470.62
2-W18-23	2/04/88	696.81	226.86	469.95
2-W18-23	2/11/88	696.81	226.58	470.23
2-W18-23	2/18/88	696.81	226.89	469.92
2-W18-23	3/09/88	696.81	226.58	470.23
2-W18-23	3/23/88	696.81	226.35	470.46
2-W18-23	3/31/88	696.81	226.59	470.22
2-W18-23	5/26/88	696.81	226.63	470.18
2-W18-23	6/30/88	696.81	226.77	470.04
2-W18-23	7/28/88	696.81	226.94	469.87

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL 2-W18-24

WELL NAME	DATE	CASING ELEVATION	DEPTH TO WATER	COMPUTED HEAD
2-W18-24	12/10/87	684.35	213.14	471.21
2-W18-24	1/07/88	684.35	212.82	471.53
2-W18-24	1/14/88	684.35	212.55	471.80
2-W18-24	1/20/88	684.35	212.87	471.48
2-W18-24	1/29/88	684.35	212.59	471.76
2-W18-24	2/04/88	684.35	213.15	471.20
2-W18-24	2/11/88	684.35	212.89	471.46
2-W18-24	2/18/88	684.35	213.21	471.14
2-W18-24	3/09/88	684.35	212.89	471.46
2-W18-24	3/23/88	684.35	212.72	471.63
2-W18-24	5/26/88	684.35	212.89	471.46
2-W18-24	6/30/88	684.35	213.04	471.31
2-W18-24	7/28/88	684.35	213.28	471.07

WATER-LEVEL DATA AND HYDROGRAPH FOR WELL S-WB-24

WELL NAME	DATE	CASING ELEVATION	WATER TO CORRECTED
S-WB-24	11/26/88	684.38	671.08
S-WB-24	12/03/88	684.38	671.31
S-WB-24	12/10/88	684.38	671.40
S-WB-24	12/17/88	684.38	671.63
S-WB-24	12/24/88	684.38	671.88
S-WB-24	12/31/88	684.38	672.14
S-WB-24	1/07/89	684.38	672.46
S-WB-24	1/14/89	684.38	672.82
S-WB-24	1/21/89	684.38	673.18
S-WB-24	1/28/89	684.38	673.55
S-WB-24	2/04/89	684.38	673.92
S-WB-24	2/11/89	684.38	674.29
S-WB-24	2/18/89	684.38	674.66
S-WB-24	2/25/89	684.38	675.03
S-WB-24	3/04/89	684.38	675.40
S-WB-24	3/11/89	684.38	675.77
S-WB-24	3/18/89	684.38	676.14
S-WB-24	3/25/89	684.38	676.51
S-WB-24	4/01/89	684.38	676.88
S-WB-24	4/08/89	684.38	677.25
S-WB-24	4/15/89	684.38	677.62
S-WB-24	4/22/89	684.38	677.99
S-WB-24	4/29/89	684.38	678.36
S-WB-24	5/06/89	684.38	678.73
S-WB-24	5/13/89	684.38	679.10
S-WB-24	5/20/89	684.38	679.47
S-WB-24	5/27/89	684.38	679.84
S-WB-24	6/03/89	684.38	680.21
S-WB-24	6/10/89	684.38	680.58
S-WB-24	6/17/89	684.38	680.95
S-WB-24	6/24/89	684.38	681.32
S-WB-24	7/01/89	684.38	681.69
S-WB-24	7/08/89	684.38	682.06
S-WB-24	7/15/89	684.38	682.43
S-WB-24	7/22/89	684.38	682.80
S-WB-24	7/29/89	684.38	683.17
S-WB-24	8/05/89	684.38	683.54
S-WB-24	8/12/89	684.38	683.91
S-WB-24	8/19/89	684.38	684.28
S-WB-24	8/26/89	684.38	684.65
S-WB-24	9/02/89	684.38	685.02
S-WB-24	9/09/89	684.38	685.39
S-WB-24	9/16/89	684.38	685.76
S-WB-24	9/23/89	684.38	686.13
S-WB-24	9/30/89	684.38	686.50
S-WB-24	10/07/89	684.38	686.87
S-WB-24	10/14/89	684.38	687.24
S-WB-24	10/21/89	684.38	687.61
S-WB-24	10/28/89	684.38	687.98
S-WB-24	11/04/89	684.38	688.35
S-WB-24	11/11/89	684.38	688.72
S-WB-24	11/18/89	684.38	689.09
S-WB-24	11/25/89	684.38	689.46
S-WB-24	12/02/89	684.38	689.83
S-WB-24	12/09/89	684.38	690.20
S-WB-24	12/16/89	684.38	690.57
S-WB-24	12/23/89	684.38	690.94
S-WB-24	12/30/89	684.38	691.31
S-WB-24	1/06/90	684.38	691.68
S-WB-24	1/13/90	684.38	692.05
S-WB-24	1/20/90	684.38	692.42
S-WB-24	1/27/90	684.38	692.79
S-WB-24	2/03/90	684.38	693.16
S-WB-24	2/10/90	684.38	693.53
S-WB-24	2/17/90	684.38	693.90
S-WB-24	2/24/90	684.38	694.27
S-WB-24	3/02/90	684.38	694.64
S-WB-24	3/09/90	684.38	695.01
S-WB-24	3/16/90	684.38	695.38
S-WB-24	3/23/90	684.38	695.75
S-WB-24	3/30/90	684.38	696.12
S-WB-24	4/06/90	684.38	696.49
S-WB-24	4/13/90	684.38	696.86
S-WB-24	4/20/90	684.38	697.23
S-WB-24	4/27/90	684.38	697.60
S-WB-24	5/04/90	684.38	697.97
S-WB-24	5/11/90	684.38	698.34
S-WB-24	5/18/90	684.38	698.71
S-WB-24	5/25/90	684.38	699.08
S-WB-24	6/01/90	684.38	699.45
S-WB-24	6/08/90	684.38	699.82
S-WB-24	6/15/90	684.38	700.19
S-WB-24	6/22/90	684.38	700.56
S-WB-24	6/29/90	684.38	700.93
S-WB-24	7/06/90	684.38	701.30
S-WB-24	7/13/90	684.38	701.67
S-WB-24	7/20/90	684.38	702.04
S-WB-24	7/27/90	684.38	702.41
S-WB-24	8/03/90	684.38	702.78
S-WB-24	8/10/90	684.38	703.15
S-WB-24	8/17/90	684.38	703.52
S-WB-24	8/24/90	684.38	703.89
S-WB-24	8/31/90	684.38	704.26
S-WB-24	9/07/90	684.38	704.63
S-WB-24	9/14/90	684.38	705.00
S-WB-24	9/21/90	684.38	705.37
S-WB-24	9/28/90	684.38	705.74
S-WB-24	10/05/90	684.38	706.11
S-WB-24	10/12/90	684.38	706.48
S-WB-24	10/19/90	684.38	706.85
S-WB-24	10/26/90	684.38	707.22
S-WB-24	11/02/90	684.38	707.59
S-WB-24	11/09/90	684.38	707.96
S-WB-24	11/16/90	684.38	708.33
S-WB-24	11/23/90	684.38	708.70
S-WB-24	11/30/90	684.38	709.07
S-WB-24	12/07/90	684.38	709.44
S-WB-24	12/14/90	684.38	709.81
S-WB-24	12/21/90	684.38	710.18
S-WB-24	12/28/90	684.38	710.55
S-WB-24	1/04/91	684.38	710.92
S-WB-24	1/11/91	684.38	711.29
S-WB-24	1/18/91	684.38	711.66
S-WB-24	1/25/91	684.38	712.03
S-WB-24	2/01/91	684.38	712.40
S-WB-24	2/08/91	684.38	712.77
S-WB-24	2/15/91	684.38	713.14
S-WB-24	2/22/91	684.38	713.51
S-WB-24	2/29/91	684.38	713.88
S-WB-24	3/06/91	684.38	714.25
S-WB-24	3/13/91	684.38	714.62
S-WB-24	3/20/91	684.38	714.99
S-WB-24	3/27/91	684.38	715.36
S-WB-24	4/03/91	684.38	715.73
S-WB-24	4/10/91	684.38	716.10
S-WB-24	4/17/91	684.38	716.47
S-WB-24	4/24/91	684.38	716.84
S-WB-24	5/01/91	684.38	717.21
S-WB-24	5/08/91	684.38	717.58
S-WB-24	5/15/91	684.38	717.95
S-WB-24	5/22/91	684.38	718.32
S-WB-24	5/29/91	684.38	718.69
S-WB-24	6/05/91	684.38	719.06
S-WB-24	6/12/91	684.38	719.43
S-WB-24	6/19/91	684.38	719.80
S-WB-24	6/26/91	684.38	720.17
S-WB-24	7/03/91	684.38	720.54
S-WB-24	7/10/91	684.38	720.91
S-WB-24	7/17/91	684.38	721.28
S-WB-24	7/24/91	684.38	721.65
S-WB-24	7/31/91	684.38	722.02
S-WB-24	8/07/91	684.38	722.39
S-WB-24	8/14/91	684.38	722.76
S-WB-24	8/21/91	684.38	723.13
S-WB-24	8/28/91	684.38	723.50
S-WB-24	9/04/91	684.38	723.87
S-WB-24	9/11/91	684.38	724.24
S-WB-24	9/18/91	684.38	724.61
S-WB-24	9/25/91	684.38	724.98
S-WB-24	10/02/91	684.38	725.35
S-WB-24	10/09/91	684.38	725.72
S-WB-24	10/16/91	684.38	726.09
S-WB-24	10/23/91	684.38	726.46
S-WB-24	10/30/91	684.38	726.83
S-WB-24	11/06/91	684.38	727.20
S-WB-24	11/13/91	684.38	727.57
S-WB-24	11/20/91	684.38	727.94
S-WB-24	11/27/91	684.38	728.31
S-WB-24	12/04/91	684.38	728.68
S-WB-24	12/11/91	684.38	729.05
S-WB-24	12/18/91	684.38	729.42
S-WB-24	12/25/91	684.38	729.79
S-WB-24	1/01/92	684.38	730.16
S-WB-24	1/08/92	684.38	730.53
S-WB-24	1/15/92	684.38	730.90
S-WB-24	1/22/92	684.38	731.27
S-WB-24	1/29/92	684.38	731.64
S-WB-24	2/05/92	684.38	732.01
S-WB-24	2/12/92	684.38	732.38
S-WB-24	2/19/92	684.38	732.75
S-WB-24	2/26/92	684.38	733.12
S-WB-24	3/05/92	684.38	733.49
S-WB-24	3/12/92	684.38	733.86
S-WB-24	3/19/92	684.38	734.23
S-WB-24	3/26/92	684.38	734.60
S-WB-24	4/02/92	684.38	734.97
S-WB-24	4/09/92	684.38	735.34
S-WB-24	4/16/92	684.38	735.71
S-WB-24	4/23/92	684.38	736.08
S-WB-24	4/30/92	684.38	736.45
S-WB-24	5/07/92	684.38	736.82
S-WB-24	5/14/92	684.38	737.19
S-WB-24	5/21/92	684.38	737.56
S-WB-24	5/28/92	684.38	737.93
S-WB-24	6/04/92	684.38	738.30
S-WB-24	6/11/92	684.38	738.67
S-WB-24	6/18/92	684.38	739.04
S-WB-24	6/25/92	684.38	739.41
S-WB-24	7/02/92	684.38	739.78
S-WB-24	7/09/92	684.38	740.15
S-WB-24	7/16/92	684.38	740.52
S-WB-24	7/23/92	684.38	740.89
S-WB-24	7/30/92	684.38	741.26
S-WB-24	8/06/92	684.38	741.63
S-WB-24	8/13/92	684.38	742.00
S-WB-24	8/20/92	684.38	742.37
S-WB-24	8/27/92	684.38	742.74
S-WB-24	9/03/92	684.38	743.11
S-WB-24	9/10/92	684.38	743.48
S-WB-24	9/17/92	684.38	743.85
S-WB-24	9/24/92	684.38	744.22
S-WB-24	10/01/92	684.38	744.59
S-WB-24	10/08/92	684.38	744.96
S-WB-24	10/15/92	684.38	745.33
S-WB-24	10/22/92	684.38	745.70
S-WB-24	10/29/92	684.38	746.07
S-WB-24	11/05/92	684.38	746.44
S-WB-24	11/12/92	684.38	746.81
S-WB-24	11/19/92	684.38	747.18
S-WB-24	11/26/92	684.38	747.55
S-WB-24	12/03/92	684.38	747.92
S-WB-24	12/10/92	684.38	748.29
S-WB-24	12/17/92	684.38	748.66
S-WB-24	12/24/92	684.38	749.03
S-WB-24	12/31/92	684.38	749.40

APPENDIX I

FIELD MOISTURE CONTENT OF CORE-BARREL SAMPLES
FROM WELLS IN THE 200-EAST
AND 200-WEST AREAS

APPENDIX I

FIELD MOISTURE CONTENT OF CORE-BARREL SAMPLES FROM WELLS IN THE 200-EAST AND 200-WEST AREAS

This appendix presents field moisture content of core-barrel samples collected during the drilling of 24 monitoring wells in the 200-East Area and 200-West Areas.

TABLE I.1. Field Moisture Content of Core-Barrel Samples from Wells in the 200-East Area

<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>	<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>
Well 299-E27-8		Well 299-E28-26 (contd)	
109-110	7.01	214-215	2.16
114-115	6.10	225	2.31
119-120	5.51	230	1.06
124-125	5.84		
129-130	6.13		
136-137	6.01		
139-140	6.59	Well 299-E28-27	
144-145	13.43	4-5	1.16
149-150	11.90	64-65	1.89
154-155	9.20	69-70	2.45
159-160A	6.87	74-75	2.18
159-160B	6.37	99-100	2.40
164-165	7.37	104-105	2.52
169-170	7.57	109-110	2.12
174-175	6.58	114-115	4.23
179-180	6.81	119-120	2.55
184-185	7.55	124-125	2.86
189-190	6.13	129-130	2.65
194-195	8.60	134-135	3.54
		139-140	2.36
		144-145	4.68
		149-150	2.01
Well 299-E28-26		154-155	2.26
84-85	1.47	164-165	1.89
89-90	1.46	169-170	2.09
100	1.80	174-175	2.62
105	1.63	179-180	2.45
109-110	1.51	185	2.55
114-115	2.03	190	2.57
119-120	1.70	194-195	4.18
129-130	3.35	210	3.09
134-135	2.35	214-215A	2.29
139-140	2.19	214-215B	2.53
144-145	1.84	219-220	2.23
149-150	1.98	224-225	2.25
154-155	1.98	239-240	4.05
159-160	1.94	249-250	2.44
164-165	2.14	254-255	1.58
169-170	2.94		
174-175	3.65		
179-180	2.09		
184-185	1.88		
189-190	2.92		
194-195	2.21		
209-210	1.99		

TABLE I.1. (contd)

<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>	<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>
Well 299-E32-2		Well-299-E32-3 (contd)	
59-60	1.98	94-95	2.12
64-65	2.86	99-100	2.45
69-70	3.17	104-105	2.51
74-75	1.70	109-110	2.29
79-80	2.89	115	3.93
84-85	1.94	120	2.44
89-90	1.88	125	2.45
94-95	1.77	129-130	2.54
99-100	1.63	134-135	1.85
104-105	1.60	139-140	1.98
109-110	2.00	150	2.09
114-115	2.03	155	1.93
120	2.09	160	1.89
125	2.19	164-165	1.78
129-130	2.24	169-170	2.44
134-135	2.56	174-175	2.15
139-140	2.36	179-180	2.00
144-145	2.47	180	2.70
149-150	2.61	185	2.49
154-155	1.92	189-190	3.21
159-160	2.03	194-195	2.70
169-170	2.08	200	2.46
164-165	2.06	204-205	2.36
174-175	2.20	210	3.33
179-180	2.83	215	2.84
184-185	2.47	219-220	2.44
194-195	2.59	224-225	2.59
199-200	2.37	229-230	2.43
204-205	2.64	234-235	2.09
209-210	2.53	239-240	2.26
214-215	2.47	244-245	2.88
220	2.54	249-250	2.20
225	2.18	254-255	1.83
230	2.15		
234-235	1.97		
239-240	1.97		
Well 299-E32-3		Well 299-E32-4	
74-75	17.99	64-65	3.61
79-80	3.13	69-70	3.02
84-85	2.47	80	9.06
89-90	2.23	90	3.06
		95	3.96
		100	3.62
		104-105	3.41

TABLE I.1. (contd)

Sample Interval, ft	Moisture Content, wt%	Sample Interval, ft	Moisture Content, wt%
Well 299-E32-4 (contd)		Well 299-E33-29 (contd)	
109-110	4.72	194-195	2.44
114-115	5.03	199-200	3.27
119-120	5.25	202-203	16.06
124-125	5.85	209-210	5.30
130	3.42	210	2.86
135	4.14	214-215	2.78
140	3.40	219-220	2.68
145	2.84	234-235	2.19
149-150	2.77	239-240	2.81
154-155	2.78		
159-160	6.30	Well 299-E33-30	
164-165	4.87	59-60	3.48
169-170	2.77	69-70	1.97
174-175	2.33	64-65	2.27
180	2.69	74-75	2.39
185	7.12	79-80	2.16
190	3.23	84-85	2.28
195	2.59	89-90	2.39
209-210	3.14	95	3.60
214-215	2.54	100	1.55
219-220	2.68	104-105	1.55
224-225	2.22	109-110	1.72
229-230	2.01	115	2.35
		120	3.66
Well 299-E33-29		124-125	2.00
69-70	2.42	129-130	1.91
84-85	2.66	134-135	1.85
89-90	2.05	139-140	2.04
96-97	2.12	144-145	2.08
99-100	2.52	149-150	1.78
114-115	3.54	154-155	1.94
119-120	1.95	159-160 A	1.89
124-125	1.94	159-160 B	2.03
129-130	1.95	174-175	2.10
144-145	2.44	179-180	2.42
150	1.83	184-185	2.43
154-155	2.06	169-170	1.95
159-160	2.04	189-190	2.96
164-165	1.90	194-195	2.49
169-170	2.76	203	16.20
174-175	2.37	204-205	3.86
179-180	2.25	Unmarked	
184-185	2.25	depth	3.78
189-190	2.37	209-210	2.15

TABLE I.1. (contd)

<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>
Well 299-E33-30 (contd)	
214-215	2.79
219-220	2.53
224-250	2.77
234-235	2.28
239-240	2.21
244-245	2.03
249-250	2.33
Well 299-E34-6	
4-5	4.40

A,B = Duplicate samples.

TABLE I.2. Field Moisture Content of Core-Barrel Sample from Wells in the 200-West Area

Sample Interval, ft	Moisture Content, wt%	Sample Interval, ft	Moisture Content, wt%
Well 299-W6-2		Well 299-W7-5 (contd)	
5	2.28	174-175	2.34
10	1.87	179-180	2.15
		189-190	2.12
		194-195	2.45
Well 299-W7-1		199-200	3.38
5-6	2.53	209-210	2.47
10-11	1.98	214-215	2.22
130	1.85	219-220	2.32
135	11.39		
140	1.96	Well 299-W7-6	
142-143	1.31	5	2.92
		10	5.25
Well 299-W7-2			
4-5	7.90	Well 299-W9-1	
		5	3.51
Well 299-W7-3		10	4.13
5	1.94	15	7.22
		20	2.20
Well 299-W7-5		25	2.39
5	6.57	30	2.38
10	2.95	35	3.02
65	2.15	40	2.56
69-70	2.35	45	4.64
75	1.76	50	2.65
80	2.60	55 A	1.79
84-85	1.80	55 B	2.30
89-90	1.94		
94-95	2.13	Well 299-W10-13	
99-100	2.03	5	5.98
104-105	1.80	10	9.91
109-110	3.09	15	5.89
114-115	2.79	20	3.92
119-120	1.62	25	4.17
124-125	2.03	30	4.97
129-130	1.87	36	7.33
144-145	2.07	40	3.94
149-150	2.10	45	3.78
154-155	2.00	50	6.20
		55	4.46

TABLE I.2. (contd)

Sample Interval, ft	Moisture Content, wt%	Sample Interval, ft	Moisture Content, wt%
Well 299-W10-13 (contd)		Well 299-W15-16 (contd)	
60	3.60	85	3.85
65	3.84	89-90	3.80
70	3.21	95	3.51
75	3.64	100	1.88
80	5.46	105	2.26
		110	2.06
Well 299-W10-14		Well 299-W15-18	
4-5	5.92	4-5	8.11
9-10	6.94	10-11	7.04
		15-16	4.40
Well 299-W15-15		20	8.14
10	3.66	25	4.12
15	4.27	30	4.19
20-21	3.38	35	4.28
25	5.94	40	11.00
30	3.12	45.5	8.34
35	5.39	50-51	11.47
40	4.71	54-55	4.38
45	9.84	60	4.67
50	5.73	65	10.57
55	4.30	70	5.80
		75	9.28
Well 299-W15-16		79-80	4.23
4-5	13.87	84-85	18.69
9-10	3.39	89-90	10.97
15	2.85	91-92	10.15
20	5.62	94-95	6.55
25	4.55	99-100	7.10
30	2.92	104-105	3.34
35	6.19	109-110	2.82
40	5.47	124-126	2.75
45	14.88		
50	4.04	Well 299-W18-21	
55	4.59	4-5	4.72
60	4.45	9	14.92
65	10.86	10	4.01
70	6.08	15	3.94
75	3.33	20	3.32
80	3.67	25	6.63
		30	6.47

TABLE 1.2. (contd)

<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>	<u>Sample Interval, ft</u>	<u>Moisture Content, wt%</u>
Well 299-W18-21 (contd)		Well 299-W18-24	
35	4.46	5	5.27
40	11.13	9-10	6.99
42	5.38	14-15	7.93
		17	3.46
		20	3.13
Well 299-W18-23		21-22	5.81
		24-25	3.07
4-5	8.72	30	3.17
9-10	4.23	34-35	6.81
14-15	3.42	38	2.79
19-20	4.99	40-41	2.15
24-25	10.32	75	8.15
29-30	9.17	80	6.87
34-35	4.38	85	4.34
39-40	17.29	90	2.90
44-45	3.79	95	5.37
49-50	7.96	99-100	2.48
54-55	2.87	104-105	3.53
59-60	2.83	109-111	2.49
		112-113	2.54
		114-115	2.97
		119-121	2.77

APPENDIX J

PARTICLE-SIZE AND CALCIUM CARBONATE DATA
FOR 200-EAST AREA WELLS

APPENDIX J

PARTICLE-SIZE AND CALCIUM CARBONATE DATA FOR 200-EAST AREA WELLS

This appendix presents particle-size and calcium carbonate data for borehole samples collected during the drilling of 16 monitoring wells in the 200-East Area.

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 1

**** REPORT ON WELL 8299-E27-008 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	FAN (>4.75)	
6	N/A	H	8.6	43.3	48.1	msG	WT	N/A	176.1	38.3	36.1	38.0	27.6	29.9	N/A	31.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.1	9.3	9.6	9.0	7.6	8.1	N/A	8.6
SPLIT	WT=	372.4					CUM	WT %	N/A	48.1	58.4	66.9	76.0	83.3	91.4	N/A	100.0
10	N/A	H	10.7	40.4	48.8	msG	WT	N/A	448.3	74.0	84.3	74.0	70.3	68.6	N/A	98.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.9	8.1	9.2	8.1	7.7	7.6	N/A	10.7
SPLIT	WT=	919.8					CUM	WT %	N/A	48.9	58.9	66.1	74.2	81.8	89.3	N/A	100.0
15	N/A	H	8.7	43.8	47.4	msG	WT	N/A	488.7	87.7	94.2	99.0	71.3	44.8	N/A	75.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.4	7.9	10.9	11.8	8.3	6.2	N/A	6.8
SPLIT	WT=	886.9					CUM	WT %	N/A	47.4	56.3	66.2	77.8	86.1	91.3	N/A	100.0
20	N/A	H	8.8	39.6	51.8	msG	WT	N/A	490.9	83.7	108.2	89.1	62.7	63.6	N/A	81.3	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	61.8	6.7	11.2	9.4	8.8	6.7	N/A	6.6
SPLIT	WT=	949.2					CUM	WT %	N/A	61.8	88.6	89.8	79.2	86.8	91.4	N/A	100.0
25	N/A	H	8.8	78.4	12.8	(m)gS	WT	N/A	93.4	39.8	289.8	176.4	92.1	63.3	N/A	83.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.8	6.6	28.0	24.2	12.0	7.3	N/A	8.8
SPLIT	WT=	726.2					CUM	WT %	N/A	12.8	18.3	47.1	71.3	83.9	91.2	N/A	100.0
30	N/A	H	6.8	59.1	35.3	msG	WT	N/A	322.6	288.3	158.8	94.6	53.0	33.7	N/A	58.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.3	22.8	16.6	10.3	6.8	3.7	N/A	6.8
SPLIT	WT=	988.8					CUM	WT %	N/A	35.3	58.1	74.8	86.8	90.5	94.4	N/A	100.0
35	N/A	H	8.2	87.8	26.8	gS	WT	N/A	214.3	238.4	139.4	101.1	58.6	28.9	N/A	61.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	28.8	28.8	10.9	12.2	8.8	3.3	N/A	6.2
SPLIT	WT=	826.4					CUM	WT %	N/A	28.8	64.6	71.6	83.7	90.6	93.8	N/A	100.0
40	N/A	H	7.1	88.1	32.8	msG	WT	N/A	297.6	236.2	141.6	81.0	54.8	32.4	N/A	64.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.8	26.9	16.6	8.9	6.8	3.6	N/A	7.1
SPLIT	WT=	904.0					CUM	WT %	N/A	32.8	68.7	74.3	83.3	89.3	92.9	N/A	100.0
45	N/A	H	7.0	84.6	28.8	gS	WT	N/A	239.6	278.8	131.9	88.3	41.8	29.4	N/A	58.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	28.8	33.0	16.7	7.2	5.0	3.6	N/A	7.0
SPLIT	WT=	839.2					CUM	WT %	N/A	28.8	61.8	77.4	84.6	89.5	93.0	N/A	100.0
50	N/A	H	7.2	89.4	23.4	gS	WT	N/A	206.3	267.6	146.8	101.4	61.4	32.4	N/A	63.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	23.4	30.6	18.8	11.8	7.0	3.7	N/A	7.2
SPLIT	WT=	873.8					CUM	WT %	N/A	23.4	63.8	70.6	82.1	89.1	92.8	N/A	100.0
55	N/A	H	6.7	74.6	18.7	gS	WT	N/A	136.9	136.8	147.8	158.8	73.2	33.8	N/A	48.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	18.7	18.6	20.1	21.4	10.8	4.8	N/A	6.7
SPLIT	WT=	727.7					CUM	WT %	N/A	18.7	37.2	67.3	78.7	88.7	93.3	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E27-008 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	H	5.4	65.5	29.1	gS	WT	N/A	144.4	109.8	97.4	66.5	34.3	17.2	N/A	28.9
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.1	22.1	19.6	13.4	8.9	3.8	N/A
SPLIT	WT=	496.5						CUM WT %	N/A	29.1	51.2	70.8	84.2	91.1	94.6	100.0
66	N/A	H	7.1	66.0	32.3	msG	WT	N/A	272.5	155.7	171.8	84.2	58.5	40.2	N/A	59.9
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.3	18.5	28.4	18.0	6.9	4.6	N/A
SPLIT	WT=	846.7						CUM WT %	N/A	32.3	50.8	71.2	81.2	86.1	92.9	100.0
70	N/A	H	5.7	74.6	19.8	gS	WT	N/A	162.5	168.9	208.0	112.1	53.6	31.9	N/A	44.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.9	21.9	27.0	14.5	7.0	4.1	N/A
SPLIT	WT=	777.0						CUM WT %	N/A	19.8	41.7	68.7	83.2	90.2	94.3	100.0
76	N/A	H	7.1	78.2	14.7	gS	WT	N/A	122.7	197.4	218.0	131.3	69.1	35.6	N/A	59.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	14.8	23.7	28.1	16.8	8.3	4.3	N/A
SPLIT	WT=	830.5						CUM WT %	N/A	14.8	38.5	64.5	80.3	88.0	92.9	100.0
80	N/A	H	6.8	77.1	17.3	gS	WT	N/A	146.8	253.0	218.5	93.1	68.7	31.3	N/A	47.8
SDRT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.3	29.8	24.8	11.8	7.8	3.7	N/A
SPLIT	WT=	864.7						CUM WT %	N/A	17.3	47.1	71.9	82.8	90.7	94.4	100.0
86	N/A	H	6.0	70.5	23.5	gS	WT	N/A	205.2	247.9	183.0	98.7	81.9	23.2	N/A	52.0
SDRT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	23.5	28.4	21.0	11.3	7.1	2.7	N/A
SPLIT	WT=	874.7						CUM WT %	N/A	23.5	52.0	73.0	84.3	91.4	94.0	100.0
90	N/A	H	5.7	85.8	8.5	(g)S	WT	N/A	78.4	145.3	279.8	184.6	78.3	29.8	N/A	47.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.5	17.0	33.8	22.9	8.5	3.6	N/A
SPLIT	WT=	828.9						CUM WT %	N/A	8.5	26.1	59.9	82.2	90.7	94.3	100.0
96	N/A	H	4.0	76.3	18.8	gS	WT	N/A	165.0	181.4	240.1	121.1	71.2	32.5	N/A	40.9
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.8	19.5	20.7	14.8	8.6	3.9	N/A
SPLIT	WT=	825.2						CUM WT %	N/A	18.8	38.2	67.9	82.5	91.1	95.1	100.0
100	N/A	H	6.4	89.9	23.7	gS	WT	N/A	194.0	185.2	213.2	98.9	62.4	34.5	N/A	52.1
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	23.7	28.1	28.0	12.0	7.6	4.2	N/A
SPLIT	WT=	810.0						CUM WT %	N/A	23.7	43.9	69.9	81.8	89.4	93.7	100.0
106	N/A	C	5.9	84.3	29.8	gS	WT	N/A	245.8	178.2	174.8	83.4	61.3	33.1	N/A	46.8
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.8	21.0	21.2	10.1	7.4	4.0	N/A
SPLIT	WT=	824.8						CUM WT %	N/A	29.8	51.4	72.5	82.7	90.1	94.1	100.0
110	N/A	C	4.9	74.8	20.5	gS	WT	N/A	137.2	202.8	178.1	63.1	34.2	20.1	N/A	32.4
SDRT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.6	25.3	26.7	9.5	5.1	3.0	N/A
SPLIT	WT=	869.2						CUM WT %	N/A	20.6	50.9	77.6	87.0	92.1	95.1	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0290-E27-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUO	%SAND	%GRAVEL	CLASS		FINE PES (≤-2)	VFINE PES (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.76)	PAN (>4.76)
116	N/A	C	1.7	98.1	10.2	gS	WT	N/A	82.8	208.8	218.8	80.4	33.3	12.7	N/A	10.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.3	34.1	35.7	10.0	5.4	N/A	1.7
SPLIT	WT=	813.6					CUM WT %	N/A	10.3	44.3	80.0	90.0	96.3	98.3	N/A	100.0
120	N/A	C	4.7	98.2	16.1	gS	WT	N/A	108.2	228.7	212.8	69.2	30.3	22.8	N/A	33.6
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	16.1	32.0	29.8	9.7	5.6	N/A	4.7
SPLIT	WT=	716.2					CUM WT %	N/A	16.1	47.2	76.9	86.6	92.1	95.3	N/A	100.0
125	N/A	C	5.1	98.6	14.3	gS	WT	N/A	92.0	180.2	210.3	85.1	43.6	23.9	N/A	33.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	14.3	24.7	32.4	13.1	8.7	N/A	5.1
SPLIT	WT=	650.8					CUM WT %	N/A	14.3	39.0	71.4	84.6	91.2	94.9	N/A	100.0
130	N/A	C	5.4	98.7	13.8	gS	WT	N/A	95.0	191.7	220.0	86.0	44.4	24.6	N/A	37.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.8	26.3	31.9	12.8	6.4	N/A	5.4
SPLIT	WT=	690.0					CUM WT %	N/A	13.8	40.2	72.0	84.6	91.0	94.6	N/A	100.0
135	N/A	C	0.7	95.6	3.0	S	WT	N/A	22.1	104.7	304.1	121.3	21.9	8.3	N/A	4.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	17.9	52.1	20.0	3.6	N/A	0.7
SPLIT	WT=	585.6					CUM WT %	N/A	3.0	21.7	73.9	94.6	98.4	99.3	N/A	100.0
140	N/A	C	4.9	91.2	3.9	S	WT	N/A	24.9	120.1	279.2	108.9	41.6	21.0	N/A	30.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.9	20.2	44.1	16.9	6.6	N/A	4.9
SPLIT	WT=	635.2					CUM WT %	N/A	3.9	24.2	68.3	85.1	91.7	95.1	N/A	100.0
145	N/A	C	1.0	96.2	13.0	gS	WT	N/A	87.2	182.0	270.3	83.5	24.2	10.3	N/A	12.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.0	27.2	40.4	12.5	3.6	N/A	1.0
SPLIT	WT=	671.6					CUM WT %	N/A	13.0	40.2	80.8	93.0	96.7	98.2	N/A	100.0
160	N/A	C	1.0	91.4	16.7	gS	WT	N/A	93.2	143.7	176.6	101.2	24.2	8.2	N/A	10.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	16.7	25.0	31.7	10.1	4.3	N/A	1.0
SPLIT	WT=	500.2					CUM WT %	N/A	16.7	42.5	74.1	92.3	98.6	99.1	N/A	100.0
165	N/A	C	1.4	88.0	11.9	gS	WT	N/A	80.8	113.3	212.6	137.5	20.1	7.0	N/A	0.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.9	19.7	30.9	23.9	4.9	N/A	1.4
SPLIT	WT=	678.1					CUM WT %	N/A	11.9	31.8	60.6	82.4	97.2	98.6	N/A	100.0
180	N/A	C	1.0	77.3	20.0	gS	WT	N/A	122.7	159.0	173.4	92.2	23.2	8.7	N/A	11.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.0	26.9	29.4	15.6	3.9	N/A	1.0
SPLIT	WT=	602.6					CUM WT %	N/A	20.0	47.7	77.1	92.7	98.6	99.1	N/A	100.0
186	N/A	C	1.9	71.6	28.8	gS	WT	N/A	104.3	177.8	179.9	100.6	27.6	10.0	N/A	13.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.6	25.7	26.0	14.5	4.0	N/A	1.0
SPLIT	WT=	995.0					CUM WT %	N/A	20.6	62.2	78.2	92.7	98.7	99.1	N/A	100.0

2.5

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E27-008 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
170	N/A	C	5.0	85.2	29.8	gS	WT	N/A	211.0	171.2	148.7	86.0	37.7	21.9	N/A	35.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.8	24.1	20.7	12.0	5.3	3.1	N/A	5.0
SPLIT	WT=	709.8					CUM	WT %	N/A	29.8	53.9	74.6	86.6	91.9	95.0	N/A	100.0
175	N/A	C	6.7	59.0	33.7	msG	WT	N/A	258.0	159.8	130.9	96.5	48.4	30.8	N/A	51.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	93.7	20.9	17.1	11.3	0.3	4.0	N/A	5.7
SPLIT	WT=	767.2					CUM	WT %	N/A	33.7	54.6	71.7	83.0	89.3	93.3	N/A	100.0
180	N/A	C	3.6	71.5	24.9	gS	WT	N/A	185.1	282.7	143.8	55.9	30.5	17.3	N/A	28.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	25.0	38.1	19.4	7.5	4.1	2.3	N/A	8.8
SPLIT	WT=	742.0					CUM	WT %	N/A	25.0	63.1	82.4	90.0	94.1	98.4	N/A	100.0
185	N/A	C	4.4	70.1	25.5	gS	WT	N/A	166.0	222.1	124.1	58.1	31.2	21.0	N/A	28.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	25.5	34.2	19.1	8.6	4.8	3.4	N/A	4.4
SPLIT	WT=	657.3					CUM	WT %	N/A	25.5	59.7	78.8	87.4	92.2	95.6	N/A	100.0
190	N/A	C	7.4	81.0	10.7	gS	WT	N/A	72.2	113.1	154.5	168.9	74.0	42.8	N/A	50.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.7	18.7	22.9	25.0	11.0	0.3	N/A	7.4
SPLIT	WT=	675.0					CUM	WT %	N/A	10.7	27.4	50.3	75.3	86.2	92.6	N/A	100.0
195	N/A	C	9.4	87.4	3.1	S	WT	N/A	15.7	41.7	130.2	185.0	70.1	32.2	N/A	47.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.1	8.3	25.9	32.9	14.0	0.4	N/A	9.4
SPLIT	WT=	504.4					CUM	WT %	N/A	3.1	11.4	37.4	70.2	84.2	90.6	N/A	100.0
200	N/A	H	12.0	48.4	38.7	msG	WT	N/A	290.0	96.0	78.1	70.6	74.5	38.8	N/A	98.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.7	12.8	10.4	10.2	9.0	5.2	N/A	12.9
SPLIT	WT=	757.4					CUM	WT %	N/A	38.7	51.5	61.9	72.0	82.0	87.1	N/A	100.0
205	N/A	H	12.6	52.0	34.0	msG	WT	N/A	268.1	84.0	96.2	88.3	71.8	62.7	N/A	96.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.0	10.0	12.5	11.7	9.3	0.1	N/A	12.0
SPLIT	WT=	777.9					CUM	WT %	N/A	34.0	45.7	58.2	70.0	79.3	87.4	N/A	100.0
210	N/A	H	8.6	63.4	28.0	(m)gS	WT	N/A	244.0	138.7	134.2	144.1	88.7	51.8	N/A	75.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.0	15.8	15.3	15.5	10.1	5.9	N/A	8.6
SPLIT	WT=	883.4					CUM	WT %	N/A	28.0	43.6	58.9	75.3	86.5	91.4	N/A	100.0
215	N/A	H	8.5	53.8	39.7	msG	WT	N/A	358.3	183.1	149.4	83.4	53.5	35.8	N/A	58.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.7	18.1	15.6	9.3	5.9	4.0	N/A	8.5
SPLIT	WT=	910.8					CUM	WT %	N/A	39.7	57.8	74.4	83.8	89.8	93.5	N/A	100.0
220	N/A	H	8.2	37.2	56.8	msG	WT	N/A	497.5	87.9	92.0	66.0	58.0	31.3	N/A	54.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	56.8	10.0	10.5	7.5	5.7	3.8	N/A	8.2
SPLIT	WT=	878.9					CUM	WT %	N/A	56.8	66.8	77.1	84.6	90.3	93.8	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E27-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE P60 (-2)	VFINE P60 (-1)	VERY COARSE (0)	COARSE (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	N/A	H	11.3	41.6	47.2	msG	WT	N/A	382.0	98.3	70.3	63.2	65.2	41.6	N/A	91.6
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.2	11.9	8.7	7.8	8.1	N/A	11.3
SPLIT	WT=	819.8					CUM	WT %	N/A	47.2	59.0	87.7	76.6	83.0	N/A	100.0
230	N/A	H	6.1	38.2	66.7	msG	WT	N/A	481.0	102.0	80.7	60.6	47.8	34.7	N/A	60.1
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	66.7	12.4	9.8	6.1	4.2	N/A	6.1
SPLIT	WT=	834.1					CUM	WT %	N/A	66.7	66.1	77.9	64.0	89.7	N/A	100.0
235	N/A	H	4.6	18.9	78.6	msG	WT	N/A	617.8	66.3	32.7	24.2	21.3	19.3	N/A	36.7
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	78.6	6.9	4.1	3.0	2.4	N/A	4.6
SPLIT	WT=	889.1					CUM	WT %	N/A	78.6	83.4	87.4	80.4	93.1	N/A	100.0
240	N/A	H	4.8	80.1	15.1	gS	WT	N/A	102.8	104.0	100.2	117.3	46.6	20.1	N/A	32.6
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	16.1	24.2	27.9	17.2	4.1	N/A	4.8
SPLIT	WT=	871.9					CUM	WT %	N/A	16.1	39.3	67.2	64.4	81.1	N/A	100.0
245	N/A	H	4.1	76.6	20.4	gS	WT	N/A	140.9	116.1	160.6	150.6	88.6	40.8	N/A	29.9
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.4	18.1	21.0	20.6	11.6	N/A	4.1
SPLIT	WT=	736.1					CUM	WT %	N/A	20.4	36.6	68.1	78.8	90.4	N/A	100.0
250	N/A	H	4.3	48.3	48.4	gG	WT	N/A	414.7	167.7	93.4	85.9	83.6	40.0	N/A	38.0
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.4	17.7	10.6	9.0	7.1	N/A	4.3
SPLIT	WT=	893.3					CUM	WT %	N/A	48.4	64.1	74.8	84.2	91.3	N/A	100.0
255	N/A	H	4.4	86.2	10.3	gS	WT	N/A	76.6	66.8	98.9	142.5	223.1	112.4	N/A	32.9
SDRT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	10.3	7.6	13.1	19.3	30.2	N/A	4.4
SPLIT	WT=	741.9					CUM	WT %	N/A	10.3	17.9	31.0	60.2	80.4	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAND REPORT

*** REPORT ON WELL 0209-E27-009 ***

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	H	10.3	33.0	56.8	msG	WT	N/A	540.8	88.1	89.0	65.9	67.6	50.3	N/A	99.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.8	8.0	7.2	5.8	5.9	N/A	10.3
SPLIT	WT=	971.0						CUM WT %	N/A	58.8	65.7	72.8	78.0	84.6	N/A	100.0
10	N/A	H	10.0	32.9	56.2	msG	WT	N/A	541.7	76.0	89.4	51.3	60.7	50.6	N/A	104.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.2	7.9	7.2	5.3	6.3	N/A	10.0
SPLIT	WT=	972.5						CUM WT %	N/A	56.2	64.1	71.3	76.6	82.9	N/A	100.0
15	N/A	H	12.8	28.2	59.0	msG	WT	N/A	539.7	70.0	49.7	38.4	47.3	52.4	N/A	117.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.0	7.7	5.3	4.2	5.2	N/A	12.8
SPLIT	WT=	914.9						CUM WT %	N/A	59.0	68.0	72.1	78.3	81.6	N/A	100.0
20	N/A	H	13.6	57.0	29.5	(m)ps	WT	N/A	89.6	38.0	38.2	28.7	42.6	26.0	N/A	41.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.5	12.5	12.6	9.4	14.0	N/A	13.6
SPLIT	WT=	300.1						CUM WT %	N/A	29.5	41.9	54.5	63.9	77.9	N/A	100.0
30	N/A	H	5.0	19.3	75.7	msG	WT	N/A	665.1	80.0	39.0	25.4	27.1	22.2	N/A	44.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	75.7	8.0	4.4	2.0	3.0	N/A	5.0
SPLIT	WT=	905.2						CUM WT %	N/A	75.7	82.4	86.8	89.8	92.0	N/A	100.0
35	N/A	H	5.7	22.8	70.5	msG	WT	N/A	733.0	89.3	52.7	35.2	41.0	38.8	N/A	70.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	70.5	8.7	5.1	3.4	4.0	N/A	6.7
SPLIT	WT=	1039.3						CUM WT %	N/A	70.5	77.1	82.2	85.0	89.6	N/A	100.0
40	N/A	H	8.5	24.0	66.0	msG	WT	N/A	642.5	57.9	63.4	40.9	42.9	41.9	N/A	82.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.0	8.0	5.0	4.3	4.5	N/A	8.5
SPLIT	WT=	964.7						CUM WT %	N/A	60.0	72.8	78.4	82.0	87.1	N/A	100.0
45	N/A	H	5.0	45.5	45.6	msG	WT	N/A	384.4	124.0	62.7	68.7	60.5	68.5	N/A	76.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.0	14.0	7.4	6.2	7.2	N/A	8.0
SPLIT	WT=	841.0						CUM WT %	N/A	45.0	60.4	67.9	78.0	83.2	N/A	100.0
50	N/A	H	7.8	51.6	40.7	msG	WT	N/A	355.2	200.0	87.1	78.5	51.3	32.0	N/A	67.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.7	22.0	10.0	9.0	5.9	N/A	7.8
SPLIT	WT=	871.9						CUM WT %	N/A	40.7	63.7	73.6	82.0	88.5	N/A	100.0
55	N/A	H	5.8	54.0	39.0	msG	WT	N/A	337.5	213.4	121.1	60.1	43.9	29.9	N/A	49.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.7	25.1	14.2	6.0	5.2	N/A	5.8
SPLIT	WT=	851.8						CUM WT %	N/A	39.7	64.7	79.0	85.6	90.7	N/A	100.0
60	N/A	H	5.8	44.3	50.0	msG	WT	N/A	375.4	136.1	85.4	48.5	36.0	28.0	N/A	43.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	18.0	11.4	6.5	4.9	N/A	5.8
SPLIT	WT=	755.1						CUM WT %	N/A	50.0	88.0	79.3	85.8	90.7	N/A	100.0

6.9

ROCKWELL MANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E27-009 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
65	N/A	H	5.8	39.8	55.2	msG	WT	N/A	489.7	165.7	87.8	36.4	27.6	N/A	49.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.2	19.6	8.0	4.3	4.1	3.2
SPLIT	WT=	850.7						CUM WT %	N/A	55.2	74.7	82.8	88.9	91.8	94.2
70	N/A	H	7.4	52.8	39.8	msG	WT	N/A	337.8	190.8	117.4	81.4	44.4	33.7	N/A
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.8	22.6	13.8	7.2	5.2	4.0
SPLIT	WT=	843.9						CUM WT %	N/A	39.8	82.3	78.1	83.4	88.8	92.6
75	N/A	H	8.8	58.8	34.4	msG	WT	N/A	299.3	188.3	153.1	75.8	51.7	33.5	N/A
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.4	22.8	17.6	8.7	5.9	3.9
SPLIT	WT=	874.1						CUM WT %	N/A	34.4	57.1	74.7	83.4	89.4	93.2
80	N/A	H	8.9	77.7	13.3	(m)gS	WT	N/A	118.7	240.8	222.6	103.8	78.0	46.7	N/A
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	13.4	27.0	25.0	11.7	8.8	5.3
SPLIT	WT=	886.5						CUM WT %	N/A	13.4	40.3	65.4	77.0	85.8	91.1
85	N/A	H	5.8	70.8	23.8	gS	WT	N/A	211.9	208.7	195.8	78.8	60.8	32.2	N/A
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	23.8	30.0	21.8	8.8	5.7	3.8
SPLIT	WT=	897.8						CUM WT %	N/A	23.8	53.8	75.4	84.2	90.9	94.4
91	N/A	H	8.4	56.8	37.8	msG	WT	N/A	329.9	192.8	120.9	81.8	58.5	31.3	N/A
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.8	22.0	14.8	9.3	6.4	3.8
SPLIT	WT=	877.8						CUM WT %	N/A	37.8	59.5	74.3	83.6	90.1	93.8
96	N/A	H	7.1	47.7	45.1	msG	WT	N/A	398.2	123.5	117.3	80.1	58.8	34.4	N/A
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	14.0	13.3	10.8	8.8	3.9
SPLIT	WT=	881.8						CUM WT %	N/A	45.1	59.1	72.4	82.4	89.8	92.8
100	N/A	H	9.8	88.7	22.3	(m)gS	WT	N/A	193.2	78.4	150.1	189.8	127.3	51.8	N/A
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.3	8.8	17.3	21.9	14.7	8.8
SPLIT	WT=	867.8						CUM WT %	N/A	22.3	31.1	48.5	70.4	85.1	91.8
105	N/A	H	7.5	81.8	10.9	gS	WT	N/A	93.8	41.1	157.2	244.4	129.9	52.8	N/A
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.9	5.4	28.5	31.9	17.8	8.8
SPLIT	WT=	788.5						CUM WT %	N/A	10.9	16.3	38.6	68.7	85.7	92.5
110	N/A	H	3.1	95.8	1.9	S	WT	N/A	14.8	55.7	278.1	283.4	103.4	29.3	N/A
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.9	7.1	34.8	36.3	13.2	3.8
SPLIT	WT=	782.1						CUM WT %	N/A	1.9	9.0	43.8	79.9	93.2	98.8
115	N/A	H	5.2	93.8	0.9	S	WT	N/A	8.9	25.8	186.2	297.7	141.1	40.6	N/A
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	3.4	25.3	40.4	19.2	5.5
SPLIT	WT=	739.1						CUM WT %	N/A	0.9	4.3	29.6	70.1	89.3	94.8

J.10

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0200-E27-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
120	N/A	H	4.6	85.5	9.9	(g)S	WT	N/A	80.2	194.8	214.5	157.0	88.1	38.2	N/A	37.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.9	24.1	26.0	19.4	18.9	4.5	N/A	4.8
SPLIT	WT=	908.2					CUM WT %	N/A	9.9	34.0	60.0	80.0	90.9	95.4	N/A	100.0	
125	N/A	H	3.0	81.4	15.0	gS	WT	N/A	114.8	277.7	193.2	74.0	37.3	18.4	N/A	21.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	15.0	37.0	26.3	10.1	5.1	2.2	N/A	3.0
SPLIT	WT=	732.4					CUM WT %	N/A	15.0	53.4	79.7	89.8	94.8	97.1	N/A	100.0	
130	N/A	H	4.3	77.9	17.8	gS	WT	N/A	147.9	274.0	247.0	70.4	34.0	20.1	N/A	35.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.0	33.1	29.8	8.5	4.1	2.4	N/A	4.3
SPLIT	WT=	829.8					CUM WT %	N/A	17.0	60.9	80.8	89.2	93.3	95.7	N/A	100.0	
135	N/A	H	0.2	80.2	5.6	(g)S	WT	N/A	40.3	143.9	242.0	120.0	67.0	37.1	N/A	50.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.6	20.0	33.0	18.0	8.3	5.2	N/A	0.2
SPLIT	WT=	718.3					CUM WT %	N/A	5.6	25.8	59.4	77.4	86.7	91.8	N/A	100.0	
140	N/A	H	5.9	90.4	3.0	S	WT	N/A	20.2	98.0	274.0	189.9	73.3	30.1	N/A	42.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	13.7	38.1	23.5	10.2	5.0	N/A	5.9
SPLIT	WT=	728.7					CUM WT %	N/A	3.0	17.3	55.4	78.9	89.1	94.1	N/A	100.0	
145	N/A	H	7.3	89.3	3.4	S	WT	N/A	21.0	90.1	208.6	168.0	80.2	35.0	N/A	47.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.4	15.2	32.1	20.2	10.3	5.0	N/A	7.3
SPLIT	WT=	844.8					CUM WT %	N/A	3.4	18.0	50.7	78.0	87.1	92.7	N/A	100.0	
150	N/A	H	4.2	89.0	6.0	(g)S	WT	N/A	54.0	147.0	278.3	180.1	64.4	20.2	N/A	32.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.9	10.0	35.4	22.9	8.2	3.7	N/A	4.2
SPLIT	WT=	790.7					CUM WT %	N/A	8.9	25.7	61.0	83.9	92.1	95.0	N/A	100.0	
155	N/A	H	0.4	91.0	1.0	S	WT	N/A	12.7	64.1	231.5	234.0	85.0	37.1	N/A	45.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	9.0	32.0	33.0	12.0	5.2	N/A	0.4
SPLIT	WT=	714.3					CUM WT %	N/A	1.0	10.8	43.4	76.4	88.3	93.6	N/A	100.0	
160	N/A	H	6.8	76.2	19.0	gS	WT	N/A	148.0	170.0	197.9	128.3	82.9	31.0	N/A	46.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.0	21.0	26.3	16.1	8.0	4.0	N/A	6.8
SPLIT	WT=	778.5					CUM WT %	N/A	19.0	40.0	60.1	82.2	90.2	94.2	N/A	100.0	
165	N/A	H	5.0	61.0	42.0	gG	WT	N/A	390.0	210.2	130.1	50.0	33.0	24.0	N/A	51.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	24.0	14.0	8.2	3.7	2.7	N/A	5.0
SPLIT	WT=	907.0					CUM WT %	N/A	42.0	66.9	81.8	88.0	91.7	94.4	N/A	100.0	
170	N/A	H	8.1	63.4	30.5	gG	WT	N/A	267.0	210.3	157.3	70.0	55.4	24.5	N/A	52.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.5	26.9	18.0	9.4	6.0	2.9	N/A	8.2
SPLIT	WT=	842.0					CUM WT %	N/A	30.5	60.4	75.0	84.4	91.0	93.9	N/A	100.0	

7.11

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL #299-E27-809 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
175	N/A	H	8.1	79.8	12.8	gS	WT	N/A	101.1	229.6	242.3	118.9	69.9	19.7	N/A	68.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.0	27.3	28.9	14.2	7.1	2.4	N/A
SPLIT	WT= 837.3							CUM WT %	N/A	12.0	39.4	68.2	82.4	89.5	91.9	100.0
180	N/A	H	5.1	84.8	10.0	gS	WT	N/A	78.3	229.5	245.8	111.7	61.5	30.8	N/A	48.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.0	28.6	31.5	14.3	6.6	3.9	N/A
SPLIT	WT= 779.2							CUM WT %	N/A	10.0	38.6	70.1	84.4	91.0	94.9	100.0
185	N/A	H	7.1	85.2	27.7	gS	WT	N/A	240.9	240.4	166.8	78.4	58.3	28.4	N/A	81.8
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	27.7	28.3	19.2	9.0	5.8	3.0	N/A
SPLIT	WT= 868.6							CUM WT %	N/A	27.7	56.0	75.1	84.1	89.9	92.9	100.0
190	N/A	H	8.2	80.0	11.8	gS	WT	N/A	94.1	168.4	216.1	134.6	81.1	44.5	N/A	65.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.8	20.2	27.1	16.9	10.2	5.8	N/A
SPLIT	WT= 795.1							CUM WT %	N/A	11.8	32.0	59.1	78.0	86.2	91.0	100.0
195	N/A	H	11.8	87.2	21.2	(m)gS	WT	N/A	188.1	194.8	171.6	115.5	87.1	20.4	N/A	101.5
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.2	22.1	19.0	13.2	9.9	2.3	N/A
SPLIT	WT= 878.1							CUM WT %	N/A	21.2	43.4	63.0	78.1	88.1	88.4	100.0
200	N/A	H	9.3	73.4	17.3	(m)gS	WT	N/A	129.8	172.2	176.8	97.8	62.5	40.0	N/A	89.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	17.3	23.1	23.6	13.1	8.4	5.4	N/A
SPLIT	WT= 745.8							CUM WT %	N/A	17.3	40.3	63.0	76.9	85.3	90.7	100.0
205	N/A	H	7.5	84.1	26.5	(m)gS	WT	N/A	268.7	271.3	150.3	88.5	58.8	25.9	N/A	85.8
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	28.5	30.8	17.1	7.8	5.7	2.9	N/A
SPLIT	WT= 888.8							CUM WT %	N/A	28.5	59.3	78.4	83.9	89.8	92.5	100.0
210	N/A	H	8.8	78.6	12.7	(m)gS	WT	N/A	183.0	168.7	213.8	128.9	77.6	48.5	N/A	71.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.7	22.9	28.3	14.8	9.5	5.0	N/A
SPLIT	WT= 812.3							CUM WT %	N/A	12.7	35.7	61.9	76.7	88.3	91.2	100.0
215	N/A	H	8.2	78.4	15.4	gS	WT	N/A	122.7	195.8	190.8	115.1	68.8	37.7	N/A	85.4
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	15.4	24.6	24.0	14.5	8.8	4.7	N/A
SPLIT	WT= 789.7							CUM WT %	N/A	15.4	40.0	64.0	78.4	87.0	91.8	100.0
220	N/A	H	9.8	73.1	17.9	(m)gS	WT	N/A	138.3	194.4	188.6	86.1	57.3	38.7	N/A	88.4
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.9	25.6	23.7	11.2	7.5	5.1	N/A
SPLIT	WT= 758.5							CUM WT %	N/A	17.9	43.5	67.2	78.4	85.9	91.0	100.0
225	N/A	H	8.0	64.4	29.5	gS	WT	N/A	249.1	208.9	170.3	81.8	48.9	35.6	N/A	50.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.5	24.5	20.2	9.7	5.8	4.2	N/A
SPLIT	WT= 835.6							CUM WT %	N/A	28.5	54.1	74.3	84.0	89.8	94.0	100.0

0.12

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E27-000 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
230	N/A	H	16.3	81.2	22.6	gms	WT	N/A	180.2	122.7	135.8	112.8	99.8	18.8	N/A	129.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.6	16.4	17.0	14.1	12.4	2.4	N/A	18.3
SPLIT	WT=	799.1						CUM WT %	N/A	22.6	37.9	64.8	89.0	81.4	83.7	N/A	100.0
236	N/A	H	7.9	64.6	27.6	(m)gS	WT	N/A	244.1	127.7	190.2	118.5	81.8	65.8	N/A	70.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.8	14.4	21.5	13.2	9.2	6.3	N/A	7.9
SPLIT	WT=	860.0						CUM WT %	N/A	27.8	42.8	63.4	76.6	85.8	92.1	N/A	100.0
240	N/A	H	8.2	49.7	44.1	msG	WT	N/A	360.3	127.3	142.3	81.1	43.3	21.9	N/A	62.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.1	15.2	17.0	9.7	5.2	2.8	N/A	6.2
SPLIT	WT=	833.7						CUM WT %	N/A	44.1	59.3	76.3	86.0	91.1	93.8	N/A	100.0
246	N/A	H	8.3	60.0	42.9	msG	WT	N/A	333.5	203.2	127.2	42.7	21.2	0.0	N/A	48.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.9	28.1	18.4	6.6	2.7	0.0	N/A	6.3
SPLIT	WT=	781.8						CUM WT %	N/A	42.9	69.0	85.4	91.0	93.8	93.8	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E27-010 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	H	7.4	30.6	62.0	msG	WT	N/A	508.9	30.9	81.6	21.6	31.7	104.4	N/A	80.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	62.0	3.8	7.6	2.8	3.9	N/A	7.6
SPLIT	WT=	813.6						CUM WT %	N/A	62.0	66.8	73.3	76.9	79.8	N/A	100.0
15	N/A	H	10.3	44.6	45.0	msG	WT	N/A	437.8	84.2	73.2	98.2	113.4	64.8	N/A	100.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.0	8.7	7.6	10.1	11.7	N/A	10.3
SPLIT	WT=	971.2						CUM WT %	N/A	46.0	53.7	61.2	71.3	83.0	N/A	100.0
20	N/A	H	10.5	38.4	53.1	msG	WT	N/A	528.9	90.2	86.4	72.8	74.4	58.4	N/A	105.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.1	9.1	6.7	7.3	6.9	N/A	10.6
SPLIT	WT=	993.9						CUM WT %	N/A	53.1	62.2	68.8	76.1	83.6	N/A	100.0
25	N/A	H	6.4	21.1	72.5	msG	WT	N/A	742.8	57.2	43.9	33.8	43.3	38.1	N/A	65.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	72.5	6.8	4.3	3.3	4.2	N/A	6.4
SPLIT	WT=	1030.0						CUM WT %	N/A	72.5	78.1	82.4	86.7	89.9	N/A	100.0
30	N/A	H	12.9	40.4	48.7	msG	WT	N/A	433.3	85.6	72.8	78.1	79.4	61.5	N/A	119.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.7	9.2	7.8	8.2	8.6	N/A	12.9
SPLIT	WT=	927.5						CUM WT %	N/A	48.7	55.9	63.7	71.9	80.6	N/A	100.0
35	N/A	H	12.8	36.7	50.5	msG	WT	N/A	428.5	71.6	58.4	80.4	61.7	59.2	N/A	108.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.5	8.4	6.9	7.1	7.0	N/A	12.8
SPLIT	WT=	844.9						CUM WT %	N/A	50.5	58.9	65.8	72.9	80.2	N/A	100.0
40	N/A	H	9.8	23.9	66.8	msG	WT	N/A	684.8	53.0	50.5	42.0	52.1	47.8	N/A	98.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	66.8	5.2	4.9	4.1	5.1	N/A	9.8
SPLIT	WT=	1027.2						CUM WT %	N/A	66.8	71.7	76.6	80.7	85.8	N/A	100.0
45	N/A	H	9.9	42.0	48.1	msG	WT	N/A	484.3	92.6	107.7	87.7	58.8	59.0	N/A	95.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.1	9.6	11.2	9.1	6.1	N/A	9.9
SPLIT	WT=	972.2						CUM WT %	N/A	40.1	57.7	60.8	77.9	84.0	N/A	100.0
50	N/A	H	5.0	75.1	19.8	gS	WT	N/A	184.4	127.9	279.4	128.4	52.0	36.2	N/A	41.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.8	15.4	33.7	15.6	6.3	N/A	5.0
SPLIT	WT=	828.1						CUM WT %	N/A	19.8	35.3	69.0	84.6	90.7	N/A	100.0
55	N/A	H	6.7	49.8	43.5	msG	WT	N/A	382.3	172.4	107.1	74.3	47.3	36.2	N/A	59.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.5	19.8	12.2	8.6	5.4	N/A	6.7
SPLIT	WT=	078.3						CUM WT %	N/A	43.5	63.1	75.3	83.8	89.2	N/A	100.0
60	N/A	H	5.2	34.3	60.4	msG	WT	N/A	603.0	125.0	85.3	58.4	48.0	27.6	N/A	52.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.5	12.5	8.8	5.9	4.6	N/A	5.2
SPLIT	WT=	1003.9						CUM WT %	N/A	60.5	73.0	81.6	87.4	92.0	N/A	100.0

J.15

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 2

**** REPORT ON WELL 0209-E27-010 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (<= -2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
85	N/A	H	8.0	35.1	56.9	msG	WT	N/A	520.0	111.4	75.6	54.8	44.7	33.8	N/A	72.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	57.0	12.2	8.3	8.0	4.9	3.7	N/A
SPLIT	WT=	911.7						CUM WT %	N/A	57.0	69.2	77.4	83.4	88.3	92.0	N/A
70	N/A	H	6.7	37.8	53.4	msG	WT	N/A	503.2	99.2	80.8	88.0	53.0	46.9	N/A	81.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.4	10.6	9.6	7.2	5.6	4.9	N/A
SPLIT	WT=	947.3						CUM WT %	N/A	53.4	64.0	73.6	80.8	86.5	91.3	N/A
75	N/A	H	10.0	38.8	51.2	msG	WT	N/A	410.4	107.7	60.3	48.8	48.9	38.3	N/A	80.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.2	13.4	8.8	6.1	5.9	4.8	N/A
SPLIT	WT=	799.2						CUM WT %	N/A	51.2	64.8	73.3	79.3	85.2	90.0	N/A
80	N/A	H	11.1	42.8	46.0	msG	WT	N/A	452.3	122.7	103.1	78.3	72.4	44.7	N/A	109.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.0	12.6	10.5	8.0	7.4	4.8	N/A
SPLIT	WT=	988.8						CUM WT %	N/A	46.0	58.6	69.0	76.9	84.3	88.9	N/A
85	N/A	H	11.0	33.4	55.0	msG	WT	N/A	514.3	98.2	67.2	47.9	60.0	37.0	N/A	100.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.0	10.5	7.2	6.1	6.6	4.0	N/A
SPLIT	WT=	933.9						CUM WT %	N/A	55.0	65.6	72.7	77.9	84.4	88.4	N/A
90	N/A	H	9.7	42.8	47.5	msG	WT	N/A	460.8	112.5	88.8	85.0	83.1	49.3	N/A	93.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.5	11.7	8.4	8.9	8.8	5.1	N/A
SPLIT	WT=	981.5						CUM WT %	N/A	47.5	69.2	87.6	78.6	85.2	90.3	N/A
95	N/A	H	12.2	40.4	47.4	msG	WT	N/A	452.1	110.4	70.8	71.8	65.0	59.5	N/A	118.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.4	11.8	8.3	7.6	8.8	6.2	N/A
SPLIT	WT=	953.5						CUM WT %	N/A	47.4	58.9	67.3	74.8	81.6	87.8	N/A
100	N/A	H	12.8	42.1	45.1	msG	WT	N/A	358.9	90.9	70.7	61.5	56.0	55.0	N/A	101.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	11.4	8.9	7.7	7.1	6.9	N/A
SPLIT	WT=	800.8						CUM WT %	N/A	45.1	60.6	65.4	73.2	80.3	87.2	N/A
105	N/A	H	7.9	24.3	66.0	msG	WT	N/A	679.5	69.3	55.8	38.7	40.8	38.6	N/A	77.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.0	6.9	5.8	3.9	4.1	3.9	N/A
SPLIT	WT=	1004.0						CUM WT %	N/A	60.0	74.9	80.6	84.3	88.4	92.3	N/A
110	N/A	H	6.3	24.3	70.4	msG	WT	N/A	700.5	87.2	55.7	37.8	33.7	27.1	N/A	52.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	70.4	8.8	5.8	3.8	3.4	2.7	N/A
SPLIT	WT=	1000.1						CUM WT %	N/A	70.4	79.2	84.8	88.8	92.0	94.7	N/A
115	N/A	H	11.2	50.2	38.6	msG	WT	N/A	338.3	111.0	122.6	84.1	82.0	55.7	N/A	97.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.0	12.9	14.1	9.7	7.1	6.4	N/A
SPLIT	WT=	868.5						CUM WT %	N/A	38.0	51.5	65.8	75.3	82.4	88.8	N/A

7.16

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E27-010 ****

02/02/89

DEPTH	%C&B3	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE P&B (≤-2)	VFINE P&B (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	N/A	H	8.8	29.8	63.6	msG	WT	N/A	568.6	91.3	82.6	39.0	39.0	28.5	N/A	57.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.6	18.4	7.2	4.6	3.3	N/A	8.6
SPLIT	WT=	873.6						CUM WT %	N/A	63.6	74.0	81.1	86.7	90.1	N/A	100.0
125	N/A	H	6.2	81.3	12.6	gS	WT	N/A	90.8	114.2	210.6	152.3	72.3	37.8	N/A	44.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.6	15.8	29.1	21.1	10.0	N/A	6.2
SPLIT	WT=	726.1						CUM WT %	N/A	12.6	28.4	57.5	78.6	88.6	N/A	100.0
130	N/A	H	5.7	83.6	10.7	gS	WT	N/A	87.8	153.2	286.1	131.3	79.7	38.4	N/A	46.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.7	19.0	34.8	16.0	9.7	N/A	5.7
SPLIT	WT=	828.6						CUM WT %	N/A	10.7	29.3	64.0	80.0	89.7	N/A	100.0
135	N/A	H	5.2	78.8	24.3	gS	WT	N/A	198.6	160.9	261.8	99.8	48.3	27.0	N/A	42.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	24.3	18.4	30.8	12.2	5.9	N/A	5.2
SPLIT	WT=	816.9						CUM WT %	N/A	24.3	42.7	73.5	85.6	91.6	N/A	100.0
140	N/A	H	4.6	79.8	15.8	gS	WT	N/A	189.8	125.6	254.0	105.9	43.1	24.8	N/A	32.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	15.8	18.1	36.5	15.2	6.2	N/A	4.6
SPLIT	WT=	889.7						CUM WT %	N/A	15.8	33.8	70.4	85.6	91.8	N/A	100.0
145	N/A	H	6.6	25.3	68.2	msG	WT	N/A	684.3	88.9	60.2	47.6	38.3	31.8	N/A	63.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.2	7.1	6.2	4.9	3.9	N/A	8.6
SPLIT	WT=	970.9						CUM WT %	N/A	60.2	76.2	81.4	88.3	90.2	N/A	100.0
150	N/A	H	8.3	42.1	49.6	msG	WT	N/A	418.9	95.2	95.6	69.3	60.7	35.2	N/A	78.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.6	11.3	11.3	8.2	7.2	N/A	8.4
SPLIT	WT=	842.1						CUM WT %	N/A	49.6	60.8	72.1	80.3	87.6	N/A	100.0
155	N/A	H	10.3	62.6	37.2	msG	WT	N/A	311.7	107.8	123.3	68.0	69.4	52.8	N/A	88.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.2	12.9	14.7	10.4	8.3	N/A	10.3
SPLIT	WT=	844.9						CUM WT %	N/A	37.2	60.1	64.9	76.2	83.6	N/A	100.0
160	N/A	H	6.7	71.4	21.9	gS	WT	N/A	169.6	185.2	211.8	78.5	50.9	28.3	N/A	51.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	21.9	23.0	27.4	18.1	5.8	N/A	6.7
SPLIT	WT=	778.6						CUM WT %	N/A	21.9	45.8	73.2	83.3	89.9	N/A	100.0
165	N/A	H	6.8	73.8	19.6	gS	WT	N/A	154.7	147.3	222.8	113.7	65.7	31.9	N/A	51.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.6	18.7	28.3	14.4	8.3	N/A	6.8
SPLIT	WT=	784.8						CUM WT %	N/A	19.6	38.3	66.6	81.1	89.4	N/A	100.0
170	N/A	H	6.8	79.8	13.4	gS	WT	N/A	98.0	77.8	163.5	187.3	93.3	42.1	N/A	49.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.4	18.6	25.1	25.6	12.8	N/A	6.8
SPLIT	WT=	738.9						CUM WT %	N/A	13.4	24.0	49.1	74.7	87.6	N/A	100.0

3.17

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E27-010 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
175	N/A	H	9.8	58.1	32.8	msG	WT	N/A	219.5	107.3	104.2	88.8	58.2	38.7	N/A	84.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.4	15.8	16.4	12.8	8.8	5.7	N/A	9.6
SPLIT	WT=	883.0						CUM WT %	N/A	32.4	48.2	63.5	76.2	84.7	90.4	N/A	100.0
180	N/A	H	11.4	58.2	32.4	msG	WT	N/A	219.8	106.8	98.2	78.8	54.6	47.3	N/A	76.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.4	15.8	14.2	11.3	8.1	7.0	N/A	11.4
SPLIT	WT=	673.9						CUM WT %	N/A	32.4	48.1	62.3	73.8	81.7	88.6	N/A	100.0
185	N/A	H	7.3	68.1	24.8	gS	WT	N/A	193.8	103.1	171.4	125.0	83.4	53.3	N/A	67.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.8	13.1	21.8	18.9	10.8	8.8	N/A	7.3
SPLIT	WT=	792.5						CUM WT %	N/A	24.8	37.7	69.6	76.3	85.9	92.7	N/A	100.0
190	N/A	H	11.8	48.0	42.6	msG	WT	N/A	328.4	98.2	81.8	75.1	68.5	58.6	N/A	85.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.6	11.7	10.6	9.7	7.8	6.5	N/A	11.6
SPLIT	WT=	769.8						CUM WT %	N/A	42.6	54.1	64.6	74.3	81.9	88.4	N/A	100.0
195	N/A	H	9.1	64.8	26.1	(m)gS	WT	N/A	234.8	134.8	179.8	141.0	84.1	43.1	N/A	82.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.1	15.0	20.0	15.7	9.4	4.8	N/A	9.1
SPLIT	WT=	895.8						CUM WT %	N/A	28.1	41.1	61.1	70.8	88.1	98.9	N/A	100.0
200	N/A	H	5.8	85.3	29.7	gS	WT	N/A	255.8	183.2	184.1	114.1	62.3	27.9	N/A	43.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.7	21.3	21.4	13.3	8.1	3.3	N/A	5.8
SPLIT	WT=	864.8						CUM WT %	N/A	29.7	51.0	72.4	85.7	91.7	96.0	N/A	100.0
205	N/A	H	8.9	90.1	3.8	S	WT	N/A	21.7	35.8	133.0	318.1	125.2	37.9	N/A	48.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.0	5.0	18.4	44.1	17.4	5.8	N/A	6.9
SPLIT	WT=	718.4						CUM WT %	N/A	3.0	8.0	26.4	70.6	87.9	93.1	N/A	100.0
210	N/A	H	7.3	81.0	1.7	S	WT	N/A	12.8	28.3	128.1	320.2	152.0	49.0	N/A	62.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.7	3.7	17.8	41.6	21.2	6.8	N/A	7.3
SPLIT	WT=	714.7						CUM WT %	N/A	1.7	5.3	22.9	64.7	85.9	92.7	N/A	100.0
215	N/A	H	8.0	52.6	41.6	msG	WT	N/A	373.8	63.3	88.5	175.4	128.9	47.6	N/A	53.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.8	6.9	7.4	19.5	14.3	5.3	N/A	6.0
SPLIT	WT=	898.5						CUM WT %	N/A	41.8	47.5	54.9	74.4	88.8	94.1	N/A	100.0
220	N/A	H	6.8	35.1	58.2	msG	WT	N/A	488.5	123.8	48.2	44.2	43.6	35.8	N/A	55.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.2	14.7	6.7	5.3	5.2	4.2	N/A	6.6
SPLIT	WT=	837.6						CUM WT %	N/A	68.2	73.0	78.7	84.0	89.1	93.4	N/A	100.0
225	N/A	H	8.2	30.8	55.8	msG	WT	N/A	425.8	125.8	87.0	40.8	47.5	32.5	N/A	72.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.8	14.2	7.5	6.3	5.4	3.7	N/A	8.2
SPLIT	WT=	888.2						CUM WT %	N/A	55.8	70.0	77.6	82.8	88.1	91.8	N/A	100.0

7.18

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0299-E27-010 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
230	N/A	H	5.9	93.3	0.8	S	WT	N/A	5.7	100.1	358.2	142.0	43.0	22.0	N/A	42.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.0	15.0	49.6	19.7	0.0	3.1	N/A	5.9
SPLIT	WT=	719.0					CUM	WT %	N/A	0.6	15.0	85.3	85.0	90.9	94.1	N/A	100.0
235	N/A	H	0.0	31.9	66.1	SG	WT	N/A	552.5	140.0	85.0	21.1	4.7	1.2	N/A	0.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	86.1	18.0	10.8	2.0	0.0	0.2	N/A	0.0
SPLIT	WT=	810.8					CUM	WT %	N/A	60.1	86.1	98.7	99.3	99.9	100.0	N/A	100.0
240	N/A	H	0.0	7.0	92.2	G	WT	N/A	770.5	30.0	22.3	0.5	2.0	0.0	N/A	0.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	92.2	3.0	2.7	1.1	0.4	0.1	N/A	0.0
SPLIT	WT=	834.1					CUM	WT %	N/A	92.2	95.0	98.4	99.0	99.9	100.0	N/A	100.0

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-E28-028 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	N/	10.7	37.2	52.1	msG	WT	N/A	390.4	82.4	82.4	56.2	46.9	50.9	N/A	80.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.1	8.3	8.3	7.6	8.3	6.8	N/A
SPLIT	WT=	756.3						CUM WT %	N/A	52.1	80.4	88.8	76.3	82.6	89.3	N/A
10	N/A	H	5.6	60.5	33.9	sG	WT	N/A	258.7	149.5	158.6	90.4	48.0	29.0	N/A	43.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.9	19.0	20.2	13.6	8.1	3.7	N/A
SPLIT	WT=	785.7						CUM WT %	N/A	33.9	53.0	73.1	84.6	90.8	94.4	N/A
15	N/A	H	6.9	45.4	48.7	msG	WT	N/A	389.2	89.9	100.6	73.8	55.8	43.1	N/A	47.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.7	11.3	12.6	9.2	6.9	5.4	N/A
SPLIT	WT=	797.1						CUM WT %	N/A	48.7	60.0	72.6	81.8	88.7	94.1	N/A
20	N/A	H	4.2	18.7	79.1	msG	WT	N/A	894.7	35.2	22.8	22.7	33.6	31.8	N/A	37.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	79.1	4.0	2.6	2.0	3.9	3.0	N/A
SPLIT	WT=	877.8						CUM WT %	N/A	79.1	83.1	86.7	88.3	92.1	95.9	N/A
30	N/A	H	7.7	79.6	12.7	gS	WT	N/A	93.3	41.4	168.6	219.5	113.6	50.6	N/A	50.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	12.7	5.6	21.0	29.9	15.6	6.9	N/A
SPLIT	WT=	730.1						CUM WT %	N/A	12.7	18.4	40.0	69.9	85.4	92.3	N/A
35	N/A	H	5.8	25.6	68.7	msG	WT	N/A	501.9	40.7	43.1	39.1	32.8	31.1	N/A	42.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.7	5.6	5.9	5.4	4.5	4.3	N/A
SPLIT	WT=	738.8						CUM WT %	N/A	68.7	74.2	80.1	85.5	90.0	94.2	N/A
45	N/A	H	11.0	31.6	58.1	msG	WT	N/A	218.8	30.0	26.3	24.0	20.8	18.8	N/A	41.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.1	8.8	8.7	6.4	5.5	4.5	N/A
SPLIT	WT=	377.0						CUM WT %	N/A	58.1	66.0	72.7	79.1	84.0	89.0	N/A
49	N/A	H	10.7	37.2	52.1	msG	WT	N/A	390.4	82.4	82.4	56.2	46.9	50.9	N/A	80.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.1	8.3	8.3	7.6	8.3	6.8	N/A
SPLIT	WT=	756.3						CUM WT %	N/A	52.1	60.4	68.8	76.3	82.6	89.3	N/A
50	N/A	H	5.3	25.8	68.9	msG	WT	N/A	303.8	31.9	31.4	18.9	17.7	13.9	N/A	23.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.9	7.2	7.1	4.3	4.0	3.2	N/A
SPLIT	WT=	448.1						CUM WT %	N/A	68.9	76.2	83.3	87.8	91.0	94.7	N/A
55	N/A	H	8.4	33.9	59.7	msG	WT	N/A	293.3	53.4	44.6	31.5	22.9	14.9	N/A	31.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.7	10.9	9.1	6.4	4.5	3.0	N/A
SPLIT	WT=	467.1						CUM WT %	N/A	59.7	70.0	79.7	86.1	90.6	93.8	N/A
60	N/A	H	5.8	59.6	34.9	sG	WT	N/A	281.8	68.8	202.6	84.1	41.4	29.2	N/A	42.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.9	11.8	27.0	11.2	5.5	3.9	N/A
SPLIT	WT=	768.7						CUM WT %	N/A	34.9	45.8	73.8	85.0	90.5	94.4	N/A

0.21

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0290-E28-026 ****

02/02/89

DEPTH	%ACCS	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
95	N/A	C	2.4	97.1	0.5	S	WT	N/A	2.9	76.5	327.7	65.1	22.1	11.2	N/A	12.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.5	14.2	60.9	16.0	4.1	2.1	N/A
SPLIT	WT=	540.2						CUM WT %	N/A	0.5	14.0	75.0	91.4	96.6	97.8	N/A
101	N/A	C	3.0	92.4	3.0	S	WT	N/A	22.0	84.3	162.2	127.0	124.0	40.8	N/A	21.5
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	11.3	28.4	22.4	21.9	8.5	N/A
SPLIT	WT=	570.4						CUM WT %	N/A	3.0	15.1	43.5	65.9	87.7	96.2	N/A
106	N/A	C	3.0	92.8	4.2	S	WT	N/A	20.1	76.3	230.1	172.1	163.1	23.0	N/A	18.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.2	12.4	30.5	27.9	10.2	3.9	N/A
SPLIT	WT=	619.2						CUM WT %	N/A	4.2	16.0	55.1	83.0	93.2	97.0	N/A
110	N/A	C	4.1	95.6	0.1	S	WT	N/A	0.0	10.2	300.9	148.7	35.1	15.4	N/A	25.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.1	1.0	62.2	23.9	5.6	2.5	N/A
SPLIT	WT=	627.1						CUM WT %	N/A	0.1	1.7	63.9	87.8	93.4	95.9	N/A
115	N/A	C	4.0	94.5	0.9	S	WT	N/A	5.7	42.0	350.1	129.0	51.3	41.6	N/A	30.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.9	6.4	54.3	19.7	7.8	0.3	N/A
SPLIT	WT=	657.2						CUM WT %	N/A	0.9	7.3	61.0	81.2	89.1	95.4	N/A
120	N/A	C	5.6	93.7	0.7	S	WT	N/A	4.0	41.9	341.9	130.4	49.6	29.5	N/A	30.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.8	6.6	53.2	21.7	7.7	4.6	N/A
SPLIT	WT=	643.3						CUM WT %	N/A	0.8	7.3	60.4	82.1	89.0	94.4	N/A
130	N/A	C	2.5	91.1	6.4 (S)	S	WT	N/A	40.0	198.5	171.3	151.2	43.9	17.2	N/A	16.2
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	0.4	31.1	20.8	23.7	0.9	2.7	N/A
SPLIT	WT=	643.4						CUM WT %	N/A	0.4	37.4	64.2	87.9	94.8	97.5	N/A
135	N/A	C	2.0	92.0	4.0	S	WT	N/A	30.2	221.3	222.5	109.1	37.4	15.0	N/A	17.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.0	33.9	34.1	16.7	5.7	2.3	N/A
SPLIT	WT=	653.7						CUM WT %	N/A	4.0	38.5	72.6	89.4	95.1	97.4	N/A
140	N/A	C	1.2	94.9	3.9	S	WT	N/A	25.1	73.3	204.4	214.0	43.1	12.9	N/A	7.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.9	11.4	41.3	33.4	0.7	2.0	N/A
SPLIT	WT=	645.0						CUM WT %	N/A	3.9	15.4	56.8	90.0	90.8	98.8	N/A
145	N/A	C	2.0	95.0	2.2	S	WT	N/A	13.8	26.0	146.0	334.0	77.0	10.0	N/A	12.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.2	4.1	23.3	53.1	12.2	3.2	N/A
SPLIT	WT=	631.2						CUM WT %	N/A	2.2	6.3	29.0	82.0	94.0	98.0	N/A
150	N/A	C	2.0	96.5	0.7	S	WT	N/A	4.0	23.0	90.1	272.8	130.1	25.1	N/A	15.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	4.2	10.9	40.1	22.9	4.4	N/A
SPLIT	WT=	507.0						CUM WT %	N/A	0.7	4.9	21.8	69.9	92.0	97.2	N/A

0.22

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0299-E28-020 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
155	N/A	C	1.6	95.5	3.0	S	WT	N/A	19.5	118.3	281.4	167.8	48.2	14.8	N/A	9.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.0	18.8	41.7	25.2	7.7	2.4	N/A	1.5
SPLIT	WT= 828.8						CUM WT %	N/A	3.0	21.0	83.3	88.5	96.2	98.5	N/A	100.0
160	N/A	C	8.3	91.9	1.8	S	WT	N/A	10.9	93.4	229.1	120.9	62.1	37.1	N/A	37.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	1.8	15.4	38.4	21.3	10.4	8.2	N/A	6.3
SPLIT	WT= 604.2						CUM WT %	N/A	1.8	17.6	55.9	77.1	87.5	93.7	N/A	100.0
186	N/A	C	2.1	95.7	2.2	S	WT	N/A	13.0	102.4	209.4	134.9	45.8	16.1	N/A	12.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	2.2	17.3	45.6	22.8	7.8	2.8	N/A	2.1
SPLIT	WT= 595.0						CUM WT %	N/A	2.2	19.5	64.9	87.7	95.3	97.9	N/A	100.0
170	N/A	C	8.7	82.6	10.7	gS	WT	N/A	37.8	75.7	82.9	47.2	69.1	35.3	N/A	23.5
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	WT %	N/A	10.7	21.8	17.9	13.4	19.7	10.1	N/A	6.7
SPLIT	WT= 360.4						CUM WT %	N/A	10.7	32.3	50.2	83.8	83.3	93.3	N/A	100.0
175	N/A	C	1.4	52.5	48.8	gG	WT	N/A	338.7	209.4	100.7	48.5	20.4	9.0	N/A	10.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	48.8	29.5	13.7	8.3	2.8	1.3	N/A	1.4
SPLIT	WT= 737.8						CUM WT %	N/A	48.8	74.5	88.2	94.5	97.3	98.6	N/A	100.0
180	N/A	C	1.2	97.7	1.1	S	WT	N/A	4.4	50.7	210.5	82.3	23.1	9.7	N/A	4.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	1.1	14.9	53.6	20.9	5.9	2.5	N/A	1.2
SPLIT	WT= 399.1						CUM WT %	N/A	1.1	16.0	69.6	90.5	96.8	98.9	N/A	100.0
185	N/A	C	2.4	97.2	0.5	S	WT	N/A	1.7	60.8	192.5	55.2	21.7	11.2	N/A	8.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	0.5	17.3	54.8	16.7	8.2	3.2	N/A	2.4
SPLIT	WT= 357.1						CUM WT %	N/A	0.5	17.8	72.8	88.3	94.5	97.6	N/A	100.0
190	N/A	C	5.0	81.3	13.7	gS	WT	N/A	84.2	101.5	215.1	100.4	48.0	24.4	N/A	30.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	13.7	18.6	35.1	17.7	7.9	4.0	N/A	5.0
SPLIT	WT= 820.2						CUM WT %	N/A	13.7	30.3	65.4	83.1	91.0	96.0	N/A	100.0
195	N/A	H	3.2	50.3	38.6	gG	WT	N/A	147.8	102.9	82.1	30.8	18.5	9.8	N/A	12.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	38.5	28.8	10.2	8.0	4.0	2.6	N/A	3.2
SPLIT	WT= 363.2						CUM WT %	N/A	38.5	85.3	81.5	89.5	94.3	96.8	N/A	100.0
200	N/A	C	0.1	72.1	27.8	gS	WT	N/A	187.5	188.8	209.1	81.8	21.1	8.0	N/A	0.4
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	WT %	N/A	27.8	24.8	31.0	12.1	3.1	1.0	N/A	0.1
SPLIT	WT= 677.4						CUM WT %	N/A	27.8	62.6	83.8	95.8	98.9	99.9	N/A	100.0
205	N/A	C	2.9	94.6	2.5	S	WT	N/A	11.4	57.7	100.7	148.4	40.0	12.9	N/A	13.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	2.5	12.6	39.1	31.7	8.7	2.8	N/A	2.9
SPLIT	WT= 481.3						CUM WT %	N/A	2.5	14.9	54.0	85.7	94.3	97.1	N/A	100.0

0.23

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

**** REPORT ON WELL 0299-E20-020 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
210	N/A	C	2.7	95.6	1.8	S	WT	N/A	10.7	65.1	233.4	206.1	50.4	16.2	N/A	16.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.8	10.9	39.1	34.4	8.4	2.7	N/A
SPLIT	WT=	592.0						CUM WT %	N/A	1.8	12.7	51.8	86.1	94.6	97.3	N/A
215	N/A	C	3.8	95.8	0.6	S	WT	N/A	3.7	19.0	172.7	278.2	121.7	32.3	N/A	23.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.6	2.9	26.6	42.6	18.8	5.0	N/A
SPLIT	WT=	646.3						CUM WT %	N/A	0.6	3.5	30.1	72.7	91.4	96.4	N/A
220	N/A	C	47.8	51.8	0.8	mS	WT	N/A	3.4	1.7	0.9	9.1	42.9	222.8	N/A	254.8
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.8	0.3	0.2	1.7	8.0	41.6	N/A
SPLIT	WT=	529.2						CUM WT %	N/A	0.8	1.0	1.1	2.8	10.8	52.4	N/A
225	N/A	C	1.8	55.1	43.2	sG	WT	N/A	357.4	198.3	168.8	57.3	21.9	13.1	N/A	13.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.3	23.8	20.2	6.9	2.7	1.6	N/A
SPLIT	WT=	824.9						CUM WT %	N/A	43.3	67.0	87.2	94.1	96.8	98.4	N/A
230	N/A	C	2.8	33.9	63.2	sG	WT	N/A	547.8	97.9	98.9	52.5	28.2	18.6	N/A	24.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.2	11.3	11.4	6.1	3.0	2.2	N/A
SPLIT	WT=	862.0						CUM WT %	N/A	63.2	74.5	85.9	92.0	95.0	97.2	N/A
235	N/A	C	3.4	36.3	60.4	sG	WT	N/A	448.4	85.8	92.9	48.6	24.3	18.6	N/A	24.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.4	11.6	12.6	6.3	3.3	2.5	N/A
SPLIT	WT=	740.0						CUM WT %	N/A	60.4	72.0	84.5	90.8	94.1	96.6	N/A
240	N/A	H	8.0	91.3	0.7	S	WT	N/A	5.0	33.5	172.0	279.0	120.1	46.4	N/A	57.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	4.7	24.1	39.1	16.8	6.5	N/A
SPLIT	WT=	712.3						CUM WT %	N/A	0.7	5.4	29.5	68.6	85.5	92.0	N/A
247	N/A	H	13.8	43.2	43.0	msG	WT	N/A	335.0	81.8	84.0	84.3	63.5	63.4	N/A	107.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	10.5	8.2	6.2	8.1	8.1	N/A
SPLIT	WT=	777.1						CUM WT %	N/A	43.0	53.4	61.7	69.9	78.0	86.2	N/A
255	N/A	H	15.2	72.0	12.8	(m)gS	WT	N/A	91.7	148.7	115.7	88.3	98.7	67.8	N/A	108.4
SORT=	N/A	MEDIAN=	2.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	12.8	20.5	18.2	12.1	13.8	9.5	N/A
SPLIT	WT=	709.8						CUM WT %	N/A	12.8	33.3	49.5	61.6	75.4	84.9	N/A
260	N/A	H	2.0	39.0	59.0	sG	WT	N/A	477.5	134.4	94.4	53.3	23.5	9.7	N/A	16.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.0	18.8	11.7	6.8	2.9	1.2	N/A
SPLIT	WT=	809.3						CUM WT %	N/A	59.0	75.8	87.3	93.9	98.8	98.0	N/A
265	N/A	H	7.0	62.8	30.5	msG	WT	N/A	212.8	65.1	96.7	97.9	105.1	72.1	N/A	48.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.5	9.3	13.9	14.0	15.1	10.3	N/A
SPLIT	WT=	700.2						CUM WT %	N/A	30.5	39.8	53.6	67.7	82.7	93.0	N/A

J.24

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E28-026 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
270	N/A	H	12.1	44.8	43.2	msG	WT	N/A	316.1	70.3	80.3	87.8	76.6	61.8	N/A	88.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.2	9.6	8.3	9.3	10.5	N/A	12.1
SPLIT	WT=	728.2					CUM WT %	N/A	43.2	62.9	61.1	70.4	80.8	87.9	N/A	100.0
275	N/A	H	9.8	37.4	52.8	msG	WT	N/A	431.5	59.5	83.8	88.7	88.8	47.1	N/A	80.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.8	7.3	7.8	8.2	8.4	N/A	9.8
SPLIT	WT=	817.1					CUM WT %	N/A	52.8	60.1	67.9	76.0	84.4	90.2	N/A	100.0
280	N/A	H	4.9	40.6	54.5	msG	WT	N/A	450.1	130.9	93.2	43.8	40.0	21.8	N/A	40.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.5	16.8	11.3	5.3	4.8	N/A	4.9
SPLIT	WT=	822.2					CUM WT %	N/A	54.5	71.1	82.3	87.8	92.5	95.1	N/A	100.0
285	N/A	H	0.8	34.9	58.3	msG	WT	N/A	241.0	68.5	35.2	20.7	18.0	13.7	N/A	28.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.3	13.7	8.5	5.0	4.4	N/A	8.9
SPLIT	WT=	413.8					CUM WT %	N/A	58.3	72.0	80.5	85.5	89.8	93.2	N/A	100.0
295	N/A	H	3.8	22.7	73.7	msG	WT	N/A	286.8	24.3	17.1	14.7	15.1	11.0	N/A	13.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.7	6.7	4.7	4.1	4.2	N/A	3.8
SPLIT	WT=	362.5					CUM WT %	N/A	73.7	80.4	85.1	89.2	93.3	96.4	N/A	100.0
300	N/A	H	3.1	44.4	52.5	sG	WT	N/A	427.7	99.7	110.7	91.8	38.3	17.9	N/A	25.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.5	12.2	14.3	11.2	4.5	N/A	3.1
SPLIT	WT=	807.4					CUM WT %	N/A	52.5	64.7	79.0	90.3	94.7	98.9	N/A	100.0
305	N/A	H	4.1	25.6	70.3	msG	WT	N/A	295.3	43.1	20.1	15.2	13.1	9.9	N/A	17.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	70.3	10.3	8.2	3.8	3.1	N/A	4.1
SPLIT	WT=	420.5					CUM WT %	N/A	70.3	80.8	86.8	90.5	93.8	95.9	N/A	100.0
310	N/A	H	2.4	38.5	81.1	sG	WT	N/A	464.8	139.6	82.8	28.1	19.3	8.1	N/A	18.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	81.1	18.4	10.9	3.7	2.5	N/A	2.4
SPLIT	WT=	758.4					CUM WT %	N/A	81.1	79.5	90.3	94.0	96.8	97.6	N/A	100.0
315	N/A	H	2.9	68.4	28.6	qS	WT	N/A	213.0	73.8	160.5	163.8	82.1	29.5	N/A	21.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.6	9.9	21.6	22.0	11.0	N/A	2.9
SPLIT	WT=	741.4					CUM WT %	N/A	28.6	38.5	60.1	82.1	93.1	97.1	N/A	100.0
320	N/A	H	3.4	65.5	31.1	sG	WT	N/A	245.8	92.0	211.5	137.2	54.3	21.8	N/A	26.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.1	11.7	20.8	17.4	8.9	N/A	3.4
SPLIT	WT=	788.9					CUM WT %	N/A	31.1	42.8	69.8	87.0	93.9	98.8	N/A	100.0
325	N/A	H	5.7	52.7	41.6	sG	WT	N/A	311.0	137.2	127.8	70.3	34.0	18.1	N/A	42.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.6	18.4	17.1	10.2	4.8	N/A	5.7
SPLIT	WT=	747.9					CUM WT %	N/A	41.6	60.0	77.1	87.3	91.9	94.3	N/A	100.0

J.25

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

*** REPORT ON WELL 0290-E28-027 ***

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
36	N/A	H	10.1	54.0	35.0	msG	WT	N/A	298.0	154.2	113.2	64.0	65.0	50.0	N/A	88.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.1	18.1	13.3	9.9	7.7	N/A	10.1
SPLIT	WT=	860.3					CUM WT %	N/A	35.1	53.2	66.4	76.3	84.0	89.9	N/A	100.0
40	N/A	H	8.3	60.7	31.0	msG	WT	N/A	271.0	170.3	105.2	69.5	58.0	40.0	N/A	72.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	19.4	16.0	10.2	6.7	N/A	8.3
SPLIT	WT=	884.9					CUM WT %	N/A	31.0	50.4	69.3	79.5	86.2	91.7	N/A	100.0
46	N/A	H	7.0	57.0	25.4	(m)gS	WT	N/A	199.0	210.1	154.0	75.0	51.7	35.1	N/A	59.0
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	25.4	28.7	19.7	9.6	6.0	N/A	7.0
SPLIT	WT=	786.4					CUM WT %	N/A	25.4	52.2	71.0	81.4	87.9	92.4	N/A	100.0
50	N/A	H	12.0	82.1	5.9	(gm)S	WT	N/A	35.0	126.7	102.7	95.3	62.3	50.1	N/A	72.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.9	20.0	20.9	15.8	10.3	N/A	12.0
SPLIT	WT=	802.0					CUM WT %	N/A	5.9	26.7	53.0	69.4	79.7	88.0	N/A	100.0
66	N/A	H	0.2	76.4	24.4	gS	WT	N/A	100.1	197.2	211.5	62.0	14.0	7.4	N/A	1.2
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	24.4	30.1	32.3	9.0	2.3	N/A	0.2
SPLIT	WT=	861.0					CUM WT %	N/A	24.4	54.5	80.8	95.4	98.7	99.0	N/A	100.0
68	N/A	H	2.0	90.2	0.9	S	WT	N/A	0.4	51.3	207.0	246.3	50.7	10.7	N/A	10.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.9	7.5	41.0	35.0	8.3	N/A	2.0
SPLIT	WT=	893.7					CUM WT %	N/A	0.9	8.4	50.3	80.2	94.4	97.2	N/A	100.0
69	N/A	C	2.2	90.5	1.4	S	WT	N/A	0.7	130.5	300.0	67.8	20.0	11.3	N/A	13.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.4	21.9	50.4	10.5	3.1	N/A	2.2
SPLIT	WT=	839.2					CUM WT %	N/A	1.4	23.1	82.5	93.0	98.1	97.0	N/A	100.0
70	N/A	C	N/A	95.6	4.6	N/A	WT	N/A	14.1	44.4	166.7	82.0	12.0	4.1	N/A	N/A
SORT=	N/A	MEDIAN=	1.00	MODE=	N/A	MEAN=	N/A	WT %	N/A	4.6	14.2	49.0	20.9	4.1	N/A	N/A
SPLIT	WT=	919.7					CUM WT %	N/A	4.6	10.6	60.3	94.0	98.7	100.0	N/A	N/A
76	N/A	C	0.2	97.4	2.4	S	WT	N/A	12.7	62.7	202.4	128.2	10.0	7.0	N/A	1.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.4	12.0	55.0	24.6	3.0	N/A	0.2
SPLIT	WT=	530.1					CUM WT %	N/A	2.4	14.4	70.2	94.7	98.5	99.8	N/A	100.0
80	N/A	C	2.9	94.9	2.2	S	WT	N/A	15.1	114.4	320.7	103.0	30.1	17.3	N/A	20.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.2	10.5	47.0	23.5	5.5	N/A	2.9
SPLIT	WT=	701.0					CUM WT %	N/A	2.2	10.0	65.7	89.1	94.0	97.1	N/A	100.0
85	N/A	C	2.0	90.2	1.0	S	WT	N/A	5.3	11.0	38.0	100.5	230.2	50.0	N/A	15.1
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	1.0	2.2	0.4	31.7	44.0	N/A	2.0
SPLIT	WT=	530.4					CUM WT %	N/A	1.0	3.2	0.6	41.0	66.1	97.2	N/A	100.0

J.27

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0299-E28-027 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
90	N/A	C	9.7	42.8	47.5	msG	WT	N/A	468.7	112.5	80.8	85.6	83.1	49.3	N/A	93.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.5	11.7	8.4	8.9	6.1	N/A	9.7
SPLIT	WT=	961.5					CUM WT %	N/A	47.5	59.2	87.8	78.5	85.2	90.3	N/A	100.0
95	N/A	C	1.2	97.7	1.2	S	WT	N/A	6.9	111.7	383.0	76.8	17.2	4.8	N/A	8.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.2	19.1	82.0	12.9	2.9	N/A	1.2
SPLIT	WT=	586.2					CUM WT %	N/A	1.2	20.2	82.2	95.1	98.0	98.9	N/A	100.0
100	N/A	C	1.5	92.1	8.4	(g)S	WT	N/A	22.8	61.3	149.2	94.0	17.8	6.8	N/A	5.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.4	17.2	41.8	28.3	4.9	N/A	1.5
SPLIT	WT=	353.1					CUM WT %	N/A	6.4	23.8	65.4	91.7	96.8	98.5	N/A	100.0
105	N/A	C	3.4	88.8	29.8	gS	WT	N/A	103.1	39.1	45.9	73.4	58.5	18.0	N/A	11.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.8	11.3	13.3	21.2	16.3	N/A	3.4
SPLIT	WT=	342.1					CUM WT %	N/A	29.8	41.1	54.4	75.6	91.9	96.8	N/A	100.0
110	N/A	C	2.3	97.8	0.1	S	WT	N/A	0.4	7.0	70.8	171.3	80.0	11.2	N/A	7.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	2.1	21.5	52.2	18.3	N/A	2.3
SPLIT	WT=	325.4					CUM WT %	N/A	0.1	2.3	23.8	78.0	94.3	97.7	N/A	100.0
115	N/A	C	4.8	94.8	0.8	S	WT	N/A	1.8	18.4	64.0	63.1	101.4	28.1	N/A	13.9
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.8	5.7	22.2	21.9	35.1	N/A	4.8
SPLIT	WT=	285.2					CUM WT %	N/A	0.8	8.3	28.5	50.3	85.5	95.2	N/A	100.0
120	N/A	C	1.4	98.4	0.3	S	WT	N/A	0.8	18.9	205.8	70.3	12.3	4.6	N/A	4.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.3	6.0	64.9	22.2	3.9	N/A	1.4
SPLIT	WT=	314.4					CUM WT %	N/A	0.3	6.2	71.1	93.3	97.2	98.8	N/A	100.0
125	N/A	C	1.8	97.1	1.1	S	WT	N/A	3.8	79.2	173.7	54.2	15.2	6.8	N/A	8.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.1	23.4	51.3	18.0	4.5	N/A	1.8
SPLIT	WT=	335.7					CUM WT %	N/A	1.1	24.4	75.7	91.7	96.2	98.2	N/A	100.0
130	N/A	C	8.2	91.0	2.8	S	WT	N/A	17.7	105.3	217.9	133.5	77.2	38.2	N/A	38.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.8	16.7	34.6	21.2	12.3	N/A	6.2
SPLIT	WT=	834.7					CUM WT %	N/A	2.8	19.5	54.1	75.3	87.6	93.8	N/A	100.0
135	N/A	C	4.1	92.9	3.0	S	WT	N/A	18.3	88.9	221.3	183.4	54.5	23.8	N/A	25.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	14.2	38.1	29.9	8.9	N/A	4.1
SPLIT	WT=	889.4					CUM WT %	N/A	3.0	17.2	53.3	83.2	92.1	95.9	N/A	100.0
140	N/A	C	10.1	88.7	1.3	(m)S	WT	N/A	9.3	167.5	392.9	61.7	30.5	2.8	N/A	74.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.3	22.7	53.2	8.4	4.1	N/A	10.1
SPLIT	WT=	748.4					CUM WT %	N/A	1.3	23.9	77.1	85.4	89.8	89.9	N/A	100.0

7.28

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E28-027 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
145	N/A	C	4.8	91.4	3.9	S	WT	N/A	21.5	99.3	223.1	135.4	40.4	19.9	N/A	20.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.9	10.2	40.0	24.3	7.3	3.0	N/A	4.8
SPLIT	WT=	555.5					CUM	WT %	N/A	3.9	20.1	80.1	84.4	91.6	95.2	N/A	100.0
150	N/A	C	2.8	94.7	2.8	S	WT	N/A	13.8	64.0	201.9	160.5	38.3	12.0	N/A	12.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.8	12.0	40.4	31.7	7.3	2.6	N/A	2.8
SPLIT	WT=	490.4					CUM	WT %	N/A	2.8	15.6	65.9	87.6	94.9	97.4	N/A	100.0
155	N/A	C	5.0	91.0	4.0	S	WT	N/A	24.2	102.8	222.7	149.7	52.8	28.4	N/A	30.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.0	10.8	38.5	24.5	8.8	4.7	N/A	5.0
SPLIT	WT=	600.5					CUM	WT %	N/A	4.0	20.8	57.2	81.7	90.3	95.0	N/A	100.0
160	N/A	C	5.0	93.9	0.5	S	WT	N/A	2.0	27.0	172.0	232.3	66.9	29.0	N/A	31.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.5	4.9	30.8	41.3	11.0	5.3	N/A	5.0
SPLIT	WT=	507.3					CUM	WT %	N/A	0.5	5.4	30.0	77.3	89.1	94.4	N/A	100.0
165	N/A	C	3.4	90.2	0.4	S	WT	N/A	1.4	24.7	120.0	123.3	36.2	9.4	N/A	11.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.4	7.4	30.4	36.0	18.0	2.0	N/A	3.4
SPLIT	WT=	333.0					CUM	WT %	N/A	0.4	7.0	40.2	83.0	93.8	96.0	N/A	100.0
170	N/A	C	0.2	93.8	0.0	S	WT	N/A	0.0	20.3	132.9	114.7	43.2	17.8	N/A	21.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.0	5.0	37.0	32.7	12.3	5.1	N/A	0.2
SPLIT	WT=	353.7					CUM	WT %	N/A	0.0	5.0	43.7	70.4	88.7	93.8	N/A	100.0
175	N/A	C	3.6	98.0	0.4	S	WT	N/A	2.2	10.5	134.2	290.3	93.5	23.0	N/A	21.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	1.0	23.1	51.0	10.1	4.0	N/A	3.0
SPLIT	WT=	570.0					CUM	WT %	N/A	0.4	2.2	25.3	70.3	92.4	96.4	N/A	100.0
180	N/A	C	3.0	98.0	0.4	S	WT	N/A	2.2	11.0	100.0	290.2	113.4	24.5	N/A	17.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	1.0	18.0	51.0	19.0	4.3	N/A	3.0
SPLIT	WT=	570.0					CUM	WT %	N/A	0.4	2.3	21.2	72.9	82.7	97.0	N/A	100.0
185	N/A	C	0.1	93.2	0.7	S	WT	N/A	4.1	32.7	139.0	224.5	89.9	34.2	N/A	34.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	5.0	24.9	40.2	10.1	8.1	N/A	0.1
SPLIT	WT=	550.4					CUM	WT %	N/A	0.7	0.0	31.5	71.7	87.0	93.9	N/A	100.0
190	N/A	C	3.1	48.0	48.3	SG	WT	N/A	370.1	145.2	120.0	57.0	20.9	17.1	N/A	23.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.3	19.0	10.5	7.4	3.5	2.2	N/A	3.1
SPLIT	WT=	784.2					CUM	WT %	N/A	48.3	07.3	03.7	01.2	04.7	08.0	N/A	100.0
195	N/A	C	2.0	75.4	22.0	GS	WT	N/A	134.1	102.7	184.4	51.7	21.1	10.7	N/A	15.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	22.0	31.6	30.2	0.5	3.5	1.0	N/A	2.0
SPLIT	WT=	010.0					CUM	WT %	N/A	22.0	53.5	63.7	92.2	95.7	97.4	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E28-027 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (<= -2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
200	N/A	C	4.4	84.5	11.0	gS	WT	N/A	68.8	103.3	224.2	68.1	28.1	16.9	N/A	27.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.0	31.1	10.2	4.5	2.7	N/A	4.4
SPLIT	WT=	822.0						CUM WT %	N/A	11.0	42.1	88.8	92.9	95.6	N/A	100.0
205	N/A	C	1.0	77.1	21.0	gS	WT	N/A	142.7	173.9	193.0	89.2	33.9	13.8	N/A	0.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	21.0	26.6	13.7	6.2	2.1	N/A	1.0
SPLIT	WT=	653.0						CUM WT %	N/A	21.0	46.4	78.1	91.7	99.0	N/A	100.0
210	N/A	C	3.0	70.2	20.0	gS	WT	N/A	187.8	184.0	197.5	123.8	44.1	23.5	N/A	21.1
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	26.0	14.8	28.1	17.8	6.3	N/A	3.0
SPLIT	WT=	780.7						CUM WT %	N/A	26.8	41.6	69.7	87.4	93.6	N/A	100.0
215	N/A	C	3.1	74.8	22.1	gS	WT	N/A	155.5	148.0	221.1	107.9	34.9	17.0	N/A	21.3
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	22.1	20.7	31.4	15.3	5.0	N/A	3.1
SPLIT	WT=	704.0						CUM WT %	N/A	22.1	42.6	74.2	89.5	94.5	N/A	100.0
220	N/A	C	3.9	93.0	3.0	S	WT	N/A	10.0	100.0	240.0	151.7	53.7	24.1	N/A	24.0
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.1	17.0	38.0	24.3	8.0	N/A	4.0
SPLIT	WT=	831.4						CUM WT %	N/A	3.1	20.7	59.3	83.6	92.2	N/A	100.0
225	N/A	C	0.8	89.0	0.0	S	WT	N/A	5.4	07.0	221.3	178.5	84.1	49.6	N/A	04.1
SDRT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.8	10.0	33.0	28.0	12.0	N/A	9.0
SPLIT	WT=	669.3						CUM WT %	N/A	0.8	10.8	43.8	70.5	83.0	N/A	100.0
230	N/A	C	7.0	90.0	2.2	S	WT	N/A	14.4	75.0	170.2	179.7	110.1	51.4	N/A	51.0
SDRT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.2	11.4	25.0	27.2	17.9	N/A	7.0
SPLIT	WT=	600.0						CUM WT %	N/A	2.2	13.5	30.3	88.6	84.4	N/A	100.0
235	N/A	C	7.8	89.0	2.4	S	WT	N/A	15.2	71.2	165.1	174.7	98.3	77.0	N/A	50.3
SDRT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.4	11.1	24.2	27.2	16.3	N/A	7.0
SPLIT	WT=	640.0						CUM WT %	N/A	2.4	13.5	37.0	64.9	80.2	N/A	100.0
240	N/A	C	0.1	53.0	40.3	msG	WT	N/A	258.5	72.9	118.0	60.2	42.5	45.9	N/A	39.3
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.3	11.4	10.2	10.3	8.0	N/A	0.1
SPLIT	WT=	647.9						CUM WT %	N/A	40.3	51.0	60.8	60.1	60.7	N/A	100.0
245	N/A	C	5.0	34.0	60.2	msG	WT	N/A	509.9	63.3	124.6	62.0	31.1	12.4	N/A	42.4
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.2	7.5	14.7	7.4	3.7	N/A	5.0
SPLIT	WT=	653.0						CUM WT %	N/A	60.2	67.7	82.4	89.9	93.5	N/A	100.0
250	N/A	C	3.2	53.5	43.3	msG	WT	N/A	319.0	89.0	188.8	80.2	35.6	20.0	N/A	23.3
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.3	12.2	22.0	10.9	4.0	N/A	3.2
SPLIT	WT=	737.3						CUM WT %	N/A	43.3	55.5	78.4	89.2	94.1	N/A	100.0

U.30

ROCKWELL HANFORD OPERATIONS STEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0209-E28-027 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
255	N/A	C	0.2	34.1	59.7	msG	WT	N/A	469.2	68.4	71.2	53.8	43.2	33.1	N/A	48.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	59.7	8.6	9.1	6.9	5.5	4.2	N/A	8.2
SPLIT	WT=	791.4					CUM WT %	N/A	59.7	68.2	77.2	84.1	89.6	93.8	N/A	100.0
280	N/A	H	10.6	52.3	37.2	msG	WT	N/A	389.4	100.0	78.3	101.4	101.5	54.2	N/A	87.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	37.2	12.0	8.4	12.2	12.2	6.5	N/A	10.5
SPLIT	WT=	832.1					CUM WT %	N/A	37.2	49.2	59.6	70.8	83.0	89.5	N/A	100.0
285	N/A	H	12.2	55.4	32.4	msG	WT	N/A	284.0	100.0	90.5	114.8	109.6	82.0	N/A	107.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	32.4	12.4	10.3	13.1	12.6	7.2	N/A	12.2
SPLIT	WT=	876.4					CUM WT %	N/A	32.4	44.8	55.1	68.2	80.8	87.8	N/A	100.0
270	N/A	H	13.0	51.8	34.3	msG	WT	N/A	279.0	98.4	80.2	86.1	128.0	50.7	N/A	112.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	34.3	11.8	9.8	8.4	15.6	6.2	N/A	13.9
SPLIT	WT=	917.6					CUM WT %	N/A	34.3	46.2	56.0	64.4	79.9	88.1	N/A	100.0
275	N/A	H	11.1	50.7	38.2	msG	WT	N/A	301.0	122.3	95.9	73.9	64.8	43.1	N/A	87.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	38.2	15.6	12.2	9.4	8.2	5.6	N/A	11.1
SPLIT	WT=	789.4					CUM WT %	N/A	38.2	53.7	65.9	75.3	83.5	89.0	N/A	100.0
280	N/A	H	11.0	84.9	4.1	(m)S	WT	N/A	29.0	100.0	226.0	105.0	60.1	37.0	N/A	77.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	4.1	22.7	32.1	15.0	9.8	5.2	N/A	11.0
SPLIT	WT=	700.1					CUM WT %	N/A	4.1	28.8	50.9	73.9	83.7	89.0	N/A	100.0
285	N/A	H	6.0	78.2	13.7	qS	WT	N/A	113.2	288.0	202.1	94.0	50.8	35.0	N/A	68.2
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	WT %	N/A	19.8	32.3	24.6	10.2	8.9	4.3	N/A	8.0
SPLIT	WT=	821.7					CUM WT %	N/A	19.8	46.1	70.5	80.8	87.7	92.0	N/A	100.0
290	N/A	H	0.0	93.4	0.0	S	WT	N/A	0.0	4.0	37.9	154.0	308.4	142.0	N/A	45.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.7	5.5	22.3	44.4	20.0	N/A	8.0
SPLIT	WT=	894.7					CUM WT %	N/A	0.0	0.7	6.2	28.4	72.8	93.4	N/A	100.0
295	N/A	H	1.4	40.8	57.8	msG	WT	N/A	473.2	125.0	111.8	87.7	22.2	7.2	N/A	11.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	57.8	15.3	13.7	8.3	2.7	0.9	N/A	1.4
SPLIT	WT=	819.0					CUM WT %	N/A	57.8	73.0	86.7	95.0	97.7	98.8	N/A	100.0

J.31

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 1

**** REPORT ON WELL 0209-E32-002 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	H	13.1	45.2	41.8	msG	WT	N/A	340.6	55.4	58.0	57.3	84.3	142.4	N/A	100.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.8	0.0	0.0	7.7	17.1	N/A	13.1
SPLIT WT=	833.6							CUM WT %	N/A	41.8	48.4	82.2	89.9	88.9	N/A	100.0
10	N/A	H	15.1	78.9	8.0	(gm)S	WT	N/A	51.4	45.0	90.4	112.7	144.0	101.5	N/A	97.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	8.0	7.1	14.1	22.5	15.8	N/A	15.1
SPLIT WT=	643.3							CUM WT %	N/A	8.0	15.1	29.2	46.7	64.9	N/A	100.0
15	N/A	H	12.7	45.2	42.1	msG	WT	N/A	392.1	133.0	92.5	72.4	70.7	52.4	N/A	110.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	14.3	9.9	7.0	5.6	N/A	12.7
SPLIT WT=	930.8							CUM WT %	N/A	42.1	56.4	66.3	74.1	81.7	N/A	100.0
23	N/A	H	11.7	59.8	20.5	(m)gS	WT	N/A	223.8	164.0	139.8	78.1	57.4	40.0	N/A	91.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.5	19.0	10.0	7.3	5.1	N/A	11.7
SPLIT WT=	781.0							CUM WT %	N/A	20.5	48.1	66.9	76.9	80.3	N/A	100.0
40	N/A	H	0.0	23.7	88.6	msG	WT	N/A	520.7	40.7	37.0	34.5	30.0	28.0	N/A	50.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	88.6	0.6	5.0	4.5	3.7	N/A	6.7
SPLIT WT=	758.4							CUM WT %	N/A	88.6	70.1	81.1	85.7	89.7	N/A	100.0
45	N/A	H	7.0	49.9	42.1	msG	WT	N/A	351.4	158.8	121.9	61.7	44.4	29.4	N/A	60.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	19.1	14.0	7.4	5.3	N/A	7.9
SPLIT WT=	832.5							CUM WT %	N/A	42.1	61.2	75.0	83.2	88.5	N/A	100.0
50	N/A	H	0.0	40.7	41.4	msG	WT	N/A	342.2	158.1	89.0	85.3	46.0	31.0	N/A	73.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.4	19.1	10.0	5.7	3.0	N/A	8.0
SPLIT WT=	818.9							CUM WT %	N/A	41.4	60.5	71.3	81.0	87.3	N/A	100.0
55	N/A	H	5.0	73.0	21.3	gS	WT	N/A	180.1	170.5	231.7	90.0	50.0	20.0	N/A	44.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	21.3	22.5	20.2	11.5	8.4	N/A	5.6
SPLIT WT=	790.7							CUM WT %	N/A	21.3	43.8	73.1	84.0	91.0	N/A	100.0
60	N/A	C	3.3	78.3	18.4	gS	WT	N/A	144.3	221.1	244.4	89.0	30.0	20.0	N/A	25.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.4	28.2	31.2	11.4	4.9	N/A	3.3
SPLIT WT=	784.6							CUM WT %	N/A	18.4	46.6	77.7	89.1	94.1	N/A	100.0
65	N/A	C	8.0	75.6	18.3	gS	WT	N/A	127.2	192.7	180.4	74.2	44.9	32.1	N/A	41.7
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	18.4	27.0	28.0	10.7	6.5	N/A	0.0
SPLIT WT=	604.8							CUM WT %	N/A	18.4	46.2	72.2	82.9	89.4	N/A	100.0
70	N/A	C	0.7	70.5	20.8	(m)gS	WT	N/A	144.9	218.0	115.3	40.0	47.0	69.7	N/A	60.5
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.8	31.4	10.0	5.7	6.0	N/A	8.7
SPLIT WT=	898.4							CUM WT %	N/A	20.8	52.2	60.8	74.5	81.3	N/A	100.0

U.33

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E32-002 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE P60 (<= -2)	VFINE P60 (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
76	N/A	C	3.7	93.7	2.8	S	WT	N/A	20.4	196.4	383.8	89.4	38.2	18.9	N/A	28.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	2.8	25.3	49.8	11.8	4.7	2.8	N/A	3.7
SPLIT	WT=	773.5					CUM WT %	N/A	2.8	27.9	77.6	89.1	93.8	98.3	N/A	100.0
80	N/A	C	4.3	75.4	20.3	S	WT	N/A	161.5	211.9	219.5	74.2	33.8	23.7	N/A	31.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	20.3	28.4	29.4	9.9	4.5	3.2	N/A	4.3
SPLIT	WT=	748.1					CUM WT %	N/A	20.3	48.7	78.1	88.0	92.6	95.7	N/A	100.0
85	N/A	C	1.0	98.0	3.0	S	WT	N/A	18.3	171.1	303.8	38.9	10.4	4.1	N/A	5.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.0	31.2	55.2	7.1	1.9	0.0	N/A	1.0
SPLIT	WT=	548.6					CUM WT %	N/A	3.0	34.1	89.3	98.4	99.3	99.0	N/A	100.0
90	N/A	C	5.1	91.8	3.1	S	WT	N/A	21.5	164.0	308.3	97.2	48.2	28.8	N/A	35.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.1	23.5	43.7	13.9	8.8	4.1	N/A	5.1
SPLIT	WT=	693.4					CUM WT %	N/A	3.1	26.6	70.3	84.2	90.8	94.9	N/A	100.0
95	N/A	C	1.2	93.9	4.8	S	WT	N/A	34.3	268.9	321.3	54.6	18.3	7.0	N/A	8.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	4.8	37.6	45.3	7.7	2.3	1.0	N/A	1.2
SPLIT	WT=	710.3					CUM WT %	N/A	4.8	42.5	87.8	95.5	97.8	98.8	N/A	100.0
100	N/A	C	2.9	95.3	1.8	S	WT	N/A	13.4	143.8	486.6	118.0	39.2	17.1	N/A	22.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	1.8	18.0	53.8	16.3	5.2	2.3	N/A	2.9
SPLIT	WT=	758.1					CUM WT %	N/A	1.8	20.7	74.4	89.7	94.8	97.1	N/A	100.0
105	N/A	C	4.9	92.7	2.4	S	WT	N/A	18.8	115.0	358.5	113.8	42.8	24.8	N/A	34.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	2.4	18.3	50.8	16.1	8.1	3.4	N/A	4.9
SPLIT	WT=	708.9					CUM WT %	N/A	2.4	18.7	89.6	85.7	91.7	95.1	N/A	100.0
110	N/A	C	1.8	93.8	5.2	(S)	WT	N/A	37.9	133.6	368.6	141.4	33.8	13.1	N/A	13.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	5.2	18.3	49.0	19.3	4.5	1.0	N/A	1.8
SPLIT	WT=	733.1					CUM WT %	N/A	5.2	23.4	72.4	91.8	95.4	98.2	N/A	100.0
115	N/A	C	10.3	86.7	3.0	(m)S	WT	N/A	22.1	98.4	279.9	162.8	68.8	44.0	N/A	75.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.0	12.3	38.1	20.8	9.5	6.1	N/A	10.3
SPLIT	WT=	737.5					CUM WT %	N/A	3.0	15.3	53.4	74.1	83.8	99.7	N/A	100.0
120	N/A	C	2.1	97.9	0.1	S	WT	N/A	0.4	8.4	161.5	354.1	91.1	17.1	N/A	13.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.1	1.0	26.1	55.0	14.2	2.7	N/A	2.1
SPLIT	WT=	845.0					CUM WT %	N/A	0.1	1.1	26.1	61.1	85.3	97.9	N/A	100.0
125	N/A	C	6.4	93.6	0.1	S	WT	N/A	0.6	9.1	45.1	327.9	163.6	38.9	N/A	39.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.1	0.5	7.3	53.0	28.4	8.3	N/A	6.4
SPLIT	WT=	821.0					CUM WT %	N/A	0.1	0.6	7.9	60.8	87.3	93.8	N/A	100.0

J.34

ROCKWELL MANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0299-E32-002 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
130	N/A	C	3.7	96.3	0.0	S	WT	N/A	0.0	0.0	20.4	338.0	245.1	39.0	N/A	24.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.0	0.0	3.1	60.5	38.8	0.0	N/A	3.7
SPLIT	WT=	687.2					CUM WT %	N/A	0.0	0.0	3.1	62.5	90.4	90.3	N/A	100.0
135	N/A	C	5.0	95.0	0.0	S	WT	N/A	0.1	0.0	13.5	263.4	288.0	67.2	N/A	32.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.0	2.1	39.3	44.7	8.9	N/A	5.0
SPLIT	WT=	646.9					CUM WT %	N/A	0.0	0.0	2.1	41.4	86.1	95.0	N/A	100.0
140	N/A	C	7.6	92.4	0.0	S	WT	N/A	0.0	0.5	5.6	167.8	320.4	72.7	N/A	45.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.1	0.9	26.2	53.2	12.1	N/A	7.0
SPLIT	WT=	603.1					CUM WT %	N/A	0.0	0.1	1.0	27.2	80.4	92.6	N/A	100.0
145	N/A	C	6.8	94.2	0.0	S	WT	N/A	0.1	0.5	3.0	190.1	313.9	82.3	N/A	35.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.1	0.5	32.1	61.3	10.2	N/A	5.8
SPLIT	WT=	612.2					CUM WT %	N/A	0.0	0.1	0.0	32.7	84.0	94.2	N/A	100.0
150	N/A	C	5.8	94.3	0.0	S	WT	N/A	0.1	0.4	0.5	80.7	303.1	70.8	N/A	33.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.1	0.1	13.0	67.2	13.1	N/A	5.0
SPLIT	WT=	585.4					CUM WT %	N/A	0.0	0.1	0.2	14.0	81.2	94.4	N/A	100.0
155	N/A	C	0.0	90.4	2.7	S	WT	N/A	10.3	40.9	154.7	102.1	138.8	55.2	N/A	42.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	2.7	0.7	25.4	20.6	22.7	9.0	N/A	5.9
SPLIT	WT=	618.0					CUM WT %	N/A	2.7	9.4	34.7	81.3	84.0	93.1	N/A	100.0
160	N/A	C	12.0	87.0	0.1 (m)	S	WT	N/A	0.7	2.4	8.2	137.3	331.1	80.1	N/A	77.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.1	0.4	1.3	21.3	61.3	13.7	N/A	12.0
SPLIT	WT=	640.4					CUM WT %	N/A	0.1	0.5	1.0	23.0	74.3	88.0	N/A	100.0
165	N/A	C	2.0	97.3	0.1	S	WT	N/A	0.5	2.0	13.5	210.3	208.0	41.0	N/A	14.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.1	0.4	2.4	39.3	47.7	7.5	N/A	2.0
SPLIT	WT=	564.4					CUM WT %	N/A	0.1	0.5	2.9	42.2	89.9	97.4	N/A	100.0
170	N/A	C	6.9	93.8	0.3	S	WT	N/A	1.5	1.5	2.5	124.7	334.4	62.5	N/A	32.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.3	0.3	0.5	22.3	59.7	11.2	N/A	5.9
SPLIT	WT=	557.6					CUM WT %	N/A	0.3	0.5	1.0	23.3	83.0	94.1	N/A	100.0
175	N/A	C	0.1	93.5	0.4	S	WT	N/A	2.2	1.1	0.5	72.5	361.4	60.0	N/A	34.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.4	0.2	0.1	12.9	60.1	12.2	N/A	0.1
SPLIT	WT=	559.3					CUM WT %	N/A	0.4	0.0	0.7	13.6	81.7	93.9	N/A	100.0
180	N/A	C	12.1	87.0	0.3 (m)	S	WT	N/A	1.3	1.9	0.1	17.5	292.2	141.0	N/A	52.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.3	0.4	0.0	3.4	50.5	27.4	N/A	12.1
SPLIT	WT=	522.1					CUM WT %	N/A	0.3	0.6	0.6	4.0	60.5	87.9	N/A	100.0

7.35

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E32-002 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
185	N/A	C	11.8	86.4	2.9	(m)S	WT	N/A	16.7	8.2	7.8	19.8	284.6	156.2	N/A	82.1	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	2.9	1.5	1.3	3.7	49.8	29.3	N/A	11.6
SPLIT	WT=	532.2					CUM WT %	N/A	2.9	4.5	5.8	9.5	59.1	88.4	N/A	100.0	
190	N/A	H	9.8	61.9	28.2	(m)gS	WT	N/A	229.7	163.3	119.3	104.9	71.9	44.4	N/A	79.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.2	20.1	14.7	12.9	8.8	6.5	N/A	9.8
SPLIT	WT=	613.3					CUM WT %	N/A	28.2	48.3	63.0	75.9	84.7	90.2	N/A	100.0	
195	N/A	C	4.7	72.9	22.6	gS	WT	N/A	146.4	131.1	181.0	87.9	45.6	27.7	N/A	38.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	22.6	20.1	27.9	13.5	7.0	4.3	N/A	4.7
SPLIT	WT=	665.3					CUM WT %	N/A	22.6	42.8	70.6	84.1	91.1	95.4	N/A	100.0	
200	N/A	C	4.1	95.3	0.6	S	WT	N/A	3.8	57.4	231.9	175.6	76.5	29.2	N/A	24.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.6	9.6	38.7	29.3	12.8	4.9	N/A	4.1
SPLIT	WT=	590.3					CUM WT %	N/A	0.6	10.2	49.0	78.3	91.1	95.9	N/A	100.0	
205	N/A	C	0.3	92.8	0.9	S	WT	N/A	6.4	28.0	87.1	207.2	147.2	57.8	N/A	38.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	4.5	16.0	35.9	25.6	10.8	N/A	0.3
SPLIT	WT=	573.5					CUM WT %	N/A	0.9	5.5	22.3	58.2	83.7	93.7	N/A	100.0	
210	N/A	C	0.4	56.9	36.7	msG	WT	N/A	270.6	105.3	122.1	81.2	61.9	49.2	N/A	47.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.7	14.3	16.6	11.0	6.4	8.7	N/A	0.4
SPLIT	WT=	741.8					CUM WT %	N/A	36.7	61.0	87.6	78.5	88.9	93.6	N/A	100.0	
215	N/A	C	6.9	42.4	51.7	msG	WT	N/A	398.7	109.2	100.6	52.6	37.2	27.9	N/A	45.4	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.7	14.2	12.0	8.8	4.8	3.6	N/A	6.9
SPLIT	WT=	770.2					CUM WT %	N/A	51.7	65.9	78.9	85.7	90.5	94.1	N/A	100.0	
220	N/A	C	4.8	45.6	50.6	sg	WT	N/A	360.8	82.5	117.7	63.8	32.1	20.2	N/A	28.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.6	11.9	16.0	9.2	4.6	2.6	N/A	4.8
SPLIT	WT=	892.2					CUM WT %	N/A	50.6	62.3	79.3	88.5	93.1	96.0	N/A	100.0	
235	N/A	C	2.8	24.7	72.7	sg	WT	N/A	590.1	62.8	60.3	40.1	23.5	15.6	N/A	21.3	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	72.7	7.7	7.4	4.9	2.9	1.9	N/A	2.8
SPLIT	WT=	825.7					CUM WT %	N/A	72.7	80.4	87.7	92.6	95.6	97.4	N/A	100.0	
240	N/A	C	7.8	48.7	43.7	msG	WT	N/A	399.9	133.2	136.2	81.5	58.4	37.1	N/A	89.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	14.6	14.8	8.9	6.4	4.1	N/A	7.8
SPLIT	WT=	921.0					CUM WT %	N/A	43.7	58.3	73.1	82.0	86.3	92.4	N/A	100.0	
250	N/A	H	11.7	48.7	39.6	msG	WT	N/A	329.7	106.5	82.9	72.2	79.4	64.7	N/A	97.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.6	12.9	10.0	8.7	9.5	7.8	N/A	11.7
SPLIT	WT=	829.9					CUM WT %	N/A	39.6	52.4	62.3	71.0	80.6	88.3	N/A	100.0	

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E32-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
265	N/A	H	10.4	45.1	44.6	msG	WT	N/A	398.2	115.3	85.0	72.0	73.0	66.7	N/A	92.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.6	12.9	9.5	8.1	8.2	8.4	N/A
SPLIT	WT=	891.3					CUM	WT %	N/A	44.6	57.5	67.0	75.1	83.3	89.6	N/A
260	N/A	H	19.7	70.4	9.8	(g)ms	WT	N/A	60.5	73.0	87.0	93.5	97.3	81.5	N/A	121.1
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.9	12.0	14.2	15.2	15.8	13.3	N/A
SPLIT	WT=	614.4					CUM	WT %	N/A	9.9	21.8	36.0	51.2	67.0	80.3	N/A
265	N/A	H	7.0	48.3	43.9	msG	WT	N/A	382.4	101.0	98.7	54.7	46.3	40.8	N/A	88.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.9	20.8	11.3	6.3	5.3	4.7	N/A
SPLIT	WT=	870.7					CUM	WT %	N/A	43.9	64.6	76.0	82.2	87.6	92.2	N/A
270	N/A	H	7.1	34.8	50.2	msG	WT	N/A	497.0	88.3	72.0	50.7	46.5	41.5	N/A	80.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.2	10.1	8.4	5.9	5.4	4.9	N/A
SPLIT	WT=	860.9					CUM	WT %	N/A	58.2	88.3	76.7	82.6	88.1	92.9	N/A
275	N/A	H	3.0	78.3	18.7	gS	WT	N/A	143.3	131.0	177.2	149.4	101.5	39.7	N/A	23.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.7	17.2	23.1	19.6	13.3	5.2	N/A
SPLIT	WT=	765.7					CUM	WT %	N/A	18.7	35.9	59.0	78.5	91.8	97.0	N/A
280	N/A	H	18.5	79.9	1.5	(m)S	WT	N/A	9.3	20.5	39.4	89.0	180.7	164.0	N/A	114.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	1.5	3.3	8.4	14.4	29.3	26.8	N/A
SPLIT	WT=	618.2					CUM	WT %	N/A	1.5	4.8	11.2	25.6	54.9	81.5	N/A
285	N/A	H	11.7	71.0	16.4	(m)gS	WT	N/A	137.1	88.9	132.8	181.8	210.5	7.0	N/A	98.0
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	16.4	8.2	15.9	21.7	25.2	0.9	N/A
SPLIT	WT=	844.3					CUM	WT %	N/A	16.4	24.6	40.5	62.2	87.4	88.3	N/A
290	N/A	H	10.3	68.7	21.0	(m)gS	WT	N/A	147.6	125.2	145.5	103.8	88.8	39.6	N/A	72.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.0	17.8	20.7	14.8	9.8	5.6	N/A
SPLIT	WT=	703.3					CUM	WT %	N/A	21.0	38.8	59.5	74.3	84.1	89.7	N/A

J.37

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 1

**** REPORT ON WELL B299-E32-B03 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	N/	9.0	40.0	51.0	msG	WT	N/A	205.2	32.6	65.6	54.0	39.0	40.0	N/A	52.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.0	5.6	11.3	9.3	6.0	N/A	9.0
SPLIT	WT=	587.0						CUM WT %	N/A	51.0	50.0	67.2	84.1	91.0	N/A	100.0
10	N/A	H	12.3	48.2	41.5	msG	WT	N/A	366.7	60.3	85.1	94.9	74.2	67.1	N/A	100.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.0	9.8	9.0	10.8	8.4	N/A	12.3
SPLIT	WT=	570.0						CUM WT %	N/A	41.0	51.3	61.0	71.7	80.1	N/A	100.0
15	N/A	H	8.6	36.4	50.1	msG	WT	N/A	533.5	92.6	70.4	75.9	50.0	37.1	N/A	50.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.1	9.0	8.6	0.3	5.5	N/A	8.6
SPLIT	WT=	810.0						CUM WT %	N/A	50.1	67.1	75.7	83.9	89.5	N/A	100.0
20	N/A	H	0.4	50.4	34.2	msG	WT	N/A	287.1	110.7	107.0	110.4	80.5	40.0	N/A	70.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.2	13.9	12.0	14.2	10.7	N/A	0.4
SPLIT	WT=	055.4						CUM WT %	N/A	34.2	48.1	60.9	75.1	85.8	N/A	100.0
25	N/A	H	11.4	44.9	43.7	msG	WT	N/A	384.1	93.6	74.7	97.2	77.5	61.8	N/A	100.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	10.0	8.6	11.1	8.0	N/A	11.4
SPLIT	WT=	883.3						CUM WT %	N/A	43.7	54.4	62.9	73.9	82.7	N/A	100.0
30	N/A	H	7.5	41.0	50.0	msG	WT	N/A	400.0	90.2	90.5	107.0	71.0	37.3	N/A	72.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	9.4	9.5	11.3	7.5	N/A	7.5
SPLIT	WT=	062.0						CUM WT %	N/A	50.0	50.3	60.0	81.0	88.6	N/A	100.0
35	N/A	H	0.1	60.0	33.0	msG	WT	N/A	205.0	191.0	130.5	90.3	40.5	27.4	N/A	40.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.0	23.9	18.2	11.2	6.2	N/A	0.1
SPLIT	WT=	880.3						CUM WT %	N/A	33.0	50.9	73.1	84.4	90.5	N/A	100.0
40	N/A	H	4.4	56.1	40.5	msG	WT	N/A	323.1	180.0	125.3	80.5	38.3	23.5	N/A	36.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.5	23.4	15.7	0.3	4.0	N/A	4.4
SPLIT	WT=	795.7						CUM WT %	N/A	40.5	63.0	79.5	87.9	92.7	N/A	100.0
45	N/A	H	0.1	40.2	43.7	msG	WT	N/A	384.2	120.0	93.2	91.4	70.2	30.3	N/A	71.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	14.4	10.0	10.4	0.7	N/A	0.1
SPLIT	WT=	000.4						CUM WT %	N/A	43.7	50.1	60.7	79.1	87.7	N/A	100.0
50	N/A	H	0.1	40.0	51.0	msG	WT	N/A	467.7	130.0	74.3	60.5	50.0	30.1	N/A	72.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.3	16.3	8.3	0.6	4.1	N/A	0.1
SPLIT	WT=	002.2						CUM WT %	N/A	51.3	66.0	74.0	81.5	87.0	N/A	100.0
55	N/A	H	0.0	44.1	47.0	msG	WT	N/A	404.3	109.0	87.7	80.1	44.0	10.0	N/A	75.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.0	10.7	10.2	7.9	1.2	N/A	0.0
SPLIT	WT=	005.3						CUM WT %	N/A	47.0	60.7	76.0	84.0	89.9	N/A	100.0

U.39

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0299-E32-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	H	4.7	68.7	26.6	gS	WT	N/A	220.9	260.1	167.9	67.6	47.4	19.1	N/A	39.1
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	26.6	32.4	20.2	8.1	5.7	2.3	N/A
SPLIT	WT=	830.0						CUM WT %	N/A	26.6	69.0	79.2	87.3	93.0	95.3	N/A
65	N/A	H	8.0	75.9	16.1	gS	WT	N/A	157.0	206.6	201.2	69.8	67.0	22.3	N/A	52.1
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.1	32.2	23.1	10.3	7.7	2.0	N/A
SPLIT	WT=	860.4						CUM WT %	N/A	10.1	50.3	73.6	83.6	91.5	94.0	N/A
70	N/A	H	4.4	78.7	16.8	gS	WT	N/A	136.3	179.1	242.3	120.5	54.4	20.4	N/A	35.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.8	22.3	30.2	16.0	8.0	3.6	N/A
SPLIT	WT=	800.0						CUM WT %	N/A	18.8	39.1	69.3	85.3	92.1	95.6	N/A
75	N/A	C	7.7	83.4	8.9	(g)S	WT	N/A	79.4	207.1	286.4	104.2	60.4	60.0	N/A	60.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.9	23.2	32.0	11.7	7.7	9.0	N/A
SPLIT	WT=	894.7						CUM WT %	N/A	8.9	32.1	64.0	75.7	83.4	92.3	N/A
80	N/A	C	3.4	83.9	12.7	gS	WT	N/A	80.0	196.6	192.9	60.4	57.6	26.6	N/A	21.7
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	12.7	30.9	30.3	9.5	9.1	4.2	N/A
SPLIT	WT=	831.3						CUM WT %	N/A	12.7	43.5	73.8	83.3	92.4	96.6	N/A
85	N/A	C	1.4	83.4	15.2	gS	WT	N/A	106.7	241.0	260.0	55.0	17.5	9.5	N/A	10.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	15.2	34.5	37.2	8.0	2.5	1.2	N/A
SPLIT	WT=	700.0						CUM WT %	N/A	15.2	49.7	86.9	94.9	97.4	98.6	N/A
90	N/A	C	2.2	94.3	3.5	S	WT	N/A	25.7	243.6	308.6	94.4	29.6	13.5	N/A	15.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.5	33.4	42.1	13.0	4.1	1.0	N/A
SPLIT	WT=	730.3						CUM WT %	N/A	3.5	36.9	79.0	91.9	98.0	97.0	N/A
95	N/A	C	2.1	93.5	4.4	S	WT	N/A	32.0	194.2	351.7	90.4	20.4	13.2	N/A	15.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.4	26.8	48.5	12.5	3.9	1.8	N/A
SPLIT	WT=	726.1						CUM WT %	N/A	4.4	31.2	79.7	92.1	96.1	97.9	N/A
100	N/A	C	1.3	90.0	8.1	(g)S	WT	N/A	58.1	168.4	310.4	113.4	25.6	9.2	N/A	9.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.1	24.3	44.8	10.4	3.7	1.3	N/A
SPLIT	WT=	803.6						CUM WT %	N/A	8.1	32.4	77.3	93.6	97.3	99.7	N/A
105	N/A	C	3.5	92.8	3.7	S	WT	N/A	24.1	64.5	233.9	216.2	70.1	23.6	N/A	22.0
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.7	9.6	35.7	33.0	10.7	2.0	N/A
SPLIT	WT=	857.0						CUM WT %	N/A	3.7	13.5	49.2	82.2	92.9	96.5	N/A
110	N/A	C	3.3	94.0	1.8	S	WT	N/A	12.5	53.1	191.2	278.8	104.9	25.9	N/A	22.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.8	7.7	27.8	40.5	15.2	3.0	N/A
SPLIT	WT=	690.0						CUM WT %	N/A	1.8	9.5	37.3	77.7	93.0	96.7	N/A

J.40

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0289-E32-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	N/A	C	10.0	88.0	0.3	(m)S	WT	N/A	1.9	7.2	40.4	151.1	238.0	114.9	N/A	86.9
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.3	1.2	8.6	24.3	38.4	N/A	10.0
SPLIT	WT=	821.2					CUM	WT %	N/A	0.3	1.5	8.0	32.9	70.7	N/A	100.0
120	N/A	C	12.0	87.0	0.0	(m)S	WT	N/A	0.2	2.1	73.7	190.8	213.7	90.2	N/A	70.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.3	11.2	29.1	32.0	N/A	12.1
SPLIT	WT=	857.7					CUM	WT %	N/A	0.0	0.4	11.6	40.7	73.3	N/A	100.0
125	N/A	C	5.1	73.2	21.7	gS	WT	N/A	107.0	270.8	194.1	80.4	32.9	18.0	N/A	39.7
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.7	29.0	25.1	11.6	4.8	N/A	6.1
SPLIT	WT=	772.3					CUM	WT %	N/A	21.7	51.5	78.0	88.2	92.4	N/A	100.0
130	N/A	C	10.5	83.7	5.7	(gm)S	WT	N/A	44.2	137.6	280.5	90.6	66.3	62.0	N/A	81.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.0	17.9	36.5	12.0	8.6	N/A	18.5
SPLIT	WT=	777.0					CUM	WT %	N/A	5.0	23.8	60.1	72.7	81.3	N/A	100.0
135	N/A	C	3.3	90.3	0.4	(g)S	WT	N/A	35.0	103.7	202.4	126.4	57.9	19.0	N/A	18.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.4	10.4	35.9	22.3	10.3	N/A	3.3
SPLIT	WT=	550.0					CUM	WT %	N/A	0.4	24.0	60.7	83.0	93.3	N/A	100.0
140	N/A	C	8.7	92.5	0.0	S	WT	N/A	5.0	91.0	302.1	100.7	78.5	39.9	N/A	49.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.0	12.0	41.5	22.1	10.0	N/A	0.0
SPLIT	WT=	720.0					CUM	WT %	N/A	0.0	13.4	54.9	77.0	87.8	N/A	100.0
145	N/A	C	0.0	80.0	2.0	S	WT	N/A	18.5	92.5	269.0	151.0	75.2	48.3	N/A	63.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.0	12.9	37.6	21.1	10.5	N/A	0.0
SPLIT	WT=	710.0					CUM	WT %	N/A	2.0	15.4	52.9	74.0	84.5	N/A	100.0
147	N/A	C	7.4	80.3	3.2	S	WT	N/A	20.2	101.5	234.2	127.5	59.3	35.4	N/A	40.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.2	10.3	37.5	20.4	9.5	N/A	7.4
SPLIT	WT=	821.0					CUM	WT %	N/A	3.2	19.5	57.0	77.4	80.0	N/A	100.0
150	N/A	C	11.1	87.3	1.5	(m)S	WT	N/A	9.0	54.9	200.0	103.2	89.3	49.0	N/A	71.0
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.0	0.0	31.4	25.5	14.0	N/A	11.1
SPLIT	WT=	830.2					CUM	WT %	N/A	1.0	10.1	41.6	67.1	81.1	N/A	100.0
155	N/A	C	5.5	93.7	0.0	S	WT	N/A	4.0	10.4	95.3	290.7	124.5	20.1	N/A	32.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	2.0	10.1	40.1	21.0	N/A	5.5
SPLIT	WT=	590.0					CUM	WT %	N/A	0.0	3.0	19.7	60.7	80.7	N/A	100.0
160	N/A	C	4.1	95.0	0.2	S	WT	N/A	0.5	4.4	29.1	150.0	84.0	16.4	N/A	12.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	1.4	9.4	40.0	30.7	N/A	4.1
SPLIT	WT=	307.5					CUM	WT %	N/A	0.2	1.0	11.0	50.0	90.0	N/A	100.0

U.41

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0200-E32-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (<=-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAH (>4.75)
166	N/A	C	8.0	91.6	0.3	S	WT	N/A	2.2	6.3	48.6	288.7	188.1	49.2	N/A	50.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	0.0	7.7	45.8	29.7	7.8	N/A
SPLIT	WT=	631.5						CUM WT %	N/A	0.4	1.2	0.9	54.5	84.2	92.0	N/A
170	N/A	C	7.7	92.0	0.2	S	WT	N/A	1.4	1.3	13.0	171.4	273.0	92.3	N/A	48.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	0.2	2.2	28.8	45.8	15.4	N/A
SPLIT	WT=	597.1						CUM WT %	N/A	0.2	0.5	2.6	31.3	76.9	92.3	N/A
175	N/A	C	8.2	91.7	0.0	S	WT	N/A	0.2	3.2	18.5	188.1	264.7	22.2	N/A	44.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.6	3.1	34.0	49.1	4.1	N/A
SPLIT	WT=	548.0						CUM WT %	N/A	0.0	0.6	3.7	38.6	87.7	91.0	N/A
180	N/A	C	4.0	94.8	0.4	S	WT	N/A	2.3	1.4	2.3	90.8	366.6	72.7	N/A	28.9
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	0.3	0.4	16.2	65.1	12.9	N/A
SPLIT	WT=	558.8						CUM WT %	N/A	0.4	0.7	1.1	17.2	62.3	95.2	N/A
185	N/A	C	10.3	81.8	0.2	(m)S	WT	N/A	0.9	1.3	0.0	50.5	389.6	19.1	N/A	103.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	0.2	0.0	9.0	89.0	3.4	N/A
SPLIT	WT=	671.4						CUM WT %	N/A	0.2	0.4	0.4	9.3	78.4	81.7	N/A
190	N/A	C	10.4	89.2	0.0	(m)S	WT	N/A	0.0	0.2	0.0	10.1	144.8	89.4	N/A	28.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.1	0.0	3.7	59.1	32.8	N/A
SPLIT	WT=	273.9						CUM WT %	N/A	0.0	0.1	0.1	3.8	58.9	89.6	N/A
195	N/A	C	3.5	83.1	33.4	gG	WT	N/A	271.0	144.0	144.7	52.0	115.1	57.2	N/A	28.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.4	17.0	17.0	8.4	14.1	7.0	N/A
SPLIT	WT=	813.7						CUM WT %	N/A	33.4	61.2	60.9	75.3	89.5	98.6	N/A
200	N/A	C	8.0	70.5	20.0	(m)gS	WT	N/A	142.7	145.7	152.5	78.0	59.6	41.4	N/A	61.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.0	21.1	23.5	11.4	0.6	0.0	N/A
SPLIT	WT=	622.6						CUM WT %	N/A	20.6	41.7	65.2	76.5	85.2	91.1	N/A
205	N/A	C	7.0	78.7	21.6	gS	WT	N/A	163.9	152.4	168.1	85.9	58.5	41.7	N/A	56.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	21.6	21.3	23.2	12.0	8.4	5.8	N/A
SPLIT	WT=	715.8						CUM WT %	N/A	21.5	42.8	65.9	77.9	86.4	92.2	N/A
210	N/A	C	2.9	45.4	51.7	gG	WT	N/A	360.0	124.9	104.0	40.8	24.5	15.9	N/A	20.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.7	17.9	14.9	6.7	3.5	2.3	N/A
SPLIT	WT=	693.7						CUM WT %	N/A	51.7	69.5	84.6	91.3	94.6	97.1	N/A
215	N/A	C	4.5	47.8	47.7	gG	WT	N/A	364.4	103.4	104.3	44.2	32.1	80.8	N/A	34.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.7	13.5	13.7	5.8	4.2	10.6	N/A
SPLIT	WT=	783.1						CUM WT %	N/A	47.7	61.3	74.9	80.7	84.9	95.6	N/A

J.42

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 5

**** REPORT ON WELL 0299-E32-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
220	N/A	C	3.0	38.9	58.1	msG	WT	N/A	447.1	103.4	93.7	52.2	30.4	19.5	N/A	22.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.1	13.4	12.2	8.8	4.0	2.5	N/A	3.0
SPLIT	WT=	778.7					CUM	WT %	N/A	58.1	71.6	83.8	90.6	94.5	97.0	N/A	100.0
225	N/A	C	8.5	42.4	51.1	msG	WT	N/A	410.5	117.0	88.8	58.5	45.4	31.7	N/A	52.2	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.1	14.7	11.1	7.0	5.7	4.0	N/A	6.5
SPLIT	WT=	801.4					CUM	WT %	N/A	51.1	65.8	76.9	83.9	89.6	93.5	N/A	100.0
230	N/A	C	8.7	30.0	52.3	msG	WT	N/A	428.0	110.2	76.9	50.7	47.4	34.8	N/A	71.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.3	13.4	9.4	6.2	5.8	4.2	N/A	8.7
SPLIT	WT=	817.4					CUM	WT %	N/A	52.3	65.7	76.1	81.3	87.0	91.3	N/A	100.0
235	N/A	C	4.8	25.1	70.1	msG	WT	N/A	555.2	89.9	58.0	30.0	21.5	20.0	N/A	37.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	70.1	8.0	7.2	3.9	2.7	2.6	N/A	4.0
SPLIT	WT=	792.6					CUM	WT %	N/A	70.1	79.0	86.1	90.0	92.7	95.2	N/A	100.0
240	N/A	C	15.0	54.1	31.0	msG	WT	N/A	218.4	93.3	83.1	74.0	67.5	53.8	N/A	105.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	13.2	11.8	10.5	9.0	N/A	16.0	
SPLIT	WT=	703.5					CUM	WT %	N/A	31.0	44.2	55.0	65.4	70.0	85.0	N/A	100.0
245	N/A	C	9.5	80.4	10.0	(m)gS	WT	N/A	76.0	80.6	143.0	124.3	150.0	100.7	N/A	71.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	10.1	11.6	19.0	18.5	20.0	13.4	N/A	9.5
SPLIT	WT=	758.9					CUM	WT %	N/A	10.1	21.0	40.6	57.1	77.1	90.6	N/A	100.0
250	N/A	C	7.9	35.2	56.9	msG	WT	N/A	421.1	80.0	54.0	51.0	40.9	39.4	N/A	58.4	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	56.9	9.3	7.3	7.0	6.3	6.2	N/A	7.9
SPLIT	WT=	734.0					CUM	WT %	N/A	56.9	66.2	73.5	80.5	86.0	92.1	N/A	100.0
255	N/A	C	12.5	37.9	49.7	msG	WT	N/A	371.7	65.2	59.5	53.0	50.7	48.3	N/A	93.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.7	8.7	8.0	7.2	7.8	6.5	N/A	12.5
SPLIT	WT=	740.4					CUM	WT %	N/A	49.7	58.4	66.3	73.5	81.1	87.6	N/A	100.0
260	N/A	H	10.0	40.5	48.7	msG	WT	N/A	341.0	60.7	53.4	62.5	59.3	42.1	N/A	78.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.7	9.5	7.5	8.9	8.5	8.0	N/A	10.9
SPLIT	WT=	700.5					CUM	WT %	N/A	48.7	59.2	65.0	74.7	83.1	89.1	N/A	100.0
265	N/A	H	10.0	44.5	38.9	msG	WT	N/A	287.8	81.3	60.3	83.4	83.0	16.0	N/A	122.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.9	11.0	9.0	11.3	11.2	2.0	N/A	10.0
SPLIT	WT=	740.8					CUM	WT %	N/A	38.9	49.9	59.9	70.2	81.4	83.4	N/A	100.0
270	N/A	H	11.0	47.2	41.0	msG	WT	N/A	327.7	72.8	66.9	73.4	109.2	55.7	N/A	94.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.0	9.1	8.4	9.2	13.7	7.0	N/A	11.0
SPLIT	WT=	799.4					CUM	WT %	N/A	41.0	50.1	60.4	67.6	81.2	88.2	N/A	100.0

J.43

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 8

**** REPORT ON WELL 0299-E32-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (34.75)	
275	N/A	H	9.0	85.9	5.2	(g)S	WT	N/A	40.6	105.3	217.7	135.0	80.1	54.9	N/A	70.2	
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.2	23.6	27.0	17.2	10.2	7.0	N/A	9.0
SPLIT	WT=	780.8						CUM WT %	N/A	5.2	28.8	50.0	73.8	84.0	91.0	N/A	100.0
280	N/A	H	8.1	35.0	55.9	msG	WT	N/A	475.9	127.1	60.1	41.0	46.0	22.2	N/A	77.0	
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.9	14.9	7.1	4.9	5.5	2.6	N/A	9.1
SPLIT	WT=	857.0						CUM WT %	N/A	55.9	70.0	77.9	82.8	86.3	90.5	N/A	100.0
285	N/A	H	3.7	92.4	3.9	S	WT	N/A	14.5	31.1	88.0	135.6	72.1	19.3	N/A	13.0	
SDRT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.9	8.3	23.5	30.2	19.3	5.2	N/A	3.7
SPLIT	WT=	301.2						CUM WT %	N/A	3.9	12.2	35.7	71.9	91.2	96.3	N/A	100.0
290	N/A	H	13.0	83.9	3.1	(m)S	WT	N/A	9.2	15.3	20.3	52.8	84.9	87.4	N/A	30.8	
SDRT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	3.1	5.1	9.9	17.7	28.5	22.6	N/A	13.0
SPLIT	WT=	302.0						CUM WT %	N/A	3.1	8.2	18.1	35.9	64.3	87.0	N/A	100.0
294	N/A	H	3.3	29.4	67.3	msG	WT	N/A	306.0	30.7	41.7	28.7	10.5	14.1	N/A	15.2	
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	67.3	8.8	9.2	8.3	4.1	3.1	N/A	3.3
SPLIT	WT=	403.8						CUM WT %	N/A	67.3	74.0	83.2	89.5	93.0	96.7	N/A	100.0
300	N/A	H	5.7	82.6	11.8	gS	WT	N/A	44.7	41.3	64.4	127.0	50.2	21.1	N/A	21.5	
SDRT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.8	10.9	17.0	33.0	16.4	5.0	N/A	5.7
SPLIT	WT=	384.3						CUM WT %	N/A	11.8	22.7	39.8	73.4	88.7	94.3	N/A	100.0

U.44

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0290-E22-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
5	N/A	N/	10.0	50.5	25.5	gmS	WT	N/A	159.0	27.9	00.1	34.6	00.0	174.4	N/A	99.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	25.5	4.5	10.0	5.5	0.7	27.9	N/A	10.0
SPLIT	WT=	827.0					CUM	WT %	N/A	25.6	29.9	40.8	46.4	50.1	54.0	N/A	100.0
10	N/A	H	9.5	34.2	50.2	msG	WT	N/A	439.1	59.3	45.0	46.0	45.0	70.7	N/A	74.3	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	56.2	7.0	5.0	5.0	0.1	N/A	9.5	
SPLIT	WT=	777.0					CUM	WT %	N/A	50.2	63.8	69.7	75.7	81.4	90.6	N/A	100.0
15	N/A	H	10.4	40.3	35.3	msG	WT	N/A	284.2	90.0	00.3	02.3	76.0	01.4	N/A	132.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.3	12.4	11.1	7.7	0.4	7.0	N/A	10.4
SPLIT	WT=	803.5					CUM	WT %	N/A	35.3	47.7	50.0	00.5	76.0	03.0	N/A	100.0
20	N/A	H	11.0	40.0	41.3	msG	WT	N/A	345.5	00.1	03.0	00.6	50.0	00.0	N/A	99.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.3	10.7	10.0	11.0	7.0	7.2	N/A	11.0
SPLIT	WT=	841.2					CUM	WT %	N/A	41.3	52.0	02.0	73.0	01.0	00.2	N/A	100.0
25	N/A	H	12.1	40.0	41.3	msG	WT	N/A	357.9	100.3	75.7	05.0	07.2	05.1	N/A	105.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.3	11.0	8.7	11.1	7.0	7.5	N/A	12.1
SPLIT	WT=	804.0					CUM	WT %	N/A	41.3	52.0	01.0	72.0	00.4	07.9	N/A	100.0
30	N/A	H	7.6	41.0	50.0	msG	WT	N/A	400.0	00.2	00.0	107.0	71.0	07.3	N/A	72.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	0.4	0.5	11.3	7.5	0.0	N/A	7.5
SPLIT	WT=	952.0					CUM	WT %	N/A	50.0	00.3	00.0	01.0	00.0	02.5	N/A	100.0
35	N/A	H	0.5	46.2	46.3	msG	WT	N/A	434.0	07.6	127.9	07.6	55.7	30.0	N/A	50.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.3	10.0	14.2	0.7	0.2	4.3	N/A	0.6
SPLIT	WT=	895.3					CUM	WT %	N/A	46.3	59.1	73.3	03.0	00.2	03.5	N/A	100.0
40	N/A	H	7.0	40.0	43.2	msG	WT	N/A	303.7	141.3	03.0	03.0	55.0	30.0	N/A	05.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.2	10.0	11.2	0.0	0.0	4.0	N/A	7.0
SPLIT	WT=	830.0					CUM	WT %	N/A	43.2	00.0	71.2	01.0	07.6	02.2	N/A	100.0
45	N/A	H	5.4	43.7	50.0	msG	WT	N/A	427.0	140.4	03.3	00.0	41.0	20.0	N/A	45.2	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	17.0	0.0	0.0	4.0	3.2	N/A	5.4
SPLIT	WT=	844.0					CUM	WT %	N/A	50.0	00.7	70.0	00.5	01.4	04.0	N/A	100.0
50	N/A	H	0.5	04.3	20.2	gS	WT	N/A	241.5	215.1	135.3	00.1	51.0	30.2	N/A	53.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.2	20.0	10.4	12.0	0.2	3.7	N/A	0.5
SPLIT	WT=	820.0					CUM	WT %	N/A	20.2	55.3	71.0	03.0	00.0	03.5	N/A	100.0
55	N/A	H	5.9	72.0	21.2	gS	WT	N/A	101.1	247.3	203.0	00.2	40.3	33.1	N/A	50.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.2	20.0	23.0	10.5	0.0	3.0	N/A	0.0
SPLIT	WT=	959.2					CUM	WT %	N/A	21.2	50.1	73.9	04.4	00.2	04.1	N/A	100.0

U.45

ROCKWELL MANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E32-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
60	N/A	H	5.2	70.1	10.7	gS	WT	N/A	140.9	242.1	220.0	100.3	65.7	30.9	N/A	44.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.7	20.7	20.1	11.9	7.0	3.7	N/A	5.2
SPLIT	WT= 846.1						CUM WT %	N/A	10.7	45.3	71.5	93.3	91.1	94.0	N/A	100.0	
66	N/A	C	0.7	89.0	30.4	gS	WT	N/A	107.4	203.3	109.0	10.5	0.7	0.2	N/A	4.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	30.4	45.9	17.7	3.0	1.4	1.0	N/A	0.7
SPLIT	WT= 620.1						CUM WT %	N/A	30.4	76.3	93.9	96.9	98.3	99.3	N/A	100.0	
70	N/A	C	1.0	70.7	10.4	gS	WT	N/A	117.0	241.1	100.6	41.0	20.8	10.7	N/A	11.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.4	27.7	30.7	0.4	3.3	1.7	N/A	1.9
SPLIT	WT= 644.0						CUM WT %	N/A	10.4	50.1	80.0	93.2	90.0	90.1	N/A	100.0	
76	N/A	C	1.4	93.1	5.4	(g)S	WT	N/A	32.2	207.1	270.2	40.0	10.0	7.0	N/A	0.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.0	35.0	46.7	0.2	2.0	1.3	N/A	1.4
SPLIT	WT= 500.3						CUM WT %	N/A	5.0	40.5	86.2	94.4	97.3	98.0	N/A	100.0	
80	N/A	C	3.0	95.5	0.9	S	WT	N/A	2.4	11.0	31.4	01.0	111.7	10.3	N/A	0.6	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.9	4.1	11.0	30.7	42.0	0.0	N/A	3.6
SPLIT	WT= 203.5						CUM WT %	N/A	0.9	5.0	10.0	47.0	80.0	90.4	N/A	100.0	
86	N/A	C	1.0	90.0	3.0	S	WT	N/A	10.3	171.1	303.0	30.0	10.4	4.1	N/A	5.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	31.2	65.2	7.1	1.0	0.0	N/A	1.0
SPLIT	WT= 540.0						CUM WT %	N/A	3.0	34.1	80.3	90.4	90.0	90.0	N/A	100.0	
90	N/A	C	2.3	90.3	7.5	(g)S	WT	N/A	20.1	103.1	130.7	25.3	0.0	5.4	N/A	7.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.5	32.3	44.2	0.2	2.0	1.0	N/A	2.3
SPLIT	WT= 300.5						CUM WT %	N/A	7.5	40.0	65.0	93.2	98.0	97.7	N/A	100.0	
96	N/A	C	2.6	93.7	3.0	S	WT	N/A	21.0	130.7	270.0	04.0	20.5	13.2	N/A	14.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	24.4	47.5	14.0	4.7	2.3	N/A	2.6
SPLIT	WT= 505.5						CUM WT %	N/A	3.0	20.2	75.7	90.0	95.2	97.5	N/A	100.0	
100	N/A	C	1.0	90.0	7.5	(g)S	WT	N/A	42.7	170.1	245.0	57.0	00.0	17.2	N/A	11.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.5	20.7	42.0	10.1	5.0	3.0	N/A	1.9
SPLIT	WT= 570.4						CUM WT %	N/A	7.5	37.2	80.0	90.1	95.1	90.3	N/A	100.0	
105	N/A	C	1.0	91.0	7.4	(g)S	WT	N/A	43.4	104.7	217.3	04.1	20.1	11.0	N/A	5.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.4	33.3	37.1	14.4	5.0	1.9	N/A	1.0
SPLIT	WT= 509.7						CUM WT %	N/A	7.4	40.7	77.0	92.2	97.2	99.0	N/A	100.0	
110	N/A	C	1.0	87.3	0.0	S	WT	N/A	5.0	107.0	313.0	120.0	23.0	0.1	N/A	10.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.9	10.2	53.2	20.4	3.0	1.5	N/A	1.0
SPLIT	WT= 507.0						CUM WT %	N/A	0.9	19.1	72.3	92.7	98.0	98.2	N/A	100.0	

J.46

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0209-E32-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	N/A	C	0.8	98.3	3.3	S	WT	N/A	18.9	188.6	251.2	81.8	28.1	7.9	N/A	3.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.1	29.6	46.4	15.1	3.7	N/A	0.8
SPLIT	WT=	548.1						CUM WT %	N/A	3.1	32.0	79.1	94.2	97.9	99.4	100.0
120	N/A	C	2.1	98.5	1.4	S	WT	N/A	7.3	79.4	251.8	142.0	28.8	10.8	N/A	10.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.4	14.0	48.0	27.1	5.6	N/A	2.1
SPLIT	WT=	520.5						CUM WT %	N/A	1.4	15.4	63.4	90.5	96.0	97.9	100.0
125	N/A	C	3.4	95.8	8.8	S	WT	N/A	4.0	1.4	1.4	135.7	279.2	42.0	N/A	10.1
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.8	0.3	0.3	28.3	58.2	8.8	3.4
SPLIT	WT=	473.8						CUM WT %	N/A	0.8	1.1	1.4	29.7	87.9	98.8	100.0
130	N/A	C	3.3	95.8	10.9	gS	WT	N/A	22.8	83.7	77.6	24.1	7.8	4.6	N/A	6.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.9	30.7	37.5	11.8	3.8	N/A	3.3
SPLIT	WT=	206.2						CUM WT %	N/A	10.9	41.7	79.1	98.7	94.5	96.7	100.0
135	N/A	C	3.7	98.4	8.8 (g)	S	WT	N/A	11.4	35.2	55.3	48.7	24.2	7.8	N/A	7.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.0	18.6	34.2	21.3	12.7	N/A	3.7
SPLIT	WT=	189.8						CUM WT %	N/A	6.0	24.4	58.8	80.0	92.7	98.3	100.0
140	N/A	C	1.8	98.4	7.8 (g)	S	WT	N/A	47.7	158.1	225.8	125.8	32.8	11.9	N/A	10.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.8	25.8	37.0	20.8	5.3	N/A	1.8
SPLIT	WT=	606.2						CUM WT %	N/A	7.8	33.4	78.4	91.8	96.3	98.2	100.0
145	N/A	C	2.9	98.0	6.3 (g)	S	WT	N/A	38.3	99.7	229.0	153.8	42.1	18.8	N/A	17.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.3	16.4	37.7	27.0	8.9	N/A	2.9
SPLIT	WT=	607.1						CUM WT %	N/A	6.3	22.7	60.5	87.4	94.4	97.1	100.0
150	N/A	C	1.8	92.0	5.1 (g)	S	WT	N/A	31.2	89.0	248.0	188.2	46.9	13.9	N/A	11.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.1	14.8	48.8	27.7	7.7	N/A	1.8
SPLIT	WT=	602.7						CUM WT %	N/A	5.1	19.8	60.5	88.2	95.9	98.2	100.0
155	N/A	C	2.1	91.9	5.9 (g)	S	WT	N/A	37.2	78.6	262.9	170.3	45.3	20.3	N/A	13.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.9	12.2	42.0	27.2	7.2	N/A	2.1
SPLIT	WT=	632.1						CUM WT %	N/A	5.9	18.2	80.2	87.4	94.0	97.9	100.0
160	N/A	C	7.5	81.8	1.4	S	WT	N/A	3.9	5.8	18.7	82.1	105.8	37.5	N/A	20.6
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	1.4	2.1	5.1	38.2	38.9	13.8	7.5
SPLIT	WT=	271.8						CUM WT %	N/A	1.4	3.6	9.6	39.8	78.7	92.5	100.0
165	N/A	C	8.2	91.3	0.5	S	WT	N/A	1.8	18.8	38.4	108.6	187.9	37.1	N/A	28.9
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.5	3.3	11.7	32.4	32.8	11.3	8.2
SPLIT	WT=	334.4						CUM WT %	N/A	0.5	3.8	15.5	47.8	88.8	91.8	100.0

J.47

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E32-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
170	N/A	C	3.1	96.3	0.6	S	WT	N/A	1.8	10.8	48.5	126.8	89.0	17.0	N/A	9.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.6	3.5	16.4	40.3	31.5	5.8	N/A	3.2
SPLIT	WT=	313.7					CUM	WT %	N/A	0.6	4.0	19.5	59.8	91.3	96.9	N/A	100.0
175	N/A	C	3.0	84.0	12.0	gS	WT	N/A	75.0	95.0	165.8	163.0	88.7	32.5	N/A	24.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.0	15.1	24.3	14.9	6.2	N/A	4.0	
SPLIT	WT=	626.7					CUM	WT %	N/A	12.0	27.1	51.8	76.0	90.9	96.1	N/A	100.0
180	N/A	C	2.7	85.6	11.0	gS	WT	N/A	70.0	131.1	201.1	125.7	78.4	24.5	N/A	17.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.0	20.1	30.8	19.2	11.7	3.0	N/A	2.7
SPLIT	WT=	650.3					CUM	WT %	N/A	11.0	31.0	62.0	81.9	93.8	97.3	N/A	100.0
185	N/A	C	15.9	79.4	4.6	(m)S	WT	N/A	27.0	128.0	193.8	67.4	36.5	48.7	N/A	92.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.0	22.0	33.3	9.0	8.0	N/A	16.0	
SPLIT	WT=	580.6					CUM	WT %	N/A	4.0	26.8	69.9	89.8	78.0	84.0	N/A	100.0
190	N/A	C	3.6	82.0	13.5	gS	WT	N/A	89.1	153.1	190.4	93.8	67.7	34.0	N/A	23.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.5	23.2	30.1	14.2	10.3	5.2	N/A	3.0
SPLIT	WT=	658.2					CUM	WT %	N/A	13.5	38.7	68.7	80.9	91.2	98.4	N/A	100.0
195	N/A	C	3.5	84.0	12.5	gS	WT	N/A	88.8	215.8	246.8	76.1	37.0	22.3	N/A	25.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.5	30.4	34.6	10.0	5.3	3.1	N/A	3.6
SPLIT	WT=	700.9					CUM	WT %	N/A	12.5	42.0	77.4	85.0	93.3	98.5	N/A	100.0
200	N/A	C	3.3	50.1	48.7	sG	WT	N/A	345.3	158.4	127.7	44.1	28.7	15.8	N/A	24.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.7	21.1	17.3	8.0	3.6	2.1	N/A	3.3
SPLIT	WT=	737.4					CUM	WT %	N/A	40.7	67.8	85.0	91.0	94.6	98.7	N/A	100.0
210	N/A	C	4.1	70.0	26.3	gS	WT	N/A	106.1	110.0	178.8	66.2	40.0	31.1	N/A	26.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	25.3	17.0	27.4	13.5	7.2	4.0	N/A	4.1
SPLIT	WT=	661.4					CUM	WT %	N/A	25.3	43.1	70.5	84.0	91.1	96.9	N/A	100.0
215	N/A	C	6.8	63.1	31.3	sG	WT	N/A	114.2	94.8	73.0	32.6	17.0	11.9	N/A	20.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.3	20.0	20.0	0.9	4.9	3.3	N/A	5.0
SPLIT	WT=	382.2					CUM	WT %	N/A	31.3	67.3	77.3	88.3	91.1	94.4	N/A	100.0
220	N/A	C	3.8	62.4	43.8	sg	WT	N/A	185.5	79.7	70.0	26.3	13.4	6.1	N/A	14.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.8	21.1	18.7	7.0	3.0	2.1	N/A	3.8
SPLIT	WT=	376.3					CUM	WT %	N/A	43.8	64.9	83.0	90.5	94.1	98.2	N/A	100.0
225	N/A	C	21.8	70.0	0.3	mS	WT	N/A	1.4	1.2	0.4	1.8	09.4	205.5	N/A	112.0	
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.3	0.2	0.1	0.4	10.3	58.0	N/A	21.8
SPLIT	WT=	514.7					CUM	WT %	N/A	0.3	0.6	0.0	0.9	20.2	70.2	N/A	100.0

J.48

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0290-E32-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
230	N/A	C	14.5	79.4	6.1	(gm)S	WT	N/A	20.8	14.4	14.4	5.7	127.0	107.2	N/A	48.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	8.2	4.3	1.7	37.5	31.7	N/A	14.5
SPLIT	WT=	337.0						CUM WT %	N/A	8.2	10.4	14.7	18.4	53.9	65.6	100.0
235	N/A	H	0.4	50.2	40.4	msG	WT	N/A	371.8	113.9	97.9	89.1	81.0	79.0	N/A	86.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.4	12.4	10.6	9.7	8.0	8.7	N/A
SPLIT	WT=	926.6						CUM WT %	N/A	40.4	52.8	63.4	73.1	81.9	90.6	100.0
240	N/A	H	2.4	43.2	54.4	sg	WT	N/A	408.3	90.5	152.1	79.5	32.3	10.1	N/A	20.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.4	10.5	17.7	9.2	3.0	2.1	N/A
SPLIT	WT=	862.8						CUM WT %	N/A	54.4	64.9	82.6	91.7	95.5	97.6	100.0
245	N/A	H	10.2	49.5	40.2	msG	WT	N/A	345.1	100.7	133.0	76.4	62.7	51.8	N/A	87.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.2	11.7	15.0	9.9	7.3	8.0	N/A
SPLIT	WT=	855.7						CUM WT %	N/A	40.2	52.0	67.6	78.5	83.8	89.0	100.0
250	N/A	H	0.8	47.5	43.0	msG	WT	N/A	305.5	93.0	89.0	80.1	60.0	60.7	N/A	86.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	10.5	10.0	9.0	9.7	7.0	N/A
SPLIT	WT=	903.2						CUM WT %	N/A	43.0	53.4	63.4	73.0	82.7	90.4	100.0
255	N/A	H	10.3	53.4	30.2	msG	WT	N/A	300.0	187.4	110.7	89.4	77.3	61.0	N/A	87.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.3	12.7	13.8	10.0	9.1	7.2	N/A
SPLIT	WT=	851.3						CUM WT %	N/A	30.3	49.0	62.8	73.3	82.5	89.7	100.0
260	N/A	H	0.2	30.0	55.0	msG	WT	N/A	437.5	70.8	55.0	50.2	40.2	42.4	N/A	64.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.0	10.2	7.1	7.4	5.9	5.4	N/A
SPLIT	WT=	780.4						CUM WT %	N/A	55.0	65.0	73.0	80.5	88.4	91.0	100.0
265	N/A	H	8.4	74.1	19.5	ps	WT	N/A	135.0	100.1	112.0	123.3	115.0	50.0	N/A	44.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	19.5	10.2	10.2	17.7	18.8	8.5	N/A
SPLIT	WT=	892.4						CUM WT %	N/A	19.5	34.7	50.9	68.0	85.2	93.0	100.0
270	N/A	H	11.4	49.0	39.0	msG	WT	N/A	342.1	100.0	91.7	92.3	83.9	65.5	N/A	90.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.0	11.8	9.5	10.7	9.7	7.0	N/A
SPLIT	WT=	858.4						CUM WT %	N/A	39.0	51.2	60.0	71.3	81.0	88.5	100.0
275	N/A	H	12.7	45.4	42.0	msG	WT	N/A	285.7	65.3	50.0	75.0	54.0	54.2	N/A	86.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	9.6	8.7	11.1	8.1	8.0	N/A
SPLIT	WT=	882.2						CUM WT %	N/A	42.0	51.0	60.2	71.3	79.4	87.3	100.0
280	N/A	H	9.8	46.0	43.0	msG	WT	N/A	312.0	89.0	85.0	70.4	50.4	43.1	N/A	70.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	12.5	9.2	10.0	8.3	8.0	N/A
SPLIT	WT=	713.0						CUM WT %	N/A	43.0	50.1	65.3	75.9	84.2	90.2	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0200-E32-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
285	N/A	H	7.8	79.7	12.7	gS	WT	N/A	85.0	84.1	104.4	124.5	143.3	82.3	N/A	51.8
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	12.7	12.4	15.5	18.4	21.2	N/A	7.6
SPLIT	WT=	872.3						CUM WT %	N/A	12.7	25.1	40.6	59.0	80.2	N/A	100.0
290	N/A	H	5.8	45.9	49.3	msG	WT	N/A	393.0	159.4	57.4	83.1	82.9	32.3	N/A	47.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.3	19.4	7.0	7.7	4.0	N/A	5.8
SPLIT	WT=	813.0						CUM WT %	N/A	48.3	67.7	74.8	82.5	90.2	N/A	100.0
295	N/A	H	8.2	53.7	38.0	msG	WT	N/A	381.7	107.5	77.8	116.5	120.0	88.1	N/A	78.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.1	11.3	8.2	12.3	9.3	N/A	8.3
SPLIT	WT=	650.6						CUM WT %	N/A	38.1	49.4	57.5	69.9	82.5	N/A	100.0
298	N/A	H	5.7	92.8	0.7	S	WT	N/A	3.8	7.7	46.8	189.8	204.8	47.3	N/A	30.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.7	1.5	8.0	36.7	8.0	N/A	5.7
SPLIT	WT=	625.7						CUM WT %	N/A	0.7	2.2	11.0	46.7	85.4	N/A	100.0
300	N/A	H	8.4	50.6	35.0	msG	WT	N/A	269.0	95.3	95.0	90.5	93.7	60.2	N/A	64.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.0	12.4	12.5	11.0	12.2	N/A	8.4
SPLIT	WT=	774.8						CUM WT %	N/A	35.0	47.4	59.8	71.0	83.0	N/A	100.0
305	N/A	H	8.4	70.8	20.7	(m)gS	WT	N/A	140.5	57.7	60.7	173.7	139.3	75.0	N/A	50.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	20.7	8.1	8.5	24.3	19.5	N/A	8.5
SPLIT	WT=	717.9						CUM WT %	N/A	20.7	28.8	37.3	61.6	81.0	N/A	100.0
310	N/A	H	5.0	73.6	21.3	gS	WT	N/A	105.1	61.5	47.1	273.4	140.8	47.1	N/A	39.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	21.3	8.0	5.1	35.3	18.2	N/A	5.0
SPLIT	WT=	770.8						CUM WT %	N/A	21.3	29.3	35.4	70.7	88.9	N/A	100.0

7.50

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0289-E33-028 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	N/A	N/	5.0	54.2	40.8	sg	WT	N/A	351.4	154.5	139.0	88.9	44.3	82.9	N/A	43.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	17.9	10.1	7.8	6.1	7.3	N/A	5.0
SPLIT	WT=	862.3					CUM	WT %	N/A	40.8	56.7	74.8	82.8	97.7	95.0	N/A	100.0
10	N/A	H	10.7	82.0	27.3	(m) gS	WT	N/A	252.4	118.4	177.0	122.3	85.2	69.4	N/A	98.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.3	12.0	19.2	13.2	9.2	7.5	N/A	10.7
SPLIT	WT=	924.5					CUM	WT %	N/A	27.3	40.1	59.3	72.8	91.0	89.3	N/A	100.0
15	N/A	H	5.5	83.6	11.1	gS	WT	N/A	91.8	182.5	282.2	135.2	58.9	32.3	N/A	45.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.1	22.0	34.1	18.3	7.1	3.9	N/A	5.5
SPLIT	WT=	838.1					CUM	WT %	N/A	11.1	33.1	67.2	89.5	96.8	94.6	N/A	100.0
20	N/A	H	7.0	23.4	69.6	msG	WT	N/A	587.0	56.5	43.3	41.5	38.4	28.8	N/A	59.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	69.6	8.7	5.1	4.0	3.6	3.1	N/A	7.0
SPLIT	WT=	852.3					CUM	WT %	N/A	69.6	76.3	81.4	88.3	99.9	93.0	N/A	100.0
25	N/A	H	12.4	59.2	28.4	(m) gS	WT	N/A	245.2	188.5	95.8	123.3	122.1	64.5	N/A	107.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.4	12.3	11.1	14.3	14.1	7.5	N/A	12.4
SPLIT	WT=	855.0					CUM	WT %	N/A	28.4	40.7	51.7	66.0	80.1	67.6	N/A	100.0
30	N/A	H	5.0	87.2	27.8	gS	WT	N/A	214.3	212.1	158.8	83.3	44.1	27.3	N/A	38.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.8	27.8	19.6	10.8	5.7	3.6	N/A	5.0
SPLIT	WT=	773.0					CUM	WT %	N/A	27.8	55.4	74.9	85.8	91.5	95.0	N/A	100.0
35	N/A	H	6.7	77.5	15.7	gS	WT	N/A	125.8	221.4	228.2	90.2	49.2	29.3	N/A	53.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	15.0	27.7	28.7	11.3	6.2	3.7	N/A	6.7
SPLIT	WT=	785.2					CUM	WT %	N/A	15.0	43.5	72.2	83.4	89.6	93.3	N/A	100.0
40	N/A	H	5.5	87.7	8.7	(g) S	WT	N/A	63.4	283.4	385.1	91.1	70.5	25.5	N/A	44.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.7	25.7	38.5	11.5	8.9	3.2	N/A	5.0
SPLIT	WT=	793.2					CUM	WT %	N/A	8.7	32.4	70.9	82.3	91.2	94.6	N/A	100.0
45	N/A	H	5.1	87.0	7.9	(g) S	WT	N/A	88.3	241.9	287.8	109.7	81.3	36.5	N/A	44.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.9	27.8	33.1	12.0	9.4	4.2	N/A	5.1
SPLIT	WT=	885.2					CUM	WT %	N/A	7.9	35.7	68.7	81.3	90.7	94.9	N/A	100.0
50	N/A	H	5.0	80.6	5.3	(g) S	WT	N/A	42.6	187.0	288.4	155.8	88.7	34.8	N/A	48.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.3	21.0	38.0	19.7	8.6	4.4	N/A	5.1
SPLIT	WT=	790.0					CUM	WT %	N/A	5.3	26.3	62.3	82.0	90.6	95.0	N/A	100.0
55	N/A	H	4.5	90.4	5.1	(g) S	WT	N/A	37.0	90.3	245.9	214.1	73.0	29.0	N/A	32.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.1	12.5	34.0	29.0	19.2	4.1	N/A	4.5
SPLIT	WT=	720.0					CUM	WT %	N/A	5.1	17.0	51.5	81.2	91.4	95.5	N/A	100.0

7.51

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0299-E33-020 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (<= -2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	M	3.0	88.9	16.5	gS	WT	N/A	110.7	164.9	233.6	142.1	59.9	30.3	N/A	27.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	16.5	20.2	30.4	10.6	7.6	4.0	3.0
SPLIT	WT=	770.9						CUM WT %	N/A	16.5	36.7	66.1	84.7	92.6	98.4	100.0
85	N/A	C	0.7	88.8	12.6	gS	WT	N/A	86.1	208.4	284.0	72.0	19.1	9.6	N/A	6.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.6	30.6	41.0	10.6	2.8	1.4	0.7
SPLIT	WT=	688.2						CUM WT %	N/A	12.6	43.0	84.6	95.1	97.9	99.3	100.0
70	N/A	C	1.4	96.2	3.4	S	WT	N/A	20.1	98.9	161.3	195.7	88.0	30.0	N/A	0.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.4	10.7	26.6	33.0	16.0	6.1	1.4
SPLIT	WT=	591.0						CUM WT %	N/A	3.4	20.1	46.0	70.6	93.5	98.0	100.0
75	N/A	C	0.7	90.7	2.0	S	WT	N/A	10.3	84.0	376.1	124.0	18.3	6.0	N/A	4.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.0	13.6	50.8	19.8	2.9	0.8	0.7
SPLIT	WT=	526.9						CUM WT %	N/A	2.0	16.1	76.9	96.0	98.6	99.3	100.0
80	N/A	C	1.2	94.4	4.4	S	WT	N/A	27.4	188.0	283.8	88.4	22.6	8.6	N/A	7.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.4	30.0	46.3	14.1	3.6	1.4	1.2
SPLIT	WT=	624.1						CUM WT %	N/A	4.4	34.4	79.7	93.0	97.6	98.8	100.0
85	N/A	C	2.3	97.3	0.4	S	WT	N/A	2.0	80.8	302.0	110.1	20.4	12.9	N/A	14.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.4	12.6	50.0	10.2	4.1	2.0	2.3
SPLIT	WT=	646.7						CUM WT %	N/A	0.4	12.0	73.4	91.7	96.7	97.7	100.0
90	N/A	C	0.2	94.7	6.1	(g)S	WT	N/A	31.6	194.0	319.4	30.3	22.4	13.4	N/A	1.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.1	31.4	61.4	6.2	3.0	2.2	0.2
SPLIT	WT=	627.2						CUM WT %	N/A	6.1	36.4	87.9	94.0	97.0	99.0	100.0
95	N/A	C	1.1	96.3	3.0	S	WT	N/A	23.2	167.0	341.3	80.7	20.2	7.6	N/A	7.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.0	24.6	63.0	13.6	3.1	1.2	1.1
SPLIT	WT=	642.6						CUM WT %	N/A	3.0	29.1	81.1	94.0	97.7	98.9	100.0
100	N/A	C	2.6	96.2	2.3	S	WT	N/A	13.3	87.7	279.6	168.0	31.0	13.4	N/A	14.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.3	11.7	40.3	27.4	6.6	2.3	2.6
SPLIT	WT=	573.2						CUM WT %	N/A	2.3	14.0	62.3	80.7	95.2	97.6	100.0
105	N/A	C	1.6	97.6	1.0	S	WT	N/A	0.0	66.0	371.0	136.0	20.3	0.2	N/A	9.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.0	10.7	80.2	22.0	3.3	1.3	1.6
SPLIT	WT=	613.3						CUM WT %	N/A	1.0	11.7	71.9	93.9	97.2	98.6	100.0
110	N/A	C	6.0	93.2	1.0	S	WT	N/A	9.0	62.1	120.5	29.3	107.6	87.4	N/A	20.6
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	1.0	11.7	22.0	6.6	37.1	10.4	6.0
SPLIT	WT=	529.4						CUM WT %	N/A	1.0	13.6	36.1	41.0	70.0	95.0	100.0

0.52

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0200-E33-020 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	N/A	C	3.0	88.1	9.9	(0)S	WT	N/A	84.0	101.5	230.4	77.0	35.7	21.3	N/A	25.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.9	20.2	37.0	12.1	5.5	N/A	8.9
SPLIT	WT= 841.6						CUM	WT %	N/A	9.9	38.1	75.1	87.2	98.1	N/A	100.0
120	N/A	C	2.5	90.1	1.4	S	WT	N/A	5.0	49.2	199.4	68.0	20.2	10.0	N/A	9.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.4	13.6	55.1	19.0	6.6	N/A	2.5
SPLIT	WT= 368.8						CUM	WT %	N/A	1.4	16.0	70.0	89.0	94.6	N/A	100.0
125	N/A	C	1.4	95.4	3.1	S	WT	N/A	19.0	83.1	300.1	168.0	30.0	15.4	N/A	0.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.1	13.2	48.9	24.9	0.0	N/A	1.4
SPLIT	WT= 633.1						CUM	WT %	N/A	3.1	15.3	65.2	90.1	98.1	N/A	100.0
130	N/A	C	0.2	94.0	4.9	S	WT	N/A	33.3	81.3	260.3	234.0	54.7	10.7	N/A	1.4
SDRT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.9	12.0	38.5	34.0	8.1	N/A	0.2
SPLIT	WT= 879.0						CUM	WT %	N/A	4.9	17.0	55.5	90.1	98.2	N/A	100.0
135	N/A	C	3.0	93.0	2.0	S	WT	N/A	10.4	55.9	249.4	264.0	73.4	24.0	N/A	25.7
SDRT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.0	7.9	35.0	37.2	10.3	N/A	3.0
SPLIT	WT= 709.1						CUM	WT %	N/A	2.0	10.4	45.5	82.0	92.9	N/A	100.0
140	N/A	C	2.3	97.2	0.4	S	WT	N/A	2.4	15.1	102.7	274.8	73.5	10.1	N/A	13.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	2.7	20.1	40.1	13.1	N/A	2.3
SPLIT	WT= 557.0						CUM	WT %	N/A	0.4	3.1	32.2	81.3	94.4	N/A	100.0
145	N/A	C	3.0	94.0	2.2	S	WT	N/A	13.2	87.0	282.0	157.0	40.4	23.0	N/A	10.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.2	14.4	43.0	25.0	7.0	N/A	3.0
SPLIT	WT= 614.0						CUM	WT %	N/A	2.2	16.5	59.5	86.4	93.1	N/A	100.0
150	N/A	C	5.0	93.0	1.4	S	WT	N/A	9.0	40.5	288.4	231.3	75.4	34.7	N/A	35.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.4	7.0	32.2	36.1	11.0	N/A	5.0
SPLIT	WT= 638.4						CUM	WT %	N/A	1.4	9.0	41.2	77.3	89.0	N/A	100.0
155	N/A	C	2.5	90.5	7.0	(0)S	WT	N/A	45.0	51.1	233.7	224.3	50.0	22.4	N/A	10.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.0	7.0	30.0	34.5	8.7	N/A	2.5
SPLIT	WT= 554.4						CUM	WT %	N/A	7.0	14.0	50.0	85.4	94.1	N/A	100.0
160	N/A	C	2.5	92.7	14.0	0S	WT	N/A	112.3	144.4	247.7	150.0	55.7	24.2	N/A	10.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	14.0	19.0	32.0	20.0	7.3	N/A	2.5
SPLIT	WT= 768.2						CUM	WT %	N/A	14.0	33.0	68.4	87.0	94.3	N/A	100.0
165	N/A	C	3.2	85.6	11.3	0S	WT	N/A	70.3	82.3	201.7	214.1	55.0	27.5	N/A	23.0
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.3	11.0	29.2	31.0	9.5	N/A	3.2
SPLIT	WT= 897.2						CUM	WT %	N/A	11.3	23.2	52.4	83.4	92.8	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0299-E33-028 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
170	N/A	C	3.8	84.8	11.8	gs	WT	N/A	75.4	142.9	191.6	131.3	58.7	25.7	N/A	24.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.6	22.0	29.6	20.3	8.8	4.0	N/A	3.8
SPLIT	WT=	654.1					CUM WT %	N/A	11.6	33.7	63.2	83.5	92.2	96.2	N/A	100.0	
175	N/A	C	2.3	83.8	13.8	gs	WT	N/A	88.3	220.4	189.0	82.3	32.8	13.8	N/A	14.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	13.8	34.4	29.5	12.9	5.1	2.1	N/A	2.3
SPLIT	WT=	638.7					CUM WT %	N/A	13.8	48.2	77.7	90.5	95.6	97.7	N/A	100.0	
180	N/A	C	3.4	74.4	22.1	gs	WT	N/A	158.8	118.1	154.7	182.6	88.6	24.3	N/A	24.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	22.1	18.4	21.8	23.6	9.9	3.4	N/A	3.4
SPLIT	WT=	706.5					CUM WT %	N/A	22.1	38.5	60.4	83.8	93.1	96.6	N/A	100.0	
185	N/A	C	2.4	97.3	0.3	S	WT	N/A	2.0	10.7	86.0	313.1	154.4	33.4	N/A	14.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.3	1.0	11.0	52.8	26.1	5.8	N/A	2.4
SPLIT	WT=	598.8					CUM WT %	N/A	8.3	2.2	13.1	86.8	92.6	97.6	N/A	100.0	
190	N/A	C	2.6	98.8	0.6	S	WT	N/A	3.9	38.9	154.7	273.8	183.8	28.2	N/A	15.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.6	8.3	25.0	44.3	16.7	4.6	N/A	2.6
SPLIT	WT=	821.8					CUM WT %	N/A	8.6	8.9	31.9	76.2	92.9	97.4	N/A	100.0	
195	N/A	C	3.3	98.2	0.5	S	WT	N/A	2.0	18.6	122.2	283.7	181.0	26.1	N/A	18.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.5	3.5	22.0	47.5	18.4	4.7	N/A	3.3
SPLIT	WT=	551.8					CUM WT %	N/A	0.5	4.0	26.1	73.8	92.0	96.7	N/A	100.0	
200	N/A	C	13.0	86.6	0.4	(m)S	WT	N/A	1.9	0.9	0.8	2.6	137.3	289.2	N/A	64.9	
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.4	0.2	0.1	8.5	27.8	58.2	N/A	13.1
SPLIT	WT=	494.9					CUM WT %	N/A	0.4	0.6	0.7	1.2	28.8	87.0	N/A	100.0	
210	N/A	C	2.8	87.4	30.0	sg	WT	N/A	221.9	175.8	210.1	68.8	29.5	14.9	N/A	19.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.0	23.7	28.4	9.3	4.8	2.0	N/A	2.6
SPLIT	WT=	744.9					CUM WT %	N/A	38.0	53.7	82.1	91.4	95.4	97.4	N/A	100.0	
215	N/A	C	1.7	38.2	62.1	sg	WT	N/A	588.2	128.6	188.9	32.8	16.5	9.3	N/A	13.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	62.1	15.7	13.3	4.0	2.0	1.1	N/A	1.7
SPLIT	WT=	816.4					CUM WT %	N/A	62.1	77.8	91.1	95.2	97.2	98.3	N/A	100.0	
220	N/A	C	2.6	39.0	63.8	sg	WT	N/A	588.4	90.0	99.2	42.7	23.7	14.7	N/A	20.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.6	11.3	12.4	5.3	3.0	1.8	N/A	2.6
SPLIT	WT=	757.3					CUM WT %	N/A	63.6	74.9	87.3	92.6	95.6	97.4	N/A	100.0	
225	N/A	C	1.8	41.8	56.6	sg	WT	N/A	458.4	149.8	118.2	44.0	20.3	11.8	N/A	14.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.5	18.6	13.7	5.5	2.5	1.5	N/A	1.9
SPLIT	WT=	804.9					CUM WT %	N/A	68.5	75.1	88.7	94.2	96.7	98.2	N/A	100.0	

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E33-020 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
230	N/A	H	0.0	52.7	30.3	msG	WT	N/A	290.0	98.7	138.4	79.5	66.8	38.5	N/A	89.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	38.3	12.7	17.6	10.3	7.2	5.0	N/A	9.0
SPLIT	WT=	773.1					CUM WT %	N/A	38.3	51.0	68.0	78.8	86.0	91.0	N/A	100.0
236	N/A	H	8.1	48.4	43.5	msG	WT	N/A	339.0	148.2	103.7	63.0	46.1	31.9	N/A	83.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	43.6	19.0	13.3	8.9	5.1	4.1	N/A	8.1
SPLIT	WT=	776.3					CUM WT %	N/A	43.6	62.5	75.8	82.7	87.8	91.9	N/A	100.0
240	N/A	H	8.8	33.0	59.2	msG	WT	N/A	497.0	88.2	83.7	51.4	48.0	33.7	N/A	75.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	58.2	10.1	7.6	6.0	6.6	3.8	N/A	8.0
SPLIT	WT=	853.1					CUM WT %	N/A	58.2	68.3	76.7	81.8	87.2	91.2	N/A	100.0
245	N/A	H	12.6	84.4	3.0	(m)S	WT	N/A	18.0	121.1	177.1	104.0	81.7	45.6	N/A	78.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.0	19.3	28.2	16.6	13.0	7.3	N/A	12.0
SPLIT	WT=	618.9					CUM WT %	N/A	3.0	22.3	50.6	67.1	80.2	87.4	N/A	100.0
250	N/A	H	7.3	33.8	58.9	msG	WT	N/A	404.0	123.1	65.5	39.0	32.7	5.9	N/A	57.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	59.0	15.8	8.3	4.9	4.2	0.0	N/A	7.3
SPLIT	WT=	795.8					CUM WT %	N/A	59.0	74.6	82.9	87.8	92.0	92.7	N/A	100.0
255	N/A	H	7.7	29.1	63.2	msG	WT	N/A	528.4	63.9	45.9	39.6	49.1	43.8	N/A	64.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	63.2	7.7	5.5	4.8	5.9	5.3	N/A	7.7
SPLIT	WT=	829.2					CUM WT %	N/A	63.2	70.9	76.4	81.2	87.1	92.8	N/A	100.0
260	N/A	H	7.3	50.1	42.8	msG	WT	N/A	347.9	197.1	90.9	49.1	42.7	29.6	N/A	59.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	42.8	24.1	11.1	6.0	5.2	3.6	N/A	7.3
SPLIT	WT=	811.7					CUM WT %	N/A	42.8	60.7	77.9	83.9	89.1	92.7	N/A	100.0
266	N/A	H	6.4	93.5	0.1	S	WT	N/A	0.6	47.5	304.8	186.4	75.5	40.7	N/A	44.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	0.1	8.8	43.6	26.8	10.8	5.8	N/A	6.4
SPLIT	WT=	708.3					CUM WT %	N/A	0.1	6.9	50.4	77.6	87.8	93.6	N/A	100.0
270	N/A	H	2.1	84.6	33.5	msG	WT	N/A	242.8	210.3	183.3	62.1	20.0	10.9	N/A	15.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	33.5	29.0	22.5	8.8	2.9	1.5	N/A	2.1
SPLIT	WT=	722.4					CUM WT %	N/A	33.5	62.5	85.0	93.6	96.4	97.9	N/A	100.0

3.55

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-E33-029 ****

02/02/89

DEPTH	%CAC03	OW	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	N/	0.4	6.8	92.8	G	WT	N/A	658.8	20.3	12.6	5.7	3.0	6.2	N/A	2.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	92.9	2.9	1.8	0.8	0.4	0.9	0.4
SPLIT	WT=	711.4					CUM	WT %	N/A	92.9	95.7	97.5	98.3	98.7	99.6	100.0
15	N/A	H	9.5	45.5	45.1	msG	WT	N/A	385.2	97.2	80.5	78.8	58.4	77.7	N/A	81.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	11.4	9.4	9.0	6.6	9.1	9.5
SPLIT	WT=	861.3					CUM	WT %	N/A	45.1	56.4	65.8	74.8	81.4	90.5	100.0
20	N/A	H	18.3	30.8	52.9	msG	WT	N/A	481.8	72.9	58.7	50.4	61.9	38.7	N/A	148.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.9	8.8	6.4	5.5	6.8	4.0	16.3
SPLIT	WT=	919.9					CUM	WT %	N/A	52.9	60.9	67.3	72.9	79.7	83.7	100.0
25	N/A	H	2.2	52.8	45.8	sg	WT	N/A	419.2	109.9	109.4	74.4	80.2	138.8	N/A	28.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.0	11.8	11.7	8.0	6.6	14.9	2.2
SPLIT	WT=	937.8					CUM	WT %	N/A	45.0	56.8	68.6	76.5	82.9	97.8	100.0
30	N/A	H	1.8	43.1	55.1	sg	WT	N/A	527.4	87.6	87.8	68.0	51.0	140.1	N/A	16.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.1	9.2	7.1	6.9	6.3	14.6	1.8
SPLIT	WT=	980.1					CUM	WT %	N/A	55.1	64.3	71.4	78.3	83.6	98.2	100.0
35	N/A	H	12.2	34.4	53.5	msG	WT	N/A	504.2	79.9	58.3	54.0	74.4	57.7	N/A	114.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.5	8.5	6.2	5.7	7.9	6.1	12.2
SPLIT	WT=	942.1					CUM	WT %	N/A	53.5	61.9	68.1	73.8	81.7	87.9	100.0
40	N/A	H	7.1	32.1	60.7	msG	WT	N/A	593.6	87.9	59.9	46.3	68.4	51.3	N/A	69.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.7	9.0	6.1	4.7	7.0	6.3	7.1
SPLIT	WT=	984.0					CUM	WT %	N/A	60.7	69.7	75.9	80.8	87.8	92.9	100.0
45	N/A	H	7.6	36.9	55.4	msG	WT	N/A	521.8	116.3	80.1	81.8	51.3	88.4	N/A	71.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.4	12.4	8.5	6.6	5.5	4.1	7.6
SPLIT	WT=	938.4					CUM	WT %	N/A	55.4	67.8	76.3	82.8	88.3	92.4	100.0
50	N/A	H	7.3	44.1	48.8	msG	WT	N/A	381.9	116.7	79.6	69.8	45.0	35.2	N/A	57.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.8	14.9	10.1	8.9	5.7	4.5	7.3
SPLIT	WT=	782.1					CUM	WT %	N/A	48.8	63.5	73.6	82.5	88.2	92.7	100.0
55	N/A	H	5.9	72.7	21.4	gS	WT	N/A	176.0	220.4	187.5	100.9	58.6	38.1	N/A	48.6
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.4	28.8	22.8	12.3	7.1	3.7	6.9
SPLIT	WT=	819.9					CUM	WT %	N/A	21.4	40.2	71.0	83.3	90.4	94.1	100.0
60	N/A	C	3.2	95.0	1.8	S	WT	N/A	10.3	126.6	290.3	69.7	34.0	18.7	N/A	10.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.8	22.3	51.1	12.3	6.0	3.3	3.2
SPLIT	WT=	567.0					CUM	WT %	N/A	1.8	24.1	75.2	87.5	93.5	98.8	100.0

J.57

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E33-029 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
85	N/A	C	3.3	92.1	4.8	S	WT	N/A	28.1	282.3	241.3	68.6	33.4	28.7	N/A	28.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.8	32.9	39.3	11.1	6.4	3.4	N/A
SPLIT	WT=	611.8						CUM WT %	N/A	4.8	37.6	78.7	87.9	93.3	98.7	N/A
70	N/A	C	3.7	94.4	1.9	S	WT	N/A	12.3	186.3	331.9	60.4	29.6	12.8	N/A	29.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.9	28.0	52.2	9.5	4.7	2.0	N/A
SPLIT	WT=	632.8						CUM WT %	N/A	1.9	27.9	80.1	89.6	94.3	96.3	N/A
76	N/A	C	22.1	76.3	2.6	mS	WT	N/A	17.4	127.2	240.9	51.6	41.6	44.8	N/A	149.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.6	18.9	36.8	7.7	6.2	6.7	N/A
SPLIT	WT=	673.1						CUM WT %	N/A	2.6	21.6	57.3	66.0	71.2	77.9	N/A
80	N/A	C	18.2	79.4	18.6	(m) S	WT	N/A	67.2	138.0	177.0	99.9	68.7	38.1	N/A	85.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.6	21.2	27.8	15.8	8.1	5.9	N/A
SPLIT	WT=	643.1						CUM WT %	N/A	18.6	31.8	59.2	74.7	83.9	89.8	N/A
85	N/A	C	6.8	98.1	3.8	S	WT	N/A	26.9	131.0	286.1	108.9	52.1	35.6	N/A	41.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.8	19.3	42.0	16.0	7.7	6.2	N/A
SPLIT	WT=	678.8						CUM WT %	N/A	3.8	23.1	66.0	81.1	88.7	94.0	N/A
90	N/A	C	1.6	97.9	0.6	S	WT	N/A	3.9	92.3	489.7	105.7	28.2	9.2	N/A	9.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.6	14.2	63.0	16.2	3.1	1.4	N/A
SPLIT	WT=	667.2						CUM WT %	N/A	0.6	14.8	77.7	94.0	97.1	98.6	N/A
97	N/A	C	0.8	98.9	2.6	S	WT	N/A	6.6	67.3	280.8	48.7	8.4	2.3	N/A	2.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.6	19.9	59.4	14.4	2.6	0.7	N/A
SPLIT	WT=	838.2						CUM WT %	N/A	2.6	22.4	81.8	96.2	98.7	99.4	N/A
100	N/A	C	6.8	92.1	2.3	S	WT	N/A	7.4	64.4	148.3	59.2	22.4	14.3	N/A	18.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.3	18.9	46.4	18.4	7.0	4.4	N/A
SPLIT	WT=	321.9						CUM WT %	N/A	2.3	19.2	64.0	83.0	89.9	94.4	N/A
106	N/A	C	4.0	96.6	0.6	S	WT	N/A	1.6	2.7	25.1	138.8	113.8	26.0	N/A	12.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.6	0.8	7.9	43.3	36.5	8.1	N/A
SPLIT	WT=	328.0						CUM WT %	N/A	0.6	1.3	9.1	52.4	87.9	98.0	N/A
110	N/A	C	4.2	96.8	0.8	S	WT	N/A	0.8	0.4	10.3	116.7	135.3	22.2	N/A	12.8
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.8	0.1	3.6	39.0	46.6	7.6	N/A
SPLIT	WT=	298.8						CUM WT %	N/A	0.8	0.1	3.8	42.6	88.3	96.7	N/A
116	N/A	C	6.8	93.8	0.4	S	WT	N/A	1.9	1.2	0.7	32.7	350.1	98.6	N/A	38.8
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	0.2	0.1	8.4	68.8	18.1	N/A
SPLIT	WT=	616.1						CUM WT %	N/A	0.4	0.6	0.7	7.1	75.8	94.2	N/A

0.58

ROCKWELL HANFORD OPERATIONS STEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-E33-020 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	N/A	C	18.1	75.6	0.4	(gm)S	WT	N/A	14.8	25.8	74.8	28.4	18.2	28.2	N/A	41.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.4	11.2	32.8	12.4	7.9	N/A	18.1
SPLIT	WT=	230.1					CUM WT %	N/A	6.4	17.7	60.2	82.8	78.5	81.9	N/A	100.0
125	N/A	C	1.4	98.7	1.9	S	WT	N/A	6.8	46.8	172.6	81.2	21.4	8.3	N/A	4.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.9	13.7	60.6	23.8	8.3	N/A	1.4
SPLIT	WT=	347.8					CUM WT %	N/A	1.9	16.6	66.1	89.9	96.2	98.6	N/A	100.0
130	N/A	C	7.9	91.7	0.3	S	WT	N/A	1.1	5.0	35.1	142.9	88.8	22.8	N/A	25.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.3	1.8	10.9	44.5	27.4	N/A	7.9
SPLIT	WT=	321.4					CUM WT %	N/A	0.3	2.2	13.1	57.8	84.9	92.1	N/A	100.0
136	N/A	C	1.3	98.5	0.2	S	WT	N/A	0.9	3.7	72.2	349.8	137.5	28.3	N/A	7.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	0.6	12.2	59.1	23.2	N/A	1.3
SPLIT	WT=	697.4					CUM WT %	N/A	0.2	0.8	13.8	72.8	96.3	98.7	N/A	100.0
139	N/A	C	5.8	94.8	0.2	S	WT	N/A	1.1	18.1	181.1	386.5	97.8	38.3	N/A	34.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	1.6	28.2	48.8	14.2	N/A	5.8
SPLIT	WT=	898.6					CUM WT %	N/A	0.2	1.6	27.9	76.5	98.8	99.8	N/A	100.0
150	N/A	C	5.8	92.8	1.5	S	WT	N/A	9.7	70.2	271.7	172.6	59.7	38.8	N/A	37.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.5	18.8	41.7	28.5	9.2	N/A	6.8
SPLIT	WT=	851.0					CUM WT %	N/A	1.5	12.3	54.8	88.5	89.8	94.3	N/A	100.0
155	N/A	C	8.8	92.1	1.9	S	WT	N/A	11.8	39.7	281.9	218.8	87.8	32.4	N/A	38.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.9	8.8	33.4	85.7	11.1	N/A	6.8
SPLIT	WT=	811.8					CUM WT %	N/A	1.9	8.6	41.9	77.8	88.7	94.1	N/A	100.0
180	N/A	C	8.2	83.1	10.8	gs	WT	N/A	89.4	182.2	244.5	114.4	58.1	31.4	N/A	48.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	18.6	15.7	37.5	17.5	7.7	N/A	8.2
SPLIT	WT=	859.4					CUM WT %	N/A	18.8	28.3	83.8	81.3	89.8	93.8	N/A	100.0
165	N/A	C	3.5	98.8	5.7	(g)S	WT	N/A	39.1	92.8	288.8	178.2	47.3	21.4	N/A	24.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.7	13.4	41.8	25.8	8.8	N/A	3.5
SPLIT	WT=	898.8					CUM WT %	N/A	5.7	19.1	68.8	86.8	93.4	98.5	N/A	100.0
170	N/A	C	3.8	89.9	8.3	(g)S	WT	N/A	38.7	145.8	248.9	187.7	33.4	17.3	N/A	23.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.3	23.8	48.3	17.8	5.5	N/A	3.8
SPLIT	WT=	613.1					CUM WT %	N/A	8.3	38.1	78.4	87.9	93.4	98.2	N/A	100.0
175	N/A	C	8.8	84.9	9.1	(g)S	WT	N/A	57.8	148.5	189.4	188.8	64.7	31.3	N/A	37.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.1	22.8	31.7	17.2	8.7	N/A	8.8
SPLIT	WT=	628.5					CUM WT %	N/A	9.1	31.4	63.1	88.3	89.8	94.8	N/A	100.0

J.59

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

*** REPORT ON WELL 0299-E33-029 ***

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	WT	WT %	CUM WT %	FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
180	N/A	C	4.0	85.5	10.5	gs	WT	N/A	71.2	182.7	223.7	105.5	44.6	22.8	N/A	27.4	N/A	4.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.6	26.9	33.0	16.6	6.8	3.4	N/A	N/A	4.0
SPLIT	WT=	678.4						CUM WT %	N/A	10.6	37.4	70.4	86.0	92.6	96.0	N/A	100.0	
185	N/A	C	5.7	83.5	0.8	S	WT	N/A	4.8	17.5	127.9	294.7	94.5	36.4	N/A	34.7	N/A	5.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.8	2.9	21.0	48.4	15.5	5.9	N/A	N/A	5.7
SPLIT	WT=	636.5						CUM WT %	N/A	0.8	3.7	24.6	73.0	88.5	94.3	N/A	100.0	
190	N/A	C	5.3	94.5	0.2	S	WT	N/A	1.3	18.4	170.0	288.3	88.4	20.7	N/A	32.5	N/A	5.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	3.0	20.8	43.7	14.4	4.8	N/A	N/A	5.3
SPLIT	WT=	614.2						CUM WT %	N/A	0.2	3.2	31.0	75.6	89.9	94.7	N/A	100.0	
195	N/A	C	9.7	88.1	0.2	S	WT	N/A	0.7	20.3	105.2	112.2	40.6	22.9	N/A	33.2	N/A	9.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	8.0	30.8	32.9	13.7	6.7	N/A	N/A	9.7
SPLIT	WT=	341.1						CUM WT %	N/A	0.2	6.2	37.0	69.9	83.6	90.3	N/A	100.0	
200	N/A	C	0.3	91.5	0.2	S	WT	N/A	1.2	32.3	104.8	225.0	89.7	45.4	N/A	53.3	N/A	0.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	5.0	30.4	35.1	13.0	7.1	N/A	N/A	0.3
SPLIT	WT=	647.5						CUM WT %	N/A	0.2	5.2	35.0	70.8	84.0	91.7	N/A	100.0	
205	N/A	C	18.2	81.8	0.0	(m)S	WT	N/A	0.0	1.5	37.1	39.7	75.7	271.4	N/A	94.9	N/A	18.2
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.3	7.1	7.8	14.6	52.2	N/A	N/A	18.2
SPLIT	WT=	526.8						CUM WT %	N/A	0.0	0.3	7.4	15.1	29.6	61.0	N/A	100.0	
210	N/A	C	24.2	75.0	0.0	mS	WT	N/A	0.0	0.0	5.5	10.4	00.0	288.0	N/A	118.0	N/A	24.2
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.1	1.1	2.1	13.7	58.0	N/A	N/A	24.2
SPLIT	WT=	493.7						CUM WT %	N/A	0.0	0.1	1.3	3.4	17.0	75.0	N/A	100.0	
215	N/A	C	4.8	60.8	34.6	sg	WT	N/A	134.2	77.3	89.1	37.4	20.0	12.1	N/A	17.7	N/A	4.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.6	19.0	23.0	9.8	5.2	3.1	N/A	N/A	4.8
SPLIT	WT=	388.0						CUM WT %	N/A	34.6	64.5	77.5	87.2	92.3	95.4	N/A	100.0	
220	N/A	C	0.9	57.1	42.0	sg	WT	N/A	155.3	93.1	80.0	21.9	10.2	5.0	N/A	3.2	N/A	0.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	25.2	21.7	5.9	2.0	1.0	N/A	N/A	0.9
SPLIT	WT=	375.0						CUM WT %	N/A	42.0	67.2	88.9	94.0	97.6	98.2	N/A	100.0	
227	N/A	C	0.0	29.1	02.1	msG	WT	N/A	516.7	65.1	73.2	00.4	39.1	5.0	N/A	73.0	N/A	0.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	02.1	7.0	0.0	7.2	4.7	0.7	N/A	N/A	0.0
SPLIT	WT=	842.1						CUM WT %	N/A	02.1	69.9	70.6	85.9	90.5	91.2	N/A	100.0	
230	N/A	C	4.7	44.6	50.7	sg	WT	N/A	340.4	75.0	104.3	55.0	37.0	24.2	N/A	32.5	N/A	4.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.7	10.9	15.2	9.8	5.4	3.5	N/A	N/A	4.7
SPLIT	WT=	893.6						CUM WT %	N/A	50.7	61.0	70.8	86.4	91.8	95.3	N/A	100.0	

0.60

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0200-E33-020 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
235	N/A	C	0.0	58.2	35.9	ssG	WT	N/A	291.0	105.5	142.5	50.0	40.0	30.3	N/A	40.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.9	24.1	17.6	7.2	4.9	N/A	0.0
SPLIT	WT=	011.8					CUM	WT %	N/A	35.9	59.9	77.5	84.7	89.6	N/A	100.0
240	N/A	C	12.1	47.1	40.8	msG	WT	N/A	315.0	91.1	53.0	99.0	07.2	40.7	N/A	93.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	11.0	8.2	12.0	8.7	N/A	12.1
SPLIT	WT=	770.7					CUM	WT %	N/A	40.8	52.6	60.8	73.0	82.3	N/A	100.0
245	N/A	C	6.9	34.9	59.2	msG	WT	N/A	446.1	64.0	50.1	85.0	48.4	31.5	N/A	53.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.2	8.6	7.7	8.0	6.1	N/A	0.9
SPLIT	WT=	780.0					CUM	WT %	N/A	59.2	60.8	74.3	82.9	89.0	N/A	100.0
250	N/A	H	12.0	28.5	59.5	msG	WT	N/A	532.0	68.5	57.4	52.0	61.0	10.1	N/A	107.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.5	7.0	6.4	5.9	1.8	N/A	12.0
SPLIT	WT=	904.4					CUM	WT %	N/A	59.5	67.1	73.5	79.4	86.2	N/A	100.0
255	N/A	H	0.2	36.0	54.0	msG	WT	N/A	500.5	87.6	64.0	67.0	70.0	47.5	N/A	80.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	64.0	9.3	6.9	7.1	6.4	N/A	0.2
SPLIT	WT=	936.2					CUM	WT %	N/A	64.0	63.3	70.2	77.3	85.7	N/A	100.0
260	N/A	H	11.3	25.3	63.4	msG	WT	N/A	572.1	70.5	53.4	44.2	48.5	13.0	N/A	101.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.4	7.0	5.9	4.9	5.2	N/A	11.3
SPLIT	WT=	909.5					CUM	WT %	N/A	63.4	71.2	77.2	82.1	87.2	N/A	100.0
265	N/A	H	10.0	44.7	44.4	msG	WT	N/A	391.7	67.0	69.7	80.1	94.6	54.0	N/A	90.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.4	0.9	7.9	10.0	10.7	N/A	10.0
SPLIT	WT=	980.0					CUM	WT %	N/A	44.4	54.3	62.2	72.2	82.9	N/A	100.0
270	N/A	H	10.0	72.7	17.3	(m)GS	WT	N/A	142.4	200.1	218.2	87.4	54.0	22.7	N/A	82.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	17.3	25.0	20.5	11.0	8.6	N/A	10.0
SPLIT	WT=	833.8					CUM	WT %	N/A	17.3	42.9	68.0	80.0	87.2	N/A	100.0
275	N/A	H	8.7	64.5	26.8	(m)GS	WT	N/A	230.0	254.9	130.4	82.0	53.3	40.0	N/A	75.0
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.8	29.0	10.1	7.2	6.2	N/A	9.7
SPLIT	WT=	861.0					CUM	WT %	N/A	20.8	50.6	72.5	79.8	85.9	N/A	100.0
280	N/A	H	6.0	87.1	7.0	(g)S	WT	N/A	57.1	45.3	100.4	214.7	100.1	67.3	N/A	30.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	7.0	8.2	15.0	29.6	27.2	N/A	5.0
SPLIT	WT=	727.0					CUM	WT %	N/A	7.0	14.1	29.1	50.0	65.0	N/A	100.0
285	N/A	H	0.0	11.1	80.3	G	WT	N/A	600.3	10.0	20.1	24.5	13.5	0.1	N/A	4.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	80.3	2.0	3.5	3.2	1.0	N/A	0.0
SPLIT	WT=	700.4					CUM	WT %	N/A	80.3	90.0	94.4	97.0	99.4	N/A	100.0

3.61

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E33-029 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
290	N/A	H	1.6	46.6	51.9	SG	N/A	982.6	90.8	92.8	66.8	53.0	10.8	N/A	11.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.9	12.3	12.6	12.0	7.2	2.0
SPLIT WT=	736.9							CUM WT %	N/A	51.9	64.2	76.8	88.8	95.8	98.4

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0200-E33-030 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤ -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	N/A	N/	7.6	19.4	73.1	msG	WT	N/A	529.7	36.1	37.3	10.0	20.0	32.2	N/A	54.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.1	4.9	6.2	2.2	2.0	4.5	N/A	7.5
SPLIT	WT= 724.0						CUM WT %	N/A	73.1	78.0	83.1	85.3	88.1	92.0	N/A	100.0	
15	N/A	H	13.0	37.5	49.5	msG	WT	N/A	410.0	72.4	63.0	60.0	82.0	50.2	N/A	110.2	
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.5	8.6	6.3	7.0	9.7	6.9	N/A	33.0
SPLIT	WT= 840.5						CUM WT %	N/A	49.5	58.0	64.3	71.4	81.1	87.0	N/A	100.0	
20	N/A	H	12.0	45.2	41.9	msG	WT	N/A	350.0	90.0	71.4	70.3	76.4	80.4	N/A	107.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.9	10.0	8.5	9.5	9.1	7.2	N/A	12.9
SPLIT	WT= 832.0						CUM WT %	N/A	41.9	52.0	61.3	70.8	79.9	87.2	N/A	100.0	
25	N/A	H	8.0	40.1	42.1	msG	WT	N/A	385.1	159.3	92.2	87.1	54.5	32.4	N/A	70.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	10.4	10.0	6.3	3.7	N/A	8.0	
SPLIT	WT= 864.3						CUM WT %	N/A	42.1	60.5	71.1	81.1	87.4	91.2	N/A	100.0	
30	N/A	H	10.5	41.0	40.0	msG	WT	N/A	413.7	95.0	83.0	93.0	50.5	17.4	N/A	80.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	11.3	9.0	10.0	7.0	2.0	N/A	10.5
SPLIT	WT= 852.4						CUM WT %	N/A	40.0	59.0	69.0	80.5	87.5	89.5	N/A	100.0	
35	N/A	H	9.5	42.0	47.7	msG	WT	N/A	394.4	114.7	75.5	60.0	53.0	41.2	N/A	78.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.7	13.9	9.1	8.4	6.4	6.0	N/A	9.5
SPLIT	WT= 822.0						CUM WT %	N/A	47.7	61.0	70.0	79.1	85.5	90.5	N/A	100.0	
40	N/A	H	10.2	40.4	41.5	msG	WT	N/A	370.9	125.2	90.3	82.0	75.1	70.4	N/A	83.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.5	13.7	9.9	9.0	8.2	7.7	N/A	10.2
SPLIT	WT= 910.0						CUM WT %	N/A	41.5	65.1	65.0	74.0	82.2	89.0	N/A	100.0	
45	N/A	H	6.4	70.3	23.3	gS	WT	N/A	104.3	237.6	150.0	84.4	82.2	35.2	N/A	53.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	23.3	20.4	10.9	11.8	7.5	4.2	N/A	8.4
SPLIT	WT= 826.1						CUM WT %	N/A	23.3	51.7	70.0	81.9	89.4	93.6	N/A	100.0	
50	N/A	H	5.6	74.1	20.3	gS	WT	N/A	103.0	239.1	105.0	80.1	53.4	20.5	N/A	44.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.4	20.7	23.1	11.1	6.0	3.7	N/A	5.5
SPLIT	WT= 800.1						CUM WT %	N/A	20.4	50.1	73.1	84.2	90.8	94.5	N/A	100.0	
55	N/A	H	0.1	73.0	20.1	gS	WT	N/A	177.4	250.0	200.0	107.0	62.7	32.4	N/A	53.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.1	20.3	22.0	12.2	7.1	3.7	N/A	8.1
SPLIT	WT= 803.8						CUM WT %	N/A	20.1	40.4	71.0	83.2	90.3	93.0	N/A	100.0	
60	N/A	C	0.0	87.0	12.1	gS	WT	N/A	82.2	100.0	200.0	84.4	10.3	0.4	N/A	5.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.1	27.0	42.0	12.5	2.9	0.9	N/A	0.0
SPLIT	WT= 676.0						CUM WT %	N/A	12.1	40.0	82.0	95.4	98.2	99.2	N/A	100.0	

J.63

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAND REPORT

**** REPORT ON WELL 0200-E33-030 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=2)	VFINE PEB (+1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
85	N/A	C	2.6	98.1	7.6	(g)S	WT	N/A	61.9	192.3	314.4	76.7	28.4	15.0	N/A	17.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.6	27.8	46.4	10.8	3.8	2.2	N/A
SPLIT	WT=	694.1						CUM WT %	N/A	7.6	35.3	80.8	91.8	96.4	97.8	N/A
70	N/A	C	1.9	91.8	0.6	(g)S	WT	N/A	46.3	268.1	289.9	69.3	24.0	11.6	N/A	13.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.6	36.6	41.4	8.5	3.4	1.7	N/A
SPLIT	WT=	699.0						CUM WT %	N/A	6.6	43.1	84.5	93.0	96.4	98.1	N/A
75	N/A	C	3.4	91.3	6.3	(g)S	WT	N/A	38.0	170.2	309.1	92.8	35.4	18.1	N/A	23.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.3	26.1	44.7	13.7	5.2	2.7	N/A
SPLIT	WT=	876.5						CUM WT %	N/A	6.3	30.4	75.0	88.7	93.9	98.0	N/A
80	N/A	C	4.5	95.1	0.4	S	WT	N/A	2.1	2.1	12.3	217.6	221.1	34.5	N/A	23.2
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	0.4	2.4	42.4	43.1	0.7	N/A
SPLIT	WT=	613.6						CUM WT %	N/A	0.4	0.8	3.2	45.7	88.8	95.5	N/A
85	N/A	C	4.0	95.8	0.2	S	WT	N/A	1.2	2.6	17.1	285.4	210.3	29.7	N/A	22.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	0.5	3.0	50.2	37.0	5.2	N/A
SPLIT	WT=	567.4						CUM WT %	N/A	0.2	0.7	3.7	53.9	80.8	98.1	N/A
90	N/A	C	4.9	94.8	0.3	S	WT	N/A	1.0	0.6	0.4	144.3	288.4	44.8	N/A	25.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.3	0.1	1.3	28.4	58.3	0.8	N/A
SPLIT	WT=	588.2						CUM WT %	N/A	0.3	0.4	1.7	90.1	88.2	95.1	N/A
95	N/A	C	0.8	90.3	0.9	S	WT	N/A	5.6	3.9	7.0	48.8	253.9	235.4	N/A	63.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.9	0.8	1.2	8.0	41.8	38.7	N/A
SPLIT	WT=	880.0						CUM WT %	N/A	0.9	1.6	2.7	10.7	52.5	91.2	N/A
100	N/A	C	8.7	90.6	2.7	S	WT	N/A	18.1	105.5	302.3	101.0	59.5	38.8	N/A	44.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.7	15.8	45.2	15.2	8.9	5.5	N/A
SPLIT	WT=	825.1						CUM WT %	N/A	2.7	18.5	63.7	79.0	87.9	93.3	N/A
105	N/A	C	1.7	97.8	0.7	S	WT	N/A	4.4	32.9	375.8	173.4	29.8	11.5	N/A	16.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.7	5.2	58.8	27.2	4.7	1.8	N/A
SPLIT	WT=	834.9						CUM WT %	N/A	0.7	5.8	64.7	91.8	98.5	98.3	N/A
110	N/A	C	3.3	95.9	0.8	S	WT	N/A	5.1	48.9	310.1	204.0	53.3	22.8	N/A	22.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.8	7.4	46.5	30.8	8.0	3.3	N/A
SPLIT	WT=	858.5						CUM WT %	N/A	0.8	8.1	54.7	85.3	93.4	98.7	N/A
115	N/A	C	1.8	86.0	13.2	gS	WT	N/A	92.4	217.7	233.3	102.2	26.5	12.4	N/A	12.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.2	31.1	33.4	14.8	4.1	1.8	N/A
SPLIT	WT=	892.7						CUM WT %	N/A	13.2	44.3	77.7	92.3	98.4	98.2	N/A

J.64

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-E33-030 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	N/A	C	4.3	93.1	2.6	S	WT	N/A	16.8	46.6	220.3	191.6	85.8	40.9	N/A	26.9
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	2.8	7.6	38.4	31.7	18.9	8.8	N/A	4.3
SPLIT	WT=	689.1					CUM WT %	N/A	2.8	10.1	48.6	78.1	89.0	96.7	N/A	100.0
125	N/A	C	3.3	96.6	1.1	S	WT	N/A	0.9	87.1	331.1	169.6	47.3	21.6	N/A	21.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	1.1	10.2	60.5	24.4	7.2	3.3	N/A	3.3
SPLIT	WT=	652.6					CUM WT %	N/A	1.1	11.3	61.8	66.2	93.4	96.7	N/A	100.0
130	N/A	C	6.2	93.1	0.7	S	WT	N/A	4.8	36.8	248.2	228.8	67.3	33.1	N/A	40.6
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	0.7	6.8	37.8	34.5	10.2	6.0	N/A	6.2
SPLIT	WT=	660.4					CUM WT %	N/A	0.7	8.3	44.1	78.8	88.8	93.8	N/A	100.0
135	N/A	C	10.4	88.2	1.4	(m)S	WT	N/A	8.9	32.4	172.3	188.9	79.0	60.0	N/A	120.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	1.4	6.0	26.4	29.0	12.1	7.7	N/A	18.4
SPLIT	WT=	654.3					CUM WT %	N/A	1.4	8.3	32.8	61.8	73.9	81.0	N/A	100.0
140	N/A	C	8.6	87.2	4.3	S	WT	N/A	26.6	82.9	183.7	189.2	76.4	41.7	N/A	62.1
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	4.3	10.3	30.0	27.6	12.6	8.8	N/A	8.6
SPLIT	WT=	615.8					CUM WT %	N/A	4.3	14.8	44.8	72.2	84.7	91.5	N/A	100.0
145	N/A	C	12.6	82.7	4.6	(m)S	WT	N/A	29.8	107.7	183.1	130.3	84.2	53.3	N/A	83.2
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	4.6	10.6	25.0	20.0	12.9	8.2	N/A	12.8
SPLIT	WT=	662.1					CUM WT %	N/A	4.6	21.1	48.1	68.1	79.0	87.2	N/A	100.0
150	N/A	C	2.8	98.8	0.8	S	WT	N/A	3.1	28.8	186.4	249.4	79.8	18.2	N/A	16.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.8	4.8	29.8	44.8	14.2	3.3	N/A	2.8
SPLIT	WT=	669.7					CUM WT %	N/A	0.8	6.3	36.1	79.7	93.9	97.2	N/A	100.0
155	N/A	C	4.8	92.4	3.1	S	WT	N/A	20.2	79.9	250.0	176.2	82.9	27.9	N/A	29.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.1	12.2	39.4	28.9	9.6	4.3	N/A	4.8
SPLIT	WT=	666.2					CUM WT %	N/A	3.1	16.3	64.7	81.8	91.2	96.4	N/A	100.0
160	N/A	C	2.8	98.8	0.7	S	WT	N/A	4.7	37.9	221.0	273.8	76.6	22.1	N/A	17.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.7	6.8	33.8	41.9	11.7	3.4	N/A	2.6
SPLIT	WT=	662.8					CUM WT %	N/A	0.7	6.6	40.4	82.3	94.8	97.4	N/A	100.0
165	N/A	C	3.3	96.1	1.8	S	WT	N/A	9.4	37.7	176.8	242.8	76.6	22.6	N/A	19.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	1.8	8.4	30.1	41.4	13.4	3.8	N/A	3.3
SPLIT	WT=	667.1					CUM WT %	N/A	1.8	8.8	38.1	79.6	92.9	98.7	N/A	100.0
170	N/A	C	4.4	94.9	0.6	S	WT	N/A	3.8	19.8	184.9	262.8	139.1	31.3	N/A	26.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.6	3.4	18.2	49.7	24.2	6.4	N/A	4.4
SPLIT	WT=	674.9					CUM WT %	N/A	0.6	4.0	22.2	68.0	90.1	96.8	N/A	100.0

0.65

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAM REPORT

**** REPORT ON WELL 0299-E33-030 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
175	N/A	C	3.4	95.9	0.7	S	WT	N/A	3.9	0.0	60.6	268.3	161.3	31.8	N/A	19.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	1.5	10.0	40.7	31.6	5.6	N/A
SPLIT	WT=	571.1						CUM WT %	N/A	0.7	2.2	12.7	60.6	91.1	98.6	N/A
180	N/A	C	3.7	95.9	0.4	S	WT	N/A	1.9	0.6	0.0	30.5	303.4	60.6	N/A	18.7
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	0.1	0.0	7.7	70.5	23.7	N/A
SPLIT	WT=	500.8						CUM WT %	N/A	0.4	0.5	0.5	0.2	84.6	96.3	N/A
185	N/A	C	0.1	93.6	0.4	S	WT	N/A	2.2	1.3	0.0	21.0	379.7	72.5	N/A	41.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	0.3	0.1	4.3	72.8	14.1	N/A
SPLIT	WT=	513.8						CUM WT %	N/A	0.4	0.7	0.8	6.1	77.8	91.9	N/A
190	N/A	C	29.0	69.6	0.5	mS	WT	N/A	2.0	1.0	0.3	11.0	260.2	71.5	N/A	144.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.5	0.4	0.1	2.4	51.8	14.8	N/A
SPLIT	WT=	480.9						CUM WT %	N/A	0.6	0.9	1.0	3.4	56.2	70.1	N/A
195	N/A	C	7.3	92.1	0.8	S	WT	N/A	3.0	1.0	1.4	1.4	133.8	336.4	N/A	37.8
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.8	0.4	0.3	20.0	65.3	N/A	7.3
SPLIT	WT=	511.8						CUM WT %	N/A	0.6	0.9	1.2	1.6	27.4	92.7	N/A
200	N/A	C	65.8	33.6	0.6	sM	WT	N/A	2.3	1.3	0.0	2.8	82.7	61.7	N/A	271.0
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.6	0.3	0.0	0.7	20.1	12.8	N/A
SPLIT	WT=	411.2						CUM WT %	N/A	0.8	0.9	0.9	1.6	21.8	34.2	N/A
205	N/A	C	40.3	44.8	0.0	(g)sM	WT	N/A	37.8	63.4	77.2	24.6	32.1	40.5	N/A	283.1
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.9	11.0	14.2	4.0	5.9	0.5	N/A
SPLIT	WT=	545.3						CUM WT %	N/A	0.9	10.8	32.8	37.3	43.2	51.7	N/A
210	N/A	C	3.7	89.8	0.5	(g)S	WT	N/A	46.4	268.2	235.0	72.0	34.0	21.7	N/A	25.3
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	0.6	37.3	34.0	10.4	4.5	3.1	N/A
SPLIT	WT=	892.2						CUM WT %	N/A	0.6	43.9	77.9	88.3	93.2	90.3	N/A
215	N/A	C	2.0	80.5	10.7	gS	WT	N/A	106.0	200.7	130.4	64.8	34.1	10.5	N/A	10.2
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.7	41.9	20.3	10.1	5.3	2.9	N/A
SPLIT	WT=	644.1						CUM WT %	N/A	10.7	58.6	78.9	69.0	94.3	97.2	N/A
220	N/A	C	4.7	84.9	10.4	gS	WT	N/A	71.5	102.4	257.7	72.9	40.5	27.0	N/A	32.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.4	20.0	37.0	10.0	5.9	4.1	N/A
SPLIT	WT=	685.6						CUM WT %	N/A	10.4	37.1	74.7	86.3	91.2	95.3	N/A
225	N/A	C	9.2	78.0	14.0	(m)gS	WT	N/A	80.3	9.0	4.0	22.5	191.4	277.5	N/A	52.7
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	14.0	0.7	0.7	3.9	23.0	48.6	N/A
SPLIT	WT=	570.4						CUM WT %	N/A	14.0	14.7	15.4	19.3	42.3	90.8	N/A

J. DG

ROCKWELL HAMFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0290-E33-030 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
230	N/A	C	2.0	32.7	64.7	sg	WT	N/A	668.3	89.7	93.4	63.6	31.7	19.0	N/A	23.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	84.7	10.1	10.7	8.1	3.0	2.2	N/A	2.0
SPLIT	WT=	877.7					CUM WT %	N/A	84.7	74.8	85.5	91.8	96.2	97.4	N/A	100.0
235	N/A	C	2.5	32.6	64.8	sg	WT	N/A	421.8	89.8	88.9	38.2	21.6	14.2	N/A	10.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	84.8	10.7	10.6	5.9	3.3	2.2	N/A	2.5
SPLIT	WT=	861.0					CUM WT %	N/A	84.8	75.5	86.1	92.0	96.3	97.5	N/A	100.0
240	N/A	C	6.1	34.0	69.0	msG	WT	N/A	476.9	63.2	89.7	68.9	42.5	27.8	N/A	48.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	59.0	7.0	11.1	7.3	5.3	3.4	N/A	8.1
SPLIT	WT=	809.2					CUM WT %	N/A	59.0	88.9	78.0	85.3	90.5	93.9	N/A	100.0
245	N/A	C	5.1	58.9	35.9	sg	WT	N/A	278.7	100.4	178.0	91.1	52.3	34.3	N/A	39.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	35.9	13.0	23.1	11.0	6.7	4.4	N/A	6.1
SPLIT	WT=	772.3					CUM WT %	N/A	35.9	40.0	72.0	83.7	90.6	94.9	N/A	100.0
250	N/A	C	3.1	53.2	43.7	sg	WT	N/A	327.5	101.0	170.0	71.4	35.0	20.1	N/A	23.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	43.7	13.5	22.8	9.5	4.0	2.7	N/A	3.1
SPLIT	WT=	747.5					CUM WT %	N/A	43.7	57.1	79.9	89.4	94.2	98.9	N/A	100.0
255	N/A	C	2.9	24.7	72.4	msG	WT	N/A	575.4	72.0	51.6	34.9	22.3	14.8	N/A	23.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	72.4	9.2	6.6	4.4	2.8	1.9	N/A	2.9
SPLIT	WT=	793.4					CUM WT %	N/A	72.4	81.5	88.0	92.4	95.2	97.1	N/A	100.0
260	N/A	C	10.1	37.4	52.5	msG	WT	N/A	422.8	77.0	65.0	64.4	50.2	35.0	N/A	81.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	52.5	9.7	8.1	8.0	7.2	4.5	N/A	10.1
SPLIT	WT=	805.2					CUM WT %	N/A	52.5	82.1	70.2	78.2	85.4	89.9	N/A	100.0
265	N/A	H	9.0	61.0	30.0	msG	WT	N/A	239.0	229.0	114.4	63.1	48.1	30.8	N/A	71.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	30.0	28.8	14.4	7.9	8.0	3.9	N/A	9.0
SPLIT	WT=	793.2					CUM WT %	N/A	30.0	58.8	73.2	81.1	87.1	91.0	N/A	100.0
270	N/A	H	10.3	89.5	0.2	(m)S	WT	N/A	1.2	2.6	43.1	277.9	229.2	81.7	N/A	70.0
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	WT %	N/A	0.2	0.4	0.3	40.5	33.4	9.0	N/A	10.3
SPLIT	WT=	687.9					CUM WT %	N/A	0.2	0.6	0.8	47.3	89.7	89.7	N/A	100.0
275	N/A	H	8.3	46.3	48.4	msG	WT	N/A	410.4	178.5	87.5	51.8	38.8	30.2	N/A	53.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	48.4	20.8	10.3	5.1	4.0	3.6	N/A	6.3
SPLIT	WT=	847.6					CUM WT %	N/A	48.4	69.2	79.5	85.8	90.1	93.7	N/A	100.0
280	N/A	H	7.3	82.7	10.0	gS	WT	N/A	74.0	104.3	103.7	195.2	110.3	41.4	N/A	54.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	10.0	14.0	22.0	20.9	14.0	5.6	N/A	7.3
SPLIT	WT=	741.8					CUM WT %	N/A	10.0	24.0	46.0	72.3	87.1	92.7	N/A	100.0

J.67

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-E34-002 ****

02/02/89

DEPTH	%CAC83	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)
6	N/A	C	3.1	31.3	65.6	sg	WT	N/A	422.6	18.4	115.1	31.4	21.6	16.1	N/A	20.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	86.6	2.0	17.9	4.8	3.3	N/A	3.1
SPLIT	WT=	648.6						CUM WT %	N/A	86.6	88.6	91.2	94.0	96.9	N/A	100.0
12	N/A	H	7.8	32.6	59.6	msG	WT	N/A	550.4	69.4	53.9	69.6	82.7	49.8	N/A	73.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.6	7.4	6.8	7.4	6.7	N/A	7.8
SPLIT	WT=	936.1						CUM WT %	N/A	69.6	67.0	72.8	80.2	86.9	N/A	100.0
16	N/A	H	9.3	42.4	48.3	msG	WT	N/A	434.0	73.7	64.9	96.4	73.7	64.6	N/A	83.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.3	9.2	9.4	10.8	8.2	N/A	9.3
SPLIT	WT=	695.4						CUM WT %	N/A	48.3	68.6	86.9	76.6	84.7	N/A	100.0
20	N/A	H	10.0	38.9	51.7	msG	WT	N/A	482.0	78.1	67.9	87.8	72.0	61.2	N/A	83.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	61.7	8.4	7.3	8.4	7.7	N/A	10.0
SPLIT	WT=	924.4						CUM WT %	N/A	61.7	80.1	67.4	76.8	84.6	N/A	100.0
26	N/A	H	7.8	31.2	61.1	msG	WT	N/A	539.3	71.8	67.9	68.6	62.2	33.8	N/A	68.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	61.1	8.0	8.0	6.9	5.9	N/A	7.8
SPLIT	WT=	875.4						CUM WT %	N/A	61.1	69.1	76.7	82.6	88.4	N/A	100.0
36	N/A	H	2.6	34.3	63.2	sg	WT	N/A	602.2	104.6	108.9	62.3	38.6	16.4	N/A	23.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.2	11.2	11.6	6.7	3.3	N/A	2.6
SPLIT	WT=	934.2						CUM WT %	N/A	63.2	74.3	86.0	92.8	96.9	N/A	100.0
50	N/A	H	3.7	49.8	48.6	sg	WT	N/A	417.4	130.3	92.0	93.6	64.8	68.2	N/A	32.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.6	16.4	18.3	18.4	6.1	N/A	3.7
SPLIT	WT=	897.1						CUM WT %	N/A	46.6	62.0	72.2	82.6	88.7	N/A	100.0
66	N/A	H	7.0	54.4	38.6	msG	WT	N/A	387.7	177.8	121.8	81.8	41.7	31.0	N/A	56.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.6	22.3	16.3	7.8	6.2	N/A	7.0
SPLIT	WT=	792.8						CUM WT %	N/A	38.6	80.9	76.1	83.9	89.1	N/A	100.0
80	N/A	H	3.4	58.6	40.0	sg	WT	N/A	300.9	169.9	136.3	51.6	28.2	21.6	N/A	26.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	26.2	18.0	6.8	3.8	N/A	3.4
SPLIT	WT=	748.0						CUM WT %	N/A	40.0	86.2	83.2	90.0	93.7	N/A	100.0
87	N/A	H	6.0	68.4	27.6	gs	WT	N/A	244.3	234.7	181.8	91.3	63.3	28.7	N/A	63.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.6	26.6	20.6	18.3	6.8	N/A	6.0
SPLIT	WT=	879.8						CUM WT %	N/A	27.6	54.1	74.7	86.0	91.8	N/A	100.0
70	N/A	H	6.1	68.4	26.6	gs	WT	N/A	220.8	214.6	201.2	96.7	60.6	27.9	N/A	62.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.6	24.9	23.3	11.1	6.9	N/A	6.1
SPLIT	WT=	880.3						CUM WT %	N/A	26.6	50.4	73.8	84.9	90.7	N/A	100.0

2.69

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E34-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
75	N/A	H	4.0	73.0	21.0	gS	WT	N/A	191.4	273.7	213.6	81.3	49.4	27.0	N/A	40.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.0	31.2	24.3	9.3	5.6	3.2	N/A	4.6
SPLIT	WT= 874.1						CUM	WT %	N/A	21.0	53.0	77.4	86.6	92.3	96.4	N/A	100.0
80	N/A	H	4.0	73.3	22.2	gS	WT	N/A	190.1	269.0	214.4	74.5	43.4	23.3	N/A	38.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	22.2	30.9	25.5	8.9	5.2	2.8	N/A	4.6
SPLIT	WT= 890.3						CUM	WT %	N/A	22.2	53.1	78.6	87.5	92.7	96.4	N/A	100.0
85	N/A	H	4.4	76.6	20.1	gS	WT	N/A	189.9	189.2	200.4	114.0	48.0	26.6	N/A	37.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.1	22.4	30.8	13.0	5.6	3.2	N/A	4.4
SPLIT	WT= 838.0						CUM	WT %	N/A	20.1	42.5	73.3	80.0	92.6	96.0	N/A	100.0
90	N/A	H	5.0	74.7	20.4	gS	WT	N/A	169.7	140.6	203.0	130.0	69.6	29.0	N/A	41.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.4	16.9	31.0	15.0	7.2	3.0	N/A	5.0
SPLIT	WT= 831.0						CUM	WT %	N/A	20.4	37.2	60.0	84.4	91.6	96.1	N/A	100.0
95	N/A	H	7.3	84.7	7.0	(g)S	WT	N/A	68.0	119.0	267.4	182.9	65.0	3.0	N/A	54.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.0	16.1	34.7	24.6	8.0	0.5	N/A	7.3
SPLIT	WT= 737.7						CUM	WT %	N/A	7.0	24.1	60.7	83.4	92.2	92.7	N/A	100.0
105	N/A	H	3.3	70.8	19.9	gS	WT	N/A	151.0	200.7	248.0	89.0	32.6	17.4	N/A	25.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.9	26.3	32.3	11.7	4.3	2.3	N/A	3.3
SPLIT	WT= 750.0						CUM	WT %	N/A	19.9	46.1	78.4	90.1	94.4	98.7	N/A	100.0
110	N/A	H	3.2	84.1	12.7	gS	WT	N/A	103.1	224.3	279.8	101.5	43.4	24.0	N/A	25.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.7	27.0	34.6	12.6	5.4	4.2	N/A	3.2
SPLIT	WT= 804.7						CUM	WT %	N/A	12.7	40.3	74.8	87.3	92.7	96.0	N/A	100.0
115	N/A	H	5.9	80.3	13.0	gS	WT	N/A	116.2	180.2	232.3	132.1	74.1	42.0	N/A	40.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.0	22.6	27.0	15.9	8.0	5.1	N/A	5.9
SPLIT	WT= 828.6						CUM	WT %	N/A	13.0	36.4	64.3	80.1	89.0	94.1	N/A	100.0
120	N/A	H	7.3	64.4	28.3	(m)gS	WT	N/A	227.0	100.0	191.2	84.0	40.0	7.4	N/A	50.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.3	23.6	23.0	10.6	5.7	0.0	N/A	7.3
SPLIT	WT= 790.0						CUM	WT %	N/A	28.3	51.0	75.6	86.1	91.0	92.7	N/A	100.0
125	N/A	H	0.4	80.7	12.0	gS	WT	N/A	107.7	204.9	270.1	103.3	62.6	14.3	N/A	53.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.0	24.5	32.3	14.7	7.6	1.7	N/A	0.4
SPLIT	WT= 833.0						CUM	WT %	N/A	12.0	37.4	69.0	84.4	91.0	93.6	N/A	100.0
145	N/A	H	0.2	83.7	0.1	(g)S	WT	N/A	02.6	125.7	200.9	101.7	59.0	10.0	N/A	03.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.1	16.3	35.6	21.0	7.0	2.2	N/A	0.2
SPLIT	WT= 768.5						CUM	WT %	N/A	0.1	24.4	60.9	91.9	99.7	91.0	N/A	100.0

J.70

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0209-E34-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
156	N/A	H	5.0	86.7	0.3	(g) S	WT	N/A	75.2	253.9	281.7	123.7	42.2	11.0	N/A	40.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.3	31.4	32.3	15.3	5.2	N/A	5.0
SPLIT	WT=	885.0					CUM	WT %	N/A	0.3	40.7	73.0	88.3	93.5	95.0	100.0
181	N/A	H	4.7	81.0	14.3	g S	WT	N/A	117.8	288.1	213.8	90.2	45.7	24.3	N/A	30.9
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	14.3	34.9	25.9	11.7	5.5	N/A	4.7
SPLIT	WT=	818.6					CUM	WT %	N/A	14.3	49.2	75.1	86.8	92.3	95.3	100.0
185	N/A	H	3.8	80.0	16.2	g S	WT	N/A	131.6	248.0	220.1	107.8	44.0	23.0	N/A	31.1
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.2	30.0	27.8	13.2	6.6	N/A	3.8
SPLIT	WT=	810.9					CUM	WT %	N/A	10.2	40.7	74.5	87.7	93.3	98.2	100.0
170	N/A	H	5.0	81.8	12.8	g S	WT	N/A	89.0	202.8	185.7	102.4	54.2	31.3	N/A	41.0
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	12.0	28.7	20.3	14.5	7.7	N/A	5.8
SPLIT	WT=	703.0					CUM	WT %	N/A	12.0	41.3	67.6	82.1	89.8	94.2	100.0
175	N/A	H	5.0	77.8	17.4	g S	WT	N/A	153.1	260.6	222.6	113.3	57.0	20.7	N/A	43.9
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.4	29.6	25.3	12.9	8.5	N/A	5.0
SPLIT	WT=	875.2					CUM	WT %	N/A	17.4	47.0	72.3	85.2	91.8	95.0	100.0
180	N/A	H	5.5	76.0	19.5	g S	WT	N/A	185.8	247.2	210.5	103.7	55.8	21.1	N/A	46.5
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	19.5	29.1	24.8	12.2	8.6	N/A	5.5
SPLIT	WT=	840.4					CUM	WT %	N/A	19.5	48.6	73.3	86.5	92.1	94.5	100.0
185	N/A	H	4.5	83.0	1.0	S	WT	N/A	12.7	30.8	154.2	314.0	124.4	32.0	N/A	31.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	5.6	21.8	44.4	17.8	N/A	4.5
SPLIT	WT=	700.9					CUM	WT %	N/A	1.0	7.3	29.1	73.6	91.0	95.5	100.0
190	N/A	H	8.0	77.0	14.2	g S	WT	N/A	90.0	188.8	160.4	90.0	51.0	30.7	N/A	56.9
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	14.2	28.7	23.0	14.1	8.7	N/A	8.0
SPLIT	WT=	690.5					CUM	WT %	N/A	14.2	40.9	64.7	70.9	87.6	92.0	100.0
195	N/A	H	6.7	83.2	10.2	g S	WT	N/A	75.9	185.9	180.8	135.0	70.4	30.8	N/A	40.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.2	24.9	25.5	19.1	9.4	N/A	6.7
SPLIT	WT=	740.6					CUM	WT %	N/A	10.2	35.1	60.6	79.7	88.1	93.3	100.0
200	N/A	H	7.9	83.7	0.4	(g) S	WT	N/A	54.0	150.1	170.8	105.5	61.1	30.2	N/A	51.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.4	24.5	27.8	16.3	9.5	N/A	7.9
SPLIT	WT=	842.4					CUM	WT %	N/A	0.4	32.8	60.7	77.0	86.5	92.1	100.0
205	N/A	H	9.3	78.4	12.4	(m) g S	WT	N/A	91.3	183.2	178.1	128.0	75.3	13.2	N/A	68.3
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	12.4	24.8	24.2	17.4	10.2	N/A	9.3
SPLIT	WT=	735.8					CUM	WT %	N/A	12.4	37.2	61.4	78.7	90.9	90.7	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E34-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
210	N/A	H	0.2	51.1	42.7	msG	WT	N/A	300.5	184.6	130.4	74.7	42.8	14.2	N/A	55.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.7	20.7	15.0	8.4	4.0	1.0	N/A	0.2
SPLIT	WT=	889.3						CUM WT %	N/A	42.7	83.5	79.0	87.4	92.2	93.8	N/A	100.0
215	N/A	H	8.9	68.0	25.2	(m)gS	WT	N/A	200.7	90.0	87.1	80.1	100.7	61.5	N/A	70.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.2	12.3	10.9	10.1	24.9	7.7	N/A	0.9
SPLIT	WT=	799.4						CUM WT %	N/A	25.2	37.5	48.4	58.6	83.4	91.1	N/A	100.0
220	N/A	H	0.0	31.4	62.0	msG	WT	N/A	517.0	64.4	63.2	53.0	52.0	30.2	N/A	40.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	82.0	7.0	0.4	0.4	4.4	N/A	0.0	
SPLIT	WT=	823.0						CUM WT %	N/A	62.0	70.4	70.8	83.2	88.0	94.0	N/A	100.0
225	N/A	H	9.7	54.5	35.0	msG	WT	N/A	283.7	117.0	109.1	80.0	76.0	50.3	N/A	77.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.0	14.0	10.1	9.5	0.3	N/A	0.7	
SPLIT	WT=	791.3						CUM WT %	N/A	35.0	50.0	64.3	74.4	83.9	88.3	N/A	100.0
230	N/A	H	11.0	53.4	35.0	msG	WT	N/A	270.7	95.0	83.4	90.3	80.0	54.9	N/A	80.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.0	12.4	10.8	11.7	11.5	7.1	N/A	11.6
SPLIT	WT=	770.3						CUM WT %	N/A	35.0	47.4	58.1	69.8	81.3	88.4	N/A	100.0
235	N/A	H	0.0	53.0	39.4	msG	WT	N/A	332.1	230.1	90.0	43.0	40.4	31.4	N/A	50.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.4	20.3	11.7	5.1	4.0	3.7	N/A	0.9
SPLIT	WT=	830.0						CUM WT %	N/A	39.4	67.7	70.4	84.5	89.3	93.1	N/A	100.0

U.72

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E34-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
6	N/A	N/	10.4	38.0	53.6	msG	WT	N/A	478.3	41.3	47.0	35.6	54.7	142.0	N/A	93.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.8	4.0	5.4	4.0	6.1	15.9	N/A
SPLIT	WT=	896.2						CUM WT %	N/A	53.8	50.2	63.8	67.6	73.7	89.6	N/A
10	N/A	H	9.6	40.4	50.0	msG	WT	N/A	472.5	83.0	60.4	87.2	97.1	54.1	N/A	90.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	0.0	5.4	9.2	10.3	5.7	N/A
SPLIT	WT=	943.2						CUM WT %	N/A	50.0	50.0	65.2	74.6	84.7	90.6	N/A
15	N/A	H	11.6	41.2	47.3	msG	WT	N/A	443.8	77.4	83.3	75.4	106.5	84.3	N/A	108.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.3	8.3	8.0	8.0	11.3	8.0	N/A
SPLIT	WT=	938.3						CUM WT %	N/A	47.3	55.6	62.3	70.3	81.0	88.6	N/A
20	N/A	H	7.3	26.0	67.7	msG	WT	N/A	617.9	47.7	53.3	38.0	62.7	30.0	N/A	67.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	67.7	5.2	5.0	4.2	5.0	3.9	N/A
SPLIT	WT=	917.9						CUM WT %	N/A	67.7	72.9	78.7	83.0	88.7	92.7	N/A
25	N/A	H	10.9	34.2	54.9	msG	WT	N/A	617.5	83.0	85.1	55.3	80.5	50.1	N/A	102.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.9	8.7	6.9	6.9	8.6	6.2	N/A
SPLIT	WT=	944.1						CUM WT %	N/A	54.9	61.8	68.6	74.4	82.9	89.1	N/A
32	N/A	H	6.3	44.0	49.1	msG	WT	N/A	448.1	171.7	111.8	52.2	40.0	30.2	N/A	57.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.1	18.0	12.3	5.7	4.5	3.3	N/A
SPLIT	WT=	911.4						CUM WT %	N/A	49.1	67.9	80.2	85.9	90.4	93.7	N/A
35	N/A	H	8.1	29.3	63.6	msG	WT	N/A	639.2	71.2	59.3	60.1	59.5	33.9	N/A	81.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.0	7.1	5.9	6.0	5.9	3.4	N/A
SPLIT	WT=	1000.0						CUM WT %	N/A	63.0	70.7	76.6	82.6	88.6	91.0	N/A
40	N/A	H	0.4	31.2	68.4	msG	WT	N/A	604.3	85.0	57.4	70.0	70.4	49.1	N/A	84.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	80.4	0.0	5.7	7.0	7.0	4.9	N/A
SPLIT	WT=	998.2						CUM WT %	N/A	80.4	68.9	72.7	79.7	86.7	91.6	N/A
45	N/A	H	0.8	56.7	36.4	msG	WT	N/A	324.7	147.4	105.3	88.8	98.0	65.8	N/A	60.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.4	16.6	11.0	10.0	11.1	7.4	N/A
SPLIT	WT=	890.6						CUM WT %	N/A	36.4	53.0	64.0	74.7	85.0	93.2	N/A
50	N/A	H	7.2	49.9	42.9	msG	WT	N/A	380.0	172.3	103.5	77.7	55.3	33.2	N/A	83.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.9	19.5	11.7	8.0	6.2	3.8	N/A
SPLIT	WT=	865.0						CUM WT %	N/A	42.9	62.3	74.0	82.0	89.0	92.8	N/A
55	N/A	H	6.8	28.0	66.1	msG	WT	N/A	845.4	115.2	60.4	37.1	34.2	26.8	N/A	57.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.1	11.0	6.2	3.8	3.6	2.8	N/A
SPLIT	WT=	974.6						CUM WT %	N/A	60.1	77.9	84.1	87.9	91.4	94.2	N/A

U.73

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-E34-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	H	4.8	27.2	68.0	N/A	WT	N/A	816.9	92.1	53.4	52.0	42.4	7.3	43.4	N/A
SORT=	N/A	MEDIAN=	-1.00	MODE=	N/A	MEAN=	N/A	WT %	N/A	88.0	10.2	6.9	5.7	4.7	0.8	N/A
SPLIT	WT=	926.7						CUM WT %	N/A	88.0	78.1	84.0	89.7	94.4	96.2	100.0
65	N/A	H	7.8	28.4	63.7	msG	WT	N/A	822.3	87.2	61.0	64.4	48.5	15.7	N/A	77.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	83.7	8.9	8.2	6.6	5.1	1.6	N/A
SPLIT	WT=	976.3						CUM WT %	N/A	83.7	72.6	78.8	85.4	90.5	92.1	100.0
70	N/A	H	9.7	36.0	55.2	msG	WT	N/A	643.8	104.8	77.4	77.3	57.3	28.1	N/A	95.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	65.2	10.6	7.9	7.9	6.8	2.9	N/A
SPLIT	WT=	984.7						CUM WT %	N/A	65.2	85.9	73.7	81.6	87.4	90.3	100.0
75	N/A	H	7.2	24.8	67.9	msG	WT	N/A	702.9	76.0	62.5	39.0	47.6	41.8	N/A	75.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	67.9	7.3	5.1	3.8	4.6	4.0	N/A
SPLIT	WT=	1027.4						CUM WT %	N/A	67.9	75.3	80.3	84.1	88.7	92.8	100.0
86	N/A	H	7.6	64.1	28.4	(m)gS	WT	N/A	258.5	238.6	181.5	89.4	57.3	32.3	N/A	88.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.4	26.4	17.9	9.9	6.3	3.6	N/A
SPLIT	WT=	897.7						CUM WT %	N/A	26.4	54.8	72.6	82.5	88.9	92.4	100.0
90	N/A	H	6.7	42.0	51.4	msG	WT	N/A	484.4	147.2	112.9	80.2	43.7	31.6	N/A	63.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.4	15.8	12.0	6.4	4.6	3.4	N/A
SPLIT	WT=	940.9						CUM WT %	N/A	51.4	67.0	79.0	85.3	90.0	93.3	100.0
95	N/A	H	7.5	68.2	24.3	gS	WT	N/A	210.3	184.1	238.2	95.1	58.4	32.5	N/A	67.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	24.3	20.7	28.7	10.7	6.6	3.7	N/A
SPLIT	WT=	890.8						CUM WT %	N/A	24.3	44.0	71.8	82.3	98.9	92.5	100.0
100	N/A	H	5.1	90.3	4.6	S	WT	N/A	33.2	195.0	280.9	88.6	55.6	25.9	N/A	35.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.6	27.3	39.2	12.4	7.6	3.6	N/A
SPLIT	WT=	713.9						CUM WT %	N/A	4.6	32.0	71.2	83.5	91.3	94.9	100.0
105	N/A	H	4.9	84.9	10.2	gS	WT	N/A	78.9	264.6	280.7	81.7	30.5	0.0	N/A	37.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.2	34.2	36.3	10.6	3.9	0.0	N/A
SPLIT	WT=	772.6						CUM WT %	N/A	10.2	44.4	80.7	91.2	95.2	96.2	100.0
110	N/A	H	4.3	88.4	7.3	(g)S	WT	N/A	52.6	201.7	201.5	95.0	36.7	19.4	N/A	38.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.3	26.1	39.2	13.2	5.1	2.7	N/A
SPLIT	WT=	713.5						CUM WT %	N/A	7.3	35.4	74.7	87.9	93.0	95.7	100.0
115	N/A	H	3.2	81.2	5.6	(g)S	WT	N/A	44.3	192.4	363.9	117.7	40.9	18.1	N/A	25.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.6	24.3	44.7	14.9	5.2	2.3	N/A
SPLIT	WT=	790.6						CUM WT %	N/A	5.6	29.9	74.5	89.4	94.5	98.8	100.0

U.74

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E34-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	N/A	H	2.0	87.2	10.2	qS	WT	N/A	78.2	141.0	280.1	193.4	81.5	14.2	N/A	20.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.2	16.4	33.8	25.1	9.0	1.9	N/A
SPLIT	WT= 789.0							CUM WT %	N/A	10.2	20.0	62.4	87.5	96.6	97.4	N/A
125	N/A	H	3.5	91.0	4.7	S	WT	N/A	35.8	68.0	231.4	241.7	109.0	27.4	N/A	28.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.7	11.0	30.7	32.0	13.8	3.0	N/A
SPLIT	WT= 754.9							CUM WT %	N/A	4.7	16.6	47.2	79.2	92.9	96.6	N/A
130	N/A	H	1.8	84.0	13.5	qS	WT	N/A	109.4	252.4	272.2	109.7	30.1	16.2	N/A	13.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.5	31.1	33.6	13.5	4.7	2.0	N/A
SPLIT	WT= 817.0							CUM WT %	N/A	13.5	44.6	78.2	91.7	96.4	98.4	N/A
135	N/A	H	5.1	85.9	9.0	(q)S	WT	N/A	73.1	113.7	205.9	227.8	109.3	40.5	N/A	41.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.0	14.0	25.4	28.1	13.5	5.0	N/A
SPLIT	WT= 812.0							CUM WT %	N/A	9.0	23.0	40.4	70.5	89.0	94.9	N/A
141	N/A	H	8.3	23.8	68.1	msG	WT	N/A	651.0	85.1	41.6	32.7	31.0	34.5	N/A	79.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	88.1	8.8	4.3	3.4	3.3	3.0	N/A
SPLIT	WT= 958.3							CUM WT %	N/A	88.1	77.0	81.3	84.7	88.1	91.7	N/A
145	N/A	H	10.2	23.1	68.7	msG	WT	N/A	809.9	62.4	45.1	38.6	33.5	31.0	N/A	82.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.7	8.8	4.9	4.2	3.7	3.5	N/A
SPLIT	WT= 820.0							CUM WT %	N/A	68.7	73.5	78.6	82.7	86.4	89.0	N/A
150	N/A	H	8.2	22.9	68.8	msG	WT	N/A	805.3	75.5	44.1	33.0	30.2	32.3	N/A	79.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	80.9	7.8	4.6	3.4	3.0	3.0	N/A
SPLIT	WT= 907.0							CUM WT %	N/A	80.9	78.7	81.3	84.7	88.4	91.0	N/A
155	N/A	H	10.6	24.7	64.7	msG	WT	N/A	592.3	61.0	46.7	39.9	43.0	33.5	N/A	87.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	64.7	8.8	5.1	4.4	4.0	3.7	N/A
SPLIT	WT= 914.7							CUM WT %	N/A	64.7	71.5	76.8	80.9	85.7	89.4	N/A
160	N/A	H	13.6	32.6	53.9	msG	WT	N/A	479.1	77.0	57.9	55.0	57.0	40.9	N/A	120.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.9	8.7	8.5	6.3	6.5	4.0	N/A
SPLIT	WT= 888.1							CUM WT %	N/A	53.9	62.0	69.1	75.4	81.9	86.5	N/A
165	N/A	H	6.8	33.5	59.7	msG	WT	N/A	545.3	92.4	68.5	68.0	47.4	28.8	N/A	62.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.7	10.1	7.5	7.5	5.2	3.2	N/A
SPLIT	WT= 906.3							CUM WT %	N/A	59.7	69.0	77.3	84.8	90.0	93.2	N/A
170	N/A	H	8.1	31.5	60.4	msG	WT	N/A	551.9	137.9	59.5	33.7	32.0	24.3	N/A	74.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.4	15.1	8.5	3.7	3.0	2.7	N/A
SPLIT	WT= 913.1							CUM WT %	N/A	60.4	75.6	82.0	85.7	89.3	91.9	N/A

J.75

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E34-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
175	N/A	H	11.0	33.8	54.8	msG	WT	N/A	491.8	119.8	63.1	44.4	49.4	38.0	N/A	104.4
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.6	13.3	6.6	4.9	5.5	3.3
SPLIT WT=	900.1								CUM WT %	N/A	54.6	87.9	74.7	79.6	85.1	88.4
180	N/A	H	7.7	28.5	63.8	msG	WT	N/A	606.3	105.3	60.6	40.0	32.5	28.0	N/A	72.1
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.8	11.3	6.5	4.3	3.6	3.0
SPLIT WT=	935.9								CUM WT %	N/A	63.8	75.0	81.5	85.6	89.3	92.3
185	N/A	H	6.2	53.2	40.8	msG	WT	N/A	300.0	236.8	110.8	66.6	38.9	29.1	N/A	55.8
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	20.3	13.2	8.3	4.9	3.2
SPLIT WT=	903.3								CUM WT %	N/A	40.8	88.0	80.0	60.3	20.6	93.8
190	N/A	H	6.7	52.8	30.7	sg	WT	N/A	270.0	280.4	152.2	64.5	38.0	30.7	N/A	60.7
SORT=	N/A		MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	30.7	31.0	10.8	7.1	4.2	3.4
SPLIT WT=	910.6								CUM WT %	N/A	30.7	61.7	70.6	86.7	89.9	93.3
195	N/A	H	10.0	60.5	26.5	(m)gs	WT	N/A	220.0	149.8	94.8	100.0	74.0	47.5	N/A	83.5
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.5	19.4	12.3	13.1	9.0	6.2
SPLIT WT=	770.4								CUM WT %	N/A	26.5	46.1	60.3	73.4	83.0	89.2
200	N/A	H	4.2	50.7	45.1	sg	WT	N/A	437.8	158.2	173.3	94.0	42.0	24.7	N/A	41.1
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	18.3	17.0	9.7	4.4	2.6
SPLIT WT=	969.6								CUM WT %	N/A	45.1	61.3	79.2	88.8	93.2	95.8
205	N/A	H	13.6	60.6	30.0	msG	WT	N/A	276.8	132.9	126.5	90.9	70.0	80.2	N/A	124.3
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	14.4	13.6	10.6	8.3	9.0
SPLIT WT=	928.3								CUM WT %	N/A	30.0	44.4	58.1	68.6	76.9	86.5
210	N/A	H	9.2	43.2	47.6	msG	WT	N/A	377.0	105.0	82.7	61.7	54.0	39.0	N/A	73.4
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.6	13.2	10.4	7.0	6.0	5.0
SPLIT WT=	796.4								CUM WT %	N/A	47.6	80.8	71.2	70.0	85.0	90.8

J.76

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL B299-E34-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
4	N/A	N/	3.2	22.2	74.6	msG	WT	N/A	610.0	33.3	67.8	42.7	21.8	28.2	N/A	25.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	74.6	4.1	5.2	2.7	3.2	N/A	3.2
SPLIT	WT=	814.5					CUM	WT %	N/A	74.6	70.7	85.8	91.0	98.8	N/A	100.0
10	N/A	H	13.1	39.1	47.9	msG	WT	N/A	399.7	65.6	61.3	60.9	64.6	80.1	N/A	100.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.9	7.8	8.0	7.7	10.8	N/A	13.1
SPLIT	WT=	832.5					CUM	WT %	N/A	47.9	55.7	61.0	68.7	80.9	N/A	100.0
15	N/A	H	10.4	63.4	25.1	(m)gS	WT	N/A	214.0	97.1	105.2	150.0	100.2	51.7	N/A	85.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.2	11.9	12.9	19.4	8.3	N/A	10.5
SPLIT	WT=	810.5					CUM	WT %	N/A	28.2	38.0	50.9	70.3	83.2	N/A	100.0
20	N/A	H	7.0	81.3	11.1	gS	WT	N/A	77.8	47.7	181.6	212.1	85.0	43.0	N/A	53.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.1	6.8	25.9	30.2	8.1	N/A	7.0
SPLIT	WT=	701.8					CUM	WT %	N/A	11.1	17.9	43.8	74.0	86.1	N/A	100.0
25	N/A	H	0.2	83.5	10.3	gS	WT	N/A	67.2	51.7	110.3	207.3	123.7	51.6	N/A	40.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.3	7.9	18.9	31.8	19.0	N/A	6.2
SPLIT	WT=	648.4					CUM	WT %	N/A	10.3	18.2	35.2	67.0	85.9	N/A	100.0
30	N/A	H	4.6	89.6	25.0	gS	WT	N/A	204.6	100.1	149.6	102.2	67.5	34.4	N/A	30.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.0	25.1	18.0	12.9	8.5	N/A	4.0
SPLIT	WT=	782.0					CUM	WT %	N/A	25.0	60.8	89.7	82.5	91.0	N/A	100.0
36	N/A	H	7.7	65.0	37.3	msG	WT	N/A	294.2	131.8	92.6	76.6	78.7	57.7	N/A	61.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.3	16.7	11.7	9.6	7.3	N/A	7.7
SPLIT	WT=	794.7					CUM	WT %	N/A	37.3	54.0	65.7	75.3	85.0	N/A	100.0
40	N/A	H	9.0	38.2	52.8	msG	WT	N/A	387.2	99.9	60.0	48.7	43.1	33.0	N/A	60.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.8	13.6	7.8	8.4	5.9	N/A	9.0
SPLIT	WT=	729.0					CUM	WT %	N/A	52.8	60.5	74.2	80.6	88.5	N/A	100.0
45	N/A	H	11.1	37.1	51.7	msG	WT	N/A	470.6	92.0	65.7	75.3	70.2	39.3	N/A	103.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.7	10.0	7.1	8.1	4.3	N/A	11.1
SPLIT	WT=	928.1					CUM	WT %	N/A	51.7	61.0	68.9	77.0	84.6	N/A	100.0
50	N/A	H	0.0	40.0	49.8	msG	WT	N/A	495.0	101.4	60.0	66.3	100.7	50.7	N/A	97.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.8	10.2	8.8	6.0	11.0	N/A	9.0
SPLIT	WT=	995.0					CUM	WT %	N/A	49.8	69.0	68.6	73.2	84.2	N/A	100.0
55	N/A	H	11.7	28.0	59.5	msG	WT	N/A	450.3	54.0	48.2	41.1	48.7	30.0	N/A	90.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.5	7.1	8.0	8.3	5.1	N/A	11.7
SPLIT	WT=	774.0					CUM	WT %	N/A	50.5	65.0	71.0	76.9	83.2	N/A	100.0

U.77

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0299-E34-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	H	18.7	40.3	43.0	msG	WT	N/A	381.2	77.6	68.1	82.5	69.2	51.8	N/A	140.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	9.2	8.9	9.8	8.2	8.2	16.7
SPLIT	WT=	839.5						CUM WT %	N/A	43.0	62.2	69.1	68.9	77.1	83.3	100.0
65	N/A	H	7.6	23.3	69.1	msG	WT	N/A	818.3	82.0	41.6	38.4	38.3	27.7	N/A	67.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	69.1	7.0	4.7	4.3	3.1	N/A	7.6
SPLIT	WT=	896.9						CUM WT %	N/A	69.1	76.1	80.7	85.0	89.3	92.4	100.0
70	N/A	H	10.1	47.2	36.7	msG	WT	N/A	300.7	91.0	69.4	86.0	83.4	56.2	N/A	132.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.7	11.1	8.6	10.6	6.9	N/A	16.1
SPLIT	WT=	818.4						CUM WT %	N/A	38.7	47.8	66.3	66.9	77.0	83.9	100.0
75	N/A	H	13.0	41.7	46.4	msG	WT	N/A	341.0	79.4	69.8	83.5	82.0	47.5	N/A	97.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.4	10.8	8.0	8.5	6.3	N/A	13.0
SPLIT	WT=	748.6						CUM WT %	N/A	46.4	58.0	63.9	72.4	80.7	87.1	100.0
80	N/A	H	8.0	45.4	45.7	msG	WT	N/A	412.0	141.2	114.2	66.7	84.2	23.0	N/A	79.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.7	16.7	12.7	7.4	7.1	2.8	8.8
SPLIT	WT=	908.4						CUM WT %	N/A	45.7	61.4	74.1	81.5	88.0	91.2	100.0
85	N/A	H	8.2	28.7	83.0	msG	WT	N/A	676.6	67.6	47.4	56.0	48.8	42.5	N/A	75.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	83.0	7.4	5.2	6.1	4.7	N/A	6.3
SPLIT	WT=	913.8						CUM WT %	N/A	83.0	70.4	75.8	81.0	87.1	91.7	100.0
90	N/A	H	8.8	68.5	24.7	(m)gS	WT	N/A	174.8	124.1	149.9	95.4	60.9	41.2	N/A	62.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.7	17.5	21.2	13.5	8.6	N/A	8.8
SPLIT	WT=	713.1						CUM WT %	N/A	24.7	42.2	63.3	70.8	85.4	91.2	100.0
95	N/A	H	10.9	61.6	27.5	(m)gS	WT	N/A	209.8	130.1	128.3	101.1	71.5	37.9	N/A	82.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.5	17.1	18.9	13.3	9.4	N/A	10.9
SPLIT	WT=	767.4						CUM WT %	N/A	27.5	44.8	61.5	74.8	84.1	89.1	100.0
100	N/A	H	11.4	44.9	43.7	msG	WT	N/A	384.7	113.8	79.2	82.0	70.9	49.0	N/A	100.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	12.9	9.0	9.3	8.1	N/A	11.4
SPLIT	WT=	874.7						CUM WT %	N/A	43.7	58.6	65.6	75.0	83.0	88.6	100.0
105	N/A	H	13.3	60.8	35.9	msG	WT	N/A	312.1	100.9	82.0	111.9	92.5	48.4	N/A	115.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.9	12.3	9.5	12.9	10.6	N/A	13.3
SPLIT	WT=	874.3						CUM WT %	N/A	35.9	48.1	67.7	70.5	81.1	86.7	100.0
110	N/A	H	11.6	44.9	43.5	msG	WT	N/A	388.0	115.1	84.5	89.8	84.8	45.8	N/A	103.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.5	12.9	9.5	7.8	9.6	N/A	11.6
SPLIT	WT=	889.1						CUM WT %	N/A	43.5	58.4	65.9	73.7	83.2	88.4	100.0

J.78

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-E34-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
115	N/A	H	14.1	47.4	38.5	msG	WT	N/A	331.5	118.1	82.4	76.6	80.1	53.7	N/A	121.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.5	13.5	9.8	9.3	8.2	N/A	14.1	
SPLIT	WT=	858.2					CUM WT %	N/A	38.5	52.0	81.6	70.3	79.6	88.9	N/A	100.0	
120	N/A	H	12.9	37.7	49.4	msG	WT	N/A	400.3	82.0	59.0	54.3	89.0	39.3	N/A	104.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.4	10.2	7.4	6.7	8.6	4.9	N/A	12.9
SPLIT	WT=	866.0					CUM WT %	N/A	49.4	69.6	66.9	73.6	82.2	87.1	N/A	100.0	
125	N/A	H	17.0	44.4	38.6	msG	WT	N/A	317.9	88.8	85.0	78.0	77.2	58.8	N/A	148.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.6	10.0	7.9	9.6	9.4	8.9	N/A	17.0
SPLIT	WT=	817.6					CUM WT %	N/A	38.6	49.4	67.3	68.7	76.1	83.0	N/A	100.0	
130	N/A	H	11.2	37.4	51.4	msG	WT	N/A	370.0	76.5	50.6	50.4	49.4	35.3	N/A	80.6	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.4	10.6	7.0	8.1	8.9	4.9	N/A	11.2
SPLIT	WT=	726.2					CUM WT %	N/A	51.4	82.0	89.0	77.1	84.0	88.8	N/A	100.0	
135	N/A	H	15.3	50.1	34.8	msG	WT	N/A	305.1	100.2	81.0	111.0	94.6	49.7	N/A	135.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.8	12.0	9.2	12.0	10.7	5.8	N/A	15.4
SPLIT	WT=	879.9					CUM WT %	N/A	34.8	40.0	55.8	68.3	79.0	84.7	N/A	100.0	
140	N/A	H	13.7	54.4	31.9	msG	WT	N/A	233.5	141.7	85.1	67.7	55.1	58.3	N/A	100.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.9	19.4	11.0	7.9	7.6	8.0	N/A	13.7
SPLIT	WT=	738.6					CUM WT %	N/A	31.9	51.3	62.0	70.8	78.3	88.3	N/A	100.0	
145	N/A	H	8.7	48.7	50.6	msG	WT	N/A	402.7	113.2	74.8	55.8	45.7	35.3	N/A	80.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.6	14.2	9.4	7.0	5.7	4.4	N/A	8.7
SPLIT	WT=	800.0					CUM WT %	N/A	50.6	84.0	74.2	81.2	86.9	91.3	N/A	100.0	
150	N/A	H	13.3	48.3	38.4	msG	WT	N/A	333.9	118.8	87.0	85.0	82.4	48.7	N/A	115.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.4	13.7	10.0	9.8	9.6	5.4	N/A	13.3
SPLIT	WT=	864.7					CUM WT %	N/A	38.4	52.1	82.1	71.9	81.4	86.7	N/A	100.0	
155	N/A	H	7.9	38.2	53.9	msG	WT	N/A	489.7	102.3	89.5	64.5	61.7	34.4	N/A	68.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.0	11.8	8.0	7.4	7.1	4.0	N/A	7.9
SPLIT	WT=	967.2					CUM WT %	N/A	54.0	65.7	73.7	81.1	88.2	92.1	N/A	100.0	
160	N/A	H	12.4	45.6	42.0	msG	WT	N/A	340.1	80.2	79.7	80.4	74.9	47.2	N/A	100.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	10.7	9.9	9.9	9.3	5.8	N/A	12.4
SPLIT	WT=	813.8					CUM WT %	N/A	42.1	62.7	82.6	72.5	81.0	87.6	N/A	100.0	
165	N/A	H	11.1	54.0	34.9	msG	WT	N/A	290.3	128.1	95.0	103.5	82.5	40.6	N/A	92.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.9	15.4	11.4	12.4	9.9	4.9	N/A	11.1
SPLIT	WT=	820.7					CUM WT %	N/A	34.9	60.2	61.7	74.1	84.0	88.0	N/A	100.0	

U.79

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-E34-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	WT	WT %	CUM WT %	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	N/A	H	4.7	68.6	26.7	gS	WT	N/A	220.5	268.8	172.5	71.1	41.7	23.4	N/A	38.9		
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	26.7	21.1	20.9	6.6	6.1	2.8	N/A	4.7	
SPLIT	WT=	821.6						CUM WT %	N/A	28.7	57.8	78.8	87.4	92.5	96.3	N/A	100.0	
175	N/A	H	7.6	71.6	21.1	gS	WT	N/A	162.1	104.7	147.3	91.0	64.0	29.1	N/A	63.9		
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.1	27.0	20.4	12.8	7.5	4.0	N/A	7.6	
SPLIT	WT=	726.7						CUM WT %	N/A	21.1	48.0	68.4	81.0	88.5	92.5	N/A	100.0	

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-E34-006 ****

02/02/89

DEPTH	%CAC03	DM	%WUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	N/A	N/	2.3	21.0	75.9	sg	WT	N/A	031.8	20.1	40.8	39.2	35.0	31.0	N/A	19.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	75.9	3.1	5.9	4.7	4.3	N/A	2.3
SPLIT	WT=	829.0						CUM WT %	N/A	75.9	79.0	84.9	89.8	93.9	N/A	100.0
10	N/A	H	9.9	53.3	36.7	msG	WT	N/A	316.4	103.9	118.9	114.9	73.3	48.3	N/A	85.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.7	12.1	13.0	13.9	8.6	N/A	9.9
SPLIT	WT=	861.9						CUM WT %	N/A	36.7	48.8	62.8	75.9	84.5	N/A	100.0
15	N/A	H	10.2	49.8	40.2	msG	WT	N/A	337.0	92.1	89.5	102.0	77.0	54.3	N/A	65.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.2	11.0	10.7	12.2	8.3	N/A	10.2
SPLIT	WT=	837.3						CUM WT %	N/A	40.2	51.2	61.0	74.1	83.3	N/A	100.0
20	N/A	H	9.0	43.2	47.2	msG	WT	N/A	403.3	104.0	06.0	104.2	70.7	53.5	N/A	94.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.2	10.0	0.7	10.6	5.5	N/A	9.0
SPLIT	WT=	976.3						CUM WT %	N/A	47.2	57.9	68.5	77.1	85.0	N/A	100.0
25	N/A	H	10.5	70.6	10.9	(m)gS	WT	N/A	162.4	53.7	01.0	200.3	107.5	85.9	N/A	84.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.9	0.7	7.8	24.9	20.0	N/A	10.5
SPLIT	WT=	805.1						CUM WT %	N/A	10.9	25.6	33.2	50.0	70.0	N/A	100.0
30	N/A	H	7.7	88.0	3.7	S	WT	N/A	20.0	25.0	143.7	204.0	120.0	60.7	N/A	55.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.7	3.5	19.9	40.7	10.7	N/A	7.7
SPLIT	WT=	722.0						CUM WT %	N/A	3.7	7.3	27.1	67.8	84.5	N/A	100.0
35	N/A	H	7.0	09.0	3.2	S	WT	N/A	22.0	12.0	09.0	302.2	155.7	50.5	N/A	50.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.2	1.0	12.4	40.0	21.0	N/A	7.0
SPLIT	WT=	721.2						CUM WT %	N/A	3.2	4.9	17.4	63.4	84.9	N/A	100.0
40	N/A	H	0.1	75.1	10.0	gS	WT	N/A	140.6	120.2	121.0	172.9	110.3	54.9	N/A	47.7
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.0	10.2	15.5	22.2	14.2	N/A	0.1
SPLIT	WT=	770.1						CUM WT %	N/A	10.0	35.0	60.5	72.7	88.0	N/A	100.0
45	N/A	H	0.0	44.4	47.0	msG	WT	N/A	417.0	07.1	00.5	04.3	00.1	00.5	N/A	00.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.7	10.0	9.2	10.0	7.0	N/A	0.0
SPLIT	WT=	874.1						CUM WT %	N/A	47.7	57.0	66.0	77.0	85.4	N/A	100.0
50	N/A	H	7.7	20.4	71.9	msG	WT	N/A	714.0	53.7	35.9	02.4	44.0	37.1	N/A	70.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	71.9	6.4	3.0	3.3	4.4	N/A	7.7
SPLIT	WT=	902.2						CUM WT %	N/A	71.9	77.3	80.0	84.2	88.0	N/A	100.0
65	N/A	H	0.1	23.5	00.4	msG	WT	N/A	040.0	55.1	39.3	42.7	41.5	44.1	N/A	70.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	00.4	5.0	4.2	4.5	4.4	N/A	0.1
SPLIT	WT=	942.0						CUM WT %	N/A	00.4	74.2	79.3	82.0	87.2	N/A	100.0

2.01

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0200-C34-006 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	N/A	H	8.8	27.6	83.9	msG	WT	N/A	628.3	65.8	48.8	60.5	49.2	47.4	N/A	84.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.9	8.7	4.8	8.2	5.0	N/A	8.8
SPLIT	WT=	977.2						CUM WT %	N/A	63.9	70.8	76.3	81.6	86.5	N/A	100.0
70	N/A	H	7.4	29.7	82.9	msG	WT	N/A	478.1	78.3	45.3	38.6	34.7	31.1	N/A	56.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	82.9	10.0	6.0	5.1	4.8	N/A	7.4
SPLIT	WT=	762.9						CUM WT %	N/A	82.9	72.9	78.9	84.0	88.5	N/A	100.0
76	N/A	H	12.0	29.7	58.2	msG	WT	N/A	431.5	65.9	38.4	39.3	45.3	31.5	N/A	89.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.2	8.0	5.2	6.3	8.1	N/A	12.0
SPLIT	WT=	748.7						CUM WT %	N/A	58.2	67.1	72.3	77.6	83.7	N/A	100.0
80	N/A	H	14.2	38.1	49.7	msG	WT	N/A	381.3	75.9	49.7	51.1	53.0	48.7	N/A	108.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.7	9.9	6.5	8.7	7.0	N/A	14.2
SPLIT	WT=	784.3						CUM WT %	N/A	49.7	59.6	65.1	72.7	79.7	N/A	100.0
85	N/A	H	7.7	24.8	87.7	msG	WT	N/A	809.2	70.1	41.1	33.9	45.8	30.3	N/A	69.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	87.7	7.8	4.0	3.8	5.1	N/A	7.7
SPLIT	WT=	982.8						CUM WT %	N/A	87.7	75.5	80.1	83.8	88.9	N/A	100.0
90	N/A	H	8.5	24.2	87.2	msG	WT	N/A	648.9	75.9	43.9	32.7	38.5	41.9	N/A	82.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	67.3	7.9	4.8	3.4	4.0	N/A	8.5
SPLIT	WT=	956.6						CUM WT %	N/A	67.3	75.1	79.7	83.1	87.1	N/A	100.0
95	N/A	H	5.4	23.1	88.5	msG	WT	N/A	677.0	69.0	40.7	30.1	47.3	41.4	N/A	82.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.6	7.0	4.1	3.1	4.8	N/A	8.4
SPLIT	WT=	986.9						CUM WT %	N/A	68.6	75.5	79.8	82.7	87.5	N/A	100.0
105	N/A	H	6.8	39.1	54.3	msG	WT	N/A	522.5	206.1	77.7	33.1	30.6	28.0	N/A	64.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.3	21.4	8.1	3.4	3.2	N/A	6.7
SPLIT	WT=	956.3						CUM WT %	N/A	54.3	75.7	83.8	97.2	98.4	N/A	100.0
110	N/A	H	8.6	22.0	69.5	msG	WT	N/A	640.4	51.9	32.8	39.2	39.0	39.7	N/A	78.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	89.5	5.8	3.8	4.3	4.3	N/A	8.6
SPLIT	WT=	919.9						CUM WT %	N/A	89.5	75.1	78.7	82.9	87.2	N/A	100.0
115	N/A	H	12.7	28.1	59.2	msG	WT	N/A	566.6	81.7	40.6	51.0	52.8	57.8	N/A	119.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.2	8.8	4.3	5.4	6.8	N/A	12.7
SPLIT	WT=	937.3						CUM WT %	N/A	59.2	65.7	70.1	75.5	81.1	N/A	100.0
120	N/A	H	8.9	21.9	69.2	msG	WT	N/A	608.0	48.3	34.7	32.7	49.5	47.7	N/A	86.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	69.2	4.8	3.6	3.4	5.1	N/A	8.9
SPLIT	WT=	964.9						CUM WT %	N/A	69.2	74.0	77.8	81.0	85.1	N/A	100.0

J.82

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0280-E34-006 ****

02/02/89

DEPTH	%AC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
125	N/A	H	0.3	32.7	59.0	msG	WT	N/A	502.4	75.7	54.9	84.1	67.3	40.8	N/A	81.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.0	7.7	5.6	8.5	4.1	N/A	0.3
SPLIT	WT=	983.0					CUM	WT %	N/A	59.0	66.7	72.2	80.0	87.6	N/A	100.0
130	N/A	H	6.2	31.7	62.2	msG	WT	N/A	571.4	100.0	59.8	55.0	39.0	20.0	N/A	50.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	62.2	11.5	8.5	6.2	4.3	N/A	6.2
SPLIT	WT=	918.9					CUM	WT %	N/A	62.2	73.7	80.2	86.4	90.7	N/A	100.0
135	N/A	H	6.1	34.3	59.8	msG	WT	N/A	536.4	143.0	64.0	41.2	33.7	26.0	N/A	54.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.8	16.0	7.1	4.8	3.0	N/A	0.1
SPLIT	WT=	903.1					CUM	WT %	N/A	59.8	75.0	82.7	87.3	91.1	N/A	100.0
140	N/A	H	6.0	32.3	61.7	msG	WT	N/A	525.7	129.0	59.0	32.8	29.5	23.4	N/A	51.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	61.7	15.2	7.0	3.8	3.5	N/A	0.0
SPLIT	WT=	850.1					CUM	WT %	N/A	61.7	70.9	84.0	87.8	91.2	N/A	100.0
145	N/A	H	7.1	40.3	44.6	msG	WT	N/A	404.1	187.1	121.5	62.0	38.3	26.0	N/A	64.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.6	20.7	13.4	8.9	4.2	N/A	7.1
SPLIT	WT=	909.7					CUM	WT %	N/A	44.6	85.3	78.7	85.6	89.0	N/A	100.0
150	N/A	H	10.3	70.4	19.3	(m)gS	WT	N/A	167.5	224.4	144.3	120.0	83.5	93.4	N/A	89.3
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.3	25.0	10.0	14.5	9.0	N/A	10.3
SPLIT	WT=	878.1					CUM	WT %	N/A	10.3	45.1	61.8	70.3	85.9	N/A	100.0
155	N/A	H	4.3	54.6	41.1	sg	WT	N/A	383.2	220.0	120.3	83.8	42.5	61.3	N/A	38.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.1	23.7	12.9	6.0	4.0	N/A	4.3
SPLIT	WT=	825.6					CUM	WT %	N/A	41.1	64.0	77.7	84.0	89.1	N/A	100.0
160	N/A	H	4.0	76.6	19.4	gS	WT	N/A	167.4	341.5	181.5	70.9	44.4	22.4	N/A	94.8
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	19.4	39.6	21.0	8.2	5.2	N/A	4.0
SPLIT	WT=	859.5					CUM	WT %	N/A	19.4	59.0	80.0	88.3	93.4	N/A	100.0
165	N/A	H	0.2	72.3	21.5	gS	WT	N/A	197.4	355.4	135.1	88.0	44.4	22.8	N/A	54.1
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.5	41.2	15.5	7.9	5.1	N/A	0.2
SPLIT	WT=	807.1					CUM	WT %	N/A	21.5	62.7	78.2	88.1	91.2	N/A	100.0
170	N/A	H	10.3	72.0	17.7	(m)gS	WT	N/A	144.9	242.4	158.5	93.0	64.9	34.5	N/A	84.7
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.7	29.6	19.1	11.3	7.9	N/A	10.3
SPLIT	WT=	817.1					CUM	WT %	N/A	17.7	47.2	66.2	77.6	85.6	N/A	100.0
175	N/A	H	0.8	70.6	20.7	(m)gS	WT	N/A	174.4	233.2	183.3	97.4	68.8	32.5	N/A	74.6
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.7	27.6	19.4	11.5	8.1	N/A	0.8
SPLIT	WT=	841.5					CUM	WT %	N/A	20.7	48.3	67.6	79.2	87.3	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0290-E34-005 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
180	N/A	H	6.6	82.0	32.4	sg	WT	N/A	288.3	268.8	147.6	83.6	48.8	23.8	N/A	58.1
SORT= N/A MEDIAN= 0.00 MODE= -1.00 MEAN= N/A							WT %	N/A	32.4	30.3	18.6	7.2	5.2	2.7	N/A	5.8
SPLIT WT= 888.2							CUM WT %	N/A	32.4	62.7	79.3	86.5	91.7	94.4	N/A	100.0
185	N/A	H	10.4	48.0	48.7	msG	WT	N/A	438.2	142.3	69.8	64.6	48.2	46.1	N/A	99.7
SORT= N/A MEDIAN= 0.00 MODE= -1.00 MEAN= N/A							WT %	N/A	48.7	15.8	7.7	7.2	5.1	5.1	N/A	10.4
SPLIT WT= 903.3							CUM WT %	N/A	48.7	64.5	72.2	79.4	84.6	89.6	N/A	100.0
190	N/A	H	10.8	47.2	42.0	msG	WT	N/A	323.7	119.7	79.8	66.3	59.0	37.4	N/A	83.8
SORT= N/A MEDIAN= 0.00 MODE= -1.00 MEAN= N/A							WT %	N/A	42.0	15.6	18.3	8.9	7.7	4.9	N/A	10.8
SPLIT WT= 777.7							CUM WT %	N/A	42.0	57.6	67.8	78.7	84.3	89.2	N/A	100.0
192	N/A	H	0.7	95.6	3.8	S	WT	N/A	27.8	248.8	321.8	105.8	21.9	3.8	N/A	5.1
SORT= N/A MEDIAN= 1.00 MODE= 1.00 MEAN= N/A							WT %	N/A	3.8	33.2	44.3	14.6	3.8	0.4	N/A	0.7
SPLIT WT= 727.7							CUM WT %	N/A	3.8	37.0	81.3	95.9	98.9	99.3	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

*** REPORT ON WELL 0290-E34-000 ***

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	N/A	N/	8.9	48.4	44.7	msG	WT	N/A	265.0	29.0	50.3	75.4	42.7	83.3	N/A	41.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.7	4.9	9.5	12.7	7.2	14.1	N/A	8.0
SPLIT	WT=	666.0					CUM	WT %	N/A	44.7	49.0	59.1	71.8	79.0	93.1	N/A	100.0
10	N/A	H	5.7	20.3	74.0	msG	WT	N/A	709.0	52.1	34.6	38.0	30.7	30.4	N/A	54.5	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	74.0	5.4	3.6	4.0	3.2	N/A	6.7	
SPLIT	WT=	957.9					CUM	WT %	N/A	74.0	79.5	83.1	87.1	91.1	94.3	N/A	100.0
15	N/A	H	8.5	32.8	58.9	msG	WT	N/A	577.9	65.8	50.5	60.2	79.1	48.4	N/A	83.2	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.9	8.7	6.0	7.0	8.1	4.0	N/A	8.5
SPLIT	WT=	981.1					CUM	WT %	N/A	68.9	65.6	71.8	78.5	86.0	91.5	N/A	100.0
20	N/A	H	9.5	81.5	29.0	(m)gS	WT	N/A	238.2	32.2	41.3	84.1	241.9	105.0	N/A	77.8	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	29.0	3.0	5.0	10.3	29.5	12.0	N/A	9.5
SPLIT	WT=	825.1					CUM	WT %	N/A	29.0	33.0	38.0	48.2	77.7	90.5	N/A	100.0
25	N/A	H	10.8	77.1	12.1	(m)gS	WT	N/A	80.1	12.0	21.6	68.4	306.1	120.8	N/A	70.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	12.1	1.7	3.0	12.4	43.0	17.0	N/A	10.0
SPLIT	WT=	718.4					CUM	WT %	N/A	12.1	13.0	16.0	29.2	72.2	89.2	N/A	100.0
30	N/A	H	9.1	88.7	2.2	S	WT	N/A	10.0	22.3	134.4	220.0	188.0	87.0	N/A	87.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.2	3.0	10.2	30.0	25.0	11.0	N/A	9.1
SPLIT	WT=	737.3					CUM	WT %	N/A	2.2	5.2	23.4	53.4	79.0	90.9	N/A	100.0
35	N/A	H	8.5	88.0	5.4	(g)S	WT	N/A	35.9	82.0	90.4	100.2	158.0	71.4	N/A	58.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.4	12.4	14.6	24.3	23.0	10.0	N/A	8.5
SPLIT	WT=	859.4					CUM	WT %	N/A	5.4	17.0	32.4	50.7	80.6	91.5	N/A	100.0
40	N/A	H	4.7	77.0	17.0	gS	WT	N/A	144.1	187.7	169.5	131.0	115.0	51.2	N/A	38.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	17.0	20.5	20.7	10.0	14.1	8.3	N/A	4.7
SPLIT	WT=	819.5					CUM	WT %	N/A	17.0	38.1	58.9	74.9	89.0	95.3	N/A	100.0
45	N/A	H	8.0	75.1	10.9	gS	WT	N/A	101.4	110.5	220.0	162.4	97.3	53.0	N/A	51.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.9	14.0	20.7	17.9	10.2	6.3	N/A	8.0
SPLIT	WT=	852.6					CUM	WT %	N/A	10.9	32.0	59.5	77.4	87.7	94.0	N/A	100.0
50	N/A	H	5.3	31.7	63.0	msG	WT	N/A	504.0	70.0	73.0	80.0	49.7	32.1	N/A	40.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	83.0	7.7	7.9	7.3	5.4	3.5	N/A	5.3
SPLIT	WT=	929.2					CUM	WT %	N/A	83.0	70.7	78.0	86.0	91.3	94.7	N/A	100.0
55	N/A	H	8.4	27.0	85.7	msG	WT	N/A	687.9	79.4	50.6	65.4	55.4	34.0	N/A	60.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	85.7	7.0	5.4	6.3	5.3	3.3	N/A	8.4
SPLIT	WT=	1050.4					CUM	WT %	N/A	85.7	73.3	78.7	85.0	90.3	93.0	N/A	100.0

7.85

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 2

**** REPORT ON WELL 0299-E34-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PES (<=-2)	VFINE PES (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
60	N/A	H	5.0	21.4	72.8	msG	WT	N/A	720.2	83.7	42.4	29.9	31.3	24.5	N/A	67.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	72.8	8.6	4.3	3.0	3.2	2.5	N/A	5.0
SPLIT	WT=	987.0					CUM WT %	N/A	72.8	81.2	86.5	88.5	91.7	94.1	N/A	100.0	
85	N/A	H	6.4	35.6	58.0	msG	WT	N/A	578.2	124.4	87.4	73.4	43.1	27.2	N/A	63.5	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.0	12.5	8.0	7.4	4.3	2.7	N/A	6.4
SPLIT	WT=	993.2					CUM WT %	N/A	58.0	70.5	79.2	86.6	90.9	93.6	N/A	100.0	
70	N/A	H	8.1	40.6	51.4	msG	WT	N/A	480.3	133.6	73.6	87.6	50.1	33.7	N/A	78.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.4	14.3	7.9	9.4	5.4	3.0	N/A	8.1
SPLIT	WT=	820.4					CUM WT %	N/A	51.4	85.7	73.5	82.9	88.3	91.9	N/A	100.0	
75	N/A	H	6.2	47.6	46.3	msG	WT	N/A	372.1	149.8	88.1	77.0	44.6	24.4	N/A	49.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.3	18.0	10.7	9.0	5.5	3.0	N/A	5.2
SPLIT	WT=	880.4					CUM WT %	N/A	46.3	64.9	75.0	85.2	90.8	93.9	N/A	100.0	
80	N/A	H	9.2	41.1	49.7	msG	WT	N/A	450.7	105.1	73.1	88.6	69.4	38.2	N/A	82.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.8	11.6	8.1	9.0	7.7	4.2	N/A	9.2
SPLIT	WT=	902.1					CUM WT %	N/A	49.8	61.4	89.4	79.0	88.6	90.9	N/A	100.0	
85	N/A	H	14.9	30.3	46.9	msG	WT	N/A	243.0	80.0	60.0	73.0	60.2	8.1	N/A	111.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.9	11.6	9.2	9.8	7.0	1.1	N/A	14.9
SPLIT	WT=	748.0					CUM WT %	N/A	46.9	67.4	66.6	78.3	84.1	85.1	N/A	100.0	
90	N/A	H	4.6	70.3	25.2	gS	WT	N/A	210.0	139.9	235.4	127.5	50.3	20.0	N/A	37.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	25.2	16.7	20.2	15.3	6.7	3.6	N/A	4.6
SPLIT	WT=	844.9					CUM WT %	N/A	25.2	41.0	70.1	86.3	92.1	95.6	N/A	100.0	
95	N/A	H	4.6	70.0	10.6	gS	WT	N/A	139.6	181.1	239.4	140.9	71.6	33.0	N/A	30.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.6	21.6	28.4	10.7	8.6	4.0	N/A	4.6
SPLIT	WT=	842.0					CUM WT %	N/A	10.6	38.0	60.3	83.0	91.6	95.6	N/A	100.0	
100	N/A	H	9.0	29.1	62.1	msG	WT	N/A	614.1	80.3	69.3	57.6	50.6	40.1	N/A	87.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	82.1	8.1	8.0	5.8	5.1	4.1	N/A	8.0
SPLIT	WT=	989.2					CUM WT %	N/A	82.1	70.2	76.2	82.0	87.2	91.2	N/A	100.0	
105	N/A	H	8.1	28.0	63.9	msG	WT	N/A	820.7	70.7	61.8	60.8	40.9	34.4	N/A	80.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.9	7.2	5.3	7.1	5.0	3.5	N/A	8.1
SPLIT	WT=	984.9					CUM WT %	N/A	63.9	71.1	78.3	83.4	88.4	91.9	N/A	100.0	
110	N/A	H	10.5	20.3	63.2	msG	WT	N/A	622.6	76.8	49.1	44.6	49.0	41.4	N/A	103.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	83.2	7.7	5.0	4.5	5.0	4.2	N/A	10.5
SPLIT	WT=	966.0					CUM WT %	N/A	83.2	70.9	76.9	80.4	85.3	89.6	N/A	100.0	

U.86

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0299-E34-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	N/A	H	10.5	32.0	57.5	msG	WT	N/A	587.1	72.7	88.2	88.2	87.3	49.8	N/A	100.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	87.6	7.1	8.7	8.6	4.9	N/A	10.5
SPLIT	WT=1022.3							CUM WT %	N/A	57.8	84.7	71.4	78.0	84.6	89.5	100.0
120	N/A	H	11.4	30.5	58.0	msG	WT	N/A	587.6	72.9	81.7	80.6	81.6	47.2	N/A	109.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.1	7.0	5.4	8.2	8.4	4.9	11.4
SPLIT	WT= 958.1							CUM WT %	N/A	58.1	85.0	71.0	77.2	83.7	88.6	100.0
130	N/A	H	8.0	48.3	45.7	msG	WT	N/A	410.7	120.8	77.4	115.4	67.2	41.3	N/A	73.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.7	13.2	8.5	12.7	7.4	4.6	8.1
SPLIT	WT= 907.2							CUM WT %	N/A	45.7	58.9	87.4	80.1	97.4	92.0	100.0
135	N/A	H	8.5	50.9	30.7	msG	WT	N/A	280.4	188.7	116.3	143.0	68.7	39.7	N/A	77.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.7	20.8	12.7	16.0	7.6	4.3	8.5
SPLIT	WT= 906.9							CUM WT %	N/A	30.7	51.3	64.0	79.7	87.2	91.5	100.0
140	N/A	H	9.9	64.7	25.4	(m)gS	WT	N/A	229.8	193.3	155.1	142.0	77.0	17.1	N/A	89.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.4	21.4	17.2	16.7	8.6	1.9	9.9
SPLIT	WT= 905.3							CUM WT %	N/A	25.4	46.8	63.9	79.6	88.2	90.1	100.0
145	N/A	H	0.1	72.0	19.9	(m)gS	WT	N/A	173.5	211.2	171.5	127.3	77.3	40.5	N/A	70.3
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	19.9	24.2	19.7	14.8	8.9	4.7	0.1
SPLIT	WT= 869.8							CUM WT %	N/A	19.9	44.1	63.8	78.4	87.3	92.0	100.0
150	N/A	H	5.0	77.5	10.0	gS	WT	N/A	138.6	245.1	210.0	183.7	54.8	27.0	N/A	47.8
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.0	29.7	26.4	12.8	8.6	3.3	5.0
SPLIT	WT= 824.6							CUM WT %	N/A	10.0	48.4	71.9	84.4	91.0	94.3	100.0
155	N/A	H	4.0	92.0	2.5	S	WT	N/A	18.7	184.8	281.0	162.2	81.1	31.1	N/A	33.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.5	22.2	37.8	28.6	8.2	4.2	4.0
SPLIT	WT= 739.0							CUM WT %	N/A	2.5	24.7	62.5	83.0	91.2	95.5	100.0
160	N/A	H	6.3	85.9	7.8	(g)S	WT	N/A	68.2	198.7	254.3	163.1	77.8	48.4	N/A	53.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.8	23.2	30.0	18.1	9.2	5.6	6.3
SPLIT	WT= 644.1							CUM WT %	N/A	7.8	31.0	61.0	79.1	86.3	93.7	100.0
170	N/A	H	6.4	83.1	10.5	gS	WT	N/A	80.5	205.0	200.5	146.4	87.0	30.7	N/A	52.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.5	24.8	25.4	17.7	10.6	4.7	6.4
SPLIT	WT= 826.2							CUM WT %	N/A	10.5	35.3	80.7	79.4	88.9	93.0	100.0
175	N/A	H	5.8	83.3	1.0	S	WT	N/A	7.1	73.8	254.9	233.1	94.4	30.2	N/A	42.7
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.0	9.0	34.3	31.4	12.7	4.9	5.8
SPLIT	WT= 738.6							CUM WT %	N/A	1.0	10.0	45.2	76.7	89.4	94.3	100.0

J.87

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-E34-000 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
180	N/A	H	4.4	94.9	0.7	S	WT	N/A	4.8	43.7	197.4	277.6	120.0	31.0	N/A	31.4
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	6.1	27.7	38.9	17.0	4.4
SPLIT	WT=	707.0							CUM WT %	N/A	0.7	6.8	34.6	73.4	91.2	95.6
185	N/A	H	10.3	73.0	10.1	(m)G\$	WT	N/A	141.4	208.7	189.9	148.6	68.5	13.0	N/A	90.3
SORT=	N/A		MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.1	23.8	21.7	18.7	0.9	1.0
SPLIT	WT=	877.0							CUM WT %	N/A	10.1	39.9	61.6	78.3	88.1	89.7
190	N/A	H	7.8	45.8	46.4	msG	WT	N/A	424.2	145.2	87.0	75.5	72.3	38.2	N/A	71.0
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.4	15.0	9.6	9.3	7.9	4.2
SPLIT	WT=	910.3							CUM WT %	N/A	46.4	62.2	71.0	80.1	88.0	92.2
195	N/A	H	7.3	42.6	50.1	msG	WT	N/A	480.1	140.4	104.7	80.7	49.1	33.9	N/A	67.5
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.1	18.2	11.4	6.6	4.7	3.7
SPLIT	WT=	918.4							CUM WT %	N/A	50.1	68.3	77.7	84.3	89.0	92.7

APPENDIX K

PARTICLE-SIZE AND CALCIUM CARBONATE DATA FOR 200-WEST AREA WELLS

APPENDIX K

PARTICLE-SIZE AND CALCIUM CARBONATE DATA FOR 200-WEST AREA WELLS

This appendix presents particle-size and calcium carbonate data for borehole samples collected during the drilling of 19 monitoring wells in the 200-West Area.

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0299-W05-002 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	2.4	N/	1.6	9.7	88.9	G	WT	N/A	842.1	17.9	18.4	8.2	8.3	18.0	N/A	18.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	88.9	2.6	1.1	1.3	2.5	N/A	1.6
SPLIT WT=	725.9							CUM WT %	N/A	88.9	91.3	93.6	94.7	98.0	N/A	100.0
10	1.9	N/	4.4	24.0	71.7	msG	WT	N/A	492.4	23.1	30.0	23.9	32.7	55.0	N/A	30.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	71.7	3.4	4.4	3.5	4.8	N/A	4.4
SPLIT WT=	688.9							CUM WT %	N/A	71.7	75.0	79.4	82.9	87.6	N/A	100.0
16	0.8	H	10.0	38.1	53.1	msG	WT	N/A	460.3	79.5	58.1	64.3	63.9	47.0	N/A	94.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.1	9.2	8.7	7.4	5.4	N/A	10.0
SPLIT WT=	856.2							CUM WT %	N/A	53.1	62.3	69.0	76.4	83.7	N/A	100.0
20	1.1	H	10.7	48.6	40.8	msG	WT	N/A	326.2	101.4	73.7	92.7	71.4	40.4	N/A	80.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	12.8	9.1	12.4	8.8	N/A	10.0
SPLIT WT=	808.2							CUM WT %	N/A	40.8	53.2	62.3	74.7	83.5	N/A	100.0
26	0.9	H	11.4	37.6	51.0	msG	WT	N/A	462.1	89.3	69.3	62.0	73.8	46.1	N/A	103.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.0	9.9	7.6	6.9	6.1	N/A	11.6
SPLIT WT=	907.7							CUM WT %	N/A	51.0	60.8	68.6	76.4	83.6	N/A	100.0
36	1.5	H	1.2	83.2	36.6	sg	WT	N/A	301.5	97.9	88.0	111.4	109.0	129.2	N/A	10.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.6	11.5	10.4	13.1	13.0	N/A	1.2
SPLIT WT=	849.9							CUM WT %	N/A	36.6	47.1	57.5	70.6	83.6	N/A	100.0
40	1.6	H	4.3	54.6	41.3	sg	WT	N/A	358.4	106.6	90.4	81.6	70.6	120.7	N/A	38.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.3	12.2	10.2	9.4	6.1	N/A	4.3
SPLIT WT=	869.1							CUM WT %	N/A	41.3	53.4	63.8	73.0	81.1	N/A	100.0
46	0.0	H	11.6	43.2	45.3	msG	WT	N/A	433.1	128.1	103.7	78.5	59.9	44.8	N/A	110.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.3	13.4	10.9	8.0	6.3	N/A	11.6
SPLIT WT=	958.5							CUM WT %	N/A	45.3	58.7	69.6	77.5	83.7	N/A	100.0
55	5.1	H	0.7	49.3	50.0	sg	WT	N/A	392.5	117.4	87.3	70.9	40.2	91.1	N/A	5.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	15.0	8.6	9.0	5.1	N/A	0.7
SPLIT WT=	784.0							CUM WT %	N/A	50.0	65.0	73.0	82.6	87.7	N/A	100.0
60	6.7	H	0.3	74.4	26.3	ps	WT	N/A	185.0	137.0	113.0	89.8	161.3	73.0	N/A	2.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.3	10.7	16.5	9.5	20.7	N/A	0.3
SPLIT WT=	732.6							CUM WT %	N/A	26.3	44.0	59.5	69.0	89.7	N/A	100.0
66	5.0	H	37.3	54.6	8.1	(g)ms	WT	N/A	53.4	29.3	39.0	42.0	53.4	107.7	N/A	240.9
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	8.1	4.4	5.9	6.4	8.1	N/A	37.3
SPLIT WT=	667.7							CUM WT %	N/A	8.1	12.5	18.4	24.7	32.8	N/A	100.0

K.3

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0299-W06-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
130	0.3	H	9.3	55.4	35.3	msG	WT	N/A	281.6	178.7	102.3	61.7	55.3	40.4	N/A	74.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.3	22.1	12.0	7.7	0.9	5.0	N/A	8.3
SPLIT	WT=	798.2					CUM WT %	N/A	35.3	57.4	70.2	78.0	84.0	90.7	N/A	100.0	
136	0.6	H	12.9	60.1	27.0	(m)gS	WT	N/A	219.4	70.0	87.1	115.1	151.7	63.0	N/A	104.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.0	8.0	10.7	14.2	10.7	7.9	N/A	12.9
SPLIT	WT=	817.0					CUM WT %	N/A	27.0	35.6	46.4	60.5	70.2	87.1	N/A	100.0	
140	0.4	H	8.1	50.0	34.0	msG	WT	N/A	908.0	81.8	80.7	213.0	114.1	50.2	N/A	73.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.0	8.0	9.0	23.5	12.0	5.5	N/A	8.1
SPLIT	WT=	908.4					CUM WT %	N/A	34.0	40.7	50.3	73.0	86.4	91.9	N/A	100.0	
146	0.5	H	11.8	62.7	25.5	(m)gS	WT	N/A	217.0	76.7	74.6	163.8	150.8	60.5	N/A	100.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.5	9.0	8.8	10.3	10.0	7.1	N/A	11.8
SPLIT	WT=	850.4					CUM WT %	N/A	25.5	34.5	43.3	62.5	81.1	90.2	N/A	100.0	
150	0.0	H	9.5	54.0	35.9	msG	WT	N/A	331.9	80.2	85.9	175.4	125.5	52.1	N/A	87.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.9	9.3	7.1	19.0	13.0	5.0	N/A	9.5
SPLIT	WT=	925.5					CUM WT %	N/A	35.9	45.2	52.3	71.3	84.9	90.5	N/A	100.0	
156	0.0	H	12.0	62.9	24.5	(m)gS	WT	N/A	214.4	98.0	74.0	138.1	157.2	84.0	N/A	110.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.5	11.3	6.5	15.5	10.0	9.0	N/A	12.0
SPLIT	WT=	978.0					CUM WT %	N/A	24.5	35.8	44.3	59.9	77.0	87.4	N/A	100.0	
160	0.0	H	9.1	67.2	23.7	(m)gS	WT	N/A	177.8	41.0	32.0	237.1	142.4	51.1	N/A	80.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	23.7	5.5	4.4	31.0	19.0	0.0	N/A	9.1
SPLIT	WT=	762.0					CUM WT %	N/A	23.7	29.1	33.5	65.1	84.1	90.9	N/A	100.0	
166	0.0	H	11.2	60.6	30.2	msG	WT	N/A	205.0	60.0	84.1	147.1	139.1	75.0	N/A	99.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.3	9.9	7.3	10.0	15.0	8.7	N/A	11.2
SPLIT	WT=	870.1					CUM WT %	N/A	30.3	40.1	47.5	64.2	80.1	88.0	N/A	100.0	
170	0.0	H	12.3	61.6	26.9	(m)gS	WT	N/A	227.9	68.7	80.4	170.3	151.1	81.1	N/A	107.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.9	7.0	7.0	20.1	17.2	0.2	N/A	12.3
SPLIT	WT=	880.9					CUM WT %	N/A	26.9	33.5	41.3	61.3	70.5	87.7	N/A	100.0	
175	0.0	H	11.0	47.9	40.6	msG	WT	N/A	375.7	75.0	67.7	122.0	132.4	85.7	N/A	107.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.6	8.2	7.3	13.2	12.1	7.1	N/A	11.0
SPLIT	WT=	932.0					CUM WT %	N/A	40.6	48.7	50.0	69.2	81.3	88.4	N/A	100.0	
180	0.0	H	10.9	46.2	42.9	msG	WT	N/A	304.7	82.0	51.9	85.1	140.9	80.0	N/A	92.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.9	7.4	6.1	7.7	17.3	7.0	N/A	10.9
SPLIT	WT=	850.5					CUM WT %	N/A	42.9	50.3	58.4	64.0	81.3	89.1	N/A	100.0	

2.5

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0290-W06-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	WT	WT %	CUM WT %	FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
185	0.0	H	8.3	48.1	43.6	msG	WT	N/A	375.9	116.1	62.7	78.8	103.2	54.1	N/A	71.4		
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	13.4	7.3	9.2	12.0	8.3	N/A	8.3	
SPLIT	WT= 668.0							CUM WT %	N/A	43.7	57.0	64.3	73.5	85.4	91.7	N/A	100.0	
190	0.0	H	8.0	68.3	22.1	(m)gS	WT	N/A	169.0	72.4	71.7	188.0	123.2	69.8	N/A	74.2		
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	22.1	9.4	9.3	24.4	16.0	9.1	N/A	9.7	
SPLIT	WT= 768.0							CUM WT %	N/A	22.1	31.5	40.8	65.3	81.3	90.4	N/A	100.0	
195	0.0	H	9.6	71.6	18.8	(m)gS	WT	N/A	143.6	90.0	70.3	189.2	113.8	73.5	N/A	72.7		
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	18.0	11.8	10.4	24.8	14.9	9.7	N/A	9.6	
SPLIT	WT= 781.6							CUM WT %	N/A	18.0	30.8	41.1	65.9	80.8	90.6	N/A	100.0	
200	0.1	H	9.3	67.1	23.6	(m)gS	WT	N/A	180.6	90.2	88.6	182.6	110.7	61.4	N/A	73.8		
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.6	11.4	10.9	23.1	14.0	7.8	N/A	9.3	
SPLIT	WT= 796.0							CUM WT %	N/A	23.6	35.0	46.0	68.9	82.9	90.7	N/A	100.0	
205	0.2	H	10.2	67.1	22.7	(m)gS	WT	N/A	178.7	94.6	83.7	179.6	106.9	64.3	N/A	80.6		
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	22.7	12.0	10.6	22.8	13.6	8.2	N/A	10.2	
SPLIT	WT= 787.4							CUM WT %	N/A	22.7	34.7	46.3	68.1	81.6	89.8	N/A	100.0	
210	1.0	H	10.2	66.4	23.4	(m)gS	WT	N/A	180.3	80.3	85.0	184.3	101.0	60.7	N/A	79.0		
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	23.4	10.4	11.1	23.9	13.1	7.9	N/A	10.2	
SPLIT	WT= 773.6							CUM WT %	N/A	23.4	33.8	44.9	68.8	81.9	89.8	N/A	100.0	
215	1.3	H	10.4	64.6	25.0	(m)gS	WT	N/A	190.3	83.9	74.3	177.2	94.4	61.1	N/A	79.4		
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.0	11.0	9.8	23.3	12.4	8.0	N/A	10.4	
SPLIT	WT= 762.8							CUM WT %	N/A	25.0	36.1	46.8	69.1	81.5	89.6	N/A	100.0	
220	0.9	H	9.9	64.9	35.2	msG	WT	N/A	267.3	86.2	82.0	125.8	91.8	51.2	N/A	75.0		
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.2	11.2	8.3	16.0	12.1	6.8	N/A	9.9	
SPLIT	WT= 760.3							CUM WT %	N/A	35.2	46.5	54.7	71.3	83.4	88.1	N/A	100.0	
225	2.3	H	14.2	61.2	24.6	(m)gS	WT	N/A	176.1	84.4	84.6	118.5	108.8	62.0	N/A	101.3		
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.6	11.6	9.0	18.6	15.2	8.7	N/A	14.2	
SPLIT	WT= 717.4							CUM WT %	N/A	24.6	36.4	45.4	62.0	77.2	85.8	N/A	100.0	
231	1.1	H	11.0	60.3	28.7	(m)gS	WT	N/A	154.0	73.0	75.1	186.4	114.6	60.1	N/A	82.1		
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	20.7	9.8	10.1	24.9	15.4	9.1	N/A	11.0	
SPLIT	WT= 749.2							CUM WT %	N/A	20.7	30.6	40.6	65.6	80.9	89.0	N/A	100.0	
236	1.0	H	11.4	61.0	27.6	(m)gS	WT	N/A	220.4	80.1	78.8	158.3	107.4	64.9	N/A	91.2		
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.6	11.0	9.8	19.0	13.4	8.9	N/A	11.4	
SPLIT	WT= 803.8							CUM WT %	N/A	27.6	38.8	48.6	65.3	81.7	89.6	N/A	100.0	

K.6

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0209-W07-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
5	1.1	C	0.7	29.0	84.3	msG	WT	N/A	519.3	60.6	40.6	24.3	41.9	69.3	N/A	53.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	84.3	8.6	5.0	3.0	5.2	7.3	N/A	6.7
SPLIT	WT=	807.7					CUM	WT %	N/A	84.3	72.8	77.8	80.9	86.0	93.3	N/A	100.0
10	1.3	C	2.1	18.7	79.2	msG	WT	N/A	669.7	68.9	62.0	16.0	10.7	14.9	N/A	18.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	79.3	7.9	0.0	1.0	1.2	1.7	N/A	2.1
SPLIT	WT=	670.2					CUM	WT %	N/A	79.3	67.2	93.1	95.0	96.2	97.9	N/A	100.0
16	0.6	H	26.2	42.4	32.4	msG	WT	N/A	140.0	53.8	47.3	35.8	32.9	23.6	N/A	114.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.4	11.0	10.4	7.0	6.2	N/A	26.2	
SPLIT	WT=	460.2					CUM	WT %	N/A	32.4	44.2	54.6	62.5	69.7	74.8	N/A	100.0
20	0.9	H	22.3	62.8	25.1	pmS	WT	N/A	109.4	92.8	80.4	34.0	25.9	18.1	N/A	97.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.1	21.3	13.9	7.0	5.9	3.7	N/A	22.3
SPLIT	WT=	436.1					CUM	WT %	N/A	25.1	40.4	60.2	68.0	74.0	77.7	N/A	100.0
26	0.8	H	13.8	38.0	48.4	msG	WT	N/A	140.6	38.9	27.2	21.5	18.2	11.1	N/A	41.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.4	12.2	9.0	7.1	0.0	3.7	N/A	13.8
SPLIT	WT=	302.6					CUM	WT %	N/A	48.4	60.6	69.6	78.7	82.7	86.4	N/A	100.0
30	0.9	H	17.7	44.0	38.3	msG	WT	N/A	140.7	57.4	40.9	28.0	25.8	18.9	N/A	68.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.3	14.0	10.5	7.2	0.0	4.9	N/A	17.7
SPLIT	WT=	368.6					CUM	WT %	N/A	38.3	63.0	63.6	70.8	77.4	82.3	N/A	100.0
36	1.1	H	24.6	38.0	36.6	msG	WT	N/A	149.9	60.6	36.3	27.2	26.3	17.8	N/A	89.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.6	12.4	8.9	6.7	0.2	4.4	N/A	24.6
SPLIT	WT=	406.0					CUM	WT %	N/A	36.6	49.2	66.2	64.8	71.1	76.4	N/A	100.0
40	1.3	H	19.0	39.2	41.1	msG	WT	N/A	150.6	46.7	33.7	25.6	21.3	14.3	N/A	71.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.1	13.3	9.2	7.0	5.8	3.9	N/A	19.0
SPLIT	WT=	368.0					CUM	WT %	N/A	41.1	54.4	63.8	70.6	76.5	80.4	N/A	100.0
46	1.3	H	19.6	39.7	40.6	msG	WT	N/A	150.9	47.6	32.0	26.9	24.4	16.0	N/A	71.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.6	12.9	9.7	7.3	6.6	4.3	N/A	19.6
SPLIT	WT=	369.7					CUM	WT %	N/A	40.6	63.7	62.3	69.6	76.2	80.6	N/A	100.0
50	2.7	H	13.4	53.6	33.1	msG	WT	N/A	106.4	50.6	49.4	32.8	24.2	14.9	N/A	43.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.1	16.0	15.4	10.2	7.5	4.6	N/A	13.4
SPLIT	WT=	321.7					CUM	WT %	N/A	33.1	48.9	64.2	74.4	82.0	88.6	N/A	100.0
56	2.9	H	12.2	62.3	35.6	msG	WT	N/A	141.8	60.3	55.6	39.2	27.0	10.1	N/A	40.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.6	17.3	14.1	9.8	7.0	4.0	N/A	12.2
SPLIT	WT=	399.6					CUM	WT %	N/A	35.6	62.0	67.0	70.8	83.7	87.8	N/A	100.0

K.7

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL B299-W07-B01 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
60	2.9	H	10.5	64.6	34.9	msG	WT	N/A	130.8	48.9	64.3	48.6	28.6	14.2	N/A	39.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.9	13.1	17.2	13.0	7.6	3.0	N/A	10.6
SPLIT	WT=	374.8					CUM WT %	N/A	34.9	48.0	66.1	78.1	85.7	89.5	N/A	100.0	
65	4.4	H	23.3	43.1	33.6	msG	WT	N/A	136.6	53.8	41.2	39.1	24.5	15.3	N/A	93.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.7	13.3	10.2	9.7	6.1	3.8	N/A	23.3
SPLIT	WT=	403.0					CUM WT %	N/A	33.7	47.0	57.2	66.9	73.0	76.8	N/A	100.0	
70	3.7	H	65.2	28.3	10.6	gsM	WT	N/A	35.1	19.0	12.1	9.3	17.6	28.8	N/A	210.1	
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.6	6.9	3.0	2.0	5.3	8.7	N/A	63.2
SPLIT	WT=	332.6					CUM WT %	N/A	10.6	10.5	20.1	22.9	28.2	30.8	N/A	100.0	
75	20.8	H	33.0	62.0	14.1	gmS	WT	N/A	45.2	22.7	22.3	24.0	43.3	63.3	N/A	108.6	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.1	7.1	7.0	7.8	13.6	16.7	N/A	33.9
SPLIT	WT=	320.3					CUM WT %	N/A	14.1	21.2	28.2	36.9	48.4	60.1	N/A	100.0	
80	13.7	H	25.6	59.4	16.0	gmS	WT	N/A	50.4	43.5	50.3	30.1	51.7	41.2	N/A	100.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	15.0	11.2	16.2	8.3	13.8	10.6	N/A	26.7
SPLIT	WT=	390.3					CUM WT %	N/A	15.0	26.1	41.3	50.6	63.8	74.4	N/A	100.0	
85	7.7	H	17.3	81.7	21.0	gmS	WT	N/A	00.2	48.0	52.4	47.8	49.4	40.0	N/A	66.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.0	12.2	13.7	12.5	12.9	10.5	N/A	17.3
SPLIT	WT=	382.7					CUM WT %	N/A	21.0	33.1	46.8	59.3	72.2	82.7	N/A	100.0	
90	5.2	H	16.6	77.4	6.0	(gm)S	WT	N/A	21.4	22.0	65.0	79.6	57.7	51.3	N/A	59.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.0	5.4	18.3	22.2	10.1	14.3	N/A	16.6
SPLIT	WT=	357.8					CUM WT %	N/A	6.0	12.4	30.7	52.9	69.1	83.4	N/A	100.0	
95	5.0	H	15.2	75.0	9.0	(gm)S	WT	N/A	33.2	35.6	75.9	77.5	53.7	37.0	N/A	55.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.0	9.9	20.6	20.9	14.5	10.0	N/A	15.2
SPLIT	WT=	370.2					CUM WT %	N/A	9.0	10.8	39.3	60.3	74.0	84.8	N/A	100.0	
100	8.6	H	12.0	78.8	9.2	(gm)S	WT	N/A	32.6	45.2	105.3	60.2	37.1	23.6	N/A	42.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.2	12.0	29.7	19.2	10.5	6.7	N/A	12.0
SPLIT	WT=	354.5					CUM WT %	N/A	9.2	21.9	51.6	70.9	81.3	88.0	N/A	100.0	
105	3.1	H	13.2	76.1	10.7	(m)gS	WT	N/A	37.0	61.2	107.1	62.1	27.2	15.4	N/A	45.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.7	14.0	31.0	19.0	7.9	4.5	N/A	13.2
SPLIT	WT=	345.7					CUM WT %	N/A	10.7	25.6	56.6	74.4	82.3	86.8	N/A	100.0	
110	2.3	H	12.1	83.6	4.3	(m)S	WT	N/A	14.1	23.8	92.1	104.1	30.5	14.9	N/A	39.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.3	7.3	28.2	31.8	11.8	4.5	N/A	12.1
SPLIT	WT=	320.9					CUM WT %	N/A	4.3	11.6	39.8	71.0	83.4	87.9	N/A	100.0	

K
0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0290-W07-001 ****

02/02/89

DEPTH	%CAC03	DM	%WUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	1.2	H	0.0	80.6	1.8	(m)S	WT	N/A	5.2	0.5	74.0	120.7	51.2	15.0	N/A	31.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	3.0	23.4	41.0	10.2	N/A	9.9
SPLIT	WT=	310.0						CUM WT %	N/A	1.0	4.0	28.0	69.0	85.1	N/A	100.0
120	0.0	H	0.4	89.4	1.1	S	WT	N/A	3.0	3.0	50.5	172.0	45.1	19.0	N/A	31.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.2	0.0	17.1	52.1	13.0	N/A	9.4
SPLIT	WT=	331.2						CUM WT %	N/A	1.2	2.1	19.1	71.2	84.9	N/A	100.0
125	0.0	H	4.0	93.4	1.7	S	WT	N/A	4.2	13.0	70.0	111.1	28.0	7.3	N/A	12.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.7	5.3	20.4	45.1	11.7	N/A	4.9
SPLIT	WT=	248.3						CUM WT %	N/A	1.7	7.0	35.4	80.4	92.2	N/A	100.0
130	0.0	C	7.7	80.0	11.5	gs	WT	N/A	92.0	177.9	242.0	121.0	71.1	30.7	N/A	62.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.5	22.1	30.3	15.1	0.0	N/A	7.7
SPLIT	WT=	800.3						CUM WT %	N/A	11.5	33.5	63.8	70.9	87.0	N/A	100.0
135	0.0	C	17.7	73.0	8.4	(pm)S	WT	N/A	28.7	31.4	120.0	40.1	20.0	10.0	N/A	00.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.4	0.2	37.8	14.4	0.4	N/A	17.7
SPLIT	WT=	340.3						CUM WT %	N/A	8.4	17.7	55.5	80.9	70.3	N/A	100.0
140	1.1	C	5.3	01.0	2.0	S	WT	N/A	20.1	72.3	329.1	107.6	50.0	23.0	N/A	30.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.0	0.0	45.2	25.0	7.0	N/A	5.3
SPLIT	WT=	720.7						CUM WT %	N/A	2.0	12.7	57.9	83.0	91.4	N/A	100.0
145	0.0	H	12.4	39.0	47.7	msG	WT	N/A	221.4	43.0	47.5	44.0	31.7	17.0	N/A	57.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.0	0.5	10.2	0.5	0.0	N/A	12.4
SPLIT	WT=	403.0						CUM WT %	N/A	47.0	57.2	67.6	77.0	83.0	N/A	100.0
150	0.0	H	19.0	41.0	40.0	msG	WT	N/A	105.0	40.1	40.3	43.0	33.0	21.2	N/A	00.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	0.0	10.0	0.3	4.0	N/A	19.0
SPLIT	WT=	404.0						CUM WT %	N/A	40.0	40.0	50.0	60.1	70.4	N/A	100.0
155	0.4	H	15.1	39.0	45.1	msG	WT	N/A	100.3	30.3	41.0	42.4	27.4	10.1	N/A	03.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	0.4	10.0	10.1	0.5	N/A	15.1
SPLIT	WT=	419.0						CUM WT %	N/A	45.1	54.5	84.4	74.5	81.1	N/A	100.0
160	0.2	H	21.4	40.0	30.0	msG	WT	N/A	133.1	45.0	47.3	50.0	30.1	23.0	N/A	03.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	10.5	10.0	13.1	0.3	N/A	21.4
SPLIT	WT=	435.1						CUM WT %	N/A	30.0	41.1	52.0	65.0	73.3	N/A	100.0
165	0.2	H	11.0	35.2	53.0	msG	WT	N/A	197.1	35.0	27.4	30.5	23.0	13.4	N/A	43.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.0	0.0	7.4	0.2	0.4	N/A	11.0
SPLIT	WT=	371.5						CUM WT %	N/A	53.0	62.0	70.0	70.2	84.0	N/A	100.0

K.9

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

**** REPORT ON WELL 0299-W07-001 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	0.2	H	20.7	48.1	33.2	msG	WT	N/A	123.8	40.9	44.0	35.0	31.4	20.3	N/A	77.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.2	11.0	9.5	6.4	5.4	N/A	20.7
SPLIT	WT=	373.2					CUM WT %	N/A	33.2	44.1	65.9	85.5	79.9	79.3	N/A	100.0
175	0.2	H	15.2	39.2	45.6	msG	WT	N/A	181.1	46.8	34.3	31.0	26.3	17.0	N/A	80.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.6	11.0	7.8	6.6	4.3	N/A	15.2
SPLIT	WT=	366.0					CUM WT %	N/A	45.6	57.4	66.1	73.9	80.5	84.8	N/A	100.0
180	0.4	H	17.8	37.5	44.7	msG	WT	N/A	224.7	45.0	38.0	30.3	43.4	24.3	N/A	80.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.7	9.1	7.2	7.8	5.8	N/A	17.0
SPLIT	WT=	503.2					CUM WT %	N/A	44.7	63.7	60.9	60.7	77.3	82.2	N/A	100.0
185	0.3	H	20.3	47.4	32.3	msG	WT	N/A	120.5	41.9	33.4	42.7	48.3	23.7	N/A	81.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.3	10.6	8.3	10.7	12.0	N/A	20.3
SPLIT	WT=	401.0					CUM WT %	N/A	32.3	42.7	61.1	61.7	73.8	79.7	N/A	100.0
190	0.3	H	22.7	48.4	28.9	gmS	WT	N/A	128.9	44.7	34.0	40.0	52.3	34.9	N/A	89.7
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.9	10.2	7.9	10.5	11.9	N/A	22.7
SPLIT	WT=	439.1					CUM WT %	N/A	28.9	39.1	47.0	57.4	69.4	77.3	N/A	100.0
195	0.2	H	20.6	48.5	32.9	msG	WT	N/A	131.2	44.3	29.7	45.2	43.3	22.8	N/A	82.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.9	11.1	7.5	11.3	10.0	N/A	20.6
SPLIT	WT=	398.7					CUM WT %	N/A	32.9	44.0	61.5	62.0	73.7	79.4	N/A	100.0
200	0.3	H	21.0	53.5	25.5	gmS	WT	N/A	89.2	46.1	31.4	44.4	44.3	21.1	N/A	73.3
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.5	13.2	9.0	12.7	12.7	N/A	21.0
SPLIT	WT=	349.7					CUM WT %	N/A	25.5	30.7	47.7	60.4	73.0	79.0	N/A	100.0
205	0.3	H	23.1	60.0	26.9	gmS	WT	N/A	92.0	41.5	20.9	42.9	39.3	10.7	N/A	70.2
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.9	12.1	8.4	12.5	11.5	N/A	23.1
SPLIT	WT=	342.4					CUM WT %	N/A	26.9	39.0	47.4	60.0	71.4	76.0	N/A	100.0
210	2.6	H	10.9	45.3	34.8	msG	WT	N/A	131.9	46.1	29.7	39.0	30.0	18.9	N/A	75.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.8	11.9	7.8	10.5	10.0	N/A	19.9
SPLIT	WT=	378.7					CUM WT %	N/A	34.8	46.7	64.6	65.1	75.1	80.1	N/A	100.0
215	2.4	H	20.8	51.9	21.6	gmS	WT	N/A	89.3	60.8	37.5	47.8	52.7	27.4	N/A	110.9
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.6	12.2	9.0	11.4	12.7	N/A	20.8
SPLIT	WT=	416.5					CUM WT %	N/A	21.6	33.7	42.7	54.1	66.8	73.4	N/A	100.0
220	1.3	H	23.0	61.1	25.4	gmS	WT	N/A	90.4	49.8	33.1	42.3	36.0	20.9	N/A	84.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.4	13.9	9.3	11.9	10.1	N/A	23.0
SPLIT	WT=	356.3					CUM WT %	N/A	25.4	39.3	48.6	60.5	70.0	76.4	N/A	100.0

K.10

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0289-W07-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
225	3.9	H	24.0	46.9	29.1	gmS	WT	N/A	101.5	41.4	29.5	40.3	35.3	17.3	N/A	84.0	
SDRT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.1	11.0	8.5	11.5	10.1	5.0	N/A	24.1
SPLIT	WT=	349.4					CUM	WT %	N/A	29.1	40.9	40.4	60.9	71.0	76.0	N/A	100.0
230	2.3	H	19.0	44.4	36.5	msG	WT	N/A	120.0	42.0	29.4	39.2	30.8	14.7	N/A	87.1	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.8	12.1	8.3	11.1	8.7	4.2	N/A	19.0
SPLIT	WT=	353.0					CUM	WT %	N/A	36.0	49.0	57.1	68.2	76.9	81.0	N/A	100.0
235	0.8	H	18.0	45.8	35.9	msG	WT	N/A	116.2	43.2	26.0	30.9	32.6	17.2	N/A	80.9	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.6	13.2	7.0	9.5	10.0	5.3	N/A	18.7
SPLIT	WT=	328.0					CUM	WT %	N/A	35.6	48.8	56.7	66.1	76.1	81.4	N/A	100.0
240	N/A	H	21.0	40.8	32.2	msG	WT	N/A	120.9	36.6	31.1	45.9	38.9	23.3	N/A	70.7	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.2	9.8	8.3	12.2	10.4	6.2	N/A	21.0
SPLIT	WT=	375.0					CUM	WT %	N/A	32.2	42.0	50.2	62.5	72.0	79.0	N/A	100.0
245	N/A	H	20.2	60.3	19.4	gmS	WT	N/A	68.8	38.4	20.2	60.4	52.5	25.5	N/A	71.0	
SDRT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.4	10.8	8.2	19.3	14.8	7.2	N/A	20.3
SPLIT	WT=	354.0					CUM	WT %	N/A	19.4	30.2	38.5	57.8	72.6	79.8	N/A	100.0

K.11

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W07-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	N/A	N/	8.4	38.6	55.1	msG	WT	N/A	348.6	69.2	61.9	34.9	44.4	39.1	N/A	53.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	66.1	8.4	6.8	5.8	7.1	6.2	N/A	8.4
SPLIT	WT=	629.8					CUM WT %	N/A	66.1	64.6	72.8	78.3	86.4	91.8	N/A	100.0	
10	0.8	N/	16.3	34.2	50.5	msG	WT	N/A	237.3	40.7	46.6	34.8	23.4	17.3	N/A	72.1	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.6	6.7	9.7	7.2	6.0	3.7	N/A	15.3
SPLIT	WT=	470.4					CUM WT %	N/A	60.6	69.1	68.6	76.0	81.0	84.7	N/A	100.0	
15	0.3	H	21.3	44.8	34.0	msG	WT	N/A	148.1	67.4	46.4	36.1	30.2	28.2	N/A	92.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.0	13.2	10.4	8.1	6.9	6.0	N/A	21.3
SPLIT	WT=	436.2					CUM WT %	N/A	34.0	47.2	57.7	66.7	72.7	78.7	N/A	100.0	
25	1.2	H	23.3	36.9	39.8	msG	WT	N/A	187.8	52.4	39.4	31.6	27.8	23.7	N/A	109.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.8	11.1	8.4	6.7	6.0	N/A	23.3	
SPLIT	WT=	471.2					CUM WT %	N/A	39.8	60.0	69.3	80.0	71.7	78.7	N/A	100.0	
30	2.8	H	36.7	53.0	10.3	gmS	WT	N/A	36.2	50.8	45.2	30.0	27.5	21.0	N/A	124.9	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.3	14.9	13.3	10.0	9.1	8.2	N/A	36.7
SPLIT	WT=	340.8					CUM WT %	N/A	10.3	25.2	38.5	49.1	67.2	63.8	N/A	100.0	
35	1.8	N	30.4	34.7	26.9	gmS	WT	N/A	102.0	42.4	30.4	25.1	18.4	15.9	N/A	146.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.9	11.1	8.0	6.8	4.8	4.2	N/A	38.4
SPLIT	WT=	381.4					CUM WT %	N/A	26.9	36.0	48.0	52.6	57.4	61.8	N/A	100.0	
40	2.0	H	70.7	23.3	0.0	(0)msH	WT	N/A	16.1	0.0	0.5	5.1	5.1	37.8	N/A	189.4	
SORT=	N/A	MEDIAN=	6.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.0	3.0	2.4	1.9	1.9	14.1	N/A	70.7
SPLIT	WT=	267.7					CUM WT %	N/A	6.0	0.0	11.4	13.3	15.2	20.3	N/A	100.0	
45	0.6	H	8.4	18.4	73.2	msG	WT	N/A	413.3	29.7	22.2	20.0	17.6	13.0	N/A	47.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.2	6.3	3.0	3.7	3.1	2.4	N/A	9.4
SPLIT	WT=	664.3					CUM WT %	N/A	73.2	70.6	82.4	86.1	89.2	91.8	N/A	100.0	
50	10.0	H	28.1	43.2	28.7	gmS	WT	N/A	100.4	38.6	38.4	24.8	23.4	20.1	N/A	98.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.7	11.0	11.0	7.1	6.7	7.6	N/A	26.1
SPLIT	WT=	350.2					CUM WT %	N/A	20.7	39.7	60.7	57.7	64.4	71.9	N/A	100.0	
55	6.8	H	16.3	37.1	47.7	msG	WT	N/A	194.8	61.2	38.2	28.8	19.0	16.1	N/A	82.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.7	12.5	8.9	7.1	4.7	3.9	N/A	15.3
SPLIT	WT=	408.3					CUM WT %	N/A	47.7	60.2	69.1	78.1	88.8	84.7	N/A	100.0	
60	3.1	H	16.5	58.3	20.2	gmS	WT	N/A	109.7	63.6	70.7	63.6	30.0	18.4	N/A	65.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.2	12.0	16.0	16.2	7.2	4.4	N/A	16.6
SPLIT	WT=	416.9					CUM WT %	N/A	20.2	39.0	67.0	72.9	80.1	84.6	N/A	100.0	

K.13

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0209-W07-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)		
66	4.1	H	16.9	48.4	34.7	msG	WT	N/A	140.8	49.5	53.9	50.7	28.7	10.0	N/A	64.2		
SDRT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.7	12.3	13.3	12.6	6.6	4.7	N/A	15.0
SPLIT	WT=	404.2					CUM WT %	N/A	34.7	47.0	60.3	72.8	79.4	84.1	N/A	100.0		
70	5.1	H	14.0	69.6	16.6	(m)gS	WT	N/A	61.9	38.4	91.0	71.2	30.2	21.0	N/A	52.6		
SDRT=	N/A		MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	16.5	10.2	24.5	19.0	5.6	N/A	14.8	
SPLIT	WT=	375.1					CUM WT %	N/A	16.5	26.7	51.2	70.2	80.4	85.0	N/A	100.0		
76	4.0	H	9.8	61.9	8.3	(gm)S	WT	N/A	31.4	43.3	142.9	67.7	36.9	19.7	N/A	37.3		
SDRT=	N/A		MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.3	11.4	37.7	17.9	5.2	N/A	9.6	
SPLIT	WT=	379.2					CUM WT %	N/A	8.3	19.7	57.4	75.2	86.0	90.2	N/A	100.0		
80	1.9	H	18.8	77.6	6.9	(gm)S	WT	N/A	21.2	26.0	137.8	74.9	24.1	16.3	N/A	59.7		
SDRT=	N/A		MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.9	7.5	38.3	20.6	4.3	N/A	16.6	
SPLIT	WT=	368.7					CUM WT %	N/A	5.9	13.4	61.6	72.4	79.1	83.4	N/A	100.0		
85	0.9	H	13.3	83.8	2.9	(m)S	WT	N/A	10.7	19.4	139.8	109.8	20.3	15.0	N/A	49.3		
SDRT=	N/A		MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.9	5.2	37.8	20.6	7.1	N/A	13.3	
SPLIT	WT=	370.2					CUM WT %	N/A	2.9	8.1	45.0	75.6	62.8	88.7	N/A	100.0		
96	0.8	H	6.8	48.2	47.9	msG	WT	N/A	100.0	13.4	61.6	80.7	18.9	9.5	N/A	23.3		
SDRT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.9	3.4	15.5	20.3	4.8	2.4	N/A	6.9
SPLIT	WT=	398.2					CUM WT %	N/A	47.9	61.3	66.8	87.0	91.0	94.2	N/A	100.0		
100	0.8	H	0.9	73.6	18.6	(m)gS	WT	N/A	57.8	7.8	32.0	164.9	48.5	13.8	N/A	34.5		
SDRT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.6	2.3	9.2	44.6	13.4	4.0	N/A	9.9
SPLIT	WT=	347.0					CUM WT %	N/A	16.6	16.8	28.1	72.7	86.1	90.1	N/A	100.0		
106	0.5	H	13.5	38.4	48.0	msG	WT	N/A	226.4	49.6	43.8	43.0	26.0	17.8	N/A	63.8		
SDRT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.0	10.6	9.3	6.5	3.8	N/A	13.5	
SPLIT	WT=	471.4					CUM WT %	N/A	48.0	58.6	67.9	77.2	82.7	86.5	N/A	100.0		
113	0.2	H	13.6	88.2	0.2	(m)S	WT	N/A	0.6	9.0	57.8	147.0	61.5	18.7	N/A	46.4		
SDRT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	2.6	17.0	43.1	5.5	N/A	13.6	
SPLIT	WT=	341.0					CUM WT %	N/A	0.2	2.8	19.6	62.9	80.9	88.4	N/A	100.0		
116	0.5	H	9.5	47.6	42.9	msG	WT	N/A	101.3	46.3	69.2	69.1	24.2	14.6	N/A	42.5		
SDRT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.9	10.4	13.3	15.3	5.4	3.3	N/A	9.5
SPLIT	WT=	446.3					CUM WT %	N/A	42.9	53.3	68.5	81.8	87.2	90.6	N/A	100.0		
120	0.5	H	18.5	61.0	30.5	msG	WT	N/A	132.7	34.8	58.4	71.7	36.9	21.4	N/A	60.6		
SDRT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.5	9.0	13.4	10.5	6.2	4.9	N/A	18.5
SPLIT	WT=	435.6					CUM WT %	N/A	30.5	38.5	61.9	68.3	76.6	81.5	N/A	100.0		

K.14

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0299-W07-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
125	0.6	H	10.5	42.7	46.8	msG	WT	N/A	189.3	37.5	34.9	54.0	31.1	14.9	N/A	42.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.8	9.3	8.6	13.4	7.7	3.7	N/A	10.5
SPLIT	WT=	404.2					CUM	WT %	N/A	46.8	56.1	64.7	78.1	85.8	89.5	N/A	100.0
130	0.6	H	14.9	53.0	32.1	msG	WT	N/A	137.5	34.4	45.3	77.2	46.5	23.5	N/A	63.6	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.1	8.0	10.8	18.0	10.9	5.5	N/A	14.9
SPLIT	WT=	428.1					CUM	WT %	N/A	32.1	40.2	50.8	68.8	79.7	85.1	N/A	100.0
135	0.5	H	15.7	41.1	43.3	msG	WT	N/A	157.4	32.2	33.2	41.8	26.6	16.8	N/A	57.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.3	8.9	9.1	11.4	7.0	4.0	N/A	15.7
SPLIT	WT=	383.9					CUM	WT %	N/A	43.3	52.1	61.2	72.7	79.7	84.3	N/A	100.0
140	0.2	H	19.2	40.2	40.8	msG	WT	N/A	173.4	40.0	38.0	37.4	30.9	24.7	N/A	61.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	9.4	9.0	8.8	7.2	5.0	N/A	19.2
SPLIT	WT=	428.7					CUM	WT %	N/A	40.8	50.0	59.0	67.0	75.0	80.0	N/A	100.0
145	0.2	H	10.3	70.2	19.5	(m)GS	WT	N/A	83.1	74.7	101.1	82.5	26.0	14.7	N/A	44.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.5	17.5	23.7	19.4	6.1	3.5	N/A	10.4
SPLIT	WT=	426.3					CUM	WT %	N/A	19.5	37.0	80.8	80.1	86.2	89.7	N/A	100.0
150	0.2	H	20.3	49.6	30.1	msG	WT	N/A	107.2	28.0	44.9	46.1	32.0	24.7	N/A	72.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.1	8.1	12.6	13.0	9.0	6.9	N/A	20.3
SPLIT	WT=	358.0					CUM	WT %	N/A	30.1	36.2	50.8	63.8	72.8	79.7	N/A	100.0
155	0.1	H	17.0	51.1	31.8	msG	WT	N/A	153.3	55.0	68.2	51.8	40.0	29.7	N/A	62.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.8	11.0	14.2	10.8	6.5	6.2	N/A	17.0
SPLIT	WT=	481.0					CUM	WT %	N/A	31.8	43.4	57.6	66.3	76.0	83.0	N/A	100.0
160	0.1	H	18.6	44.2	39.2	msG	WT	N/A	174.4	42.0	38.9	45.2	39.6	33.3	N/A	73.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.2	9.4	8.3	10.2	8.9	7.5	N/A	16.0
SPLIT	WT=	445.2					CUM	WT %	N/A	39.2	46.6	56.9	67.0	75.9	83.4	N/A	100.0
165	0.1	H	10.0	35.4	54.6	msG	WT	N/A	221.9	37.0	26.3	39.8	25.9	15.1	N/A	40.8	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	54.6	9.1	8.5	9.7	6.4	3.7	N/A	10.0
SPLIT	WT=	406.4					CUM	WT %	N/A	54.6	63.7	70.2	79.9	86.3	90.0	N/A	100.0
170	0.1	H	20.6	51.9	27.5	gmS	WT	N/A	108.2	40.1	39.4	62.6	37.6	24.4	N/A	60.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.5	10.2	10.0	15.9	9.0	6.2	N/A	20.5
SPLIT	WT=	392.9					CUM	WT %	N/A	27.5	37.8	47.8	63.7	73.3	79.5	N/A	100.0
175	0.1	H	29.2	46.2	24.5	gmS	WT	N/A	108.2	40.1	39.4	62.6	37.6	24.4	N/A	129.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	24.5	9.1	8.9	14.2	8.5	5.5	N/A	29.3
SPLIT	WT=	441.4					CUM	WT %	N/A	24.5	33.6	42.5	56.7	65.2	70.8	N/A	100.0

K.15

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 4

**** REPORT ON WELL 0290-W07-002 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
185	0.9	H	25.8	52.2	22.3	gms	WT	N/A	68.9	32.9	31.3	44.0	29.3	19.1	N/A	76.6
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	22.3	11.0	10.4	14.7	8.8	N/A	25.6
SPLIT	WT=	300.0					CUM WT %	N/A	22.3	93.3	43.7	58.4	68.1	74.6	N/A	100.0
190	0.2	H	22.1	55.3	19.8	gms	WT	N/A	73.7	59.6	46.7	48.6	39.1	25.6	N/A	83.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.6	15.6	12.4	12.9	10.4	N/A	22.1
SPLIT	WT=	276.2					CUM WT %	N/A	19.6	35.4	47.8	60.7	71.1	77.9	N/A	100.0
195	0.4	H	10.7	64.9	24.3	(m)gS	WT	N/A	80.6	40.9	42.0	67.2	38.4	28.2	N/A	35.6
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.3	12.4	12.7	20.3	11.0	N/A	10.7
SPLIT	WT=	334.4					CUM WT %	N/A	24.3	38.7	40.4	69.7	81.3	89.3	N/A	100.0
210	2.0	H	11.8	63.6	24.9	(m)gS	WT	N/A	77.4	42.6	30.6	57.2	41.0	25.6	N/A	36.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.9	13.7	9.9	18.4	13.2	N/A	11.6
SPLIT	WT=	311.6					CUM WT %	N/A	24.9	38.6	48.6	68.9	80.1	88.4	N/A	100.0
215	2.0	H	9.2	60.2	10.6	(m)gS	WT	N/A	67.8	135.2	111.0	113.4	98.0	61.1	N/A	69.0
SORT=	N/A	MEDIAN=	2.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.6	21.1	17.6	17.7	14.6	N/A	9.2
SPLIT	WT=	646.8					CUM WT %	N/A	10.6	31.7	49.1	66.8	81.3	90.6	N/A	100.0
220	2.2	H	7.6	53.3	39.2	msG	WT	N/A	319.2	95.7	76.0	115.8	98.0	47.4	N/A	61.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.2	11.8	9.3	14.2	12.1	N/A	7.6
SPLIT	WT=	814.8					CUM WT %	N/A	39.2	61.0	60.3	74.0	86.7	92.6	N/A	100.0
225	0.9	H	5.4	64.4	30.2	gG	WT	N/A	212.1	38.7	38.1	260.2	81.7	34.3	N/A	36.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	30.2	5.6	6.4	37.0	11.6	N/A	6.4
SPLIT	WT=	704.7					CUM WT %	N/A	30.2	35.7	41.1	78.1	89.7	94.6	N/A	100.0
230	0.1	H	2.1	56.0	41.0	sg	WT	N/A	329.4	49.2	57.7	262.2	70.1	17.6	N/A	16.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.0	8.1	7.2	32.7	8.7	N/A	2.1
SPLIT	WT=	804.7					CUM WT %	N/A	41.0	47.2	54.3	87.0	95.7	97.9	N/A	100.0
235	0.2	H	7.3	73.3	19.4	gS	WT	N/A	105.0	39.8	40.6	190.3	67.6	30.3	N/A	30.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	19.4	7.3	7.6	35.1	10.1	N/A	7.3
SPLIT	WT=	547.1					CUM WT %	N/A	19.4	20.7	34.2	69.3	86.4	92.7	N/A	100.0

K.16

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0290-W07-003 ****

02/02/89

DEPTH	%CAC03	OW	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	0.0	N/	N/A	12.0	87.1	N/A	WT	N/A	719.9	51.0	39.1	10.3	3.9	2.1	N/A	N/A
SORT=	N/A	MEDIAN=	-1.00	MODE=	N/A	MEAN=	N/A	WT %	N/A	87.1	5.2	4.7	1.3	0.6	N/A	N/A
SPLIT	WT=	832.3					CUM	WT %	N/A	87.1	93.3	98.0	99.3	99.7	100.0	N/A
10	0.4	H	14.4	28.1	57.6	msG	WT	N/A	285.2	42.8	36.0	24.0	22.0	19.7	N/A	71.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	57.6	8.6	8.1	5.0	4.4	N/A	14.4
SPLIT	WT=	495.8					CUM	WT %	N/A	57.6	86.1	72.2	77.2	81.7	85.6	100.0
15	0.5	H	18.2	31.5	52.3	msG	WT	N/A	263.2	41.1	37.6	30.2	28.0	22.0	N/A	81.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.3	8.2	7.6	8.0	5.3	N/A	16.2
SPLIT	WT=	502.8					CUM	WT %	N/A	52.3	80.5	68.0	74.0	79.3	83.8	100.0
20	1.7	H	18.4	35.0	46.6	msG	WT	N/A	198.2	40.0	36.0	28.0	23.0	19.0	N/A	77.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.6	9.6	8.5	6.0	4.6	N/A	18.4
SPLIT	WT=	421.4					CUM	WT %	N/A	46.6	58.2	64.8	71.6	77.0	81.0	100.0
25	1.5	H	24.7	39.2	38.1	msG	WT	N/A	145.6	44.7	37.3	30.2	23.9	21.8	N/A	99.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.2	11.1	9.3	7.6	5.9	N/A	24.7
SPLIT	WT=	402.5					CUM	WT %	N/A	38.2	47.3	56.5	64.0	70.0	75.3	100.0
30	2.7	H	13.0	22.3	84.7	msG	WT	N/A	291.4	34.0	21.6	18.1	14.4	12.0	N/A	58.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	84.7	7.0	4.8	4.0	3.2	N/A	13.0
SPLIT	WT=	460.2					CUM	WT %	N/A	84.7	72.3	77.1	81.2	84.4	87.0	100.0
35	1.0	H	58.0	20.4	21.0	gsm	WT	N/A	82.5	10.0	17.2	12.0	11.6	17.3	N/A	221.8
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.0	4.7	4.5	3.0	4.5	N/A	58.0
SPLIT	WT=	382.3					CUM	WT %	N/A	21.0	20.3	30.8	34.4	37.6	42.0	100.0
40	3.2	H	74.3	22.3	3.4	sm	WT	N/A	10.0	3.0	4.0	3.2	5.6	52.4	N/A	229.0
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	3.4	1.0	1.3	1.0	1.9	N/A	74.3
SPLIT	WT=	389.2					CUM	WT %	N/A	3.4	4.7	6.0	7.0	8.8	25.7	100.0
45	25.1	H	41.8	35.3	23.0	gsm	WT	N/A	61.3	16.7	13.0	12.0	17.0	31.9	N/A	111.4
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	23.0	7.0	5.1	4.8	8.4	N/A	41.8
SPLIT	WT=	267.0					CUM	WT %	N/A	23.0	30.0	35.1	39.9	46.3	60.3	100.0
50	13.1	H	20.3	44.7	35.0	msG	WT	N/A	127.5	51.8	44.2	23.4	21.3	21.0	N/A	73.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.0	14.2	12.2	6.4	5.9	N/A	20.3
SPLIT	WT=	363.8					CUM	WT %	N/A	35.0	49.3	61.4	67.0	73.7	79.7	100.0
55	6.7	H	21.2	38.1	40.7	msG	WT	N/A	160.3	68.0	42.4	20.8	16.3	14.0	N/A	83.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.7	14.2	10.8	5.3	4.1	N/A	21.2
SPLIT	WT=	394.1					CUM	WT %	N/A	40.7	64.9	65.8	70.9	75.0	78.6	100.0

K.17

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 2

**** REPORT ON WELL 0299-W07-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FTNE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	FAN (>4.75)
60	4.7	H	21.5	51.0	27.5	gmS									
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT	N/A	121.4	61.3	57.7	45.2	28.1	32.5
SPLIT	WT=	441.2						WT %	N/A	27.5	18.9	13.1	10.2	6.4	7.4
								CUM WT %	N/A	27.5	41.4	54.5	64.7	71.1	78.5
85	5.2	H	21.9	70.4	7.7	(g)ms									
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT	N/A	8.7	10.7	21.6	25.6	10.0	11.7
SPLIT	WT=	133.4						WT %	N/A	7.7	9.5	19.3	22.5	8.6	10.3
								CUM WT %	N/A	7.7	17.1	36.4	58.9	67.8	78.1
70	2.4	H	15.1	80.0	4.0	(m)S									
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT	N/A	17.8	39.7	117.4	81.6	32.4	23.5
SPLIT	WT=	368.0						WT %	N/A	4.0	10.0	31.9	22.2	8.8	6.4
								CUM WT %	N/A	4.0	16.0	47.5	69.7	78.5	84.9
75	11.1	H	14.8	77.5	7.7	(gm)S									
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT	N/A	27.1	38.1	116.2	60.4	31.0	20.3
SPLIT	WT=	350.6						WT %	N/A	7.7	10.9	32.9	17.2	9.0	7.5
								CUM WT %	N/A	7.7	18.6	51.5	68.7	77.7	85.2
85	0.5	H	4.4	77.7	17.8	gS									
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT	N/A	60.4	33.5	140.0	93.7	18.7	8.0
SPLIT	WT=	391.1						WT %	N/A	17.9	8.8	38.9	24.8	4.9	2.6
								CUM WT %	N/A	17.9	28.7	63.6	88.2	93.1	95.6
87	N/A	H	8.5	89.3	2.2	S									
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT	N/A	7.3	20.9	172.4	86.8	18.9	11.8
SPLIT	WT=	334.1						WT %	N/A	2.2	8.7	51.8	19.9	5.7	3.5
								CUM WT %	N/A	2.2	10.8	62.4	82.4	88.0	91.5
90	0.5	H	4.5	91.7	3.8	S									
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT	N/A	12.3	22.1	129.7	100.2	23.5	13.6
SPLIT	WT=	321.9						WT %	N/A	3.8	6.8	40.3	33.0	7.3	4.2
								CUM WT %	N/A	3.8	10.7	61.0	84.0	91.3	95.5
95	0.8	H	7.4	92.0	0.8	S									
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT	N/A	2.1	4.3	128.3	150.7	24.0	15.0
SPLIT	WT=	350.3						WT %	N/A	0.6	1.2	38.6	43.0	6.9	4.3
								CUM WT %	N/A	0.6	1.8	38.5	81.5	88.3	92.6
106	0.8	H	11.4	49.0	39.0	msG									
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT	N/A	148.8	20.6	28.2	85.1	32.3	15.1
SPLIT	WT=	371.8						WT %	N/A	39.0	5.8	7.8	23.0	8.7	4.1
								CUM WT %	N/A	39.8	45.2	52.8	75.8	84.8	88.6
110	24.1	H	38.4	43.9	17.6	gmS									
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT	N/A	61.0	28.0	24.0	23.3	31.3	48.4
SPLIT	WT=	349.3						WT %	N/A	17.6	7.6	8.9	6.7	9.0	13.9
								CUM WT %	N/A	17.8	25.2	32.1	38.8	47.7	61.6
110	0.4	H	17.2	49.2	33.0	msG									
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT	N/A	157.6	78.7	81.7	33.0	21.4	18.1
SPLIT	WT=	469.1						WT %	N/A	33.6	16.0	17.4	7.0	4.6	3.4
								CUM WT %	N/A	33.6	50.4	67.8	74.8	79.4	82.8

K.18

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0200-W07-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	0.0	H	15.0	57.0	27.2	gmS	WT	N/A	103.5	20.9	39.8	112.0	31.9	15.2	N/A	58.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	27.2	6.6	10.6	20.6	0.4	N/A	15.0
SPLIT	WT=	300.1					CUM	WT %	N/A	27.2	32.7	43.2	72.7	81.0	N/A	100.0
125	0.0	H	12.0	40.3	40.0	msG	WT	N/A	100.1	27.4	31.2	52.9	34.3	17.0	N/A	52.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	6.0	7.7	13.0	0.4	N/A	12.9
SPLIT	WT=	400.2					CUM	WT %	N/A	40.0	53.0	61.2	74.3	82.7	N/A	100.0
130	0.7	H	12.0	40.0	38.5	msG	WT	N/A	171.3	30.7	35.6	80.4	44.5	19.4	N/A	50.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	0.9	0.2	19.4	10.0	N/A	12.0
SPLIT	WT=	444.9					CUM	WT %	N/A	30.6	45.4	53.8	73.0	83.0	N/A	100.0
135	0.5	H	10.0	43.0	40.3	msG	WT	N/A	100.4	30.1	40.6	49.0	35.0	22.0	N/A	71.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.3	0.7	10.8	11.1	0.0	N/A	15.0
SPLIT	WT=	447.9					CUM	WT %	N/A	40.3	49.0	59.6	71.0	79.0	N/A	100.0
140	0.6	H	10.1	34.0	49.1	msG	WT	N/A	220.0	42.4	31.0	32.0	27.4	21.5	N/A	72.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.1	0.5	7.1	7.3	0.1	N/A	10.1
SPLIT	WT=	447.0					CUM	WT %	N/A	40.1	50.0	65.7	73.0	70.1	N/A	100.0
145	0.1	H	10.1	42.0	39.3	msG	WT	N/A	103.0	40.0	45.9	42.0	20.0	21.2	N/A	75.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.3	0.0	11.0	10.2	0.4	N/A	10.1
SPLIT	WT=	410.0					CUM	WT %	N/A	30.3	40.1	60.1	70.3	70.0	N/A	100.0
150	0.2	H	10.0	43.0	38.2	msG	WT	N/A	102.0	36.2	45.5	40.7	33.1	23.3	N/A	70.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.2	0.3	10.7	11.7	7.0	N/A	10.0
SPLIT	WT=	425.9					CUM	WT %	N/A	30.2	40.4	57.1	60.0	70.5	N/A	100.0
155	0.1	H	13.2	41.0	45.0	msG	WT	N/A	203.7	30.2	42.7	40.0	30.0	20.6	N/A	50.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.0	0.1	9.0	9.0	0.0	N/A	13.2
SPLIT	WT=	444.3					CUM	WT %	N/A	45.0	54.0	63.0	72.0	80.0	N/A	100.0
160	0.1	H	10.0	44.4	30.0	msG	WT	N/A	100.3	33.3	34.0	37.0	41.4	44.7	N/A	71.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	7.7	0.0	0.7	0.0	N/A	10.0
SPLIT	WT=	431.3					CUM	WT %	N/A	30.0	40.7	54.0	63.5	73.1	N/A	100.0
165	0.1	H	10.0	43.9	30.3	msG	WT	N/A	107.0	43.4	34.7	45.9	37.5	20.4	N/A	00.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.3	10.0	0.0	10.0	0.0	N/A	19.0
SPLIT	WT=	434.7					CUM	WT %	N/A	30.3	40.3	54.3	64.0	73.5	N/A	100.0
170	0.1	H	12.0	27.4	60.7	msG	WT	N/A	209.6	20.1	20.1	30.0	24.0	10.7	N/A	50.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	00.7	0.9	5.7	7.4	0.0	N/A	12.0
SPLIT	WT=	403.7					CUM	WT %	N/A	00.7	00.0	72.3	70.7	04.7	N/A	100.0

K.19

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W07-003 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
175	0.1	H	19.2	43.0	37.8	msG	WT	N/A	105.9	30.8	30.5	55.2	33.3	22.9	N/A	84.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.0	8.8	12.6	7.8	5.2	N/A	19.2
SPLIT	WT=	438.4						CUM WT %	N/A	37.8	48.8	68.0	75.8	80.8	N/A	100.0
180	0.1	H	11.0	30.0	58.1	msG	WT	N/A	255.0	24.0	23.0	48.4	23.1	15.7	N/A	48.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.1	6.6	11.0	6.3	3.6	N/A	11.1
SPLIT	WT=	440.0						CUM WT %	N/A	50.1	63.7	69.1	80.1	89.0	N/A	100.0
215	0.1	H	11.1	59.0	29.8	(m)gS	WT	N/A	200.0	91.5	61.0	89.5	97.5	65.5	N/A	74.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.9	13.8	9.2	13.3	14.5	N/A	11.1
SPLIT	WT=	673.2						CUM WT %	N/A	29.9	43.6	52.8	66.1	80.8	N/A	100.0
220	0.4	H	5.1	32.8	62.1	msG	WT	N/A	489.6	42.0	33.1	65.8	82.8	34.8	N/A	39.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	82.1	5.4	4.2	8.3	10.5	N/A	5.1
SPLIT	WT=	793.2						CUM WT %	N/A	62.1	67.5	71.7	80.1	90.6	N/A	100.0
225	0.2	H	10.3	58.7	31.0	msG	WT	N/A	217.0	50.9	50.2	99.0	131.0	82.2	N/A	72.1
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	9.0	7.2	14.2	18.7	N/A	10.9
SPLIT	WT=	706.3						CUM WT %	N/A	31.0	40.0	48.0	62.1	80.9	N/A	100.0
230	0.1	H	1.0	58.0	39.4	sg	WT	N/A	315.9	98.3	63.6	214.1	70.7	17.0	N/A	14.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.5	12.0	7.9	20.7	10.0	N/A	1.0
SPLIT	WT=	802.9						CUM WT %	N/A	39.5	51.5	59.4	86.2	96.1	N/A	100.0
235	0.1	H	3.0	92.9	3.2	S	WT	N/A	21.3	34.1	85.0	228.2	208.8	57.3	N/A	25.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.2	5.2	13.0	34.5	31.8	N/A	3.0
SPLIT	WT=	581.4						CUM WT %	N/A	3.2	8.4	21.4	55.9	87.5	N/A	100.0
240	0.1	H	5.3	66.7	28.0	gS	WT	N/A	155.0	75.0	50.5	142.0	73.5	29.8	N/A	29.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.0	13.5	9.1	25.5	13.2	N/A	5.3
SPLIT	WT=	500.7						CUM WT %	N/A	28.0	41.8	50.7	70.1	89.3	N/A	100.0
245	0.1	H	4.9	61.9	33.1	sg	WT	N/A	174.9	31.4	24.7	134.7	106.4	28.7	N/A	20.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.1	0.0	4.7	25.6	20.2	N/A	4.9
SPLIT	WT=	533.3						CUM WT %	N/A	33.1	39.1	43.8	69.4	89.0	N/A	100.0
250	0.1	H	4.1	79.0	16.9	gS	WT	N/A	101.0	44.3	31.9	239.1	126.3	30.0	N/A	24.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.9	7.4	6.3	40.0	21.1	N/A	4.1
SPLIT	WT=	500.5						CUM WT %	N/A	16.9	24.3	29.7	69.7	90.3	N/A	100.0
255	0.1	H	0.2	86.3	0.5	(g)S	WT	N/A	37.4	33.9	22.7	164.2	164.2	38.0	N/A	27.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.5	7.7	7.5	37.5	23.8	N/A	6.2
SPLIT	WT=	443.3						CUM WT %	N/A	8.5	16.3	23.7	61.2	81.3	N/A	100.0

K 20

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0290-W07-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
260	0.1	H	4.1	95.7	0.2	S	WT	N/A	1.1	4.4	20.0	334.0	189.0	30.4	N/A	25.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	0.7	4.3	63.0	30.6	0.3	N/A	4.1
SPLIT	WT=	823.1						CUM WT %	N/A	0.2	0.9	5.2	69.0	69.0	95.0	N/A	100.0
265	0.0	H	1.7	25.0	72.5	sG	WT	N/A	558.0	04.2	30.7	55.7	33.0	14.0	N/A	15.4	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	72.6	0.4	4.0	7.3	4.4	1.0	N/A	1.7
SPLIT	WT=	770.1						CUM WT %	N/A	72.6	80.0	84.8	92.1	96.4	98.3	N/A	100.0
270	0.4	H	2.5	30.2	59.3	sG	WT	N/A	400.5	110.0	59.2	70.0	43.0	19.0	N/A	21.0	
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	69.3	14.0	7.1	9.3	5.2	2.3	N/A	2.5
SPLIT	WT=	640.2						CUM WT %	N/A	69.3	73.0	80.6	89.9	95.2	97.6	N/A	100.0
275	1.0	H	2.3	29.0	07.9	sG	WT	N/A	524.0	75.0	34.3	07.0	30.7	15.0	N/A	17.5	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	07.0	9.0	4.4	0.6	4.8	2.1	N/A	2.3
SPLIT	WT=	774.2						CUM WT %	N/A	07.0	77.7	82.1	90.9	95.7	97.7	N/A	100.0
280	1.1	H	11.5	74.2	14.3	(m)gS	WT	N/A	02.2	31.4	40.2	100.4	114.6	71.0	N/A	00.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	14.3	5.6	8.0	27.0	20.0	12.6	N/A	11.5
SPLIT	WT=	570.0						CUM WT %	N/A	14.3	19.0	20.4	60.0	80.5	80.5	N/A	100.0
285	0.0	H	3.1	30.5	06.4	sG	WT	N/A	553.3	02.0	41.9	60.0	38.0	22.0	N/A	20.1	
SDRT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	00.4	11.0	6.0	7.2	4.0	2.0	N/A	3.1
SPLIT	WT=	037.0						CUM WT %	N/A	00.4	77.4	02.4	09.0	94.2	90.0	N/A	100.0
290	0.5	H	7.0	55.3	30.0	msG	WT	N/A	100.3	45.2	35.2	94.0	00.0	37.0	N/A	30.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.9	9.0	7.0	10.0	13.1	7.6	N/A	7.0
SPLIT	WT=	500.0						CUM WT %	N/A	30.9	45.9	52.9	71.7	04.7	92.2	N/A	100.0
295	0.4	H	5.0	07.1	27.0	gS	WT	N/A	223.0	110.3	50.2	201.0	05.0	42.4	N/A	40.1	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.0	14.0	11.1	25.2	10.7	5.3	N/A	5.0
SPLIT	WT=	000.2						CUM WT %	N/A	27.0	42.7	53.0	70.0	09.7	05.0	N/A	100.0
300	0.4	H	0.2	30.0	55.0	msG	WT	N/A	345.0	59.3	40.1	70.0	44.0	20.7	N/A	30.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	55.0	0.4	5.4	11.1	7.1	4.7	N/A	0.2
SPLIT	WT=	034.4						CUM WT %	N/A	55.0	04.5	70.0	02.0	09.1	93.0	N/A	100.0
305	0.3	H	0.0	71.4	22.0	gS	WT	N/A	120.0	121.7	00.2	117.1	50.7	20.0	N/A	30.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	22.0	22.1	12.0	21.3	10.3	5.1	N/A	0.0
SPLIT	WT=	550.4						CUM WT %	N/A	22.0	44.1	56.7	70.0	00.3	93.4	N/A	100.0
310	0.2	H	1.0	31.2	00.0	sG	WT	N/A	407.1	74.1	41.1	77.0	26.7	12.0	N/A	13.7	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	00.0	10.0	5.5	10.4	3.0	1.7	N/A	1.0
SPLIT	WT=	760.2						CUM WT %	N/A	00.0	70.9	02.5	92.0	96.4	98.2	N/A	100.0

K.21

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 6

**** REPORT ON WELL 0209-W07-003 ****

02/02/80

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
315	0.2	H	14.6	80.7	4.8	(m)S	WT	N/A	17.3	8.2	7.4	108.0	112.8	85.2	N/A	52.4
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	4.8	2.3	2.1	29.9	31.2	15.3	N/A	14.5
SPLIT	WT=	355.9					CUM WT %	N/A	4.8	7.1	9.1	39.0	70.2	85.5	N/A	100.0
320	0.4	H	1.3	35.9	82.8	sG	WT	N/A	423.3	78.4	22.9	83.7	45.8	11.4	N/A	9.0
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	82.8	11.8	3.4	12.4	8.8	1.7	N/A	1.3
SPLIT	WT=	679.2					CUM WT %	N/A	82.8	74.4	77.8	90.2	97.0	98.7	N/A	100.0
325	0.3	H	2.0	39.7	58.3	sG	WT	N/A	418.3	58.8	22.7	120.1	67.2	14.8	N/A	14.3
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	58.3	8.2	9.2	18.8	9.4	2.0	N/A	2.0
SPLIT	WT=	717.3					CUM WT %	N/A	58.3	60.6	69.7	86.0	90.0	90.0	N/A	100.0
330	0.9	H	5.3	87.6	27.1	gS	WT	N/A	114.1	49.2	32.0	119.2	82.8	21.5	N/A	22.4
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	27.1	11.7	7.6	28.3	14.9	5.1	N/A	5.3
SPLIT	WT=	421.8					CUM WT %	N/A	27.1	38.8	40.4	74.7	89.6	94.7	N/A	100.0
335	0.9	H	9.2	72.7	18.1	(m)gS	WT	N/A	73.2	39.4	65.8	97.3	60.2	32.3	N/A	37.4
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	18.1	9.7	16.2	24.0	14.9	8.0	N/A	9.2
SPLIT	WT=	486.8					CUM WT %	N/A	18.1	27.8	44.0	68.0	82.8	90.8	N/A	100.0
340	0.4	H	4.6	59.7	36.7	sG	WT	N/A	238.1	94.9	60.4	126.1	70.5	28.7	N/A	29.6
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	36.7	14.6	9.3	19.5	10.9	4.4	N/A	4.6
SPLIT	WT=	647.2					CUM WT %	N/A	36.7	51.4	60.7	80.1	91.0	95.4	N/A	100.0
345	0.5	H	4.1	83.8	12.4	gS	WT	N/A	80.3	51.7	62.6	248.0	144.1	35.2	N/A	26.3
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	12.4	8.0	9.6	36.3	22.2	5.4	N/A	4.1
SPLIT	WT=	651.9					CUM WT %	N/A	12.4	20.4	30.0	68.3	90.5	95.9	N/A	100.0
350	0.5	H	8.4	68.7	24.8	gS	WT	N/A	131.9	65.1	37.9	152.3	86.6	34.7	N/A	34.3
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	24.8	10.4	7.1	25.8	16.1	6.6	N/A	6.5
SPLIT	WT=	529.5					CUM WT %	N/A	24.8	36.2	42.3	70.9	87.0	93.6	N/A	100.0
355	0.6	H	7.5	77.3	15.3	gS	WT	N/A	85.3	74.7	52.1	153.3	100.8	41.2	N/A	41.8
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	15.3	13.4	9.3	29.2	18.0	7.4	N/A	7.5
SPLIT	WT=	557.6					CUM WT %	N/A	15.3	28.6	37.9	67.1	85.2	92.5	N/A	100.0
360	0.3	H	7.9	82.9	9.2	(g)S	WT	N/A	39.3	32.5	42.5	152.6	92.0	35.7	N/A	34.0
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	9.2	7.8	9.8	35.6	21.5	8.3	N/A	7.9
SPLIT	WT=	429.0					CUM WT %	N/A	9.2	10.6	28.7	62.3	83.7	92.1	N/A	100.0
365	0.2	H	7.2	84.8	8.0	(g)S	WT	N/A	38.7	34.0	52.5	205.2	90.4	35.7	N/A	34.6
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	8.0	7.1	10.9	42.7	16.7	7.4	N/A	7.2
SPLIT	WT=	484.0					CUM WT %	N/A	8.0	15.1	26.0	68.7	85.4	92.8	N/A	100.0

K.22

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 7

**** REPORT ON WELL 0299-W07-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
375	0.2	H	11.9	84.6	3.5	(m)S	WT	N/A	16.5	20.0	37.9	151.2	123.2	62.0	N/A	55.4	
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.5	4.3	8.1	32.4	26.4	13.3	N/A	11.9
SPLIT	WT= 469.2							CUM WT %	N/A	3.5	7.8	16.0	48.4	74.8	88.1	N/A	100.0
380	0.2	H	4.5	71.2	24.3	gS	WT	N/A	158.3	65.6	45.2	217.2	106.7	28.1	N/A	29.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	24.4	10.1	7.0	33.4	16.4	4.3	N/A	4.5
SPLIT	WT= 652.1							CUM WT %	N/A	24.4	34.4	41.4	74.8	91.2	95.5	N/A	100.0
385	0.2	H	3.4	49.4	47.2	sg	WT	N/A	318.1	68.0	42.2	133.4	66.7	28.2	N/A	22.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.2	10.2	6.3	19.9	10.0	3.0	N/A	3.4
SPLIT	WT= 870.3							CUM WT %	N/A	47.2	57.4	63.7	83.6	93.6	96.6	N/A	100.0
390	0.1	H	8.3	83.7	8.0	(g)S	WT	N/A	41.0	41.0	46.5	182.9	111.9	47.8	N/A	42.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.0	8.0	9.1	35.6	21.8	9.3	N/A	8.3
SPLIT	WT= 620.2							CUM WT %	N/A	8.0	16.0	25.0	60.6	82.4	91.7	N/A	100.0
395	0.2	H	4.7	85.2	10.2	gS	WT	N/A	51.2	35.0	38.8	231.0	95.8	27.3	N/A	23.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.2	7.0	7.7	46.0	19.0	5.4	N/A	4.7
SPLIT	WT= 607.5							CUM WT %	N/A	10.2	17.1	24.8	70.9	89.9	95.3	N/A	100.0
405	0.1	H	9.8	84.2	6.0	(gm)S	WT	N/A	24.3	30.1	36.2	120.7	97.3	56.0	N/A	39.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.0	7.4	9.0	29.9	24.1	13.9	N/A	9.8
SPLIT	WT= 409.6							CUM WT %	N/A	8.0	13.5	22.4	52.3	76.3	90.2	N/A	100.0
415	0.1	H	8.7	88.9	2.4	S	WT	N/A	12.8	47.9	57.8	185.2	122.7	62.9	N/A	46.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.4	8.9	10.8	34.5	22.9	11.7	N/A	8.8
SPLIT	WT= 642.4							CUM WT %	N/A	2.4	11.3	22.1	56.6	79.6	91.3	N/A	100.0
420	0.1	H	7.5	78.5	16.0	gS	WT	N/A	83.8	40.3	52.8	107.3	67.7	36.1	N/A	28.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.0	10.1	13.2	27.0	17.0	9.1	N/A	7.5
SPLIT	WT= 405.3							CUM WT %	N/A	16.0	26.1	39.4	66.4	83.4	92.5	N/A	100.0
425	0.1	H	7.1	80.8	12.2	gS	WT	N/A	58.0	52.5	80.8	137.3	75.7	39.0	N/A	33.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	12.2	11.0	10.9	28.8	15.9	8.2	N/A	7.1
SPLIT	WT= 484.4							CUM WT %	N/A	12.2	23.2	40.1	68.9	84.7	92.9	N/A	100.0
435	0.4	H	7.5	84.1	8.5	(g)S	WT	N/A	43.7	46.4	60.2	173.3	109.8	44.5	N/A	38.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.5	9.0	11.7	33.8	21.3	6.6	N/A	7.5
SPLIT	WT= 520.9							CUM WT %	N/A	8.5	17.4	29.1	62.7	83.9	92.5	N/A	100.0
450	0.2	H	5.3	72.7	22.0	gS	WT	N/A	145.1	132.5	109.8	134.0	68.7	35.1	N/A	35.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.0	20.1	18.6	20.3	10.4	5.3	N/A	5.3
SPLIT	WT= 664.4							CUM WT %	N/A	22.0	42.1	58.7	79.0	89.4	94.7	N/A	100.0

K.23

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W07-003 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
465	0.3	H	5.7	88.1	26.2	gS	WT	N/A	168.8	182.2	65.0	96.6	83.8	30.9	N/A	36.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.2	25.3	13.2	14.9	9.9	4.8	N/A	5.7
SPLIT	WT=	649.0					CUM WT %	N/A	26.2	51.5	64.7	79.6	89.5	94.3	N/A	100.0	
468	0.1	H	5.2	85.3	9.8	(g)S	WT	N/A	65.0	97.2	124.7	197.9	118.9	41.5	N/A	35.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.6	14.3	18.3	29.1	17.5	6.1	N/A	7.2
SPLIT	WT=	684.8					CUM WT %	N/A	9.6	23.8	42.7	71.3	88.7	94.8	N/A	100.0	
465	0.1	H	0.3	98.2	1.5	S	WT	N/A	10.8	57.0	162.5	241.2	138.1	61.1	N/A	60.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.6	7.8	22.3	33.1	18.7	8.4	N/A	8.3
SPLIT	WT=	732.8					CUM WT %	N/A	1.6	9.3	31.6	64.6	83.3	91.7	N/A	100.0	
470	0.2	H	6.5	80.8	33.7	gQ	WT	N/A	195.2	104.2	82.4	91.2	48.7	28.3	N/A	31.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.7	18.0	14.2	15.7	6.1	4.8	N/A	5.5
SPLIT	WT=	587.8					CUM WT %	N/A	33.7	51.6	65.9	81.6	89.6	94.6	N/A	100.0	
475	0.2	H	6.1	84.3	9.8	(g)S	WT	N/A	40.8	60.7	136.9	120.4	51.8	23.6	N/A	30.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.8	18.5	27.9	24.8	10.6	4.8	N/A	6.1
SPLIT	WT=	497.7					CUM WT %	N/A	9.8	26.0	54.0	78.5	89.1	93.9	N/A	100.0	

K.24

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 3

**** REPORT ON WELL 0299-W07-004 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	0.3	N/	12.3	48.4	39.3	msG	WT	N/A	275.7	28.3	38.3	38.7	77.1	157.5	N/A	00.4
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.3	4.0	5.5	11.0	22.4	N/A	12.3
SPLIT	WT=	701.0						CUM WT %	N/A	39.3	43.3	48.8	54.3	65.3	N/A	100.0
10	0.4	H	1.3	49.3	49.4	sG	WT	N/A	400.2	92.2	75.1	93.9	62.0	141.6	N/A	12.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.4	9.8	8.0	10.0	8.0	N/A	1.3
SPLIT	WT=	944.0						CUM WT %	N/A	49.4	59.2	67.2	77.1	83.7	N/A	100.0
16	1.1	H	2.2	45.1	52.7	sG	WT	N/A	450.1	87.8	81.7	74.1	59.1	100.0	N/A	19.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.7	10.1	7.1	8.6	12.5	N/A	2.2
SPLIT	WT=	808.0						CUM WT %	N/A	52.7	62.8	69.9	78.5	85.3	N/A	100.0
20	1.8	H	8.2	28.1	63.7	msG	WT	N/A	503.0	74.0	51.0	40.1	45.9	30.0	N/A	74.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	63.7	8.1	5.0	5.4	4.0	N/A	8.2
SPLIT	WT=	917.1						CUM WT %	N/A	63.7	71.8	77.6	82.0	87.8	N/A	100.0
25	1.8	H	8.2	29.8	62.0	msG	WT	N/A	522.9	75.0	48.3	48.4	47.5	31.2	N/A	60.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	62.0	9.0	5.7	5.7	3.7	N/A	8.2
SPLIT	WT=	845.2						CUM WT %	N/A	62.0	71.0	76.7	82.5	88.1	N/A	100.0
30	1.8	H	8.2	32.0	59.2	msG	WT	N/A	474.8	78.8	52.7	51.0	40.2	32.5	N/A	66.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	59.2	9.0	6.0	6.4	4.1	N/A	8.2
SPLIT	WT=	808.1						CUM WT %	N/A	59.2	69.0	75.5	82.0	87.7	N/A	100.0
35	1.8	H	6.2	35.9	58.9	msG	WT	N/A	480.0	75.9	71.7	75.2	47.7	28.2	N/A	43.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.9	9.1	8.6	9.0	3.4	N/A	5.2
SPLIT	WT=	838.3						CUM WT %	N/A	58.9	68.0	76.7	85.7	91.4	N/A	100.0
39	1.8	H	0.3	42.3	51.4	msG	WT	N/A	424.3	112.3	70.5	75.0	49.2	33.5	N/A	51.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.4	13.8	9.5	9.2	6.0	N/A	6.3
SPLIT	WT=	830.5						CUM WT %	N/A	51.4	65.0	74.5	83.7	89.7	N/A	100.0
45	1.5	H	0.0	51.0	47.5	sG	WT	N/A	371.1	138.5	70.1	77.8	46.9	69.9	N/A	7.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.5	17.7	9.0	10.0	8.0	N/A	0.0
SPLIT	WT=	784.7						CUM WT %	N/A	47.5	65.2	74.2	84.1	90.1	N/A	100.0
50	2.1	H	1.2	60.0	38.0	sG	WT	N/A	309.0	171.1	102.4	83.3	59.4	61.0	N/A	9.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.0	21.5	12.9	10.6	7.5	N/A	1.2
SPLIT	WT=	799.5						CUM WT %	N/A	38.0	60.3	73.1	83.0	91.1	N/A	100.0
55	7.1	H	1.0	65.0	33.4	sG	WT	N/A	272.5	145.0	132.4	110.6	66.4	60.4	N/A	12.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.4	17.0	10.2	14.3	8.2	N/A	1.0
SPLIT	WT=	810.0						CUM WT %	N/A	33.4	51.2	67.5	81.8	94.9	N/A	100.0

K.25

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 2

**** REPORT ON WELL 0290-W07-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
60	3.1	H	28.0	65.4	6.8	(g)mS	WT	N/A	32.7	21.3	20.5	68.1	32.6	189.4	N/A	137.9	
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	8.6	4.3	4.2	11.0	6.6	38.5	N/A	20.0
SPLIT	WT=	496.6					CUM WT %	N/A	6.8	11.0	16.1	26.0	33.5	72.0	N/A	100.0	
65	9.6	H	29.4	55.9	14.6	gmS	WT	N/A	96.2	39.1	38.5	69.2	77.7	117.0	N/A	173.5	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.6	8.6	6.2	10.1	13.2	19.9	N/A	29.5
SPLIT	WT=	595.5					CUM WT %	N/A	14.6	23.3	27.5	37.5	50.7	70.6	N/A	100.0	
70	0.4	H	17.8	75.1	7.0	(gm)S	WT	N/A	44.2	29.3	24.2	97.5	183.9	128.1	N/A	112.3	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	7.0	4.7	5.4	15.5	29.2	20.4	N/A	17.5
SPLIT	WT=	633.2					CUM WT %	N/A	7.0	11.7	17.1	32.6	61.8	82.2	N/A	100.0	
75	11.0	H	10.0	79.7	10.3	(m)gS	WT	N/A	65.7	31.0	69.3	83.7	195.6	128.7	N/A	64.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	10.3	4.9	10.9	13.1	38.7	28.2	N/A	10.0
SPLIT	WT=	639.7					CUM WT %	N/A	10.3	15.2	26.0	39.1	69.8	98.0	N/A	100.0	
80	1.1	H	5.8	79.3	14.9	gS	WT	N/A	111.7	100.2	262.8	130.8	51.9	38.5	N/A	43.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	14.9	13.4	35.1	17.5	8.3	5.1	N/A	5.6
SPLIT	WT=	750.0					CUM WT %	N/A	14.9	28.3	63.4	80.8	69.1	94.3	N/A	100.0	
85	0.9	H	3.2	90.5	6.3	(g)S	WT	N/A	38.7	39.6	244.8	174.2	44.9	28.0	N/A	18.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.3	6.8	41.9	29.8	7.7	4.5	N/A	3.2
SPLIT	WT=	581.2					CUM WT %	N/A	6.3	13.0	54.9	84.7	92.4	98.8	N/A	100.0	
90	0.9	H	6.1	93.8	1.2	S	WT	N/A	7.4	8.8	233.7	256.1	60.2	37.4	N/A	32.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.2	1.4	36.0	40.3	9.5	5.9	N/A	5.1
SPLIT	WT=	640.9					CUM WT %	N/A	1.2	2.5	39.3	79.6	89.0	94.9	N/A	100.0	
95	0.9	H	5.2	94.7	0.2	S	WT	N/A	1.3	6.6	210.4	315.6	53.2	31.0	N/A	33.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	1.0	32.9	48.0	8.1	4.7	N/A	5.2
SPLIT	WT=	660.3					CUM WT %	N/A	0.2	1.2	34.1	82.1	90.1	94.9	N/A	100.0	
100	1.1	H	4.9	90.5	4.6	S	WT	N/A	32.4	13.3	164.4	341.7	79.0	41.2	N/A	34.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.6	1.9	23.3	48.4	11.2	5.8	N/A	4.9
SPLIT	WT=	711.7					CUM WT %	N/A	4.6	8.5	29.7	78.1	89.3	95.1	N/A	100.0	
105	1.5	H	6.7	72.0	21.5	gS	WT	N/A	166.3	54.4	164.1	238.7	69.2	37.4	N/A	44.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	21.5	7.0	21.2	30.8	8.9	4.8	N/A	5.7
SPLIT	WT=	778.7					CUM WT %	N/A	21.5	28.5	49.7	80.5	89.5	94.3	N/A	100.0	
110	0.5	H	9.5	82.2	28.3	(m)gS	WT	N/A	222.0	78.7	105.9	169.3	69.8	44.9	N/A	74.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.3	10.0	13.5	21.5	11.4	5.7	N/A	9.5
SPLIT	WT=	781.7					CUM WT %	N/A	28.3	38.3	61.8	73.3	84.8	90.5	N/A	100.0	

K.26

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0200-W07-004 ****

02/02/00

DEPTH	%CAC03	DM	%MUO	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
115	0.0	H	7.6	42.9	49.5	msG	WT	N/A	383.3	66.7	63.7	103.0	71.6	30.8	N/A	60.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.5	8.3	8.0	13.0	9.0	4.6	N/A	7.6
SPLIT	WT=	796.9					CUM	WT %	N/A	49.5	67.8	66.8	78.8	87.8	92.4	N/A	100.0
120	0.0	H	8.7	49.0	41.5	msG	WT	N/A	346.7	79.0	66.4	132.4	82.1	54.8	N/A	72.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.5	9.0	7.9	15.9	9.9	6.6	N/A	8.7
SPLIT	WT=	834.2					CUM	WT %	N/A	41.5	51.1	59.0	74.9	84.7	91.3	N/A	100.0
126	0.0	H	9.0	49.0	41.4	msG	WT	N/A	354.2	84.1	63.5	103.0	79.4	59.2	N/A	81.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.4	9.0	10.9	12.1	9.3	8.9	N/A	8.6
SPLIT	WT=	866.0					CUM	WT %	N/A	41.4	61.2	62.1	74.2	83.6	90.4	N/A	100.0
130	0.4	H	9.4	50.6	31.9	msG	WT	N/A	276.2	83.0	114.8	145.3	98.6	66.4	N/A	81.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.9	9.0	13.3	10.8	11.4	7.8	N/A	8.4
SPLIT	WT=	866.0					CUM	WT %	N/A	31.9	41.6	54.8	71.6	83.0	90.6	N/A	100.0
136	0.6	H	8.4	47.4	44.2	msG	WT	N/A	376.0	73.7	70.1	116.7	106.4	39.0	N/A	71.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.2	8.6	8.2	13.0	12.4	4.8	N/A	8.4
SPLIT	WT=	862.1					CUM	WT %	N/A	44.2	62.0	61.1	74.0	87.0	91.6	N/A	100.0
140	0.0	H	8.6	48.3	43.0	msG	WT	N/A	370.0	80.1	81.8	103.9	100.7	51.2	N/A	70.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	9.1	9.3	11.8	12.4	6.8	N/A	8.6
SPLIT	WT=	866.0					CUM	WT %	N/A	43.0	62.1	61.4	73.1	85.0	91.4	N/A	100.0
145	0.7	H	9.3	48.1	44.6	msG	WT	N/A	423.0	76.4	91.4	103.4	100.2	59.0	N/A	88.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.6	8.0	9.0	10.9	11.4	6.2	N/A	9.3
SPLIT	WT=	956.1					CUM	WT %	N/A	44.6	62.6	62.2	73.1	84.6	90.7	N/A	100.0
150	0.1	H	10.5	42.5	47.0	msG	WT	N/A	398.9	71.2	51.9	111.1	91.9	32.0	N/A	80.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.0	8.4	6.2	13.2	10.9	3.9	N/A	10.6
SPLIT	WT=	848.0					CUM	WT %	N/A	47.0	66.4	61.6	74.0	86.6	89.6	N/A	100.0
155	0.2	H	10.7	53.1	36.2	msG	WT	N/A	319.0	90.2	70.9	132.2	114.0	52.1	N/A	83.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.2	11.2	8.1	16.0	13.8	6.9	N/A	10.7
SPLIT	WT=	866.4					CUM	WT %	N/A	36.2	47.4	55.6	70.6	83.4	89.3	N/A	100.0
160	0.1	H	9.0	61.1	39.3	msG	WT	N/A	324.6	69.4	60.6	137.9	97.9	50.8	N/A	79.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.3	8.4	7.3	10.7	11.9	6.9	N/A	9.0
SPLIT	WT=	833.6					CUM	WT %	N/A	39.3	47.7	66.0	71.7	83.0	90.4	N/A	100.0
165	0.2	H	9.6	63.1	27.4	(n)95	WT	N/A	214.8	99.8	70.8	154.6	113.6	50.1	N/A	74.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.4	12.7	9.8	19.7	14.5	8.4	N/A	9.6
SPLIT	WT=	789.1					CUM	WT %	N/A	27.4	40.1	49.9	62.7	84.2	90.6	N/A	100.0

K.27

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

**** REPORT ON WELL 0299-W07-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	0.1	H	9.4	58.3	32.3	msG	WT	N/A	246.6	83.4	77.0	136.9	92.6	53.1	N/A	71.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.3	11.0	10.1	18.0	12.2	7.0	N/A
SPLIT	WT=	767.9						CUM WT %	N/A	32.3	43.3	53.4	71.4	83.6	90.6	N/A
175	0.1	H	10.6	64.9	24.5	(m)gS	WT	N/A	171.9	84.4	64.3	133.0	108.9	66.0	N/A	74.8
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.5	12.0	9.2	19.0	15.5	9.3	N/A
SPLIT	WT=	708.5						CUM WT %	N/A	24.5	36.5	45.6	64.6	80.1	89.4	N/A
180	0.1	H	7.6	47.9	44.5	msG	WT	N/A	339.7	67.7	46.0	122.2	91.0	48.4	N/A	57.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.5	8.9	6.0	16.0	10.6	6.4	N/A
SPLIT	WT=	768.7						CUM WT %	N/A	44.5	53.4	59.4	75.5	86.1	92.4	N/A
185	0.1	H	8.9	52.6	28.5	(m)gS	WT	N/A	183.1	63.8	59.2	140.2	88.5	50.6	N/A	57.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.5	9.9	9.2	21.0	13.8	7.9	N/A
SPLIT	WT=	847.0						CUM WT %	N/A	28.5	38.4	47.7	69.6	83.3	91.1	N/A
190	0.1	H	9.7	55.6	34.6	msG	WT	N/A	247.6	80.1	52.8	117.4	93.9	51.3	N/A	68.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.6	11.3	7.4	18.5	13.2	7.2	N/A
SPLIT	WT=	714.1						CUM WT %	N/A	34.6	46.0	53.4	69.9	83.1	90.3	N/A
195	0.1	H	8.1	50.4	35.4	msG	WT	N/A	247.4	79.8	57.0	122.7	91.3	53.3	N/A	56.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.4	11.4	8.2	17.6	11.6	7.0	N/A
SPLIT	WT=	899.2						CUM WT %	N/A	35.4	46.9	55.0	72.6	84.2	91.9	N/A
200	0.1	H	7.1	42.9	50.0	msG	WT	N/A	374.2	60.0	50.6	84.7	67.4	43.1	N/A	58.3
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.0	8.0	6.0	11.3	9.0	6.0	N/A
SPLIT	WT=	750.1						CUM WT %	N/A	60.0	68.6	86.8	76.1	87.1	92.9	N/A
205	0.0	H	6.0	66.7	28.3	gS	WT	N/A	160.6	32.4	39.5	220.6	112.3	44.6	N/A	34.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	28.3	4.0	5.9	32.7	18.7	6.8	N/A
SPLIT	WT=	675.8						CUM WT %	N/A	28.3	33.1	39.0	71.7	88.3	95.0	N/A
210	0.1	H	7.2	75.0	17.8	gS	WT	N/A	94.1	29.4	29.4	148.5	130.6	57.8	N/A	37.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	17.8	5.6	5.6	28.2	24.8	11.0	N/A
SPLIT	WT=	528.2						CUM WT %	N/A	17.8	23.4	29.0	57.1	81.9	92.0	N/A
215	0.1	H	8.3	87.7	4.0	S	WT	N/A	27.1	18.1	00.5	378.1	65.2	51.1	N/A	56.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.0	2.7	9.8	55.3	12.5	7.5	N/A
SPLIT	WT=	881.7						CUM WT %	N/A	4.0	8.8	18.4	71.7	84.2	91.7	N/A
220	0.2	H	8.9	66.6	24.6	gS	WT	N/A	173.0	30.8	61.5	237.3	102.6	48.7	N/A	48.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	24.0	4.4	8.0	39.8	14.6	6.9	N/A
SPLIT	WT=	702.4						CUM WT %	N/A	24.0	29.0	37.8	71.6	86.1	93.1	N/A

K.28

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W07-004 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	0.2	H	7.8	82.1	30.3	msG	WT	N/A	184.3	50.7	65.1	164.0	78.5	41.9	N/A	48.7
SORT= N/A MEDIAN= 2.00 MODE= -1.00 MEAN= N/A							WT %	N/A	30.3	7.9	10.1	25.7	11.9	6.5	N/A	7.6
SPLIT WT= 648.4							CUM WT %	N/A	30.3	38.2	48.3	74.0	85.9	92.4	N/A	100.0
230	0.2	H	3.9	43.4	52.7	msG	WT	N/A	404.5	140.2	57.9	71.2	42.7	21.3	N/A	28.6
SORT= N/A MEDIAN= -1.00 MODE= -1.00 MEAN= N/A							WT %	N/A	52.7	18.3	7.6	9.3	5.0	2.8	N/A	3.9
SPLIT WT= 768.6							CUM WT %	N/A	52.7	71.0	78.6	87.8	93.3	96.1	N/A	100.0
235	2.2	H	4.0	26.8	69.4	msG	WT	N/A	590.8	71.6	36.3	51.9	40.1	22.9	N/A	33.2
SORT= N/A MEDIAN= -1.00 MODE= -1.00 MEAN= N/A							WT %	N/A	69.4	8.6	4.3	6.2	4.8	2.7	N/A	4.0
SPLIT WT= 636.6							CUM WT %	N/A	69.4	79.0	82.3	88.5	93.3	98.0	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W07-005 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.4	N/	0.5	10.9	82.8	G	WT	N/A	588.4	9.9	31.2	48.6	22.8	8.8	N/A	3.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	82.8	1.4	4.4	8.8	3.2	1.1	N/A	0.5
SPLIT	WT=	711.3					CUM WT %	N/A	82.6	84.0	88.3	95.2	98.4	99.5	N/A	100.0
10	2.4	N/	1.2	11.7	87.1	G	WT	N/A	618.3	16.0	21.0	18.0	13.4	14.8	N/A	0.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	87.1	2.3	3.0	2.6	1.9	2.1	N/A	1.2
SPLIT	WT=	710.6					CUM WT %	N/A	87.7	89.4	92.3	94.9	96.8	98.9	N/A	100.0
20	3.9	H	9.0	42.7	47.7	msG	WT	N/A	405.1	78.0	68.3	100.0	75.0	40.6	N/A	61.6
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	47.7	9.3	8.0	11.8	8.8	4.8	N/A	9.6
SPLIT	WT=	855.3					CUM WT %	N/A	47.7	57.0	65.0	76.8	85.8	90.4	N/A	100.0
30	2.9	H	28.3	52.3	19.4	pmS	WT	N/A	141.3	81.4	31.3	68.2	58.1	164.2	N/A	206.7
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	WT %	N/A	19.4	8.4	4.3	9.1	8.0	22.6	N/A	28.4
SPLIT	WT=	732.3					CUM WT %	N/A	19.4	27.8	32.1	41.2	49.1	71.7	N/A	100.0
40	10.7	H	10.7	71.4	17.0	(m)gS	WT	N/A	130.8	68.8	76.3	113.2	142.5	123.9	N/A	77.8
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	WT %	N/A	17.9	9.2	10.3	15.5	19.5	17.0	N/A	10.7
SPLIT	WT=	730.3					CUM WT %	N/A	17.9	27.1	37.4	52.9	72.4	89.4	N/A	100.0
45	7.9	H	5.2	50.2	44.7	sg	WT	N/A	382.0	117.0	79.0	162.7	87.2	82.0	N/A	44.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	44.7	13.8	9.2	12.0	7.9	7.3	N/A	5.2
SPLIT	WT=	852.1					CUM WT %	N/A	44.7	58.4	67.7	79.7	87.5	94.8	N/A	100.0
50	4.3	H	9.3	73.7	17.0	(m)gS	WT	N/A	134.5	75.2	171.3	164.8	165.0	75.4	N/A	73.5
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	17.0	9.6	21.7	19.6	13.3	9.6	N/A	9.3
SPLIT	WT=	783.0					CUM WT %	N/A	17.0	26.6	48.2	67.8	81.1	90.7	N/A	100.0
55	3.7	H	7.9	81.7	10.4	gs	WT	N/A	82.6	93.7	173.2	182.8	121.3	98.8	N/A	82.5
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	10.4	11.0	21.9	20.6	16.3	12.2	N/A	7.9
SPLIT	WT=	791.2					CUM WT %	N/A	10.4	22.2	44.1	64.7	80.0	92.1	N/A	100.0
60	6.2	H	8.8	86.4	5.8	(g)S	WT	N/A	41.0	69.0	148.4	251.8	88.5	54.3	N/A	62.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	5.8	9.8	21.0	35.0	11.4	7.7	N/A	8.8
SPLIT	WT=	783.0					CUM WT %	N/A	5.8	15.5	36.5	72.1	83.5	91.2	N/A	100.0
65	6.9	H	13.2	77.4	9.4	(gm)S	WT	N/A	88.4	59.6	119.0	159.0	181.0	107.1	N/A	92.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	9.4	8.4	17.0	22.5	14.4	15.2	N/A	13.2
SPLIT	WT=	710.8					CUM WT %	N/A	9.4	17.8	34.8	57.3	71.7	88.9	N/A	100.0
70	13.4	H	9.5	82.0	8.4	(gm)S	WT	N/A	54.2	59.4	178.5	135.7	78.9	77.0	N/A	62.2
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	WT %	N/A	8.4	9.2	27.4	21.0	12.4	11.9	N/A	9.0
SPLIT	WT=	645.0					CUM WT %	N/A	8.4	17.8	45.0	66.0	76.4	90.4	N/A	100.0

K.31

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W07-005 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
76	3.0	H	7.2	60.2	12.5	gS	WT	N/A	100.4	71.0	241.6	187.4	81.1	62.8	N/A	50.1
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	12.6	8.9	30.1	23.4	10.1	7.8	N/A	7.2
SPLIT	WT= 801.6						CUM WT %	N/A	12.6	21.4	51.6	74.8	84.9	92.8	N/A	100.0
80	0.7	H	9.2	55.7	36.8	msG	WT	N/A	284.9	84.6	114.8	108.3	78.9	34.0	N/A	69.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	30.0	11.2	15.2	14.4	10.6	4.6	N/A	9.3
SPLIT	WT= 754.7						CUM WT %	N/A	30.0	40.2	61.4	75.8	86.4	90.8	N/A	100.0
86	0.4	H	0.1	53.2	37.7	msG	WT	N/A	329.2	93.2	106.9	120.8	101.9	37.5	N/A	79.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	37.7	10.7	12.1	14.6	11.7	4.3	N/A	9.1
SPLIT	WT= 878.8						CUM WT %	N/A	37.7	48.3	60.4	74.9	86.6	90.9	N/A	100.0
90	0.3	H	7.6	52.3	40.2	msG	WT	N/A	360.6	74.3	131.6	162.1	87.1	43.8	N/A	67.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	40.2	8.3	14.7	17.0	7.6	4.9	N/A	7.6
SPLIT	WT= 906.8						CUM WT %	N/A	40.2	49.6	83.2	80.1	87.6	92.6	N/A	100.0
96	1.1	H	2.0	67.9	39.2	sG	WT	N/A	327.1	84.1	99.2	137.7	81.6	99.7	N/A	24.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	39.2	10.1	11.9	16.5	7.4	12.0	N/A	2.9
SPLIT	WT= 835.6						CUM WT %	N/A	39.2	49.3	61.2	77.8	86.1	97.1	N/A	100.0
100	0.6	H	0.6	64.0	29.5	gS	WT	N/A	227.3	80.4	163.0	190.7	54.7	29.1	N/A	50.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	29.5	7.8	19.0	25.6	7.1	3.8	N/A	6.6
SPLIT	WT= 784.9						CUM WT %	N/A	29.5	37.3	67.1	82.6	89.7	93.5	N/A	100.0
110	0.7	H	9.1	58.0	33.0	msG	WT	N/A	275.0	95.3	174.7	117.4	62.6	35.4	N/A	75.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	33.0	11.4	20.9	14.0	7.6	4.2	N/A	9.1
SPLIT	WT= 837.8						CUM WT %	N/A	33.0	44.3	65.2	79.2	86.7	90.9	N/A	100.0
116	0.2	H	3.6	62.9	33.6	sG	WT	N/A	270.7	69.9	109.0	155.2	81.4	90.2	N/A	20.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	33.6	8.7	13.6	19.3	10.1	11.2	N/A	3.6
SPLIT	WT= 808.1						CUM WT %	N/A	33.6	42.3	65.9	75.2	86.3	96.5	N/A	100.0
125	0.4	H	11.1	60.7	28.3	(m)gS	WT	N/A	266.3	103.1	97.3	107.4	116.6	63.6	N/A	90.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	28.3	11.4	10.8	18.6	12.9	7.0	N/A	11.1
SPLIT	WT= 902.6						CUM WT %	N/A	28.3	39.7	50.5	69.0	81.9	99.0	N/A	100.0
130	0.3	H	9.0	33.6	57.2	msG	WT	N/A	626.8	76.8	63.9	58.7	81.8	50.9	N/A	82.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	57.2	8.3	6.9	8.4	6.7	5.6	N/A	9.0
SPLIT	WT= 826.9						CUM WT %	N/A	57.2	66.6	72.4	78.8	86.6	91.0	N/A	100.0
136	0.4	H	7.5	58.5	34.0	msG	WT	N/A	291.8	133.3	114.9	120.6	82.2	49.7	N/A	64.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	34.0	15.6	13.4	14.8	9.8	5.3	N/A	7.5
SPLIT	WT= 800.6						CUM WT %	N/A	34.0	42.5	82.8	77.6	87.2	92.6	N/A	100.0

K.32

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 8299-W87-005 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
140	0.0	H	9.4	82.0	28.0	(m)gS	WT	N/A	247.5	93.0	125.1	146.3	129.9	80.5	N/A	83.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.0	10.6	14.1	16.4	6.8	N/A	9.4
SPLIT	WT=	888.8						CUM WT %	N/A	28.0	38.5	52.7	69.1	83.0	N/A	100.0
145	0.2	H	0.0	62.6	40.9	msG	WT	N/A	346.0	76.4	94.3	117.9	108.5	48.1	N/A	56.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.9	9.9	11.1	13.9	5.7	N/A	6.8
SPLIT	WT=	848.0						CUM WT %	N/A	40.9	49.8	60.9	74.9	87.7	N/A	100.0
160	0.1	H	9.3	52.2	38.4	msG	WT	N/A	341.3	87.4	74.3	128.2	119.1	54.7	N/A	82.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.5	9.9	8.4	14.4	8.2	N/A	9.3
SPLIT	WT=	890.4						CUM WT %	N/A	38.5	48.3	56.7	71.1	84.5	N/A	100.0
165	0.2	H	9.0	58.0	40.4	msG	WT	N/A	330.2	91.2	72.1	121.2	83.0	54.3	N/A	75.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.4	11.0	8.7	14.6	8.5	N/A	9.0
SPLIT	WT=	833.1						CUM WT %	N/A	40.4	51.3	60.0	74.6	84.5	N/A	100.0
180	0.0	H	12.5	57.4	30.1	msG	WT	N/A	259.8	104.4	77.5	123.3	132.4	57.7	N/A	100.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.1	12.1	9.0	14.3	8.7	N/A	12.5
SPLIT	WT=	865.7						CUM WT %	N/A	30.1	42.2	61.2	66.4	80.8	N/A	100.0
170	0.0	H	9.7	60.7	30.6	msG	WT	N/A	384.7	142.3	85.8	97.0	88.5	55.1	N/A	88.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	15.5	9.3	18.5	9.4	N/A	9.7
SPLIT	WT=	921.1						CUM WT %	N/A	30.6	55.1	64.4	75.0	84.4	N/A	100.0
180	0.0	H	11.0	89.1	20.3	(m)gS	WT	N/A	170.9	109.7	85.5	177.9	153.7	70.3	N/A	102.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.3	12.4	9.7	20.1	17.4	N/A	11.0
SPLIT	WT=	888.7						CUM WT %	N/A	20.3	32.7	42.4	62.5	79.0	N/A	100.0
190	0.0	H	10.2	80.7	23.1	(m)gS	WT	N/A	181.7	111.2	84.8	151.7	111.0	65.5	N/A	80.5
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.1	14.1	10.0	19.3	14.2	N/A	10.2
SPLIT	WT=	787.0						CUM WT %	N/A	23.1	37.2	48.0	67.2	81.5	N/A	100.0
195	0.1	H	12.0	82.3	24.8	(m)gS	WT	N/A	197.0	102.1	80.1	157.5	105.0	52.3	N/A	103.3
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.8	12.8	10.0	19.7	13.3	N/A	12.9
SPLIT	WT=	804.2						CUM WT %	N/A	24.8	37.5	47.0	67.3	80.5	N/A	100.0
200	0.1	H	12.0	87.6	19.0	(m)gS	WT	N/A	182.0	124.0	88.4	173.4	106.1	60.3	N/A	104.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	19.0	15.1	10.7	21.0	12.8	N/A	12.6
SPLIT	WT=	830.6						CUM WT %	N/A	19.0	34.7	45.4	68.4	79.2	N/A	100.0
215	0.1	H	11.1	66.4	22.5	(m)gS	WT	N/A	151.7	76.3	65.3	157.8	87.0	50.3	N/A	74.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	22.5	11.8	10.1	23.4	12.9	N/A	11.1
SPLIT	WT=	678.9						CUM WT %	N/A	22.5	34.1	44.3	67.7	80.8	N/A	100.0

K.33

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

*** REPORT ON WELL 0299-W07-005 ***

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
220	0.1	H	4.4	95.6	60.1	msG	WT	N/A	451.6	95.6	49.0	69.1	38.2	24.7	N/A	32.9
SORT= N/A MEDIAN= -1.00 MODE= -1.00 MEAN= N/A							WT %	N/A	60.1	12.7	6.6	7.9	6.1	3.3	N/A	4.4
SPLIT WT= 754.1							CUM WT %	N/A	60.1	72.9	79.4	87.2	92.3	95.6	N/A	100.0
225	0.2	H	11.6	80.2	0.2	(gm)S	WT	N/A	52.6	88.0	99.3	100.9	95.7	69.5	N/A	74.4
SORT= N/A MEDIAN= 2.00 MODE= 2.00 MEAN= N/A							WT %	N/A	0.2	13.7	15.6	25.1	14.9	10.9	N/A	11.6
SPLIT WT= 846.9							CUM WT %	N/A	0.2	22.0	37.5	61.6	77.5	88.4	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W07-006 ****

02/02/89

K.35

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	2.0	N/	1.3	12.5	88.2	G	WT	N/A	88.2	20.7	28.1	11.8	18.3	18.3	N/A	9.9
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	88.2	2.0	3.8	1.0	1.0	2.5	N/A
SPLIT	WT=	734.2						CUM WT %	N/A	88.2	89.8	92.8	94.4	96.2	98.7	N/A
10	1.0	N/	2.2	34.8	83.2	*G	WT	N/A	488.7	30.7	48.9	66.2	49.8	26.9	N/A	13.6
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	83.2	4.0	7.4	18.3	7.9	4.2	N/A
SPLIT	WT=	632.7						CUM WT %	N/A	63.2	68.0	75.4	86.7	93.6	97.8	N/A
15	0.0	H	13.0	43.4	43.8	msG	WT	N/A	346.7	89.4	86.7	68.3	87.8	61.5	N/A	102.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.8	11.9	8.3	11.1	8.6	N/A	13.8
SPLIT	WT=	794.9						CUM WT %	N/A	43.6	64.9	63.2	69.6	80.6	87.1	N/A
20	5.7	H	9.4	40.1	44.5	msG	WT	N/A	377.9	118.0	88.2	84.1	82.2	47.7	N/A	79.9
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.6	13.9	9.4	7.5	9.7	6.0	N/A
SPLIT	WT=	847.8						CUM WT %	N/A	44.6	68.8	67.8	75.3	86.0	90.8	N/A
25	9.9	H	6.2	52.6	41.2	msG	WT	N/A	341.7	119.2	97.6	82.2	88.6	41.0	N/A	61.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.2	14.4	11.8	9.9	11.7	4.9	N/A
SPLIT	WT=	827.4						CUM WT %	N/A	41.2	66.6	67.3	77.2	88.9	93.8	N/A
30	8.2	H	9.6	81.2	29.4	(m) pS	WT	N/A	229.6	100.2	98.0	99.8	123.9	64.4	N/A	74.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.4	12.8	12.8	12.8	16.9	7.0	N/A
SPLIT	WT=	782.8						CUM WT %	N/A	29.4	42.2	56.0	67.7	83.6	90.6	N/A
35	22.8	H	8.4	88.9	22.7	(m) pS	WT	N/A	109.8	87.6	90.6	90.7	162.4	88.7	N/A	83.2
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.7	11.7	12.9	12.1	20.4	11.8	N/A
SPLIT	WT=	748.0						CUM WT %	N/A	22.7	34.4	47.3	59.4	79.7	91.6	N/A
40	10.4	H	7.8	65.6	36.6	msG	WT	N/A	280.0	92.4	81.6	77.6	86.0	69.4	N/A	66.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.6	13.0	11.4	10.9	12.1	8.3	N/A
SPLIT	WT=	713.4						CUM WT %	N/A	36.6	49.6	60.9	71.8	83.8	92.2	N/A
45	7.9	H	6.0	89.2	24.8	pS	WT	N/A	212.8	138.1	118.3	123.0	139.4	77.1	N/A	61.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.8	10.1	13.6	14.4	10.2	9.0	N/A
SPLIT	WT=	866.4						CUM WT %	N/A	24.8	46.0	64.4	88.8	86.0	94.0	N/A
50	5.0	H	13.7	74.9	11.4	(m) pS	WT	N/A	87.7	71.6	166.0	107.9	124.4	117.3	N/A	100.0
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.4	9.3	20.3	14.0	10.1	15.2	N/A
SPLIT	WT=	773.6						CUM WT %	N/A	11.4	20.0	41.0	54.9	71.1	90.3	N/A
55	3.8	H	10.0	83.7	0.3	(gm) S	WT	N/A	46.4	48.6	203.8	179.1	92.1	80.6	N/A	71.9
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.3	6.7	28.3	24.8	12.8	11.2	N/A
SPLIT	WT=	723.3						CUM WT %	N/A	6.3	13.0	41.3	66.1	78.9	90.0	N/A

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

*** REPORT ON WELL 0299-W07-006 ***

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
00	3.3	H	0.3	88.9	4.8	S	WT	N/A	33.5	54.0	178.7	227.1	95.6	58.1	N/A	58.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.8	7.7	25.4	32.3	13.6	8.0	N/A	8.3
SPLIT	WT= 701.4							CUM WT %	N/A	4.8	12.4	37.8	70.1	83.7	91.7	N/A	100.0
05	2.6	H	6.1	87.0	3.9	S	WT	N/A	20.2	55.7	235.6	200.2	75.2	63.8	N/A	68.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.9	7.9	32.8	27.9	10.6	8.9	N/A	8.1
SPLIT	WT= 720.0							CUM WT %	N/A	3.9	11.8	44.6	72.5	83.8	91.9	N/A	100.0
70	5.6	H	8.9	84.5	6.7	(p)S	WT	N/A	50.7	72.0	251.3	175.1	65.9	57.7	N/A	67.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.7	9.6	33.0	23.0	11.4	7.6	N/A	8.9
SPLIT	WT= 760.8							CUM WT %	N/A	6.7	18.2	49.2	72.1	83.5	91.1	N/A	100.0
75	3.8	H	6.7	77.8	16.5	gS	WT	N/A	123.7	120.6	233.0	138.3	55.7	36.5	N/A	42.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	16.5	15.1	31.1	10.2	7.4	4.9	N/A	5.7
SPLIT	WT= 745.1							CUM WT %	N/A	16.5	32.7	63.8	82.0	89.4	94.3	N/A	100.0
80	8.0	H	7.4	68.1	24.5	gS	WT	N/A	225.7	162.0	192.7	136.6	92.0	44.0	N/A	68.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.5	17.7	20.9	14.7	10.0	4.8	N/A	7.4
SPLIT	WT= 923.3							CUM WT %	N/A	24.5	42.2	63.1	77.8	87.8	92.6	N/A	100.0
95	0.3	H	10.0	57.9	22.1	(m)gS	WT	N/A	210.1	131.0	164.4	213.9	89.6	48.3	N/A	95.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	22.1	13.8	17.3	22.6	9.4	5.1	N/A	10.0
SPLIT	WT= 951.6							CUM WT %	N/A	22.1	35.9	53.1	75.6	84.9	90.0	N/A	100.0
98	0.2	H	9.3	70.0	21.0	(m)gS	WT	N/A	198.7	110.0	152.3	205.1	112.0	62.7	N/A	76.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	21.0	12.0	16.6	22.4	12.3	6.8	N/A	8.3
SPLIT	WT= 915.8							CUM WT %	N/A	21.0	33.6	50.2	72.6	84.8	91.7	N/A	100.0
96	0.6	H	8.7	71.1	20.2	(m)gS	WT	N/A	152.8	92.0	167.2	126.6	61.2	59.5	N/A	66.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.2	12.2	22.1	19.3	10.7	7.9	N/A	8.7
SPLIT	WT= 759.2							CUM WT %	N/A	20.2	32.3	54.4	72.7	83.4	91.3	N/A	100.0
100	0.5	H	9.0	57.4	33.6	msG	WT	N/A	270.7	110.6	135.0	95.1	72.9	48.3	N/A	72.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.6	13.7	16.8	11.8	9.1	6.0	N/A	9.0
SPLIT	WT= 804.4							CUM WT %	N/A	33.6	47.3	64.2	78.0	85.0	91.0	N/A	100.0
105	0.6	H	8.1	59.3	32.7	msG	WT	N/A	258.2	96.0	155.9	109.1	75.3	49.4	N/A	66.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.7	11.8	19.0	13.3	9.2	6.0	N/A	8.1
SPLIT	WT= 813.8							CUM WT %	N/A	32.7	44.5	63.4	76.7	86.9	91.9	N/A	100.0
110	0.6	H	7.4	68.8	23.8	gS	WT	N/A	183.2	78.7	192.1	125.3	77.9	58.6	N/A	57.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	23.8	10.2	24.9	16.3	12.1	7.3	N/A	7.4
SPLIT	WT= 771.2							CUM WT %	N/A	23.8	34.0	58.9	78.1	85.2	92.6	N/A	100.0

K.30

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0209-W07-008 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	0.8	H	7.8	59.2	33.2	msG	WT	N/A	288.6	75.4	110.9	149.6	92.3	51.3	N/A	81.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	33.2	9.3	13.7	18.5	11.4	6.3	N/A	7.6
SPLIT	WT=	802.5					CUM WT %	N/A	33.2	42.5	56.2	74.7	86.1	92.4	N/A	100.0
120	0.8	H	7.2	48.8	44.0	msG	WT	N/A	383.0	79.8	94.4	119.1	83.2	49.0	N/A	82.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	44.0	9.1	10.8	13.7	9.8	6.0	N/A	7.2
SPLIT	WT=	871.2					CUM WT %	N/A	44.0	53.1	64.0	77.6	87.2	92.8	N/A	100.0
125	0.5	H	8.4	54.2	37.4	msG	WT	N/A	328.9	80.9	100.0	137.9	100.4	57.3	N/A	73.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	37.4	9.2	11.4	15.7	11.4	6.5	N/A	8.4
SPLIT	WT=	893.0					CUM WT %	N/A	37.4	46.6	58.0	73.7	85.1	91.6	N/A	100.0
130	0.2	H	8.1	48.4	43.4	msG	WT	N/A	375.0	112.6	84.4	90.0	74.8	50.5	N/A	70.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	43.4	13.0	9.8	11.1	8.7	5.9	N/A	8.1
SPLIT	WT=	864.0					CUM WT %	N/A	43.4	56.5	66.2	77.4	86.0	91.9	N/A	100.0
135	0.3	H	9.8	53.1	37.4	msG	WT	N/A	337.3	95.1	91.4	122.0	110.3	62.2	N/A	86.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	37.4	10.5	10.1	13.5	13.1	5.8	N/A	9.8
SPLIT	WT=	904.2					CUM WT %	N/A	37.4	47.9	58.0	71.5	84.8	90.4	N/A	100.0
140	0.4	H	10.0	53.3	36.7	msG	WT	N/A	325.1	75.6	84.6	140.0	109.0	60.7	N/A	88.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	36.7	8.6	9.6	15.0	12.4	6.9	N/A	10.0
SPLIT	WT=	889.9					CUM WT %	N/A	36.7	45.3	54.6	70.7	83.2	90.0	N/A	100.0
150	0.1	H	7.4	38.1	54.4	msG	WT	N/A	513.0	100.0	71.3	77.8	84.0	48.0	N/A	70.1
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	54.6	10.7	7.8	8.2	6.0	4.9	N/A	7.4
SPLIT	WT=	948.1					CUM WT %	N/A	54.6	65.1	72.7	90.9	97.7	92.6	N/A	100.0
155	0.4	H	11.0	81.5	27.4	(m)G5	WT	N/A	268.7	100.0	81.7	124.4	100.0	73.2	N/A	103.3
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	WT %	N/A	27.4	11.2	8.7	13.3	20.4	7.8	N/A	11.0
SPLIT	WT=	936.7					CUM WT %	N/A	27.4	38.7	47.5	60.8	81.2	89.0	N/A	100.0
160	0.2	H	9.8	53.3	37.7	msG	WT	N/A	358.1	97.7	69.8	114.1	141.5	83.5	N/A	85.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	37.7	10.3	7.3	12.0	14.9	8.8	N/A	9.8
SPLIT	WT=	960.9					CUM WT %	N/A	37.7	48.0	55.3	67.3	82.2	91.0	N/A	100.0
165	0.2	H	8.3	42.4	49.3	msG	WT	N/A	409.3	97.4	83.3	82.8	108.5	52.2	N/A	79.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	49.3	10.2	6.6	8.7	11.4	6.5	N/A	8.3
SPLIT	WT=	953.8					CUM WT %	N/A	49.3	59.5	66.1	74.8	80.2	91.7	N/A	100.0
170	0.1	H	10.3	55.4	34.3	msG	WT	N/A	314.4	141.7	87.8	101.3	120.7	57.1	N/A	94.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	34.3	16.4	9.8	11.0	13.2	6.2	N/A	10.3
SPLIT	WT=	917.3					CUM WT %	N/A	34.3	49.7	59.3	70.3	83.5	89.7	N/A	100.0

K.37

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAND REPORT

**** REPORT ON WELL 0299-W07-006 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (24.75)
175	0.2	H	10.1	57.3	32.6	msG	WT	N/A	287.0	86.1	72.6	116.6	161.5	68.0	N/A	68.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.6	9.0	8.3	13.1	18.4	7.7	N/A
SPLIT	WT=	680.5						CUM WT %	N/A	32.6	42.4	50.7	63.8	82.2	89.9	N/A
180	0.2	H	12.2	54.7	33.1	msG	WT	N/A	261.3	86.8	64.3	116.2	119.6	57.7	N/A	92.5
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.1	9.1	7.2	15.2	16.8	7.8	N/A
SPLIT	WT=	757.4						CUM WT %	N/A	33.1	42.2	49.3	64.5	80.2	87.8	N/A
185	0.3	H	10.8	55.1	34.1	msG	WT	N/A	270.6	90.3	66.2	115.0	101.5	54.0	N/A	86.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.1	11.4	8.3	14.6	12.8	8.1	N/A
SPLIT	WT=	793.1						CUM WT %	N/A	34.1	45.6	53.8	68.4	81.2	89.2	N/A
190	0.2	H	10.4	64.9	24.6	(m)gS	WT	N/A	166.1	87.5	72.0	102.4	166.6	67.8	N/A	70.5
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.6	11.6	9.6	13.6	22.4	7.7	N/A
SPLIT	WT=	754.2						CUM WT %	N/A	24.6	36.3	46.8	59.6	81.9	89.8	N/A
195	0.2	H	8.3	47.8	43.9	msG	WT	N/A	392.6	62.3	64.7	127.3	86.7	68.0	N/A	74.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.9	9.2	7.2	14.2	9.7	7.5	N/A
SPLIT	WT=	893.2						CUM WT %	N/A	43.9	63.1	60.3	74.6	84.2	91.7	N/A
200	0.2	H	10.7	67.8	26.5	(m)gS	WT	N/A	204.6	124.1	104.9	102.6	100.1	53.7	N/A	82.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.5	18.1	13.6	13.3	13.0	7.0	N/A
SPLIT	WT=	772.0						CUM WT %	N/A	26.5	42.6	56.1	69.4	82.4	89.3	N/A
205	0.2	H	8.2	45.5	46.3	msG	WT	N/A	371.8	80.6	64.1	81.5	93.1	45.4	N/A	65.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.3	10.1	8.0	10.2	11.0	5.7	N/A
SPLIT	WT=	803.0						CUM WT %	N/A	46.3	66.4	64.4	74.6	86.1	91.8	N/A
210	0.2	H	10.0	59.6	30.4	msG	WT	N/A	220.2	102.3	97.4	103.1	78.9	61.0	N/A	72.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.4	14.1	13.6	14.2	10.6	7.2	N/A
SPLIT	WT=	723.7						CUM WT %	N/A	30.4	44.6	58.0	72.2	82.9	90.0	N/A
215	0.0	H	8.6	59.1	31.5	msG	WT	N/A	260.9	103.8	119.9	109.7	66.2	52.5	N/A	75.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.5	13.0	15.0	13.8	10.7	6.0	N/A
SPLIT	WT=	797.6						CUM WT %	N/A	31.5	44.6	59.6	73.3	84.0	90.6	N/A
220	0.0	H	9.3	63.0	26.0	(m)gS	WT	N/A	210.5	80.0	72.0	106.6	102.4	68.0	N/A	72.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.0	10.3	9.3	23.9	13.1	7.2	N/A
SPLIT	WT=	784.0						CUM WT %	N/A	26.0	37.3	46.6	70.4	83.6	90.7	N/A
226	0.0	H	8.6	68.0	25.5	(m)gS	WT	N/A	195.8	107.3	127.8	136.3	89.2	47.9	N/A	66.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.5	14.0	16.6	17.7	11.6	6.2	N/A
SPLIT	WT=	776.6						CUM WT %	N/A	25.5	39.4	56.0	73.7	86.2	91.4	N/A

K.38

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W07-005 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
236	1.5	H	7.8	84.9	27.3	(m)gS	WT	N/A	179.1	71.8	82.8	142.4	102.9	46.1	N/A	51.1
SORT= N/A MEDIAN= 2.00 MODE= -1.00 MEAN= N/A							WT %	N/A	27.3	11.8	9.8	21.7	15.7	8.9	N/A	7.8
SPLIT WT= 854.9							CUM WT %	N/A	27.3	38.3	47.9	69.6	85.3	92.2	N/A	100.0
240	1.1	H	8.4	88.8	43.6	msQ	WT	N/A	329.7	84.8	83.8	118.2	74.6	37.7	N/A	48.8
SORT= N/A MEDIAN= 0.00 MODE= -1.00 MEAN= N/A							WT %	N/A	43.6	11.1	8.4	16.6	9.9	6.0	N/A	8.4
SPLIT WT= 762.7							CUM WT %	N/A	43.6	54.7	63.1	78.7	88.6	93.6	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 1

**** REPORT ON WELL 0299-W08-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	1.3	H	18.8	43.8	38.2	msG	WT	N/A	156.7	37.0	34.1	24.4	47.3	32.4	N/A	77.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.2	9.3	8.3	6.0	11.6	7.9	N/A	18.8
SPLIT	WT=	408.8						CUM WT %	N/A	38.2	47.5	56.8	61.8	73.3	81.2	N/A	100.0
10	0.8	H	17.9	41.4	40.8	msG	WT	N/A	167.2	46.8	44.1	24.0	31.5	23.2	N/A	73.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.8	11.4	10.8	5.9	7.7	5.7	N/A	17.9
SPLIT	WT=	418.0						CUM WT %	N/A	40.8	62.2	63.0	68.8	76.5	82.1	N/A	100.0
15	0.6	H	21.7	41.3	37.0	msG	WT	N/A	149.6	56.1	41.8	25.5	24.8	18.9	N/A	67.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.0	13.9	10.3	6.3	6.1	4.7	N/A	21.7
SPLIT	WT=	404.2						CUM WT %	N/A	37.0	58.9	61.2	67.5	73.6	78.3	N/A	100.0
20	0.8	H	21.8	37.4	41.8	msG	WT	N/A	219.9	64.2	48.8	33.4	31.3	23.3	N/A	115.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.1	12.0	9.0	6.2	5.8	4.4	N/A	21.8
SPLIT	WT=	636.7						CUM WT %	N/A	41.1	53.9	62.8	68.2	74.1	78.4	N/A	100.0
25	1.2	H	18.6	40.6	40.9	msG	WT	N/A	108.0	35.6	28.0	17.6	15.4	10.8	N/A	49.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.9	13.3	10.8	6.0	5.8	4.1	N/A	18.6
SPLIT	WT=	288.4						CUM WT %	N/A	40.9	54.2	66.6	71.8	77.4	81.4	N/A	100.0
30	1.1	H	30.1	28.9	40.9	msG	WT	N/A	143.7	48.4	N/A	22.7	21.8	18.7	N/A	106.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.9	11.6	N/A	8.5	8.2	4.8	N/A	30.1
SPLIT	WT=	351.1						CUM WT %	N/A	40.9	52.4	N/A	58.9	66.1	69.9	N/A	100.0
35	0.8	H	17.3	37.8	45.7	msG	WT	N/A	142.6	34.7	27.3	19.7	19.5	14.4	N/A	59.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.7	11.1	8.8	8.3	4.6	4.6	N/A	17.3
SPLIT	WT=	312.1						CUM WT %	N/A	45.7	56.8	66.6	71.9	78.1	82.7	N/A	100.0
40	0.8	H	28.5	37.3	42.1	msG	WT	N/A	208.3	66.7	42.0	31.7	30.7	23.5	N/A	101.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.2	11.3	8.7	6.4	6.2	4.8	N/A	28.5
SPLIT	WT=	494.1						CUM WT %	N/A	42.2	53.4	62.1	68.5	74.7	79.5	N/A	100.0
45	0.8	H	28.8	37.2	42.1	msG	WT	N/A	186.2	68.8	38.1	27.8	27.4	21.2	N/A	92.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	11.3	8.6	6.3	6.2	4.8	N/A	28.8
SPLIT	WT=	442.8						CUM WT %	N/A	42.1	53.3	61.9	68.2	74.4	79.2	N/A	100.0
50	0.8	H	24.8	40.6	34.7	msG	WT	N/A	157.2	52.8	42.3	32.4	31.8	23.9	N/A	112.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.8	11.7	9.4	7.2	7.0	5.3	N/A	24.8
SPLIT	WT=	452.6						CUM WT %	N/A	34.8	48.4	55.8	62.9	69.8	75.2	N/A	100.0
55	1.1	H	19.8	33.2	47.1	msG	WT	N/A	215.1	51.1	35.1	24.8	23.1	17.4	N/A	88.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.1	11.2	7.7	6.4	5.1	3.8	N/A	19.8
SPLIT	WT=	457.0						CUM WT %	N/A	47.1	58.3	66.0	71.4	76.4	80.2	N/A	100.0

K.41

ROCKWELL MANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0299-W08-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
60	1.3	H	26.3	39.0	35.7	msG	WT	N/A	158.1	69.3	40.6	20.6	25.2	19.2	N/A	111.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.7	13.4	9.2	6.4	6.7	4.3	N/A	26.3
SPLIT	WT=	442.0					CUM WT %	N/A	35.7	49.1	58.3	64.7	70.4	74.7	N/A	100.0	
65	1.4	H	24.0	39.0	35.4	msG	WT	N/A	167.0	56.8	41.2	30.9	28.0	21.0	N/A	110.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.6	12.0	9.3	7.0	6.3	4.7	N/A	24.0
SPLIT	WT=	444.5					CUM WT %	N/A	35.5	48.0	57.3	64.2	70.5	75.2	N/A	100.0	
70	1.6	H	19.7	38.7	41.0	msG	WT	N/A	167.0	60.0	40.4	29.7	25.4	18.1	N/A	88.4	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.0	13.6	9.0	6.6	6.7	4.0	N/A	19.7
SPLIT	WT=	449.7					CUM WT %	N/A	41.0	56.1	64.1	70.7	76.3	80.4	N/A	100.0	
75	2.0	H	26.0	33.2	41.9	msG	WT	N/A	106.5	50.2	16.2	31.6	24.0	15.9	N/A	110.5	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.9	13.1	3.7	7.1	5.8	3.6	N/A	25.0
SPLIT	WT=	442.9					CUM WT %	N/A	41.9	55.0	60.7	66.0	71.5	76.0	N/A	100.0	
80	5.0	H	52.0	20.4	20.0	gsm	WT	N/A	75.0	20.7	10.0	12.6	17.6	20.0	N/A	190.0	
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.0	7.9	4.7	3.6	4.8	5.5	N/A	62.0
SPLIT	WT=	361.4					CUM WT %	N/A	20.0	20.7	33.4	36.0	41.7	47.2	N/A	100.0	
86	3.0	H	76.0	16.5	7.0	(g)M	WT	N/A	23.0	8.0	5.1	4.5	11.4	10.0	N/A	241.1	
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	7.0	2.0	1.0	1.6	3.0	6.0	N/A	76.0
SPLIT	WT=	313.5					CUM WT %	N/A	7.0	10.4	12.0	13.5	17.1	23.1	N/A	100.0	
91	20.0	H	30.0	20.4	34.1	msG	WT	N/A	124.2	15.8	10.6	10.9	23.4	35.4	N/A	144.4	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	34.1	4.3	2.0	3.0	6.4	0.7	N/A	39.0
SPLIT	WT=	364.7					CUM WT %	N/A	34.1	36.4	41.3	44.3	50.7	60.4	N/A	100.0	
95	21.1	H	28.0	41.9	30.2	msG	WT	N/A	126.7	41.0	29.6	32.7	40.0	31.8	N/A	117.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.2	10.0	7.0	7.0	9.6	7.6	N/A	28.0
SPLIT	WT=	420.3					CUM WT %	N/A	30.2	40.1	47.1	54.0	64.4	72.0	N/A	100.0	
100	12.0	H	21.0	38.4	42.0	msG	WT	N/A	179.1	57.6	32.0	20.4	26.1	10.4	N/A	92.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	13.5	7.7	4.0	6.1	4.3	N/A	21.0
SPLIT	WT=	420.2					CUM WT %	N/A	42.0	55.5	63.2	68.0	74.1	78.4	N/A	100.0	
106	8.4	H	29.6	51.2	19.4	gms	WT	N/A	70.9	37.0	40.0	49.5	30.0	30.1	N/A	121.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.4	9.2	11.2	12.0	0.4	3.6	N/A	20.5
SPLIT	WT=	412.0					CUM WT %	N/A	19.4	20.6	39.7	51.7	61.1	70.5	N/A	100.0	
110	9.1	H	30.0	58.1	5.9	(g)ms	WT	N/A	21.0	21.0	42.3	51.3	40.1	44.1	N/A	140.5	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	5.9	6.9	11.4	13.9	13.0	11.9	N/A	30.0
SPLIT	WT=	370.2					CUM WT %	N/A	5.9	11.0	23.2	37.1	50.1	62.0	N/A	100.0	

K.42

ROCKWELL MANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-W08-001 ****

02/02/89

DEPTH	%CACGS	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	13.2	H	30.0	60.0	10.0	pmS	WT	N/A	33.9	22.0	41.7	55.3	44.1	40.0	N/A	102.0
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.0	6.7	12.3	10.3	13.0	11.0	N/A
SPLIT	WT=	339.6						CUM WT %	N/A	10.0	10.6	20.9	45.2	50.2	70.0	N/A
120	6.1	H	10.0	70.0	4.4	(m)S	WT	N/A	15.0	13.4	50.7	115.2	48.4	25.9	N/A	04.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.4	3.9	17.2	33.0	14.2	7.6	N/A
SPLIT	WT=	340.0						CUM WT %	N/A	4.4	8.3	25.6	59.4	73.0	81.2	N/A
125	2.9	H	12.0	80.2	1.0	(m)S	WT	N/A	3.7	14.5	112.0	130.4	45.0	10.7	N/A	47.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	3.0	30.0	35.0	12.1	5.3	N/A
SPLIT	WT=	373.1						CUM WT %	N/A	1.0	4.9	34.9	69.9	81.0	87.2	N/A
130	2.7	H	10.2	82.0	0.9	(m)S	WT	N/A	3.2	0.1	67.5	100.3	40.2	20.7	N/A	50.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	2.2	10.3	43.5	13.3	6.0	N/A
SPLIT	WT=	300.0						CUM WT %	N/A	0.9	3.1	21.4	64.8	70.2	83.0	N/A
135	1.7	H	9.3	89.0	0.0	S	WT	N/A	3.4	1.0	30.5	200.0	05.7	10.5	N/A	37.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	0.5	0.1	51.0	23.0	4.0	N/A
SPLIT	WT=	401.0						CUM WT %	N/A	0.9	1.3	10.4	02.3	00.1	00.7	N/A
140	1.0	H	15.0	84.1	0.0	(m)S	WT	N/A	0.0	2.0	54.2	170.0	03.2	17.2	N/A	50.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	0.5	14.4	47.0	10.0	4.0	N/A
SPLIT	WT=	375.7						CUM WT %	N/A	0.0	0.5	15.0	62.7	70.6	84.1	N/A
145	1.3	H	14.4	83.4	2.2	(m)S	WT	N/A	0.5	17.2	05.4	172.4	50.4	10.5	N/A	00.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.2	4.1	20.2	40.7	14.0	4.4	N/A
SPLIT	WT=	423.2						CUM WT %	N/A	2.2	6.3	20.5	67.2	81.3	85.0	N/A
150	1.7	H	10.7	79.1	1.2	(m)S	WT	N/A	4.7	0.4	37.3	155.5	70.3	10.0	N/A	74.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.3	1.7	0.9	41.2	21.0	5.3	N/A
SPLIT	WT=	377.3						CUM WT %	N/A	1.3	3.0	12.0	54.1	75.1	80.3	N/A
155	1.1	H	10.1	50.7	33.2	msG	WT	N/A	157.0	37.3	00.1	74.0	41.0	10.0	N/A	70.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.2	7.9	14.4	15.7	0.7	4.0	N/A
SPLIT	WT=	473.4						CUM WT %	N/A	33.2	41.1	55.4	71.2	79.0	83.0	N/A
160	0.0	H	10.2	47.2	34.6	msG	WT	N/A	100.0	47.7	01.7	52.2	30.0	21.0	N/A	04.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.0	10.3	13.3	11.2	7.0	4.5	N/A
SPLIT	WT=	404.3						CUM WT %	N/A	34.0	44.0	50.2	69.4	77.3	81.0	N/A
165	0.7	H	10.0	47.5	30.5	msG	WT	N/A	177.3	44.3	00.0	05.2	35.1	10.7	N/A	77.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	00.5	0.1	13.7	13.4	7.2	4.1	N/A
SPLIT	WT=	405.0						CUM WT %	N/A	30.5	45.0	50.3	72.0	80.0	84.0	N/A

K.43

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W06-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤+2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
170	0.4	H	16.1	40.2	43.7	msG	WT	N/A	198.6	42.6	61.1	42.1	29.6	17.3	N/A	73.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.7	9.4	11.3	9.3	6.6	3.0	N/A	10.1
SPLIT	WT=	464.0						CUM WT %	N/A	43.7	63.1	94.3	73.0	80.1	83.9	N/A	100.0
175	0.2	H	18.6	36.6	40.0	msG	WT	N/A	226.2	46.6	37.6	37.1	20.6	10.0	N/A	77.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	9.7	8.0	7.9	6.1	3.8	N/A	10.6
SPLIT	WT=	469.2						CUM WT %	N/A	40.0	67.7	66.7	73.6	79.7	63.6	N/A	100.0
180	0.2	H	22.6	40.0	30.9	msG	WT	N/A	164.1	83.1	63.6	60.9	30.9	26.9	N/A	112.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.9	12.7	10.7	10.2	7.0	6.2	N/A	22.0
SPLIT	WT=	499.0						CUM WT %	N/A	30.9	43.6	64.3	64.6	72.3	77.4	N/A	100.0
185	0.2	H	24.6	44.7	30.0	msG	WT	N/A	147.0	64.1	49.1	49.3	30.6	23.1	N/A	117.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	11.3	10.2	10.3	9.0	4.0	N/A	24.6
SPLIT	WT=	479.4						CUM WT %	N/A	30.0	42.1	62.3	62.6	70.7	76.6	N/A	100.0
190	0.2	H	22.1	41.6	30.5	msG	WT	N/A	101.0	48.9	30.6	30.6	37.6	23.6	N/A	97.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	10.0	8.3	8.7	6.6	6.3	N/A	22.1
SPLIT	WT=	441.4						CUM WT %	N/A	30.6	47.1	66.4	64.1	72.0	77.9	N/A	100.0
195	0.2	H	27.3	40.8	22.9	gmS	WT	N/A	91.0	58.6	40.3	40.4	37.6	23.0	N/A	109.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	22.9	14.8	10.0	10.1	9.4	6.7	N/A	27.3
SPLIT	WT=	401.2						CUM WT %	N/A	22.9	37.6	47.6	67.0	67.0	72.7	N/A	100.0
200	0.2	H	14.9	63.6	31.0	msG	WT	N/A	122.7	13.8	11.6	114.6	63.9	14.4	N/A	67.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	3.0	3.0	29.6	13.0	3.7	N/A	14.0
SPLIT	WT=	360.0						CUM WT %	N/A	31.0	36.1	30.1	67.6	61.4	66.1	N/A	100.0
205	0.3	H	19.1	56.0	25.0	gmS	WT	N/A	103.2	39.6	27.0	90.3	64.2	19.6	N/A	70.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.0	9.0	8.0	21.0	13.1	4.7	N/A	10.1
SPLIT	WT=	412.6						CUM WT %	N/A	25.0	34.6	41.1	63.0	70.2	60.9	N/A	100.0
210	0.2	H	22.0	64.4	23.0	gmS	WT	N/A	80.0	43.6	29.6	66.0	49.6	21.3	N/A	87.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.0	11.2	7.6	17.2	12.0	6.6	N/A	22.0
SPLIT	WT=	386.7						CUM WT %	N/A	23.0	34.2	41.8	69.1	71.0	77.4	N/A	100.0
215	0.1	H	20.0	44.4	35.6	msG	WT	N/A	147.3	30.6	20.2	67.0	30.0	19.0	N/A	63.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.0	9.3	7.1	14.0	9.4	4.0	N/A	20.0
SPLIT	WT=	414.4						CUM WT %	N/A	36.0	44.0	61.0	65.0	75.2	60.0	N/A	100.0
220	0.0	H	31.3	48.6	40.2	msG	WT	N/A	164.2	40.1	29.9	40.1	36.1	19.6	N/A	41.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.2	12.4	8.2	11.0	9.0	5.3	N/A	11.3
SPLIT	WT=	306.3						CUM WT %	N/A	42.2	64.6	62.0	73.7	63.4	68.7	N/A	100.0

K.44

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL #299-W08-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAYEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
226	2.4	H	22.7	41.2	36.1	msG	WT	N/A	136.3	37.3	27.8	36.9	33.6	18.7	N/A	85.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.1	10.0	7.4	9.8	9.8	5.0	N/A	22.7
SPLIT	WT=	374.6					CUM	WT %	N/A	36.1	48.1	63.6	63.4	72.3	77.9	N/A	100.0
230	1.8	H	23.4	43.1	33.5	msG	WT	N/A	130.1	41.4	30.4	38.0	37.4	19.3	N/A	90.0	
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.6	10.7	7.8	10.0	9.8	5.0	N/A	23.4
SPLIT	WT=	388.2					CUM	WT %	N/A	33.6	44.2	62.0	62.0	71.6	76.6	N/A	100.0
236	0.9	H	21.8	39.3	39.2	msG	WT	N/A	102.3	42.6	30.9	38.7	32.7	19.8	N/A	89.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.2	10.3	7.6	8.9	7.9	4.8	N/A	21.8
SPLIT	WT=	414.3					CUM	WT %	N/A	39.2	48.6	65.0	65.0	73.7	78.4	N/A	100.0
240	1.4	H	37.4	50.0	12.0	pmS	WT	N/A	43.3	45.4	36.2	37.0	38.0	20.2	N/A	134.9	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	12.0	12.0	9.0	10.6	10.6	7.3	N/A	37.4
SPLIT	WT=	380.0					CUM	WT %	N/A	12.0	24.0	34.3	44.8	55.4	62.0	N/A	100.0
248	1.0	H	30.8	32.0	37.2	msG	WT	N/A	139.6	37.0	22.9	20.8	24.0	14.6	N/A	115.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.2	10.1	0.1	5.0	0.4	3.9	N/A	30.8
SPLIT	WT=	376.0					CUM	WT %	N/A	37.2	47.3	63.4	60.9	66.3	69.2	N/A	100.0
250	0.8	H	29.8	40.3	24.1	pmS	WT	N/A	74.2	37.0	20.8	20.6	30.9	18.7	N/A	91.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	24.1	12.2	8.7	9.3	10.0	6.1	N/A	29.8
SPLIT	WT=	307.9					CUM	WT %	N/A	24.1	38.3	46.0	64.3	64.3	70.4	N/A	100.0
266	0.0	H	21.2	40.0	32.1	msG	WT	N/A	120.3	30.0	20.4	63.0	48.5	21.4	N/A	84.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.1	7.6	0.0	15.7	11.6	6.4	N/A	21.2
SPLIT	WT=	400.1					CUM	WT %	N/A	32.1	39.6	40.1	61.9	73.6	78.9	N/A	100.0
280	1.2	H	26.1	47.0	27.0	pmS	WT	N/A	100.4	39.7	31.0	46.9	38.0	22.5	N/A	93.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.0	10.7	0.6	12.4	10.2	8.1	N/A	26.1
SPLIT	WT=	371.6					CUM	WT %	N/A	27.0	37.7	48.2	68.6	88.8	74.8	N/A	100.0
286	0.7	H	20.7	47.1	32.1	msG	WT	N/A	122.0	41.0	30.6	49.1	38.9	19.4	N/A	70.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.2	10.0	0.0	12.0	10.3	5.1	N/A	20.7
SPLIT	WT=	379.9					CUM	WT %	N/A	32.2	43.0	51.0	63.9	74.2	79.3	N/A	100.0
270	0.7	H	28.7	39.0	33.6	msG	WT	N/A	121.8	2.3	27.4	67.1	39.2	18.2	N/A	90.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.6	0.0	7.0	10.0	5.0	N/A	20.7	
SPLIT	WT=	362.7					CUM	WT %	N/A	33.6	34.2	41.0	57.6	68.3	73.3	N/A	100.0

K.45

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0209-W09-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	0.2	C	8.1	91.6	0.4	S	WT	N/A	1.6	3.3	27.8	64.3	84.4	141.7	N/A	27.6
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.4	1.0	15.9	24.8	41.6	N/A	8.1
SPLIT	WT=	348.6						CUM WT %	N/A	0.4	1.4	26.6	50.3	91.9	N/A	100.0
10	1.4	C	3.0	97.0	0.8	S	WT	N/A	0.1	1.0	18.0	70.0	84.8	88.8	N/A	8.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.4	26.6	32.0	38.8	N/A	3.0
SPLIT	WT=	294.4						CUM WT %	N/A	0.0	0.4	33.4	66.3	97.0	N/A	100.0
15	2.7	C	47.9	52.0	0.1	mS	WT	N/A	0.3	0.8	1.0	6.6	83.2	71.7	N/A	132.0
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.1	0.3	2.4	22.8	25.9	N/A	47.9
SPLIT	WT=	275.0						CUM WT %	N/A	0.1	0.4	3.3	26.2	52.1	N/A	100.0
20	1.1	C	1.8	98.0	42.8	mG	WT	N/A	308.7	149.9	152.6	58.7	24.6	13.9	N/A	13.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.6	20.9	21.2	8.2	3.4	N/A	1.8
SPLIT	WT=	720.0						CUM WT %	N/A	42.6	63.4	84.7	92.8	96.2	N/A	100.0
25	0.8	C	0.8	98.0	3.3	S	WT	N/A	21.7	120.2	331.8	127.0	28.7	10.0	N/A	4.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.3	19.4	51.0	19.6	4.4	N/A	0.7
SPLIT	WT=	656.2						CUM WT %	N/A	3.3	22.8	73.8	93.4	97.8	N/A	100.0
30	0.6	C	2.6	92.1	5.2	(g)S	WT	N/A	38.2	150.0	379.2	67.0	25.4	14.1	N/A	18.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.3	21.7	66.0	9.7	3.7	N/A	2.0
SPLIT	WT=	689.8						CUM WT %	N/A	5.3	27.0	82.0	91.7	95.3	N/A	100.0
35	0.6	C	0.6	99.3	0.2	S	WT	N/A	1.1	7.1	246.0	328.6	40.1	10.1	N/A	3.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	1.1	38.7	51.7	6.3	N/A	0.6
SPLIT	WT=	841.8						CUM WT %	N/A	0.2	1.3	40.6	91.8	97.9	N/A	100.0
40	1.0	C	10.1	89.4	0.4	(m)S	WT	N/A	2.4	15.3	53.0	116.6	147.6	188.7	N/A	50.8
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.4	2.7	9.0	20.6	26.3	N/A	10.1
SPLIT	WT=	559.0						CUM WT %	N/A	0.4	3.2	12.0	33.4	59.7	N/A	100.0
45	0.9	C	13.2	86.3	0.6	(m)S	WT	N/A	1.6	7.3	36.1	61.2	80.4	80.7	N/A	46.4
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.6	2.4	11.5	20.0	20.3	N/A	13.2
SPLIT	WT=	312.7						CUM WT %	N/A	0.6	2.9	14.3	34.3	60.6	N/A	100.0
50	1.0	C	7.9	91.9	0.2	S	WT	N/A	0.9	3.3	4.7	30.6	298.3	197.1	N/A	46.8
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	0.8	6.3	51.2	34.1	N/A	7.9
SPLIT	WT=	601.1						CUM WT %	N/A	0.2	0.7	1.6	6.8	58.0	N/A	100.0
55	1.4	C	0.1	98.6	33.3	mG	WT	N/A	290.1	172.0	181.0	84.6	51.0	37.6	N/A	53.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.3	19.8	20.9	9.7	5.9	N/A	6.1
SPLIT	WT=	877.2						CUM WT %	N/A	33.3	53.1	74.0	83.7	89.6	N/A	100.0

K.47

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0209-W09-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
60	1.0	H	0.0	80.3	31.7	m=0	WT	N/A	238.3	169.2	139.9	88.3	46.6	33.3	N/A	80.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.7	22.6	18.6	8.8	8.1	4.4	N/A	8.0
SPLIT	WT=	757.2					CUM WT %	N/A	31.7	64.2	72.7	61.6	87.8	92.0	N/A	100.0	
65	1.3	H	9.5	84.7	25.8	(m)gS	WT	N/A	182.0	160.1	144.2	72.3	61.0	32.8	N/A	67.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.8	22.3	20.4	10.2	7.2	4.0	N/A	9.6
SPLIT	WT=	700.9					CUM WT %	N/A	25.8	40.1	68.6	78.7	86.9	90.6	N/A	100.0	
70	1.0	H	11.2	64.0	34.8	m=0	WT	N/A	200.9	138.0	114.6	80.2	58.9	46.0	N/A	90.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.8	18.9	14.2	8.9	7.3	6.7	N/A	11.2
SPLIT	WT=	810.4					CUM WT %	N/A	34.8	61.7	66.9	76.9	83.2	88.9	N/A	100.0	
80	1.3	H	0.0	60.0	26.2	gS	WT	N/A	212.8	124.1	102.1	160.7	81.6	33.6	N/A	60.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.2	14.7	22.7	17.0	9.7	4.0	N/A	0.0
SPLIT	WT=	848.7					CUM WT %	N/A	26.2	39.9	82.0	80.4	90.1	94.0	N/A	100.0	
85	N/A	H	4.6	83.6	11.9	gS	WT	N/A	93.2	92.0	273.3	176.2	88.6	25.8	N/A	36.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	11.9	11.9	34.8	22.3	11.3	3.3	N/A	4.6
SPLIT	WT=	788.9					CUM WT %	N/A	11.9	23.7	60.6	80.9	92.1	96.4	N/A	100.0	
90	1.8	H	6.3	83.7	10.0	gS	WT	N/A	88.7	118.0	264.9	182.0	79.7	36.2	N/A	60.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.0	14.0	31.7	22.7	9.9	4.6	N/A	6.3
SPLIT	WT=	803.1					CUM WT %	N/A	10.0	24.0	66.6	78.3	89.2	93.7	N/A	100.0	
95	1.2	H	6.3	79.9	14.8	gS	WT	N/A	120.3	102.9	263.6	176.0	81.8	36.0	N/A	43.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	14.8	12.0	31.2	21.6	10.1	4.6	N/A	6.3
SPLIT	WT=	816.4					CUM WT %	N/A	14.8	27.4	68.0	80.1	90.1	94.7	N/A	100.0	
100	3.3	H	7.3	72.1	20.6	gS	WT	N/A	166.7	120.9	172.3	144.2	69.2	41.7	N/A	66.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.6	16.0	22.7	10.0	9.1	6.6	N/A	7.3
SPLIT	WT=	762.8					CUM WT %	N/A	20.6	36.6	60.2	70.1	87.2	92.7	N/A	100.0	
105	1.3	H	1.9	87.2	10.9	gS	WT	N/A	87.0	163.2	287.0	136.9	68.8	56.9	N/A	16.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.9	19.0	36.0	17.0	8.6	7.1	N/A	1.9
SPLIT	WT=	804.0					CUM WT %	N/A	10.9	29.9	65.6	82.5	91.1	98.1	N/A	100.0	
110	1.6	H	6.2	81.4	13.3	gS	WT	N/A	112.0	126.3	223.6	167.1	90.0	40.0	N/A	49.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.3	14.0	20.6	23.6	11.7	4.0	N/A	6.2
SPLIT	WT=	640.6					CUM WT %	N/A	13.3	26.3	64.9	78.4	90.0	94.8	N/A	100.0	
116	1.6	H	0.4	86.6	7.0	(g)S	WT	N/A	57.2	107.6	231.6	221.0	107.4	30.7	N/A	62.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.0	13.2	20.4	27.2	13.2	4.7	N/A	0.4
SPLIT	WT=	820.1					CUM WT %	N/A	7.0	20.2	48.0	76.7	88.9	93.6	N/A	100.0	

K.48

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0290-W00-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4-75)	PAN (>4.75)	
120	1.2	H	5.1	84.2	10.7	gS	WT	N/A	85.8	82.6	227.2	221.7	98.5	43.8	N/A	48.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.7	10.3	28.4	27.7	12.3	5.4	N/A	6.1
SPLIT	WT= 795.3							CUM WT %	N/A	10.7	21.1	49.6	77.3	89.8	95.0	N/A	100.0
125	1.3	H	6.5	88.3	5.2	(g)S	WT	N/A	37.0	71.8	174.3	223.4	186.8	58.8	N/A	46.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.2	10.1	24.6	31.5	14.9	7.2	N/A	8.5
SPLIT	WT= 711.8							CUM WT %	N/A	5.2	15.3	39.8	71.4	86.3	93.5	N/A	100.0
130	1.3	H	5.9	89.8	4.3	S	WT	N/A	33.8	96.3	223.8	222.7	104.8	47.4	N/A	45.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.4	12.5	28.9	28.8	13.5	8.1	N/A	5.9
SPLIT	WT= 778.4							CUM WT %	N/A	4.4	16.8	45.7	74.5	88.8	94.3	N/A	100.0
135	1.6	H	5.3	88.6	26.2	gS	WT	N/A	218.6	114.8	181.8	189.7	98.7	34.9	N/A	44.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.2	13.8	19.3	28.4	18.9	4.2	N/A	5.3
SPLIT	WT= 837.8							CUM WT %	N/A	28.2	49.0	58.3	79.6	90.5	94.7	N/A	100.0
140	1.8	H	5.8	84.6	29.7	gS	WT	N/A	248.7	134.8	147.1	142.2	76.8	38.2	N/A	47.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.7	16.2	17.7	17.1	9.1	4.4	N/A	5.8
SPLIT	WT= 831.5							CUM WT %	N/A	29.7	45.9	63.8	80.8	89.9	94.2	N/A	100.0
145	3.0	H	6.8	78.1	23.1	gS	WT	N/A	188.7	110.4	178.3	159.8	72.9	48.3	N/A	55.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.1	13.7	22.8	19.7	9.8	5.7	N/A	8.8
SPLIT	WT= 814.8							CUM WT %	N/A	23.1	36.7	58.8	78.4	87.4	93.2	N/A	100.0
150	1.2	H	4.9	89.3	5.8	(g)S	WT	N/A	45.8	108.8	247.8	226.4	78.9	37.1	N/A	38.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.9	13.9	31.8	28.9	18.1	4.7	N/A	4.9
SPLIT	WT= 772.4							CUM WT %	N/A	5.9	19.8	51.4	80.3	90.4	95.1	N/A	100.0
155	3.8	H	9.7	73.1	17.1	(m)gS	WT	N/A	131.4	108.5	178.4	144.3	73.9	55.9	N/A	74.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	17.1	14.1	23.4	18.8	9.8	7.3	N/A	9.8
SPLIT	WT= 774.1							CUM WT %	N/A	17.1	31.2	54.8	73.4	83.8	90.3	N/A	100.0
160	4.1	H	21.9	87.8	10.5	gmS	WT	N/A	78.2	86.4	91.5	119.7	83.2	131.2	N/A	159.2	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	18.5	9.1	12.8	15.6	11.4	18.8	N/A	21.9
SPLIT	WT= 729.7							CUM WT %	N/A	18.5	19.6	32.2	48.7	60.1	78.1	N/A	100.0
165	17.9	H	9.3	79.9	18.8	(m)gS	WT	N/A	79.1	82.9	109.2	142.8	154.4	94.1	N/A	67.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	18.8	11.4	15.8	18.8	21.1	12.9	N/A	9.3
SPLIT	WT= 732.3							CUM WT %	N/A	18.8	22.2	37.1	56.7	77.8	90.7	N/A	100.0
170	12.7	H	10.1	82.9	7.8	(gm)S	WT	N/A	52.8	88.9	208.4	182.8	121.1	83.8	N/A	75.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.8	8.9	27.8	21.8	18.2	8.4	N/A	18.1
SPLIT	WT= 754.1							CUM WT %	N/A	7.8	16.8	43.8	65.4	81.5	90.8	N/A	100.0

K.49

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W09-001 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
175	N/A	H	8.8	88.8	4.8	S	WT	N/A	34.3	38.1	166.6	239.0	130.1	67.7	N/A	63.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.6	6.1	22.3	32.1	18.3	N/A	8.6
SPLIT	WT= 746.9						CUM WT %	N/A	4.6	9.7	32.1	64.1	82.4	91.4	N/A	100.0
180	5.9	H	7.8	90.6	1.6	S	WT	N/A	10.0	12.6	41.6	320.0	129.0	38.1	N/A	47.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.7	2.1	6.9	54.2	21.3	N/A	7.8
SPLIT	WT= 610.4						CUM WT %	N/A	1.7	3.7	10.6	64.7	86.0	92.3	N/A	100.0
185	1.7	H	6.4	93.4	0.2	S	WT	N/A	1.1	1.4	27.0	430.1	170.6	45.8	N/A	46.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	0.2	3.7	59.6	23.6	N/A	6.4
SPLIT	WT= 723.9						CUM WT %	N/A	0.2	0.3	4.1	63.6	87.3	93.6	N/A	100.0
190	1.7	H	7.0	92.9	0.1	S	WT	N/A	0.7	0.8	42.9	400.0	175.0	45.9	N/A	50.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	0.1	6.0	55.9	24.6	N/A	7.0
SPLIT	WT= 719.0						CUM WT %	N/A	0.1	0.2	6.2	62.1	86.6	93.0	N/A	100.0
196	1.4	H	6.7	74.3	20.0	gS	WT	N/A	171.5	43.8	76.8	324.4	130.1	61.6	N/A	49.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	20.0	5.1	9.0	37.8	15.2	N/A	5.7
SPLIT	WT= 863.4						CUM WT %	N/A	20.0	25.1	34.1	71.9	87.1	94.3	N/A	100.0
200	0.5	H	7.8	65.1	27.3	(m)gS	WT	N/A	232.7	83.6	103.7	217.3	102.3	48.3	N/A	65.1
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.3	9.8	12.2	25.5	12.0	N/A	7.6
SPLIT	WT= 867.9						CUM WT %	N/A	27.3	37.1	49.2	74.7	86.7	92.4	N/A	100.0
205	0.6	H	9.8	74.9	16.3	(m)gS	WT	N/A	129.5	104.5	119.0	236.8	112.0	59.7	N/A	82.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.4	12.4	14.1	28.0	13.3	N/A	9.8
SPLIT	WT= 845.6						CUM WT %	N/A	15.4	27.7	41.8	69.9	83.2	90.2	N/A	100.0
210	0.4	H	11.4	60.5	28.1	(m)gS	WT	N/A	250.0	99.2	161.1	157.6	93.1	43.7	N/A	104.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.1	10.8	17.6	17.2	10.2	N/A	11.4
SPLIT	WT= 919.2						CUM WT %	N/A	28.1	38.9	56.5	73.7	83.9	88.6	N/A	100.0
215	0.2	H	11.9	65.6	22.3	(m)gS	WT	N/A	180.8	88.4	137.1	142.2	122.9	42.0	N/A	90.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.3	10.9	16.9	17.6	15.2	N/A	11.9
SPLIT	WT= 814.8						CUM WT %	N/A	22.3	33.2	50.2	67.7	82.9	88.1	N/A	100.0
220	0.1	H	12.8	58.1	29.3	(m)gS	WT	N/A	170.9	54.5	64.6	94.1	68.8	57.1	N/A	73.7
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.3	9.3	11.1	16.1	11.8	N/A	12.6
SPLIT	WT= 590.0						CUM WT %	N/A	29.3	38.6	49.7	65.8	77.6	87.4	N/A	100.0
225	0.0	H	9.8	59.9	30.3	msG	WT	N/A	263.2	94.7	100.4	153.6	124.2	47.2	N/A	85.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.3	10.9	11.6	17.7	14.3	N/A	9.8
SPLIT	WT= 871.6						CUM WT %	N/A	30.3	41.2	52.8	70.4	84.7	90.2	N/A	100.0

K.50

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 6

**** REPORT ON WELL 0298-W09-001 ****

02/02/89

DEPTH	%CAC03	OM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
230	0.1	H	0.1	91.0	88.9	msG	WT	N/A	468.3	74.5	44.1	38.9	41.3	33.7	N/A	80.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.9	9.9	5.9	5.2	5.5	N/A	0.1
SPLIT	WT=	753.0						CUM WT %	N/A	60.9	70.8	61.9	87.4	91.9	N/A	100.0
236	0.0	H	0.7	40.1	53.2	msG	WT	N/A	493.1	135.0	77.1	63.6	57.6	38.9	N/A	62.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	53.2	14.6	8.3	6.9	4.2	N/A	6.7
SPLIT	WT=	927.3						CUM WT %	N/A	53.2	57.7	70.0	82.9	89.1	N/A	100.0
240	0.1	H	10.2	64.2	25.8	(m)gS	WT	N/A	207.4	95.1	111.1	137.8	105.0	71.0	N/A	63.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.6	11.7	13.7	17.0	0.9	N/A	10.2
SPLIT	WT=	811.0						CUM WT %	N/A	25.6	37.3	51.0	68.0	69.0	N/A	100.0
246	0.1	H	0.0	84.6	27.6	(m)gS	WT	N/A	211.0	107.3	81.2	144.8	97.7	61.9	N/A	80.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.8	14.0	10.6	10.9	8.1	N/A	8.0
SPLIT	WT=	788.0						CUM WT %	N/A	27.8	41.8	52.2	71.2	84.0	N/A	100.0
250	0.1	H	9.3	85.0	24.7	(m)gS	WT	N/A	193.7	130.0	115.9	104.5	92.2	60.3	N/A	72.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.7	17.8	14.8	13.3	11.9	N/A	9.3
SPLIT	WT=	783.0						CUM WT %	N/A	24.7	42.3	57.1	70.4	82.3	N/A	100.0
255	0.1	H	12.2	73.9	13.9	(m)gS	WT	N/A	95.5	111.3	124.0	108.7	104.6	68.1	N/A	83.9
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.9	10.2	10.2	15.8	8.5	N/A	12.2
SPLIT	WT=	801.1						CUM WT %	N/A	13.9	30.1	48.3	64.1	79.3	N/A	100.0
260	0.3	H	9.8	67.0	22.6	(m)gS	WT	N/A	173.5	124.7	120.8	105.0	103.2	65.6	N/A	75.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.0	18.2	15.7	13.7	13.4	N/A	9.0
SPLIT	WT=	773.5						CUM WT %	N/A	22.0	30.8	54.6	68.3	81.7	N/A	100.0
265	1.2	H	10.2	64.9	24.9	(m)gS	WT	N/A	109.5	87.3	84.2	130.8	112.3	78.5	N/A	77.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.9	11.5	11.1	17.2	14.0	N/A	10.2
SPLIT	WT=	766.2						CUM WT %	N/A	24.9	36.4	47.6	64.7	79.5	N/A	100.0
270	1.4	H	10.8	65.3	23.9	(m)gS	WT	N/A	100.7	90.0	74.5	119.1	101.0	69.5	N/A	75.2
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.9	13.0	10.7	17.1	14.0	N/A	10.8
SPLIT	WT=	898.6						CUM WT %	N/A	23.9	30.9	47.6	64.7	79.3	N/A	100.0
275	0.9	H	10.8	75.2	14.0	(m)gS	WT	N/A	87.1	74.9	85.7	134.2	103.8	70.3	N/A	87.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	14.0	12.0	13.8	21.5	16.7	N/A	10.8
SPLIT	WT=	829.0						CUM WT %	N/A	14.0	26.0	39.7	51.3	77.9	N/A	100.0
280	0.5	H	0.1	42.0	50.0	msG	WT	N/A	300.9	88.3	53.5	75.0	85.2	42.0	N/A	50.3
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	9.2	7.4	10.5	5.9	N/A	0.1
SPLIT	WT=	727.5						CUM WT %	N/A	50.0	59.1	68.8	77.0	86.1	N/A	100.0

K.51

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W09-001 ****

02/02/99

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
285	0.8	H	7.9	51.7	40.4	msG	WT	N/A	263.9	60.2	59.6	109.4	76.6	43.6	N/A	61.4
SDRT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.4	7.7	9.1	16.7	11.6	6.7	7.9
SPLIT	WT=	650.0						CUM WT %	N/A	40.4	40.1	67.2	73.9	85.6	92.1	100.0
295	1.6	H	7.8	48.2	44.0	msG	WT	N/A	310.9	74.8	82.0	88.2	73.7	42.1	N/A	55.2
SDRT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.0	10.0	8.8	12.5	10.4	6.0	7.8
SPLIT	WT=	710.9						CUM WT %	N/A	44.0	54.0	63.3	76.8	86.2	92.2	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0290-W10-013 ****

02/02/89

DEPTH	%CACCS	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	0.9	N/	0.0	91.1	0.0	S	WT	N/A	0.2	4.3	41.0	80.5	114.7	229.3	N/A	40.5
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.0	8.0	10.5	21.0	43.0	N/A
SPLIT	WT= 523.4							CUM WT %	N/A	0.0	0.9	8.0	25.4	47.3	91.1	N/A
10	1.0	N/	10.3	89.9	0.0	(#)S	WT	N/A	3.0	2.5	17.0	61.3	170.7	179.7	N/A	50.1
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.5	3.7	12.0	35.1	37.0	N/A
SPLIT	WT= 406.0							CUM WT %	N/A	0.0	1.3	6.0	17.5	52.7	69.7	N/A
15	1.0	C	10.9	81.5	7.0	(#m)S	WT	N/A	42.3	7.5	24.1	63.0	103.3	170.2	N/A	60.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	7.0	1.4	4.3	11.3	32.9	31.0	N/A
SPLIT	WT= 667.2							CUM WT %	N/A	7.0	0.0	13.3	24.6	67.6	89.1	N/A
20	0.4	C	2.0	87.7	20.5	ps	WT	N/A	200.4	162.7	100.3	105.6	74.3	20.3	N/A	10.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.5	22.5	14.0	15.5	11.0	3.9	N/A
SPLIT	WT= 670.0							CUM WT %	N/A	29.5	52.1	60.0	82.4	93.4	97.2	N/A
25	0.9	C	3.1	74.7	22.2	ps	WT	N/A	105.3	129.0	215.3	135.0	54.0	20.0	N/A	22.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	22.2	17.3	20.0	10.2	7.4	2.0	N/A
SPLIT	WT= 744.7							CUM WT %	N/A	22.2	39.6	60.6	86.0	94.1	97.0	N/A
30	0.8	C	13.4	46.3	40.3	msG	WT	N/A	354.0	102.2	70.0	84.2	104.0	38.0	N/A	117.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.3	11.0	9.0	9.0	11.0	4.3	N/A
SPLIT	WT= 880.0							CUM WT %	N/A	40.3	51.9	60.9	70.5	82.3	86.6	N/A
35	1.1	C	6.9	91.3	1.0	S	WT	N/A	10.3	35.4	124.7	179.7	117.4	65.2	N/A	39.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	6.2	21.0	31.4	20.5	11.4	N/A
SPLIT	WT= 672.7							CUM WT %	N/A	1.0	8.0	29.0	61.2	81.7	93.1	N/A
40	1.5	C	4.5	95.0	0.4	S	WT	N/A	3.1	73.3	337.0	120.6	60.1	86.5	N/A	31.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.5	10.0	40.7	17.4	8.7	9.0	N/A
SPLIT	WT= 091.0							CUM WT %	N/A	0.5	11.0	59.7	77.2	85.9	95.6	N/A
45	1.7	C	6.3	94.7	N/A	G	WT	N/A	N/A	2.4	60.0	270.7	129.5	84.1	N/A	31.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	N/A	0.4	14.0	46.3	22.2	11.0	N/A
SPLIT	WT= 584.0							CUM WT %	N/A	N/A	0.4	15.2	61.5	83.7	94.7	N/A
50	1.2	C	9.0	90.4	0.7	S	WT	N/A	4.0	11.1	28.0	70.4	313.0	124.7	N/A	54.2
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.7	1.0	4.0	11.0	51.7	20.0	N/A
SPLIT	WT= 604.9							CUM WT %	N/A	0.7	2.5	7.1	10.0	70.5	91.1	N/A
55	1.3	C	4.7	94.4	0.9	S	WT	N/A	4.4	27.9	95.4	160.7	149.5	40.0	N/A	24.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	5.5	10.7	31.5	29.3	9.6	N/A
SPLIT	WT= 510.2							CUM WT %	N/A	0.9	6.3	25.0	60.4	86.7	95.3	N/A

K.53

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-W10-013 ****

02/02/89

DEPTH	%CAC03	DW	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	2.0	C	4.9	94.8	0.3	S	WT	N/A	1.0	55.2	202.0	116.6	88.1	68.2	N/A	25.6
SORT=	N/A		MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.3	10.6	30.6	22.0	13.0	10.7
SPLIT	WT=	620.3					CUM WT %	N/A	0.3	10.9	40.4	71.4	84.4	95.1	N/A	100.0
85	1.0	C	6.4	94.2	0.4	S	WT	N/A	2.2	0.1	122.7	228.1	105.2	58.9	N/A	29.8
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	1.0	22.2	40.8	19.0	10.6
SPLIT	WT=	552.8					CUM WT %	N/A	0.4	2.0	24.2	65.0	84.0	94.0	N/A	100.0
70	0.8	C	1.7	57.0	40.8	msG	WT	N/A	280.9	93.2	194.4	76.3	23.0	12.8	N/A	12.1
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.6	13.6	20.1	10.9	3.3	1.8
SPLIT	WT=	806.7					CUM WT %	N/A	40.6	64.1	82.2	93.1	96.4	99.3	N/A	100.0
76	0.9	C	2.5	79.3	18.1	ps	WT	N/A	124.2	134.0	205.7	89.3	26.4	14.3	N/A	17.3
SORT=	N/A		MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.1	10.0	41.7	12.2	3.9	2.1
SPLIT	WT=	686.0					CUM WT %	N/A	10.1	37.7	79.4	91.8	95.4	97.5	N/A	100.0
80	1.5	C	4.0	31.0	63.5	msG	WT	N/A	401.2	69.4	80.2	38.9	24.7	17.2	N/A	36.7
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	03.6	9.2	11.8	5.1	3.3	2.3
SPLIT	WT=	769.4					CUM WT %	N/A	03.6	72.7	84.6	89.0	92.0	95.2	N/A	100.0
86	1.1	H	10.8	43.6	37.7	msG	WT	N/A	140.9	50.4	60.2	32.0	22.0	16.1	N/A	73.0
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.7	12.0	12.0	8.3	5.0	4.1
SPLIT	WT=	306.9					CUM WT %	N/A	37.7	50.6	63.2	71.6	77.1	81.2	N/A	100.0
90	1.0	H	23.4	46.9	29.7	gmS	WT	N/A	112.7	61.0	43.2	35.1	26.2	21.9	N/A	89.0
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.7	13.0	11.4	9.2	6.0	6.0
SPLIT	WT=	370.9					CUM WT %	N/A	20.7	43.3	64.7	83.9	70.0	76.8	N/A	100.0
96	0.8	H	24.3	49.3	26.4	gmS	WT	N/A	99.0	48.6	49.2	37.4	27.7	21.0	N/A	90.8
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.4	13.0	13.1	10.0	7.4	5.8
SPLIT	WT=	374.3					CUM WT %	N/A	26.4	39.4	62.6	62.6	69.9	76.7	N/A	100.0
100	0.8	H	17.1	35.2	47.7	msG	WT	N/A	204.9	51.2	30.9	25.7	20.0	17.2	N/A	73.3
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	47.7	11.9	0.0	4.7	4.0	N/A
SPLIT	WT=	420.0					CUM WT %	N/A	47.7	69.7	60.3	74.3	70.9	82.9	N/A	100.0
106	0.8	H	13.7	40.7	46.0	msG	WT	N/A	196.7	68.2	49.9	25.8	17.0	14.0	N/A	59.2
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.0	16.8	11.0	8.0	4.1	3.3
SPLIT	WT=	431.4					CUM WT %	N/A	46.0	81.4	73.0	79.0	83.0	86.3	N/A	100.0
110	1.0	H	14.9	70.0	15.2	(m)ps	WT	N/A	60.0	46.7	85.7	90.3	30.0	16.3	N/A	60.0
SORT=	N/A		MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.2	11.0	21.7	24.0	7.6	4.1
SPLIT	WT=	390.0					CUM WT %	N/A	16.2	27.0	40.0	73.4	81.0	86.1	N/A	100.0

K.54

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 3

**** REPORT ON WELL R200-W10-B13 ****

02/02/89

K.55

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
115	1.0	H	17.0	75.0	7.2	(gm)S	WT	N/A	20.4	20.0	64.0	123.0	40.1	21.0	N/A	62.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	7.2	6.6	17.6	33.7	13.2	0.0	N/A	17.0
SPLIT	WT=	305.4						CUM WT %	N/A	7.2	12.7	30.2	63.9	77.0	83.0	N/A	100.0
120	3.0	H	27.0	70.0	2.2	mS	WT	N/A	7.9	10.4	34.6	93.1	68.3	49.4	N/A	97.4	
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	2.2	2.0	9.6	26.0	18.0	13.7	N/A	27.0
SPLIT	WT=	361.1						CUM WT %	N/A	2.2	6.1	14.7	40.4	59.3	73.0	N/A	100.0
125	3.0	H	55.0	43.5	0.7	mM	WT	N/A	2.1	4.3	16.6	42.3	34.8	20.4	N/A	176.6	
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.7	1.4	6.3	13.4	11.0	12.6	N/A	66.9
SPLIT	WT=	316.2						CUM WT %	N/A	0.7	2.0	7.3	20.7	31.7	44.1	N/A	100.0
130	0.1	H	50.1	30.0	2.3	mM	WT	N/A	0.0	0.2	12.0	27.2	20.0	34.4	N/A	166.6	
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	2.3	2.2	4.6	9.7	12.2	N/A	60.1	
SPLIT	WT=	281.6						CUM WT %	N/A	2.3	4.6	9.1	18.8	28.7	40.9	N/A	100.0
135	10.4	H	45.1	48.7	0.2	(g)mS	WT	N/A	10.2	13.3	26.6	39.4	32.6	21.0	N/A	132.0	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.2	4.6	9.0	13.4	11.0	10.0	N/A	45.1
SPLIT	WT=	294.0						CUM WT %	N/A	0.2	10.7	19.7	33.1	44.1	64.9	N/A	100.0
140	6.4	H	21.6	52.9	25.6	gmS	WT	N/A	01.0	32.6	30.6	62.7	31.0	21.0	N/A	76.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.0	9.2	11.1	17.0	9.0	0.1	N/A	21.6
SPLIT	WT=	350.2						CUM WT %	N/A	26.0	34.7	46.8	63.4	72.4	78.6	N/A	100.0
145	2.4	H	16.2	56.7	20.1	gmS	WT	N/A	123.6	30.0	62.6	95.6	37.0	19.7	N/A	04.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.1	7.3	12.4	22.6	8.9	4.6	N/A	16.2
SPLIT	WT=	424.3						CUM WT %	N/A	29.1	30.4	46.0	71.3	80.2	84.8	N/A	100.0
150	0.0	H	9.0	61.2	30.0	msG	WT	N/A	170.2	70.6	64.9	83.0	28.6	13.0	N/A	44.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	16.0	12.2	14.1	8.3	3.0	N/A	9.0
SPLIT	WT=	461.0						CUM WT %	N/A	30.0	64.0	66.0	80.0	87.2	90.2	N/A	100.0
155	0.3	H	7.0	61.7	31.2	msG	WT	N/A	205.6	105.3	120.0	171.1	02.6	35.0	N/A	69.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.2	12.4	14.2	20.1	10.9	4.1	N/A	7.1
SPLIT	WT=	840.3						CUM WT %	N/A	31.2	43.6	67.8	70.0	80.0	93.0	N/A	100.0
160	0.2	H	7.3	47.0	46.1	msG	WT	N/A	403.1	104.0	100.6	110.6	70.4	20.0	N/A	65.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.1	11.7	12.3	12.4	7.0	3.4	N/A	7.3
SPLIT	WT=	060.6						CUM WT %	N/A	45.1	60.0	60.1	61.6	60.4	62.7	N/A	100.0
165	0.2	H	0.4	65.6	30.2	msG	WT	N/A	327.0	132.0	130.2	132.2	67.6	30.7	N/A	76.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.2	14.7	14.4	14.8	7.6	4.3	N/A	6.4
SPLIT	WT=	006.2						CUM WT %	N/A	30.2	60.9	66.3	70.9	87.4	91.0	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W10-013 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
170	0.4	H	10.9	59.7	29.4	(m)gS	WT	N/A	218.8	84.4	97.8	132.8	97.8	57.2	N/A	80.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.4	11.5	9.2	18.0	13.3	7.8	N/A	10.8
SPLIT	WT=	737.3					CUM WT %	N/A	29.4	40.9	50.1	60.1	81.4	89.1	N/A	100.0	
175	0.2	H	9.1	53.0	37.9	msG	WT	N/A	333.9	92.5	122.3	120.6	77.2	45.9	N/A	80.3	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.9	10.5	13.9	14.6	8.8	5.2	N/A	9.1
SPLIT	WT=	878.5					CUM WT %	N/A	37.9	48.4	62.3	76.9	85.7	90.9	N/A	100.0	
180	0.2	H	10.3	55.2	24.5	(m)gS	WT	N/A	209.4	92.0	169.0	122.7	124.3	58.2	N/A	87.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.5	10.8	18.7	14.4	14.6	6.0	N/A	10.3
SPLIT	WT=	855.6					CUM WT %	N/A	24.5	35.3	54.0	68.4	82.2	89.7	N/A	100.0	
185	0.3	H	10.2	51.6	28.2	(m)gS	WT	N/A	121.8	53.5	70.2	50.8	43.1	35.0	N/A	44.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.2	12.4	17.0	13.5	10.0	8.1	N/A	10.2
SPLIT	WT=	431.9					CUM WT %	N/A	28.2	40.6	50.2	71.7	81.7	89.8	N/A	100.0	
190	0.2	H	10.0	55.1	34.1	msG	WT	N/A	134.2	41.3	40.1	57.7	47.0	29.7	N/A	42.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.1	10.5	10.2	14.7	12.2	7.8	N/A	10.0
SPLIT	WT=	394.3					CUM WT %	N/A	34.1	44.6	54.8	69.5	81.7	89.2	N/A	100.0	
195	0.2	H	7.8	42.9	49.3	msG	WT	N/A	163.3	32.2	35.3	26.0	22.1	17.9	N/A	24.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.3	10.4	11.4	8.4	7.1	5.8	N/A	7.8
SPLIT	WT=	314.8					CUM WT %	N/A	49.3	59.6	71.0	79.4	86.5	92.2	N/A	100.0	
200	0.2	H	10.1	38.5	51.5	msG	WT	N/A	79.8	19.5	12.5	10.1	9.5	8.1	N/A	15.6	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.5	12.0	8.1	6.5	6.1	5.2	N/A	10.1
SPLIT	WT=	154.9					CUM WT %	N/A	51.5	64.0	72.1	78.6	84.7	89.9	N/A	100.0	
205	0.2	H	10.5	44.9	44.6	msG	WT	N/A	121.3	25.2	18.3	32.4	28.9	17.5	N/A	28.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.6	9.3	6.7	11.9	10.6	8.4	N/A	10.5
SPLIT	WT=	271.5					CUM WT %	N/A	44.6	53.8	60.5	72.4	83.1	89.6	N/A	100.0	
210	0.2	H	9.0	50.4	40.6	msG	WT	N/A	139.2	28.3	21.7	52.4	47.3	22.8	N/A	30.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.6	8.3	8.3	15.3	13.8	9.7	N/A	9.0
SPLIT	WT=	343.3					CUM WT %	N/A	40.6	48.9	55.2	70.5	84.4	91.0	N/A	100.0	
215	0.2	H	7.2	43.9	48.9	msG	WT	N/A	170.5	29.5	23.0	42.5	38.8	19.4	N/A	25.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.9	8.5	6.6	12.2	11.1	5.0	N/A	7.2
SPLIT	WT=	352.3					CUM WT %	N/A	48.9	57.3	63.9	76.1	87.2	92.0	N/A	100.0	
220	0.2	H	8.5	48.8	42.7	msG	WT	N/A	154.7	34.0	23.9	52.8	42.9	22.5	N/A	30.7	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.7	9.6	6.6	14.6	11.9	8.2	N/A	8.5
SPLIT	WT=	361.4					CUM WT %	N/A	42.7	52.3	58.9	73.5	86.3	91.5	N/A	100.0	

K.56

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0200-W10-013 ****

02/02/80

DEPTH	%AC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
226	0.2	H	20.7	60.2	20.2	gmS	WT	N/A	54.6	22.6	15.8	19.6	22.8	13.3	N/A	30.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.2	12.0	8.4	10.5	12.2	7.1	N/A	20.7
SPLIT	WT=	187.3						CUM WT %	N/A	29.2	41.2	49.6	60.1	72.2	79.3	N/A	100.0
230	0.2	H	9.9	63.8	27.5	(m)gS	WT	N/A	67.4	30.7	30.1	30.0	30.9	19.2	N/A	21.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.5	15.0	12.3	15.0	12.6	7.0	N/A	8.9
SPLIT	WT=	247.8						CUM WT %	N/A	27.5	42.5	54.8	70.7	83.3	91.1	N/A	100.0
235	0.2	H	22.8	48.2	29.2	gmS	WT	N/A	43.4	15.0	12.6	15.3	10.8	11.9	N/A	33.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.2	10.1	8.5	10.3	11.3	8.0	N/A	22.8
SPLIT	WT=	140.8						CUM WT %	N/A	29.2	39.3	47.8	50.1	69.4	77.4	N/A	100.0
240	0.2	H	7.3	53.2	30.5	msG	WT	N/A	245.0	41.9	43.0	134.0	72.7	37.0	N/A	45.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.5	8.7	7.0	21.7	11.7	0.1	N/A	7.3
SPLIT	WT=	622.5						CUM WT %	N/A	39.5	46.3	53.3	74.9	86.0	92.7	N/A	100.0
245	0.2	H	2.2	88.4	1.4	S	WT	N/A	3.3	1.6	3.7	122.4	91.5	0.3	N/A	5.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.4	0.0	1.0	51.0	30.0	3.0	N/A	2.2
SPLIT	WT=	241.4						CUM WT %	N/A	1.4	2.0	3.6	55.2	93.0	97.0	N/A	100.0
260	0.2	H	2.1	97.9	0.0	S	WT	N/A	0.0	1.0	2.0	171.0	90.0	7.3	N/A	5.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	0.4	0.7	62.1	32.1	2.6	N/A	2.1
SPLIT	WT=	275.8						CUM WT %	N/A	0.0	0.4	1.1	63.2	95.3	97.9	N/A	100.0

K.57

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0290-W10-014 ****

02/02/89

DEPTH	%CACO3	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.1	N/	4.2	83.7	2.1	S	WT	N/A	0.9	7.3	29.4	70.0	156.1	174.9	N/A	19.6
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	2.1	1.6	6.3	15.0	33.4	37.4	4.2
SPLIT	WT=	471.0					CUM WT %	N/A	2.1	3.7	10.0	25.0	50.4	95.8	N/A	100.0
10	1.5	N/	9.1	80.9	0.0	S	WT	N/A	0.0	1.0	0.0	35.9	157.2	172.7	N/A	37.3
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.2	1.6	8.7	30.3	42.1	9.1
SPLIT	WT=	410.1					CUM WT %	N/A	0.0	0.2	1.9	10.6	48.9	90.9	N/A	100.0
15	1.5	C	11.6	87.0	20.7	(m)S	WT	N/A	42.2	32.4	17.3	23.0	40.3	18.9	N/A	23.7
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	20.7	15.9	8.5	11.3	22.7	0.2	11.6
SPLIT	WT=	203.7					CUM WT %	N/A	20.7	30.0	45.1	56.4	70.1	88.4	N/A	100.0
20	0.0	C	8.9	70.1	21.0	(m)S	WT	N/A	50.1	70.9	40.0	22.5	26.0	14.2	N/A	23.9
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	21.0	20.7	17.9	8.4	9.7	5.3	8.9
SPLIT	WT=	207.4					CUM WT %	N/A	21.0	49.7	67.0	70.1	86.6	91.1	N/A	100.0
25	1.2	H	17.0	72.6	10.4	(m)S	WT	N/A	20.3	31.6	47.1	55.0	32.4	16.0	N/A	42.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.4	12.6	10.7	22.2	12.9	6.3	17.0
SPLIT	WT=	251.0					CUM WT %	N/A	10.4	23.0	41.7	63.0	76.7	83.0	N/A	100.0
30	1.3	H	20.4	73.4	6.1	(g)MS	WT	N/A	24.2	34.3	70.3	84.4	52.8	40.2	N/A	81.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.1	6.7	20.0	21.3	13.3	10.2	20.4
SPLIT	WT=	390.2					CUM WT %	N/A	0.1	14.0	34.0	50.1	69.4	79.0	N/A	100.0
35	1.3	H	17.0	80.1	2.0	(m)S	WT	N/A	7.6	10.0	03.3	101.8	01.0	30.3	N/A	67.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	2.0	4.7	22.0	20.0	10.3	10.4	17.0
SPLIT	WT=	379.5					CUM WT %	N/A	2.0	6.7	20.7	56.6	71.0	82.1	N/A	100.0
40	1.0	H	10.1	80.0	1.1	(m)S	WT	N/A	4.2	17.4	08.3	90.0	00.7	50.4	N/A	00.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.1	4.6	22.0	23.3	17.2	13.0	18.1
SPLIT	WT=	307.0					CUM WT %	N/A	1.1	6.0	20.4	51.7	60.9	81.0	N/A	100.0
45	1.0	H	16.0	83.5	0.7	(m)S	WT	N/A	2.0	10.1	00.0	110.6	04.4	43.1	N/A	60.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	2.7	21.2	31.4	10.0	21.3	15.0
SPLIT	WT=	300.0					CUM WT %	N/A	0.7	3.4	24.0	50.0	72.9	84.2	N/A	100.0
53	N/A	H	16.0	83.1	0.9	(m)S	WT	N/A	3.4	13.4	02.6	96.1	07.2	53.1	N/A	00.1
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	3.0	10.7	25.4	23.3	14.2	10.0
SPLIT	WT=	374.0					CUM WT %	N/A	0.0	4.6	21.2	40.0	69.0	84.0	N/A	100.0
55	1.3	H	12.6	86.0	0.7	(m)S	WT	N/A	2.4	10.4	07.4	120.7	71.1	33.4	N/A	42.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	3.1	17.0	35.7	21.1	0.9	12.5
SPLIT	WT=	337.7					CUM WT %	N/A	0.7	3.0	20.0	50.0	77.0	87.5	N/A	100.0

K.59

02/02/00

К. 60

DEPTH	%CACB3	DM	%MUO	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY CDARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	1.5	H	11.0	88.1	0.2	(m)S	WT	N/A	0.0	0.0	55.4	124.1	70.0	30.7	N/A	30.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.2	1.0	10.5	23.5	9.2	N/A	11.0
SPLIT	WT= 335.0							CUM WT %	N/A	0.2	2.0	10.5	55.0	70.1	N/A	100.0
65	1.9	H	13.9	85.3	0.8	(m)S	WT	N/A	2.7	0.0	70.8	117.0	62.2	33.3	N/A	47.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	1.0	23.5	34.0	15.4	N/A	13.9
SPLIT	WT= 339.0							CUM WT %	N/A	0.0	2.6	26.1	60.9	76.3	N/A	100.0
70	1.5	H	14.4	80.2	5.4	(gm)S	WT	N/A	21.3	24.0	102.3	97.0	54.3	35.0	N/A	60.3
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.4	6.1	20.1	25.0	13.9	N/A	14.4
SPLIT	WT= 301.0							CUM WT %	N/A	5.4	11.6	37.7	62.7	76.5	N/A	100.0
75	1.1	H	10.2	72.3	9.0	(g)mS	WT	N/A	17.0	10.0	66.3	20.3	13.0	9.3	N/A	34.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.0	0.0	34.9	15.1	7.4	N/A	10.2
SPLIT	WT= 107.0							CUM WT %	N/A	9.0	10.0	64.4	89.5	76.9	N/A	100.0
80	1.3	H	15.0	63.5	17.0	gmS	WT	N/A	03.0	40.4	95.3	40.3	25.3	10.1	N/A	07.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	17.0	11.3	20.0	13.5	7.1	N/A	10.0
SPLIT	WT= 357.0							CUM WT %	N/A	17.0	20.9	55.5	69.0	76.1	N/A	100.0
85	1.1	H	10.5	30.0	50.0	msG	WT	N/A	224.0	45.0	50.1	33.0	21.0	14.2	N/A	40.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.0	10.1	13.3	7.4	4.9	N/A	10.0
SPLIT	WT= 444.0							CUM WT %	N/A	50.0	60.7	74.0	81.4	86.3	N/A	100.0
90	1.2	H	10.7	30.5	41.0	msG	WT	N/A	100.0	40.4	47.2	26.0	10.4	14.4	N/A	70.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.0	11.7	11.9	8.5	4.9	N/A	19.7
SPLIT	WT= 300.4							CUM WT %	N/A	41.0	53.5	65.3	71.0	76.7	N/A	100.0
95	1.1	H	22.0	34.5	43.5	msG	WT	N/A	203.4	49.1	45.7	25.7	22.0	10.0	N/A	102.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.5	10.5	9.0	5.5	4.7	N/A	22.0
SPLIT	WT= 407.4							CUM WT %	N/A	43.5	54.0	63.0	89.3	74.0	N/A	100.0
100	0.0	H	20.5	30.7	42.0	msG	WT	N/A	200.3	57.7	51.0	20.0	23.1	17.0	N/A	90.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	11.0	10.5	5.9	4.0	N/A	20.5
SPLIT	WT= 406.0							CUM WT %	N/A	42.0	54.7	65.2	71.1	76.0	N/A	100.0
105	1.1	H	23.1	45.0	31.0	msG	WT	N/A	153.0	54.3	61.0	47.0	30.1	22.7	N/A	111.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	11.3	12.0	9.9	6.3	N/A	23.2
SPLIT	WT= 400.0							CUM WT %	N/A	31.0	43.1	65.9	65.0	72.1	N/A	100.0
110	1.3	H	17.2	50.1	24.7	gmS	WT	N/A	05.0	34.7	82.3	64.1	25.4	15.2	N/A	50.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.7	10.0	10.0	10.5	7.3	N/A	17.2
SPLIT	WT= 340.0							CUM WT %	N/A	24.7	34.7	62.0	71.1	70.4	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 8288-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
115	2.3	H	15.8	74.8	9.4	(gm)S	WT	N/A	10.6	14.1	42.6	68.6	21.2	9.6	N/A	32.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.4	0.0	20.6	32.7	10.2	N/A	15.0
SPLIT	WT= 208.0						CUM WT %	N/A	9.4	10.2	36.7	69.4	78.6	84.2	N/A	100.0
120	2.8	H	26.8	68.6	6.9	(g)mS	WT	N/A	20.4	11.8	34.4	75.0	46.6	30.1	N/A	79.0
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.9	4.0	11.6	25.2	15.7	N/A	26.6
SPLIT	WT= 297.1						CUM WT %	N/A	6.9	10.8	22.4	47.6	63.3	73.4	N/A	100.0
125	3.0	H	50.5	37.0	2.8	mM	WT	N/A	8.6	5.5	13.2	31.1	28.8	36.3	N/A	178.4
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	2.9	1.0	4.6	10.6	9.0	N/A	59.6
SPLIT	WT= 286.6						CUM WT %	N/A	2.9	4.7	9.2	19.7	28.6	40.5	N/A	100.0
130	4.0	H	63.5	36.4	0.2	sM	WT	N/A	0.3	1.3	4.3	11.0	17.3	23.4	N/A	100.0
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.2	0.0	2.7	7.0	11.0	N/A	63.6
SPLIT	WT= 167.6						CUM WT %	N/A	0.2	1.0	3.7	10.7	21.7	36.6	N/A	100.0
135	10.7	H	38.8	58.0	5.3	(g)mS	WT	N/A	11.2	9.0	22.3	27.6	31.6	32.0	N/A	78.1
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.3	4.6	10.6	13.0	14.9	N/A	36.0
SPLIT	WT= 212.4						CUM WT %	N/A	6.3	9.6	20.3	33.3	48.2	63.2	N/A	100.0
140	6.9	H	19.7	63.5	16.8	gmS	WT	N/A	58.8	25.7	63.5	80.3	38.2	23.0	N/A	68.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.9	7.4	16.4	23.1	11.0	N/A	19.7
SPLIT	WT= 347.0						CUM WT %	N/A	16.9	24.2	39.6	62.7	73.7	80.3	N/A	100.0
145	5.3	H	10.5	49.8	33.7	msG	WT	N/A	107.1	29.3	34.3	61.5	20.8	10.6	N/A	52.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.7	9.2	10.8	18.2	8.4	N/A	16.5
SPLIT	WT= 317.6						CUM WT %	N/A	32.7	42.9	63.7	69.9	78.3	83.5	N/A	100.0
150	2.4	H	7.8	72.4	19.7	gS	WT	N/A	64.6	39.1	70.8	66.8	22.3	7.7	N/A	25.0
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	19.8	12.0	21.8	29.4	6.6	N/A	7.9
SPLIT	WT= 328.5						CUM WT %	N/A	19.8	31.7	53.3	62.9	69.6	82.1	N/A	100.0
155	1.9	H	15.7	55.0	29.3	gmS	WT	N/A	110.6	38.2	43.1	82.7	38.7	20.7	N/A	64.3
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.3	0.0	10.6	20.3	0.6	N/A	15.0
SPLIT	WT= 408.3						CUM WT %	N/A	29.3	38.9	49.6	69.7	79.2	84.3	N/A	100.0
160	0.9	H	15.9	42.1	42.0	msG	WT	N/A	192.0	41.7	43.6	55.6	31.1	20.4	N/A	72.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	9.1	0.6	12.1	8.0	N/A	15.9
SPLIT	WT= 467.0						CUM WT %	N/A	42.0	51.1	60.7	72.8	79.0	84.1	N/A	100.0
165	0.8	H	26.0	54.1	19.0	gmS	WT	N/A	70.7	46.3	44.0	60.9	30.4	30.6	N/A	100.3
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.0	11.2	10.6	14.8	9.0	N/A	26.9
SPLIT	WT= 403.0						CUM WT %	N/A	19.0	30.3	41.2	55.8	66.6	73.1	N/A	100.0

K.61

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0290-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)
170	1.0	H	37.1	57.8	5.8	(g)ms	WT	N/A	18.1	28.6	40.7	42.7	38.2	24.7	N/A	106.7
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	WT %	N/A	5.8	9.2	14.2	14.9	10.6	8.8	N/A	37.1
SPLIT	WT=	207.5					CUM WT %	N/A	5.8	14.8	29.0	43.8	64.3	82.9	N/A	100.0
175	0.8	H	17.3	38.8	48.9	msG	WT	N/A	181.1	42.8	37.8	37.3	24.8	18.5	N/A	71.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	43.9	10.4	9.1	9.8	5.8	4.5	N/A	17.3
SPLIT	WT=	412.7					CUM WT %	N/A	43.9	54.3	63.4	72.4	78.2	82.7	N/A	100.0
180	0.5	H	18.7	46.4	38.8	msG	WT	N/A	180.0	58.0	54.2	45.9	28.5	10.0	N/A	72.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	38.8	12.9	12.5	10.6	6.1	4.4	N/A	16.7
SPLIT	WT=	434.2					CUM WT %	N/A	38.8	49.7	62.2	72.8	78.9	83.3	N/A	100.0
185	0.4	H	23.8	48.3	38.3	msG	WT	N/A	115.5	42.9	43.8	39.9	28.5	22.8	N/A	90.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	38.1	11.2	11.4	10.4	7.4	5.9	N/A	23.7
SPLIT	WT=	364.0					CUM WT %	N/A	38.1	41.3	52.7	63.1	70.5	78.4	N/A	100.0
190	0.1	N	18.9	44.4	38.7	msG	WT	N/A	178.4	44.5	55.8	49.8	32.2	24.5	N/A	87.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	38.7	9.6	12.0	10.7	8.9	6.3	N/A	10.9
SPLIT	WT=	484.9					CUM WT %	N/A	38.7	48.2	58.2	68.9	75.8	81.1	N/A	100.0
195	0.1	H	20.8	43.8	36.1	msG	WT	N/A	160.9	43.2	43.4	42.3	34.9	28.1	N/A	83.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	38.1	9.7	9.7	9.5	7.8	6.3	N/A	26.9
SPLIT	WT=	445.8					CUM WT %	N/A	38.1	45.8	55.6	65.0	72.8	78.1	N/A	100.0
200	0.1	H	27.7	47.9	24.4	pmS	WT	N/A	54.0	39.9	34.3	33.9	32.2	28.5	N/A	96.6
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	WT %	N/A	24.4	11.5	9.9	9.7	9.3	7.6	N/A	27.7
SPLIT	WT=	348.3					CUM WT %	N/A	24.4	35.8	45.7	55.4	64.7	72.3	N/A	100.0
205	0.1	H	18.8	44.9	38.3	msG	WT	N/A	182.7	45.9	39.0	58.9	41.4	23.8	N/A	84.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	38.3	10.2	8.7	11.4	9.2	5.3	N/A	18.9
SPLIT	WT=	448.2					CUM WT %	N/A	38.3	48.5	56.2	66.6	75.6	81.1	N/A	100.0
210	0.1	H	15.8	34.7	49.5	msG	WT	N/A	226.6	32.3	29.8	41.8	35.1	28.1	N/A	72.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	49.5	7.1	8.5	9.1	7.7	4.4	N/A	15.6
SPLIT	WT=	468.3					CUM WT %	N/A	49.5	58.6	63.0	72.1	79.8	84.2	N/A	100.0
215	0.1	H	12.2	32.8	55.8	msG	WT	N/A	245.1	33.5	19.6	33.6	37.8	16.7	N/A	53.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	55.8	7.6	4.5	7.7	8.4	3.8	N/A	12.2
SPLIT	WT=	439.5					CUM WT %	N/A	55.8	63.4	67.9	75.6	84.8	87.9	N/A	100.0
220	0.1	H	11.6	87.2	21.2	(m)gS	WT	N/A	92.8	81.8	86.8	69.8	40.1	14.8	N/A	58.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	WT %	N/A	21.2	18.7	19.9	16.8	9.2	3.4	N/A	31.6
SPLIT	WT=	436.3					CUM WT %	N/A	21.2	40.0	59.9	75.6	85.0	88.4	N/A	100.0

K.62

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 5

**** REPORT ON WELL 0299-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	0.2	H	19.7	41.2	39.0	msG	WT	N/A	174.5	38.9	31.7	42.4	47.0	28.3	N/A	88.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.0	8.3	7.1	9.6	10.6	6.9	N/A
SPLIT	WT=	447.0						CUM WT %	N/A	39.0	47.3	64.4	83.9	74.4	80.3	N/A
230	0.2	H	24.2	49.6	26.3	gmS	WT	N/A	102.1	47.3	32.6	37.3	48.8	28.4	N/A	83.9
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.3	12.2	8.4	9.8	12.0	7.3	N/A
SPLIT	WT=	388.1						CUM WT %	N/A	28.3	38.6	46.9	58.6	68.6	76.8	N/A
235	0.1	H	28.4	60.3	23.3	gmS	WT	N/A	86.2	32.7	28.8	28.3	32.8	22.9	N/A	75.2
SORT=	N/A	MEDIAN=	2.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	23.3	11.5	9.4	9.9	11.5	8.0	N/A
SPLIT	WT=	284.7						CUM WT %	N/A	23.3	34.7	44.2	54.1	66.6	73.6	N/A
240	0.1	H	35.6	55.7	8.8	(g)ms	WT	N/A	25.1	31.6	28.7	34.6	38.0	28.8	N/A	101.9
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	8.8	11.0	10.0	12.0	13.3	9.4	N/A
SPLIT	WT=	286.6						CUM WT %	N/A	8.8	19.8	29.8	41.8	55.1	64.4	N/A
245	0.1	H	9.1	28.8	82.1	msG	WT	N/A	271.2	23.0	15.8	28.1	46.3	14.7	N/A	39.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	62.1	6.3	3.6	8.0	10.6	3.4	N/A
SPLIT	WT=	436.8						CUM WT %	N/A	62.1	87.4	71.0	77.0	87.6	98.9	N/A
250	0.3	H	8.7	82.0	31.3	sG	WT	N/A	119.2	33.6	34.4	51.9	90.3	26.0	N/A	25.4
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.3	8.8	9.0	13.6	23.7	8.8	N/A
SPLIT	WT=	376.6						CUM WT %	N/A	31.3	40.1	49.2	62.8	86.6	93.3	N/A
255	0.1	H	5.3	83.8	10.9	gS	WT	N/A	72.8	21.9	15.3	288.4	194.4	41.9	N/A	35.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.9	3.3	2.3	42.9	29.1	8.3	N/A
SPLIT	WT=	884.2						CUM WT %	N/A	10.9	14.2	16.4	59.3	88.4	94.7	N/A
260	0.2	H	5.1	87.8	27.1	gS	WT	N/A	190.8	61.8	48.6	211.3	118.4	38.6	N/A	35.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	27.1	8.8	6.8	30.0	16.8	5.5	N/A
SPLIT	WT=	780.6						CUM WT %	N/A	27.1	35.9	42.8	72.8	89.4	94.9	N/A
265	0.2	H	4.8	71.8	23.6	gS	WT	N/A	188.4	69.1	55.4	228.2	117.4	43.5	N/A	34.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	23.6	9.7	7.8	31.7	18.4	6.1	N/A
SPLIT	WT=	717.1						CUM WT %	N/A	23.6	33.3	41.0	72.7	89.1	95.2	N/A
270	0.2	H	8.3	72.3	21.4	gS	WT	N/A	132.2	58.9	48.4	194.3	104.2	44.1	N/A	38.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	21.4	9.2	7.6	31.5	18.9	7.2	N/A
SPLIT	WT=	612.6						CUM WT %	N/A	21.4	30.7	38.2	69.7	86.6	93.7	N/A
275	0.1	H	5.8	82.4	11.7	gS	WT	N/A	77.0	38.8	27.6	149.3	279.2	48.6	N/A	38.3
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	11.7	5.9	4.2	22.8	42.6	7.1	N/A
SPLIT	WT=	853.6						CUM WT %	N/A	11.7	17.6	21.8	44.6	87.1	94.2	N/A

K.63

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
280	0.1	H	4.4	93.3	2.3	S	WT	N/A	14.1	10.4	63.8	145.9	299.9	58.7	N/A	26.9
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	2.3	1.7	8.8	23.9	49.2	9.8	N/A
SPLIT	WT= 607.3							CUM WT %	N/A	2.3	4.0	12.8	36.8	86.0	95.8	N/A
285	0.1	H	11.7	86.5	1.8	(m)S	WT	N/A	5.9	7.2	5.7	163.9	91.3	25.2	N/A	38.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	2.2	1.7	47.0	27.9	7.7	N/A
SPLIT	WT= 327.8							CUM WT %	N/A	1.0	4.0	5.7	52.7	80.6	88.3	N/A
290	0.1	H	4.0	96.4	0.6	S	WT	N/A	2.0	1.8	18.5	108.6	262.5	36.5	N/A	17.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.6	0.4	3.8	24.8	67.9	8.4	N/A
SPLIT	WT= 430.5							CUM WT %	N/A	0.6	1.0	4.8	29.7	87.8	96.0	N/A
295	0.1	H	3.3	96.0	0.8	S	WT	N/A	4.2	3.0	26.7	183.0	358.8	50.1	N/A	21.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.7	0.5	4.1	28.3	65.4	7.7	N/A
SPLIT	WT= 647.1							CUM WT %	N/A	0.7	1.1	5.2	33.6	88.9	96.7	N/A
300	0.1	H	3.8	82.8	13.6	gS	WT	N/A	95.8	32.0	54.4	289.9	188.1	36.4	N/A	26.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.6	4.6	7.7	41.2	23.9	5.2	N/A
SPLIT	WT= 698.0							CUM WT %	N/A	13.6	18.2	25.9	67.1	91.0	96.2	N/A
305	0.6	H	5.4	85.4	29.2	gS	WT	N/A	169.5	73.6	68.0	120.9	84.1	33.4	N/A	31.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.2	12.7	11.7	20.8	14.5	5.8	N/A
SPLIT	WT= 574.3							CUM WT %	N/A	29.2	41.9	53.6	74.4	88.9	94.8	N/A
310	0.9	H	5.7	75.1	19.2	gS	WT	N/A	121.0	67.1	61.0	213.1	100.5	38.5	N/A	38.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	19.2	10.8	8.1	33.8	18.9	5.8	N/A
SPLIT	WT= 629.1							CUM WT %	N/A	19.2	29.8	37.9	71.6	88.5	94.3	N/A
316	1.1	H	6.0	64.1	29.9	gS	WT	N/A	209.3	89.5	68.5	167.9	81.9	40.4	N/A	42.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.9	12.8	9.8	24.0	11.7	5.8	N/A
SPLIT	WT= 704.5							CUM WT %	N/A	29.9	42.7	62.5	76.5	88.2	94.0	N/A
320	0.3	H	3.7	63.0	33.3	gS	WT	N/A	195.8	53.4	32.7	169.3	90.4	23.6	N/A	21.8
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.3	9.1	5.8	28.9	15.4	4.0	N/A
SPLIT	WT= 581.4							CUM WT %	N/A	33.3	42.4	48.0	76.9	92.3	96.3	N/A
326	0.2	H	2.3	97.3	0.4	S	WT	N/A	2.3	12.6	80.6	283.1	192.3	37.0	N/A	14.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	2.0	13.0	45.6	30.9	8.0	N/A
SPLIT	WT= 519.1							CUM WT %	N/A	0.4	2.4	15.3	60.9	91.8	97.7	N/A
330	0.2	H	12.2	69.9	17.9	(m)gS	WT	N/A	98.1	65.8	82.7	112.0	86.3	56.8	N/A	67.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	17.9	12.0	11.4	20.5	15.7	10.3	N/A
SPLIT	WT= 553.8							CUM WT %	N/A	17.9	29.8	41.2	61.7	77.4	87.8	N/A

K.64

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 7

**** REPORT ON WELL 0209-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
335	0.4	H	8.7	86.5	24.9	(m)gS	WT	N/A	170.1	84.8	51.2	132.1	127.4	50.3	N/A	59.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.9	12.4	7.5	19.3	18.0	8.7	N/A	8.7
SPLIT	WT= 880.4							CUM WT %	N/A	24.9	37.3	44.7	64.0	82.7	91.3	N/A	100.0
340	0.8	H	7.1	70.1	22.9	gS	WT	N/A	187.5	133.8	107.5	115.2	111.2	46.7	N/A	51.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.9	18.3	14.7	15.7	16.2	6.2	N/A	7.1
SPLIT	WT= 729.9							CUM WT %	N/A	22.9	41.1	56.8	71.5	80.7	92.9	N/A	100.0
345	0.5	H	7.0	64.4	20.6	gS	WT	N/A	190.0	102.4	128.0	95.7	85.1	39.2	N/A	45.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.6	15.3	19.2	14.3	9.8	5.0	N/A	7.0
SPLIT	WT= 681.6							CUM WT %	N/A	20.6	43.9	63.0	77.4	87.1	93.0	N/A	100.0
350	0.8	H	9.4	72.2	10.4	(m)gS	WT	N/A	132.0	123.1	84.9	154.0	94.2	61.2	N/A	67.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	18.4	17.2	13.0	21.5	13.1	6.5	N/A	9.4
SPLIT	WT= 717.8							CUM WT %	N/A	18.4	35.6	47.4	68.9	82.0	90.5	N/A	100.0
355	1.2	H	9.8	75.8	14.4	(m)gS	WT	N/A	85.7	68.9	67.4	111.2	63.7	36.7	N/A	44.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	14.4	15.1	14.7	24.3	15.9	7.8	N/A	9.8
SPLIT	WT= 454.0							CUM WT %	N/A	14.4	29.4	44.2	68.5	82.4	90.2	N/A	100.0
360	1.3	H	5.2	88.8	25.4	gS	WT	N/A	171.4	97.0	74.5	155.7	97.6	39.1	N/A	39.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.4	14.5	11.0	23.0	14.4	6.8	N/A	5.2
SPLIT	WT= 873.8							CUM WT %	N/A	25.4	39.8	50.9	73.9	88.3	94.1	N/A	100.0
365	0.6	H	8.0	80.8	11.4	gS	WT	N/A	57.7	95.4	90.1	119.9	69.8	33.8	N/A	40.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.4	18.8	17.8	23.5	13.8	8.7	N/A	8.0
SPLIT	WT= 504.6							CUM WT %	N/A	11.4	30.2	47.9	71.3	85.3	92.0	N/A	100.0
370	0.6	H	13.1	81.8	5.1	(gms)S	WT	N/A	24.1	49.0	73.9	133.7	79.2	40.8	N/A	61.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.1	10.4	16.7	28.4	18.8	10.4	N/A	13.1
SPLIT	WT= 473.8							CUM WT %	N/A	5.1	15.5	31.3	59.7	78.5	88.9	N/A	100.0
375	0.4	H	18.2	70.7	13.1	(m)gS	WT	N/A	63.8	42.0	55.0	122.4	75.1	48.8	N/A	76.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.1	8.7	11.3	25.2	15.5	10.1	N/A	18.2
SPLIT	WT= 483.1							CUM WT %	N/A	13.1	21.8	33.1	58.3	73.8	83.8	N/A	100.0
380	0.4	H	12.1	83.9	4.0	(m)S	WT	N/A	14.0	26.4	39.1	147.9	59.5	30.5	N/A	43.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.0	7.3	10.0	40.9	16.5	8.4	N/A	12.1
SPLIT	WT= 355.5							CUM WT %	N/A	4.0	11.3	22.2	63.1	79.5	87.9	N/A	100.0
385	0.2	H	8.8	82.4	11.0	gS	WT	N/A	52.2	52.4	78.7	179.6	59.0	24.5	N/A	31.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.0	11.0	16.1	37.7	12.4	5.2	N/A	6.8
SPLIT	WT= 473.0							CUM WT %	N/A	11.0	22.0	38.1	75.8	88.2	93.4	N/A	100.0

K.65

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 8

**** REPORT ON WELL 0299-W10-014 ****

02/02/09

K.66

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	WT	WT %	CUM WT %	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
390	0.2	H	6.4	86.0	7.7	(g)S	WT	N/A	33.7	46.4	69.1	172.9	59.0	27.9	N/A	27.9	N/A	27.9
390	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	7.7	18.8	15.0	39.5	13.0	6.4	N/A	6.4	N/A
SPLIT	WT=	441.9						CUM WT %	N/A	7.7	18.3	34.1	73.6	97.2	99.6	N/A	100.0	
395	0.0	H	7.6	84.2	0.2	(g)S	WT	N/A	32.7	57.6	52.2	143.2	57.2	29.2	N/A	30.5	N/A	30.5
395	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.2	14.4	13.1	35.3	14.3	7.1	N/A	7.6	N/A
SPLIT	WT=	394.3						CUM WT %	N/A	8.2	22.6	35.7	71.0	85.3	92.4	N/A	100.0	
400	0.5	H	3.9	78.8	17.2	gS	WT	N/A	83.7	88.5	77.4	78.2	36.8	18.5	N/A	14.5	N/A	14.5
400	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.2	21.8	21.2	9.9	5.0	N/A	3.9	N/A	3.9
SPLIT	WT=	372.4						CUM WT %	N/A	17.2	39.0	60.0	81.2	91.1	96.1	N/A	100.0	
405	0.8	H	6.9	74.0	19.1	gS	WT	N/A	110.1	90.7	135.0	111.7	69.0	31.3	N/A	40.0	N/A	40.0
405	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	19.1	15.7	23.4	19.3	10.2	5.4	N/A	8.9	N/A
SPLIT	WT=	574.7						CUM WT %	N/A	19.1	34.8	58.1	77.5	97.7	93.1	N/A	100.0	
410	0.7	H	22.9	65.2	11.0	gmS	WT	N/A	37.9	42.2	29.2	66.8	48.0	21.1	N/A	72.7	N/A	72.7
410	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	11.0	13.3	9.2	20.7	15.4	8.7	N/A	22.9	N/A
SPLIT	WT=	317.5						CUM WT %	N/A	11.0	25.2	34.4	55.1	70.5	77.1	N/A	100.0	
415	0.7	H	5.5	78.0	16.5	gS	WT	N/A	77.0	39.9	106.1	130.7	63.7	25.6	N/A	25.0	N/A	25.0
415	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.5	8.6	22.7	29.7	11.5	5.5	N/A	5.5	N/A
SPLIT	WT=	460.0						CUM WT %	N/A	16.5	25.1	47.0	77.5	89.0	94.5	N/A	100.0	
420	0.4	H	5.3	79.7	15.0	gS	WT	N/A	62.1	58.4	85.0	115.0	47.0	22.5	N/A	22.0	N/A	22.0
420	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.0	13.6	20.7	20.8	11.5	5.4	N/A	5.3	N/A
SPLIT	WT=	413.4						CUM WT %	N/A	15.0	28.5	49.2	77.0	89.3	94.7	N/A	100.0	
425	0.4	H	15.9	72.4	11.7	(m)gS	WT	N/A	40.0	29.0	27.0	110.4	60.3	15.4	N/A	54.4	N/A	54.4
425	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.7	8.7	8.1	34.6	10.5	4.5	N/A	15.9	N/A
SPLIT	WT=	341.8						CUM WT %	N/A	11.7	20.4	28.5	63.1	79.6	84.1	N/A	100.0	
430	0.5	H	26.7	63.6	0.7	(g)mS	WT	N/A	24.9	21.2	31.5	63.1	32.0	14.5	N/A	66.6	N/A	66.6
430	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.7	8.3	12.3	24.6	12.0	5.7	N/A	26.7	N/A
SPLIT	WT=	256.6						CUM WT %	N/A	9.7	18.0	30.2	54.8	67.0	73.3	N/A	100.0	
435	0.5	H	12.6	70.9	16.0	(m)gS	WT	N/A	50.7	40.0	40.0	79.1	30.7	12.2	N/A	38.4	N/A	38.4
435	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.0	10.0	13.1	25.0	12.0	4.0	N/A	12.6	N/A
SPLIT	WT=	305.9						CUM WT %	N/A	16.0	32.5	45.6	71.5	83.5	87.5	N/A	100.0	
440	0.5	H	21.1	70.2	0.7	(g)mS	WT	N/A	21.3	28.1	26.7	61.7	30.9	10.9	N/A	51.6	N/A	51.6
440	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.7	11.5	10.9	25.1	16.9	6.0	N/A	21.1	N/A
SPLIT	WT=	245.6						CUM WT %	N/A	8.7	20.1	31.0	56.2	72.0	78.0	N/A	100.0	

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W10-014 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
445	0.6	H	24.8	55.6	19.6	gms	WT	N/A	51.2	30.6	22.1	35.3	31.3	19.0	N/A	64.9
SORT= N/A MEDIAN= 2.00 MODE= 5.00 MEAN= N/A							WT %	N/A	19.6	14.0	8.5	13.5	12.0	7.6	N/A	24.9
SPLIT WT= 261.3							CUM WT %	N/A	19.6	33.6	42.1	55.6	67.6	75.1	N/A	100.0
450	0.4	H	38.0	49.6	14.4	gms	WT	N/A	37.2	30.2	22.1	38.2	25.1	12.8	N/A	93.3
SORT= N/A MEDIAN= 3.00 MODE= 5.00 MEAN= N/A							WT %	N/A	14.4	11.7	8.5	14.0	9.7	4.9	N/A	36.0
SPLIT WT= 258.0							CUM WT %	N/A	14.4	26.0	34.6	49.3	59.0	64.0	N/A	100.0
455	0.8	H	50.9	31.9	1.1	gm	WT	N/A	2.0	5.8	7.8	23.7	22.7	14.6	N/A	150.3
SORT= N/A MEDIAN= 5.00 MODE= 5.00 MEAN= N/A							WT %	N/A	1.1	2.5	3.3	10.2	9.7	6.3	N/A	66.9
SPLIT WT= 233.5							CUM WT %	N/A	1.1	3.6	6.9	17.1	26.8	33.1	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0200-W16-016 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.6	C	29.3	69.1	1.8	MS	WT	N/A	7.9	10.1	37.2	50.2	100.0	130.0	N/A	140.0
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.0	3.0	9.0	21.0	27.4	N/A	29.3
SPLIT	WT=	507.8					CUM	WT %	N/A	1.0	5.1	12.5	22.4	43.4	N/A	100.0
10	0.2	C	0.7	99.8	2.5	S	WT	N/A	18.0	134.3	320.3	133.0	23.4	4.6	N/A	4.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.5	20.0	51.1	20.0	3.0	N/A	0.7
SPLIT	WT=	645.4					CUM	WT %	N/A	2.5	23.3	74.4	95.0	99.3	N/A	100.0
15	0.4	C	4.6	89.3	20.0	MS	WT	N/A	106.0	100.2	210.3	63.1	30.6	25.7	N/A	35.9
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.0	20.0	27.9	7.1	4.0	N/A	4.0
SPLIT	WT=	764.3					CUM	WT %	N/A	20.0	62.0	79.9	87.0	91.0	N/A	100.0
20	0.4	C	2.7	85.8	31.7	MS	WT	N/A	243.0	90.2	220.0	110.3	47.0	18.0	N/A	20.6
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.7	12.0	29.9	14.3	0.2	N/A	2.7
SPLIT	WT=	789.0					CUM	WT %	N/A	31.7	44.5	74.3	89.7	94.0	N/A	100.0
25	0.5	C	5.0	92.3	1.0	S	WT	N/A	10.6	80.2	204.3	139.3	50.0	37.5	N/A	32.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.0	15.7	36.3	24.7	9.0	N/A	5.0
SPLIT	WT=	603.3					CUM	WT %	N/A	1.0	17.5	53.8	70.5	87.5	N/A	100.0
30	0.4	C	1.6	93.0	4.0	S	WT	N/A	30.0	210.3	203.3	80.0	10.0	0.0	N/A	0.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.0	34.0	41.7	12.0	3.0	N/A	1.6
SPLIT	WT=	631.4					CUM	WT %	N/A	4.0	39.5	61.2	94.0	96.9	N/A	100.0
35	0.0	C	5.0	92.0	2.1	S	WT	N/A	12.4	60.1	276.4	141.0	30.2	27.4	N/A	29.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	2.1	11.0	47.0	24.2	6.2	N/A	5.0
SPLIT	WT=	500.1					CUM	WT %	N/A	2.1	13.9	61.0	85.2	90.4	N/A	100.0
40	1.1	C	2.7	67.1	40.2	MS	WT	N/A	205.0	91.3	170.7	99.0	31.0	17.3	N/A	20.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.2	12.4	24.4	13.0	4.4	N/A	2.7
SPLIT	WT=	734.3					CUM	WT %	N/A	40.2	62.0	77.0	90.0	94.0	N/A	100.0
45	1.6	C	0.0	88.0	1.5	S	WT	N/A	8.0	22.7	99.1	84.1	84.7	151.0	N/A	43.5
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.5	5.0	21.9	14.2	14.3	N/A	0.0
SPLIT	WT=	453.2					CUM	WT %	N/A	1.5	6.5	20.4	42.0	50.0	N/A	100.0
50	1.2	C	4.4	94.0	0.7	S	WT	N/A	3.4	19.4	50.4	140.1	100.1	50.0	N/A	20.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.7	4.1	10.0	29.5	40.1	N/A	4.4
SPLIT	WT=	474.0					CUM	WT %	N/A	0.7	4.8	15.4	45.0	85.1	N/A	100.0
55	1.2	C	3.1	70.2	20.7	MS	WT	N/A	150.5	137.7	151.3	57.5	40.0	30.1	N/A	10.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.7	23.2	25.5	9.7	6.7	N/A	3.1
SPLIT	WT=	504.2					CUM	WT %	N/A	20.7	49.9	75.4	65.1	81.0	N/A	100.0

K.09

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W15-015 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
80	0.0	H	23.0	37.4	39.6	m#G	WT	N/A	190.4	50.1	44.5	32.5	25.9	20.6	N/A	110.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.0	11.7	9.3	6.8	4.3	N/A	23.0
SPLIT	WT=	480.9						CUM WT %	N/A	39.0	51.3	60.5	67.3	72.7	77.0	100.0
65	1.0	H	23.3	43.0	33.0	m#G	WT	N/A	142.9	57.3	48.8	33.0	24.6	19.2	N/A	99.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.0	13.5	11.6	7.0	5.8	N/A	23.4
SPLIT	WT=	424.9						CUM WT %	N/A	33.0	47.1	58.6	66.4	72.2	76.7	100.0
70	0.1	H	17.5	62.0	20.5	gmS	WT	N/A	68.0	83.0	57.9	30.3	19.9	14.4	N/A	58.1
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	20.5	25.0	17.5	9.1	6.0	N/A	17.5
SPLIT	WT=	331.0						CUM WT %	N/A	20.5	45.5	63.0	72.1	78.1	82.5	100.0
75	0.4	H	28.7	39.3	32.0	m#G	WT	N/A	105.5	37.3	29.7	23.7	20.7	18.1	N/A	94.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.0	11.3	9.0	7.2	6.3	N/A	26.7
SPLIT	WT=	329.0						CUM WT %	N/A	32.0	43.3	52.3	59.5	65.0	71.3	100.0
80	0.0	H	18.4	29.7	51.0	m#G	WT	N/A	212.5	40.8	30.2	21.2	16.4	13.3	N/A	75.4
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.0	9.9	7.4	6.2	4.0	N/A	18.4
SPLIT	WT=	409.0						CUM WT %	N/A	51.0	61.8	69.2	74.3	78.3	81.0	100.0
85	1.1	H	23.3	51.2	25.5	gmS	WT	N/A	117.5	41.7	60.0	74.4	34.3	20.1	N/A	107.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.5	9.0	14.3	10.1	7.4	N/A	23.3
SPLIT	WT=	461.0						CUM WT %	N/A	25.5	34.5	40.0	64.9	72.3	78.7	100.0
90	1.3	H	16.0	67.9	10.5	(m)gS	WT	N/A	72.1	55.5	88.0	90.3	39.4	24.4	N/A	88.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.5	12.7	20.1	20.0	9.0	N/A	16.0
SPLIT	WT=	430.0						CUM WT %	N/A	10.5	29.1	49.2	69.0	76.0	84.4	100.0
95	1.2	H	20.7	75.4	3.9	mS	WT	N/A	14.3	29.1	72.0	102.2	47.7	24.0	N/A	75.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.9	6.0	19.7	28.0	13.1	N/A	20.7
SPLIT	WT=	365.4						CUM WT %	N/A	3.9	11.9	31.8	59.5	72.6	79.3	100.0
100	1.0	H	24.1	73.1	2.0	mS	WT	N/A	9.0	13.9	32.4	63.7	71.4	50.0	N/A	70.0
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	2.0	4.3	9.9	19.0	21.0	N/A	24.1
SPLIT	WT=	325.7						CUM WT %	N/A	2.0	7.0	17.0	30.5	50.4	75.0	100.0
105	1.4	H	18.5	79.0	1.9	(m)S	WT	N/A	0.9	17.0	50.7	67.3	67.0	66.5	N/A	60.5
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.9	4.0	15.3	23.0	18.1	N/A	18.5
SPLIT	WT=	309.0						CUM WT %	N/A	1.9	8.5	21.0	45.4	63.5	81.5	100.0
110	1.6	H	17.9	80.9	1.2	(m)S	WT	N/A	3.0	19.0	05.5	102.4	52.5	29.4	N/A	59.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.2	6.7	19.0	31.0	16.9	N/A	17.9
SPLIT	WT=	330.9						CUM WT %	N/A	1.2	6.9	20.7	67.7	73.5	82.1	100.0

K.70

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL B290-W16-015 ****

02/02/89

DEPTH	%AC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
116	1.8	H	24.9	74.8	0.6	mS	WT	N/A	1.7	15.2	58.9	58.9	39.4	80.0	N/A	78.9
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	WT %	N/A	0.6	4.9	18.4	19.1	12.8	19.4	N/A	24.9
SPLIT	WT=	309.8					CUM WT %	N/A	0.6	6.6	29.9	42.9	55.7	75.1	N/A	100.0
120	1.8	H	23.7	75.8	0.5	mS	WT	N/A	1.7	12.0	43.6	63.2	61.0	80.9	N/A	75.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	WT %	N/A	0.6	3.8	13.7	19.9	19.4	19.1	N/A	23.7
SPLIT	WT=	318.2					CUM WT %	N/A	0.6	4.3	18.0	37.0	57.2	78.3	N/A	100.0
126	1.6	H	26.8	72.9	0.3	mS	WT	N/A	0.9	8.4	38.1	46.6	71.5	77.6	N/A	88.2
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	WT %	N/A	0.3	2.6	9.4	14.5	22.3	24.2	N/A	26.8
SPLIT	WT=	321.3					CUM WT %	N/A	0.3	2.9	12.3	26.8	49.0	73.2	N/A	100.0
130	1.3	H	21.5	78.6	0.8	mS	WT	N/A	0.1	13.8	31.8	46.2	78.8	77.1	N/A	87.8
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	WT %	N/A	0.0	4.4	18.2	14.5	24.6	24.8	N/A	21.5
SPLIT	WT=	311.5					CUM WT %	N/A	0.0	4.6	14.6	29.1	53.7	76.6	N/A	100.0
136	1.4	H	22.5	77.0	0.6	mS	WT	N/A	1.6	7.9	29.8	72.3	87.9	81.4	N/A	75.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.5	2.4	8.9	21.5	26.1	18.2	N/A	22.5
SPLIT	WT=	336.6					CUM WT %	N/A	0.6	2.8	11.7	33.2	59.3	77.5	N/A	100.0
140	2.0	H	36.3	63.3	0.4	mS	WT	N/A	1.1	5.4	17.2	38.0	55.7	59.3	N/A	100.7
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	WT %	N/A	0.4	2.0	8.2	13.7	20.1	21.4	N/A	36.3
SPLIT	WT=	277.4					CUM WT %	N/A	0.4	2.4	8.6	22.3	42.3	63.7	N/A	100.0
146	2.4	H	61.4	38.6	0.8	mS	WT	N/A	0.1	2.2	8.9	21.0	31.0	40.8	N/A	179.8
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	WT %	N/A	0.0	0.6	3.0	7.2	18.0	16.8	N/A	61.4
SPLIT	WT=	292.8					CUM WT %	N/A	0.0	0.8	3.8	11.0	21.0	38.0	N/A	100.0
160	2.8	H	78.3	20.7	0.8	mS	WT	N/A	0.6	0.9	3.9	8.6	13.6	31.5	N/A	224.4
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	WT %	N/A	0.0	0.3	1.4	3.0	4.8	11.1	N/A	79.4
SPLIT	WT=	282.7					CUM WT %	N/A	0.0	0.3	1.7	4.7	9.6	20.7	N/A	100.0
166	17.1	H	59.7	28.6	11.8	gmS	WT	N/A	30.3	12.9	10.1	9.9	14.6	25.5	N/A	162.7
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	WT %	N/A	11.8	5.0	4.0	3.9	5.7	10.0	N/A	59.7
SPLIT	WT=	266.9					CUM WT %	N/A	11.8	18.9	20.8	24.7	30.4	40.3	N/A	100.0
180	27.4	H	39.5	48.6	11.7	gmS	WT	N/A	31.9	22.4	18.8	23.2	33.8	34.9	N/A	107.3
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	WT %	N/A	11.7	8.2	6.8	8.6	12.4	12.8	N/A	39.5
SPLIT	WT=	271.9					CUM WT %	N/A	11.7	20.0	26.8	35.3	47.7	60.5	N/A	100.0
166	27.1	N	27.4	54.7	18.0	gmS	WT	N/A	59.2	38.0	28.3	31.9	43.3	37.6	N/A	90.1
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	WT %	N/A	18.0	11.0	8.6	9.7	19.2	11.4	N/A	27.4
SPLIT	WT=	329.4					CUM WT %	N/A	18.0	29.8	38.4	48.1	61.3	72.8	N/A	100.0

K.71

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

**** REPORT ON WELL 0290-W16-015 ****

02/02/89

DEPTH	%CAC08	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	20.3	H	20.0	88.1	8.8	(p)ms	WT	N/A	30.2	23.1	44.4	103.8	44.8	34.3	N/A	90.4
SORT=	N/A		2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.0	6.1	11.7	27.4	11.8	9.1	N/A
SPLIT	WT= 379.1							CUM WT %	N/A	8.0	14.1	25.0	53.2	65.0	74.0	N/A
175	4.6	H	33.8	62.2	4.0	ms	WT	N/A	11.7	7.5	18.1	61.9	53.9	42.5	N/A	90.9
SORT=	N/A		3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	4.0	2.5	6.1	21.0	18.2	14.4	N/A
SPLIT	WT= 295.4							CUM WT %	N/A	4.0	6.5	12.6	33.6	51.8	66.2	N/A
180	1.0	H	16.6	43.7	39.6	msG	WT	N/A	139.3	25.2	30.1	39.4	32.0	20.2	N/A	56.4
SORT=	N/A		1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.6	7.2	10.3	11.2	9.3	5.8	N/A
SPLIT	WT= 351.5							CUM WT %	N/A	39.0	48.8	57.1	68.3	77.5	83.4	N/A
185	0.4	H	17.6	42.1	40.3	msG	WT	N/A	161.5	47.2	43.0	33.6	25.0	16.0	N/A	70.4
SORT=	N/A		0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.3	11.0	10.7	8.4	6.7	4.5	N/A
SPLIT	WT= 400.4							CUM WT %	N/A	40.3	52.1	62.9	71.2	77.9	82.4	N/A
190	0.1	H	20.2	41.2	38.8	msG	WT	N/A	120.3	39.6	37.0	24.9	20.1	15.4	N/A	67.0
SORT=	N/A		0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.8	11.8	11.3	7.4	6.0	4.6	N/A
SPLIT	WT= 334.0							CUM WT %	N/A	38.6	50.5	61.0	69.2	75.2	79.8	N/A
195	0.0	H	11.7	40.1	40.1	msG	WT	N/A	95.7	25.1	27.6	27.0	20.0	15.1	N/A	28.0
SORT=	N/A		0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.1	10.5	11.0	11.3	8.4	6.3	N/A
SPLIT	WT= 235.3							CUM WT %	N/A	40.1	50.7	62.2	73.5	81.0	88.3	N/A
200	0.1	H	19.8	41.0	38.4	msG	WT	N/A	100.0	43.7	35.5	49.9	42.0	25.1	N/A	93.4
SORT=	N/A		1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.4	9.3	7.7	10.0	8.9	5.3	N/A
SPLIT	WT= 471.4							CUM WT %	N/A	36.4	47.0	55.4	68.0	74.0	80.2	N/A
205	0.1	H	21.0	43.7	34.0	msG	WT	N/A	145.1	39.5	32.0	43.0	41.5	27.0	N/A	90.7
SORT=	N/A		1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.0	9.4	7.0	10.4	9.0	6.4	N/A
SPLIT	WT= 420.3							CUM WT %	N/A	34.0	44.2	51.0	62.1	72.0	78.4	N/A
210	0.1	H	22.0	41.2	38.2	msG	WT	N/A	140.0	37.9	31.3	33.0	40.0	25.2	N/A	92.7
SORT=	N/A		1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	36.2	9.2	7.0	8.2	10.0	8.1	N/A
SPLIT	WT= 410.1							CUM WT %	N/A	36.2	45.0	53.1	61.3	71.3	77.4	N/A
215	0.1	H	18.0	40.0	34.3	msG	WT	N/A	134.5	30.8	22.2	52.1	50.0	21.0	N/A	74.0
SORT=	N/A		2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.3	7.0	5.7	13.3	14.5	5.5	N/A
SPLIT	WT= 391.4							CUM WT %	N/A	34.3	42.1	47.0	61.1	75.6	81.1	N/A
220	0.1	H	19.9	45.4	34.7	msG	WT	N/A	100.7	44.1	30.2	50.9	59.7	25.0	N/A	92.1
SORT=	N/A		1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.7	9.5	8.6	11.0	12.9	5.0	N/A
SPLIT	WT= 463.2							CUM WT %	N/A	34.7	44.2	50.7	61.7	74.6	80.1	N/A

K.72

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W16-015 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
226	0.1	H	20.2	43.7	36.1	msG	WT	N/A	143.7	32.0	25.4	46.9	47.0	22.4	N/A	00.2
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.1	8.1	8.4	11.8	11.8	5.6
SPLIT	WT=	397.6					CUM WT %	N/A	30.1	44.2	60.6	62.4	74.2	79.8	N/A	100.0
230	0.1	H	17.4	51.0	30.8	msG	WT	N/A	138.8	66.9	45.7	52.8	45.3	20.3	N/A	77.3
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.8	14.9	10.3	10.2	4.6	N/A
SPLIT	WT=	443.9					CUM WT %	N/A	30.8	45.0	55.9	57.8	70.0	82.6	N/A	100.0
235	0.0	H	24.2	40.4	27.4	gmS	WT	N/A	111.2	40.0	31.4	40.3	47.7	22.1	N/A	98.1
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.4	11.5	7.7	11.9	11.0	6.6
SPLIT	WT=	405.0					CUM WT %	N/A	27.4	39.0	46.7	58.6	70.4	75.0	N/A	100.0
240	0.0	H	23.5	47.9	28.6	gmS	WT	N/A	86.0	40.5	25.3	31.9	28.7	17.2	N/A	70.4
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.6	13.5	0.4	10.0	9.0	6.7
SPLIT	WT=	290.8					CUM WT %	N/A	28.6	42.1	50.6	61.2	70.6	76.5	N/A	100.0
246	0.0	H	20.0	42.5	31.5	msG	WT	N/A	105.0	29.1	16.0	31.7	37.5	20.3	N/A	86.0
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.5	0.7	5.1	9.5	11.3	7.9
SPLIT	WT=	332.0					CUM WT %	N/A	31.5	40.3	45.3	54.8	60.1	74.0	N/A	100.0
250	0.0	H	7.2	82.7	10.1	gS	WT	N/A	37.0	34.1	27.9	57.2	135.6	45.3	N/A	27.0
SORT=	N/A		MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	10.1	9.1	7.4	17.9	38.2	12.1
SPLIT	WT=	374.9					CUM WT %	N/A	10.1	19.2	20.6	44.0	80.7	92.8	N/A	100.0
255	0.0	H	13.2	67.5	29.3	(m)gS	WT	N/A	108.0	54.5	40.0	41.2	53.9	24.0	N/A	49.0
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.3	14.7	10.0	11.1	14.5	0.5
SPLIT	WT=	371.4					CUM WT %	N/A	29.3	44.0	54.7	65.0	80.3	88.0	N/A	100.0

K.73

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W15-010 ****

02/02/89

K.75

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	0.1	N/	35.9	63.3	0.9	mS	WT	N/A	4.0	11.7	27.0	51.4	98.6	144.6	N/A	187.7
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.9	2.2	5.2	9.8	10.6	N/A	35.9
SPLIT	WT=	525.0						CUM WT %	N/A	0.9	3.1	8.3	18.1	38.6	N/A	100.0
10	0.2	N/	0.6	84.5	15.0	gS	WT	N/A	97.9	274.9	189.7	82.9	18.0	3.0	N/A	3.0
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	15.1	42.3	29.2	9.7	2.9	N/A	8.5
SPLIT	WT=	651.0						CUM WT %	N/A	15.1	57.3	86.5	96.1	99.0	N/A	100.0
15	0.0	C	10.9	47.0	41.5	msG	WT	N/A	373.8	113.3	70.1	107.0	89.9	89.3	N/A	98.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.6	12.8	8.4	11.9	7.8	N/A	10.9
SPLIT	WT=	903.0						CUM WT %	N/A	41.6	54.0	62.5	74.3	82.1	N/A	100.0
20	0.4	C	1.0	89.6	8.9	(B)S	WT	N/A	55.1	147.3	297.2	96.3	35.7	11.2	N/A	10.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.9	22.4	45.3	14.7	5.4	N/A	1.0
SPLIT	WT=	657.5						CUM WT %	N/A	8.9	31.3	76.6	91.2	96.7	N/A	100.0
25	0.4	C	10.8	40.0	40.2	msG	WT	N/A	348.3	109.2	70.7	122.1	71.6	44.5	N/A	93.7
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.2	12.0	6.9	14.1	6.1	N/A	10.5
SPLIT	WT=	809.1						CUM WT %	N/A	40.2	52.8	61.7	75.8	84.1	N/A	100.0
30	0.5	C	1.0	40.0	52.9	gG	WT	N/A	395.4	161.0	135.4	33.7	0.6	5.0	N/A	7.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	52.9	21.5	18.1	4.6	1.3	N/A	1.0
SPLIT	WT=	750.5						CUM WT %	N/A	52.9	74.4	92.5	97.0	98.3	N/A	100.0
35	1.0	C	2.6	97.4	0.1	S	WT	N/A	0.3	22.3	220.7	231.2	63.2	17.7	N/A	14.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	3.9	30.7	40.8	11.1	N/A	2.6
SPLIT	WT=	571.2						CUM WT %	N/A	0.1	4.0	42.7	83.3	94.4	N/A	100.0
40	1.2	C	4.0	95.3	0.7	S	WT	N/A	3.9	30.7	170.1	204.8	80.8	62.0	N/A	23.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.7	8.4	30.5	35.4	14.0	N/A	4.0
SPLIT	WT=	578.4						CUM WT %	N/A	0.7	7.0	37.5	72.9	86.9	N/A	100.0
45	1.0	C	10.9	80.7	0.4	(m)S	WT	N/A	2.0	3.1	7.0	13.6	132.7	243.3	N/A	93.0
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.4	0.8	1.6	2.7	28.8	N/A	10.9
SPLIT	WT=	494.3						CUM WT %	N/A	0.4	1.0	2.0	6.3	32.0	N/A	100.0
50	1.3	C	2.0	97.2	0.0	S	WT	N/A	0.0	1.3	116.2	817.1	91.0	61.2	N/A	17.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	0.2	19.2	52.6	16.2	N/A	2.0
SPLIT	WT=	805.4						CUM WT %	N/A	0.0	0.2	19.5	71.9	87.1	N/A	100.0
55	1.3	C	2.0	98.8	0.4	S	WT	N/A	2.3	36.5	120.0	181.0	140.6	31.4	N/A	14.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	0.7	23.8	34.1	26.4	N/A	2.0
SPLIT	WT=	534.3						CUM WT %	N/A	0.4	7.1	30.5	65.0	91.3	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0200-W15-016 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	1.2	C	5.9	94.1	N/A	G	WT	N/A	N/A	N/A	33.8	252.2	170.0	71.7	N/A	22.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	N/A	0.0	46.0	30.3	12.0	N/A	5.9
SPLIT	WT=	561.6						CUM WT %	N/A	N/A	0.0	51.0	81.4	94.2	N/A	100.0
65	1.1	C	14.0	85.2	0.2	(m)S	WT	N/A	0.9	6.9	29.9	86.3	182.8	152.1	N/A	74.8
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	1.2	6.9	31.8	29.7	N/A	14.8
SPLIT	WT=	512.8						CUM WT %	N/A	0.2	1.3	23.9	66.7	86.4	N/A	100.0
70	1.8	C	2.6	97.3	0.1	S	WT	N/A	0.8	6.5	74.0	233.8	147.6	27.0	N/A	12.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	1.1	48.0	20.4	6.6	N/A	2.0
SPLIT	WT=	503.1						CUM WT %	N/A	0.1	1.2	10.0	82.5	91.9	N/A	100.0
75	1.1	C	0.5	70.9	20.8	ps	WT	N/A	180.0	147.0	223.1	76.0	12.7	3.3	N/A	3.2
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.0	22.7	34.2	11.8	2.0	N/A	0.5
SPLIT	WT=	663.0						CUM WT %	N/A	20.0	61.3	86.4	97.1	99.0	N/A	100.0
80	0.8	C	0.4	79.6	20.0	ps	WT	N/A	133.0	213.2	225.0	71.1	14.6	5.4	N/A	2.4
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	20.0	32.1	33.9	10.7	2.2	N/A	0.4
SPLIT	WT=	688.5						CUM WT %	N/A	20.0	52.1	85.9	90.6	98.8	N/A	100.0
85	0.9	C	0.8	70.3	22.8	ps	WT	N/A	154.3	214.0	223.0	59.3	14.3	5.5	N/A	5.7
SORT=	N/A	MEDIAN=	0.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	22.8	31.7	33.0	8.0	2.1	N/A	0.9
SPLIT	WT=	676.9						CUM WT %	N/A	22.8	54.5	87.5	90.2	98.3	N/A	100.0
90	0.6	C	0.4	56.0	43.6	msG	WT	N/A	260.7	172.0	130.0	30.0	0.9	2.2	N/A	2.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.0	20.2	21.3	5.0	1.1	N/A	0.4
SPLIT	WT=	613.1						CUM WT %	N/A	43.0	71.8	93.1	98.1	99.2	N/A	100.0
95	2.0	C	2.2	32.1	65.7	msG	WT	N/A	488.5	90.4	80.3	36.9	20.0	10.9	N/A	10.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	85.7	12.2	10.0	5.0	2.7	N/A	2.2
SPLIT	WT=	745.0						CUM WT %	N/A	85.7	77.0	88.7	93.6	96.3	N/A	100.0
100	0.0	C	3.2	40.8	55.0	msG	WT	N/A	404.0	131.0	114.4	46.0	20.2	10.2	N/A	20.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.0	15.9	13.0	6.0	3.4	N/A	3.2
SPLIT	WT=	831.7						CUM WT %	N/A	60.0	71.0	86.6	91.2	94.0	N/A	100.0
105	1.0	C	3.0	20.9	76.2	msG	WT	N/A	639.2	65.2	42.1	30.9	27.8	21.9	N/A	32.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	76.2	0.5	5.0	3.0	3.3	N/A	3.0
SPLIT	WT=	851.6						CUM WT %	N/A	76.2	81.7	86.7	90.3	93.6	N/A	100.0
110	2.0	C	4.5	21.0	73.9	msG	WT	N/A	590.5	56.1	40.0	29.4	26.6	20.2	N/A	30.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.9	7.0	5.1	3.7	3.2	N/A	4.5
SPLIT	WT=	800.1						CUM WT %	N/A	73.9	81.0	86.1	89.8	93.0	N/A	100.0

K.76

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W16-010 ****

02/02/69

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PER (≤-2)	VFINE PER (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
115	0.6	H	17.2	82.8	0.0	(m)S	WT	N/A	0.0	9.0	124.0	249.8	159.2	82.1	N/A	129.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	1.3	18.6	33.1	21.1	18.8	N/A	17.2
SPLIT	WT= 766.2							CUM WT %	N/A	0.0	1.3	17.8	60.9	72.0	82.0	N/A	100.0
123	0.4	H	4.3	64.3	31.4	sG	WT	N/A	261.4	72.3	97.4	138.8	140.3	74.7	N/A	34.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.4	9.0	12.2	18.3	17.5	9.3	N/A	4.3
SPLIT	WT= 803.5							CUM WT %	N/A	31.4	48.4	62.6	80.9	86.4	95.7	N/A	100.0
126	0.6	H	4.4	51.0	44.7	sG	WT	N/A	369.6	141.0	149.8	88.1	38.0	22.0	N/A	36.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	44.7	17.8	18.8	7.5	4.8	2.7	N/A	4.4
SPLIT	WT= 805.8							CUM WT %	N/A	44.7	82.3	80.6	88.3	92.9	95.6	N/A	100.0
130	0.9	H	0.2	50.7	41.1	msG	WT	N/A	388.9	130.9	131.1	77.9	66.3	60.7	N/A	73.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.1	14.0	14.0	8.7	7.3	6.6	N/A	8.2
SPLIT	WT= 899.9							CUM WT %	N/A	41.1	66.0	70.2	78.9	88.2	91.8	N/A	100.0
136	0.7	H	33.6	24.6	42.1	mG	WT	N/A	123.0	21.4	11.0	6.7	30.3	2.6	N/A	97.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.1	7.3	4.0	2.0	10.4	0.9	N/A	33.6
SPLIT	WT= 292.3							CUM WT %	N/A	42.1	49.4	63.4	65.3	66.7	66.0	N/A	100.0
140	4.0	H	59.0	28.8	3.0	sM	WT	N/A	11.9	7.0	6.6	9.2	23.0	41.4	N/A	230.6	
SORT=	N/A	MEDIAN=	6.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	3.0	2.1	2.0	2.8	7.2	12.6	N/A	69.8
SPLIT	WT= 330.1							CUM WT %	N/A	3.0	6.7	7.7	10.6	17.7	30.2	N/A	100.0
146	10.1	H	39.0	44.4	16.7	gmS	WT	N/A	47.8	27.1	17.6	19.2	33.7	37.2	N/A	121.1	
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	16.7	6.9	6.0	6.3	11.1	12.3	N/A	39.9
SPLIT	WT= 303.7							CUM WT %	N/A	16.7	24.7	30.4	36.8	47.9	60.1	N/A	100.0
150	21.1	H	40.4	49.7	9.9	(p)mS	WT	N/A	32.0	20.6	26.4	20.6	41.4	41.3	N/A	134.4	
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	9.9	8.6	7.6	8.8	12.6	12.4	N/A	48.4
SPLIT	WT= 332.3							CUM WT %	N/A	9.9	18.4	28.1	34.7	47.1	69.6	N/A	100.0
156	13.4	H	31.0	63.7	6.3	(p)mS	WT	N/A	14.5	12.6	23.7	63.0	49.9	23.2	N/A	84.2	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.3	4.6	8.7	23.6	18.4	8.6	N/A	31.0
SPLIT	WT= 271.9							CUM WT %	N/A	6.3	9.9	18.7	42.1	60.6	69.0	N/A	100.0
160	4.3	H	61.6	45.1	3.4	sM	WT	N/A	11.2	8.7	22.9	17.4	83.3	18.4	N/A	172.0	
SORT=	N/A	MEDIAN=	6.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	3.4	2.6	6.9	6.2	25.0	5.6	N/A	61.6
SPLIT	WT= 334.0							CUM WT %	N/A	3.4	6.0	12.8	18.0	43.0	48.6	N/A	100.0
165	2.4	H	49.9	48.4	1.6	sM	WT	N/A	6.6	4.0	11.3	93.7	33.8	22.3	N/A	170.2	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.6	1.2	3.3	27.6	8.9	0.6	N/A	49.9
SPLIT	WT= 340.9							CUM WT %	N/A	1.6	2.8	6.1	33.6	43.6	60.1	N/A	100.0

K.77

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

**** REPORT ON WELL 0200-W15-010 ****

02/02/88

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	1.9	H	25.1	70.0	4.9	ms	WT	N/A	16.0	8.2	13.8	83.0	103.7	29.5	N/A	77.5
SORT=	N/A		MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	4.9	2.0	4.4	20.4	33.0	9.8
SPLIT	WT=	308.6					CUM WT %	N/A	4.9	6.9	11.3	21.7	65.9	74.9	N/A	100.0
175	1.1	N	22.7	62.7	25.7	gmS	WT	N/A	107.1	40.7	38.4	48.6	64.0	24.1	N/A	94.8
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.7	9.8	11.6	15.3	5.6	22.7
SPLIT	WT=	417.4					CUM WT %	N/A	25.7	35.4	44.6	56.2	71.6	77.3	N/A	100.0
180	0.0	H	21.1	70.3	2.0	ms	WT	N/A	9.0	13.0	21.3	89.7	116.7	23.0	N/A	72.9
SORT=	N/A		MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	2.0	3.9	6.2	26.9	33.6	8.8
SPLIT	WT=	345.6					CUM WT %	N/A	2.0	8.6	12.7	38.8	72.1	78.9	N/A	100.0
185	0.0	H	11.4	54.0	34.5	msG	WT	N/A	288.0	83.5	64.6	159.3	103.2	67.0	N/A	94.7
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.6	10.1	7.9	10.8	12.4	7.0
SPLIT	WT=	633.0					CUM WT %	N/A	34.6	44.6	62.4	69.2	81.6	88.0	N/A	100.0
195	0.2	H	10.0	58.0	32.0	msG	WT	N/A	240.9	60.2	84.2	110.9	103.0	66.9	N/A	77.9
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.0	10.9	8.7	16.1	14.1	7.0
SPLIT	WT=	739.3					CUM WT %	N/A	32.0	43.7	62.6	87.8	81.7	89.4	N/A	100.0
210	0.1	H	12.1	64.2	23.7	(m)gS	WT	N/A	170.0	97.0	75.0	137.6	92.7	80.0	N/A	87.3
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.7	13.0	10.6	19.1	12.8	6.3
SPLIT	WT=	728.1					CUM WT %	N/A	23.7	37.2	47.7	88.7	79.6	87.9	N/A	100.0
215	0.2	H	22.0	50.0	27.5	gmS	WT	N/A	120.8	45.7	38.4	55.0	40.8	31.2	N/A	99.2
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.5	10.4	8.7	12.6	11.1	7.1
SPLIT	WT=	439.0					CUM WT %	N/A	27.5	37.9	48.6	59.2	70.3	77.4	N/A	100.0
220	0.2	H	25.0	52.1	22.1	gmS	WT	N/A	88.5	48.9	37.4	48.2	47.0	29.5	N/A	103.3
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	22.1	12.2	9.3	11.6	11.7	7.4
SPLIT	WT=	400.0					CUM WT %	N/A	22.1	34.3	43.6	55.1	68.9	74.2	N/A	100.0
230	0.2	H	11.9	55.9	32.2	msG	WT	N/A	109.7	60.1	45.1	44.0	28.1	12.0	N/A	40.4
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.2	17.7	13.3	12.9	6.3	3.8
SPLIT	WT=	340.3					CUM WT %	N/A	32.2	49.9	63.2	76.1	84.3	88.1	N/A	100.0
235	0.2	H	4.2	22.2	73.0	msG	WT	N/A	339.4	15.7	12.3	34.8	29.7	9.9	N/A	19.6
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.0	3.4	2.7	7.5	0.4	2.2
SPLIT	WT=	461.4					CUM WT %	N/A	73.0	77.0	79.0	87.2	93.6	95.8	N/A	100.0
240	0.2	H	8.0	35.4	57.7	msG	WT	N/A	217.0	61.0	23.0	20.0	10.0	0.4	N/A	25.9
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	57.7	16.4	0.8	5.0	2.2	N/A
SPLIT	WT=	375.0					CUM WT %	N/A	57.7	74.1	80.5	85.9	90.9	93.1	N/A	100.0

K.78

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAND REPORT

PAGE 5

**** REPORT ON WELL 0200-W16-010 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PE0 (<= -2)	VFINE PE0 (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
265	N/A	H	20.2	85.8	14.0	gms	WT	N/A	46.2	41.0	35.5	70.9	48.2	21.7	N/A	88.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	14.0	12.4	10.8	21.6	14.6	6.6	N/A	20.2
SPLIT	WT=	290.2					CUM WT %	N/A	14.0	26.4	37.2	58.0	73.2	79.8	N/A	100.0

K.79

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W15-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.2	H	27.1	59.0	13.1	gmS	WT	N/A	47.6	42.3	32.0	29.4	46.3	86.1	N/A	97.0
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.2	11.7	9.1	8.1	12.6	18.3	N/A
SPLIT	WT=	381.3						CUM WT %	N/A	13.2	24.0	33.9	42.1	54.8	72.9	N/A
10	0.0	H	11.3	81.0	0.0	(gm)S	WT	N/A	26.7	68.0	77.6	40.7	60.1	49.9	N/A	42.0
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.9	18.2	20.8	13.3	18.1	13.4	N/A
SPLIT	WT=	372.8						CUM WT %	N/A	0.9	25.1	45.9	59.2	76.4	88.7	N/A
16	0.6	H	7.3	86.6	7.1	(g)S	WT	N/A	26.0	73.1	92.6	63.9	60.0	26.9	N/A	26.6
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.1	20.0	27.2	17.6	13.9	7.1	N/A
SPLIT	WT=	366.8						CUM WT %	N/A	7.1	27.1	54.3	71.7	86.7	92.7	N/A
20	0.6	H	6.8	89.8	4.8	N/A	WT	N/A	18.3	63.7	130.9	90.7	60.2	17.0	21.6	N/A
SORT=	N/A	MEDIAN=	1.00	MODE=	N/A	MEAN=	N/A	WT %	N/A	4.8	10.0	34.2	21.1	13.1	4.7	6.6
SPLIT	WT=	383.2						CUM WT %	N/A	4.8	21.4	66.6	76.8	89.7	94.4	100.0
25	0.6	H	7.8	82.4	9.7	(g)S	WT	N/A	38.6	67.2	101.6	97.4	46.0	14.6	N/A	31.0
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.7	17.0	26.7	24.8	11.6	3.7	N/A
SPLIT	WT=	396.8						CUM WT %	N/A	9.7	26.7	62.4	77.0	88.6	92.2	N/A
30	0.6	H	11.6	61.6	26.8	(m)gS	WT	N/A	112.0	101.8	61.2	37.0	22.2	14.3	N/A	48.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.8	24.4	10.6	8.1	6.3	3.4	N/A
SPLIT	WT=	417.0						CUM WT %	N/A	20.8	61.2	70.7	70.7	86.0	88.6	N/A
35	0.0	H	30.6	87.9	1.7	mS	WT	N/A	6.8	12.1	66.6	61.4	60.6	36.1	N/A	106.7
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.7	3.6	16.0	23.6	14.0	10.4	N/A
SPLIT	WT=	347.0						CUM WT %	N/A	1.7	6.2	21.2	44.8	69.2	69.6	N/A
40	1.1	H	26.7	72.0	1.7	mS	WT	N/A	0.4	11.0	83.8	106.1	49.2	30.9	N/A	99.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.7	3.0	21.7	27.2	12.7	8.0	N/A
SPLIT	WT=	368.4						CUM WT %	N/A	1.7	4.7	20.4	63.6	86.3	74.3	N/A
45	1.2	H	30.0	69.7	1.3	mS	WT	N/A	6.2	13.0	70.6	80.1	61.0	43.1	N/A	110.1
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.3	3.4	10.2	22.6	13.2	11.1	N/A
SPLIT	WT=	388.9						CUM WT %	N/A	1.3	4.7	22.9	45.7	59.9	70.0	N/A
50	1.3	H	31.0	68.4	0.0	mS	WT	N/A	2.1	0.4	64.7	82.7	62.0	60.3	N/A	116.6
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	0.0	2.2	14.6	22.0	14.1	16.6	N/A
SPLIT	WT=	376.7						CUM WT %	N/A	0.0	2.0	17.4	39.4	63.5	60.0	N/A
55	1.3	H	20.8	72.4	0.8	mS	WT	N/A	3.0	9.8	64.1	90.3	64.6	68.0	N/A	102.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.8	2.0	14.2	23.0	16.9	16.2	N/A
SPLIT	WT=	382.1						CUM WT %	N/A	0.8	3.4	17.6	41.1	69.0	73.2	N/A

K.01

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAND REPORT

**** REPORT ON WELL 0209-W16-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
80	1.4	H	24.7	74.0	0.4	mS	WT	N/A	1.3	4.6	29.7	90.5	81.4	58.4	N/A	87.4
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.4	1.3	8.4	25.8	23.0	10.5	N/A
SPLIT	WT=	363.7						CUM WT %	N/A	0.4	1.7	10.1	36.7	58.7	75.3	N/A
85	1.5	H	31.0	69.0	0.0	mS	WT	N/A	0.0	1.7	10.0	58.2	60.4	43.0	N/A	81.0
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.7	6.4	22.2	23.1	10.7	N/A
SPLIT	WT=	261.8						CUM WT %	N/A	0.0	0.7	7.1	28.3	52.4	69.1	N/A
70	1.9	H	31.2	68.0	0.0	mS	WT	N/A	0.0	0.7	12.7	52.0	58.2	35.9	N/A	72.2
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.3	5.5	22.4	26.1	15.5	N/A
SPLIT	WT=	231.7						CUM WT %	N/A	0.0	0.3	5.0	28.2	53.3	68.8	N/A
75	1.7	H	25.7	70.9	3.3	mS	WT	N/A	12.6	12.0	34.9	80.3	88.4	40.3	N/A	90.8
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	3.3	3.4	9.3	23.0	23.0	12.3	N/A
SPLIT	WT=	375.9						CUM WT %	N/A	3.3	0.8	16.0	39.0	82.0	74.3	N/A
80	1.1	H	12.8	73.8	13.4	(m)gS	WT	N/A	53.0	67.7	94.0	87.5	59.3	21.0	N/A	50.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.4	17.2	24.0	17.1	10.0	5.5	N/A
SPLIT	WT=	394.4						CUM WT %	N/A	13.4	30.0	54.0	71.7	81.7	87.2	N/A
85	1.0	H	9.1	72.4	18.5	(m)gS	WT	N/A	70.7	119.7	108.9	47.0	20.0	11.4	N/A	38.8
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	10.5	25.1	25.0	11.1	4.9	2.7	N/A
SPLIT	WT=	424.5						CUM WT %	N/A	10.5	40.6	72.2	83.3	88.2	90.9	N/A
90	1.1	H	20.0	68.5	13.6	gmS	WT	N/A	46.5	60.2	73.8	41.2	27.0	17.8	N/A	60.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.6	19.9	21.5	12.0	7.9	5.2	N/A
SPLIT	WT=	343.1						CUM WT %	N/A	13.6	33.4	55.0	67.0	74.8	80.0	N/A
95	1.0	H	17.8	64.8	17.6	gmS	WT	N/A	60.6	81.0	77.9	43.0	29.3	10.6	N/A	49.2
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.0	20.8	20.0	11.2	7.6	5.0	N/A
SPLIT	WT=	389.1						CUM WT %	N/A	17.6	38.4	58.5	69.7	77.2	82.2	N/A
100	0.9	H	23.1	50.8	28.1	gmS	WT	N/A	99.1	60.1	53.4	35.7	25.4	17.9	N/A	87.5
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.1	15.9	14.1	9.4	8.7	4.7	N/A
SPLIT	WT=	379.2						CUM WT %	N/A	20.1	42.0	58.1	66.5	72.2	76.9	N/A
105	0.8	H	18.5	44.7	36.8	msG	WT	N/A	141.7	54.6	44.2	31.1	24.3	17.7	N/A	71.1
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.8	14.2	11.5	8.1	6.3	4.8	N/A
SPLIT	WT=	384.7						CUM WT %	N/A	30.8	51.0	82.5	70.8	70.9	81.5	N/A
110	0.8	H	20.4	46.5	33.0	msG	WT	N/A	123.5	55.4	44.9	31.5	24.1	16.0	N/A	76.4
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.0	14.8	12.0	8.5	6.5	4.0	N/A
SPLIT	WT=	373.5						CUM WT %	N/A	33.0	47.9	59.9	68.3	74.8	79.8	N/A

K.82

ROCKWELL HANFORD OPERATIONS STEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-W15-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)	
116	0.6	H	10.1	85.2	4.7	(m)S	WT	N/A	15.9	64.6	84.7	83.0	47.4	18.8	N/A	34.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.7	18.1	25.0	24.7	14.0	5.5	N/A	10.1
SPLIT	WT=	339.4						CUM WT %	N/A	4.7	20.7	45.7	70.4	84.3	89.9	N/A	100.0
120	0.6	H	10.2	69.2	30.6	msG	WT	N/A	143.7	124.0	84.9	34.6	19.8	14.2	N/A	47.0	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	20.4	18.1	7.4	4.2	3.0	N/A	10.2
SPLIT	WT=	460.1						CUM WT %	N/A	30.6	57.1	75.2	82.5	85.6	89.9	N/A	100.0
125	0.6	H	9.0	80.2	30.8	msG	WT	N/A	271.1	227.0	117.0	61.2	89.6	63.2	N/A	79.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.8	25.8	13.4	7.0	7.9	0.1	N/A	9.0
SPLIT	WT=	875.0						CUM WT %	N/A	30.8	56.7	70.1	77.0	84.9	91.0	N/A	100.0
130	0.6	H	9.5	61.2	39.3	msG	WT	N/A	377.3	171.0	104.5	75.0	71.7	60.6	N/A	91.3	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.3	17.9	10.9	7.8	7.5	7.2	N/A	0.5
SPLIT	WT=	980.3						CUM WT %	N/A	39.3	57.2	68.0	75.9	83.3	90.5	N/A	100.0
135	0.8	H	11.1	42.4	46.5	msG	WT	N/A	400.2	147.2	80.5	44.4	60.7	49.1	N/A	97.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	46.5	16.9	7.0	5.1	7.0	5.0	N/A	11.1
SPLIT	WT=	871.3						CUM WT %	N/A	46.5	83.4	71.2	78.3	83.2	88.0	N/A	100.0
140	3.1	H	20.7	73.2	6.2	(p)ms	WT	N/A	46.7	81.5	88.3	130.3	127.4	127.0	N/A	157.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.2	10.7	11.6	17.2	16.8	18.8	N/A	20.7
SPLIT	WT=	767.0						CUM WT %	N/A	6.2	10.9	20.6	45.7	62.6	79.3	N/A	100.0
145	10.4	H	17.3	70.6	4.1	(m)S	WT	N/A	29.1	53.7	64.2	140.2	152.3	144.2	N/A	123.7	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	4.1	7.6	9.0	20.7	21.3	20.2	N/A	17.3
SPLIT	WT=	711.8						CUM WT %	N/A	4.1	11.8	20.0	41.3	62.6	82.7	N/A	100.0
160	10.6	H	11.1	84.0	4.0	(m)S	WT	N/A	27.2	59.2	91.7	163.7	168.9	92.0	N/A	75.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	4.0	8.7	13.5	24.2	24.9	13.6	N/A	11.1
SPLIT	WT=	679.0						CUM WT %	N/A	4.0	12.8	26.3	50.4	75.4	88.9	N/A	100.0
165	0.3	H	39.2	50.0	1.2	ms	WT	N/A	3.3	10.7	21.5	40.1	55.3	30.4	N/A	109.8	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.2	3.8	7.7	17.5	19.7	10.0	N/A	39.2
SPLIT	WT=	279.0						CUM WT %	N/A	1.2	5.0	12.7	30.2	50.0	60.0	N/A	100.0
160	7.3	H	37.0	61.0	0.0	ms	WT	N/A	1.9	0.2	10.1	42.3	50.0	20.4	N/A	89.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	2.0	6.7	17.7	29.5	11.1	N/A	37.0
SPLIT	WT=	230.7						CUM WT %	N/A	0.0	3.4	10.1	27.9	51.3	62.4	N/A	100.0
165	4.0	H	37.8	61.0	0.0	ms	WT	N/A	1.4	1.0	0.0	32.2	63.0	27.7	N/A	93.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.7	2.4	13.1	34.1	11.3	N/A	37.0
SPLIT	WT=	245.0						CUM WT %	N/A	0.0	1.3	3.7	10.8	50.9	62.2	N/A	100.0

K.03

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 02PR-W16-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	4.3	H	31.8	59.8	8.6	(g)ms	WT	N/A	25.9	22.4	25.6	40.1	65.2	28.1	N/A	98.9
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	8.5	7.3	13.1	21.7	9.2	N/A
SPLIT	WT=	305.1							CUM WT %	N/A	8.5	15.8	24.2	37.3	59.0	N/A
175	3.1	H	23.8	55.8	20.6	gmS	WT	N/A	79.3	53.4	46.0	40.4	50.0	24.4	N/A	98.7
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.6	13.9	10.6	13.0	8.4	N/A
SPLIT	WT=	384.1							CUM WT %	N/A	20.6	34.5	46.5	57.0	70.0	N/A
180	2.0	H	17.6	43.3	39.1	msQ	WT	N/A	161.1	57.3	34.1	25.9	30.1	20.2	N/A	68.0
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.1	14.8	8.8	8.7	5.2	N/A
SPLIT	WT=	388.8							CUM WT %	N/A	39.1	53.9	62.7	69.4	77.2	N/A
185	1.1	H	22.3	46.7	31.0	msG	WT	N/A	104.5	43.7	33.4	27.9	30.4	22.3	N/A	75.4
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	12.9	9.9	8.3	9.0	N/A
SPLIT	WT=	337.6							CUM WT %	N/A	31.0	43.9	53.8	62.0	71.0	N/A
190	0.8	H	22.9	53.6	23.8	gmS	WT	N/A	85.6	63.3	49.4	47.7	41.3	25.0	N/A	92.7
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.8	13.2	11.8	10.2	8.2	N/A
SPLIT	WT=	404.9							CUM WT %	N/A	23.8	36.8	49.0	60.7	70.9	N/A
195	0.2	H	31.7	48.9	19.3	gmS	WT	N/A	84.6	50.4	42.4	41.7	45.0	34.7	N/A	139.0
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.3	11.5	9.7	9.5	10.3	N/A
SPLIT	WT=	437.8							CUM WT %	N/A	19.3	30.8	40.5	50.0	60.3	N/A
200	0.1	H	12.4	36.9	48.7	msG	WT	N/A	180.0	52.2	29.5	26.9	25.1	14.8	N/A	47.2
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.7	19.7	7.7	7.1	6.6	N/A
SPLIT	WT=	381.6							CUM WT %	N/A	48.7	62.4	70.1	77.2	83.6	N/A
205	0.2	H	27.3	59.3	13.4	gmS	WT	N/A	38.0	29.7	24.4	30.9	58.4	24.6	N/A	77.2
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.4	10.5	8.6	10.9	20.6	N/A
SPLIT	WT=	283.1							CUM WT %	N/A	13.4	23.9	32.5	43.4	64.1	N/A
210	0.2	H	17.0	43.4	39.6	msG	WT	N/A	184.8	57.5	30.6	29.3	42.4	21.1	N/A	70.9
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	39.6	13.8	7.4	7.0	5.1	N/A
SPLIT	WT=	416.7							CUM WT %	N/A	39.6	53.4	60.7	67.7	77.9	N/A
215	0.1	H	22.5	64.2	13.3	gmS	WT	N/A	62.7	77.5	68.0	60.4	60.7	35.9	N/A	105.8
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.3	15.5	14.4	12.8	7.8	N/A
SPLIT	WT=	471.8							CUM WT %	N/A	13.3	29.8	44.2	57.0	69.8	N/A
220	0.1	H	26.1	46.3	27.6	gmS	WT	N/A	90.7	38.3	28.8	30.5	31.9	22.5	N/A	85.8
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.6	11.7	8.8	9.3	9.7	N/A
SPLIT	WT=	378.7							CUM WT %	N/A	27.6	39.3	48.0	57.3	67.0	N/A

K.84

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 6

**** REPORT ON WELL 0299-W16-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUO	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	0.1	H	22.4	53.2	24.4	gmS	WT	N/A	96.1	40.9	37.4	55.7	49.8	20.1	N/A	88.3
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.4	10.4	9.6	14.1	12.6	6.6	N/A
SPLIT	WT=	394.4					CUM	WT %	N/A	24.4	34.7	44.2	58.4	71.0	77.6	N/A
230	0.1	H	21.7	55.6	22.7	gmS	WT	N/A	84.8	42.2	30.0	61.4	49.2	24.7	N/A	81.2
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.7	11.3	8.0	16.4	13.2	6.6	N/A
SPLIT	WT=	373.4					CUM	WT %	N/A	22.7	34.0	42.0	58.5	71.6	78.3	N/A
235	0.1	H	25.6	60.9	13.5	gmS	WT	N/A	47.0	56.1	30.7	49.0	42.6	24.7	N/A	89.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.5	16.1	11.1	14.3	12.2	7.1	N/A
SPLIT	WT=	347.5					CUM	WT %	N/A	13.5	29.7	40.8	55.1	67.3	74.4	N/A
240	0.1	H	20.8	53.3	26.9	gmS	WT	N/A	88.3	41.7	32.4	53.0	37.0	18.0	N/A	71.0
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.9	12.2	9.6	15.8	11.1	4.7	N/A
SPLIT	WT=	341.0					CUM	WT %	N/A	25.9	38.1	47.8	63.4	74.6	79.2	N/A
245	0.1	H	21.4	55.3	23.2	gmS	WT	N/A	91.0	45.5	39.5	64.4	45.6	22.1	N/A	84.1
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.2	11.6	10.1	16.4	11.0	5.8	N/A
SPLIT	WT=	392.0					CUM	WT %	N/A	23.2	34.0	44.9	61.3	72.9	78.5	N/A
250	0.1	H	19.8	59.7	20.5	gmS	WT	N/A	80.7	46.2	35.5	70.7	51.9	25.1	N/A	78.1
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.5	11.7	9.0	19.5	13.2	6.4	N/A
SPLIT	WT=	394.3					CUM	WT %	N/A	20.5	32.2	41.2	60.7	73.8	80.2	N/A
255	0.1	H	21.5	63.0	15.5	gmS	WT	N/A	60.4	49.1	41.0	77.0	52.9	25.2	N/A	83.5
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	15.5	12.6	10.6	19.8	13.6	6.6	N/A
SPLIT	WT=	389.1					CUM	WT %	N/A	15.5	28.1	38.7	58.5	72.1	78.6	N/A
260	0.1	H	20.7	63.0	16.3	gmS	WT	N/A	66.3	45.7	35.7	97.8	61.3	25.4	N/A	83.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.3	11.3	8.0	21.0	15.1	8.3	N/A
SPLIT	WT=	405.9					CUM	WT %	N/A	16.3	27.6	36.4	58.0	73.1	79.3	N/A
265	0.1	H	18.9	68.6	12.5	gmS	WT	N/A	46.2	30.1	30.1	103.0	63.6	27.3	N/A	70.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	12.5	9.1	8.1	27.8	17.2	7.4	N/A
SPLIT	WT=	370.2					CUM	WT %	N/A	12.5	20.6	28.7	50.0	73.7	81.1	N/A
270	0.1	H	20.2	62.4	17.4	gmS	WT	N/A	67.8	40.1	34.7	84.5	57.7	26.7	N/A	78.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	17.4	10.3	8.9	21.7	14.8	6.8	N/A
SPLIT	WT=	390.4					CUM	WT %	N/A	17.4	27.6	36.5	58.2	73.0	79.8	N/A
275	0.2	H	22.0	60.0	18.0	gmS	WT	N/A	67.4	42.0	47.8	62.7	44.1	27.6	N/A	82.2
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	18.0	11.2	12.7	16.8	11.0	7.4	N/A
SPLIT	WT=	373.8					CUM	WT %	N/A	18.0	29.3	42.0	58.6	70.6	78.0	N/A

K.85

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0290-W16-017 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
280	0.1	H	18.0	80.4	21.6	gmS	WT	N/A	89.9	57.2	58.1	73.6	47.6	22.7	N/A	75.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.6	13.0	12.0	17.7	11.4	5.6	N/A	18.0
SPLIT	WT=	416.9					CUM WT %	N/A	21.8	35.4	47.4	66.1	76.6	82.0	N/A	100.0	
285	0.1	H	22.0	80.4	17.0	gmS	WT	N/A	58.1	42.2	38.3	61.6	41.0	22.2	N/A	77.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	17.0	12.4	11.2	18.0	12.3	0.6	N/A	22.0
SPLIT	WT=	341.2					CUM WT %	N/A	17.0	29.4	40.6	50.7	70.9	77.4	N/A	100.0	
290	0.1	H	22.2	62.2	15.5	gmS	WT	N/A	46.0	39.9	33.0	60.7	39.0	21.2	N/A	69.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	15.5	12.7	10.0	19.3	12.7	0.0	N/A	22.2
SPLIT	WT=	314.1					CUM WT %	N/A	15.5	28.2	39.0	58.3	71.0	77.8	N/A	100.0	
295	0.2	H	24.4	65.2	10.4	gmS	WT	N/A	39.0	30.4	30.5	62.5	58.0	32.0	N/A	93.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.4	9.0	10.1	21.6	15.4	0.0	N/A	24.4
SPLIT	WT=	381.2					CUM WT %	N/A	10.4	19.9	30.0	51.7	67.1	76.0	N/A	100.0	
300	0.1	H	21.7	62.5	15.8	gmS	WT	N/A	80.0	43.0	30.3	84.3	40.0	24.3	N/A	63.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.8	11.4	9.0	21.9	13.0	0.3	N/A	21.7
SPLIT	WT=	395.1					CUM WT %	N/A	15.8	27.2	37.2	59.0	72.0	78.3	N/A	100.0	
305	0.2	H	20.4	54.1	17.5	gmS	WT	N/A	50.0	32.3	35.0	61.1	39.7	26.4	N/A	97.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	17.5	9.5	10.4	15.0	11.0	7.7	N/A	20.4
SPLIT	WT=	342.0					CUM WT %	N/A	17.5	28.0	37.4	52.3	63.0	71.6	N/A	100.0	
310	0.2	H	23.0	63.7	12.5	gmS	WT	N/A	40.0	50.0	57.5	75.3	41.0	22.7	N/A	92.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	12.5	12.0	14.0	19.4	10.0	6.0	N/A	23.0
SPLIT	WT=	308.4					CUM WT %	N/A	12.5	25.4	40.2	59.0	70.3	78.2	N/A	100.0	
315	0.2	H	26.2	65.2	9.6	(g)mS	WT	N/A	35.7	25.4	30.3	112.4	52.7	20.4	N/A	93.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.0	6.9	8.2	30.4	14.2	6.6	N/A	25.2
SPLIT	WT=	370.1					CUM WT %	N/A	9.0	10.5	24.7	55.0	69.3	74.8	N/A	100.0	
320	0.2	H	7.8	83.0	8.8	(g)S	WT	N/A	33.0	73.9	130.0	84.2	21.6	5.7	N/A	29.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.0	19.3	35.5	22.0	5.0	1.6	N/A	7.6
SPLIT	WT=	363.2					CUM WT %	N/A	0.0	27.9	63.4	65.3	91.0	92.4	N/A	100.0	
325	0.2	H	11.2	66.3	22.5	(m)gS	WT	N/A	74.0	40.2	44.3	61.5	44.8	23.0	N/A	37.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.6	13.9	13.3	18.5	13.5	7.2	N/A	11.2
SPLIT	WT=	331.4					CUM WT %	N/A	22.6	30.4	49.7	60.2	81.7	88.0	N/A	100.0	
335	0.1	H	7.1	63.0	9.0	(g)S	WT	N/A	61.1	103.4	110.1	211.3	63.4	48.3	N/A	47.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.1	15.3	10.3	31.3	13.0	7.2	N/A	7.1
SPLIT	WT=	670.1					CUM WT %	N/A	9.1	24.4	40.7	72.0	85.6	92.9	N/A	100.0	

K.05

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 7

**** REPORT ON WELL 0299-W16-017 ****

02/02/89

K.87

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
340	0.1	H	6.9	81.8	11.3	gS	WT	N/A	74.9	89.1	114.8	198.9	99.7	48.8	N/A	45.6
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.3	13.4	17.3	30.0	15.0	N/A	8.9
SPLIT	WT=	861.7						CUM	WT %	N/A	11.3	24.7	42.0	72.0	87.1	100.0
345	0.1	H	5.8	91.1	3.1	S	WT	N/A	21.1	37.8	145.2	304.8	84.0	41.1	N/A	38.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.1	5.6	21.8	45.3	12.5	N/A	5.8
SPLIT	WT=	874.6						CUM	WT %	N/A	3.1	8.7	30.3	75.6	88.1	100.0
350	0.1	H	7.3	82.2	10.5	gS	WT	N/A	67.3	33.5	71.2	294.1	82.8	44.4	N/A	48.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.5	5.2	11.1	46.0	12.9	N/A	7.3
SPLIT	WT=	833.6						CUM	WT %	N/A	10.5	16.8	28.9	72.9	85.8	100.0
365	0.1	H	5.2	85.7	9.0	(g)S	WT	N/A	88.0	47.3	88.5	320.2	95.7	39.8	N/A	34.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.0	7.1	10.0	48.2	14.4	N/A	5.2
SPLIT	WT=	868.6						CUM	WT %	N/A	9.0	16.2	28.2	74.4	88.8	100.0
380	0.1	H	5.3	71.0	23.7	gS	WT	N/A	132.9	78.7	68.8	189.7	80.2	29.9	N/A	29.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	23.7	14.1	10.5	30.3	10.8	N/A	5.3
SPLIT	WT=	561.8						CUM	WT %	N/A	23.7	37.8	48.3	78.8	89.4	100.0
365	0.1	H	4.0	77.7	18.3	gS	WT	N/A	118.9	80.3	73.7	246.8	88.0	30.2	N/A	25.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	18.3	12.8	11.5	38.8	10.3	N/A	4.0
SPLIT	WT=	642.7						CUM	WT %	N/A	18.3	30.8	42.4	80.9	91.3	100.0
370	0.1	H	5.7	88.3	8.1	(g)S	WT	N/A	47.4	47.6	126.8	212.3	81.3	37.4	N/A	33.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.1	8.1	21.8	38.3	13.9	N/A	5.7
SPLIT	WT=	583.0						CUM	WT %	N/A	8.1	16.2	37.8	74.1	88.0	100.0
375	1.8	H	5.4	87.7	6.8	(g)S	WT	N/A	45.3	64.9	184.1	287.1	85.1	41.7	N/A	38.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.8	9.8	15.7	43.2	12.8	N/A	5.5
SPLIT	WT=	687.9						CUM	WT %	N/A	6.8	18.8	32.3	75.6	88.3	100.0
380	0.9	H	6.4	82.9	11.8	gS	WT	N/A	78.8	82.8	88.7	275.8	87.3	36.3	N/A	35.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.8	9.5	13.1	41.8	13.2	N/A	5.4
SPLIT	WT=	659.0						CUM	WT %	N/A	11.8	21.3	34.4	78.8	89.2	100.0
385	0.4	H	6.2	78.2	15.8	gS	WT	N/A	112.2	64.4	79.1	250.5	110.4	59.8	N/A	44.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.8	8.9	11.0	34.7	15.3	N/A	6.2
SPLIT	WT=	725.1						CUM	WT %	N/A	15.8	24.5	35.5	70.2	85.5	100.0
390	0.4	H	5.2	90.9	3.9	S	WT	N/A	22.3	30.2	52.0	275.9	117.2	42.2	N/A	29.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.9	5.3	9.1	48.4	20.8	N/A	5.2
SPLIT	WT=	573.1						CUM	WT %	N/A	3.9	9.2	18.4	66.8	87.4	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0209-W15-017 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
395	0.6	H	6.3	74.6	20.1	gS	WT	N/A	96.7	60.6	92.8	105.9	84.8	31.9	N/A	25.4
SORT=	N/A	MEDIAN=	1.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	20.1	12.7	19.5	22.2	13.6	6.7	N/A
SPLIT	WT=	477.2					CUM	WT %	N/A	20.1	32.8	52.2	74.4	88.0	94.7	100.0
400	0.4	H	5.1	83.6	11.2	gS	WT	N/A	71.3	53.8	67.4	268.3	101.1	41.3	N/A	32.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.2	8.6	10.6	42.2	15.9	6.6	N/A
SPLIT	WT=	630.0					CUM	WT %	N/A	11.2	19.7	30.3	72.5	88.4	94.9	100.0
405	0.3	H	4.3	79.7	16.0	gS	WT	N/A	98.1	62.8	75.5	241.0	79.3	31.5	N/A	26.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	16.0	10.2	12.3	39.2	12.9	5.1	N/A
SPLIT	WT=	811.3					CUM	WT %	N/A	16.0	28.2	38.5	77.7	90.6	95.7	100.0
410	0.2	H	3.1	85.4	11.5	gS	WT	N/A	68.9	39.8	78.1	279.7	83.5	30.4	N/A	19.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.5	6.8	13.0	48.7	13.9	5.1	N/A
SPLIT	WT=	803.0					CUM	WT %	N/A	11.5	18.1	31.2	77.9	91.8	98.9	100.0
415	0.2	H	4.1	82.9	13.0	gS	WT	N/A	85.4	47.4	78.8	284.8	110.1	43.5	N/A	26.8
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.0	7.2	12.0	40.3	16.8	6.8	N/A
SPLIT	WT=	860.2					CUM	WT %	N/A	13.0	20.2	32.2	72.5	89.3	95.9	100.0
420	0.5	H	5.9	79.3	14.8	gS	WT	N/A	97.8	62.8	67.4	250.9	107.0	47.8	N/A	39.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	14.8	8.5	8.7	37.9	18.2	7.2	N/A
SPLIT	WT=	857.0					CUM	WT %	N/A	14.8	24.2	32.9	70.8	88.9	94.1	100.0
425	1.5	H	5.1	79.8	15.0	gS	WT	N/A	91.6	71.2	103.7	185.6	87.5	38.5	N/A	31.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.0	11.7	17.0	30.5	14.4	6.3	N/A
SPLIT	WT=	812.8					CUM	WT %	N/A	15.0	28.7	43.7	74.2	88.0	94.9	100.0
430	1.2	H	6.2	80.8	13.0	gS	WT	N/A	91.3	83.5	138.0	192.6	107.9	43.5	N/A	43.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.0	11.9	19.7	27.5	15.4	8.2	N/A
SPLIT	WT=	898.0					CUM	WT %	N/A	13.0	25.0	44.7	72.2	87.8	93.8	100.0
435	1.0	H	7.5	78.6	13.9	gS	WT	N/A	90.3	93.9	102.3	175.3	94.1	45.7	N/A	48.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.9	14.4	15.7	27.0	14.5	7.0	N/A
SPLIT	WT=	843.9					CUM	WT %	N/A	13.9	28.3	44.1	71.0	85.5	92.5	100.0
440	0.6	H	3.2	91.8	5.0	(g)S	WT	N/A	24.0	31.3	160.8	174.0	55.1	21.6	N/A	15.5
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.0	6.5	33.3	36.1	11.4	4.5	N/A
SPLIT	WT=	482.2					CUM	WT %	N/A	5.0	11.5	44.8	80.9	92.3	96.8	100.0
445	0.4	H	55.7	39.7	4.6	sM	WT	N/A	7.7	10.8	13.1	24.4	11.5	7.4	N/A	93.9
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	4.6	6.3	7.8	14.5	6.8	4.4	N/A
SPLIT	WT=	168.7					CUM	WT %	N/A	4.6	10.9	18.6	33.1	39.9	44.3	100.0

K.88

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W15-018 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.6	C	17.2	81.4	1.4	(m)S	WT	N/A	9.1	15.0	57.1	98.5	171.8	204.6	N/A	115.9
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.4	2.2	8.5	14.7	25.6	N/A	17.3
SPLIT	WT=	871.8						CUM WT %	N/A	1.4	3.6	12.1	26.7	52.3	N/A	100.0
10	0.9	C	4.9	83.8	11.6	gS	WT	N/A	70.3	73.2	82.3	138.4	175.4	46.2	N/A	30.1
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	11.5	11.9	13.4	22.2	28.6	N/A	4.9
SPLIT	WT=	614.0						CUM WT %	N/A	11.5	23.4	36.6	59.0	87.6	N/A	100.0
15	0.8	C	6.2	88.5	7.3	(g)S	WT	N/A	55.0	156.2	187.9	118.7	100.2	78.6	N/A	46.4
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.3	20.9	25.1	15.6	14.5	N/A	6.2
SPLIT	WT=	751.4						CUM WT %	N/A	7.3	28.2	53.3	68.9	83.3	N/A	100.0
20	1.7	C	14.0	85.9	0.1	(m)S	WT	N/A	0.6	0.1	2.9	52.5	305.5	180.0	N/A	88.2
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.1	0.0	0.5	8.3	48.5	N/A	14.0
SPLIT	WT=	829.7						CUM WT %	N/A	0.1	0.1	0.6	8.9	57.4	N/A	100.0
25	0.0	C	2.5	98.8	0.9	S	WT	N/A	6.7	165.0	370.5	101.3	35.0	19.7	N/A	17.8
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	0.9	23.0	51.8	14.2	4.9	N/A	2.5
SPLIT	WT=	715.9						CUM WT %	N/A	0.9	24.0	75.7	69.9	94.8	N/A	100.0
30	0.6	C	10.4	85.7	4.0	(m)S	WT	N/A	32.7	324.4	278.7	59.5	14.7	24.2	N/A	84.8
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	4.0	39.6	34.0	7.3	1.8	N/A	10.4
SPLIT	WT=	819.0						CUM WT %	N/A	4.0	43.6	77.6	84.9	88.7	N/A	100.0
35	0.8	C	1.9	66.3	31.9	sG	WT	N/A	282.7	313.5	180.0	48.5	8.8	17.4	N/A	15.3
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	31.9	38.1	19.4	5.6	1.0	N/A	1.9
SPLIT	WT=	824.0						CUM WT %	N/A	31.9	69.9	89.4	95.0	96.0	N/A	100.0
40	1.6	C	15.8	84.1	0.1	(m)S	WT	N/A	0.0	1.1	27.8	152.0	172.9	207.6	N/A	105.7
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.1	0.2	4.2	22.9	25.9	N/A	15.8
SPLIT	WT=	872.1						CUM WT %	N/A	0.1	0.3	4.4	27.3	53.2	N/A	100.0
45	2.0	C	20.4	79.8	0.0	mS	WT	N/A	0.0	0.0	12.4	58.4	146.2	287.9	N/A	129.1
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.0	2.0	9.2	23.1	N/A	20.4
SPLIT	WT=	834.0						CUM WT %	N/A	0.0	0.0	2.0	11.2	34.2	N/A	100.0
50	1.8	C	31.5	88.5	0.0	mS	WT	N/A	0.0	0.0	0.0	4.5	N/A	443.5	N/A	205.7
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.0	0.0	0.7	N/A	N/A	31.5
SPLIT	WT=	853.7						CUM WT %	N/A	0.0	0.0	0.0	0.7	N/A	N/A	100.0
55	1.6	C	8.3	87.6	4.0	S	WT	N/A	28.7	17.1	141.3	264.1	102.5	96.7	N/A	59.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.1	2.4	19.9	37.2	14.5	N/A	8.3
SPLIT	WT=	709.6						CUM WT %	N/A	4.1	6.5	26.4	83.6	78.1	N/A	100.0

K.89

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0200-W16-010 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
80	1.2	C	0.4	93.4	0.1	S	WT	N/A	0.9	4.3	37.3	206.8	309.0	60.2	N/A	42.6
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.1	0.7	6.0	31.3	46.8	9.1	N/A
SPLIT	WT=	664.0						CUM WT %	N/A	0.1	0.8	0.4	37.7	84.6	93.6	N/A
85	2.8	C	10.8	80.8	0.4	(m)S	WT	N/A	2.5	22.8	92.7	186.2	191.6	97.4	N/A	132.5
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.4	3.2	13.1	23.6	27.1	13.0	N/A
SPLIT	WT=	705.5						CUM WT %	N/A	0.4	3.6	16.7	40.3	67.4	81.2	N/A
70	1.7	C	11.7	88.3	0.0	(m)S	WT	N/A	0.0	0.0	9.0	117.1	206.9	140.2	N/A	75.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.0	1.5	18.3	48.5	22.0	N/A
SPLIT	WT=	838.7						CUM WT %	N/A	0.0	0.0	1.5	19.8	68.3	88.3	N/A
75	1.0	C	13.1	86.9	0.0	(m)S	WT	N/A	0.0	1.5	11.0	34.9	228.0	282.1	N/A	80.9
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.2	1.9	5.6	36.8	42.3	N/A
SPLIT	WT=	819.0						CUM WT %	N/A	0.0	0.2	2.1	7.8	44.6	86.9	N/A
90	2.0	C	9.8	90.1	0.0	S	WT	N/A	0.0	12.2	147.1	232.4	100.0	83.4	N/A	64.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.0	1.9	22.7	35.9	16.7	12.9	N/A
SPLIT	WT=	847.1						CUM WT %	N/A	0.0	1.9	24.6	60.6	77.2	90.1	N/A
85	1.9	C	20.3	79.7	0.0	mS	WT	N/A	0.2	9.4	32.8	70.2	179.0	285.4	N/A	128.7
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	1.5	5.3	11.3	28.7	32.0	N/A
SPLIT	WT=	823.7						CUM WT %	N/A	0.0	1.6	8.0	18.1	46.8	79.7	N/A
90	1.0	C	17.4	82.6	0.0	(m)S	WT	N/A	0.0	0.0	8.4	98.6	298.5	167.2	N/A	118.4
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.0	1.2	14.5	43.6	23.1	N/A
SPLIT	WT=	680.7						CUM WT %	N/A	0.0	0.0	1.2	15.7	59.6	82.0	N/A
92	N/A	C	17.9	77.4	4.7	(m)S	WT	N/A	11.4	52.7	25.4	41.7	40.1	26.9	N/A	42.9
SORT=	N/A	MEDIAN=	2.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	4.0	22.0	10.0	17.4	16.7	10.8	N/A
SPLIT	WT=	240.1						CUM WT %	N/A	4.0	26.7	37.3	54.7	71.4	82.1	N/A
95	1.8	C	10.1	69.9	0.0	(m)S	WT	N/A	0.0	0.1	0.7	38.0	368.1	103.0	N/A	84.1
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.1	0.0	5.0	55.1	25.7	N/A
SPLIT	WT=	635.0						CUM WT %	N/A	0.0	0.0	0.1	6.1	64.2	89.9	N/A
100	1.6	C	9.1	90.7	0.2	S	WT	N/A	1.1	2.8	17.8	79.8	282.7	153.0	N/A	64.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	0.4	3.0	13.6	47.8	26.0	N/A
SPLIT	WT=	592.0						CUM WT %	N/A	0.2	0.5	3.8	17.1	64.9	90.9	N/A
105	1.6	C	8.4	81.7	11.9	gS	WT	N/A	96.9	48.5	234.9	260.4	90.1	36.1	N/A	51.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.0	5.0	29.2	31.1	11.2	4.5	N/A
SPLIT	WT=	805.0						CUM WT %	N/A	11.9	17.7	48.8	77.9	69.1	93.6	N/A

K.90

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-W15-018 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
110	1.2	C	4.4	57.0	38.8	sg	WT	N/A	321.0	43.8	198.2	159.8	47.0	25.8	N/A	38.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	38.8	5.2	23.8	19.2	6.7	3.1	N/A	4.4
SPLIT	WT=	832.4					CUM	WT %	N/A	38.8	43.8	87.7	88.9	92.6	95.6	N/A	100.0
116	1.8	C	6.6	86.9	7.8	(g)S	WT	N/A	44.0	41.8	202.8	177.2	63.1	28.9	N/A	31.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	7.8	7.2	35.1	30.7	9.2	4.7	N/A	5.6
SPLIT	WT=	677.5					CUM	WT %	N/A	7.6	14.8	50.0	80.7	89.9	94.6	N/A	100.0
120	1.2	C	7.1	84.3	8.6	(g)S	WT	N/A	58.8	64.9	221.8	184.8	65.8	38.7	N/A	48.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.6	9.6	32.8	27.2	9.6	6.4	N/A	7.1
SPLIT	WT=	681.0					CUM	WT %	N/A	8.6	18.1	50.7	77.8	87.6	92.9	N/A	100.0
126	1.3	C	1.8	31.4	68.8	sg	WT	N/A	689.1	135.4	78.8	31.8	15.0	7.1	N/A	15.4	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.8	15.9	9.2	3.7	1.8	0.8	N/A	1.8
SPLIT	WT=	853.2					CUM	WT %	N/A	68.8	82.8	91.9	95.6	97.4	98.2	N/A	100.0
130	1.3	H	22.8	65.5	21.7	gmS	WT	N/A	88.9	45.8	89.7	52.3	33.6	26.0	N/A	93.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.7	11.2	17.0	12.8	8.2	8.4	N/A	22.8
SPLIT	WT=	489.7					CUM	WT %	N/A	21.7	32.9	49.9	62.7	70.8	77.2	N/A	100.0
136	1.7	H	41.8	44.3	13.9	gmS	WT	N/A	43.9	28.3	39.9	29.3	20.1	22.8	N/A	132.4	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.9	8.9	12.6	9.3	6.4	7.2	N/A	41.8
SPLIT	WT=	316.7					CUM	WT %	N/A	13.9	22.8	35.4	44.7	51.0	58.2	N/A	100.0
140	7.3	H	43.3	47.5	9.3	(g)mS	WT	N/A	29.4	24.5	38.0	37.5	25.9	26.4	N/A	137.0	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.3	7.7	11.4	11.8	8.2	8.3	N/A	43.3
SPLIT	WT=	316.8					CUM	WT %	N/A	9.3	17.0	28.4	40.2	48.4	56.8	N/A	100.0
146	9.7	H	22.9	41.3	35.7	msG	WT	N/A	152.1	33.8	45.8	42.3	30.7	23.4	N/A	97.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.8	7.9	10.8	9.9	7.2	6.6	N/A	22.9
SPLIT	WT=	426.4					CUM	WT %	N/A	35.8	43.7	54.4	64.4	71.6	77.1	N/A	100.0
160	4.2	H	19.3	65.2	15.4	gmS	WT	N/A	78.1	34.8	138.3	73.4	30.6	19.3	N/A	87.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	15.4	7.8	30.5	18.2	6.7	4.3	N/A	19.3
SPLIT	WT=	454.0					CUM	WT %	N/A	15.4	23.1	53.5	69.7	76.4	80.7	N/A	100.0
166	2.4	H	18.9	73.7	9.4	(gm)S	WT	N/A	34.2	19.5	102.8	88.7	41.5	17.8	N/A	81.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	9.4	5.4	28.3	23.8	11.4	4.8	N/A	18.9
SPLIT	WT=	383.8					CUM	WT %	N/A	9.4	14.8	43.0	68.9	78.3	83.1	N/A	100.0
180	1.3	H	18.5	75.1	6.5	(gm)S	WT	N/A	24.0	16.7	127.7	84.7	33.9	18.0	N/A	88.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	6.5	4.6	34.4	22.8	9.1	4.3	N/A	18.5
SPLIT	WT=	371.8					CUM	WT %	N/A	6.5	11.0	45.3	68.1	77.2	81.5	N/A	100.0

K.91

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 4

**** REPORT ON WELL 0299-W15-010 ****

02/02/89

K.92

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
185	0.4	H	10.5	70.0	10.7	gmS	WT	N/A	39.0	31.6	110.4	64.1	33.2	17.1	N/A	69.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	10.7	8.6	31.7	17.2	8.9	4.6	N/A	18.6
SPLIT	WT=	373.3						CUM WT %	N/A	10.7	19.2	60.9	68.1	78.9	81.6	N/A	100.0
170	0.2	H	20.0	66.2	8.7	(g)ms	WT	N/A	39.5	39.0	140.7	64.8	33.9	16.0	N/A	110.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.7	8.7	31.0	14.3	7.5	3.7	N/A	20.1
SPLIT	WT=	453.4						CUM WT %	N/A	8.7	17.4	48.5	62.8	70.2	74.0	N/A	100.0
175	0.1	H	15.3	41.3	43.4	msG	WT	N/A	166.9	47.0	53.3	27.2	10.8	12.4	N/A	50.9	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.4	12.4	13.9	7.1	4.0	3.2	N/A	15.3
SPLIT	WT=	384.9						CUM WT %	N/A	43.4	66.7	89.6	76.7	81.5	84.7	N/A	100.0
180	0.2	H	22.0	49.1	20.0	gmS	WT	N/A	101.1	40.7	43.3	44.5	20.2	20.5	N/A	62.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.0	11.3	12.0	12.3	7.8	5.7	N/A	22.9
SPLIT	WT=	361.1						CUM WT %	N/A	20.0	39.3	61.3	63.6	71.4	77.1	N/A	100.0
190	0.2	H	17.1	40.3	42.6	msG	WT	N/A	173.5	25.0	19.5	34.0	60.0	26.1	N/A	69.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.0	0.1	4.8	8.5	14.7	8.2	N/A	17.2
SPLIT	WT=	407.7						CUM WT %	N/A	42.0	46.7	53.5	62.0	76.7	82.9	N/A	100.0
195	0.1	H	32.9	63.3	3.9	mS	WT	N/A	9.2	24.7	30.7	31.2	41.0	23.0	N/A	78.2	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	3.9	10.4	12.9	13.1	17.2	9.7	N/A	32.9
SPLIT	WT=	238.0						CUM WT %	N/A	3.9	14.3	27.2	40.3	57.5	67.2	N/A	100.0
200	0.2	H	22.1	41.0	36.9	msG	WT	N/A	111.3	35.5	25.1	22.4	23.8	16.0	N/A	60.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.9	11.8	8.3	7.4	7.9	5.6	N/A	22.1
SPLIT	WT=	300.8						CUM WT %	N/A	30.9	46.7	67.0	64.5	72.3	77.9	N/A	100.0
205	0.1	H	23.9	45.0	30.5	msG	WT	N/A	114.5	44.9	32.7	38.2	32.9	22.6	N/A	69.7	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.5	12.0	0.7	10.2	8.6	6.0	N/A	23.9
SPLIT	WT=	375.4						CUM WT %	N/A	30.5	42.5	61.2	61.3	70.1	78.1	N/A	100.0
210	0.2	H	26.4	52.2	21.4	gmS	WT	N/A	78.3	38.7	34.7	47.1	43.1	27.0	N/A	96.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.4	10.0	9.5	12.9	11.8	7.5	N/A	28.4
SPLIT	WT=	366.0						CUM WT %	N/A	21.4	32.0	41.4	54.3	68.1	73.6	N/A	100.0
215	0.1	H	21.1	50.1	22.8	gmS	WT	N/A	90.3	49.4	43.6	60.2	46.4	22.2	N/A	83.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.8	12.6	11.0	15.2	11.7	5.6	N/A	21.1
SPLIT	WT=	395.6						CUM WT %	N/A	22.8	35.3	46.3	61.6	73.3	78.9	N/A	100.0
220	0.2	H	20.0	51.1	20.9	gmS	WT	N/A	60.7	36.4	27.0	32.8	33.7	18.9	N/A	61.5	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.9	12.6	9.3	11.3	11.6	6.5	N/A	28.0
SPLIT	WT=	290.8						CUM WT %	N/A	20.9	33.4	42.7	53.9	65.5	72.0	N/A	100.0

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0299-W16-018 ****

02/02/89

DEPTH	%CAC03	OM	%MUD	%SAND	%GRAVEL	CLASS		FINE PES (<= -2)	YFINE PES (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	0.1	H	19.8	48.8	31.6	msG	WT	N/A	102.5	26.3	20.8	57.8	37.7	18.2	N/A	83.8
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.6	8.1	6.4	17.8	11.8	6.8
SPLIT	WT=	325.8							CUM WT %	N/A	31.6	39.8	46.8	63.8	75.4	88.4
230	0.1	H	23.9	68.8	10.2	gmS	WT	N/A	27.2	20.9	21.4	55.3	60.1	18.8	N/A	83.8
SORT=	N/A		MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	10.2	7.8	8.8	20.7	22.5	7.8
SPLIT	WT=	267.5							CUM WT %	N/A	10.2	18.0	26.8	40.7	69.1	78.2
235	0.1	H	28.5	55.1	18.4	gmS	WT	N/A	40.1	34.2	28.1	31.9	35.8	10.8	N/A	78.8
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	18.4	12.8	9.8	12.8	13.4	7.1
SPLIT	WT=	268.8							CUM WT %	N/A	18.4	31.2	41.8	62.9	88.4	73.5
240	N/A	H	29.3	68.8	11.7	gmS	WT	N/A	27.1	24.7	28.5	31.3	34.9	19.8	N/A	87.8
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	11.7	10.7	11.5	13.6	15.3	8.2
SPLIT	WT=	231.2							CUM WT %	N/A	11.7	22.4	23.9	47.4	62.5	78.7

K.93

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W18-021 ****

02/02/89

DEPTH	%CAC03	DM	%MUO	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	0.9	C	4.8	95.0	0.2	S	WT	N/A	1.8	29.6	40.7	148.4	155.7	228.3	N/A	30.8	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.3	4.6	7.3	23.2	24.3	35.6	N/A	4.8
SPLIT	WT=	840.7						CUM WT %	N/A	0.3	4.9	12.2	35.3	59.6	95.2	N/A	100.0
9	2.4	C	17.0	82.9	0.1	(m)S	WT	N/A	0.5	7.9	39.8	90.5	222.4	185.8	N/A	111.9	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.1	1.2	6.0	13.7	33.8	28.2	N/A	17.0
SPLIT	WT=	858.8						CUM WT %	N/A	0.1	1.3	7.3	21.1	54.8	83.0	N/A	100.0
10	0.6	C	2.9	95.6	1.5	S	WT	N/A	9.6	121.6	322.8	135.0	35.3	18.2	N/A	19.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.5	18.4	48.8	20.4	5.3	2.8	N/A	2.9
SPLIT	WT=	681.9						CUM WT %	N/A	1.5	19.8	68.6	89.0	94.3	97.1	N/A	100.0
15	0.5	C	1.5	95.0	3.5	S	WT	N/A	25.0	168.4	360.6	103.9	33.5	18.9	N/A	11.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.5	23.1	50.2	14.4	4.7	2.6	N/A	1.5
SPLIT	WT=	719.5						CUM WT %	N/A	3.5	26.6	76.8	91.2	95.9	98.5	N/A	100.0
20	0.4	C	1.0	78.5	22.5	gS	WT	N/A	183.9	278.5	234.0	33.7	5.4	8.4	N/A	7.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	22.5	38.0	32.2	4.6	0.7	0.9	N/A	1.0
SPLIT	WT=	727.2						CUM WT %	N/A	22.5	60.6	92.8	97.4	98.1	99.0	N/A	100.0
25	1.0	C	11.4	73.2	15.4	(m)gS	WT	N/A	105.7	281.7	111.5	29.8	43.2	55.0	N/A	77.8	
SORT=	N/A	MEDIAN=	0.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	15.4	38.2	18.3	4.4	0.3	8.0	N/A	11.4
SPLIT	WT=	684.8						CUM WT %	N/A	15.4	53.7	69.9	74.3	80.6	88.6	N/A	100.0
30	1.0	C	7.5	92.5	0.0	S	WT	N/A	0.0	0.2	38.6	150.9	157.4	270.3	N/A	49.7	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.0	5.8	22.6	23.6	40.5	N/A	7.5
SPLIT	WT=	667.2						CUM WT %	N/A	0.0	0.0	5.8	28.4	52.0	92.6	N/A	100.0
35	1.2	C	2.4	91.9	5.7	(g)S	WT	N/A	39.4	73.6	263.9	151.2	89.8	54.2	N/A	16.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.7	10.7	38.4	22.0	13.0	7.9	N/A	2.4
SPLIT	WT=	688.2						CUM WT %	N/A	5.7	16.4	54.6	76.8	89.8	97.7	N/A	100.0
39	N/A	C	9.0	88.0	5.0	(g)S	WT	N/A	14.0	18.5	71.8	61.5	48.1	39.0	N/A	24.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.0	6.7	25.8	22.2	17.3	14.1	N/A	9.0
SPLIT	WT=	277.6						CUM WT %	N/A	5.0	11.7	37.5	59.6	77.0	91.0	N/A	100.0
40	1.4	C	5.8	86.3	7.9	(g)S	WT	N/A	58.4	59.7	131.5	192.3	111.4	121.8	N/A	41.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	7.9	8.4	18.4	28.9	15.6	17.1	N/A	5.8
SPLIT	WT=	714.5						CUM WT %	N/A	7.9	16.3	34.7	61.6	77.2	94.2	N/A	100.0
42	1.2	H	3.1	40.9	56.0	gS	WT	N/A	455.0	122.5	108.3	53.1	29.1	19.8	N/A	25.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	56.0	15.1	13.3	8.5	3.6	2.4	N/A	3.1
SPLIT	WT=	612.8						CUM WT %	N/A	56.0	71.1	84.4	90.9	94.5	96.9	N/A	100.0

K.95

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 2

**** REPORT ON WELL 0299-W18-021 ****

02/02/09

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (≥4.75)
45	0.7	H	7.6	55.0	37.0	msG	WT	N/A	149.0	89.1	80.0	34.6	19.0	12.9	N/A	30.2
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	22.0	17.0	8.5	4.0	3.2	N/A	7.5
SPLIT	WT=	405.2					CUM	WT %	N/A	37.0	59.0	70.0	84.5	89.4	92.5	100.0
50	1.1	H	14.0	31.1	54.3	msG	WT	N/A	236.0	42.2	31.1	23.1	20.0	10.2	N/A	63.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	64.3	9.7	7.1	5.3	4.0	4.2	14.0
SPLIT	WT=	436.7					CUM	WT %	N/A	64.3	64.0	71.1	76.4	81.2	85.4	100.0
55	0.8	H	13.0	30.6	49.9	msG	WT	N/A	210.7	65.4	34.0	21.6	17.4	15.2	N/A	57.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.9	15.5	8.2	5.1	4.1	3.0	13.0
SPLIT	WT=	422.3					CUM	WT %	N/A	49.9	65.4	73.6	78.7	82.8	88.4	100.0
60	1.2	H	11.7	29.0	58.7	msG	WT	N/A	250.2	38.2	32.7	24.0	10.2	14.1	N/A	49.0
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.7	0.5	7.7	5.0	4.3	3.3	11.7
SPLIT	WT=	420.2					CUM	WT %	N/A	50.7	67.2	74.9	80.7	85.0	88.3	100.0
65	1.6	H	19.0	02.0	10.6	gmS	WT	N/A	73.3	20.7	34.0	71.5	03.0	50.5	N/A	77.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.5	0.7	0.0	10.0	16.9	12.7	19.0
SPLIT	WT=	398.4					CUM	WT %	N/A	10.6	20.2	33.8	51.0	67.7	80.4	100.0
70	1.6	H	24.0	04.0	10.6	gmS	WT	N/A	30.0	30.9	49.0	50.0	45.0	50.0	N/A	80.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.5	0.0	14.1	14.5	13.1	14.4	24.0
SPLIT	WT=	361.0					CUM	WT %	N/A	10.6	19.3	33.4	47.9	61.0	75.4	100.0
75	1.0	H	21.3	00.1	12.0	gmS	WT	N/A	43.7	31.2	55.0	55.0	42.7	45.0	N/A	73.9
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	12.0	0.0	15.0	15.0	12.3	13.1	21.3
SPLIT	WT=	347.1					CUM	WT %	N/A	12.0	21.0	37.4	53.0	65.6	78.7	100.0
75	1.0	H	24.7	05.0	9.7	(g)mS	WT	N/A	30.0	22.7	51.3	72.2	40.3	60.1	N/A	90.2
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	5.0	13.2	10.5	12.7	15.4	24.7
SPLIT	WT=	389.7					CUM	WT %	N/A	0.0	15.0	20.7	47.3	59.9	75.3	100.0
80	1.9	H	17.1	01.4	1.6	(m)S	WT	N/A	5.5	10.1	30.7	43.5	100.3	100.0	N/A	62.5
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.5	2.0	0.4	11.0	29.1	29.2	17.1
SPLIT	WT=	305.3					CUM	WT %	N/A	1.5	4.3	12.7	24.0	53.7	82.9	100.0
85	1.0	H	19.1	70.0	1.2	(m)S	WT	N/A	4.3	13.0	50.0	40.5	70.7	05.4	N/A	00.1
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.2	3.0	14.0	13.4	22.0	20.0	19.1
SPLIT	WT=	302.5					CUM	WT %	N/A	1.2	5.0	19.0	32.4	54.4	61.0	100.0
90	1.5	H	15.0	04.0	1.0	(m)S	WT	N/A	2.7	7.1	27.5	30.0	07.0	03.4	N/A	00.0
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.0	2.7	10.4	13.0	25.0	31.0	15.0
SPLIT	WT=	204.7					CUM	WT %	N/A	1.0	3.7	14.1	27.0	53.5	85.0	100.0

K.96

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0290-W18-021 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
95	1.6	H	16.7	83.1	0.1	(m)S	WT	N/A	0.4	5.4	31.2	73.9	71.0	70.0	N/A	50.7
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	1.6	10.3	24.4	23.3	N/A	16.7
SPLIT WT=	303.2							CUM WT %	N/A	0.1	1.9	12.2	36.6	60.0	N/A	100.0
100	1.6	H	17.0	82.9	0.1	(m)S	WT	N/A	0.4	4.9	27.5	71.5	69.0	62.5	N/A	48.4
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	1.7	9.7	25.1	22.0	N/A	17.0
SPLIT WT=	264.7							CUM WT %	N/A	0.1	1.9	11.5	35.6	61.1	N/A	100.0
105	1.0	H	26.0	73.5	0.7	mS	WT	N/A	1.0	2.1	11.1	33.4	57.0	91.3	N/A	68.5
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.7	0.8	4.2	12.6	21.5	N/A	25.8
SPLIT WT=	265.1							CUM WT %	N/A	0.7	1.5	6.7	18.3	39.7	N/A	100.0
110	1.0	H	23.5	75.0	0.9	mS	WT	N/A	2.6	3.6	16.8	45.8	64.3	71.0	N/A	62.7
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.9	1.4	8.3	17.1	24.1	N/A	25.5
SPLIT WT=	267.3							CUM WT %	N/A	0.9	2.3	8.6	25.7	49.0	N/A	100.0
115	1.0	H	28.2	73.1	0.7	mS	WT	N/A	2.1	4.2	21.5	55.0	80.1	80.3	N/A	62.0
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.7	1.3	6.6	17.5	25.5	N/A	28.2
SPLIT WT=	314.8							CUM WT %	N/A	0.7	2.0	8.8	28.3	49.3	N/A	100.0
120	1.0	H	28.4	73.0	0.6	mS	WT	N/A	1.7	2.4	13.3	45.3	69.1	70.3	N/A	75.4
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.6	0.6	4.7	16.9	24.2	N/A	26.4
SPLIT WT=	265.6							CUM WT %	N/A	0.6	1.4	6.1	22.0	46.2	N/A	100.0
125	2.1	H	30.9	62.8	0.6	mS	WT	N/A	1.0	2.1	10.4	42.7	68.4	84.8	N/A	122.9
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.6	0.6	3.1	12.0	20.6	N/A	30.9
SPLIT WT=	323.2							CUM WT %	N/A	0.6	1.2	4.3	17.1	37.0	N/A	100.0
130	2.3	H	45.4	54.1	0.5	mS	WT	N/A	1.0	1.0	7.4	29.0	50.6	80.4	N/A	147.3
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.5	0.5	2.3	9.1	16.0	N/A	45.4
SPLIT WT=	324.4							CUM WT %	N/A	0.5	1.0	3.3	12.4	28.6	N/A	100.0
135	2.4	H	51.0	47.0	0.0	sm	WT	N/A	1.0	1.0	6.7	22.2	37.0	71.0	N/A	151.3
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.7	2.3	7.0	12.0	N/A	51.0
SPLIT WT=	293.3							CUM WT %	N/A	0.0	1.3	3.5	11.1	23.9	N/A	100.0
140	3.1	H	57.3	41.5	1.1	sm	WT	N/A	2.1	2.5	3.9	10.1	20.9	40.9	N/A	108.1
SORT=	N/A	MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	1.1	1.3	2.1	5.4	11.1	N/A	57.4
SPLIT WT=	180.0							CUM WT %	N/A	1.1	2.4	4.6	9.9	21.0	N/A	100.0
145	5.0	H	48.0	39.4	11.0	gsM	WT	N/A	30.0	17.8	16.2	14.6	18.5	32.0	N/A	124.1
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	11.0	7.0	6.4	16.0	12.0	N/A	48.0
SPLIT WT=	254.4							CUM WT %	N/A	11.0	18.6	25.2	31.0	38.3	N/A	100.0

K.97

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 4

**** REPORT ON WELL 0299-W10-021 ****

02/02/00

DEPTH	XCAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
150	2.1	H	20.7	49.4	23.9	gmS	WT	N/A	91.3	53.0	60.4	30.9	22.8	23.2	N/A	101.0
SORT=	N/A		MEDIAN=	1.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	23.9	13.9	13.2	10.2	8.0	8.1
SPLIT WT=	381.4						CUM WT %	N/A	23.9	37.8	61.1	61.8	67.2	73.3	N/A	100.0
155	1.3	H	10.4	50.0	32.0	msQ	WT	N/A	139.3	48.2	60.4	92.7	27.1	22.2	N/A	43.9
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.9	11.4	11.9	21.9	8.4	5.2
SPLIT WT=	423.6						CUM WT %	N/A	32.9	44.2	56.1	78.0	84.4	89.6	N/A	100.0
160	0.9	H	10.6	55.0	25.0	gmS	WT	N/A	119.6	41.3	61.6	99.8	31.3	23.0	N/A	90.0
SORT=	N/A		MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	25.6	0.8	13.2	21.3	6.7	4.0
SPLIT WT=	467.1						CUM WT %	N/A	25.6	34.4	47.6	68.9	76.6	80.6	N/A	100.0
165	0.4	H	27.4	53.6	19.0	gmS	WT	N/A	78.2	66.4	62.3	46.3	37.1	29.0	N/A	112.0
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.0	13.6	12.7	11.3	9.0	7.2
SPLIT WT=	411.6						CUM WT %	N/A	19.0	32.6	45.2	60.4	65.4	72.6	N/A	100.0
180	0.2	H	20.0	50.0	26.7	gmS	WT	N/A	121.7	64.4	50.6	42.3	20.8	21.8	N/A	80.1
SORT=	N/A		MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.7	16.2	13.3	10.0	7.0	6.1
SPLIT WT=	424.6						CUM WT %	N/A	23.7	43.9	67.2	87.1	74.1	70.2	N/A	100.0
185	0.1	H	22.1	67.0	20.1	gmS	WT	N/A	90.0	64.7	60.8	60.2	47.1	28.0	N/A	99.6
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.2	14.9	13.5	13.3	10.4	8.2
SPLIT WT=	451.2						CUM WT %	N/A	20.2	34.5	48.0	61.3	71.0	78.0	N/A	100.0
190	0.2	H	25.7	59.0	15.3	gmS	WT	N/A	61.3	55.0	47.0	53.5	40.6	30.7	N/A	103.1
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	15.3	13.9	12.0	13.2	7.7	N/A
SPLIT WT=	400.9						CUM WT %	N/A	15.3	29.2	41.2	54.5	68.8	74.3	N/A	100.0
195	0.2	H	33.1	57.2	9.0	(g)ms	WT	N/A	29.7	30.3	31.1	46.0	41.1	27.8	N/A	102.4
SORT=	N/A		MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	9.6	9.8	10.1	15.1	13.3	9.0
SPLIT WT=	300.0						CUM WT %	N/A	9.6	19.4	29.5	44.6	57.9	60.9	N/A	100.0
200	0.2	H	32.7	67.6	9.8	(g)ms	WT	N/A	20.9	24.0	24.2	40.7	36.0	23.5	N/A	90.0
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.8	9.0	8.8	17.7	13.4	8.0
SPLIT WT=	274.0						CUM WT %	N/A	9.8	19.8	27.8	46.3	60.7	67.3	N/A	100.0
205	0.2	H	32.2	67.7	10.1	gmS	WT	N/A	20.2	30.9	28.8	42.7	36.2	22.9	N/A	89.7
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	10.1	11.1	10.3	15.3	8.2	N/A
SPLIT WT=	270.4						CUM WT %	N/A	10.1	21.2	31.6	48.0	59.6	67.8	N/A	100.0
210	0.1	H	28.1	60.2	15.7	gmS	WT	N/A	47.7	30.4	31.2	42.5	34.9	22.6	N/A	85.2
SORT=	N/A		MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	15.1	12.7	10.5	14.0	7.6	N/A
SPLIT WT=	303.1						CUM WT %	N/A	15.1	28.4	36.9	62.0	84.4	71.9	N/A	100.0

K.98

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 5

**** REPORT ON WELL 0290-W18-021 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<= -2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
216	0.1	H	24.9	61.0	14.1	gmS	WT	N/A	43.0	45.1	34.5	38.1	44.1	23.9	N/A	75.7
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.1	14.0	11.3	12.5	14.5	7.9	N/A
SPLIT WT=	304.3							CUM WT %	N/A	14.1	29.0	40.3	52.8	67.3	75.1	100.0
220	0.2	H	31.3	60.3	8.4	(g) mS	WT	N/A	21.1	28.7	20.0	30.8	41.4	23.7	N/A	78.5
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	8.4	11.4	10.6	12.3	10.5	N/A	31.3
SPLIT WT=	260.7							CUM WT %	N/A	8.4	19.9	30.5	42.7	59.3	60.7	100.0
226	0.2	H	25.1	65.5	9.4	(g) mS	WT	N/A	21.4	37.0	29.0	32.6	30.5	19.0	N/A	57.3
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.4	16.2	13.0	14.3	13.4	8.7	N/A
SPLIT WT=	227.9							CUM WT %	N/A	9.4	25.6	38.6	52.8	68.2	74.0	100.0

K.99

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W10-022 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
5	1.1	N/	13.9	82.1	4.0	(m)S	WT	N/A	9.5	4.0	12.1	20.8	60.3	82.8	N/A	32.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	4.0	1.9	5.1	11.3	20.8	34.9	N/A	13.9
SPLIT	WT=	237.0					CUM WT %	N/A	4.0	0.0	11.1	22.4	61.2	86.1	N/A	100.0	
10	1.1	H	12.3	86.0	1.7	(m)S	WT	N/A	6.0	36.9	100.7	65.4	71.5	59.6	N/A	49.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.7	9.7	27.2	16.4	17.9	14.9	N/A	12.3
SPLIT	WT=	400.1					CUM WT %	N/A	1.7	11.4	38.6	64.9	72.8	87.7	N/A	100.0	
15	0.6	H	12.5	73.6	13.0	(m)gS	WT	N/A	60.0	90.0	115.9	55.7	35.7	22.5	N/A	62.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	13.9	19.0	27.6	13.2	8.5	5.4	N/A	12.5
SPLIT	WT=	420.9					CUM WT %	N/A	13.9	32.9	60.5	73.7	82.2	87.6	N/A	100.0	
20	0.5	H	9.0	60.1	22.9	(m)gS	WT	N/A	96.0	112.1	100.2	44.9	10.0	10.9	N/A	37.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	22.9	25.5	23.0	10.7	4.4	2.0	N/A	9.0
SPLIT	WT=	421.2					CUM WT %	N/A	22.9	49.5	73.3	84.0	86.4	91.0	N/A	100.0	
25	0.9	H	17.3	76.0	6.1	(gm)S	WT	N/A	26.6	95.0	100.0	50.3	40.7	38.4	N/A	75.1	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	5.1	19.7	24.4	13.0	10.7	8.0	N/A	17.3
SPLIT	WT=	435.0					CUM WT %	N/A	6.1	25.9	50.2	63.2	73.9	82.7	N/A	100.0	
30	1.2	H	17.4	81.2	1.4	(m)S	WT	N/A	5.5	26.2	50.2	92.3	60.6	64.0	N/A	69.1	
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.4	0.0	14.7	23.3	20.3	10.3	N/A	17.4
SPLIT	WT=	395.6					CUM WT %	N/A	1.4	0.0	22.7	46.0	66.3	82.6	N/A	100.0	
35	1.1	H	13.4	84.0	1.0	(m)S	WT	N/A	7.0	27.0	96.0	104.7	61.4	41.0	N/A	62.7	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	1.0	7.1	24.7	20.7	15.7	10.7	N/A	13.4
SPLIT	WT=	302.2					CUM WT %	N/A	1.0	0.9	33.6	60.3	75.9	86.0	N/A	100.0	
40	1.3	H	16.7	79.3	4.0	(m)S	WT	N/A	16.0	25.1	82.3	90.9	67.0	40.0	N/A	67.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.0	0.3	20.5	24.1	10.9	11.0	N/A	16.7
SPLIT	WT=	401.7					CUM WT %	N/A	4.0	10.2	30.7	54.8	71.7	83.3	N/A	100.0	
50	1.1	H	0.0	60.6	33.2	sg	WT	N/A	132.7	41.5	42.5	0.1	132.3	20.6	N/A	23.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.2	10.4	10.0	0.0	33.1	6.7	N/A	0.0
SPLIT	WT=	399.7					CUM WT %	N/A	33.2	43.8	54.2	54.3	87.4	94.0	N/A	100.0	
55	1.1	H	12.2	47.2	40.7	msG	WT	N/A	102.3	62.7	48.0	33.7	26.2	19.5	N/A	40.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.7	15.7	11.5	0.5	0.0	4.9	N/A	12.2
SPLIT	WT=	398.9					CUM WT %	N/A	40.7	60.4	67.9	76.4	83.0	87.9	N/A	100.0	
60	1.3	H	10.1	16.3	73.0	msG	WT	N/A	364.7	24.0	16.4	14.0	13.0	11.5	N/A	49.0	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	73.0	0.0	3.3	3.0	2.3	0.0	N/A	10.1
SPLIT	WT=	406.4					CUM WT %	N/A	73.0	78.6	81.0	84.9	87.6	89.9	N/A	100.0	

K.101

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	OM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
86	1.1	H	18.4	60.3	31.3	msG	WT	N/A	154.5	54.4	55.0	57.4	45.4	35.9	N/A	90.8	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.3	11.0	11.3	11.0	9.2	7.3	N/A	18.4
SPLIT	WT=	494.1					CUM WT %	N/A	31.3	42.3	53.6	65.2	74.4	81.6	N/A	100.0	
70	1.4	H	23.3	83.6	13.2	gmS	WT	N/A	53.8	38.0	65.8	60.5	44.7	51.0	N/A	95.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.2	8.8	10.1	14.8	11.0	12.7	N/A	23.3
SPLIT	WT=	407.9					CUM WT %	N/A	13.2	22.0	38.2	53.0	64.0	76.7	N/A	100.0	
76	1.3	H	21.2	75.9	2.9	mS	WT	N/A	11.3	17.9	57.0	69.2	69.2	80.0	N/A	82.1	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	2.9	4.0	14.8	17.8	17.8	20.8	N/A	21.2
SPLIT	WT=	388.1					CUM WT %	N/A	2.9	7.5	22.4	40.2	58.0	78.8	N/A	100.0	
80	1.3	H	15.9	81.6	2.5	(m)S	WT	N/A	9.2	33.3	58.0	39.8	83.0	84.2	N/A	50.1	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	2.5	9.1	15.9	10.8	22.7	23.0	N/A	15.9
SPLIT	WT=	366.3					CUM WT %	N/A	2.5	11.0	27.5	38.3	61.1	84.1	N/A	100.0	
85	1.4	H	14.7	83.9	1.4	(m)S	WT	N/A	5.3	15.8	66.5	55.8	70.2	98.0	N/A	54.7	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.4	4.2	17.9	15.0	20.5	26.3	N/A	14.7
SPLIT	WT=	372.1					CUM WT %	N/A	1.4	5.0	23.5	38.6	59.0	85.3	N/A	100.0	
90	1.4	H	8.4	92.2	1.4	S	WT	N/A	5.4	48.1	159.9	64.2	43.7	43.3	N/A	25.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	1.4	12.4	41.0	16.5	11.2	11.1	N/A	0.4
SPLIT	WT=	389.7					CUM WT %	N/A	1.4	13.7	54.8	71.3	82.5	93.6	N/A	100.0	
95	1.6	H	35.6	84.5	0.0	mS	WT	N/A	0.0	2.0	10.4	24.1	55.4	80.1	N/A	100.3	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.7	3.7	8.6	23.2	20.4	N/A	35.5
SPLIT	WT=	282.2					CUM WT %	N/A	0.0	0.7	4.4	12.9	30.1	54.5	N/A	100.0	
100	1.0	H	37.1	82.9	0.0	mS	WT	N/A	0.1	0.5	6.3	28.2	45.3	45.6	N/A	74.2	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.1	0.3	3.2	14.1	22.0	22.8	N/A	37.1
SPLIT	WT=	200.1					CUM WT %	N/A	0.1	0.3	3.5	17.5	40.2	63.0	N/A	100.0	
105	1.0	H	47.3	52.5	0.2	mS	WT	N/A	0.6	0.2	2.7	15.3	50.8	78.1	N/A	132.7	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.2	0.1	1.0	5.6	18.1	27.9	N/A	47.3
SPLIT	WT=	280.3					CUM WT %	N/A	0.2	0.3	1.2	6.7	24.8	52.7	N/A	100.0	
110	1.0	H	44.7	55.2	0.1	mS	WT	N/A	0.3	0.6	4.3	17.7	45.0	52.5	N/A	97.3	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.1	0.3	2.0	8.1	20.7	24.1	N/A	44.7
SPLIT	WT=	217.7					CUM WT %	N/A	0.1	0.4	2.4	10.5	31.2	55.3	N/A	100.0	
115	1.9	H	39.4	60.4	0.2	mS	WT	N/A	0.5	1.5	8.8	33.5	73.7	67.0	N/A	121.0	
SORT=	N/A	MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.2	0.5	2.9	10.9	24.0	22.1	N/A	39.4
SPLIT	WT=	306.7					CUM WT %	N/A	0.2	0.7	3.5	14.4	50.5	60.6	N/A	100.0	

K.102

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	DW	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	CDARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
120	1.9	H	50.2	41.0	0.0	sM	WT	N/A	0.0	0.4	3.8	16.3	19.7	38.0	N/A	100.1
SORT=	N/A		MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.2	1.9	0.2	10.6	50.2
SPLIT	WT=	105.7							CUM WT %	N/A	0.0	0.2	2.2	10.4	21.0	100.0
125	2.9	H	60.6	39.1	0.4	sM	WT	N/A	0.7	1.0	1.1	7.5	23.0	30.2	N/A	107.9
SORT=	N/A		MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.4	0.6	0.6	4.2	13.4	60.6
SPLIT	WT=	178.0							CUM WT %	N/A	0.4	1.0	1.6	5.8	19.1	100.0
130	2.5	H	60.0	43.0	0.4	sM	WT	N/A	0.8	1.1	1.7	7.2	29.0	50.0	N/A	114.4
SORT=	N/A		MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.4	0.5	0.6	3.6	14.2	60.0
SPLIT	WT=	204.4							CUM WT %	N/A	0.4	0.9	1.5	5.0	19.2	100.0
135	2.7	H	63.2	38.6	0.3	sM	WT	N/A	1.1	1.0	2.7	10.0	30.0	71.0	N/A	203.0
SORT=	N/A		MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.3	0.0	0.0	3.3	0.6	63.2
SPLIT	WT=	322.0							CUM WT %	N/A	0.3	0.0	1.7	5.0	14.6	100.0
140	3.1	H	55.5	43.9	0.0	sM	WT	N/A	1.3	2.1	2.2	10.4	33.2	56.0	N/A	131.0
SORT=	N/A		MEDIAN=	5.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.0	0.0	0.9	4.4	14.1	55.5
SPLIT	WT=	230.1							CUM WT %	N/A	0.0	1.4	2.4	0.8	20.0	100.0
145	12.2	H	30.0	47.0	14.2	gmS	WT	N/A	30.2	10.0	23.1	23.0	29.6	32.1	N/A	104.3
SORT=	N/A		MEDIAN=	4.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.2	7.0	0.6	0.6	11.0	30.0
SPLIT	WT=	269.0							CUM WT %	N/A	14.2	21.2	29.0	30.4	49.3	100.0
150	6.1	H	10.2	31.0	50.3	msG	WT	N/A	100.3	30.0	31.1	10.6	10.0	10.0	N/A	00.4
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	50.3	0.2	0.3	5.2	5.0	10.2
SPLIT	WT=	370.6							CUM WT %	N/A	50.3	50.5	00.7	71.9	70.0	100.0
155	1.3	H	9.2	33.2	57.0	msG	WT	N/A	277.6	00.0	35.7	25.4	17.7	12.3	N/A	44.3
SORT=	N/A		MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	57.0	14.3	7.4	5.3	3.7	9.2
SPLIT	WT=	481.4							CUM WT %	N/A	57.0	71.9	70.3	04.0	00.3	100.0
160	0.0	H	0.4	45.0	45.7	msG	WT	N/A	213.0	04.1	00.2	41.0	10.4	7.7	N/A	39.5
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	45.7	10.0	13.6	0.0	3.9	0.5
SPLIT	WT=	467.0							CUM WT %	N/A	45.7	03.7	77.2	00.0	00.0	100.0
165	0.0	H	0.0	57.3	33.0	msG	WT	N/A	127.2	02.0	02.0	40.0	10.0	10.3	N/A	33.3
SORT=	N/A		MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	33.0	22.0	10.7	10.9	5.0	0.0
SPLIT	WT=	370.2							CUM WT %	N/A	33.0	55.0	72.0	00.4	00.2	100.0
170	0.4	H	30.0	54.7	9.3	(g)ms	WT	N/A	20.7	20.0	27.0	25.2	24.5	10.0	N/A	70.0
SORT=	N/A		MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.3	11.7	12.0	11.4	11.0	30.0
SPLIT	WT=	221.7							CUM WT %	N/A	9.3	21.0	33.0	45.0	04.0	100.0

K.103

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
176	0.1	H	23.7	46.7	30.5	msG	WT	N/A	92.3	43.4	39.4	23.8	16.7	15.1	N/A	71.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	14.4	13.0	7.8	5.6	N/A	23.7
SPLIT	WT=	302.2					CUM WT %	N/A	30.6	44.0	57.9	66.8	71.3	76.3	N/A	100.0
180	0.2	H	18.0	44.5	37.5	msG	WT	N/A	170.3	47.3	41.1	62.6	39.3	21.9	N/A	82.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.5	10.4	9.0	11.8	8.7	N/A	18.1
SPLIT	WT=	454.4					CUM WT %	N/A	37.5	47.9	58.9	68.5	77.1	82.0	N/A	100.0
186	0.1	H	22.8	47.2	30.0	msG	WT	N/A	115.5	38.2	32.8	43.5	42.5	24.4	N/A	87.7
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	9.9	8.5	11.3	11.1	N/A	22.8
SPLIT	WT=	384.8					CUM WT %	N/A	30.0	40.0	48.5	59.8	70.9	77.2	N/A	100.0
190	0.1	H	7.1	80.8	12.1	gS	WT	N/A	39.8	60.8	81.3	74.8	45.2	14.1	N/A	23.3
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.1	15.4	24.7	13.7	4.3	N/A	7.1
SPLIT	WT=	329.3					CUM WT %	N/A	12.1	27.6	52.2	74.9	88.7	92.9	N/A	100.0
196	0.2	H	28.6	55.6	16.0	gmS	WT	N/A	60.3	48.0	40.0	48.3	45.6	26.1	N/A	107.5
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	16.0	13.0	10.6	12.8	6.9	N/A	28.5
SPLIT	WT=	376.8					CUM WT %	N/A	16.0	29.0	39.8	52.4	64.5	71.5	N/A	100.0
200	0.1	H	11.7	40.4	48.0	msG	WT	N/A	133.6	10.6	8.4	49.5	34.6	9.4	N/A	32.5
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	48.0	3.8	3.0	17.8	12.4	N/A	11.7
SPLIT	WT=	278.3					CUM WT %	N/A	48.0	51.7	54.7	72.6	85.0	88.3	N/A	100.0
206	0.1	H	24.6	53.7	21.8	gmS	WT	N/A	72.4	38.8	27.9	43.1	45.8	22.7	N/A	81.3
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.8	11.8	8.4	13.0	13.8	N/A	24.5
SPLIT	WT=	331.7					CUM WT %	N/A	21.8	33.6	41.9	54.9	68.7	75.5	N/A	100.0
210	0.1	H	18.4	46.1	35.4	msG	WT	N/A	119.6	42.2	29.7	28.9	38.3	18.7	N/A	82.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	35.4	12.6	8.8	8.0	11.3	N/A	18.4
SPLIT	WT=	337.6					CUM WT %	N/A	35.4	47.9	56.7	64.7	76.0	81.8	N/A	100.0
216	0.1	H	25.4	51.2	23.4	gmS	WT	N/A	79.1	43.9	34.3	32.4	41.5	21.2	N/A	86.1
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	23.4	13.0	10.1	9.8	12.3	N/A	25.4
SPLIT	WT=	338.0					CUM WT %	N/A	23.4	38.3	46.5	56.0	68.3	74.8	N/A	100.0
220	0.1	H	29.1	54.7	16.2	gmS	WT	N/A	48.2	37.0	30.9	32.1	40.1	22.3	N/A	86.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	16.2	12.6	10.4	10.8	13.5	N/A	29.1
SPLIT	WT=	290.9					CUM WT %	N/A	16.2	28.7	39.1	49.9	63.4	70.9	N/A	100.0
226	0.1	H	3.9	72.9	23.3	gS	WT	N/A	89.9	94.3	96.8	58.9	27.6	6.2	N/A	14.9
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	23.3	24.4	25.0	14.7	7.1	N/A	3.9
SPLIT	WT=	386.2					CUM WT %	N/A	23.3	47.7	72.7	87.4	94.5	96.1	N/A	100.0

K.104

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
RUCKSAN REPORT

PAGE 5

**** REPORT ON WELL 0299-W19-022 ****

02/02/88

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
230	0.1	H	8.6	27.4	54.1	msG	WT	N/A	268.2	26.6	20.3	25.3	28.8	13.4	N/A	35.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	84.1	8.4	4.9	6.0	6.9	3.2	N/A	8.6
SPLIT	WT=	418.8					CUM WT %	N/A	84.1	70.5	75.3	81.4	88.2	91.4	N/A	100.0	
235	0.1	H	11.5	48.8	41.7	msG	WT	N/A	106.6	69.5	44.6	41.1	32.3	12.3	N/A	46.6	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	41.7	14.7	11.0	10.1	8.0	3.0	N/A	11.5
SPLIT	WT=	405.3					CUM WT %	N/A	41.7	60.3	67.4	77.5	85.5	88.5	N/A	100.0	
240	0.2	H	7.9	69.4	23.7	(m)gS	WT	N/A	139.1	64.4	101.4	122.0	75.2	36.7	N/A	48.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.7	11.0	17.3	20.0	12.0	6.0	N/A	7.9
SPLIT	WT=	584.9					CUM WT %	N/A	23.7	34.7	51.9	72.7	85.6	92.1	N/A	100.0	
245	0.3	H	9.0	73.2	17.9	(m)gS	WT	N/A	84.0	63.2	70.9	91.5	55.0	31.7	N/A	42.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.9	19.8	15.1	19.5	12.1	6.7	N/A	9.0
SPLIT	WT=	484.5					CUM WT %	N/A	17.9	37.7	52.7	72.2	84.3	91.0	N/A	100.0	
250	0.2	H	7.4	77.4	15.2	gS	WT	N/A	98.6	110.9	93.0	145.2	101.1	61.3	N/A	48.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.2	17.1	14.4	22.5	15.6	7.9	N/A	7.4
SPLIT	WT=	655.7					CUM WT %	N/A	15.2	32.3	46.7	68.2	84.7	92.6	N/A	100.0	
254	0.3	H	8.9	70.6	16.5	gS	WT	N/A	91.4	93.2	81.0	130.7	78.5	40.6	N/A	38.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.5	10.9	14.6	23.7	13.8	7.4	N/A	7.0
SPLIT	WT=	652.5					CUM WT %	N/A	10.5	33.4	48.2	71.9	85.7	93.1	N/A	100.0	
261	0.3	H	7.5	83.9	8.6	(g)S	WT	N/A	49.2	94.2	82.4	154.2	100.8	46.2	N/A	42.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.6	16.5	14.5	27.1	17.7	8.1	N/A	7.5
SPLIT	WT=	684.2					CUM WT %	N/A	8.6	25.2	39.6	66.7	84.4	92.5	N/A	100.0	
266	0.2	H	8.0	86.4	7.8	(g)S	WT	N/A	46.2	105.9	100.5	189.5	101.5	44.1	N/A	36.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	7.8	17.3	17.5	27.8	10.5	7.2	N/A	6.0
SPLIT	WT=	811.9					CUM WT %	N/A	7.8	24.9	42.4	70.1	85.8	94.0	N/A	100.0	
270	N/A	H	23.7	87.1	9.2	(g)ms	WT	N/A	26.0	43.4	35.4	54.5	47.1	22.0	N/A	71.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.2	14.3	11.7	18.0	15.5	7.6	N/A	23.7
SPLIT	WT=	303.2					CUM WT %	N/A	9.2	23.5	35.2	53.2	69.7	78.3	N/A	100.0	
275	0.1	H	16.1	80.8	23.9	gms	WT	N/A	87.8	51.9	42.0	57.7	47.0	22.2	N/A	59.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	23.9	14.1	11.4	15.7	12.0	6.0	N/A	16.1
SPLIT	WT=	367.7					CUM WT %	N/A	23.9	30.0	40.4	65.1	77.9	83.9	N/A	100.0	
280	0.1	H	22.0	57.7	20.3	gms	WT	N/A	53.9	29.5	24.5	44.5	38.5	18.3	N/A	58.4	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.3	11.1	9.2	16.8	13.7	8.9	N/A	22.0
SPLIT	WT=	265.7					CUM WT %	N/A	20.3	31.4	40.8	57.4	71.1	78.0	N/A	100.0	

K.105

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
285	0.1	H	19.9	59.7	20.4	gmS	WT	N/A	67.6	41.2	29.0	61.0	46.0	21.2	N/A	88.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	20.4	12.4	8.7	18.6	13.6	8.4	N/A	19.9
SPLIT	WT=	331.9					CUM WT %	N/A	20.4	32.8	41.5	60.2	73.7	80.1	N/A	100.0	
290	0.4	H	23.8	66.8	9.8	(g)mS	WT	N/A	29.3	41.3	36.8	68.8	46.9	21.5	N/A	72.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	9.8	13.6	12.0	19.2	15.0	7.0	N/A	23.6
SPLIT	WT=	305.9					CUM WT %	N/A	9.6	23.1	35.1	54.3	69.3	76.4	N/A	100.0	
295	0.2	H	17.0	67.4	15.7	gmS	WT	N/A	40.2	29.4	21.3	77.7	60.7	18.3	N/A	52.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	15.7	9.6	6.9	25.2	19.7	6.0	N/A	17.0
SPLIT	WT=	307.8					CUM WT %	N/A	15.7	25.2	32.1	57.4	77.1	83.0	N/A	100.0	
300	0.2	H	19.8	58.7	21.5	gmS	WT	N/A	79.7	46.6	32.8	84.8	53.8	20.7	N/A	73.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.5	12.5	8.8	17.4	14.4	6.6	N/A	19.8
SPLIT	WT=	371.8					CUM WT %	N/A	21.5	34.0	42.8	60.2	74.6	80.2	N/A	100.0	
305	0.1	H	20.8	60.1	19.3	gmS	WT	N/A	68.8	40.4	41.7	66.7	42.4	18.4	N/A	71.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.3	14.0	12.1	16.4	12.3	6.3	N/A	20.0
SPLIT	WT=	345.8					CUM WT %	N/A	19.3	33.3	45.4	61.8	74.1	79.4	N/A	100.0	
310	0.2	H	22.7	65.5	11.8	gmS	WT	N/A	38.8	37.8	31.8	83.8	55.7	24.9	N/A	74.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	11.8	11.6	9.7	19.6	17.0	7.6	N/A	22.7
SPLIT	WT=	328.5					CUM WT %	N/A	11.8	23.4	33.1	52.8	69.7	77.3	N/A	100.0	
315	0.4	H	25.0	57.9	16.3	gmS	WT	N/A	54.2	55.3	35.1	42.4	38.0	21.2	N/A	85.9	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	16.3	16.8	10.5	12.7	11.7	6.4	N/A	25.8
SPLIT	WT=	332.8					CUM WT %	N/A	16.3	32.9	43.4	58.2	67.8	74.2	N/A	100.0	
320	0.7	H	24.5	61.3	14.2	gmS	WT	N/A	48.1	40.8	37.2	54.0	48.0	27.9	N/A	83.1	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.2	12.0	11.0	15.9	14.2	8.2	N/A	24.5
SPLIT	WT=	338.9					CUM WT %	N/A	14.2	26.2	37.2	53.1	67.2	75.5	N/A	100.0	
325	0.3	H	22.2	65.9	12.0	gmS	WT	N/A	40.8	40.1	37.6	62.1	51.0	24.8	N/A	75.6	
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	12.0	14.1	11.0	18.2	15.2	7.3	N/A	22.2
SPLIT	WT=	340.8					CUM WT %	N/A	12.0	26.1	37.1	55.4	70.8	77.9	N/A	100.0	
330	0.3	H	25.7	67.6	6.7	(g)mS	WT	N/A	18.3	22.4	20.3	61.3	43.5	10.6	N/A	62.3	
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.7	9.2	8.4	25.3	17.9	6.8	N/A	25.7
SPLIT	WT=	242.7					CUM WT %	N/A	6.7	10.0	24.3	49.6	67.5	74.3	N/A	100.0	
335	0.6	H	24.0	65.4	10.6	gmS	WT	N/A	33.1	25.5	21.7	79.0	58.9	18.8	N/A	75.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.6	8.2	7.0	25.3	18.9	6.0	N/A	24.0
SPLIT	WT=	312.0					CUM WT %	N/A	10.6	18.8	25.7	51.1	69.9	76.0	N/A	100.0	

K.106

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 7

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	DW	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (<=-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
340	0.6	H	22.4	63.7	13.9	gmS	WT	N/A	48.5	32.4	25.0	95.2	59.1	20.7	N/A	78.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	13.9	9.3	7.2	24.4	16.9	6.9	N/A
SPLIT	WT=	349.0					CUM	WT %	N/A	13.9	23.2	30.3	54.7	71.7	77.6	N/A
345	0.6	H	22.6	59.9	17.5	gmS	WT	N/A	54.9	33.9	25.9	65.8	44.0	16.8	N/A	71.1
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	17.5	10.8	8.2	20.9	14.0	6.8	N/A
SPLIT	WT=	314.4					CUM	WT %	N/A	17.5	28.3	36.5	57.4	71.4	77.4	N/A
350	0.2	H	21.4	58.2	20.4	gmS	WT	N/A	66.4	38.0	29.1	65.9	38.9	17.9	N/A	69.9
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.4	11.7	8.9	20.2	11.9	6.5	N/A
SPLIT	WT=	326.0					CUM	WT %	N/A	20.4	32.0	40.9	61.1	73.1	78.6	N/A
355	0.2	H	18.1	80.4	21.5	gmS	WT	N/A	77.2	62.9	37.9	74.6	36.1	15.5	N/A	64.9
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.5	14.7	10.6	20.9	10.1	4.3	N/A
SPLIT	WT=	359.0					CUM	WT %	N/A	21.5	36.2	48.9	67.8	77.0	81.9	N/A
360	0.2	H	22.1	69.8	8.3	(g)mS	WT	N/A	24.3	30.0	31.2	60.2	45.2	17.6	N/A	64.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	8.3	10.2	10.0	27.3	15.4	6.0	N/A
SPLIT	WT=	293.4					CUM	WT %	N/A	9.3	10.6	29.1	58.5	71.9	77.9	N/A
365	0.2	H	24.5	69.5	5.1	(g)mS	WT	N/A	18.9	37.6	34.4	64.9	36.4	17.9	N/A	68.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	0.1	13.6	12.4	23.3	13.0	6.4	N/A
SPLIT	WT=	278.2					CUM	WT %	N/A	0.1	19.6	32.0	55.3	69.1	75.6	N/A
370	0.3	H	24.2	70.8	5.2	(g)mS	WT	N/A	12.9	21.1	26.6	65.3	43.4	19.1	N/A	60.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.2	8.5	10.7	28.3	17.6	7.7	N/A
SPLIT	WT=	248.6					CUM	WT %	N/A	5.2	13.7	24.4	50.7	68.1	75.0	N/A
375	0.9	H	28.7	63.3	8.0	(g)mS	WT	N/A	18.8	23.0	23.7	64.7	38.1	17.4	N/A	70.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	8.0	9.4	9.7	22.3	14.7	7.1	N/A
SPLIT	WT=	245.0					CUM	WT %	N/A	8.0	17.4	27.1	49.4	64.2	71.3	N/A
380	0.6	H	28.0	65.4	6.6	(g)mS	WT	N/A	19.0	28.1	24.9	49.5	28.7	13.0	N/A	57.3
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	6.6	12.7	11.3	22.5	13.0	6.9	N/A
SPLIT	WT=	220.5					CUM	WT %	N/A	8.6	21.4	32.7	55.1	68.1	74.0	N/A
385	0.6	H	25.6	67.9	6.5	(g)mS	WT	N/A	15.0	22.7	24.9	62.0	32.9	13.0	N/A	59.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.5	9.8	10.6	27.1	14.3	5.9	N/A
SPLIT	WT=	230.0					CUM	WT %	N/A	6.5	10.3	27.1	54.3	68.5	74.4	N/A
390	0.5	H	7.4	80.8	4.8	S	WT	N/A	19.2	72.0	101.0	145.3	71.3	32.6	N/A	35.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.0	15.2	21.2	30.4	14.9	8.8	N/A
SPLIT	WT=	472.2					CUM	WT %	N/A	4.0	19.2	40.4	70.8	95.8	92.5	N/A

K.107

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-022 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
398	0.4	H	9.1	96.7	5.1	(g)S	WT	N/A	21.0	83.9	79.4	100.4	87.8	33.3	N/A	37.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	5.1	15.8	19.4	26.0	10.0	N/A	9.1
SPLIT	WT= 408.4							CUM WT %	N/A	5.1	20.9	40.2	68.2	82.7	98.9	100.0
401	0.2	H	5.7	89.8	4.7	S	WT	N/A	18.6	61.5	95.8	91.5	45.7	23.3	N/A	20.2
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.7	17.4	27.0	26.8	12.9	N/A	5.7
SPLIT	WT= 360.0							CUM WT %	N/A	4.7	22.0	49.0	74.8	87.7	94.3	100.0
406	0.4	H	11.7	84.4	3.9	(m)S	WT	N/A	18.6	54.4	62.2	89.7	88.0	54.1	N/A	49.0
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.9	12.8	14.8	23.5	20.7	N/A	11.7
SPLIT	WT= 422.9							CUM WT %	N/A	3.9	16.7	31.4	54.8	75.6	88.3	N/A
411	0.2	H	6.3	89.6	4.1	S	WT	N/A	14.0	41.1	87.4	110.4	53.4	25.2	N/A	22.3
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	4.1	11.8	24.7	31.2	15.1	N/A	6.3
SPLIT	WT= 351.8							CUM WT %	N/A	4.1	15.7	40.4	71.5	88.6	93.7	N/A
418	0.4	H	4.7	91.4	3.9	S	WT	N/A	17.4	58.2	115.2	146.9	60.2	28.8	N/A	21.1
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.9	13.0	25.8	32.7	13.6	N/A	4.7
SPLIT	WT= 448.7							CUM WT %	N/A	3.9	16.9	42.7	75.4	88.6	95.3	N/A
420	0.0	H	22.5	85.0	11.0	gmS	WT	N/A	24.0	22.3	21.9	52.7	27.5	13.0	N/A	40.9
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	11.0	10.7	10.5	25.2	13.2	N/A	22.5
SPLIT	WT= 208.8							CUM WT %	N/A	11.0	22.5	32.9	58.2	71.3	77.5	N/A
426	0.0	H	22.7	87.4	10.0	gmS	WT	N/A	20.8	21.5	26.7	53.8	28.2	12.8	N/A	47.4
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	10.0	10.3	12.8	25.7	12.5	N/A	22.7
SPLIT	WT= 208.9							CUM WT %	N/A	10.0	20.2	33.0	58.7	71.2	77.3	N/A
430	0.6	H	24.2	85.9	9.9	(g)mS	WT	N/A	17.3	14.8	21.6	45.3	22.0	11.3	N/A	42.2
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	9.9	8.4	12.4	20.0	12.6	N/A	24.2
SPLIT	WT= 174.2							CUM WT %	N/A	9.9	18.3	30.7	50.7	69.3	75.8	N/A
435	0.5	H	22.5	81.5	10.0	gmS	WT	N/A	38.3	32.4	30.8	48.5	24.0	13.1	N/A	64.0
SORT=	N/A	MEDIAN=	2.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	10.0	13.5	12.8	19.4	10.3	N/A	22.5
SPLIT	WT= 230.9							CUM WT %	N/A	10.0	29.5	42.3	61.7	72.0	77.5	N/A
440	0.4	H	28.2	68.1	5.7	(g)mS	WT	N/A	11.0	25.4	29.0	50.8	24.6	12.7	N/A	55.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	5.7	12.1	14.2	24.1	11.7	N/A	20.2
SPLIT	WT= 210.0							CUM WT %	N/A	5.7	17.8	32.0	58.1	67.8	73.8	N/A
445	0.2	H	21.0	58.4	21.0	gmS	WT	N/A	58.3	28.4	33.4	49.3	26.3	13.7	N/A	55.5
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	21.0	10.8	12.5	12.4	9.0	N/A	21.0
SPLIT	WT= 207.9							CUM WT %	N/A	21.0	32.4	44.8	63.2	73.1	78.2	N/A

K108

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

**** REPORT ON WELL 0299-W1B-023 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
6	1.8	C	10.1	77.6	12.4	(m) gS	WT	N/A	75.1	190.3	82.1	41.1	93.9	54.7	N/A	61.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	12.4	32.8	13.6	8.0	15.5	N/A	10.1	
SPLIT	WT= 867.8						CUM WT %	N/A	12.4	45.2	68.7	86.4	88.9	88.9	N/A	100.0	
10	1.2	C	4.8	86.8	9.4	(g) S	WT	N/A	65.5	265.9	218.8	40.2	25.8	42.0	N/A	33.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	9.4	38.1	31.5	6.6	3.7	N/A	4.8	
SPLIT	WT= 696.2						CUM WT %	N/A	9.4	47.5	78.9	85.5	89.2	95.2	N/A	100.0	
15	0.6	C	3.1	88.1	8.8	(g) S	WT	N/A	83.4	279.7	268.3	48.4	11.2	32.5	N/A	22.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	8.8	39.0	38.3	8.8	1.8	N/A	3.1	
SPLIT	WT= 717.6						CUM WT %	N/A	8.8	47.8	84.1	90.9	92.4	98.9	N/A	100.0	
20	1.3	C	9.8	90.1	0.1	S	WT	N/A	0.9	7.5	65.7	241.2	181.2	69.1	N/A	61.3	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.1	1.2	10.5	38.5	28.9	N/A	9.8	
SPLIT	WT= 827.0						CUM WT %	N/A	0.1	1.3	11.8	50.3	79.2	90.2	N/A	100.0	
25	1.8	C	27.2	72.7	0.1	mS	WT	N/A	0.7	2.0	22.4	117.4	238.5	75.9	N/A	167.8	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.1	0.6	3.8	19.0	37.3	N/A	27.2	
SPLIT	WT= 617.4						CUM WT %	N/A	0.1	0.6	4.2	23.2	60.5	72.8	N/A	100.0	
30	1.3	C	25.8	74.4	0.0	mS	WT	N/A	0.3	4.1	41.0	175.0	211.0	82.9	N/A	177.1	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.0	0.8	5.9	25.3	30.6	N/A	25.8	
SPLIT	WT= 682.3						CUM WT %	N/A	0.0	0.6	6.6	31.9	62.4	74.4	N/A	100.0	
35	0.7	C	2.6	94.1	3.3	S	WT	N/A	21.7	154.3	288.0	111.4	47.8	15.8	N/A	17.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.3	23.5	43.9	17.0	7.3	N/A	2.6	
SPLIT	WT= 855.9						CUM WT %	N/A	3.3	28.8	70.7	87.7	95.0	97.4	N/A	100.0	
40	1.6	C	11.2	86.4	0.4	(m) S	WT	N/A	2.5	23.9	63.4	20.9	192.1	202.1	N/A	76.5	
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.4	3.5	9.3	4.4	28.2	42.0	N/A	11.2
SPLIT	WT= 680.4						CUM WT %	N/A	0.4	3.9	13.2	17.8	45.8	88.8	N/A	100.0	
45	0.8	C	2.5	92.7	4.9	S	WT	N/A	38.3	263.7	332.7	82.7	21.5	11.6	N/A	18.4	
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	4.9	35.3	44.5	8.4	2.9	N/A	2.5	
SPLIT	WT= 747.0						CUM WT %	N/A	4.9	40.2	84.7	93.1	98.0	97.5	N/A	100.0	
50	1.5	C	10.7	89.3	0.0	(m) S	WT	N/A	0.0	0.0	35.9	119.1	180.0	235.1	N/A	88.3	
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.0	0.1	5.8	18.6	28.2	36.8	N/A	10.7
SPLIT	WT= 639.1						CUM WT %	N/A	0.0	0.1	5.8	24.4	52.5	89.3	N/A	100.0	
55	1.1	C	2.1	88.8	28.1	gS	WT	N/A	221.2	147.4	215.3	190.3	38.0	12.6	N/A	18.5	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.1	18.7	27.4	17.8	4.0	N/A	2.1	
SPLIT	WT= 788.3						CUM WT %	N/A	28.1	48.8	74.2	91.8	96.3	97.9	N/A	100.0	

K.109

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAND REPORT

**** REPORT ON WELL 0209-W18-B23 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FES (<=-2)	VFINE FES (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
60	0.6	C	1.8	85.4	12.8	qS	WT	N/A	85.6	221.2	258.3	63.2	19.5	8.4	N/A	11.7
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	12.8	33.2	30.5	9.6	2.9	1.3	N/A
SPLIT	WT=	885.8						CUM WT %	N/A	12.8	48.1	84.8	94.1	97.0	98.2	N/A
85	1.2	H	11.3	31.9	56.8	msG	WT	N/A	264.9	44.4	38.4	27.7	22.0	18.4	N/A	52.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	56.8	9.6	8.2	5.9	4.7	3.5	N/A
SPLIT	WT=	466.6						CUM WT %	N/A	56.8	66.3	74.3	80.5	85.2	88.7	N/A
70	0.9	H	18.4	39.1	42.6	msG	WT	N/A	183.8	51.8	41.3	31.2	24.6	20.2	N/A	70.8
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	42.6	12.0	9.6	7.2	5.7	4.7	N/A
SPLIT	WT=	432.3						CUM WT %	N/A	42.6	54.5	64.0	71.2	76.9	81.6	N/A
75	0.8	H	24.0	46.3	29.7	gmS	WT	N/A	128.2	63.7	62.6	35.6	26.2	19.7	N/A	102.0
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.7	15.0	12.4	8.4	5.9	4.6	N/A
SPLIT	WT=	424.7						CUM WT %	N/A	29.7	44.7	57.1	65.4	71.4	76.0	N/A
80	1.1	H	23.1	42.3	34.6	msG	WT	N/A	120.2	48.2	35.9	25.4	20.3	16.8	N/A	80.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.7	13.9	10.4	7.3	5.9	4.6	N/A
SPLIT	WT=	348.8						CUM WT %	N/A	34.7	48.5	58.9	66.2	72.1	76.9	N/A
85	0.8	H	20.0	79.7	0.3	mS	WT	N/A	1.0	5.6	17.7	176.8	132.7	117.3	N/A	113.6
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.3	1.0	3.1	31.6	23.4	20.7	N/A
SPLIT	WT=	687.4						CUM WT %	N/A	0.3	1.3	4.4	35.9	69.3	80.0	N/A
90	0.9	H	26.0	43.3	31.7	msG	WT	N/A	144.4	65.2	48.5	33.4	28.2	24.0	N/A	114.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.7	14.3	10.0	7.3	5.8	5.3	N/A
SPLIT	WT=	455.9						CUM WT %	N/A	31.7	46.0	58.6	63.9	69.7	75.0	N/A
95	1.1	H	19.7	48.0	34.3	msG	WT	N/A	148.0	52.0	61.6	44.2	27.4	20.4	N/A	83.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.3	12.2	12.1	10.4	8.4	4.8	N/A
SPLIT	WT=	425.3						CUM WT %	N/A	34.3	48.6	60.7	69.1	75.5	80.3	N/A
100	1.5	H	18.6	53.0	28.4	gmS	WT	N/A	128.3	39.6	48.4	54.7	42.5	39.1	N/A	78.8
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.4	9.3	11.4	12.9	10.0	9.2	N/A
SPLIT	WT=	423.2						CUM WT %	N/A	28.4	37.8	49.2	62.1	72.1	81.4	N/A
105	1.6	H	19.0	80.4	19.8	gmS	WT	N/A	83.1	35.1	52.0	55.3	54.5	47.1	N/A	83.2
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	19.8	8.4	12.4	16.5	13.0	11.2	N/A
SPLIT	WT=	420.2						CUM WT %	N/A	19.8	29.1	40.6	50.0	59.0	60.2	N/A
110	1.6	H	25.9	85.4	8.6	(g)mS	WT	N/A	33.0	18.3	39.4	63.2	62.4	69.4	N/A	99.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	8.6	4.3	10.3	16.5	18.3	18.1	N/A
SPLIT	WT=	383.0						CUM WT %	N/A	8.6	12.9	23.1	39.5	55.9	74.1	N/A

K.110

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 3

**** REPORT ON WELL 0299-W16-023 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
116	1.6	H	24.0	89.9	8.0	(g)MS	WT	N/A	20.2	10.1	40.7	63.6	63.7	60.6	N/A	80.6
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	0.0	4.8	12.1	19.0	18.0	N/A	24.0
SPLIT	WT=	335.3					CUM	WT %	N/A	0.0	10.8	23.0	41.9	57.9	N/A	100.0
120	1.6	H	25.9	70.8	3.3	MS	WT	N/A	11.4	12.0	24.4	53.6	60.7	83.5	N/A	89.0
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	3.9	3.5	10.0	15.0	17.6	N/A	25.9
SPLIT	WT=	345.3					CUM	WT %	N/A	3.3	6.0	16.7	32.3	49.9	N/A	100.0
126	1.6	H	20.2	70.2	1.7	MS	WT	N/A	6.9	0.7	25.4	45.5	72.0	84.4	N/A	80.1
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	1.7	2.5	7.2	12.9	20.7	N/A	28.2
SPLIT	WT=	351.7					CUM	WT %	N/A	1.7	4.2	11.4	24.3	45.0	N/A	100.0
130	1.3	H	19.9	70.9	1.3	MS	WT	N/A	3.7	10.0	47.9	43.9	60.2	70.7	N/A	58.7
SORT=	N/A	MEDIAN=	3.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	1.3	3.4	16.2	14.9	20.4	N/A	19.9
SPLIT	WT=	295.1					CUM	WT %	N/A	1.3	4.0	20.9	35.8	50.2	N/A	100.0
135	1.7	H	24.1	74.9	1.0	MS	WT	N/A	3.7	7.4	35.3	60.3	70.9	85.1	N/A	85.9
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	1.0	2.1	9.9	10.9	22.1	N/A	24.1
SPLIT	WT=	368.8					CUM	WT %	N/A	1.0	3.1	13.0	29.9	62.1	N/A	100.0
140	1.6	H	24.5	74.0	1.0	MS	WT	N/A	2.6	7.5	36.4	62.0	60.0	86.1	N/A	90.1
SORT=	N/A	MEDIAN=	3.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	1.0	2.0	9.9	10.8	21.9	N/A	24.5
SPLIT	WT=	388.0					CUM	WT %	N/A	1.0	3.0	12.9	20.7	51.5	N/A	100.0
145	1.8	H	20.1	71.0	0.9	MS	WT	N/A	2.5	4.0	22.0	45.3	64.4	84.3	N/A	92.0
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.9	1.5	6.9	14.2	19.7	N/A	20.1
SPLIT	WT=	327.1					CUM	WT %	N/A	0.9	2.3	9.2	23.4	43.1	N/A	100.0
150	1.8	H	48.3	60.0	0.8	MS	WT	N/A	2.4	2.3	9.0	21.9	37.0	60.7	N/A	144.1
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	0.0	0.0	3.3	7.3	12.4	N/A	48.3
SPLIT	WT=	298.1					CUM	WT %	N/A	0.0	1.8	4.9	12.2	24.8	N/A	100.0
155	2.4	H	57.5	41.0	0.8	SM	WT	N/A	2.4	1.9	6.0	16.2	27.1	71.0	N/A	109.7
SORT=	N/A	MEDIAN=	6.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	0.8	0.0	2.3	5.2	9.2	N/A	57.5
SPLIT	WT=	294.0					CUM	WT %	N/A	0.8	1.5	3.0	8.0	10.1	N/A	100.0
160	2.7	H	74.0	24.8	1.2	SM	WT	N/A	3.0	1.4	3.0	7.7	14.6	46.0	N/A	219.9
SORT=	N/A	MEDIAN=	6.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	1.2	0.5	1.2	2.0	4.9	N/A	74.0
SPLIT	WT=	297.0					CUM	WT %	N/A	1.2	1.7	2.9	5.5	10.4	N/A	100.0
165	10.1	H	40.8	44.2	9.3	(g)SM	WT	N/A	20.3	13.0	13.1	20.0	35.2	44.0	N/A	142.2
SORT=	N/A	MEDIAN=	4.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	9.3	4.5	4.3	9.4	11.5	N/A	40.8
SPLIT	WT=	306.3					CUM	WT %	N/A	9.3	13.0	10.1	27.5	39.0	N/A	100.0

K.111

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-023 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
170	8.4	H	27.8	68.7	3.5	mS	WT	N/A	10.0	8.5	8.9	71.1	80.8	30.1	N/A	79.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	3.5	2.3	3.1	24.8	28.1	10.5	27.8
SPLIT	WT=	266.9					CUM	WT %	N/A	3.5	5.8	8.9	33.6	61.7	72.2	100.0
175	7.0	H	31.2	68.7	2.1	mS	WT	N/A	7.8	4.4	7.6	68.3	119.0	42.8	N/A	112.7
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	2.1	1.2	2.1	18.4	33.2	11.9	31.2
SPLIT	WT=	361.3					CUM	WT %	N/A	2.1	3.3	5.4	23.8	57.0	68.8	100.0
180	3.6	H	17.8	79.1	3.1	(m)S	WT	N/A	12.0	45.3	89.6	66.2	79.0	29.5	N/A	69.7
SORT=	N/A	MEDIAN=	2.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	3.1	11.0	22.9	18.9	20.2	7.5	17.8
SPLIT	WT=	391.1					CUM	WT %	N/A	3.1	14.7	37.5	54.5	74.6	82.2	100.0
185	1.0	H	18.4	55.5	26.0	gmS	WT	N/A	119.0	54.3	79.6	49.6	43.9	26.3	N/A	84.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.0	11.9	17.4	10.9	9.0	5.8	18.5
SPLIT	WT=	467.0					CUM	WT %	N/A	26.0	37.9	55.3	66.2	75.8	81.6	100.0
190	0.4	H	21.8	58.8	21.6	gmS	WT	N/A	80.8	49.3	61.4	42.5	34.4	24.7	N/A	80.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	21.6	13.2	18.4	11.4	9.2	6.6	21.6
SPLIT	WT=	373.8					CUM	WT %	N/A	21.6	34.8	51.2	62.6	71.0	78.4	100.0
195	0.2	H	24.5	56.7	18.8	gmS	WT	N/A	77.7	64.1	70.0	44.4	32.9	23.7	N/A	101.5
SORT=	N/A	MEDIAN=	1.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	18.8	15.5	16.9	10.7	7.9	5.7	24.5
SPLIT	WT=	414.3					CUM	WT %	N/A	18.8	34.2	51.1	61.8	69.8	76.5	100.0
200	0.1	H	14.8	56.3	28.8	gmS	WT	N/A	111.5	41.7	40.4	61.3	55.3	19.2	N/A	57.3
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.8	10.8	10.5	15.9	14.3	5.0	14.8
SPLIT	WT=	388.7					CUM	WT %	N/A	28.8	39.8	50.1	65.9	80.2	85.2	100.0
205	0.1	H	21.6	58.3	20.1	gmS	WT	N/A	87.3	40.4	38.8	62.8	75.2	35.7	N/A	93.6
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	20.1	9.3	8.9	14.5	17.3	8.2	21.6
SPLIT	WT=	433.9					CUM	WT %	N/A	20.1	29.4	38.4	52.9	70.2	78.4	100.0
210	0.1	H	25.2	57.5	17.3	gmS	WT	N/A	71.0	41.8	41.8	56.4	60.4	35.0	N/A	103.0
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	17.3	10.2	10.2	13.8	14.8	8.6	25.2
SPLIT	WT=	409.4					CUM	WT %	N/A	17.3	27.6	37.8	51.5	66.3	74.8	100.0
215	0.2	H	26.0	58.7	17.3	gmS	WT	N/A	64.5	48.0	40.2	47.4	47.5	20.7	N/A	97.3
SORT=	N/A	MEDIAN=	2.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	17.3	12.9	10.8	12.7	12.7	7.7	26.0
SPLIT	WT=	373.5					CUM	WT %	N/A	17.3	30.1	40.9	53.6	66.3	74.0	100.0
220	0.2	H	30.8	55.7	13.5	gmS	WT	N/A	47.9	47.3	39.7	41.9	40.4	28.1	N/A	109.3
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	13.5	13.3	11.2	11.8	11.4	7.9	30.8
SPLIT	WT=	354.8					CUM	WT %	N/A	13.5	26.9	38.1	49.9	61.3	69.2	100.0

K.112

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
 ROCKSAN REPORT

**** REPORT ON WELL 0299-W10-023 ****

02/02/00

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
225	0.1	H	21.9	43.3	34.7	msG	WT	N/A	130.8	43.3	32.4	33.2	32.0	22.4	N/A	82.7
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	34.7	11.5	8.8	8.6	5.9	N/A	22.0
SPLIT	WT=	376.8						CUM WT %	N/A	34.7	46.2	54.8	63.6	72.1	N/A	100.0
230	0.1	H	27.3	58.3	14.3	gmS	WT	N/A	41.7	35.4	31.7	35.1	40.8	26.6	N/A	79.4
SORT=	N/A	MEDIAN=	3.00	MODE=	5.00	MEAN=	N/A	WT %	N/A	14.3	12.2	10.9	12.1	14.0	N/A	27.3
SPLIT	WT=	290.8						CUM WT %	N/A	14.3	26.5	37.4	49.5	63.5	N/A	100.0
235	0.1	H	19.2	52.8	28.0	gmS	WT	N/A	81.3	45.2	31.5	29.5	28.4	18.8	N/A	55.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	28.0	15.6	10.9	10.2	9.8	N/A	19.3
SPLIT	WT=	290.2						CUM WT %	N/A	28.0	43.6	54.4	64.6	74.4	N/A	100.0
240	0.1	H	13.8	54.0	32.5	msG	WT	N/A	106.3	60.7	42.8	30.0	27.3	15.9	N/A	44.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.5	18.5	13.1	9.2	8.3	N/A	13.8
SPLIT	WT=	327.4						CUM WT %	N/A	32.5	51.0	64.1	73.2	81.6	N/A	100.0
245	0.0	H	6.8	35.8	58.8	msG	WT	N/A	218.5	88.3	29.8	12.9	12.9	9.8	N/A	20.7
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	68.8	18.5	8.0	3.5	2.4	N/A	5.0
SPLIT	WT=	369.7						CUM WT %	N/A	68.8	77.0	85.0	88.5	92.0	N/A	100.0
250	0.1	H	18.1	54.7	27.2	gmS	WT	N/A	75.0	35.8	29.1	25.4	38.4	22.3	N/A	50.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	27.2	13.0	10.5	9.2	13.9	N/A	18.2
SPLIT	WT=	278.0						CUM WT %	N/A	27.2	40.1	50.7	59.9	73.8	N/A	100.0
255	0.6	H	4.9	88.9	8.2	(g)S	WT	N/A	26.1	82.7	88.6	65.3	29.5	9.2	N/A	15.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	N/A	WT %	N/A	8.2	26.1	28.0	20.6	9.3	N/A	4.9
SPLIT	WT=	318.8						CUM WT %	N/A	8.2	34.3	62.3	82.9	92.2	N/A	100.0

K.113

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 1

**** REPORT ON WELL 0299-W18-024 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE FEB (≤-2)	VFINE FEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
5	1.0	C	7.0	82.0	0.2	S	WT	N/A	0.0	3.4	11.1	37.2	128.1	282.1	N/A	39.2
	N/A						WT %	N/A	0.2	0.7	2.2	7.4	25.6	68.2	N/A	7.8
							CUM WT %	N/A	0.2	0.8	3.1	10.6	36.0	82.2	N/A	100.0
10	1.0	C	14.6	84.3	1.0	(m)S	WT	N/A	4.9	6.7	14.6	53.4	175.3	144.8	N/A	60.6
	N/A						WT %	N/A	1.1	1.4	3.1	11.4	37.5	30.9	N/A	14.6
							CUM WT %	N/A	1.1	2.5	5.6	17.0	54.4	85.4	N/A	100.0
15	2.2	C	11.5	79.1	9.4	(gms)S	WT	N/A	48.7	83.7	49.0	87.5	138.8	59.7	N/A	59.8
	N/A						WT %	N/A	9.4	16.1	9.4	10.9	25.2	11.6	N/A	11.6
							CUM WT %	N/A	9.4	25.6	35.0	51.8	77.0	88.6	N/A	100.0
17	1.2	C	2.2	76.1	22.8	gS	WT	N/A	166.1	293.2	144.0	39.6	24.5	9.7	N/A	14.7
	N/A						WT %	N/A	22.8	43.0	21.2	5.8	3.6	1.4	N/A	2.2
							CUM WT %	N/A	22.8	66.8	87.0	92.8	96.4	97.8	N/A	100.0
20	0.4	C	1.7	95.6	2.7	S	WT	N/A	10.1	206.1	322.7	104.7	27.3	8.6	N/A	11.6
	N/A						WT %	N/A	2.7	29.4	46.1	15.0	3.9	1.2	N/A	1.7
							CUM WT %	N/A	2.7	32.2	78.3	93.2	97.1	98.3	N/A	100.0
22	N/A	C	6.2	92.7	1.1	S	WT	N/A	7.3	168.7	120.6	169.2	128.7	41.8	N/A	41.3
	N/A						WT %	N/A	1.1	23.6	19.4	24.0	19.4	8.3	N/A	6.2
							CUM WT %	N/A	1.1	24.7	44.1	68.1	87.6	93.8	N/A	100.0
25	0.4	C	0.6	88.0	10.6	gS	WT	N/A	80.6	321.4	284.4	49.6	12.4	4.8	N/A	4.6
	N/A						WT %	N/A	10.6	42.4	37.5	8.6	1.6	0.6	N/A	0.6
							CUM WT %	N/A	10.6	63.0	90.5	97.1	98.8	99.4	N/A	100.0
30	0.5	C	1.6	82.9	15.6	gS	WT	N/A	114.0	253.2	257.3	69.0	20.0	8.0	N/A	11.9
	N/A						WT %	N/A	15.6	34.6	35.0	8.4	2.8	1.1	N/A	1.6
							CUM WT %	N/A	15.6	50.0	85.1	94.5	97.3	98.4	N/A	100.0
31	0.4	C	1.7	83.0	15.3	gS	WT	N/A	104.6	221.2	244.2	70.9	21.4	9.0	N/A	11.6
	N/A						WT %	N/A	15.3	32.4	36.0	10.4	3.1	1.3	N/A	1.7
							CUM WT %	N/A	15.3	47.7	83.4	93.8	97.0	98.3	N/A	100.0
35	0.8	C	6.4	93.6	0.0	S	WT	N/A	0.0	3.7	145.7	285.3	99.6	52.3	N/A	34.8
	N/A						WT %	N/A	0.0	0.7	28.9	37.9	18.4	9.7	N/A	6.4
							CUM WT %	N/A	0.0	0.7	27.8	65.6	82.9	93.6	N/A	100.0
38	0.6	C	1.2	57.0	41.6	sg	WT	N/A	329.9	163.7	208.1	60.6	19.1	6.7	N/A	9.8
	N/A						WT %	N/A	41.8	20.7	25.3	7.7	2.4	0.9	N/A	1.2
							CUM WT %	N/A	41.8	62.6	87.8	95.5	97.9	98.8	N/A	100.0

K.115

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-024 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
40	0.8	C	2.1	41.3	56.6	sg	WT	N/A	471.8	118.4	144.9	50.9	20.8	10.9	N/A	17.9	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	58.8	14.0	17.4	6.1	2.6	1.3	N/A	2.2
SPLIT	WT= 833.8							CUM WT %	N/A	58.6	70.8	87.9	94.1	96.8	97.9	N/A	100.0
45	0.9	H	12.3	79.0	8.8	(gm)S	WT	N/A	63.9	47.7	70.2	113.0	241.2	112.6	N/A	91.3	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	8.6	6.5	9.5	15.3	32.6	15.2	N/A	12.3
SPLIT	WT= 734.6							CUM WT %	N/A	8.6	15.1	24.6	39.9	72.5	87.7	N/A	100.0
50	1.5	H	0.7	71.1	20.2	(m)gS	WT	N/A	141.8	34.8	74.6	128.9	188.0	74.3	N/A	60.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	20.2	4.9	10.6	18.1	26.8	10.6	N/A	8.7
SPLIT	WT= 700.7							CUM WT %	N/A	20.2	25.2	35.8	53.9	80.7	91.3	N/A	100.0
65	0.8	H	0.9	57.9	32.2	msG	WT	N/A	232.8	77.8	82.2	87.4	111.3	69.9	N/A	71.9	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	32.2	10.7	11.4	12.1	15.4	8.3	N/A	9.9
SPLIT	WT= 722.5							CUM WT %	N/A	32.2	42.9	54.3	65.4	81.8	90.1	N/A	100.0
80	1.0	H	4.0	35.2	60.8	msG	WT	N/A	453.1	38.0	29.8	62.3	92.4	40.1	N/A	30.2	
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	60.8	5.1	4.0	8.4	12.4	5.4	N/A	4.1
SPLIT	WT= 744.7							CUM WT %	N/A	60.8	65.9	69.8	78.2	90.6	96.0	N/A	100.0
85	1.1	H	5.2	88.3	6.5	(g)S	WT	N/A	48.8	48.0	134.0	201.7	198.6	83.8	N/A	39.2	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.5	0.1	17.8	26.8	26.4	11.1	N/A	5.2
SPLIT	WT= 751.6							CUM WT %	N/A	6.5	12.6	30.4	57.3	83.7	94.8	N/A	100.0
70	1.5	H	0.8	89.9	3.8	S	WT	N/A	25.0	25.8	97.0	212.4	194.7	95.3	N/A	45.8	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	3.8	3.7	13.9	30.5	28.0	13.7	N/A	6.8
SPLIT	WT= 695.8							CUM WT %	N/A	3.8	7.3	21.2	51.8	79.8	93.5	N/A	100.0
75	1.5	H	13.5	85.1	1.5	(m)S	WT	N/A	7.5	6.9	32.4	96.3	163.0	130.0	N/A	67.8	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	1.5	1.4	6.4	19.1	32.4	25.8	N/A	13.5
SPLIT	WT= 503.7							CUM WT %	N/A	1.5	2.9	9.3	28.4	60.8	86.6	N/A	100.0
80	2.0	H	20.7	79.2	0.2	mS	WT	N/A	0.8	2.1	7.1	24.4	136.8	244.2	N/A	108.3	
SORT=	N/A	MEDIAN=	4.00	MODE=	4.00	MEAN=	N/A	WT %	N/A	0.2	0.4	1.4	4.7	26.1	46.6	N/A	20.7
SPLIT	WT= 524.3							CUM WT %	N/A	0.2	0.6	1.9	6.6	32.7	79.3	N/A	100.0
85	1.5	H	12.2	87.4	0.3	(m)S	WT	N/A	1.7	6.0	44.7	131.4	124.7	129.7	N/A	61.0	
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.3	1.2	9.0	26.3	25.0	26.0	N/A	12.2
SPLIT	WT= 498.8							CUM WT %	N/A	0.3	1.5	10.5	36.8	61.8	87.8	N/A	100.0
90	1.4	H	9.4	90.4	0.2	S	WT	N/A	0.9	0.5	18.1	116.9	212.2	125.6	N/A	49.3	
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	0.2	0.1	3.5	22.3	40.5	24.0	N/A	9.4
SPLIT	WT= 523.6							CUM WT %	N/A	0.2	0.3	3.7	26.1	66.6	90.6	N/A	100.0

K.116

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAM REPORT

PAGE 3

**** REPORT ON WELL 0200-W10-024 ****

02/02/86

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
96	1.7	H	12.2	87.6	0.2	(m)S	WT	N/A	1.3	5.8	56.7	158.3	142.9	137.5	N/A	58.7
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	WT %	N/A	0.2	1.0	10.1	25.7	25.4	24.4	N/A	12.2
SPLIT	WT=	563.0					CUM WT %	N/A	0.2	1.2	11.3	38.0	63.4	87.8	N/A	100.0
100	0.9	H	8.3	93.6	0.0	S	WT	N/A	0.1	2.7	21.0	140.3	299.4	60.2	N/A	35.6
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	WT %	N/A	0.0	0.5	3.9	25.1	53.5	10.0	N/A	6.4
SPLIT	WT=	559.2					CUM WT %	N/A	0.0	0.5	4.3	29.4	82.9	93.7	N/A	100.0
105	1.2	H	0.1	91.7	0.1	S	WT	N/A	0.0	1.0	51.9	244.0	172.5	78.4	N/A	48.8
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	WT %	N/A	0.1	0.3	8.7	40.9	28.8	13.1	N/A	8.2
SPLIT	WT=	598.8					CUM WT %	N/A	0.1	0.4	9.1	50.0	78.8	91.9	N/A	100.0
106	N/A	H	7.2	92.8	0.0	S	WT	N/A	0.1	2.3	50.0	245.2	216.8	52.0	N/A	44.4
SORT=	N/A	MEDIAN=	3.00	MODE=	2.00	MEAN=	WT %	N/A	0.0	0.4	9.1	39.8	35.0	0.0	N/A	7.2
SPLIT	WT=	610.4					CUM WT %	N/A	0.0	0.4	9.5	42.3	84.2	92.8	N/A	100.0
110	1.5	H	6.0	91.3	0.7	S	WT	N/A	3.9	15.1	110.5	179.2	120.5	119.3	N/A	47.7
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	WT %	N/A	0.7	2.5	18.5	30.1	20.2	20.0	N/A	8.0
SPLIT	WT=	596.3					CUM WT %	N/A	0.7	3.2	21.7	51.8	72.0	92.0	N/A	100.0
112	1.2	H	3.4	52.1	44.5	sG	WT	N/A	319.7	140.8	117.0	55.8	34.8	20.1	N/A	24.4
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	44.5	19.9	10.0	7.9	4.0	2.0	N/A	3.4
SPLIT	WT=	709.9					CUM WT %	N/A	44.5	64.4	81.0	88.8	93.7	96.8	N/A	100.0
113	N/A	H	2.0	47.2	49.9	sG	WT	N/A	427.0	102.1	134.2	50.5	24.0	13.4	N/A	24.0
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	WT %	N/A	49.9	21.3	15.7	5.9	2.8	1.0	N/A	2.0
SPLIT	WT=	867.0					CUM WT %	N/A	49.9	71.2	86.8	92.7	95.5	97.1	N/A	100.0
115	1.5	H	4.4	83.3	12.3	gS	WT	N/A	77.6	51.0	229.3	170.3	46.0	20.5	N/A	27.5
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	12.3	5.2	30.4	28.3	7.2	3.3	N/A	4.4
SPLIT	WT=	830.8					CUM WT %	N/A	12.3	20.5	50.9	85.2	92.4	96.8	N/A	100.0
118	1.5	H	3.2	38.4	58.5	sG	WT	N/A	467.9	121.2	92.1	42.0	30.5	21.1	N/A	25.8
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	58.5	15.1	11.5	5.3	3.0	2.6	N/A	3.2
SPLIT	WT=	800.2					CUM WT %	N/A	58.5	73.6	85.1	90.4	94.2	96.8	N/A	100.0
120	1.1	H	7.4	88.7	3.9	S	WT	N/A	23.3	70.1	219.4	183.6	51.9	20.9	N/A	44.2
SORT=	N/A	MEDIAN=	1.00	MODE=	1.00	MEAN=	WT %	N/A	3.9	11.7	30.0	27.3	8.7	4.5	N/A	7.4
SPLIT	WT=	599.5					CUM WT %	N/A	3.9	15.0	52.2	79.5	80.1	92.0	N/A	100.0
125	1.3	H	10.2	26.7	57.1	msG	WT	N/A	258.1	41.1	27.7	19.5	10.9	14.0	N/A	72.5
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	WT %	N/A	57.1	9.2	6.2	4.4	3.8	3.3	N/A	10.2
SPLIT	WT=	448.5					CUM WT %	N/A	57.1	66.3	72.4	70.8	60.5	83.0	N/A	100.0

K.117

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W10-024 ****

02/02/89

DEPTH	%CAC09	DM	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (<=-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
130	1.1	H	18.0	33.1	49.0	msG	WT	N/A	220.0	64.3	30.9	26.2	20.2	10.4	N/A	00.1	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	49.0	11.7	0.0	6.6	4.4	3.6	N/A	10.0
SPLIT	WT=	482.0						CUM WT %	N/A	49.0	60.7	60.7	74.1	78.6	82.0	N/A	100.0
135	2.4	H	73.0	22.0	4.4	sm	WT	N/A	13.9	10.0	7.0	5.3	10.2	30.2	N/A	231.0	
SORT=	N/A	MEDIAN=	5.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	4.4	3.2	1.7	3.2	12.4	N/A	73.0	
SPLIT	WT=	316.5						CUM WT %	N/A	4.4	7.6	9.8	11.4	14.7	27.0	N/A	100.0
140	2.8	H	83.9	13.0	2.3	M	WT	N/A	6.0	3.0	1.7	1.4	3.0	20.2	N/A	219.0	
SORT=	N/A	MEDIAN=	6.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	2.3	1.2	0.7	0.6	1.6	10.0	N/A	03.0
SPLIT	WT=	201.7						CUM WT %	N/A	2.3	3.4	4.1	4.0	6.1	10.1	N/A	100.0
146	14.6	H	80.5	31.9	7.6	(g)sm	WT	N/A	28.9	13.0	11.4	12.0	26.7	50.7	N/A	210.0	
SORT=	N/A	MEDIAN=	5.00	MODE=	6.00	MEAN=	N/A	WT %	N/A	7.6	3.9	3.6	7.2	14.2	N/A	00.6	
SPLIT	WT=	357.9						CUM WT %	N/A	7.6	11.4	14.0	10.1	26.3	39.6	N/A	100.0
150	13.4	H	21.0	37.0	40.0	msG	WT	N/A	160.4	30.2	31.2	29.9	26.0	24.0	N/A	00.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	40.0	0.2	0.4	0.1	0.5	N/A	21.0	
SPLIT	WT=	370.0						CUM WT %	N/A	40.0	40.7	67.1	66.2	72.0	78.4	N/A	100.0
160	2.0	H	14.7	42.0	43.3	msG	WT	N/A	177.7	46.1	40.8	42.0	22.2	15.1	N/A	00.2	
SORT=	N/A	MEDIAN=	0.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	43.3	11.0	11.4	10.6	6.4	3.7	N/A	14.7
SPLIT	WT=	400.0						CUM WT %	N/A	43.3	64.3	65.8	70.2	01.6	05.3	N/A	100.0
180	0.3	H	20.0	73.2	6.9	(g)ms	WT	N/A	26.3	17.4	40.0	146.0	43.3	15.0	N/A	73.4	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	0.9	4.7	12.6	30.9	11.8	4.3	N/A	20.0
SPLIT	WT=	307.0						CUM WT %	N/A	6.9	11.0	24.1	64.0	76.7	00.1	N/A	100.0
105	0.1	H	3.7	90.9	5.4	(g)S	WT	N/A	36.8	13.6	223.7	201.1	83.4	36.7	N/A	26.0	
SORT=	N/A	MEDIAN=	2.00	MODE=	2.00	MEAN=	N/A	WT %	N/A	6.4	2.0	32.9	38.4	12.3	6.3	N/A	3.7
SPLIT	WT=	079.7						CUM WT %	N/A	6.4	7.4	40.4	70.0	91.1	90.3	N/A	100.0
170	0.1	H	1.2	80.9	17.9	gS	WT	N/A	140.6	240.2	200.4	166.0	60.6	10.0	N/A	10.2	
SORT=	N/A	MEDIAN=	1.00	MODE=	0.00	MEAN=	N/A	WT %	N/A	17.9	29.0	24.2	16.0	0.0	2.0	N/A	1.2
SPLIT	WT=	020.0						CUM WT %	N/A	17.9	40.9	71.0	09.9	90.7	90.0	N/A	100.0
175	0.2	H	20.7	40.7	30.6	msG	WT	N/A	129.5	66.0	50.4	42.1	27.3	20.6	N/A	07.0	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.0	13.3	13.9	10.0	0.6	4.9	N/A	20.7
SPLIT	WT=	419.7						CUM WT %	N/A	30.0	43.9	57.8	07.0	74.4	79.3	N/A	100.0
180	0.1	H	10.3	40.9	31.8	msG	WT	N/A	147.3	60.2	56.1	34.0	36.4	41.1	N/A	00.6	
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.0	13.0	12.1	7.6	7.9	0.0	N/A	10.3
SPLIT	WT=	403.6						CUM WT %	N/A	31.0	44.3	56.4	04.0	71.0	00.7	N/A	100.0

K.110

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

**** REPORT ON WELL 0299-W18-024 ****

02/02/89

DEPTH	%CAC03	DW	%MUD	%SAND	%GRAVEL	CLASS		FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)
186	N/A	H	21.0	48.0	31.1	msG	WT	N/A	138.0	63.2	66.9	37.6	29.5	26.9	N/A	93.2
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	31.1	12.0	14.8	8.4	8.1	N/A	21.0
SPLIT	WT=	444.2					CUM WT %	N/A	31.1	43.1	67.9	68.3	73.0	79.0	N/A	100.0
190	0.1	H	22.1	48.2	29.7	gmS	WT	N/A	132.4	61.6	67.7	43.7	38.4	26.0	N/A	98.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.7	11.6	12.9	9.8	6.8	N/A	22.1
SPLIT	WT=	446.5					CUM WT %	N/A	29.7	41.2	64.1	63.9	72.0	77.9	N/A	100.0
196	0.0	H	19.6	42.9	37.8	msG	WT	N/A	166.7	40.2	34.3	39.4	48.6	28.3	N/A	86.9
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.8	9.1	7.8	9.0	8.4	N/A	19.6
SPLIT	WT=	440.4					CUM WT %	N/A	37.8	46.8	64.6	63.6	74.1	80.5	N/A	100.0
200	0.0	H	19.8	66.3	26.0	gmS	WT	N/A	96.4	23.9	17.8	81.2	82.6	26.9	N/A	76.6
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.0	6.3	4.6	16.0	6.8	N/A	19.8
SPLIT	WT=	382.1					CUM WT %	N/A	26.0	31.2	36.8	61.9	73.6	80.3	N/A	100.0
206	0.0	H	19.9	60.8	29.4	gmS	WT	N/A	124.8	43.1	31.0	45.2	67.7	27.7	N/A	84.4
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	29.4	10.2	7.3	10.7	6.6	N/A	19.9
SPLIT	WT=	423.9					CUM WT %	N/A	29.4	39.6	46.9	67.6	73.6	80.1	N/A	100.0
210	0.0	H	22.5	88.9	10.6	gmS	WT	N/A	44.6	28.2	24.4	98.8	103.4	31.3	N/A	96.0
SORT=	N/A	MEDIAN=	3.00	MODE=	3.00	MEAN=	N/A	WT %	N/A	10.6	6.2	6.8	23.0	7.4	N/A	22.6
SPLIT	WT=	421.6					CUM WT %	N/A	10.6	16.8	22.6	46.6	70.1	77.6	N/A	100.0
216	0.0	H	7.6	87.6	24.9	(m)gS	WT	N/A	94.7	81.7	33.7	67.0	70.2	14.7	N/A	28.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	24.9	21.6	8.9	16.0	3.9	N/A	7.6
SPLIT	WT=	380.7					CUM WT %	N/A	24.9	46.3	66.2	70.1	88.6	92.4	N/A	100.0
220	0.0	H	3.4	69.2	37.3	*G	WT	N/A	149.6	46.8	64.6	76.8	49.2	10.8	N/A	13.8
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	37.4	11.7	13.6	18.9	2.7	N/A	3.6
SPLIT	WT=	400.4					CUM WT %	N/A	37.4	49.0	62.7	81.6	93.9	98.8	N/A	100.0
226	0.0	H	8.6	80.9	30.5	msG	WT	N/A	112.3	32.0	24.6	77.7	73.0	10.8	N/A	31.6
SORT=	N/A	MEDIAN=	2.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	30.6	8.7	6.7	21.1	4.8	N/A	8.6
SPLIT	WT=	367.9					CUM WT %	N/A	30.6	39.2	46.9	67.0	86.9	91.4	N/A	100.0
230	0.0	H	4.1	70.8	26.1	gS	WT	N/A	98.1	88.6	60.8	78.0	67.8	13.7	N/A	10.1
SORT=	N/A	MEDIAN=	1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	26.1	17.0	16.6	19.4	3.6	N/A	4.1
SPLIT	WT=	390.9					CUM WT %	N/A	26.1	42.7	68.2	77.6	92.4	96.9	N/A	100.0
236	0.1	H	8.3	42.6	51.1	msG	WT	N/A	171.3	86.0	34.3	20.3	16.6	7.4	N/A	21.2
SORT=	N/A	MEDIAN=	-1.00	MODE=	-1.00	MEAN=	N/A	WT %	N/A	51.1	19.4	10.2	8.1	4.7	N/A	6.3
SPLIT	WT=	335.1					CUM WT %	N/A	51.1	70.6	80.8	88.0	91.6	93.7	N/A	100.0

K.119

ROCKWELL HANFORD OPERATIONS SIEVE ANALYSIS
ROCKSAN REPORT

PAGE 6

**** REPORT ON WELL 0290-W18-024 ****

02/02/89

DEPTH	%CAC03	DM	%MUD	%SAND	%GRAVEL	CLASS	FINE PEB (≤-2)	VFINE PEB (-1)	VERY COARS (0)	COARS (1)	MED (2)	FINE (3)	VERY FINE (4)	SILT (4.75)	PAN (>4.75)	
240	0.1	H	0.7	63.7	29.0	GS	WT	N/A	97.2	95.6	59.0	31.2	10.1	7.1	N/A	22.2
SORT= N/A MEDIAN= 0.00 MODE= -1.00 MEAN= N/A							WT %	N/A	29.0	20.0	10.1	9.6	4.9	2.2	N/A	6.0
SPLIT WT= 328.0							CUM WT %	N/A	29.0	58.6	76.7	86.2	91.1	93.3	N/A	100.0

APPENDIX L

BOREHOLE GEOPHYSICAL LOGGING PROCEDURES

STANDARD OPERATING PROCEDURE

TITLE: GL-5 NEUTRON PROBE PROCEDURE

1.0 Objective

The objective of this procedure is to establish a standardized format for the operation of the neutron probe.

2.0 Applicability

When this procedure is selected for implementation by a QA plan prepared and approved in accordance with PNL-MA-60, Quality Assurance Manual for License-Related Programs, this procedure is applicable to borehole neutron logging. The neutron logging system provides a means for determining formation hydrogen content, moisture content, and porosity. Maximum logging speed is 25 ft per minute. Procedures for use and handling of the radioactive source for this probe are described in RWP HR-9 and SRSP NO. 007B.

3.0 Definitions

3.1 Definitions of abbreviations used in this procedure

- a. NBP is NIMS Bin Panel. NIMS refers to nuclear instrument modules specifications.
- b. SRP refers to solid state recorder panel.
- c. LPM refers to line power module.
- d. RMM refers to rate meter module.

4.0 Responsibilities

It will be the responsibility of each person authorized to operate the equipment to follow the step-by-step operating procedure.

5.0 Procedure

5.1 Equipment

The following equipment is used to run neutron logs:

- a. Logging truck with cable and reel
- b. AC power source
- c. NIMS Bin panel
- d. Chart recorder
- e. Line power module

QA0 Approval <i>DR Dahl 8-4-86</i>		Approved (Line Manager) <i>R. Woodruff for P. Brannon 8/6/86</i>	
Prepared by VL McGhan <i>V.L. McGhan 8-4-86</i>		Technical Review <i>J.R. Raymond 8/11/86</i>	
Procedure No. GL-5	Revision No. 2	Date Issued 7/86	Page <u>1</u> of <u>3</u>

STANDARD OPERATING PROCEDURE

- f. Ratemeter module
- g. Neutron probe
- h. 3 Ci ^{241}Am Be source
- i. Well sheave
- j. 50 mCi ^{241}Am Be calibration source.

5.2 Equipment Setup

- a. Attach a 3 Ci Am Be source to the probe and the probe to the cable head.
- b. NBP and SRP power to ON.
- c. RMM MODE switch to LINE.
- d. RMM SUPPRESSION and RECORDER OUTPUT controls fully clockwise.
- e. RMM TC switch to 2.
- f. RMM POSITIVE-NEGATIVE polarity switch to POSITIVE.
- g. RMM REVERSE-NORMAL switch to NORMAL.
- h. LPM CURRENT-VOLTAGE switch to CURRENT.
- i. LPM NEG-OFF-POS switch to POSITIVE.
- j. LPM CURRENT ADJUST to 70 milliamps.

5.3 Calibration

- a. RMM MODE switch to CAL 100.
- b. RMM CPS switch to 100.
- c. SRP--Switch a recorder amplifier to ON.
- d. RMM--Depress ZERO and hold in.
- e. Adjust recorder amplifier ZERO to position pen to its preselected zero point on the chart.
- f. RMM--Release the ZERO.
- g. Adjust the recorder amplifier SPAN control to the desired position on the chart. Record this span on the chart.
- h. RMM MODE switch to LINE.
- i. RMM CPS switch to 500.
- j. With the probe resting on a dry surface at least three feet above the ground, take a one minute background count and record this on the chart. Use the time drive to turn the recorder.
- k. Place the 50mCi Am Be neutron calibrator at the proper position on the probe and take a one minute count. Record this on the chart.

5.4 Logging

- a. Place the probe in the well and set to proper measuring point. Probe zero is at the detector tube. Change CPS switch to 1000 or 5000.
- b. Run the log. Maximum logging speed is 25 ft per minute. Rerun a 50-ft section for system check, or if well has been logged before, overlap a 50-ft section of the previous log.
- c. Review the log for reasonableness. Sign and date the log to document review.

Procedure No.	Revision No.	Date Issued	Page
GL-5	2	7/86	2 of 3

STANDARD OPERATING PROCEDURE

5.5 Calibration Check

- a. RMM CPS switch to 500.
- b. Record a one minute background count with the probe resting on a dry surface and three feet above ground surface.
- c. Place the 50 mCi Am Be source on the probe and record a one minute count.
- d. Record the span on the chart.
- e. If the count rate does not match the calibration background and source count, the probe has malfunctioned and the log should not be used.

Procedure No.
GL-5

Revision No.
2

Date Issued
7/86

Page 3 of 3

STANDARD OPERATING PROCEDURE

TITLE: GL-E BULK DENSITY PROBE PROCEDURE

1.0 Objective

The objective of this procedure is to establish a standardized format for the operation of the bulk density probe.

2.0 Applicability

When this procedure is selected for implementation by a QA plan prepared and approved in accordance with PNL-MA-60, Quality Assurance Manual for License-Related Programs, this procedure is applicable to borehole bulk density logging. The bulk density logging system provides continuous recording of bulk density of materials surrounding the borehole. Maximum logging speed is 25 ft per minute. Procedures for use and handling of the probe and radioactive sources are described in RWP HR-9 and SRSP No. 0078.

3.0 Definitions

3.1 Definition of abbreviations used in this procedure

- a. NBP is NIMS Bin Panel. NIMS refers to nuclear instrument modules specifications.
- b. SRP refers to solid state recorder panel.
- c. LPM refers to line power module.
- d. RMM refers to rate meter module.

4.0 Responsibilities

It will be the responsibility of each person authorized to operate the equipment to follow the step-by-step operating procedure.

5.0 Procedure

5.1 Equipment

The following equipment is used to run density logs:

- a. Logging truck with cable and reel
- b. AC power source
- c. NIMS Bin panel
- d. Chart recorder
- e. Line power module

QAO Approval <i>DR Dall</i> 8-4-86		Approved (Line Manager) <i>R. Woodruff</i> 8/6/86	
Prepared by VL McGhan <i>V.L. McGhan</i> 8-4-86		Technical Review <i>J.R. Raymond</i> 8/1/86	
Procedure No. GL-6	Revision No. 2	Date Issued 7/86	Page <u>1</u> of <u>2</u>

STANDARD OPERATING PROCEDURE

- f. Ratemeter module
- g. Density probe
- h. 125 mCi ^{137}Cs source
- i. Well sheave.

5.2 Equipment Setup

- a. Attach probe to cable head.
- b. Place probe in well and set to proper measuring point. Probe zero is at the detector, 3.7 ft from top of cable head spring.
- c. NBP and SRP power switches to ON.
- d. RMM NORMAL-Reverse switch to REVERSE.
- e. RMM MODE switch to LINE.
- f. RMM SUPPRESSION and RECORDER OUTPUT control fully clockwise.
- g. RMM CPS switch to 500.
- h. RMM TC switch to 3.
- i. RMM POSITIVE-NEGATIVE switch to NEGATIVE.
- j. LPM NEG-OFF-POS switch to POSITIVE.
- k. LPM CURRENT ADJUST to 70 milliamps.
- l. RMM MODE switch to 100 CAL.
- m. RMM CPS switch to 100.
- n. Switch a recorder amplifier to ON.
- o. RMM Depress the zero and hold in.
- p. SRP Adjust the recorder amplifier ZERO to position pen to its preselected position on the right side of the chart.
- q. RMM Release zero.
- r. SRP Adjust recorder SPAN control to desired position on the left side of the chart. Record this span on the chart.
- s. RMM MODE switch to LINE.
- t. RMM CPS switch to 500. System is ready to operate. Maximum logging speed is 25 ft per minute.
- u. Rerun a 50-ft section for system check, or if well has been logged before, overlap a 50-ft section of previous log.
- v. Check the span and record it on the chart.
- w. Review log for reasonableness. Sign and date log to document review.

Procedure No. GL-6	Revision No. 2	Date Issued 7/86	Page <u>2</u> of <u>2</u>
-----------------------	-------------------	---------------------	---------------------------

STANDARD OPERATING PROCEDURE

TITLE: GL-7 GAMMA RAY PROBE PROCEDURE

1.0 Objective

The objective of this procedure is to establish a standardized format for the operation of the gamma ray probe.

2.0 Applicability

When this procedure is selected for implementation by a QA plan prepared and approved in accordance with PNL-MA-60, Quality Assurance Manual for License-Related Programs, this procedure is applicable to borehole gamma ray logging. Gamma Ray logs are used for the determination of lithology and measurement of natural and induced gamma radiation. Gamma Ray logs may be recorded in cased or uncased wells, fluid-filled or dry. Maximum logging speed is 20 ft per minute. Procedures for handling the source that is used with this probe are described in RWP HR-9 and SRSP No. 0078.

3.0 Definitions

3.1 Definitions of abbreviations used in this procedure

- a. NBP is NIMS Bin Panel. NIMS refers to nuclear instrument modules specifications.
- b. SRP refers to solid state recorder panel.
- c. LPM refers to line power module.
- d. RMN refers to rate meter module.

4.0 Responsibilities

It will be the responsibility of each person authorized to operate this equipment to follow the step-by-step operating procedure.

5.0 Procedure

5.1 Equipment

The following equipment is used to run gamma ray logs:

- a. Logging truck with cable and reel
- b. AC power source
- c. NIMS Bin panel
- d. Chart recorder

QAO Approval <i>DR Dall 8-4-86</i>		Approved (Line Manager) <i>R. Woodruff for P. Brown 8/6/86</i>	
Prepared by VL McGhan <i>V.L. McGhan 8-4-86</i>		Technical Review <i>J.R. Raymond 8/1/86</i>	
Procedure No. GL-7	Revision No. 3	Date issued 7/86	Page <u>1</u> of <u>3</u>

STANDARD OPERATING PROCEDURE

- e. Line power module
- f. Ratemeter module
- g. Gamma ray probe
- h. Well sheave
- i. .02 mCi Ra 226 calibration source.

5.2 Equipment Setup

- a. NBP and SRP switches to ON.
- b. RMM switch to LINE.
- c. RMM SUPPRESSION and RECORDER OUTPUT controls fully clockwise.
- d. RMM TC switch to 3.
- e. RMM POSITIVE-NEGATIVE polarity switch to NEGATIVE.
- f. RMM REVERSE-NORMAL switch to NORMAL.
- g. LPM CURRENT-VOLTAGE switch to CURRENT.
- h. LPM INSTRUMENT POWER switch to POSITIVE.
- i. LPM CURRENT ADJUST to 75 milliamps for probe NO. NG-001. For probe NO. CG-27A97 use 60 milliamps.

5.3 Calibration

- a. RMM CPS switch to 100.
- b. RMM switch to CAL 100. RMM CPS meter should read 100 cps at this point.
- c. SRP--Switch a recorder amplifier to ON.
- d. RMM--Depress the zero and hold in.
- e. SRP--Adjust recorder ZERO to position pen to its preselected position on the chart.
- f. RMM--Release the ZERO.
- g. SRP--Adjust the SPAN control to position the pen to a desired position on the chart.
- h. Record this span on the chart.
- i. RMM MODE switch to LINE.
- j. RMM CPS switch to 500.
- k. Record zero on the chart.
- l. Record gamma ray background in air.
- m. Record the probe response to the .02 mCi Ra 226 source placed perpendicular to the probe and 42 in. from the detector. Make sure the source is pointing toward the top of the probe.

5.4 Logging

- a. Place probe in the well and set depth to proper measuring point. Probe zero is at the counting tube.
- b. Proceed to the bottom of the hole and log up. Log at 15 ft per minute.
- c. For system check, rerun a 50-ft section, or if the well has been logged before, overlap a 50-ft section of the previously logged section.

Procedure No. GL-7	Revision No. 3	Date Issued 7/86	Page <u>2</u> of <u>3</u>
-----------------------	-------------------	---------------------	---------------------------

STANDARD OPERATING PROCEDURE

- d. Review the log for reasonableness. Sign and date the log to document the review.

5.5 Calibration Check

- a. Record zero.
- b. Record gamma ray background in air.
- c. Record the probe response to the .02 mCi Ra 226 source.
- d. Record the span.
- e. If the calibration check does not match the calibration count rate, the probe has malfunctioned and the log should not be used.

Procedure No. GL-7	Revision No. 3	Date Issued 7/86	Page <u>3</u> of <u>3</u>
-----------------------	-------------------	---------------------	---------------------------

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

25 Pacific Northwest Laboratory

10 DOE/Office of Scientific and
Technical Information

S. P. Airhart
M. P. Bergeron
B. N. Bjornstad
R. W. Bryce
M. A. Chamness
J. W. Falco
M. D. Freshley
J. M. Hales
P. C. Hays
G. V. Last (3)
R. E. Lundgren
D. R. Newcomer
J. A. Schramke
R. L. Skaggs
R. M. Smith
J. A. Stottlemire
D. W. Wallace

ONSITE

4 DOE Richland Operations Office

E. A. Bracken
A. J. Knepp
K. M. Thompson
M. W. Tiernan

Publishing Coordination
Technical Report Files (5)

60 Westinghouse Hanford Company

D. L. Armstrong
D. R. Duncan
G. C. Evans (50)
K. R. Fecht
R. L. Jackson
R. B. Mercer
N. M. Naiknimbalkar
J. D. Payne
S. M. Price
W. H. Price
S. P. Reidel