DOE/PC/88812--T12

**PROCESS AND ANALYTICAL STUDIES OF ENHANCED LOW
SEVERITY CO-PROCESSING USING SELECTIVE COAL
PRETREATMENT**

DOE/PC/88812--T12

DE92 005496

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**R.M. Baldwin, S. Gaur, and R.L. Miller
Chemical Engineering and Petroleum Refining Dept.
Colorado School of Mines
Golden, CO 80401**

Received OSTI
JAN 15 1992

**Quarterly Technical Progress Report for the Period
June - August, 1991**

DOE Contract No. DE-AC22-88PC88812

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EP

ABSTRACT

This report describes progress on research during the 12th and final quarter of this contract dealing with applications of coal pretreatment techniques in coal/oil co-processing and direct hydroliquefaction. The overall objectives of the project are to investigate various coal pretreatment techniques and to determine the effect of these pretreatment procedures on the reactivity of the coal. Reactivity enhancement will be evaluated under both direct hydroliquefaction and co-processing conditions. Coal conversion utilizing low rank coals and low severity conditions (reaction temperatures generally less than 350 °C) is the primary focus of the liquefaction experiments, as it is expected that the effect of pretreatment conditions and the attendant reactivity enhancement will be greatest for these coals and at these conditions.

This document presents a summary of results for a series of runs intended to investigate the effect of mild selective alkylation on the activation energy for liquefaction. Results of this study show that mild alkylation has a very significant effect on the reaction rate, as indicated by lower global activation energies for conversion to THF, toluene, and hexane solubles.

TECHNICAL DISCUSSION

Introduction

The objective of this study was to investigate the effect of mild selective alkylation on the reactivity of coal under direct hydroliquefaction reaction conditions. Previous studies by these authors have indicated that liquefaction activation energy provides a sensitive tool for assessing differences in coal reactivity (1). For this study, O-alkylation of a subbituminous coal was utilized as the pretreatment step. Pretreated and parent coals were then liquefied at 3 temperatures and 5 times. Modeling of the rate data using simple first and second-order expressions then ensued for conversion of coal to three solvent solubility classifications (THF, toluene, hexane).

Experimental

A Wyodak subbituminous coal from the Argonne Premium Coal Sample Bank was utilized for this study. A 20 cc 1/2" diameter microautoclave tubing bomb reactor system was used to carry out the liquefaction experiments. Tetralin (1,2,3,4-tetrahydronaphthalene) was used as the vehicle for all experiments in order to mimic operation under direct hydroliquefaction conditions. Industrial grade hydrogen gas (General Air Services Inc.) was used as the reaction gas.

The micro reactor was filled with a weighed amount of coal sample (0.5 gr) and carrier solvent (tetralin) in 1:2 weight ratio. Two 3mm stainless steel balls were placed

inside the reactor to facilitate mixing. Reactions were run utilizing two reactors in parallel under identical operating conditions, with one reactor containing catalyst. Following reaction and cool-down, the reactors were weighed, depressurized and then weighed again to give a quantitative measure of the gas make. Rate data were obtained at 3 temperatures (350, 375, 400 °C) and 5 reaction times (5, 10, 15, 30, 60 minutes).

The reaction products were extracted with tetrahydrofuran (THF), toluene, and hexane to precipitate THF, toluene, and hexane insoluble materials. The insolubles were oven dried overnight and then weighed. The micro reactors were also weighed after extraction so as to ensure that residual insolubles had not been left behind in the reactor. A few experiments were duplicated to verify the reproducibility of the data. It was observed that the reproducibility of the numbers was generally within $\pm 3\%$. Further run and analytical procedures as well as alkylation details have been described elsewhere (2).

Conversions (THF , toluene, and hexane) were calculated using the following expression:

$$\text{conversion} = \frac{\text{insols in} - \text{insols out}}{\text{insols in}}$$

Results and Interpretations

The effect of alkylation on conversion of Wyodak coal has been shown in previous reports to be significant in promoting enhanced conversions over a broad range of reaction severities (2). As an additional check on the effect of alkylation, rate data for liquefaction were obtained for raw and O-methylated Wyodak coal at 350, 375, and 400 °C by measuring reaction profiles at 5, 10, 15, 30, and 60 minutes reaction time. For these studies, a fresh batch of Wyodak subbituminous coal was alkylated following the Liotta procedures outlined previously. Subsequent elemental analysis of the alkylated coal indicated that the extent of alkylation achieved was 8 methyl groups per 100 carbon atoms.

Rate data for conversion of dry and O-methylated Wyodak coal to THF, toluene, and hexane solubles are shown in Figures 1 through 6. From these data it can be readily seen that the O-methylated Wyodak coal exhibits higher conversions over the entire reaction profile and at each reaction temperature when compared to dry Wyodak coal.

In order to examine the effect of alkylation in more detail, the global rate data was next fit to a variety of kinetic models in order to facilitate calculation of an overall (global) activation energy for liquefaction of both raw and alkylated coals. Two kinetic models were tested with the rate data as shown below:

	Rate expression -----	Integrated Form -----
1 st order	$\frac{dx}{dt} = k(a-x)$	$x = a[1-\exp(-kt)]$
2 nd order	$\frac{dx}{dt} = k(a-x)^2$	$x = \frac{ka^2t}{kat + 1}$

where x = coal conversion (moisture and ash-free (MAF)
basis, wt%)

a = pseudo-equilibrium conversion

k = kinetic constant

t = reaction time (min.)

Two different interpretations for the parameter "a" are possible. First, "a" can represent a reactive fraction of the coal that indicates that all of the organic material is not convertible even at infinite reaction time. Under this interpretation, "a" is a true constant that is a characteristic of the organic geochemistry of the coal. Traditionally, this fraction has been obtained by other researchers from a maceral analysis of the raw coal, and defined as total macerals (vitrinite + liptinite + inertinite) less the fusinite and semi-fusinite maceral subgroups (2). Data from the Argonne National Laboratories are available which would permit estimation of this factor for raw Wyodak coal, but use of this approach for alkylated coal presents a problem. It is likely that the chemistry of the

maceral groups are significantly altered by the alkylation procedure, and "a" for alkylated coal is hence not the same as for the parent material. A second interpretation is that the "a" parameter reflects a pseudo-equilibrium conversion level. Under this interpretation, "a" introduces reversibility into the otherwise irreversible batch reactor material balance expressions shown above ("a" = 1.0 if reaction is irreversible), and hence represents a parameter that is not a pure constant but one that changes with temperature. In this type of model, parameter "a" is treated as an additional fitting parameter and the only restrictions on this factor are:

- 1) "a" · maximum observed conversion for each solvent solubility classification;

- 2) "a" must increase with increasing temperature.

In the following discussion, the second interpretation has been applied to parameter "a".

The results of fitting data to the integrated forms of the rate models are presented in Tables 1-3 for dry Wyodak coal, and Tables 4-6 for O-methylated coal. The test statistic used to discriminate between these various models in terms of overall adequacy was based on regression analysis of the linearized rate models to give the highest value of R^2 and the smallest value of the standard error of estimate (SEE) defined as:

$$SEE = \frac{[\sum (X - X^*)^2]^{\frac{1}{2}}}{n-1}$$

Where, X = the experimental values of coal conversion
(wt %)

X^* = the calculated values of coal conversion
by the model (wt %)

n = the number of data points

As can be seen, the first-order pseudo irreversible model and the second-order pseudo irreversible model both gave nearly identical results for the SEE test statistic for THF, toluene, and hexane solubles conversion data sets. However, the second order irreversible model give R^2 values higher than 0.90 for the linearized batch reactor material balance (for all cases) while the first order model gave R^2 values ranging from 0.63 to 0.79. The superior R^2 values for the second-order model indicates that this expression is better in terms of the ability to describe the data when compared to the first-order. Additionally, unrealistically low values for the pseudo-equilibrium conversion parameter ("a") are obtained from the first-order model while reasonable and realistic values for "a" are obtained when the data are fit with the second-order expression. Therefore, the second-order pseudo irreversible rate model was selected for subsequent calculation of reaction rate parameters (rate constants) and the global activation energy.

Parity plots (observed conversion vs. calculated conversion using the pseudo second order irreversible model) for dry Wyodak coal are shown in Figure 7 for hexane solubles, Figure 8 for toluene solubles, and Figure 9 for THF solubles. As can be seen, the second-order model provides an excellent description of the liquefaction data.

Arrhenius plots of these rate constants vs. absolute temperature for conversion of raw and O-methylated Wyodak coal to THF, toluene, and hexane solubles are shown in Figures 10 to 12. The coefficient of determination (R^2) for the Arrhenius plots was over 0.9 for all data sets except for the case of toluene soluble of dry Wyodak coal ($R^2 = 0.81$).

The calculated activation energies based on the slope of the Arrhenius plots are shown in Table 5. As can be seen, the derived global activation energy is significantly lower for the O-methylated coals as compared to liquefaction of raw Wyodak coal for all solvent solubility groups (THF, toluene, hexane). The difference in activation energy is approximately 6 Kcal/mole for all three solubility classifications. These parameters indicate that a very significant enhancement in the rate of liquefaction to THF, toluene, and hexane solubles is brought about by the O-methylation process employed.

It is important to note that the activation energies derived from the rate data and modeling do not have any fundamental significance in terms of the chemical rate

processes involved in coal liquefaction. In fact, these parameters are only useful for purposes of making relative comparisons between coals, and should not be used for generalization and/or extrapolation to other coals or processing conditions. As relative indicators of reactivity however, these results do show that the effect of O-methylation on the rate of liquefaction of Wyodak subbituminous coal is highly significant and nearly catalytic in magnitude.

Plans for the Coming Months

The project has been completed, and the final report is now in preparation.

References Cited

1. S.C. Shin; R.M. Baldwin; R.L. Miller; Energy and Fuels (1989), 3, 193
2. R.M. Baldwin; D.R. Kennar; O. Nguanprasert; R.L. Miller; FUEL (1991), 70, 429

Table 1

Pseudo First Order Irreversible Model for Raw Wyodak Coal

Hexane Solubles

Temperature	a	k	R ²	SEE
350 °C	7.92	0.0086	0.74	1.41
375 °C	9.67	0.0115	0.69	0.95
400 °C	20.90	0.0221	0.73	0.82

Toluene Solubles

Temperature	a	k	R ²	SEE
350 °C	11.13	0.0080	0.71	1.22
375 °C	18.19	0.0097	0.74	0.83
400 °C	23.10	0.0174	0.68	0.92

THF Solubles

Temperature	a	k	R ²	SEE
350 °C	15.18	0.0059	0.67	1.21
375 °C	20.08	0.0097	0.70	0.96
400 °C	26.04	0.0129	0.69	0.74

Table 2

Pseudo First Order Irreversible Model for O-methylated
Wyodak Coal

Hexane Solubles

Temperature	a	k	R ²	SEE
350 °C	18.17	0.0043	0.79	1.09
375 °C	28.50	0.0058	0.74	1.07
400 °C	37.33	0.0100	0.62	1.20

Toluene Solubles

Temperature	a	k	R ²	SEE
350 °C	25.27	0.0041	0.70	1.73
375 °C	36.23	0.0057	0.69	1.39
400 °C	43.38	0.0092	0.66	1.23

THF Solubles

Temperature	a	k	R ²	SEE
350 °C	28.78	0.0037	0.70	1.66
375 °C	38.09	0.0051	0.71	1.26
400 °C	45.15	0.0081	0.65	1.16

Table 3

Pseudo Second Order Irreversible Model for Raw Wyodak Coal

Hexane Solubles

Temperature	a	k	R ²	SEE
350 °C	30.95	0.0017	0.94	1.29
375 °C	30.76	0.0046	0.99	0.49
400 °C	34.16	0.0069	0.96	0.57

Toluene Solubles

Temperature	a	k	R ²	SEE
350 °C	32.78	0.0019	0.95	0.56
375 °C	34.72	0.0062	0.95	0.74
400 °C	36.63	0.0067	0.97	0.55

THF Solubles

Temperature	a	k	R ²	SEE
350 °C	34.01	0.0033	0.98	0.83
375 °C	35.58	0.0053	0.95	0.65
400 °C	36.23	0.0106	0.92	0.71

Table 4

Pseudo Second Order Irreversible Model for O-methylated
Wyodak Coal

Hexane Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	34.01	0.0045	0.95	0.58
375 °C	39.37	0.0100	0.96	0.39
400 °C	47.39	0.0120	0.99	0.15

Toluene Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	42.91	0.0049	0.95	0.82
375 °C	49.75	0.0080	0.95	0.52
400 °C	53.76	0.0119	0.93	0.45

THF Solubles

Temperature -----	a -----	k -----	R ² -----	SEE -----
350 °C	45.45	0.0056	0.97	0.56
375 °C	50.50	0.0092	0.95	0.51
400 °C	55.24	0.0116	0.94	0.48

Table 5
Activation Energy and Frequency Factor

	Dry Wyodak Coal -----	O-methylated Wyodak Coal -----
<u>Hexane Solubles</u>		
Activation Energy (Kcal/mole)	23.71	16.99
Frequency Factor	3.60E+5	4536.00
R ²	0.95	0.92
<u>Toluene Solubles</u>		
Activation Energy (Kcal/mole)	21.02	14.53
Frequency Factor	5.42E+4	626.41
R ²	0.81	0.99
<u>THF Solubles</u>		
Activation Energy (Kcal/mole)	19.09	12.32
Frequency Factor	1.60E+4	121.51
R ²	0.97	0.98

FIGURE 1

CONVERSION TO THF SOLUBLES VS. TIME
WYODAK COAL

FIGURE 2

CONVERSION TO TOLUENE SOLUBLES VS. TIME
WYODAK COAL

FIGURE 3

CONVERSION TO HEXANE SOLUBLES VS. TIME
WYODAK COAL

FIGURE 4

CONVERSION TO THF SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

FIGURE 5

CONVERSION TO TOLUENE SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

FIGURE 6

CONVERSION TO HEXANE SOLUBLES VS. TIME
ALKYLATED WYODAK COAL

FIGURE 7
PARITY PLOT FOR THF SOLUBLES

FIGURE 8
PARITY PLOT FOR TOLUENE SOLUBLES

FIGURE 9
PARITY PLOT FOR HEXANE SOLUBLES

FIGURE 10
ARRHENIUS PLOTS FOR THF SOLUBLES

FIGURE 11
ARRHENIUS PLOTS FOR TOLUENE SOLUBLES

FIGURE 12
ARRHENIUS PLOTS FOR HEXANE SOLUBLES

END

**DATE
FILMED**

2 / 26 / 92