348
11/6/79

DOE/NASA CONTRACTOR
REPORT

DR. 236

DOE/NASA CR-161094

MASTER

OWENS-ILLINOIS SUBSYSTEM DESIGN PACKAGE FOR THE SEC-601 AIR-COOLED SOLAR COLLECTOR

Prepared by

Owens-Illinois
P. O. Box 1035
Toledo, Ohio 43666

Under Contract NAS8-32259 with

National Aeronautics and Space Administration
George C. Marshall Space Flight Center, Alabama 35812

For the U. S. Department of Energy

U.S. Department of Energy

Solar Energy

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE

This report was prepared to document work sponsored by the United States Government. Neither the United States nor its agents the United States Department of Energy, the United States National Aeronautics and Space Administration, nor any federal employees, nor any of their contractors, subcontractors or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represent that its use would not infringe privately owned rights.

MASTER

TECHNICAL REPORT STANDARD TITLE PAGE

1. REPORT NO. DOE/NASA CR-161094	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO.	
4. TITLE AND SUBTITLE Owens-Illinois Subsystem Design Package for the SEC 601 Air-Cooled Solar Collector		5. REPORT DATE February 1979	
		6. PERFORMING ORGANIZATION CODE	
7. AUTHOR(S)		8. PERFORMING ORGANIZATION REPORT #	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Owens-Illinois P.O. Box 1035 Toledo, Ohio 43666		10. WORK UNIT NO.	
		11. CONTRACT OR GRANT NO. NASA8-32259	
12. SPONSORING AGENCY NAME AND ADDRESS National Aeronautics and Space Administration Washington, D.C. 20546		13. TYPE OF REPORT & PERIOD COVERED Contractor Report	
		14. SPONSORING AGENCY CODE	
15. SUPPLEMENTARY NOTES This work was done under the technical management of Mr. John Caudle, George C. Marshall Space Flight Center, Alabama.			
16. ABSTRACT This document contains information used to evaluate the subsystem design of the Owens-Illinois Model SEC-601 Solar Collector. The collector is of modular design and is approximately 12 feet three inches wide and eight feet seven inches tall. It contains 72 collector tube elements and weighs approximately 300 pounds. Included in this report are the Subsystem Performance Specifications and the Assembly and Installation Drawings of the Solar Collectors and Manifold.			
17. KEY WORDS		18. DISTRIBUTION STATEMENT UC-59C Unclassified-Unlimited <i>William A. Brooksbank Jr</i> WILLIAM A. BROOKSBANK, JR. Mgr, Solar Energy Applications Office	
19. SECURITY CLASSIF. (of this report) Unclassified	20. SECURITY CLASSIF. (of this page) Unclassified	21. NO. OF PAGES 17	22. PRICE NTIS

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

MASTER

TABLE OF CONTENTS

I.	Subsystem Performance Specifications	I-1
II.	Assembly and Installation Drawings	II-1

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

leg

MASTER

OWENS-ILLINOIS
AIR COOLED THERMAL
SOLAR COLLECTOR

SUBSYSTEM PERFORMANCE SPECIFICATION
SHC-3060
Dated 8/11/78

Subsystem Performance Specification
SUNPAKTM Model SEC-601
Air Cooled Solar Thermal Collector

- 1.0 This performance specification establishes the requirements for the design and performance of the air cooled collector subsystem for use with solar combined heating and cooling systems. It designates the Interim Performance Criteria applicable to this collector subsystem.
- 2.0 The document applicable to this performance specification is the Interim Performance Criteria for Commercial Solar Heating and Combined Heating/Cooling Systems and Facilities, Document N. 98M10001, Revision Basic, date February 28, 1975. George C. Marshall Space Flight Center, National Aeronautics and Space Administration.
- 3.0 All of the applicable Interim Performance Criteria for Commercial Subsystems as outlined in Table II so indicated are applicable after completion of the development and testing of the air cooled collector subsystem as outlined in the Statement of Work.
- 4.0 No deviations from the Interim Performance Criteria are proposed.
- 5.0 No Government furnished property will be installed in the air cooled collector subsystem.
- 6.0 No specific requirements have been directed by the Contracting Officer.
- 7.0 Preliminary performance and installation specifications for the air cooled collector subsystem are attached.

SUBSYSTEM PERFORMANCE SPECIFICATION
OWENS-ILLINOIS

8.0 Warranty - Contractor warrants for a period of five years that the solar collector material will be free of defects in quality and workmanship. Warranty is limited to shipping replacement parts prepaid which in the contractor's opinion are required to correct such defects. No field labor is included, and in no event shall Contractor be liable for special or consequential damages.

TABLE II

SPECIFICATION NO. SHC-3060
 REVISION 3
 DATE June 27, 1977

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY							
APPLICATION				TYPE SYSTEMS			
A - APPLICABLE TO SYSTEMS INDICATED NA - NOT APPLICABLE				H - HEATING HC - HEATING AND COOLING HW - HOT WATER			
COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
1.1 H and HC System Performance	NA	NA	NA	1.6 Energy Transport	NA	NA	NA
1.1.1 Heating Design Temperature	NA	NA	NA	1.6.1 Thermal Losses and Electrical Power	NA	NA	NA
1.1.2 Cooling Design Temperature	NA	NA	NA	1.7 Control	NA	NA	NA
1.1.3 Relative Humidity	NA	NA	NA	1.7.1 Installation and Maintenance	NA	NA	NA
1.1.4 Solar Contribution	NA	NA	NA	1.7.2 Manual Adjustment	NA	NA	NA
1.2 HW System/Subsystem Performance	NA	NA	NA	1.7.3 Inhabited Space Temperature Control	NA	NA	NA
1.2.1 Draw and Temperature Design Output	NA	NA	NA	1.7.4 Hot Water Temperature	NA	NA	NA
1.2.2 Non-Tap Temperature Design Output	NA	NA	NA	1.8 Auxiliary Energy	NA	NA	NA
1.2.3 Solar Contribution	NA	NA	NA	1.8.1 Design Heat Loads	NA	NA	NA
1.3 Collector Performance	A	A	A	1.8.2 Design Cooling Loads	NA	NA	NA
1.3.1 Collector Efficiency	A	A	A	1.8.3 Impairment of Operation	NA	NA	NA
1.4 Thermal Storage Performance	NA	NA	NA	2.1 System Design Conditions	A	A	A
1.4.1 Storage Capacity and Rate	NA	NA	NA	2.1.1 Equipment Capabilities	A	A	A
1.5 Habitability of Occupied Spaces	NA	NA	NA	2.1.2 Noise or Erosion-Corrosion	A	A	A
1.5.1 Heat or Humidity Transfer Effects	NA	NA	NA	2.1.3 Operating Conditions	A	A	A
				2.1.4 Fluid Flow in Collectors	A	A	A
				2.1.5 Entrapped Air	NA	NA	NA
				2.1.6 Thermal Expansion of Fluids	NA	NA	NA
				2.1.7 Pressure Drops	A	A	A

TABLE II

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY

SHEET 2 OF 6

APPLICATION				TYPE SYSTEMS			
A - APPLICABLE TO SYSTEMS INDICATED NA - NOT APPLICABLE				H - HEATING HC - HEATING AND COOLING HW - HOT WATER			
COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
2.1.8 Condensate Removal	NA	NA	NA	2.6.2 Air Quality	A	A	A
2.2 Mechanical Stresses	A	A	A	2.6.3 Fluid Treatment	NA	NA	NA
2.2.1 Vibration Stress Levels	A	A	A	2.6.4 Freezing Protection	NA	NA	NA
2.2.2 Vibration from Moving Parts	A	A	A	2.7 Piping Supports	NA	NA	NA
2.2.3 Water Hammer	NA	NA	NA	2.7.1 Applicable Plumbing Standards	NA	NA	NA
2.2.4 Vacuum Relief Protection	A	A	A	2.8 Excessive Pressure and Temperature Protection	NA	NA	NA
2.2.5 Thermal Changes	A	A	A	2.8.1 Relief Valves and Vents	NA	NA	NA
2.2.6 Flexible Joints	A	A	A	3.1 Structural Design Basis	A	A	A
2.3 Leakage Prevention	A	A	A	3.1.1 Service Loads	A	A	A
2.3.1 Pressure Test: Non-Potable Fluids	A	A	A	3.2 Failure Loads and Load Capacity	A	A	A
2.3.2 Pressure Test: Potable Water	A	A	A	3.2.1 Ultimate Load Combinations	A	A	A
2.3.3 Air Transport System	A	A	A	3.2.2 Ice Loads	A	A	A
2.4 Collector Adjustments	A	A	A	3.2.3 Vehicular Loads	NA	NA	NA
2.4.1 Orientation and Tilt	A	A	A	3.2.4 Load Capacity	A	A	A
2.4.2 Mutual Shadowing	A	A	A	3.3 Damage Control	A	A	A
2.5 Subsystem Isolation	NA	NA	NA	3.3.1 Resistance to Damage	A	A	A
2.5.1 Shutdown in Multi-unit Facilities	NA	NA	NA	3.4 Cyclic Loads	A	A	A
2.6 Heat Transfer Fluid Quality	A	A	A	3.4.1 Deflection Limitations	A	A	A
				3.5 Cutting of Structural Elements	NA	NA	NA
				3.5.1 Design Provisions	NA	NA	NA

TABLE II

SPECIFICATION NO. SHC-3060REVISION 3DATE June 27, 1977

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY

SHEET 3 OF 6APPLICATION

A APPLICABLE TO SYSTEMS INDICATED

NA NOT APPLICABLE

TYPE SYSTEMS

H HEATING

HC HEATING AND COOLING

HW HOT WATER

COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
3.6 Creep and Residual Deflection	A	A	A	4.3.2 Penetrations Through Fire-Rated Assemblies	NA	NA	NA
3.6.1 Deflection Limitations	A	A	A	4.4 Toxic and Flammable Fluids	NA	NA	NA
3.7 Hail Resistance	A	A	A	4.4.1 Provision of Catch Basins	NA	NA	NA
3.7.1 Hail Size and Loading	A	A	A	4.4.2 Detection of Toxic and Flammable Fluids	NA	NA	NA
3.8 Constraint Loads	A	A	A	4.5 Safety Under Emergency Conditions	NA	NA	NA
3.8.1 Foundation Settlement	A	A	A	4.5.1 Emergency Egress and Access	NA	NA	NA
3.9 Ponding Conditions	A	A	A	4.5.2 Identification and Location of Controls	NA	NA	NA
3.9.1 Design Provisions	A	A	A	4.6 Protection of Water and Circulated Air	A	A	A
4.1 Plumbing and Electrical Installation	NA	NA	NA	4.6.1 Contamination by Materials	NA	NA	NA
4.1.1 Plumbing Codes and Standards	NA	NA	NA	4.6.2 Separation of Circulation Loops	NA	NA	NA
4.1.2 Electrical Codes and Standards	NA	NA	NA	4.6.3 Backflow Prevention	NA	NA	NA
4.2 Fail-Safe Controls	A	A	A	4.6.4 Growth of Fungi	A	A	A
4.2.1 System Failure Prevention	A	A	A	4.7 Excessive Surface Temperature	A	A	A
4.2.2 Automatic Pressure Relief Valves	NA	NA	NA	4.7.1 Protection from Heated Components	A	A	A
4.3 Fire Safety	A	A	A	5.1 Effects of External Environment	A	A	A
4.3.1 Applicable Fire Standards	A	A	A	5.1.1 Solar Degradation	A	A	A
				5.1.2 Soil Corrosion	NA	NA	NA
				5.1.3 Airborne Pollutants	A	A	A

TABLE II

SPECIFICATION NO. SHC-3060
 REVISION 3
 DATE June 27, 1977

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY

SHEET 1 of 6

APPLICATION

A APPLICABLE TO SYSTEMS INDICATED
 NA NOT APPLICABLE

TYPE SYSTEMS

H HEATING
 HC HEATING AND COOLING
 HW HOT WATER

COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
5.1.4 Dirt Retention on Cover Plate Surfaces	A	A	A	5.4 Components Involving Moving Parts	NA	NA	NA
5.1.5 Abrasive Wear	A	A	A	5.4.1 Wear and Fatigue	NA	NA	NA
5.1.6 Fluttering by Wind	A	A	A	6.1 Accessibility for Maintenance and Servicing	A	A	A
5.2 Temperature and Pressure Resistance	A	A	A	6.1.1 Access for System Maintenance	A	A	A
5.2.1 Thermal Degradation	A	A	A	6.1.2 Access for System Monitoring	A	A	A
5.2.2 Deterioration of Heat Transfer Fluids	NA	NA	NA	6.1.3 Draining and Filling of Liquids	NA	NA	NA
5.2.3 Thermal Cycling Stresses	A	A	A	6.1.4 Flushing of Liquid Subsystems	NA	NA	NA
5.2.4 Leakage	NA	NA	NA	6.1.5 Filters	NA	NA	NA
5.2.5 Deterioration of Gaskets and Sealants	A	A	A	6.1.6 Water Shutoff	NA	NA	NA
5.2.6 Transmission of Losses Due to Out- glassing	A	A	A	6.2 Installation, Operation and Maintenance Manual	A	A	A
5.3 Chemical Compa- tibility of Components	A	A	A	6.2.1 Installation Instructions	A	A	A
5.3.1 Materials/Trans- fer Fluid Compatibility	A	A	A	6.2.2 Maintenance and Oper- ating Instructions	A	A	A
5.3.2 Corrosion of Dis- similar Materials	A	A	A	6.2.3 Maintenance Plan	A	A	A
5.3.3 Corrosion by Leachable Substances	NA	NA	NA	6.2.4 Replacement Parts	A	A	A
5.3.4 Effects of Deco- mposition Products	A	A	A	6.3 Repair and Service Personnel	A	A	A
				6.3.1 Servicing of H and HC Systems	A	A	A
				6.3.2 Servicing of HW Systems	A	A	A
				7.1 Design	NA	NA	NA

TABLE II

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY

SHEET 5 OF 6APPLICATION

A APPLICABLE TO SYSTEMS INDICATED

NA NOT APPLICABLE

TYPE SYSTEMS

H HEATING

HC HEATING AND COOLING

HW HOT WATER

COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
7.1.1 Design-Habit- able Facilities	NA	NA	NA	8.1.3 Sensor Location	NA	NA	NA
7.1.2 Esthetics	NA	NA	NA	8.2 Mechanical and Elec- trical Functioning of Facility and Site	NA	NA	NA
7.1.3 Materials				8.2.1 Exhaust and Venting	NA	NA	NA
7.1.4 Passive Use of Solar Energy	NA	NA	NA	8.2.2 Utilities	NA	NA	NA
7.2 Adequate Space	NA	NA	NA	8.3 Mechanical and Elec- trical Functioning of Connections	NA	NA	NA
7.2.1 Solar Collector	NA	NA	NA	8.3.1 Plumbing Connections	NA	NA	NA
7.2.2 Storage	NA	NA	NA	8.3.2 Electrical Connections	NA	NA	NA
7.2.3 Interface Bet- ween Facility and H and HC Systems				8.3.3 Lightning Protection	NA	NA	NA
7.2.4 Portability	NA	NA	NA	9.1 Structural Integrity of H, HC and HW Systems	NA	NA	NA
7.3 Functioning of Facilities and Sites	NA	NA	NA	9.1.1 Movement of Adjacent Structures	NA	NA	NA
7.3.1 Space Use	NA	NA	NA	9.2 Structural Integrity of Facilities	NA	NA	NA
7.3.2 Shading	NA	NA	NA	9.2.1 Loads	NA	NA	NA
7.3.3 Impact on En- vironment	NA	NA	NA	9.2.2 Penetration of Struc- tural Members	NA	NA	NA
7.3.4 View	NA	NA	NA	9.3 Structural Connections	NA	NA	NA
7.4 Compatibility with Conventional Systems	NA	NA	NA	9.3.1 Structural Connections	NA	NA	NA
7.4.1 Utility Compati- bility	NA	NA	NA	9.3.2 Brittle Components	NA	NA	NA
8.1 Interference with Mechanical Operation	NA	NA	NA	9.3.3 Strength and Stiffness	NA	NA	NA
8.1.1 Blockage of Solar Solar Components	NA	NA	NA	10.1 Safety of Facility and Site	NA	NA	NA
8.1.2 Shading of Collec- tors	NA	NA	NA	10.1.1 Fire	NA	NA	NA
				10.1.2 Accidents	NA	NA	NA

TABLE II

COMMERCIAL SUBSYSTEMS, INTERIM PERFORMANCE CRITERIA SUMMARY							
APPLICATION				TYPE SYSTEMS			
A APPLICABLE TO SYSTEMS INDICATED				H HEATING			
NA NOT APPLICABLE				HC HEATING AND COOLING			
				HW HOT WATER			
COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS			COMMERCIAL INTERIM PERFORMANCE CRITERIA PARAGRAPH	TYPE SYSTEMS		
	H	HC	HW		H	HC	HW
11.1 Durability and Reliability of H, HC and HW Systems	NA	NA	NA	12.3.1 Accessibility	NA	NA	NA
11.1.1 Vegetation	NA	NA	NA	13.1 Visual Characteristics of Facility and Site	NA	NA	NA
11.2 Durability and Reliability of Facili- ties and Sites	NA	NA	NA	13.1.1 Facility	NA	NA	NA
11.2.1 Chemical Corrosion	A	A	A	13.1.2 Neighborhood	NA	NA	NA
11.2.2 Heat and Moisture	A	A	A				
11.2.3 Exterior Pene- trations	NA	NA	NA				
11.3 Durability and Reliability of Connec- tions	A	A	A				
11.3.1 Material Com- patibility	A	A	A				
12.1 Maintainability of H, HC and HW Systems	NA	NA	NA				
12.1.1 Accessibility	NA	NA	NA				
12.1.2 Misuse	NA	NA	NA				
12.1.3 Permanent Main- tenance Accessories	NA	NA	NA				
12.2 Maintainability of Facility and Site	NA	NA	NA				
12.2.1 Accessibility	NA	NA	NA				
12.2.2 Ice Dams	NA	NA	NA				
12.3 Connections	NA	NA	NA				

Spec. No. SHC-3060
Revision 5
Date 8/11/78

Air Cooled Collector Performance

The Owens-Illinois Solar Collector Model SEC 601 will collect a minimum of 1050 Btu/ft.² day of energy at an inlet fluid temperature equal to or less than 160° and an air flow rate equal to or greater than 2 SCFM/ft.² under the following conditions:

Tilt Angle: Equal to latitude; Azimuth Angle: 0°

Ambient Temperature: 30°F

Wind Velocity: 0-5000 ft./min.

Date: March, September 21

Daily Solar Flux in the Plane of the Collector Surface: 2330 Btu/ft.² day.

Longitude: Any; Latitude: Any

The Solar Collector will collect a minimum of 900 Btu/ft.² day of energy at an inlet fluid temperature equal to or less than 220°F and an air flow rate equal to or greater than 2 SCFM/ft.² under the following conditions:

Tilt Angle: Equal to latitude; Azimuth Angle: 0°

Ambient Temperature: 50°F

Wind Velocity: 0-5000 ft./min.

Date: March, September 21

Daily Solar Flux in the Plane of Collector Surface: 2330 Btu/ft.² day.

Longitude: Any; Latitude: Any

$$n = \frac{MC_p(T_o - T_i)}{A_c \bar{I}}$$

T_o = collector transport media hourly average outlet temperature (°F)

T_i = collector transport media hourly average inlet temperature (°F)

T_a = average hourly ambient temperature (°F)

M = transport media hourly average flow rate (lb./hr.)

C_p = specific heat of transport media (Btu/lb.°F)

A_c = area of collector (sq. ft.) (based on aperture area)

$\bar{I}$ = hourly average total solar insolation in the collector plane (Btu/hr. - sq. ft.)

NOTE: The data utilized to obtain the hourly averages must be for at least one full day.

I-11

FIGURE 1 - EFFICIENCY AS A FUNCTION OF OPERATING CONDITIONS
PERFORMANCE MUST BE ABOVE LINE

ASSEMBLY AND INSTALLATION DRAWINGS

SK-5076-Manifold Assembly, Complete

SK-5075-Solar Collector Installation

Note: Drawings of the detail parts called out on each of the above drawings may be obtained from Owens-Illinois, P.O. Box 1035, Toledo, Ohio 43666.

SK-5075

"INFORMATION CONTAINED HEREIN CONSTITUTES
PROPRIETARY CONFIDENTIAL INFORMATION OF
OWENS-ILLINOIS, AND IS ACCEPTED ONLY SUBJECT TO
THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL
AND NOT COPIED, USED, OR CONVEYED TO OTHERS
WITHOUT OWENS-ILLINOIS' WRITTEN AUTHORIZATION."

TOLERANCE UNLESS OTHERWISE NOTED	2 PLACE DEC. ±	3 PLACE DEC. ±	ANGLES ±	CORNERS AND/OR EDGES BROKEN	OUTSIDE RAD. MAX.	INSIDE RAD. MAX.	RADI UNLESS OTHERWISE NOTED	DEFINITION OF SYMBOLS (Total Indicator Reading)	SCALE NOTED INCHES	MATERIAL	HEAT TREAT	CASE DEPTH	HARDNESS	SUR TREAT
								CONCENTRICITY						
								ROUNDNESS						
								FLATNESS						
								SYMMETRY						
								PARALLEL						
								PERPENDICULAR						

PROJECT NO.		DES'D	9/28/77	DR'N	1/1	CK'D	1/1
C-2370		SOLAR COLLECTOR MODEL		SEC-601		NUMBER	
SK-5075		SHEET		1 OF 1		SIZE	
D

TOLERANCE UNLESS OTHERWISE NOTED	2 PLACE DEC. ±	3 PLACE DEC. ±	ANGLES ±	CORNERS AND/OR EDGES BROKEN	OUTSIDE RAD.	INSIDE RAD.	UNLESS SPECIFIED, MACHINED SURFACE ROUGHNESS NOT TO EXCEED	DEFINITION OF SYMBOLS (Total Indicator Reading)	SCALE NO	SCALE	MATERIAL	HEAT TREAT	CASE DEPTH	SUR. TREAT
								CONCENTRICITY						
								ROUNDNESS						
								FLATNESS						
								SYMMETRY						
								PARALLEL						
								PERPENDICULAR						

OWENS-ILLINOIS

 CORPORATE TECHNOLOGY

 TOLEDO, OHIO

CHG.	DESCRIPTION	BY	DATE	MF
1	USED ON ASSEMBLY NO. SK 5075			
PROJECT NO. C-2370				
DESIGNER: DRN, 9/14/77, GEM				
CHECKER: CK'D, 9/14/77, GEM				
MANIFOLD ASSEM. COMPLETE				
NUMBER SK-5076				
SHEET 1 OF 1				
D				