Derivative Classifier D. B. Moore

WSRC-TR-91-87

Received by OSTI
MAR 19 1992

PEN BRANCH FAULT PROGRAM: CONSOLIDATED REPORT ON THE
SEISMIC REFLECTION SURVEYS AND THE SHALLOW DRILLING (U)

A. L. Stieve, D. E. Stephenson, R. K. Aadland

March 28, 1991

Authentication: Alice L. Stieve

Approved by: D. B. Moore
D. B. Moore, Manager
Environmental Sciences Section
Savannah River Laboratory

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
Aiken, South Carolina 29808

Prepared for the U. S. Department of Energy under
Contract No. DE-AC09-89SR18035

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Executive Summary

The Pen Branch fault was identified in the subsurface at the Savannah River Site (SRS) in 1989 based upon interpretation of earlier seismic reflection surveys and other geologic investigations. A program of drilling and high resolution shallow seismic reflection lines was initiated to determine the capability of the fault to release seismic energy as defined in the Nuclear Regulatory Commission regulatory guidelines, 10 CFR 100 Appendix A. The results presented herein are based upon the Conoco standard seismic reflection, EMEX high-resolution shallow seismic reflection, and the shallow drilling program (PBF well series) that includes lithologic and geophysical logs.

The Pen Branch fault is considered to be a continuation of the northern boundary fault of the Triassic Dunbarton basin and was interpreted as being at least a Cretaceous/Tertiary reactivation of that fault. The fault dips steeply to the southeast and the displacement at the basement/Coastal Plain interface ranges from about 85 feet to about 30 feet along the trace of the fault.

The Earth Science Advisory Committee (ESAC) has reviewed the results of these investigations and unanimously agrees with the conclusion of WSRC that all data indicate that the Pen Branch fault is a non-capable fault. Supporting observations include:

1. There are flat-lying undeformed layers in the shallow portion of the Coastal Plain Section in both the geophysical and stratigraphic data. This indicates that the fault is not expressed at the surface.
2. The Upland unconformity is an essentially flat-lying surface that is undeformed and overlies any deformation seen in the stratigraphic sections. This surface is at least 5 million years old. Therefore, deformation related to the fault must be greater than 5 million years and falls outside the criteria that define a capable fault in terms of age. The Upland unconformity is not identified on the seismic sections.
3. The seismic reflection profiles show offset layers of the fault at depth (standard seismic data) and deformed layers over the fault decreasing in amplitude upward toward the surface (standard and high-resolution seismic data). The deformed layers could be the result of tectonic folding or the result of passive sedimentation over a pre-existing structure or a fault scarp. In either case, deformation ceases within a few hundred feet of the surface.
4. The amount of dip reversal observed in these data, attributed to deformation by the fault is small and occurs in a geologic section covering a time span of over 100 million years. This implies a slow deformation rate that further implies either slow, possibly aseismic, movement over a period of 100 million years or an event driven mechanism with a long recurrence interval.

There are several newly proposed investigations that will extend the geologic and seismologic data base at SRS. These proposals tie in with the Pen Branch Fault Program and other seismologic programs currently underway.

A field investigation of the Upland unit and the Upland unconformity will be initiated this spring . This study will address the suggestions presented by the ESAC review. The study will include surface and subsurface geologic investigations and surface geophysical investigations. An additional drilling program will start this summer to confirm reflectors observed in the high-resolution shallow seismic reflection profiles to lithologic layers or unconformities.

TABLE OF CONTENTS

1. INTRODUCTION.....	1
2. GEOLOGY AT SRS.....	1
3. SHALLOW DRILLING FOR THE PEN BRANCH FAULT.....	2
3.1. Purpose and Scope of Work.....	2
3.2. Conclusions of the Shallow Drilling.....	2
3.4. Coastal Plain Stratigraphy.....	4
3.4.1. Cape Fear Formation.....	4
3.4.2. Lumbee Group.....	4
3.4.3. Black Mingo Group.....	5
3.4.4. Orangeburg Group.....	6
3.4.5. Barnwell Group.....	7
3.4.6. Upland Unit.....	8
3.5. Methods and Materials.....	9
4. DEEP SEISMIC REFLECTION SURVEY.....	11
4.1. Purpose and Scope of Work.....	11
4.2. Conclusions of the Deep Seismic Reflection Survey.....	11
4.3. Interpretation.....	12
4.3.1. Basement Reflector.....	12
4.3.2. Structural Configuration of Basement Blocks.....	13
4.3.4. Structure Within and Below the Triassic Basin.....	14
4.4. Data Acquisition.....	14
4.5. Processing.....	15
5. HIGH-RESOLUTION, SHALLOW SEISMIC REFLECTION SURVEY (1990-1991).....	16
5.1. Purpose and Scope.....	16
5.2. Results of the High-Resolution, Shallow Seismic Reflection Survey.....	16
5.3. Associated Seismic Reflection Data.....	17
5.4. Production Lines.....	17
5.4.1. Line 6.....	18
5.4.2. Line 12.....	18
5.4.3. Line 14.....	19
5.4.4. Line 15.....	20
5.5. Field Acquisition.....	20
5.6. Processing.....	21
7. CONCLUSIONS BASED ON THE PRESENTLY AVAILABLE DATA.....	22
8. PATH FORWARD.....	22
9. REFERENCES.....	23

List of Figures

Figure 1. Location of Pen Branch fault (PBF) at SRS with the PBF drill hole series indicated on either side of the fault.

Figure 2. Stratigraphic column for SRS.

Figure 3. Location map for geologic cross-sections.

Figure 4. Location of seismic reflection lines (Conoco, 1887-1988).

Figure 5. Location map of the Pen Branch fault and other basement faults identified in the Conoco seismic reflection survey (1987-1988).

Figure 6. Diagram for the interpreted crustal blocks in the basement terranes at SRS based on seismic reflection, gravity and magnetic data.

Figure 7. Location map of high-resolution shallow seismic reflection survey completed by EMEX (1990-1991) at SRS.

Figure 8. Location map of seismic reflection survey conducted by Seismograph Service Cooperation, 1969.

Figure 9. Portion of Conoco seismic line 3 that shows the Pen Branch fault.

Figure 10. Interpretation diagram for line 6

Figure 11. Interpretation diagram for line 12.

Figure 12. Interpretation diagram for line 14.

Figure 13. Interpretation diagram for line 15.

Insert 1a. Detailed lithostratigraphic correlation chart, wells PBF-4 and 5; PBF-3 and 7 and 8; PBF-1 and 2.

Insert 1b True scale lithostratigraphic correlation chart, wells PBF-3 and 7&8

Insert 2. Geophysical log and core data display, PBF-5

Insert 3. Regional hydrostratigraphic cross-section A-A'

Insert 4. Regional hydrostratigraphic cross-section B-B'

Insert 5. PBF cross-section A-A'

Insert 6. PBF cross-section B-B'

Insert 7. PBF cross-section C-C'

Insert 8. PBF cross-section D-D'

Insert 9. Conoco seismic reflection Line 1.

Insert 10. Conoco seismic reflection Line 2.

Insert 11. Conoco seismic reflection Line 3.

Insert 12. Conoco seismic reflection Line 29.

Insert 13. Deep seismic reflection along Conoco seismic reflection Line 1.

Insert 14. EMEX seismic reflection line 6.

Insert 15. EMEX seismic reflection line 12.

Insert 16. EMEX seismic reflection line 14.

Insert 17. EMEX seismic reflection line 15.

1. INTRODUCTION

The Pen Branch fault (Figure 1) was identified in the subsurface at the Savannah River Site (SRS) in 1989 based upon interpretation of earlier seismic reflection surveys and other geologic investigations (Seismograph Services Incorp., 1973; Chapman and DiStefano, 1989; Snipes, Fallaw and Price, 1989). A program was initiated at that time to determine the capability of the fault to release seismic energy (Price and others, 1989) as defined in the Nuclear Regulatory Commission regulatory guidelines, 10 CFR 100 Appendix A. This report presents the results of the Pen Branch fault investigation based on data acquired from seismic reflection surveys and shallow drilling across the fault completed at this time. The Earth Science Advisory Committee (ESAC) has reviewed the results of these investigations and unanimously agrees with the conclusion of WSRC that the Pen Branch fault is a non-capable fault. ESAC is a committee of 12 earth science professionals from academia and industry with the charter of providing outside peer review of SRS geotechnical, seismic, and ground water modeling programs.

2. GEOLOGY AT SRS

The SRS is located on the Atlantic Coastal Plain, which is an essentially flat-lying, undeformed wedge of unconsolidated marine and fluvial sediments. The sediments are stratified sand, clay, limestone, and gravel that dip gently seaward and range in age from Late Cretaceous to Recent. The sedimentary sequence thickens from zero at the Fall Line to more than 4,000 feet at the coast. There are about 600 to 1,200 feet of Coastal Plain sediments at SRS. The Coastal Plain section is divided into several groups based principally on age and lithology (Figure 2).

Beneath the Coastal Plain sedimentary sequence, below a pre-Cretaceous unconformity, are two geologic terranes; 1) a Triassic-Jurassic rift basin, the Dunbarton basin, filled with lithified terrigenous and lacustrine sediments with minor amounts of mafic volcanic and intrusive rock (Marine, 1974a and b; Marine and Siple, 1974) and 2) a crystalline terrane of metamorphosed sedimentary and igneous rock that may range in age from Precambrian to late Paleozoic. The Paleozoic rocks and the Triassic sediments were leveled by erosion, forming the base for Coastal Plain sediment deposition. The erosional surface dips approximately 41 feet per mile toward the southeast.

The Dunbarton basin has been the subject of intense investigation since Siple (1967) identified the basin from aeromagnetic and well data. Subsequent seismic reflection surveys and additional well data were described by Marine (1974a and b), and Marine and Siple (1974). The structure was interpreted as an asymmetric graben approximately 50 kilometers long and 10 to 15 kilometers wide with normal faults to the northwest and southeast. Additional investigations conducted at the SRS from 1985 to 1989 have focused on the Dunbarton Basin in an attempt to determine its association with two microearthquakes that occurred at

Figure 1. Location of Pen Branch fault at SRS with PBF series shallow coring locations shown as large filled circles. Two other possible north-south trending faults are thought to intersect the Pen Branch fault.

North American Stage	European Stage	Groups	Formations	
AgeUnknown	AgeUnknown	Barnwell Group	"Upland Unit"	
Jacksonian	Priabonian		Tobacco Road Sand	
			Dry Branch Formation	Irwinton Sand Mbr Twiggs Clay Mbr Griffins Landing Mbr
			Clinchfield Formation	
Claibornian	Bartonian	Orangeburg Group	Santee Limestone	McBean Member Caw Caw Member Warley Hill Member
	Lutetian		Congaree Formation	
Sabinian	Ypresian	BlackMingo Group	Four Mile Mbr Fishburne Fm	
Midwayan	Thanetian		Snapp Mbr Williamsburg Fm	
	Danian		Ellenton Member Rhens Formation	
Navarroan	Maestrichtian	Lumbee Group	Steel Creek Member Peedee Formation	
Taloran	Campanian		Black Creek Formation	
Austinian	Santonian		Middendorf Formation	
	— ? — Coniacian ? Turonian ?			Cape Fear Formation

Note: Modified from Aadland and Bledsoe (1990)

Figure 2. Stratigraphic column for SRS.

the site in 1985 (Local magnitude: 2.6, Talwani and others, 1985) and in 1988 (Local Magnitude: 2.0, Stephenson, 1988).

Geometric and kinematic arguments suggest that early Mesozoic normal faults may be reactivated Alleghanian thrust faults (Peterson and others, 1984; Crespi, 1986; Hutchinson and Klitgord, 1986). Studies of the exposed and buried rift basins show that the faults controlling basin formation are complex, with border faults of variable dip, antithetic faults of variable magnitude, and cross or transfer faults that fragment the basin into sub-basins.

The Pen Branch fault constitutes a possible continuation of the northern boundary fault of the Triassic Dunbarton basin and is interpreted as being a Cretaceous/Tertiary reactivation of that fault. In other words, renewed faulting during Cretaceous into Tertiary time resulted in the formation of the Pen Branch fault in the Coastal Plain sediments covering the basement rock. The fault dips steeply to the southeast. In the crystalline basement, slip direction was originally down to the southeast resulting in the formation of the Dunbarton rift basin. However, movement during Cretaceous into Tertiary time appears to be reverse movement, that is, up to the southeast (Stephenson and Chapman, 1988). There could also be a component of strike-slip movement (Stephenson and others, 1985).

3. SHALLOW DRILLING FOR THE PEN BRANCH FAULT

3.1. Purpose and Scope of Work

Eight PBF series wells were drilled along the projected trace of the Pen Branch fault (Figure 1 and 3). The wells were drilled as pairs to straddle the fault trace on both the up-thrown and down-thrown sides. Insert 1a includes correlated cross-sections of the three pairs of PBF wells (1 and 2; 4 and 5; 3 and 7&8) that were used in the present study. Insert 1b is a 2:1 vertical scaled cross-section between PBF wells 3, 7&8 which illustrates the subtlety of the displacement observed across the fault trace. The detailed analysis and synthesis of the lithostratigraphic data derived from the PBF wells were used to determine structural relationships in the Cretaceous-Tertiary section resulting from movement on the fault. The stratigraphic and structural relationships derived from the PBF well data were placed in the regional geologic framework with data from the surrounding "P" wells (Inserts 3,4,5,6,7,8), which were installed throughout SRS as part of the site-wide hydrologic investigation (Bledsoe, Aadland and Sargent, 1990).

3.2. Conclusions of the Shallow Drilling

1. Examination and correlation of core and geophysical logs indicate that the uppermost portion of the Coastal Plain section is undeformed at least to and including the Upland unconformity. This unconformity is at least 5 million years old.
2. Between each of the PBF well pairs that straddle the Pen Branch fault there are north dipping horizons (dip reversal), whereas regional dip is to the southeast.

C-3

The north dip observed in the Coastal Plain section from the basement up to and including the Congaree Formation and the overlying Caw Caw Member ("Green Clay") of the Santee Limestone is unequivocal. The presence of north dipping horizons is less certain in the overlying Tobacco Road Sand of the Barnwell Group.

3. The "Upland" unit which rests unconformably on the Tobacco Road Formation has not been involved in the deformation observed in the underlying formations. Surface exposures of the "Upland" unit as well as core and electric log data from wells penetrating the unit indicate no deformation has occurred in this unit.

4. The age and timing of deformation observed in the Barnwell Group and older sediments predates the age of the "Upland" (Miocene) and must have occurred in the time frame prior to Late Miocene time but after Late Eocene time, between 5 and 36 million years before the present.

3.3. Discussion

The sediments penetrated in the PBF and "P" wells are typical of the Atlantic Coastal Plain sequence in South Carolina. The sequence includes stratified sand, clay, limestone, and gravel beds that dip gently seaward; it ranges in age from Late Cretaceous to Recent. At the SRS, the basement surface dips approximately 40 feet/mile from the northwest to the southeast across the site, while the dip rate at the Cretaceous-Tertiary contact is approximately 21 feet/mile and 12 feet/mile at the top of the Orangeburg Group.

The PBF wells that straddle the trace of the Pen Branch fault were analyzed in conjunction with the surrounding "P" wells and placed in the overall regional stratigraphic context. Inserts 5,6,7 and 8, illustrate the lithostratigraphy of the PBF wells in the context of the nearby "P" wells. The correlations established north dip (dip reversal) between each of the pairs of PBF wells (Inserts 1a,1b,2). Each of the PBF wells on the south side (up-thrown side) of the Pen Branch fault trace (PBF-2,5,7 and 8) proved to be 40 to 50 feet structurally high to the paired wells on the north side (down-thrown side) of the fault trace. The north dip is unequivocal in the section up to and including the Santee Formation of the Orangeburg Group (Fig 2). North dip is apparent but equivocal in the overlying Tobacco Road Sand of the Barnwell Group. Here the stratigraphic section is not as laterally continuous as in the underlying Orangeburg Group and correlations are more ambiguous.

The "Upland" unit which overlies the Late Eocene Barnwell Group is flat lying in the area of the PBF wells and does not exhibit the north dip observed in the underlying section (Inserts 1a,1b,2,5,6,7 and 8). The unit rests unconformably on the partially eroded upper surface of the Tobacco Road Sand of the Barnwell Group. Analysis of the "Upland unit" indicates that it has not been involved in the deformation observed in the underlying section. Therefore, the age and timing of deformation observed in the Barnwell Group and older sediments predates the age of the "Upland unit" (Miocene) and must have occurred in the time frame prior to Late Miocene time but after Late Eocene time, between about 5 and 36 million years before the present.

The north dip observed in the section below the "Upland" is subtle (Insert 1b). At the upper contact of the Congaree Formation the north dip measures about 45 feet/mile between PBF wells 1 and 2; 32 feet/mile between PBF wells 4 and 5; and 33 feet/mile between PBF wells 3 and 7&8. The regional south dip at the Cretaceous-Tertiary contact is about 21 feet/mile for comparison.

Prior to the current study, the observed north dip was attributed to offset of the sediments involved in the dip reversal to displacement on the Pen Branch fault. However, the shallow high resolution seismic data developed in the current study have constrained the offset on the Pen Branch fault to the lower portion of the Cretaceous section (Cape Fear Formation and possibly the Middendorf Formation) at depths below approximately 800 feet. The north dip observed in the overlying section is therefore attributed to tectonic draping of the unconsolidated Coastal Plain sediments over the displaced section. This constrains the age of the faulting to the youngest sediments involved in the draping over the deep seated structure namely the late Eocene aged Tobacco Road Formation (older than 35 million years old).

3.4. Coastal Plain Stratigraphy

Numerous stratigraphic studies have been undertaken to delineate and define the stratigraphic sequence in the SRS region. Among the more important studies are those of Sloan (1908), Veatch and Stephenson (1911), Cooke and Shearer (1918), Cooke (1936), Cooke and MacNeil (1952), Siple (1967), Huddlestun (1982), Nystrom and Willoughby (1982), Colquhoun and others. (1983), Colquhoun and Steele (1985), Prowell and others (1985a), Prowell and others (1985b), Huddlestun and Hetrick (1979, 1985), Steele and Colquhoun (1985), and Nystrom and others (1986). The relative age and environments of deposition of the Cretaceous-Tertiary sequence in the site region have been established by (1) the lithologic data, (2) the analysis of sedimentary features and (3) extensive paleontological data retrieved from many cores collected at SRS. Figure 2 illustrates the lithostratigraphic classification of the Tertiary-Cretaceous sequence at SRS.

3.4.1. Cape Fear Formation.

The Cape Fear Formation is the basal Cretaceous unit at the SRS and is composed of poorly sorted, silty-to-clayey quartz sand and interbedded clay. The Cape Fear Formation sediments are more indurated than the overlying Cretaceous formations because of their high clay content and abundance of cristobalite in the matrix. The environment of deposition has been interpreted as upper delta plain (Prowell and others, 1985a). The unit is more than 150 feet thick near the center of SRS.

3.4.2. Lumbee Group.

The Lumbee Group overlies the Cape Fear Formation and comprises, from oldest to youngest, the Middendorf, the Black Creek, and the Pee Dee Formations (Inserts 1&2). These Cretaceous formations have been referred to as the "Tuscaloosa Formation" in past SRS studies.

In general, the Lumbee Group deposits are variably colored sand and clay that become calcareous downdip from the SRS. Thickness of the group varies across the site from 380 feet in the northwestern part of the SRS to more than 740 feet near the southeastern boundary. The dip of the upper surface of the Lumbee Group strata is to the southeast at approximately 21 feet/mile across the SRS.

Middendorf Formation. The Middendorf Formation, the basal formation of the Lumbee Group, is composed mostly of quartz sand, and unconformably overlies the Cape Fear Formation with a sharp, distinct contact (Inserts 1&2). The sediments of the Middendorf Formation at the SRS probably were deposited in fluvial and deltaic environments. The formation varies from approximately 130 feet thick to 180 feet thick southeast across the site. The Middendorf has been assigned a late Austinian (late Santonian) age in the SRS area (Prowell and others, 1985a).

Black Creek Formation. The Black Creek Formation unconformably overlies the Middendorf Formation. The formation distinctly onlaps over the Middendorf erosional surface from southeast to northwest (Inserts 3&5). The truncated Cretaceous section observed at the Middendorf-Black Creek contact in the PBF 3,7&8 wells (Insert 1) reflects the relative up-dip position of the three wells compared to the other PBF well pairs.

The Black Creek consists of quartz sand, silt and clay. It is generally darker, more micaceous, and lignitic than the other Cretaceous units. The middle portion of the formation is mostly shale, while the upper section consists of silty micaceous sand in much of the SRS area. In the northwestern part of the SRS however, the lower portion of the Black Creek Formation is mostly light colored.

Lithofacies suggest a lower deltaic plain environment for the Black Creek Formation except for the light-colored sand in the northwestern part of the SRS. Here the lithofacies suggests an upper delta plain environment. The Black Creek Formation is about 110 feet thick at the northwestern boundary of the SRS (Prowell and others, 1985a), and thickens to more than 250 feet near the southeastern boundary. The unit in South Carolina is assigned a Taylorian and Early Navarroan (Campanian and Early Maastrichtian) age.

Peedee Formation. The Peedee Formation is composed of light-colored sand and highly colored clay. The lower part of the unit is sandy with a pebble-rich zone at its base suggesting a basal unconformity. The upper part of the unit is clay-rich and varies from less than 3 feet to more than 50 feet in thickness. Fining upward sands are interbedded with clay in some areas. Lithofacies suggest an upper delta plain environment in the northwest portion of the SRS and a lower delta plain in the southeast. Dinoflagellates indicate some marine influence in parts of the unit. The Peedee is about 110 feet thick at the northwestern SRS boundary and 130 feet thick at the southeastern boundary. The Peedee Formation in South Carolina is middle and late Navarroan (middle and late Maastrichtian) in age (Prowell and others, 1985a).

3.4.3. Black Mingo Group.

In southwestern South Carolina, the Black Mingo Group consists of the Midwayan (Danian-early Thanetian/early Paleocene) Rhems Formation, the early and middle Sabinian (middle Thanetian/late Paleocene) Williamsburg Formation (Colquhoun and others., 1983), and the late Sabinian (late Thanetian/early Eocene) Fishburne Formation (Gohn and others, 1983). These units, with the possible exception of the Fishburne, have been traced updip in the subsurface from their type localities in the lower Coastal Plain of South Carolina to the SRS. The upper surface of the group dips to the southeast at approximately 15 feet/mile; the group is about 70 feet thick at the northwestern site boundary and thickens to about 150 feet near the southeastern boundary.

Rhems Formation. The Midwayan Rhems Formation (Danian to early Thanetian) has been informally referred to as the "Ellenton Clay" in previous SRS reports. The formation lies unconformably on the Cretaceous sediments and consists of gray, poorly sorted, micaceous, lignitic, silty and clayey quartz sand interbedded with gray clay.

Upper delta plain deposits composed of light-colored, moderately to poorly sorted, micaceous quartz sand are common in the northwestern part of the SRS, with the darker, poorly sorted, micaceous, lignitic lower deltaic plain facies becoming dominant in the southeastern part. The unit is approximately 40 feet thick at the northwestern boundary of the SRS and thickens to about 100 feet near the southeastern boundary.

Williamsburg Formation. The sediments of the Williamsburg Formation are typically silty, medium-to-coarse grained quartz sand interbedded with clay. Dark, micaceous, lignitic sand also occurs. In the northwestern part of the SRS, the unit is less silty and better sorted, with thinner interbedded clay layers. The formation changes from an upper delta plain facies in the northeast to a lower delta plain facies in the southeastern part of the SRS. The unit is about 30 feet thick at the northwestern SRS boundary and thickens to about 50 feet near the southeastern boundary. Near the coast the Williamsburg Formation (Colquhoun, and others, 1983) is about 350 feet thick and calcareous.

3.4.4. Orangeburg Group.

The Claibornian (Lutetian-Bartonian) Orangeburg Group consists of the lower Middle Eocene Congaree Formation (Tallahatta equivalent) and the upper Middle Eocene Santee Limestone Formation (Lisbon equivalent). The sediments thicken from approximately 100 feet at the northwestern SRS boundary to about 160 feet near the southeastern boundary. Dip of the upper surface is about 12 feet /mile to the southeast across the site. Downdip at the coast, the Orangeburg Group is about 325 feet thick (Colquhoun and others, 1983).

Congaree Formation. The Congaree Formation consists of yellow, orange, tan, gray and greenish gray, well-sorted, fine-to-coarse quartz sand. Thin clay lamina occur throughout the section, and pebbly layers, clay clasts, and

Tobacco Road Formation. The Tobacco Road Sand conformably overlies the Dry Branch Formation. The formation consists of moderately to poorly sorted, red, brown, tan, purple, and orange quartz sand. Ophiomorpha burrows are abundant in parts of the formation, and pebble layers are fairly common. The unit has the characteristics of a shallow marine deposit. The formation is widely exposed at the SRS and varies in thickness because of the eroded upper surface. It is at least 50 feet thick in places. The Late Eocene age of the Tobacco Road Sand has been established in Georgia (Huddleston and Hetrick, 1985), but parts of the formation may be younger (Prowell and others, 1985a; Colquhoun and others, 1983).

3.4.6. Upland Unit.

The "Upland unit" is an informal stratigraphic term applied to deposits that unconformably overlie the Tobacco Road sand at higher elevations (Inserts 5,6,7&8) in the southwestern South Carolina Coastal Plain (Nystrom and Willoughby, 1982; Nystrom and others, 1986). The most common lithofacies in the "Upland unit" is highly cross-bedded, fine to very coarse sand containing large micas and weathered feldspars. The sand generally consists of angular to sub-angular quartz and large mica flakes in a matrix of kaolinitic clay. White, kaolinitic clay balls are also common in this lithology and may range from coarse sand to cobble size. Siple (1967) reported large clay-lined noded burrows in this unit in the southeastern one third of the SRS. Dennehy and others (1989) found similar burrows in the unit southeast of the Defense Waste Processing Facility (DWPF) within the SRS boundary. This suggests estuarine environments for parts of the "Upland unit".

The "Upland unit" was deposited in high-energy, highly variable fluvial to estuarine depositional environments (Dennehy and others, 1989). The deposits conform to the shapes of large stream and river channels with extensive cross cutting and refilling. A reconstruction of the depositional environments of the unit from regional mapping done by Nystrom and Willoughby (1982), Nystrom and others (1986), and Prowell (unpublished data) suggests that a large ancient river system may have existed along a north-south axis near the present Savannah River drainage basin. The angular in-situ-weathered feldspars suggest that this drainage system quickly eroded fresh rock sources in the Piedmont. The burrows present in the "Upland unit" indicate that this river network flowed into a nearby sea and formed estuaries as far north as Dunbarton near P reactor. This observation explains the decrease in the amount of coarse stream gravel in the "Upland unit" in the southeastern one third of the SRS because of the lower stream gradients and current velocities in a fluvio-estuarine environment.

In general the "Upland Unit" sediments observed in the PBF wells support the conclusions by Dennehy and others (1989) of a transition from high-energy fluvial environments located near the ancient river system to the west to lower energy environments located at or near the shoreline estuarine environments further to the east. The PBF-5 well includes an "Upland" section containing coarse sand and gravels typical of the high-energy fluvial environments, whereas the PBF-2 well includes mostly fine to medium grained sand with minor gravel beds suggestive of lower stream gradients and current velocities in the fluvio-estuarine environments.

The age of the "Upland unit" is not precisely known. Siple (1967) tentatively assigned this unit (his Hawthorn Formation) a Miocene age through downdip correlation with Hawthorn deposits exposed along the Savannah River in Effingham County, Ga. This is consistent with Cooke and MacNeill's (1952) reference to Hawthorn strata in a railroad cut near Dunbarton at the SRS. The true Hawthorn, however, is a carbonate-rich open marine deposit unlike any of the lithologies in the "Upland unit". Colquhoun and Steele (1985) considered the "Upland unit" as a regressive phase of the Barnwell Group deposition, and by association, applied a late Eocene age. Nystrom and others (1986) favor downdip correlation with the middle Miocene Altamaha Formation (post-Hawthorn) of Huddleston (1985), whereas McCartan and others (1984) offer evidence that the "Upland unit" may be as young as Pliocene.

A three phase study of the "Upland unit" at SRS is planned to define and delineate the unit as to its precise age, areal distribution and geometry, and environments of deposition. At the present time the "Upland unit" has been conservatively assigned a Late Miocene age.

3.5. Methods and Materials

All the wells utilized in the study, the PBF wells as well as the "P" wells, were continuously cored and geophysically logged from the surface to basement. The logs included gamma (natural), spontaneous potential (SP) and caliper surveys; 16", 64" and single point resistivity surveys. In addition, borehole compensated density and neutron porosity surveys were run in the PBF wells. The cores taken from the PBF wells and the "P" wells were analyzed foot by foot by binocular examination in the SRL core-logging laboratory. Sand, gravel, clay and carbonate percentages were determined, as were the muscovite, lignite, glauconite and sulfide content of the cores. An example of the core data from PBF well pairs 4&5 and 3&7 is graphically displayed in Insert 2, along with the gamma (natural), SP, and resistivity surveys run in each of the PBF wells.

Quality control and reliability of the downhole geophysical surveys were analyzed and calibrated by comparing the lithologies of the cored sediments recovered from intervals of interest with the geophysical log response. The correspondence of the log response to the associated lithologies was excellent and consistent in all the PBF wells. Because no depth corrections were necessary the uncertainties in the depth to a particular lithologic horizon is minimal (± 2 feet). Insert 2 is a graphical display of the core data correlated with natural gamma, spontaneous potential, and short and long resistivity logs run in PBF wells. The correlation of the sand-clay percentage curves with the natural gamma curves is excellent for each well and between wells. As the clay content increases the gamma curve deflects toward the right in each case.

Correlation of the PBF well pairs is illustrated in Inserts 1a and 1b. All the surveys (curves) run in the wells were compared and correlated on the basis of pattern recognition of the various curves, as well as the sequential order of the patterns observed. The resulting correlations were confirmed using the lithological, paleoenvironmental and paleontological data (Insert 2) derived from the cored sediments retrieved from the wells. The wells are illustrated as pairs

across the fault (PBF 4 and 5; PBF 3 and 7) to demonstrate the offset caused by the fault. Further corroboration of the correlations was obtained by analyzing the PBF wells in the regional context using the surrounding "P" wells (Inserts 3,4,5,6,7,8).

Glauconite, which is present at and near the base of the Santee Formation, is observed in all the PBF wells. The glauconite in the Santee Formation is located at different elevations across the fault in each well pair. The geophysical curve associated with the glauconite is also located at different elevations across the fault in each pair. Different bracket symbols have been employed in Insert 2 to group various other components of the sediments (gravel percentage, lignite content, muscovite content, etc.) at several stratigraphic horizons. Invariably, the bracketed components in each well pair are offset the same amount as the glauconite in the Santee Formation. Thus the offset observed in the PBF well pairs across the Pen Branch fault is substantiated by both the downhole geophysical surveys run in the wells and by analysis of the lithologies encountered in the wells.

A detailed and comprehensive lithostratigraphic study of the entire coastal plain sequence (Aadland and Bledsoe, 1990) was undertaken to characterize and classify the aquifer and aquifer systems in the SRS region. The core data and downhole geophysical surveys run in the "P" wells and numerous other deep wells were analyzed to define the geometry and areal distribution of the lithostratigraphic sequence in the region. In this context the PBF wells drilled in a fairly straight line from west north-west to east south-east across the site, lie essentially perpendicular to the regional dip of the Coastal Plain sequence. The thickness variations observed in the PBF well pairs (Insert 1), especially in the Cretaceous part of the section near the Middendorf-Black Creek contact is attributed to the relative dip position of the various well pairs in the Coastal Plain sequence. Regional Hydrostratigraphic Cross Sections A-A' (Insert 3), and B-B' (Insert 4), from the Aadland and Bledsoe, (1990) report, illustrate the north-south and east-west lithostratigraphic framework at SRS. Well P-19 on Cross Section A-A' is located on the up-thrown side of the Pen Branch fault and within 2000 feet of the PBF-7&8 wells, placing these two wells in the regional stratigraphic framework (Fig. 3). PBF-1 is included on Cross-Section B-B'.

4. DEEP SEISMIC REFLECTION SURVEY

4.1. Purpose and Scope of Work

A seismic reflection program was initiated by the Savannah River Laboratory to be performed by Conoco (1987-88) to provide information on the basement structure underlying the Savannah River Site (SRS) in South Carolina (Figure 4). The specific objectives at the onset of the program were to better define basement structure and previously identified faults and to identify any other faults that might exist (Figure 5). A secondary objective was to image any shallower or deeper structure that appeared on the seismic records. Seismic data acquisition and processing were optimized for the primary objective: basement imaging.

From August to November 1987, an initial 135 line miles (Figure 4) of Vibroseis seismic reflection data were acquired over the central part of the SRS and analyzed using Conoco's Geoscience Workstation. The results of the preliminary interpretation highlighted areas that required additional definition. An additional 28 line miles (8 lines) were acquired during April and May 1988 to fill in these specific areas with greater detail.

A small fault identified in the west central part of the SRS (line 6) and a fault in the northern part of the SRS (line 9) were investigated further to determine their lateral extent. Additional data were collected in the vicinity of the computed epicenter of the 1985 earthquake and along the eastward extension of the Dunbarton basin.

A sequence of three shallow velocity surveys were also conducted to provide time-depth calibration for the seismic reflection data.

4.2. Conclusions of the Deep Seismic Reflection Survey

1. The basement reflector, located at about 0.4 seconds two-way travel time on the records, is clearly faulted or offset in these data. In the shallower portions of the record this offset grades into deformation over the fault indicating that the fault extends beyond the basement/Coastal Plain interface into Cretaceous sediments.
2. The Pen Branch fault dips steeply to the southeast. The crustal block southeast of the fault has moved up relative to the crustal block northwest of the fault. This places the Triassic rock at higher elevations than the Paleozoic crystalline basement. This corroborates the stratigraphic data.
3. The fault is interpreted as a continuation of the northwest border fault of the buried Dunbarton basin.
4. Other basement faults observed in these data indicate a subsurface basement structure consisting of three separate blocks. These faults have not been investigated in detail at this time because they are not observed to penetrate shallow portions of the Coastal Plain and hence are not considered to meet the age criteria in Appendix A.

Figure 4. Location of deep seismic reflection lines done by Conoco, 1987-1988. Dark lines were run first, followed by the light colored fill-in lines.

Figure 5. Location map of the Pen Branch fault and other basement faults identified based upon the Seismic Reflection Survey (Conoco, 1987-1988) data. Steel Creek fault was identified at a later date.

4.3. Interpretation

The fully processed seismic lines were analyzed visually for evidence of faults and continuous seismic reflectors. The data were then digitized to produce a data set suitable for computerized mapping procedures. Therefore, all further data manipulations were completed using a geologic work station. Maps produced using the work station represent the best attempt of the computer to regularly sample irregularly spaced data and create a realistic map of a specified surface. This output is, however, subject to the way the seismic sections are interpreted and the selection of mapping parameters by the seismic interpreter.

Following the initial interpretation by Conoco (Chapman and DiStefano, 1989), the SRS staff performed an interpretation using the same general procedures used by Conoco, but expanding the scope of the work to look at the deeper section and to use additional geologic data collected on SRS during the intervening year (Stephenson and Acree, 1989). The results of the SRS interpretation are presented in this report.

The most prominent features on the seismic profiles are the package of sub-horizontal reflections visible in the 0 to 0.4 second two-way travel time interval (Insert 9, 10, 11, 12). The reflections generally parallel the basement, thinning toward the northwest. Although the reflections originate from the Coastal Plain sedimentary strata, they do not correlate with stratigraphic units defined from geologic logs of cored wells at the SRS. The reflections are generally coherent and continuous across the seismic sections, but the reflections become weaker and less continuous in the shallower portions of the section.

The deepest of the sub-horizontal reflections, between 0.3 and 0.5 seconds two-way travel time, correlates with crystalline basement/Triassic sediments. Several less distinct reflectors were also picked both above and below the basement reflector on the line section where they could be identified. Three other seismic horizons were identified in the shallow section above the basement reflector. They were not as continuous as the basement reflector, and the uppermost reflector became fairly discontinuous. The reflectors were visually tied at line intersections, where possible, or interpolated during the computer mapping phase.

4.3.1. Basement Reflector. The seismically reflective basement changes in geologic age, lithologic character, and seismic velocity from north to south across the Dunbarton basin northern border fault, now identified as the Pen Branch fault. North of the fault, Paleozoic metamorphic gneiss and schist are imaged as basement along with some inferred granitic rock in the northwestern portion of the site. Southeast of the fault Triassic rock constitutes the basement reflector. This is suggested by the change in refraction velocities across the fault, measured during this study. In the northern area of the site, the velocity contrast between the shallow, low velocity (approximately 7,000 ft/sec) sand, silt, clay sequences of the coastal plain sediments and the high velocity (average about 19,000 ft/sec) crystalline basement rock is very high and produces a strong reflection. Southeast of the fault, the contrast in velocity between the sand, silt, clay sequences of the Coastal Plain and the consolidated clastic rock of the basin

(velocity approximately 14,000 ft/sec) while not as great is sufficient to generate a prominent reflector.

The effective basement reflector is the strongest event on all line sections and can easily be mapped over the entire site regardless of the actual rock type (metamorphic or sandstone). The basement reflector indicates a surface characteristic of peneplanation or an erosional leveling process prior to renewed disposition. Within the basement there are reflectors. They are discontinuous, but distinct enough to provide useful information about the structure of the shallow crystalline terrane.

4.3.2. Structural Configuration of Basement Blocks. The northeast-southwest trending faults identified in the Conoco data (Figure 5) break the Paleozoic crystalline basement into three distinct blocks (Figure 6). These blocks exhibit different amounts of vertical displacement and differential tilting with respect to each other. Cross-sections developed from the seismic data across the northern and southern blocks of the basement surface illustrate this difference in attitude of the basement blocks (Chapman and DiStefano, 1989). This difference in tilt may have been enhanced by the reverse movement on the faults during the Tertiary.

Analysis of the intrabasement seismic horizons suggests that the basement could be explained by three distinct blocks or zones. The seismic properties and structural styles within the basement blocks are distinguishable from each other.

The most obvious block or zone is the Triassic-Jurassic sediments within the basin southeast of the border fault (Block 1, Figure 6). Within this area, there were no obvious intrabasin reflectors seen below the sediment/basement contact until the 5 sec two-way travel time depth. A second block or zone is located in the center of SRS, bounded on the southeast by the northwest border fault of the basin and extending northwest to the Upper Three Runs Creek area (Price and Cumbest, submitted)(Block 2, Figure 6). The intrabasement reflectors in this block are the most distinct and continuous. This block also returned high frequency data. The third block or zone identified from seismic properties is located northwest of Upper Three Runs Creek and extends at least to the northern boundary of the site (Block 3, Figure 6). Within this region, there are some intrabasement reflectors; however, they are not as continuous as those in the middle block nor do they indicate the same structural style or geologic complexity.

Two other lines of evidence, one of which came from the seismic study and the other from potential field investigations (Daniels, 1974 ; Anderson, 1990) support the existence of the three blocks.

An unusual characteristic of these intrabasement seismic reflectors is their high frequency content. Some of the events contain frequencies near 100 HZ, and this appears to hold to a depth of about 11 sec two-way travel time. Normally, deep events will be low frequency in character due to their long travel paths that preferentially attenuate the high frequencies. The most likely explanation is that the Coastal Plain sedimentary section is relatively thin within the borders of SRS and the travel path for the intrabasement events is mostly through well indurated

Figure 6. Diagram indicating location of crustal blocks based upon Westinghouse interpretation of gravity, magnetic and seismic reflection data.

crystalline rock that has a high velocity and transmits the seismic waves with little distortion.

4.3.4. Structure Within and Below the Triassic Basin.

Well control (Marine and Siple, 1974) established the approximate location of the border fault that forms the northwest boundary of the Dunbarton Triassic basin and the existence of Triassic age rock southeast of that boundary. The northwest border fault was further constrained during the 1973 seismic survey (Seismograph Services Corp.) where a total of 5 lines crossed the fault. In the Conoco (1987-88) survey, a total of 9 lines cross the border fault clearly showing the fault and providing good control for mapping its location. However, as discussed earlier only one of these lines was specially located and oriented to record and identify deep basement reflection within and beneath the basin using different data acquisition parameters. The processed data for this line are shown in insert 12. While only a few clearly defined events were identified within and below the basin, there is improvement in the imaging over the other data. The reflectors between 2.1 and 2.5 seconds on the left side of the figure appear to come from features within the basin; however, their true source location is not known. Also, there appear to be deeper reflections in the interval between 3 and 5 seconds that may be continuous, indicating the depth of the basin to be at least less than this. Marine (1974) estimated the depth of the basin to be approximately 7,000 ft. Using the observed two-way travel time from the Conoco seismic profiles and the subsurface velocity model determined in that investigation a maximum depth of 14,000 ft can be determined for the basin.

4.4. Data Acquisition

The data were acquired by Conoco, Inc. using Vibroseis equipment. The data acquisition program was laid out along existing roads and rights-of-way within the SRS site to minimize the impacts on the natural environment. This was generally accomplished without compromising the objectives of the survey. While straight lines are desirable for seismic surveys, the main criteria is that the curvature be gradual relative to the recording geometry. The short geometries used in this program to meet the objectives allowed moderate curvature in the lines without degrading data quality.

Seismic acquisition parameters were selected on the basis of the previous seismic study performed in the early 1970's (Seismograph Services Corp. survey, 1974) and the known basement depth. Initial parameters were selected to provide data for both reflection and refraction analysis. The refraction data provided a backup data set for basement mapping. The initial seismic acquisition parameters listed in Table 1 column A were used on the first 5 lines recorded (lines 1, 4, 6, 7, and 8). Initial processing indicated that the reflection data quality was sufficient to satisfy the objectives and that the longer refraction geometries were not necessary. For this reason, the parameters listed in column B on Table 1 were used on the remainder of the lines recorded. The column B parameters were more singly focused for mapping the shallow basement reflector with the maximum offset at 2,000 feet and sourcing of 80 feet spacing providing data for 24 fold CDP stack. Line 29 was located approximately perpendicular to the northwest border fault of

the Dunbarton Basin to image deeper than the previous lines to see if any features could be identified that would provide a measure of the depth of the basin. The geometries and source were, therefore, effectively doubled for this line (Table 1, Column C).

Table 1

	A	B	C
Flag spacing	55	40	20
CDP Stack (fold)	48	24	20
Near offset (ft)	137	140	50
Far offset (ft)	2722	2020	990
Sweep frequencies (Hz)	20-120	20-120	30-150
Length (sec)	10	10	8
Source	3x6	3x6	1x4
Array length (ft)	90	90	0
Geophones	1x14	1x14	1x14
Array length (ft)	55	55	0
Record time (ses)	14	14	10
Sample rate (milliseconds)	2	2	2
Alias filter	2	2	2
Low cut filter	18	18	30
Slope	18	18	18
60 Hz notch	out	out	out
COS box	in	in	in

4.5. Processing

Processing of the data was performed using the Conoco seismic data processing system. This system consists of an extensive menu of computer programs that are designed to operate sequentially on reflection seismic data in incremental steps toward final processed data for displays. Several of the processes are

standard data preconditioning steps and are run in the appropriate sequence; others are designed for generic type conditioning or analysis and may be inserted at any point in the processing stream. The final processing sequence is selected by the data processor to solve specific problems that are encountered with the data.

For the SRS data, as with any seismic data, demultiplexing was the first step in the processing. For vibroseis data the next step is to cross-correlate with the reference or sweep signal that compresses the recorded data back to a discrete wavelet seismogram. The next processing zeros out early refraction arrivals and high velocity direct noises. Automatic gain control was subsequently applied to the data followed by amplitude spectrum normalization. This is done to balance high and low frequencies within the data. Elevation and datum corrections were applied before the normal moveout correction. The data were then resorted into common depth points gathers and statics corrections applied. Filtering, spatial deconvolution, and migration after stack were then applied to the data. Following this processing data displays were prepared at a scale of 50 traces/inch and 10 inches/second.

5. HIGH-RESOLUTION, SHALLOW SEISMIC REFLECTION SURVEY (1990-1991)

5.1. Purpose and Scope

The purpose of this project was to determine the shallowest extent of the fault and to determine the presence of any flat-lying, undeformed layers over the fault. The scope of work was to acquire, process, and interpret 28 km (17.4 miles) of high resolution seismic reflection data taken across the trace of the Pen Branch fault and other suspected, intersecting north-south trending faults (Figure 5 and 7). Field acquisition and processing parameters were selected to optimize for the upper 300 ft of geologic strata where previous data suggested the fault terminated. Other geophysical, borehole, and geologic data were incorporated into the investigation to assist in the determination of optimal parameters and aid in the interpretation.

The work covered by this seismic survey was conducted under subcontract by Emerald Exploration Consultants, Inc. (EMEX) from August 14, 1990 to February 28, 1991.

5.2. Results of the High-Resolution Shallow Seismic Reflection Survey.

- 1) There is clearly faulting at depth offsetting the basement/Coastal Plain interface and perhaps some early Cretaceous sediments based on the deep seismic reflection(1987-1988). All seismic reflection data suggest that there is deformation over the fault in the form of draped layers. Deformation decreases upward toward the surface and all deformation ceases within the upper few hundred feet.

Figure 7. Location map for the high-resolution, shallow seismic reflection done by EMEX, 1990-1991. Seismic reflection conducted by D'Appolonia at the AFR site is found in the center of the map.

2) The seismic data show other geologic features not related to the Pen Branch fault but important to consider when making any interpretation about the section. Numerous small-scale sedimentary features such as possible unconformities, and channels interrupt the normal stratigraphic sequence.

5.3. Associated Seismic Reflection Data

In addition to the Conoco seismic there were two other prior seismic reflection surveys conducted at the Savannah River Site.

1.) Seismograph Service Corporation, 1969 Survey. The oldest survey on site was analog single fold data obtained by Seismograph Service Corporation in 1969. This survey gave the first indication of the basement faults buried underneath the Coastal Plain section at SRS (Figure 8). An additional survey was run in 1973. There were no written reports for either of these surveys.

2) D'Appolonia, Inc., 1978 Survey. In 1978 D'Appolonia, Inc. conducted a high resolution minisose reflection survey (Murdock, 1982) in the Away From Reactor Spent Fuel Storage Facility (AFR) area (Figure 7). A 24 trace recording system was used with a sample rate of 1 ms, shot to first trace offset was 480 ft, trace spacing was 40 ft, shot to far trace offset was 1400 ft. The large offset between the seismic source and the first trace precluded the recording of data between the surface and 250 ft. A sea level datum was used that gives the appearance of the data starting at zero time. The final processing filter was 25-40/90-110 Hz. The indicated 6 fold was not attained until the same time as their basement reflection, as evidenced by the mute pattern utilized in data processing. All the reflectors are essentially flat lying and the Pen Branch fault is not observed in these data. The seismic lines do not cross the trace of the fault and are not expected to image the fault.

5.4. Production Lines

The locations of all the high-resolution shallow seismic lines are indicated in Figure 7. Four full scale seismic sections for lines that cross the Pen Branch fault are included with this document (Insert 14, 15, 16,17). As indicated in the information panel on each line, the vertical time scale needs to be multiplied by 200 to convert to two way travel time in milliseconds. There is no vertical exaggeration in these displays. The distance between marked shotpoint locations on the display is 200 feet.

In general all the seismic data show features that reflect current understanding of the regional geology of the Coastal Plain. Local and regional unconformities, seen as channel-bar or channel-fill deposits are seen throughout the seismic sections. Some of the strong continuous reflectors may be major unconformities rather than lithologic layers because laterally continuous lithologic layers are not expected in the Coastal Plain Section.

The reflectors in the shallow seismic data are interpreted to be predominantly sand/clay interfaces. Some of the reflectors are believed to be caused by carbonate material. Other extensively continuous reflectors may actually be

Figure 8. Outline of the buried Triassic basin at the Savannah River Site with the seismic reflection lines done by Seismograph services in 1973. The figure is derived from Marine, I. W., 1974.

unconformities. The continuity of any reflector is affected by lateral facies changes such as increasing sand content in a clay layer and changing thickness of a clay layer causing simple and complex tuning changes. Channels cutting out clay layers also effect the continuity of reflection events. Closely spaced shallow drilling done along one of the seismic lines could confirm the correlation of lithology or unconformities to reflectors.

Seismic reflection data show deformation decreasing upward in the vicinity of the Pen Branch fault. Offset of the pre-Cretaceous surface changes to flexure or folding of layers overlying the fault. This feature can be observed in the seismic sections and compared to the dip reversals discussed in the shallow drilling section (Section 3). The dip reversals or flexed layers in the vicinity of the fault could be due to passive sedimentation or draping of sediments over a pre-existing structure or fault scarp after the fault moved. It could also be due to tectonic deformation of layers already in place when the fault moved. In either case deformation or draping ceases within a few hundred feet of the surface.

5.4.1. Line 6.

Line 6 (Insert 14) is located in the northeast section of the site, at the northeast extreme of the EMEX survey. The nearest Conoco reflection line is Conoco line 28. Data quality is generally good. The refraction analysis shows the thickness of the weathered layer is generally 20 ft., with variations between 10 and 30 ft. Variations in thickness and structural attitude may be due to the orientation of the line which is neither true dip nor true strike.

The location of the Pen Branch fault is interpreted to be at about shotpoint 285 (Figure 10, Insert 14). The data show no faulting of the Cape Fear or younger strata. The presence of the fault is based on character correlation across the fault at the basement level.

Some strong reflection segments are observed in the data that may relate to local variations in clay content. Other features have the appearance of narrow to wide stream channels or meander belts.

5.4.2. Line 12.

Line 12 (Insert 15) is located in the central portion of the plant, approximately 0.3 of a mile away from line 11. Data quality is generally fair to good depending on the amount of high frequency noise. A loss of fold in the area of shotpoint 295 was due to a railroad crossing. Local variations exist in the reflection character along this line.

The Conoco data (Line 3) ties this line. The Conoco data located the fault at shot point 1151 at depths greater than the shallow data record (Figure 9). This location translates to approximately shot point 130- 140 on the shallow data (line 12) (Figure 11). A bending of reflection events at depth is where the Pen Branch fault is interpreted in the shallow seismic data. The northern end of line 11 which is a third of a mile away from 12 has no bend in the survey line and the reflectors do not show any flexure.

Figure 9

LINE 3

Conoco Seismic Survey, 1987-88

Figure 10
LINE 6
INTERPRETATION SKETCH

Figure 11
LINE 12
INTERPRETATION SKETCH

The reflectors highlighted on the seismic section are intended to demonstrate examples of continuous, essentially flat-lying reflectors at various depths. The upper reflector at shotpoint 180 is at 130 milliseconds two way travel time (time measured from the datum plane). This reflector is located on the vertical scale at 0.6. In this portion of the section, using a stacking velocity of 5-6000 ft/sec, that reflection is at approximately 425 feet below ground surface.

The next reflector is located at 286 milliseconds (1.4 on the vertical scale), two-way travel time or approximately 858 ft. This reflector is showing some deformation or dip reversal over the fault. Between shotpoints 125 and 135, a time fluctuation of 10 milliseconds two-way travel time corresponds to a change in elevation of 30 ft over 100 ft horizontal distance.

5.4.3. Line 14.

Line 14 (Insert 16) is located just southwest of K-Reactor. Data quality is highly variable and generally degrades with depth. The loss of fold in the areas of shotpoints 285, 240, and 195 was due to the Indian Grave Branch Creek and cultural features associated with it. Local variations exist in the reflection character along this line.

The Pen Branch Fault may be present at depth in the vicinity of shot point 160-200. The fault seen in Conoco line 8 projected onto this line is observed on EMEX line 14 by shot point 180-200 (Figure 12). The strong amplitude reflection event at shot point 120, close to the bottom of the seismic section is probably a Paleozoic basement reflector (340 milliseconds two-way travel time measured from datum or 2.0 on the vertical scale). Using a stacking velocity of 6000 ft/sec this places the reflector at approximately 1020 ft below the surface. It abruptly terminates at shot point 140. The fault is probably located in the area following this termination. On the south side of the fault Triassic rock is expected. Triassic rock did not return good reflection events in both the Conoco data and the EMEX data. For this reason it is not surprising that there is no corresponding high amplitude reflector on the south side of the fault.

The reflectors highlighted on the seismic section are intended to demonstrate examples of continuous essentially flat-lying reflectors at various depths. The upper reflector at shotpoint 130 is at 40 milliseconds two way travel time (measured from the datum). At this portion of the section that reflection is at approximately 80 feet below land surface.

The next reflector is located at 120 milliseconds, two-way travel time or approximately 300 ft. This reflector has minor time fluctuations and amplitude changes across the profile. Compare the overall change in time across the profile from shotpoint 270 to 130. At shotpoint 270 the reflection event is at 120 milliseconds two-way travel time and at shotpoint 130 it is at 114 milliseconds two-way travel time (as measured from the datum), a change of 6 milliseconds (two-way travel time). This corresponds to a change in elevation of 12 feet over a distance of 2800 ft.

Figure 12

LINE 14

INTERPRETATION SKETCH

Table 2**Shallow Drilling from the PBF well series**

	total depth	bottomed in...	pre-Cretaceous boundary (elev)	Relation to fault
PBF-1	1065'	crystalline rock	-753	north, downthrown
PBF-2	1054'	Triassic rock	-683	south, upthrown
PBF-3	1135'	crystalline rock	-779	north, downthrown
PBF-4	1079'	crystalline rock	-839	north, downthrown
PBF-5	1125'	Triassic rock	-810	south, upthrown
PBF-6	902'	Triassic rock	-778	south, upthrown
PBF-7	1030'	Triassic rock	-701	south, upthrown
PBF-8	1030'	Cretaceous sediments	-692	south, upthrown

The next reflector is located at 240 milliseconds two-way travel time or approximately 720 feet (based on stacking velocity of 6000 ft/sec). For this reflection event the time change across the section is 26 milliseconds (two-way travel time) or approximately 78 feet. This reflector may be indicative of deformation caused by the Pen Branch fault. The lowest reflector is located at 350 milliseconds two-way travel time or approximately 1100 feet.

The dip of the Triassic basement along this line is west, southwest. The change in elevation on the Triassic surface determined from recovered core from PBF-5,7, and 8 indicate a change in elevation of 109 feet on the same side of the fault (Table 2). This can be an alternative explanation for the gentle anti-regional dip seen in the seismic section.

Strong reflection segments which may relate to local variations in clay content are observed in this section. There are other features that have the appearance of stream channels and meander belts.

5.4.4. Line 15.

Line 15 (Insert 17) is located in the southwestern portion of the survey area. Data quality is generally fair to good. The Pen Branch is interpreted at shotpoint 135. The fault shows approximately 35 ft or 10 milliseconds of displacement at the basement (Figure 13).

5.5. Field Acquisition

The acquisition program for the shallow seismic survey consisted of an asymmetric split-spread layout with parameters as listed below. Reversed refraction shots were taken at both ends of each line. Filter and charge size tests were repeated periodically.

Acquisition Parameters

Recording System	24 channel EGG 2401
Sample Rate	0.2 ms
Record Length	0.400 second
Shot Location	Trace 4 or 4.5
Shot Interval	10 ft
Trace Interval	20 ft
Subsurface Trace Spacing	5 ft
Fold	12
Geophone Array	6 - spaced over 1.5 ft parallel to the line
Geophone Frequency	40 Hz, 3 inch spike
Energy Source	Buffalo Gun - 12-Gauge - light load
Record Filter	50 - 1000 Hz, with 60 Hz notch

When shot locations had to be skipped due to bridges, railroads, etc., extra shots were taken on both sides of the shotpoint gap to minimize the loss of fold. These extra shots minimized the loss of "deep" fold due to the skipped shots, but did not provide the near trace information to maintain the "shallow" fold.

Figure 13
LINE 15
INTERPRETATION SKETCH

The initial lines had some variation in the position of the shot. The final determination of the shot location was chosen to record more data outside the noise wave where better data quality was observable, and to obtain data at larger incident angles for the amplitude versus offset analysis. Lines 1, 2, and 3 were recorded with the shot location at trace 12 or 12.5, and line 5 was recorded with the shot location at trace 6 or 6.5. A portion of line 1 was re-acquired with 24 fold data (designated line 16) by shooting twice at each location into cables that utilized traces at 10 ft intervals. Line 16 also utilized a sample rate of 0.5 ms and a record length of 1.000 second.

Consistent "time breaks" required for high resolution stacking of the data were obtained by triggering the instruments with an uphole geophone. The time delay caused by the acoustic wave traveling the 3 ft from the shot location to the surface is minimal considering the distance involved. The travel time is less than the 1.5 ms calculated with 2,000 ft/sec propagation. Examination of the data recorded at the shot location indicates that the delay was between 0.4 and 0.6 ms. When line 16 was shot to record the near distance traces, trace 1 remained at the shotpoint to verify adequate instrument triggering. When line 16 was shot to record the far distance traces, trace 1 duplicates the location of trace 24 of the shot to record the near distance traces, to allow for consistent adjustment of the time breaks.

5.6. Processing

The final data processing included the following steps.

- 1 Demultiplex and Reformat to SEG Y
- 2 Geometry and Trace Editing
- 3 Filter
- 4 Gain Recovery
- 5 Time Break Correction (where applicable)
- 6 Elevation Datum and Refraction Statics
- 7 Surface Consistent Deconvolution and Spectral Balancing
- 8 Surface Consistent Residual Statics
- 9 Velocity Analysis
- 10 Surface Consistent Residual Statics
- 11 Application of Normal Move Out (NMO) Correction
- 12 Offset/Fold Limiting - Muting
- 13 Stack
- 14 F-K Noise Filter
- 15 Final Filter
- 16 Final Scaling
- 17 Display
- 18 Migration
- 19 Display

The processing and output display parameter selection were based upon numerous tests. The final displays utilized horizontal and vertical scales of 32.5 inches per second and 12 traces per inch (no vertical exaggeration).

7. CONCLUSIONS BASED ON THE PRESENTLY AVAILABLE DATA

All data indicate that the Pen Branch fault is a non-capable fault. Supporting observations include:

1. There are flat-lying undeformed layers in the shallow portion of the Coastal Plain Section in both the geophysical and stratigraphic data . This indicates that the fault is not expressed at the surface.
2. The Upland unconformity is an essentially flat-lying surface that is undeformed and overlies any deformation seen in the stratigraphic sections. This surface is at least 5 million years old. Therefore, deformation related to the fault must be greater than 5 million years and falls outside the criteria that define a capable fault in terms of age. The Upland unconformity is not identified on the seismic sections.
3. The seismic reflection profiles show offset layers of the fault at depth (standard seismic data) and deformed layers over the fault decreasing in amplitude upward toward the surface (standard and high-resolution seismic data). The deformed layers could be the result of tectonic folding or the result of passive sedimentation over a pre-existing structure or a fault scarp. In either case, deformation ceases within a few hundred feet of the surface.
4. The amount of dip reversal observed in these data, attributed to deformation by the fault is small and occurs in a geologic section covering a time span of over 100 million years. This implies a slow deformation rate that further implies either slow, possibly aseismic, movement over a period of 100 million years or an event driven mechanism with a long recurrence interval.

8. PATH FORWARD

A field investigation of the Upland unit and the Upland unconformity will be initiated this spring in order to further extend the geologic and seismologic data base at SRS to support future programs. This study will address the suggestions for further work made by the ESAC review. The study will include surface and subsurface geologic and geophysical investigations to characterize these units. An additional drilling project will be initiated to confirm reflectors observed in the high-resolution, shallow seismic reflection profiles to lithologic layers or unconformities.

9. REFERENCES

- Aadland, R. K. and H. W. Bledsoe, 1990, Classification of hydrostratigraphic units at Savannah River Site, South Carolina, USDOE Report WSRC-RP-90-987, Savannah River Site, Aiken South Carolina.
- Anderson, E. E., 1990, The seismotectonics of the Savannah River Site: The results of a detailed gravity survey, Master of Science Thesis, University of South Carolina, Columbia, South Carolina, 248 pp.
- Chapman, W. L., and Di Stefano, M. P., 1989, Savannah River Plant Seismic Survey, 1987-88: Conoco Inc., Seismic Acquisition Section, Research Report 1809-005-006-1-89, 110 p.
- Code of Federal Regulations, 10 CFR 100 Appendix A, 1982, Seismic and geologic siting criteria for nuclear power plants: Office of the Federal Register, National Archives and Records Administration.
- Colquhoun, D.J., and Steele, K.B., 1985, Chronostratigraphy and hydrostratigraphy of the northwestern South Carolina Coastal Plain: Project No. G868-05, Annual Cooperative Grant Agreement No. 13040 R-83-591, Interim Technical Report to Water Resources Research Institute, Clemson University, Clemson, South Carolina, 15 p.
- Colquhoun, D.J., Woolen, I.D., Van Nieuwenhuise, D.S., Padgett, G.G., Oldham, R.W., Boylan, D.C., Bishop, J.W., and Howell, P.D., 1983, Surface and subsurface stratigraphy, structure and aquifers of the South Carolina Coastal Plain: Report to the Department of Health and Environmental Control, Ground Water Protection Division, published through the Office of the Governor, State of South Carolina, 78 p.
- Cooke, C.W., 1936, Geology of the Coastal Plain of South Carolina: U.S. Geological Survey Bulletin 867, 196 p.
- Cooke, C.W., and MacNeil, F.S., 1952, Tertiary stratigraphy of South Carolina: U.S. Geological Survey Professional Paper 243-B, p. 19-29.
- Cooke, C.W., and Shearer, H.K., 1918, Deposits of Claiborne and Jackson age in Georgia: U.S. Geological Survey Professional Paper 120, 243-B, p. 19-29.
- Daniels, D. L., 1974, "Geologic Interpretation of Geophysical Maps, Central Savannah River Area, South Carolina and Georgia." U.S. Geological Survey, Geophysical Investigation Map GP-893.
- Dennehy, K.F., Prowell, D.C., and McMahon, P.B., 1989, Reconnaissance hydrogeologic investigation of the Defense Waste Processing Facility and Vicinity, Savannah River Plant, South Carolina: U.S. Geological Survey Water-Resources Investigations Report 88-4221, 74 p.

- Gohn, F.S., Hazel, J.E., Bybell, L.M., and Edwards, L.E., 1983, The Fishburne Formation (Lower Eocene), a newly defined subsurface unit in the South Carolina Coastal Plain: U.S. Geological Survey Bulletin 1537-C, p. 1-16.
- Huddlestun, P.F., 1982, The development of the stratigraphic terminology of the Claibornian and Jacksonian marine deposits of western South Carolina and eastern Georgia, in P.G. Nystrom, Jr., and R.H. Willoughby (eds.), Geological investigations related to the stratigraphy in the kaolin mining district, Aiken County, South Carolina: South Carolina Geological Survey, 1982 Carolina Geological Society Field Trip Guidebook, p. 21-33.
- Huddlestun, P.F., 1985, An examination of the Altamaha Formation near Oak Park, Emanuel County, Georgia, the Miocene through Holocene: Georgia Geological Society 20th Annual Field Trip Guidebook, p. 1-19.
- Huddlestun, P.F., and Hetrick, J.H., 1979, The stratigraphy of the Barnwell Group in Georgia: Georgia Geologic Survey Open File Report 80-1, published for the 14th Field Trip of the Georgia Geological Society, 89 p.
- Huddlestun, P.F., and Hetrick, J.H., 1985, Upper Eocene stratigraphy of central and eastern Georgia: Georgia Geologic Survey Bulletin 95, 78 p.
- Hutchinson and Klitgord, 1986,
- Marine, I. W., 1974a, Geohydrology of a buried Triassic basin at Savannah River Plant, South Carolina: AAPG Bull. v. 58 p. 1825-1837.
- Marine, I. W., 1974b, Geohydrology of the buried Triassic basin at the Savannah River Plant, Groundwater, vol12, 96 pp.
- Marine, I. W., and Siple, G. E., 1974, Buried Triassic basin in the Central Savannah River Area, South Carolina and Georgia : GSA Bull. v. 85 p. 311-320.
- McCartan, Lucy, Lemon, E.M., Jr., and Weems, R.E., 1984, Geologic map of the area between Charleston and Orangeburg, South Carolina: U.S. Geological Survey Miscellaneous Investigations Series Map I-1472, scale 1:250,000.
- Murdock, J. S., 1982, Preliminary Safety Analysis Defense Waste Processing Facility: E. I. du Pont de Nemours and Co., Savannah River Laboratory, DPST-82-675, 4 volumes, prepared for the DOE under contract DE-AC09-76SR00001.
- Nystrom, P.G., Jr., and Willoughby, R.H., 1982, Geological investigations related to the stratigraphy in the kaolin mining district, Aiken County, South Carolina: South Carolina Geological Survey, 1982 Carolina Geological Society Field Trip Guidebook, 183 p.
- Nystrom, P.G., Willoughby, R.H., and Kite, L.E., 1986, Cretaceous-Tertiary stratigraphy of the upper edge of the Coastal Plain between North Augusta

and Lexington, South Carolina: South Carolina Geological Survey, 1986
Carolina Geological Society Field Trip Guidebook, 82 p.

Petersen, T. A., L. D. Brown, F. A. Cook, S. Kaufman, and J. E. Oliver, 1984,
Structure of the Riddleville Basin from COCORP seismic data and
implications for reactivation tectonics. *Journal of Geology*, v. 92, pp. 261-
271.

Price, V., Steele, I., Stieve, A., 1989, Pen Branch Fault Investigation Program Plan,
ESS-SRL-89-395.

Price, V., and Cumbest, R., 1991, submitted to the GSA Bulletin.

Prowell, D.C., Christopher, R.A., Edwards, L.E., Bybell, L.M., and Gill, H.E.,
1985a, Geologic section of the updip Coastal Plain from central Georgia to
western South Carolina: U.S. Geological Survey Map MF-1737.

Prowell, D.C., Edwards, L.E., and Frederiksen, N.O., 1985b, The Ellenton
Formation in South Carolina- A revised age designation from Cretaceous to
Paleocene: U. S. Geological Survey Bulletin 1605-A, p. A63-A69.

Siple, G.E., 1967, Geology and ground water of the Savannah River Plant and
vicinity, South Carolina: U.S. Geological Survey Water Supply Paper No.
1841, 113 p.

Sloan, Earle, 1908, Catalogue of mineral localities of South Carolina: South
Carolina Geological Survey, Serial 4, Bulletin 2, p. 449-453.

Snipes, D. S., Fallaw, W. C., Price, Jr., V., 1989, The Pen Branch Fault:
Documentation of Late Cretaceous-Tertiary faulting in the Coastal Plain of
South Carolina (U), Westinghouse-SRS, DP-MS-88-219.

Steele, K.B., and Colquhoun, D.J., 1985, Subsurface evidence of the Triassic
Newark Supergroup in the South Carolina Coastal Plain: *South Carolina
Geology*, v. 28, p. 11-22.

Stephenson, D. E., 1988, August 1988 Savannah River Plant Earthquake: E. I. du
Pont de Nemours & Co., Savannah River Laboratory, Aiken, South
Carolina, DPST-88-841, p. 1-12, 6 figures.

Stephenson, D. S., and Acree, J., 1989, Presentation at Lawrence Livermore
Information Dissemination Meeting for Seismic Hazards Study, Seismicity
Panel, Hilton Head, South Carolina.

Stephenson, D. S. and Chapman, W. L., 1988, Structure associated with the
buried Dunbarton basin, South Carolina from recent seismic data.
*Geological Society of America, Southeastern Section Abstracts with
Programs*, v. 20, p 318.

- Stephenson, D. E., Talwani, P., and Rawlins, J., 1985, Savannah River Plant earthquake of June 1985: E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina, DPST-85-583, p. 1-31, 13 figures, 2 tables.
- Talwani, P., Rawlins, J. and Stephenson, D. E., 1985, The Savannah River Plant, South Carolina, earthquake of June 9, 1985 and its tectonic setting, Earthquake Notes, v. 56 no. 4, p. 101-106.
- Veatch, Otto, and Stephenson, L.W., 1911, Preliminary report on the geology of the Coastal Plain of Georgia: Georgia Geologic Survey Bulletin 26, p. 237-296.

END

**DATE
FILMED**

4 / 23 / 92