TECHNICAL REPORT

September 1, through November 30, 1991

DE92 007865

Project Title: Combustion Characterization of the Blend of
Plant Coal and Recovered Coal Fines

DE-FQ22-91PC91334

Principal Investigator: Shyam Singh, SS Energy
Environmental International, Inc.

Other Investigators: Dr. Alan Scaroni & Mr. Bruce Miller
Combustion Laboratory, Penn State Univ.

Vas Choudhry
Praxis Engineers, Inc.

Project Monitor: Dr. Ken Ho, CRSC

ABSTRACT

The overall objective of this proposed research program is to determine the combustion characteristics of the blend derived from mixing a plant coal and recovered and clean coal fines from the pond. During this study, one plant coal and three blend samples will be prepared and utilized. The blend samples will be of a mixture of 90% plant coal + 10% fines, 85% plant coal + 15% fines, 80% plant coal + 20% fines having particle size distribution of 70% passing through -200 mesh size. These samples' combustion behavior will be examined in two different furnaces at Penn State University, i.e., a down-fired furnace and a drop-tube furnace. The down-fired furnace will be used mainly to measure the emissions and ash deposition study, while the drop tube furnace will be used to determine burning profile, combustion efficiency, etc.

This report covers the first quarter's progress. Major activities during this period were focused on finding the plants where a demo MTU column will be installed to prepare the samples needed to characterize the combustion behavior of slurry effluents. Also, a meeting was held at Penn State University to discuss the availability of the laboratory furnace for testing the plant coal/recovered coal fines blends.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

This project is funded by the U. S. Department of Energy (PETC) and by the Illinois Department of Energy and Natural Resources as part of their cost-shared program.

4b

EXECUTIVE SUMMARY

The overall objective of the research program is to determine the combustion behavior of plant coal and recovered coal fines blend (ignition temperature, flame stability, emissions and ash characteristics) in a laboratory scale furnace in which the time and temperature history of the burning particles are similar to the utility boiler furnace.

The effluent sample is being collected at Peabody Coal Co. This sample will be thickened prior to shipping to MTU for recovery of clean coal. Also, a sample of plant clean coal collected earlier has been crushed to 1/4" top size and kept ready for blending with the effluent recovered coal. The plant clean coal will be shipped shortly to Penn State for calibration testing of the furnace.

Recovery of clean coal from effluent sample will be done at the MTU facilities. Following telephone discussions it was decided that a Praxis engineer will visit MTU to assist in the test work and dewatering of the sample. This work has been scheduled for December 1991 to January 1992. There is a significant advantage to getting the recovered coal from a pilot plant. The sample will be very close to a commercial blend, thus generating realistic combustion data which may form the basis for approaching a utility for the next phase.

The principal investigator made a trip to Penn State University to discuss the readiness of the laboratory scale down-fired furnace when the samples are ready to be shipped and testing is to be resumed. Dr. Alan Scaroni and Principal Investigator discussed the possible difficulties in the sample preparation and maintaining an optimum moisture content to avoid any delivery problem in the coal feed line to the burner. Suggestions were made by Dr. Scaroni that 5 pounds of the blended fuel must be tested first to characterize the feeding system. Once the system performance is established, then full scale testing should resume.

OBJECTIVE

The objective of the proposed research project is to determine the combustion behavior plant of coal and recovered coal fines blend (ignition temperature, flame stability, ash behavior and unburned fuel composition) in a laboratory scale furnace in which the residence time and temperature history of the burning particles are similar to the utility boiler furnace. To understand the combustion phenomenon, the blend compositions will be varied by adding different percentages of coal fines to the plant coal by maintaining 75% of the particles passing through -200 mesh size, but the weight percentage of coal fines will not exceed 20% in the total mixture. Praxis Engineers will guide the selection and appropriate composition of the fuel due to their experience and involvement in other similar projects. The overall combustion study will be done in the down-fired furnace and the drop tube furnace of the combustion laboratory at the Penn State University.

The objective of this study is to have three blends of plant coal mixed with recovered coal fines and having with constant moisture content. The blends and the plant coal will be burned in the Penn State combustion laboratory furnaces at different firing rates to determine the ignition temperature, carbon burnout, ash behavior, SO_x , CO, NO_x , particulates, etc.

INTRODUCTION AND BACKGROUND

Use of recovered coal fines from a slurry effluent as a part of the blended fuel for utility will not be possible unless a systematic study is conducted to identify the variables that influence its economic advantage. The proposed research program is designed to understand the impact of the variables, i.e., the blend composition, moisture, etc. The proposed concept utilizes a mixture of certain percentage of recovered coal fines with the plant coal as a plant fines coal fuel. When this new fuel is prepared, the bulk properties of this fuel change and thus, the combustion characteristics change as well. It is not certain how this will affect the overall economics of the operation of a utility. Therefore, to systematically investigate this issue, a number of samples will be prepared and stored in a controlled manner to prevent contamination. These samples will then be analyzed using standard analytical tools. Simultaneously, a literature review of similar work done on other coal and blend will be conducted to establish the research methodology for the proposed program. In addition, drop tube furnaces will be used to determine the burning profile, and ignition temperature while down-fired will be used to measure the emissions and ash deposition.

EXPERIMENTAL PROCEDURE

To carry out the proposed research activities, a systematic plan was discussed among the participants. Discussion included the need of blended samples amount, their preparation to meet the particle size distribution and the combustion test furnace instrumentation to evaluate the overall combustion behavior. It was decided that plant coal and blended fuel, i.e., plant coal and recovered coal fines should be burned within a few days time period to avoid any ambient oxidation of original plant coal. All the calibration must be done to ensure the functionability of the components.

TECHNICAL WORK COMPLETED

As a first step, a communication guideline was developed for this project which identifies the contacts in each organization and describes methods of transferring technical information and data on the project between the participating organizations.

Also, the principal investigator outlined the methodologies to be used in the combustion evaluation of the blended and plant coal samples. This plan was discussed with Mr. Miller and Dr. Scaroni who will be assisting during the study. Dr. Scaroni stressed that the moisture content in the sample should not be more than 10 to 20% on weight basis, otherwise the feed line may clog during the delivery. An estimate was made regarding the amount of recovered coal fines needed.

• 0% recovered coal	120 lb.
• 10% recovered coal	240 lb.
• 15% recovered coal	160 lb.
• 20% recovered coal	160 lb.

Grind size for the plant coal stated in the proposal is 1/4" x 0, followed by blending with reclaimed coal, and then grinding to 70% passing 200 M prior to shipping to Penn State. We can make small bags of test samples of 40 pounds each if desired. This will eliminate the need for double handling to prepare a representative sample during testing.

The effluent sample is being collected at Peabody Coal Co. This sample will be thickened prior to shipping to MTU for recovery of clean coal. Also, a sample of plant clean coal collected earlier has been crushed to 1/4" top size and kept ready for blending with the effluent recovered coal. The plant clean coal will be shipped shortly to Penn State for calibration testing of the furnace.

Recovery of clean coal from effluent sample will be done at the MTU facilities. Following telephone discussions it was decided that a Praxis engineer will visit MTU to assist in the test work and dewatering of the sample. This work has been scheduled for December 1991 to January 1992. There is a significant advantage to getting the recovered coal from a pilot plant. The sample will be very close to a commercial blend, thus generating realistic combustion data which may form the basis for approaching a utility for the next phase.

There is a significant advantage to getting the recovered coal from a pilot plant. The sample will be very close to a commercial blend, thus generating realistic combustion data which may form the basis for approaching a utility for the next phase.

CONCLUSIONS AND RECOMMENDATIONS

In this quarter, project execution plans, responsibilities to transfer technical information among SSEEI, Praxis Engineers and Penn State University were finalized. Partial progress has been made against proposed activities. Laboratory furnace availability and samples needed to accomplish the overall objectives have been finalized.

The test facility to recover coal from effluent is proposed to be commissioned in December 1991. However, the base sample containing 0% reclaimed coal has been collected, prepared, and can be shipped for furnace calibration as soon as we get the work scheduled at the Penn State which is expected to be this month.

PROJECT MANAGEMENT REPORT
September 1, through November 30, 1991

Project Title: Combustion Characterization of the Blend of
Plant Coal and Recovered Coal Fines

Principal Investigator: Shyam Singh, SS Energy
Environmental International, Inc.

Other Investigators: Dr. Alan Scaroni & Mr. Bruce Miller
Combustion Laboratory, Penn State Univ.

Vas Choudhry
Praxis Engineers, Inc.

Project Monitor: Dr. Ken Ho, CRSC

COMMENTS

Because of the delay in awarding of the contract, the project has not been carried out at an accelerated pace. The SS Energy Environmental International, Inc. is a private organization and is unable to take a bigger risk. A similar statement is true in the case of Praxis Engineers.

END

**DATE
FILMED**

4 / 02 / 92