NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

DOE/PC/88855--T4

ENZYMATIC DESULFURIZATION OF COAL

DOE/PC/88855--T4

DE92 006534

Second Quarterly Report

Holometrix Report No. 2461
Holometrix Project No. DOE-12
DOE Contract No. DE-AC22-88PC88855

Submitted to:

Mr. Elias J. George
Project Manager,
U.S. Department of Energy
P.O. Box 10940, Building 922
Chochrane Mill Road
Pittsburgh, Pennsylvania 15236-0940

Prepared by:

Judith K. Marquis, Ph.D.
Principal Investigator
Boston University School of Medicine
and
Judith P. Kitchell, Ph.D.
Holometrix, Inc.

December 15, 1988

Submitted by:

HOLOMETRIX, INC.
99 Erie Street
Cambridge, Massachusetts 02139

Telephone (617) 868-8050

MASTER

ENZYMATIC DESULFURIZATION OF COAL

Second Quarterly Report

Holometrix Report No. 2461
Holometrix Project No. DOE-12
DOE Contract No. DE-AC22-88PC88855

Submitted to:

Mr. Elias J. George
Project Manager,
U.S. Department of Energy
P.O. Box 10940, Building 922
Chochrane Mill Road
Pittsburgh, Pennsylvania 15236-0940

Prepared by:

Judith K. Marquis, Ph.D.
Principal Investigator
Boston University School of Medicine
and
Judith P. Kitchell, Ph.D.
Holometrix, Inc.

December 15, 1988

Submitted by:

HOLOMETRIX, INC.
99 Erie Street
Cambridge, Massachusetts 02139
Telephone (617) 868-8050

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, name, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

EP

TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
1	INTRODUCTION	1
1.1	Program Overview	1
1.2	Summary of Results	2
2	TECHNICAL DISCUSSION	4
2.1	Utilization of Organic Solvents	4
2.2	Analytical Methods	5
3	EXPERIMENTAL PROCEDURES AND RESULTS	6
3.1	Materials and Methods	6
3.1.1	Materials	6
3.1.2	Methods	6
3.2	Results	6
3.2.1	Horseradish Peroxidase Assays With DBT	6
3.2.2	Laccase Assays With DBT	9
3.2.3	Horseradish Peroxidase/Laccase Assays With DBT	10
3.2.4	Examination of H ₂ O ₂ /DBT Reactivity	10
3.3	Microbial Studies	12
4	EVALUATION OF PROGRESS AND PLANS FOR THIRD QUARTER	15
4.1	Progress	15
4.2	Plans for the Third Quarter	15
	Appendix A: UV SCANS	
	Appendix B: MICROBIAL MEDIA	
	Appendix C: BIBLIOGRAPHY	

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.1	The "4S" Pathway	3

LIST OF TABLES

<u>Table</u>		<u>Page</u>
3.1	Horseradish Peroxidase, Laccase, and DBT Assays	8
3.2	Laccase/DBT Assays and Standards	11
3.3	Concentration Effect of H ₂ O ₂ on DBT in Isopropyl Ether	13

Section 1

INTRODUCTION

1.1 Program Overview

Numerous studies are underway to develop biological processes for the removal of both mineral and organic sulfur from coal. To remove the organic sulfur which is covalently bound, various research groups are studying strains of bacteria and fungi which can be induced to utilize organic sulfur compounds as feedstocks.

A consideration of industrial scale-up and operational requirements indicates that microbial ingestion of sulfur may produce technical difficulties that can be circumvented by the use of extracellular (i.e., secreted) or purified enzymes rather than whole microbes. For example, a 20,000 ton/day coal process would require about 200 tons of microbes to achieve a 1 percent removal of organic sulfur. If this sulfur is incorporated into the microbe, the daunting task of separating the fuel from the sulfur-enriched organisms presents added cost and process requirements.

Our current efforts to develop clean coal technology emphasize the advantages of enzymatic desulfurization techniques and have specifically addressed the potential of using partially-purified extracellular microbial enzymes or commercially available enzymes. Our work is focused on the treatment of "model" organic sulfur compounds such as dibenzothiophene (DBT) and ethylphenylsulfide (EPS). Furthermore, we are designing experiments to facilitate the enzymatic process by means of a hydrated organic solvent matrix.

During the first and second quarters of this project, our laboratories have pursued primarily the multi-step, enzymatic breakdown of DBT and the development of the Klivanov-type hydrated solvent reaction system. Previous studies with the aromatic sulfur compound DBT have shown that there are two general biological pathways for the oxidative breakdown of this compound. In the reaction most frequently observed in microbial oxidative

pathways, DBT is oxidized at a ring carbon, and the reaction is accompanied by a considerable decrease in the free energy of the compound. Our work is focused on oxidation at the sulfur with consequent liberation of inorganic sulfate. The identification of this multi-step ("4S") reaction pathway has led us to examine each of the oxidized sulfur intermediates, as well as the desulfurized product. These compounds are illustrated in Figure 1.1.

1.2 Summary of Results

This report covers the period October 1, 1988 to December 15, 1988.

Our technical progress in the first quarter can be summarized as follows. We have worked with laccase and horseradish peroxidase in buffer and in aqueous organic solvents. After establishing the activity of our enzymes in buffer, many tests of activity against standard substrates in hydrated dioxane and hydrated DMF media were made. In both solvents, conditions were found for obtaining activity. We obtained some evidence of activity against dibenzothiophene [DBT]. We also investigated spectral and chromatographic methods of identification of the compounds in the "4S" pathway.

In the second quarter, the screening of media for the enzyme reactions with DBT was expanded. Changes in buffer were examined and several more hydrophobic solvents were utilized. An extensive amount of data was obtained by gas chromatography, utilizing a method which identifies the products of the "4-S" pathway. Particular success was noted with peroxidase in new solvents. It does seem that the high concentrations of DBT often utilized for easy detection with the GC may inhibit enzyme activity. The reactivity of DBT with H_2O_2 at varying concentrations was measured and it was shown that at the levels utilized, little if any oxidation occurs.

Figure 1.1

THE "4S" PATHWAY

Section 2

TECHNICAL DISCUSSION

2.1 Utilization of Organic Solvents

This quarter has been especially productive in our work on Task 2 (Development of an Enzymatic Model Compound Desulfurization Process in Non-Aqueous Media). We have achieved a breakthrough as the result of Judith K. Marquis' technical discussions of the general concept with Dr. Alexander Klibanov when he recently visited the Boston University Medical School to present a seminar. Recalling that it was the work of Dr. Klibanov on changing activities of enzymes inorganic solvents which led to the initial concept of an organic reaction medium for the coal program, it was of particular interest to learn of his most recent work on enzyme-catalyzed processes in organic solvents.

Dr. Klibanov's comments made it clear that while the range of solvents which may be utilized is large, the number of solvents which may be effective for a specific task could be very limited. Klibanov and his co-workers have now elucidated the importance of the effect of the organic solvent on the enzyme-bound water. Many enzymes require a certain amount of water (essential water) for activity. If the essential water molecules are loosely bound to the enzyme surface, they may be stripped away by hydrophilic or water-miscible solvents, and this stripping can destroy catalytic activity. The extent to which such stripping may be a significant factor will vary depending on the charge distribution on the surface of the enzyme molecule as well as on the electrostatic interaction required for correct formation of an enzyme-(water)-substrate complex, and, further, the need to maintain a critical level of enzyme-bound water in the system.

The importance of the hydrophilicity of organic solvents in achieving successful enzyme activity within an essential water layer, as emphasized by Dr. Klibanov's discussion, causes us to carefully reexamine our own work. In our initial use of only DMF and dioxane, two solvents which are highly water absorbant, as components of the enzyme media, we may

have severely underestimated the impact of solvent-related physicochemical factors and, thus, seriously restricted the likelihood of success. Based on the new information which we obtained, we have designed a more comprehensive "solvent survey" experiment. A range of solvents of varying (but generally low) hydrophilicity was chosen for evaluation. In the last month, several new organic media have been tested with the enzyme-DBT assays. Solvents used with one or both enzymes were: heptane, isopropyl ether, hexane, ethyl acetate, toluene, benzene, THF, and acetonitrile, the latter two solvents having been suggested by our DOE TPO. The procedures and results are described in Section 3.

2.2 Analytical Methods

We are presently utilizing two analytical methods in the DBT assays. Both of these methods were briefly described in the First Quarterly Report; however, we would like to comment on the values of the two procedures. One method is UV/VIS spectrophotometry. This method is fast, sensitive (0.2 mM DBT), and is certainly an indication of change in media composition. It is useful especially in noting the decrease in DBT concentration and the presence of colored open-ring products. Because the various oxidation products have overlapping spectra, the results are difficult to interpret with much detail.

The second method of analysis of DBT assays is gas chromatography. We have set up a system which quantitates DBT (in the range of 0.2 to 20 mM) and sulfur oxidation products in the media. The "turn-around-time" for each sample in this method is thirty minutes, so the number of measurements made per day is limited. The GC method measures reduction in the DBT level regardless of the products, but it does not identify open-ring products.

It will be most helpful to our work to obtain GC-mass spectroscopy analysis of our assay. Product identification will greatly assist us in designing the work with coal and the scale-up work. Also, the capabilities of these commercially available enzymes will be compared with those of the microbial systems being isolated at Woods Hole Oceanographic Institute.

Section 3

EXPERIMENTAL PROCEDURES AND RESULTS

3.1 Materials and Methods

3.1.1 Materials

In addition to the materials listed in the First Quarterly Report, the following materials are used: Rainin Nylon-66, syringe filter units (0.2 μ pore size, 3 mm diameter; catalogue no. 38-159).

3.1.2 Methods

The gas chromatography is performed on a Varian 3700 gas chromatograph with a flame ionization detector. The column is a 3 percent SP2250, 100/120 supelcoport. The carrier gas is N₂, at 30 ml/min. The column conditions are: detector = 260°C and injector = 260°C. For screening, the column is initially held at 150°C for 5 minutes after injection; a rise of 10°C/min. until a final temperature of 250°C is reached; this is held for 10 minutes. Under these conditions, the DBT sulfone and sulfoxide are not resolved, however, resolution is obtained if the temperature rise is slowed to 2°C/minute. The output is recorded and integrated on a Varian 4270 integrator.

Assays are performed either at room temperature or at 30°C, as noted. Except as noted, enzymes were dissolved in buffer or water at 20 mg/ml concentration. Hydrogen peroxide (200 mM) was added to the enzyme solution in peroxidase assays and the concentrated enzyme solution was then added to the organic media. Vigorous agitation was utilized in assays, except as noted. Aliquots were taken at various intervals and filtered to remove enzyme.

3.2 Results

3.2.1 Horseradish Peroxidase Assays With DBT

(A) INITIAL TESTS WITH NEW SOLVENTS: A range of solvents of varying (but generally very low) hydrophilicity was selected to evaluate HRP

activity: heptane, isopropyl ether, hexane, ethyl acetate, toluene, and benzene. DBT (290 μ M) was added directly to the solvent. HRP (20 mg/ml) plus 200 nM H_2O_2 is dissolved in double distilled water (pH 5.5). The trace concentration of H_2O_2 was selected as that which is just below the threshold for producing spectrophotometric interference. 100 μ l of enzyme-cofactor mixture is added to each 20 ml solvent-substrate sample. Each sample is incubated with continuous agitation to overcome diffusional energy reaction barriers. Each sample was analyzed by UV spectroscopy at T = 1 hour, 5 days, and 7 days. The UV scans are included in Appendix A. The UV results are summarized as follows.

- Heptane : strong shift of low wavelength peaks to longer 225 to 230 and 265 disappears, then 230 to 257.
- Hexane : broad absorbance around 230 to 250 disappears.
- IPRE : slight separation of peaks at 265 and 280.
- Benzene : no change for one week.
- Ethyl Acetate: slight separation of peaks at 265 and 280.
- Toluene : no change for one week.

An aliquot of each sample was filtered and analyzed by GC at 7 days. The GC results are shown in Table 3.1. It can be seen that several new compounds show up at this time, particularly in the heptane, hexane, and ethyl acetate media. The design of scale-up experiments is focused on the observation that the two most apolar solvents, heptane and hexane, provided good media for the enzymatic reaction of HRP and DBT with only trace amounts of H_2O_2 added. In addition, experiments with acetate, a considerably more polar solvent, produced a second substantial peak with a very long RT on the GC. These reaction products await GC/MS analysis for identification.

(B) INCREASE IN DBT CONCENTRATION: On Day 8, to the above solutions, enough new DBT was added to make them 20 mM. No spectroscopic changes were observed in the toluene and benzene systems, so they were discarded. The others (heptane, hexane, isopropyl ether, and ethyl acetate)

Table 3.1

HORSERADISH PEROXIDASE, LACCASE, AND DBT ASSAYS

ENZYME AND SOLVENT PRESENT	TIME (days)	[DBT] (mM)	AREAS UNDER CURVES ($\times 10^{-3}$) AND PERCENTS OF TOTAL AREA AT VARIOUS RETENTION TIMES** (min)			
			11.6	11.7 to 17.6	17.9 to 20	20.1 to 24
HRP/heptane	2	0.29	3.18 (82.8%)	0.48 (12.5%)	0.18 (4.7%)	
HRP/isopropyl ether	2	0.29	8.76 (95.3%)	0.20 (2.1%)	0.15 (1.6%)	
HRP/hexane	2	0.29	9.86 (85.8%)	1.64 (14.2%)		
HRP/EtOAc	2	0.29	6.31 (68.4%)	1.30 (14.1%)	0.46 (5.0%)	1.15 (12.5%)
HRP/benzene	2	0.29	9.25 (90.7%)	0.46 (4.5%)	0.26 (2.5%)	0.23 (2.3%)
HRP/toluene	2	0.29	7.25 (97.4%)	0.19 (2.6%)		
HRP/LAC/heptane	14	20	7,330.33 (99.1%)	30.10 (0.4%)	33.45 (0.5%)	6.15 (0.1%)
HRP/LAC/isopreth	14	20	4,715.89 (99.8%)	8.23 (0.2%)		
HRP/LAC/hexane	14	20	5,413.43 (100.0%)	0.79 (0.0%)	0.28 (0.0%)	
HRP/LAC/EtOAc	14	20	4,053.70 (99.9%)	0.14 (0.0%)	2.23 (0.1%)	

* This table covers the experiments described in Sections 3.2.1A, 3.2.1B, and 3.2.3.

**Standards run in dioxane show retention times are follows: diphenol - 10.42; DBT - 11.6; DBT sulfoxide and DBT sulfone - 17.7 - 17.89.

were kept under agitating conditions until Day 12 when laccase was added to the media as described in Section 3.2.3.

3.2.2 Laccase Assays With DBT

(A) LACCASE IN 5% PHOSPHATE BUFFER/ORGANIC SOLVENT MEDIA: The buffer is 0.001 M phosphate (pH 6.5); the solvents were DMF and dioxane. The first set of assays was done in 5% buffer/95% solvent (v/v) with a final DBT concentration of 20 mM. For the "dry" method assays, dry laccase - 5 mg in 10 ml of buffer/DMF media (0.5 mg/ml) and 4.8 mg in 10 ml of buffer/dioxane media (0.48 mg/ml) - was added. The assays were done without agitation at 30°C. For the "wet" method, 19.9 mg laccase was added to 8 ml of buffer but it did not all dissolve and the solution was filtered. The stock concentration was thus less than 2.49 mg/ml. Of the stock, 0.5 ml was added to 9.5 ml of 21 mM buffer/DMF and buffer/dioxane media. The final enzyme concentration was less than 0.13 mg/ml and the final DBT concentration was 20 mM.

The changes in DBT concentration over time were measured daily for two days by GC, and the results are shown below.

MEASUREMENT OF CHANGE IN CONCENTRATION OF DBT:

- "Dry" Buffer/DMF: Down 17.2% at 24 hours;
Up at 48 hours (evaporation had occurred).
- "Wet" Buffer/DMF: Down 4.55 at 24 hours;
Up at 48 hours (evaporation had occurred).
- "Dry" Buffer/Dioxane: Down 13.9% at 24 hours;
Up at 48 hours (evaporation had occurred).
- "Wet" Buffer/Dioxane: Up 11.2% at 24 hours;
Up at 48 hours (evaporation had occurred).

(B) 1% PHOSPHATE BUFFER/99% ORGANIC MEDIA: The buffer is 0.001 M phosphate (pH 6.5); the solvents were DMF and dioxane. The second set of assays was done in 1% buffer/99% solvent (v/v) with a final DBT concentration of 20 mM. Only the "dry" method of assay was used and dry lac-

case - 5 mg in 10 ml of buffer/DMF media (0.5 mg/ml) and 5 mg in 10 ml of buffer/dioxane media (0.5 mg/ml) - was added. The assays were done without agitation at 30°C. The final DBT concentration was 20 mM. The results showed that the DBT concentration did not change over two days.

(C) LACCASE IN ACETATE BUFFER/ORGANIC SOLVENT MEDIA: The buffer is 0.01 M acetate (pH 5); the solvents were DMF and dioxane. The second set of assays was done in 5% buffer/95% solvent (v/v) with a final DBT concentration of 20 mM. The "dry" method of assay was used and dry laccase - about 5 mg in 10 ml of media (0.5 mg/ml) - was added. The assays were done without agitation at 30°C. The final DBT concentration was 20 mM.

The changes in DBT concentration over time were measured after two days by GC. The results are shown in Table 3.2.

(D) LACCASE IN NEW ORGANIC SOLVENTS: Additional solvents tested without water or buffer added were: THF, toluene, heptane, hexane, isopropyl ether, ethylacetate, dioxane, acetonitrile, DMF, and benzene. The laccase (100 µl of 20 mg/ml) was added to 20 ml solvent with 20 mM DBT. For the first two systems, a sample was taken at time zero and another at fourteen days. For the latter eight, aliquots were taken at two and eight days. The aliquots were filtered and analyzed by GC. The results are shown in Table 3.2. It can be seen that some new compounds appear.

3.2.3 Horseradish Peroxidase/Laccase Assays With DBT

The four samples described in Section 3.2.1B on Day 12 of incubation were altered by the addition of 100 µl of a 20 mg/ml solution of laccase. They were agitated for an additional two days. The experiment was terminated and aliquots were filtered and analyzed by GC. The results, shown in Table 3.1, indicate that laccase showed slight activity.

3.2.4 Examination of H₂O₂/DBT Reactivity

For these experiments, 20 mM DBT solutions in isopropyl ether were prepared. Four concentrations of H₂O₂ were tested: 0.3, 0.15, 0.06, and 0.03 percent. The analyses were made after three days. The results,

Table 3.2

LACCASE/DBT ASSAYS AND STANDARDS

EXPERIMENT REFERENCE	SOLVENT	TIME (days)	AREAS UNDER CURVES ($\times 10^{-3}$) AND PERCENTS OF TOTAL AREA AT VARIOUS RETENTION TIMES (min)								
			10.42		11.6		11.7 to 17.6		17.7 to 17.9		20.1 to 24
			DIPHENOL	DBT	UNKNOWN	SULFOXIDE SULFONE	UNKNOWN	UNKNOWN			
Standard Standard	DBT in acetate/DMF "4S" compounds in dioxane		736.46	2,364.99 (99.62) 1,395.32 ( )	6.82 (0.32) 0.09	2.31 (0.12) 1,783.99	1.38 (0.12)				
Standard	DBT in aq. toluene			1,494.28 (99.52)	4.65 (0.32)		3.45 (0.22)				
Standard	DBT in acetate/DMF			1,611.45 (100.02)	0.72 (0.02)						
Standard	DBT in acetate/diox.			3,064.91 (100.02)	0.31 (0.02)		0.21 (0.02)				
3.2.2-C	Acetate/DMF*	0		1,157.76 (98.22)	20.05 (1.72)		0.79 (0.12)				
3.2.2-C	Acetate/DMF*	0		2,198.95 (99.92)	0.56 (0.02)		2.17 (0.12)				
3.2.2-C	Acetate/DMF*	1		2,787.38 (99.62)	1.82 (0.12)		1.28 (0.02)		4.52 (0.22)		
3.2.2-C	Acetate/DMF*	1		2,937.74 (100.02)	1.23 (0.02)		1.21 (0.12)		0.27 (0.02)		
3.2.2-C	Acetate/DMF	0		1,165.33 (98.22)	19.84 (1.72)		2.11 (0.22)		1.06 (0.12)		
3.2.2-C	Acetate/DMF	0		1,202.87 (97.72)	25.18 (2.02)		0.91 (0.02)		12.92 (0.42)		
3.2.2-C	Acetate/DMF	1		3,579.58 (99.62)	11.34 (0.32)		8.22 (0.32)				
3.2.2-C	Acetate/DMF	1		2,904.39 (99.22)	2.33 (0.12)		0.22 (0.02)		2.17 (0.02)		
3.2.2-C	Acetate/Dioxane*	0		1,172.50 (100.02)	0.14 (0.02)		0.45 (0.02)				
3.2.2-C	Acetate/Dioxane*	0		5,288.22 (99.92)	0.28 (0.02)		0.75 (0.02)				
3.2.2-C	Acetate/Dioxane*	1		3,036.83 (99.72)	5.85 (0.22)		5.26 (0.22)		0.74 (0.02)		
3.2.2-C	Acetate/Dioxane*	1		2,541.31 (99.32)	12.89 (0.52)		0.63 (0.02)				
3.2.2-C	Acetate/Dioxane	0		4,753.57 (99.92)	5.08 (0.12)		1.93 (0.12)				
3.2.2-C	Acetate/Dioxane	0		2,247.94 (99.82)	3.36 (0.12)		3.16 (0.12)				
3.2.2-C	Acetate/Dioxane	1		2,456.91 (99.52)	8.10 (0.32)						
3.2.2-C	Acetate/Dioxane	1		2,968.07 (99.62)	11.64 (0.42)						
3.2.2-D	Toluene	14		1,167.17 (99.82)	2.26 (0.22)						
3.2.2-D	Toluene	14		950.02 (99.22)	7.43 (0.82)						
3.2.2-D	THF	14		2,075.45 (99.92)	2.44 (0.12)						
3.2.2-D	THF	14		1,479.76 (100.02)	0.42 (0.02)		0.32 (0.02)		31.26 (0.72)		
3.2.2-D	Heptane	2		4,641.75 (97.72)	31.42 (0.72)		45.10 (0.92)		2.11 (0.02)		
3.2.2-D	Hexane	2		5,651.31 (99.92)	4.01 (0.12)		1.68 (0.02)		1.30 (0.02)		
3.2.2-D	DMF	2		2,912.93 (98.72)	35.63 (1.22)		1.60 (0.12)		0.20 (0.02)		
3.2.2-D	Dioxane	2		2,912.79 (99.92)	1.28 (0.02)		0.38 (0.02)				
3.2.2-D	Acetonitrile	2		2,744.89 (99.72)	6.48 (0.22)		0.61 (0.02)				
3.2.2-D	Benzene	2		2,730.09 (99.82)	4.57 (0.22)		0.28 (0.02)				
3.2.2-D	Isopropyl ether	2		4,311.50 (100.02)	0.31 (0.02)		0.00 (0.02)				
3.2.2-D	Ethyl acetate	2		4,120.66 (99.92)	2.47 (0.12)		0.19 (0.02)				

* Dry addition of laccase.

shown in Table 3.3, indicate that at these concentrations some oxidation does occur. It should be noted that the amount utilized in the experiments is much less than 0.03 percent.

3.3 Microbial Studies

Samples (9) from the Guaymas Basin hydrothermal vents were inoculated into a marine basal salt medium (see Appendix B for recipe) containing 0.1 percent dibenzothiophene (DBT) or ethylphenylsulfide (EPS) as the sole carbon and energy source. After more than ten weeks at room temperature (~24°C), only one of the enrichment cultures (sample from core 1967 with DBT) appeared to be positive for growth and DBT oxidation. The culture had little turbidity and had turned a reddish color that was clearly water soluble (see Appendix A). In addition, the appearance of the added DBT had changed. One milliliter of this culture was inoculated into 50 ml of similar medium and medium that contained 0.05 percent salicylate in addition to DBT. Both subsequent cultures had a reddish-yellow appearance after one to two weeks incubation. A photograph of the cultures is shown in Figure 3.1. Material from all three cultures has now been streaked on 0.01 percent yeast extract agar plates, plates with no added carbon source (other than DBT), and plates with 0.05 percent thiophene carboxylate. All plates contained the Lyman and Fleming seawater basal salts as diluent and were sprayed with a DBT solution (2 percent in acetone) to coat the plates with a fine suspension of DBT crystals. Each plate received approximately 0.75 to 1 ml of solution. From here we hope to obtain colonies of pure or mixed cultures that can oxidize DBT. We have also reinoculated from DBT-mineral salt medium with the same mud sample that was used to get the original positive enrichment.

Table 3.3

CONCENTRATION EFFECT OF H_2O_2 ON DBT IN ISOPROPYL ETHER

CONCENTRATION OF H ₂ O ₂	AREAS UNDER CURVES (x10 ⁻³)		AND PERCENTS OF TOTAL AREA AT VARIOUS RETENTION TIMES (min)			
	10.42 DIPHENOL	11.6 DBT	11.7 to 17.6 UNKNOWN	17.7 to 17.9 SULFOXIDE SULFONE	17.9 to 20 UNKNOWN	20.1 to 24 UNKNOWN
0.3%	0	379.43 (97.1%)	3.21 (0.8%)	2.8 (0.7%)	5.17 (1.3%)	0 (0.0%)
0.15%	0	2,447.70 (93.5%)	8.76 (0.3%)	0 (0.0%)	160.59 (6.1%)	0 (0.0%)
0.06%	0	470.49 (99.4%)	0 (0.0%)	0 (0.0%)	2.85 (0.6%)	0 (0.0%)
0.03%	0	774.07 (95.6%)	2.2 (0.3%)	0 (0.0%)	33.28 (4.1%)	0.304 (0.0%)

Figure 3.1

FLASKS CONTAINING THE ORIGINAL INOCULUM FROM THE GUAYMAS BASIN
WITH DBT (CENTER), THE SECOND INOCULUM IN SIMILAR MEDIUM (RIGHT), AND
THE SECOND INOCULUM IN SALICYLATE ENRICHED MEDIUM (LEFT)

Section 4

EVALUATION OF PROGRESS AND PLANS FOR THIRD QUARTER

4.1 Progress

The data presented here provide initial evidence that at least a fraction of DBT can be converted to other compounds with very low concentrations of HRP and H_2O_2 , and also to a lesser extent with laccase. The data also support the suggestion made in our original proposal that laccase can function in sequence with peroxidase. The reaction system requires considerable definition and amplification and it remains to be seen whether enzymatic reaction mechanisms can, in fact, lead to the actual removal of oxidized organic sulfur moieties from the model compounds.

The microbial data are also quite promising, as one of eight source samples has provided microbes that alter DBT, although considerable analytical work must be done to define the nature of these alterations and to identify the reaction products.

4.2 Plans for the Third Quarter

Our plans for the third quarter are: (1) to continue the enzyme assays with greater emphasis on EPS as a substrate; (2) to identify the reaction products obtained by GC/MS; (3) to evaluate various ratios of aqueous/non-aqueous conditions with both enzymes and both substrates; (4) to determine the accelerating effects, if any, of co-factor and buffer concentrations; and (5) to scale up the productive reactions defined recently. In addition, we will shortly begin the analytical evaluation of the microbial desulfurization media.

Appendix A

UV SCANS

Note - medium was filtered at
0.22µm prior to spectral analysis

Scale: 0-0.6 OD.
GRANN #2

CAT NO. 33-35-16
PRINTED IN U.S.A.

SPECTRONIC (A X X)

Filtered Medium

Scale 0-2.5 O.D.

GRAPH #1

CAT NO 33-35-16

PRINTED IN U.S.A.

SPECTRONIC 1000

Note:

Filtered medium from original culture 0.22 μ m filter

LKB WAVELENGTH SCAN

Heptane
1 hour

Operator: VARYING SOLVENTS D=1

Date: 11-23-1988

Plot title: N-HEPTANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	225.5	2.066	1	225.5	2.066
2	265.5	0.875	3	285.5	1.329
3	285.5	1.329	2	265.5	0.875
4	315.5	0.368	5	325.5	0.437
5	325.5	0.437	4	315.5	0.368

T = 1 HOUR

Heptane
5 days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-28-1988
Plot title: HEPTANE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	230.5	2.144	1	230.5	2.144
2	285.5	1.342	2	285.5	1.342
3	315.5	0.373	4	325.5	0.453
4	325.5	0.453	3	315.5	0.373
5	420.5	0.008	5	420.5	0.008

Heptane
7 days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT

Date: 11-30-1988

Plot title: HEPTANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs

1	257.5	1.872	1	257.5	1.872
2	285.5	1.527	2	285.5	1.527
3	315.5	0.545	4	325.5	0.616
4	325.5	0.616	3	315.5	0.545
5	386.0	0.171	5	386.0	0.171

LKB WAVELENGTH SCAN

Heptane
7 Days
Expanded Scale

Operator: EXPANDED DBT DAY7

Date: 11-30-1988

Plot title: HEPTANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 350

Scan speed,nm/s: 2

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	284.5	1.386	1	284.5	1.386
2	325.5	0.451	2	325.5	0.451

T: 7 DAYS, EXPANDED SCALE

Hexane

1 Hr

LKB WAVELENGTH SCAN

Operator: VARYING SOLVENTS D=1

Date: 11-23-1988

Plot title: HEXANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	285.5	1.537	1	285.5	1.537
2	315.5	0.449	3	325.5	0.531
3	325.5	0.531	2	315.5	0.449
4	385.5	0.005	4	385.5	0.005

T = 1 HOUR

Hexane
5 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-28-1988
Plot title: HEXANE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	285.5	1.549	1	285.5	1.549
2	315.5	0.457	3	325.5	0.553
3	325.5	0.553	2	315.5	0.457
4	390.5	0.004	5	405.5	0.010
5	405.5	0.010	4	390.5	0.004
6	419.5	-0.001	6	419.5	-0.001

Hexane

7 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT

Date: 11-30-1988

Plot title: HEXANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	285.5	1.631	1	285.5	1.631
2	315.5	0.481	3	325.5	0.570
3	325.5	0.570	2	315.5	0.481
4	420.5	0.003	4	420.5	0.003

T = 7 DAYS

LKB WAVELENGTH SCAN

Hexane
Expanded Scale
Day 7

Operator: EXPANDED DBT DAY7

Date: 11-30-1988

Plot title: HEXANE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 350

Scan speed, nm/s: 2

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	284.5	1.648	1	284.5	1.648
2	313.5	0.497	3	324.5	0.575
3	324.5	0.575	2	313.5	0.497

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	284.5	1.648	1	284.5	1.648
2	313.5	0.497	3	324.5	0.575
3	324.5	0.575	2	313.5	0.497

T = 7 DAYS, EXPANDED SCALE

LKB WAVELENGTH SCAN

*The prep of Ether
1 hour*

Operator: VARYING SOLVENTS D=1

Date: 11-23-1988

Plot title: ISOPROPOL ETHER

Mode Abs/%T: Abs

Plot scaler: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 600

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	285.5	1.623	1	285.5	1.623
2	325.5	0.630	2	325.5	0.630
3	395.5	-0.020	6	585.5	0.003
4	455.5	-0.016	5	490.5	-0.009
5	490.5	-0.009	4	455.5	-0.016
6	585.5	0.003	3	395.5	-0.020

IPE
5 days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-28-1988
Plot title: IPE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	265.5	1.593	1	265.5	1.593
2	280.5	1.569	2	280.5	1.569
3	310.5	0.555	4	325.5	0.620
4	325.5	0.620	3	310.5	0.555
5	400.5	0.045	5	400.5	0.045

T: 5 DAYS

I PE
7 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
 Date: 11-30-1988
 Plot title: *I PE*
 Mode Abs/%T: Abs
 Plot scale: 3
 Plot offset: 0
 Start W/length: 200
 Stop W/length: 450
 Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	265.5	1.488	1	265.5	1.488
2	280.5	1.451	2	280.5	1.451
3	310.5	0.597	4	325.5	0.634
4	325.5	0.634	3	310.5	0.597
5	391.0	0.009	6	410.5	0.026
6	410.5	0.026	5	391.0	0.009

IPE
Day 7
Expanded Scale

LKB WAVELENGTH SCAN

Operator: EXPANDED DBT DAY7
Date: 11-30-1988
Plot title: ISOPROPOL ETHER
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 250
Stop W/length: 350
Scan speed, nm/s: 2

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	264.5	1.574	1	264.5	1.574
2	280.5	1.562	2	280.5	1.562
3	312.5	0.584	4	324.5	0.632
4	324.5	0.632	3	312.5	0.584

T = 7 DAYS, EXPANDED SCALE

LKB WAVELENGTH SCAN

Benzene

1 Hr

Operator: VARYING SOLVENTS D=1
Date: 11-23-1988
Plot title: BENZENE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 600
Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	285.5	1.811	1	285.5	1.811
2	315.5	0.740	3	325.5	0.840
3	325.5	0.840	2	315.5	0.740
4	400.5	-0.002	4	400.5	-0.002

Benzene

5 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT

Date: 11-28-1988

Plot title: BENZENE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	285.5	1.823	1	285.5	1.823
2	315.5	0.733	3	325.5	0.845
3	325.5	0.845	2	315.5	0.733
4	395.5	0.010	4	395.5	0.010

Benzene
7 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-30-1988
Plot title: BENZENE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	285.5	1.801	1	285.5	1.801
2	315.5	0.705	3	325.5	0.809
3	325.5	0.809	2	315.5	0.705
4	385.5	0.025	5	405.5	0.035
5	405.5	0.035	4	385.5	0.025

T= 7 DAYS

LKB WAVELENGTH SCAN

Ethyl Acetate
1 Hour

Operator: VARYING SOLVENTS D=1

Date: 11-23-1988

Plot title: ETHYL ACETATE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 600

Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	265.5	1.935	1	265.5	1.935
2	285.5	1.662	2	285.5	1.662
3	325.5	0.517	3	325.5	0.517
4	400.5	-0.033	7	475.5	-0.030
5	410.5	-0.044	4	400.5	-0.033
6	425.5	-0.037	6	425.5	-0.037
7	475.5	-0.030	5	410.5	-0.044

T = 1 HOUR

Ethyl Acetate
5 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-28-1988
Plot title: ETHYL ACETATE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	260.5	1.129	1	260.5	1.129
2	285.5	0.938	2	285.5	0.938
3	325.5	0.156	3	325.5	0.156
4	395.0	-0.011	4	395.0	-0.011

T = 5 DAYS

Ethyl Acetate
7 days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT

Date: 11-30-1988

Plot title: ETHYL ACETATE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed,nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	260.5	1.099	1	260.5	1.099
2	285.5	0.970	2	285.5	0.970
3	325.5	0.183	3	325.5	0.183

Toluene
1 Hr

LKB WAVELENGTH SCAN

Operator: VARYING SOLVENTS D=1
Date: 11-23-1988
Plot title: TOLUENE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 600
Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	286.0	0.549	1	286.0	0.549
2	315.5	0.333	3	325.5	0.387
3	325.5	0.387	2	315.5	0.333
4	570.5	-0.004	4	570.5	-0.004
5	596.0	-0.010	5	596.0	-0.010

LKB WAVELENGTH SCAN

Toluene
5 Days

Operator: SOL. TEST .29MM DBT

Date: 11-28-1988

Plot title: TOLUENE

Mode Abs/%T: Abs

Plot scale: 3

Plot offset: 0

Start W/length: 200

Stop W/length: 450

Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :

By Peak Height:

Peak	WAVELENGTH nm	Peak Height Abs	Peak	WAVELENGTH nm	Peak Height Abs
1	285.5	0.963	1	285.5	0.963
2	315.5	0.477	3	325.5	0.579
3	325.5	0.579	2	315.5	0.477

T = 5 DAYS

Toluene
7 Days

LKB WAVELENGTH SCAN

Operator: SOL. TEST .29MM DBT
Date: 11-30-1988
Plot title: TOLUENE
Mode Abs/%T: Abs
Plot scale: 3
Plot offset: 0
Start W/length: 200
Stop W/length: 450
Scan speed, nm/s: 5

SAMPLE NUMBER: 2

By WAVELENGTH :			By Peak Height:		
Peak	WAVELENGTH	Peak Height	Peak	WAVELENGTH	Peak Height
	nm	Abs		nm	Abs
1	285.5	0.947	1	285.5	0.947
2	315.5	0.451	3	325.5	0.540
3	325.5	0.540	2	315.5	0.451

Appendix B
MICROBIAL MEDIA

DESCRIPTIONS OF MEDIA AND SOLUTIONS

DILUENT: Lyman and Fleming* Artificial Sea Water (Modified)
 (* J. Mar. Res. 3:134-146)

MATERIAL	AMOUNT (grams/liter)
NaCl	23.477
MgCl ₂ •6H ₂ O	4.981 (changed from 10.635)
Na ₂ SO ₄	3.917
CaCl ₂ •2H ₂ O	1.102 (changed from 1.459)
KCl	0.664
NaHCO ₃	0.192
KBr	0.096
H ₃ BO ₃	0.026
SrCl ₂ •6H ₂ O	0.026 (changed from 0.040)
NaF	eliminated

BASAL MEDIUM: to 1 liter of Lyman and Fleming Artificial Sea Water

MATERIAL	AMOUNT (grams/liter)
*NH ₄ Cl	0.5
KHPO ₄ (buffer), 750 mM, pH 7.2	2.7 ml (final concentration 2 mM PO ₄)
Wolfe's Mineral Solution	5 ml
*DAB's Vitamin Solution	5 ml

* Added after autoclaving as sterile stocks.
 Medium was pH'ed to ~7.2, aseptically with sterile NaOH or HCl after autoclaving.

WOLFE's MINERAL SOLUTION (Modified)

MATERIAL	AMOUNT (grams/liter)
Nitrilotriacetic Acid (NTA)	1.5
MgSO ₄ ·7H ₂ O	3.0
MnSO ₄ ·H ₂ O	0.5
NaCl	1.0
FeSO ₄ ·7H ₂ O	0.1
CoSO ₇ or CoCl ₂	0.1
CaCl ₂ ·2H ₂ O	0.1
ZnSO ₄	0.1
CuSO ₄ ·5H ₂ O	0.01
AlK(SO ₄) ₂	0.01
H ₃ BO ₃	0.01
NaMoO ₄	0.40

Dissolve NTA with KOH in 500 ml of distilled H₂O. pH to 6.5, and add each ingredient in order. Bring to 1 liter after addition of all components.

DAB's 10 VITAMIN SOLUTION (add 5 ml per liter of medium)

MATERIAL	mg/500 ml	FINAL CONCENTRATION OF MEDIA ($\mu\text{g L}^{-1}$)
Niacin	5	50
Biotin	2	20
Pantothenate	5	50
Lipic (Thioctic) Acid	5	50
Folic Acid	2	20
p-aminobenzoic Acid	5	50
Thiamine (B ₁)	5	50
Riboflavin (B ₂)	5	50
Pyridoxine (B ₆)	5	50
Cobalamin (B ₁₂)	5	50

Filter, sterilize, and store refrigerated in the dark

Appendix C
BIBLIOGRAPHY

BIBLIOGRAPHY FOR ENZYMATIC DESULFURIZATION OF COAL

- Clark, D.P., K.Y. Alam, N. Absulrashid, and B. Klubek, "Successive Mutation of E. coli for Improved Thiophene Degradation, Scientific Note," Applied Biochem. & Biotechnol. 18:393-401 (1988).
- Dordick, J.S., M.A. Marletta, and A.M. Klibanov, "Peroxidases Depolymerize Lignin in Organic Media but Not in Water," Proc. Natl. Acad. Sci. U.S.A. 83:6255-6257 (1986).
- Dordick, J.S., A.M. Klibanov, and M.A. Marletta, "Horseradish Peroxidase Catalyzed Hydroxylations: Mechanistic Studies," Biochemistry 25:2946-2951 (1986).
- Ensley, Jr., B.D., "Microbial Metabolism of Condensed Thiophenes," Microbial Degradation of Organic Compounds, New York, Dekker, pp 309-317 (1984).
- Evans, T.L. and M.M. Grade, "Phase Transfer Controlled Selective Oxidation of Diarylsulfides to Diarylsulfoxides Using Potassium Hydrogen Persulfate," Synthetic Communications 16(10):1207-1216 (1986).
- Gilman, H. and D.L. Esmay, "The Oxidation of Dibenzothiophene and Phenoxathiin With Hydrogen Peroxide," J. Am. Chem. Soc. (74):2021-2024 (1952).
- Jannasch, H.W., C.O. Wirsén, S.J. Molyneaux, and T.A. Langworthy, "Extremely Thermophilic Fermentative Archaeobacteria of the Genus Desulfurococcus from Deep-Sea Hydrothermal Vents," Applied and Environmental Microbiology 54(5):1203-1209 (1988).
- Kabanov, A.V., A.V. Levashov, N.L. Klyachko, S.N. Namyotkin, A.V. Pshezhetsky, and K. Martinek, "Enzymes Entrapped in Reversed Micelles of Surfactants in Organic Solvents: A Theoretical Treatment of the Catalytic Activity Regulation," J. Theor. Biol. 133:327-343 (1988).
- Kirk, T.K., "Enzymatic "Combustion": The Microbial Degradation of Lignin," Ann. Rev. Microbiol. 41:465-505 (1987).
- Krawiec, S., "Detection, Isolation, and Initial Characterization of Bacteria With the Ability to Desulfurize Dibenzothiophene to o,o'-Biphenol," Presented at the Bioprocessing of Coals Workshop, Tyson's Corner, Virginia, August 15-18, 1988.
- Mal, D. and G. Biswas, "Detection of Organosulphur Compounds on Thin Layers Using Dragendorff's Reagent," J. of Chromatography 387:556-558 (1987).
- Monticello, D.J., "Microbial Desulfurization of Fossil Fuels," Ann. Rev. Microbiol. 39:371-389 (1985).
- Ngaiza, O.G., D.L. Wise, and T.R. Gilbert, "Enzymatic Removal of Organic Sulfur from Coal," Northeastern University, Boston, MA (1988).

- Scott, C.D. and S.N. Lewis, "Biological Solubilization of Coal Using Both In Vivo and In Vitro Processes, Scientific Note," Applied Biochem. & Biotechnol. 18:403-412 (1988).
- Srinivasan, C., A. Chellamani, and S. Rajagopal, "Mechanism of the Oxidation of Alkyl Aryl and Diphenyl Sulfides by Chromium (VI)," J. Org. Chem. 50:1201-1205 (1985).
- Srinivasan, C. and P. Subramaniam, "Selective Oxidation of Sulphides to Sulphoxides With Peroxodisulphate," Indian Journal of Chemistry 26B:193-194 (1987).
- Takayanagi, H., M. Akita, K. Fujimura, and T. Ando, "Ligand-Exchange Gas Chromatographic Separation of Aromatic Sulphides," J. of Chromatography 350:75-85 (1985).
- Umezawa, T. and T. Higuchi, "Mechanism of Aromatic Ring Cleavage of β -O-4 Lignin Substructure Models by Lignin Peroxidase," FEBS Lett. 218(2):255-260 (1987).
- van Afferden, M., S. Schacht, M. Beyer, and J. Klein, "Microbial Desulfurization of Dibenzothiophene," Applied Biochem. & Biotechnol 33(4):561-572, September, 1988.
- Zaks, A. and A.M. Klibanov, "The Effect of Water on Enzyme Action in Organic Media," J. Biol. Chem. 263(17):8017-8021 (1988).
- Zaks, A. and A.M. Klibanov, "Substrate Specificity of Enzymes in Organic Solvents Vs. Water Is Reversed," J. Am. Chem. Soc. 108:2767-2768 (1986).
- Zaks, A. and A.M. Klibanov, "Enzymatic Catalysis in Organic Media at 100°C," Science 224:1249-1251 (1984).

END

**DATE
FILMED**

2 / 27 / 92