ADVANCED
FUEL
RESEARCH

P.O. Box 380343
East Hartford, Connecticut 06138-0343
Telephone (203) 528-9806

DOE/PC/89878--T6

"FUNDAMENTAL STUDIES OF WATER PRETREATMENT OF COAL"

DOE/PC/89878--T6

Seventh Quarterly Report

DE92 004871

#523070-21

For the Period

April 1, 1991 - June 30, 1991

MICHAEL A. SERIO
PETER R. SOLOMON
ERIK KROO
SYLVIE CHARPENAY
AND
ROSEMARY BASSILAKIS

Work Performed Under Contract No. DE-AC22-89PC89878

William E. McKinstry, Project Manager

by

ADVANCED FUEL RESEARCH, INC.

87 Church Street
East Hartford, CT 06108
(203) 528-9806

"US/DOE Patent Clearance is not required prior to the publication of this document."

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

402

Research, analytical services and consulting for the development of new and improved clean fuels.

"FUNDAMENTAL STUDIES OF WATER PRETREATMENT OF COAL"**SEVENTH QUARTERLY REPORT
CONTRACT NO. DE-AC22-89PC89878**

OCT 28 1991

Table of Contents

DISCLAIMER	i
ABSTRACT	ii
I. Introduction and Summary	1
II. Task 1 - Project Planning and Sample Selection	5
III. Task 2 - Experiments on the Water Pretreatment Stage	6
IV. Task 3 - Analysis of Products	8
V. Task 4 - Rates, Mechanisms and Modeling	12
VI. Plans for the Eighth Quarter	13
REFERENCES	14

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

During the seventh quarter, water pretreatment experiments were done at lower pressures (1000 psig), with early H₂O injection or continuous H₂O injection, and with demineralized coals. In addition, a set of blank experiments was done with all four coals in helium at the following conditions: 350°C; 4000 psig; 20 minutes. An additional experiment was done with the Zap lignite at atmospheric pressure. Helium was used instead of nitrogen since it can be obtained in highly pure grades. The purpose of the blank experiments is to determine how much of the water pretreatment process is a thermal and/or pressure effort.

The residues from the standard water pretreatment experiments with Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen reactivity index and donor solvent liquefaction. It was found that, for the bituminous coals, the tar yield generally declines slowly with increasing pretreatment time, although, for the Illinois coal, the existence of a slight maximum cannot be ruled out. This is in contrast to the lower rank coals where the tar yield goes through a sharp maximum at short pretreatment times before undergoing a slow decline.

The results for the pyridine extractables are very interesting. In the case of the Illinois coal, pretreatment for 20 minutes resulted in a more than doubling of the % DAF pyridine extractables (81 vs. 36%). The results were lower when an ampoule of Illinois coal was used which was not freshly opened (75 vs 81%). The results to date indicate that of the four coals examined (Zap, Wyodak, Illinois, Pittsburgh), the Illinois coal is the most sensitive to coal freshness. Qualitatively, the results for pyridine extractables from the Illinois coal are similar to Zap coal (rapid increase followed by a slow decline). For the Pittsburgh coal, the pyridine extractables increase slowly with increasing pretreatment time.

With regard to liquefaction behavior, improvements in the yields of oils and toluene solubles are observed for selected Illinois and Pittsburgh coals at longer pretreatment times (≥ 60 minutes). However, these results could not be reproduced consistently with the Illinois coal. It appeared that the results were sensitive to the "freshness" of the coal. For ampoules which were just opened, the yields of soluble products from the pretreated coals were lower than for samples which had been opened days or weeks earlier and stored in a nitrogen purged glove box. The results are consistent with the fact that the pretreated samples are reacting with the solvent, especially the observation of negative oil yields. The very fresh samples appear to be the most reactive toward solvent adduction. This same phenomenon may explain why the liquefaction yields for the pretreated Zap lignite go through a minimum at short pretreatment times, and are less than for the raw lignite. This hypothesis will be tested during the next quarter.

The data from the experiments done on water pretreatment were entered into a spreadsheet in order to facilitate comparison with the changes in experimental conditions and coal types. A visit was made to AFR by Dr. Michael Siskin who has been working for several years on the reactions of water with model compounds in the temperature range of 200-350°C. His work has demonstrated that there are plausible pathways for water to remove or reduce oxygen functional groups (e.g., conversion of alcohols to methyl groups) which is observed in water pretreatment of coal.

I. INTRODUCTION AND SUMMARY

Introduction

The goals of this project are to gain understanding of the chemistry of water or steam coal pretreatments and to assess the importance of such pretreatments on subsequent coal liquefaction. For the achievement of these goals, coals, modified coals and model-polymers will be treated with water or steam. This study will include three coals, five modifications (dried, demineralized, ion-exchanged, Ca-loaded, Ba-loaded), three polymers and two polymer modifications (e.g. acid chlorides, amides). Experiments will be performed to investigate both conventional steam pretreatment and the possibility of using the CO/H₂O system of Ross and coworkers as a pretreatment method. The main experimental variables will be sample type and temperature. Detailed characterization of the gas, liquid and solid products from the pretreatment stage will be done. This will include analysis of gases by GC or FT-IR, liquids by capillary GC, FT-IR and FIMS, and residues by solvent swelling, solvent extraction, and elemental analysis. Selected residues will also be evaluated by a standard liquefaction test. Analysis of the raw coals and pretreatment samples will be performed using the above techniques to study changes in the crosslinking, donatable hydrogen, heteroatom composition, evolved gases, functional group composition, extraction yields, molecular weight distributions, etc. Standard tubing bomb liquefaction tests will be used to determine the effect of pretreatment on coal reactivity toward coal liquefaction. A previously developed model for coal liquefaction, the FG-DVC liquefaction model, will be used (after appropriate modifications) to model the physics and chemistry of water pretreatment.

Summary of Work During the Seventh Quarter

Task 2 - Pretreatment Experiments - During the seventh quarter, additional low pressure (1000 psig) water pretreatment experiments were done with the Illinois coal at 350°C, 180 minutes. These were done in order to study the effects of water pretreatment under lower pressure conditions which were more common in previous studies (Graff and Brandes, 1986, 1987; Khan et al., 1989).

The water pretreatment system was modified to allow the water to be injected (and removed) continuously during the pretreatment process. This capability is important in light of recent work

by Michael Siskin and coworkers with model compounds which suggests that the initial reaction of water with organics produces compounds (e.g., formaldehyde) which act as reducing agents in subsequent reactions.

Additional water pretreatment experiments were done with Illinois No. 6 and Pittsburgh seam bituminous coals at 350°C, 4000 psig and pretreatment times of 20-1200 minutes. These are conditions where interesting results were observed with the two lower rank coals. The standard water injection procedure was used. The experiments were done primarily at very short times (20-60 minutes) and very long times (300 - 1000 minutes) with selected intermediate points to cover the range of pretreatment behavior.

Water pretreatment experiments were also done with demineralized Zap, Wyodak and Illinois coals. The demineralized coals were prepared using the procedure of Bishop and Ward (1958), which involves treatment with HCl and HF. The pretreatment experiments were done at the following conditions: 350°C; 4000 psig; 20, 60 or 1200 minutes.

A set of blank experiments was done with all four coals in helium at the following conditions: 350°C; 4000 psig; 20 minutes. An additional experiment was done with the Zap lignite at atmospheric pressure. Helium was used instead of nitrogen since it can be obtained in highly pure grades. The purpose of the blank experiments is to determine how much of the water pretreatment process is a thermal and/or pressure effort.

Task 3 - Analysis of Products - The residues from the low pressure (1000 psig) experiments with Illinois No. 6 coal were subjected to TG-FTIR analysis (programmed pyrolysis) and donor solvent liquefaction. When compared to results at 4000 psig, there was a slight reduction in the pyrolysis tar yield and slight improvement in yields of oils (with a corresponding reduction in toluene solubles) and pyridine solubles from liquefaction. There was a significant improvement in the yield of oils from the lower pressure pretreatment experiment when compared to the raw coal (again, with a corresponding reduction in the yield of toluene solubles). Consequently, it appears that water pretreatment at lower pressures may offer some benefits in liquefaction of Illinois coal that were not observed for the Wyodak coal (reported previously).

The residues from the continuous water injection experiments with Zap, Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen

reactivity index and donor solvent liquefaction. One of the more interesting results is that the amount of CO_2 evolved during the water pretreatment step was significantly higher with continuous water injection. This suggests that the formation of CO_2 may be limited by equilibrium under these conditions.

It was also found that the oxygen reactivities of the residues produced with continuous water injection were higher. Consequently, it appears that the film of water soluble material which normally deposits on the water pretreated residues must mask the true reactivity.

The gas and tar yields from programmed pyrolysis in the TG-FTIR were similar for the residues produced from either the Case 1 (standard) or Case 3 (continuous) pretreatment methods. The results for the pyridine extractables measurements and liquefaction experiments are not yet complete.

The residues from the standard water pretreatment experiments with Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen reactivity index and donor solvent liquefaction. It was found that, for the bituminous coals, the tar yield generally declines slowly with increasing pretreatment time, although, for the Illinois coal, the existence of a slight maximum cannot be ruled out. This is in contrast to the lower rank coals where the tar yield goes through a sharp maximum at short pretreatment times before undergoing a slow decline.

The results for the pyridine extractables are very interesting. In the case of the Illinois coal, pretreatment for 20 minutes resulted in a more than doubling of the % DAF pyridine extractables (81 vs. 36%). The results were lower when an ampoule of Illinois coal was used which was not freshly opened (75 vs 81%). The results to date indicate that of the four coals examined (Zap, Wyodak, Illinois, Pittsburgh), the Illinois coal is the most sensitive to coal freshness. Qualitatively, the results for pyridine extractables from the Illinois coal are similar to Zap coal (rapid increase followed by a slow decline). For the Pittsburgh coal, the pyridine extractables increase slowly with increasing pretreatment time.

With regard to liquefaction behavior, improvements in the yields of oils and toluene solubles are observed for selected Illinois and Pittsburgh coals at longer pretreatment times (≥ 60 minutes). However, these results could not be reproduced consistently with the Illinois coal. It appeared

that the results were sensitive to the "freshness" of the coal. For ampoules which were just opened, the yields of soluble products from the pretreated coals were lower than for samples which had been opened days or weeks earlier and stored in a nitrogen purged glove box. The results are consistent with the fact that the pretreated samples are reacting with the solvent, especially the observation of negative oil yields. The very fresh samples appear to be the most reactive toward solvent adduction. This same phenomenon may explain why the liquefaction yields for the pretreated Zap lignite go through a minimum at short pretreatment times, and are less than for the raw lignite. This hypothesis will be tested during the next quarter.

Task 4 - Modeling - The data from the experiments done on water pretreatment were entered into a spreadsheet in order to facilitate comparison with the changes in experimental conditions and coal types. The spreadsheet program also interfaces with a plotting program which simplifies the generation and updating of plots. A macro is being developed to automatically generate plots from this database. We have now done more than 85 experiments and each experiment has more than 50 columns of data on conditions, pretreatment yields, residue analyses, etc., since the data are often calculated on more than one basis (dry, DAF, normalized, etc.). Consequently, the use of the spreadsheet became necessary. While it will take some time to set this up, it is easy to maintain and will also make it easy to share data with others in the water pretreatment research area.

A visit was made to AFR by Dr. Michael Siskin who has been working for several years on the reactions of water with model compounds in the temperature range of 200-350°C. His work concludes that 1) it is the ionic chemistry of water that is important under the pretreatment conditions; 2) that reactions in water systems are often "autocatalyzed" by water soluble organic reaction products; 3) aqueous chemistry provides cleavage pathways for major oxygen crosslinks which are too stable to cleave thermally; 4) reactions of water with organics can be catalyzed by clays. His work has demonstrated that there are plausible pathways for water to remove or reduce oxygen functional groups (e.g., conversion of alcohols to methyl groups) which is observed in water pretreatment of coal.

II. TASK 1 - PROJECT PLANNING AND SAMPLE SELECTION

This task has been completed.

III. TASK 2 - EXPERIMENTS ON THE WATER PRETREATMENT STAGE

Low Pressure Experiments - During the seventh quarter, additional low pressure (1000 psig) water pretreatment experiments were done with the Illinois coal at 350°C, 180 minutes. These were done in order to study the effects of water pretreatment under lower pressure conditions which were more common in previous studies (Graff and Brandes, 1986, 1987; Khan et al., 1989).

Early H₂O Injection - In the water pretreatment experiments that have been done to date, ~ 1 ml of water is added at the beginning and then the sample is immersed in the fluidized sand bath for rapid heating to the final pretreatment temperature, during which water is pumped continuously until a volume corresponding to the desired final pressure has been injected (Case 1). For example, to achieve 4000 psig at 350°C, ~ 15 ml of water is pumped into the system. A concern was raised that the samples may be heated through the active crosslinking period (200-350°C) without the full water pressure being exerted. Consequently, the experiment was modified so that the full 15 ml is injected at the very beginning prior to the heatup period (Case 2). Experiments were done for both Zap and Illinois coals using this modified procedure.

Continuous H₂O Injection - The water pretreatment system was modified to allow the water to be injected (and removed) continuously during the pretreatment process (Case 3). This capability is important in light of recent work by Michael Siskin and coworkers with model compounds which suggest that the initial reaction of water with organics produces compounds (e.g., formaldehyde) which act as reducing agents in subsequent reactions. A second motivation was that reactivity tests were being done on the residues from water pretreatment to test the hypothesis of geological aging (more mature coals are less reactive). It was thought that the water soluble material may deposit on the surface of the residue and obscure these results. The continuous water extraction experiments were done with Zap, Illinois and Pittsburgh coals at conditions of 350°C, 4000 psig, 60-180 minutes pretreatment time.

Experiments with Bituminous Coals - Additional water pretreatment experiments were done with Illinois No. 6 and Pittsburgh seam bituminous coals at 350°C, 4000 psig and pretreatment times of 20-1200 minutes. These are conditions where interesting results were observed with the

two lower rank coals. The standard water injection procedure was used (Case 1). The experiments were done primarily at very short times (20-60 minutes) and very long times (300 - 1000 minutes) with selected intermediate points to cover the range of pretreatment behavior.

Demineralized Coals - Water pretreatment experiments were done with demineralized Zap, Wyodak and Illinois coals. The demineralized coals were prepared using the procedure of Bishop and Ward (1958), which involves treatment with HCl and HF. The pretreatment experiments were done at the following conditions: 350°C; 4000 psig; 20, 60 or 1200 minutes.

Blank Experiments - A set of blank experiments was done with all four coals in helium at the following conditions: 350°C; 4000 psig; 20 minutes. An additional experiment was done with the Zap lignite at atmospheric pressure. Helium was used instead of nitrogen since it can be obtained in highly pure grades. The purpose of the blank experiments is to determine how much of the water pretreatment process is a thermal and/or pressure effort. Of course, since the coals contain moisture, it is difficult to rule out the effect of H₂O on the basis of these blank experiments. A second series of experiments will be done where the coal is dried "in-situ" prior to the helium pretreatments. However, even this is not definitive for low rank coals since water is formed from pyrolysis reactions under the standard pretreatment temperatures (~350°C).

IV. TASK 3 - ANALYSIS OF PRODUCTS

Low Pressure Experiments - The residues from the low pressure (1000 psig) experiments with Illinois No. 6 coal were subjected to TG-FTIR analysis (programmed pyrolysis) and donor solvent liquefaction. When compared to results at 4000 psig, there was a slight reduction in the pyrolysis tar yield and slight improvement in yields of oils (with a corresponding reduction in toluene solubles) and pyridine solubles from liquefaction. There was a significant improvement in the yield of oils from the lower pressure pretreatment experiment when compared to the raw coal (again, with a corresponding reduction in the yield of toluene solubles). Consequently, it appears that water pretreatment at lower pressures may offer some benefits in liquefaction of Illinois coal that were not observed for the Wyodak coal (reported previously). However, this result will have to be considered in light of the difficulty in reproducing the liquefaction results for water pretreated Illinois coals, as discussed below.

Early H₂O Injection - The residues from the water pretreatment experiments with Illinois and Wyodak coal using early H₂O injection were subjected to analysis by TG-FTIR and donor solvent liquefaction. For the Wyodak coal, the tar yields from pyrolysis were not much different than for the standard water pretreatment experiments under the same final temperature (350°C), pressure (4000 psig) and time (20 min., 60 min.) conditions. However, the yields of major gaseous species from pyrolysis (CO₂, CO, CH₄) were lower. There was a significant increase in the yields of pyridine extractables (~ factor of two) from the Wyodak coal pretreated with early H₂O injection. There was also a significant improvement in the yields of toluene solubles and pyridine solubles from liquefaction of the Wyodak coal compared to the standard pretreatment condition. However, the liquefaction results were still lower than for the raw coal.

In the case of the Illinois coal, pretreated with early H₂O injection, the pyrolysis results were similar to the standard pretreatment case and the liquefaction results are not yet available.

Continuous H₂O Injection - The residues from the continuous water injection experiments with Zap, Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen reactivity index and donor solvent liquefaction. One of the more interesting results is that the amount of CO₂ evolved during the water pretreatment step was significantly higher with continuous water injection. This suggests that the formation of CO₂ may be limited by equilibrium under these conditions.

It was also found that the oxygen reactivities of the residues produced with continuous water injection were higher. Consequently, it appears that the film of water soluble material which normally deposits on the water pretreated residues must mask the true reactivity.

The gas and tar yields from programmed pyrolysis in the TG-FTIR were similar for the residues produced from either the Case 1 (standard) or Case 3 (continuous) pretreatment methods. The results for the pyridine extractables measurements and liquefaction experiments are not yet complete.

Experiments with Bituminous Coals - The residues from the standard water pretreatment experiments with Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen reactivity index and donor solvent liquefaction. Some of these results were presented in Table IV-1 of the Sixth Quarterly Report, which is repeated here for the purpose of discussion, and which includes additional data and corrections to the original table. It was found that, for the bituminous coals, the tar yield generally declines slowly with increasing pretreatment time, although, for the Illinois coal, the existence of a slight maximum cannot be ruled out (see Table IV-1). This is in contrast to the lower rank coals where the tar yield goes through a sharp maximum at short pretreatment times before undergoing a slow decline.

The results for the pyridine extractables are very interesting. In the case of the Illinois coal, pretreatment for 20 minutes resulted in a more than doubling of the % DAF pyridine extractables (81 vs. 36%). The results were lower when an ampoule of Illinois coal was used which was not freshly opened (75 vs 81%). The results to date indicate that of the four coals examined (Zap, Wyodak, Illinois, Pittsburgh), the Illinois coal is the most sensitive to coal freshness. Qualitatively, the results for pyridine extractables from the Illinois coal are similar to Zap coal (rapid increase followed by a slow decline). For the Pittsburgh coal, the pyridine extractables increase slowly with increasing pretreatment time.

With regard to liquefaction behavior, improvements in the yields of oils and toluene solubles are observed for selected Illinois and Pittsburgh coals at longer pretreatment times (≥ 60 minutes). However, these results could not be reproduced consistently with the Illinois coal. It appeared that the results were sensitive to the "freshness" of the coal. For ampoules which were just opened, the yields of soluble products from the pretreated coals were lower than for samples

which had been opened days or weeks earlier and stored in a nitrogen purged glove box. The results are consistent with the fact that the pretreated samples are reacting with the solvent, especially the observation of negative oil yields. The very fresh samples appear to be the most reactive toward solvent adduction. This same phenomenon may explain why the liquefaction yields for the pretreated Zap lignite go through a minimum at short pretreatment times, and are less than for the raw lignite. This hypothesis will be tested during the next quarter.

Demineralized Coals and Blank Experiments - The residues from the water pretreatment experiments with demineralized Zap, Wyodak and Illinois coals and the blank experiments in helium with Zap, Wyodak, Illinois and Pittsburgh coals were subjected to analysis by TG-FTIR, solvent extraction, solvent swelling, oxygen reactivity index and donor solvent liquefaction.

The pyrolysis and liquefaction results for the demineralized residues are not yet complete. The preliminary results suggest that demineralization is beneficial prior to water pretreatment of Zap lignite but not for Illinois No. 6. coal. In the latter case, a problem with demineralization is that it is difficult to prevent partial oxidation of the coal during this procedure. As discussed above, it has been found that the Illinois coal from the Argonne premium sample bank is particularly sensitive to exposure to oxygen.

The liquefaction results for the blank experiments are not yet available. The pyrolysis results for the Zap and Illinois blank experiments do indicate that the presence of added water is important. This was not the case for the Wyodak coal, where the tar yields were comparable. However, the Wyodak does have a high moisture content so the intrinsic moisture content or the pyrolysis water may be providing the water function. Additional blanks will be done with dried coals to address this question.

The data on pyridine extractables yield were only available for the Illinois coal. In this case the amounts were comparable to the reference water pretreatment experiment.

TABLE IV-1
COMPARISON OF PYROLYSIS TAR, EXTRACTABLES, AND LIQUEFACTION YIELDS
FOR FOUR COALS WHICH HAVE UNDERGONE WATER PRETREATMENT

Coal	Run Number	Experimental Conditions			Pyrolysis Results (norm. 1 wt.%)			Pyridine Extractables		Liquefaction Yields (DAF wt.%)		
		Temp (°C)	Press (psig)	Time (min.)	Tar	CO ₂	CH ₄	Norm. Wt. %	Dry DAF %	Oils	Toluene Solubles	Pyridine Solubles
Zap	1001	—	—	—	6	4.8	1.1	9	5	14	36	44
	6	350	4000	20	12	3.3	1.5	8		12	18	21
	26	350	4000	600	10	2.1	1.6	3		7	35	50
Wyodak	1003	—	—	—	9	6.1	1.5	11	11	15	41	65
	23	350	4000	20	13	3.9	1.9			18	35	53
	25	350	4000	600	8	1.8	2.1	8		10	30	54
Illinois	1005*	—	—	—	29	0.9	2.2	33	36	17	47	98
	36	350	4000	20	31	0.7	2.1		75	1	47	86
	66*	350	4000	20	34	0.7	2.4		81	-13	11	58
	37	350	4000	60	27	1.1	2.4		79	39	59	93
	60*	350	4000	60	20	0.5	1.8		76	-27	40	90
	48	350	4000	300	22	0.5	1.3		45	17	41	86
Pittsburgh	68*	350	4000	300	23	1.2	2.9		40	14	35	50
	45	350	4000	1080	17	0.7	2.2		32	11	27	40
	39	—	—	—	23	2.6	3.7	23	28	3	31	82
	38	350	4000	20	21	0.7	3.0		44	10	26	85
	61	350	4000	1080	24	2.1	4.1		58	14	37	58

* Experiments run with freshly opened ampoules.

V. TASK 4 - RATES, MECHANISMS AND MODELING

The data from the experiments done on water pretreatment were entered into a spreadsheet in order to facilitate comparison with the changes in experimental conditions and coal types. The spreadsheet program also interfaces with a plotting program which simplifies the generation and updating of plots. A macro is being developed to automatically generate plots from this database. We have now done more than 85 experiments and each experiment has more than 50 columns of data on conditions, pretreatment yields, residue analyses, etc., since the data are often calculated on more than one basis (dry, DAF, normalized, etc.). Consequently, the use of the spreadsheet became necessary. While it will take some time to set this up, it is easy to maintain and will also make it easy to share data with others in the water pretreatment research area.

A visit was made to AFR by Dr. Michael Siskin who has been working for several years on the reactions of water with model compounds in the temperature range of 200-350°C. His work concludes that 1) it is the ionic chemistry of water that is important under the pretreatment conditions; 2) that reactions in water systems are often "autocatalyzed" by water soluble organic reaction products; 3) aqueous chemistry provides cleavage pathways for major oxygen crosslinks which are too stable to cleave thermally; 4) reactions of water with organics can be catalyzed by clays. His work has demonstrated that there are plausible pathways for water to remove or reduce oxygen functional groups (e.g., conversion of alcohols to methyl groups) which is observed in water pretreatment of coal.

END

DATE
FILMED
2 120192

I