DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE/ER/40622--1

DE92 006942

Progress Report

Period: January 1, 1991 to October 31, 1991

U.S. Department of Energy Grant No. DE-FG05-91ER40622

EXPERIMENTAL STUDY OF HEAVY FLAVOR PHYSICS AND SSC RESEARCH AND DEVELOPMENT

at

The University of Mississippi

Principal Investigator

James J. Reidy, Chair and Professor of Physics

Co-Principal Investigators

Lucien M. Cremaldi, Assistant Professor of Physics

Donald J. Summers, Assistant Professor of Physics

Physics Department

University, MS 38677

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *EB*

Table of Contents

	Page
A. Introduction	1
B. Progress in the Experimental and Theoretical High Energy Physics Program During the Period 1/1/91 to 10/31/91	2
1. E691	2
2. E769	5
3. E791	7
4. Theory	11
C. Progress in the SSC Research and Development Program During the Period 1/1/91 to 10/31/91	11
1. Adaptation of the HETC-based CALOR89 Code to a UNIX Environment	12
2. Liquid Scintillator R&D	19
3. The Hanging File Calorimeter Program(T841) at Fermilab	20
4. Contributions to the Calorimeter Programs for GEM and SDC ..	21
5. The SAHEP Initiative and the TNRLC	22
D. Summary	23
Appendix	25
1. Publications	
2. Abstracts	
3. E769	
4. E791	
5. Theory	
6. SSC R&D	

A. Introduction

The University of Mississippi High Energy Physics (UMiss HEP) Group is partially supported by the U.S. Department of Energy grant no. DE-FG05-91ER40622 and the Texas National Research Laboratory Commission (TNRLC) project number RCFY91 30 through the SAHEP consortium. It presently consists of three tenured or tenure-track faculty - Professors Cremaldi, Reidy and Summers, one visiting faculty - Professor Weinstein, two postdoctoral associates - Drs. Gounder and Moore, one technician(temporary) and five graduate students with assistance from the physics department's electronics technician, machinist, computer systems manager and administrative coordinator. One of the postdoctoral associates is funded by the TNRLC and the technician has a one year appointment funded through the SSC R&D program. Two of the graduate students, Mr. Ali Rafatian and Ms. Danying Yi, having passed their Ph.D. qualifying examinations, are presently in residence at Fermilab. Three undergraduate students and three additional graduate students in computer science have made significant contributions to the E791 and SSC R&D programs. A 4.0 GPA B.S. physics student from Mississippi State University, Breese Quinn, who was supported by us to work on E791 in the summer 1990, accepted our offer of the one year technician position in our group and will enter physics graduate school next fall.

The UMiss HEP group has also established a cooperative program with the Memphis State University Physics Department whereby those students at Memphis State who are interested in high energy physics can work with our group and later transfer to the University of Mississippi as Ph.D. candidates in high energy physics. One student from Memphis State University, Mr. John Turner, has participated in E791 at Fermilab and is planning to transfer here next year. Prof. M. S. Jahan is collaborating on radiation damage studies using TLD and ESR techniques and several others are assisting us in the CALOR89 development. The HEP group also has a cooperative research program with Jackson State University(an HBCU). Two faculty, Profs. Fred Lott and H. Zhang, work with us on SSC-related detector simulation projects.

The HEP group is involved in three Fermilab experiments, E691, E769 and E791 with the latter experiment presently running at the Tagged Photon Laboratory. This series of trend-setting heavy quark experiments has been the most productive at the lab in the past few years. E691/E769/E791 have set the standard for high rate data acquisition systems, innovative reconstruction of large data samples and analysis techniques. These experiments have been manned by international collaborations and have produced a number of quality Ph.D. students. Drs. Summers and Cremaldi are senior collaboration members and guide many day-to-day decisions. The UMiss group has expended major resources toward the success of the experiments and is expected to be a leader in the large analysis efforts in the future. In support of these analysis efforts a 900 MIP "farm" is presently being assembled at UMiss.

In addition, the group has an ongoing SSC R&D program dealing with (a) the adaptation and use of the HETC-based detector simulation code CALOR89, (b) the development of liquid scintillator technology for use in SSC detector calorimeters, (c) the hanging file calorimeter project (T841 at FNAL), (d) the calorimetry program for GEM and SDC and (e) serving as Principal Investigator of the SAHEP program funded by the Texas National Research Laboratory Commission and chair of the executive committee for SAHEP. This \$1M (FY91) program involves a consortium of sixteen universities and Oak Ridge National Laboratory and has as its purpose the enhancement of the infrastructure of these universities thereby enabling them to make significantly greater contributions to the SSC program. The major contributions of the UMiss HEP group in these SSC efforts lie mainly in the areas of detector development and simulation, simulation code development and fast data acquisition systems.

**B. Progress in the Experimental High Energy Physics Program during the period
1/1/91 to 10/31/91**

1. E691 (Photoproduction of Charm): Centro Brasileiro de Pesquisas Fisicas(CBPF), Carleton University, University of Cincinnati, FNAL, University

of Mississippi, National Research Council of Canada, Princeton University, Universidade de Sao Paulo, University of Toronto, Yale University - Prof. Cremaldi.

E691 was a high statistics charm photoproduction experiment run at FNAL in the summer of 1985. About 20 journal articles, mostly in Physical Review Letters have been published. Additional papers are forthcoming and 25-30 papers should result in all. We have about 25 invited talks appearing in conference proceedings over the years. Seven graduate students have completed theses on E691, five more are now finishing. The E691 analyses will come to completion in the next year or so with the graduation of these students.

Dr. Cremaldi has published two papers on charmed baryon production and decays. He has published a very accurate Λ_c lifetime measurement "Measurement of the Λ_c^+ Lifetime", which soundly established the lifetime at about $2.2 (\pm 15\%)$ psec. In 1989 he published in PRL a measurement of the Σ_c^0 mass and production ratio relative to $\Lambda_c \rightarrow pK\pi$, "Observation of $\Sigma_c \rightarrow \Lambda_c^+ \pi^-$ Decays". Two additional papers were published by Dr. M. Gibney at U. of Colorado in PRD, "A Study of the Decays of the Λ_c^+ " and "A Study of the Decays of $D \rightarrow K^0 \pi^+$ and $D \rightarrow K^0 K^+$ ". In all the Colorado/Mississippi group has been quite productive.

Dr. Cremaldi is finishing a Dalitz plot analysis of the $pK\pi$ final state produced in Λ_c decays. There have been no other accounts of such an analysis in the literature. An interesting feature has shown up on the Dalitz plot, first reported at the Spring 1991 Meeting of the APS (Bulletin of the American Physical Society **36-4**, 1246). In addition to a strong K^* band, a low mass pK enhancement appears on the Dalitz plot. It may be explained by an accumulation of low mass NK resonances ($\Lambda(1405)$, $\Lambda(1520)$, etc.) whose tails feed into the low end of the Dalitz plot on the $m^2(pK)$ axis. The K^* and low pK enhancement practically saturate the Dalitz plot and thus few nonresonant decays of the Λ_c charmed baryon into $pK\pi$ may exist. A related, but alternative explanation of this phenomena is that of a final state interaction between proton and kaon which may occur deep within the weak decay. Such effects in lower energy phenomena have been reported. These

explanations may have exciting implications for other charmed baryon decays, yet to be studied in detail. This analysis is being completed.

A list of recent papers published by the E691 collaboration since our last DOE progress report is given below. Copies of these papers are appended to this document.

1- "Some Cabibbo-Suppressed Decays of the D^0 Meson", The Tagged Photon Spectrometer Collaboration, J.C.C. Anjos et al., Phys. Rev. D. Rapid Communications **43**, R635 (1991).

2- "A Study of the Decay $D_s^+ \rightarrow \eta' \pi^+$ ", The Tagged Photon Spectrometer Collaboration, J. C. Anjos et al., Phys. Rev. D. Rapid Comm. **43**, R2063 (1991).

3- "A Study of the Decay $D^+ \rightarrow \bar{K}^0 e^+ \nu_e$ ", The Tagged Photon Spectrometer Collaboration, J. C. Anjos et al., Phys. Rev. Lett. **67**, 1507 (1991).

Papers slated for 1991-92 publication are:

1- "Measurement of the Decays $D^0 \rightarrow \pi^+ \pi^-$ and $D^0 \rightarrow K^+ K^-$ ", The Tagged Photon Spectrometer Collaboration, J.C. Anjos et al., to be published in Phys. Rev. D. Rapid Comm. (1991).

2- "A Study of Decays $D \rightarrow K \pi \pi \nu$ and $D \rightarrow K^* \pi \nu$ ", The Tagged Photon Spectrometer Collaboration, J. C. Anjos et al., submitted to Phys. Rev. Lett.

3- "Study of the $D_s^+ \rightarrow \phi e^+ \nu_e$ and the Absolute $D_s^+ \rightarrow \phi \pi^+$ Branching Fraction", The Tagged Photon Spectrometer Collaboration, J.C.C. Anjos et al., submitted to Phys. Rev. Lett.

4- "Dalitz Plot Analysis of $\Lambda_c^+ \rightarrow p K \pi$ Decays", The Tagged Photon Spectrometer Collaboration, J.C. Anjos et al., in preparation.

5- "A Dalitz plot analysis of $K\pi\pi$ Decays", The Tagged Photon Spectrometer Collaboration, J.C. Anjos et al., in preparation.

6- "A Dalitz plot analysis of $K\pi\pi\pi$ Decays", The Tagged Photon Spectrometer Collaboration, J.C. Anjos et al., in preparation.

Some mature studies in progress include:

1- $D^{+-} \rightarrow K^- \pi^+ (\pi^0) e^+ \nu_e$ decays

2- $D \rightarrow \pi \pi e$ final states

3- $D, D_s \rightarrow K K K$ final states

2.E769 (Hadroproduction of Charm): Centro Brasileiro de Pesquisas Fisicas(CBPF), FNAL, University of Mississippi, Northeastern University, University of Toronto, Tufts University, University of Wisconsin-Madison, Yale University - Profs. Cremaldi and Summers; Rafatian.

E769 is a high statistics charm hadroproduction experiment run at FNAL's Tagged Photon Lab in the summer and fall of 1987. Charm states were produced in hadron-N interactions at $E_h=250$ GeV and reconstructed on a farm of UNIX/RISC computers. This was the first time UNIX/RISC computers had been used for reconstructing such a large data set in a high energy physics analysis.

All of E769's 10,000 nine track tapes are reconstructed. A sub-sample of events has been made based on the reconstruction of multiple vertices as seen in our silicon micro-vertex detector. Recent results were presented at the DPF meeting in Vancouver(1). They are appended to this document and include Feynman x_F and P_t distributions for charm as well as measurements of the A-dependence of charm production. E769 is the highest statistics charm hadroproduction experiment in the world. Its production studies of A-dependence and flavor

production are unique and will help guide decisions about future heavy quark experiments. Three Ph.D. dissertations have resulted so far, two from the University of Toronto and one from Yale University.

A paper describing the reconstruction farm that Prof. Don Summers and Dr. Chris Stoughton (Fermilab) put together to reconstruct E769 data has been submitted for publication(2). A copy is included in the Appendix. This reconstruction method is now being duplicated throughout the world and has been the subject of many conference talks.

Ali Rafatian is a senior graduate student working toward a Ph.D. at the University of Mississippi using E769 data. He has participated in the reconstruction effort at Fermilab for two years. Over the past year Rafatian has done studies to understand the effect of our transverse trigger on the charm production cross sections. He has been working closely with Dr. Jeff Spalding of Fermilab on this project. A full report to the E769 collaboration by Rafatian and colleagues is in the Appendix. He is also working on the extraction of the $D^0 \rightarrow K^- \pi^+ \pi^+ \pi^-$ in the data set. He will use this additional D^0 signal to crosscheck and improve the significance of production studies in other channels. A copy of Rafatian's prospectus, "Study of the Cross-section for Hadroproduced Neutral D Mesons in Experiment E769 at FNAL", has been submitted to his dissertation committee. A copy can be found in the Appendix. The defense of the prospectus is the final formal requirement before submission of the dissertation.

References

- (1) "Charm Production in 250 GeV/c Hadron-Nucleon Interactions", Robert Jedicke and Lee Lueking for the E769 Collaboration, Physics of Particles and Fields, August, 1991, Vancouver, British Columbia, CANADA
- (2) "Using Parallel Risk Computers and 8mm Tapes to Find Charm Quarks", submitted to "Computers in Physics".

3. E791 (Hadroproduction of Charm): University of California-Santa Cruz(UCSC), Centro Brasileiro de Pesquisas Fisicas(CBPF), University of Cincinnati, FNAL, Illinois Institute of Technology(IIT), University of Mississippi(UMiss), Princeton University, Ohio State University(OSU), Tel-Aviv University, Tufts University, Universidade Federal do Rio de Janeiro(UFRJ), University of Wisconsin-Madison, Yale University - Profs. Cremaldi, Reidy and Summers; Dr. Gounder; Aitala, Rafatian, Rich and Yi.

E791 is a very high statistics charm hadroproduction experiment running at FNAL's Tagged Photon Laboratory. Through π^-N interactions at $E_\pi=500$ GeV we expect to reconstruct over 100 K charm particles for detailed studies. An unbiased transverse energy trigger is used for the collection of data containing charm and other heavy states. Through an enormous data writing capability of about 10 MB/s we are able to log about 1 billion interactions per week (1000 EXABYTE tapes/wk). This resulting large data sample will be reconstructed on KMIP computing farms being set up by CBPF, OSU, and UMiss. A detailed status report on E791 is included in the Appendix with the event accumulation represented in Figure 1. A K^0 -short peak obtained from analyzing 1M events(1 tape) is represented in Figure 2.

The spectrometer had a successful shakedown run in the summer of 1990. Problems were identified and fixed. The experiment began data taking in July 1991 and has logged about 10 billion events to tape by mid-October. The University of Mississippi is involved with a number of the E791 systems. These involvements include both hardware and software. The systems include the spectrometer Cerenkov detectors, the beamline and spectrometer PWC's, the muon detection systems, the low voltage monitoring system, the platinum/diamond target and the data acquisition system. As mentioned above, we are also commissioning a KMIP farm at UMiss for the reconstruction of approximately 1/3 of the E791 data sample.

Cerenkov Detectors

Two large multi-cell Cerenkov detectors provide particle identification in the

Figure 1

The first check of the magnetic field improvement was the K-short peak. Now, I get around 1000 SMD K-shorts for a million events (1 tape). This is with a SDZ cut of around 14, corresponding to roughly 10mm. (The sigma in z is presently dominated by secondary vertex errors of 700 microns, the error is only 200 microns for the primary). The width is 4.9 ± 0.5 MeV/c², quite respectable. A sample K-short peak is reproduced below.

```

35      **
34      I
33      --I
32      * I
31      I I-
30      I *
29      -I I
28      I I
27      I I
26      * I
25      I I
24      I I*
23      I I
22      I I
21      I I
20      I I-
19      *I I
18      -I I
17      I I*
16      I I
15      I I -
14      I I-I
13      -*I I
12      I-I I
11      I *
10      - I
9      I I
8      - I -- * I--
7      I I II I *I -
6      I I II I I I
5      I --I --II*I * I
4      I I I - I * I I*- --I
3      *****I I I *****
2      I I ---I I I I-I I-I I-I- I I I I--
1      I I--I I-I- I I-I I I I I

```

Figure 2

spectrometer at the Tagged Photon Lab (TPL). All physics done at TPL has depended in varying degrees on this system. No large upgrades have been made since E691 (summer 1984) although some of the photomultiplier tubes have had to be replaced.

The Cerenkov system has operated in a stable and efficient fashion and is under the supervision of Dr. Cremaldi. The E791 spectrometer Cerenkov counters were successfully brought up for the summer 91 run with the assistance of Reidy, Summers and graduate student Eric Aitala. Eric kept a close watch on the system through the summer run phase and became quite knowledgeable about the hardware and many other details of the system. Recently a new postdoctoral research associate, Dr. Krish Gounder, has joined our group. He has phased-in to oversee the operation of these counters for the final months of the run.

The Tel Aviv University and Mississippi groups, under the supervision of Dr. Cremaldi, has taken the principal responsibility in bringing up the offline software. They are responsible for Cerenkov code conversion to the E791 CMS code management system, and calibration of the counters. Dr. Cremaldi, working closely with members of the Tel Aviv group, has recently made significant advances in bringing up the reconstruction and calibration packages. Gounder and Cremaldi, along with the Tel Aviv group, will verify the Cerenkov package for the final E791 reconstruction.

A threshold light curve using only a small amount of data but demonstrating the proper light sensing characteristics of the detectors is shown in Figure 3 on the next page.

Added Muon Detection at TPL

A major shortcoming of the E791 spectrometer at TPL is the muon detection. The semileptonic muon signal has not been competitive with the $D \rightarrow X \nu$ decays because of an added level of reconstruction background. This background originates from the unavoidable π and K decays in the spectrometer and reconstruction accidentals due to unassociated hadron track overlaps in the simple single layered TPL muon wall. We determined that even a modest

CHERENKOV LIGHT YIELD vs MOMENTUM

Here we display a normalized yield of Cherenkov photons versus momentum (GeV) for a small sample of data taken by E791. The fits show that the threshold behavior is as predicted for a N_2 gas radiator in C1 and a 80:20 mix of He to N_2 in C2.

Figure 3

addition to the existing system would greatly reduce background by misassociation. In our last proposal we requested funds for construction of a second layer of scintillator spaced behind the existing system but we received no FY91 funds for this project. However, we were convinced that this addition would enable us to extend our studies to semileptonic decays. Ultimately the University contributed \$10K and we erected a new 17 paddle wall of new scintillator to enhance the E791 muon detection in the central region. Our E791 advanced graduate student Danying Yi is responsible for this system. She assembled, checked out and mounted the system during May-July, 1991. Now she is overseeing all muon systems at TPL. Danying is hoping to be able to extract clean semileptonic charm decays in muon channels, something not done before in any TPL analysis.

Danying Yi is an excellent student who achieved the highest scores in her class on the PH.D. comprehensive examination. She has been supported by Fermilab as funds were requested but not provided for her in our FY91 budget although she had been supported in our FY90 budget! J. Peoples has only agreed to support her for the E791 running time so we must provide funds for her after January, 1992. University funds are not available for this type of support.

PWC System

This system is composed of eight beamline PWCs for beam particle tracking and two downstream Y-view planes mainly used for pattern recognition. There are about 1000 channels in all. These beam chambers are used for beam tracking in conjunction with the beamline silicon detectors. Early analysis puts our total beam track finding efficiency near 98% for a snapshot of runs. Beam tracking is important in our vertex reconstruction, especially for the implementation of a fast filter/reconstruction. The TPL PWC systems were commissioned by senior graduate student Ali Rafatian and graduate student Tim Rich. Drs. Summers and Cremaldi guided their work through the 1990 summer run and maintain close contact with them. Tim Rich worked with Ali in the summer of 91 on further checks of the PWCs, but has returned for fall classes. During this time they set the operating voltages and fixed bad readout cards as well as writing online monitoring routines for the PWC system. Rich gave an excellent summary

of the work at the last summer group meeting of the E791 collaboration. Although Rafatian is doing a dissertation on experiment E769, he is still available for consultation and emergencies relating to the PWC systems.

Low Voltage Monitoring

Dr. Summers and student Eric Aitala have implemented the low voltage monitoring system for E791. This system records and checks all low voltage levels at TPL. It is very important to the stable running of the experiment. Aitala has written and implemented much of the software and is regarded as the expert on call for this system.

Data Acquisition System

The E791 data acquisition system is performing as advertised, accepting an event every 100 microseconds and writing them to tape at 10MB/s. D. Summers was intimately involved in the design and procurement of the system. He has also designed NIM electronics for the FERA ADC readout and, working with P. Kasper at IIT, continues to maintain this system. Dr. Gounder of our group is the system manager for the TPL VAX cluster.

UMiss Reconstruction "Farm"

We are assembling a parallel UNIX/RISC computing farm at the University of Mississippi to be used in the reconstruction of E791 and in SSC simulations. About 1/3 of this \$200k system was purchased with DOE funds and the remainder with TNRLC funds. Breese Quinn, who was hired with SSC funds as the farm manager, has made exceptional progress on bringing up the UNIX farm. The farm consists of 40 DECstation Model 5000/200s with 25 MHz MIPS R3000 CPUs. The CPUs are connected over ETHERNET. For E791 analysis events will be distributed over the 40 nodes for parallel reconstruction. It is intended that this system will process 1/3 of the E791 data set or about 5 billion events (6000 raw data tapes). This reconstruction will generate about 3000 additional data summary tapes.

We received the 40 CPUs in July '91 and they have all been tested and installed. They are connected to the HEP community over INTERNET provided by UMiss.

The E769 reconstruction program has been compiled and run on these workstations as a test and to establish the "effective MIPs" for the system. We have read data from and written data to 8mm tape drives. E791 software is being ported to the DECstations for further tests. Diskless clients are currently online. Figure 4 shows a schematic of the "farm".

4. Theory (Hadron - Hadron Interaction Mechanisms): University of Mississippi, Oak Ridge National Laboratory and University of Tennessee - Prof. Weinstein

Studies are being carried out on possible hadron-hadron interaction mechanisms and a model for incorporating these mechanisms in a coupled channel formalism(1). In reviewing an application of these ideas to pseudoscalar-pseudoscalar S-wave scattering we find that s-channel resonance formation with quark exchange processes are sufficient to reproduce experimental observations and meson exchange forces are not required. We are extending this study to various systems(2).

References

1. "Low Mass Pseudoscalar-Pseudoscalar Dynamics", in preparation.
2. "Strangeness ± 2 KK Scattering in a qq $\bar{q}\bar{q}$ Potential Model, submitted to Phys. Rev. D

C. Progress in the SSC Research and Development Program during the period

1/1/91 to 10/31/91 - Profs. Cremaldi, Reidy and Summers; Dr. Moore; Brown, Ping and Yi.

Our major efforts deal mainly with (1) the adaptation of the HETC-based detector simulation code CALOR89 to a UNIX environment, (2) the development of liquid scintillator technology for use in SSC detector calorimeters, (3) the hanging file calorimeter project (T841 at FNAL), (4) the calorimetry program for GEM and

.phy.olemiss.edu

KEY

	Ethernet backbone
	Terminator
h1, c1	DECstation 5000/200 servers (workstations)
ha-hk, ca-cv	DECstation 5000/200 diskless clients (cpu's only)
hl-hp	DECstation 5000/200 diskless clients (workstations)
b1	DECstation 5000/120 (workstation)
Ds	DECserver 901
Db	DECbridge 90
DI	DECLaser 2100
SG	Silicon Graphics 4D/20
Vax	VAXstation II/GPX
ts	DECserver 200/MC
Mac	Macintosh Plus
3100	VAXstation 3100/76
fiber optic	GCI 1100 1B1F fiber optic repeater

Figure 4

SDC and (5) serving as Principal Investigator of the SAHEP proposal to the Texas National Research Laboratory Commission and chair of the executive committee for SAHEP.

This work has been primarily carried out by Dr. Brent Moore and Professors Cremaldi, Reidy and Summers with assistance from three graduate students and two undergraduate students. The calculational effort has been carried out on our Silicon Graphics workstation and the PDSF at the SSC Laboratory although we are beginning to use some of the facilities of the 900 MIP DECstation 5000/200 "farm" being assembled by the UMiss HEP group.

1. Adaptation of the HETC-based CALOR89 Code to a UNIX Environment

The CALOR computer code system, which has prime application in hadronic and electromagnetic cascade simulation as required for calorimeter design, has been in development for nearly 20 years. This code system has been heavily utilized during the past several years to carry out SSC calorimeter design. A flow diagram of the code is given in Figure 5. The three-dimensional, multimedia, high-energy nucleon-meson transport code(HETC) is used, with modifications, to obtain a detailed description of the nucleon-meson cascade produced in the calorimeter. This Monte Carlo code takes into account the slowing down of charged particles via the continuous slowing-down approximation, the decay of charged pions and muons, inelastic nucleus-nucleus and charged-pion-nucleus (excluding hydrogen) collisions through the use of the intermediate-energy intranuclear cascade-evaporation(MECC) model ($E < 3$ GeV), scaling model ($3 \leq E \leq \sim 25$ GeV), and a multi-chain fragmentation model, FLUKA, ($E \geq \sim 25$ GeV) as well as inelastic nucleon-hydrogen and charged-pion-hydrogen collisions via the isobar model ($E < 3$ GeV) and phenomenological fits to experimental data ($E > 3$ GeV). Also accounted for are elastic neutron-nucleus ($E < 100$ MeV) collisions and elastic nucleon and charged pion collisions with hydrogen. The transport of electrons, positrons and gammas is carried out using the EGS4 system. Neutrons which are produced with energies below 20 MeV are transported using the MORSE MC transport code. Time dependence is included in MORSE.

Flow diagram of the CALOR code system

CALOR

Figure 5

We originally obtained CALOR89 from Tony Gabriel of ORNL, the author of the package of programs. He and T. Handler had been running the program on an IBM 3090 mainframe at the University of Tennessee. After extensive revision it was run with some success on the UMiss mainframe IBM 3084, but this computer was difficult to use. This was due in part to the awkwardness of the VM/CMS operating system and in part to the operating policies of the university computer center which maintains the machine.

It had been our intention all along to port the package of programs to a UNIX workstation. These machines are in the process of becoming, if they have not become already, the preferred computer for use in scientific applications. In addition to being powerful and easy to use, the machines are generally workstations. This means the cost is relatively low and the scientific users who have such a computer available have control over and exclusive use of the machine.

The first UNIX machine on which CALOR was installed and run was a Silicon Graphics Personal Iris 4D/20 Workstation at the University of Mississippi. After some preliminary benchmarking, the code was taken to SSCL in May 1991 where work was done in conjunction with Lee Roberts, an SSCL physicist, to check the performance of the code on various UNIX platforms. The code was compiled and run on the Silicon Graphics 40/380 and Sun Sparc 2 Workstations of the Physics Detector Simulation Facility (PDSF) at SSCL. The code was also compiled and run on a DECstation and an IBM RISC machine. A variety of portability problems arose and quick, temporary solutions found. The code at times stopped running because of bugs in the programs. Some of these problems had arisen before and were thought to be rare, but we learned they were not as rare as supposed.

CALOR89 has also been brought up on an Apollo DN10000 at the University of Alabama by Yuwu Yu and Jerry Busenitz. We helped them, through electronic mail exchanges, in bringing up the code on this computer, and we learned about several more problems related to the portability of the code in the process. During a visit to the University of Mississippi by Yuwu Yu in August, we helped them understand how the analysis is done in the user written subroutines of SPECT,

MORSE and the EGS4 programs and assisted them in putting some tracking code in place.

The UNIX version of a couple of CALOR programs, HETC and MORSE, were given to Ken Johns of the University of Arizona who was working at Fermilab. As they intended to use the programs on a Silicon Graphics, few portability issues arose, but they have been running the program to do some neutron studies.

The high energy physics group at the University of Mississippi now has a farm of 41 DECstation 5000/Model 200 workstations that are being configured into a farm that will give the group about 900 MIPS of CPU computing power. The equipment arrived in late June and early July and is presently being checked out and the "farm" configuration assembled. Some workstations are available for computing, however, and CALOR has been run for a few events on one of the DECstations. Version 3.0 of DEC Fortran is considered to have considerable problems, but the compiler nonetheless did an excellent job of finding some dead code and undefined variables that other compilers -- particularly, the Silicon Graphics and Sun compilers -- did not detect.

In the meantime, the UNIX version that was taken to SSCL was rewritten by us to make the code as transportable as possible with as little alteration as possible. The code now runs on Silicon Graphics, Sun, and DECstation computers without alteration and requires only minimal change for use on IBM RISC and Apollo UNIX platforms.

In addition, the bugs that were in the package have been addressed. Due to a problem in the original CALOR89 program, particles sometimes tend to get lost in the geometry. A work-around for this problem has been implemented by throwing away the particle that is lost and treating it as though it had escaped. This allows the program to continue running. As the error occurs only rarely, this is not of great concern. The program prints out considerable information about the lost particle including the particle type, the energy of the particle and its energy, the particles old and new locations, and the event number in which the error occurred. This information can help the user decide whether the loss of a

particle can be expected to significantly affect the results enough to warrant throwing out the event in the final analysis.

It would be preferable, of course, to fix the bug that is causing the problem in the first place. Diagnosing the difficulty, however, is expected to be a very involved undertaking. While this certainly should be pursued, the temporary work-arounds should assure that the programs are viable and useful until a permanent solution is found.

Considerable and detailed documentation has been written and is continuing to be developed on the new UNIX versions to help users and to outline the changes from the IBM version that have been put in place.

The current UNIX version of CALOR89 has been labeled Unix Version 3 or CALOR89/U3. On November 10, 1991 this version of CALOR89 was made available to SSCL for installation on PDSF and for general distribution to users in the high energy physics community who wish to run the code on their own machines.

In summary, CALOR89 is now running at the University of Mississippi on a Silicon Graphics Personal Iris 4D/20 workstation and on DEC 5000/200 workstations as well as the IBM 3084 campus mainframe. We have been running the UNIX version of the code on the PDSF facility at the SSCL where it runs on both the Silicon Graphics batch ranch machines and on the Sun Sparc 2 front-end workstations.

In addition, UNIX versions of CALOR89 created at the University of Mississippi are currently being used by groups at the University of Alabama on an Apollo DN10000 and at Fermilab by University of Arizona researchers.

Some features of CALOR/U3:

A number of new features and enhancements have been incorporated into the

UNIX version of CALOR which should make the code easier to use and more robust. Following is a partial list of these features:

1 -Parameters Set in Input Files Rather than Being "Hardwired" Into the Programs

Previously, in HETC and EGSPREP for electrons only, one had to edit user-modified subroutines to input information such as type of particle to begin transporting, the energy, position and direction of the initial particle, and the dimensions of the calorimeter. This information is now included in the standard input files. Thus, one should only need to compile HETC and EGSPREP once the code is installed on the computer. It is no longer necessary to recompile these programs each time one wishes to change parameters for a new run. Other programs which need never be compiled more than once for use on a machine are LIGHT, PEGS, and the SLABGEOM geometry routine which creates the geometry file.

This SLABGEOM routine is very useful. Without it, one would need to write out the geometry input file oneself. This program was written by Tom Handler in PASCAL. He ran it on a PC and transferred the resulting geometry file to the computer on which he was running CALOR. The program was converted from PASCAL to FORTRAN at the University of Mississippi so it could be run on the same UNIX machines that were being used to run CALOR.

2 -Makefiles

One feature of UNIX is the ability to use makefiles to link routines into an executable. Each program has its own directory. Within this directory, the main program and each subroutine, function, and block data subroutine is in its own file. If one wishes to change subroutine BANKR in MORSE, for example, one edits the file, bankr.f. After making all changes, one then types 'make'. The computer automatically recompiles only those routines which have been re-written since

the last compile. The resulting object files are then linked with the object files of the routines which had not been changed to form a new executable. This reduces compile time considerably for those programs which do have to be altered and recompiled by the user.

3 -Option to Reduce the Size of the History File

The history file of HETC contains all the information about collisions, escaping particles and boundary crossings that occurred during the particle transport in HETC. This history file can be several hundred megabytes, or even a few gigabytes in size. For a slab calorimeter that has many slabs, most of the history file will consist of records of boundary crossings. A great deal of space can be saved by not writing out all of the boundary crossings. Some of the boundary crossings must be written out since dE/dx losses contribute to the energy detected by the active media. However, one can avoid writing out boundary crossings where particles have traveled through passive media if the user does not intend to analyze directly the energy deposited in the passive media. This can reduce the size of the history file by a factor of almost 2 to as much as 10 or more.

The user includes in the input the number of active media and for which media to write out the dE/dx losses. Up to seven may be chosen. If the number of active media is chosen to be zero, then all boundary crossings will be written out as before. Invoking this option allow the simulation of many events at a time in situations where the simulation would have otherwise been broken up into several runs of a few events each -- saving both disk space and much time.

4 -Standard Random Number Generator

The CALOR89/U3 package now uses a standard random number generator from CERNLIB. Thus, the code should be able to be run on a variety of machines and give similar results on these different machines if the same set of random number seeds is used. This is possible even for those machines that don't have

native random number generators provided the machines have CERNLIB installed. If desired, it is a very simple matter for a user to change the random number generator to be used.

5 -Additional Diagnostics for Errors

It is easy to make many simple mistakes when running the CALOR package of programs. An effort has been made to incorporate diagnostics to warn the user of a number of common errors that may be made when running the program. These diagnostics say explicitly what went wrong and what needs to be done to correct the situation.

6 -Greater Ease in Increasing the Size of Arrays and Common Blocks

A number of parameter statements have been incorporated to allow the user to quickly change the size of arrays in various programs and to change the size of the MCOMM common block in MORSE. This common block is used to store a great deal of information, including geometry and cross section information. Should the common block not have enough space to store all this information, a diagnostic is printed out telling the user how much larger the common block should be. The user simply edits an include file, mcomm.h, which contains a parameter statement defining the size of common block MCOMM. After editing, the user types 'make', and the program automatically recompiles only those programs which use the MCOMM common block and links them with the rest of the program.

7 -Report Files

On UNIX computers which have the intrinsic subroutine, FLUSH, available, the report files are a very nice feature. Calling FLUSH with an output file unit number as argument causes the contents of the buffer for that file to be written out

immediately. The MORSE, SPECT, and EGS4 routines each print out a line to a report file as soon as they finish with each event. The report file includes the event number, the number of energy depositions recorded for that event, and the total energy deposited for the event. While the program runs in the background, therefore, the user can at any time check the number of events that have been processed by the routine. The number of energy depositions per event helps to give some measure of how long the program be expected to take to run. Finally, the average energy per event can be checked to see if it is feasible and consistent with what is expected. Thus, a user may quickly and easily monitor the progress of a CALOR program.

2. Liquid Scintillator R&D

Dr. Reidy is co-Principal Investigator and contact person for the liquid scintillator calorimetry R&D program which was funded by the SSC laboratory for FY91. A copy of the FY91 MOU and the FY92 R&D renewal proposal with the first year progress report is in the Appendix. Funds only became available during the summer, so progress has not been as rapid as we had hoped. However, from the report one can tell that some results have already been achieved in terms of compatibility studies and radiation damage studies. The University of Mississippi is in the process of modifying a UV visible photometer and a fluorescence spectrophotometer for use in these studies. The University has both a high rate cobalt-60 source (200k rads per hour) and a low dose rate Cs-137 source (125 rads per hour max) which give us the capability of obtaining radiation damage information at both high rates and the more SSC type low rates. A graduate student, David Brown, is assisting in this effort and the first set of fibers will be radiated in November. In addition, detector simulation calculations on a rudimentary calorimeter are being performed using the CALOR89 code. These calculations will be compared with the test beam results on a rudimentary calorimeter which will be performed at the Institute for Theoretical and Experimental Physics in Moscow in early December. This calorimeter is described in the appendix. The test beam results will allow us to parameterize CALOR for this particular geometry and enable us to more accurately predict the

performance of an actual calorimeter both for single particles and for jets.

3. The Hanging File Calorimeter Program(T841) at Fermilab

We have participated in the design, assembly, and beam test of the "hanging file" calorimeter at FNAL which has become part of SDC. A copy of the MOU with the SSCL is in the Appendix. Profs Cremaldi and Reidy, Dr. Moore and two students have contributed to the effort. Radiation damage studies on plastic tiles and wavelength shifting(WLS) fibers have been initiated at UMiss using the Low Dose Rate Facility and extensive detector simulation calculations have been done. We are presently comparing our calculations with the results of some of the initial runs and using this to "fine tune" some of the parameters in CALOR. Our calculations first showed that one could achieve compensation using a lead/iron calorimeter using shaping times of less than 90 nanoseconds. Only a 1 to 2 percent difference is calculated if shaping times of 30 nanoseconds are used.

One configuration which was extensively studied consisted of an EM section **EMcal** composed of 40 cells, each cell being 1/8 Inch Pb - 3mm plastic scintillator, followed by a hadron section **Hcal** having 55 cells, each being 1 inch Pb - 3mm plastic scintillator. The energy deposition in the scintillator calculated for an incident energy of 225 GeV is represented in Figure 6. The break at slab 41 corresponds to the change in the calorimeter configuration. Now it is not clear which is the best method to use to weight the EMcal and Hcal response. One method is to maximize the hadron resolution in Hcal. From Figure 7 one finds a weight of about 4.7 gives the best resolution. By contrast using the dE/dx method gives a factor of 6.5. It is interesting to note the effect of the weighting factor on the e/π ratio; this is represented in Figure 8. A factor of 6.5 would give an e/π ratio of about 0.85. The experimental data from the hanging file should aid us in our understanding of the best method to use as well as what values of other parameters such as electron energy cut-off should be chosen. Some more detailed results are shown in Table 1.

Figure 6

Weighting of Hadron Signals (Fe)

Figure 7

Figure 8

Table 1

Results for Hanging File Calorimeter Simulation

EMcal: 1/8 inch Pb/3mm Plastic Scintillator x 40 96ns Time Gate
Hcal: 1 inch Fe/3mm Plastic Scintillator x 55 All-Data Fits

Energy	Hadronic	Electronic	e/pi
--------	----------	------------	------

Relative Weighting of HCAL to ECAL: 4.2

10 GeV	14.2 +/- 0.6	3.71 +/- 0.14	1.297 +/- 0.009
25 GeV	11.6 +/- 0.5	2.31 +/- 0.08	1.293 +/- 0.007
50 GeV	8.8 +/- 0.3	1.51 +/- 0.06	1.252 +/- 0.005
100 GeV	6.7 +/- 0.3	1.09 +/- 0.05	1.239 +/- 0.005
225 GeV	6.2 +/- 0.2	0.88 +/- 0.03	1.232 +/- 0.003

Relative Weighting of HCAL to ECAL: 4.7

10 GeV	13.3 +/- 0.5	3.73 +/- 0.14	1.192 +/- 0.007
25 GeV	11.0 +/- 0.4	2.37 +/- 0.08	1.183 +/- 0.006
50 GeV	8.0 +/- 0.3	1.55 +/- 0.06	1.152 +/- 0.004
100 GeV	5.8 +/- 0.3	1.10 +/- 0.05	1.132 +/- 0.004
225 GeV	5.6 +/- 0.2	0.86 +/- 0.03	1.125 +/- 0.003

Additional results are given in the Appendix.

4. Contributions to the Calorimeter Programs for GEM and SDC

Our expertise in detector simulation calculation, our experience with scintillation detectors and our developing program in radiation damage studies has resulted in a natural interest in scintillation-based calorimetry. Our principle efforts have been devoted to parallel plate scintillation calorimetry, both with rigid plastic scintillators and with liquid scintillator plate-type cells. Some of our activities are described above in section C(2 and 3). We were charter members of the

scintillation plate calorimetry SSC R&D program at ANL and FNAL. The focus of this R&D effort has been toward calorimetry for SDC since it has chosen scintillating plate as the primary technology for the electromagnetic and hadron calorimeter. We are playing a significant role in this program and plan to continue.

About two years ago, as an alternate technology to the scintillating plate, we formed a collaboration with personnel from ORNL, ITP and University of Tennessee to study liquid scintillator technology for use in an SSC calorimeter. Dr. Reidy is co-Principal Investigator and contact person for this funded SSC R&D work. This technology had been proposed for use in the L* hadron calorimeter and the R&D effort was pursued with this in mind. Later this effort evolved into part of the GEM collaboration. Consequently, the UMiss HEP group also has a role in the GEM detector program. Much of our work with CALOR89 and liquid scintillation calorimetry has been focussed on the GEM detector. In addition, there is a great deal of complementarity between the studies needed for scintillating plate calorimetry and the liquid scintillator calorimetry and the UMiss HEP group provides a valuable interface between these two technologies. In addition, Dr. Reidy currently serves as secretary for the Collaboration Council of GEM.

5. The SAHEP Initiative and the TNRLC

Several years ago, a number of high energy physicists in the South were convinced that the success of the SSC project would depend on broadly based support throughout the nation and, in particular, the South can and must play a major role in this initiative. We also recognized that, in general, the high energy groups in the southern institutions were smaller and had more limited resources than their counterparts in many other parts of the country. A number of us decided that the best way to participate more fully in the SSC program was to establish a consortium of southern groups where we could draw on the expertise and facilities of a number of institutions. With this in mind, a consortium of southern high energy physics groups, the Southern Association for High Energy

Physics (SAHEP) was formed in May 1988 to help contribute the considerable strengths of the southern region to the SSC program. This consortium is growing and presently consists of 23 university-based groups and four research oriented laboratories and industries including Oak Ridge National Laboratory. Dr. Reidy of UM.s.s was elected the chairman of the consortium. Later, a subgroup of 16 universities and Oak Ridge National Laboratory with Oak Ridge Associated Universities as the administrative arm formed a sub-consortium and applied to the Texas National Research Laboratory Commission (TNRLC) for funds. The use of these funds is to enhance the infrastructure of these universities through the addition of staff and equipment thereby enabling these institutions to make greater contributions to the SSC program. The TNRLC has expressed a willingness to provide long-term funding so the universities could develop their infrastructure at a reasonable and assured pace. Professor Reidy was chosen as the chair of the executive board for this sub-consortium. In April 1991, this group was awarded \$1M by the TNRLC. The University of Mississippi received \$90,000 primarily for the support of a postdoctoral associate and a new faculty member. The postdoctoral associate position was funded September 1, 1991 and a search is currently underway to fill the faculty position. In addition, the TNRLC, also in 1990, awarded the University of Mississippi \$200,000 toward the establishment of a UNIX based "farm" to assist us in performing calculations for the SSC program. This "farm" is presently being assembled and has been described in section B(3). These funds have enabled us to have a postdoctoral associate full-time on E791 funded by DCE/HEP and another postdoctoral associate full-time on detector simulation calculations and code development. In addition, the TNRLC funds have been used to support two graduate students to assist in these calculations. Dr. Reidy is Principal Investigator for this \$1M contract and ORAU serves as the administrative unit to distribute the funds.

D. Summary

The University of Mississippi High Energy Physics Group is active in three Fermilab experiments and the SSC R&D program. During the calendar year, most of our efforts at Fermilab have been devoted to running on E791 where we

have extensive on-line responsibilities. These include the Cerenkov counters, PWCs, low voltage monitoring system, beam counters, a muon "wall" of scintillation counters and part of the data acquisition system. At the University we have devoted a major effort in the last six months toward the assembly and checkout of a 900 MIP 40 DECstation 5000/200 "farm" which will be used for data analysis of the Fermilab experiments and SSC-related calculations. We have a strong SSC R&D program involving detector simulation calculations and radiation damage studies in support of the scintillation plate program at Fermilab (an SDC initiative), the liquid scintillator calorimetry SSC R&D program (with Prof. Reidy as co-P.I. and as part of the GEM initiative) and detector simulation code(CALOR) adaptation for use at the SSCL and other UNIX environments. Professor Reidy also serves as secretary of the GEM Collaboration Council and as P.I. on the \$1M funded initiative from TNRLC which involves the enhancement of the infrastructure of 16 universities in the South. Finally, members of the group have co-authored three refereed publications, submitted two proposals to the SSCL and one to the TNRLC and have presented seven papers at national meetings. In addition, they have authored numerous reports many of which are included in the Appendix.

APPENDIX

PUBLICATIONS

Abstract Submitted
for the April 1990 Meeting of the
American Physical Society
April 22-25, 1991

PACS
14.20

Suggested Session
High Energy Particle Physics

RESONANT DECAYS of the Λ_c^+ - The Tagged Photon

Spectrometer Collaboration *,**. The resonant decays of the Λ_c^+ into pK^{*0} and $\Delta^{++} K^-$ can give insight into the weak decay of this charmed baryon. We have performed a Dalitz plot analysis of the three body decay $\Lambda_c^+ \rightarrow pK^-\pi^+$. A sample of 101 ± 13 decays reconstructed in Fermilab photoproduction experiment E691 were used in the analysis. We present results on the measured resonant and nonresonant decay fractions from these Λ_c^+ decays.

* submitted by L. M. Cremaldi.

** Work supported by the U.S. Department of Energy, by the National Research Council of Canada, and the Brazilian Conselho Nacional de Desenvolvimento Cientifico Tecnológico.

Prefer Standard Session

Lucien M. Cremaldi
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

Abstract Submitted
for the 1991 Annual Meeting of the
Southeastern Section of the
American Physical Society
November 11-13, 1991

PACS
12.13.14

Suggested Session
High Energy Particle
Phenomenology

Low Mass Pseudoscalar Pseudoscalar Dynamics- JOHN WEINSTEIN, University of Mississippi*--We discuss a simple quark model which successfully describes the dynamics of low mass pseudoscalar-pseudoscalar interactions and compare the results with scattering and production data. We conclude that quark exchange interactions and quark antiquark annihilation and creation processes alone describe the data, there is no need to include effects due to the more traditional meson exchange processes.

*Supported in part by the U.S. Department of Energy (DE-FG05-91ER40622) and the Texas National Research Laboratory Commission.

Prefer Standard Session

John Weinstein
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

Abstract Submitted
for the 1991 Annual Meeting of the
Southeastern Section of the
American Physical Society
November 11-13, 1991

PACS
01

Suggested Session
High Energy Particle Physics

SAHEP and the TNRLC - Partners in a Vision - JAMES J. REIDY, University of Mississippi*--A group of 20 institutions in the Southern Association for High Energy Physics (SAHEP) has received one million dollars (\$1M) this year from the Texas National Research Laboratory Commission (TNRLC) to assist in enhancing the infrastructure in high energy physics research at these institutions. This is part of a commitment by the TNRLC to assist Southern institutions in playing a greater role in the Superconducting Super Collider (SSC) program. The present status of the SAHEP/TNRLC program will be described and future plans and goals outlined.

*Supported in part by the U.S. Department of Energy (DE-FG05-91ER40622) and the Texas National Research Laboratory Commission.

Prefer Standard Session

James J. Reidy
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

Abstract Submitted
for the 1991 Annual Meeting of the
Southeastern Section of the
American Physical Society
November 11-13, 1991

PACS
29

Suggested Session
High Energy Particle Physics

High Speed Data Acquisition at the Fermilab E791 Charm Quark Factory- D. J. SUMMERS, University of Mississippi*--The goal of Fermilab Experiment 791 is to produce and reconstruct over 100,000 mesons and hadrons containing the charm quark. New particles and rare or forbidden charm decays will be searched for. One of the upgrades that has made this possible is a new high speed data acquisition system. Front end TDCs, ADCs, latches, and crate controllers capable of digitizing and reading out in 30 microseconds have been added. Eight 80MB spill buffers store data so that events may be built, compressed, and written to tape during an entire 56 second spill cycle, and not just during a 22 second spill. Events are processed in parallel in six VME crates with Motorola 68020 CPUs. A wall of 42 8mm Exabyte tape drives is used to record data continuously at 10 MB/s. Offline systems of numerous parallel RISC computers are being assembled to reconstruct the data.

*Supported in part by U.S. Department of Energy (DE-FG05-91ER40622) and the Texas National Research Laboratory Commission.

Prefer Standard Session

Don Summers
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

Abstract Submitted
for the 1991 Annual Meeting of the
Southeastern Section of the
American Physical Society
November 11-13, 1991

PACS
29

Suggested Session
High Energy Particle Physics

Calorimetry Simulation Using CALOR89 on Unix Computers- BRENT MOORE, University of Mississippi* and T. GABRIEL, Oak Ridge National Laboratory ---The CALOR 89 simulation package has been used for a number of years for calorimeter benchmarking and design calculations. The code has recently been adapted for use on UNIX machines at the University of Mississippi. The UNIX version of the CALOR89 package is being made available on the PDSF computing ranch at the SSCL. This version has been benchmarked using two slab configurations: one having iron absorber with plastic scintillator, and the other having depleted uranium absorber with plastic scintillator. These results will be presented as well as preliminary results of simulations for the Hanging File Calorimeter at FNAL.

*Supported in part by the U.S. Department of Energy (DE-FG05-91ER40622) and the Texas National Research Laboratory Commission.

Prefer Standard Session

Don Summers
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

Abstract Submitted
for the 1991 Annual Meeting of the
Southeastern Section of the
American Physical Society
November 11-13, 1991

PACS
29

Suggested Session
High Energy Particle Physics

Finding Charm Quarks with Parallel RISC Computers and 8mm Tapes - Breese Quinn, University of Mississippi for the *E791 Collaboration* *-- Experiment 791 at Fermilab is currently recording over 10 billion hadronic interactions onto 8mm magnetic tape. They are interactions of 500 GeV/c negative pions with a fixed target. A silicon microvertex detector is being used with a magnetic spectrometer to find charm particles in these events. The University of Mississippi is constructing a system of parallel RISC computers to analyze 1/3 of this data. Because the interactions are independent, many CPU's can be made to work in parallel with a minimum of interprocessor communication. This system, to be discussed, will help to provide over 100,000 fully reconstructed charm decays for further study.

* Work supported by the U.S. Department of Energy, the National Science Foundation, the Texas National Research Laboratory Commission and the Brazilian Conselho Nacional de Desenvolvimento Cientifico Tecnológico.

Prefer Standard Session

Breese Quinn
Department of Physics
and Astronomy
University of Mississippi
University, MS 38677

E769

Charm Production in 250 GeV/c Hadron-Nucleon Interactions

Presented by

Robert Jedicke

The University of Toronto

and

Lee Lueking

Fermilab

for the E769 Collaboration* at Fermilab

ABSTRACT

During the 1987-88 fixed target running period at Fermilab, Experiment 769 recorded 400 million triggers using a tagged 250 GeV/c hadron beam and a global transverse energy trigger. Details of the production properties measured from this data sample for $D^\pm$, $D^0/\bar{D}^0$ and $D_s^\pm$ mesons are reported including preliminary values of the cross section $\times$ branching ratio for the $D_s^\pm$, and x_F and p_t^2 dependences.

1. Introduction

The principal focus of the experiment is to measure the characteristics of charm hadroproduction including the cross section, the x_F and p_t^2 distributions and the dependence on the beam particle type. The contributions to the charm cross section at Leading Order (LO) perturbative QCD were calculated by Ellis and Quigg.¹ Recent calculations^{2,3} have been made including the Next to Leading Order (NLO) terms, showing that $\sigma_{\text{ch}}(\alpha_s^2 + \alpha_s^3)/\sigma_{\text{ch}}(\alpha_s^2) \approx 3$. The most important process contributing to the hadroproduction of charm at 250 GeV is gluon-gluon fusion. The cross section depends on the value of the charm quark mass and the structure functions employed in these calculations.

E769 is well suited to test these calculations with a large data set consisting of 400M triggers of both beam polarities. The 160M negative beam triggers are 85% pion and 15% kaon induced, while the 240M positive data triggers are a mixture of pions, kaons and protons. From these data, we have extracted charm signals for the modes

*C.B.P.F. (Rio de Janeiro), Fermilab, U. of Mississippi, Northeastern U., U. of Toronto, Tufts U., U. of Wisconsin and Yale U.

Figure 1: A) $D^+ \rightarrow K^-\pi^+\pi^+$ B) $D^0 \rightarrow K^-\pi^+$ and C) $D_s^+ \rightarrow \phi\pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ signals including all trigger and beam particle types.

Figure 2: $D^+ \rightarrow K^-\pi^+\pi^+$ A) x_F and B) p_t^2 acceptance.

$D^+ \rightarrow K^-\pi^+\pi^+$, $D^0 \rightarrow K^-\pi^+$, and $D_s^+ \rightarrow K^-K^+\pi^+$.[†] The E769 detector has been described elsewhere.⁴

2. Analysis and Results

2.1. Event selection and Acceptance

Charm signals are extracted from the data by forming vertex candidates using the SMD track information. From this list of vertices for each event, the primary vertex is defined to be the one with the largest number of attached tracks and is required to be within the target.

A secondary $D^\pm$ decay vertex candidate is chosen based on the values of the following parameters: 1) The significance of the primary to secondary vertex separation

[†]Unless otherwise noted a decay mode refers to both charge conjugate modes.

Charm Meson	events	a	b
$D^\pm$	534 ± 31	3.13 ± 0.25	0.74 ± 0.04
D^+	267 ± 24	3.47 ± 0.36	0.82 ± 0.06
D^-	269 ± 24	2.90 ± 0.35	0.68 ± 0.05
$D^\pm_{\text{nonleading}}$	239 ± 23	3.54 ± 0.38	0.78 ± 0.06
$D^\pm_{\text{leading}}$	295 ± 25	2.88 ± 0.35	0.72 ± 0.05
$D^0/\bar{D}^0$	344 ± 29	4.37 ± 0.47	0.95 ± 0.11
D^0	159 ± 23	4.69 ± 0.79	1.08 ± 0.18
$\bar{D}^0$	186 ± 21	4.10 ± 0.53	0.85 ± 0.12

Table 1: Results from the ML minimization for $D^+ \rightarrow K^-\pi^+\pi^+$ and $D^0 \rightarrow K^-\pi^+$ for π^- incident beams.

($\Delta z/(\sigma_{z_1}^2 + \sigma_{z_2}^2)^{1/2} > 12$), 2) The product $\prod_{i=1}^n (b_{s,i})/(b_{p,i})$ with n being the number of tracks in the secondary decay mode. For each track (i) in the secondary vertex candidate the product uses the transverse distance to the primary vertex (b_p) and to the secondary vertex (b_s) (< 0.006), 3) The impact parameter of the momentum vector of the reconstructed $D^\pm$ with respect to the primary vertex ($< 80\mu\text{m}$), 4) The transverse distance between the decay vertex location and any other track in the event ($> 60\mu\text{m}$), 5) The sum of the p_t^2 of the $D^\pm$ candidate decay tracks relative to the $D^\pm$ direction ($> 0.5 \text{ GeV}^2$) and 6) The probability for the kaon identification. Similar values were used for other particles and decay modes. These data include a correction for the standard transverse energy trigger using a technique based on the total transverse momentum in an event. The trigger efficiency for charm was measured to be 0.78 ± 0.05 . The signals for this data set after these cuts are shown in Figure 1 as well as the signals for the D^0 and the $D^\pm$.

The acceptances were determined using a Monte Carlo simulation based on the Lund PYTHIA V4.8 and JETSET 6.3 routines for event generation and fragmentation, and a detailed simulation of the detector. Acceptance functions which are employed in the analysis are based on fully reconstructed Monte Carlo events which meet the complete analysis criteria.

Events passing these requirements are binned in the variable for which the acceptance is being determined and normalized by the generated distributions binned similarly. The resulting x_F and p_t^2 acceptance distributions for $D^+ \rightarrow K^-\pi^+\pi^+$ are presented in Figure 2A and 2B respectively with the fitted fourth order polynomials used in the analysis superimposed on them.

Figure 3: $D^+ \rightarrow K^- \pi^+ \pi^+$ A) x_F and B) p_t^2 standard trigger data only, after acceptance corrections with the ML fit superimposed. Errors are statistical only. The LO QCD curves are explained in the text.

2.2. Results for $D^+ \rightarrow K^- \pi^+ \pi^+$ and $D^0 \rightarrow K^- \pi^+$

The following results are based on events passing the analysis cuts discussed above. Only data from our standard trigger are included: this represents two-thirds of our total sample. The beam types are selected by requiring $> 90\%$ beam probability based on an analysis of the beam Cerenkov counter and TRD⁵ information. The distributions for mass, x_F , p_t^2 and A-dependence are fit simultaneously employing a Maximum Likelihood (ML) technique. The functional forms used include a quadratic background and gaussian signal shape for the mass, $(1 - x_F)^n$, $\exp(-bp_t^2)$, and A^α .

The ML fits are shown superimposed on the acceptance corrected signal for $D^+ \rightarrow K^- \pi^+ \pi^+$ for $\pi^\pm$ beams in Figure 3. The LO QCD curves superimposed on the Figure were calculated using the work of Ellis and Quigg¹ for $Q^2 = \mu^2 = m_c^2 = (1.5 \text{ GeV})^2$ using the structure functions of DO1^{9,10}. Results for $D^\pm$ and $D^0/\bar{D}^0$ as well as various sub-samples are summarized in Table 1. Results for two incident beam particle types are given in Table 2 for the $D^\pm$. We are continuing to study our proton induced signals.

2.3. Results for $D_s^+ \rightarrow K^- K^+ \pi^+$

The analysis of the $D_s^+ \rightarrow K^- K^+ \pi^+$ data is based on the two resonant decay modes $D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$. The cuts made were similar to the $D^+ \rightarrow K^- \pi^+ \pi^+$ however the primary vertex candidate in the $D_s^+ \rightarrow K^- K^+ \pi^+$ study was assumed to be the vertex with the smallest impact parameter for a given secondary vertex candidate. A cut on the angle ($|\cos \theta| > 0.56$) between the like-sign particles in the $KK\pi$ decays in the resonant particle's rest frame was used in the $D_s^+ \rightarrow \phi \pi^+$ analysis.

A least squares fit using two gaussian peaks and a linear background to the combined $\phi\pi$ and $\bar{K}^*(892)^0 K^+$ invariant mass distributions yields a total of 83 ± 13 $D_s^\pm$ and 45 ± 11 $D^\pm$ in the Cabibbo suppressed $D^+ \rightarrow \phi \pi^+$ and $D^+ \rightarrow \bar{K}^*(892)^0 K^+$ modes as shown in Figure 1C. For the measurement of $\sigma \cdot B$ and the x_F and p_t^2

Beam type	Charm Meson	events	n	b
$\pi^\pm$	$D^\pm$	534 ± 31	3.13 ± 0.25	0.74 ± 0.04
	$D_s^\pm$	29 ± 8	3.2 ± 0.2	0.9 ± 0.3
$K^\pm$	$D^\pm$	172 ± 20	3.71 ± 0.44	0.71 ± 0.07
	$D_s^\pm$	15 ± 5	2.9 ± 1.6	1.3 ± 0.5

Table 2: Results from the ML minimization for $D^+ \rightarrow K^- \pi^+ \pi^+$ and ($D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$) for $\pi^\pm$ and $K^\pm$ incident beams and standard trigger data only.

differential distributions we use only the events which passed the standard trigger.

The x_F and p_t^2 acceptances for each of the two resonant decays of the $D_s^\pm$ are similar in shape to the $D^\pm$ acceptances shown in Figure 1. There is no significant difference between the shapes of the $D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ acceptances. The total acceptances using the Monte Carlo for $x_F > 0$ were 0.0151 ± 0.0030 and 0.0090 ± 0.0018 for the $D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ modes respectively.

We combine the $D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ signals and form a weighted average of $\sigma \cdot B$ by normalizing the $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ to the $D_s^+ \rightarrow \phi \pi^+$ using the world average of the ratio of the branching fractions of 0.96 ± 0.11 .⁶ The weighting for the average is given by the quadratic sum of the statistical error on the measurement with those systematic errors which are not common to each decay mode. The common systematic errors are added in quadrature with the error calculated for the weighted average and quoted as the final error.

Assuming a linear A-dependence to calculate $\sigma \cdot B$ we find 0.038 ± 0.014 and 0.046 ± 0.016 $\mu\text{b/nucleon}$ for the π and K beams respectively. The values in the π and K beams are consistent with those reported by the NA32 collaboration.¹³

We perform a ML fit to the combined $D_s^+ \rightarrow \phi \pi^+$ and $D_s^+ \rightarrow \bar{K}^*(892)^0 K^+$ signals in order to simultaneously fit the mass, x_F and p_t^2 distributions for the signal and the background. The fitted values of n and b for the x_F and p_t^2 distributions respectively are shown in Table 2. The errors on the $D_s^\pm$ data are statistical only.

3. Comparison to QCD Predictions and other Recent Measurements

We have recently calculated total charm cross sections to LO and NLO following the work of Ellis and Quigg¹ and Nason, Dawson and Ellis,^{7,8} and the theoretical differential x_F and p_t^2 distributions to LO following Ellis and Quigg.¹ We repeat their calculations to produce distributions specific to our beam particles and energy. We use the parton distributions in π and p from Duke and Owens (DO1).^{9,10}

Our measurements of n for the $D^\pm$ mesons (Table 2) are lower than our LO pre-

prediction for the charm quark ($n \approx 4.5$) and also lower than the NLO value ($n \approx 3.6$) given by a fit to points extracted from Figure 21 of reference [8]. The NLO calculations used the structure functions of DFLM^{11,12} and DO1.^{9,10} The measurement has interesting implications for the hadronization process since it implies fragmentation unlike that of $e^+e^- \rightarrow c\bar{c} \rightarrow cq$ where q is one of the light quarks. Our measurements of b for the $D^\pm$ mesons (Table 2) are higher than the theoretical predictions of b for the charm quark. We are continuing to study the theoretical predictions and compare them to our data. This includes predicting KN cross sections and studying the fragmentation process.

All of the results for the x_F distributions in Table 1 for the $D^\pm$ are consistent with one another and with recent results from NA32 at CERN¹³. We see no significant difference between the leading and non-leading $D^\pm$. Our measurement of n for the kaon produced $D^\pm$ is consistent with our measurement for the pion beam. We see no evidence of a flavour dependence in the differential distributions for π and K production of $D^\pm$ mesons. The $D^\pm$ measurements of the values of n and b in Table 2 are consistent with one another and with measurements by NA32.

4. Acknowledgments

We gratefully acknowledge the assistance we received from the Fermilab staff and the support staffs at the various universities. This research was supported by the U.S. Department of Energy, the National Science Foundation and the Brazilian Conselho Nacional de Desenvolvimento Científico e Tecnológico.

References

1. R.K. Ellis, C. Quigg, FN-445 (1987).
R.K. Ellis, FERMILAB-Conf-89/168-T, 1989.
2. G. Altarelli et al., Nuclear Physics B308 (1988) 724.
3. E.L. Berger, ANL-HEP-CP-89-107.
4. D.J. Summers et al., Charm Hadroproduction at Fermilab E769, Proc. XXIIIrd Rencontre de Moriond (13-19 March 1988) 451.
5. D. Errede, M. Sheaff, H. Fenker, L. Lucking, P. Mantsch and R. Jedicke, A High Rate Transition Radiation Detector for Particle Identification in a Hadron Beam, accepted by NIM for publication, FERMILAB-Conf-88/180-E.
6. Particle Data Group, Review of Particle Properties, Physics Letters B239 (1990) VII.128.
7. P. Nason, S. Dawson and R.K. Ellis, Nuclear Physics B303 (1988) 607.
8. P. Nason, S. Dawson and R.K. Ellis, Nuclear Physics B327 (1989) 49.
9. D.W. Duke and J.F. Owens, Physical Review, D30, Number 1, (1984) 49.
10. J.F. Owens, Physical Review, D30, Number 5, (1984) 943.
11. M. Diemoz et al., Zeitschrift für Physik 39 (1988) 21.
12. J.V. Allaby et al., Physics Letters B197 (1987) 281.
13. S. Barlag et al., Zeitschrift für Physik C49 (1991) 555.

September 30, 1991 7:26 pm
 E791 Numbers of Events by Week and Run Type

Week Starting	Normal	Interaction	Good_Beam	Alignment	Magnet_Off	Special
6/17/91						3,300,646
6/24/91				252,376		4,226,369
7/1/91						17,813,234
7/8/91	34,618,229	31,680,496				28,039,495
7/15/91	149,166,564	37,854,733	2,414,999			123,238,152
7/22/91	285,223,607	36,851,105			873,380	53,177,790
7/29/91	305,916,359	105,494,594	323,177			3,316,357
8/5/91	501,214,852		406,724		1,022,130	1,140,127
8/12/91	273,033,713	76,035,753	40,395,899			13,833,174
8/19/91	1,072,128,014	131,583,426				52,251,508
8/26/91	951,489,620	184,695,330				21,462,809
9/2/91	608,647,786	75,437,088		651,836		
9/16/91	628,380,615	59,818,543	435,902	126,582	13,792,134	
9/23/91	856,684,384	180,348,191	225,578	42,862	327,234	28,703,777
9/30/91	30,303,804	37,792,725				
Totals:	6,196,807,547	957,591,984	44,202,279	1,073,656	16,014,928	355,503,436

J. Spalding
C. Gay
A. Rafatian

August 16, 1991
E769 Trigger Correction
DRAFT

The E769 Et trigger used the global transverse energy from SLIC and HADROMETER. With a threshold of about 5.5 GeV, something like 25% of total cross-section was collected. The charm signal in INTERACTION trigger data indicates that Et trigger was about (76 +/- 9)% efficient for reconstructed charm.

We need this trigger correction: 1) to correct the shapes of the differential distributions (X_f and P_t) for the effects of the trigger and 2) to calculate the absolute cross-sections. While these are very necessary corrections, it should be noted that INTERACTION data indicates that the scale of the corrections is not large.

Et triggers were:

ETPI (standard)	=== TRD.GB. PS. KILL_B. ETS
ETK	=== DISC. ETS
ETB	=== TRD.GB. PS. KILL_B. ETB
ETE	=== highPT. ETB

where

GB	=== BS. HALO_BAR
PS	=== pre-scaler on GB input of ETPI and ETB
KILL_B	=== killer bit not on

The conditions for E769 Et trigger changed during the run. One was the amount of energy contributing to Et due to "other" in-time beam particle, and out-of-time interactions.(pp.4-5) This is very much dependent on the beam intensity. Whereas in-time effects such as efficiencies and noise are well modelled by E769 Monte Carlo, the contributions due to out-of-time energy in the calorimeter are not.

To overcome this problem we have transferred our parameterisation of the trigger efficiency to an in-time variable PT715, which is basically the contribution to Et due to in-time charged tracks.(p.6)

We then use the prescaled INTERACTION data from pairstrip tapes to determine the efficiency functions. There is a very reasonable assumption in using the interaction data; i.e. the

relationship between PT715 and ET (for the event only) is the same for INTERACTION data as for the reconstructed charm events. That is, the shape of the neutral ET in the event, relative to the charged ET is the same. Since our typical charged track multiplicity is something like 9, this is a pretty safe assumption.

We obtain each efficiency function by first dividing the histogram of PT715 of the good_track events which passed both INTERACTION trigger and the corresponding Et trigger by the histogram of PT715 of what passed INTERACTION trigger. The resultant histogram is then fitted with a function with the following general form:

$$\text{TRIG_EFF} = P1 - (P2 / 1 + \text{EXP} ((PT715 - P3) / P4))$$

It should be added that all histograms were weighted properly to correct for the variable prescaler (PS) settings throughout the run. Also, the data was weeded according to Rob Jedicke's weeding standards for bad runs, bad spills and ... !

Since we have divided the data into four running periods of -210 GeV, -250 GeV, +250 GeV (excluding proton run), and proton run, our efficiencies are effectively functions of two variables: PT715, and NRUN. (pp.7-20) (Each function is followed by its error function.) As you can see there is an efficiency function for each trigger type, and one for (ETPI .or. ETB) out of concern that a portion of events is shared by both triggers and we do not want to count them twice in our cross-section calculations.

There is a set of efficiency curves which use the trigger input bit for Et contribution to the trigger. These are the relative efficiency curves. They should plateau at 100%. (p.21)

The absolute efficiency curves which use the trigger PLU output include the effects of beam pre-scalers settings and beam particle ID. (p.22)

Now, how to use which curve depends on what kind of correction one is attempting to make. There are generally two methods for trigger correction: 1) to apply the relative efficiency to the Monte Carlo data, 2) to weight the signal data by the reciprocal of the relative or the absolute efficiency.

Here follows an example of trigger correction for differential distributions (e.g. Xf distribution with an arbitrary scale on the Y-axis) using both methods:

Method 1 (or MC rejection method):

a. Select your signal events using the trigger bit:

e.g. ETPI (ITRGL2 .AND. 2) .NE. 0

b. Use the corresponding relative trigger efficiency function:
ET_RELEFF (NRUN, PT715)

c. Apply the trigger to each MC event by comparing a random number to ET_RELEFF (NRUN, PT715). The MC efficiency function MC_EFF (Xf) then includes the trigger.

d. Divide the background subtracted signal distribution in Xf by MC_EFF (Xf) and get the corrected distribution.

Method 2:

a. Repeat steps a and b in method 1.

b. Divide the background subtracted signal distribution in Pt715 for each Xf bin by ET_RELEFF (NRUN, PT715) and get the corrected distribution for that Xf bin.

***CAUTION: This method is not recommended for low statistics data. We are much better off to use the first method for most of our analysis.

INTERACTION

INTERACTION * KILLER-BIT

$$\frac{INT * \overline{KILL-B}}{INT}$$

Function PT715(N715)
SAVE

c
c----This function returns the value of the PT715 (the sum
c of Pt's in region 1 for cat 7 and 15 tracks) , with the number
c of such tracks returned in the argument.
c
c it assumes you've unpacked the track info, and makes no
c inflag checks.

+SEQ, TRACKS.

REAL PT715
INTEGER N715

C-- Initialize
PT715=0.
N715=0
if (NTRK.lt.1) return

C-- Do the loop
DO I = 1, NTRK
IF ((JCATSG (I) .EQ. 7) .OR. (JCATSG (I) .EQ. 15)) THEN
c PT715 = PT715 +
SQRT ((PR (1, 1, I) ** 2) + (PR (2, 1, I) ** 2))
N715=N715+1
END IF
END DO

return
end

C-- Given the run number and pt715 this function returns Et standard
C trigger efficiency

FUNCTION ETPI_EFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)
+ /0.389, 0.362, 1.925, 0.793,
+ 0.160, 0.155, 2.035, 0.871,
+ 0.027, 0.027, 1.831, 0.806,
+ 0.000, 0.000, 0.000, 0.000/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

& IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
(NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

& IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
(NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

& IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
(NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETPI EFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
RETURN
END

C-- Given the run number and pt715 this function returns error in
 C Et standard trigger efficiency

FUNCTION ETPI_EFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /0.389, 0.362, 1.925, 0.793,

+ 0.160, 0.155, 2.035, 0.871,

+ 0.027, 0.027, 1.831, 0.806,

+ 0.000, 0.000, 0.000, 0.000/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0067, 0.0195, 0.0663, 0.0579,

+ 0.0020, 0.0064, 0.0569, 0.0469,

+ 0.0009, 0.0031, 0.1618, 0.1176,

+ 0.0000, 0.0000, 0.0000, 0.0000/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETPI_EFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

9
C-- Given the run number and pt715 this function returns (Et.or.Et_b)
C trigger efficiency

FUNCTION ETPIB_EFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /0.529, 0.571, 2.127, 1.226,
+ 0.298, 0.336, 2.849, 1.663,
+ 0.114, 0.115, 3.767, 1.263,
+ 0.020, 0.016, 2.957, 0.557/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETPIB EFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))

RETURN

END

C-- Given the run number and pt715 this function returns error in
 C (Et.or.Et_b) trigger efficiency

FUNCTION ETPIB Eff_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /0.529, 0.571, 2.127, 1.226,
 + 0.298, 0.336, 2.849, 1.663,
 + 0.114, 0.115, 3.767, 1.263,
 + 0.020, 0.016, 2.957, 0.557/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0165, 0.0493, 0.1213, 0.1252,
 + 0.0042, 0.0099, 0.0698, 0.0616,
 + 0.0044, 0.0058, 0.0856, 0.0835,
 + 0.0025, 0.0043, 0.2701, 0.3423/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 GeV negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 GeV negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETPIB_Eff_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

C-- Given the run number and pt715 this function returns Et_k
C trigger efficiency

FUNCTION ETK_EFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)
+ /0.050, 0.039, 1.956, 0.586,
+ 0.026, 0.022, 1.741, 0.511,
+ 0.015, 0.018, 0.967, 0.773,
+ 0.155, 0.097, 2.290, 0.655/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

& IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

& IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

& IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETK EFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
RETURN
END

C-- Given the run number and pt715 this function returns error in
 C Et_k trigger efficiency

FUNCTION ETK EFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /0.050, 0.039, 1.956, 0.586,

+ 0.026, 0.022, 1.741, 0.511,

+ 0.015, 0.018, 0.967, 0.773,

+ 0.155, 0.097, 2.290, 0.655/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0019, 0.0048, 0.1410, 0.1123,

+ 0.0004, 0.0016, 0.0924, 0.0496,

+ 0.0004, 0.0074, 0.6428, 0.1832,

+ 0.0063, 0.0166, 0.2280, 0.1686/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

& IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

& IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

& IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETK EFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

C-- Given the run number and pt715 this function returns Et_b
 C trigger efficiency

FUNCTION ETB_EFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)
 + /0.205, 0.205, 4.646, 1.049,
 + 0.162, 0.161, 4.878, 0.978,
 + 0.077, 0.076, 4.087, 0.839,
 + 0.013, 0.011, 3.190, 0.191/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam
 IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam
 IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam
 IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
 IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETB EFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
 RETURN
 END

C-- Given the run number and pt715 this function returns error in
 C Et_b trigger efficiency

FUNCTION ETB_EFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

```
DATA ((PAR(I,J), J=1,4), I=1,4)
+      /0.205, 0.205, 4.646, 1.049,
+      0.162, 0.161, 4.878, 0.978,
+      0.077, 0.076, 4.087, 0.839,
+      0.013, 0.011, 3.190, 0.191/
DATA ((ERR(I,J), J=1,4), I=1,4)
+      /0.0048, 0.0051, 0.0664, 0.0538,
+      0.0017, 0.0018, 0.0285, 0.0203,
+      0.0019, 0.0021, 0.0490, 0.0332,
+      0.0015, 0.0016, 0.1239, 0.0768/
```

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam
 IF ((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam
 IF ((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam
 IF ((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
 IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETB_EFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

C-- Given the run number and pt715 this function returns Et_electron
C trigger efficiency

FUNCTION ETE_EFF(NRUN, PT715)

REAL PAR(4,4)
DATA ((PAR(I,J), J=1,4), I=1,4)
+ /0.000, 0.000, 0.000, 0.000,
+ 0.000, 0.000, 0.000, 0.000,
+ 0.030, 0.030, 4.242, 1.382,
+ 0.028, 0.025, 3.121, 0.612/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam
IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam
IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam
IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETE EFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
RETURN
END

C-- Given the run number and pt715 this function returns error in
 C Et_electron trigger efficiency

FUNCTION ETE EFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /0.000, 0.000, 0.000, 0.000,

+ 0.000, 0.000, 0.000, 0.000,

+ 0.030, 0.030, 4.242, 1.382,

+ 0.028, 0.025, 3.121, 0.612/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0000, 0.0000, 0.0000, 0.0000,

+ 0.0000, 0.0000, 0.0000, 0.0000,

+ 0.0015, 0.0018, 0.1441, 0.1341,

+ 0.0036, 0.0049, 0.2205, 0.2083/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETE EFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

C-- Given the run number and pt715 this function returns relative Et
C trigger efficiency

FUNCTION ET_RELEFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)
+ /1.013, 1.166, 1.650, 1.238,
+ 0.958, 0.957, 2.042, 0.897,
+ 0.991, 0.820, 1.818, 0.783,
+ 0.992, 0.834, 1.761, 0.807/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam
IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1002)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam
IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam
IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ET_RELEFF = PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
RETURN
END

C-- Given the run number and pt715 this function returns error in
 C relative Et trigger efficiency

FUNCTION ET_RELEFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /1.013, 1.166, 1.650, 1.238,
 + 0.958, 0.957, 2.042, 0.897,
 + 0.991, 0.820, 1.818, 0.783,
 + 0.992, 0.834, 1.761, 0.807/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0010, 0.0355, 0.0759, 0.0296,
 + 0.0019, 0.0110, 0.0193, 0.0115,
 + 0.0011, 0.0133, 0.0265, 0.0117,
 + 0.0047, 0.0605, 0.1192, 0.0506/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
 & ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
 & ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
 & ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam

IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ET_RELEFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

C-- Given the run number and pt715 this function returns relative Etb
C trigger efficiency

FUNCTION ETB_RELEFF(NRUN, PT715)

REAL PAR(4,4)

DATA ((PAR(I,J), J=1,4), I=1,4)
+ /1.000, 1.000, 4.676, 1.075,
+ 1.000, 1.000, 4.878, 0.978,
+ 1.000, 1.000, 4.144, 1.027,
+ 1.000, 1.000, 4.243, 1.074/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam
IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam
IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam
IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

ETB_RELEFF=PAR(I,1) - (PAR(I,2)/(1+EXP((PT715-PAR(I,3)) / PAR(I,4))))
RETURN
END

C-- Given the run number and pt715 this function returns error in
C relative Et_b trigger efficiency

FUNCTION ETB_RELEFF_ERR(NRUN, PT715)

REAL PAR(4,4), ERR(4,4), ERR1, ERR2, ERR3, ERR4

REAL EXP0, W1, W2, W3, W4

DATA ((PAR(I,J), J=1,4), I=1,4)

+ /1.000, 1.000, 4.676, 1.075,

+ 1.000, 1.000, 4.876, 0.977,

+ 1.000, 1.000, 4.144, 1.027,

+ 1.000, 1.000, 4.243, 1.074/

DATA ((ERR(I,J), J=1,4), I=1,4)

+ /0.0000, 0.0000, 0.0651, 0.0539,

+ 0.0000, 0.0000, 0.0285, 0.0203,

+ 0.0000, 0.0000, 0.0311, 0.0212,

+ 0.0000, 0.0000, 0.0837, 0.0663/

C-- Check the run number (different sets of parameters for different runs)

C-- If run number corresponds to 210 Gev negative beam

IF (((NRUN .GE. 822) .AND. (NRUN .LE. 1062)) .OR.
& ((NRUN .GE. 1065) .AND. (NRUN .LE. 1098))) I = 1

C-- If run number corresponds to 250 Gev negative beam

IF (((NRUN .GE. 1063) .AND. (NRUN .LE. 1064)) .OR.
& ((NRUN .GE. 1099) .AND. (NRUN .LE. 1635))) I = 2

C-- If run number corresponds to positive mixed beam

IF (((NRUN .GE. 1636) .AND. (NRUN .LE. 1960)) .OR.
& ((NRUN .GE. 2010) .AND. (NRUN .LE. 2081))) I = 3

C-- If run number corresponds to positive proton beam
IF ((NRUN .GE. 1961) .AND. (NRUN .LE. 2009)) I = 4

EXP0 = EXP((PT715 - PAR(I,3)) / PAR(I,4))

W1 = 1.0

W2 = 1/(1+EXP0)**2

W3 = (PAR(I,2)*EXP0/(PAR(I,4)*(1+EXP0)**2))**2

W4 = (PAR(I,2)*EXP0*(PT715-PAR(I,3))/((PAR(I,4)**2)*(1+EXP0)**2))**2

ERR1 = ERR(I,1)**2

ERR2 = ERR(I,2)**2

ERR3 = ERR(I,3)**2

ERR4 = ERR(I,4)**2

ETB_RELEFF_ERR = SQRT(W1*ERR1 + W2*ERR2 + W3*ERR3 + W4*ERR4)

RETURN

END

etnzeff 210zneq

etnzeff 250zneq

etnzeff 250zpos

etnzeff proton

etpizelf 210zneg

etpizelf 250zneg

etpizelf 250zpos

etkzefl proton

**Strangeness ± 2 KK Scattering
in a $qq\bar{q}\bar{q}$ Potential Model**

John Weinstein

Department of Physics, University of Mississippi, Oxford, MS, 38677

ABSTRACT

We extend our study of pseudoscalar-pseudoscalar S -wave scattering to the $I=1$, strangeness ± 2 KK and $\overline{KK}$ systems using a model which is based on quark exchange processes rather than t -channel meson exchange. This model has previously been applied to the $I=0$, $\frac{1}{2}$, 1 , $\frac{3}{2}$, and 2 $J^P = 0^+$ pseudoscalar-pseudoscalar systems and successfully describes many experimental features. We predict a repulsive $I=1$ KK potential, and suggest that its effects may be observable in high statistics production experiments as a suppression of the KK invariant mass distributions near threshold.

Draft

November 23, 1991

INTRODUCTION

In several earlier papers we presented coupled-channel scattering analyses of $I = 0, 1$, and 2 nonstrange^{1,2} and $I = \frac{1}{2}$ and $\frac{3}{2}$ strangeness ± 1 ³ S -wave pseudoscalar meson pairs. In this paper we complete this program by presenting our results for the elastic phase shift and KK invariant mass distributions in production experiments. The strangeness 2 $I = 1$ K^+K^+ , $(K^+K^0 + K^0K^+)/\sqrt{2}$, and K^0K^0 systems, and their strangeness -2 Hermitian conjugates, are the only light pseudoscalar meson pairs we had not previously considered. These final states can be observed, for example, at LASS (in the process $K^+p \rightarrow K^+K^+\Lambda$) and in current and planned hyperon beam experiments at KEK, BNL, and ITEP. Note that we do not consider the $I = 0$ $(K^+K^0 - K^0K^+)/\sqrt{2}$ system and its Hermitian conjugate as they are antisymmetric in flavor and so cannot be in a relative S -wave. In this paper we review our model, present results for this sector, and discuss a possible measurement to test the prediction.

THE MODEL

Our model employs a matrix radial Schrödinger equation

$$(\mathbf{K} + \mathbf{M} + \mathbf{V}) \mathbf{u}_{I,S}(r) = E \mathbf{u}_{I,S}(r) \quad (1)$$

which couples S -wave pseudoscalar pairs and $q\bar{q}$ scalar mesons within each isospin (I) and strangeness (S) sector. In eq. (1) $\mathbf{K}$ is a diagonal nonrelativistic kinetic energy operator and $\mathbf{M}$ is a diagonal mass matrix, so that E is the total nonrelativistic energy rather than the usual kinetic energy. The non-diagonal potential matrix $\mathbf{V}$ contains three different types of entries, which correspond to the three distinct physical processes $P_1P_2 \leftrightarrow P'_1P'_2$, $P_1P_2 \leftrightarrow S$, and $S \leftrightarrow S$, where P_i represents a pseudoscalar and S a scalar meson.

The $P_1P_2 \leftrightarrow P'_1P'_2$ potentials are determined from a variational nonrelativistic quark model calculation which concluded that the $qq\bar{q}\bar{q}$ low-lying states are mainly scattering states of 0^-0^- meson pairs (with a numerically insignificant 1^-1^- admixture) and that the main intermeson forces arise from quark-exchange processes driven by the hyperfine interaction.^{1,2,3} All but one of the parameters used in this model is determined by low energy meson spectroscopy, the final parameter is chosen by a fit to the $I=2$ $\pi\pi$ S -wave phase shift data.

The $P_1 P_2 \leftrightarrow S$ potentials are based on an $SU(3)$ symmetric 3P_0 $q\bar{q}$ annihilation picture which depends on the $P_1 P_2$ and S flavor wavefunctions, a mass dependent form factor, and a potential chosen to give the $f_0(1300) \rightarrow \pi\pi$ width found by Kokoski and Isgur.⁵

The $S \leftrightarrow S$ potential has a $q\bar{q}$ confining component, a repulsive $1/r^2$ centrifugal barrier, and constant chosen to reproduce the ground state 3P_0 masses.⁶

The dimensions of the matrices in eq. (1) depend on the number of S -wave pseudoscalar pairs and scalar $q\bar{q}$ mesons in a given isospin and strangeness sector. The wavefunction vectors $\mathbf{u}_{I,S}$ have subscripts which denote the isospin and strangeness of the sector and have the form

$$\begin{aligned} \mathbf{u}_{1,2} &= (u_{\kappa\kappa}), \\ \mathbf{u}_{\frac{1}{2},1} &= (u_{\kappa\pi^{I=\frac{1}{2}}}), \\ \mathbf{u}_{\frac{1}{2},1} &= \begin{pmatrix} u_{\kappa\pi^{I=\frac{1}{2}}} \\ u_{\kappa\eta} \\ u_{\kappa\eta'} \\ u_{\kappa^*(1410)} \end{pmatrix}, \quad \text{or} \quad \mathbf{u}_{0,0} = \begin{pmatrix} u_{\eta\pi^{I=0}} \\ u_{\kappa\bar{\kappa}^{I=0}} \\ u_{\eta\eta} \\ u_{\eta\eta'} \\ u_{\eta'\eta'} \\ u_{f_0(1300)} \\ u_{f'_0(1500)} \end{pmatrix}. \end{aligned} \quad (2)$$

We solve eq. (1) numerically in each sector at a given scattering energy E to determine the wavefunctions and hence the S -matrix. Scanning over a range of energies allows us to find, for example, the energy dependent phase shifts.

A comparison of the predictions of this model with experimental data in other sectors has lead to many insights into the behaviour of these systems and the possible resolution of a wide range of issues. A list of successes would include understanding the masses, widths, and branching fractions of the S^* and δ scalars⁷ (also known as the $f_0(975)$ and $a_0(980)$) and the $q\bar{q}$ scalar mesons, low energy pseudoscalar-pseudoscalar phase shifts,^{1,2,3} the two photon widths of the S^* and δ , the $\Delta I = \frac{1}{2}$ in K decay,⁸ pseudoscalar-pseudoscalar spectra in $J/\psi \rightarrow P_1 P_2 V^{*,10}$, the physical origins of backgrounds⁹, and so on.

RESULTS FOR KK SCATTERING

We now discuss elastic scattering phase shifts and production spectra predictions for S -wave $I=1$ strangeness $+2$ K^+K^+ , $(K^+K^0 + K^0K^+)/\sqrt{2}$, and K^0K^0 (and their strangeness -2 Hermitian conjugates). As these systems contain two strange antiquarks the ground-state flavor wavefunctions must be symmetric in quark or antiquark exchange. There are no strangeness ± 2 $q\bar{q}$ states which can be produced as s -channel resonances so these mesons interact only through quark-exchange processes in this model.

Our study of the $P_1P_2 \leftrightarrow P'_1P'_2$ which lead to the potentials used in the other sectors predicts a repulsive KK interaction. In the same approximations used in the previous studies we represent this potential by a square well with height $V = +0.29$ GeV and with range $a=0.8$ fm. In fig. 1 we show the predicted exotic strangeness ± 2 KK S -wave scattering phase shift as a function of the KK nonrelativistic energy $E = T + 2m_K$ where T is the kinetic energy. This phase shift is found by solving eq. (1) numerically or equivalently by

$$\delta_0^{KK} = \begin{cases} \arctan(k/\kappa \tanh \kappa a) - ka & T < V \\ \arctan(k/\kappa \tan \kappa a) - ka & T > V \end{cases} \quad (3)$$

where $k = \sqrt{2\mu T}/\hbar$, $\kappa = \sqrt{2\mu|T - V|}/\hbar$, and $\mu = 0.2475$ GeV/ c^2 .

This phase shift can be converted into an s -wave cross section prediction through

$$\sigma_0 = \frac{4\pi}{k^2} \sin^2(\delta_0) \quad (4)$$

and leads to a cross section prediction of 6.6 mb at threshold.¹¹ In the absence of real K^+K^+ colliding beams we cannot compare this prediction with data, the effects due to the vertex $P \rightarrow K^+ \Lambda$ are not known and presumably large.

We can, however, predict the effects of final state interactions due to the repulsive K^+K^+ potential on the invariant mass distribution of, for example, the K^+K^+ events which are kinematically well separated from the recoiling Λ in the reaction $K^+p \rightarrow K^+K^+\Lambda$. The matrix element for the K^+K^+ production in the nonrelativistic limit will be due to the wavefunction at the origin squared, a quantity easily calculated in the potential model. The results of this calculation are shown in fig. 2 where we compare our line shape with the phase space distribution. As expected the repulsive potential leads to an observable depletion of events at low K^+K^+ invariant mass.

We are unaware of any analysis done on this channel although LASS has some data on tape¹² and other experiments are being planned which will have KK final states.¹³

CONCLUSIONS

We have applied the quark-exchange meson-meson scattering model, which is successful in the $I = 0, \frac{1}{2}, 1, \frac{3}{2},$ and 2 S -wave $P_1 P_2$ sectors, to the $I = 1$ strangeness ± 2 KK and $\overline{KK}$ sectors. With no free parameters we predict a repulsive KK interaction and show the resulting elastic phase shift and production invariant mass distribution.

ACKNOWLEDGEMENTS

I would like to thank Ted Barnes and Nathan Isgur for many discussions and contributions.

REFERENCES

1. J. Weinstein and N. Isgur, Phys. Rev. Lett. **48**, 659 (1982); Phys. Rev. D**27**, 588 (1983).
2. J. Weinstein and N. Isgur, Phys. Rev. D**41**, 2236 (1990).
3. J. Weinstein and N. Isgur, Phys. Rev. D**43**, 95 (1991).
4. J. Weinstein, UMSPHY-....., Proceedings of the 4th International Conference on Hadron Spectroscopy, Washington, 1991.
5. R. Kokoski and N. Isgur, Phys. Rev. D**35**, 907 (1987).
6. S. Godfrey and N. Isgur, Phys. Rev. D**32**, 189 (1985).
7. T. Barnes, Phys. Lett. **165B**, 434 (1985).
8. N. Isgur, K. Maltman, J. Weinstein, T. Barnes, Phys. Rev. Lett. **64**, 161 (1990).
9. For a discussion of preliminary production results see J. Weinstein, Proceedings of the Tau-Charm Factory Workshop, SLAC-Report-343, 1989; J. Weinstein, Proceedings of HADRON89, Int. Conf. on Hadron Spectroscopy, Corsica, 1989.
10. J. Weinstein and N. Isgur, unpublished.

11. This compares with a cross section of 10 mb in a complementary quark exchange Born approximation calculation, T. Barnes and E. Swanson, MIT/CTP, ORNL/CCIP/91/23, UTK/91/08 preprint.
12. W. Dunwoodie, private communication.
13. See, for example, Dolgolenko, R. Schumacher, and K. Imai Proceedings of the 4th International Conference on Hadron Spectroscopy, Washington, 1991.

Fig. 1: The $I=1$ strangeness ± 2 KK elastic scattering phase shift predicted from the model and given by eq. (3).

Fig. 2: The predicted $I = 1$ strangeness ± 2 KK invariant mass distribution compared to phase space.

Low Mass Pseudoscalar-Pseudoscalar Dynamics

John Weinstein

Department of Physics, University of Mississippi, University, MS, 38677

ABSTRACT

We discuss possible hadron-hadron interaction mechanisms and a model for incorporating these mechanisms in a coupled channel formalism. An application of these ideas to pseudoscalar-pseudoscalar S -wave scattering is reviewed. We find that s -channel resonance formation with quark exchange processes are sufficient to reproduce experimental observations, meson exchange forces are not required.

HADRON-HADRON INTERACTIONS

When two scattering hadrons are within a few fermi of each other they may interact via the strong force. The mechanisms driving their interactions are, however, not well understood.

One idea, dating back to Yukawa, is that the interaction takes place via " t -channel" meson exchange as depicted in fig. 1a. The S -matrix for hadron-hadron scattering may be formally determined by summing over the exchange of all allowed intermediate mesons. The range of these interactions is dependent on the mass m of the exchanged meson; it is of the order of the Compton wavelength $\lambda = \hbar/mc$. The Compton wavelength of the π is about 1.4 fm, but the Compton wavelengths of the next lightest pseudoscalar mesons, the K and the η , are $\lambda_K = 0.4$ fm and $\lambda_\eta = 0.36$ fm. The lightest vector meson is the ρ and $\lambda_\rho = 0.26$ fm. Thus we see that when two scattering hadrons, whose individual wavefunctions are finite over ranges of about 0.5 to 1.0 fm, are close enough to scatter via meson exchange they are, with the exception of π exchange, overlapping. It follows that the whole picture of meson exchange interactions between point like hadrons loses much of its footing when applied to physical hadrons.

The picture of overlapping hadron wavefunctions which undermines the meson exchange picture suggests two other interaction mechanisms. The one we shall discuss first is due to $q\bar{q}$ annihilation and $q\bar{q}$ creation processes, depicted in fig. 1b for the specific case of meson-meson (MM') scattering. This reaction can occur if a quark in one meson can annihilate with an antiquark in the other meson. This leads to the production of an " s -channel" meson and the S -matrix can again be determined by summing over all s -channel resonances.

The duality of s - and t -channel meson exchange for MM' scattering is evident from figs. 1a and 1b, which may be continuously deformed into one another. Thus the S -matrix can be described in terms of a complete set of either process, considering subsets of both processes runs the risk of unphysical predictions due to double counting.

The next mechanism we discuss is that of quark exchange, depicted in fig. 1c. When two scattering hadrons are near enough that their wavefunctions overlap this is clearly a likely occurrence. In fact, if there are identical particles in the scattering hadrons, the wavefunction representing the system must contain such diagrams in order to be properly antisymmetrized. Thus we see that the dynamics of quark exchange are intrinsic to the dynamics of hadron scattering.

Earlier we noted that the s and t -channel diagrams for MM' scattering may be deformed into one another. We now consider deformations of fig. 1c. As can be seen in fig. 1d we can deform fig. 1c

to look like t -channel meson exchange if we scatter a quark backwards and then forwards in time. This requires the introduction of additional annihilation and creation operators in the Hamiltonian and leads to an intermediate state with 6 quark lines; in fig. 1a we can cut the diagram and have only 2 lines.¹ Hence fig. 1c is deformable into a subset of the processes in 1a but it cannot be deformed into the process depicted by fig. 1b and so fig. 1c represents new physics.

FIGURE 1: Representation of possible mechanisms for MM' scattering; in (a) t -channel meson exchange, in (b) s -channel resonances, and in (c) quark exchange. In (d) we show (c) deformed by having a quark line scatter backwards and forwards in time. Time runs up the page and space runs across the page.

In several earlier papers²⁻⁴ we described how we used the non-relativistic quark model to calculate effective potentials based on fig. 1c. The Hamiltonian used in those calculations is a simplified version of the Hamiltonian used in calculations of the spectroscopy and decays of mesons and baryons, as well as the deuteron, thus leading to a unified description of both stationary and scattering quark states in a single model. Here we discuss the physics underlying the scattering systems based on the dynamics embodied in figs. 1b and 1c. It turns out that, at the present levels of experimental and theoretical accuracy, no contributions from fig. 1a are required.

AN APPLICATION TO S-WAVE PSEUDOSCALAR-PSEUDOSCALAR SCATTERING

In both figs. 1b and 1c there is no general requirement that the individual mesons leaving the interaction region have the same quantum numbers as those in the initial state; the requirement is rather that the overall quantum numbers of the initial and final states be the same. (In specific cases such as $\pi^+\pi^+ \rightarrow \pi^+\pi^+$, $K^+\pi^+ \rightarrow K^+\pi^+$, and $K^+K^+ \rightarrow K^+K^+$, it is true that the individual mesons retain their identity, and it also follows that they scatter only through the process in fig. 1c.) Thus, for example, an incoming $I=0$ $\pi^+\pi^-$ state may scatter into an asymptotic $\eta\eta$ state if the $\pi\pi$ invariant mass exceeds $2m_\eta$. This final state may also lead to a K^+K^- final state via either of the processes in fig. 1b or 1c: An $s\bar{s}$ creation in 1b can lead directly from $\pi^+\pi^-$ to K^+K^- ; The scattering from $\pi^+\pi^-$ to a virtual $\eta\eta$, followed by the conversion of a $d\bar{d}$ component of the η into an $s\bar{s}$ component, followed by a second scattering process, $\eta\eta \rightarrow K^+K^-$, leads indirectly from $\pi^+\pi^-$ to K^+K^- and plays an essential role in the dynamics of such systems.

Thus we see that a complete description of these scattering processes requires a coupled-channel approach. A reasonable starting point for S -wave pseudoscalar-pseudoscalar scattering is the radial coupled-channel matrix Schrödinger equation:

$$(K + M + V) u_{I,s}(r) = E u_{I,s}(u). \quad (1)$$

Here the wavefunction $u_{I,S}(r)$ represents the amplitude for two mesons or a $q\bar{q}$ meson with net isospin I and strangeness S to have relative separation r . In eq. (1) K is a diagonal nonrelativistic kinetic energy operator and M is a diagonal mass matrix, so that E is the total nonrelativistic energy rather than the usual kinetic energy. The non-diagonal potential matrix V contains three different types of entries, which correspond to the three distinct physical processes $P_1 P_2 \leftrightarrow P'_1 P'_2$ of fig. 1c, and $P_1 P_2 \leftrightarrow S$, and $S \leftrightarrow S$ which are the components of fig. 1b, where P_i represents a pseudoscalar and S a scalar meson.

The $P_1 P_2 \leftrightarrow P'_1 P'_2$ potentials due to quark exchange have been determined from a variational nonrelativistic quark model calculation which concluded that the $qq\bar{q}\bar{q}$ low-lying states are mainly scattering states of 0^-0^- meson pairs (with a numerically insignificant 1^-1^- component) and that intermeson "nuclear" forces are, in fact, dominated by quark-exchange processes driven by the hyperfine interaction.^{2,9} One model parameter is chosen from a fit to the $I=2$ $\pi\pi$ S -wave phase shift data, and the remaining parameters are determined by low energy meson spectroscopy. We use approximate square well potentials with ranges of 0.8 fm to solve eq. (1) numerically.

The $P_1 P_2 \leftrightarrow S$ potentials which determine the vertex factors in fig. 1b are calculated from an $SU(3)$ symmetric 3P_0 $q\bar{q}$ annihilation picture which includes Clebsch-Gordan factors dependent on the F, P_2 and S flavor wavefunctions, mass dependent form factors, and an overall square well depth chosen to reproduce the $f_0(1300) \rightarrow \pi\pi$ width of Kokoski and Isgur.⁵

The $S \leftrightarrow S$ potential, which allows the $q\bar{q}$ meson to propagate from one vertex to the other in fig. 1b, consists of a square well $q\bar{q}$ confining potential, a repulsive $1/r^2$ P -wave centrifugal barrier, and a set of constants chosen to reproduce the ground state 3P_0 masses in agreement with both experiment and the predictions of the quark model.⁶

The dimensions of the matrices in eq. (1) are determined by the number of S -wave pseudoscalar pairs and scalar $q\bar{q}$ mesons in the flavor sector being investigated. The subscripts of $u_{I,S}$ denote the net isospin and strangeness of the sector, and are of the form

$$\begin{aligned} u_{1,2} &= (u_{\kappa\kappa}), & u_{1,0} &= \begin{pmatrix} u_{\eta\pi} \\ u_{\kappa\bar{\kappa}I=1} \\ u_{\eta'\pi} \\ u_{a_0(1300)} \end{pmatrix}, \\ u_{\frac{1}{2},1} &= (u_{\kappa\pi I=\frac{1}{2}}), \\ u_{\frac{1}{2},1} &= \begin{pmatrix} u_{\kappa\pi I=\frac{1}{2}} \\ u_{\kappa\eta} \\ u_{\kappa\eta'} \\ u_{\kappa_0^*(1410)} \end{pmatrix}, & u_{0,0} &= \begin{pmatrix} u_{\pi\pi I=0} \\ u_{\kappa\bar{\kappa}I=0} \\ u_{\eta\eta} \\ u_{\eta\eta'} \\ u_{\eta'\eta'} \\ u_{f_0(1300)} \\ u_{f'_0(1500)} \end{pmatrix}, \\ \text{or } u_{2,0} &= (u_{\pi\pi I=2}). \end{aligned} \tag{2}$$

We solve eq. (1) numerically in each sector at a given scattering energy E to determine the wavefunctions and hence the S -matrix. The asymptotic behavior of the scattering states determines the energy dependent phase shifts, and the inelasticities are determined by comparing the relative amplitudes of outgoing waves in each channel for a given incoming wave. We have found that these solutions are not extremely sensitive to the parameter set we choose for these three sets of potentials.²⁻⁴

A comparison of the predictions of this model with experimental data has lead to many insights into the behaviour of these systems and the possible resolution of several outstanding problems in hadron physics. A list of successes includes an understanding of the masses, widths, and branching fractions of the S^* and δ (also known as the $f_0(975)$ and $a_0(980)$ respectively) scalars and the the $q\bar{q}$ scalar mesons, low energy pseudoscalar-pseudoscalar phase shifts,²⁻⁴ the two-photon widths of the S^* and δ ,⁵ the $\Delta I=1/2$ rule in K decay,⁶ pseudoscalar-pseudoscalar invariant mass distributions in $J/\psi \rightarrow P_1 P_2 V$,⁷ the physical origins of backgrounds,⁸ and other related problems.

Of special interest is the nature of the S^* and δ which we find in the model to be predominantly $K\bar{K}$ bound states. In fig. 2 we show the probability amplitude to find the components of $u_{0,0}$ in $I=0$ $\pi\pi$ scattering as a function of the $I=0$ $\pi\pi$ invariant mass. These probabilities have been normalized to unit incoming $\pi\pi$ amplitude and demonstrate the overwhelming domination of the bound $K\bar{K}$ channel just below $K\bar{K}$ threshold.

FIGURE 2: The probability of finding an $I=0$ $\pi\pi$ scattering system as $K\bar{K}$, $f_0(1300)$ and $f'_0(1530)$ in the central region. These curves are obtained by integrating the component probabilities over all space and are normalized to unit incoming $I=0$ $\pi\pi$ amplitude. It is clear that near $K\bar{K}$ threshold the system is dominated by the $K\bar{K}$ system, leading to the conclusion that the S^* is mainly a $K\bar{K}$ bound state.

CONCLUSIONS

We have discussed possible mechanisms for the interaction of scattering hadrons and conclude from both general arguments and a specific calculation in the S-wave PP scattering systems that the interaction is dominated by s -channel resonance production and quark exchange effects, meson exchange is not yet required to fit this data. In this sector quark exchange leads to the binding of $K\bar{K}$ states within the framework of a simple intuitive Schrödinger equation. As discussed elsewhere in the literature this interpretation solves many problems.

ACKNOWLEDGEMENTS

I would like to thank Ted Barnes and Nathan Isgur for many discussions and contributions.

REFERENCES

1. N. Isgur, Acta Physica Austriaca (Suppl) XXVII 177-266 1985.
2. J. Weinstein and N. Isgur, Phys. Rev. Lett. **48**, 659 (1982); Phys. Rev. D**27**, 588 (1983).
3. J. Weinstein and N. Isgur, Phys. Rev. D**41**, 2236 (1990).
4. J. Weinstein and N. Isgur, Phys. Rev. D**43**, 95 (1991).
5. R. Kokoski and N. Isgur, Phys. Rev. D**35**, 907 (1987), Phys. Rev. Lett. **44**, 869, (1985).
6. S. Godfrey and N. Isgur, Phys. Rev. D**32**, 189 (1985).
7. T. Barnes, Phys. Lett. **165B**, 434 (1985).
8. N. Isgur, K. Maltman, J. Weinstein, and T. Barnes, Phys. Rev. Lett. **64**, 161 (1990).
9. J. Weinstein, Proceedings of the Tau-Charm Factory Workshop, SLAC-Report-343, 1989. Proceedings of HADRON89, Int. Conf. on Hadron Spectroscopy, Corsica, 1989; J. Weinstein and N. Isgur, unpublished.

E791

E791 STATUS REPORT

Presented at the All Experimenter's Meeting Oct.14,1991

E791 STATUS REPORT
All Experimenter's Mtg. Oct. 14th, 1991

E791 -- Continued Study of Charm at TPL

Hadro Production -- 500 GeV Pion beam
3% Interaction Length Target

**Fairly typical magnetic spectrometer + 23 Silicon strip
planes in the target region**

Global Et trigger gives charm enhancement of 1.5 - 2.0

High rate DA system -- 200K events per spill

Goal is 100,000 reconstructed charm events

CURRENT STATUS

In stable data-taking mode

will show data written vs time for 1991 run

Monitoring data quality

New SMD planes

New Drift Chamber gas

will show sample plots we use for monitoring

Tuning up offline reconstruction software

Cumulative Number of Events, By Day

14-oct-1991

91/09/26 14

Currently ~ 20 μ m RESOLUTION FOR 50 μ m PLANES

14 μ m RESOLUTION FOR 25 μ m PLANES

90% to 95% EFFICIENT

SAMPLE DRIFT CHAMBER

91/10/14 12.30

DCCHECKz933.RZFz2 RESIDUAL (BACKGROUND SUBTRACTED)

STANDARD PLOT WE USE FOR MONITORING DETECTORS AND SOFTWARE

VERY ROUGH "VERTEX" ALGORITHM - NO CUTS APPLIED

Ave. 5 to 6 TRACKS PER PRIMARY VERTEX

STATUS OF OFFLINE SOFTWARE

Full detector tracking package is in place. Tuning up alignments and track linking in the magnets.

Producing threshold curves for calibrating Cerenkov detectors

Calibrating calorimeters using electron and muon data

**Full Reconstruction package (tracking + calorimeters + Cerenkov)
is getting pulled together**

**Multi-processor version of code for use on Farm Production systems
is under development**

Monte Carlo produces data tapes for verification of all the above

Filter is under development on ACP2

**All code gets distributed to and tested on all platforms we expect
to use : Vax, SGI, IBM-Rios, ACP2, SUN, DEC-station**

© 2006 The Authors
Journal compilation © 2006 Blackwell Publishing Ltd

DATE 07/11/91

CHANNELS	10	0	1	2	3	4	5
	1	1234567890123456789012345678901234567890123456789012345678901234567890					

CONTENTS 10 1 11123333211
1. 833112223131 5503425588232893351045882421333 44722

[illegible]

```

* ENTRIES = 499 * ALL CHANNELS = 0.3930E+03 * UNDERFLOW = 0.56
OOE+02 * OVERFLOW = 0.5000E+02
* BIN WID = 0.2000E-02 * MEAN VALUE = 0.5054E+00 * R . M . S = 0.19
11E-01
* CHISQUAR = 0.4876E+02
Number of events = 230 +- 17

```

CHERENKOV LIGHT YIELD vs MOMENTUM

Here we display a normalized yield of Cherenkov photons versus momentum (GeV) for a small sample of data taken by E791. The fits show that the threshold behavior is as predicted for a N_2 gas radiator in C1 and a 80:20 mix of He to N_2 in C2.

E791 PROPORTIONAL WIRE CHAMBERS
BEAM PWC WIRE PARTICIPATION PLOTS

- 38 -

03/08/91 22.00

Part. plot for pwc plane 5

Part. plot for pwc plane 6

Part. plot for pwc plane 7

Part. plot for pwc plane 8

E791 CERENKOV COUNTER
FITTED SINGLE PHOTO-ELECTRON PEAKS

- 22 -

25/09/91 12.32

CERENKOV 1-1

CERENKOV 1-2

CERENKOV 1-3

CERENKOV 1-4

E791 MUON IDENTIFICATION SYSTEM
3 METER LONG SCINTILLATION COUNTER TDC TIMES

25/09/91 12.54

- 7 -
muon TDC distributions for each channel

muon TDC time y 13

muon TDC time y 14

muon TDC time y 15

muon TDC time y 16

KEY

Ethernet backbone

Terminator

h1,c1

DECstation 5000/200 servers
(workstations)

ha-hk, ca-cv

DECstation 5000/200 diskless
clients (cpu's only)

hl-hp

DECstation 5000/200 diskless
clients (workstations)

b1

DECstation 5000/120
(workstation)

Ds

DECserver 90l

Db

DECbridge 90

DI

DECLaser 2100

SG

Silicon Graphics 4D/20

Vax

VAXstation II/GPX

ts

DECserver 200/MC

Mac

Macintosh Plus

3100

VAXstation 3100/76

fiber optic

GCI 1100 1B1F fiber optic repeater

Prospectus for a Doctoral Dissertation in Physics:

STUDY OF CHARM PARTICLES

Study of Cross Section of Hadroproduced Neutral D Meson
in Experiment 769 at FNAL

SUBMITTED BY

Ali Rafatian
University of Mississippi

I. Introduction: During the period of 1987-88 of the fixed target run at Fermilab, experiment 769 recorded about 400 million events corresponding to the interactions of a mixed hadron beam of pions, kaons, and protons with the target foils of Be, Al, Cu and W.

As a result of the initial analysis of these data some 1300 $D^0 \rightarrow K^- \pi^+$ decays were found. Knowing that the branching ratio for this mode is about half of that for $D^0 \rightarrow K^- \pi^+ \pi^- \pi^+$ decay, we can expect to get at least a few hundred of these decays. From a preliminary look we can estimate about 500 decays in all. This sample of decays is the largest of its kind produced in hadron-hadron collisions. They will help augment our studies of charm particle production and give our experiment a more accurate estimation of the total cross section for the hadroproduction of charm.

II. The Theory of Hadroproduction of Charm:¹

The hadroproduction of heavy quarks in high energies is treated as a hard scattering problem in the QCD parton model. This model expresses the cross section σ for a hard interaction with characteristic momentum scale Q as follows:

$$\sigma(P_1, P_2) = \sum_{ij} \int dx_1 dx_2 f_i(x_1, \mu) f_j(x_2, \mu) \hat{\sigma}_{ij}(\alpha_s(\mu), x_1 P_1, x_2 P_2)$$

where P_1 and P_2 are the momenta of the incoming hadrons, x_1 and x_2 are the momentum fractions carried by the constituent partons of each hadron, and $f_i(x)$ is the distribution function (or density) of the partons of type i with momentum fraction between x and $x+dx$. μ is an arbitrary scale of the order of Q , the hard momentum scale, and α_s is the strong coupling, and the sum on i and j runs over the light quarks and gluons. This formula is illustrated in figure 1.

The parton reactions which contribute most to the production of a heavy quark are the following two which are also presented as Feynman diagrams in figure 2.

$$(a) \quad q(p_1) + \bar{q}(p_2) \rightarrow Q(p_3) + \bar{Q}(p_4)$$

$$(b) \quad g(p_1) + g(p_2) \rightarrow Q(p_3) + \bar{Q}(p_4)$$

¹ R. K. Ellis, FERMILAB-Conf-89/168-T, August 9, 1989.

III. Experiment:² E769 was a fixed target experiment performed at Tagged Photon Laboratory at Fermilab, by an international collaboration of several institutions from Brazil, Canada, and the United States.

The beam was a mix of 250 GeV π , K, and p incident on different target materials. The spectrometer which is shown in figure 3 consisted of the following components:

1. Beam ID:

- a) Differential Isochronous Self-collimating Cerenkov Counter (DISC)
- b) Transition Radiation Detector (TRD)

These two detectors were used in tagging the beam particles as pions, kaons or protons.

2. Beam Tracking:

- a) 2 sets of Proportional Wire Chambers (PWC)
- b) Silicon Microstrip Detector (SMD)

Each PWC consisted of four planes X, Y, X', and W. The beam SMD had two views X and Y.

3. Down Stream Tracking System:

- a) Silicon Microstrip Detector (SMD)
- b) Proportional Wire Chambers (PWC)
- c) Drift Chambers (DC)

This system consisted of 11 SMD planes used as vertex telescope, 2 PWC Y-planes to complement the first set of DC planes upstream of the analysis magnets, and a total of 35 DC planes interspersed along the spectrometer in four regions.

4. Analysis magnets:

M1 and M2 were used along with drift chambers in determining the momentum of tracks. The experimental resolution of a high mass state is about 8 MeV/c²

5. Cerenkov Counters:

C1 and C2 were threshold gas chambers used in identifying the non-leptonic decay products such as π , K, and p's. The momentum thresholds are 5.9 GeV and 10.2 GeV respectively for the counters. C1 uses pure N₂ as a cherenkov radiator and C2 uses a 80:20 mix of He and N₂.

Figure 1. The parton model picture of a high energy scattering

Figure 2. Lowest order Feynman diagrams for heavy quark production

6. Calorimeter:

- a) Segmented Liquid Ionization Calorimeter (SLIC)
- b) Hadrometer

SLIC, an electromagnetic calorimeter, along with Hadrometer, the hadronic calorimeter were used to determine the energy of the decay products and also to implement a transverse energy (E_T) trigger.

TAGGED PHOTON SPECTROMETER
E791

Figure 3. E769 spectrometer

IV. Analysis: After some preliminary reconstructions known as Passes, where tracks were reconstructed and their momenta and energies were calculated, the information most necessary to the analysis was passed on the the Data Summary Tapes (DSTs). The DSTs have taken years and hard work by many people to prepare.

The first analysis pass known as PAIR STRIP was performed on DSTs to select events containing multiple vertices. The vertex with the most number of tracks is picked as the primary vertex. There are certain requirements and cuts applied to the selection process to ensure quality vertices.

The next step is an analysis strip of the decay mode. $D^0 \rightarrow K3\pi$, the charm decay I'm interested in studying. The basic criterion in this strip is to look for 4-track vertices where the sum of the charges of the tracks is zero.

5

I mark one of the tracks as a kaon so that later on I can impose a cut on its probability as a kaon using cerenkov information. The other important criterion in selecting an event is to develop appropriate cuts on the tracks, vertices and events as a whole. Cuts like Chi squared per degree of freedom, isolation and mass cuts.

To develop these strip cuts we use Monte Carlo (MC). First, we generate a large number of the decay products we are interested in. Then we use the digitizer to place the generated events into the raw data format. Next, this simulated raw data is run through the same reconstruction code that was used on the real data. At this point, we could also run the pair strip code on it to get a smaller data sample for our Ntuple maker. The Ntuple maker is a program which follows similar criteria for a good candidate as the strip does. The main purpose of the Ntuple maker is to enable the experimenter to investigate the proper and unbiased cuts on different variables to optimize signal to noise.

The method used to achieve this is to turn the same Ntuple maker on the pair stripped data and try to maximize the ratio of the signal size in the MC data to the square root of the events that pass the same cut in the pair stripped data.

Having selected the appropriate cuts through the above method, we can incorporate them into our stripping program. After the analysis is performed on the pair strip tapes, we run our Ntuple maker on the output tapes. Having obtained our long-awaited ntuple, we now proceed with the analysis. Here, we try to measure our signal sizes and calculate the errors associated with them through a series of fitting programs. I should mention here that all along this process, we should try to make sure we have generated enough MC data in order to calculate the acceptance with good enough statistics.

V. Timeline: At the present time, I have the stripping code ready. I anticipate a few months for stripping and ntuple making, assuming free access to and smooth running of the Silicon Graphics computing facilities. I also need to generate at least 500K MC events, and considering the parallel production of other modes and their reconstruction on ACPIIs, it won't be till sometime next year before I have enough statistics in hand. I believe after having acquired all the relevant data, I will need a couple of months to work with the data and probably to

deal with some unforeseen problems.

Even assuming that some of the work like writing up the dissertation can be done concurrently with other jobs, I don't think I can finish in less than a year from now. THIS IS AN OPTIMISTIC ESTIMATE.

Using Parallel RISC Computers and 8mm Tapes to find Charm Quarks

by

C. Stoughton

Fermilab, Batavia, Illinois 60510 USA

and

D. J. Summers

Department of Physics and Astronomy

University of Mississippi, Oxford, MS 38677 USA

ABSTRACT

We have integrated a system of 16 parallel RISC CPUs to help reconstruct and analyze a 1.3 Terabyte data set of 400 million high energy physics interactions. These new CPUs provided an affordable means of processing a very large data set. The data was generated using a hadron beam and a fixed target of metal foils at Fermilab Experiment 769. Signals were recorded on tape from particles created in or decaying near the target and passing through a magnetic spectrometer. Because all the interactions were independent, each CPU could completely reconstruct any interaction without reference to other CPUs. Problems of this sort are ideal for parallel processors. In the offline reconstruction system, we used Exabyte 8mm video tape drives with an I/O capacity of 7 Terabytes per year and a storage capacity of 2.3 Gigabytes per tape. This reduced tape mounts to one or two per day rather than one or two per hour as would be the case with 9-track tapes. An ETHERNETTM network was used to link the CPUs and had an I/O capacity of 15 Terabytes per year. The RISC CPUs came in the form of commercially supported workstations with little memory and no graphics to minimize cost. Each 25 MHz MIPS R3000 RISC CPU processed data 20 times faster than 16MHz Motorola 68020 CPUs that were also used. About 8000 hours of number crunching was needed to reconstruct the data set. A sample of thousands of fully reconstructed particles containing a charm quark has been produced. The sample is being used to study how hadrons produce this heavy quark [1].

I. INTRODUCTION

The computing needs of many experiments in high energy particle physics can be met using multiple CPUs working in parallel. Typical experiments record 10^8 to 10^{11} independent events. The results of the computation performed on one event do not affect other events. Therefore, it is straight forward to adapt these problems to a parallel processing environment.

Experiment 769 [2] at the Fermi National Accelerator Laboratory (Fermilab) studies the production of particles containing the charm quark. During this experiment, 400 million interactions were recorded at the Tagged Particle Spectrometer [3] on 9000 nine track tapes. The system of UNIX workstations that we describe here performs two compute intensive tasks on this data set. First, the event reconstruction algorithm, which requires $3/4$ of a CPU second per event, reconstructs particle trajectories, momenta, and type. Second, a filtering algorithm inspects each event and retains candidates that could contain charm particles. We could have performed both tasks at once but chose instead to write all of the reconstructed events on serial media during the first pass of the data. Then, we read the reconstructed events and filter during the second pass.

High energy particle physics is often similar to gold mining. A miner sifts through an enormous amount of rock to find specks of gold. A physicist often has to examine an enormous number of particle interactions to find rare events. In E769, a beam of 250 GeV/c pions, kaons, and protons interacted with 26 metal foils. A 9 month run produced a yield of over 2 billion interactions, of which 400 million were selected and recorded. Out of these interactions, we have been able to reconstruct thousands of particles containing the charm quark [1]. Typical decays include the two modes shown in Figure 1,

$$\begin{aligned} D^0(c\bar{u}) &\rightarrow K^-(s\bar{u}) \pi^+(u\bar{d}) \text{ and} \\ D^+(c\bar{d}) &\rightarrow K^-(s\bar{u}) \pi^+(u\bar{d}) \pi^+(u\bar{d}). \end{aligned}$$

Charm particles are relatively massive and long lived. We calculated the mass from the measured four-momentum of decay particles. The long charm lifetime leads to a decay length of a few millimeters. The decay length in each event is the difference between two positions: the location of the interaction of the beam particle with the target foil and the

location of the decay of the charm particle. If the mass and decay length were calculated as each event happened, it would be easy to select only the few thousand containing charm quarks. However, it is very expensive to calculate these quantities in real time. We found it easier to selectively record 400 million events out of 2 billion interactions with quantities constructed directly from the analog signals of the detector. This selection was based on the amount of energy that is produced transverse to the beam direction, since events containing charm quarks will have more transverse energy than the more frequent events with the lighter up, down, and strange quarks. This selection yielded 1.3 terabytes of event data, which were written on 9,000 nine track tapes with a high bandwidth data acquisition system [4]. We later copied these data to the 8mm format. The rapidly improving price/performance of some types of offline computing allowed us to play back these tapes and completely reconstruct the events.

II. SYSTEM REQUIREMENTS

We wanted to speed the extraction of charm events from this data. To do this a system of Reduced Instruction Set Computer (RISC) processors was devised. This supplemented a large number of Fermilab Advanced Computer Program Motorola 68020 microprocessors (ACP-I) [5] already shared by many Fermilab experiments. The idea was to build a dedicated system for one project which would avoid the delays and expense of a general purpose computer which could support scores of software packages and users.

An in-depth market survey was performed and then vendors were asked to bid on a fully competitive basis. This led to the purchase of one Silicon Graphics (SGI) [6] 4D/240S compute server by the Fermilab Physics Section which was used by E769 and other experiments. Figure 2 shows this compute server in a test configuration. Three additional SGI 4D/240S compute servers dedicated to E769 were subsequently purchased. The network architecture of this system of compute servers is shown in Figure 3.

Each SGI 4D/240S utilizes four 25 MHz processors developed by MIPS Computer Systems, the MIPS R3000 RISC CPU and MIPS R3010 Floating Point Unit. The four processors in one of the 4D/240S servers share 16MB of memory. The other three servers

each have 8MB of shared local memory. A dedicated bus is used to connect processors and memory within the compute server. We tested the performance of the shared memory by measuring the performance of a task when it is running alone, and then with three other tasks on the compute server. A performance degradation of a few per cent was noticed in the first job run on the 4D/240S when three more jobs ran concurrently. Characteristics of the processor and memory systems are in Table 1. Table 2 compares its performance to Fermilab's ACP-I Motorola 68020 processors. We had nine key goals. The SGI systems solved our nine goals as follows:

1. **GOAL.** We needed enough CPU power to complete the event reconstruction in a year. Additional delays would dilute the scientific interest in the results of this data set. We needed the processing power of an additional 300 Motorola 68020 CPUs. Our goal was get this processing power and to simultaneously minimize the cost of reconstructing an event.

SOLUTION. The SGI system provided the raw CPU power that we needed to find charm quarks in a timely fashion at a price about 50 times lower than a traditional mainframe, and three times lower than the cost of additional ACP-I systems. Anything that needlessly added cost (e.g. graphics displays or extra memory) was rejected.

2. **GOAL.** Commercial availability: We wanted to minimize designing, building and maintaining the computer hardware and operating system.

SOLUTION. The SGI system was commercially supported and incurred little in the way of engineering and self-maintenance costs. A three year software and hardware maintenance contract was bundled with each compute server.

3. **GOAL.** We needed robust, optimizing FORTRAN and C compilers. It would have been difficult to translate the 58,000 lines of the E769 FORTRAN reconstruction program into assembly code by hand. The assembly code would

have been nearly impossible to maintain even if it could be produced. We also wished to avoid debugging a FORTRAN compiler.

SOLUTION. The MIPS corporation took the unusual approach of developing their high level language compilers and hardware in parallel. RISC compilers in general must be able to overlap instructions in order to take advantage of the hardware. For example, during a MIPS floating point divide 11 other instructions can also be executed [7]. MIPS brought out excellent FORTRAN and C compilers at the same time they brought out their RISC chips. SGI provided and supported versions of these compilers. FORTRAN licenses were purchased for the two compute servers that were used for software development.

4. **GOAL.** Data Throughput: Moving 1.3 terabytes of input data and an equal amount of output data to and from processors over a period of a year requires an average I/O rate of 85 kilobytes per second. The data had to be read from the input media, distributed to the processors, collected, and written to the output media.

SOLUTION. The data throughput was provided by Exabyte 8mm tape drives [8] for the input and output data streams. ETHERNETTM provided a network data path between servers. Small Computer System Interfaces (SCSI) were used to move data to and from the tape drives. The I/O rate of an Exabyte 8mm drive is 210 kByte/sec on the SGI 4D/240S, about a factor of five faster than necessary for an E769 reconstruction input tape. For a comparison of various media characteristics see Table 3. A single ETHERNETTM can move 15 terabytes per year given a rate of 0.5 MB/s. This exceeded our minimal I/O requirement by a factor of six. Typically a CPU processed a 4kb data event for $\frac{3}{4}$ of a second. During this time no I/O was required.

5. **GOAL.** Convenience: For operational simplicity, we wanted to limit tape mounting to a few short periods per day. This avoids having to run shifts 24 hours per day to load tapes.

SOLUTION. If we had used nine track tapes directly, the system of compute servers would have required over 30 tape mounts per day to process 6,000 input and output tapes over a year. To avoid this bottleneck, we used the Fermilab tape copy facility to transfer data to the 8mm media. Each 8mm tape can hold 2.3 Gigabytes of data, or up to 13 nine track tapes. This decoupled the large number of nine track tape mounts from the continuous data flow required by the compute servers and reduced the media cost for the reconstructed data by a factor of 25. We worked with SGI to adapt the Exabyte 8mm tape drives to the 4D/240S. Our data format has variable length blocks up to 65 kilobytes. Before purchasing the system we copied an E769 nine track data tape to an 8mm cartridge. By reading this tape on an SGI system we verified that the software drivers included in the operating system handle large variable length blocks. We purchased the first tape drive from SGI to ensure system integrity. The remaining drives were supplied by third party vendors.

6. **GOAL.** Software to distribute the events to CPUs and collect results: The compute tasks can be performed in parallel by having a complete copy of the reconstruction or filtering algorithm on each of many parallel CPUs. The data flow, process scheduling, and bookkeeping tasks require careful software design.

SOLUTION. The Fermilab Advanced Computer Program's Cooperative Process Software (CPS) [9] was used to distribute events and collect results.

7. **GOAL.** Software to communicate with VAX/VMS computers: The Fermilab Physics Section's Local Area VAX Cluster (LAVC) is an interactive system of VAXstations which supports the general computing needs of physicists at Fermilab. The LAVC is shown in Figure 3. The FORTRAN code for our reconstruction and filtering algorithms was developed and maintained on this cluster.

SOLUTION. The SGI computers support TCP/IP communications. Multi-net [10] software was in use at Fermilab, and this was installed on the

VAX/VMS systems that we used, to provide them with TCP/IP communications.

8. **GOAL.** Sufficient memory for efficient CPU use: 1.3 MB of memory was needed per CPU during execution to contain the E769 reconstruction program and required data without paging to disk.

SOLUTION. A total of 8 MB of memory was put on three of the SGI computers and 16 MB on the fourth. The 8MB computers thus had 2 MB per CPU which allowed the 1.3 MB E769 reconstruction program to run without paging, even after the operating system's memory usage. Excessive memory can add substantially to the cost of a system. To minimize our memory requirements the reconstruction and filtering algorithms were run as separate passes through the data.

9. **GOAL.** We needed about 5 gigabytes of disk to store user programs and intermediate data.

SOLUTION. We wished to try to reserve the bandwidth of the SCSI buses for Exabyte 8mm tape drives. To do this we had SGI put one four-channel Enhanced Small Disk Interface (ESDI) in three of the compute servers and two in the fourth. As shown in Figure 3 all system disks are ESDI as well as seven user disks on the first compute server. Five SCSI disks are also used. All disks are 5 1/4". Many of the disks included a 5 year warranty. This greatly lowers the life cycle cost of a disk. Network File System (NFSTM) software is used to share disks between the different compute servers.

III. SOFTWARE

The compute servers ran the IRIX operating system, which is the Silicon Graphics implementation of UNIX, based on System V.3 with BSD 4.3 enhancements. IRIX is fully symmetric, allowing each process to run on any of the processors within one of the compute servers. The IRIX operating system managed CPU scheduling automatically.

A good FORTRAN-77 compiler was an essential software tool for our application, since the algorithms contain 58,000 lines of FORTRAN. The MIPS FORTRAN compiler is reliable, and we had little trouble porting our code from the VAX/VMS environment. The three optimization levels are -O0 (no optimization), -O1 (default, basic optimizations), and -O2 (global optimization). In Table 4 we compare the performance of one R3000 processor at these three optimization levels. The source line debugger (dbx) and profiler (pixie) utilities were useful in porting and optimizing this code.

We kept the sixteen processors in this system busy by using the CPS package developed at Fermilab to distribute events among the processors. The structure of one job is shown in Figure 4. Each of the bubbles represents one process on a compute server. There were three different kinds of tasks: input, output, and compute. The input and output tasks were each carried out by a single process. The compute task was either the event reconstruction algorithm or the event filtering algorithm. This compute-intensive part of the application was carried out by sixteen processes distributed among the four compute servers. One additional process, the job manager, synchronized the work of these processes.

The input process read the data stream from tape and sent blocks of events to each compute process. It then waited until one of the compute processes became available. The compute process received the event block, performed the event reconstruction or event filtering algorithm to generate an output event block, sent this block to the output process, and then signaled the input process that it was available. The output process polled the compute processes, received data from each process as it became available, and wrote it to tape or disk.

To keep the system busy full time while we were running the reconstruction algorithm, we used two pairs of tape drives. One pair had the input and output tapes for the active job, and the second pair of drives contained the tapes for the next job. The physicist on shift who determined which data to process and monitored the progress of the event reconstruction needed to attend to the system only two or three times daily. This avoided the costs associated with 24-hour operator coverage, and kept the system utilization above 95%, comparable to batch mainframe utilization. System failures were infrequent and caused no appreciable loss of time.

After the event reconstruction was completed we used the same system to reduce the data sample from 400 million reconstructed events to the few thousand events containing charm quarks. Filtering algorithms select events with charm quarks and reject events that do not contain charm quarks. First, we reduced the data set through a general filter that selected events containing a pair of particle tracks intersecting at a point downstream of the primary interaction point. This first stage reduced the number of events by a factor of 15, and required 10% of the compute time per event (compared to the reconstruction) to decide whether to pass the event to the output data stream. Second, we further reduced this sample with filters specific to each of the charm particle decay modes, such as D^+ or D^0 . We were able to use the same system by making a few minor changes to our operation strategy.

The most significant difference in the filtering jobs is that the number of compute cycles required for each event is lower. We characterize different tasks by the average number of CPU instructions performed, per byte of data input and output. For the reconstruction jobs, we averaged 3,500 instructions per byte. The filtering task, however requires only 1,975 instructions per byte. We found that for the filtering task we could only keep eight, rather than sixteen, processors busy. Two independent data streams, each feeding data to eight processors, kept the entire system utilized. A second, and related, difference was with tape mounts. Since each 8mm cartridge was filtered in three hours (instead of the ten hours required for event reconstruction), we used additional tape drives to hold the tapes waiting for execution. With all the tape drives loaded, the system ran the filtering algorithm unattended for over 12 hours. The final difference is the output data stream. The amount of data is reduced by a factor of 15 in this process, so we wrote the output to separate disk files. Once a day, these files were copied to an output tape to free up disk space.

After the first stage of filtering the reduced data set fit on 23 8mm cartridges. The next stage of data filtering used criteria specific to the different charm particles and decay modes that we are studying. We ran different filtering algorithms on the reduced data set to extract the final event samples. For these final filtering stages we have been using an automatic tape loader [11] which has two Exabyte 8mm tape drives and slots for 54 8mm

cartridges in a carousel. These stages of the data filtering algorithms also ran in the CPS environment. The automatic tape mounts allowed us to scan and filter the complete data set without intervention. Different teams of physicists have developed, tested, and run new filtering algorithms on the complete filtered data set in a matter of days.

IV. CONCLUSIONS AND FUTURE POSSIBILITIES

We have successfully operated a system of UNIX workstations with 2.3 GB Exabyte 8mm tape drives and an ETHERNETTM network. One year after the arrival of the 16 RISC CPUs in July 1989, the reconstruction of the 400 million E769 events was completed, and the physics analysis of thousands of particles with charm quarks was well under way. This is the first time UNIX/RISC computers have been used for such a large data set in High Energy Physics. The transition to this environment has been straight forward because of the many software tools that are available. The affordable compute power in workstations can be exploited because our processing can be broken down into tasks which process independent events. This system adapts well to our two different activities: event reconstruction and data filtering. Thus the same system served both as a CPU engine for event reconstruction and as an I/O engine for event filtering.

As shown in Table 5, we have run our 58,000 line FORTRAN benchmark program on a number of new machines. The E769 benchmark has a mix of integer and floating point arithmetic and a very large number of conditional branches. With the exception of Hewlett-Packard/Apollo, all the workstation vendors sell 8mm Exabyte tape drives. Even for a given processor and clock speed, performance can differ. For example, the MIPS R2000 and R3000 chips have a write back cache design. This can cause two writes in a row to stall the CPU until the second word written to cache memory reaches the slower main memory. A deep write buffer can avoid this. Cache memory is fast enough (e.g. 19 nanoseconds for a 25 MHz R3000) to keep up with a CPU. A large cache decreases the number of slow accesses to main memory for data and instructions. However, fast cache memory is expensive. A fast interface to main memory can reduce the need for a large cache. Dynamic Random Access Memory (DRAM) can supply a bit in 70 nanoseconds. A second immediate access to the same DRAM will take 140 nanoseconds unless the bit is at

a nearby address and has already been put into on-chip latches. DRAM requires the extra time to prepare for the second operation. A fast memory interface exploits cases when a second bit is nearby. A design with two interleaved memory banks also helps. Even and odd addresses are stored in alternate banks under the assumption that instructions and data will typically be accessed in order. While the first bank is getting ready, the second bank can be read. CPUs can be made to *guess* which fork of a conditional branch will be taken and execute instructions on that fork before knowing which fork is really wanted. The more simultaneous operations a CPU can perform efficiently, the faster it will be. Memory fetches, integer arithmetic, and floating point arithmetic can all execute simultaneously. Good high level language compilers can help and do continue to improve. For example, using version 3.0 rather than 2.1 of the DEC FORTRAN compiler [12] gives a 12% improvement in our benchmark on a DECstation 5000-200.

All the architectures in Table 5 are continuing to progress. Integrated Device Technology has put a 40MHz MIPS R3000 on the same chip (R3052E) as an 8kb instruction cache, 2kb data cache, and 4 level deep write buffer. Floating point is simulated. MIPS is coming out with a 50 MHz R4000 chip with 64-bit wide data paths, a pair of 8kb on-chip caches and on-chip floating point. HP/Apollo is pushing particularly hard on increased clock speeds. LSI Logic, Texas Instruments, and Cypress/Ross are working on the Lightning, Viking, and Pinnacle implementations of the SUN Sparc architecture, respectively.

We expect that improvements in the cost/performance ratio of available systems will rapidly continue. Future experiments will search for processes that are even rarer than the production of charm quarks. Although this existing system is now being used for more general computing needs at Fermilab, later experiments can reasonably expect to obtain significantly more reconstruction and filtering power to study rare processes and phenomena. It is quite prudent to buy a system *just in time* and then to bring it on-line quickly. We do not rely on any vendor-specific features for the success of the system we are operating. This strategy gives us the agility to quickly adapt to the best available hardware for future compute tasks.

We thank D. Green, L. Lederman, C. Kastner, S. Bracker, C. Johnstone, M. Isely, J. Pfister, R. Sidwell, L. Lueking, M. Streetman, G. Luste and P. Karchin for their contributions to this effort. The majority of this work was performed at the Fermi National Accelerator Laboratory, which is operated by Universities Research Association, Inc., under contract DE-AC02-76CHO3000 with the U.S. Department of Energy. This work was also supported by the U. S. Department of Energy (DE-FG05-91ER40622) and the National Research Council of Canada.

REFERENCES

- TM ETHERNET is a trademark of the Xerox Corporation. NFS is a trademark of SUN Microsystems.
- [1] D. Errede et al., Hadroproduction of Charm at Fermilab E769, 25th International Conf. on High Energy Physics, Singapore, 2-8 Aug. 1990.
 - [2] E769 Collaborators. CBPF-Rio de Janeiro, Fermilab, Mississippi, Northeastern, Toronto, Tufts, Wisconsin and Yale.
 - [3] B. H. Denby et al. (E516), Inelastic and Elastic Photoproduction of $J/\psi(3097)$, Phys. Rev. Lett. 52 (1984) 795;
 J. R. Raab et al. (E691), Measurement of the D^+ , D^0 , and D_s^+ Lifetimes, Phys. Rev. D37 (1988) 2391;
 J. C. Anjos et al. (E691), Measurement of D_s^+ Decays and Cabibbo-Suppressed D^+ Decays, Phys. Rev. Lett. 60 (1988) 897;
 J. C. Anjos et al. (E691), A Study of $D^0-\overline{D}^0$ Mixing from Fermilab E-691, Phys. Rev. Lett. 60 (1988) 1239;
 J. C. Anjos et al. (E691), Measurement of the Λ_c^+ Lifetime, Phys. Rev. Lett. 60 (1988) 1379;
 J. C. Anjos et al. (E691), Measurement of the Form-Factors in the Decay, $D^+ \rightarrow \overline{K}^{*0} e^+ \nu_e$, Phys. Rev. Lett. 65 (1990) 2630.
 - [4] C. Gay and S. Bracker, IEEE Trans. Nucl. Sci. 34 (1987) 870;
 R. Vignani et al., IEEE Trans. Nucl. Sci. 34 (1987) 756;
 S. Hansen et al., IEEE Trans. Nucl. Sci. 34 (1987) 1003;
 Mark Bennett et al., IEEE Trans. Nucl. Sci. 34 (1987) 1047;
 R. Hance et al., IEEE Trans. Nucl. Sci. 34 (1987) 878.

- [5] I. Gaines et al., The ACP Multiprocessor System at Fermilab, Proc. of the International Conf. on Computing in High Energy Physics, Asilomar, USA (2-6 Feb. 1987) 323; FERMILAB-Conf-87/21.
J. Biel et al., Software for the ACP Multiprocessor System, Proc. of the International Conf. on Computing in High Energy Physics, Asilomar, USA (2-6 Feb. 1987) 331; FERMILAB-Conf-87/22.
- [6] Silicon Graphics (SGI), 2011 N Shoreline, Mountain View, CA 94039
Digital Equipment (DEC), 146 Main St., Maynard, MA 01754
Sony Microsystems, 645 River Oaks Parkway, San Jose, CA 95134
MIPS Computer Systems, 950 DeGuigne Dr., Sunnyvale, CA 94086
Hewlett-Packard/Apollo, 3000 Hanover St., Palo Alto, CA 94304
IBM, Research Park, Suite 106, Starkville, MS 39759
SUN Microsystems, 2550 Garcia Ave., Mountain View, CA 94043
Cray Research, 655 Lone Oak Dr., Eagan, MN 55121
- [7] Gerry Kane, MIPS RISC Architecture, Prentice Hall (1989) 7-12.
- [8] Exabyte Corp., 1745 38th Street, Boulder, CO 80301.
- [9] Joe Biel, Mike Isely, Mark Fishler, Chip Kaliher and Matt Fausey, ACP Cooperative Processes User's Manual, Fermilab GA0006, 19 Nov. 1990.
- [10] TGV Inc., 603 Mission St., Santa Cruz, CA 95060
- [11] IGM Data Autoloader Division, 4041 Home Rd., Bellingham, WA 98226
- [12] DEC Fortran for ULTRIX RISC Systems, No. AA-PE1CA-TE, Digital Equipment Corp. (Mar. 1991) Chapter 6, Pages 5-21.
- [13] System Performance Evaluation Cooperative (SPEC) c/o Waterside Associates, 39510 Paseo Padre Parkway, Suite 350, Fremont, CA 94538.

TABLES

Processor:	Central Processor	R3000
	FP Processor	R3010
	FP Data Format	IEEE 754, 32- and 64-bit formats
	Registers	32 CPU, 32 FP (single precision)
	Word Length	32 bits
	Clock Speed	25 MHz
Cache Memory:	Cache Type	Write-back
	Cache Size	64 KB instruction
		64 KB Data (1st level)
		256 KB Data (2nd level)
	Write Buffer	4 words deep
	Read Buffer	16 words deep
	Processor Bus BW	64 MB/sec sustained
CPU Memory:	Size	8MB (16 MB on one server)
	Maximum allowed	128 MB
	Bandwidth	64 MB/sec sustained
Virtual Memory:		2 GB per process
MPLink Bus:	Width	32 bit address; 64 bit data
	Bandwidth	64 MB/sec sustained

Table 1. Characteristics of Silicon Graphics 4D/240S processors. Each SGI 4D/240S contains four R3000 central processing units and four R3010 floating point units with local caches and shared main memory.

	CPU Maker	CPU/FPU	Clock MHz	Instruction Cache	Data Cache	E769 sec/event
ACP-I	Motorola	68020/68881	16	256 bytes	0	18.01
ACP-I	Motorola	68020/68882	16	256 bytes	0	15.32
SGI 4D/240S	MIPS	R3000/R3010	25	64kb	320kb	0.76

Table 2. A comparison of SGI 4D/240S and Fermilab ACP I computers. The time shown is that required to run the E769 particle reconstruction benchmark on one CPU. The Motorola 68882 is a faster version of the Motorola 68881 floating point chip. Concurrent execution of some floating point instructions are allowed in the 68882 and not allowed in the 68881.

Tape Type	Length	Capacity	\$/tape	\$/Terabyte	Tapes/ Terabyte
8mm Video	106m	2.3 GB	\$4.25	\$ 1848	435
4mm DAT	60m	1.2 GB	\$7.79	\$ 6492	833
IBM 3480	165m	0.22 GB	\$4.60	\$20909	4545
9-track	732m	0.16 GB	\$9.31	\$58188	6250

Table 3. A Comparison of Storage Media. The 8mm, 9-track, and 3480 tape prices are from the Fermilab stockroom catalog. The 4mm DAT price is from the New York Times, 20 Jan. 1991, page 31.

Optimization Level:	Time:
-O0 (no optimization)	1.45 seconds/E769 event
-O1 (default optimization)	1.09 seconds/E769 event
-O2 (global optimization)	0.76 seconds/E769 event

Table 4. MIPS R3000 at different optimization levels. The time shown is that required to run the E769 particle reconstruction benchmark on a single CPU of an SGI 4D/240 computer.

COMPUTER [6]	CPU Type	CPU Clock MHz	Cache Memory I+D kByte	Write Back Buffer Depth	Main Memory Speed. MB/sec	SPEC-marks [13]	E769 sec/event	E769 Normalized to 25MHz
SGI 4D/35S	R3000	36	64+64	11	97	31.	0.53	0.76
SGI INDIGO	R3000	33	32+32	11	91	26.	0.60	0.79
SGI 4D/30	R3000	30	64+64	11	97	27.		
SGI 4D/25S	R3000	20	64+32	1	7	14.	1.07	0.86
SGI 4D/20	R3000	12	16+ 8	1	7	8.	1.94	0.93
DEC 3100	R2000	16	64+64	4	13	11.7	1.10	0.73
DEC 5000-200	R3000	25	64+64	6	100	19.9	0.66	0.66
DEC 5000-120	R3000	20	64+64	1	50	13.9	0.91	0.73
Sony 3710	R3000	20	64+64	1		12.6	1.00	0.80
MIPS Magnum	R3000	33	32+32	8	133	25.1		
HP/Apollo 720	PA-RISC	50	128+256	N/A	400	59.5	0.39	0.78
HP/Apollo 730	PA-RISC	66	128+256	N/A	528	76.8		
IBM 6000-320	IBM	20	8+32	N/A	160	32.8	0.82	0.66
IBM 6000-320H	IBM	25	8+32	N/A	200	41.2		
SUN 2	Sparc	40	64	N/A	49	24.7	0.72	1.15
SUN ELC	Sparc	33	64	N/A	41	20.1		
Cray Y-MP	Cray	166	0	N/A	4200	142.9	0.32	2.13

Table 5. Comparison of Current Workstations. The Cray figures are for a single CPU. Only the MIPS R2000 and R3000 use a write back cache architecture. The fifth column does not apply to the other CPU types. The last column shows how long it would take to reconstruct an E769 benchmark event if the computer clock speed were *scaled* to 25 MHz.

FIGURES

Figure 1. Charm Meson Signals. $D^+(1.869) \rightarrow K^-\pi^+\pi^+$ and $D^0(1.865) \rightarrow K^-\pi^+$.

color photograph included here

Figure 2. One Silicon Graphics 4D/240S Compute Server. The photograph shows 8mm Exabyte tape drives as there were attached for testing.

Figure 3. Network Configuration for Compute Servers and LAVC. ETHERNETTM was used to connect four SGI 4D/240S compute servers and a Local Area VAX cluster of VAXstations. The VAXstations have 8-user VAX/VMS licenses.

Figure 4. Structure of a CPS job. Fermilab's Cooperative Process Software [9] was used to distribute independent events from tape to CPUs which processed the data. CPS was then used to gather results together.

THEORY

Preparation of a UNIX Version of CALOR89

We originally obtained CALOR89 from Tom Handler of the University of Tennessee who had been working with Tony Gabriel of Oak Ridge, the author of the package of programs. The program had been running on an IBM 3090 mainframe at the University of Tennessee and was put onto an IBM 3084 mainframe at the University of Mississippi. It was run with some success on the IBM 3084, but this computer was difficult to use. This was due in part to the awkwardness of the VM/CMS operating system the IBM uses and in part to the operating policies of the university computer center which maintains the machine.

It had been our intention all along to port the package of programs to a UNIX workstation. These machines are in the process of becoming, if they have not become already, the preferred computer for use in scientific applications. In addition to being powerful and easy to use, the machines used are generally workstations. This means the cost is relatively low, and the scientific users who have such a computer available have control over and exclusive use of the machine.

The first UNIX machine on which CALOR was installed and run was a Silicon Graphics Personal Iris 4D/20 Workstation at the University of Mississippi. After some preliminary benchmarking, the code was taken to SSCL in May where work was done in conjunction with Lee Roberts to check the performance of the code on various UNIX platforms. The code was compiled and run on the Silicon Graphics 380 and Sun Sparc 2 Workstations of the Physics Detector Simulation Facility (PDSF) at SSCL. The code was also compiled and run on a DECstation and an IBM RISC machine. A variety of portability problems arose and quick, temporary solutions found. The code at times stopped running because of bugs in the programs. Some of these problems had arisen before and were thought rare, but we learned they were not as rare as had been thought.

CALOR89 has also been brought up on an Apollo DN10000 at the University of Alabama by Yuwu Yu and Jerry Busenitz. We helped them, through electronic mail exchanges, in bringing up the code on this computer, and we learned about several more problems related to the portability of the code in the process. During a visit to the University of Mississippi by Yuwu

Yu in August, we helped them understand how the analysis is done in the user written subroutines of SPECT, MORSE and the EGS4 programs and assisted them in putting some tracking code in place.

The UNIX version of a couple of CALOR programs, HETC and MORSE, were given to Ken Johns of the University of Arizona who was working at Fermilab. As they intended to use the programs on a Silicon Graphics, few portability issues arose, but they have been running the program to do some neutron studies.

The high energy physics group at the University of Mississippi now has a farm of 41 DECstation 5000/Model 200 workstations that are being configured into a farm that will give the group about 900 MIPS of CPU computing power. The equipment arrived in late June and early July and is presently being checked out and the "farm" configuration assembled. Some workstations are available for computing, however, and CALOR has been run for a few events on one of the DECstations. Version 3.0 of DEC Fortran is considered to have considerable problems, but the compiler nonetheless did an excellent job of finding some dead code and undefined variables that other compilers -- particularly, the Silicon Graphics and Sun compilers -- did not detect.

In the meantime, the UNIX version that was taken to SSCL was rewritten by us to make the code as transportable as possible with as little alteration as possible. The code now runs on Silicon Graphics, Sun, and DECstation computers without alteration and requires only minimal change for use on IBM RISC and Apollo UNIX platforms.

In addition, the bugs that were in the package have been addressed. Due to a problem in the original CALOR89 program, particles sometimes tend to get lost in the geometry. A work-around for this problem has been implemented by throwing away the particle that is lost and treating it as though it had escaped. This allows the program to continue running. As the error occurs only rarely, this is not of great concern. The program prints out considerable information about the lost particle including the particle type, the energy of the particle and its energy, the particles old and new locations, and the event number in which the error occurred. This information can help the user decide whether the loss of a particle can be expected to significantly affect the results enough to warrant throwing out

the event in the final analysis.

It would be preferable, of course, to fix the bug that is causing the problem in the first place. Diagnosing the difficulty, however, is expected to be a very involved undertaking. While this certainly should be pursued, the temporary work-arounds should assure that the programs are viable and useful until a permanent solution is found.

Considerable and detailed documentation has been written and is continuing to be developed on the new UNIX versions to help users and to outline the changes from the IBM version that have been put in place.

The current UNIX version of CALOR89 has been labeled Unix Version 3 or CALOR89/U3. On November 10, 1991 this version of CALOR89 was made available to SSCL for installation on PDSF and for general distribution to users in the high energy physics community who wish to run the code on their own machines.

In summary, CALOR89 is now running at the University of Mississippi on a Silicon Graphics Personal Iris 4D/20 workstation and on DEC 5000/200 workstations as well as the IBM 3084 campus mainframe. We have been running the UNIX version of the code on the PDSF facility at the SSCL where it runs on both the Silicon Graphics batch ranch machines and on the Sun Sparc 2 front-end workstations.

In addition, UNIX versions of CALOR89 created at the University of Mississippi are currently being used by groups at the University of Alabama on an Apollo DN10000 and at Fermilab by University of Arizona researchers.

Some features of CALOR/U3

A number of new features and enhancements have been incorporated into the UNIX version of CALOR which should make the code easier to use and more robust. Following is a partial list of these features:

- 1 -Parameters Set in Input Files Rather than Being "Hardwired" Into the

Programs

Previously, in HETC and EGSPREP for electrons only, one had to edit user-modified subroutines to input information such as type of particle to begin transporting, the energy, position and direction of the initial particle, and the dimensions of the calorimeter. This information is now included in the standard input files. Thus, one should only need to compile HETC and EGSPREP once the code is installed on the computer. It is no longer necessary to recompile these programs each time one wishes to change parameters for a new run. Other programs which need never be compiled more than once for use on a machine are LIGHT, PEGS, and the SLABGEOM geometry routine which creates the geometry file.

This SLABGEOM routine is very useful. Without it, one would need to write out the geometry input file oneself. This program was written by Tom Handler in PASCAL. He ran it on a PC and transferred the resulting geometry file to the computer on which he was running CALOR. The program was converted from PASCAL to FORTRAN at the University of Mississippi so it could be run on the same UNIX machines that were being used to run CALOR.

2 -Makefiles

One feature of UNIX is the ability to use makefiles to link routines into an executable. Each program has its own directory. Within this directory, the main program and each subroutine, function, and block data subroutine is in its own file. If one wishes to change subroutine BANKR in MORSE, for example, one edits the file, bankr.f. After making all changes, one then types 'make'. The computer automatically recompiles only those routines which have been re-written since the last compile. The resulting object files are then linked with the object files of the routines which had not been changed to form a new executable. This reduces compile time considerably for those programs which do have to be altered and recompiled by the user.

3 -Option to Reduce the Size of the History File

The history file of HETC contains all the information about collisions,

escaping particles and boundary crossings that occurred during the particle transport in HETC. This history file can be several hundred megabytes, or even a few gigabytes in size. For a slab calorimeter that has many slabs, most of the history file will consist of records of boundary crossings. A great deal of space can be saved by not writing out all of the boundary crossings. Some of the boundary crossings must be written out since dE/dx losses contribute to the energy detected by the active media. However, one can avoid writing out boundary crossings where particles have traveled through passive media if the user does not intend to analyze directly the energy deposited in the passive media. This can reduce the size of the history file by a factor of almost 2 to as much as 10 or more.

The user includes in the input the number of active media and for which media to write out the dE/dx losses. Up to seven may be chosen. If the number of active media is chosen to be zero, then all boundary crossings will be written out as before. Invoking this option allow the simulation of many events at a time in situations where the simulation would have otherwise been broken up into several runs of a few events each -- saving both disk space and much time.

4 -Standard Random Number Generator

The CALOR89/U3 package now uses a standard random number generator from CERNLIB. Thus, the code should be able to be run on a variety of machines and give similar results on these different machines if the same set of random number seeds is used. This is possible even for those machines that don't have native random number generators provided the machines have CERNLIB installed. If desired, it is a very simple matter for a user to change the random number generator to be used.

5 -Additional Diagnostics for Errors

It is easy to make many simple mistakes when running the CALOR package of programs. An effort has been made to incorporate diagnostics to warn the user of a number of common errors that may be made when running the program. These diagnostics say explicitly what went wrong and what needs to be done to correct the situation.

6 -Greater Ease in Increasing the Size of Arrays and Common Blocks

A number of parameter statements have been incorporated to allow the user to quickly change the size of arrays in various programs and to change the size of the MCOMM common block in MORSE. This common block is used to store a great deal of information, including geometry and cross section information. Should the common block not have enough space to store all this information, a diagnostic is printed out telling the user how much larger the common block should be. The user simply edits an include file, mcomm.h, which contains a parameter statement defining the size of common block MCOMM. After editing, the user types 'make', and the program automatically recompiles only those programs which use the MCOMM common block and links them with the rest of the program.

7 -Report Files

On UNIX computers which have the intrinsic subroutine, FLUSH, available, the report files are a very nice feature. Calling FLUSH with an output file unit number as argument causes the contents of the buffer for that file to be written out immediately. The MORSE, SPECT, and EGS4 routines each print out a line to a report file as soon as they finish with each event. The report file includes the event number, the number of energy depositions recorded for that event, and the total energy deposited for the event. While the program runs in the background, therefore, the user can at any time check the number of events that have been processed by the routine. The number of energy depositions per event helps to give some measure of how long the program be expected to take to run. Finally, the average energy per event can be checked to see if it is feasible and consistent with what is expected. Thus, a user may quickly and easily monitor the progress of a CALOR program.

A Systematic Test of Compensation in a Hadron Calorimeter

The "Hanging File" Calorimeter Beam Test FNAL T841

Ames Laboratory - Iowa State University
Argonne National Laboratory
Fermi National Accelerator Laboratory
Lawrence Berkeley Laboratory
Lawrence Livermore Laboratory
University of Mississippi
Northeastern University
Oak Ridge National Laboratory
Purdue University
University of Rochester
Rockefeller University
CEN Saclay
University of South Carolina
University of Tennessee
Virginia Tech
Westinghouse Corp.
University of Wisconsin
Yale University

Pion/Electron Energy Scan: 10, 20, 100 and 200 GeV/c

Duration: 10 minutes per energy (40 minutes per configuration)

Gate Times: 16, 32, 48 and 64 nsec.

Duration Between Scans: 23 hours

- a) Changeover to new configuration: 4 - 8 hours
- b) Source calibration: 1 - 2 hours
- c) Parasitic muon running: remaining time

UNIX Version of CALOR89 - General Geometry

HEPLIB91 Conference

SSCL

September 20, 1991

Presented by

Brent R. Moore

SSC R&D

Memorandum of Understanding

between

Liquid Scintillator Calorimetry Collaboration

and

**The Superconducting Super Collider
Laboratory**

FY 1991

MEMORANDUM OF UNDERSTANDING FOR FY 1991

between

THE LIQUID SCINTILLATOR CALORIMETRY COLLABORATION

and

THE SUPERCONDUCTING SUPER COLLIDER LABORATORY

This memorandum of understanding between the Liquid Scintillator Calorimetry Collaboration and the Superconducting Super Collider Laboratory (SSCL) is intended solely for the purpose of providing a budget estimate and a work breakdown for the SSC Laboratory, the funding agencies, and the participating institutions. It is an agreement that is currently satisfactory to the parties. However, it is recognized and anticipated that changing circumstances of this evolving research and development program may necessitate revisions. The parties agree to negotiate amendments to this memorandum that will state such required adjustments. A short summary describing the research objectives of this experiment is given in Appendix I.

A. Personnel

The list of participating institutions, the names of the people in each (identifying the contact person and overall manager), and the percent of their time which will be dedicated to the project are listed below:

LAWRENCE LIVERMORE NATIONAL LABORATORY

R. Bionta	0.10 FTE
M. Lowry	0.20 FTE
C. Wuest*	0.50 FTE

UNIVERSITY OF MISSISSIPPI

L. Cremaldi	0.15 FTE
B. Moore	0.10 FTE
B. Quinn	0.50 FTE
J. Reidy**†	0.20 FTE

OAK RIDGE NATIONAL LABORATORY

M. Bauer	0.20 FTE
H. Cohen	0.25 FTE
T. Gabriel	0.10 FTE
F. Plasil*	0.10 FTE
K. Read	0.20 FTE

UNIVERSITY OF TENNESSEE

A. Dezkra	0.50 FTE
T. Handler	0.25 FTE
Y. Kamyshkov*	1.00 FTE
K. Read	0.20 FTE
A. Savin	0.50 FTE
A. Smirnoff	0.50 FTE
E. Tarkovski	0.50 FTE

* Contact person

† Overall manager

SSC Liaison Person	Dr. Willi Chinowsky Physics Research Division M/S 2001 SSC Laboratory 2550 Beckleymeade Avenue Dallas, Texas 75237
--------------------	---

B. Responsibilities for Research Tasks

In this section we give a brief overview of our R&D program for FY91. Any modifications from our original Liquid Scintillator Calorimetry subsystem proposal were made to adjust to different constraints and to accommodate suggestions given us from the SSC Laboratory. The long-term goals of our detector development project are summarized in Appendix I.

Task 1: Tests of compatibility of various liquid scintillators with a variety of wavelengths shifting fibers (WLSF) and light reflecting agents at elevated temperatures to simulate long-term exposures. Light yield and transmission measurements and visual observation will be used to characterize the compatibility. Small test cells will be constructed for this work. (LLNL, ORNL, UT)

Task 2: Radiation damage studies on liquid scintillator and wavelength shifting fibers including reflecting agents. This includes characterizing the scintillator and wavelength shifters attenuation response as a function of wavelength with radiation exposures to several megarads of Co-60 radiation and neutrons to the range of about 10^{13} neutrons/cm². Test cells incorporating the most robust components will be irradiated. These will be tested as a unit using a photometry system assembled for this purpose. (LLNL, UM, ORNL, UT)

Task 3: Initial studies of calorimeter cell design including readout schemes, optical couplings, Monte Carlo simulations of light collection geometries and of the transport properties of the optical light-collecting system. (LLNL, UM, ORNL, UT)

Task 4: Initial studies on possible calorimeter cell calibration schemes. (UM, UT)

C. Test Beam Requirements

No test beams are required for FY91. For FY92 we shall require the use of an electron/pion beam to test the rudimentary calorimeter. The momentum range should be 10-200 GeV/c with an intensity of 1K/sec or greater. Momentum resolution of 1% is adequate with spatial extent of 1cm or less.

D. Special Considerations

- The contact person for the Liquid Scintillator Calorimetry collaboration, James J. Reidy, agrees to be responsible for equipment borrowed by our collaboration and will ensure its timely return.
- We understand that funding for this project will be provided in allocations of a single year, with successive year's funding dependent on successful progress to date and available funds as determined by an appropriate review process.

E. Milestones

Milestones for Liquid Scintillator Calorimetry research during FY91 are presented in this section. This R&D, if successful, will lead to a determination of a set of liquid scintillator, wavelength shifting fibers and reflective materials or surfaces that are physically compatible in a radiation environment. In addition, one should be able to decide whether sufficient light output can be obtained using a reasonable geometry so there is a high probability that viable cells for a liquid scintillator-based SSC hadron calorimeter can be reliably developed.

Task 1

- 1/91: Obtain samples of commercially available liquid scintillator, WLSF, and reflecting material; search out other sources as well (LLNL, ORNL);
- 1/91 - 5/91: Physical compatibility tests (LLNL, ORNL, UT);
- 5/91: Complete physical compatibility tests; choose best candidate(s) for radiation damage studies (LLNL, UM, ORNL, UT).

Task 2

- 1/91: Begin assembly of photometer test stand (LLNL);
- 3/91: Finish assembly and calibration of photometer test stand (LLNL);
- 1/91 - 6/91: Design and fabricate test cells for radiation damage studies; perform efficiency and uniformity measurements on non-irradiated cells (LLNL, ORNL);
- 6/91 - 8/91: Perform radiation damage studies on initial material using Co-60 sources (LLNL, UM, ORNL, UT);
- 6/91 - 10/91: Measure efficiency and uniformity of test cells following irradiation (LLNL, UM, UT);
- 7/91 - 11/91: Perform radiation damage studies with neutrons on most gamma resistant material (LLNL, ORNL, UT);
- 8/91 - 12/91: Measure efficiency and uniformity of test cells following neutron irradiation (LLNL, ORNL, UT).

Task 3

- 2/91: Initiate calculational effort devoted to light collection geometries and light transport calculations (UM, ORNL, UT);
- 6/91 - 8/91: Compare calculations with measured values of light collection efficiency and uniformity for non-irradiated test cells; tune MC to account for differences (UM, ORNL, UT);
- 8/91 - 12/91: Perform similar comparisons and tuning for irradiated cells (UM, ORNL, UT).

Task 4

- 5/91: Begin studies on calibration schemes (UM, UT);
- 8/91: Incorporate calibration method into test cells and/or test procedure; compare results with MC calculations (UM, UT).

F. Reporting

The collaboration will provide the SSC Laboratory with copies of all talks and publications resulting from this R&D project. A short interim progress report will be provided to SSCL by April 1991 and a detailed written report will be provided SSCL by September 1, 1991. Proposals for continued support with a budget for FY1992 are to be presented to the SSCL together with the report.

G. Funding

- In this section we specify the allocation of funds by institution and by research task as defined in Section B.

Table I
Sources of Research Funds (\$K)

	SSCL	Other
Capital equipment	56	20
Operating funds	394 ^a	330
Total	450	350

a) includes \$0.5K sub-contracted to LBL.

Table II
Distribution of Funds by Institution (\$K)

	Capital Equipment (SSCL)	Operating Funds (SSCL)
LLNL	51.0	24.0
UM	-0-	45.0
ORNL	-0-	222.0
UT	5.0	103.0
Total	56.0	394.0

Table III
Expenditures by Research Task (\$K)

	Capital Equipment	Operating Funds
TASK I	21.0	89.0
Compatibility Tests		
Task II	30.0	160.0
Radiation Damage Studies		
Task III	-0-	90.0
Test cell design including Monte Carlo simulations and readout schemes		
Task IV	5.0	55.0
Cell calibration design and fabrication		
Total	56.0	394.0

The SSC Laboratory has identified and selected the Liquid Scintillator Calorimetry project for funding. It is expected that the DOE/OSSC will provide the Liquid Scintillator Calorimetry Collaboration with \$394K of operating funds and \$56K in equipment funds in FY 1991 for the above described detector R&D project.

H. Signatures

The undersigned have agreed to fulfill to the best of their abilities the terms of this Memorandum of Understanding between the Liquid Scintillator Calorimetry Collaboration and the Superconducting Super Collider Laboratory.

AGREED

~~The~~ Liquid Scintillator Calorimetry
Collaboration

Date

James J. Reidy

Chair and Professor of Physics
University of Mississippi

July 5, 1991

R. Schwitters, Director
Superconducting Super Collider Laboratory

IN CONCURRENCE

Date

R. Diebold, DOE OSSC

J. O'Fallon, DOE OHEP

Appendix I Physics Goals and Motivation

I. PHYSICS MOTIVATION

Precise calorimetric measurements are expected to be of great importance in experiments at the Superconducting Super Collider. In most experiments a calorimeter is a precision instrument used for searching for new physics through, firstly, lepton and photon channels and, secondly, quark channels. Consequently, a calorimeter is a multifunctional device. It provides identification of jets, electrons and muons, and working as a "tracking device" it helps to solve pattern recognition problems. It can be a means to separate electrons from hadrons by measuring shower shape and to separate muons from other particles by total absorption of the hadronic component. It measures accurately the jet energy and angles as well as electron energy and angles: it detects muon bremsstrahlung and provides corresponding correction to the muon energy measurement performed in the muon detector. Muon energy loss measurement in hadron calorimeters will essentially contribute to precision measurement of muons and consequently to reconstruction of Z^0 and new physics objects in SSC experiments. The performance criteria for a calorimeter should include excellent hermiticity, good lateral and longitudinal segmentation, e/h as close to one as possible (which implies good linearity), ability to contain most of the shower and capability for precise calibration. The Superconducting Super Collider is a high luminosity machine with very short bunch crossing times. Hence, it is imperative that the detectors be able to withstand high radiation doses and have short response times in order to handle the high data rates. Short response time also enables a suitable designed calorimeter to contribute to the first level trigger - an important consideration given the particle production rate of the SSC. As an example it was shown in the L * EOI that in order to perform a wide search for new physics phenomena the precision of the calorimetric energy measurement should be very high: $\sigma_e/E = 1.3\%/ \sqrt{E} + 0.5\%$ for electrons and photons, and $\sigma_h/E = 50\%/ \sqrt{E} + 4\%$ for jets.

A number of calorimeter designs (including one incorporating liquid scintillator) have been suggested for inclusion in SSC detectors. For sampling calorimeters, liquid scintillator-based systems offer an attractive solution. Physical properties of a typical scintillator are; a) light yield $\approx 60\%$ of anthracene, b) light attenuation length up to 4-5 m, c) decay time ≈ 2 ns and d) maximum emission wavelength ≈ 420 nm. Note that liquid scintillators (LS) have a short response time of a few nsec like plastics, but are far more flexible in operation. Inherently LS are more resistant to radiation damage than plastics and they can be replaced conveniently. As an example the proposed L * hadron calorimeter was similar to a conventional Pb/scintillator plate sampling calorimeter except the scintillator plates are replaced by cells containing liquid scintillator with a wavelength shifter fiber providing the light output. The high hydrogen content in LS allows one to achieve compensation via the mechanism of detection of the neutron component of the hadronic shower.

A liquid scintillator cell consists basically of a container for the LS and a means for obtaining the information from the scintillation light. In some cases a photodetector is placed directly in contact with the LS or interfaces through a transparent surface. Alternatively the wavelength shifting (WLS) mechanism can be employed for light readout. The plastic or glass fiber containing the WLS dopants can be immersed in LS. Usually the absorption spectrum of the WLS matches the emission spectrum of the scintillator and a corresponding absorption length is a fraction of a millimeter. In a cell with highly reflective walls WLS fiber will play a role of light drain. It will absorb significant amount of scintillation light and reemit it isotropically with a shifted wavelength to which WLS fiber body is transparent. Due to the difference of refractive indices of fiber and LS (or fiber core and fiber cladding) the reemitted light will be channeled via total internal reflection and transported along the length of the fiber to the end where the photodetector will be attached.

For an SSC-type sampling calorimeter calculations show that the LS should be a few millimeters in thickness. In addition, one must cover large areas. Uniformity of response is an important characteristic of any scintillator used in a calorimeter. This suggests that small cells of LS would be preferred. This has the added advantage of providing fine granularity for the calorimeter. Before one can confidently expect that LS technology could be the basis for an SSC-type calorimeter a number of basic questions need to be addressed. What is the extent of the physical compatibility of the LS, WLSF and cell material including reflecting agents or surfaces? What is the effect of radiation on these components? The uniformity of response of a cell must be studied using Monte Carlo calculations for light transport and collection efficiencies - and these must be checked with test beam data. Fast readout schemes and calibration procedures need developing. Preliminary work on some of these problems have been done at ITEP. We propose to build on this work and provide definitive results pointing to the feasibility of using LS technology in a calorimeter for an SSC detector.

2. PROJECT GOALS FOR THE LIQUID SCINTILLATOR CALORIMETRY PROGRAM

The R&D program proposed by the Liquid Scintillator Calorimetry Collaboration as modified by discussions with SSC Laboratory personnel will lead, if successful, to the complete design and testing of a calorimeter tower using liquid scintillator plates as the active media.

- The immediate goal in FY91 is to identify liquid scintillator (LS), wavelength shifting fibers (WLSF) and reflecting materials or surfaces that are physically compatible and can function together as a scintillation cell in a radiation environment comparable to that expected at the SSC for calorimeters. Test cells will be constructed with reasonable geometry for the LS, WLSF, and reflecting surfaces; studies on uniformity and efficiency as a function of time and radiation exposure will be carried out. The design will be driven by the characteristics of the physically compatible components with guidance from the Monte Carlo simulation of light collection efficiency and light transport.
- An intermediate goal for FY92 is to produce a prototype plane of cells (approximately 10 x 10), design a tower prototype and perform beam tests with a rudimentary Pb/scin calorimeter using the prototype plane.
- A long-term goal is to fabricate a prototype Pb/scin tower of about 12λ and perform beam tests to determine its performance. This includes signal processing and calorimeter simulation.

Liquid Scintillator Calorimetry

(Second Year)

A Research and Development Renewal Proposal

submitted to

The Superconducting Super Collider Laboratory

by

Lawrence Livermore National Laboratory, Livermore, California, USA

University of Mississippi, University, Mississippi, USA

Mississippi State University, Mississippi State, Mississippi, USA

Oak Ridge National Laboratory, Oak Ridge, Tennessee, USA

University of Tennessee, Knoxville, Tennessee, USA

Tata Institute of Fundamental Research, Bombay, India

Institute for Theoretical and Experimental Physics, ITEP, Moscow, USSR

Institute for High Energy Physics, Serpukhov, USSR

September 1991

A Research and Development Proposal

submitted by

E. ABLES, P. ARMATIS, R. BIONTA, H. BRITT, O. CLAMP, C. COCHRAN,
G. GRAHAM, M. LOWRY, D. MASQUELIER, K. SKULINA, C. WUEST
Lawrence Livermore National Laboratory, Livermore, California, USA

L. BOLEN, L. CREMALDI, S. HARPER, B. MOORE, B. QUINN,
J. REIDY (CO-SPOKESMAN AND CONTACT PERSON), J. ZHOU
University of Mississippi, University, Mississippi, USA

L. CROFT, R. PIERCEY,
Mississippi State University, Mississippi State, Mississippi, USA

M. L. BAUER, B. L. BISHOP, H. O. COHN, T. A. GABRIEL, A. GORDEEV,
YU. KAMYSHKOV (CO-SPOKESMAN), R. A. LILLIE, F. PLASIL,
K. READ, M. J. RENNICH, A. SAVIN, K. SHMAKOV, B. H. SINGELTARY,
A. SMIRNOV, E. TARKOVSKY, R. A. TODD, K. G. YOUNG,
Oak Ridge National Laboratory, Oak Ridge, Tennessee, USA

S. C. BERRIDGE, W. M. BUGG, T. HANDLER, M. PISHARODY,
University of Tennessee, Knoxville, Tennessee, USA

T. AZIZ, S. BANERJEE, S. R. CHENDVANKAR, S. N. GANGULI, P. K. MALHOTRA,
K. MAZUMDAR, R. RAGHAVAN, K. SHANKAR, K. SUDHAKAR, S. C. TONWAR
Tata Institute of Fundamental Research, Bombay, India

A. AREFIEV, O. BARANOV, S. BUROV, N. BYSTROV, YU. GALAKTIONOV,
YU. GORODKOV, A. MALININ, A. NIKITIN, V. MARKIZOV, V. PLYASKIN, V. POJIDAEV,
A. ROZJKOV, E. SHOUMILOV, V. SHOUTKO, V. TCHUDAKOV, O. ZELDOVICH
Institute for Theoretical and Experimental Physics, ITEP, Moscow, USSR

A. KOZELOV, A. LEBEDEV, S. MEDVED, E. SLOBODYUK, A. VASILIEV.
Institute for High Energy Physics, Serpukhov, USSR

CONTENTS

Chapter 1. INTRODUCTION

- 1.1. Calorimeter Design Criteria
- 1.2. Liquid Scintillator Option
- 1.3. Liquid Scintillator R&D Initiation

Chapter 2. LIQUID SCINTILLATOR R&D STATUS

- 2.1. Chemical Compatibility of Components
- 2.2. Radiation Resistance of Components
- 2.3. Light Yield. Optimization of Light Collection
- 2.4. Calibration and Monitoring of Liquid Scintillator Calorimeter
- 2.5. Mechanical Design of Calorimeter Cells and Modules
- 2.6. Light Readout in the Magnetic Field. Electronics
- 2.7. Simulation Calculations
- 2.8. Alternative Light Readout Schemes
- 2.9. Initial Studies on a Liquid Scintillator Electromagnetic Calorimeter Design
- 2.10. Additional Facilities and Support Personnel

Chapter 3. PROPOSED R&D PROGRAM FOR 1992/1993 FY

- 3.1. R&D Program
- 3.2. Plans of Participating Laboratories
- 3.3. Beam Tests with LS Prototype Detector Plane and Module

Chapter 4. MILESTONES

Chapter 5. BUDGET

Chapter 6. ORGANIZATION

Addendum 1

Chapter 1. INTRODUCTION

1.1. Calorimeter Design Criteria

Precision electromagnetic and hadronic calorimeters are among the major tools for studying the new physics in experiments at the Superconducting Super Collider. High precision (usually correlated with energy resolution) is an important property of SSC calorimeters because it usually results in a better signal/background ratio and, consequently, a higher discovery potential. The major calorimeter task is to provide the means to measure precisely (together with other detector subsystems), firstly, gammas, electrons and muons and, secondly, hadronic jets and missing energy. Emphasis on precision measurements on gammas and leptons has been made by the L*, EMPACT and GEM collaborations[1,2,3,4]. Therefore, the optimization of calorimeter performance implies that techniques and designs are best directed toward precision measurements on gammas and leptons while the hadronic resolution properties can be compromised to some extent if necessary.

The performance criteria for a calorimeter should include excellent e-m resolution, good hermiticity and response uniformity, good lateral and longitudinal segmentation, e/h as close to one as possible (which implies good linearity), ability to contain most of the shower and capability for precise calibration [1,2,3]. Through SSC R&D projects significant progress has been made recently in the development of high precision e-m calorimeters particularly those based on BaF_2 and Liquid Xenon technology. Depending on financial constraints it appears that one of these technologies could be the choice for the e-m calorimeter. Compatibility with the e-m calorimeter would be a significant factor in the choice of the hadron calorimeter.

An important calorimeter feature which is often underestimated is longitudinal segmentation. It provides the muon/hadron separation (by shower profile), corrections to muon radiative energy losses in the calorimeter (short energy spikes on muon track), pattern reconstruction for muons which are close to jets (generally more detailed topological event information), and muon coordinate and angle measurements inside the calorimeter. Segmentation controls longitudinal hadronic and e-m shower leakages, reduces the effect of radiation damage on calorimeter performance and allows one to use the muon tracking pattern in the low level trigger. Because of the large radial extension in an SSC detector the longitudinal segmentation in the hadronic part of the calorimeter is particularly

essential.

The Superconducting Super Collider is a high luminosity machine with very short bunch crossing time. Hence, it is imperative that the detectors be able to withstand high radiation doses and have short response times in order to handle the high data rates. Short response time also enables a suitably designed calorimeter to contribute to the first level trigger - an important consideration given the particle production rate of the SSC. Short response time becomes particularly important for the SSC at a luminosity of $10^{34}/\text{cm}^2/\text{sec}$. If the calorimeter resolution time is significantly better than 16 ns then SSC machine operation with shorter bunch spacing (8 or 5 ns) can be envisaged which will considerably improve the major high luminosity problem - event overlap.

Energy resolution is a major requirement for the electro-magnetic part of the calorimeter. Though homogeneous techniques offer exceptionally good resolution for electrons and photons, $\sigma_e/E = 1.5\%/\sqrt{E} \pm 0.5\%$ [1,2], refined sampling technology can presently provide an e-m resolution as good as $\sigma_e/E = 6 - 7\%/\sqrt{E} \pm 0.5\%$ [3]. The constant term in e-m energy resolution is very important as it sets the resolution limit at high energies. It is a function of detector response uniformity, electronic stability and calibration accuracy. For hadronic response the constant term in the resolution depends also on the e/h ratio. This contribution is zero for a "compensated" calorimeter where e/h=1. A compensated uniform calorimeter (same active and passive material configurations for the e-m and hadronic sections) therefore will provide the best possible hadronic resolution. Unfortunately, if the uniform sampling technique is used both in the e-m and hadronic sections of the calorimeter, the e-m resolution for practical reasons cannot be optimized without affecting the e/h ratio (i.e. hadronic resolution). On the other hand the e-m calorimeter section with high resolution (BaF_2 is an example) will essentially affect the e/h=1 as well as the global calorimeter response. In the latter case the presence of a compensated hadronic section rather than a non-compensated one behind the e-m section was shown to improve the constant term in the hadronic jet resolution [2]. The goal for the hadronic jet resolution in an SSC detector is of the order $\sigma_h/E = 50\%/\sqrt{E} \pm 2\%$ [2,3].

1.2. Liquid Scintillator Option

The Liquid Scintillator (LS) sampling calorimeter technique had been proposed within the L* collaboration [1] and became the primary option in the L* Letter of Intent [2]. Presently, the GEM collaboration also considers this technology as one of the possible

candidates for the GEM hadron calorimeter[3]. The Liquid Scintillator R&D program was approved by the SSCL R&D Committee in December 1990 [5] and has been modestly funded in FY91 through the SSC R&D Subsystem program. This international program in addition to US support has also received support in USSR : ITEP (Moscow) and in India : TIFR (Bombay).

In this report we present the results of the first year of LS technique R&D together with the plans of future development which should culminate with the construction and beam test of the full size prototype liquid scintillator hadron calorimeter module for a GEM-type detector. We also present new ideas of construction of high resolution sampling e-m calorimeter sections which can preserve the $e/h=1$ for the global hadronic response.

The basic idea of an LS sampling hadron calorimeter has been described in detail in our previous proposal [5]. Liquid scintillator between sampled absorber is divided by wall separators into cells with typical transverse size from 6×6 to 10×10 cm². The typical thickness of the liquid scintillator is 5 mm. Each cell is covered inside with reflective paint and optically isolated one from another. Light produced by ionizing particle in the scintillator cell is read out from one end via a wavelength shifting(WLS) fiber which spirals inside the cell. The absorption spectrum of the WLS matches the emission spectrum of the scintillator with the corresponding absorption length being a fraction of a millimeter. In a cell with highly reflective walls the WLS fiber will play the role of a light drain. It will absorb a significant amount of scintillation light and reemit it isotropically with a shifted wavelength to which the WLS fiber body is transparent. Due to the difference of refractive indices of the fiber cladding and the fiber core the reemitted light will be channeled via total internal reflection and transported along the length of the fiber. At the exit from the cell the WLS fiber is coupled to a clear fiber which transports the shifted light to a photodetector. Photodetectors and front-end readout electronics are located behind the hadron calorimeter absorber in the area where radiation levels are not troublesome. This scheme provides uniform transversely segmented readout of a detector plane between two absorbers. The sampling frequency of absorbers in a hadron calorimeter can be chosen as a compromise between available radial extension (for a given absorption thickness of calorimeter) and a desirable stochastic term in the energy resolution. As an example, the hadron calorimeter proposed for L* [2] and for GEM [3] is similar to a conventional Pb/scintillator plate sampling calorimeter with Pb/scintillator ratio of 4/1. The high

hydrogen content in LS allows one to achieve compensation via the mechanism of detection of the neutron component of the hadronic shower.

Liquid scintillator with WLS fiber readout is intrinsically very fast. Scintillator decay time is typically 2 ns [6]; bouncing of light before it is absorbed by the WLS fiber in the cell introduces the time spread ~ 1 ns (r.m.s.) [7]. Decay time of the available WLS dyes is 6-12 ns [8]. Available photodetectors [9] have a response time of 2 ns. In compensated hadron calorimeters the critical addition to the hadron signal (to make $e/h=1$) is provided by neutrons with energy ~ 1 MeV. This component of hadronic shower, detected by hydrogenous materials (liquid scintillator, for example), is distributed on a time scale ~ 50 ns, though a major contribution is made within the first 10 ns. The neutron component develops in time differently than the other components of the hadronic shower and can be reduced with appropriate time cuts or pulse shaping. On the other hand, as it was shown in [10], the value of e/h ratio in sampling calorimeters depends on the relative thickness of absorber and detector, and therefore can be adjusted too. The combination of these two contributions can yield a compensated response in a fast hadron calorimeter. According to major milestones for the present R&D program this issue is going to be addressed in our future beam tests.

Liquid scintillators are usually more radiation resistant than plastic scintillators. Additional advantage of the liquid scintillator technique is the fact that the scintillator can be replaced if radiation damage occurs. Thus, the radiation resistance of the whole LS + WLS fiber system is defined essentially by the radiation resistance of WLS and clear transport fibers. These fibers can withstand radiation doses of ~ 10 Megarads without significant deterioration of their performance. The rapid progress in the development of new radhard WLS fibers and in understanding the radiation damage mechanism will probably push the application limit of fibers to 10-20 MRad or even higher.

The major advantages of Liquid Scintillator calorimetry related to the SSC environment are summarized in Table 1.

1.3. Liquid Scintillator R&D Initiation

In October, 1990 we submitted an SSC R&D proposal to the SSCL in which a program of study on liquid scintillator technology leading to a beam test of a prototype calorimeter was outlined and funds requested. After subsequent review by an SSCL research panel

and in consultation with personnel from the SSCL we agreed that a modification in our first year program was appropriate and modified our request accordingly. Our proposal, SSCL No.247: Liquid Scintillation Calorimetry, was approved in December, 1990, although no funds were made available at that time. However, ever the optimists we proceeded to initiate the program using internal funds. Due to the uncertainties in the approval for L* it was not until May 30,1991, that we were given official notice that our proposal would be funded for FY91 and an MOU was approved. Funds became available in August, 1991. As one might expect, the uncertainty of the funding combined with limited internal resources has resulted in slower progress than we had originally anticipated but much more rapid than the funding profile would indicate.

TABLE 1

Major Advantages of Liquid Scintillator
calorimetry in SSC environment

- High operation speed;
- No radiation damage problem for liquid scintillator since it can be easily exchanged;
- High radiation resistance of WLS and clear transport fibers;
- Detector flexibility permits fine segmentation both transversely and longitudinally;
- Good energy resolution ($e/h=1$) as in well understood high performance plastic scintillator calorimeters;
- Simple mechanical modular design which ensures good uniformity and hermeticity and allows beam calibration of each module prior to installation in the experiment;
- Easy performance monitoring (with radioactive source per each readout channel);
- Good signal/noise ratio (1 m.i.p. $\sim$ 30 photoelectrons per readout channel in PMT);
- Low cost technology suitable for mass production.

Chapter 2. LIQUID SCINTILLATOR R&D STATUS

Because of the tight time and financial constraints implied by development of SS-C detectors we conservatively concentrated our efforts mainly on the studies of existing and commercially available components (liquid scintillators, fibers, photodetectors etc.). The quality of these components develops so rapidly in industry (and also as a result of interactions with ongoing R&D studies) that we are going to profit from them soon in improvements of radiation hardness, speed, light yield and quantum efficiency. During the first year of our LS R&D we have identified and addressed the most critical issues of the new LS technique. Results of these studies are presented in this chapter.

The Liquid Scintillator Calorimetry MOU describes the work proposed for FY91. The effort is divided into four tasks. In the following, we address the progress within each of the tasks as well as additional work which is not specifically addressed within a task. This latter work has been carried out using funds leveraged from other sources.

2.1. Chemical Compatibility of Components

The main components of an LS system are the LS proper, WLS fibers, clear transport fibers and reflective coating of the cell. These components are the subjects of potential chemical interaction with each other. Moreover the speed of chemical reaction depends on temperature and can be sensitive to radiation.

We have identified commercially available liquid scintillator (BC-517P, Bicron) which does not attack commercially available plastic fibers (BCF-91A, Bicron). Direct compatibility tests which have lasted already more than four months with this scintillator show no traces of chemical attack to the fibers. We have performed a number of accelerated and concentration extrapolation tests which are described below in order to estimate the admissible life time of the plastic fibers in this scintillators.

Most commercially available liquid scintillators are chemically active substances or have chemically active constituents. For example, the Bicron BC-517 liquid scintillator family has mineral oil (of U.S.P. grade) as a major component or scintillator base. Pure mineral oil is known to be chemically rather inert (it is confirmed also by our tests). Scintillating fluor pigments are difficult to dissolve in pure mineral oil so chemically active pseudocumene is used in BC-517 liquid scintillators as a solvent. As it was verified by our tests pure pseudocumene (100% concentration) quickly destroy plastic fibers, but at small

concentrations in mineral oil (< 5% for BC-517P) it does not attack fibers on a long time scale.

Commercially available plastic fibers are made from polystyrene (PS) clad with a thin layer (typically 3% of fiber diameter) of extruded PMMA. These two materials (PS and PMMA) chemically interact differently with active scintillator components. Polystyrene in the fiber core is attacked by active liquid scintillator components more readily than PMMA cladding. Generally, PMMA (fiber cladding) is more chemically resistant, though it can be destroyed by large concentrations of active scintillator components. There are two types of claddings available - regular extruded PMMA and fluorinated PMMA. They have different mechanical properties, chemical and radiation resistance as well as refractive indices. Generally, fluorinated PMMA is supposed to be better in all respects. Consequently, the issue of fiber core viability will depend strongly on the mechanical quality of the fiber surface, presence of micro-cracks in the cladding layer and on cladding uniformity.

Another important component of an LS detector system is the light reflector on the cell walls. So far the best result we have obtained is with white diffusive reflection TiO_2 paint prepared from a cross-linked polyurethane resin (BC-622A, Bicron). Our tests of cured BC622A samples show no sign of chemical interactions with liquid scintillator. We have also made a compatibility tests of several types of sealing o-rings and epoxy resins in different scintillators.

We have performed a number of tests in order to study chemical compatibility and to define the life time of the major components of the LS system. Results of the observational tests are presented in Tables 2-4.

We had to define the degree of interaction between liquid scintillator and fiber which could be related to the chemical damage. Conservatively we have chosen the definition for the "time of life to chemical interaction" as when liquid scintillator has attacked the polystyrene in the fiber core at the end of the fiber and we were able to see the softening, protruding or dissolution of the fiber core for a fraction of millimeter as a result of this attack. Actually, even when the chemical damage, defined as above, has occurred, the optical properties of the fiber in the liquid scintillator cell are not changed significantly. The following test made with BC-531 liquid scintillator (chemically rather active) can serve as an example. The time of life of plastic fiber in BC-531 was found to be approximately

TABLE 2

The results of measurements of the Time of Life (TOL)
for chemical compatibility of plastic fibers and Bicorn scintillators.

Scintillator	BC517S	BC517H	BC517L	BC517P
TOL @ 22°C	1 hour	16 days	>150 d	>105 d
TOL @ 42°C	short	6 hours	90 days	>105 d

60 hours though the cell built with a fiber spiral and filled with BC-531 had the light yield due to chemical attack reduced from 10 p.e./m.i.p. to 7 p.e./m.i.p. over a period of 7 days.

Another important factor in chemical time of life measurements is the temperature. The speed of chemical reactions is known to be dependent on temperature. We have performed part of our tests at elevated temperatures in order to accelerate the speed of chemical reactions. As seen in Table 2, where results of chemical compatibility study for the Bicorn BC-517 liquid scintillator family are presented, for BC-517H liquid scintillator the acceleration factor at temperature 42°C relative to 22°C is 50-60. Since all the scintillators listed in Table 2, have the same constituents, but only in different concentration [11], we can assume that temperature acceleration factor is the same for all of them. In this way the life time of plastic fiber in BC-517L at 22°C has been estimated. It is presented in Table 3 together with some other relevant parameters of the BC-517 family of liquid scintillators. Since the exact concentration of pseudocumene in these scintillators for commercial reasons is not given by the manufacturer, we must correlate the observed chemical life time with other parameters of these scintillators. From these correlations we can extrapolate the life time of plastic fibers in BC-517P liquid scintillator to be more than 70-450 years (from different extrapolations). This estimation is also shown in Table 3.

TABLE 3
Time of Life (TOL) of Plastic Fibers
in Bicron Scintillators.

Scintillator	Pseudocumene concentration (%)	Light output (% anthracene)	Flash point (°C)	H/C ratio	Time of Life @ 22°C
BC517S	< 50	66	74	1.70	1 hour
BC517H	< 40	52	81	1.89	16 days
BC517L	< 30	39	102	2.01	15 years ¹
BC517P	< 10	28	115	2.05	70-450 years ²

¹extrapolated from measurements at elevated temperature (42°C)

²extrapolated from TOL dependence on light output, flash point and H/C ratio

The compatibility tests mentioned above were made during the spring 1991. Our recent compatibility tests with fibers and scintillators which were purchased from Bicron company from 6 to 12 months later show somewhat better chemical compatibility results which probably can be attributed to the improved quality of the basic components. The summary of recent and ongoing compatibility tests at ORNL is presented in Table 4.

We have established contact with C.R.Hurlbut from Bicron Corporation, who proposed a program for improvement of chemical compatibility of plastic fibers and liquid scintillators. This program is currently being carried out by us together with Bicron Corporation. The program includes : a)search and implementation of other (than pseudocumene) scintillating fluor pigment solvents which do not attack fibers; b)compatibility tests of fibers with thicker cladding (1 mm diameter fibers with 100 microns cladding); c)study of transparent chemically protective paint (Bicron Clear EMA paint) which can be applied on the surface of the WLS fibers after they are properly shaped and connected to the clear transport fibers

TABLE 4

Summary of recent chemical compatibility tests at ORNL

Fibers used in these tests were 1 mm diameter and 7 cm long straight pieces, polished on the end inserted in the liquid. U-shaped fibers were bended in 85°C water.

Tests A. BCF91 @ 22°C

A1	in BC531	core attacked in ~2.5 days
A2	in BC517P	no change after 141 days
A3	in polysiloxane[12]	no change after 141 days
A4	in water	no change after 141 days
A5	in BC531 (end coated with epoxy)	no change after 141 days

Tests B. BCF91 @ 42°C

B1	in BC531	core attacked in <1 day
B2	in BC517P	no change after 141 days
B3	in polysiloxane[12]	no change after 141 days
B4	in water	no change after 141 days
B5	in BC531 (end coated with epoxy)	epoxy attacked in 120 days
B6	in BC531 U-shaped	turned colorless at bottom of U after 10 days

Tests C. BCF91 @ 65°

C1	in BC531	core attacked in <1 day
C2	in BC517P	no change after 141 days
C3	in polysiloxane[12]	no change after 141 days
C4	in water	cladding attacked in ~140 days
C5	in BC531 (end coated with epoxy)	epoxy attacked in 28 days

Test D. Diffusion pump fluids with BCF-91 fibers.

D1	@ 65°C CMP704	core attacked after 5 days
D2	@ 42°C CMP704	core attacked after 10 days
D3	@ 22°C CMP704	no change after 49 days
D4	@ 65°C CMP705	core attacked after 8 days
D5	@ 42°C CMP705	no change after 49 days
D6	@ 22°C CMP705	no change after 49 days

TABLE 4 (continued)

Test E. Both Kuraray Y7(150) and Bicron fibers are U-shaped.

E1	@ 22°C BC531	no change after 28 days
E2	@ 22°C BC517P	no change after 28 days
E3	@ 22°C CMP710	no change after 28 days
E4	@ 65°C BC531	liquid discolored after 3 days
E5	@ 65°C BC517P	no change after 28 days
E6	@ 65°C CMP710	no change after 28 days

Test F. BCF-91A fibers coated with clear extra mural absorber (U-shaped).

F1	@ 22°C BC517P	no change after 28 days
F2	@ 22°C CMP710	no change after 28 days
F3	@ 22°C pseudocumene	in 1 day fiber broke
F4	@ 65°C BC517P	no change after 28 days
F5	@ 65°C CMP710	no change after 28 days

Test G. Test of Liquid Scintillator Components,
one U-shaped and one straight piece of BCF-91 in each.

G1	@ 22°C pseudocumene	core attacked in < 17 hours
G2	@ 65°C mineral oil	no change after 28 days
G3	@ 65°C nbutylbenzene	fiber broke in < 17 hours
G4	@ 65°C pseudocumene	fiber broke in less than 2 hours
G5	@ 65°C mineral oil	no change after 28 days
G6	@ 65°C nbutylbenzene	dissolved in <17 hours

Test H. Comparison of Bicron Liquid Scintillators,
one U-shaped and one straight piece of BCF-91 in each.
New batch of Bicron Scintillators received in July 1991.

H1	@ 22°C BC517H	no change after 28 days
H2	@ 22°C BC517L	no change after 28 days
H3	@ 22°C BC517PKO	no change after 28 days
H4	@ 22°C BC517S	core starts to be attacked in 17 days
H5	@ 65°C BC517H	no change after 28 days
H6	@ 65°C BC517L	no change after 28 days
H7	@ 65°C BC517PKO	no change after 28 days
H8	@ 65°C BC517S	soft in < 1 day, broke in < 2 days

TABLE 5

Bicron New Scintillator Light Output.

Scintillator	Light output (% anthracene)
BC517PKO (improved BC517P)	34
CMP704 + 517 fluor system	29
517 base + PMP	36
CMP704 + PMP	52

(clear transport fibers are always painted with white reflecting Extra Mural Absorber to prevent light cross talk and provide additional chemical shield); and d) development of new liquid scintillators.

As an example, within this program, Bicron has recently performed tests of new liquid scintillators based on tetraphenyltetramethyltrisiloxane (CMP-704 Dow Corning) with the 517 fluor system [8]. One advantage of CMP-704 is that being the scintillator base it can dissolve the scintillating pigments without any additional solvent. Preliminary results of scintillator light yield in these tests are shown in Table 5. Unfortunately, it was discovered by us later that CMP-704 does slowly attack plastic fibers. For the next trial it is planned to replace CMP-704 by CMP-710, which is significantly more inert than CMP-704 (see Table 4).

As it was stated above, the improvement of chemical compatibility also depends on the quality of plastic fibers. Recently Bicron had made an improvement in the production of

BCF-91 WLS fibers. Their new product BCF-91A has a more uniform cladding with less defects and cracks as well as improved transparency. Samples of this fiber are presently under test at ORNL, LLNL and at ITEP. We have also received samples of WLS fibers from Kuraray Company. These have different dyes (Y-7, Y-8, Y-9) and various dye concentrations. The cladding of these fibers is made from fluorinated PMMA and is expected to be more chemically and radiation resistant. In addition, fluorinated PMMA has a lower refractive index (1.419) than regular PMMA (1.49) which increases the numeric aperture of this fiber and results in increased light yield for the liquid scintillator system. These fibers are currently under test at ORNL, LLNL, UMiss and ITEP too.

It was expected that the chemical life time of liquid scintillator system components can be changed in a radiation environment. Radiation creates free radicals in the liquid scintillators and in fibers, which can make them more chemically active. In order to test this mechanism we have performed compatibility tests in a radiation environment. Irradiation was made at 32°C with ^{60}Co at a dose rate of 0.377 MRad/h. Total dose was 20 MRad. We have seen no chemical damage of plastic fibers in BC-517P scintillator (also no damage in CMP710) during and after irradiation. We have also made same compatibility test under irradiation with chemically active scintillator BC-531 (Bicron) and saw no increase of interaction speed due to irradiation. From these tests we can conclude that there is no significant influence of irradiation on chemical compatibility.

2.2. Radiation Resistance of Components.

Radiation damage to most commonly used liquid scintillators has been studied by S. Majewski et al.[13]. In this work it was determined that following a dose of 5 MRad (^{60}Co source, dose rate 0.033 MRad/h) the scintillation yield of BC-517L and BC-517H scintillators was reduced by 35-40%. The 5 MRad radiation level corresponds to 5 years of SSC operation at luminosity $10^{33} \text{ cm}^{-2}\text{s}^{-1}$ in the hadron calorimeter section positioned behind the e-m section at the angle of 5-6° in the GEM detector layout. As it was mentioned above, the major advantage of liquid scintillator is that it can be removed if radiation damage occurs. In practical calorimeter operation, for example, the liquid can be renewed/purified within a few days once a year. In fact, our intention is to install a radioactive source in the liquid scintillator cell (one per readout channel) such that the sensitivity of the cell can be permanently monitored (short run every 1-2 days) with an accuracy of ~1%. In this case the sensitivity degradation (down to 30-50%) can be restored by an appropriate

correction.

Radiation resistance of the whole liquid scintillator system is defined by the radiation properties of the plastic fibers since, unlike liquid scintillator proper, they cannot be replaced in the assembled calorimeter. We have performed initial radiation damage studies of WLS and clear plastic fibers at ORNL. A ^{60}Co source of 0.377 MRad per hour was used to irradiate wave length shifting (BCF-91, Bicon) and clear (BCF-98, Bicon) plastic fibers in air and in BC-517P liquid scintillator. Samples of 1mm diameter and 1 m length were used for these tests. Before and after irradiation the transmission of fibers was measured relative to non-irradiated reference samples. For transmission measurements we have used green LED (550 nm emission) and CdS photodiode. Results of these measurements are shown in Figure 1. Test samples were extracted from the irradiator and measured several times during the total exposure dose of 26 MRad. At such high radiation dose rates ($\sim 10^4$ times higher than relevant SSC dose rate) the transmission for clear fibers drops to zero after ~ 10 MRad. Samples irradiated to total dose of 26 MRad were annealed at room temperature and have recovered to the 95% transmission level after ~ 100 hours. The WLS fibers became opaque at the lower dose of 5-6 MRad and after a total dose of 26 MRad recover to the 50% transmission level in 250 hours at room temperature. For the WLS fiber irradiated to the total dose of 6.4 Mrad the transmission recovered to 90% level after ~ 100 hours (Figure 2). These initial measurements indicate that clear and WLS fibers can withstand doses of 5-10 MRad (and maybe even higher) with transmission degradation level of few percent (provided that annealing took place). We did not notice any essential difference between fibers being irradiated and annealed in air or in liquid scintillator. We plan to perform detailed program of radiation damage measurements with plastic fibers with the dose rates which are factors 10 and 100 lower than in the present tests and then extrapolate the results to the SSC dose rate.

The radiation stability of the reflector was studied with Bicon BC-622A TiO_2 paint which is prepared from cross-linked polyurethane resin. A sample of reflecting paint was irradiated to 9 Mrad total dose over an 8 hour period using the LLNL ^{60}Co gamma ray source. The sample was a 2" x 2" x 1/2" piece of aluminum painted with three coats of Bicon BC622A. The irradiation was performed by enclosing the sample in an air filled water tight canister and lowering the canister into the ^{60}Co source, which is under 20 feet of water. The sample was then tested for differences in its diffuse scattering properties

when compared with unirradiated samples. The result is shown in Figure 3. The effect of irradiation is small.

2.3. Light Yield. Optimization of Light Collection

To design and to optimize the performance of a basic liquid scintillator detector cell with wavelength shifting fiber (WLSF) readout we have to understand and control the physics processes which are responsible for operation of this technique. This is why we have initiated the studies of separate components of the liquid scintillator system which define the light yield and the efficiency of light transport (attenuation and reflectivity characteristics, radiation effects, etc.). Using the results of these studies we try to understand the effect of the various parameters on the light output of the liquid scintillator cell. This is being done with a Monte Carlo light transport program which was developed by us for this purpose [7]. Some of our measurements after being introduced into the Monte Carlo data base provides us guidance for better understanding and further optimization.

The typical light yield of liquid scintillators ranges from 26% to 80% relative to anthracene. For example, the improved version of Bicorn BC-517P liquid scintillator (BC-517PKO) has the light yield 35% of anthracene. Other relevant parameters of this scintillator are give in Table 6 [6,8]. In the 5 mm layer of the scintillator minimum ionizing particle produces about 5000 photons with wavelength around 425 nm. A scintillator cell with highly reflective walls confines the bouncing photons until they are absorbed in a wavelength shifting fibers (WLSF) which spirals inside the cell. The efficiency of interception of photons by the WLSF in the liquid scintillator cell depends of the reflection coefficient of the wall material and on the absorption length of scintillation light in the LS and the core of the WLSF.

Specular and diffusive reflectance of the white TiO_2 paint (Bicorn BC-622A) was measured at LLNL with results presented in Figures 3 and 4. The measurement of reflectance was made using a computer controlled reflectance/transmittance spectrophotometer. Figure 4 shows the results of the measurement of the specular reflectance for three different painted samples, as well as an unpainted sample of aluminum that was bead-blasted to provide a matte finish. The results indicate that there is a small ($\sim 6\%$) specular component of reflection that varies little between 400 nm and 700 nm. The bead-blasted sample has about a 4% reflectance over the same region. The measurement of diffusive reflectance (Figure 3) was made using a scatterometer designed for accurate measurements of laser op-

TABLE 6

Physical Properties of BC-517PKO Liquid Scintillator

Light Output:	35% anthracene
Mean Free Path (400-500 nm):	> 6 meters
Decay Time (approx.):	2.2 nsec
Wavelength of Maximum Emission:	425 nm
Refractive Index:	1.47
Specific Gravity:	0.85 g/cm ³
Flash Point (T.O.F):	115°C

tics and other scattering surfaces. Using a low power laser beam, the computer controlled system measures the amount of light scattered into a photomultiplier tube fixed at normal incidence with respect to the sample surface as the laser is rotated through different angles with respect to the sample surface. The results are shown in Figure 3 for 633 nm laser light. The paint scatters light nearly ideally (Lambertian) at angles less than about 20 degrees with respect to the normal then gradually drops to about 90% of ideal out to 60 degrees. This indicates that the paint is a good diffuse scatterer of light over angles out to about 60 degrees with respect to the normal.

The total reflection coefficient integrated over all angles for several popular diffusive reflectors were measured as a function of wavelength at the Moscow Research Institute of Optical Physics Measurements. Results are shown in Figure 5, where the emission spectrum of BC-517 scintillator is plotted too. Paint reflectance matches well the scintillator emission spectrum. Monte Carlo calculations show that mirror reflectors (high grade polished aluminium for example) are almost equally as good for optimal light collection in the cell. Practically, however, available mirror reflectors (aluminized mylar for example) in the liquid scintillator cell do not show better results than white diffusive paint.

The properties of the wavelength shifting optical fibers were measured at LLNL using coils of fiber inside integrating spheres. The measurements included spectrally resolved measurements of fiber emission and responsivity, fiber attenuation length and fiber spectral emission as a function of length. The integrating sphere (a spherical cavity internally coated with a highly reflecting white paint) is an idealized analog to the liquid scintillator calorimeter cell. It allows measurements of optical properties of the waveshifting fibers to be made under the ideal condition of spherical geometry and highly uniform illumination. Figure 6 shows a schematic representation of the experimental setup. A specially tailored light spectrum was input into the integrating sphere by passing the light from a broadband light source through a filter pack containing IR and UV filters along with a piece of Bicon BC400 plastic scintillator. This spectrum approximated the light output spectrum from the liquid scintillator. A coil of BCF91 waveshifting fiber inside the integrating sphere was thus uniformly illuminated.

The fiber light output could be measured using silicon photodiodes (integrating over all wavelengths), or using spectrometers (spectrally resolved measurements). In addition, the spectrum of light in the integrating sphere could be measured by disconnecting the fiber from the detectors and measuring the light from the sphere exit port. Many different measurements were made and will not be described in detail here. All collected measurements after being analysed are put into a light transport Monte Carlo[7] data base and used for appropriate simulations. As an example of a typical measurement, Figure 7 shows a measurement of the spectral responsivity of the BCF91 waveshifting fiber. This measurement was made by introducing monochromatic light into the integrating sphere instead of the broadband scintillation light. The spectrally integrated output of the wave shifting fiber was measured using a photodiode. Thus, Figure 7 shows a measure of the fiber output (emission) as a function of incident light wavelength (excitation). Also shown in the figure is the spectrum of output light from the Bicon liquid scintillator. The WLSF is seen to be well matched to the liquid scintillator out to about 480 nm where its response falls off rapidly. Figure 8 shows spectrum of light emitted from the end of WLS fiber measured with integrating sphere and spectrometer. A paper detailing this work has been submitted to NIM [14].

The most important characteristic of the fiber is the absorption length of the light of a given wavelength. Absorption length in the clear transport plastic fibers is known to

be in the range of few meters for the wave length range 500-600 nm [15]. WLS fibers which have only recently appeared as commercial products were initially optimized by the manufacturers (Bicron, Kuraray) to have the largest possible transmission length for the reemitted light. This has been done by selection of appropriate WLS dyes as well as by optimizing the dye concentration. To be efficient the WLS fiber should not be transparent to the light emitted by liquid scintillator but should be transparent to the self emitted light with the shifted wavelength. By our Monte Carlo studies we have found that if the light in the WLS core is emitted in the skin of the fiber core rather than uniformly distributed over the core volume, i.e. if the concentration of WLS dye in the fiber core is sufficiently high, the capturing efficiency of emitted light in the fiber (during the light transport along the fiber) is increased by significant factor (up to ~ 2). For the fiber of 1 mm diameter it should correspond to the absorption length of ~ 50 -100 micron at the maximum of absorption curve. On the other hand, the typical length of WLS fiber in the liquid scintillator cell is only 25-60 cm and, therefore, the transmission properties of emitted light can be to some extent compromised. As an example, WLS fiber Y-7 (Kuraray) with dye concentration 150 ppm has an absorption length of 500 microns at 440 nm (near absorption maximum) [16] and absorption length ~ 150 cm for the self emitted light. With proper choice of WLS dye concentration we are going to improve the light yield of the liquid scintillator cell. We have started measurements of spectral absorption length at ORNL, LLNL, UMiss and ITEP with different techniques for plastic fibers and with different concentration of WLS dyes. These techniques are also planned to be used later for the measurements of radiation and annealing effects on the fiber transmission properties.

To estimate the quality of different fibers and to look at dye concentration effect we have performed measurements of self emitted light attenuation in the WLS fibers which were excited by blue LED moving along the fiber. A schematic layout of the experimental setup is shown in Figure 9. A Soviet PMT FEU-130 with K-Cs-Sb photocathode was used in these measurements. The test fiber was connected to photocathode via a 3 cm clear fiber BCF-98 painted black. The LED was installed in a white teflon housing which was slid along the fiber. The DC signal from the PMT was recorded as a function of X — the distance from the photocathode ($10 \text{ cm} < X < 190 \text{ cm}$). The HV on the PMT and the DC power supply for the LED were kept constant during the measurements which results in a systematic accuracy of ~ 1 -2%.

TABLE 7
WLS Fiber transmission measurement two exponent fit results.

WLSF	Dye concentration (ppm)	Light yield (a.u.)	Fraction of short absorption	Short absorption length (cm)	Long absorption length (cm)	χ^2/DOF
Bicron						
BCF91 #1 ¹	200	484	0.42	38.1	130	36
BCF91 #2	200	393	0.52	21.6	132	7.4
BCF91A #1	200	475	0.47	33.8	290	1.5
BCF91A #2	200	461	0.48	31.2	287	1.7
BCF9926	100	416	0.33	32.9	185	2.1
BCF9927	300	509	0.49	28.5	162	1.5
BCF9928	400	513	0.33	21.0	159	3.3
Kuraray						
Y7	60	412	0.35	26.8	215	5.9
Y7 ²	60	416	0.37	27.8	216	2.4
Y7	100	593	0.47	22.0	157	5.7
Y7	150	565	0.57	33.4	183	2.6
Y7 ³	150	584	0.53	30.9	155	3.2
Y8	100	333	0.40	18.7	241	2.1
Y8	150	350	0.42	25.6	218	1.3
Y8	250	380	0.43	27.5	208	1.7
Y9	30	409	0.33	22.6	140	1.0
Y9	60	456	0.41	26.7	113	1.4
Y9	120	538	0.50	17.8	63	1.3

¹ fiber with visible cracks on the cladding

² remeasured second time

³ far end of fiber blackened

The measured dependence was fitted with two exponents

$$Y(X) = A \times [C \times \exp (-X / B) + (1 - C) \times \exp (-X / D)] \quad \text{where}$$

A is the light yield without transport attenuation, B and D are, respectively, short and long attenuation lengths and C is the fraction of short exponent. Results of the fit are given in Table 7. These data show that the light yield increases and the long attenuation lengths decrease (but not in the same ratio) with concentration of WLS dye in the fiber. Absorption and emission spectra for Kuraray fibers are given elsewhere [17].

To test the basic concepts of a liquid scintillator system we have built several prototypes

of liquid scintillator cells with various combinations of dimensions, reflectors and WLS fiber shapes. They were designed, built, and tested independently at ITEP, LLNL and ORNL and gave similar test results. One of prototype cells build at ORNL is shown in Figures 10 and 11. The cell is constructed with an aluminum frame 5 mm thick and two aluminium lids which are sealed against the frame with o-rings. There was a regular pattern of holes of 2.5 mm diameter with spacing of 11.5 mm in both lids. Aluminized mylar was stretched and fixed to the inner surface of the lids with double-side adhesive tape. Fiber feedthroughs were sealed with small o-rings (OD 3/32"; ID 1/32"; Nitrile N674/75 Parker Seals). The o-rings had been tested for chemical compatibility with liquid scintillator. We have rejected a few types of o-ring materials because they were not chemically compatible with the liquid. After several cycles of assembly - filling - disassembly of the cell we haven't had a single problem with the leaks of the liquid. Liquid supply to the cell was made with TYGON flexible tubes which were tested for chemical compatibility as well. According to Bicron specifications liquid scintillator should be saturated with an inert gas like argon or nitrogen to insure against the presence of oxygen which reduces the light yield of liquid scintillator. Before filling the cell we have flushed nitrogen gas through the liquid scintillator in the container, through the cell and then through a bubbler filled with mineral oil for about 30-60 min. (Figure 12). After that we switched on the nitrogen to push liquid out from the container to the cell. After the cell was filled the connecting tubes were squeezed and cut from the filling system.

Figure 11 shows the cell with mirror reflecting walls (aluminized mylar) which was measured to have too small a light output. All six walls of the cell were then painted with a triple layer of BC-622A white diffuse reflecting paint. In the middle of one of the lids a ^{235}U source was glued with epoxy. This source had been made at ORNL by electron beam evaporation of enriched ^{235}U on the Ti substrate. The source was 5 mm diameter and 0.25 mm thickness. Cylindrical (Figure 11) and spiral shaped fibers of different length were used for the tests.

The test layout is shown in Figures 13 and 14. The liquid scintillator cell was placed between two scintillation counters with thickness 1 and 10 mm, respectively. An aluminum plate $125 \times 125 \times 6 \text{ mm}^3$ with rectangular 9×9 pattern of holes, which was used to position a collimated beta-source at fixed points across the surface of the cell, was installed above the 1 mm scintillation counter. The signals from the thin and thick counters were used

in coincidence to trigger the setup with the beta-source as well as with cosmic rays. In addition, the setup was triggered with pedestal-, LED- and self-triggers. All triggers were multiplexed and controlled via computer. The results of the measurements with the cell $60 \times 60 \times 5 \text{ mm}^3$ are shown in Figures 15a-15d. In these measurements the liquid scintillator was BC-517PKO (which is our best choice with regard to chemical compatibility) saturated with nitrogen gas and the cell was coated inside with a triple layer of BC-622A white reflecting paint. The WLS fiber was 1 mm diameter BCF-9928 with a concentration of K27 WLS dye of 400 ppm (standard BCF-91 has a dye concentration of 200 ppm). The fiber length was 37 cm with a spiral shape as shown in Figure 10. The WLS fiber was connected at the cell exit with a 2 m long clear transport fiber (Kuraray with fluorinated cladding) which was coated on the surface with white reflecting paint and bent approximately $\sim 720^\circ$ before coupling to a Hamamatsu PMT H1161H. Thus, the conditions of these measurements reproduced most closely the real situation with light collection in the hadron calorimeter as described in [2].

The pedestal position and single photoelectron peak are shown in Figures 15a and 15b, respectively. The cell response to minimum ionizing particles (cosmic trigger) is shown in Figure 15c. The mean value of the m.i.p. signal is 4.8 photoelectrons (per liquid scintillator cell layer of 5 mm). This value is in agreement with the initial Monte Carlo calculations [5] provided that corresponding scintillator light yield and correct light attenuation length in WLS fiber is taken into account. Cell response to beta particles from a ^{106}Ru source with external trigger (Figure 15d) is somewhat lower ~ 3.7 photoelectrons which reflects the absence of a long tail in the energy loss distribution. Table 8 presents the major factors which define the light yield and gives the estimate of expected yield for minimum ionizing particles of 5.1 p.e. (this value should be compared with the experimentally measured value of 4.8 p.e.). Most essential factors in table 8 are calculated with the Monte Carlo program[7] which includes the manufacturer's data as well as data measured by us on properties of liquid scintillator and WLS fibers. As it was noted above the concentration of dye in the WLS fibers affects a) the efficiency of light interception and reemission by WLS fiber in the cell; b) the efficiency of capturing of the emitted light for transport along the WLS fiber; c) the attenuation length for the reemitted light propagation along the WLS fiber. The results of prototype cell tests presented above were obtained with dye concentration 400 ppm. The same concentration of dye was used in corresponding Monte

TABLE 8

Light yield calculation for Liquid Scintillator cell.(Parameters of the cell are given in the text)

Average energy loss in 5 mm LS layer	0.9 MeV
Energy spent to create photon in anthracene	61 eV
Light output of BC517PKO relative to anthracene	35%
Monte Carlo factors	
Fraction of light intercepted and reemitted by WLS (BCF-9928) fiber in the cell (efficiency of WLS reemission 86%)	38%
Fraction of reemitted light captured and transported along the WLS fiber (BCF-9928)	3.9%
Transport efficiency of 2 m clear fiber	70%
Average Q.E. of Photocathode H1161H	9.6%
Total photoelectrons	5.1 p.e.

Carlo (results shown in Table 8). Based on Monte Carlo simulations we expect that at higher dye concentrations we can get efficiencies a) and b) increased, respectively, up to 50% and 7% and c) while the attenuation length for reemitted light will not be significantly decreased (see Table 7). Our present activities are aimed at finding the optimum for the dye concentration in WLS fibers by means of Monte Carlo simulation combined with attenuation measurements for fibers with different dye concentrations.

Two prototype liquid scintillator cells were also fabricated at LLNL, each measuring 60 mm x 60 mm x 5 mm. One is a sealed cell with a waveshifting optical fiber coupled to a clear transport fiber. The cell is essentially identical to cells fabricated at ORNL

(Figures 10, 11). The LLNL cell has been used for measurements of the absolute quantum efficiency of the cell when subject to minimum ionizing radiation. The radiation can be tagged cosmic ray muons incident on the cell, or ^{90}Sr beta rays. Another cell was fabricated in an identical manner except that it has a 19 mm x 5 mm quartz window centered on one side of the cell. This window allows for measurements of the light yield of the liquid scintillator. Measurements of the cell response have been carried out using tagged cosmic ray muons. The cell output is measured using a calibrated high gain photomultiplier tube (Quanticon). Absolute photoelectron levels have been calculated using the photon statistics available from the multi-photoelectron resolution of the Quanticon. The number of photoelectrons per minimum ionizing particle has been measured for the case of a cell with reflecting aluminum walls and is currently being measured in a cell with reflecting white painted walls. Additional measurements, using the quartz window cell, have begun on the absolute quantum yield of Bicron BC 517P liquid scintillator when a minimum ionizing particle traverses the scintillator cell.

Another important factor which influences the light yield and uniformity of the detector response is fiber connection. Each cell has to have the following fiber connections : WLS fiber to clear transport fiber, clear fiber to clear fiber (this joint is for assembly purposes), and clear fiber to photodetector. Before connection the fibers have to be cut. For fiber cutting we use a gold plated tungsten wire (50 micron optimal diameter) heated by a DC current of 0.7A. Our tests show this cutting method provides sufficiently good and reproducible optical surfaces. To connect fibers we used small PMMA tubes with inner diameter precisely matching to fiber diameter (Figure 16). Fibers were fixed in the tube with small amount of epoxy seal. Table 9 summarizes test results of various fiber connections. Light from the green LED was transmitted via fiber joint and measured with a CdS photodiode relative to a reference continuous fiber of the same length. Within 4% systematic error all measurements gave the same transmission efficiency suggesting that simple fiber cut and splicing technique should work reliably.

The test set up shown in Figures 13 and 14 was used to measure the spatial response of the liquid scintillator cell. In these measurements a 2.5 mm diameter collimated beta-source ^{106}Ru has been positioned on the rectangular grid with hole spacing 11.5 mm across the cell surface. Amplitude measurements from the PMT connected to 2 m clear readout fiber were triggered by signals in coincidence from the two scintillation counters as shown in

TABLE 9

Fiber Joint Tests

BCF-91 (WLS), BCF-98 (CF) dia. 1 mm
Transmission measurement — ~ 4% accur.

test #	fiber	ends	coupling	measured
1	whole CF	polished	—	1.05
2	whole WLS	polished	—	1.07
3	WLS—WLS	polished	OC	1.07
4	WLS—WLS	polished	OC	1.07, 1.03
5	CF—CF	polished	OC	1.06
6	CF—CF	polished	OC	1.05
7	WLS—WLS	polished	air	1.00
8	whole CF	wire cut	—	1.05
9	whole WLS	wire cut	—	1.02
10	WLS—WLS	wire cut	OC	1.05
11	WLS—WLS	wire cut	OC	1.05
12	CF—CF	wire cut	OC	1.04
13	CF—CF	wire cut	OC	1.05
14	WLS—WLS	wire cut	air	1.00

Figure 13. Results of measurements with the cell of $6 \times 6 \times 0.5 \text{ cm}^3$ size are shown in Table 10a and results of Monte Carlo simulation in Table 10b. Measured cell nonuniformity is 12% and calculated one is 10%. We are presently performing light transport Monte

TABLE 10a

Measured LS cell non-uniformity - 12% (Ru^{105})

77	88	99	97	78	78
95	109	103	105	101	87
100	113	93	91	104	90
105	116	103	110	100	90
95	116	122	117	103	99
81	94	105	119	115	94

TABLE 10b

MC simulated LS cell non-uniformity - 10%

86	80	84	94	85	97
100	104	101	100	79	95
115	115	82	94	83	116
105	95	90	100	101	96
110	91	106	107	106	86
87	123	101	130	117	120

Carlo simulations (as well as measurements with prototypes) with the aim of improving the uniformity.

2.4. Calibration and Monitoring of Liquid Scintillator Calorimeter

The calibration is one of the basic issues of calorimeter operation. Following the ideas which have been applied in the construction and operation of the L3 Hadron Calorimeter[18] we choose the scheme of liquid scintillator calorimeter monitoring and calibration in which every calorimeter cell is equipped with a radioactive source.

In the L3 Hadron Calorimeter the built-in source is the depleted uranium absorber which provides in every readout cell of proportional gas tube detector the counting rate of 2-40 KHz. Actual calibration in L3 HC is done with a random trigger, such that measured calibration spectra have no characteristic peaks and a shape close to a falling exponential. Nevertheless, an accuracy of about 2% per readout channel in the calibration is achievable for ~30 minute run with the whole data acquisition system with over 20,000 readout channels. The same calibration system is used for the monitoring of the long term stability of the hadron calorimeter which was found to be 1.3% over a period of two years[18].

Our present plan is to place in every liquid scintillator calorimeter cell a radioactive source of small activity (counting rate < 1KHz/cell). For this purpose we have examined several source candidates including ^{235}U , ^{90}Sr , and ^{106}Ru . Self-triggered spectra for these sources are shown in Figure 17 a-c. For example, the ^{235}U (1% ^{234}U) source consists of a 0.25 mm thick Ti disk of diameter 5 mm with high-vacuum electron-beam-evaporated enriched ^{235}U on the surface. It provides a counting rate in the cell of about 900 Hz. This source was produced at ORNL. The cost of the source for several thousand units is estimated to be \$0.25/source. This cost could be reduced by a factor two for quantities required for a full calorimeter.

Due to the modular structure of the liquid scintillator hadron calorimeter each module can be individually calibrated in a test beam prior to installation. The signal from the source can be compared to this in-beam calibration thereby establishing the source as a secondary calibration standard. The radioactive source then serves as the calibration standard in each cell in the final calorimeter assembly. During the SSC operation the induced radioactivity in the calorimeter may eventually interfere with the source calibration

signal. This question is generic for all kinds of SSC calorimeters and needs separate study. Eventually one may use this induced radioactivity as the calibration source or, more likely, rely on specific pp-interactions to provide signals of sufficient accuracy.

In addition to the radioactive sources we plan to install an optical fiber light source on every photomultiplier with light supplied by a green laser through a dedicated fiber distribution system. This will allow independent tests of photocathode and electronics sensitivity and linearity over the full dynamic range.

2.5. Mechanical Design of Calorimeter Cells and Modules

The mechanical design for the Liquid Scintillator hadron calorimeter has been improved over the last year to address the specific issues of concern. Several engineers with experience on the L3 experiment have reviewed the design to incorporate lessons from that manufacturing process in the GEM sampling calorimeter design. There are three areas of engineering which have received detailed consideration: liquid leaks, manufacturability, and PMT mounting.

The hadron calorimeter central part (Figure 18) consists of 15 rings. Each ring includes 16 trapezoidal towers. The liquid scintillator cells inside the towers are not supposed to be leak tight, so the question of tower integrity is of great importance.

Designs are now proposed which provide complete welding to close the mechanical towers. This will permit the towers to be reliably tested for leak tightness prior to filling using conventional leak test techniques. In addition welding should provide a reliable means of insuring that the towers will not develop leaks during operation.

A refinement of the fabrication scheme has been devised which will more easily provide for the installation of the lead plates, segmenting trays and fiber bundles. The each component has been reviewed and redesigned for manufacturability. The segmenting trays are currently configured to be manufactured by a commercial vendor using standard stamped components. The shroud boxes have been configured to eliminate the removable lid thus reducing the cost associated with precision machining of the double O-ring sealing surfaces.

The PMTs are expected to be the most vulnerable component in the liquid scintillator system. Four alternative designs have been developed for consideration during the next year. Each of the designs addresses the two issues of importance, namely ease of assembly

and leak tightness. All are based on conventional technology. Tests will be performed over the next year to optimize the designs and verify adequate performance.

The tower shroud is a trapezoidal box with two open opposite lids. It is made of rectangular stainless steel plates welded together. The side walls have slots where absorbers are mounted and fixed (Figures 19, 20, 21). The height of the absorbers is 4 mm less than the height of a module. This creates a space for transporting the fibers. The fiber routing is shown in Figure 22. Lid tightness against leaks is achieved by welding a thin sheet to the module walls over the rim. A thick reinforced cover is set over the thin sheet (see Figure 23).

The PMT design uses a kovar ring to which the leak tightening unit is welded. There are several designs for a tightening unit — welding, O-ring, etc. Examples of some designs are shown in Figures 24 – 26. Fibers are gathered into bundles according to the readout scheme and are set in a holder installed inside a module. The holder has three independent degrees of movement (x , y , ϕ) (see Figure 27). This allows one to adjust the position of the fiber bundle relative to the PM cathode.

A very important question in the module production concerns the number of cell types. The advantages of uniform cells are: same response for all cells, no problems with cell summing, same calibration for all cells, and simple and more reliable mass production. A Fortran program was prepared to calculate possible versions of HC segmentation. Parameters of the program are: number of cell types, number of modules in the ring, internal and external radii of ring, and sampling thickness. The program designs segmentation with the following requirements: space between last chamber and back cover of housing must be small to decrease dead volume while the space must be as big as possible for ease in assembling fibers bundles. The space between adjacent cell should be kept at a minimum to avoid large dead zones.

One variant of segmentation is shown in Figures 28 (z-projection) and 29 (ϕ -projection). Summing of cells into readout channels is shown in these Figures with thin solid lines. This approach allows one to build planes using the same size cell long trays (see Figure 30). The tray design is shown in Figure 31 and 32. They are assembled from stamped stainless steel sheet. Covers are fixed by springs. Before assembling the tray pieces are painted with BC-622A white paint. The fiber exit from each tray is made through slot in the absorber (Figure 33).

2.6. Light Readout in the Magnetic Field. Electronics

Due to funding at less than half that requested, only very modest efforts could be put into readout development.

2.6.1 Photo Detector Read-Out

Existing subsystem collaborations for fiber optic based central trackers are already examining many options for photosensitive detectors [19]. There are many similarities in the needs for central trackers and calorimeters, but important differences. The most critical issues for calorimetry are high speed, linearity and dynamic range. Therefore, though we expect to gain much useful information from these other collaboration efforts, we must do our own explorations to address these issues.

Some general design criteria for a desirable photodetector are:

- The photocathode area should be large enough to accommodate a minimum of 16 each 1 mm fibers for multi-channel operation.
- The photocathode should have good quantum efficiency ($> 15\%$) in the 500-600 nm range.
- The intrinsic rise and fall time of the device should be < 2 ns and pulse height should have fallen to less than 1% after 16 ns.
- The device output should be linear throughout the signal range 1 to 1,000,000 photoelectrons.
- The device should be radiation hard such that there is less than 10% change in response for a total exposure of 10K rads.
- The device should be minimally sensitive to magnetic fields.
- The cost per channel should be $< \$60$
- The device should be as compact as possible.

A. Vacuum Photosensitive Devices

We have discussed various PMT options with Hamamatsu. They proposed a variant of the R2490-05, a magnetic-field-resistant design. The present tube is a 16-stage, high gain

device. The proposed tube would only use 10 stages, with a gain of 10,000 in a 0.8-tesla field and would have 16 anodes in a 4x4 array. Hamamatsu projects < 1% cross-talk and a 10% QE at 550 nm.

Figure 34 shows the proposed structure of the Hamamatsu R2490-05. The details of the multi-anode structure are highlighted. Figure 35 is a graph of the gain and dark current versus magnetic field (for 2500 volts across the dynode chain). Although there is a dramatic drop of gain with field, at the 0.8 - 0.9 tesla level there is sufficient gain to meet our needs. This is with the tube axis parallel to the field. If the magnetic field and tube axis are not aligned, the gain will decrease faster with field and more cross talk will result. Operation will be impossible with a crossed field. Therefore, the tubes must be mounted axially with the field, as has been shown in design drawings to date.

B. Solid State Devices

Avalanche Photodiode (APD)

Several APDs of Soviet design were examined. Due to limited funding and to problems with equipment only the SiC units were tested. They had breakdown voltages of about 22 volts at room temperature and were rather noisy. We plan to test them at reduced temperatures as well. There are also silicon APDs of Soviet design of two different kinds that have not been tested yet.

General properties of APDs that are most attractive are:

- Small size suitable for individual elements. Larger sizes are suitable for integration of the signal from the 4 x 4 array of fibers.
- Total insensitivity to magnetic fields.
- Low power consumption (0.1 Watt) making their location at each longitudinal segment within the calorimeter a possibility. However, due to the large pulses produced in the device by traversal of shower particles through the avalanche region of the device, it will be essential to locate all of the APD's at the back of the calorimeter. Light from each longitudinal section of the calorimeter can be light

pipled to the back of the calorimeter using non-doped optical fibers.

Because of the very small readout area, the fraction of 'crack' area will be minimal. Connections between wavelength shifting fibers and undoped fibers can be made efficiently and inexpensively.

- Good matching of spectral response to wavelength shifted light of 500 nm.
- High quantum efficiency of about 80% at ~500 nm.
- Intrinsic high bandwidth capability.
- The gain of the APD's is in the range from 50-200 for linear operation, and to 100,000 for Geiger mode.
- The linear dynamic range of at least 1000.

2.6.2 Data Acquisition Concepts

Many different schemes have been proposed for data acquisition at SSC rates. Our first choice at present, for near term implementation, is an over-sampled flash ADC (FADC) system with digital pipelining for trigger delay. Figure 36 shows one possible block diagram of this approach. It can (and will) be debated as to the location of the various processing blocks, but for the present we propose to place the preamplifier at the detector element, the FADC in a near by location, and the rest of the processing at some more distant place.

By over-sampling the output of the preamplifier, it will be possible to correct for pile-up and baseline drift. This will also reduce requirements on tight shaping of the signal. The penalty is the need for a faster FADC, with its increased power and reduced accuracy.

Presently IHEP (Serpukhov) group is working on the development and prototyping of a single fast readout chain of electronics of the type shown in Figure 36 for initial tests with liquid scintillator prototype cell.

2.7. Simulation

2.7.1. Light transport simulation code LTRANS.

To simulate the light collection in Liquid Scintillator Cell with Wave Length Shifting Fiber (WLSF) readout a Monte Carlo code was developed [7]. The following processes are taken into account in this code:

1. Ionization losses in media (dE/dx).
2. Scintillator efficiency (dE/dN_{photon}).
3. Up to 3 components of emitted light with relative weights and different emission time constants.
4. Spectral light absorption in scintillator, in the core and cladding of WLS and clear (transport) fiber.
5. Spectral light reemission in WLSF.
6. Absorption at different surfaces.
7. Secular and diffuse reflection of painted and mirror surfaces.
8. Reflection/refraction at the boundary of two transparent media.
9. Light propagation through WLSF and clear fibers.
10. Response of the PMT photocathodes.
11. Time development of light propagation.

The program operates with two basic kinds of objects: volumes and surfaces. Volumes can be filled with the media of the following types: air, scintillator, WLSF core, WLSF cladding, clear fiber core, clear fiber cladding, PM window etc. The possible types of surfaces are: frenel (natural boundary of two transparent media), mirror or diffuse reflection, black body, PMT cathode etc.

Characteristics of the corresponding real substances like spectral dependences of absorption length, refraction indices, emission light intensity, reemission probability, reflection coefficients for diffuse paints, refraction indices and extinction coefficient for mirror surfaces are stored in data base file and are extracted in the required combination at the start of the task. Existing data base file includes data for following materials:

scintillators : BC-531, BC517S, BC517H, BC517L, BC517P, BC517POK;

WLSF core : BCF-91, BCF-91A with K27 dye (different concentration),

Kuraray WLSF core with Y-7, Y-8 and Y-9 dyes (different concentration);

WLSF cladding : pure PMMA, fluorinated PMMA;

clear fiber core : pure polystyrene;

clear fiber cladding : pure PMMA, fluorinated PMMA;

diffuse paints : BC-622A(Bicron), NE-561(Nuclear Enterprise),

BaSO₄ based white paint;

mirrors : Ag, Al, Na, stainless steel;

photocathodes : bialkaly, trialkaly, green extended, 400K (Hamamatsu),

R2490-05, Si

To simulate the response of a Liquid Scintillator cell with WLS fiber readout three geometrical shapes were built in the code : rectangular box, cylinder and toroid (Figures 37, 38). Practically, any reasonable configuration of the cell with WLS readout can be described by the combination of these shapes. That makes the variations of the cell design rather simple. Typical process speed of the code is about 2 initial photons per second for the CPU VAX 11/780.

Tables 10a and 10b illustrate the results of the Light Transport code (LTRANS) obtained in our simulations. The cell $6 \times 6 \times 0.5 \text{ cm}^3$ painted with BC-622A white paint and filled with BC-517POK scintillator; WLS fiber of 1 mm diameter makes 2 spiral turns (5.4 cm max diameter) in the cell. Transport fiber is 2 m long and has 2.5 turns before it couples to 1161H PMT. These parameters simulates the actual experimental setup for uniformity measurement. The calculation gives 5.1 ± 0.5 for mean number of photoelectrons per m.i.p.

In Figure 39 is shown the light intercept efficiency of the cell and its dependence on the the geometrical factor — ratio of WLS fiber surface to the total surface of the cell walls and WLS fibers. These calculations were made for different cell size (from $5 \times 5 \times 0.5 \text{ cm}^3$ up to $10 \times 10 \times 0.5 \text{ cm}^3$) and for spirals with 1, 2 and 3 turns. Simulations were made for two types of WLS fiber with different light attenuation length. The result of these calculation shows that it is possible to have the same intercept efficiency for cells of different sizes by means of varying the length of WLS fiber in the cell. That allows uniform light collection efficiency when different cells are ganged to one readout channel.

Figure 40 shows the dependence of light transport efficiency in a clear fiber on bending radius. One can see that the minimal bending radius for transport fiber immersed in LS is ~ 2 cm.

2.7.2. Detector Simulation Calculations

LS calorimeter detector simulations have been carried out using the global GHEISHA-GEANT simulation chain developed by the L3 collaboration. These studies have been directed toward a better understanding of the light collection non-uniformity on hadron energy resolution as well as total thickness of absorber material. Hardonic jets with energy 50, 100, 200, 500 and 1000 GeV were simulated for a calorimeter consisting of a 50 cm BaF₂ electromagnetic section followed by a hadronic section (20 mm lead + 0.5 cm liquid scintillator) [2]. Simulated events passed the full reconstruction procedure and optimal weighting factors were applied for the combination BaF₂ and hadron calorimeter section responses. The resulting energy resolution vs hadronic jet energy is shown in Figure 41, respectively, with and without liquid scintillator cell nonuniformity contributions. From these calculations we can conclude that 5% light collection nonuniformity does not affect the hadronic resolution of the calorimeter. The results of these calculations together with results for different absorber structure simulations are shown in Table 11. We are presently repeating these calculations with nonuniformity values determined from our tests.

Ideally, these calculations should be carried out with HETC which requires using CALOR. Presently the CALOR code system is being converted to a CRAY UNICOS machine at LLNL by ORNL personnel, has been installed on PDSF at the SSCL by UMiss personnel and is being installed on the UMiss HEP 900MIP "farm" at UMiss. Calculations similar to those described above are being initiated on PDSF and will be carried out on the other facilities as they become operational. These initial studies are rudimentary since they involve only planar geometry and single hadrons rather than jets. However, they appear to be consistent with the GHEISHA-GEANT calculations. In addition, code improvements which reflect experience gained in the scintillating plate calorimeter studies are being incorporated into CALOR. This includes modification so access to a radiation damage data base becomes simpler which will aid in studying the effect of radiation damage on resolution, timing, compensation, etc.

TABLE 11

Monte Carlo LS HC resolution
BaF₂ in front, 5 mm LS gap

Fine sampling sect.	Tail catcher	Light collect. nonunif. 5%	B (%)	A (%)
2 cm Pb x 90	—	—	1.1 ± 0.2	66 ± 3
2 cm Pb x 90	—	+	1.2 ± 0.2	66 ± 3
2 cm Pb x 38	4 cm Pb x 20	+	1.7 ± 0.2	59 ± 3
2 cm Pb x 78	—	+	1.6 ± 0.2	63 ± 3

2.8. Alternative Light Readout Ideas

A. UV Light Sensitive Microgap Photodetector Development

A new type of UV light sensitive photodetector was developed at LLNL as a means of replacing the photomultiplier tube reading out the light from a liquid scintillator cell.[20]

Two detector concepts are shown schematically in Figure 42. The detector consists of a thin parallel plate gas avalanche counter optically coupled to a liquid or solid scintillator by a UV sensitive photocathode. The photocathode can either be semi-transparent (transmission mode) or opaque (reflectance mode) similar to photocathode technologies found in standard photomultiplier tubes. The photocathode chosen for this detector is yttrium and is sensitive to photons with wavelengths shorter than 400 nm.

The photocathode is separated from the anode by a thin 100 micron gap filled with a gas of 90% argon and 10% methane. Application of a few hundred volts across the gap is sufficient to operate the counter in the proportional regime. Photoelectrons are amplified by the formation of electron avalanches in the gas. Typically, the detector operates with a

gain of about 10^5 — 10^6 . A 36 cm^2 area detector has been fabricated and tested for response to a nitrogen laser (337 nm) and to UV light emitted from liquid scintillator. A photograph of the detector is shown in Figure 43. The detector is inherently fast because of the very short electron drift time across the 100 micron gap (about 1 ns). The ion transit time back to the photocathode is also short (15-20 ns) and so the pulses from this detector are quite narrow. This can be seen in Figure 44, which shows an oscilloscope picture of the output of a typical detector.

At our request, a UV emitting liquid scintillator was specially developed for this detector by Bicron Corporation with a peak emission of 310 nm. The Microgap UV detector has been observed to be sensitive to light emitted by the scintillator when excited by a radiation source. However, absolute efficiencies have not yet been measured.

2.9. Initial Studies on a Liquid Scintillator Electromagnetic Calorimeter Design

The idea of Liquid Scintillator with WLS fiber readout was first proposed by us for hadron calorimeter applications. Recently we have tried to extend this concept to electromagnetic calorimetry. Modern EM sampling calorimeters can achieve a resolution of $5\%/\sqrt{E}$ [21] with small constant term (0.5-1%) which results from the non-uniformity, non-stability, limited calibration etc. Sampling calorimeters for SSC applications should be fast and radiation hard. Radiation requirements for the EM calorimeter is an order of magnitude higher than for hadron calorimeter and are about 50 MRad at $\eta=3$ for 10 years of operation at luminosity 10^{33} . We believe that the radiation stability of WLS fibers can be proven to satisfy these requirements.

Obvious problems for a high resolution sampling LS EM calorimeter (apart from radiation resistance of fibers) are cell response non-uniformity and the potentially large amount of fibers, since a large number of very thin LS cells must be read out. According to parametrizations of the work [21] and our EGS4 [22] simulations the structure of 2 mm Pb and 4.5 mm liquid scintillator should have the stochastic resolution term of $7.5\%/\sqrt{E}$. A $25X_0$ thickness EM calorimeter should consist of 70 layers (2 mm Pb + 4.5 mm LS). The basic idea of our design is that in order to reduce the number of readout fibers a single WLS fiber should spiral through the absorber collecting the scintillation light from several longitudinal layers. Figures 45, 46 show the possible layout of a Pb/LS EM tower where WLS fiber runs through several layers of LS between lead absorber before being routed for readout to photodetector via clear transport fiber. Longitudinal segmentation can be

easily achieved in this scheme (Figure 47). The lead absorber in the EM-tower is installed in the punched stainless steel box (Figure 45) with wall thickness of approximately 0.2 mm. Spiral shaped fibers can be inserted from the top in between absorber plates. The box is covered by a thin lid of 0.2 mm stainless steel and sealed by glueing or micro-welding. The assembled tapered tower is a self-supporting unit with the interior continuous for the liquid flow. It has several readout segments (by the number of WLS spirals). Figures 48 and 49 illustrate possible LS EM calorimeter layout for an SSC GEM detector [3] geometry and proposed assembly sequence.

It was estimated with EGS4 MC simulations that the Moliere radius for such a structure is about 4 cm. This suggests that the front size of the tower can be $30 \times 30 \text{ mm}^2$ or somewhat larger. The longitudinal and transverse uniformity of the LS readout segment (one WLS spiral) as simulated by the LTRANS code is shown in Figures 50 and 51 for the tower with the front size of $30 \times 30 \text{ mm}^2$. Transverse uniformity has an rms of 5.3% and longitudinal variation of 18%. The light yield is higher for the end of the WLS spiral which is closer to the readout. In this simulation the diameter of each spiral turn was increased with the tower depth. By adjusting the diameter of the turns one can find the compromise between longitudinal and integral transverse non-uniformity. This optimization has not yet been done.

Data from light transport simulation mentioned above were used in the EGS4 code simulation of the performance of the EM array of 10×10 tapered towers with front size $30 \times 30 \text{ mm}^2$. The results of these simulations are shown in Figures 52, 53, 54 for different thickness of stainless steel structure between individual towers (1.0, 0.5 and 0.25 mm). EM energy resolution is almost independent on the wall thickness and equal to $7.5\%/\sqrt{E} \pm 0.6\%$. Longitudinal and transverse cell non-uniformity contributes to the increase of the constant term in the energy resolution.

In an SSC experiment the EM-calorimeter precedes the hadron calorimeter and together with it measures the energy of hadrons. Since the LS hadronic calorimeter described in [2,3,5] can be made compensated the issue of e/h for the EM section becomes important. A sampling structure 2 mm Pb/4.5 mm LS is far from the sampling 4/1 required for compensation calorimeter [10]. Nevertheless, the effective compensated readout of LS EM tower can be arranged by combining together (possibly with separate specially shaped WLS fiber) signals from every 9-th LS layer in the tower. The rest of the tower layers are

readout by the regular scheme described above and used for the purpose of EM energy measurement. In this approach an excellent EM resolution of $7.5\%/\sqrt{E} \pm 0.6\%$ does not spoil the compensation properties of the global calorimeter. Detailed Monte Carlo simulations (and later corresponding beam tests) are required in order to confirm this concept.

We plan to construct first a single tower prototype and then an array of 5x5 towers in order to test the concept of LS EM calorimeter. The EM towers will be designed and assembled at ORNL and tested in the beam at ITEP or elsewhere.

2.10. Additional Facilities and Support Personnel

Besides the specific facilities and personnel described in the above section, each laboratory and institution has support facilities and personnel which can be or have been used in carrying out this work. In some cases these are quite extensive and give exceptional strength and flexibility to the program. The following gives a brief description of some of these facilities and personnel.

2.10.1 Lawrence Livermore Laboratory

A. Photometry Laboratory and other LLNL Facilities

A photometry laboratory was set up at LLNL in FY 1991 consisting of a large multi-purpose light-tight dark box for the measurement of fiber and liquid scintillator properties as well as the measurement of liquid scintillator calorimeter cell prototypes. Figure 55 shows a photograph of the dark box containing the pulsed broadband light source and monochromator, calibrated photodiode and calibrated photomultiplier tube. The laboratory is equipped with a NIM and CAMAC data acquisition system and a Macintosh II/FX computer for performing data acquisition and analysis. A Hamamatsu R2165 "Quanticon" high-gain first dynode photomultiplier tube allows for measurements of absolute quantum efficiency of the various components at low light levels below about 10 photoelectrons. Also, NBS calibrated photodiodes are utilized for higher light level measurements. Calibration of the phototube is performed using a pulsed nitrogen arc lamp through a monochromator system and neutral density filters, providing a range of photon wavelengths from the IR into the far UV, and photon light levels ranging from single photons on up. A LeCroy 3512 buffered ADC and LeCroy 3588 Histogramming memory are used to collect pulse height distributions from the Quanticon. Data acquisition is performed using LabView on the Mac via a GPIB data bus. Data manipulation and display is performed using Igor

scientific graphics software and custom-built software fitting routines.

B. LLNL Optics Laboratories

In addition to the custom-built Photometry laboratory, a number of optics laboratories are maintained for use by scientists at LLNL. The facilities utilized for R&D in FY 1991 were the automated spectral transmittance/reflectance system and scatterometry system in the LLNL Optics Laboratory, and the Fiber Optic Characterization Laboratory. These facilities are well equipped to perform spectrally resolved measurements of the basic components of the liquid scintillator cells such as reflecting paints, liquid scintillator and waveshifting dyes, waveshifting fiber spectral properties, fiber connection losses, and fiber transport properties (attenuation, etc.).

C. LLNL Radiation Facilities

LLNL maintains a large ^{60}Co irradiation facility as well as a number of other high flux radioactive sources including neutron sources (^{252}Cf , Pu-Be, etc.). In addition a 140 MeV electron linear accelerator is available for beam tests and for use as a high flux source of gamma rays and photoneutrons. Measurements have been made in FY 1991 using the ^{60}Co source and are planned using the ^{252}Cf source.

D. LLNL Chemistry and Material Science

Mechanical and chemical characterization facilities are also available for use in the R&D program. Microscopic characterization of materials can be performed using metallurgical techniques to produce thin samples for analysis under various types of microscopes. Trace element analysis can be done using energy dispersive spectroscopy and electron beam microprobes. Chemical and mechanical analysis of waveshifting fibers and reflecting paints can also be performed.

2.10.2 University of Mississippi

A Perkin-Elmer Lambda 3B UV/VIS Dual Beam Spectrophotometer and a Perkin-Elmer LS-5B Luminescence Spectrometer are available for use in this project. These units have been used for research for several years and are well-characterized. They are presently being modified to accept fiber samples. These units will give us the capability for studying fiber characteristics in the range of 200 — 800 nm both in transmission and via the fluorescence spectrum.

A 900 MIP Decstation 5000 "farm" belonging to the high energy group is in the final stages of check-out and will be available for use in simulations and light transport studies. Codes such as GEANT, CALOR, PYTHIA, ISAJET, CERNLIB, etc., are operational. The "farm" is accessible via Internet and plans are to establish a Decnet node as soon as funds are available.

A machine shop equipped with CNC machines is available for our use, as is the Physics department machinist at no charge.

2.10.3 ORNL Facilities for Research, Design, Fabrication, and Testing

ORNL has extensive facilities for research on the optical, chemical, and mechanical properties of scintillators, fibers, and detectors. It has 40 years of experience in the field of nuclear instrumentation, from detectors through electronics. Several divisions and many groups are actively researching detection media, detector systems, and electronics for these systems.

A. ORNL Manufacturing Facilities

Because of other missions, ORNL maintains extensive fabrication capability for electronic and mechanical systems that range from small model shops to full scale machine shops capable of fabricating intricate parts the size of freight trains.

B. ORNL Radiation Facilities

ORNL maintains small, medium, and large ^{60}Co and ^{137}Cs irradiation facility with fluxes from background to $> 1\text{MRad/hr}$, as well as a number of other high flux radioactive sources including neutron sources (^{252}Cf , Pu-Be, etc.). A 50kW, 180 MeV electron linear accelerator is available for use as a high flux source of gamma rays and photoneutrons. Efforts are presently under way at this facility for other SSC subsystems. ORNL has a 100 MW high- flux, research and isotope production reactor for very high flux irradiation. Samples can be irradiated to levels of $10^{15}\text{n/cm}^2/\text{s}$. No efforts are presently planned, since these rates are too many orders-of-magnitude greater than that expected at the SSC.

Measurements were made in FY 1991 using a large ^{60}Co source and are planned using lower dose-rate sources. Neutron irradiations can also be made but are not presently planned.

C. ORNL Analytical Chemistry and Material Science Capabilities

Mechanical and chemical characterization facilities are also available for use in the R&D program. They are well equipped to perform spectroscopy and fluorimetry measurements of the liquid scintillator, waveshifting dyes, waveshifting fibers, fiber connection losses, and fiber transport properties (attenuation, etc.). Chemical and mechanical analyses of scintillators and waveshifting fibers are being performed, including chemical compatibility between the scintillator and fiber, as well as optical properties of the fibers and scintillators.

2.10.4 University of Tennessee

The University of Tennessee has provided the use of a VAX-9000 and an IBM-3090 for the calculational effort. In addition, a five man machine shop and four man electronic shop have been used and will continue to be used in this work. In many cases the computers and shop usage is provided at no charge.

2.10.5 ITEP (Moscow)

During FY1991 ITEP provided significant support to the Liquid Scintillator R&D program. 21 ITEP staff (6 physicists, 3 postgraduate students, 4 engineers and 8 technicians) were involved. Mechanical workshop, test beam time, beam equipment, computers and other infrastructure support was provided.

Test beam area No. 211 at ITEP 10 GeV PS machine was upgraded (mechanical supports, electronics, beam MWPC system etc.) for tests with liquid scintillator prototypes. Available beam momenta are 0.3-6 GeV/c for muons, pions, protons, and electrons. Typical beam intensities are 5-50 K pions per spill of 1.0 s every 2.5 s. Available test beam equipment includes beam control system, collimators, converters, 2 gas Cerenkov counters, beam telescopes, muon filter, trigger NIM electronics, CAMAC readout system, PDP 11-40 on-line computer, Ethernet link to VAX 11-780, DAQ, monitoring and graphics software.

Initial research on chemical compatibility of liquid scintillators and fibers as well as on prototyping of detector cells and study of light collection and response uniformity have been started at ITEP by fall 1990. First basic parameters and test configurations of the Liquid Scintillator system have emerged from these researches.

The LTRANS light transport Monte Carlo code for scintillator counters with WLS fiber light readout has been developed at ITEP [7] and became available to the LS collaboration.

Data being obtained from various tests made by LS collaboration are continuously used to improve and update the code and the corresponding data base.

2.10.6 IHEP (Serpukhov)

Studies of different electronic readout schemes for prototype beam tests as well as studies of alternative liquid scintillator and plastic fiber materials available at USSR were proceeded. Development of single channel fast readout full electronics system with parameters close to these required by SSC operation have been started.

2.10.7 TIFR (Bombay)

Facilities for radiation damage studies of liquid scintillators have been created. Initial tests have been started. (See Addendum 1)

Chapter 3. PROPOSED R&D PROGRAM FOR FY92/93

The R&D Liquid Scintillator activities will be continued in 1992/1993 according to the initial plans outlined in ref.[5]. These plans later can be modified in the framework of GEM collaboration if more extensive schedule will become necessary.

In FY92 we are planning to continue the studies on the LS system and components as well as to proceed with the beam tests of the single LS detector plane and start construction of the calorimeter module for the FY93 beam tests.

3.1. R&D Program

In our studies performed in FY 1991 we have identified and addressed the most critical issues of the liquid scintillator technology. Initial tests were completed on the chemical compatibility of the principal components of the LS system, chemical compatibility under irradiation, radiation damage of WLS and clear fibers, and light yield. These tests have demonstrated that the basic concept of the LS with WLS fiber readout is correct and there are no major restrictions in applying this technology to the SSC calorimetric detectors.

In the further development of the LS technology we would like to understand and push this technique to its limits in terms of chemical compatibility, radiation stability, detector response time and light yield. Our intention is to demonstrate with beam tests of the prototype detector plane the compensation properties of a Pb/LS calorimeter, adjust sampling thickness of the absorber, study time development of compensation signal, dynamic range of the basic cell, noise, calibration, cell response uniformity with showering particles as well as to prove our mechanical approach to the construction of the cell, light cross talks, liquid circulation, leak sealing, fiber splicing, fiber interfacing with photodetector and other ideas.

Our initial radiation damage tests to the fibers were done at very high dose rates (0.377 MRad/h). In real SSC environment the irradiation rates will be few orders of magnitude lower, such that annealing will take place before the radiation damage will build up. We have seen the WLS fiber transmission recovery after 6.4 MRad (irradiated at 0.377 MRad/h) for 1 m long piece to 95% of initial value for ~100 hours at room temperature. To extrapolate the radiation hardness of fibers to the realistic SSC rates we are going to perform radiation tests (including annealing) with radioactive sources at different rates. We hope these studies can prove that LS with WLS readout technique can

be applied to the SSC luminosity range of 10^{31} — 10^{34} s⁻¹ cm⁻².

After irradiation the optical and spectral constants for tested materials will be measured and the results of the radiation tests will be expressed in terms of variations of light transmission length, reemission efficiency (light yield) and annealing time. After extrapolation of these results to the SSC radiation levels data will be fed into the LTRANS Monte Carlo code and then we will be able to predict the global light collection properties of the hadron calorimeter during the radiation.

An important goal of the R&D program is the optimization of the light yield of the LS cell and of uniformity of the cell response. We plan to construct several cell prototypes to study the dependence of light output and uniformity on cell size, fiber shapes and different WLS dye concentration in the fiber core. We plan to test new Bicron and Kuraray fibers, new materials for fiber cladding, various scintillators and wall reflectors. All cell prototypes will be simulated by the LTRANS code and simulated performance will be compared with measured one. The comparison of calculations and experimental data will result in improvement of the Monte Carlo code and allow us to predict more accurately the performance of new prototypes.

Since the light intercept efficiency by WLS fiber in the cell scales with the ratio of WLS fiber surface to the total surface of the cell we will try to equalize the response of cells of different sizes by varying the length of WLS fiber in the cell.

We will continue measurements of spectral characteristics for scintillators, WLS and clear fibers, mirrors and diffusive wall coatings. These data will be used for final cell design.

By the end of 1991 a LS plane with 36 cells will be built. This plane will be tested at the ITEP test beam in December 1991 — February 1992 period. A radioactive source of ²³⁵U will be mounted in each detector cell. The photodetector-electronics readout system for this plane will be prepared.

The construction of the prototype hadron calorimeter module will be started in FY 1992. This will be full size module with 2 cm lead absorber and 0.5 cm Liquid Scintillator sampling. This module will be assembled and tested in the CERN test beam starting from November 1992. The support for the test module will be designed and fabricated at ORNL.

We plan to simulate the performance of the HC module taking into account effects of

the radiation damage, the nonuniformity of light collection in the LS cell, the light yield variation from cell to cell and others.

3.2. Plans of Participating Laboratories

3.2.1 Plans for Continued R&D at LLNL in FY92

LLNL plans to continue with R&D in FY 1992 with efforts in the areas of radiation damage, light collection efficiency measurements and optimizations, and alternative photodetector concepts. With the completion of the photometry laboratory, we are now capable of quickly providing comparative measurements of liquid scintillator cell absolute quantum efficiency to minimum ionizing particles. These measurements will have to be carried out for the increasing number of different waveshifting optical fibers that are becoming available as this technology matures. We also expect to continue some of the more fundamental measurements of fibers, including the effects of bend radius, cladding thickness and numerical aperture (optical efficiency) optimization. The UV microgap detector offers the promise of a large area radiation hard and magnetic field-insensitive photodetector to replace photomultiplier tubes. This detector can be built with single or multiple anodes to allow flexible readout options for the liquid scintillator calorimeter. In addition, the potential exists for fabricating a microgap detector directly on a plastic scintillating substrate, thereby simplifying the design and reducing the materials cost. We expect to further develop this concept in the coming year by fabricating a detector using Bicron BC 422 UV emitting plastic scintillator. LLNL will continue to provide measurements of optical properties of the materials making up the scintillator cell. Our Optics Laboratories are well suited for measurements of spectral properties of paints and scintillators, as well as characteristics of waveshifting optical fibers. We also will continue to utilize our ^{60}Co and ^{252}Cf sources for radiation measurements, including the measurement of long-term optical fiber darkening and self-annealing under near-SSC radiation conditions. Finally, we would like to continue work on a detector concept presented in the FY 1991 proposal. This concept involves the direct stimulation of an GaAlAs lasing waveguide with ionizing radiation to induce lasing. The concept involves connecting a lasing waveguide substrate to a microgap avalanche counter in a similar fashion to the UV microgap counter. Electron avalanches striking the waveguide structure could induce laser light to be pulsed down the waveguide and detected optically via single mode fiber optics. This concept has the advantage of providing direct conversion of energy deposition in the hadron calorimeter into

light channeled into very thin single mode glass fibers that can be run for 100s or 1000s of meters without appreciable signal attenuation. The concept has not been proven but there are specially built waveguides available at LLNL which could be utilized in this study.

3.2.2. Plans for Continued R&D at UMiss in FY 1992

A. Irradiation Program

Irradiation of WLS and clear fibers in air, nitrogen and liquid scintillator will be carried out at the University of Mississippi Low Dose Rate(LDR) and High Dose Rate(HDR) Facilities. The LDR is a ^{137}Cs source with a usable maximum dose rate of 300 rad/hr. The HDR is a ^{60}Co installation with a maximum dose rate of 260 krad/hr and a minimum rate of about 50 krad/hr. We shall compare radiation effects on the fibers when irradiated at low and high dose rates. A series of irradiations on BCF-91A and Kuraray Y-7, Y-8 and Y-9 fibers with various dye concentrations and claddings and a number of clear fibers will be performed. Wherever possible we shall coordinate our program with that at LLNL and ORNL so we can obtain duplicate irradiations for a number of cases. This will be especially important where annealing effects may become significant.

B. Radiation Damage Measurements

Radiation damage will be determined by measuring the spectral properties of the fibers before and after irradiation. Transmission measurements scanning the range 200 — 800 nm will be performed using the UV/VIS dual beam spectrophotometer. In addition a fluorescence spectrometer spanning the same range will be used to ascertain the fluorescence properties of the fibers before and after irradiation. This latter information is very important in calculating the light collection and transport properties of a cell. It could also play a role in the development approach to the optical readout system.

C. Test Beam Program - Analysis of Test Beam Data

UMiss personnel will participate in the ITEP beam test which is planned for February 1992. Calculations using LTRANS coupled with CALOR will be performed to determine the expected performance of the rudimentary calorimeter. Use of CALOR is essential since we need timing information to investigate the time dependence of the compensation. Comparisons will be made with the test beam data and these comparisons will be used to modify the calculational procedure, if needed. The resultant code will be used to design the prototype tower.

D. Simulation Calculations and Code Development

The UMiss personnel will work closely with the ORNL and UT code developers to incorporate LTRANS into CALOR. The code will be ported to PDSF at the SSCL (where B. Moore from UMiss has already successfully installed CALOR) and to the UMiss HEP DEC "farm". This will give us over 2000 MIPs for our calculational effort. All of this will be needed in the design of the prototype tower. We shall begin the geometry input package for this tower in FY92 and, using the tested and modified code from the ITEP test, begin the detector simulation on the various proposed designs.

3.2.3 Plans for Continued R&D at ORNL in FY 1992

A. Major LS R&D activities will be centered at ORNL. In FY 92-93 ORNL will continue developments and tests of basic components of liquid scintillator technique. These will include detailed chemical compatibility studies, radiation damage tests, WLS and clear fiber optical properties studies under irradiation and annealing, light yield optimization, calibration system development, studies of new fibers, liquid scintillators and photodetectors, more detailed development of Monte Carlo light transport code.

B. Mechanical design towards the practical implementation of LS concept in hadron and electro-magnetic calorimetry to simplify the manufacturing, assembly, and service of calorimetric system for the basic GEM detector design will be continued. Questions of reliability and robust performance of the calorimeter will have first priority in these studies. These studies should result also in cost reduction of Liquid Scintillator technique in practical application to GEM calorimeter system.

C. Most intensive activity at ORNL in FY 92-93 will be design, manufacturing and assembly of LS calorimeter prototypes for beam tests. By the end of 1991 prototype LS detector plane has to be build and tested at ITEP beam. In 1992 full size GEM type hadron calorimeter module will be build and equipped with photodetectors, readout electronics and data acquisition system. To resolve this and other major tasks ORNL personnel will work in tight contact with personnel from ITEP.

D. In connection with development of electronic readout system for module prototype beam tests following activities will be also conducted :

D1. Light Collection Studies of the Scintillator and Wavelength-Shifting Fibers: Continued testing needs to be done to experimentally determine the light collection efficiency

of several different geometric configurations of the liquid scintillator, wavelength-shifting fibers, and PM device. This will include tests to (a) determine the optimum scintillator/fiber interface, (b) explore the use of multiple fibers for individual channels, and (c) determine the optimum fiber/PM device interface.

D2. Develop the Data Acquisition Architecture: The primary purpose of this proposal is to determine the feasibility of the liquid scintillator concept. Accordingly, the thrust of the electronics research and development will be toward those issues that directly impact the performance and construction of the calorimeter. We do not propose at this time to develop a new complete architecture for calorimetry data storage. Instead, we intend to address only those issues that pertain uniquely to this calorimeter. Specifically, we will research the optical analog data transmission concept with respect to linearity, power dissipation, noise, radiation hardness, and manufacturability. After evaluation of the measurements, we will research the optimum pulse shaping and storage for enhancing both count rate and signal-to-noise performance. A preamplifier, prefilter, optical linearizer, and optical receiver amplifier will need to be researched and developed to exhibit the highest possible speed and linearity. These will probably be a mixture of custom CMOS and bipolar technologies.

One concept we are considering is the generation of the high voltage necessary for the PM device at the tube rather than distributing high voltage from outside the tower. We are presently generating high-voltage for another project using a custom CMOS analog controller developed at Oak Ridge National Laboratory. This controller uses very low power and can generate from 500V to 2000V with some external components. Therefore, only a low voltage power supply level will have to be distributed throughout the tower. Some further development of this controller throughout the tower be undertaken to adapt it to our specific need.

D3. Evaluate Photomultiplier Devices: An evaluation of multi-anode PM tubes will be made to determine the most appropriate choice in terms of anode crosstalk for the scintillator/fiber combination we will be using. Tubes from three vendors will be purchased and evaluated: 64 channel device from Amperex (Model No. XP4702), a 16 or 64 anode tube made by Hamamatsu (Series No. R1712), and a 100 channel device from ITT. In addition, we will explore the possibility of using the new emerging technology of solid state PM devices currently being developed by Rockwell, Inc., Burle Industries, and RCA.

D4. Fabricate, Assemble and Test Data Acquisition Electronics: Data Acquisition electronics for a prototype will be fabricated, assembled and installed. This assembly will then be tested in an actual beam at a location to be determined. In addition, we will plan to instrument a prototype sections for testing in a beam. Preliminary investigations will be conducted into alternative architectures for digitizing the analog signal and processing the resulting digital information at the rear of the towers.

3.2.4. Plans for Continued R&D at the University of Tennessee in FY92

The University of Tennessee will continue to provide administrative support for the visiting ITEP personnel. A crucial support activity remains the use of the machine shop and electronic shop as well as availability of the computing facilities. A large amount of construction and computing will be done as we move into the prototyping stage of the program and the UT facilities will be heavily used in this.

3.2.5. Plans for Continued R&D at ITEP in FY92

ITEP will continue to provide essential contribution to LS project via close contacts with ORNL. ITEP technical personnel will work at Oak Ridge together with ORNL engineers. The preparation of the beam tests with a single detector plane will be carried out. This includes the preparation of the liquid scintillator filling system, absorbers, mechanical structure for absorber installation at the beam area, upgrading of software for DAQ and "on-line" data analysis.

The subcontract R&D work for new photodetectors will be supported by ITEP in the next year. The measurements of optical properties for wall coating material will be continued at MRIOPM.

Part of ITEP group working at CERN will be involved in test beam test preparation at CERN SPS.

3.2.6. Plans for Continued R&D at IHEP in FY92

The further development of electronic readout schemes for the prototype beam tests will be continued as well as the development of a fast single channel readout system prototype with parameters similar to those required for SSC operation.

3.2.7. Plans for Continued R&D at TIFR in FY92

The TIFR group will expand their study on radiation damage to liquid scintillators, as it is presented in Addendum 1. If sufficient funds are available then one or more of TIFR scientists or engineers will come to ORNL or UMiss to assist in this work.

3.3. Beam Tests with LS Prototype Detector Plane and Module

The beam test of a rudimentary calorimeter using a single movable LS detector plane is planned at ITEP in February 1992. This rudimentary calorimeter is a stack of absorber plates with one instrumented LS detector plane (composed of 36 LS cells) which can be inserted at various places in the stack. The ITEP beam is normally incident on the face of the stack. Personnel from ITEP, UMiss and ORNL will carry out the test. The primary goal of the beam test is to measure the response of this rudimentary calorimeter with different absorbers (Pb, Fe, U) for pions, electrons and muons in the momentum range 0.5-6.0 GeV/c. Most importantly, this includes testing the readout system for the LS plane. The analysis of the beam test data will give us information about the e/h ratio (which is directly related to the constant term in the hadron calorimeter energy resolution), side and rear leak determinations, time dependence of the calorimeter response, signal/noise ratio and dynamic range of signals. Also the calibration system concept based on radioactive sources installed in each LS cell will be tested.

The next step will be a beam test at CERN of a prototype tower starting November 1992. In this test the energy resolution will be determined, the calibration system checked, the mechanical integrity tested (including leak testing, fiber/PMT interface testing and check-out of the liquid filling system) as well as determinations of the e/h ratio and testing of the readout system.

Chapter 4. MILESTONES

TABLE 12

Major LS R&D Milestones

1. MOU was approved by SSSL	05/91
2. Funds became available	08/91
3. Accomplish initial compatibility and radiation stability tests	09/91
4. Design and build a prototype detector plane	11/91
5. Beam test of a prototype detector plane in rudimentary calorimeter at ITEP test beam 1-6 GeV/c	02/92
6. Complete mechanical design of a full size prototype HC module	05/92
7. Beam test of a full size prototype HC module at CERN	11/92
8. Beam test of a full size prototype HC module with e-m section in front at CERN	03/93

Chapter 5. BUDGET

The following budget (Table 13) is presented on the premise that work will continue with currently available manpower. If the liquid scintillator calorimeter is selected as one of the primary options of the GEM collaboration, we expect an increase in the current effort, as well as an acceleration of the schedule. In such a case, the budget may require revision.

In the event that the GEM collaboration decides not to pursue the liquid scintillator calorimeter option, the current manpower will remain available to complete this R&D project. Some adjustment of the budget might be necessary, and will be negotiated with the SSCL. However, the need for completion of the work, resulting in publications and documentation is stressed.

In addition to the funds obtained from the DOE/SSC this R&D project is supported at a significant level by funds and resources of the collaborating institutions. This support will continue in FY92 with the level depending on the funding support of this request. We give below an estimate of additional funding and resources in FY91 other than those obtained from SSCL funds. This indicates a reasonably high anticipated level of such support in FY92.

ITEP

Salaries of several scientists, engineers and technicians were covered. The total FTE is estimated to be 12.5 in FY91. In addition, beam time, various materials and a certain amount of shop time has been made available for tests carried out at ITEP. Also ITEP had subcontracted several R&D tasks for Liquid Scintillator Calorimetry in Soviet industry in FY 1991 for the total of 268K Rubles (development of various photodetectors, optical measurements, electronics).

Lawrence Livermore Laboratory

LLNL provided internal discretionary funding in FY91 of about \$90K for R&D on liquid scintillator calorimetry. In addition, scientific manpower (about 0.3 FTE) was provided and incidental expenses (travel, publication, etc) were covered. This funding was tied to the \$75K in funding received from the SSCL in FY91. In this way LLNL was able to successfully reach all the major milestones outlined in the MOU.

TABLE 13

Liquid Scintillator R&D cost estimate in K\$

	FY 1992	FY 1993
Photometry	150	45
Cell prototyping	70	30
Tests of photodetectors	65	45
Electronics for prototype	140	115
Design of prototype	90	50
Construction of prototype	150	280
Beam tests	100	190
Calibration	30	50
Radiation damage tests	80	60
Simulations	80	80
Support for ITEP scientists at ORNL	150	150
TOTAL	1105	1095

The situation for funding in FY92 is similar to that for the previous year in that LLNL discretionary money can be made available for continuing the R&D plan as outlined above. However, this money, about \$100K- \$200K, is once again tied to the promise of support in the form of funding from the SSCL or the GEM collaboration R&D programs. In addition, one of the LLNL physicists (C.Wuest) maintains a separate source of funding for travel and incidental expenses (publication services, etc.) which can be drawn on for the R&D effort in FY92.

The University of Mississippi

The University of Mississippi has approximately \$50K in FY91 from the Texas Commission in support of this work. Additional support was provided from part of the continuing DOE grant funds (\$70K) and by means of the availability of shop time, computer time and faculty release time (\$90K). Thus, the total support provided via the University of Mississippi was \$210K in FY91.

ORNL

This project has been extensively supported with Director's exploratory funds. Support has been provided in the areas of electronics development, engineering, and scientific manpower. The cost of the US assignment of one of the principal investigators (Yu. Kamyshev) has also been covered from these funds. The total funding provided was \$285K in FY91.

Chapter 8. ORGANIZATION AND MANAGEMENT

This R&D activity is centered at ORNL. Strong contributions are also focussed at LLNL, The University of Mississippi and ITEP. Further help is provided by Mississippi State University, the University of Tennessee and TIFR.

Much of the activity is carried out at ORNL by ITEP personnel, who are on extended assignments. Assurances have been provided at the highest institutional levels by ITEP that this personnel will remain available at the current level throughout the lifetime of this R&D project.

ITEP will provide important testing facilities in the future. On-site staff is dedicated to this project and is involved in test preparations and in other support work.

Close contact is maintained between the primary collaborating institutions via frequent collaboration meetings, etc. The commitment of LLNL has recently been discussed at high institutional levels. Provided that this R&D project continues to be funded, LLNL resources will continue to be available, including sources of internal discretionary funds.

ORNL management is committed to the success of this project, and Director's discretionary funds will continue to be available through FY92. The project is being carried out under the auspices of the ORNL Detector Center (T. A. Gabriel, Director) and the ORNL Physics Division (F. Plasil, Section Head), with the encouragement of the Laboratory Director, A. M. Trivelpiece.

Radiation Hardness Study of Liquid Scintillator

Tata Institute of Fundamental Research, Bombay

We have planned to carry out radiation hardness studies of materials that would be used in a liquid scintillator detector. In the first instance, we have planned for studying the effect of MeV neutrons on the liquid and wavelength shifter fibre. We are at present using BICRON liquid BC 517 L and the wavelength shifter fibre BCF-99-01. A test module has been fabricated using stainless steel CONFLAT flanges with a square cavity for the liquid and four portholes. While one porthole is reserved for taking out the fibre, the other three will have an electronic pressure transducer, a stainless steel bellows and a stainless steel valve for filling the liquid attached to them. We will be studying two effects :

- (1) Change in light yield from the scintillator due to the radiation damage to liquid or the fibre or both.
- (2) Likely pressure buildup in the closed module due the decomposition of the liquid by radiation and consequent release of gases.

The irradiation to neutrons will be done at the research reactor Apsara in the Bhabha Atomic Research Centre, Bombay. Apsara is a swimming pool type research reactor in the Bhabha Atomic Research Centre. It uses a core of uranium rods enriched with ^{235}U in a pool filled with natural water. The core consists of a 7×7 matrix with fuels, graphite reflectors and cadmium control rods interleaved. The reactor normally operates at 300 KW. The reactor has a relatively small (~ 2) cadmium ratio indicating that the energy spectrum of the neutrons is fairly hard. The neutrons are thermalized quickly inside water so that the flux of high energy neutrons (of energy 1 MeV or above) drops off rapidly as one goes away from the core. The pool is covered all around by a 8 feet thick concrete wall except around one corner where the portion of the wall is detachable, it being on wheels and rails. This place is called the shielding corner. With the core positioned at a special position labelled C' in the pool near the shielding corner one can irradiate the object by placing it outside the reactor after 36 cm of water and a thin wall made of 0.3 cm thick stainless steel and 3.8 cm thick aluminium. With the core at C' position, the flux of neutrons of energy 1 MeV or above in the shielding corner has been estimated to

be 5.0×10^7 neutrons /cm²/sec with the reactor operating at 300 KW. Thus the shielding corner has been chosen as the suitable place for the irradiation of our liquid scintillator test module, to avoid the problem of immersing the module in water inside the pool. However, the thermal neutron flux at this position will be a factor of ~ 100 times higher. To cut down this thermal neutron flux, we are planning to have a shield of 3 mm cadmium sheet, which will cut down the thermal neutron flux to a negligible level.

After several discussions with scientists in charge of the reactor facilities at BARC, a detailed proposal for irradiating our liquid scintillator module at Apsara with the core at position C' was submitted in May 1991. Exposure to a fluence of 10^{13} neutrons /cm² was requested with the total duration of exposure being 56 hours on the basis of the nominal value of flux of 5.0×10^7 neutrons /cm²/sec mentioned above. The proposal has been duly approved by the Reactor Safety Committee. The exposure will be made over a period of 8 days since the reactor is operated only for 7 hours in a day. However a detailed measurement of spectrum and flux of neutrons will be made before the irradiation to determine the actual period of irradiation needed. The reactor is normally operated with the core in the middle of the pool far from the corner. The pending experiments with the core in the regular position at Apsara have to be completed. Also before moving the reactor core to the C' position extra biological shield in the form of several concrete blocks have to be provided outside the reactor around the place of irradiation. Because of these and other reasons the irradiation of the liquid scintillator module is scheduled to take place by middle of October 1991.

We have been studying the response of the test module to minimum ionising particles using cosmic muons. The wavelength shifter fibre of 2 meters length shaped into a spiral coil is immersed in the liquid and the ends which are brought out are attached to the face of a high gain photomultiplier using optical grease. The photomultiplier is operated at 2000 Volts and the corresponding current amplification factors are typically $1.0-2.0 \times 10^7$. The output from this photomultiplier is fed into a delay circuit for a delay of 85 nanoseconds and led to a Lecroy ADC mounted on a CAMAC crate. The trigger is provided by the coincidence of two plastic scintillators mounted above and below the liquid scintillator module. A gate width of 400 nanoseconds is used for charge integration. The CAMAC crate is connected to a PC through the GPIB interface. A data acquisition system has been set up to read out the ADC's using a polling mechanism. With the same fibre remaining

in the liquid for 40 days there has been no detectable change in the ADC spectrum due to cosmic muons. Thus the fibre (BCF-99-01) seems to be chemically compatible with the liquid BC 517L.

A 1 meter long fibre shaped into a helical coil of 1.5 cm diameter and 3.0 cm length was exposed to a beam of MeV neutrons in the Apsara reactor near the core. At this position the flux of MeV neutrons is high and had been measured to be 10^{10} neutrons /cm²/sec, when the reactor operates at 100KW. The fibre coil was wrapped in 0.5 mm thick cadmium foil to filter the thermal neutrons and irradiated for 20 minutes with the reactor operating at 100 KW. Thus it was exposed to a fluence of 10^{13} neutrons /cm². After irradiation it was taken out and examined visually. There was no change in colour and no visible damages. No transmission measurement was done as we do not have as yet a setup for it.

We have recently obtained Bicorn liquid BC 531. We have ordered the white paints NE 561 and BC 622A. We plan to get a few other different fibres. We propose to study radiation hardness of these materials also. For the liquid scintillators BC517L and BC517P and fibres BCF-99-01, BCF-91A, BCF-98 we intend to go upto fluence of 10^{14} neutrons per cm² in the future.

REFERENCES

- [1] Expression of Interest to the SSC Laboratory by the L* Collaboration, May 1990
- [2] Letter of Intent to the SSC Laboratory by the L* Collaboration, November 1990
- [3] Expression of Interest to the SSC Laboratory by the GEM Collaboration, June 1991
- [4] Expression of Interest to the SSC Laboratory by the EMPACT Collaboration, May 1990.
- [5] Liquid Scintillator Calorimetry
A Research and Development Proposal Submitted to SSCL
September 1990
- [6] BICRON data sheets
- [7] A.Savin, V.Shoutko, E.Shumilov, E.Tarkovsky
LTRANS - Monte Carlo Program (in preparation)
- [8] C.Hurlbut, Bicron, private communication
- [9] Hamamatsu, R2490-05 data sheets
- [10] R.Wigmans, Nucl.Instr.Meth. 259 (1987) 389
- [11] BICRON, product safety sheets
- [12] We are grateful to J.Walker and J.Harmon from University of Florida who provided us with liquid polysiloxane sample.
- [13] S.Majewski et. al, IEEE Trans.Nucl.Science,37(1990)513
- [14] E. Ables, et al., "Measurements of Optical Properties of Waveshifting Optical Fiber for Liquid Scintillator Hadron Calorimetry," UCRL-JC-106823, March, 1991 (Submitted to NIM).
- [15] B.Abbot et al., Scintillating Fiber Tracking Subsystem,
report at SSCL Detector symposium, Fort Worth, October 1990
- [16] T.Shimizu, KURARAY, private communication

- [17] Kuraray, WLS fibers data sheets
- [18] S.Burov et al., L3 Collaboration, CERN-EP/88-84; O.Adriani et al., L3 Collaboration , Hadron Calorimetry in the L3 Detector, NIM (1991)
- [19] Subsystem R&D for SSC tracking
Hybrid Central Tracking Chamber Collaboration, Al Goshaw, spokesman.
Scintillating Fiber Tracking Subsystem Collaboration, Muzafer Atac, spokesman.
Central and Forward Tracking Collaboration, Gail Hansen, spokesperson.
- [20] C. Wuest and R. Bionta, "Microgap UV Detector," LLNL Disclosure and Record of Invention No. IL-8790, July, 1991.
- [21] J.Del Peso and E.Ros, NIM A276 (1989)456-467
- [22] W.R.Nelson, H.Hirayama and D.O.Rogers, SLAC-265 (1985)

- Clear BCF - 98
- Clear BCF - 98 + LS (BC517P)
- ◇ WLSF BCF - 91
- ◆ WLSF BCF - 91 + LS (BC517P)

Fig.1. Transmission of 1 mm diameter 1 m long fibers vs irradiation dose (26 Mrad max) and annealing time relative to reference nonirradiated fiber.

◇ WLSF BCF - 91

◆ WLSF BCF - 91 + LS (BC-517P)

measured with green LED (550 nm) and Si photodiode
(relative to reference nonirradiated fiber)

Fig.2. Transmission of 1 mm diameter 1 m long fibers vs irradiation dose (6.4 Mrad max) and annealing time relative to reference nonirradiated fiber.

Fig.3. Measurement of Bicon BC622A reflecting paint for radiation damage. A sample was irradiated to 9 Mrad total dose over an 8 hour period using the LLNL Co⁶⁰ source. The measurement of the diffuse scattering efficiency as a function of laser illumination angle from the irradiated sample is shown along with a similar measurement from an unirradiated sample. Zero degrees corresponds to scattering directly back in the direction of the source, 90 degrees corresponds to scattering parallel to the surface of the sample. There is no significant difference between the irradiated and unirradiated samples.

Fig.4. Measurement of the near-normal specular reflectance of Bicon BC622A paint as a function of wavelength. Three painted samples are compared along with an unpainted bead-blasted aluminum sample.

Fig.5. Results of measurements at MRIOPM for diffusive paint reflection coefficient.

Fig.6. Schematic representation of the integrating sphere containing a coiled length of waveshifting fiber optic. The sphere is illuminated using a tailored spectrum approximating the emission of the liquid scintillator. Spectrally resolved and integrated measurements of the waveshifting fiber or integrating sphere are accomplished with silicon diodes or spectrophotometers by either connecting or disconnecting the fiber from the photodetectors.

Fig.7. Result of the measurement of the waveshifting fiber output (emission) as a function of incident light wavelength (excitation). Also shown in the figure is the spectrum of output light from the Bicron liquid scintillator. The waveshifting fiber is seen to be well matched to the liquid scintillator out to about 480 nm where its response drops to nearly zero.

Fig.8. Spectrum of light emitted from the end of WLS fiber measured with integrating sphere and spectrometer.

Fig.9. Schematic view of the setup for WLS fiber attenuation length measurements.

Fig.10. Schematic view of LS cell prototype.

Fig.11. Photograph of LS cell prototype.

Fig.12. Photograph of LS cell filling system.

Fig.13. Schematic view of cell test setup.

Fig.14. Photograph of LS cell prototype test setup.

Fig.15. Cell prototype light yield measurement results.

Fig.16. Fiber splicing schematic view.

Fig.17. Self triggered radioactive source spectra in LS cell.

Fig.18. Liquid scintillator hadron calorimeter side view.

Fig.19. Module shroud perspective view. Absorbers are set in slots in module walls.

Fig.20. Absorber installation.

Fig.21. Module assembly.

Fig.22. Design of sealing of module inner space. Thin sheet is welded to the module walls

Fig.23. Transport fiber routs inside the module.

Fig.24. Variant No 1 of PM seal by welding

Fig.25. Variant No 2 of PM seal with O-ring.

Fig.26. Variant No 3 of PM seal with two O-rings.

Fig.27. The fiber — PMT holder design.

Version 16-1 (192)

Support tube

Read out channels 192

Fig.28. One of version of HC module segmentation into cells (z-projection). The summing of cells to readout channels is shown with thin solid lines.

Version 16-1 (192)

Longitudinal segmentation - 8	
Cell type 1	90.4 × 90.4 mm
Read out channels	192
Fibers/photocathode 8, 16, 24, 32	
8	108
16	8
24	4
32	72
<hr/>	
Total	192

Fig.29. One of version of HC module segmentation into cells (ϕ -projection). The summing of cells to readout channels is shown with thin solid lines.

Fig.30. Perspective view of a module plane. Each of 12 trays contains 4 cell with WLS fiber inside.

Detail "A"
Scale 5:1

Fig.31. Drawing of assembled tray for LS cells.

Fig.32. Exploded view of LS detector tray.

Fig.33. Transport fiber routs through slots in absorbers.

Figure 1

Hamamatsu R2490

Fig.34. Hamamatsu R2490-05 PMT schematic view.

Fig.35. Graph of the gain and dark current versus magnetic field for Hamamatsu R2490-05 PMT.

BOX

CYLINDER

TOROID

Fig.37. Geometrical shapes built in the Light Transport code : rectangular box, cylinder and toroid.

Fig.38. Example of geometry for LS cell prototype designed with box, cylinders and toroids.

Fig.39. Light intercept efficiency in the cell vs ratio of WLSF surface to total surface inside the cell. Cell size - 5x5x0.5 cm³, 6x6x0.5 cm³, 8x8x0.5 cm³, 10x10x0.5 cm³. WLSF is made like spiral with 1, 2 and 3 turns. Cell walls are painted with BC-622A white paint.

Fig.40. The dependence of transmitted light intensity on the bending radius of transport fiber. That allows to choose the optimal bending radius for transport fiber.

Fig.41. Energy resolution vs hadronic jet energy simulated for a calorimeter consisting of a 50 cm BaF₂ section followed by a hadronic section (20 mm lead + 5 mm liquid scintillator) [2].

Fig.42. Schematic representation of two different UV detector concepts. Both detectors consists of a thin parallel plate gas avalanche counter optically coupled to a liquid or solid scintillator by a UV sensitive photocathode. The photocathode can either be semitransparent (transmission mode) as shown in the bottom diagram, or opaque (reflectance mode) as in the top diagram. The photocathode chosen for this detector is yttrium and is sensitive to photons with wavelengths shorter than 400 nm while being robust enough to expose to air or other gases. The photocathode is separated from the anode by a thin 100 micron gap filled with a gas of 90% argon and 10% methane. Note that in the diagrams the gas microgap is not drawn to scale and is greatly exaggerated for clarity.

Fig.43. Photograph of the UV microgap detector showing the yttrium photocathode and two different semitransparent anodes, 500 angstroms of chrome (mounted on the detector) and a stepped 200- 500 angstrom gold anode in the plastic case next to the detector. Also shown is Bicron's BC-599-06 310 nm emitting liquid scintillator.

5 keV ^{55}Fe xrays
Gain = 5×10^5

Fig.44. Oscilloscope photograph showing the characteristic pulses out of the micro-gap detector. The pulse shape is stretched by the amplification electronics and the rise time has been calculated, from the known electron drift velocity across the 100 micron gap, to be about 1 ns.

Fig.45. Layout of Pb/LS EM tower with WLS fiber running through several layers of LS between lead absorbers.

Fig.46. Cross section of e-m calorimeter tower. Spiral ring is between two adjacent absorber sheets.

Fig.47. Fiber routing in LS e-m calorimeter tower with longitudinal segmentation.

Fig.48. LS e-m calorimeter side view.

$$\Delta\varphi = \Delta\eta = 0.063$$

Fig.49. LS e-m calorimeter assembly.

r.m.s. 5.3%

Fig.50. The transverse uniformity of the LS readout segment (one WLS spiral) as it was simulated by LTRANS code for the tower with the front size of 30x30 mm².

MC simulation

Light transport
efficiency, %

Fig.51. Light transport efficiency from 4.5 mm LS layer to photocathode for conical 22-turn spiral of e-m calorimeter projected tower. (+ 2 m clear fiber with two 90° turns).

Fig.52. EGS4 code simulation of the performance of the EM array of 10x10 tapered towers with front size 30x30 mm². Wall thickness is 1 mm.

Fig.53. EGS4 code simulation of the performance of the EM array of 10x10 tapered towers with front size 30x30 mm². Wall thickness is 0.5 mm.

Fig.54. EGS4 code simulation of the performance of the EM array of 10x10 tapered towers with front size 30x30 mm². Wall thickness is 0.25 mm.

Fig.55. Photograph of the photometry dark box assembled at LLNL. Visible in the photograph are the input port from the pulsed nitrogen arc lamp, the monochromator, a NBS calibrated photodiode for high light level measurements and the calibrated "Quanticon" (Hamamatsu R2165) phototube for low light (< 10 pc) measurements. A number of feed-throughs allow for flexible operation of experiments inside the box.

Memorandum of Understanding

between

Liquid Argon Calorimetry Collaboration

and

**The Superconducting Super Collider
Laboratory**

FY 1991

MEMORANDUM OF UNDERSTANDING FOR FY 1991

between

LIQUID ARGON CALORIMETRY COLLABORATION

and

THE SUPERCONDUCTING SUPER COLLIDER LABORATORY

This memorandum of understanding between the Liquid Argon Calorimetry Collaboration and the Superconducting Super Collider Laboratory (SSCL) is intended solely for the purpose of providing a budget estimate and a work breakdown for the SSC Laboratory, the funding agencies, and the participating institutions. It is an agreement that is currently satisfactory to the parties. However, it is recognized and anticipated that changing circumstances of this evolving research and development program may necessitate revisions. The parties agree to negotiate amendments to this memorandum that will state such required adjustments. A short summary describing the research objectives of this experiment is given in Appendix I.

A. Personnel

The list of participating institutions, the names of the people in each (identifying the contact person and overall manager), and the percent of their time which will be dedicated to the project are listed below:

BNL	Howard Gordon - 50% Contact Person - Overall Manager Edward Kistenev - 50% Peter Kroon - 50% Hong Ma - 75% Don Makowiecki - 50% Veljko Radeka - 10% David Rahm - 75% Sergio Rescia - 10%
Rochester :	Fred Lobkowicz - 25% Contact Person Jan Ftacnik - 70% Ivan Horvath - 50% Gian DiLoretto - 25%
Maryland	Nick Hadley - 20% Contact Person Andris Skuja - 10% Drew Baden - 10% Doug Fong - 50% Hand Deud - 50%
LBL (SSCL)	Gerry Abrams - 100% Contact Person ✓ Chris Hearty - 95% Jim Siegrist - 10% Mark Turcotte - 50% Louis Villasenor - 100%
ORNL	Tony Gabriel - 5% Contact Person R.G. Alsmiller - 10% Peter Fu - 20%
Tennessee	Tom Handler - 10% Contact Person
Mississippi	James Reidy - 10% Contact Person L. Cremaldi - 10% B. Moore - 20%
Washington	Paul Mockett - 40% Contact Person Vic Cook - 30% Toby Burnett - 25%
Florida State	John Womersley - 15% Contact Person
Michigan State	Harry Weerts - 10% Contact Person
Adelphi U.	Robert Steiner - 50% Contact Person Dan Martin - 100% Joe Singh - 100%

Iowa State	John Hauptman -25% Contact Person M. Pang - 60% S. DeBoer - 50% A. Zinchenko - 50%
Arizona	John Rutherford - 20% Contact Person Andrew Nelson - 40%
SSC Liaison Person	Dr. Willi Chinowsky Physics Research Division M/S 2001 SSC Laboratory 2550 Beckleymeade Avenue Dallas, Texas 75237

B. Responsibilities for Research Tasks

In this section we give a brief overview of our R&D program for FY91. Any modifications from our original Liquid Argon Calorimetry subsystem proposal were made to adjust to different constraints and to accommodate suggestions given us from the SSC Laboratory. The long-term goals of our detector development project are summarized in Appendix I.

Task 1	Completion of A3 Beam Line (BNL)
Task 2	Operation of Test Beam (BNL)
Task 3	Fabrication of steel/lead stack (BNL)
Task 4	Electronics (BNL)
Task 5	Support of Accordion Tests (BNL)
Task 6	Radiation Damage to Components used in calorimetry (BNL)
Task 7	Studies of Cooling Preamps in Liquid Argon (BNL, Rochester, SSCL, Martin Marietta)
Task 8	R&D on Tiles (Michigan State U.)
Task 9	Support for Shielding Transformer; design studies for electron ID and forward calorimetry; and support of beam test. (Rochester)
Task 10	Fabrication of items for beam test (Maryland)
Task 11	Support for beam test (Maryland, Washington, Rochester, Florida State U., Adelphi U., Iowa State, Arizona)
Task 12	Electrical and Mechanical Design and Fabrication of a Test Beam EM Module (LBL(SSCL))
Task 13	Support for Simulation (ORNL, Tennessee, Mississippi, Iowa State, Arizona)
Task 14	Development of Calorimeter Segmentation based on Brite Pads (Washington)
Task 15	Fabrication of Signal Boards (Michigan State U.)

C. Test Beam Requirements

0.5 - 20 GeV $e^{\pm}, \pi^{\pm}$ beams up to $10^7/\text{sec}$

D. Special Considerations

- The contact person for the Liquid Argon Calorimetry collaboration, Howard Gordon, agrees to be responsible for equipment borrowed by our collaboration and will ensure its timely return.
- We understand that funding for this project will be provided in allocations of a single year, with successive year's funding dependent on successful progress to date and available funds as determined by an appropriate review process.

E. Milestones

Milestones for Liquid Argon Calorimetry research during FY91 are presented in this section. This R&D, if successful, will lead to:

April 30, 1991- Start of test beam program at BNL.

Sept 30, 1991- Measurement of e/π for lead/liquid argon calorimeter in the range of energies of 0.5 - 20 GeV/c. This should include both pure lead plates as well as lead plates clad with stainless steel. Also an electromagnetic prototype will be tested. (All collaborators)

Sept. 30, 1991- Further measurements of radiation damage to calorimeter components.

Sept. 30, 1991- Physical test of a concept for active cooling of preamps plus engineering analysis to be able to make decisions for specific experiments. (BNL, Rochester, Martin Marietta, SSCL(LBL))

Sept. 30, 1991- Further results on simulation of liquid argon calorimetry. (ORNL, Tennessee, Mississippi, Iowa State)

Sept. 30, 1991- Fabrication and test of a prototype BRITE pad array. (Washington)

Sept. 30, 1991- Developments for the shielding of transformers, progress on electron ID and forward calorimetry. (Rochester)

Sept. 30, 1991- Development of tiled electrodes (Michigan State)

F. Reporting

The collaboration will provide the SSC Laboratory with copies of all talks and publications resulting from this R&D project. A short interim progress report will be provided to SSCL by April 1991 and a detailed written report will be provided SSCL by September 1, 1991. Proposals for continued support with a budget for FY1992 are to be presented to the SSCL together with the report.

G. Funding

- In this section we specify the allocation of funds by institution and by research task as defined in Section B.

Table I
Sources of Research Funds (\$K)

	SSCL	Other
Capital equipment	800.	0
Operating funds	<u>473.</u>	
Total	1273.	

Table II
Distribution of Funds by Institution (\$K)

	Capital Equipment (SSCL)	Operating Funds (SSCL)
BNL	485	200
Rochester	55	57
Maryland	15	50
LBL(SSCL)	200	0
ORNL	0	30
Tennessee	0	10
Mississippi	0	10
Washington	35	51
Florida State	0	10
Michigan St.	10	0
Adelphi U.	0	5
Iowa State	0	30
Arizona	0	20
Total	800	473

Table III
Expenditures by Research Task (\$K)

	Capital Equipment	Operating Funds
BNL - Completion of A3 Beam Line	120	
BNL - Operation of Test Beam		60
BNL - Fabrication of steel/lead stack	140	
BNL - Electronics	75	
BNL - Support of Accordion Tests		<u>40</u>
BNL - Radiation Damage to Components		<u>100</u>
BNL - Cooling of Preamps(Subcontract to Martin Marietta)	<u>150</u>	
Rochester - Support of Test Beam		<u>57</u>
Rochester - Support for Cooling Preamps, Shielding Transformers, Connections	<u>55</u>	
Maryland - Fabrication of items for beam test	<u>15</u>	
Maryland - Support for beam test		<u>50</u>
SSCL(LBL) - Calorimeter Electrical and Mechanical Design	<u>75</u>	
SSCL - EM Prototype for beam test	<u>90</u>	
SSCL - Preamp cooling- convective solution	<u>35</u>	
ORNL - Support for simulation		<u>30</u>
Tennessee - Support for simulation		<u>10</u>
Mississippi - Support for simulation		<u>10</u>
Washington - Support of beam tests		<u>41</u>
Washington - Development of BRITE pads	<u>35</u>	<u>10</u>
Florida State - Support of Beam tests		<u>10</u>
Michigan State - Tile development	<u>10</u>	
Adelphi - Support of Beam Test		<u>5</u>
Iowa State - Support of Beam Test and Simulation		<u>30</u>
Arizona - Support of Beam Test and Simulation		<u>20</u>
Total	800	473

The SSC Laboratory has identified and selected the Liquid Argon Calorimetry project for funding. It is expected that the DOE/OSSC will provide the Liquid Argon Calorimetry Collaboration with \$473K of operating funds and \$800K in equipment funds in FY 1991 for the above described detector R&D project.

H. Signatures

The undersigned have agreed to fulfill to the best of their abilities the terms of this Memorandum of Understanding between the Liquid Argon Calorimetry Collaboration and the Superconducting Super Collider Laboratory.

AGREED

Liquid Argon Calorimetry Collaboration

Date

Howard Gordon, BNL

R. Schwitters, Director
Superconducting Super Collider Laboratory

IN CONCURRENCE

Date

R. Diebold, DOE OSSC

J. O'Fallon, DOE OHEP

Appendix I Physics Goals and Motivation

We believe the use of the liquid argon approach to calorimetry at the SSC will lead to the best performance for physics. Liquid argon has a number of important advantages: unity gain leading to straight forward calibration; linearity over full dynamic range; excellent uniformity; good energy resolution; minimal systematic variations; small fluctuations in the waveform; ease of segmentation; hermeticity; radiation hard; and the experience of many other large systems.[1] However, we have decided to work on a number of issues that need development before a serious design can begin for a SSC detector. The first is the choice of the absorber material. We know that uranium/liquid argon give $e/\pi \sim 1$. However, the use of uranium may prove to be too costly so we have begun an extensive beam test of lead/liquid argon in a beam at BNL in 1991. Studies have shown that thin iron cladding of the lead may further reduce e/π and we intend to test this concept this year also. We will also test a small EM prototype to show the uniformity across the gap between modules. A large simulation effort is also in progress both to understand the beam test results and to be able to extrapolate these data to other configurations. .

Also we are seriously studying solutions for cooling the preamps located in the liquid. This will be done by both tests of hardware and simulation to be able to extend the results of these tests to other configurations.

We also will work on other issues that need attention: radiation damage to components, transformer development, producing electrode structures, etc.

1. See for example: H. A. Gordon, "Liquid Argon Calorimetry for the SSC," Proceedings of the Fort Worth Symposium on Detector R&D for the SSC, Oct. 1990 (and references contained therein).

END

**DATE
FILMED**

3 / 4 / 92