**PROGRESS REPORT
ON
THE SEARCH FOR THE DECONFINED QUARK-GLUON PHASE
TRANSITION USING 2 TeV P-P COLLISIONS; THE SEARCH FOR
CRITICAL PHENOMENA IN MULTIFRAGMENTATION USING 1
GeV/NUCLEON HEAVY ION COLLISIONS; THE DEVELOPMENT
OF THE SOLENOIDAL DETECTOR (STAR) FOR THE
RELATIVISTIC HEAVY ION COLLIDER (RHIC)**

Prepared by
Department of Physics
Purdue University
West Lafayette, Indiana 47907
September 15, 1991
Project Period Jan. 1, 1991- Dec. 31, 1991
Grant: DE-FG02-88ER40412

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

JMP
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

1. Progress Report Synopsis	3
2. Fermilab Experiment 735, A Search for the Quark-Gluon Plasma	5
2.1 Introduction	5
2.2 Milestones set in 1991.	6
3. An Exclusive Study of Nuclear Fragmentation using the EOS-TPC	13
3.1 The Search for Critical Phenomena using the EOS-TPC.	13
3.2 Design and Construction of the EOS-TPC Beamline.	15
3.3 Results of the May 1991 Test Run	16
3.4 Extraction of Critical Indices from Small Percolation Lattices.	17
3.5 Time Line for 1992	20
4. Solenoidal Tracker At RHIC	21
4.1 Conception in 1990	21
4.2 Progress in 1991.	22
4.3 Time of Flight System	23
4.4 Scintillator TOF Schemes.	24
4.5 Silicon Avalanche Diodes.	25
4.6 Other Photomultiplier Technologies	29

1. Progress Report Synopsis

The investigation of the phase structure of hadronic matter is proceeding on three fronts. First the study of high density hadronic matter using 2 TeV $\bar{p}$ -p collisions is well into the analysis phase. In particular the E-735 data which has determined the dependence of π , K, and $\bar{p}$ transverse momentum (p_t) as a function of multiplicity $dN/d\eta$ can be interpreted in terms of transverse flow as possible evidence for a quark-gluon plasma. It's an open question whether minijet production is also able to explain this data. The flow analysis was reported by P. Levai and B. Müller, Physical Review Letters (PRL) 12 1519 (1991). Higher statistics p_t versus $dN/d\eta$ analysis is currently underway at Purdue and Notre Dame.

Further analyses based on E-735 data involve multiplicity studies at Purdue and Iowa State. Handbury-Brown, Twiss measurements using pions are being analyzed at the University of Wisconsin. A paper on λ and $\bar{\lambda}$ production is currently being prepared for publication.

The second front involves multifragmentation of nuclei. This mechanism which was first observed in the high precision proton nucleus inclusive studies by the Purdue group has been confirmed in exclusive studies at the Gesellschaft für Schwerionenforschung (GSI) and at Michigan State University (MSU). At GSI the energy deposition in heavy ion-heavy ion collisions was studied which confirms the power law $A^{-\tau}$ behavior PRL 10 1214 (1991). At intermediate impact parameters i.e. intermediate energy deposition, the observed minimum value of τ is in close agreement with the value expected for critical behavior. At MSU the overall fragment multiplicity seen in multifragmentation suggest that this process occurs from an expanded system where the nucleon density $\rho < 0.4 \rho_0$. (ρ_0 is the normal nuclear density). This value is close to the density region where critical phenomena

could occur. See PRL 12 152, (1991). Consequently our equation of state research program at LBL which focuses on critical behavior in multifragmentation is the mainstream in this field.

Finally the Solenoidal Tracker at the Relativistic Heavy Ion Collider proposal (STAR) has been accepted. This means that much larger volumes of very hot hadronic matter can be produced. If critical behavior occurs at RHIC, then the presence of new degrees of freedom could be observed by the onset of violent critical fluctuations. Fluctuations in the event by event production of antiprotons could be an example of such phenomena. The time scale for STAR is mid 1997 so that participation by the Purdue group which has been involved in the development of the proposal will accelerate in the immediate future with a focus on a high resolution Time of Flight system (TOF). During the spring and summer of 1991 simulations of such a high resolution TOF system was begun. The major design decisions for STAR must be made by late 1992. Thus STAR research questions must receive immediate intense attention during 1991-1992.

2. Fermilab Experiment 735, A Search for the Quark-Gluon Plasma

2.1 Introduction

E735 was proposed in 1983 as a dedicated search for the quark-gluon plasma at the Fermilab Tevatron. The experiment was motivated by intriguing results from UA1 and UA5 as well as theoretical suggestions that one should be able to form states of energy density of about 10 times that of normal nuclear matter in proton-antiproton collisions at $\sqrt{s} = 1.8$ TeV. At that time, lattice gauge calculations suggested that the phase transition from confined quarks and gluons to the deconfined state was first order, involving a large latent heat and a change from few degrees of freedom in the hadronic phase to many degrees of freedom in the QGP phase. Van Hove suggested that the correlation between average transverse momentum, $\langle p_t \rangle$, and the charged particle multiplicity per unit pseudorapidity, $dN_c/d\eta$, be used to search for evidence of the phase transition. In his picture, a rise in $\langle p_t \rangle$ vs. $dN_c/d\eta$, followed by a plateau, followed by a second rise, would signify the hadronic, mixed, and quark-gluon phases of nuclear matter, respectively. In such a small system transverse hadronic flow is unlikely. The observation of transverse flow could consequently indicate collisions between constituents, providing an indication of the quark-gluon degrees of freedom (See Section 1). E735 was designed to carry out this program as a function of particle type at the C0 collision region of the Tevatron. Charged particles were measured in two ways. A scintillator hodoscope, consisting of 240 elements, gave coverage over 6.5 units of pseudorapidity. The hodoscope gave a fast first estimate of the event multiplicity and was used for event selection on-line. A central tracking chamber, CTC, was used to provide more precise tracking information off-line. It covered 3.2 units of pseudorapidity. The

design and construction of the CTC was the responsibility of the Purdue High Energy Nuclear Physics group. The momentum of charged tracks was sampled by a small single arm spectrometer, consisting of tracking chambers and two time-of-flight arrays. Particle momenta from about 0.15 GeV/c to 2.0 GeV/c, depending on particle type, were measured. Typically, a few tracks per event entered the spectrometer. A short 3 month test run was made during the spring of 1987. At this time, the CTC was still under construction. Final installation of the apparatus was made in May, 1988, followed by a full year of running.

2.2 Milestones set in 1991.

The Purdue High Energy Nuclear Physics group had sole responsibility for the analysis of the CTC data. This required the development of sophisticated pattern recognition algorithms and criteria for identifying 'primary' tracks, i.e., those tracks originating from the beam-beam interaction. Graduate student Charles Allen has played the leading role in this project. During this past year, he has performed a detailed comparison between the data and a GEANT simulation of the E735 experiment. This simulation was developed by the Purdue High Energy Nuclear Physics group and distributed to all members of the E735 collaboration. The complexities of the experimental data have made comparison to such a simulation a necessary part of the E735 analysis. Furthermore, it has proven to be essential in the debugging of the sophisticated analysis programs developed for the analysis of the data. Charles Allen will receive his doctorate in September, 1991. Below we briefly discuss some results from his analysis.

The two major quantities the CTC measures are multiplicity and the pseudorapidity density in the range $|\eta| \leq 1.6$. The multiplicity is independently measured by a scintillator

hodoscope that covers the range $|\eta| \leq 3.5$ but with a much coarser grain. The CTC is able to resolve two tracks separated by 3 mm in the xy plane. In terms of multiplicity, the CTC is able to measure total charged multiplicity in the CTC up to approximately 100, corresponding to $\frac{dN_c}{d\eta} = 30$.

For the multiplicity analysis, approximately 150,000 minimum bias events were used. Two separate algorithms were implemented to extract the true multiplicity into the CTC volume, giving the results show in Figure 1.

Figure 1 Charged primary multiplicity into the CTC volume.

The CTC measures the z coordinate by charge division. For mechanical reasons, a relatively low resistance ($190 \, \Omega/\text{m}$) sense wire material was used. This limited the intrinsic z resolution to approximately 4 cm. The CTC measured a typically 10 cm long track length.

In addition, capacitive crosstalk between the sense and field wires introduced a systematic shift in the measured z . A correction was developed that works at a statistical level, but it is still unclear how well it works on a track by track basis. The result is that the z coordinate of hits, and hence the pseudorapidity of tracks, is not well known. Still, one can calculate the pseudorapidity density as a function of pseudorapidity. The value at $\eta = 0$ is expected to be fairly good, since the z correction is minimal there. Figure 2 shows what the CTC measures for $\frac{dN_c}{d\eta}$ versus η for $\bar{p}$ -p collisions averaging over all multiplicities.

Figure 2 Pseudorapidity density in the CTC vs pseudorapidity.

A second major analysis effort has been conducted by Philip Cole, our graduate student based at Fermilab. He has analyzed spectrometer information and is examining the relationship between $\langle p_t \rangle$ and multiplicity for pions and antiprotons. During the past year, he has analyzed approximately 15 million events, using both the Fermilab Amdahl and Vax cluster computers. A large part of this analysis involves corrections for the geometrical acceptance of the spectrometer, tracking inefficiencies, and other subtle effects. We have used the GEANT simulation of the experiment to study these effects and to correct the data. Uncorrected and corrected transverse momentum distributions are shown in Figure 3 for pions and kaons. The corrections are substantial for the lowest p_t bin measured. After the above corrections have been applied, the average transverse momentum can be computed as a function of the multiplicity interval. The multiplicity has been measured using two different devices, the scintillator hodoscope and the Central Tracking Chamber. Shown in Figures 4 and 5 are $\langle p_t \rangle$ vs. charged rapidity density for various particle species. These results will comprise the major portion of Philip Cole's Ph.D. thesis which will be completed in September, 1991.

Figure 3 p_t spectra for π and K acceptance uncorrected (a) and corrected (b)

Figure 4 $\langle p_t \rangle$ vs multiplicity for π 's

Figure 5 $\langle p_t \rangle$ vs multiplicity for antiprotons

3. An Exclusive Study of Nuclear Fragmentation using the EOS-TPC

3.1 The Search for Critical Phenomena using the EOS-TPC.

The Purdue High Energy Nuclear Physics group has initiated an experimental program to study multifragmentation at the Lawrence Berkeley Laboratory Bevalac. Heavy ion projectile beams at 1 GeV/nucleon will bombard light targets. The resulting projectile fragments will be detected in a Time Projection Chamber, TPC, and other ancillary detectors, permitting the determination of the charge and momentum of all of the interaction products on an event-by-event basis. The unique features of this experiment are:

- the use of reverse kinematics, i.e., a heavy projectile incident on a light target. All of the interaction products have essentially the same velocity and are carried forward into the TPC.
- the development of a new detector, the Equation Of State (EOS) TPC. This device is being built by the Relativistic Nuclear Physics group at LBL.
- the characterization on an event-by-event basis of the nature of the interaction.

This last point is detailed below.

The Purdue High Energy Nuclear Physics group has a long history of working in the field of nuclear fragmentation. Our previous inclusive studies have led us to suggest the analogy between nuclear fragmentation and a liquid-gas phase transition occurring in a van der Waals gas. Recently, Campi has analyzed 400 exclusive gold-emulsion events and concluded that nuclear fragmentation has the characteristics of a critical phenomenon. The experiment we will conduct at the Bevalac could allow us to extract the critical exponents

describing the phase transition. Using the EOS-TPC, the time of flight wall and a Multiple Sampling Ionization Chamber (MUSIC), the momentum and charge of each projectile fragment will be determined. Events can then be characterized as subcritical, critical, or supercritical. Further physics details can be found in our proposal submitted to LBL.

Our experiment is part of a larger program of the EOS-TPC group, of which the Purdue High Energy Nuclear Physics group is a part. In fact, we are participating in two additional experiments, both of which concentrate on flow effects in nuclear matter at Bevalac energies. All of these experiments will begin running in the latter half of 1991. At present we have three graduate students, James Elliott, Mark Gilkes, and Penny Warren, who will obtain Ph. D. theses from the fragmentation experiment. In addition, Eric Hjort, a post doctoral research assistant is stationed at LBL to participate in the hardware and software development of the EOS-TPC system.

The primary responsibilities of the Purdue High Energy Nuclear Physics group are:

- design, testing, and installation of the beam line between the last quadrupole magnet and the TPC. This includes beam-defining scintillation detectors and a gas ionization detector to distinguish beam particles from multifragmentation interaction products. The beam line will be used in all of the TPC experiments. A brief description of this portion of the apparatus follows in the next section of this report.
- simulations for calculating track reconstruction efficiencies.
- development of analysis techniques for extracting the critical indices from the data.

- participating in the other two TPC experiments. This will include running shifts, maintaining detectors, and analyzing data.

The three TPC proposals were accepted by the Program Advisory Committee at LBL in June 1990. The experiments will begin running in the first half of 1992.

3.2 Design and Construction of the EOS-TPC Beamline

A vacuum beamline for the EOS-TPC series of experiments at Lawrence Berkeley Laboratory was designed and built at Purdue. This line will be installed after the last Bevatron magnet and will terminate inside the superconducting dipole magnet. The beamline will house a series of detectors and a target changer. These detectors comprise part of the trigger system. The function of each detector requires a particular placement for it along the line. For example, the PLUTO beam vectoring detectors need to be separated by a relatively large distance to maximize the accuracy in determining the angle of the beam in its approach to the target. The S2-V2 detector, for beam centering, must be as close to the target as the stray magnetic field allows.

The beamline is shown in Figure 6. The stainless steel 4-way crosses were made commercially. The mating flanges on these crosses were later modified for pumping ports and feedthroughs for the light guides on the S2 and V2 scintillators. The target changer sits in its own custom housing. The gas detector is mounted on a special low mass flange.

The method of assembly is compatible with the type of coupling used at the LBL Bevatron. A system for supporting and leveling the beamline was built at Purdue and consists of a pair of aluminum rails on which sit tables bearing jack screws. Once in place in the experimental area, the beamline is expected to operate at a fore vacuum.

Figure 6: Beamline assembly

The gas ionization detector, located directly downstream of the target, is the last detector through which the beam passes before entering the TPC. It is used as a slow veto detector in the on-line trigger logic to reject beam projectiles which have not undergone a nuclear collision. It features a low mass design, employing plexiglass and aluminized mylar, a Frisch grid, and a field cage for shaping the electrostatic field in the drift region. This detector was designed and built during the winter and spring of 1991.

3.3 Results of the May 1991 Test Run

During May 1991, the detectors in the trigger system and the PLUTO detectors were tested at the LBL Bevalac using niobium and gold beams. The individual detectors were examined, the trigger system was tested, and target-in/target-out ratios were determined.

The ionization chamber performed well. The observed resolution, $\Delta Z/Z$, was 2% and 1.5% for the niobium and gold beams, respectively. Thus we will be able to reject those beam particles which have not undergone a nuclear interaction. A primary goal of the test run was to determine what fraction of triggered events originate in the target, and what frac-

tion originate in materials other than the target. The number of target fragmentation events was determined from the energy loss spectrum observed in the ionization detector. Shown in Figure 7 is the spectrum for target in and target out runs. Target-in/target-out ratios were 1.6 for a gold beam on a gold target and 1.8 for a gold beam on a niobium target. This is in agreement with calculated values 1.5 and 1.9, respectively. This target-in/target-out ratio can be improved significantly by reducing the mass of the upstream detectors, especially S2.

The PLUTO beam vectoring detectors using photodiodes and plastic scintillator were also tested. A position resolution of about 1mm FWHM was measured for the 600 MeV/nucleon gold beam over a limited area. Scintillating fibers coupled to photodiodes were used in the trigger for on-line calibration. The detectors are presently being modified to increase their sensitive area.

3.4 Extraction of Critical Indices from Small Percolation Lattices

Previous inclusive studies have suggested the analogy between nuclear fragmentation and a liquid-gas phase transition in a van der Waals gas. This analogy has been confirmed by the GSI and MSU groups (See Section 1). Campi analyzed exclusive gold-emulsion events by comparing the moments of percolation simulations and the moments of the data. He concluded that nuclear fragmentation has the characteristics of a critical phenomenon.

In modern phase transition theory, all physical quantities depend on the critical exponents: α , β , γ , σ , and τ . With any two, we can derive the others. We can extract these critical exponents by exploiting the properties of the moments:

$$M_k = \sum_s s^k n_s \quad (1)$$

Figure 7: Ionization Chamber Spectra

For percolation lattices:

$$M_2 \propto |p - p_c|^{-\gamma} \quad (2)$$

thus γ can be determined by plotting $\log (M_2)$ vs. $\log |p - p_c|$, where M_2 is the second moment and $|p - p_c|$ is the probability minus the critical probability, and determining the slope. Problems arising due to the finite size of the lattices can be alleviated by altering the value of p_c from its theoretical value.

An exclusive nuclear fragmentation experiment will not explicitly determine a probability, p , so the above method will not work directly. However, taking advantage of the approximately linear relationship between M_0 (or M), the multiplicity, and p in the critical region, i.e., $p \approx aM + b$, we substitute M for p in equation (2):

$$M_2 \propto |M - M_c|^{-\gamma} \quad (3)$$

Plotting $\log (M_2)$ vs. $\log |M - M_c|$ and determining the slope would determine the critical exponent γ .

Similar methods apply for determining β :

$$P \propto |p - p_c|^\beta \quad (4)$$

therefore:

$$P \propto |M - M_c|^\beta \quad (5)$$

Plotting $\log (P)$, where P is the largest cluster, or the largest fragment, vs. $\log |M - M_c|$ and determining the slope yields β .

The critical exponent τ can also be determined in a more straight forward manner. In general, equation (2) is written as:

$$M_k \propto |p - p_c|^{\left(\frac{\tau - k - 1}{\sigma}\right)} \quad (6)$$

Plotting $\log (M_3)$ vs. $\log (M_2)$ and computing the slope we find:

$$\frac{\Delta \log (M_3)}{\Delta \log (M_2)} = \frac{4 - \tau}{3 - \tau} \quad (7)$$

which does not directly depend on the probability.

The important issue which we are currently addressing is how to extract the critical exponents from nuclear fragmentation data. To this end, we have first attempted to use the above methods to extract the critical indices from small percolation lattices. By studying the behavior of the above relations in small lattices, we have been able to develop a systematic procedure for the extraction of the critical exponents. Our studies indicate that it should be feasible to extract the critical indices from the experimental data.

3.5 Time Line for 1992

- Installation of TPC and beamline Oct.-Nov. 1991
- Testing of TPC Nov. 1991
- Final test runs Feb. 1992
- Fragmentation experiment block running time Mar. - Dec. 1992

4. Solenoidal Tracker At RHIC

4.1 Conception in 1990

In June, 1990, a collaboration formed with the goal of proposing, building, and operating an experiment on particle and jet production at RHIC. The primary emphasis of this experiment is large solid angle coverage about midrapidity with hadron identification. The physics objectives include:

- identified particle production at $0.1 \leq p_t \leq 1.5$ GeV/c particularly particle spectra,
- fluctuations in energy, entropy, multiplicity, and transverse momentum,
- flavor composition, including multiply strange baryons,
- particle correlations and identical particle interferometry (HBT) with π , K, p,

With the very high multiplicity events available at RHIC, most of these topics (except multiply strange baryons and K and p interferometry) can be studied on an *event-by-event* basis. A large acceptance hadron experiment at RHIC provides an unprecedented opportunity to observe statistically significant ensembles of particles *in individual events*, and do exclusive event characterization.

An additional goal was to study hard QCD and rare processes in event ensembles, specifically:

- jet production and jet quenching in a quark-gluon plasma (QGP),

The experiment was designed with a large cylindrical Time Projection Chamber (TPC) 2 meters in radius, 5 meters in length. This will fit inside a superconducting solenoid magnet with an axial field of strength 0.5 Tesla. The inner radius of the TPC will be 0.5

meter; inside this is a Silicon Vertex Tracker (SVT). Between the TPC and magnet is a Time Of Flight (TOF) system with >10,000 channels. Outside the solenoid is a layer of Pb/scintillator EM calorimetry 20 radiation lengths thick. The solid angle coverage chosen for the particle identification (TPC + TOF) was $|\eta| \leq 1$ and 2π in azimuth.

4.2 Progress in 1991

In the past year this collaboration adopted the name STAR (Solenoid Tracker At RHIC) with John Harris as spokesman. An updated Letter of Intent was submitted to BNL in July, 1991. After lengthy negotiations, the RHIC Letter of Intent #3 collaboration merged with STAR in August. *In September, 1991, STAR became the first (and at present, only) approved experiment at RHIC.*

The major changes in the Update were to:

- expand pseudorapidity coverage to $|\eta| \leq 4.5$ by the addition of tracking chambers external to the magnet (without particle identification),
- reduce the cost of the Time Projection Chamber (TPC) electronics, and
- modify the Silicon Vertex Tracker (SVT) to use a silicon drift chamber technique.

Definitive simulations demonstrated that the TPC would not suffer undue distortions due to space charge build-up, even at luminosities 50 times the initial RHIC design goal. A tracking algorithm was shown to reconstruct the momentum of well over 90% of primary tracks for very high multiplicity events. Two interactions in a bunch crossing are usually separable by vertex position. Events that pile up within the 50 μ s drift time of the TPC are also resolvable. Members of STAR have built and operated TPC's at the CERN (Center for European Nuclear Research), and the TPC at BNL (Brookhaven National Laboratory). The

EOS-TPC at the LBL Bevalac is also under construction by members of the collaboration, using many of the design features proposed for the STAR TPC.

4.3 Time of Flight System

The Time Of Flight (TOF) system has been one of the most troublesome areas of the STAR design. Particle identification is required to characterize RHIC events, particularly on an event-by-event basis. For example, π , K, and p momentum spectra could indicate a temperature for an event, and particle ratios could indicate changing quark content in the final state products. Critical fluctuations in baryon content may be a signature for the phase transition from the QGP to a hadron gas, in analogy with the critical behavior of phase transitions in other systems. Particle identification requires a momentum measurement and an independent determination of either the ionization energy loss (dE/dx) or velocity (via time of flight). To cover the momentum range from 0.1 GeV/c to 1.5 GeV/c in $|\eta| \leq 1$ in STAR requires both techniques. The TPC will measure dE/dx , which identifies particles with momentum $0.1 < p_T < 0.6$ GeV/c. The goals for the TPC-TOF blended system are:

- to cover of the pseudorapidity range $|\eta| \leq 1$ subtended by the barrel surface of the TPC,
- identify π 's with momentum $0.3 < p_T < 1.5$ GeV/c, K's with momentum $0.3 < p_T < 1.5$ GeV/c, and p's with momentum $0.3 < p_T < 2.3$ GeV/c,
- provide a fast event trigger sensitive to charged particle multiplicity in the central region.

The technical requirements posed by these goals are challenging. The timing resolution needed is $\sigma < 100$ ps, and the system should cover a $60 m^2$ area. The TOF system is

inside the solenoid coil and cryostat to minimize secondary particles, particularly photon conversions; this means the TOF system must function in the 0.5 T magnetic field.

No definite design for the full TOF system has been adopted. Several approaches are under consideration, including plastic scintillators and photodetectors, silicon avalanche diodes (AVD's), and Pestov counters. The High Energy Nuclear Group is pursuing several avenues to help develop a TOF system for STAR.

4.4 Scintillator TOF Schemes

Scintillators and photodetectors are the closest to established technology, and there are several designs using this basic technology. One design featured in the Update to the RHIC Letter of Intent uses 9900 scintillator slats 42 cm x 1.5 cm x 1.5 cm to cover the 60 m^2 area. These could be viewed with mesh dynode photomultiplier tubes (PMT's) that operate in the magnetic field, or the scintillation light could be piped out of the field by optical fibers to conventional PMT's. The problems with these schemes are cost (Hamamatsu tubes cost >\$1000 each) and time resolution. The photoelectron transit time spread (TTS) of mesh dynode PMT's is a factor of 2-3 worse than conventional PMT's. The inefficient light collection by optical fibers would reduce the intensity of the light pulse on conventional PMT's, located outside the magnetic field. These issues are under investigation.

Another novel idea uses multiple layers of crossed scintillator slats 5 to 7 meters long, 1.5 cm x 1.5 cm, to cover the TOF area. One scheme that has been studied employs 6 layers, with 750 slats in each layer. A total of 9000 PMT's would view both ends of each slat, outside the magnetic field. The scheme works by requiring a TOF signal for any particle in only a minimum of 3 out of a possible 12 (= 6 layers x 2 ends) PMT's. This redundancy

compensates for the loss of information due to an average of 2 hits per slat per layer. M. Tincknell and undergraduate student T. Keaffaber conducted an extensive Monte Carlo and analytic study of this scheme, and confirmed that the efficiency is near the theoretical maximum. More work is required to understand the time resolution available from 7 m long scintillators.

4.5 Silicon Avalanche Diodes

Silicon avalanche diodes (AVD's) are being investigated as a generic R&D project. Avalanche photodiodes 0.5 cm x 0.5 cm have been purchased from EG&G ElectroOptics, Montreal, for laboratory tests of their time resolution. Thin (0.15 mm thick) silicon p-i-n diodes will be exposed directly to fast charged particles (initially β 's), and the internal electric field in the diodes will collect electrons and holes deposited in the silicon by dE/dx . The avalanche region at the diode junction will give a current gain of 20 to 50, and a series of fast amplifiers will boost the signal by another factor of 1000. The resulting current pulse will have a rise time of about 2 ns, duration 5 ns, and an amplitude of 1.5 V. These signals will be processed by leading edge discriminators and both time and amplitude signals will be recorded. This system has a 9 ps time dispersion. The detectors are very low mass and are insensitive to 1 T magnetic fields. Time resolution of significantly less than 100 ps is anticipated. A description of the diode design and pre-amplifier module, which are being built by EG&G, Montreal (R. J. McIntyre), is given below.

The diode is a 5 x 5 mm silicon APD of the reach-through design. Typical diode parameters are: diode capacitance -21-25 pF; diode dark current - $I_{ds} = 200 \mu A$; $I_{db} = < 100$ pA; $I_{total} = I_{ds} + MI_{db}$. Effective k value = 0.02. (For a fuller description of the diode and

its properties see, for example, Petrillo et al., IEEE Trans. Nucl. Sci., vol. NS-31, no. 1, pp 4127-423, Feb. 1984.). A schematic profile of the reach-through diode is shown in Figure 8.

The diode impulse response function, for a delta-function source such as a minimum ionizing particle (MIP) which generates e-h pairs uniformly along a line perpendicular to the junction, is a current pulse having an approximately trapezoidal shape with rise and fall times equal to the electron transit time, τ_e , a FWHM equal to the hole transit time, τ_h , and a peak amplitude equal to $NweM/\tau_h$, where N is the number of e-h pairs generated per unit length (80-100 per μm), w is the width of the "drift" region (120-130 μm), e is the electronic charge, and M is the average effective gain. These transit times depend on the operating voltage but are expected to be in the range of about 1.5-2 ns for τ_e and about 2-4 ns for τ_h . In the frequency domain, this is equivalent to a frequency response given by:

$$M(\omega) = M \left[\frac{\sin\left(\frac{\omega\tau_e}{2}\right)}{\frac{\omega\tau_e}{2}} \right] \left[\frac{\sin\left(\frac{\omega\tau_h}{2}\right)}{\frac{\omega\tau_h}{2}} \right]$$

This expression has a 3 dB frequency response in the 90-120 MHz range. Thus not a lot is to be gained in time response by using a preamp much faster than this. Since the preamp noise current is proportional to $B^{3/2}$, where B is the preamp bandwidth, a wider bandwidth only means a poorer signal-to-noise ratio. Accordingly, we have chosen the preamp bandwidth to be about 100 MHz. This is expected to stretch the current pulse FWHM by a factor of approximately $2^{1/2}$.

It should be pointed out that the primary e-h pairs generated by a MIP are all in a cylinder of the order of a few μm 's in diameter. Some space-charge saturation effects are ex-

pected which will mean that the effective gain will be less than the low-signal gain. The magnitude of this gain compression is not known at present; it could turn out to be either beneficial, by reducing timing jitter due to gain non-uniformities, or major source of timing jitter if some of the MIP's pass through the diode at an angle such that their charge cloud is spread out and the gain saturation reduced. One of the objectives of the proposed experimental evaluation should be to demonstrate whether or not this is a serious limitation.

The preamplifier is a transimpedance preamplifier with a feedback resistor of about 3000Ω and a GaAs FET as the input transistor. The circuit diagram is shown in Figure 9. Other parameters are shown in Table I:

Table 1: Parameters

Voltages Required	$\pm 5V$
High Voltage:	To be determined, but likely to be in the +300 to +500 volt range. Note that an earlier suggestion by us to change the polarity, in order to remove the bypass capacitor from the path of the particles, has been abandoned. Instead, we have moved this capacitor to the side, as shown in the drawing, and in fact added a second capacitor, in order to minimize jitter resulting from signal propagation times across the diode. We are also investigating the possibility of coating the p^+ surface of the diode with a thin metallic layer to reduce its spreading resistance. If this seems feasible, we will leave part of the diode uncoated so that calibration using optical inputs is still possible.
Output Impedance:	30Ω
Amplifier 3 dB Bandwidth:	$\sim 100 \text{ MHz}$
Maximum Noise Voltage (expected to be at about the 3 dB frequency):	$40 \text{ nV/Hz}^{1/2}$
Total Integrated Noise Voltage:	$\sim 0.5 \text{ mV}$
Expected signal from a MIP at an effective gain 50:	$\sim 50\text{-}60 \text{ mV}$ in a pulse with a FWHM of about 4-5 ns
Expected main source of timing jitter:	Gain non-uniformity across the diode, expected to be about $\pm 5\%$ typical, $\pm 10\%$ maximum, at a gain of 50. If this proves to be a problem, it may be reducible using constant-fraction electronics. As discussed above, gain non-uniformity should also be suppressed somewhat by the space-charge induced gain-compression.

4.6 Other Photomultiplier Technologies

One photodetector that operates well in strong magnetic fields, and has outstanding photoelectron transit time spread (TTS), is a microchannel plate photomultiplier (MCP-PMT). These devices have gains of $\gg 10^3$ per stage, and quantum efficiencies $> 10\%$. The main problem is cost (MCP-PMT's from Hamamatsu cost \$7000). M. Tincknell has been in contact with several vendors to obtain performance data, and discuss the feasibility of unit costs $< \$1000$ for a large number of elements. These discussions will continue.

Fig. 8 Diode Schematic

Fig. 9 Preamplifier Schematic

NOTE:

1. - ALL RESISTORS VALUES ARE IN OHMS UNLESS OTHERWISE NOTED.
2. - ALL CAPACITORS VALUES ARE IN NANOFARADS UNLESS OTHERWISE SPECIFIED.

END

**DATE
FILMED**

2 / 20 / 92