Energy

NO-HA-KV-BMS-20C

155
2-12-92 JS

6/3/10

DOE/ID/12830-2
(DE92005060)

DEVELOPMENT AND EVALUATION OF A WORKPIECE TEMPERATURE
ANALYZER FOR INDUSTRIAL FURNACES

Phase I-A

November 1991

Work Performed Under Contract No. FC07-89ID12830

For
U.S. Department of Energy
Office of Industrial Technologies
Washington, D.C.

By
Surface Combustion, Inc.
Maumee, Ohio

and

Textron Defense Systems
Everett, Massachusetts

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

DOE/ID/12830--2

DE92 005060

**DEVELOPMENT AND EVALUATION OF A WORKPIECE TEMPERATURE
ANALYZER FOR INDUSTRIAL FURNACES**

Phase I-A

November 1991

**Prepared for the
U.S. Department of Energy
Assistant Secretary for Conservation and Renewable Energy
Under DOE Idaho Field Office
Contract No. DE-FC07-89ID12830**

**Prepared by
Surface Combustion, Inc.
Maumee, Ohio 43537
and
Textron Defense System
Everett, Massachusetts**

ABSTRACT

The Workpiece Temperature Analyzer (WPTA) is a unique approach for measuring bulk temperature for metallic materials. It applies polarizing interferometer technique with an impulse laser to measure time-of-flight (TOF) for ultrasonic waves and converts these measurements to bulk temperatures. It has potential applications for controlling or monitoring several metallurgical heat treatment processes.

During Phase 1A of the development program a bench scale unit was built and operated. The TOF for a variety of materials such as carbon steel, stainless steel, brass and aluminum were measured at room temperature as well as elevated temperatures up to 1875°F in some cases. The measurements were made for various thicknesses ranging from 1/4" to 3".

The instrument was modified to improve signal to noise ratio, and to accommodate speckle phenomenon associated with diffusive surfaces. Normal equipment vibrations in the industrial environment did not adversely affect the measurements. On the contrary, they were beneficial and allowed to eliminate one of the two photomultipliers.

The testing has demonstrated technical feasibility of the concept. Further development work is planned to investigate reproducibility and accuracy of measurements.

TABLE OF CONTENTS

<u>Section</u>	<u>Page No.</u>
List of Illustrations	iv
List of Tables.	vii
Executive Summary	viii
1.0 INTRODUCTION.	1
1.1 Background	3
1.2 Objective.	12
1.3 Benefits	13
2.0 DESCRIPTION OF EQUIPMENT AND MATERIALS.	14
2.1 Assembly of Test System.	14
2.2 Metal Samples.	17
3.0 RESULTS	21
3.1 Initial PI Concept Tests - No Ultrasound Generation. . .	21
3.2 Ultrasound Generation by PZT - Detection by PI	27
3.2.1 Diffusive Surfaces.	30
3.3 Ultrasound Generation by IL - Detection by PZT	33
3.4 Ultrasound Generation by IL - Detection by PI.	36
3.5 Rayleigh Waves Generation by IL.	42
3.6 System Performance Optimization.	45
3.6.1 Compact PI.	45
3.6.2 Signal Processing Implementation.	47

TABLE OF CONTENTS CONTINUED

<u>Section</u>	<u>Page No.</u>
3.7 Temperature Tests.	51
3.7.1 Room Temperature Tests (All Samples).	51
3.7.2 Aluminum Samples.	56
3.7.3 Brass Samples	59
3.7.4 Stainless Steel Samples	59
3.7.5 Carbon Steel Samples.	63
3.8 Physical State Tests	63
3.9 Market Assessment.	66
4.0 CONCLUSIONS	68
5.0 RECOMMENDATIONS	70
6.0 REFERENCES.	71

LIST OF ILLUSTRATIONS

FIGURES

<u>Number</u>	<u>Title</u>	<u>Page No.</u>
1	Soundwave Propagation and Detection Modes	5
2	Schematic Illustration of Ultrasound Generation and Detection. Two Configurations Are Presented Depending on the Location of the Detection System (PI)	7
3	Schematic drawing of the Workpiece Temperature Analyzer (Single-Sided)	8
4	Advanced Workpiece Temperature Measurement System	9
5	Motion Sensing Polarizing Interferometer	15
6	Experimental Setup for Temperature Tests	16
7	Combination of Two 90 deg. Apart Phototubes Signals on X-Y Oscilloscope	22
8	Glass Wheel with Multiple Wedges Used in the Shakedown Tests	24
9	Signals from the Two Phototubes Through the Glass Wheel Sectors	25
10	Frequency Response Test of the Phototubes (Photodiodes)	26
11	Ultrasound Generated by PZT and Detected by the Polarizing Interferometer (PI)	28
12	Validation tests of the PI Performance (a) PI Signal Beam Blocked (b) PI Signal Beam Open	29
13	PI Signal Variation with the Strength of the PZT Generated Ultrasound	31
14	Laser Speckle Phenomenon (from Ref.5) (a) Image of Rough Object Formed with Coherent Light (b) Physical Origin of Speckle for Free Space Propagation	32
15	PI Detection of PZT Generated Ultrasound through Target with Diffusive Surface	34
16	Target Setup for Impulse Laser (IL) Generation of Ultrasound and Detection with the PZT	35

LIST OF ILLUSTRATIONS

FIGURES

<u>Number</u>	<u>Title</u>	<u>Page No.</u>
17	Validation Tests for the IL Generated Ultrasound (a) Reference Signal for IL Generation of Ultrasound (b) Receiver PZT Signal with IL Beam Open (c) Receiver PZT Signal with IL Beam Blocked	37
18	Schematic Drawing of the Experimental Setup Around the Target for the Pulser/Receiver Tests	38
19	Schematic Drawing of the Experimental Setup Around the Target for the Tests with IL Generated Ultrasound Through Targets of Various Thicknesses (a) Ultrasound Generated by PZT and Detected by both PZT and PI (b) Ultrasound Generated by IL and Detected by Both PZT and PI	40
20	IL Generated Ultrasound Through Aluminum Pieces of Various Thickness as Detected by PZT and PI	41
21	IL Generated Ultrasound Through Steel Samples of Various Thickness as Detected by the PI	43
22	Target Setup for the IL Generated Rayleigh (Surface) Waves	44
23	IL Rayleigh Waves Generation and Detection by Top and Bottom PZT's (as in Fig. 22)	46
24	Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 1" Thick Mild Steel Sample at Room Temperature. The Time Point of Ultrasound Generation is to the Left of the Traces (Not Shown) (a) Unprocessed Signal, Wave Arrival Impossible to Detect (b) Processed Signal, Wave Arrival Easily Detectable	48
25	Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 1" Thick Mild Steel Sample at Room Temperature. The Time Point of Ultrasound Generation is to the Left of the Traces (Not Shown) (a) Unprocessed Signal, Wave Arrival Present but Barely Detectable (b) Processed Signal, Wave Arrival Easily Detectable	49

LIST OF ILLUSTRATIONS

FIGURES

<u>Number</u>	<u>Title</u>	<u>Page No.</u>
26	Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 3" Thick Stainless Steel 316 Sample at Room Temperature. The Improvement in the Signal-to-Noise Ratio is Quite Clear. The Time Point of Ultrasound Generation is Approximately 13.16 Microseconds to the Left of the Wave Arrival Point (Highest Peak). (a) Unprocessed Signal, Wave Arrival Impossible to Detect (b) Processed Signal, Wave Arrival Easily Detectable	50
27	TOF Variation with Thickness for Steels	54
28	TOF Variation with Thickness for Aluminums	55
29	TOF Variation with Carburized Depth	57
30	TOF Variation with Carbon Content in Steel	58
31	Time-of-Flight (TOF) Delay as a Function of Temperature for Homogenized (#32) and Non-Homogenized (#15) 1" Aluminum Samples	60
32	Time-of-flight (TOF) Delay as a Function of Temperature for 1" Brass Sample (#19)	61
33	Temperature Effect on Time-of-flight of Ultrasound Through 1" Thick Stainless Steel 316 Sample. Time Point of Ultrasound Generation to the Left of the Traces (Not Shown)	62
34	Temperature Effect on Time-of-Flight of Ultrasound Through 1" Thick 8620 Carbon Steel Sample (as received). Time Point of Ultrasound Generation to the Left of the Traces (Not Shown)	64
35	Time-of-Flight (TOF) Delay as a Function of Temperature for 1" Thick Non-Heat Treated Carbon Steel 1010 (#3)	65

LIST OF TABLES

<u>Number</u>	<u>Title</u>	<u>Page No.</u>
1	Problems with Conventional Temperature Measuring Instruments	2
2	Nonheat Treated Samples and Heat Treated Samples	18
3	Chemical Composition of Materials Tested, AISI Standards	19
4	High Temperature Test Samples (All Samples 1" Thick)	20
5	TOF at Room Temperature	52

EXECUTIVE SUMMARY

The Workpiece Temperature Analyzer (WPTA) is a unique approach to controlling heating processes. This analyzer measures the sub-surface temperature of the material being heated to determine the gradients and uniformity. The sub-surface temperature and the uniformity are generally the parameters needed to monitor the heating, but they can not be measured directly and must be inferred from other measurements. The WPTA offers the ability to better control heating and thus reduce heating times, lower operating costs, and save energy. The features of this analyzer are:

1. Measures sub-surface temperatures and uniformity
2. Suitable for industrial heating applications
3. Independent of the emissivity of the material being heated

The analyzer measures the speed of an ultrasound wave as it passes through the workpiece. The speed is a function of the temperature of the material. An ultrasound wave is generated using an Impulse Laser (IL) that strikes the surface of the work piece at a precisely known position. The time required for the wave to travel to a second point is termed the Time of Flight (TOF). The vibration of the wave reaching the second point is measured using a Polarizing Interferometer (PI). The TOF is converted to the speed of the ultrasound wave by knowing the path length the wave has travelled between the two points. The speed can be converted to the temperature using the proper correlations for that material.

The analyzer is being developed by Surface Combustion Inc. and Textron Defense Systems (formerly AVCO Research Laboratories) in a multiphase program. In the previous phase, the approach was verified mathematically and some potential markets for this analyzer were identified. During this phase it became apparent that since the speed of sound was dependent upon the physical and metallurgical state of the material as well as the material itself, the analyzer could be used to examine the metallurgy if the temperature were known.

The work documented in this report includes, designing and building a test sensor, confirmation that the sensor can measure the TOF for a sound wave and measurements of TOF for selected materials and metallurgical states. First, the PI was assembled and tested in order to define its sensitivity limits, and signal-to-noise ratio (SNR). The instrument was modified to accommodate speckle phenomenon associated with diffusive surfaces of workpieces. Comparisons with mathematical model predictions and shakedown tests confirmed the proper operation of the PI. An IL was then integrated into the system. The ability of the PI-IL system to generate and detect ultrasound at room temperature was evaluated and compared to that of contact piezoelectric transducers (PZT). Tests were then initiated to determine the ability of the PI-IL system to detect the metallurgical state of heat treated and prepared samples. Finally, extensive tests were conducted to investigate the effect of temperature on the ultrasound TOF through the samples and evaluate the ability of the system to detect TOF differences and predict the temperature of the sample. A simple signal processing scheme

was also implemented to improve the SNR of the measurement. It was therefore demonstrated that the system could generate an ultrasound wave in metallic materials and to measure the TOF accurately and repeatedly.

Testing was done at room temperature and elevated temperatures. The TOF for a variety of materials and thicknesses from 1/4" to 3" were measured at room temperature. Aluminum, carbon steel, stainless steel, and brass were examined in both a heat treated and un-heat treated state at room temperature. Samples that were 1" thick were heated in a furnace and the TOF was measured. It was possible to determine the change in TOF due to temperature for all of the materials. The highest temperature tested was 1875°F for AISI 8620 carbon steel and AISI 316 stainless steel. The measured TOF differential for an 1800°F temperature rise was 650 micro-seconds for SS 316. With a TOF resolution of 2 nano-seconds, the temperature measurements can be made with a resolution of $\pm 6^\circ\text{F}$. The measured results for variation of TOF with temperature follow the expected trends. Aluminum, brass and stainless steel show a nearly linear relationship between TOF and temperature. Carbon steels go through metallurgical phase changes upon heating so the relationship between TOF and temperature is nonlinear. The relationship should be reproducible so it should be possible to derive a correlation between TOF and temperature.

The surface temperature of the material can be measured simultaneously with the subsurface temperature if the surface waves are detected as well as those that pass through the material. The IL was used to generate proper surface waves in samples, which were detected by a PZT. It is anticipated that this feature would be a part of the final sensor.

A circular pattern was observed on the x-y oscilloscope during these tests. This pattern is indicative of low frequency room vibrations. The effect of these vibrations was beneficial, as it allowed to eliminate one of the two photomultipliers from the system.

The testing in this phase has proven that it is possible to use an IL and PI to measure the TOF for an ultrasound wave as it passes through a material. Although there is limited data, the results indicate that it should be possible to correlate the TOF to either the subsurface temperature of a material or the metallurgical state if the temperature is known. The results confirm the earlier predictions of a very valuable sensor that can reduce operating costs and save energy.

1.0 INTRODUCTION

Control of industrial heating processes depends upon knowing the temperature of the object being heated (workpiece). Early control technology depended upon the temperature of a thermocouple located in the furnace. The thermocouple reading represented a combination of the conditions in the furnace. Technology advances include methods to measure or infer the temperature of the surface of the workpiece. The critical unanswered question is how does one know the temperature of the inside of the workpiece. The objective of this research is the development of an instrument that can measure the temperature of the entire workpiece as it is being heated. The instrument is called a Workpiece Temperature Analyzer or WPTA.

The traditional method of determining the workpiece surface temperature in industrial furnaces is to use a radiation pyrometer or a contact thermocouple. The contact thermocouples have a limited use because they scratch the workpiece surface in a continuous process and difficult to incorporate into batch processes. Radiation pyrometers are used for non-contact surface temperature measurements, but can suffer inaccuracies because of interference by radiation from furnace hot walls and gases in the furnace. Moreover, the accuracy of radiation pyrometers is adversely affected by varying emissivity of the workpiece during heating. Table 1 summarizes the problems associated with the conventional temperature measuring instruments.

TABLE 1

**PROBLEMS WITH CONVENTIONAL
TEMPERATURE MEASURING INSTRUMENTS**

TEMPERATURE MEASURING INSTRUMENT	PROBLEMS
1. Thermocouple	<ul style="list-style-type: none">a. Does not provide direct measurement of temperature of workpiece.b. Furnace cycle time calibration required.c. Sacrificial samples needed during cycle time calibration as holes need to be drilled in sample to place thermocouple.d. Recalibration needed at regular time intervals as the system dynamics change burner performance and insulation degradation.
2. Radiation Pyrometer	<ul style="list-style-type: none">a. Does not provide bulk or core temperature. It measures only surface temperature.b. Inaccurate due to emissivity changes in material and interference from furnace walls and gases.

The traditional non-destructive temperature measuring instruments lack capability to measure average bulk temperature in a workpiece. There are thermal processes where temperature uniformity from surface to core is critical for uniform phase transformation reactions in the bulk of the workpiece. Moreover, the knowledge of the time at which this uniformity is achieved is important to optimize process cycle time. Some specific examples for such processes are solution annealing and age hardening of aluminum and interrupted quenching of steels. There is a need for an instrument which can measure the surface temperature as well as the average bulk temperature to provide knowledge of temperature uniformity in the bulk of the workpiece. Such an instrument can be used to optimize process cycles and to improve product quality. It will have a major impact on saving of material and energy resources and U. S. competitiveness in the world market.

1.1 BACKGROUND

The Surface Combustion and Textron Defense Systems (formerly AVCO Research Laboratory) are developing a new type of temperature sensor based upon the variation of the speed of sound in a material as its temperature changes. The approach is laser based using one laser to generate a sound wave at one point and an interferometer to detect the arrival of that sound wave a known distance from that point.

The workpiece temperature analyzer as conceptualized has three primary elements:

1. Impulse laser which generates a sound wave in a workpiece.

2. Polarizing Interferometer which detects surface displacement from sound wave and determines "time of flight" for sound waves to pass through the workpiece.
3. Microprocessor which converts the "time of flight" and initial workpiece thickness data into temperature readings.

The workpiece temperature analyzer concept under this program utilizes the idea of using sound waves to monitor the interior temperature of a workpiece in an industrial furnace. To make measurements, one can apply an impulse to one side of a workpiece by a pulsed laser beam. This laser beam acts like a hammer and generates a sound wave in the ultrasonic frequency range. The wave propagates through the workpiece and arrives after a time lapse to the interferometer sensor.

The sensor can be on the same side or opposite side as the impulse laser as shown in Figure 1. If the sensor is on the same side as the impulse laser, the wave can be detected after it is reflected from the far side (Figure 1B). Knowing the time of impact and the time of arrival of the incident sound wave at the other side or reflected sound wave on the same side, the speed of sound in the workpiece can be calculated if the thickness is known. The speed of sound in a workpiece is directly related to the average bulk temperature. A mathematical model can be used to convert the measured sound speed into bulk temperature of the workpiece. Similarly, measurement of surface sound wave (Figure 1A) speed can provide surface temperature. Thus, a temperature gradient and the surface temperature of a workpiece can be measured simultaneously. For thin materials, only surface wave measurements are required, because temperature gradients are very small. A lower energy

FIGURE 1

SOUNDWAVE PROPAGATION AND DETECTION MODES

NOTES:

1. For thin workpieces surface temperature is indicative of bulk temperature, so only surface wave measurements are adequate.
2. The detector for reflected waves in thick pieces can also be used for surface wave measurements.

impulse laser can be used for this purpose to reduce the cost of an instrument significantly if the instrument is to be used for only surface temperature measurements.

The schematic illustrated in Figure 2 shows the various modes of operation of the WPTA. The impulse laser generates an ultrasound wave that travels through the workpiece. At the same time surface waves (Rayleigh waves) are generated. A polarizing interferometer detects the arrival of both the bulk waves and the surface waves as vibration of the material surface. The spacing between the impulse laser and the interferometer is such that the two waves arrive at different times. In thicker pieces the interferometer can be placed opposite the impulse laser to achieve a stronger signal.

The optics of the system are shown in Figure 3. It is assumed that the workpiece would be located inside the furnace and the instrument would sight in it through a sight glass. This arrangement is shown in Figure 4.

The instrument in this development has three key features:

1. Measures the surface temperature of the work independent of the emissivity of the piece.
2. Measures the bulk average temperature of the work.
3. measures the physical state of the work if the temperature is known.

With these features there are several types of applications where this unit can be used for non-contact measurement. The four metals heating process areas investigated during Phase I for the application of this instrument are steel heat treat, aluminum heat treat, galvanneal and ion processing.

FIGURE 2: Schematic Illustration of Ultrasound Generation and Detection. Two Configurations Are Presented Depending on the Location of the Detection System (PI)

FIGURE 3

SCHEMATIC DRAWING OF THE
WORKPIECE TEMPERATURE ANALYZER
(SINGLE-SIDED)

FIGURE 4

ADVANCED WORKPIECE TEMPERATURE MEASUREMENT SYSTEM

It was determined that the most promising applications for the sensor would be for galvanneal and aluminum heat treat. The savings from the use of the WPTA system will be primarily from reduction of scrap, increased productivity, and improved energy efficiency. The total savings for these applications were estimated to be in the range of \$50,000 to \$500,000 per year with an average value of about \$125,000/year.

The technical feasibility of the WPTA system concept was investigated through mathematical simulations for an impulse laser and a polarizing interferometer during Phase I. The parameters for an impulse laser system were determined for selected applications and were found to be within the range of reasonably priced commercially available off-the-shelf equipment. The simulation indicated that the sensor was technically feasible and actually exceeded expectations in some areas. The sensitivity was sufficient to attain the desired accuracy. It was relatively insensitive to vibrations of the surrounding furnace. Measurements need only be taken on one side of the work, and the distance between the work and the sensor can vary without recalibration. But most important, it should be possible to measure the physical state of the work if the temperature is known. This last feature opens the door to actually monitoring the metallurgical changes as they proceed in a heat treat operation and allow one to optimize the process.

The multiphase development program at Surface Combustion was divided into three phases as follows:

Phase I: Define market, approximate value, instrument specification and proof of concept.

Phase IA: Bench tests, hot tests on laboratory furnace.

Phase II: Design and assemble prototype unit, develop software, and test on actual heat treat furnace.

Phase III: Field test of unit on commercial furnace, verify costs and economics.

All the technical feasibility work in Phase I was done using a computer simulation.

Phase IA of the development of the Workpiece Temperature Analyzer was undertaken to confirm the feasibility beyond a computer simulation through actual testing of the proposed sensor. Some of the critical issues tested in Phase 1A were:

1. Can the ultrasonic vibrations be sensed in a hot environment in sufficient detail to determine the "time of flight" of the wave?
2. Can the ultrasonic vibrations be sensed in the presence of other vibrations typically found in an industrial environment?
3. Can the polarizing interferometer also be used to determine differences in the physical state of the material?

These are key feasibility questions that greatly affect the applicability and usefulness of the sensor. Therefore, Phase IA was directed toward the resolution of these issues prior to embarking into the full development program in Phases II and III.

1.2 OBJECTIVES

The primary objective of the workpiece temperature analyzer program is to develop a bulk temperature measuring instrument for industrial furnaces to significantly improve:

- a. Product quality
- b. Production rate
- c. Energy efficiency

The specific results to be achieved in Phase 1A of the program were:

- a. Determination of technical feasibility of the polarized interferometer hardware.
- b. Demonstration of temperature sensing at higher temperatures.
- c. Demonstration of sensing changes in physical state (phase changes) in solid state.

This report is for the activities carried out during Phase IA of the program. This phase was started in May, 1990. The following tasks were completed during this phase.

Task 1 - Test Plan

Task 2 - Assembly and Testing of Polarized Interferometer

Task 3 - Sample Preparations

Task 4 - Testing of Integrated System

Task 5 - Temperature Testing

Task 6 - Market Assessment

Task 7 - Phase Report

Tasks 2, 4 and 5 were primarily performed by the subcontractor, Textron Defense Systems. Tasks 3 and 6 were performed by Surface Combustion and the remaining tasks were accomplished by joint effort between Textron Defense Systems and Surface.

1.3 BENEFITS

The workpiece temperature analyzer concept in this program uses a pulsed laser polarizing interferometer for detecting the arrival of the acoustic wave at the surface after passing through a workpiece. This measurement can be converted to speed of sound. This type of instrument has a high resolution and could detect surface motion of as small as 10 picometer. The sound speed measurement can be converted to an average workpiece temperature through a mathematical equation programed into the microprocessor used for control. The major benefits from this type of instrument are:

1. The instrument is non-contact and measurements are non-destructive. The measurements can be made from one side of the workpiece.
2. The temperature readings are independent of the emissivity of the surface of the workpiece. Thus, this instrument can be effectively used for processes where emissivity changes during processing (as in the process like galvanneal).
3. The instrument provides remote sensing with long stand-off distance (1 to 2 meters).
4. It provides an average bulk temperature as well as surface temperature of the workpiece rather than only surface temperature provided by a radiation pyrometer.

5. A single instrument can be used to measure temperature at various points on a workpiece through mirror arrangement for temperature uniformity determination.
6. The instrument readings are not affected by a glow discharge as encountered in ion-processing.
7. The readings are not affected by low frequency vibrations as encountered in normal industrial furnaces.
8. Less costly system can be used to measure surface temperature in thin materials.

2.0 DESCRIPTION OF EQUIPMENT AND MATERIALS

2.1 ASSEMBLY OF TEST SYSTEM

A test system was assembled at Textron consisting of a polarizing interferometer, impulse laser, and sample furnace. The interferometer was built from components following the schematic shown in Figure 5.

The impulse laser was an older existing unit available at Textron. The test set-up is shown in Figure 6. Verifications of capabilities of the individual components is discussed in the Results, Section 3.0 of this report. Testing started with room temperature confirmation that signals could be generated and detected. Samples were then heated in a Lindberg tube furnace to determine the change with temperature.

The furnace had two optical windows on opposite ends. The laser beam from the impulse laser passed through one optical window and strucked the sample on one flat (right side) face (see Figure 6). The acoustic wave generated by the impulse of the laser beam travelled through the sample. The

Figure 5 : Motion Sensing Polarizing Interferometer

Figure 6: Experimental Setup for Temperature Tests

polarizing interferometer on the other end of the furnace sends another laser beam to detect the time of arrival of the acoustic wave at the left side face of the sample. The difference between the time at which the impulse is generated and the time at which the arrival of wave is detected is measured as TOF.

2.2 METAL SAMPLES

The samples included eight different materials and a maximum of four thicknesses for some materials. The samples were cut from 2" diameter rods to the desired thickness by a rotary blade cutter. The thickness varied from 1/4" to 3". The materials used for the samples were:

1. SS304 and SS316
2. Carbon steels 1010, 1018, 1045 and 8620
3. Aluminum 6061
4. Brass

In addition, samples were prepared to measure the physical state by the WPTA system. These samples included different carbon penetration for carburized samples (1X for 0.025" and 2X for 0.05") and heat treated aluminum samples for homogenization measurements. A list of the samples for room temperature testing is presented in Table 2. The composition of the materials is provided in Table 3. These samples had diffusive surface rather than highly polished.

Thirteen (13) 1" thick samples from the thirty-four (34) samples prepared by Surface were selected for high temperature testing. These samples are listed in Table 4.

TABLE 2
NONHEAT TREATED SAMPLES

<u>Sample No.</u>	<u>Description</u>
1	1/4" Carbon Steel 1010 (as received)
2	1/2" Carbon Steel 1010 (as received)
3	1" Carbon Steel 1010 (as received)
4	3" Carbon Steel 1010 (as received)
5	1/4" Stainless 304 (as received)
6	1/2" Stainless 304 (as received)
7	1" Stainless 304 (as received)
8	3" Stainless 304 (as received)
9	1/4" Stainless 316 (as received)
10	1/2" Stainless 316 (as received)
11	1" Stainless 316 (as received)
12	3" Stainless 316 (as received)
13	1/4" Aluminum 6061 (as received)
14	1/2" Aluminum 6061 (as received)
15	1" Aluminum 6061 (as received)
16	3" Aluminum 6061 (as received)
17	1/4" Brass 6061 (as received)
18	1/2" Brass (as received)
19	1" Brass (as received)
20	3" Brass (as received)
21	1" 8620 Carbon Steel (as received)
22	1" 1045 Carbon Steel (as received)
23	1" 1018 Carbon Steel (as received)

HEAT TREATED SAMPLES

24	1/4" Carbon Steel (1010) Case Depth 1X
25	1/4" Carbon Steel (1010) Case Depth 2X
26	1/2" Carbon Steel (1010) Case Depth 1X
27	1/2" Carbon Steel (1010) Case Depth 2X
29	1" Carbon Steel (1010) Case Depth 1X
29	1" Carbon Steel (1010) Case Depth 2X
30	1/4" Aluminum (6061) Homogenized
31	1/2" Aluminum (6061) Homogenized
32	1" Aluminum (6061) Homogenized
33	1" 8620 Carbon Steel with Case Depth 1X
34	1" 8620 Carbon Steel with Case Depth 2X

NOTE: 1X = 0.025"

TABLE 3
CHEMICAL COMPOSITION OF MATERIALS TESTED,
AISI STANDARDS

Material Notation	Chemical Composition
1010	0.08-0.13% C, 0.3-0.6% Mn, 0.04% maxm. P, 0.05% maxm. S
1018	0.15-0.20% C, 0.6-0.9% Mn, 0.04 maxm. P, 0.05% maxm. S
1045	0.43-0.5% C, 0.6-0.9% Mn, 0.04% maxm. P, 0.05% maxm. S
8620	0.2% C, 0.8% Mn, 0.15-0.3% S, 0.4-0.6% Cr, 0.4-0.7% Ni, 0.15-0.25 Mo
304 SS	18-20% Cr, 8-12% Ni, 0.08% maxm. C, 2% maxm. Mn, 1% maxm. Si
316 SS	16-18% Cr, 10-14% Ni, 2-3% Mo, 0.08% maxm. C, 2% maxm. Mn, 1% maxm. Si
6061 Al	0.6% Si, 0.27% Cu, 1.0% Mg, 0.2% Cr, Rest Aluminum

TABLE 4
HIGH TEMPERATURE TEST SAMPLES
(ALL SAMPLES 1" THICK)

NON-HEAT TREATED SAMPLES

<u>Sample No.</u>	<u>Description</u>
3	Carbon Steel 1010 (as received)
7	Stainless 304 (as received)
11	Stainless 316 (as received)
15	Aluminum 6061 (as received)
19	Brass (as received)
21	8620 Carbon Steel (as received)
22	1045 Carbon Steel (as received)
23	1018 Carbon Steel (as received)

HEAT TREATED SAMPLES

28	Carbon Steel 1010 Case 1X
29	Carbon Steel 1010 Case 2X
32	Aluminum 6061 - Homogenized
33	8620 Carbon Steel Case 1X
34	8620 Carbon Steel Case 2X

3.0 RESULTS

3.1 INITIAL PI CONCEPT TESTS - NO ULTRASOUND GENERATION

Since the PI represented the most important component of the WPTA system, a series of proof-of-concept tests was initiated. The objective of these tests was not the detection of ultrasound, but rather the characterization of the PI and the determination of its proper operation under well controlled conditions. The workpiece was replaced by a mirror in order to eliminate problems associated with light scattering on the sample surface. When the system is properly aligned and the intensities I_1 and I_2 of the two photomultipliers (see Figure 5) are equal, then the two signals will form a circle on the display of an x-y mode oscilloscope. This indicates that they are exactly 90° out of phase. Figure 7 presents a typical display. Notice that the formation of the circle is not due to a deliberate motion of the signal mirror, but the random room vibrations of low frequency. No such circular signal is generated when the system is resting in an absolutely calm environment and, in that case, a single point (not a circle) in the x-y plane represents the signal. The beneficial effect of these low frequency vibration was the elimination of one of the photomultipliers from the system. It should also be pointed out that any fluctuations in the intensity of the He-Ne laser will not appear as 90° apart signals, but rather as in phase ones. They can therefore be easily distinguished.

The ability of the PI to detect prescribed phase differences due to optical path changes in the signal beam under controlled conditions was then investigated. Although slow, such path changes can be easily generated, our interest was focused on faster ones in order to simulate the action of ultrasound with frequencies higher than 1 MHz. For that purpose, a glass

Figure 7: Combination of Two 90 deg. Apart Phototubes Signals on X-Y Oscilloscope

wheel was fabricated with eight sectors, as shown in Figure 8. The wheel was spun, intercepting the return signal beam from the mirror. Each sector of the wheel had a slight wedge in its circumference (such as points A to B or C to D in Figure 8), which differed among sectors. The wheel speed was about 1000 rpm. By taking the beam through the various wedges, optical path delays of different magnitudes were generated. Figure 9 presents the results of these tests. Each picture corresponds to one wheel sector. The two signals are clearly 90° apart. The number of cycles in the signals indicate the presence of a wedge. The more complete cycles there are, the steeper the wedge is. Very precise quantitative information for the thickness change in each sector can be obtained by counting the cycles, since each complete cycle corresponds to a displacement of one wavelength (for He-Ne light, this is 632.8 nm). Comparisons with the measured (with static conventional interferometer) thickness changes led to excellent agreements.

These results were very encouraging and proved the principle of operation of the PI. The frequency response of our system was also investigated in anticipation of the much higher ultrasonic signals. The glass wheel was spun at two different speeds, 100 and 1000 rpm, and the results are shown in Figure 10. As expected, the number of complete cycles in the signals did not change, since the thickness variation or wedge in that sector of the wheel did not change either. However, the amplitude of the signal was reduced. At even higher speeds, the sinusoidal character of the signal disappeared. The conclusion drawn from this test was that the photodiodes used so far would not be fast enough to capture ultrasonic signal of frequencies as high as 5 MHz.

Figure 8: Glass Wheel with Multiple Wedges Used in the Shakedown Tests

Figure 9: Signals from the Two Phototubes Through the Glass Wheel Sectors

Figure 10: Frequency Response Test of the Phototubes (Photodiodes)

In order to address this problem, we replaced the photodiodes with photomultiplier tubes. The tests were repeated with the glass wheel spun at various speeds. No change in the signals was observed, confirming the adequate frequency response of the photomultipliers. The same photomultipliers were used throughout the tests described in this report.

3.2 ULTRASOUND GENERATION BY PZT - DETECTION BY PI

Although the PI's principle of operation was proven, the ultimate test would be the evaluation of its capability to capture real ultrasonic signals.

PZT's are commercially available sensors that can generate and detect ultrasonic waves. They operate in contact with the sample and can be specifically ordered to generate longitudinal or shear waves at prescribed frequencies. A set of PZT's (both longitudinal and shear) along with a Pulser/Receiver Unit (PRU) were purchased and installed. The longitudinal PZT was attached at the back side of the signal mirror. The first tests were done with the original glass mirror. The arrival of the ultrasonic wave was detected by the PI, which was focused on the front surface of the signal mirror (0.235" thick). Figure 11 presents the signal out of the two photomultipliers (PM's). The point of ultrasound generation is to the left of the signals (not shown). The signals are 90° apart as expected. The TOF through the mirror compared well with that measured by using both PZT's (one on each side of the mirror).

Verification tests were also performed to ensure the validity of the results. Figure 12A presents the signal from one of the PM's with the signal beam blocked, and Figure 12B with the beam open. As expected, the

Figure 11: Ultrasound Generated by PZT and Detected by the Polarizing Interferometer (PI)

Figure 12: Validation Tests of the PI Performance
(a) PI Signal Beam Blocked
(b) PI Signal Beam Open

characteristic signal of ultrasonic waves arrival disappears when the PI beam is blocked.

The dependence of the PI signal on the strength of the generated ultrasound was also investigated. This was considered an important tests, because it proved that the PI signal was strongly correlated with the ultrasound strength (or surface displacement) rather than some other extraneous source of interference. The PRU allows for variation of the ultrasound pulse strength. Figure 13 presents the results for four pulse strengths. Good correlation is observed and, as expected, the signal disappears when the ultrasound pulse becomes extremely weak.

3.2.1 Diffusive Surfaces

Detection of ultrasound on diffusive surfaces represents a challenge to the detection system. This is due to the phenomenon of speckle formation, discovered as early as 1960 when the first He-Ne laser was operated. Objects viewed in highly coherent light acquire a peculiar granular appearance. As illustrated in Figure 14A from Ref. 5, the detailed structure of this granularity bears no obvious relationship to the macroscopic properties of the illuminated object, but rather it appears chaotic and unordered, with an irregular pattern that is best described by the methods of probability theory and statistics. The physical origin of this phenomenon stems from the fact that surfaces of most materials are extremely rough on the scale of an optical wavelength. When nearly monochromatic light is reflected from such a surface, the optical wave

Figure 13: PI Signal Variation with the Strength of the PZT Generated Ultrasound

(a)

(b)

Figure 14: Laser Speckle Phenomenon (from Ref. 5)
(a) Image of Rough Object Formed with Coherent Light
(b) Physical Origin of Speckle for Free Space Propagation

resulting at any moderately distant point consists of many coherent components or wavelets, each arising from a different microscopic element of the surface. With reference to Figure 14B from Ref. 5, the distances traveled by these various wavelets may differ by several or many wavelengths if the surface is truly rough. Interference of the dephased, but coherent wavelets results in the granular pattern of intensity that we call speckle.

The PI was properly modified to accommodate the speckle phenomenon. After a series of tests, the ultrasound was clearly detected by the PI. The results are shown in Figure 15. The time-point of ultrasound generation by the PZT is to the left of the picture (not shown). The time-of-flight measured by the PI compared very well with that of the PZT Pulser/Receiver test. It should be pointed out that the second signal in Figure 15 corresponds to the arrival of shear waves, which are also generated by the PZT. These results proved that the PI can indeed detect ultrasound through pieces with diffusive surfaces.

3.3 ULTRASOUND GENERATION BY IL - DETECTION BY PZT

The goal of these tests was to evaluate the ability of the IL to generate ultrasound in metal samples. The PZT signals would be used as an independent check of the generated waves.

A (XeCl) laser was used as impulse laser. Proper lenses and mirrors were used to focus the rectangular IL beam down to a small spot. Figure 16 presents the sample setup for these tests. The IL beam was focused on the back surface and a PZT transducer was attached on the front surface to

Figure 15: PI Detection of PZI Generated Ultrasound through Target with Diffusive Surface

Figure 16: Target Setup for Impulse Laser (IL) Generation of Ultrasound and Detection with the PZT

detect the arrival of ultrasound. This is the same side facing the PI, which, of course, was not used for these tests. The sample was a 1/4" thick steel piece. The results are presented in Figure 17. The time-point when the IL fires and ultrasound is generated is shown in Figure 17A. Strong ultrasound pulses were detected by the receiver PZT (Figure 17B). The IL generates both longitudinal and shear waves. The latter generate small longitudinal displacements in addition to those normal to the direction of propagation. Therefore, the longitudinal PZT used in this experiment picked up both longitudinal and shear waves (Figure 17B).

Validation tests were also performed. The configuration of Figure 16 was used. The IL was blocked and, as shown in Figure 17C, the signal disappeared. When the IL beam was again allowed to impinge on the sample, the signal came back. This test proved that there was no cross-talking of the electronics or other external sources, and the detected signal was a true laser generated ultrasound.

A comparison with the Pulser/Receiver PZT tests was also carried out. Figure 18 presents the experimental arrangement of the two PZT's (compare also with Figure 16). As expected, the TOF measurements from both tests were consistent.

3.4 ULTRASOUND GENERATION BY IL - DETECTION BY PI

All the tests described in the previous sections were aimed towards validation of the components performance, namely the PI and the IL. The goal of these tests was to evaluate the ability of the integrated system (PI and IL) to generate and detect ultrasound through metal samples.

Impulse Laser Firing and Ultrasound Generation

Figure 17: Validation Tests for the IL Generated Ultrasound
(a) Reference Signal for IL Generation of Ultrasound
(b) Receiver PZT Signal with IL Beam Open
(c) Receiver PZT Signal with IL Beam Blocked

Figure 18: Schematic Drawing of the Experimental Setup Around the Target for the Pulser/Receiver Tests

A detailed sample arrangement is shown in Figure 19A and B. The following steps were taken as part of the test procedure. First, ultrasound was generated using a PZT (Figure 19A). Then the pulser PZT was removed and the IL beam was allowed to impinge on the backside of the target (Figure 19B), while both the PI and the receiver PZT remained in place to detect the ultrasound. This procedure provided immediate confirmation of our readings and ensured that no extraneous signals interfered with the measurement. Additional checks of the system included the disappearance of the signal when the PI beam was blocked, implying that there was no cross-talk among the electronics.

Figure 20 presents the results of the tests with the configuration of Figure 19B. The samples were aluminum pieces of various thicknesses with semi-diffusive surfaces. These are raw data points. The top two traces in Figure 20 corresponds to the signals from the receiver PZT and the PI for a 1/4" aluminum sample. The TOF from both detectors is the same, although the shape of the waves is different. This, however, is not important, since the TOF is the only information needed to measure the speed of ultrasound and hence the bulk temperature.

A crucial test of our measurement was the comparison of TOF for samples of various thicknesses. As shown Figure 20, the TOF is very well correlated with the sample thickness (double TOF for double thickness, etc.). The time-point of IL firing and ultrasound generation is also shown on the left of Figure 20.

Figure 19: Schematic Drawing of the Experimental Setup Around the Target for the Tests with IL Generated Ultrasound Through Targets of Various Thicknesses
 (a) Ultrasound Generated by PZT and Detected by Both PZT and PI
 (b) Ultrasound Generated by IL and Detected by Both PZT and PI

Figure 20: IL Generated Ultrasound Through Aluminum Pieces of Various Thickness as Detected by PZT and PI

The same test procedure, including all validation checks was followed for steel samples. The sample arrangement was that of Figure 19B. The results are shown in Figure 21 for 1/8", 1/4", and 1/2" steel samples. A comparison with Figure 20 indicates the significantly reduced SNR for the steel tests. In particular, for the 1/2" steel the wave arrival is barely distinguished from the background noise. This problem was the primary reason for the development of a special signal processing scheme. Based on the results of Figure 21, it would appear that the maximum possible thickness measured was 1/2" for steel. However, as it will be described later in Sections 3.6 and 3.8, the implementation of the signal processing technique has increased this thickness to at least 3".

3.5 RAYLEIGH WAVES GENERATION BY IL

These tests were undertaken in order to determine the ability of the IL to generate Rayleigh (surface) waves on metal samples. As described in Ref. 1, these waves have some important advantages over the bulk waves, and they might be preferable in certain situations. The Rayleigh waves travel only through a thin layer near the surface of the sample, hence their designation as surface waves. Typical depth of penetration is a few thousandths of an inch. This property of the Rayleigh waves can, in principle, be used to measure surface temperature of the sample. The simultaneous measurement of TOF for Rayleigh and bulk waves can provide valuable information towards the determination of the temperature profile in the workpiece.

Figure 22 presents the experimental setup for these tests. A 2.5" thick aluminum piece was used. Two PZT's were also used for the detection of both Rayleigh and bulk waves. The top PZT was placed 2" away from the IL beam

Figure 21: IL Generated Ultrasound Through Steel Samples of Various Thickness as Detected by the PI

Figure 22: Target Setup for the IL Generated Rayleigh (Surface) Waves

impingement point. Figure 23 presents the signal from the top (Figure 23A) and the bottom PZT (Figure 23B). All velocities measured from these tests compared very well with theoretical predictions from Ref. 1. Therefore, it was concluded that the IL can indeed simultaneously generate all three types of ultrasound waves, namely longitudinal, shear, and Rayleigh. (See Figures 15 and 22.)

3.6 SYSTEM PERFORMANCE OPTIMIZATION

The goal of this effort was to improve the WPTA's performance, evaluate its capability to handle more realistic operating environments, and answer questions relating to its incorporation into industrial processes. These improvements were carried out in anticipation of the limited SNR during tests on thick samples (thicknesses greater than 1") and the increased background noise during temperature testing.

3.6.1 Compact PI

One of the major advantages of the PI is its compact and rugged construction. In order to prove this claim, the PI was assembled into a very compact unit, occupying an area of only 10 in. x 20 in. A conventional tripod was used to direct the compact PI towards the sample. No vibration isolation was used. The system can be easily made even smaller by using smaller components, such as mirrors, beam splitters, etc., which are commercially available. This, however, was not done here, since this exercise was not intended to achieve the smallest size possible, but rather to prove the principle of operation under compact construction. The results of this effort confirmed our original claim that the PI can be assembled into a compact, easy to use, rugged system.

Figure 23: IL Rayleigh Waves Generation and Detection by Top and Bottom PZT's (as in Fig. 22)

3.6.2 Signal Processing Implementation

A signal processing technique was implemented in order to improve the SNR of the measurement and eliminate problems associated with external vibrations. In addition, high sensitivity operation of the PI was achieved at all operating points of the detection system.

A set of tests was initiated to prove the advantages of the new signal processing scheme. Figures 24 and 25 present a representative sample of the data. A 1" thick mild steel sample was used for these tests at room temperature. In Figure 24A, the arrival of the ultrasound cannot be detected. This signal represents a snapshot of the data during a single pulse. However, when a number of pulses are acquired, the signal appears with a dramatically improved SNR (Figure 24B). Figure 25A shows data during a single pulse, where the arrival of the wave can be detected even without signal processing. The application of the latter, however, improves the clarity of the signal, as shown in Figure 25B. These two figures correspond to the cases of low or zero (Figure 24A) and high (Figure 25A) sensitivity of the PI. The advantage of combining a number of pulses rather than a single one is now clearly demonstrated.

This signal processing scheme has also made it possible to detect ultrasound through 3" thick samples. Figure 26 presents a comparison between the unprocessed and processed signals for a 3" thick stainless steel 316 sample. The ultrasound was generated at a time point not included in this picture (total TOF: 13.685 microseconds). It is clear again from this figure that without the signal processor no ultrasound could be detected through this sample, because the signal is "buried" under the background noise. The

(a) UNPROCESSED SIGNAL

(b) PROCESSED SIGNAL

Figure 24: Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 1" Thick Mild Steel Sample at Room Temperature. The Time Point of Ultrasound Generation is to the Left of the Traces (Not Shown).
(a) Unprocessed Signal, Wave Arrival Impossible to Detect
(b) Processed Signal, Wave Arrival Easily Detectable

Figure 25: Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 1" Thick Mild Steel Sample at Room Temperature. The Time Point of Ultrasound Generation is to the Left of the Traces (Not Shown).
 (a) Unprocessed Signal, Wave Arrival Present, but Barely Detectable
 (b) Processed Signal, Wave Arrival Easily Detectable

Figure 26: Impulse Laser (IL) Generated Ultrasound Detected by the Polarizing Interferometer (PI) Through a 3" Thick Stainless Steel 316 Sample at Room Temperature. The Improvement in the Signal-to-Noise Ratio is Quite Clear. The Time Point of Ultrasound Generation is Approximately 13.16 Microseconds to the Left of the Wave Arrival Point (Highest Peak).
 (a) Unprocessed Signal, Wave Arrival Impossible to Detect
 (b) Processed Signal, Wave Arrival Easily Detectable

signal processing technique extracts this information and suppresses the background noise, as shown in Figure 26B.

The excellent SNR of Figure 26B implies that the 3" steel sample might not be the limit of our measuring capabilities. Although all 3" thick samples (aluminum, brass, carbon steel, etc.) that we tested presented the same signal clarity and sharpness, we did not test any thicker ones. In addition, the signals from these tests are identical to that of Figure 26B and will not be presented for brevity.

3.7 TEMPERATURE TESTS

The configuration shown in Figure 6 was used for these tests. Almost all samples shown in Table 2 were tested at room temperature. However, only a selected number of them with 1" thickness were tested at higher temperatures. These samples were, in general, tested at three temperature levels above room temperature. Extra care was taken to make sure that all samples had reached equilibrium conditions at each temperature prior to making measurements.

3.7.1 Room Temperature Tests

The time-of-flight (TOF) measured for the samples tested are presented in Table 5.

The measurements are corrected for small variations in thickness and hence, refer to the same nominal thickness (1/4", 1/2", 1", and 3"). The signal processing scheme described in Section 3.6 was also used here. All the

TABLE 5
TOF AT ROOM TEMPERATURE

NONHEAT TREATED SAMPLES

<u>Sample No.</u>	<u>Description</u>	<u>TOF (usecs)</u>
1	1/4" Carbon Steel 1010 (as received)	1.366
2	1/2" Carbon Steel 1010 (as received)	2.228
3	1" Carbon Steel 1010 (as received)	4.340
4	3" Carbon Steel 1010 (as received)	12.938
5	1/4" Stainless 304 (as received)	1.643
6	1/2" Stainless 304 (as received)	2.668
7	1" Stainless 304 (as received)	4.505
9	1/4" Stainless 316 (as received)	1.315
10	1/2" Stainless 316 (as received)	2.480
11	1" Stainless 316 (as received)	4.677
12	3" Stainless 316 (as received)	13.685
14	1/2" Aluminum 6061 (as received)	2.312
15	1" Aluminum 6061 (as received)	4.092
16	3" Aluminum 6061 (as received)	12.000
17	1/4" Brass 6061 (as received)	1.506
18	1/2" Brass (as received)	3.189
19	1" Brass (as received)	6.124
20	3" Brass (as received)	17.540
21	1" 8620 Carbon Steel (as received)	4.357
22	1" 1045 Carbon Steel (as received)	4.251
23	1" 1018 Carbon Steel (as received)	4.433

HEAT TREATED SAMPLES

24	1/4" Carbon Steel (1010) Case Depth 1X	1.116
25	1/4" Carbon Steel (1010) Case Depth 2X	1.134
26	1/2" Carbon Steel (1010) Case Depth 1X	2.171
30	1/4" Aluminum (6061) Homogenized	1.097
31	1/2" Aluminum (6061) Homogenized	2.005
32	1" Aluminum (6061) Homogenized	4.096
33	1" 8620 Carbon Steel with Case Depth 1X	4.415
34	1" 8620 Carbon Steel with Case Depth 2X	4.381

signals obtained look similar to those of Figures 24B, 25B, or 26B, and are not shown for each sample.

The TOF indicated in the table is that corresponding to the first peak of the signal, which is slightly later than the wave arrival time. The technique was chosen because it exhibited better reproducibility than an extrapolation back to the arrival time. Therefore, the TOF does not exactly scale with the sample thickness. The rise time of the signal and the resolution of the oscilloscope read-out were different for each thickness. Comparisons, however, can be made for samples of the same thickness but different material. In addition, the absolute value of the speed of ultrasound is irrelevant as far as temperature measurement is concerned. The important quantity is the difference in TOF as the sample is heated which can be used to calculate its bulk temperature.

The trends observed during these tests are as follow:

1. There is a linear relationship between TOF and thickness of material as shown in Figures 27 and 28.
2. The TOF values for stainless steel 316 are higher than for carbon steel 1010 for the same thickness (see Figure 27). This is expected as the modulus of elasticity for SS316 is lower than that of CS1010 and density

Figure 27
TOF Variation with Thickness for Steels

Figure 28
TOF Variation with Thickness for Aluminums

for SS316 is higher. The simplified relationship between TOF and the above properties is as follows:

$$\begin{aligned} \text{TOF} &= C \cdot \frac{1}{\frac{v}{\sqrt{\delta}}} \\ &= C \cdot \frac{\sqrt{\delta}}{v} \end{aligned}$$

Where: v = velocity
 δ = density of material
 Y = modulus of elasticity
 C = Constant

3. The TOF values for homogenized aluminum (6061) are almost the same as those of non-homogenized aluminum (6061) at room temperature.
4. Even though a small noticeable change in TOF has been observed for carbon steel samples with different carburized depths, the trends for carbon steel 1010 and 8620 are different (Figure 29 and Table 5) and will require more data to investigate these trends.
5. The TOF for three carbon steels (CS1010, 1018 and 1045) with different carbon content were observed to be different (see Figure 30). The peculiar behavior of these samples showing a peak for CS1018 emphasizes need for additional testing to understand the interaction between microstructure and ultrasonic wave propagation.

3.7.2 Aluminum Samples

Two aluminum samples were tested at high temperatures:

- Sample #15: 1" Aluminum 6061 (as received).
- Sample #32: 1" Aluminum 6061 (homogenized).

Figure 29
TOF Variation with Carburized Depth

Figure 30
TOF Variation with Carbon Content in Steel

Both samples were tested at four temperatures: room, 500°F, 900°F, and 950°F. The results are presented in Figure 31. The TOF delay for the non-homogenized sample at 950°F was measured at the end of the two hour test period. Noticeable differences between the two samples can be seen; the maximum difference being as high as 80 nsecs. In addition, substantial TOF differences, as high as 490 nsecs, can be observed between room temperature and 950°F. These differences can be easily detected by our system.

3.7.3 Brass Samples

One brass sample was tested at high temperatures:

- Sample #19: 1" Brass (as received).

Measurements were taken at room temperature, 500°F, 900°F and 950°F. At each temperature, enough time was allowed for the sample to reach equilibrium. The results are presented in Figure 32. Substantial differences in TOF can be observed between room and high temperatures (as high as 500 nsecs).

3.7.4 Stainless Steel Samples

Two samples were tested;

- Sample #7: Stainless 304, 1" Thick.
- Sample #11: Stainless 316 1" Thick.

Four temperature levels were selected. A typical set of signals (stainless 316) at three temperature levels (room temperature, 1725°F and 1875°F) are shown in Figure 33. It is clear that, even at the highest temperature, the signal is easily discernible from the background noise. It should be pointed out that a typical data acquisition system resolution is about 2 nsecs, which implies that the observed difference of 650 nsecs is very easily

Figure 31: Time-of-Flight (TOF) Delay as a Function of Temperature for Homogenized (#32) and Non-Homogenized (#15) 1" Aluminum Samples

Figure 32: Time-of-Flight (TOF) Delay as a Function of Temperature for 1" Brass Sample (#19)

Figure 33: Temperature Effect on Time-of-Flight of Ultrasound Through 1" Thick Stainless Steel 316 Sample. Time Point of Ultrasound Generation to the Left of the Traces (Not Shown).

detectable. In addition, a quick estimate of measurement uncertainty for the high temperature range (1725°F-1875°F) implies that the temperature uncertainty at these levels can be as low as $\pm 6^\circ\text{F}$ or approximately 0.3 percent, for perfectly repeatable calibration curve.

The TOF delays were also measured for 304SS. The trends were similar in both stainless steels. Minor differences between the two types of stainless steel can be observed at fixed temperature levels. The TOF values for 316SS were slightly higher than those for 304SS.

3.7.5 Carbon Steel Samples

Samples 8620 and 1010 carbon steel were tested. A typical set of signals is shown in Figure 34 for the 8620 carbon steel (#21) at three temperature levels. The wave arrival can be easily detected even at the highest temperature of 1875°F. TOF delays as high as 810 nsecs between 330°F and 1800°F can be observed.

The TOF delays for 1010 carbon steel (as received) are shown in Figure 35. Substantial TOF differences can be observed between room temperature and 1000°F.

3.8 PHYSICAL STATE TESTS

Preliminary investigations were carried out in order to identify any correlations between TOF changes and physical or metallurgical state of materials. These tests were conducted at room temperature, except for the 8620 carburized steels and the aluminum 6061. All the measurements of TOF

Figure 34: Temperature Effect on Time-of-Flight of Ultrasound Through 1" Thick 8620 Carbon Steel Sample (as received). Time Point of Ultrasound Generation to the Left of the Traces (Not Shown).

Figure 35: Time-of-Flight (TOF) Delay as a Function of Temperature for 1" Thick Non-Heat Treated Carbon Steel 1010 (#3)

delay were corrected for slight differences in sample thickness. These measurements show a potential that the instrument can be applied for monitoring processes involving phase changes and microstructure changes.

The trends observed during these tests are as follows:

1. All samples showed an increase in TOF as the temperature was raised. This result was as expected.
2. The TOF differential between homogenized and non-homogenized aluminum is narrower at room temperature and widens at higher temperature.
3. The TOF values for SS316 are higher than those of SS304. The differential is greater at room temperature and reduces slightly at very high temperatures of above 1700°F.
4. The TOF values for carburized (2x) carbon steel 8620 are higher than those for non-carburized samples.

3.9 MARKET ASSESSMENT

The two objectives of this task are to further define the potential market of the workpiece temperature analyzer and secondly to start the work that will eventually lead to a team for manufacturing and selling of the resulting analyzer. Definition of the market size was attacked by categorizing the existing Surface Combustion furnaces in the fields of interest. Using the number of furnaces, their age and the normal replacement times, it was possible to estimate the potential for sales of analyzer for new furnaces in the next ten years as well as the potential retrofit market to existing furnaces. The market share for a ten year period after introduction of the product in the market was estimated to be about 1500 units.

There is a high degree of interest from potential users, as judged by the inquiries and willingness to be a host site for field demonstration. A variety of applications are still available for field demonstration. These applications include:

1. Galvanizing of steel.
2. Continuous strip annealing.
3. Homogenization of aluminum.
4. Heat treatment of finished parts.
5. Age hardening of aluminum.
6. Continuous casting.

The application for solution treatment of aluminum is still favored for the first proto-type field demonstration.

Because of the uniqueness and far-reaching applications of the workpiece temperature analyzer in other areas such as physical state measurements, a patent disclosure has been prepared. We are currently in the process of drafting a patent application.

4.0 CONCLUSIONS

The following conclusions are derived from the test work conducted in Phase 1A of the program:

1. Bench Scale test demonstrated that it was possible to generate an ultrasound wave using an impulse laser and detect that wave using a polarizing interferometer in a manner that the time of flight for the wave can be measured.
2. The measured TOF using this technique was comparable to that measured on the same material using piezoelectric transducers.
3. Both Surface waves and bulk waves can be generated by the impulse laser so it should be possible to determine the TOF for both cases at approximately the same time.
4. The set-up was not affected by vibrations similar to those found in industrial applications.
5. There was a difference in the TOF at elevated temperatures that corresponded to the predicted change in the speed of sound for that material.
6. The TOF is also effected by the metallurgic state of the material and changes in response to changes in grain structure.

7. It was possible to measure TOF for AISI 8620 carbon steel and AISI 316 stainless steel at temperatures up to the limit of the heating system, 1875°F.
8. Homogenization of aluminum alloy is still preferred as the demonstration application for this technology.
9. The testing results have all been very positive and in our opinion, the WPTA has an excellent potential to make a major impact on industrial heating. Previous estimates of applications and savings are unchanged.

5.0 RECOMMENDATIONS

The results from this phase are very encouraging. It is recommended that a Full-Scale Unit (FSU) of the WPTA be designed and built to be tested on a furnace in Surface Combustion's laboratory. Shakedown tests should be first performed at the Textron Laboratory, followed by cold and hot tests at SCI's facilities. Subsequently, a number of applications should be tested at Surface facilities.

Key issues to be addressed in this coming phase should include:

- Generation of calibration curve for at least one material to show relationship between TOF and temperature.
- Repeatability and reliability of calibration.
- Study of mechanisms leading to ultrasound attenuation at high temperatures (over 1700°F).
- Surface roughness and surface oxidation effect on measurement.
- Dependence of attenuation on grain size, frequency, and degree of material anisotropy at normal and elevated temperatures.
- Analysis of the frequency content of received ultrasonic pulses and possible utilization as a diagnostic tool.
- More detailed study of the effect of metallurgical state and microstructural changes of the materials on TOF of ultrasound.

6.0 REFERENCES

1. Phase 1 Final Report, DOE/ID/12830-1 (DE91004352), May 1990.
2. Francon, M. and Mallick, S., "Polarization Interferometers," Wiley-Interscience, 1971.
3. Allensowrth, D.L. "Interferometer for the Determination of Strains Due to Domain Switching in Ferroelectrics," Rev. Sci. Instrum., 51 (10), October 1980.
4. Vilkomerson, D., "Measuring Pulsed Picometer-Displacement Vibrations by Optical Interferometry," Applied Physics Letters, Vol. 29, No. 3, August 1976.
5. Dainty, J.C., "Laser Speckle and Related Phenomena, "Topics in Applied Physics, Vol. 9, Springer-Verlag, 1975.
6. Eshbach, O.W., "Handbook of Engineering Fundamentals," Wiley Engineering Handbook Series, 2nd Edition.

END

**DATE
FILMED**

2 / 27 / 92