ORNL/TM-11987

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

Received

FEB 28 1982

**Expert Systems and the CPI
Product Substitution Review:
A Needs Analysis for the U.S.
Bureau of Labor Statistics**

Lloyd F. Arrowood
Bruce E. Tonn

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/TM-11987

COMPUTING AND TELECOMMUNICATIONS DIVISION
ENERGY DIVISION

ORNL/TM--11987

DE92 008237

EXPERT SYSTEMS AND THE CPI PRODUCT SUBSTITUTION REVIEW:
A NEEDS ANALYSIS FOR THE U.S. BUREAU OF LABOR STATISTICS

Lloyd F. Arrowood
Bruce E. Tonn

February, 1992

Research Sponsored by
U.S. Bureau of Labor Statistics
U.S. Department of Labor

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6207
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under
Contract No. DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

ABSTRACT	vii
1. INTRODUCTION	1
2. PROJECT GOALS	3
3. METHODOLOGY	5
4. TOOL SURVEY AND EVALUATION	7
4.1 TRENDS	9
4.2 COMMERCIALLY AVAILABLE EXPERT SYSTEM SHELLS	10
4.2.1 Aion Development System	10
4.2.2 ART/IM	11
4.2.3 CLIPS	11
4.2.4 EXSYS Professional	12
4.2.5 GURU	12
4.2.6 Intelligence Compiler	12
4.2.7 KBMS/PC	13
4.2.8 1st Class HT	13
4.2.9 KES	14
4.2.10 KnowledgePro	14
4.2.11 LEVEL5 OBJECT	15
4.2.12 NEXPERT/Object	15
4.2.13 Kappa PC	16
4.3 TOOL RECOMMENDATIONS	16
4.3.1 External Data and Program Interfaces	16
4.3.2 Support for Rule-based Processing	17
4.3.3 Support for Frame-based or Object-oriented Processing	18
4.3.4 Support for Procedural Programming	19
4.3.5 Uncertainty Measures	19
4.3.6 Induction Capabilities	20
4.3.7 Mathematical Functions	20
4.3.8 Developer and User Interfaces	20
4.3.9 Cost and Licensing Issues	21
4.3.10 Final Assessment	21
5. MACHINE LEARNING APPROACHES	23
6. FINAL RECOMMENDATIONS	29
ACKNOWLEDGEMENTS	35
REFERENCES	37

APPENDIX A: DEFINITION OF TERMS FROM THE TOOL MATRIX	39
APPENDIX B: HARDWARE AND SOFTWARE REQUIREMENTS	41
APPENDIX C: HUMAN FACTORS	43
APPENDIX D: A LEVEL5 OBJECT KNOWLEDGE BASE	45
APPENDIX E: SYSTEM EVALUATION CRITERIA	57
APPENDIX F: COMPARISON OF KNOWLEDGE-BASED SYSTEM SHELLS FOR THE PC	61
APPENDIX G: STATEMENT OF FUNCTIONAL REQUIREMENTS	65

LIST OF FIGURES

Figure 1 Learning and Classification Systems.	23
Figure 2 Types of Decision Trees	25
Figure 3 A Proposed Incremental Learning Architecture	28

ABSTRACT

This report presents recommendations relative to the use of expert systems and machine learning techniques by the Bureau of Labor Statistics (BLS) to substantially automate product substitution decisions associated with the Consumer Price Index (CPI). Thirteen commercially available, PC-based expert system shells have received in-depth evaluations. Various machine learning techniques were also reviewed. Two recommendations are given: (1) BLS should use the expert system shell **LEVEL5 OBJECT** and establish a software development methodology for expert systems; and (2) BLS should undertake a small study to evaluate the potential of machine learning techniques to create and maintain the approximately 350 ELI-specific knowledge bases to be used in CPI product substitution review.

1. INTRODUCTION

Each month, the Bureau of Labor Statistics (BLS) issues an update of the Consumer Price Index (CPI). The CPI compares the prices of a fixed set of goods and services over time. However, as the market changes so does the availability of the goods and services included in the CPI. In order to track price changes over a period of several months, it often becomes necessary to substitute a new product for one that was previously used in the index but which is not currently available. If a substitution is judged to be non-comparable, that product must generally be excluded from the reported data for one pricing period because the old and new products are not of equal quality or value and therefore cannot be compared. Comparable substitutions can be used for price change comparison through direct or adjusted comparison.

The Division of Price and Index Number Research, Consumer Prices and Price Indexes (DCCPI), Price Statistical Methods, and Consumer Prices and Consumption Studies conducted a feasibility study of expert system technology to assist DCCPI commodity analysts in determining the comparability of CPI product substitutions. Pilot applications captured the expert knowledge used in the product review process and encoded that knowledge in an expert system shell. The shell chosen for this pilot was PC Plus, a rule-based shell developed by Texas Instruments. The team initially defined the expert system to be successful if it demonstrated 100% correctness on non-comparable decisions and was able to arrive at comparability decisions 50% of the time. The results of this study are documented in an internal report entitled Feasibility of Using an Expert System to Review Product Substitutions.

In studying the applicability of expert systems for this task, members of that Expert System Research Group selected twelve of 350 Entry Level Items, (ELI, i.e., units used for product classification) for study. In order to quantify their results, the team devised a measure of complexity based upon the number and types of specifications for each ELI. Two approaches to designing the sample knowledge bases were tried. A generic approach sought to devise production rules which were applicable to all ELIs, and an ELI-specific approach dictated the creation of separate knowledge bases for each ELI. From the studies, team members found a strong positive correlation between the measure of complexity and the substitution rates. The more complex an ELI was, the more likely it was to have a higher rate of product substitution. The team concluded that those knowledge bases constructed for individual ELIs more frequently agreed with the decisions of commodity analysts and recommended that this approach be followed. The team concluded that the results of the pilot were sufficiently promising to warrant further study, but that a more rigorous approach to knowledge base construction and testing was required to reach those objectives set forth by the team.

This report presents recommendations, with supporting documentation, prepared by Oak Ridge National Laboratory (ORNL) to BLS for the next generation of expert systems for the review of CPI product substitutions. The next section discusses the project goals in more detail. Section 3 outlines the methodology used to generate the recommendations. Section 4 presents an analysis of expert system shells that could be employed by BLS. Section 5 follows with a discussion of the potential for using machine learning techniques to create ELI-specific knowledge bases for product substitution. Section 6 gives the final recommendations.

2. PROJECT GOALS

The goal of this project is to develop recommendations for the next generation of expert systems which review CPI product substitutions. Any proposed expert system should meet three criteria set by the Bureau of Labor Statistics. First, it must be able to determine whether a set of product specifications are complete and consistent. Second, it must provide a means of capturing and retaining expertise in reviewing product substitutions. Third, it should reduce the time that commodity analysts spend on routine product substitutions. This will allow them to concentrate on more difficult substitutions and to improve product checklists. In the near term, any expert system developed for this task will be a post-production research tool which allows commodity analysts to critique its performance and to refine and expand its knowledge base as needed. In the long term, a successful expert system would serve as a pre-production screening tool running in batch mode, rejecting those substitutions which are clearly non-comparable and generating reports which would assist commodity analysts in manually reviewing the remaining substitutions.

ORNL studied the CPI product substitution review process and the results of an earlier DCCPI study. In the pilot study, several difficulties were encountered in developing expert systems for product substitution review. In several cases, knowledge supplied to an expert system was insufficient and led to the system making incorrect decisions. Further investigation determined that the expert's knowledge had not been completely captured and encoded into production rules. Another problem was the apparent need to create ELI-specific knowledge bases for each of the 350 ELIs. This constitutes a major knowledge engineering effort. Still another problem was the difficulty in using the expert system shell PC Plus. Commodity analysts disliked the tool as it severely limited their ability to represent their expertise. This project addresses the resolution of these issues.

Our primary goal is to recommend tools and techniques which will promote the development of expert systems by commodity analysts. To identify them, we

- propose several approaches for implementing expert systems which review CPI product substitutions and rank them according to their fit with BLS requirements,
- for comparability, analyze hardware and software configurations used by commodity analysts, and
- define criteria by which expert system shells can be judged and perform an extensive tool evaluation based on these criteria.

A secondary goal is to explore the possibility of using machine learning techniques to automatically generate knowledge bases for each of the 350 ELIs. We

- determine the feasibility of using these techniques to produce knowledge bases from large numbers of previously reviewed product substitutions, and
- identify those techniques and tools which are the most appropriate for this task.

In Section 6 of this report, ORNL recommends an expert system shell for continued expert system development by BLS and a course of action for integrating expert system technology into BLS production activities in a timely and cost-effective manner.

The focus of this report on expert system technology should be viewed within the broader goals of the Professional Review System (PRS). When completed, the PRS will provide BLS commodity analysts with a full range of capabilities to review and work with commodity price data and quotes. The strategic issue raised with respect to expert systems is not whether to provide automated support for commodity analysts but the extent to which commodity analysts should be involved in the automation process. Traditionally, systems such as the PRS are developed and maintained by a separate computer system development team. Users are typically not allowed to alter the system, but they can exercise system functions and prepare data inputs.

Extensive use of expert systems in the PRS requires a change in system development strategy. Instead of being passive users, the commodity analysts will be responsible for developing and maintaining a large component of PRS. The principal issue under consideration is whether to empower the commodity analysts with the ability to create their own computer applications within the PRS framework. This report helps answer this question by reviewing expert system and machine learning technologies to determine the opportunities and limits that they place upon the empowerment concept. The concluding paragraphs of Section 6 extend the discussion of empowerment to include topics of quality assurance and other aspects of the PRS.

3. METHODOLOGY

As stated previously, our goals are (1) to recommend a commercially available expert system shell which commodity analysts can use to develop ELI-specific knowledge bases and (2) to investigate the use of machine learning techniques to generate these knowledge bases from historical data and user-supplied test cases. In order to identify those shells which will most closely meet the requirements for a powerful, user-friendly tool, we

- proposed several approaches for implementing expert systems which review CPI product substitutions and ranked them according to their fit with BLS/CPI requirements,
- analyzed the hardware and software configurations used by BLS/CPI commodity analysts, and
- defined criteria by which expert system shells can be judged and performed an extensive tool evaluation based on these criteria (Appendix F).

In Section 5 we propose five system alternatives which cover the spectrum of expert system development from traditional approaches to the induction of knowledge bases using machine learning techniques. The first two proposals have commodity analysts using knowledge engineering techniques to organize and represent their expertise in a user-friendly expert system shell. A comprehensive tool survey identified products which could be used in this task and a tool evaluation based on BLS/CPI needs and resources determined which tools possess the necessary capabilities. The last three proposals considered machine learning techniques to analyze large amounts of data as a means of acquiring product substitution expertise.

By proposing a number of efforts with varied degree of complexity and risk, we thoroughly covered the range of developmental techniques. As the knowledge engineering function becomes more automated, the greater the risks are in achieving complete success; conversely, the success of such ambitious projects constitutes a much greater return on investment as the need to conduct separate knowledge engineering tasks for each ELI is greatly reduced or eliminated altogether.

In an initial meeting BLS/CPI staff provided the criteria by which a successful project might be judged; these criteria are represented in a matrix shown in Appendix E. The system evaluation criteria have been broken down into project goals and system requirements. Project goals were the long-term shift of CA workloads, the checking of substitutions for completeness and consistency, and the documentation of product substitution expertise. System requirements focused upon the ease of use and basic functionality. These factors have been assigned numerical weights based upon their perceived importance by BLS staff. Using these factors, we constructed the criteria matrix to allow us to rank the proposals. Each cell in the matrix corresponding to an alternative (i.e., a row entry) was assigned a score based upon its applicability with project goals or system requirements (i.e., a column heading). These scores were multiplied by their respective weights and summed to obtain a single numerical value. The numerical values for each alternative were then used to make the recommendations in Section 6. Consulting with BLS staff, we clarified the criteria by which alternatives are to be judged and identified the hardware and software configurations in use at the Bureau of Labor Statistics (Appendix B). We also learned more about the product substitution task and the backgrounds of the commodity analysts assigned to these tasks (Appendix C).

We presented the interim findings, including a tool matrix which was constructed using data obtained by the tool survey and evaluation. We demonstrated a few of the expert system shells to give BLS staff additional exposure to the tools we considered and to learn more about their perceptions of which features in a product are user-friendly, which features they considered essential, and which additional features might be beneficial. From this discussion, we modified and expanded the set of criteria to be used in the tool matrix. We discussed the implementation of the "white bread" knowledge base in a suite of selected tools (see Appendix D for the "white bread" example encoded in the expert system shell which was ultimately recommended). This permitted us to contrast knowledge representation and processing capabilities among a representative sampling of tools. We looked principally at the knowledge representation, inference mechanisms and data management facilities of the tools being considered. Display capabilities were not a primary concern because the goal of the system is to produce an expert system that runs in batch mode and generates the necessary reports. Interface capabilities, however, are important in employing this technology in other areas which may require greater interaction with BLS staff.

A secondary goal was to explore the possibility of using machine learning techniques to automatically generate knowledge bases for each of the 350 ELIs. We

- determined the feasibility of using these techniques to produce knowledge bases from large numbers of previously reviewed product substitutions and user-supplied test cases, and
- identified those techniques and tools which are the most appropriate for this task.

To accomplish this, we first characterized the product substitution process and contrasted it with other applications that have used machine learning techniques. A literature search was conducted to identify the most promising algorithms and any software implementations.

After a set of algorithms had been identified and the software which implements these algorithms had been obtained, a small set of test data was used to obtain some preliminary results on the success of learning techniques for this application. These results were used to predict the success of using similar techniques for much larger and more complicated test data.

Upon completion of both the tool evaluation and machine learning studies, ORNL had the information to evaluate the options available to BLS for developing expert systems. The recommended strategy of expert systems development thoroughly considers the impact of expert systems on CPI product substitution review, their development, and their ultimate integration into BLS production activities in a timely and cost-effective manner.

4. TOOL SURVEY AND EVALUATION

In designing the tool matrix presented in Appendix F we have considered BLS/CPI hardware and software configurations and a set of capabilities that we believe are desirable, if not actually required, for the CPI product substitution review and other candidate expert systems being considered by BLS. We have evaluated only those PC-based tools which run under MS-DOS or OS/2. We considered the ease of integrating each tool into existing computer applications. To interact with other programs, an expert system should be able to read and write data from one or more external file formats and to call or be called from external programs. We have specified whether each tool can handle directly the following types of files: ASCII, dBase, Lotus 1-2-3 and SQL. Most shells provide the capability to call and to be called from external programs. Data exchange is then managed by file creation or Dynamic Data Exchange (DDE) capabilities. Many tools provide callable libraries, (i.e., subroutines written in a conventional programming language which are called within other computer programs). This allows rule-based processing to be embedded into larger, conventional processing, e.g. the Professional Review System (PRS). PRS programs can then access the expert knowledge and conclusions generated by the expert system without performing file I/O. Instead, the subroutines store data from the expert system in variables declared by the PRS source code. This is a much faster means of passing data between an expert system and another program.

We evaluated each tool and its support for the three most widely used programming paradigms found in the design of expert systems: rule-based, procedural, and object-oriented processing. Rule-based systems must support forward or backward chaining or both. In some cases, forward chaining rules are called demons and are attached to object, frames or other data elements. Pattern matching is seen as a necessary facility, particularly for searching through several specifications or processing free text specifications. The ability to customize the ordering of rule-firing is considered important to tune applications for better performance. Procedural processing is considered desirable since it will allow commodity analysts to implement certain functions in a more straightforward manner than with rules or objects. Central to this paradigm is the support for modular code. Language support for case and else statements signify an expressive syntax for code development. List or array processing is needed to support any type of free text processing. The object-oriented paradigm is included because its functionality in most expert system shells represents an evolution from purely rule-based paradigms. Object-oriented or frame systems provide a concise representation of hierarchical concepts. Default properties and procedures can also be supported. We indicate the degree to which each shell supports this paradigm. Most frame systems support a restricted version of encapsulation and allow inheritance. This level of sophistication appears adequate for most BLS applications.

Other features have been considered. While BLS requires 100% confidence for screening non-comparable substitutions, certainty or confidence factors can be used to perform conditional product substitution reviews which are later confirmed by commodity analysts. The expert system must be capable of justifying its reasoning like any other analyst. Typically, explanations from expert systems consist of how a conclusion was reached and which rules fired during an interaction. Commodity analysts can analyze the rule-firing patterns to detect erroneous rules or to suggest more efficient rule-firing strategies. Mathematical functions permit simple statistical analyses by the expert system. User interface support for developers and end users should be good. Team members favor a Microsoft Windows "look and feel." BLS conducts internal training classes on Windows and BLS staff are confident that most commodity analysts will prefer the Windows interface to character-based or non-standard interfaces.

Given the criteria established by BLS/CPI and our knowledge of the expert system market, we chose over a dozen commercially available PC-based shells for our evaluation. Collectively, these shells constitute an overwhelming (perhaps as high as 90%) portion of the overall market for these products. Some are high-end tools which provide a migration path from PCs to workstations and VAXes or mainframes. A few are research-oriented tools which provide complete programming support for exploratory research and development efforts. Others are available only on the PC. By covering the spectrum of shells running on numerous hardware platforms, we can present a thorough tool evaluation. The following products, with the associated vendor, are included in this survey:

<u>PRODUCT</u>	<u>VENDOR</u>
Aion Development System (ADS)	Aion Corporation
ART/IM	Inference Corporation
CLIPS	NASA
EXSYS Professional	EXSYS
GURU	mdbs, Inc.
Intelligence Compiler	Intelligence Ware, Inc.
KBMS/PC and 1st Class HT	AI Corporation
KES	Software A & E
KnowledgePro	Knowledge Garden, Inc.
LEVEL5 OBJECT	Information Builders, Inc.
NEXPERT Object	Neuron Data
Kappa PC	IntelliCorp

Material regarding these tools was gathered from several sources, including our own hands-on experience with several of the products, since many of them have been used at ORNL. Vendors have supplied us with their product literature, and this information has been supplemented by viewing several product demonstrations held at the Ninth National Conference of Artificial Intelligence in Anaheim, California. To contrast the features of a small suite of shells, the specifications of a small knowledge base, (i.e., BLS "white bread" example), have been supplied to team members. From the PC Plus specification, we encoded the knowledge base into several shells. A sample knowledge base has the following functionality:

- data are read into the system from either ASCII or dBase files,
- objects, i.e., frames represent the old and new specifications,
- rules determine completeness and comparability of specifications, and
- results are analyzed.

This is not meant to serve as a detailed prototype of an expert system for the "white bread" ELI. It is intended to demonstrate the differences between a selected suite of expert system shells in representing the same problem. Emphasis has been placed upon the knowledge representation facilities, the inference mechanisms, and the external file interfaces of each tool. Display screens were minimal since some tool interfaces were character-based while others were Graphic User Interface-based (GUI).

In its annual product survey, PC AI has compiled a less detailed survey of expert system tools from vendor submissions to the magazine. Their survey is a reference to current vendor offerings and does not compare the tools using standard criteria.

4.1 TRENDS

Several trends are emerging in the expert system shell marketplace. The capabilities matrix shown in Appendix F can be used to identify those tools which are embracing some of the new technologies or are emphasizing their compatibility with existing hardware and software environments.

Most commercial products are designed to run on more than one hardware platform. Software developers can then prototype their designs on PCs and migrate the final product to larger platforms. This is an important consideration when choosing an expert system shell.

Many vendors are integrating their product with Microsoft Windows 3.0. In this manner, an expert system shell can use the GUI provided by Windows to provide a user-friendly development environment. Developers and users familiar with Windows can begin using these shells more quickly than products with their own custom interface. In addition, the expert system shell's running under Windows DDE and Dynamic Data Library (DDL) can transfer information without reading and writing temporary ASCII files. With DDL, expert system shells can augment their set of functions with additional functions that have been compiled into the DDL. Since this represents a dramatic improvement over other methods for accessing external data and functions, several vendors are planning to support DDE and DDL in the near future.

Many tools support multiple programming paradigms. Rule-based programming has traditionally been the primary mechanism for representing and processing knowledge. However, other programming styles may be more appropriate in certain settings, and many tools are accommodating these approaches. Procedural programming, the conventional approach to building computer applications, is available in an increasing number of shells. This permits developers to encode algorithms in the shell using a high-level language. Earlier shells required all knowledge to conform to a rule-based representation or forced developers to execute external programs. The former approach resulted in convoluted representations because the rule-based paradigm was ill-suited for algorithmic design; the latter involved complicated or time-consuming communications between computer programs.

Frame-based or object-oriented programming is another paradigm being supported in expert system shells. Many of the products which claim to be object-oriented are actually frame-based. As originally defined, frames are stereotypical situations which have default values and actions. Frames can be thought of as data structures which can be manipulated by rule or procedural-based programming. Similar to frames, objects are entities which are grouped together into higher abstractions called classes which have default values and behaviors. Frame-based programming consists of accessing one or more slots within a frame, thereby activating procedures attached to those slots; object-oriented programming consists of objects requesting other objects to perform some activity, (i.e., changing the values of one or more of its slots). As expert system shells mature, many of the frame-based systems will include some type of message passing architecture.

The marketplace is constantly changing. Vendors are continually upgrading their products in the highly competitive PC markets. Software costs for PC-based expert system shells have remained stable or even decreased in the past few years as tool capabilities have increased. By continuing to assess PC-based expert system shells, the capabilities matrix can be revised and serve as a template to be used in evaluating new and existing shells.

4.2 COMMERCIALY AVAILABLE EXPERT SYSTEM SHELLS

We had hands-on experience with ten of the thirteen expert systems shells presented in this report. We had experience with recent releases of seven of the thirteen shells: ADS, ART/IM, CLIPS, EXSYS Professional, KnowledgePro, LEVEL5 Object, and NEXPERT Object. For an additional three shells, we had experience with earlier versions of the products: 1st Class HT, Intelligence Compiler, and GURU. For these products we supplemented our knowledge by reviewing more recent vendor literature, by discussing new features with vendor personnel, and by viewing later versions of the product at conferences. Two shells were evaluated on the basis of lengthy product demonstrations and discussions with vendor personnel at the Ninth National Conference on Artificial Intelligence held in Anaheim, California: KBMS/PC and Kappa PC. Only KES was evaluated solely on the basis of vendor literature and interviews with vendor personnel.

Having identified those features which were of interest, we constructed the tool matrix shown in Appendix F. In some cases, we supplemented our knowledge of a tool with additional information supplied by the vendor, either through product literature or interviews with technical personnel. The descriptions given in the following sections are brief, but should serve to differentiate the various products.

4.2.1 Aion Development System

The Aion Development System (ADS) is a high-end expert system tool which supports the procedural, rule-based and object-oriented programming paradigms. ADS supports both forward and backward chaining. Rules can be declared to fire only once or as often as needed. Several system-defined demons are provided so that rules can fire whenever data values referenced in their antecedents change. The object-oriented paradigm is supported through class definitions and user-defined methods. Objects are activated by sending messages to either an entire class or an individual instance of that class. Class hierarchies can be viewed graphically using the function keys provided in the development interface.

This product is one of the premier tools in the industry, but it is principally targeted for large IBM mainframe systems. The PC version is fully compatible with its mainframe counterpart. To achieve this compatibility, the PC version provides a character-based editing environment and display screens which seem limited compared to that of other PC products. Data import facilities are limited to DOS and IBM mainframe file formats. VAX/VMS and UNIX versions of the product are scheduled for later this year.

In order to access Lotus 1-2-3 file formats, the FIXEDREC program must convert the file into a file of fixed-length records. This program is executed by defining the command to be an ADS process object which is called at the appropriate time. To read a file from Lotus 1-2-3, an ADS record definition must be declared and the spreadsheet columns must match the ADS record definition, dates must be converted to integers or a DD-MMM-YY format. To create a Lotus 1-2-3 file, the file must be imported and other commands put the file into the appropriate format.

A developer can represent uncertainty by using certainty sets and the functions which manipulate them. Certainty sets are real numbers with a range of -1.00 to 1.00 inclusive. Values from -0.2 to 0.2 represent a value of UNKNOWN; this threshold can be modified by the developer. Those values

greater than or equal to 0.2 are interpreted as true for the purposes of rule processing; conversely, all values less than -0.2 are interpreted as false.

4.2.2 ART/IM

ART/IM is a powerful expert system tool which supports rule-based and object-oriented programming. An earlier version named ART was one of the first commercially available expert system tools. An agenda manages the forward chaining in ART/IM. As the conditions of a rule change, the rule is fired to determine whether its conclusion has been reached. A pattern matcher allows the product to represent generalized rules. Rules are defined using a `defrule` construction in place of `if .. then` statements; this syntax allows rules to be annotated with documentation and certainty factors (called *salience*s in ART/IM terminology). Backward chaining is not directly supported by ART/IM, but can be implemented easily.

ART/IM, while powerful, has a very complicated syntax and does not lend itself to end-user development. This tool can be used with a companion product, called CBR Express (CBR standing for Case-Based Reasoning). With this technology, test cases can be entered into a database and the best matches are simply retrieved. Case-based reasoning is a new paradigm for designing intelligent systems and shows great promise in several areas. CBR Express is the first commercially available product which utilizes this technology.

4.2.3 CLIPS

CLIPS (C Language Integrated Production System) is an expert system tool modeled after ART. It is developed and maintained by the Software Technology Branch at NASA Johnson Space Center. Written in the C programming language, it is meant to be a portable tool which can be embedded within conventional applications. It is patterned after ART because NASA personnel have worked with ART and needed similar functionality on conventional hardware platforms. As stated in the CLIPS Reference Manual, "the syntax of CLIPS was made to very closely resemble the syntax of a subset of the ART expert system tool developed by Inference Corporation." This was achieved without any assistance from Inference and without access to ART source code.

The CLIPS distribution includes all source code. CLIPS is installed by compiling the source code on the target platform. CLIPS can be embedded within procedural code, called as a subroutine, and integrated with programming languages other than C, e.g., FORTRAN and ADA. CLIPS can be extended with user-defined functions. In fact, some extensions to the language have included backward chaining and hypertext capabilities. These extensions are not distributed with the CLIPS source code.

The CLIPS Object Oriented Language (COOL) is a hybrid language which provides additional capabilities to the CLIPS kernel. An object in CLIPS can be one of the following: an integer or floating-point number, a symbol, a string, a multifield value, or an instance of a user-defined class. Instances of a user-defined class can only be manipulated with messages. CLIPS does not support metaclasses. Pattern matching against the state of an instance of a user-defined class is not allowed. This deficiency inhibits developers from using the multiple paradigms supported in CLIPS.

4.2.4 EXSYS Professional

EXSYS Professional supports both rule and frame-based processing. Confidence factors are supported to permit inexact reasoning. EXSYS offers a "what-if" capability which allows users to change some of the conditions during a consultation and rerun the consultation. EXSYS can then compare the old and new results to determine what caused the changes. The "Why" facility shows the trace of rules used to reach a conclusion. The rules, however, require that all data comparisons are between EXSYS variables, (i.e., the attribute-value pairs which are used to represent some concepts in EXSYS cannot be compared directly).

Production rules in EXSYS are stored in two files with the extensions .RUL and .TXT. EXSYS Professional provides a command language to control the execution of a knowledge base. The command language provides control mechanisms for data input, execution of rules, looping, and branching. These commands reside in the file <filename>.CMD.

Data are transmitted between the EXSYS and external programs using the ASCII files named PASS.DAT and RETURN.DAT, respectively.

EXSYS Options is a toolkit which extends the functionality of EXSYS Professional. This includes LINDO, a linear, integer and quadratic programming package to solve optimization problems, e.g., scheduling, routing, etc. INDUCEXS is an EXSYS front end that builds production rules from a table of data. A forms front end and user interface allows users to create screens and a fill-in-form version of the report generator. Another product, the Linkable Object Module Library, allows EXSYS to be embedded in conventional data processing applications.

4.2.5 GURU

GURU is a rule-based tool which supports forward, backward and mixed rule processing. When searching for the next rule to be fired, numerous search strategies can be defined for the application. Rudimentary statistical analyses are available. GURU also supports a structured programming language with *else* and *case* statements. This tool has no object-oriented capabilities. It supports certainty measures and fuzzy reasoning. GURU has a direct interface to SQL Server.

GURU Solveur is a diagnostic tool. In this package, experts describe an observed problem, the symptoms associated with the problem, the possible causes and solutions to the problem, along with questions that need to be asked to arrive at a solution.

4.2.6 Intelligence Compiler

Intelligence Compiler is one of several products developed and marketed by IntelligenceWare, Inc. of Los Angeles, California. It permits both rule-based and frame-based programming. The product has its own Window, Icon, Mouse, Pointer (WIMP) interface, and there are no immediate plans to integrate Intelligence Compiler with Windows. The tool's editor provides a pull-down menu and rules are entered in text. The product supports hypertext applications. Production rules can be given uncertainty measures and rule firing can be based on adjustable thresholds. The tool cannot be embedded into other applications.

Two complementary products, IXL and Auto-Intelligence, are available from the vendor. IXL discovers rules from large amounts of data which can then be used by Intelligence Compiler. There is no limit on the number of cases that can be supplied to IXL and a maximum of 64,000 attributes can be represented in each case. Learning can be influenced by placing weights on the various attributes. While the system can infer attributes with intervals, continuous attributes are not supported. IXL uses a proprietary learning algorithm that permits it to handle massive amounts of data. Technical representatives from IntelligenceWare stated that the algorithm was not designed to address problems similar to product comparability, but felt confident that their product could be modified to handle such a situation.

Auto-Intelligence is a knowledge elicitation system which interviews experts, and through a series of questions develops a set of cases which can then be used to infer production rules. The results of this activity can also be used by Intelligence Compiler.

While IXL and Auto-Intelligence are intriguing and products with these capabilities might serve to broaden BLS knowledge of machine learning paradigms, it is unlikely that the results of these programs could be used without significant customization according to the requirements of CPI product substitution. However, the pricing policies for IXL and Auto-Intelligence are such that the Bureau of Labor Statistics could study the efficacy of these products.

4.2.7 KBMS/PC

Like ADS, Knowledge-Based Management System for the PC (KBMS/PC) is a high-end product designed to run in a mainframe environment. KBMS supports forward and backward chaining, hypothetical reasoning, and object-oriented programming. KBMS allows the procedural attachment of rules (i.e., demons) at the object and attribute level. The product supports pattern matching and allows the developer to control the order in which rules are evaluated and fired. Active Objects is the facility within KBMS that supports the development of GUIs. This facility allows developers to create icons.

The INTELLECT natural language system is embedded within KBMS, allowing easy access to data and applications. This product is not embeddable, but a manual interface is available using the User Defined Object facility. This allows developers to access proprietary databases, user-written routines, and external devices.

KBMS objects support procedural attachments, or methods, that can be attached to entire object definitions or individual attributes. Object attachments may be any combination of WHEN CREATED, WHEN NEEDED, and WHEN DELETED; attribute attachments may be WHEN ASSIGNED and WHEN NEEDED. WHEN NEEDED attachments can be used to gather data only when required for processing.

4.2.8 1st Class HT

1st Class HT is an expert system tool which allows users to enter test cases into a spreadsheet editor or to specify production rules through the use of a menu-based interaction which represents the entries as a decision tree. Backward chaining is supported, but forward chaining is emulated through

the chaining of knowledge bases. A single knowledge base in 1st Class HT is limited to 255 unique examples.

This tool is designed for users with little or no experience with computer programming. While some commodity analysts might like the simple user interface, others might be frustrated with the product's lack of expressiveness. The induction capabilities of 1st Class HT are too limited to handle CPI product substitution because it can process only 255 examples. The need for specialized induction techniques has been discussed earlier.

4.2.9 KES

Knowledge Engineering System (KES) consists of two subsystems, Production Rule (PR) and Hypothesize and Test (HT). The first subsystem represents expertise as production rules and objects; the second takes several cases and tries to match the data with the new case. Since several matches are possible, H uses certainty factors to rank alternative choices. This type of reasoning, known as abduction, is very useful in diagnostic tasks where a large number of outcomes is possible.

KES is an embeddable product, which means that individual functions can be called and an external program's data structures can be used directly by the tool. Tight integration with the Professional Review Systems (PRS) might require such capability at a later date. For the purposes of this study, however, we have assumed that embeddability is not a required feature.

4.2.10 KnowledgePro

KnowledgePro is a hypertext programming environment in which functions and production rules can be represented. There are both DOS and Windows versions of the product. All instructions are coded in a high-level programming language which provides window generation and other screen functions. All knowledge in this tool is represented as one or more hierarchical concepts called *topics*. These topics are processed in a top-down fashion or invoked using the *do* command. Backward chaining is accomplished through the *value-of* command. Production rules can be represented as topics or as procedures within topics. There are no high-level explanation capabilities; these must be implemented by the developer.

The data access capabilities of KnowledgePro seem inadequate for most applications. DOS text files are read in using delimiters. External file I/O is geared primarily to reading and writing large text files. The product does not support the storage of partial sessions to permanent media and their resumption at a later date. This facility can be supplied by user-supplied code. A separate database toolkit is required for KnowledgePro to access dBase and Lotus files. KnowledgePro is too limiting, and its hypertext capabilities are not needed to perform CPI production substitution.

Memory management capabilities of the DOS version are limited. Large knowledge bases must be segmented and removed from memory. Such performance tuning would hamper the ability of commodity analysts to building knowledge bases.

4.2.11 LEVEL5 OBJECT

LEVEL5 OBJECT is a frame-based tool which supports backward chaining. Frame-based systems represent knowledge as stereotypes, (i.e. concept definitions with default values and procedures). Some form of object-oriented and procedural programming is supported using this procedural attachment. Attributes of objects represented in LEVEL5 OBJECT may possess rules, demons, or methods.

Forward chaining is accomplished using demons; these demons can be declared using an IF THEN ELSE syntax. Whenever a value referenced in a demon changes, that demon is invoked. A non-trivial expert system can be developed using only demons to create a forward-chaining system with no agenda. Pattern matching allows developers to find those objects which match a template specified in a demon.

LEVEL5 OBJECT commands are case-sensitive. The developer interface exploits the Windows capabilities to provide a point-and-click interface which is desirable for end user development. Sophisticated screens can be generated by manipulating system-defined classes which represent menus, text boxes, hypertext displays, etc.

The ACTIVATE and ESTABLISH commands allow the expert system to call external programs from rules, demons, or methods. ACTIVATE is used when the external program will be called only once; ESTABLISH is used to pass information between LEVEL5 OBJECT and an external program. When used with these commands, SEND and RECEIVE statements allow a knowledge base to transmit values to or accept values from an external program. Data values are passed via memory. The data types of the parameters in the external program must match the attribute types referenced in these statements. LEVEL5 OBJECT cannot be embedded within other programs.

LEVEL5 OBJECT provides a useful mechanism for importing dBase files into an expert system using the external database class. Similar capabilities for LOTUS and SQL files are forthcoming.

LEVEL5 OBJECT represents certainty using confidence factors which are integer values ranging from -2 to 100. A value of -2 or UNKNOWN indicates that an attribute cannot be assigned a value. A value of -1 or UNDETERMINED indicates that an attribute has not been tested; consequently, it has not been given a value. Values from 0 to 100 indicate the degree to which an attribute is known. Zero indicates a completely false value while 100 indicates a completely true value. The default confidence threshold is 50 and can be changed from within a rule, demon or method.

4.2.12 NEXPERT/Object

NEXPERT/Object is a visual programming environment in which rules are defined using templates. These templates do not permit an else statement. Backward chaining is the default inference mechanism; forward chaining can be accomplished by "volunteering" data at the start of a session. Pattern matching rules may be used to select those objects which have the desired characteristics. These rules only operate on that class specifically mentioned in the rules; any subclasses which would logically be applicable due to inheritance are not recognized by the pattern matcher.

NEXPERT/Object has recently announced a new strategy for developing GUIs to knowledge-based systems and porting this interface across different platforms. The NEXPERT Open Architecture generates C source code which is then modified by the developer to include C subroutine calls to a library of expert system functions. The use of NEXPERT/Object and its Open Architecture requires an extensive knowledge of C programming.

4.2.13 Kappa PC

Kappa PC is a truly object-oriented expert system tool developed by Intellicorp of Mountain View, California. It allows developers to represent and model processes and activities. It supports both forward and backward chaining. It has direct interfaces between dBase III, Lotus 1-2-3 and Symphony file formats. An SQL interface is not included. The use of Windows simplifies the development process since both developer and user can navigate through the tool and any applications built from it in a straightforward fashion. Kappa PC can act as a Windows DDE client or server. Error-handling capabilities appear to be a weakness of the tool.

The planned acquisition of Intellicorp by KnowledgeWare, Inc. has been announced. It is too early to speculate on whether this development will impact future support for Kappa PC.

4.3 TOOL RECOMMENDATIONS

We have considered the capabilities of each tool, its ease of use, and its cost. We have evaluated the tools against a number of desirable features (Appendix F), some of which are not required for the particular application being studied, (i.e., review of CPI product substitutions), but which are part of a robust development environment. It is conceivable that other types of applications might be developed using the tool chosen as a result of this evaluation. For example, both the post-production review of product substitutions and the pre-production screening of product substitutions are basically batch processes, with little need for sophisticated user interfaces or hypertext. However, other types of expert systems might rely heavily upon such capabilities, e.g., training systems. Our recommendations reflect a desire to select a product which provides the greatest functionality at a reasonable cost.

4.3.1 External Data and Program Interfaces

Earlier generations of expert system shells were limited by their inability to access external data or to execute external programs. Today's business environment demands that expert system shells access data from existing databases and communicate with conventional applications. Most PC expert system shells can read dBase and Lotus 1-2-3 files as well as ASCII. Expert systems can create datafiles which are used by other applications or can share data with programs through concurrent program execution and inter-process communication, or linked subroutine libraries.

The only tool surveyed which had inadequate external data interfaces was KnowledgePro. A database toolkit for KnowledgePro is sold separately by the vendor. This toolkit allows KnowledgePro to access dBase and Lotus files, but formatted ASCII files can only be read as character strings. A few

of the expert system shells have an SQL interface and other vendors plan to include this capability in future releases.

Expert systems can be integrated into existing computer applications through the use of external program interfaces. Conventional data processing systems can utilize the expertise represented in expert systems; conversely, expert systems can obtain information using existing data collection programs and analyze data using standard statistical packages. Call-in/call-out capabilities allow expert systems to be called from and executed by external programs, respectively. *This is the minimum functionality required.* Data are passed back and forth using datafiles or, less frequently, common memory locations. Many vendors use or plan to use Microsoft Windows 3.0 DDE to transmit data between applications. Embeddable expert systems are linked to conventional programs. The inference engine is then activated by subroutine calls and expert knowledge can be referenced directly by the conventional program. This approach yields tighter integration and faster processing than achievable through call-in/call-out techniques, but often requires programming expertise to implement the subroutine calls and to interpret the results. Embeddable systems introduce a level of complexity unwarranted by the target application; however, they would facilitate the integration of expert system capabilities into the PRS.

4.3.2 Support for Rule-based Processing

Production rules form the basis for most expert systems. An inference engine arrives at its decisions by searching through the set of possible conclusions and finding those that are consistent with the data provided to the system. This search is conducted by firing production rules according to a particular search strategy. Forward chaining, or data-driven reasoning, fires those rules whose antecedents (i.e., left-hand side of the rule) match the data provided to reach a conclusion (i.e., right-hand side of the rule). Backward chaining, or goal-driven reasoning, starts with the conclusion of a rule and determines whether those antecedents match the data. Mixed-mode rule firing denotes the integration of forward and backward chaining. An example of mixed-mode processing would be the use of forward-chaining rules to suggest conclusions for backward chaining. Some tools allow rules to be prioritized to dictate the order in which rules are fired when more than one rule can be fired.

Forward chaining is best suited for those problems which may have a large number of possible solutions. It requires that the information used to solve the problem be available. Forward-chaining applications include process monitoring, configuration, scheduling, and simulation. Backward chaining is preferable for those applications where a small number of possible solutions are known, but the required data may be unknown. Backward chaining tries to determine what information is available and whether it corroborates one of the possible solutions. The inference process is finished when a solution has been obtained or has been ruled out. Backward-chaining applications include diagnostic and classification problems. The problem of reviewing product substitutions has some unique aspects; these are discussed in the next paragraph.

For product substitutions, product specifications and any associated free text will be available to the commodity analyst and the expert system. While there is a single decision for determining whether products are comparable, this decision relies upon several other decisions. Product specifications could be incomplete or inconsistent, or pre-processing of free text specifications might be required to compare specifications. A forward-chaining strategy will process each of these decisions, but a backward-chaining strategy will stop processing these decisions when it has been determined that the

products are not comparable. The commodity analyst, however, might be interested in learning about incomplete or inconsistent specifications that might not be identified by backward chaining. For this reason, we conclude that the review process is best suited for a forward-chaining application. Mixed mode processing, (i.e., both forward and backward chaining), might be advantageous in determining the comparability of free-text specifications. *Therefore, a recommended tool should support both forward and backward chaining to provide a greater degree of flexibility to the developer.*

Expert systems make decisions based upon available data, and some applications need to search through this data for patterns. Pattern matching is the search for specific patterns within the data residing in the system. For instance, a single pattern matching rule might detect all free text, (i.e. '99'), specifications. Without this capability, several rules might be required to examine each specification. Pattern matching promotes more generalized production rules, thus simplifying the expert system development process. *Pattern matching should be considered an indispensable feature when discussing expert system shells. This eliminates the following tools from consideration: GURU, KnowledgePro, and 1st Class HT.*

4.3.3 Support for Frame-based or Object-oriented Processing

Frames are another form of knowledge representation. Originally proposed by Minsky, they are stereotypical situations or physical entities which have default values and actions. Frames are data structures which can be manipulated by rule or procedural-based programming. They can inherit properties from other frames. Frame-based programming consists of accessing one or more slots within a frame, thereby activating procedures attached to those slots. Production rules can access and modify slot values within frames, perhaps activating attached procedures in the process. Most expert system shells are frame-based; however, as these shells mature, more of them will support the object-oriented paradigm.

The object-oriented paradigm is more powerful than frame-based representations. Objects can be grouped together into higher abstractions called classes which have default values and behaviors. The paradigm is based on three principles: encapsulation, inheritance, and polymorphism. Encapsulation defines an object as both data, (i.e., slots), and the procedures which manipulate that data, (i.e., methods). Encapsulation encourages developers to restrict access to slot values and to enforce consistent data manipulations. Inheritance allows objects to share data and procedures among hierarchies of class objects, yet allows the inherited data and procedures to be extended through new slot and method definitions. Polymorphism permits different procedures to be invoked using the same function call by letting the type of object being processed specify which function should be called. Object-oriented programming consists of objects requesting other objects to perform some activity, e.g., changing the values of one or more of its slots. Although a more natural approach to knowledge representation, the object-oriented paradigm represents a fundamentally different approach to software development. As with all new technologies, some education will be required to introduce this approach to commodity analysts and computer programmers at the Bureau of Labor Statistics.

CPI specifications can be represented as either frames or objects. More sophisticated applications may require an object-oriented approach, but any new paradigm entails additional training. The frame-based representation introduces many of the same concepts, e.g., inheritance, but is based on

a procedural view of programming. *Any expert system shell chosen for BLS should support frame-based or object-oriented processing.*

4.3.4 Support for Procedural Programming

Rule-based programming has traditionally been the primary mechanism for representing and processing knowledge, but other programming paradigms may be more appropriate in some situations. Iterative programming constructs such as for, while and case statements, violate the spirit of rule-based processing because there is no separation of knowledge and its use. Several expert system shells have their own programming language to accommodate these constructs. In this manner, developers can use the paradigm which best fits the problem. Developers can use production rules to represent expert knowledge and can encode algorithms in an expert system using a high-level language syntax.

Most expert system shells support some degree of procedural processing. Frame-based systems allow procedures to be attached to slots. Two examples of these procedures are WHEN-NEEDED and WHEN-MODIFIED. When slots with the applicable attached procedures are accessed, these procedures are executed. Object-oriented programming allows developers to define procedural code which implements the behavior of a group of objects. A few sophisticated tools permit program modules and functions to be created independently of frames or objects. These modules are processed sequentially. Production rules are arranged into rule sets, defined in one of the program modules, and fired whenever that module is entered. Such capabilities are reserved for those mainframe and workstation-based tools which have PC versions to accommodate system development. *A tool permitting procedural attachments to frames should provide ample functionality for BLS.*

The tool should handle lists or arrays. Since natural language analysis of free text is an open research problem, processing free text associated with '99' specifications may require look-up tables containing frequently-used terms or phrases.

4.3.5 Uncertainty Measures

Humans are capable of making decisions with incomplete or uncertain information. Some expert system shells use numerical weights to represent the degree to which a piece of data is to be believed. Rules can then be fired when all its antecedents exceed the threshold value representing sufficient belief in a data item to warrant further processing. This form of inexact reasoning permits expert systems to process uncertain information, but can lead to erroneous conclusions.

Some at BLS feel that there must be no uncertainty in decision making, (i.e., there must be 100% accuracy). However, the use of inexact reasoning in a pre-production tool might grade those product substitutions which can not be categorically rejected. These grades could then serve as a decision tool to assist commodity analysts with their own decision-making processes. *Consequently, a desirable feature of a tool is to allow the assignment and processing of uncertainty measurements.*

4.3.6 Induction Capabilities

Induction is the process of forming generalizations based upon specific instances. Few shells induce production rules or decision trees from data, but several have companion products which perform induction and represent the results using data structures provided by that tool. 1st Class HT allows users to enter data using a spreadsheet layout and generates decision trees from the spreadsheet while EXSYS Professional, Intelligence Compiler, KnowledgePro and NEXPERT Object have companion learning tools. When discussing learning systems, it is important to differentiate between general-purpose and domain-specific induction algorithms. General-purpose algorithms learn decision rules based on analysis of attributes and the values that they may take; domain-specific algorithms have some knowledge of the problem which they can use to simplify the recognition of data relationships that represent knowledge and the arrangement of that knowledge in a meaningful representation. Commercial learning systems use general-purpose algorithms to solve the widest range of problems for the largest number of potential customers. *These general techniques are ineffective for specialized problems such as product comparability.* See Section 5 for a more detailed discussion of machine learning and induction algorithms.

4.3.7 Mathematical Functions

BLS needs to compile decision statistics which gauge the effectiveness of any screening tool for reviewing product substitutions. *With the exception of KnowledgePro, all the expert system shells listed in the capabilities matrix have sufficient mathematical functions to perform rudimentary analysis.* More sophisticated statistical analyses would need to be conducted using a statistical package, e.g. SAS.

4.3.8 Developer and User Interfaces

The developer and user interfaces for any expert system shell are among the most important considerations when selecting a tool. The developer's interface should be evaluated on the basis of how easy it is for the developer to represent the knowledge. Since commodity analysts will be the developers of any expert systems built for BLS, tools with a WIMP interface should be easier for the analysts to learn and use. In discussions with several staff members at BLS, we concluded that a "windows look and feel" was desirable. Using a tool that uses Windows to provide the developer and user interfaces was considered ideal because a developer or user familiar with Windows would be comfortable with the expert system interface. While recognizing that Windows might be difficult for some analysts, we feel that standard interfaces are preferable to proprietary WIMP interfaces or programming languages.

Developers should be able to build and test user interfaces as they build their system, yet most tools do not allow this. NEXPERT Object requires a separate user interface generator, the Open Interface toolkit, to create sophisticated WIMP interfaces. This toolkit allows developers to generate GUIs using a WIMP interface and generates C language templates to produce the user interface. Developers must then modify these templates by including C language subroutine calls to the NEXPERT inference engine. This approach requires too much programming expertise. Another expert system shell with limited user interface capabilities is CLIPS. Its interface-building capabilities are those of the C Programming language itself. *Due to the difficulty in building user interfaces, CLIPS and NEXPERT Object can be eliminated from further consideration.*

4.3.9 Cost and Licensing Issues

BLS plans to purchase four or five development copies of an expert system shell and will need thirty or more runtime copies. All purchases are to be made at the same time. Their budget for both the tools, and the training required to use these tools, is modest. *Considering vendors' pricing policies, we can eliminate several tools from consideration: ADS, ART/IM, GURU, Kappa PC, KBMS/PC, KES and NEXPERT Object.* These products are all priced in the \$3,000 to \$8,000 price range for a single development copy. Volume discounts and special pricing agreements might reduce costs for development software, but there would be no monies for runtime copies. Each of these vendors requires separate runtime pricing, which averages \$500 to \$1000 a copy. In addition, there would be no monies available for training. Several of these tools would warrant further consideration if and when BLS wanted greater functionality and migrated to larger hardware platforms. In each case, these products are PC-based versions of mainframe or multi-user workstation development environments. The vendors' pricing strategies are to charge \$20,000 to \$100,000 for these products and provide less expensive PC versions to facilitate software development.

There are less-expensive tools targeted for the PC environment that meet the current needs of BLS and can be used to review CPI product substitutions. PC pricing of expert system shells should reflect the nature of PC-based systems. There may be widespread or even unlimited distribution of runtime copies, consequently, runtime licensing should be royalty-free. Of the remaining shells we considered, only KnowledgePro, LEVEL5 OBJECT, and Intelligence/Compiler have free runtime copies. According to a marketing representative, IntelligenceWare is instituting a runtime pricing for Intelligence Compiler in the near future.

4.3.10 Final Assessment

Our assessment of the expert system shell marketplace is that PC versions of ADS and Kappa PC offer the greatest functionality. Both are truly object-oriented with message passing and specialized methods, and both require significant programming expertise. These products are targeted at high-end computing platforms, and have sophisticated features which are not required for many PC-based applications. Furthermore, their pricing structure is not compatible with other sectors of the PC marketplace. Frame-based shells offer the next highest level of functionality. ART/IM, EXSYS Pro, Intelligence Compiler, KBMS/PC, LEVEL5 OBJECT, and NEXPERT Object are considered to be frame-based. Of these products, LEVEL5 OBJECT is considered the most user-friendly. Among frame-based or object-oriented systems, only EXSYS Pro, Intelligence Compiler, and LEVEL5 OBJECT have not been eliminated from consideration.

We have evaluated other tools which we believe offer insufficient functionality. CLIPS and KES are tools ideally suited for building embeddable expert systems, but they require sophisticated programming skills. GURU does not offer frame-based or object-oriented processing at this time. Niche systems such as 1st Class HT and KnowledgePro do not provide the broad range of features needed for successful expert system development. Each lack sufficient external data or program interfaces, support for multiple programming paradigms, and robust user interface support. These tools are targeted to those applications which will benefit from inductive inferencing techniques or hypertext capabilities. Purely rule-based systems do not offer sufficient functionality; therefore all such systems have been eliminated from consideration.

Through a process of elimination, we are left with three candidate systems: EXSYS Professional, Intelligence Compiler, and LEVEL5 OBJECT. All other tools are either too expensive, require too much programming expertise, or offer too little functionality. Of these three remaining products, LEVEL5 OBJECT has the best developer and user interfaces and has integrated procedural and frame-based processing. Furthermore, while our evaluation considers only tool functionality and price, we have been impressed by the level of customer support for LEVEL5 OBJECT. Their training courses have been recommended to us by attendees and appear to be offered more frequently and in more locations than that of the other two vendors. We have concluded that Information Builders, Inc. has greater financial resources than the other two vendors because it offers a wide range of software products, e.g., FOCUS, while the other two vendors are principally limited to expert system software.

Our recommendation is that BLS purchase LEVEL5 OBJECT to continue their study of expert systems. LEVEL5 OBJECT is priced considerably lower than other expert system shells with comparable functionality. The vendor, Information Builders, Inc., offers excellent training courses in developing expert systems with their product. The vendor seems stable, having sufficient financial resources and a corporate commitment to advanced information technologies. However, the maturity of this field should be reassessed periodically to ensure that Bureau personnel are benefitting from market trends. The selection of LEVEL5 OBJECT does not prevent BLS from using other shells in the future. Since it supports multiple programming paradigms, the knowledge in LEVEL5 OBJECT knowledge bases can be migrated to other tools which support the same programming paradigms. However, moving from LEVEL5 OBJECT to a purely object-oriented environment might present some difficulties since a shift in paradigm would require some modification. In addition, LEVEL5 OBJECT does not preclude the use of machine learning algorithms to generate knowledge bases as long as the induced representation is given as, or can be converted to, production rules.

5. MACHINE LEARNING APPROACHES

Weiss and Kulikowski (1991) define a learning system as "a computer program that makes decisions based on the accumulated experience contained in successfully solved cases." Most learning systems are used to generate decision rules which will predict the outcome of new cases based upon historical data. In this context, learning consists of choosing those characteristics (or features) of a case which will best classify new cases. The learning system takes as its input a set of cases and their correct classifications. It gives as its output a set of decision rules which will classify new cases. The learning system creates a classifier which can solve new classification problems. The classifier takes as its input a set of features which describes a new case and gives as its output the class to which the new case belongs. Figure 1 depicts the relationship between the learning system and the classifier(s) it produces. For the comparability of CPI product substitutions, cases corresponding to (non)comparable product substitutions would be supplied to the learning system for one or more ELIs. The learning system would extract the decision rules necessary to predict the comparability of products. We discuss the motivation for using machine learning techniques in the CPI product substitution task, contrast the various approaches to learning, and describe the most promising algorithms for product substitution.

Figure 1: Learning and Classification Systems

The process of capturing and organizing the domain expertise to be represented in a knowledge-based system is called knowledge engineering. Traditional approaches to developing knowledge-based systems consist of having either the domain expert encode his knowledge into the appropriate representation or having a knowledge engineer interview the expert to determine the decision rules. While these approaches have worked reasonably well, there can be problems associated with them.

In the former, the expert must spend valuable time learning an expert system tool and representing his (or her) expertise in the appropriate form; in the latter, a knowledge engineer (i.e., systems analyst) must elicit, and encode correctly, the expertise. Difficulties in communication between the expert and analyst, lack of participation by the expert, and incompletely specified knowledge are only three examples of inherent problems. Learning systems can complement expert system development by automating much of the knowledge engineering process.

In the case of CPI product substitution, there are more than three hundred ELIs for which some form of product substitution review is required. Building a knowledge-based system for each ELI will be time consuming. Since different commodity analysts will be creating the knowledge bases for each system, it is unlikely that they will use the same design techniques or develop systems with the same degree of expertise. A more promising approach is to learn the initial knowledge bases which are then reviewed and refined by commodity analysts. This would lessen the time required by each analyst to construct an expert system by screening the more obvious cases.

Another problem may be the articulation of expert knowledge by the commodity analyst. Although commodity analysts may be quite skillful at reviewing CPI product substitutions, they may be less adept at describing the reasoning behind their decisions, especially since the analyst is expected to be both the expert and the knowledge engineer. The analyst may tend to oversimplify the decision-making process by omitting steps which may seem obvious but which must be explicitly defined in the knowledge base. It may be that the analyst does not consider exceptions which are a common occurrence. Learning systems can identify this implicit knowledge and make it explicit. The analyst can then refine the knowledge base.

Some learning systems can adapt to handle new cases. Learning is generally classified as being *supervised* or *unsupervised*. Supervised learning requires a set of examples which are used to guide classification; unsupervised learning forms classes solely on the basis of shared characteristics in its observations. In the case of CPI product substitution, a supervised learning system would take a set of examples for (non)comparable cases and derive decision rules for comparability. Commodity analysts could then critique the rules by using additional cases, reclassifying erroneous classifications, and resupplying these to the system. Clustering algorithms represent unsupervised learning techniques. It must be noted that there are no learning systems which presently function at the same level as humans. Learning systems excel at handling large amounts of data; the more creative aspects of learning remain beyond the capabilities of these systems.

There are several approaches to machine learning, e.g., statistical pattern recognition (Duda and Hart, 1973), neural networks (McClelland, Rumelhart et al, 1986a, 1986b), and symbolic approaches to learning (Quinlan, 1986; Michalski, 1980). Our efforts have concentrated upon symbolic approaches, i.e., tree and rule induction techniques, because they are more compatible with the CPI product substitution process and BLS goals for expert system technology. Machine-generated production rules can be augmented by commodity analysts as needed. Symbolic techniques, in general, provide better explanations than their statistically-based counterparts. In addition, the generation of production rules permits comparison with manually-derived knowledge bases. Case-based reasoning is another promising technique for utilizing historical data to solve new problems (Slade, 1990; Kolodner, 1991). However, there are few case-based reasoning systems available, either public-domain or commercial, and they do not integrate with conventional rule-based expert systems. Perhaps as this technology matures it will warrant further investigation.

All decisions are based on the features of each case and their correct classification. A basic assumption of all learning systems is that there is sufficient information upon which to base a decision. In reality, most of the information associated with cases is not used. Humans, and the learning systems which attempt to emulate their reasoning, use generalizations to reduce the amount of information needed to make a decision. Learning systems could search through vast amounts of information to arrive at a previous decision; this requires an exact match to be present in the data. However, such exact matches are rare. Successful learning systems generalize, but do not over generalize. Sophisticated testing procedures ensure that the learning systems perform adequately.

We consider two distinct representations for the decision rules used by the classifier: decision trees and production rules. The methods for inducing each type of structure are slightly different. As is discussed in greater detail, decision trees can be easily represented as production rules, but production rules cannot be directly transformed into decision trees. Although the most popular induction techniques generate decision trees, production rules are the preferred representation. The most common technique is to generate decision trees, convert them to production rules, and eliminate redundant rules.

A *decision tree* consists of nodes and branches where each node represents a single test or decision. The starting node is called the *root* node. Depending upon the result of a test, the tree will branch to other nodes. When a terminal node, or *leaf*, is reached, a decision is made on the class assignment. Decision trees may be either *binary* or *nonbinary*. The nodes of a binary decision tree can process only true or false test results. Two branches leave each node, and only one branch may enter a node. Typically, decision trees show true decisions branching right and false decisions branching left. Nonbinary trees allow more than two branches to leave the node, but retain the restriction of one entering node. In this tree, each decision results in a partition of two or more disjoint sets. Figure 2(a) presents a binary tree, Figure 2(b), a nonbinary tree. For any tree, all paths lead to a terminal node corresponding to a decision that is a conjunction (i.e., AND) of various tests. If there are multiple paths for a given class, then the paths represent disjunctions (i.e., OR). All paths in the decision tree are mutually exclusive. For any new case, only one path in the tree will be satisfied.

Figure 2: Types of Decision Trees

The process of learning the structure of a decision tree or the equivalent rule set from data is known as *induction*. A popular method of tree construction is to split all nodes into disjoint groups of distinct values for the test represented by a node. A tree is induced by selecting a starting feature or test, splitting that feature into disjoint sets, and then repeating the process. This is known as *recursive partitioning*. When all members of the sample belong to the same class, no further splitting is performed, forming a terminal node. Alternately, terminal nodes are formed when the number of remaining cases falls below some minimum threshold value. In this case, the node is assigned to the class having the greatest frequency at that node.

The simplest technique for splitting the nodes into disjoint partitions is to partition the data by the values of the feature being tested. Splitting by feature value can always be made to result in terminal nodes that consist of members of a single class, unless an identical case in the data is assigned to two or more different classes. In the worst case, each path to a terminal node will correspond exactly to one of the cases in the sample. There are some weaknesses in splitting by attributes. An obvious difficulty arises in splitting continuous variables. Since there may be an infinite number of possible splits, a more reasonable method for handling continuous variables is to assign them a small set of discrete intervals. Unfortunately, there is no technique for knowing in advance the number of intervals required or their ranges. In general, the use of intervals and arithmetic operators can cover more effectively the range of numerical values and help improve predictive power of the classifier.

Another problem with splitting the tree is that it tends to fragment the tree into many smaller groups. Parsimonious trees have fewer tests to perform and thus have larger samples supporting the terminal nodes. With a limited sample, the tree should not be required to consider a complete range of values for a feature when a much smaller set of numbers would serve as well. However, trees that are split by value for other types of attributes are more natural and understandable. This is particularly true for categorical values which have been defined after having considered the data.

The determination of which node to split next is handled in several ways. Variables can be selected at random, but trees formed in this manner would be larger and more error-prone. Most learning features must concern themselves with noise; noise can be characterized as those features which have no more predictive capability than random selection. Since most features are noisy, random selection can split on useless nodes. Some heuristic must be used to determine the next node.

The basic approach to selecting a variable is to evaluate its likelihood for improving the performance of the tree. Several splitting evaluation functions perform quite well. The underlying concept behind these splitting functions is to select that variable and cutoff that will select the best tree. These evaluation functions predict solely on the basis of splitting a single node, without testing possible splits of successor nodes. This heuristic tends to make good judgements with incomplete information. The most widely used splitting functions reduce the degree of randomness in the current node. The most popular functions are the *entropy* function and the *gini* function (Quinlan, 1986). Different splits are examined, and the variable selected for splitting is the one with the greatest reduction in impurity. Once a decision tree has been constructed, it must be validated. *Overfitting* occurs when the decision tree has been split to completely predict the sample cases. An obvious case of overfitting is to use the test cases as the decision rules for new cases; unless the sample is exceptionally representative of the true population, the resultant tree will perform poorly on new cases. An apparent error rate of zero for the test cases may translate to a high error rate on new cases. The true error rate must be estimated by resampling or by estimating the performance of the tree with independent test cases. Standard statistical testing, e.g., chi-square test, can measure the significance of features. When the

statistical test indicates that further splitting is not significant, no further splitting is performed on that node. This approach is successful in applications with large samples, but can result in the tree induction process terminating too quickly. The risk of underfitting the data is worse than overfitting. Empirical evidence suggests that pruning techniques are superior.

Pruning techniques start with the fully-expanded tree. The weakest branches are identified and eliminated. Reduced-error pruning breaks the samples into a training and test set. If the error rate on the test cases improves by pruning it, the subtree is removed. The process continues until there is no improvement in the tree.

While tree-based learning systems are effective, they have some limitations. Current tree induction methods are not optimal; the combinatorics involved with tree optimization would render such algorithms impractical for most large problems. Linear and boolean combinations may require more complex tree structures than would normally be desired. Some subtrees are replicated.

Since most expert systems are based on production rules, learning systems should be capable of generating rules. Two key variations on rule induction have emerged. In the first strategy, a decision tree is rewritten as a collection of production rules, and the rule set is pruned. Quinlan (1986) describes an approach in which a covering tree is induced, but pruning on the rule set is performed by rule and component deletion. This results in a simplified set of potentially nonmutually exclusive rules. In the second rule induction strategy, a single best rule is found, the cases covered by that rule are removed from the training set, and the process is repeated until all cases have been exhausted (Michalski, 1983). The set of covering rules can be refined further by pruning or by applying some statistical test. These methods work directly with nonmutually exclusive rules in disjunctive normal form (DNF). They expand only a single rule for a given class by specializing the rule, as if they were evaluating a single branch of a decision tree.

AQ is a series of learning systems developed by Michalski which have been used to learn decision rules in agricultural and medical domains (Michalski and Chilausky, 1980; Michalski and et al., 1985). AQ uses an iterative approach by selecting a new feature at each stage, starting with a null description. A new training event is chosen. A conjunction of terms is generated, (i.e., a star), by extending a description to cover as many positive examples as possible while including as few negative examples as possible. The simplest description is retained according to pre-defined criteria. When all relevant events have been covered, the description is kept; otherwise the process is repeated. When a single conjunctive description cannot cover all positive cases (which is often the case), AQ will generate several conjunction expressions, (i.e., a disjunction of conjunctive expressions). This algorithm is not incremental, (i.e., new cases cannot be processed once the descriptions have been produced). Another example of a general technique for direct rule induction is the CN2 algorithm devised by Clark and Niblett (1989); it too is nonincremental.

Learning algorithms can be considered to be non-incremental or incremental. Most of the earlier rule induction techniques, e.g., ID3, were non-incremental. While these systems produced good decision trees, they were unable to modify their structures based on new, contradictory cases. Clearly, any robust learning algorithm would need to be adaptable. Several new algorithms have been introduced to permit the incremental construction of decision trees and rule sets. Utgoff (1989) has produced ID5R. COBWEB is another incremental learning system which performs unsupervised learning (Fisher, 1987). Intuitively, learning systems should not be required to relearn all of their concepts

when new information is supplied. This new information, however, can greatly impact the existing representation. A great deal of research in this area is currently underway.

There are limitations of learning systems. Some representations do not handle inequality very well, (i.e., comparing product specifications). These algorithms would not be suitable for generating knowledge bases for product substitution review. As stated earlier, most techniques do not handle continuous variables very well; however, ranges of discrete intervals identified by either the learning system or commodity analysts could be substituted for continuous variables. Lastly, combinations of variables may require special heuristics. This would necessitate some understanding of the problem domain prior to generating the production rules. It is unclear whether this difficulty would be posed by CPI product substitution or other tasks within BLS.

BLS should consider learning systems as one approach to collecting and maintaining expertise on CPI product substitution. Learning techniques will become more prevalent as they continue to mature and improve. Some exploratory studies could be conducted to determine the feasibility of this technology. An additional approach would be to compare the knowledge bases generated by learning systems with those developed by commodity analysts. A sufficiently complex example should be selected so that both the learning system and the analysts are challenged.

It is relatively simple to envision the generation of ELI-specific knowledge bases using historical data. Information would be supplied to a learning system along with a set of initial conditions outlining those specifications which must be complete and any inconsistent combination of specifications. The learning system would be required to test its classifier against the initial knowledge base designated KB_0 in Figure 3. An incremental approach would be used to reflect the constantly changing considerations in CPI product substitution.

Figure 3: A Proposed Incremental Learning Architecture

6. FINAL RECOMMENDATIONS

A criteria matrix has been devised to serve as a decision tool in selecting the approach or approaches most compatible with the needs of BLS (see Appendix E). BLS/CPI staff specified the criteria by which each approach can be judged and assigned numerical weights to these criteria. Initially, each alternative was graded using a relative scale from one to five where a score of one signifies that the alternative provides the minimum level; a score of five signifies that the alternative is the most satisfying of the available choices. There may be alternatives which have identical scores for the same criterion. This signifies that these alternatives are not materially different for that particular criterion, e.g., developers will use the same capabilities of LEVEL5 OBJECT whether or not they are following any development methodology. Each score was multiplied by the weight of their respective criteria; in those cases where two weights were provided, two values are computed and averaged. This method of calculation reflects a desire to consider both near- and long-term implications of selecting a particular alternative. The scores were totaled and the overall scores, which are discussed at the end of this section, serve as the basis for our final recommendations.

We have arranged the five alternatives presented in the criteria matrix into two tiers. The first tier consists of those alternatives which employ traditional methods of acquiring and representing knowledge in an expert system; the second consists of those which automate much of the knowledge capture and organization necessary to build expert systems. Within the first tier, there are two approaches which involve the manual elicitation of expert knowledge and representation of that knowledge. The principal difference between these two alternatives is that one emphasizes a well-structured methodology for constructing expert systems. Expert systems are a form of computer software, and traditional methods of software development can be adapted to reflect those unique aspects of the development process. Furthermore, these methods can be further tailored for the CPI application. The second tier is comprised of more sophisticated alternatives which are predicated upon the success of using machine learning techniques to generate ELI-specific knowledge bases. Those alternatives in the first tier offer the greatest hope of near-term success with limited risk of failure; those in the second tier involve more uncertainty but promise a greater return on investment over the long-run in the form of more consistent knowledge bases and shorter development schedules.

We describe each approach and assess its prospects for success:

Tier One: Traditional Knowledge Engineering.

1. *Use LEVEL5 OBJECT. Provide training for developers.*

Give commodity analysts development copies of LEVEL5 OBJECT and train them on its use. Provide additional training which covers issues in expert system development, e.g., knowledge acquisition and representation, life-cycle development, to supplement tool-specific courses. Establish a small core team to introduce the technology into the larger organization.

LEVEL5 OBJECT training can be provided by the vendor, Information Builders, Inc. Depending upon the number of employees to be trained, it may be cost-effective to have the vendor give courses onsite. Another means of training commodity analysts would be to have BLS/CPI staff who have taken the vendor training and have some hands-on experience with LEVEL5 OBJECT teach courses to other commodity analysts. The core team studying the use of expert systems within BLS is the

obvious choice for championing the technology within the organization. Success depends heavily upon the ability of commodity analysts to learn how to identify and capture expert knowledge and how to organize and maintain that knowledge in LEVEL5 OBJECT. Representing knowledge in LEVEL5 OBJECT may be difficult for some analysts; however, our experience with expert system technology suggests that knowledge capture will be more difficult than expected for a variety of other reasons. For example, in their initial study of expert systems, the core team within BLS documented cases where highly knowledgeable analysts omitted expert knowledge critical to the success of the resulting expert system.

2. *Use LEVEL5 OBJECT. Devise and document a methodology for expert system development.*

Study existing software development methodologies for expert systems. Compare these methodologies to existing in-house procedures for developing end-user computer applications. Devise a methodology for expert system development which is compatible with current procedures. Instruct commodity analysts on the use of such a methodology.

There is a great deal of literature covering various techniques for knowledge elicitation and organization (cf. International Journal of Man-Machine Studies and Knowledge Acquisition). A methodology should make it easier for commodity analysts to build, test, and maintain expert systems. It should provide guidelines on collecting and organizing product comparability knowledge. These guidelines would presumably address issues of knowledge collection that are critical to expert system development. For this reason, a methodology which gives commodity analysts procedures to follow in constructing knowledge bases is viewed as preferable, if not essential, to simply providing the analysts with training on LEVEL5 OBJECT. A methodology might also suggest or enforce consistent user and external data interfaces. With these design decisions largely resolved, commodity analysts could then concentrate on the knowledge within the system. This would make it easier to both use and maintain a large number of expert systems.

Tier Two: Machine Learning Techniques (See Section 5 for definitions).

3. *Apply non-incremental machine learning to infer knowledge bases. Conduct pilot project.*

Select a suite of ELIs which represents the spectrum of complexity, i.e., easy, medium, or hard. Use existing machine learning algorithms to generate knowledge bases from actual comparability decisions; in addition, have commodity analysts build knowledge bases for these ELIs. Compare the knowledge bases for each ELI using several criteria (e.g., accuracy, maintainability). Extrapolate results to determine whether to pursue machine learning techniques.

Due to the nature of the domain, off-the-shelf learning systems cannot infer rules for product comparability without modification. Product substitution review entails a comparison of two or more sets of features, (i.e., vectors), to determine comparability. Most learning algorithms concentrate upon a single set of features which can predict or classify membership in a particular class. Identifying relationships between two feature vectors and their values is more challenging; however, we can simplify this learning process by recognizing the domain-specific characteristics of product comparison. A non-incremental learning algorithm can be selected and modified to generate rules by analyzing multiple feature vectors and the relationships between features in the vectors. Initial conditions, e.g., complete and consistent ELI specifications, can further simplify the learning process and improve the accuracy of the generated knowledge base. While success cannot be guaranteed,

benefits are enormous considering the number of ELI-specific knowledge bases that may be required for product substitution review. Currently, all off-the-shelf learning systems, e.g., IXL and INDUCEXS, use non-incremental algorithms.

4. *Apply incremental machine learning to infer knowledge bases. Conduct pilot project.*

Use the same approach described to study non-incremental machine learning algorithms. Determine whether the added complexity of incrementally revising knowledge bases is offset by a decrease in maintenance costs.

Incremental machine learning algorithms are seen as a more advanced solution to the problem of inductive inference and maintaining knowledge bases through automated inspection of historical data and user-supplied training cases. Incremental learning is attractive because it permits existing knowledge bases to be refined based upon new data. Non-incremental approaches require that knowledge bases be regenerated from the complete set of data. Obviously, incremental approaches offer tremendous time savings. However, there appear to be no off-the-shelf incremental learning systems. Some research and development activities would be required to produce the incremental machine learning algorithm. First, a pilot project would need to demonstrate success in learning comparability rules. Then, the algorithm used to generate comparability rules would be revised to permit incremental updates to the knowledge base. Success cannot be measured precisely without knowing the viability of machine learning techniques for product substitution review.

5. *Apply machine learning techniques. Develop front-end to assist in reviewing, testing, and revising knowledge bases.*

Use the same approach described for the machine learning algorithms. Develop an intelligent interface to the automatically generated knowledge bases which will allow commodity analysts to examine the knowledge extracted from comparability data, supplement it with knowledge not explicitly represented in the data, and test for inconsistencies between it and knowledge supplied by commodity analysts.

An intelligent tool to automate much of the expert system development process is a significant goal of the artificial intelligence community. The knowledge acquisition bottleneck has long been seen as a major impediment to the development of expert systems. Unfortunately, there is no such public domain or commercially available tool for general-purpose expert system development. Some domain-specific knowledge acquisition systems have been developed (Marcus, 1988), but these tools generally do not employ learning techniques. Development of such a tool would represent a fundamental breakthrough in the development of expert systems. Significant research and development activities would be required to produce the intelligent interface envisioned. Such an ambitious research initiative as this would entail both significant development efforts and risk of failure. This alternative should not be considered without considerable evidence that learning techniques, in particular incremental approaches, are viable technologies for learning rules to be used in product substitution review.

Using these definitions of the five alternatives presented in the matrix, and their prospects for success, we can discuss the scores presented in the criteria matrix:

	Score
Tier One: Traditional Knowledge Engineering.	
1. Use LEVEL5 OBJECT. Provide training for developers.	394.5
2. Use LEVEL5 OBJECT. Devise and document a methodology for expert system development.	425
	Score
Tier Two: Machine Learning Techniques.	
3. Apply machine learning techniques for inferring knowledge bases. Conduct pilot project.	397.5
4. Apply incremental approaches to machine learning. Conduct pilot project.	369
5. Apply machine learning techniques. Develop front-end to review, test, and revise knowledge bases.	433

Looking at tiers one and two, we see that the alternatives with the highest scores are #2 and #5, respectively. Given its reliance upon machine learning techniques for success, #5 has an unreasonably high score. This can be attributed to two factors: the attractiveness of using an intelligent tool to support and guide the expert system development process, and the relatively low weights assigned to those criteria which predict developmental effort and risk of failure. It is unrealistic, therefore, to suggest that alternative #5 be pursued at the present time. However, the promise of automating knowledge collection and organization should not be overlooked. To some extent the potential benefits of using these advanced technologies are reflected by the scores in the second tier exceeding those of the first. This suggests that machine learning techniques and intelligent tools for expert system development could provide productivity gains in the future. At a minimum, these newer technologies should be closely monitored and evaluated for future use in BLS operations.

We recommend that BLS pursue alternatives from both tiers. This approach permits BLS to judge the efficacy of newer technologies while continuing to investigate traditional expert system development. We believe that the most prudent approach at this time is to use the recommended expert system shell, LEVEL5 OBJECT, and follow a methodology for expert system development. BLS/CPI can adopt an existing methodology and adapt it as needed, or devise one uniquely suited to their needs. In addition, we recommend that a pilot study be conducted to determine the feasibility of machine learning techniques for inferring ELI-specific knowledge bases. Currently, there are no off-the-shelf machine learning algorithms which can learn rules for product comparability. It is our opinion that product comparability is such a specialized domain that it will not provide sufficient incentive for software vendors to produce the domain-specific software which would solve the problem. A pilot project could conclude whether ELI-specific knowledge could be learned by systems using algorithms designed specifically for comparison tasks.

The analyses presented in Sections 4 and 5 and the recommendations presented above support the evolving strategy of empowering commodity analysts to accept an active role in the development and administration of the PRS. An expert system shell, LEVEL5 OBJECT, was identified that possesses the requisite technical features and user-oriented facilities to allow commodity analysts to develop expert systems which render non-comparability decisions. It is also recommended that an expert system development methodology be tailored for this application in order to provide commodity analysts with structured guidance in knowledge base development.

Providing commodity analysts with an expert system shell and a knowledge base development methodology is only one component of an overall strategy. It is recommended that machine learning be explored in order to determine whether development of the knowledge bases can be partially automated. This is an important consideration because there are approximately 350 ELIs for which knowledge bases may be developed. It is envisioned that commodity analysts would provide machine learning algorithms with training examples to build initial knowledge bases. After evaluating the performance of these initial knowledge bases, commodity analysts could either develop more training cases or manually enhance the knowledge bases.

As part of a larger strategy, it is recommended that expert systems be developed for every ELI, regardless of its complexity and prevalence of comparability decisions. This effort will help reinforce the change in view from passive users to end-user system developers amongst the commodity analysts.

As a first step, attempts should be made to check for completeness and consistency. Developing machine learning systems to perform these tasks, especially consistency checking, could be quite cumbersome for ELIs with complicated product descriptions. It is recommended that completeness be approached first because it is a more tractable concept. An initial approach to consistency would be to develop rules which spot common errors.

It is recommended that at first the expert systems only make noncomparability decisions and only in those cases where there is no uncertainty. Given the check list methodology, it should be possible to develop stringent noncomparability rules for each ELI. Next, the expert systems should be enhanced to make comparability decisions, but only when there is no uncertainty. Cases which cannot be classified with absolute certainty should be referred to the commodity analysts for review. It is expected that expert systems built for ELIs whose checklists rarely include free text will make a higher percentage of decisions than those systems built for ELIs whose checklists typically include one or more free text entries.

Before expert systems are allowed to make decisions that will not be reviewed by commodity analysts, a rigorous quality assurance process must be developed and implemented. One component of the assurance process will be to review the knowledge bases for conformity to the development guidelines and establish the quality of their documentation. These checks are essential to establishing an efficient knowledge base maintenance program and transferring knowledge bases to new personnel.

A second component should focus on testing the knowledge bases. The expert systems should be fed a comprehensive set of test cases and their decisions should be reviewed. A third component should involve an independent review of the knowledge bases from a technical standpoint. Commodity analysts and their supervisors should review the knowledge bases for logical integrity and internal consistency. Problems in developing the knowledge bases may be discussed and lead to new ways of conceptualizing comparability and designing checklists.

Experiences with empowering commodity analysts to extend the development of the PRS could be used to entertain further activities. For example, commodity analysts could be given tools to automate the process of changing checklists and to explore the sensitivity of the CPI to checklist changes. The commodity analysts would then need methods to manage the adaption of knowledge bases from one checklist to another. Commodity analysts could also be given the opportunity to influence system development with respect to data collection in the field and data archival. They may also be interested in the automated access, to and report generation from, external sources.

ACKNOWLEDGEMENTS

We wish to acknowledge the time and support provided by BLS staff on this project. Members of the BLS expert system study team met with us several times to share their experiences and their goals for the project. Members of this team include Richard Kamalich, Bob Adkins, Dave Barry, Joe Chelena, Fred Conrad, Karen Flynn Huff, Jim Longacre, and Jerome Watters. We also wish to thank Marybeth Tschetter for her assistance in establishing and managing the project.

We would also like to recognize the efforts of several individuals at the Oak Ridge National Laboratory who have assisted us. We wish to thank Rick Goeltz, Ho-Ling Hwang, and Tai-Lun Chiang for reviewing the report and Sheila Moore for her assistance in preparing this report.

REFERENCES

- P. Clark and T. Niblett, 1989. "The CN2 Induction Algorithm," Machine Learning, Vol. 3, pp. 261-283.
- R. Duda and P. Hart, 1973. Pattern Classification and Scene Analysis, John Wiley and Sons, New York.
- D. Fisher, 1987. "Knowledge Acquisition via Incremental Conceptual Clustering," Machine Learning, Vol. 2, pp. 139-172.
- Kolodner, J., 1991. "Improving Human Decision Making through Case-Based Decision Aiding," AI Magazine, Vol. 12, No. 2, pp. 52-68.
- S. Marcus (ed.), 1988. Automating Knowledge Acquisition for Expert Systems, Kluwer Academic, Boston.
- R. Michalski and R. Chilausky, 1980. "Learning by Being Told and Learning by Examples: An Experimental Comparison of the Two Methods of Knowledge Acquisition in the Context of Developing an Expert System for Soybean Disease Diagnosis," Policy Analysis and Information Systems, Vol. 4, pp. 125-160.
- R. Michalski, 1983. "A Theory and Methodology of Inductive Learning," Artificial Intelligence, Vol. 20, No. 2, pp. 111-161.
- R. Michalski, I. Mozetic, J. Hong, and N. Lavrac, 1985. "The Multi-purpose Incremental Learning System AQ15 and its Testing Application to Three Medical Domains," Proceedings of the Fifth National Conference on Artificial Intelligence, pp. 1041-1045, Philadelphia, PA, Morgan Kaufmann Publishers.
- J. Quinlan, 1986. "Induction of Decision Trees," Machine Learning, Vol. 1, pp. 81-106.
- D. Rumelhart and J. McClelland eds., 1986. "Parallel Distributed Processing: Explorations and the Microstructure of Cognition," Vol. 1, Psychological and Biological Models, MIT Press, Cambridge, Mass.
- S. Slade, 1991. "Case-Based Reasoning: A Research Paradigm," AI Magazine, Vol. 12, No. 1, pp. 42-55.
- P. Utgoff, 1989. "Incremental Induction of Decision Trees," Machine Learning, Vol. 4, pp. 161-186.
- S. Weiss and C. Kulikowski, 1991. Computer Systems that Learn, Morgan Kaufmann Publishers, Palo Alto, California.

APPENDIX A: DEFINITION OF TERMS FROM THE TOOL MATRIX

Call-in/ Call-out	The expert system can be executed by application programs and data passed to the expert system via data files or other mechanisms. Conversely, the expert system can execute external programs by calling them during an expert system interaction. Contrast with Embeddable.
Embeddable	The expertise represented in a knowledge base (e.g., productions rules) and the inference mechanism (i.e., forward and backward chaining) can be invoked directly by function calls from a traditional programming language. Contrast with Call-in/Call-out.
Encapsulation	The process of incorporating data and procedures. The ability to define an object.
Inheritance	The ability to build a hierarchy of objects in which a child inherits the attributes and properties of its parent(s).
Polymorphism	The ability to use the same function-calling mechanism for a hierarchy of objects such that each object responds to the call in an appropriate manner.
Functions	Same as for procedural programming.
States/ Rule sets	The ability to organize procedural code or production rules into modules (not to be confused with separate knowledge bases).
Pattern matching	Firing production rules which contain a specified pattern, e.g., all specifications with a value of '99'.
Prioritization	The use of numerical weights which cause the inference engine to fire one rule before another when both are waiting to fire.
Hypertext	Text and graphics which are linked to related textual information. Users can retrieve this supplementary information as needed.
Induction	The process of generalizing several examples into one or more concepts.
Abduction	The process of using domain knowledge to explain the occurrence of a particular situation.

APPENDIX B: HARDWARE AND SOFTWARE REQUIREMENTS

Commodity analysts (CAs) have PCs which will be connected to a Sharebase SB 8000 via Ethernet and will typically access CPI data residing on the SB 8000. They can also access an IBM mainframe located at the Boeing Information Center via 3270 terminal emulation. The IBM mainframe performs batch processing, generates hardcopy reports, and serves as an offsite backup. Metaphor workstations provide ad-hoc query processing to databases using a connection between the SB 8000 and a MicroVAX II. The Metaphors are connected to the MicroVAX and control several Apple Laserwriters.

Most CAs have an IBM PS2/70 (16 MHz 386) with 2 MB of memory and a 60 MB hard disk, running DOS 3.3. Some of these machines will be replaced over the next three years by a GRID (20-25 MHz 386) machine with 8 MB of memory and a 100 MB hard disk, running DOS and WINDOWS 3.0. These PCs are tied into a 3COM 3+ LAN which takes up a substantial amount of PC memory. The LAN has several Postscript printers connected to it. In the next few years, BLS is moving towards the MicroSoft LAN Manager. Each PC uses QEMM software and has a math coprocessor. Presently, there are four development PCs; each section could revise knowledge bases on its development machine. There are over thirty CAs in the four sections, all of whom need a run-time version. A network licensing arrangement with the expert system vendor is an attractive fielding option.

BLS is currently developing the Professional Review System (PRS) using MicroSoft C, MicroSoft PASCAL, MicroSoft linker, internally-developed software to access data on the SB 8000, and Vermont Views, a screen generator. PRS is scheduled to be in use by CAs on their PCs by late 1993. It will allow CAs to access quotes or listings, decide on actions, and make changes on-line. Printouts will be generated only at the request of an analyst. PRS may be capable of putting a day's worth of work on the hard disk. Currently, data is downloaded from the database machines by IDM LIB, a callable library embedded in PASCAL programs and placed in main memory on the PC. Data can also be downloaded and converted to dBase formats, if necessary, using a library of C routines called APEX. Ultimately, the expert system should use the same procedures/data as PRS to collect information from the SB 8600.

It appears that any expert system fielded in this environment will reside on the CA PCs. Those IBM PS2s with 2MB of memory may need to be upgraded to between 4MB and 8MB of memory to facilitate both network and expert system software, to permit downloads from the database machines, and to accelerate processing. The BLS budget of PC hardware and software was given as \$25,000, a portion of which would be available for expert system tools. This budget limitation may influence the decision of a PC-based tool since some are relatively expensive (i.e., \$5,000-\$10,000). If machine learning programs are used to generate knowledge bases for the various ELIs, those programs should be located on a dedicated 386 machine or workstation which is connected to the Ethernet.

From these hardware and software configurations we have narrowed our consideration of tools to those PC-based products which run under MS-DOS or OS/2. Given this and those factors listed in the matrix, we developed another matrix which described PC-based products in terms of several capabilities we felt a robust product should possess. This matrix looked at several factors.

APPENDIX C: HUMAN FACTORS

Each commodity analyst (CA) has a degree in Economics and uses his or her knowledge of market conditions to determine (non)comparable substitutions. The CAs are using regression analysis more and more in the substitution process. The CAs must incorporate pricing and quality adjustments. The CAs have extensive knowledge of the commodities and brand comparability; each commodity area has its own characteristics. In the near term, CAs would utilize an expert system as part of a review process. If the prototype system is successful, then pre-production screening could reduce the number of routine cases handled by the CAs.

The volume of transactions is high. There are three pricing periods each month with each period taking 7 to 10 days. All changes to the quotes are due in by 11:00 of the cutoff date. Extraordinary circumstances (i.e., freezes, turmoil in Persian Gulf) can influence the number of incoming price quotes which must be considered. Tolerances are built into the system so that the CA often looks only at the outliers. There are 1 1/2 to 2 1/2 days at the end of the cycle when CA reviews quotes and can make changes.

The CAs are confident that they can program knowledge-based systems. This must be studied further to determine whether all CAs have the same level of computer and expert system literacy as those on the team. Team members have suggested that they and other knowledgeable CAs would assist those CAs having difficulty with the concept of expert systems. In any event, some procedure would need to be established in order to modify a knowledge base.

Team members have mixed feelings about using expert systems to evaluate CA performance. They feel that this approach might be looked upon as interference. Commodity and/or economy may have changed; single expert is being reviewed by "less experienced" manager; manager would identify quality differences in CAs; less time spent justifying actions by CAs; maintain consistency over time, i.e., shift of procedures detected; Change of rules only with approval and documentation.

Any tool that BLS uses to create, maintain or revise expert systems must be user-friendly. CAs will be expected to maintain those knowledge bases relating to their area of expertise. Consequently, the tool must provide straightforward procedures for adding, deleting or modifying production rules. The rule syntax should permit IF .. THEN .. ELSE constructions. In addition, the run-time versions should be easy to use and provide adequate explanatory capabilities so that the CA can verify the expert system's reasoning. Since the CAs expect to document their expertise using the expert system tool, the expert system should permit comment fields in the knowledge base, should allow readable rules, and should allow for hardcopy capabilities. Since BLS is moving towards a Windows environment for standalone work, the user interface might benefit from a Windows "look and feel." The tool may need both DOS and Windows versions as production work is scheduled to remain non-Windows indefinitely.

Although most CAs will be computer literate, most will not have time to read a great deal of computer literature. In addition to user documentation, the selected tool should have a set of tutorials so that the CAs can quickly learn the product. Inexpensive training would be ideal.

APPENDIX D: A LEVEL5 OBJECT KNOWLEDGE BASE

CLASS dB3 bls SINGLE EXTERNAL "dBASEIII C:\bls.DBF"

WITH outlet number STRING
SEARCH ORDER CONTEXT
WITH quote code STRING
SEARCH ORDER CONTEXT
WITH old A spec NUMERIC
SEARCH ORDER CONTEXT
WITH old C spec NUMERIC
SEARCH ORDER CONTEXT
WITH old D spec NUMERIC
SEARCH ORDER CONTEXT
WITH old F spec NUMERIC
SEARCH ORDER CONTEXT
WITH old H spec NUMERIC
SEARCH ORDER CONTEXT
WITH old J spec NUMERIC
SEARCH ORDER CONTEXT
WITH old K spec NUMERIC
SEARCH ORDER CONTEXT
WITH old size NUMERIC
SEARCH ORDER CONTEXT
WITH new A spec NUMERIC
SEARCH ORDER CONTEXT
WITH new C spec NUMERIC
SEARCH ORDER CONTEXT
WITH new D spec NUMERIC
SEARCH ORDER CONTEXT
WITH new F spec NUMERIC
SEARCH ORDER CONTEXT
WITH new H spec NUMERIC
SEARCH ORDER CONTEXT
WITH new I spec NUMERIC
SEARCH ORDER CONTEXT
WITH new J spec NUMERIC
SEARCH ORDER CONTEXT
WITH new K spec NUMERIC
SEARCH ORDER CONTEXT
WITH new size NUMERIC
SEARCH ORDER CONTEXT

INSTANCE bls ISA dB3 bls
WITH access IS write
WITH action IS open
WITH filename := "C:\bls.DBF"

ATTRIBUTE start button pushed SIMPLE

ATTRIBUTE read DB SIMPLE
 ATTRIBUTE record button pushed SIMPLE
 ATTRIBUTE A is complete SIMPLE
 ATTRIBUTE A is comparable SIMPLE
 ATTRIBUTE C is comparable SIMPLE
 ATTRIBUTE D is comparable SIMPLE
 ATTRIBUTE F is comparable SIMPLE
 ATTRIBUTE H is complete SIMPLE
 ATTRIBUTE H is comparable SIMPLE
 ATTRIBUTE I is complete SIMPLE
 ATTRIBUTE J is complete SIMPLE
 ATTRIBUTE J is comparable SIMPLE
 ATTRIBUTE K is complete SIMPLE
 ATTRIBUTE Products are comparable SIMPLE
 ATTRIBUTE exit button SIMPLE

INSTANCE the application ISA application
 WITH unknowns fail := TRUE
 WITH threshold := 50
 WITH title display := introductory screen
 WITH ignore breakpoints := FALSE
 WITH reasoning on := FALSE
 WITH numeric precision := 8
 WITH simple query text := "Is it true that:
 *
 is
 *"
 WITH numeric query text := "What is(are):
 *
 of
 *"
 WITH string query text := "What is(are):
 *
 of
 *"
 WITH time query text := "What is(are):
 *
 of
 *"
 WITH interval query text := "What is(are):
 *
 of
 *"
 WITH compound query text := "What is(are):
 *
 of
 *"
 WITH multicomponent query text := "What is(are):

★
of
★"

WITH demon strategy IS fire all

INSTANCE introductory screen ISA display

WITH wait := FALSE

WITH delay changes := FALSE

WITH items [1] := textbox 9

WITH items [2] := start button

INSTANCE comparison screen ISA display

WITH wait := FALSE

WITH delay changes := TRUE

WITH items [1] := conclusion screen title

WITH items [2] := textbox 11

WITH items [3] := valuebox 1

WITH items [4] := valuebox 2

WITH items [5] := textbox 12

WITH items [6] := textbox 13

WITH items [7] := valuebox 3

WITH items [8] := textbox 14

WITH items [9] := textbox 15

WITH items [10] := textbox 16

WITH items [11] := textbox 17

WITH items [12] := valuebox 4

WITH items [13] := textbox 18

WITH items [14] := valuebox 5

WITH items [15] := valuebox 6

WITH items [16] := valuebox 7

WITH items [17] := textbox 19

WITH items [18] := textbox 20

WITH items [19] := valuebox 8

WITH items [20] := textbox 21

WITH items [21] := textbox 22

WITH items [22] := valuebox 9

WITH items [23] := valuebox 10

WITH items [24] := valuebox 11

WITH items [25] := valuebox 12

WITH items [26] := valuebox 13

WITH items [27] := textbox 23

WITH items [28] := textbox 24

WITH items [29] := textbox 25

WITH items [30] := textbox 26

WITH items [31] := textbox 27

WITH items [32] := textbox 28

WITH items [33] := textbox 29

WITH items [34] := textbox 30

WITH items [35] := pushbutton 2
WITH items [36] := textbox 32
WITH items [37] := valuebox 14

INSTANCE final screen ISA display
WITH wait := FALSE
WITH delay changes := FALSE
WITH items [1] := textbox 31
WITH items [2] := pushbutton 3

INSTANCE start button ISA pushbutton
WITH location := 229,187,405,237
WITH label := "Press to start"
WITH attribute attachment := start button pushed

INSTANCE pushbutton 2 ISA pushbutton
WITH location := 235,389,386,420
WITH label := "read next record"
WITH attribute attachment := record button pushed

INSTANCE pushbutton 3 ISA pushbutton
WITH location := 234,271,381,335
WITH label := "Press to exit"
WITH attribute attachment := exit button

INSTANCE textbox 9 ISA textbox
WITH location := 191,34,442,148
WITH pen color := 255,255,255
WITH fill color := 0,0,255
WITH justify IS center
WITH font := "System"
WITH font style IS bold
WITH frame := TRUE
WITH text := "

Bureau of Labor Statistics
Consumer Price Index

ELI 02011 - White Bread
Expert System"

INSTANCE conclusion screen title ISA textbox
WITH location := 6,7,235,34
WITH justify IS center
WITH font := "System"
WITH text := "Results of product comparison"

INSTANCE textbox 11 ISA textbox
WITH location := 181,55,288,78

WITH justify IS left
WITH font := "System"
WITH text := "A specification"

INSTANCE textbox 12 ISA textbox
WITH location := 103,82,174,100
WITH justify IS left
WITH font := "System"
WITH text := "complete?"
"

INSTANCE textbox 13 ISA textbox
WITH location := 313,243,404,269
WITH justify IS left
WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 14 ISA textbox
WITH location := 183,129,281,148
WITH justify IS left
WITH font := "System"
WITH text := "C specification"

INSTANCE textbox 15 ISA textbox
WITH location := 86,154,175,171
WITH justify IS left
WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 16 ISA textbox
WITH location := 188,206,188,207
WITH justify IS left
WITH font := "System"
WITH text := "D specification"
"

INSTANCE textbox 17 ISA textbox
WITH location := 185,182,284,202
WITH justify IS left
WITH font := "System"
WITH text := "D specification"
"

INSTANCE textbox 18 ISA textbox
WITH location := 87,205,176,230
WITH justify IS left

WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 19 ISA textbox
WITH location := 187,237,294,254
WITH justify IS left
WITH font := "System"
WITH text := "F specification"
"

INSTANCE textbox 20 ISA textbox
WITH location := 89,261,174,280
WITH justify IS left
WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 21 ISA textbox
WITH location := 406,133,535,154
WITH justify IS left
WITH font := "System"
WITH text := "I specification"

INSTANCE textbox 22 ISA textbox
WITH location := 402,57,500,74
WITH justify IS left
WITH font := "System"
WITH text := "H specification"
"

INSTANCE textbox 23 ISA textbox
WITH location := 401,190,538,211
WITH justify IS left
WITH font := "System"
WITH text := "J specification"
"

INSTANCE textbox 24 ISA textbox
WITH location := 401,272,531,292
WITH justify IS left
WITH font := "System"
WITH text := "K specification"
"

INSTANCE textbox 25 ISA textbox
WITH location := 319,84,390,102
WITH justify IS left

WITH font := "System"
WITH text := "complete?"
"

INSTANCE textbox 26 ISA textbox
WITH location := 82,102,171,127
WITH justify IS left
WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 27 ISA textbox
WITH location := 325,219,396,237
WITH justify IS left
WITH font := "System"
WITH text := "complete?"
"

INSTANCE textbox 28 ISA textbox
WITH location := 329,295,400,313
WITH justify IS left
WITH font := "System"
WITH text := "complete?"
"

INSTANCE textbox 29 ISA textbox
WITH location := 307,105,394,129
WITH justify IS left
WITH font := "System"
WITH text := "comparable?"
"

INSTANCE textbox 30 ISA textbox
WITH location := 318,163,389,181
WITH justify IS left
WITH font := "System"
WITH text := "complete?"
"

INSTANCE textbox 31 ISA textbox
WITH location := 138,59,465,155
WITH pen color := 255,255,255
WITH fill color := 0,0,255
WITH justify IS center
WITH font := "System"
WITH frame := TRUE
WITH text := ""

This concludes the White Bread example
"

```
INSTANCE textbox 32 ISA textbox
  WITH location := 140,356,320,387
  WITH justify IS left
  WITH font := "System"
  WITH text := "Products are comparable?"
"
```

```
INSTANCE valuebox 1 ISA valuebox
  WITH location := 177,78,292,97
  WITH justify IS left
  WITH font := "System"
  WITH frame := TRUE
  WITH clipped := TRUE
  WITH attachment := A is complete
```

```
INSTANCE valuebox 2 ISA valuebox
  WITH location := 177,104,292,124
  WITH justify IS left
  WITH font := "System"
  WITH frame := TRUE
  WITH clipped := TRUE
  WITH attachment := A is comparable
```

```
INSTANCE valuebox 3 ISA valuebox
  WITH location := 181,152,296,175
  WITH justify IS left
  WITH font := "System"
  WITH frame := TRUE
  WITH clipped := TRUE
  WITH attachment := C is comparable
```

```
INSTANCE valuebox 4 ISA valuebox
  WITH location := 183,206,297,228
  WITH justify IS left
  WITH font := "System"
  WITH frame := TRUE
  WITH clipped := TRUE
  WITH attachment := D is comparable
```

```
INSTANCE valuebox 5 ISA valuebox
  WITH location := 242,6,356,29
  WITH justify IS left
  WITH font := "System"
  WITH frame := TRUE
  WITH clipped := TRUE
```

WITH attachment := outlet number OF dB3 bls

INSTANCE valuebox 6 ISA valuebox
WITH location := 381,6,496,29
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := quote code OF dB3 bls

INSTANCE valuebox 7 ISA valuebox
WITH location := 184,259,306,280
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := F is comparable

INSTANCE valuebox 8 ISA valuebox
WITH location := 399,160,519,184
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := I is complete

INSTANCE valuebox 9 ISA valuebox
WITH location := 397,78,517,99
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := H is complete

INSTANCE valuebox 10 ISA valuebox
WITH location := 398,103,516,126
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := H is comparable

INSTANCE valuebox 11 ISA valuebox
WITH location := 404,216,521,239
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE

WITH attachment := J is complete

INSTANCE valuebox 12 ISA valuebox
WITH location := 404,241,519,265
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := J is comparable

INSTANCE valuebox 13 ISA valuebox
WITH location := 405,293,522,317
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := K is complete

INSTANCE valuebox 14 ISA valuebox
WITH location := 327,351,429,379
WITH pen color := 255,255,255
WITH fill color := 0,0,255
WITH justify IS left
WITH font := "System"
WITH frame := TRUE
WITH clipped := TRUE
WITH attachment := Products are comparable

INSTANCE main window ISA window
WITH location := -1,-1,-1,-1
WITH full screen := TRUE
WITH style IS moveable, sizeable, closeable
WITH title := "(Untitled)"
WITH visible := TRUE
WITH visible OK button := TRUE

DEMON A comparability
IF new A spec OF bls <> old A spec OF bls
THEN A is comparable := FALSE
ELSE A is comparable := TRUE

DEMON C comparability
IF new C spec OF bls <> old C spec OF bls
THEN C is comparable := FALSE
ELSE C is comparable := TRUE

DEMON D comparability
IF new D spec OF bls <> old D spec OF bls

THEN D is comparable := FALSE
ELSE D is comparable := TRUE

DEMON F comparability
IF new F spec OF bls <> old F spec OF bls
THEN F is comparable := FALSE
ELSE F is comparable := TRUE

DEMON H comparability
IF new H spec OF bls <> old H spec OF bls
THEN H is comparable := FALSE
ELSE H is comparable := TRUE

DEMON J comparability
IF new J spec OF bls <> old J spec OF bls
THEN J is comparable := FALSE
ELSE J is comparable := TRUE

DEMON A completeness
IF new A spec OF bls = 0
THEN A is complete := FALSE
ELSE A is complete := TRUE

DEMON H completeness
IF new H spec OF bls = 0
THEN H is complete := FALSE
ELSE H is complete := TRUE

DEMON I completeness
IF new I spec OF bls = 0
THEN I is complete := FALSE
ELSE I is complete := TRUE

DEMON J completeness
IF new J spec OF bls = 0
THEN J is complete := FALSE
ELSE J is complete := TRUE

DEMON K completeness
IF new K spec OF bls = 0
THEN K is complete := FALSE
ELSE K is complete := TRUE

DEMON 1
IF start button pushed
THEN read DB
AND action OF dB3 bls IS open

DEMON 2

IF read DB AND NOT eof OF dB3 bls

THEN output OF main window := comparison screen

DEMON 3

IF record button pushed

THEN action OF dB3 bls IS advance

DEMON 5

IF A is complete

AND A is comparable

AND C is comparable

AND D is comparable

AND F is comparable

AND H is complete

AND H is comparable

AND I is complete

AND J is complete

AND J is comparable

AND K is complete

THEN Products are comparable := TRUE

ELSE Products are comparable := FALSE

DEMON 6

IF exit button

THEN exit OF application := TRUE

END

APPENDIX E: SYSTEM EVALUATION CRITERIA

System Evaluation Criteria Criteria Information (1-10) Alternative Approaches	Project Goals			System Requirements (p. 1 of 3)		
	Reduce Workload Near-term/ Long-term (3 9)	Make Consistent Substitutions (10)	Document Expertise (7)	Batch Processing (10)	User Friendly Interface (10)	Explanatory capabilities (9)
Use LEVEL5 OBJECT. Provide training for developers.	1 2	3	3	3	2	2
Use LEVEL5 OBJECT. Devise and document methodology for system development.	1 2	3	4	3	2	2
Apply machine learning techniques for inferring knowledge bases. Conduct pilot project.	3 4	4	4	3	2	2
Apply incremental approaches to machine learning. Conduct pilot project.	4 4	4	4	3	2	2
Apply machine learning techniques. Develop front end to assist in reviewing, testing, and revising knowledge bases	5 5	5	5	3	5	5

System Evaluation Criteria	System Requirements (p. 2 of 3)					
	Processing speed development mode (8)	Handling of free text (8)	Access to data base machine (7)	Code development cost (5)	Time to develop prototype (6)	Time to implement system (5)
Criteria Information (1-10)						
Alternative Approaches						
Use LEVEL5 OBJECT. Provide training for developers.	5	1	5	5	5	5
Use LEVEL5 OBJECT. Devise and document methodology for system development.	5	2	5	5	5	4
Apply machine learning techniques for inferring knowledge bases. Conduct pilot project.	3	2	3	3	3	3
Apply incremental approaches to machine learning. Conduct pilot project.	2	2	2	2	2	2
Apply machine learning techniques. Develop front end to assist in reviewing, testing, and revising knowledge bases	1	3	1	1	1	1

System Evaluation Criteria	System Requirements (p. 3 of 3)						
	Analysts' time for development Near-term/ Long-term (5 8)	Analysts' time for maintenance Near-term/ Long-term (5 8)	Tracking of decision statistics (10)	Software costs (5)	Interactive processing speed (8)	Project Risk (5)	Final Score
Alternative Approaches							
Use LEVEL5 OBJECT. Provide training for developers.	1 2	1 1	1	3	5	4	394.5
Use LEVEL5 OBJECT. Devise and document methodology for system development.	2 3	3 2	1	3	5	5	425
Apply machine learning techniques for inferring knowledge bases. Conduct pilot project.	3 4	3 3	3	2	4	3	397.5
Apply incremental approaches to machine learning. Conduct pilot project.	3 4	3 2	3	2	4	2	369
Apply machine learning techniques. Develop front end to assist in reviewing, testing, and revising knowledge bases	5 5	5 5	5	2	1	1	433

APPENDIX F: COMPARISON OF KNOWLEDGE-BASED SYSTEM SHELLS FOR THE PC

Comparison of Knowledge-Based System Shells for the PC (p. 1 of 3)					
Product Vendor	ADS Aion	ART/IM Inference	CLIPS NASA	EXSYS Pro EXSYS	GURU mdba
Hardware Requirements					
Extended Memory	2 MB	4 MB	640 KB	640 KB	640 KB
Hard Disk Space	2 MB	8 MB	1 MB	1 MB	5 MB
Software Requirements					
MS-DOS	Y	Y	Y	Y	Y
MS-DOS and WINDOWS 3.0	N	N	N	N	N
OS2	Y	Y	Y	Y	Y
File and Database Support					
ASCII/dBase/Lotus	Y/N ¹ /N	Y/Y/Y	Y/N/N	Y/Y/Y	Y/Y/N
SQL	Y	N	N	N	Y
Application Program Interface					
Call-in/Call-out	Y	Y	Y	Y	Y
Embeddable	N	N	Y	Y	N
Object-Oriented Features					
Encapsulation	Y	Y	Y	Y	Y
Inheritance	Y	Y	Y	Y	N
Polymorphism	Y	Y	Y	N	N
Procedural Features					
Functions	Y	Y	Y	Y	Y
States or Rule sets	Y	Y	N	Y	Y
IF .. THEN .. ELSE syntax	Y	Y	Y	Y	Y
Certainty measures	Y	Y	Y	Y	Y
Rule Processing					
Forward/Backward/Bidirectional	Y/Y/Y	Y/Y/Y	Y/N ¹ /N	Y/Y/Y	Y/Y/Y
Pattern matching	Y	Y	Y	Y	N
Prioritization	Y	Y	Y	Y	Y
Mathematical Functions	Y	Y	Y	Y ⁴	Y
Explanatory Capabilities	Y	Y	N	Y	Y
Abduction/Induction features	N	Y ²	N	Y ²	Y ⁶
User Interface Support					
WIMP	Y	Y	N	Y	Y
WINDOWS 3.0	Y	Y	N	Y	Y
Graphics	Y	Y	N	Y	Y
Hypertext	N	N	N	Y	N ¹
Price					
PC Development	\$8,500	\$8,000	\$300	starts at \$995	\$7,000
PC Runtime	\$900	\$1,600	Free	starts at \$1300	\$500
Network Licensing	Y	Y	N	N	Y

¹ Programmable using existing language constructs ² Toolkit(s) available from vendor ³ Available thru demons

⁴ Interface to LINDO ⁵ Moving to runtime licensing ⁶ Abductive reasoning

Comparison of Knowledge-Based System Shells for the PC (p. 2 of 3)					
Product Vendor	Intelligence Compiler IntelligenceWare	Kappa PC IntelliCorp	KBMS/PC AICorp	KES Software A&E	Knowledge Pro Knowledge Garden
Hardware Requirements					
Extended Memory	640 KB	640 KB	4 MB	640 KB	640 KB
Hard Disk Space	3 MB	2 MB	8 MB	2 MB	1.2 MB
Software Requirements					
MS-DOS	Y	Y	Y	Y	Y
MS-DOS and WINDOWS 3.0	Y	Y	N	Y	Y
OS2	N	N	Y	Y	N
File and Database Support					
ASCII/dBase/Lotus	Y/Y/Y	Y/Y/Y	Y/Y/Y	N ¹ /N ¹ /N ¹	Y/N ² /N ²
SQL	N	Y	Y	N	N
Application Program Interface					
Call-in/Call-out	Y	Y	Y	Y	Y
Embeddable	N	Y	N	Y	N
Object-Oriented Features					
Encapsulation	Y	Y	Y	Y	Y
Inheritance	Y	Y	Y	Y	Y
Polymorphism	N	Y	Y	N	N
Procedural Features					
Functions	Y	Y	Y	Y	Y
States or Rule sets	Y	Y	Y	Y	Y
IF .. THEN .. ELSE syntax	N	Y	Y	Y	Y
Certainty measures	Y	N ¹	Y	Y	N
Rule Processing					
Forward/Backward/Bidirectional	Y/Y/Y	Y/Y/Y	Y/Y/Y	Y ³ /Y/N	N/Y/N
Pattern matching	Y	Y	Y	Y	N
Prioritization	Y	Y	Y	Y	N ¹
Mathematical Functions	Y	Y	Y	Y	N
Explanatory Capabilities	Y	N	Y	Y	N
Abduction/Induction features	Y	N	N	Y ^o	Y ²
User Interface Support					
WIMP	Y	Y	Y	Y	Y
WINDOWS 3.0	Y	Y	Y	Y	Y
Graphics	Y	Y	Y	Y	Y
Hypertext	Y	N	Y	N	Y
Price					
PC Development	\$495	\$3500	to \$8,500	\$4,000	\$495
PC Runtime	Free ⁵	\$450	to \$600	\$400	Free
Network Licensing	N	N	OS2 only	Y	N

¹ Programmable using existing language constructs

² Toolkit(s) available from vendor

³ Available thru demons

⁴ Interface to LINDO

⁵ Moving to runtime licensing

^o Abductive reasoning

Comparison of Knowledge-Based System Shells for the PC (p. 3 of 3)			
Product Vendor	LEVELS OBJECT Information Builders	NEXPERT/Object Neuron Data	1st Class HT AICorp
Hardware Requirements			
Extended Memory	2 MB	3 MB	512 KB
Hard Disk Space	4 MB	4 to 12 MB	1 MB
Software Requirements			
MS-DOS	N	N	Y
MS-DOS and WINDOWS 3.0	Y	Y	Y
OS2	N	Y	
File and Database Support			
ASCII/dBase/Lotus	Y/Y/N	Y/Y/Y	Y/Y/Y
SQL	N	Y ¹	N
Application Program Interface			
Call-in/Call-out	Y	Y	Y
Embeddable	N	Y	N
Object-Oriented Features			
Encapsulation	Y	Y	N
Inheritance	Y	Y	N
Polymorphism	N	N	N
Procedural Features			
Functions	N	N	Y
States or Rule sets	Y	N	N
IF .. THEN .. ELSE syntax	Y	N	N
Certainty measures	Y	N ¹	Y
Rule Processing			
Forward/Backward/Bidirectional	Y ³ /Y/N	Y/Y/Y	Y/Y/Y
Pattern matching	Y ³	Y	N
Prioritization	Y	Y	N
Mathematical Functions	Y	Y	Y
Explanatory Capabilities	Y	Y	Y
Abduction/Induction features	N	Y ²	Y
User Interface Support			
WIMP	Y	Y	Y
WINDOWS 3.0	Y	Y	Y
Graphics	Y	Y	Y
Hypertext	Y	N	Y
Price			
PC Development	\$495	\$5,000	\$995 to \$2,495
PC Runtime	Free	\$1,000	Free
Network Licensing	N	Y	Y

¹ Programmable using existing language constructs ² Toolkit(s) available from vendor ³ Available thru demons

⁴ Interface to LINDO ⁵ Moving to runtime licensing ⁶ Abductive reasoning

APPENDIX G: STATEMENT OF FUNCTIONAL REQUIREMENTS

PROJECT GOALS

Reduce workload Near-term/Long-term:

Development and refinement of the expert system will probably increase rather than decrease CA workload in the near-term, with a post-production comparability research tool. In the long-term the system should reduce CA time spent on substitutions by elimination of the need to review straight-forward substitutions. This will free time to give additional attention to more difficult substitutions, improve checklists, and in general use time more effectively. This will improve the quality of data, which represents the ultimate goal.

Consistent Substitutions:

The CA, with the help of the expert system, should be able to reach the same conclusion in terms of completeness, consistency, and comparability for a given rule base, given similar spec-data relationships for reported substitutions. Improved data quality will result.

Documentation of Expertise:

The interaction between the CA and the system will produce clearly defined written documentation on ELI specific rules a commodity analyst considers when making a substitution comparability decision including specification completeness and consistency within the specifications. The criteria should be sufficiently detailed to enable a new or back-up analyst to make the same comparability decisions as the regular analyst. Again, improved data quality will result.

SYSTEM REQUIREMENTS

NEAR-TERM

User Friendly Interface:

The system needs to be relatively easy for a user (commodity analyst) to interact with in terms of obtaining any information required. The analyst should be able to interface with the system and negotiate his/her way through the system without having to refer to a manual.

Explanatory Capabilities:

The expert system shell should have the ability to fully explain its decisions. It should be clear from this reporting which rules were used and in what order. This explanation should be recorded in some form, allowing later review and perhaps aggregation.

Processing Speed Development Mode:

Based on experiences with some expert systems it was found that during the rule development phase that the system/computer can slow to unacceptable levels when running tests. In some cases simple operations took over a minute to finish. The response time in entering rules and other parameters, and changing and testing the rule base, should be minimized.

Handling of Free Text:

Because most ELIs contain free text specifications, it is important that the expert system have the ability to differentiate and/or categorize the free text entries.

Time to Develop Prototype:

The expert system package should be easy to use so that a working prototype could be developed by the BLS expert system group within 5 months.

Analysts' Time for Development Near-term:

The expert system package should allow for the development of a prototype generic rule base. A commodity analyst should be able to adapt the generic rule base to their ELI and adjust or expand the rule base to the specific needs of that ELI.

Analysts' Time for Maintenance Near-term:

The expert system package should be flexible. Changes to the rules must be easy to enter/program and must be easy to retest.

Commercial Software Costs:

The cost of the expert system shell (shells) selected for the near-term project, along with any necessary licensing fees or other incurred expenses including training, should not exceed the project's budget. A reasonable ceiling to use is \$12,500, including training.

Access to Data Base Machine:

The expert system should have interface capability with the CPI's production hardware and software as well as the PCs utilized by the CAs. A format for which there is an easily available linking option would be acceptable.

System Code Development Cost:

The cost required to acquire a computer program (either developing in-house, through external contract, or off-shelf package) that will enable the expert system to process the necessary production data should be minimized.

Interactive Processing Speed:

The lapse of time between when a commodity analyst hits a computer key until the program will accept input again, using an IBM PS/2 386 16 Mhz PC, should be minimized.

LONG-TERM

Batch Processing:

The system should have the ability to automatically process many quotes and save the decisions reached along with the associated information about how and why each decision was made for later use (possibly interactively on a quote-by-quote basis); no input would be necessary from the CA. Ideally, there would be a way to eventually incorporate the decisions into the PRS.

Time to System Implementation:

The time required for the long-term pre-production system to become operational should be minimized.

Analysts' Time for Development Long-term:

The expert system shell should allow for analysts to apply the process to a new ELI without a significant time burden. In the long-term, the product should be more automated and therefore less labor-intensive.

Analysts' Time for Maintenance Long-term:

Because the main responsibility of a analyst is the daily production work needed for the index calculation and production, time spent on maintenance should be minimal. Changes to the rules must be easy to enter/program. For example, in cases of checklist revision it is possible that all rules may have to be changed. This requirement is particularly important in the long-term, because the system would be a part of production and therefore changes would of necessity be timely.

Tracking of Decision Statistics:

The expert system must keep records of all decisions it makes to enable review at a later time. This should include what decisions were made, how they compared to production decisions, and which rules fired. The last measure is distinguished from explanatory capabilities in that this is an aggregate measure on a rule-by-rules basis, rather than relating to specific quote decisions.

CONSIDERATIONS

Project Risk:

The risk that the project may fail, leaving us with nothing to show for our money and effort, should be considered. This is to be weighed against the possible gains that may be achieved using each approach. This requirement should be interpreted in terms of the optional approaches for a long-term system.

INTERNAL DISTRIBUTION

1-10.	L. F. Arrowood	17-26.	B. E. Tonn
11.	R. T. Goeltz	27.	Central Research Library
12.	R. K. Gryder	28.	Document Reference Section
13.	E. L. Hillsman	29-30.	Laboratory Records
14.	H. L. Hwang	31.	Laboratory Records - RC
15.	J. O. Kolb	32.	ORNL Patent Office
16.	M. A. Kuliasha		

EXTERNAL DISTRIBUTION

- 33. Dr. Bruce G. Buchanan, Department of Computer Science, University of Pittsburgh, 206 Mineral Industries Building, Pittsburgh, PA 15260.
- 34. Dr. Allan Hirsch, Vice President, Environmental Sciences and Director, Washington Operations, Midwest Research Institute, 5109 Leesburg Pike, Suite 414, Falls Church, VA 22041.
- 35. Dr. Helen M. Ingram, Director, Udall Center for Studies in Public Policy, The University of Arizona, 803/811 East First Street, Tucson, Arizona 85719.
- 36-43. Mr. Richard Kamalich, Bureau of Labor Statistics, 600 E Street, N.W., Room 3307, Washington, DC 20212.
- 44. Mr. Calvin D. MacCracken, President, Calmac Manufacturing Corporation, 101 West Sheffield Avenue, Englewood, NJ 07631.
- 45. Ms. Jacqueline B. Shrager, Director, Office of Technology Transfer, 405 Kirkland Hall, Vanderbilt University, Nashville, TN 37240.
- 46. Dr. Martin Williams, Professor, Department of Economics, Northern Illinois University, DeKalb, IL 60115.
- 47. Office of Assist Manager for Energy Research and Development, DOE/ORO, P.O. Box 2001, Oak Ridge, TN 37831-8600.
- 48-49. Office of Scientific and Technical Information, U.S. Department of Energy, P.O. Box 62, Oak Ridge, TN 37831.

END

DATE
FILMED

3 / 24 / 92