TECHNICAL REPORT

September 1, 1991 through November 30, 1991

CARBONATION AS A BINDING MECHANISM FOR COAL/CALCIUM HYDROXIDE PELLETS

DE-FG 22-91PC 91334

Principle Investigator: David M. Rapp, Illinois State Geological Survey (ISGS)
615 E. Peabody Drive
Champaign, IL 61820
(217) 244-4991

Other Investigators:

Henry P. Ehrlinger	(217) 244-4989	Richard L. Berger	(217) 333-6961
Keith C. Hackley	(217) 244-2192	University of Illinois (UI-UC)	
John M. Lytle	(217) 244-8389	Civil Engineering Department	
David L. Moran	(217) 244-4985	Champaign, IL 61820	
615 E. Peabody Drive			
Champaign, IL 61820			
Gary Schanche	(217) 398-5505	Poo Chow	(217) 333-6670
Construction Engineering Research Lab		University of Illinois	
Champaign, IL 61820		Department of Forestry	
		Champaign, IL 61820	
Richard Strickland	(205) 386-2542		
Tennessee Valley Authority			
Muscle Shoals, AL 35660			

Project Monitor: Dr. Dan Banerjee

ABSTRACT

Current coal mining and processing procedures produce a significant quantity of fine coal that is difficult to handle and transport. The objective of this work is to determine if these fines can be economically pelletized with calcium hydroxide, a sulfur capturing sorbent, to produce a clean-burning fuel for fluidized-bed combustors or stoker boilers.

To harden these pellets, carbonation, which is the reaction of calcium hydroxide with carbon dioxide to produce a cementitious matrix of calcium carbonate, is being investigated. Previous research indicated that carbonation significantly improved compressive strength, impact and attrition resistance and "weatherproofed" pellets formed with sufficient calcium hydroxide (5 to 10% for minus 28 mesh coal fines).

This research is a two-year effort where the first year will focus on the production of a compliance stoker fuel from relatively low sulfur (1.46%) minus 28 mesh coal fines. The second year will seek to develop a general approach to the production of carbonated coal/calcium hydroxide pellets for fines ranging from minus 28 to minus 200 mesh.

During this quarter, a fine coal sample (-28 mesh) was collected from a southern-Illinois coal-cleaning plant. Also, an undergraduate student was hired and trained in laboratory procedures. Test work is underway, but results are too preliminary for presentation.

MASTER

This project is funded by the U. S. Department of Energy (PETC) and by the Illinois Department of Energy and Natural Resources as part of their cost-shared program.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EXECUTIVE SUMMARY

Each year, 2-3 million tons of coal fines are disposed of in Illinois due to their limited marketability. This represents approximately 5% of the state's total coal production. The objective of this work is to economically pelletize these fines with a sulfur capturing sorbent, calcium hydroxide, to produce a fuel which will meet future sulfur dioxide emissions levels.

To decrease binder costs, carbonation is being investigated as a method for improving pellet quality. Carbonation is the reaction of calcium hydroxide with carbon dioxide to produce a bonding matrix of calcium carbonate. The rate of reaction is slow at atmospheric levels of carbon dioxide (0.033%) but increases dramatically at higher concentrations. The process has been applied to harden pellets formed from iron ore fines but has yet to be applied to coal fines. Previous efforts to produce coal/sorbent pellets have used binders such as corn starch or asphalt to develop pellets of acceptable integrity. This can add significantly to the cost of pelletization.

This research represents a continuation of two projects, co-funded by the CRSC and the Army Construction Engineering Research Lab (CERL). The CRSC's interest in funding the previous work has been to develop a method for utilizing Illinois coal fines that, in many cases, are currently being disposed of in tailing ponds. CERL's interest has been to develop a fuel for their stoker boilers that will burn at the year 1995 and the year 2000 compliance sulfur dioxide emission levels. For the current work, the Tennessee Valley Authority has pledged \$10,000 dollars in cash and approximately \$5,000 of "in-kind" support to the project.

Results from past work using a Illinois No. 6 preparation-plant fines concentrate indicated that when pellets are formed with sufficient calcium hydroxide, (5 to 10% for 90% minus 28 mesh coal fines) carbonation produced significant improvements in compressive strength, impact and attrition resistance and weatherability. Of most significance is that the carbonated pellets maintain their integrity while stored under water (24 hours) while non-carbonated pellets or pellets formed with corn starch, a conventional binder, tend to disintegrate, often within 5 minutes. The "weatherproofing" is likely due to the pellet being held together by the cementitious matrix of calcium carbonate which forms when a pellet is carbonated.

Previous combustion testing conducted in a laboratory furnace at 850 C resulted in sulfur captures of greater than 70% C for a pellets formed with 10 weight per cent calcium hydroxide-a 2.3/1 Ca/S ratio. This temperature is in the range of operation for fluidized-bed combustors.

The overall goal of the work is to further develop the process of carbonation as a method of binding Illinois Coal. The proposed research is for a two-year effort with two major goals. A discussion of each of the goals follows.

1. Production of Compliance Stoker Fuel from Fine Illinois Coal - The first goal is to investigate the potential for producing a stoker fuel from fine Illinois coal with potential to burn at the year 2000 compliance sulfur dioxide emission limit of 1.2 pounds per million Btu. For this work, a relatively low sulfur Illinois coal will be tested. The sample is a composite concentrate from a flotation circuit (-100 mesh coal) and a collection of spiral concentrators (28x100 mesh coal) and is low enough in sulfur that only 45% sulfur capture is required to achieve the year 2000 sulfur dioxide emission limit. Sulfur captures of 45% and higher have been achieved in plant-scale stoker tests. Tests will be conducted investigating the production of pellets on a larger scale and to determine the potential of calcium hydroxide for capturing chlorine. Low-sulfur, low-ash cellulosic residue from TVA's acid hydrolysis processing of municipal waste will be investigated for its potential to produce stronger cleaner-burning pellets.

2. Determination of a General Approach to the Production of Carbonated Coal/Calcium Hydroxide Pellets - Because mining and processing methods differ from plant to plant, the particle size and moisture content of fine coal in this fraction will vary from plant to plant. Also, some companies may wish to pelletize their minus 28 mesh fines while others may wish to pelletize only their minus 100 mesh fines. Previous results indicated that effective binder levels and proper carbonation conditions vary as a function of particle size and moisture content. The equipment used for pelletization may also vary as a function of particle size and product moisture due to materials handling problems. Thus, it is necessary to determine a general approach to economically pelletizing and carbonating coal/calcium hydroxide pellets.

Work associated with goal number one will be completed in year one. Work associated with goal number two will start in year one and be completed in year two. The two goals are complimentary and work to produce a compliance stoker fuel will certainly be applicable to producing a fuel for fluidized-bed combustors.

During this quarter, the minus 28 mesh fine coal sample was collected. Also, an undergraduate student was hired and trained in laboratory procedures. Test work is underway, but results are too preliminary for presentation.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PROJECT DESCRIPTION

Objectives

The proposed research is for a two-year effort. The project has two major goals, each with three tasks.

1. Production of Compliance Stoker Fuel from Fine Illinois Coal - The first goal is to economically produce a stoker fuel from fine Illinois coal with potential to burn at the year 2000 compliance sulfur dioxide emission limit of 1.2 pounds per million Btu. The following three tasks will be performed for goal one.

Task 1 To investigate a potential method of preparing pellets on a larger scale, mixtures of coal and calcium hydroxide will be taken to California Pellet Mill's, Crawfordsville, Indiana facility and pelletized using their pilot-scale equipment.

Task 2 To increase the potential for achieving compliance sulfur emissions, low sulfur cellulosic residue will be incorporated into the pellets and the effect on pellet quality will be determined.

Task 3 To determine the effect of calcium hydroxide content on chlorine emissions, combustion tests will be conducted at 850 C and 1350 C on pellets containing 0, 5, and 10 weight percent calcium hydroxide.

2. Determination of a General Approach to the Production of Carbonated Coal/Calcium Hydroxide Pellets - Mining and processing methods differ from plant to plant and the particle size and moisture content (after dewatering) of the fine coal fraction will vary from plant to plant. Also, some plants may wish to pelletize their minus 28 mesh fines while others may wish to pelletize only their minus 100 mesh fines. Previous results obtained on this project have indicated that effective binder levels and proper carbonation conditions vary as a function of particle size and moisture content. The equipment used for pelletization may also vary as a function of particle size and product moisture due to materials handling problems. Thus, it is necessary to determine a general approach to economically pelletizing and carbonating coal/calcium hydroxide pellets. To address goal number two, the following work will be performed.

- Task 4 To determine the relationship among moisture and binder content and particle size on pellet quality, tests will be conducted using IBC-106 ground to several particle sizes. Several moisture contents and binder levels will be tested. IBC-106 will be used for this work because of the data base that has already been generated using this sample during year one of this project and because a grinding curve has already been generated using this sample.
- Task 5 To investigate the potential application of extrusion toward pelletizing Illinois coal fines, tests will be conducted using an extruder located at the Ceramic Engineering Building of the University of Illinois. An extruder may be an effective method of pelletization because it can be used to mix the coal and calcium hydroxide and also produce a pellet.
- Task 6 To determine if the burning of coal or municipal waste could be used as a source of carbon dioxide, the effect of increased gas temperature on carbonation and pellet quality will be investigated. These tests will be conducted at reduced gas concentrations.

To potentially further reduce processing costs, an "encapsulation" approach to carbonation will be investigated. By encapsulation it is meant that just the outer portion of the pellet will be reacted to harden and weatherproof it.

The tasks associated with the first goal of the project (tasks 1-3) will be completed during year one. The particle size study portion of goal number two (task 4) will also start in year one with the remainder of the work to be completed in year two (tasks 4-6).

Background

There are currently no coals mined in Illinois which can produce a stoker fuel which will burn at the year 2000 compliance sulfur dioxide emission level. To comply with the coming emission standard, stoker boiler operators can choose among these options: installation of flue gas scrubbers, switching to Western coals, conversion to fluidized-bed combustors or use of coal/calcium hydroxide pellets.

Battelle Columbus has burned coal/sorbent pellets in a plant-scale stoker and achieved sulfur captures in the range of 45-50% even with operating temperatures of 1350 °C and higher. The report indicated that the pellets could be burned in the stoker boiler with no major modifications to the stoker facility and that the approach was economical when compared to flue gas desulfurization. The approach advocated in this work is to target an Illinois coal that needs only 45% sulfur capture to achieve compliance sulfur emissions and to develop carbonation as a method to economically pelletize this sample for use in a stoker boiler.

For both low and high sulfur fine coal, fluidized-bed combustion is seen as a method for cleanly-burning pelletized coal fines. Several states have built or will build fluidized-bed combustors to burn waste coal. Although fluidized-bed combustors can be utilized to cleanly-burn fuels with high sulfur and mineral matter content, there are advantages to reducing the sulfur and mineral matter content prior to combustion. In a recently funded CRSC research project investigating the economics of fluidized-bed combustion of a high ash (55%) and high sulfur (4.8%) refuse, it was determined that use of a lower ash, lower sulfur refuse can significantly improve the economics of fluidized-bed combustion. This was because of the high limestone consumption and waste disposal costs associated with burning a "dirty" fuel. The same study investigated flotation for recovery/cleaning of coal from a refuse stream and indicated that doing so is economical, but dewatering the concentrate to moisture levels of less than 15% could be uneconomical. The approach advocated here of first cleaning the refuse stream to as low of sulfur and mineral matter content as possible followed by pelletization with calcium hydroxide is in accordance with the recommendations of this report. Carbonation to improve pellet quality could further improve process economics by reducing binder costs.

RESULTS AND DISCUSSION

The objectives of this research are to address both the specific and general topics related to the production of coal/calcium hydroxide pellets. The focus of the first year's research will be on the specific topics in regard to preparing a compliance stoker fuel from an Illinois coal that needs approximately 45% sulfur capture to burn at the year 2000 compliance SO_2 emission limit of 1.2 lbs SO_2 per million Btu. The sample to be used for this effort is a relatively low sulfur Springfield (Illinois No. 5) seam fines concentrate. This sample was collected this quarter from a southern-Illinois preparation plant flotation circuit (100 mesh coal) and a collection of spiral concentrators (28 x 100 mesh coal).

The objective of the work using the No. 5 seam sample will be to determine a method of pellet production specific to this coal in regard to proper pelletization and carbonation conditions including moisture level and binder content. To this end an undergraduate student in chemical engineering has been hired and trained in laboratory procedures. Research is in progress, but results are too preliminary to report.

SUMMARY AND CONCLUSIONS

During the next quarter, work on Task 1 using the Illinois No. 5 seam fines concentrate will continue along with some follow-up work on last year's research. This follow-up work will be on the Illinois No. 6 seam coal fines concentrate used in last year's work.

END

DATE
FILMED

4 / 01 / 92

I