PROGRESS REPORT

A NOVEL PROCESS FOR MANUFACTURE
OF METHANOL

Principal Investigators

John W. Tierney

Irving Wender

Chemical and Petroleum Engineering Department

University of Pittsburgh

Pittsburgh, PA 15261

Prepared for the Department of Energy

Contract No. DE-FG2289PC89786

January 10, 1990

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

US/DOE Patent Clearance is not required prior to the publication of this document.

JAN 16 1

TABLE OF CONTENTS

1.0	ABSTRACT	1
2.0	INTRODUCTION	2
3.0	RESEARCH OBJECTIVES	3
4.0	CURRENT WORK	4
5.0	FUTURE WORK	6
6.0	REFERENCES	7

1.0 ABSTRACT

A bench scale reactor setup, used previously in our laboratory for conducting studies of the conversion of 2:1 synthesis gas to methanol was modified to provide better instrumentation and control of reaction temperature, pressure and feed. A Hewlett-Packard gas chromatograph was incorporated as part of this unit. Further improvements in the reactor system are planned.

2.0 INTRODUCTION

An experimental investigation of a novel process for converting synthesis gas to methanol is being carried out. This new route to methanol was developed in our laboratory. It has significant advantages over the conventional gas phase synthesis, in that the recycle of unreacted material can be virtually eliminated and lower temperatures will suffice. The reaction is not significantly poisoned by CO_2 or H_2O products. It has been demonstrated that the reaction proceeds with good rates at 140°C and 6 MPa. pressure. However, the nature of the catalyst and of the possible intermediates is not well understood. The thrust of this research program is to obtain a better understanding of the reaction and particularly of the role of the catalyst. This information is essential for scale-up of the process.

Two papers have been published^(1,2) reporting our studies of these reactions, one on the individual reactions (carbonylation of methanol and hydrogenolysis of methyl formate) and the other on the concurrent reaction in which a homogenous carbonylation catalyst (e.g. potassium methoxide) and a heterogenous hydrogenation catalyst (e.g. copper-chromite) are used. The current work is part of a three and a half-year project which started in September, 1989.

3.0 RESEARCH OBJECTIVES

Principal research objectives are,

- To determine the effect of alternate catalysts on the synthesis. This will include copper chromite catalysts impregnated with alkali metals such as potassium, rubidium and cesium as well as their use as homogenous catalysts in the form of methoxides or similar salts. The use of various copper chromite catalysts with different compositions will be studied; e.g. substituting barium for manganese in copper chromite catalyst has a beneficial effect.
- To determine the nature of the active catalyst in this reaction and the effect of deactivating agents such as CO_2 , H_2O and CO .
- To determine the rate limiting steps in this reaction so that proper scale-up is possible. The effects of catalyst loading and reactor volume are of special importance.
- To develop mathematical models which can be used for prediction of rates of reaction and are suitable for scale-up of the reaction.

4.0 CURRENT WORK

Emphasis during the September-December quarter was placed on modifications of the laboratory reactor. The reaction is being carried out in a semi-batch manner -- continuous addition and removal of gas and periodic removal of liquid. Obtaining representative samples of gas and liquid has been difficult. The gas transfer lines leaving the reactor can cool and some of the methanol, methyl formate or other products can condense and return to the reactor. This is being solved by heating the gas transfer lines. The removal of liquid sample is complicated by flashing when the liquid pressure is reduced. We plan to install new sampling valves in both the liquid and gas lines so that a sample can be passed directly into the gas chromatograph used for analyses. Previously, manual transfer of samples was required.

In addition to the provision of on-line sampling and analysis of both phases, other modifications were made to improve the experimental setup.

A schematic of the experimental setup is shown in Figure 1. All gas and liquid transfer lines were replaced with new tubing. Gas outlet lines leading to the sample port were well insulated and wrapped with heating tape wherever possible, to prevent condensation within the lines. The heater thermocouple is now connected to a digital readout device, and the reactor temperature is controlled by a feedback temperature controller equipped with a relay. Mass flow controllers are used to control the flow rate of the inlet gases and a back pressure controller regulates the reactor pressure. All the controls were mounted on a panel and the entire experimental setup is mounted on a table built with struts. All the gas and liquid transfer lines are shortened to reduce the lag

in the lines. All the valves are replaced and the liquid withdrawing tube was shortened. A Hewlett-Packard gas chromatograph with a Porapak-Q and Carbosieve-S columns was incorporated in the experimental setup for gas and liquid analysis. A 8.5% H_2 in Helium was used as the carrier gas in place of pure Helium with the intention of measuring H_2 directly.⁽³⁾ The gas chromatograph was standardized for all the components present in the analyses.

5.0 FUTURE WORK

Equipment modifications are not complete and will be continued during the next quarter. New on-line sampling valves are being purchased and will be installed.

Preliminary runs to test the operability of the setup are being made. In the next quarter, a number of homogenous catalysts including salts of Na, K, Rb and Cs along with copper-chromite will be tested in reaction studies with the objective of identifying the possible promotion effect of alkali and the counter ion on the synthesis rate. Possible salts envisaged are sodium and potassium methoxide, potassium formate, KCl, cesium formate and cesium bicarbonate. This will help in identifying the role of the homogenous catalyst in this two step synthesis.

6.0 REFERENCES

- 1) Z. Liu, J. W. Tierney, Y. T. Shah and I. Wender, "Methanol Synthesis via Methyl Formate in a Slurry Reactor", Fuel Processing Technology, 23, 1989, p. 149-167.
- 2) Z.Liu, J. W. Tierney, Y. T. Shah and I. Wender, "Kinetics of the Two Step Methanol Synthesis in the Slurry Phase", Fuel Processing Technology, 18, 1988, p. 185-199.
- 3) "Isothermal and Temperature Programmed Analyses of Permanent Gases and Light Hydrocarbons", GC Bulletin 760F, Supelco, Inc., 1983.

Figure 1: Schematic of Experimental Setup.

END

**DATE
FILMED**

3 / 26 / 92