10
5-29-91 850

Conf-910505--68
SLAC-PUB-5515
May 1991
(A)

The Linac and Booster RF Systems for a Dedicated Injector for SPEAR*

J.N. WEAVER, S. BAIRD, M. BALTAY, M. BORLAND,† H.-D. NUHN, J. SAFRANEK, C. CHAVIS, L. EMERY,†
R.D. GENIN, R. HETTEL, H. MORALES, J. SEBEK, J. VOSS, D. WANG,‡ H. WIEDEMANN, B. YOUNGMANN

Stanford Synchrotron Radiation Laboratory, Stanford, California 94309

and

R.H. MILLER

Stanford Linear Accelerator Center, Stanford, California 94309

SLAC-PUB--5515

DE91 012376

Abstract

A 120 MeV, 2856 MHz, TW linac, with a microwave gun, alpha magnet, and chopper, has been built at SSRL as a preinjector for and along with a 3 GeV booster synchrotron ring. The resulting injector will be available on demand to fill SPEAR, which is a storage ring now dedicated to synchrotron light production. The linac sections were purchased from China, the XK-5 klystrons were obtained surplus from SLAC, the modulators are a variation on those at SLAC and were built by SSRL, the alpha magnet and chopper were designed and built at SSRL and the microwave gun was designed and built in collaboration with Varian Associates. The RF system for the booster ring is similar to those at SPEAR and PEP and was built by SSRL. Some of the interesting mechanical and electrical details are discussed and the operating characteristics of the linac and ring RF system are highlighted.

I. INTRODUCTION

The Stanford Positron Electron Accelerator Ring (SPEAR) started out in the early 1970s as an electron positron high energy physics facility with two colliding beam interaction regions. In 1974 the ψ -J particle was discovered independently at SLAC's SPEAR and BNL's (Brookhaven National Laboratories) AGS. With the advent of PEP and SLC/SLD at SLAC, the high energy physics effort at SPEAR wound down and since 1989 it has been used solely as a source for synchrotron radiation for SSRL and visiting experimenters. Initially, it was thought that SLC could continue to fill SPEAR on some reasonable schedule, but that has not been possible in practice. So a little over three years ago a major project was begun at SSRL to build a dedicated full energy injector. [1] The new injector consists of: 1) a 2 MeV microwave electron gun 2) a 120 MeV, 9 m long, short pulse, 2856 MHz linac and 3) a 3 GeV, 134 m in circumference, 358.54 MHz synchrotron booster ring, all pulsing at a 10 Hz rate. The day before Thanksgiving of 1990 a 2.34 GeV beam was injected and stored in SPEAR, marking the end of the formal construction and commissioning phases. Remoting of controls, improving the stability, familiarizing operators with the controls and quantifying machine characteristics has been the thrust of recent efforts. In the following sections a description is given of the injector's two separate and different frequency RF systems. Synchronization of the two,

non-harmonic (unfortunately) systems is achieved through the linac's chopper. [2] Synchronization of injection into SPEAR is discussed elsewhere. [3]

Figure 1. SSRL's Major RF Systems.

II. THE LINAC

The linac, as shown in Fig. 1, injects at a 10 Hz rate, three, 120 MeV bunches, spaced by 350 ps and of $\approx 4 \times 10^6$ electrons each, into the injector booster ring through a series of bend magnets, a pulsed kicker magnet and a septum magnet. A 2 MeV microwave gun puts out less than a 2 μ s long string of several thousand bunches. Since each bunch is the result of a portion of a sinusoidal electric field on a thermionic cathode, the energy spread and longitudinal extent of each bunch is considerable. [4]. An alpha magnet with an internal scraper is used to compress the bunches longitudinally and scrape off a large portion of the low energy tail. Before entering the linac a fast rising pulse, traveling upstream on a stripline chopper, sweeps the multibunch beam by a slit. The result is that only approximately three bunches emerge to be accelerated by the linac. The gun-to-linac layout is shown in Fig. 2, and it is described in detail in references [2, 4, 5] and [6]. Figure 3 shows the linac RF circuit schematically and Fig. 4 shows the high power part of the RF circuit isometrically.

Three, SLAC-type, $2\pi/3$ mode, traveling-wave accelerator sections (DLWG's) were purchased from IHEP (Institute of High Energy Physics), Beijing, PRC. The DLWG tuning was checked at SLAC as part of an acceptance test and found to be very good. Furthermore, a high power

* Work supported by Department of Energy contract DE-AC03-76SF00515 and the Office of Basic Energy Sciences, Division of Material Sciences.

† Now at Argonne National Labs, Argonne, IL 60439.

‡ Now at Bates Linac-MIT/LNS, Middleton, MA 01949.

MASTER

Contributed to the IEEE Particle Accelerator Conference, San Francisco, CA, May 6-9, 1991

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

eb

Figure 5. Linac and Booster Ring Pulse, RF and Beam Timing.

shown in Fig. 3. A beamline vacuum valve and waveguide window allow isolation of the gun vacuum from the linac when desired and a beamline valve at the end of the linac allows isolation of the linac. The ionization gauges operate interlocks that switch off the RF if the pressure goes too high. The linac has three different temperature water circuits: 1) $25^\circ \pm 5^\circ\text{C}$ low conductivity water from the SLAC system for the klystrons, 2) $45^\circ \pm 0.1^\circ\text{C}$ water for the DLWG's and 3) 35° to 55°C , adjustable but stable to $\pm < 1^\circ\text{C}$, water for the microwave gun, depending upon its operating parameters. The second system is self contained with a pump, a heater, a heat exchanger (the heat is rejected to the SLAC system) and a mixing valve. It supplies 60 gpm at 70 psig. The third system taps off < 2 gpm from the second system and puts it through a heater and/or a heat exchanger to get the desired temperature at the gun, then returns it. Separate temperature sensors for the DLWG's and the gun work through two controllers to regulate the mixing valve and a heater, respectively.

III. BOOSTER RING RF

As shown in Fig. 1 and 6, a second lower frequency RF system is part of the injector and SPEAR. The booster ring is 160 wavelengths in circumference and SPEAR is 280, so every seventh turn around the booster ring is synchronous with the same bucket in SPEAR on every fourth turn. Three bunches from the linac are let into the booster at the right time, as seen in Fig. 5h and j, by synchronizing the chopper with the booster RF. The booster RF cavity is an early SPEAR cavity refurbished, the 358.54 MHz, 500 kW cw klystron is a PEP type tube tuned for the slightly different (alas!) SPEAR frequency and the control system is a carbon (or Xerox?) copy of PEP's [8] Since the booster ring is more stable if the RF accelerating fields are not so strong during the low energy part of the ramping cycle, the reference for the amplitude feedback circuit is ramped along with the synchrotron, as shown in Fig. 6.

Figure 6. Injector Booster Ring RF Circuit.

IV. OPERATIONS

The microwave gun, alpha magnet and chopper came on-line without much difficulty, although numerous hours were spent studying and characterizing the preinjector. The linac high power RF networks RF processed in less than 40 hours initially and now pump down in less than a day, if let up to nitrogen. It takes several days, and a hot nitrogen bake of the RF loads may be required, if the linac is let up to air. The modulators had a few high voltage growing pains, but they have settled down since. The chopper with its permanent magnets is designed to limit excessive beam transmission (potentially 1000 times the design value), but under poor set-up conditions for the GTL (Fig. 2) or unusual failure modes for the chopper (e.g., slow rise time) the linac is shut off by average current monitoring circuits. In general the RF circuits for the injector are not required to be ultra stable or critically adjusted. So the broad optimums often encountered for the GTL settings in particular have not been a fundamental limitation.

REFERENCES

- [1] H. Wiedemann et al., "3 GeV Injector Synchrotron for SPEAR," Proc. 1991 PAC, San Francisco, CA.
- [2] M. Borland et al., "Design and Performance of the Traveling-Wave Beam Chopper for the SSRL Injector," Proc. 1991 PAC, San Francisco, CA.
- [3] R. Hettel et al., "Triggers and Timing System for the SSRL 3 GeV Injector," Proc. 1991 PAC, San Francisco, CA.
- [4] M. Borland, PhD thesis, Stanford University. (1991).
- [5] M. Borland et al., "Performance of the 2 MeV Microwave Gun for the SSRL 150 MeV Linac," Proc. 1990 Linac Conf., 761-3, Albuquerque, NM.
- [6] Tanabe et al., SLAC-PUB-5054, (Aug. 1989).
- [7] H. Schwarz, IEEE Trans., NS-32, 1847-51. (Oct 1985).
- [8] J.-L. Pellegrin et al., IEEE Trans., NS-28, 2320-2. (Jun 1981).