MASTER

A Preliminary Evaluation of the $^{235}\text{U}(n,f)$ Cross-Section
from 100 keV to 20 MeV

M. R. Bhat

BNL-NCS--33026

National Nuclear Data Center
Brookhaven National Laboratory
Upton, NY 11973 USA

DE83 013116

ABSTRACT

A preliminary evaluation of the fission cross-section of ^{235}U from 100 keV to 20 MeV is described. Variance-covariance matrices for a number of experimental data sets were constructed and used to evaluate the fission cross-section following a Bayesian procedure. The evaluated fission cross-section is compared with experimental data including the ^{252}Cf fission neutron spectrum averages and some of the problems encountered in carrying out the fit are discussed.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

INTRODUCTION

The fission cross-section of ^{235}U from 100 keV to 20 MeV is used as a primary cross-section standard and has to be evaluated using the experimental data available in this energy region. The evaluation methods are based on the least-squares criterion of Gauss [1] extended to the full variance-covariance matrix of experimental data by Aitken [2] and to the recursive algorithm for the step-wise inclusion of new data by Swerling [3]. The recursive method of Swerling may also be interpreted as a Bayesian procedure where starting from a prior, it is modified by using new experimental data to give a new best estimate and its variance-covariance matrix [4]. Use of these methods for the adjustment and error evaluation of neutron cross-section data was initiated by Dragt et. al. [5] and a further discussion of these procedures may be found in Refs. 6, 7. The evaluation method used here is a Bayesian procedure and follows the treatment of Dragt et. al. [5]. Similar methods have also been used by Perey [8], Hetrick and Fu [9] and by Larson [10].

EVALUATION PROCEDURE

The prior cross-section is specified by a column vector T containing n_t elements and a variance-covariance matrix M of order $(n_t \times n_t)$. The n_t elements are the fission cross-sections given on a convenient energy grid. The new experimental data are given as a vector R of n_r elements and a covariance matrix V of order $(n_r \times n_r)$. If the corresponding quantities calculated from the prior T are $\bar{R}(T)$, the new "best" estimate T' may be found as the vector that minimizes

$$q^2 = (T' - T)^t M^{-1} (T' - T) + (\bar{R}' - R)^t V^{-1} (\bar{R}' - R) \quad (1)$$

where t indicates transpose and $\bar{R}'$ corresponds to the new T' and is given by

$$\bar{R}' = \bar{R} + G (T' - T) \quad (2)$$

where G is a $(n_r \times n_t)$ sensitivity matrix

$$G = \frac{\delta \bar{R}}{\delta T} \quad (3)$$

The new vector T' and its variance-covariance matrix M' may be found as shown by Dragt from

$$T' = T + AX \quad \text{and} \quad (4)$$

$$M' = M - AWA^t \quad (5)$$

$$\text{where} \quad A = MG^t \quad (6)$$

and the vector X is a solution of

$$(N+V) X = R - \bar{R} \quad (7)$$

$$\text{and} \quad N = GMG^t \quad (8)$$

$$\text{and} \quad W = (N+V)^{-1} \quad (9)$$

To implement these equations a program BFIT (for Bayesian FIT) was written and has been used in this work. In actual practice, a type of "scaling" was used in solving these equations. Thus the vector T is set,

$$T = S_T T_S \quad (10)$$

where S_T is a diagonal matrix with diagonal elements $t_1, t_2, \dots, t_{n_t}$ and T_S indicates the "scaled" T vector.

Similarly, the vectors $R, \bar{R}, \bar{R}'$ are scaled using a diagonal scaling matrix S_R with diagonal elements $\bar{r}_1, \bar{r}_2, \dots, \bar{r}_{n_r}$. The (i,j) -th element of the scaled sensitivity matrix G_S may be written as

$$(G_S)_{ij} = \frac{t_j}{r_i} G_{ij} \quad (11)$$

where G_{ij} are the elements of the sensitivity matrix G defined by equation (3). The remaining equations (4) - (9) have exactly the same form as above provided each matrix is replaced by its "scaled" counterpart transformed by the scaling matrices S_T and S_R . Working with the scaled vectors T_S , R_S corresponds physically to using ratios of the cross-sections divided by the corresponding cross-sections given by the prior. Or in other words, the "gross" energy dependence of the cross-section is removed and the program uses ratios centered around the value 1.0 and any deviations from 1.0 are used to modify the prior.

In practice, this gives a certain amount of numerical stability to the program and the evaluation procedure.

DATA USED IN THE EVALUATION

The program BFIT can handle a prior vector T of maximum number of points equal to 150. Absolute ^{235}U (n, f) data were plotted and a smooth curve drawn through them and the cross-section values corresponding to the energy grid of the ENDF/B-V ^{235}U fission cross-section from 100 keV-20 MeV were read off from it. This is indicated by the MAT/MT/MF numbers as 5500/3/18 in the ENDF/B notation. The variance matrix M of the prior was arbitrarily set to have 3% error along the diagonal and a constant correlation coefficient $\rho=0.5$ for the off-diagonal elements. The experimental data used in this fit are given in Table I with references and the energy ranges covered by them. Two of these data sets [26,28] give ^{252}Cf fission spectrum averaged values of the ^{235}U fission cross-section.

The variance-covariance matrices of each of these data sets were formed using the procedures discussed by Perey [29] and by Mannhart [30]. All available information about a measurement obtained either from the publication, X-4 data files or private communication with the authors was used. The experimental errors were divided into statistical and a number of components of systematic errors. The correlation coefficient between the i -th component of systematic errors at two different energies was assumed to be constant and equal to 1.0 unless specifically stated by the author to be otherwise. It is quite possible that these correlation coefficients are energy dependent with different ranges of correlation. Guidance on this can only be provided by the data measurer and was unavailable in most cases. Error in the energy scale ΔE_n and the effect of finite resolution on the data were included by estimating additional data uncertainty due to these and increasing the errors. Data uncertainty due to fluctuations in the data below 350 keV were included using the results of Bowman et. al. [31]. In using the ^{252}Cf fission neutron spectrum averaged cross-sections it was assumed that the Californium spectrum could be represented by a Maxwellian with $\theta = 1.42$ MeV. This may not be the best representation of experimental data. Further, the variance-covariance matrix of the Californium spectrum is not available. These pieces of information are essential for an effective use of this integral measurement in data evaluation.

Amongst the data sets given in Table I, Nos. 1-8 were treated as shape data which could be arbitrarily normalized. The corresponding normalization constants were determined as part of the fitting procedure by extending the T vector and its covariance matrix M to include these.

RESULTS AND CONCLUSION

The result of this evaluation procedure is shown in Figs. 1-4 plotted against the experimental data used. The ENDF/B-V evaluation is also shown for comparison. It is noted that from 0.1-0.7 MeV, the present evaluation is systematically lower on an average by 1.6% (maximum deviation-3.5%) than the ENDF/B-V evaluation; from 0.7-4.0 MeV it is lower on an average by 1.2% (maximum deviation-2.8%). From 4.0-6.5 MeV, the BFIT' result is lower than ENDF/B-V on an average by 0.2% and from 6.5-13.5 MeV higher by 0.8%. Above 15 MeV the present evaluation follows Kari data whereas ENDF/B-V cross-section follows the Czirr data. The ^{252}Cf spectrum average over a Maxwellian spectrum with $\theta = 1.42$ MeV is found to be 1.217 b without including the Grundl [28] and Adamov [26] data; and equal to 1.218 b if they are included. It is noted that the final evaluated curve shows a non-smooth behaviour due to the statistical fluctuations in the input data and is quite consistent with them. A smoothing of the final result with a corresponding transformation of its variance-covariance matrix could be done to obtain a smooth curve. A "goodness-of-fit" for the whole evaluation was obtained as follows. Starting from a prior, in the first iteration the effect of each data set was incorporated into its prior. In a second iteration a "chi-square" defined by

$$\chi_i^2 = (\mathbf{R} - \overline{\mathbf{R}})^t (\mathbf{N} + \mathbf{V})^{-1} (\mathbf{R} - \overline{\mathbf{R}}) \quad (12)$$

is calculated for the i -th data set. In the above equation $\mathbf{R}$, $\overline{\mathbf{R}}$, $\mathbf{N}$ and $\mathbf{V}$ refer to this data set and have been defined before. In this iteration the evaluated curve obtained in the first iteration is not altered; thus χ_i^2 for

each data set is calculated comparing it with the same final curve obtained in the first iteration. Using these a global χ^2 /Degree of Freedom defined as

$$\text{Global } \frac{\chi^2}{\text{D.F.}} = \frac{\sum_i \chi_i^2}{(N_{\text{tot}} - N_{\text{par}})} \quad (13)$$

is calculated. Here the summation is over all the data sets and N_{tot} is the total number experimental points and N_{par} the number of parameters (number of points + normalizing constants) determined from the fit. For the fit shown here this global χ^2 /D.F. was found to be equal to 0.85 indicating a reasonable fit to the data. The diagonal elements of the variance-covariance matrix of the evaluated curve showed errors ranging from 0.5 - 2.0%. These low error estimates of the evaluated curve have to be reconciled with the spread in experimental data shown in Figs. 1-4 by further studies of the fitting procedure.

REFERENCES

1. K. F. Gauss, Werke, 4, 1-93 (1809), See also NBS. Sp. Pub. 300 Vol.1, p. 265 (1969).
2. A. C. Aitken, On least squares and linear combination of observations, Proc. Roy. Soc. Edinb. A55, 42 (1935).
3. P. Swerling, First order error propagation in a stagewise smoothing procedure for satellite observations, J. Astronautical Sci. 6, 46 (1959).
4. N. Morrison, Introduction to sequential smoothing and prediction, McGraw-Hill Book Co. (1969).
5. J. B. Dragt. et. al., Methods of adjustment and error evaluation of neutron capture cross-sections; application to fission product nuclides, Nuc. Sci. Eng. 62, 117 (1977).
6. B. A. Magurno and S. Pearlstein (Eds.), Proc. of the conference on nuclear data evaluation methods and procedures, Vols. 1,2, BNL-NCS-51363 (1981).
7. R. W. Peelle, Uncertainty in the nuclear data used for reactor calculations, Advances in Nuc. Sci. and Technology 14, 11 (1982) Plenum Pub. Corp.
8. F. G. Perey, Contributions to few-channel spectrum unfolding, ORNL/TM-6267 (ENDF-259) (1978).
9. D. M. Hetrick and C. Y. Fu, GLUCS: A generalized least-squares program for updating cross-section evaluations with correlated data sets ORNL/TM-7341 (ENDF-303) (1980).
10. N. M. Larson, User's Guide for BAYES: a general-purpose computer code for fitting a functional form to experimental data, ORNL/TM-8185 (ENDF-323) (1982).
11. A. D. Carlson and B. H. Patrick, Measurements of the ^{235}U fission cross-section in the MeV region, Proc. of an international conf. on neutron physics and nuclear data for reactors, Harwell (1978) and private communication.
12. O. A. Wasson et. al., Absolute measurement of the U-235 fission cross-section from 0.2 to 1.2 MeV, Nuc. Sci. and Eng. 81, 196 (1982).
13. J. B. Czirr and G. S. Sidhu, Fission cross-section of U-235 from 3 to 20 MeV, Nuc. Sci. and Eng. 57, 18 (1975) and Fission cross-section of U-235 from 0.8 to 4 MeV, Nuc. Sci. and Eng. 58, 371 (1975).

14. W. P. Poenitz, Relative and absolute measurements of the fast-neutron fission cross-section of U-235, Nuc. Sci. and Eng. 53, 370 (1974).
15. W. P. Poentiz, Additional measurements of the ^{235}U (n,f) cross-section in the 0.2 to 8.2 MeV range, Nuc. Sci. and Eng. 64, 894 (1977).
16. I. Szabo and G. P. Marquette, Measurements of the neutron induced fission cross-sections of U-235 and Pu-239 in the MeV energy range, ANL-76-90, 208 (1976).
17. D. B. Gayther et. al., Proc. 2nd IAEA panel on neutron standard reference data, p. 207 (1974).
18. D. M. Barton et. al., Measurement of the U-235 fission cross-section over the neutron energy range 1 to 6 MeV, Nuc. Sci. and Eng. 60, 369 (1976).
19. K. Kari, KFK-2673 (1978).
20. O. A. Wasson et. al., Measurement of the ^{235}U neutron-induced fission cross-section at 14.1 MeV, Nuc. Sci. and Eng. 80, 282 (1982).
21. M. C. Davis et. al., Absolute measurements of ^{235}U and ^{239}Pu fission cross-sections with photo neutron sources, Ann. of Nuc. Energy, 5, 569 (1978).
22. P. H. White, Measurements of the ^{235}U neutron fission cross-section in the energy range 0.04 - 14 MeV, Journ. of Nuc. Energy A/B 19, 325 (1965).
23. M. Cance' and G. Grenier, Absolute neutron fission cross-sections of ^{235}U , and ^{238}U and ^{239}Pu at 13.9 and 14.6 MeV, Nuc. Sci. and Eng. 68, 197 (1978).
24. M. Cance' and G. Grenier, CEA-N-2194 (1981).
25. I. M. Kuks, KieV 4, 18 (1973).
26. V. M. Adamov et. al., Absolute measurements of induced fission cross-sections of heavy nuclides for both ^{252}Cf fission spectrum neutrons and 14.7 - MeV neutrons, NBS Sp. Pub. 594, 995 (1980).
27. R. Arlt et. al., Kernenergie, 25, 199 (1982), ZFK-459, 35 (1981), Kernenergie, 24, 48 (1981).
28. J. Grundl et. al., Private communications (1982).

29. F. G. Perey, Covariance matrices of experimental Data, Proc. of an international conf. on neutron physics and nuclear data for reactors, Harwell (1978) p. 104.
30. W. Mannhart, A small guide to generating covariances of experimental data, PTB-FMRB-84 (1981).
31. C. D. Bowman et. al., Structure limitations on accuracy of U-235 fission cross-section measurements, 270, ANL-76-90 (1976).

TABLE I
 ^{235}U (n,f) Data Sets Used in the Fit

No	Author	Ref.	Energy Range (keV)	Comments
1	Carlson and Patrick	11	1.171+3 - 6.203+3	Preliminary
2	Wasson et. al.	12	9.9+1 - 7.5+2	
3	Czirr and Sidhu	13	7.54+2 - 2.01+4	
4	Poenitz	14	3.99+2 - 2.803+3	BND Shape data normalized at 800 keV
5	Poenitz	14	8.4+1 - 3.5+3	GND Shape data normalized at 3.5 MeV
6	Poenitz	15	2.15+2 - 3.05+2	TOF Shape Data
7	Szabo	16	7.25+1 - 1.01+3	White Counter
8	Gayther	17	7.1086+1 - 1.0039+3	
9	Barton	18	1.0+3 - 6.0+3	
10	Kari	19	1.0+3 - 2.075+4	
11	Wasson et. al.	12	2.44+2 - 1.196+3	
12	Wasson et. al.	20	1.41+4	TCAP
13	Davis et. al.	21	1.4+2 - 9.64+2	
14	Poenitz	14	3.5+3	Large BND
15	Poenitz	14	8.0+2	Small BND
16	Poenitz	14	4.48+2 - 6.44+2	Assoc. activity
17	Poenitz	14	4.98+2	Vanadium bath
18	Poenitz	15	1.93+2 - 2.93+2	

Table I (cont'd)

No	Author	Ref.	Energy Range (keV)	Comments
19	Poenitz	15	6.84+2 - 4.449+3	
20	Poenitz	15	4.396+3 - 8.275+3	
21	Szabo	16	7.8+1 - 1.99+2	Knoxville '71
22	Szabo	16	7.1+1 - 2.61+3	Kiev '73
23	Szabo	16	2.35+3 - 5.53+3	
24	White	22	1.27+2 - 1.41+4	
25	Cance' & Grenier	23	1.39+4 - 1.46+4	
26	Cance' & Grenier	24	2.5+3 - 4.45+3	
27	Kuks	25	2.5+3	
28	Adamov et. al.	26	1.48+4	Revised '77 datum
29	Adamov et. al.	26	1.4+4 - 1.47+4	TCAP
30	Arlt et. al.	27	2.56+3 - 1.47+4	TCAP
31	J. Grundl et. al.	28	Cf-252 Avg.	$\langle\sigma_f\rangle=1.216\pm0.019b$
32	Adamov et.a l.	26	Cf-252 Avg.	$\langle\sigma_f\rangle=1.241\pm0.019b$

FIG. 1. $^{235}\text{U} (n,f)$ Experimental Data with BFIT and ENDF/B-V Evaluations from 100-700 keV

FIG. 2. $^{235}\text{U}(n,f)$ Experimental Data with BFIT and ENDF/B-V Evaluations from 0.2-3.2 MeV

FIG. 3. $^{235}\text{U}(n,f)$ Experimental Data with BFIT and ENDF/B-V Evaluations from 0.6-6.6 MeV

FIG. 4. $^{235}\text{U}(n,f)$ Experimental Data with BFIT and ENDF/B-V Evaluations from 6-20 MeV