NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

2
DOE/PC/90310--T5

DE92 008698

QUARTERLY PROGRESS REPORT #5

Received 6/11
MAR 09 1992

TITLE: Combustion of Dense Streams of Coal Particles

GRANT NO: De-FG-22-90PC90310

REPORT PERIOD: Aug.29, 1991 to Nov. 28, 1991

PRINCIPAL INVESTIGATOR: Kalyan Annamalai
Mechanical Engineering
Texas A&M University
College Station, TX 77843-3123
409-845-2562

GRADUATE STUDENTS: W. Ryan
K. Esam
Du Xiang-Yang
C. Gopalakrishman

SUBMITTED TO: Pittsburgh Energy Tech. Center
US Department of Energy
P.O. Box 10940
Pittsburgh, PA 15236

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Objectives for August 29, 1991 to November 28, 1991

1. Conduct preliminary plumbing experiments on the flat flame burner with and without coal feed.
2. Set-up water cooled, and iso-kinetic sampling system.

Activities During August 29, 1991 to November 28, 1991

1. Video imaging system which includes camera, frame grabber software, etc. has been ordered while the computer for handling the image data is being ordered. Equipments are expected to be delivered by January 1992.

Flat flame burner setup is not yet complete. With Part II of Review under completion (by December 1991), the experiment is expected to progress rapidly during the next quarter.

The flat flame burner operation regimes have been identified. Appropriate rotameters have been selected. Appendix A-1 briefly describes the proposed set up and presents the regimes of operation of the burner. Appendix A-2 presents a brief schematic of the set up with video-imaging system. Appendix B describes the model of a cylindrical cloud and presents results on ignition and combustion of coal cloud. These model results will be verified with the experimental set up described in Appendix A.

2. The water-cooled iso-kinetic sampling has not yet been constructed.
3. A paper on "Group Effects on Fuel NO_x Emission" has been presented at ASME - Winter annual meeting. Two articles were submitted to journals for publications. They are under review. An article on interactive behavior will be presented at ASME-ETCE meeting (January 1992).

Objectives for November 29, 1992 to February 28, 1992

1. Submit the manuscript on Part II of review article.
2. Complete the experimental set up with the video-imaging system.
3. Obtain preliminary data on combustion of coal streams.

Flat Flame Burner Operation Regimes

The Flat Flame Burner is a pre-mixed burner used for studies of combustion, flame propagation and energy related research. It consists of a sintered porous bronze (or 316 S.S) water cooled burner surrounded by a sintered porous shroud ring for the introduction of a shielding gas (nitrogen), both enclosed in a precision machined housing assembly with connections for water cooling, research gas, and shroud gas. Fig. 1

For our project, the Flat Flame Burner is to be modified such that a coal injection tube will be added to the system. This tube will enable our system to behave as a fuel cell with coal being burned under stoichiometric, rich and lean conditions. Fig.2

The main objective of our work is to obtain a specific velocity of the resulting flame and to maintain this flame consistent throughout the experiment. To optimize our work, theoretical study has been conducted relating the flow rate of the premixed gas (gas+air), stoichiometric coal mass flow rate, interparticle distance of the coal particles, number of particles and the max. coal mass flow rate needed to maintain a specific velocity. Runs were made for velocities of 1.5, 2.0, 2.5, and 3.0 m/s.

RESULTS

Results were obtained using the following equations:

Fig. 2. Flat Flame Burner without Coal Injector (McKenna)

Schematic of Burning Cylindrical Coal Cloud

(Fig.2 Flat Flame Burner with Coal Injector)

Flat Flame Burner Equations

Used Coal $\text{CH}_{2.52}\text{O}_{0.97}\text{N}_{0.14}\text{S}_{0.003}$

$$d_{\text{inj}} = .0045 \text{ m}$$

$$d_p = 64 \times 10^{-6} \text{ m}$$

$$d_f = .66 \text{ m}$$

$$\rho_{\text{part}} = 1300 \text{ kg/m}^3$$

$$Y_{\text{O}_2} = .1$$

$$\text{Coef. O}_2 = 2.44$$

$$\rho_{\text{air}} = 1.0 \text{ kg/m}^3$$

$$(1) \quad \dot{Q} = V_{\text{inj}} * A_{\text{flow}}$$

$$\dot{Q} = V_{\text{inj}} * 3.142 * d_i^2 / 4$$

$$(2) \quad \dot{m}_{\text{flow}} = \dot{Q} * \rho_{\text{air}}$$

$$(3) \quad \dot{m}_{\text{O}_2} = \dot{m}_{\text{flow}} * Y_{\text{O}_2}$$

$$(4) \quad \text{Stoich. Coal Flow (} \dot{m}_{\text{coal}} \text{ Stoich)} = \dot{m}_{\text{O}_2} / \text{Coef. O}_2$$

$$(5) \quad \text{Max. Coal Flow (} \dot{m}_{\text{coal}} \text{ max)} = \phi * \dot{m}_{\text{coal}} \text{ Stoich}$$

$$(6) \quad \dot{m}_{\text{coal}} = (3.142/4) * (d_{\text{inj}})^2 * V_{\text{inj}} * n * 3.142 * d_p^3 / 6 * \rho_{\text{part}}$$

$$(7) \quad n = \dot{m}_{\text{coal}} * 3.52 \times 10^{14} / V_{\text{inj}} \text{ kg/s}$$

$$n = \dot{m}_{\text{coal}} * 5.83 \times 10^9 / V_{\text{inj}} \text{ g/min}$$

$$(8) \quad L = (6 * .74 / 3.142 * n)^{1/3}$$

$$L/a = (1.4/n)^{1/3} / 32 \times 10^{-6}$$

Table (1) summarizes results obtained at the four different velocities while varying the equivalence ratio (actual F/A over stoichiometric F/A) for each run from 2.0 to .03.

DISCUSSION

Figure (3) illustrates Max. Coal Mass Flow Rate Vs. Interparticle distance ($1/a$) at velocities of 1.5, 2.0, 2.5, and 3.0 m/s. The obtained relationship can be best described as inversely proportional with a polynomial behavior. This behavior is due to the fact that as coal mass flow rate increases with increasing coal injection, the particles get packed more closely and hence the interparticle distance gets smaller and smaller. Also, at stoichiometric conditions, max coal mass flow rate is 15.13 g/min. at a velocity of 1.5 m/sec. However, at 2.0, 2.5 and 3.0 m/s, max coal mass flow rate becomes 20.20, 25.22 and 30.28 g/min. respectively. This suggests a directly proportional relationship as expected. Figure (4) shows Max. Coal Mass Flow Rate Vs. Number of Particles per m^3 at velocities of 1.5, 2.0, 2.5, and 3.0 m/s. A linear relationship is observed here. At a specific velocity, the number of particles is increased with increasing the coal injection thus suggesting a directly proportional relationship. An interesting observation is the fact that at stoichiometric conditions, the number of particles is irrelevant of the injection velocity unlike max. coal mass flow rate which is dependent on the injection velocity.

Figures (5) and (6) shows the equivalence ratio ϕ Vs.

V inj (m/s)	Q flow (m/s)	m flow (g/min)	m o2 (g/min)	m coal sto (g/min)	m coal m (g/min)	EQV. Rati O	No. of Par (x10 ⁴)
1.5	0.000513	369.36	36.94	15.14	30.28	2	11.76
					22.7	1.5	8.82
					15.13	1	5.9
					7.57	0.5	2.95
					3.78	0.25	1.48
					1.9	0.15	0.74
					0.46	0.03	0.178
					40.37	2	11.76
2	0.00684	492.48	49.25	20.18	30.3	1.5	8.82
					20.2	1	5.9
					10.09	0.5	2.95
					5.04	0.25	1.48
					2.52	0.15	0.74
					0.6	0.03	0.178
					50.46	2	11.76
					37.82	1.5	8.82
2.5	0.00855	615.6	61.56	25.23	25.22	1	5.9
					12.61	0.5	2.95
					6.31	0.25	1.48
					3.16	0.15	0.74
					0.76	0.03	0.178
					60.55	2	11.76
					45.42	1.5	8.82
					30.28	1	5.9
3	0.01026	738.72	73.87	30.28	15.14	0.5	2.95
					7.57	0.25	1.48
					3.78	0.15	0.74
					0.91	0.03	0.178
					60.55	2	11.76
					45.42	1.5	8.82

(Interparticle Distance $1/a$, and the equivalence ratio Vs. Number of Particles per m^3 respectively. As expected, increasing O will decrease the interparticle spacing since the number of particles is increased thus packing the particles more closely. It is worth to note that this behavior is consistent for the four different velocities.

Coal Max. Mass Flow Rate Vs. Interparticle Distance

Figure (3)

Coal Max. Mass Flow Rate Vs. Number Of Particles

Figure (4)

Coal Max. Mass Flow Rate (g/min)

Equivalence Ratio Vs. Interparticle Distance

Figure (5)

Equivalence Ratio Vs. Number of Particles

Figure (6)

2. Experimental Description

This research project involves the determination of the combustion characteristics of a cylindrical stream of coal particles. Using an imaging system, we should be able to verify our theoretical model which suggests a double flame formation (inner and outer) at location XX as a result of coal combustion in a flat flame burner (shown in the attached schematic Fig. 7)

The Flat Flame Burner is a pre-mixed burner used for studies of combustion, flame propagation and energy related research. It consists of a sintered porous shroud ring for the introduction of a sheilding gas (nitrogen), both enclosed in a precision machined housing assembly with connections for water cooling, research gas, and shroud gas. For our project, the Flat Flame Burner has been modified to include a coal injection system.

Coal particles are to be fed with air or N₂ gas injected at 300 K into hot gas at 1500 K. Coal release gases which ignite away from cloud boundary as shown in the sketch. Once ignited, flame propagates towards the cloud boundary and then splits up into two flames I and O. Coal particles will be sucked at the top through a water cooled probe at a certain velocity to maintain the cylindrical shape of the cloud.

The instantaneous shape of the flame between WW and YY will be recorded using a video camera. We will use this recording later for image processing. Thus, the camera should be able to focus on the central plane of cylindrical cloud with a depth of focus less than 1/32" for the system shown here (Fig. 8)

FIG. 8

IMAGING SYSTEM

Group Ignition and Combustion of a Cylindrical Cloud of Coal Particles

1. Introduction

Previously a model has been developed to simulate the group ignition and combustion of a spherical cloud of pulverized coal and char particles. Results have been obtained for the ignition and combustion of such a cloud. The advantages of spherical cloud model are that the burning rate of dense cloudy of char particles tends to the combustion rate of a large isolated particle of same size as cloud but with mass density equal to cloud mass density; Further steady state solution can be readily obtained. While the spherical group combustion model is convenient to obtain simplified results under steady state conditions, it is very difficult to simulate experimentally. On the other hand, experiments could be performed with a cylindrical stream of coal particles. Thus the cylindrical group combustion model is more useful in interpreting the experimental data obtained with a monosized stream of particles. Hence, present work deals with the group combustion of a cylindrical cloud of coal particles. Conservation equations are presented for mass, species, and energy. Numerical solutions are then presented for the ignition time, group burning rate and flame structure. The model assumes that the particles are point masses.

2. Conservation Equations

2.1. The Model

Consider a cloudy of uniformly distributed coal particles of radius ' a ' within a cylinder of radius ' R_c ' (Fig. 1). If this cloud is placed in a hot furnace, a thermal wave propagates from the ambience into cloud. The bulk gas temperature increases which in turn supplies heat to the particles. When the temperature of the particles reaches the

pyrolysis level. Thermal decomposition of coal occurs releasing volatiles. The volatiles diffuse into the bulk gas zone establishing a mixture of volatiles and oxygen in the bulk gas. If the cloud is dense, then homogeneous ignition may occur provided that the gas phase temperature is high enough. On the other hand, if the cloud is dilute, a flammable mixture in the gas phase may not be formed and the carbon in the coal reacts with the oxygen adjacent to the particles resulting in heterogeneous ignition. Thus, the ignition mode may be either homogeneous or heterogeneous depending upon the denseness of the cloud. It is assumed that all gas phase chemical reaction for volatiles and CO occur by a single step globe reaction. The reaction included in the present analysis are as follows:

a.) Homogeneous Reaction

b.) Pyrolysis via Competing Reaction

where $\alpha_{II} \approx 2\alpha_I$

c.) Homogeneous (Gas Phase) Reactions

2.2. Dimensional Form

A. Mass

Assuming cylindrical symmetry, the equation of continuity in cylindrical coordinates is given as (Fig. 1)

$$\frac{\partial \rho}{\partial t} + \frac{1}{r} \frac{\partial}{\partial r} (\rho r u_r) = \dot{w}_m'' \quad (1)$$

where

ρ is the gas phase density,

t is time,

r is the radial distance from the cloud center,

u_r is the gas velocity in the radial direction,

$\dot{w}_m''$ is the gas phase volumetric mass source term, $= \dot{m}n$

n is number of particles per unit volume,

$$\dot{m} = \dot{m}_v + \dot{m}_c$$

$\dot{m}_v$ is volume liberation rate evaluated with competing pyrolysis model, and

$\dot{m}_c$ is carbon mass loss rate evaluated with heterogeneous reaction model

According to the competing reaction model

$$\dot{m}_v = \dot{m}_{v,I} + \dot{m}_{v,II}$$

where

$$\dot{m}_{v,i} = \alpha_i k_{v,i} m_{a,i}, \quad i = I, II$$

$$k_{v,i} = B_{v,i} \exp(-E_{v,i}/R_u/T_p)$$

As volatiles are released, a portion of the coal is decomposed. The rate of change of the uncomposed coal mass due to both reactions in the competing reaction model is given as,

$$dm_a/dt = (\dot{m}_{v,I}/\alpha_I) - (\dot{m}_{v,II}/\alpha_{II})$$

where, at $t=0$, m_a is the initial particle mass ($m_{p,0}$).

The mass loss rate $\dot{m}_c$ due to heterogeneous char reactions is evaluated as follows. For the first order heterogeneous reaction ($C + 1/2O_2 \rightarrow CO$) at constant density,

$$\dot{m}_c = \rho_w k_c Y_{O_2,w} V \pi d_p^2$$

where

$$k_c = B_c \exp(-E_c/R_u T)$$

B. Species

Assuming cylindrical symmetry, the species conservation in cylindrical coordinates is written as

$$\rho \left(\frac{\partial Y_k}{\partial t} \right) + \rho u_r \frac{\partial Y_k}{\partial r} - \rho D \frac{1}{r} \frac{\partial}{\partial r} \left[r \left(\frac{\partial Y_k}{\partial r} \right) \right] = \dot{w}_k'' - \dot{w}_m'' Y_k \quad (2)$$

where

$$\dot{w}_k'' = \dot{w}_{k,pp}'' + \dot{w}_{k,ch}''$$

$\dot{w}_{k,pp}''$ is the rate at which species k added to the gas phase from the particles and chemical reactions in the gas phase,

$\dot{w}_{k,ch}''$ is species addition due to chemical reaction, and

Y_k is the mass fraction of species K.

C. Energy

Assuming cylindrical symmetry, the energy conservation in cylindrical coordinates is given as

$$\rho \frac{\partial h_T}{\partial t} + \rho u_r \frac{\partial h_T}{\partial r} - \rho D \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial h_T}{\partial r} \right) = \dot{w}_h'' - \dot{w}_m'' h_T \quad (3)$$

where

h_T is the thermal enthalpy

w_T^m is the volumetric production of enthalpy resulting from convective heat transfer between the gas phase and the particles and chemical reactions in the gas phase.

2.3. Non-Dimensional Form

Let us introduce the following reference quantities:

$$\rho_{ref} = \frac{P}{RT_{ref}}, \quad (4a)$$

where $R = R_u/W$ and W is the molecular weight.

$$t_{ref} = \left(\frac{\rho_{ref} R_{c,o}^2}{\rho D} \right), \quad (4b)$$

$$m_{ref,g}^{\#} = \frac{\rho D}{R_{c,o}^2} = \left(\frac{\rho_{ref}}{t_{ref}} \right), \quad (4c)$$

where ρ is the density of the gas (determining ρ at $T=T_{ref}$ and D at $T=T_{ref}$)

$$\dot{m}_{ref,g} = 4\pi \rho D R_{c,o}, \quad (4d)$$

$$h_{ref} = C_p T_{ref}, \quad (4e)$$

and introducing the following non-dimensional variables

$$\dot{m}_{ref,p} = \frac{\dot{m}_{p,o}}{t_{ref}} , \quad (4f)$$

$$\xi = R_{c,o} / r , \quad (4g)$$

$$\rho^* = \rho / \rho_{ref} , \quad (4h)$$

$$\tau = t / t_{ref} = t (\rho D / \rho_{ref} R_{c,o}^2) , \quad (4i)$$

$$w_m = \dot{w}_m^{\#} / \dot{m}_{ref,g}^{\#} = w_m^{\#} (R_{c,o}^2 / \rho D) , \quad (4j)$$

$$\alpha' = \dot{m}' / \dot{m}_{ref,g} = \dot{m}' / (4\pi \rho D R_{c,o}) , \quad (4k)$$

$$w_k = \dot{w}_k^{\#} / \dot{m}_{ref,g}^{\#} = \dot{w}_k^{\#} (R_{c,o}^2 / \rho D) \quad (4l)$$

$$w_h = \dot{w}_h^{\#} / \dot{m}_{ref,g}^{\#} h_{ref} , \quad (4m)$$

where D is the gas phase diffusion coefficient, $R_{c,o}$ is the initial cloud radius, and $\dot{m}'$ is mass flow rate per unit length of cylindrical cloud.

In the spherical coordinate system we define $\alpha = \dot{m} / \dot{m}_{ref,g}$ ($\dot{m} = 4\pi r^2 \rho u_r$) so that α is the nondimensional mass flow rate at "r". In order to reduce the complexities involved, the definitions of the non-dimensional variables remain unchanged in the cylindrical coordinate system. However, since $\dot{m}' = 2\pi r \rho u_r$, in the cylindrical coordinate system, α' is no longer non-dimensional and can be thought of as the non-dimensional mass flow rate per unit length of the cylinder. We put the prime on the α' term to distinguish it from that in spherical coordinate system.

The equation of continuity in cylindrical coordinate becomes

$$\frac{\partial \rho^*}{\partial \tau} - \xi^3 (2 R_{c,o}) \left(\frac{\partial \alpha'}{\partial \xi} \right) = w_m \quad (5a)$$

letting

$$\alpha = 2\alpha' R_{c,o} = \dot{m}' / (2\pi\rho D) \quad (5b)$$

Equation (5a) becomes

$$\frac{\partial \rho^*}{\partial \tau} - \xi^3 \left(\frac{\partial \alpha}{\partial \xi} \right) = w_m \quad (5c)$$

Thus we use similar form of equation as in spherical coordinate system except that α' or $\dot{m}'$ must be estimated from eq. (5b) for cylindrical clouds.

the eq. (2) becomes

$$\rho^* \frac{\partial Y_k}{\partial \tau} + -\alpha \xi^3 \frac{\partial Y_k}{\partial \xi} - \xi^3 \frac{\partial Y_k}{\partial \xi} - \xi^4 \left(\frac{\partial^2 Y_k}{\partial \xi^2} \right) = W_k - w_m Y_k \quad (6)$$

The derivation of the non-dimensional energy equation is similar to the species conservation equation. The normalized equation in cylindrical coordinates becomes

$$\rho^* \frac{\partial h^*}{\partial \tau} + -\alpha \xi^3 \frac{\partial h^*}{\partial \xi} - \xi^3 \left(\frac{\partial h^*}{\partial \xi} \right) - \xi^4 \left(\frac{\partial^2 h^*}{\partial \xi^2} \right) = w_b - w_m h^* \quad (7)$$

where

h^* is the normalized thermal enthalpy ($h^* = h/h_m$),

w_m is the volumetric production of enthalpy resulting from convective heat transfer between the gas phase and the particles and chemical reactions in the gas phase.

2.4 Volumetric Integration

Let Z'' be any dependent variable z given on a per volume basis which is a function of radial position. Let Z' be the total amount of z in the cloud per unit length. Then, in cylindrical coordinates,

$$Z' = \int_0^{R_c} Z'' 2\pi r dr \quad (8a)$$

Introducing the non-dimensional variables,

$$Z' = Z_1 = 4\pi R_{c,o}^3 \int_{\xi_c}^{\infty} \left(\frac{Z''}{\xi^3} \right) \left(\frac{1}{2R_{c,o}} \right) d\xi \quad (8b)$$

Equations (8) are used to determine the mass burning rate of the cloud with $z'' = w''$.

2.5 Numerical Procedure

An explicit upwind scheme is used to solve the parabolic equations (5c), (6), and (7). The source terms $\dot{w}_T''$, $\dot{w}_m''$, and $\dot{w}_h''$ with $T_p = (T_p)_0$ was calculated with the given conditions at $t = 0$ for $(T)_0$, $(Y)_0$, $(m)_0$, $(T_p)_0$, $(\rho_p)_0$, and $(d_p)_0$. The properties at $t = \Delta t, 2\Delta t, 3\Delta t, \dots$ ect. were determined repeatedly by using the source terms and the explicit method. Since the distance variable ξ is the reciprocal radius, the center of the cloud could not be entered for calculation since $\xi \rightarrow \infty$. The maximum value of x_i used was 3. Thus the mass of the cloud within $r = R_c/3$ was neglected. However, the mass of the cloud within $r = R_c$ and $r = R_c/3$ only comprise 3.7% of the initial cloud mass.

The runs were made on VAX computer and the results are shown in figures. CPU time for ignition is 5 to 10 minutes, while CPU time for combustion is above 20 minutes.

3. Results

3.1 Ignition

The cylindrical cloud model without dissociation was used to obtain the ignition results. The results are obtained for ignition time vs. coal number density.

The coal number density was typical of number densities used in the experiments.

The following parametric cases were studied: (1) $T_{\infty} = 1000$ K, (2) $T_{\infty} = 1100$ K, (3) $T_{\infty} = 1250$ K, (4) $T_{\infty} = 1300$ K.

From fig. 2 to fig. 4, we can see that heterogeneous ignition occurs for low particle number density and ignition time increases weakly with particle number density in heterogeneous ignition regime due to the increased heat sink. As the particle number density is further increased, homogeneous ignition occurs and the ignition time decreases until a minimum is observed and then increases again as the particle number density is further increased. It is seen that the ignition time at 1100 K qualitatively agrees with experiment findings but differ quantitatively. Since there may be slight preheating in the injector, an additional case was run with fuel preheat. Fig. 3 shows the results. The time values are still larger. Three possible reasons are as follows:

a) Gas temperatures in the experiment should be measured closer to the center since the wall temperature may be cooler. Wall temperature was used in the theoretical prediction.

b) The model assumes pure diffusional mixing (zero relative velocity between fuel stream and carrier air) while the fuel relative velocity in the experiment may be non-zero. Thus there may be entrainment which accelerate the mixing process. The diffusivity could be increased by a factor 2 to 5 in steps of 1.

c) The cloud expansion was neglected in the model. This must be included in the future model.

3.2. Combustion

3.2.1. Negligible Dissociation

The results of cylindrical cloud combustion of coal particals also show the simultaneous existence of two flames: inner flame propagating into premixed volatiles and oxygen and outer diffusion flame, which have been found in spherical cloud combustion.

Let us consider an initially cold cylindricl cloud of monosized coal particles ($n = 7.3 \times 10^9$ particles/m³, $d_p = 64 \mu\text{m}$, $R_c = 0.225$ cm, $T_{c,0} = T_{p,0} = 300$ K), is introduced into a hot quienscent oxidizing atomosphere ($T_\infty = 1500$ K). The ignition time for this situation is 67.3 ms. Fig. 5 to fig. 10 shows the results for the flame profiles at different time intervals after ignition began. Once the cloud has been introduced, the surrounding ambience heats the gas phase at the surface of the cloud and an enthalpy wave propagate into the cloud. The bulk gas phase in the cloud heats the coal particles (see fig. 5, just prior to ignition). Upon reaching the pyrolysis temperature, the particles release volatiles which diffuse out of the cloud into the surrounding high temperature environment. Once the volatile concentration is high enough, ignition occurs at some location outside the cloud (see fig. 6). Since the combustion rate is faster than volatile production rate, the flame now propagates toward the cloud (see fig. 7). Once the flame moves the cloud surface, the particles heat up rapidly. Once all the oxygen is consumed at the cloud surface, two flames are formed; One which propagates into the cloud and the other which propagates away from the cloud (see fig. 8 to fig. 9). The flame which moves into the cloud consumes all the available oxygen in cloud. Then only a pure diffusion flame is formed outside the cloud (see fig. 10).

In order to obtain the effect of the cloud denseness on the combustion profile, Results are obtained for coal/air ratios: 0.5, 1 and 2 (accordingly, $n = 3.26 \times 10^9$, 6.52×10^9 , and 1.3×10^{10} particles/m³).

Fig. 11 shows the results for flame profile when coal/air ratio is 0.5. The ignition time found to be 55.29 ms. However, the double flame did not appear for this dilute cloud, since the coal mass density is low and the cloud does not release enough volatile for the flame to be supported inside the cloud.

Fig. 12 shows the results when coal/air ratio is 1 ($n = 6.52 \times 10^9$ particles/m³) at $t = 69$ ms. The ignition time for the present case is 65.05 ms. The double flame is clearly seen. The peak temperature of the outside flame is 3014 K while inner flame is 2385 K.

Fig. 13 shows the results when coal/air ratio is 2 ($n = 1.3 \times 10^{10}$ particles/m³) at $t = 89$ ms. The ignition time for this case is 83.37 ms. The peak temperature of the outer flame is 2683 K and inner flame is 1994 K. We can see that as the number of particles increase, more volatile are released and these volatiles can diffuse out into the hotter zone outside the cloud. Thus, it is more likely that a flammable mixture can be formed in the gas phase outside the cloud and ignite at decreased gas temperatures.

3.2.2. Dissociation

The previous section assumed that combustion of carbon monoxide and volatiles is complete. This assumption may be justified in the study of ignition, where temperatures are of order of 1200 K. However, such an assumption has lead to unrealistically high flame temperatures on the ensuing combustion. For this reason, backward reactions for CO_2 and H_2O species have been added to the existing group cylindrical combustion model and a comparison of the results for flame profiles is given with and without the inclusion of the backward reactions.

The base case are as follows: $n = 7.3\text{E}+9$ particles/ m^3 , $d_p = 64$ μm , $R_c = 0.225$ cm, and $T_{g,0} = T_{p,0} = 300$ K. Results are presented for both the cases of complete combustion and dissociation.

Fig. 14 shows the results for the flame profile at $t = 71$ ms, when the double flame has occurred, but the backward reactions are not included. The peak temperature of the outer flame is about 2843 K and the inner flame is about 2537 K. Fig. 15 shows the results when the backward reaction for CO_2 and H_2O are included. The peak temperature of the outer flame decreases to 2646 K and the peak temperature of inner flame decreases to 2465 K. It is seen that inclusion of backward reaction lowers the outer flame by about 300 K. However, the inner flame has been lowed by only about 70 K. Since inner flame temperature is low, there is very small effect of dissociation reaction on the inner flame temperature. This effect can be seen more clearly in Fig. 16.

Fig. 17 shows the backward effect on concentration of CO_2 . It is seen that the peak values of CO_2 have been suppressed due to the dissociation to CO . However, the inclusion of backward reaction lowers the CO_2 concentration more greatly in the outer flame region than that in the inner flame region. Since inner flame temperature is low, the two peaks on CO_2 are more apparant with dissociation reaction than that without dissociation.

For the cases studied, the dissociation of H_2O has smaller effect on the flame temperature than that of CO_2 , hence no discussion is given an H_2O dissociation.

4. Summary

- (1) A group combustion model is presented for the ignition and combustion of a cylindrical cloud of coal

particles.

- (2) Results reveal heterogeneous ignition for dilute clouds and homogeneous ignition for dense clouds.
- (3) Heterogeneous ignition time increase weakly with particle number density. As the particle number density is further increased, homogeneous ignition occurs and ignition time decreases until a minimum is observed and then increase again as the particle number density is further increased.
- (4) Results show the simultaneous existence of two flames: inner flame propagating into premixed volatiles and oxygen and outer diffusion flame.
- (5) Inclusion of dissociation reaction decreases flame temperature and concentration of CO_2 . However, since inner flame temperature is low, there is very small effect of dissociation reaction on the inner flame temperature.

Appendix A.

Given: $V_g = 5.77 \text{ m/s}$, $D_c = 0.45 \text{ cm}$, $\rho_s = 1300 \text{ kg/m}^3$, $d_p = 64 \text{ }\mu\text{m}$, $\dot{m} = 1.0 - 10.0 \text{ g/min}$.

Estimate the coal number density, n , in the feed.

1. gas volume flow rate:

$$\begin{aligned}
 \text{gas flow area} \quad A_c &= \pi d_c^2 / 4 \\
 &= 3.14 \times 0.0045^2 / 4.0 \\
 &= 0.1594 \times 10^{-4} \text{ m}^2 \\
 \text{gas volume flow rate} \quad Q_g &= V_g A_c \\
 &= 5.77 \times 0.15904 \times 10^{-4} \\
 &= 9.1767 \times 10^{-5} \text{ m}^3/\text{s}
 \end{aligned}$$

2. coal particle number density:

$$\begin{aligned}
 \text{mass of each coal particle} \quad m_p &= (\pi d_p^3 / 6) \rho \\
 &= (3.14 \times (64 \times 10^{-6})^3 / 6.0) \times 1300 \\
 &= 1.7844 \times 10^{-10} \text{ kg} \\
 \text{coal mass flow rate} \quad \dot{m}_p &= 1.0 \text{ g/min.} \\
 &= 1.0 \times 10^{-3} / 60 \\
 &= 1.66667 \times 10^{-5} \text{ kg/s} \\
 \text{particle number flow rate} \quad \dot{N} &= \dot{m}_p / m_p \\
 &= 1.6667 \times 10^5 \text{ kg/s}
 \end{aligned}$$

$$= 93404 \text{ particles/s}$$

The coal particle number density is given as

$$\begin{aligned} n &= \dot{N}/Q_s \\ &= 93404/9.1767 \times 10^{-5} \\ &= 1.0178 \times 10^9 \text{ particles/m}^3 \end{aligned}$$

The results are given below

$$v_s = 5.77 \text{ m/s}, d_c = 0.45 \text{ cm}, \rho_s = 1300 \text{ kg/m}^3, d_p = 64 \text{ }\mu\text{m}$$

m_p	$n \text{ (particles/m}^3\text{)}$
0.01	1.0178×10^7
0.02	2.0356×10^7
0.03	3.0534×10^7
0.04	4.0712×10^7
0.05	5.0890×10^7
0.06	6.1068×10^7
0.07	7.1246×10^7
0.08	8.1424×10^7
0.09	9.1602×10^7
0.10	1.0178×10^8
0.20	2.0356×10^8
0.30	3.0534×10^8
0.40	4.0712×10^8
0.50	5.0890×10^8
0.60	6.1068×10^8
0.70	7.1246×10^8
0.80	8.1424×10^8
0.90	9.1602×10^8
1.00	1.1078×10^9
2.00	2.0356×10^9
3.00	3.0543×10^9
4.00	4.0712×10^9
5.00	5.0890×10^9
6.00	6.1068×10^9
7.00	7.1246×10^9
8.00	8.1424×10^9
9.00	9.1602×10^9
10.00	1.0178×10^{10}

Ignition Time vs. Coal Number Density

cylindrical cloud, $R_c=225$ cm, $D_p=64$ μ m, $T_{go}=300$ K, $T_{po}=300$ K

Coal Number Density (10^{17} particles/m³)
Fig. 2

Effect of Gas Preheat

cylindrical cloud, $R_c=225$ cm, $T_{oo}=1100$, $D_p=64$ μ m

Coal Number Density (10^{17} particles/m³)
Fig. 3

Effect of Cloud Radius

cylindrical cloud, $T_{00}=1100$, $D_p=64$ μm , $T_{g0}=300$ K, $T_{p0}=300$ K

Coal Number Density (10^{17} particles/m³)

Fig. 4

Flame Profile at 67 ms

Cylindrical Cloud, $R_c=0.223$ cm, $T_{co}=1500$ K, $dp=64$ μ m, $n=7.3E+9$ particles/ m^3 , $T_{go}=300$ K, $T_{pe}=300$ K

Fig. 5

Flame Profile at 70 ms

Cylindrical Cloud, $R_c=0.225$ cm, $T_{co}=1500$ K, $d_p=64$ nm, $n=7.3E+9$ particles/ m^3 , $T_{go}=300$ K, $T_{po}=300$ K

Flame Profile at 71 ms

Cylindrical Cloud, $R_c=0.225$ cm, $T_{co}=1500$ K, $d_p=64$ nm, $n=7.3E+9$ particles/ m^3 , $T_{ge}=300$ K, $T_{pe}=300$ K

Fig. 8

Flame Profile at 71.5 ms

Cylindrical Cloud, $R_c=0.225$ cm, $T_{oo}=1500$ K, $d_p=64$ nm, $n=7.3E+9$ particles/m³, $T_{go}=300$ K, $T_{pe}=300$ K

Fig. 9

Flame Profile at 73 ms

Cylindrical Cloud, $R_c=0.225$ cm, $T_{oo}=1500$ K, $d_p=64$ μ m, $a=7.3E+9$ particles/ m^3 , $T_{go}=300$ K, $T_{po}=300$ K

Fig. 10

Effect of Cloud Denseness

cylindrical cloud, $R_c=0.225$ cm, $T_{oo}=1300$ K, $d_p=64$ nm, coal/air=0.5, $T_{go}=300$ K, $T_{pe}=300$ K

Fig. 11

Effect of Cloud Denseness

cylindrical cloud, $R_c=0.223$ cm, $T_{co}=1500$ K, $d_p=64$ μ m, $T_{gs}=300$ K, $T_{po}=300$ K

FIG. 12

Effect of Cloud Denseness

Cylindrical Cloud, $R_c=0.225$ cm, $T_{co}=1500$ K, $d_p=64$ μ m, coal/air=2, $T_{ge}=300$ K, $T_{po}=300$ K

Fig. 13

NO DISSOCIATION

Cylindrical Cloud, $R_c=0.225$ cm, $T_{co}=1500$ K, $d_p=64$ nm, $n=7.3E+9$ particles/m³, $T_{go}=300$ K, $T_{po}=300$ K

Fig. 14

WITH CO₂ DISSOCIATION

Cylindrical Cloud, $R_c=0.225$ cm, $T_{co}=1500$ K, $dp=64$ μ m, $n=7.3E+9$ particles/ m^3 , $T_{ge}=300$ K, $T_{pe}=300$ K

FIG. 15

TEMPERATURE PROFILE

Cylindrical cloud, $R_c=0.223$ cm, $T_{co}=1500$ K, $d_p=66$ nm, $n=7.3E+9$ particles/m³, $T_{go}=300$ K, $T_{po}=300$ K

Fig. 16

CO₂ PROFILES

Cylindrical Cloud, $R_c = 0.225$ cm, $T_{oo} = 1500$ K, $d_p = 64$ μ m, $n = 7.3E+9$ particles/ m^3 , $T_{go} = 300$ K, $T_{oo} = 300$ K

Fig. 17

END

**DATE
FILMED**

4/7/92

I