LEGIBILITY NOTICE

A major purpose of the Technical Information Center is to provide the broadest dissemination possible of information contained in DOE's Research and Development Reports to business, industry, the academic community, and federal, state and local governments.

Although a small portion of this report is not reproducible, it is being made available to expedite the availability of information on the research discussed herein.

✓
ornl

ORNL/EASA-87/82
(AL135)

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

APR 06 1989

RESULTS OF THE RADIOLOGICAL SURVEY AT
3 CROMMOND STREET, COLONIE, NEW YORK (AL135)

MASTER

OPERATED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/RASA--87/82

DE89 009207

Health and Safety Research Division

Nuclear and Chemical Waste Programs
(Activity No. AH 10 05 00 0; ONLWC01)

RESULTS OF THE RADIOLOGICAL SURVEY AT
3 CRAMMOND STREET, COLONIE, NEW YORK (AL135)

J. L. Marley

Date of Issue - December 1987

Investigation Team

B. A. Berven - RASA Program Manager
W. D. Cottrell - FUSRAP Project Director
J. L. Marley - Field Survey Supervisor

Survey Team Members

D. L. Gillespie, T. L. Owen, D. J. Thorne (ORAU)
D. J. Smith, C. N. Smith, (D. Stone Associates)

Work performed as part of the
RADIOLOGICAL SURVEY ACTIVITIES PROGRAM

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
operated by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under Contract No. DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
LIST OF TABLES	vii
ACKNOWLEDGMENTS	ix
INTRODUCTION	1
SURVEY METHODS	1
SURVEY RESULTS	2
Gamma Measurements	2
Soil Sampling	3
Surface Measurements	3
SIGNIFICANCE OF FINDINGS	3
REFERENCES	5

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Diagram showing grid point and grid block locations outdoors on the property at 3 Crammond Street, Colonie, New York (AL135)	7
2	Front view of the property at 3 Crammond Street, Colonie, New York (AL135) looking east	8
3	Surface gamma exposure rates measured at grid points outdoors on the property at 3 Crammond Street, Colonie, New York (AL135)	9
4	Locations of soil samples on the property at 3 Crammond Street, Colonie, New York (AL135)	10

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Background radiation levels in the Albany area	11
2	Results of the gamma exposure rate measurements outdoors on the property at 3 Crammond Street, Colonie, New York (AL135)	12
3	Results of soil sample analysis on the property at 3 Crammond Street, Colonie, New York (AL135)	14
4	Results of surface analysis of structures at 3 Crammond Street, Colonie, New York (AL135)	15
5	Summary of outdoor measurements and sample results on the property at 3 Crammond Street, Colonie, New York (AL135)	16

ACKNOWLEDGMENTS

Research for this project was sponsored by the Division of Facility and Site Decommissioning Projects, U.S. Department of Energy, under Contract No. DE-AC05-84OR21400 with Martin Marietta Energy Systems, Inc. The author wishes to acknowledge the support of J. E. Baublitz, Deputy Director, Office of Remedial Action and Waste Technology, J. J. Fiore, Director, Division of Facility and Site Decommissioning Projects; Andrew Wallo III, Division of Facility and Site Decommissioning projects, Office of Nuclear Energy; and members of staffs. In addition, the author expresses appreciation to B. S. Ellis, D. A. Roberts, and T. R. Stewart (ORNL) for contributions in report preparation and review; and to B. C. Littleton, and L. J. Jeffers (Information Resources Organization) for manuscript preparation.

**RESULTS OF THE RADIOLOGICAL SURVEY AT
3 CRAMMOND STREET, COLONIE, NEW YORK (AL135)**

INTRODUCTION

Work with depleted uranium began in Colonie, New York, during 1958 at a plant owned by the National Lead Company.¹ Beginning in 1961, the Atomic Energy Commission (AEC), and other federal agencies engaged the National Lead Company (presently NL Industries, Inc.) in numerous contracts and subcontracts for the fabrication of enriched (3.6%) uranium fuel elements for the Hallam Reactor (Chicago Operations Office) and for the chemical processing of unirradiated, enriched uranium scrap (New York Operations Office).^{2,3} Since the termination of the AEC contracts, the work at the plant was devoted to the fabrication of shielding components, ballast weights, and projectiles from depleted uranium.¹ This plant has operated at a reduced level of activity after February 1980, and ownership of the plant and property was transferred to the Department of Energy (DOE) in February 1984.

A number of properties in the Albany/Colonie area have been identified as being potentially contaminated with uranium originating from the former National Lead Company's uranium forming plant in Colonie, New York.⁴ Radiological surveys were performed at 9 properties by members of the Radiological Survey Activities (RSA) group at Oak Ridge National Laboratory (ORNL) during the period November 4–November 15, 1985. The property at 3 Crammond Street in Colonie, New York (AL135) was the subject of a radiological investigation initiated November 14, 1985.

The property was a vacant, asphalt-paved lot. A diagram of the property showing the approximate boundaries and the 5-m grid network established for measurements is shown in Fig. 1. The rectangular lot included in the radiological survey was ~18.5 m wide by 33.7 m deep. A front view of the property is shown in Fig. 2.

SURVEY METHODS

The radiological survey methods employed in the survey of this property are described in Ref. 5.

The radiological survey of this property included: (1) gamma exposure rates at 1 m above the ground surface and at the ground surface at outdoor grid locations; (2) a gamma scan of the entire ground surface outdoors; (3) samples of outdoor soil; and (4) direct alpha and beta-gamma activity from surfaces of structures outdoors on the property, including asphalt paving. A comprehensive description of the survey methods and instrumentation has been presented in another report.⁶

SURVEY RESULTS

Typical background radiation levels for the Albany area are presented in Table 1. The data is provided for purposes of comparison with the survey results presented in this section.

All measurements presented in this report are gross readings; background radiation levels have not been subtracted. Similarly, background concentrations have not been subtracted from radionuclide concentrations in soil samples.

Gamma Measurements

Results of grid point/grid block measurements are presented in Table 2. Surface gamma exposure rates measured at grid points over the entire outdoor property are shown on Fig. 3. Gamma exposure rates at 1 m above the ground surface ranged from 7 to 11 $\mu\text{R}/\text{h}$ (microroentgens* per hour) and averaged 9 $\mu\text{R}/\text{h}$. Gamma exposure rates at the ground surface at grid points ranged from 7 to 11 $\mu\text{R}/\text{h}$ and averaged 9 $\mu\text{R}/\text{h}$. The maximum gamma exposure rate measured on the property was 13 $\mu\text{R}/\text{h}$.

Soil Sampling

Six soil samples were taken at this property from three locations. The samples, taken without strict regard to gamma exposure rates at the sampling points, are denoted as systematic samples (AL135S). The locations of the samples are shown in Fig. 4, and the results of analysis are presented in Table 3.

*The roentgen (R) is a unit which was defined for radiation protection purposes for people exposed to penetrating x-rays or gamma radiation. A microroentgen (μR) is one millionth of a roentgen. A milliroentgen (mR) is one thousandth of a roentgen or one thousand microroentgens.

Samples were taken at 0 to 5 cm and at 5 to 15 cm depths from each location. Concentrations of ^{238}U in the soil samples ranged from 4.4 to 11 pCi/g (picocuries* per gram) and averaged 7.9 pCi/g. The concentrations of ^{238}U in the 0 to 5 cm samples averaged 6.9 pCi/g and averaged 8.8 pCi/g in the 5 to 15 cm depth samples. The concentrations in the soil at the open area at the end of the paved lot show that the area has received only minimal uranium-238 and that mixing from traffic or from rain, freezing, and thawing has changed the distribution from the usual pattern in which the highest concentrations are at or near the surface.

Radium was measured in sample AL135S1A. The concentration of ^{226}Ra was 0.61 pCi/g.

Surface Measurements

Alpha and beta-gamma activity was measured at selected locations on the asphalt paving. The results of these measurements are listed in Table 4. The alpha activity ranged from 7 to 35 dpm/100 cm² and averaged 14 dpm/100 cm². Beta-gamma activity ranged from 0.03 to 0.06 mrad/h and averaged 0.04 mrad/h.

A summary of the outdoor measurement results is provided in Table 5.

SIGNIFICANCE OF FINDINGS

The background gamma radiation exposure rate for the State of New York averages 9.5 $\mu\text{R}/\text{h}$ ^{8,9} and averages 9 $\mu\text{R}/\text{h}$ for the Albany area (Table 1). The gamma exposure rates measured on this property at 1 m above the ground surface range from 7 to 11 $\mu\text{R}/\text{h}$ and average 9 $\mu\text{R}/\text{h}$ (the same as the background for the Albany area). The DOE guidelines¹⁰ state that gamma exposure rates inside occupied or habitable structures shall not exceed 20 $\mu\text{R}/\text{h}$ above background. Gamma exposure rates outside of structures shall be such that these exposure rates, due to residual radioactivity, will not result in potential doses (assuming a conservative but plausible use scenario) in excess of 100 mrem/y for long term exposure. These guidelines are not exceeded at this property.

*The curie is a unit used to define the radioactivity in a substance and equals that quantity of any radioactive isotope undergoing 2.2×10^{12} disintegrations per minute. The picocurie is one million-millionth of a curie or that amount yielding 2.2 disintegrations per minute.

The DOE guideline for ^{238}U concentration in soil at the Colonie, New York site is: (a) the ^{238}U concentration shall not exceed the limits of 35 pCi/g averaged over an area of 10 m x 10 m (33 ft x 33 ft), and over 5 cm (2 in.) depth; and (b) the concentration shall not exceed the additional restriction of 100 pCi/g maximum at a spot (1 m²) averaged over 5 cm (2 in.) depth.^{11,12} No 10 m x 10 m area was found that contains more than 35 pCi/g of ^{238}U in the soil. The average concentration was 7.9 pCi/g of ^{238}U in the systematic samples, approximately one-fourth the limit of 35 pCi/g; therefore, the average concentration is well below the DOE guideline. The maximum concentration of ^{238}U measured was 11 pCi/g, well below the limit of 100 pCi/g averaged over 1 m² area. The 0.61 pCi/g of ^{226}Ra measured in the soil is less than the Albany area background of 0.85 pCi/g of radium-226. The concentrations of some radionuclides in the soil at this property are above background levels, but are below applicable DOE guidelines.

Surface contamination of the structures on the property, as evaluated by alpha and beta-gamma activity, was well below the DOE guidelines and the State of New York Department of Labor (DOL) Industrial Code, Rule 38.¹³ The average alpha activity of 14 dpm/100 cm² obtained by measurements on the asphalt paving is well below the DOE limit of 5000 dpm/100 cm² and the DOL limit of 1000 dpm/100 cm² for fixed alpha activity from natural uranium, uranium-235, or uranium-238. The average and maximum beta-gamma activities of 0.04 and 0.06 mrad/h from these structures are less than the DOE limits of 0.20 and 1.0 mrad/h and the DOL limit of 0.25 mrem at 1 cm, respectively.

In summary, while some radiological measurements were greater than background levels normally encountered in the State of New York and the Albany area, no radiation levels nor radionuclide concentrations exceeded the relevant state and federal guidelines used by the Department of Energy to determine if remedial action is warranted.

REFERENCES

1. J. Beck, "Report of Trip to NL Industries Plant, Colonie, N.Y." (August 10, 1983).
2. A Background Report for the Formerly Utilized Manhattan Engineer District, Atomic Energy Commission Sites Program, DOE/EV-0097A (September 1980).
3. J. L. Jacobs, Group Counsel, NL Industries, Inc., to S. R. Miller, DOE, letter "Albany" (December 21, 1983).
4. H. W. Jeter and D. M. Eagleson, A Survey of Uranium in Soils Surrounding the NL Bearings Plant, Teledyne Isotopes, IWL-9488-461 (October 31, 1980).
5. "Radiological Survey Plan for Vicinity Properties in Colonie and Albany, New York," letter from B. A. Berven, ORNL/RASA to A. J. Whitman, DOE/HQ (January 1984).
6. T. E. Myrick, B. A. Berven, W. D. Cottrell, W. A. Goldsmith, and F. F. Haywood, Procedures Manual for the Remedial Action Survey and Certification Activities (RASCA) Program, Oak Ridge National Laboratory, ORNL/TM-8600 (September 1982).
7. T. E. Myrick, B. A. Berven, and F. F. Haywood, State Background Radiation Levels: Results of Measurements Taken During 1975-1979, ORNL/TM-7343 (November 1981).
8. S. G. Levin, R. K. Stoms, E. Kuerze, and W. Huskisson, "Summary of Natural Environmental Gamma Radiation Using a Calibrated Portable Scintillation Counter," Radiological Health Data Report 9:679-695 (1968).
9. C. L. Lindekin, K. R. Peterson, D. E. Jones, and R. E. McMillen, "Geographical Variations in Environmental Radiation Background in the United States." Proceedings of the Second International Symposium on the Natural Radiation Environment, CONF-720805-P-1, pp. 317-331 (1972).
10. U.S. Department of Energy, Guidelines for Residual Radioactivity at Formerly Utilized Sites, Remedial Action Program and Remote Surplus Facilities Management Program Sites (Rev. 1, July 1985).
11. Environmental Research Division, Action Description Memorandum. "Proposed FY 1984 Remedial Actions for Vicinity Properties at the Colonie, New York, FUSRAP Site." Argonne National Laboratory (August 5, 1984).
12. G. P. Turi, FUSRAP/Surplus Facilities Group, to James P. Alexander, Oak Ridge Operations Office (correspondence dated May 10, 1984).

13. State of New York, Department of Labor, "Ionizing Radiation Protection," Part 38 of Title 12 of The Official Compilation of Codes, Rules, and Regulations of the State of New York (cited as 12, NYCRR 38), July 10, 1978.

Fig. 1. Diagram showing grid point and grid block locations outdoors on the property at 3 Crammond Street, Colonie, New York (AL135).

Fig. 2. Front view of the property at 3 Crammond Street, Colonie, New York (AL135) looking east.

Gamma exposure rate
measurements are given
in $\mu\text{R/h}$.

Fig. 3. Surface gamma exposure rates measured at grid points outdoors on the property at 3 Crammond Street, Colonie, New York (AL135).

o systematic
samples

Fig. 4. Locations of soil samples on the property at
3 Crammond Street, Colonie, New York (AL135).

Table 1. Background radiation levels in the Albany area

Type of radiation measurement or sample	Radiation level or radionuclide concentration	
	Range	Average
Gamma exposure rate at 1 m above floor or ground surface ($\mu\text{R/h}$) ^a	8-10	9
Concentration of radionuclides in soil (pCi/g) ^b		
²³⁸ U	0.76-1.2	0.96
²²⁶ Ra	0.48-1.2	0.85

^aValues obtained from four locations in the Albany area.

^bSoil samples (NY1-NY6) obtained from six locations
around the Albany area.⁷

Table 2. Results of the gamma exposure rate measurements outdoors on the property at 3 Crammond Street, Colonie, New York (AL135)

Grid location ^a	Grid point measurements ^b ($\mu\text{R/h}$)		Range of gamma exposure rate during scan of grid block ^d ($\mu\text{R/h}$)
	Gamma exposure rate at 1 m	Gamma exposure rate at the surface ^c	
0+00, BL	7	8	7-12
0+05, BL	9	7	7-12
0+10, BL	7	8	8-11
0+15, BL	8	9	9-13
0+20, BL	8	8	8-12
0+25, BL	10	9	9-13
0+30, BL	11	11	9-13
0+33.7, BL	9	10	-
0+00, 5L	9	9	9-12
0+05, 5L	9	11	10-12
0+10, 5L	9	9	9-13
0+15, 5L	10	11	11-13
0+20, 5L	10	11	11-13
0+25, 5L	9	9	9-12
0+30, 5L	8	9	9-13
0+33.7, 5L	11	11	-
0+00, 10L	8	9	8-11
0+05, 10L	9	9	9-12
0+10, 10L	9	9	9-11
0+15, 10L	9	9	9-11
0+20, 10L	10	11	11-13
0+25, 10L	10	10	10-12
0+30, 10L	11	11	9-13
0+33.7, 10L	9	9	-
0+00, 15L	8	8	8-11
0+05, 15L	8	9	9-10
0+10, 15L	9	10	9-11
0+15, 15L	10	10	9-10
0+20, 15L	9	10	10-12
0+25, 15L	11	11	10-13
0+30, 15L	9	11	11-13
0+33.7, 15L	9	9	-
0+00, 18.5L	9	9	-
0+05, 18.5L	9	9	-
0+10, 18.5L	9	9	-

Table 2 (continued)

Grid location ^a	Grid point measurements ^b ($\mu\text{R/h}$)		Range of gamma exposure rate during scan of grid block ^d ($\mu\text{R/h}$)
	Gamma exposure rate at 1 m	Gamma exposure rate at the surface ^c	
0+15, 18.5L	9	9	-
0+20, 18.5L	9	9	-
0+25, 18.5L	9	10	-
0+30, 18.5L	9	10	-
0+33.7, 18.5L	9	10	-

^aGrid location shown on Fig. 1.

^bGrid point measurements are discrete measurements at each grid point.

^cThese values are shown on Fig. 3.

^dGrid block measurements are obtained by a gamma scan of the entire block.

^eInaccessible.

Table 3. Results of soil sample analysis on the property at
3 Crammond Street, Colonie, New York (AL135)

Sample	Locations	Depth (cm)	Radionuclide concentration (pCi/g)	
			$^{226}\text{Ra}^b$	$^{238}\text{U}^c$
<u>Systematic samples^d</u>				
AL135S1A	0+33.5, 17L	0-5	0.61 ± 0.09	4.7
AL135S1B	0+33.5, 17L	5-15	$\pm$	4.4
AL135S2A	0+33.5, 11L	0-5	$\pm$	9.3
AL135S2B	0+33.5, 11L	5-15	$\pm$	11
AL135S3A	0+33.5, 1.5L	0-5	$\pm$	6.7
AL135S3B	0+33.5, 1.5L	5-15	$\pm$	11

^aLocations of soil samples are shown on Fig. 4.

^bIndicated counting error is at the 95% confidence level ($\pm 2\sigma$).

^cAnalytical error of measurement results is $< \pm 5\%$ (95% confidence level).

^dSystematic samples are taken at grid locations irrespective of gamma exposure.

Table 4. Results of surface analysis of structures at
3 Crammoud Street, Colonie, New York (AL135)

Structure	Number of measurements	Results		Average	
		(dpm/100 cm ²)	(mrad/h) ^a	(dpm/100 cm ²)	(mrad/h)
<u>Alpha Activity</u>					
Asphalt paving	10	21,35,21,7,7,14, 1,14,7,7	-	14	-
Total	10	7-35	-	14	-
<u>Beta-Gamma</u>					
Asphalt paving	10	-	0.03,0.03,0.03, 0.02,0.03,0.03, 0.06,0.03,0.05, 0.04	-	0.04
Total	10	-	0.02-0.06	-	0.04

^aThe rad is the unit of absorbed dose and is defined as the amount of radiation required to cause absorption of 100 ergs per gram of medium. (The erg is a unit of energy. One erg in the form of heat will raise the temperature of 1 gram of water about 2.4×10^{-8} °C.)

Table 5. Summary of outdoor measurements and sample results on the property at 3 Crammond Street, Colonie, New York (AL135)

Measurement of sample type	Number of measurements/ samples	Range	Mean
Gamma exposure rate at 1 m ($\mu\text{R/h}$) ^a	40	7-11	9
Gamma exposure rate at surface ($\mu\text{R/h}$) ^a	40	7-11	9
Scan, gamma exposure rate near surface ($\mu\text{R/h}$) ^b	-	7-13	-
Concentration of ^{238}U in surface soil (pCi/g), systematic locations ^c	6	4.4-11	7.9
Area estimated to contain ^{238}U concentrations exceeding guidelines (m ²)	-	-	None
Concentration of ^{226}Ra in surface soil (pCi/g), systematic locations ^c	1	-	0.61
<u>Surface measurements</u> ^d			
Alpha activity (dpm/100 cm ²)	10	7-35	14
Beta-gamma activity (mrad/h)	10	0.03-0.06	0.04

^aAt grid points.

^bScan of entire property.

^cSystematic samples, Table 3.

^dSurface measurements, Table 4.

OENL/RASA-87/82
(AL135)

INTERNAL DISTRIBUTION

1. B. A. Berven	10. T. H. Row
2. R. O. Chester	11. P. J. Walsh
3. W. D. Cottrell	12. IRgA Publications Office
4-8. J. L. Marley	13. Laboratory Records - RC
9. P. T. Owen	

EXTERNAL DISTRIBUTION

- 14-18. S. W. Ahrends, U.S. Department of Energy, P.O. Box E,
Oak Ridge, TN 37831
19. J. D. Berger, Oak Ridge Associated Universities, P.O. Box 117,
Oak Ridge, TN 37831
- 20-22. J. J. Fiore, U.S. Department of Energy, 19901 Germantown
Road, Germantown, MD 20874
- 23-25. G. K. Hovey, Bechtel National, Inc., 800 Oak Ridge Turnpike,
Oak Ridge, TN 37831
26. G. P. Turi, U.S. Department of Energy, 19901 Germantown Road,
Germantown, MD 20874
27. J. W. Wagoner, U.S. Department of Energy, 19901 Germantown Road,
Germantown, MD 20874
28. Andrew Wallo III, U.S. Department of Energy, 19901 Germantown
Road, Germantown, MD 20874
29. Charles Young, The Aerospace Corporation, Suite 4000,
955 L'Enfant Plaza, SW, Washington, DC 20024
30. Office of Assistant Manager, Energy Research and Development,
Oak Ridge Operations Office, Oak Ridge, TN 37831
- 31-32. Office of Scientific and Technical Information, U.S. Department
of Energy, Oak Ridge, TN 37831