UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Audio-magnetotelluric Data Log and Station Location Map
for the

Glamis Known Geothermal Resource Area, California

by

R. M. Senterfit and W. D. Heran

Open-File Report 78 - 105C

1978

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE.

It has been reproduced from the best available copy to permit the broadest possible availability.

zhs
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report is preliminary and has not been edited or reviewed for conformity with U.S. Geological Survey standards.

MASTER

PURCHASE ORDER NO. 031-50490
5-23-83
RECEIVED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

AUDIO-MAGNETOTELLURIC STATION LOCATION MAP

GLAMIS KNOWN GEOTHERMAL RESOURCE AREA, CALIFORNIA

R.M. SENTERFIT & W.D. HERAN

0 1 SCALE 2 3 MILES

KILOMETERS

1978

LEGEND

- AMT STATION
- ▬ RAILROAD
- ▬ CANAL
- ▬ HIGHWAY

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.	FREQUENCY												
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1 _{NE}	pa	3.4	5.8	3.2	4.5	-	45.5	-	-	-	14.7	68.0	29.7
	N	7	6	5	6		4				3	1	1
	Er	1.1	1.4	0.4	0.5		8.4				2.4	-	-
1 _{SE}	pa	7.3	8.2	5.2	6.8	-	5.5	-	-	-	108.2	20.6	37.1
	N	8	5	6	6		4				5	1	1
	Er	2.9	1.8	0.04	0.1		0.4				7.6	-	-
2 _{NE}	pa	18.8	10.4	19.5	12.9	22.3	2.6	-	-	-	21.4	24.1	-
	N	6	6	7	6	6	4				5	1	
	Er	1.1	2.6	1.9	0.9	5.4	0.1				0.3	-	
2 _{SE}	pa	26.4	22.6	17.8	12.8	7.0	2.7	-	-	-	64.4	29.6	22.0
	N	6	6	5	5	4	4				6	1	1
	Er	2.0	1.5	1.1	0.8	0.7	0.6				6.1	-	-
3 _{NE}	pa	33.5	49.8	63.6	65.6	50.1	36.8	-	-	-	23.0	24.7	13.1
	N	6	5	5	6	6	4				4	1	1
	Er	5.1	14.9	10.2	7.7	10.4	4.2				1.2	-	-
3 _{SE}	pa	87.8	88.0	75.7	56.5	44.7	12.2	-	-	-	96.5	64.6	-
	N	6	5	5	5	6	4				1	1	
	Er	11.3	9.2	12.0	5.2	6.8	3.4				-	-	
4 _{NE}	pa	70.9	79.8	102.0	76.2	46.3	-	-	-	-	29.3	36.7	29.1
	N	6	6	6	6	6					3	1	1
	Er	7.8	13.2	8.5	7.3	4.2					2.4	-	-
4 _{SE}	pa	137.8	111.7	183.0	113.3	93.2	-	-	-	-	138.0	111.1	-
	N	6	5	6	6	6					2	1	
	Er	18.2	34.2	14.6	7.8	5.5					1.5	-	

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5 _{NE}	pa	68.0	66.9	58.0	31.6	46.5	9.4	-	-	-	161.0	36.6	-
	N	6	5	6	5	6	1				2	1	
	Er	12.2	10.1	5.8	5.7	5.9	-				4.8	-	
5 _{SE}	pa	396.8	416.0	318.1	229.6	160.8	21.3	-	-	-	51.0	43.5	20.4
	N	6	5	6	6	6	7				4	1	1
	Er	40.2	52.9	28.6	12.1	17.4	1.6				4.5	-	-
6 _{NE}	pa	8.7	8.5	5.1	17.0	6.1	-	-	-	-	-	-	3.1
	N	5	4	4	6	3							1
	Er	2.4	1.5	0.3	2.8	0.9							-
6 _{SE}	pa	18.9	-	26.1	16.0	5.9	-	-	-	-	-	28.3	-
	N	5		3	5	3						1	
	Er	6.2		0.7	1.8	2.3						-	
7 _{NE}	pa	-	-	-	-	-	-	-	-	-	-	-	-
	N												
	Er												
7 _{SE}	pa	23.3	9.5	32.6	15.4	38.2	-	-	-	-	83.8	79.9	2.1
	N	4	5	6	6	6					3	1	1
	Er	7.0	3.9	4.5	5.5	4.9					8.0	-	-
8 _{NE}	pa	12.7	-	15.6	9.2	17.9	9.7	-	-	-	279.8	355.8	455.0
	N	6		4	5	7	3				3	1	1
	Er	1.9		1.2	2.8	2.1	2.9				9.2	-	-
8 _{SE}	pa	5.4	-	5.8	3.1	3.0	5.5	-	-	-	-	-	1.6
	N	6		5	5	3	3						1
	Er	1.5		1.6	0.3	0.7	1.4						-

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres - = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
9 _{NE}	pa	16.8	—	33.4	19.6	21.9	29.6	—	—	—	198.1	283.7	195.6
	N	4		9	7	6	3				5	1	1
	Er	2.3		6.5	1.5	5.1	0.7				16.3	—	—
9 _{SE}	pa	10.4	—	7.9	12.1	29.9	98.6	—	—	—	540.0	444.5	214.5
	N	5		8	6	6	5				4	1	1
	Er	1.2		0.9	1.1	0.4	30.0				17.2	—	—
10 _{NE}	pa	8.9	5.4	6.7	7.7	9.9	—	—	—	—	—	34.2	27.8
	N	5	4	5	6	5						1	1
	Er	3.2	2.1	1.0	0.1	1.0						—	—
10 _{SE}	pa	9.5	2.7	5.7	8.1	17.3	—	—	—	—	—	36.4	5.8
	N	5	4	6	5	4						1	1
	Er	0.4	0.4	1.7	1.3	0.7						—	—
11 _{NE}	pa	42.3	51.7	48.9	17.9	15.1	11.3	—	—	—	18.8	47.5	20.4
	N	3	4	6	5	5	5				5	1	1
	Er	8.7	24.0	23.0	1.5	0.7	0.9				0.6	—	—
11 _{SE}	pa	5.1	2.0	3.0	6.7	21.9	28.8	—	—	—	92.2	94.6	48.1
	N	5	4	5	4	6	5				3	1	1
	Er	0.8	1.0	0.3	1.6	2.0	1.8				30.6	—	—
12 _{NE}	pa	38.1	27.6	10.0	8.6	—	—	—	—	—	22.4	36.8	10.1
	N	5	6	6	6						4	1	1
	Er	12.2	4.3	1.3	1.1						0.01	—	—
12 _{SE}	pa	18.0	6.4	3.8	3.4	—	—	—	—	—	80.6	26.3	23.2
	N	7	5	6	5						4	1	1
	Er	9.1	1.3	0.6	0.2						7.1	—	—

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13 _{NE}	pa	24.2	21.0	11.4	18.0	8.7	2.3	—	—	—	184.1	181.0	96.3
	N	7	7	7	5	5	4				3	1	1
	Er	6.9	3.7	2.1	0.3	0.2	0.3				5.8	—	—
13 _{SE}	pa	28.6	16.6	32.3	21.0	21.2	14.3	—	—	—	298.8	515.8	31.6
	N	5	3	2	4	4	5				1	1	1
	Er	9.9	6.6	0.0	3.2	5.2	3.4				—	—	—
14 _{NE}	pa	12.6	39.7	16.7	21.0	11.4	3.0	—	—	—	8.6	45.0	—
	N	3	4	6	6	5	4				4	1	
	Er	0.4	9.0	6.1	5.1	0.8	0.4				0.4	—	
14 _{SE}	pa	16.5	9.0	4.8	5.4	9.2	11.1	—	—	—	9.1	29.7	—
	N	3	3	5	5	5	4				4	1	
	Er	4.0	2.8	0.7	1.0	2.2	5.2				0.5	—	
15 _{NE}	pa	18.5	—	13.0	21.9	12.3	36.3	—	—	—	—	968.7	1603.0
	N	4		5	7	3	3					1	1
	Er	3.0		3.0	2.0	0.5	6.4					—	—
15 _{SE}	pa	43.9	—	19.0	29.0	21.7	14.5	—	—	—	38.7	241.7	562.0
	N	4		5	6	6	1				6	1	1
	Er	7.8		5.0	5.5	3.9	—				1.9	—	—
16 _{NE}	pa	40.6	30.8	22.0	22.3	19.5	14.1	—	—	—	142.0	174.0	147.8
	N	5	3	3	6	5	5				4	1	1
	Er	7.5	3.4	2.7	1.7	3.1	1.6				7.9	—	—
16 _{SE}	pa	20.2	13.6	11.8	16.6	15.8	8.7	—	—	—	—	345.0	143.5
	N	6	6	6	5	5	4					1	1
	Er	2.4	2.0	1.7	2.2	1.2	0.5					—	—

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
17 _{NE}	pa	118.4	—	34.5	54.8	13.8	15.3	—	—	—	19.3	29.8	25.9
	N	4		4	4	5	5				4	1	1
	Er	16.2		3.2	9.6	1.1	2.8				2.1	—	—
17 _{SE}	pa	20.0	11.9	5.3	8.6	16.5	12.0	—	—	—	27.4	25.0	25.3
	N	5	4	8	5	5	6				5	1	1
	Er	7.4	2.0	1.3	2.5	1.4	0.6				5.3	—	—
18 _{NE}	pa	11.5	5.2	2.3	4.1	8.3	—	—	—	—	52.0	84.0	52.3
	N	4	3	6	6	5					4	1	1
	Er	4.8	0.2	0.8	1.1	1.2					0.1	—	—
18 _{SE}	pa	22.6	4.9	1.8	2.4	—	—	—	—	—	201.6	98.8	60.3
	N	4	3	4	5						5	1	1
	Er	5.1	1.5	0.7	0.1						17.7	—	—
19 _{NE}	pa	10.0	4.5	1.8	0.7	0.1	—	—	—	—	98.6	111.4	98.1
	N	6	3	8	6	2					4	1	1
	Er	2.1	0.7	0.2	0.1	0.01					1.4	—	—
19 _{SE}	pa	12.2	7.5	5.8	9.4	3.0	—	—	—	—	206.7	138.6	28.5
	N	6	6	6	6	2					2	1	1
	Er	2.3	0.7	0.5	0.8	0.4					7.0	—	—
20 _{NE}	pa	25.3	16.9	7.8	23.9	22.9	—	—	—	—	—	251.3	7.4
	N	4	4	4	5	3						1	1
	Er	2.4	5.2	2.0	1.8	3.2						—	—
20 _{SE}	pa	42.6	14.2	17.4	6.5	20.1	—	—	—	—	—	9.7	300.0
	N	4	5	3	4	5						1	1
	Er	6.7	3.1	2.5	2.3	6.2						—	—

GLAMIS KGRA

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
21NE	ρ_a	8.3	17.5	12.4	12.8	11.1	2.7	—	—	—	22.4	—	—
	N	8	5	6	6	6	1				2		
	Er	2.0	2.2	0.9	0.3	0.9					0.2		
21SE	ρ_a	11.0	9.3	4.7	5.7	3.9	—	—	—	—	104.0	—	—
	N	5	5	4	6	3					1		
	Er	1.7	3.2	0.4	0.4	0.2					—		
22NE	ρ_a	21.5	12.2	13.7	11.8	13.0	3.8	—	—	—	24.2	39.7	810.0
	N	7	5	6	6	8	5				5	1	1
	Er	3.6	1.1	0.5	1.2	1.5	0.3				1.7	—	—
22SE	ρ_a	20.2	10.2	7.7	8.7	9.6	4.3	—	—	—	—	49.7	26.2
	N	3	4	6	6	6	5					1	1
	Er	0.5	2.7	1.3	2.9	2.1	0.7					—	—
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												
	ρ_a												
	N												
	Er												