APPENDIX C

DE92 003436

1988 PERFORMANCE REPORT

Covering the period
August 30, 1987 to January 30, 1989

FOR

GEOLOGIC SPATIAL ANALYSIS

Dr. Richard L. Thiessen and Dr. Jay R. Eliason

Co-principal Investigators

Geology Department
Washington State University

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INTRODUCTION

The Geologic Spatial Analysis (GSA) research program was initiated at Washington State University in 1987. This research program is funded by the U. S. Department of Energy's Office of Basic Energy Science (OBES). Basic research being conducted on GSA techniques is coordinated with a companion OBES program at DOE's Pacific Northwest Laboratory (PNL). The following performance report provides a brief overview of the status of the research and includes references to publications and presentations.

Geologic spatial analysis research is focused on conducting comprehensive three-dimensional analysis of regions using geologic data sets that can be referenced by latitude, longitude and elevation/depth (Table 1). Based on these data, the GSA techniques determine the location and orientation of structural features in three-dimensional space in order to develop a regional geologic model for the user. This concept is based on, but far exceeds, classic structural analysis techniques which are more concerned with mapped patterns of lithologies and/or orientations of structures, and not their location in three-dimensions. These fundamental relationships are essential for exploration and development of energy resources, assessment of seismic risk, analysis of hydrologic systems, and regional basic geologic research.

This rapidly expanding analysis technology is based on research initiated by Dr. Jay R. Eliason for analysis of crustal fractures using topography (COPLANEV) and seismically active fracture zones (COPLANEP); and Dr. Richard Thiessen for analysis of seismically active fractures (SEISPLN), lineament analysis system (LINEAMENT), and analysis of complex fold structures (REFOLD). These analyses techniques are all based on utilization of digital analysis systems.

Input Data Sources:

- Topography
- Remote Sensing
- Seismic Foci
- Geophysical Data
- Underground Acoustic Imaging
- Field Studies
- Borehole Data
- Laboratory Analyses

Analysis Techniques:

- Coplanar
- Seismic
- Lineament
- Refold

Output Products:

- 3-D Crustal Fracture Models
- 3-D Active Seismic Surface Models
- 3-D Fold and Refold Models
- Assessment of Underground Acoustic Imaging Methods
- Stress Field Analyses
- Comprehensive 3-D Geologic Model
- Maps/Cross Sections
- Statistical Summaries/Analysis Trails

Table 1. Major components of the GSA analysis system.

RESEARCH OBJECTIVES

The objective of this research program is to develop and test a package of quantitative GSA computer programs that will enable scientists to determine the three-dimensional structural relationships of a region.

Table 1 itemizes the key components of the GSA system that are currently under development at WSU and PNL. The input data sources are research areas that have been actively developed at both WSU and PNL. Capabilities for generating the input data bases required for GSA represent years of individual research effort. These capabilities are now being exchanged as an initial part of the program. They include mapping, digitizing, structural analysis, image analysis, and computer graphics techniques.

The analysis techniques under development are currently being transferred between WSU and PNL. To facilitate this, a high speed ethernet computer link is being installed between the OBES VAXstation computer systems at WSU's Geology Department and DOE's PNL computer network. This link will provide scientists with direct access to the computer facilities from both WSU and PNL, and will accelerate the development of the techniques and will avoid duplication of effort. WSU will benefit specifically from having direct access to computer facilities at PNL's Geosciences Department and the DOE Cray supercomputer for future computation-intensive research.

Output products vary depending on the analysis technique, but preliminary three-dimensional stereo models of crustal fractures, folds, and active seismic surfaces are output options. A major research objective of both WSU and PNL is to continue the development of a comprehensive three-dimensional output model. Quantitative data output as statistical summaries and/or analysis trails are being incorporated into many of the analysis modules. The statistical summaries will provide the user a measure of the accuracy of the structural determinations to supplement graphical output products. The analysis log provides a record of the input parameter values used in the GSA analysis.

Development and testing of the GSA programs will be done with data from sites relevant to DOE's missions. These supporting field studies are essential for the verification of the GSA techniques.

1988 RESEARCH

COPLANE

A major effort in the present COPLANEV analysis sequence is the selection of dominant planar features. The present analysis system requires the user to manually select dominant planes using an interactive program for coplanar output analysis, COPOUT. The experience gained developing the COPOUT program and using the program in several analyses has led to the development of a concept for development of an automatic coplanar analysis program (AUTOCOP, Figure 1). The concept is based on the observation that dominant planar features are detected multiple times by the coplanar analysis. These dominant features are spatially clustered and are closely oriented in three-dimensional space. The initial analysis technique is based on using a central reference point (CRP) located at the DEM average latitude, average longitude, and average elevation. Pole distances (d) from this point to all planes detected in the coplanar analysis are calculated and this distance is used in conjunction with the plane orientation in three-dimensional space to sort dominant plane sets. Initial implementation of this concept is being coordinated with PNL. This major program development effort is expected to be a first step in the development of an automated crustal fracture analysis system. Research efforts on further development of this and related concepts are proposed for both the WSU and PNL programs. The PNL efforts are focused on evaluation of statistical methods while the WSU efforts are focused on development of algorithms for direct determination of spatial correlations. This complimentary research effort should provide rapid development of the automated analysis capabilities that are needed to significantly advance the present state-of-the-art of the coplanar analysis techniques.

A concept for directly digitizing valley vectors from topographic maps is being developed that will not require having DEMs. This concept requires the user to digitize contour crossings at valley bottoms directly from a topographic map in order to identify valley low points. Input requirements are the map contour interval, starting contour elevation and the direction of contour input (i.e. increasing or decreasing elevations). This technique will produce strings of valley low points that will be formatted to be compatible with input requirements of the COPLANEV (VECTOR) program. Initial versions of this program, written in 1988, will be implemented and tested in 1989. Results of these analyses will be compared with the results from the DEM noise studies being conducted by PNL, to quantify the effect of noise in DEMs on COPLANEV analysis.

Four test areas were used in 1988 to evaluate and direct development of COPLANEV analysis techniques. Northeastern Washington state and the central Columbia Plateau are local test areas where DEM scale effects on detection of planar features are being evaluated. Two additional test sites provide the opportunity to evaluate a local field area where stress analyses are being studied, Cajon Pass, California, and a site where gas production data

Figure 1. Flow diagram for the automated coplanar analysis program, AUTOCOP. This program is currently under development and will provide the user an option for automated selection of dominant planar features previously provided by manual analysis with the COPOUT program (Figure 5). Dominant sets of planes that have been detected with the COPLANE programs will be automatically defined and ranked. CRP is the central reference point for the entire topographic data base, PRP is the plane's reference point, d is the distance from the CRP to the plane (measured perpendicular to the plane itself), $p\Delta d$ is the limiting value for the plane set's correlation range for the distance (d), and SR is the plane set's reference number.

and geochemical sampling are being used to assess planar features detected, Big Sandy Gas Field, southeastern West Virginia.

Applications of the COPLANEV software system have included regional analyses using 1:250,000 DEM data in northeastern Washington state and over the central Columbia Plateau. Dr. A. John Watkinson, of WSU compiled a comprehensive structural data base for this research. These analyses are preliminary, but have resulted in identification of dominant planar features that correlate with lineament, geophysical, and structural field mapping data (Thiessen and others, 1988; Beaver and others, 1989). These studies are part of an assessment of DEM scale effects on detection of planar features. The 1:24,000 scale DEM data sets available from the U.S. Geological Survey for the central Columbia Plateau have been acquired by PNL and are now available for analysis. The quality of these data are poor due to noise introduced by the digitizing techniques. Assessment of the data quality and continued assessment of scale effects or detection of planar features will continue in 1989.

Analysis of the Continental Scientific Drilling Program study area at Cajon Pass, California with COPLANEV techniques was initiated in 1988. This overall research effort is being conducted by the U.S. Geological Survey in order to determine in-situ stress orientations near the San Andreas Fault as part of a project designed to study fundamental problems related to the processes controlling movement along the fault. Mark Ader of the U.S. Geological Survey used a borehole televiewer to measure the orientations of fractures and breakouts in support of in-situ stress analyses conducted at the site (Ader and Springer, 1987; Springer and Ader, 1987). He is now working part time at WSU on a master's degree applying the COPLANEV programs to the Cajon Pass region to assess the local fracture sets developed in the drill site area, the San Gabriel Mountains to the west, and the San Bernardino Mountains to the east. Orientations of planar features will be used to interpret regional crustal stress fields and the spatial variation of these features. Borehole fracture orientations, field measurements of fracture orientations, and seismic hypocenter location data will be used in the planned COPLANE analysis.

Coplanar analysis of the Big Sandy Gas Field in southwestern West Virginia provides a unique opportunity to use the techniques to define steeply dipping fracture sets that influence regional gas production from the Devonian shale. Data on the gas production, geologic structures, and lithologic units in the area have been collected by DOE's Morgantown Energy Technology Center (METC) personnel for evaluation of lineament mapping of the area using aerial and satellite imagery. These various data sets are in digital format and should provide a unique data base for future development of a fracture model from the planar features, topography, and lithologic units. Analyses conducted by three experienced lineament mapping groups were unable to define zones of high gas production that are believed to be controlled by natural fracture systems in this complex topographic region (Pratt and others, 1985). Initial coplanar analysis of the four 7.5 minute quadrangle test area DEMs has been conducted and preliminary results were strongly correlated with gas production trends. The results are, also, correlative with large, normal Precambrian faults in the deep

basement as mapped from seismic and borehole data and with the major cross-strike discontinuities that have been mapped in the study area (Foley and others, 1988A). The dominant planar features are being used by the METC personnel to conduct field geochemical sampling of gas seepage over these zones. Results of these surveys will be available for future use.

Specific software development during 1988 is listed below. The most recent version of the COPLANE vector (COPLANEV) analysis software has been installed on the WSU VAXstation. A program for selection, manipulation, and output of sub-regions from DEMs, TOPO_SELECT, has been developed. A preliminary users manual for the COPLANEV software system was written (Eliason and Landle, 1988) which provides a brief description of the function of each program including a typical input trail required to run each program. The trail is being annotated to provide the user with specific details on data requirements and recommended ranges for input parameters. This manual will be modified to include new software enhancements as they are developed. Dr. Jay R. Eliason, working with the PNL OBES program, designed and participated in the development of a revision of the COPLANEV program, the COPLANEV program (discussed in the seismic section below), and the VIEW_TOPO program which produces three-dimensional output from the COPLANE programs. These programs were implemented by Mary Ann Glennon (COPLANEV) and Lawrence H. Gerhardstein (COPLANEV revision and VIEW_TOPO). The concept for development of an automatic coplanar analysis program for selecting dominant planar features from COPLANE analyses (AUTOCOP) was also developed and initial implementation is now being demonstrated by Dr. Eliason. During the first part of the OBES funding period for our grant (Sept. 29-30, 1987), the technique was presented as part of a remote sensing short course for staff of the Basalt Waste Isolation Project at Hanford, which included production of a set of short course notes (Thiessen and Eliason, 1987). Dr. Eliason worked with the PNL OBES program personnel to develop and present the Program Workshop held on March 3-4, 1988 (Eliason and others, 1988) and the short course notes for the 28th International Geologic Congress, which is to be presented on July 9- 19, 1989 (Eliason and others, 1989). The COPLANE analysis techniques were presented at the International Topical Meeting on Nuclear and Hazardous Waste Management in Pasco, Washington (Foley and others, 1988B) at a Penrose Conference during September of 1988 in Mariposa, California (Eliason and Foley, 1988).

Seismically Active Planes

The concept of the COPLANEV program was developed by Dr. Jay R. Eliason in 1984, and these ideas were implemented under his direction by M.A. Glennon at PNL in 1988. The program has been tested with synthetic data bases to evaluate the sensitivity of the technique to random noise. Only limited applications of the technique to real data sets have been conducted to date. Local microseismic data sets are now being obtained to continue this research. The program has been incorporated into short course notes presented at PNL

(Eliason and others, 1988) and one to be presented at the 28th International Geologic Congress in Washington, D.C. (Eliason and others, 1989).

Eric Rieken, who wrote the original SEISPLN program package for his M.S., has started a Ph.D. at WSU in order to fully develop and test the seismicity plane algorithms. Currently, the SEISPLN package is in the process of conversion to VAX Fortran from a number of computer languages and computer systems for which it was originally designed.

A literature review of previous work on the detection of point alignments (i.e. seismic foci) was conducted. This review was the partial basis for the development of conceptual models for computer routines for the incorporation of seismic location errors and elongate shapes to the data field. Options for additional statistical techniques were examined.

With the counting box routine used by SEISPLN, incorporation of location error of the earthquakes will be relatively simple. Uncertainties will be used to define a gaussian distribution for each point, centered on the foci's nominal location. The number of quakes seen in each counting cell will be partially incremented by only that portion of the gaussian distribution which falls within that counting cell.

Other workers who have defined methods for examination of alignments of point data have discussed the shape problem (Lutz, 1986; Fehler and others, 1987; Wadge and Cross, 1988). The distribution of data on a map is rarely perfectly circular, but instead might form an elongate ellipse. Any alignments parallel to the long axis of the ellipse will have a greater chance to include more of the data points. In order to correct for this shape effect, a Monte Carlo technique has been utilized by the above authors. A large number of sets of randomly distributed data points, within the boundary of the observed data shape, are prepared. Whichever method is being used is applied to each of these random data sets, and the results of all the runs are averaged out. This average random effect is then used to normalize the results obtained from the observed data base, removing the shape effect. Conceptual models for incorporating this method into SEISPLN have been developed.

An alternative approach for handling of the shape problem with SEISPLN has been devised in 1988. The total volume of the three-dimensional shape that contains the data distribution will be determined. The number of earthquakes divided by this total volume will yield the expected concentration for a truly random distribution. The volume of the distribution of the data that falls within each individual counting box will also be calculated. The box's volume, divided by the total volume and multiplied times the total number of foci, will yield the portion of the data that should fall within the box, assuming uniform distribution. This value can be used to normalize the foci concentrations actually observed in the boxes.

The above method may also serve as a solution for the observed concentration of earthquakes at shallow depths due to seismic stations being at

the surface. A semi-random data distribution could be incorporated, with some weighting function added to the vertical dimension. The proportion of the semi-random data falling into each box would be used to normalize the number of foci observed within that box's volume.

LINEAMENT

The main part of the LINEAMENT program package was originally written in BASIC on a Hewlett Packard HP 9845B at WSU by Dr. Thiessen and staff (Thiessen, 1986A). During 1988, most of the LINEAMENT package was translated to FORTRAN and transferred to the VAXstation. The extensive graphics used by the original program were amended in order to use routines on the VAXstation, and modified so as to be able to address to the system plotter. The programs were originally written in a user friendly format, but additional internal documentation of the program packages, and capabilities unique to the VAXstation environment (i.e. simultaneous text and graphics display) were added to the program.

For her M.S. thesis at WSU, Johnson (1988) wrote her lineament comparison and statistical analysis routines as separate software for a VAX 11/780 at PNL. These routines were modified so as to be compatible with the LINEAMENT program package, and the two were meshed into one comprehensive system.

The lineament analysis system has been tested with three separate studies. In a previous study (Thiessen and others, 1987), staff at WSU utilized four different images prepared by PNL of the Paiute Ridge quadrangle at the Nevada Test Site. These included the original TM image, a shadow image based upon a DEM, a corrected TM image with the shadows removed, and a stereopair of the latter. Johnson (1988) used these lineament data to test her comparison routines. The results were presented at the DIAL symposium at WSU (Oct. 15-16, 1987) during the first part of our OBES proposal's funding period (Thiessen, 1987). A visiting scholar, B. Sekar, also used the LINEAMENT package for an analysis of structures in the Tamil-Nadu region of the south Arcot District, eastern India. The third was a multiple interpreter analysis of the central Columbia Plateau in Washington state (Thiessen and others, 1989). This was presented at the DOE-OBES sponsored Eighth International Conference on Basement Tectonics. This study compared lineaments observed on a radar image mosaic, a shadow image of the digital terrain models of the Hanford area (prepared by H. Foote of PNL), and linear features observed on aeromagnetic maps by WSU and other analysts. Using our lineament comparison routines, structures were flagged which were observed by multiple interpreters on at least two of the three data types. Major reverse fault and fold sets in the region which produce linear mountain systems, were well displayed on all the data types. However, many, more subtle lineament features, also appeared in the final compilation maps. The COPLANEV programs were utilized on a 1:250,000 scale digital terrain model of the region. COPLANEV planes which matched the trends and locations of the compilation lineaments

were identified and displayed, so as to be able to determine the three-dimensional orientation of the structures. Future research will call for the registration of the lineaments and compilation lineaments to DEMs in order to directly give them three-dimensionality. The resulting lineament vectors will be used in the COPLANE programs in combination with valley vectors.

A literature review of previous studies on automated detection of linears was performed in two parts. One portion specifically examined evidence for faults and fractures in geophysical data sets including gravity, aeromagnetic and electrical data. Several methods for the direct modelling of relative offsets along faults were assessed. The second study reviewed past lineament work using fourier analyses and edge detection routines.

Conceptual models of computer routines for automated detection of lineaments were formulated in 1988. Currently, the lineaments are manually picked, resulting in operator bias and problems with reproducibility. Burdick and Speirer (1980) used an automated counting box technique, very similar to our SEISPLN program. They examined points that were either lighter than or darker than the adjacent pixels in an image. An east-west oriented filter was the only one used. A series of boxes were placed over the anomalous points and the number of points falling within each box was counted. The whole box system was then rotated and the counting was repeated. They considered an alignment was statistically valid when the concentration of points within a box was significantly greater than uniform distribution. Other workers have utilized edge enhancement routines to find anomalous points in an image, such as ones we have written as part of our IMAGE program package (Thiessen, 1986B). Locations where there is a rapid change in the image are detected using numeric filters. These filters are directional, and, for a complete analysis, should be applied in a number of orientations. We plan, as a long term research goal, to utilize the counting box method developed for SEISPLN to find alignments of anomalous pixels in an image. These anomalous points will be defined using variously oriented edge enhancements and minimum/maximum detection filters, like Burdick and Speirer's (1980). Rather than count each detection as a single point, we plan to weight them depending upon the magnitude of the minimum or maximum and/or the edge. The results from the differently oriented detectors will be summed with the counting boxes, and strong alignments will be flagged for future analysis. The original image will be combined with a DEM so that the three dimensional location of each pixel will be known. This information will then be input into the unified counting box algorithm, UNIBOX, for comparison and simultaneous analysis with all other data bases.

A version of LINEAMENT was written that allows us to overlay lineaments onto a color contour map on the VAXstation monitor screen. This registration of lineaments to a DEM is the first stage in the correlation of lineament data to topography. When this research line is finalized, the full three-dimensional orientations and locations of structures digitized with LINEAMENT will be determined and input into future COPLANEV analyses.

LINEAMENT has been modified to allow us to digitize in fracture data observed on seismic reflection profiles. Preliminary versions of computer codes have been written that combine the observed trace of the fracture, the location of the seismic line itself and a complex velocity stack for the area in order to determine the true three-dimensional location of the fracture trace. These traces will be directly input into the COPLANEV programs in the future.

REFOLD

The REFOLD program package was utilized for two major studies during 1988. The first of these was the Loch Monar area in northern Scotland (Watkinson and Thiessen, 1988, 1989). This project was also part of a poster presentation at a Penrose Conference. The second study area is an analysis of a refolded mining district in the Northern Black Hills. Detailed structural field mapping by one of our graduate students is being supplemented by ground magnetics and thin section analysis. This data will be input into the REFOLD package in order to create three-dimensional models of the region.

The REFOLD routines currently use a passive shear type of model for the genesis of folds. Dr. A.J. Watkinson at WSU has considerable expertise with numeric and analog modelling of the generation of folds with non-passive behavior, such as buckle folds and anisotropic elements within the lithologic layers. Several of these models were examined in 1988 for possible incorporation into REFOLD. A long term goal of REFOLD is to combine this expertise with the ability to look at multiple generations of folding to create the option of modelling regions where non-passive behavior has occurred.

Computer Hardware

A key element of the WSU research effort was acquisition and installation of a VAXstation II GPX computer system that is fully compatible with systems used in the companion research program sponsored by OBES at PNL. Operating systems and utility software used at PNL have been installed on the WSU system. This provides a totally compatible computing environment for developing and testing the GSA techniques.

A campus wide high speed fiber-optic network is now being installed at WSU. As part of the network, outside computing networks will be accessible from internal nodes. The DOE's PNL is connected to the WSU network via a high speed microwave link. Working with PNL's University Relations Office and Geosciences Department staff, we have received the necessary approvals and financial support to interface the WSU Geology Department's VAXstation to the network. This direct high speed link should be operational by December 1988 and will allow WSU and PNL scientists direct system access in both directions. WSU's VAXstation system software will be directly supported by PNL systems staff over the link. This will assure that system software upgrades and utility program modifications are maintained. Total compatibility of the systems

provides a unique opportunity for rapid transfer of software and data sets required for conducting GSA research. The link also provides WSU access to PNL's unique computer input and output facilities and the high speed Cray Supercomputer that will be required for computational intensive GSA research in the future. A significant block of supercomputer time is allocated to WSU from PNL through their University Relations Office. We are planning to utilize these capabilities in future GSA research on regional analyses.

A large format HP Draft Pro, eight pen plotter, and a Scriptel 24 by 36 inch digitizer are on loan to the WSU Geology Department. These input and output devices are being integrated into the system to provide users access to map data at a variety of mapping scales. Acquisition of permanent replacements for these or equivalent hardware components will be a high priority requirement for future system development.

Software Exchange

System software configuration on the WSU VAXstation has been adapted from the PNL systems in order to maintain compatibility. The high speed data link now being installed will allow the PNL systems personnel to access directly the WSU system to maintain complete system compatibility.

The COPLANE analysis programs have been fully implemented on the WSU system. Programs such as TOPO_SELECT and AUTOCOP are now being developed at WSU and transferred to PNL.

The LINEAMENT analysis software package developed at WSU has been transferred to PNL and an image analysis system developed at WSU (Thiessen, 1986B) is now being installed on the WSU VAX system and will be installed on PNL's systems in 1989.

The executive shell for the VAXstation, being developed at PNL, to provide VAXstation interactive user friendly interfaces to existing programs with the minimum requirement for reprogramming, will be installed at WSU as it becomes operational. The RAMTEK emulator for the VAXstation developed as part of the shell has been installed at WSU for providing color image output from the image analysis system.

Mapping and digitizing programs developed at PNL are now being installed on the WSU system. Transfer of these software packages has required only minor modifications of input and output options to be compatible with the plotter and digitizer available at WSU. User documentation has not been developed for most of these programs. Development of documentation will be a priority activity for 1989.

The three-dimensional graphics software being developed at PNL will provide output capabilities needed for GSA research. This software will be installed at WSU as it becomes available from PNL.

Technology Transfer Through Education

In order to facilitate the transfer of the GSA system to the user community we have begun training other scientists on its utilization and capabilities. This includes presentation of the GSA methods as part of Dr. Thiessen's Geologic Remote Sensing course at WSU and in a short course on Remote Sensing for staff from Hanford's Basalt Waste Isolation Project (BWIP). The latter included production of a set of short course notes (Thiessen and Eliason, 1987). The GSA coplanar analysis techniques are specifically the basis for another short course, "Quantitative Three-dimensional Structural Techniques", which has been accepted for presentation at the 28th International Geologic Congress at Washington D.C. during July 9-19, 1989. Notes for the short course have been prepared for publication (Eliason and others, 1989). These notes will be updated as the coplanar analysis techniques are further developed. Future short courses are being planned.

PROGRAM IMPACT

The GSA research program at WSU has provided a unique opportunity for coordinating several key individual research efforts. This coordinated effort including the DOE PNL companion research is providing the opportunity to rapidly advance the state-of-the-art for quantitative determination of three-dimensional structural relationships of a region. These analysis capabilities are expected to develop into a unified spatial analysis system that will take advantage of developing computer hardware. We are looking forward to continuing this research and bringing these advanced techniques into the educational environment where the technology can be rapidly transferred to potential users.

REFERENCES

- Ader, M.J. and Springer, J.E., 1987, In Situ Stress Project Technical Report Number 1: Televiewer Data Report for the Test Interval, 6000-6250 ft., Cajon Pass Well, California: U.S. Geological Survey Open-File Report 87-289.
- Beaver, D.E., Eliason, J.R., and Thiessen, R.L., 1989, Regional Digital Analysis of Major Crustal Structures in Washington State: Proceedings of the Seventh International Conference on Basement Tectonics, in press.
- Burdick, R.G. and Speirer, R.A., 1980, Development of a Method to Detect Geologic Faults and Other Linear Features from Landsat Images: U.S. Bureau of Mines Report of Investigations 8413, 74 p.
- Eliason, J.R. and Foley, M.G., 1988, State of the Art in Geologic Spatial Analysis: Poster presented at Penrose Conference on Criteria for Establishing the Relative Timing of Pluton Emplacement and Regional Deformation, September, 1988, Mariposa, CA.
- Eliason, J.R., Foley, M.G., Foote, H.P., Beaver, D.E., Glennon, M.A., and Gerhardstein, L.H., 1988, Remote Geologic Analysis Workshop, Pacific Northwest Laboratory, Richland WA, 61 p.
- Eliason, J.R. and Landle, G.L., 1988, Geologic Spatial Analysis Program Users Guide for Digital Elevation Model Analysis Procedures for Detection of Crustal Fracture Planes: unpublished document, Washington State University, Pullman, WA, 27 p.
- Eliason, J.R., Thiessen, R.L., and Foote, H.P., 1989, Quantitative Three-Dimensional Structural Techniques: Short Course S36B Notes: Twenty-eighth International Congress, Washington, D.C., in press.
- Fehler, M., House, L., and Kaidea, H., 1987, Determining Planes Along Which Earthquakes Occur: Method and Application to Earthquakes Accompanying Hydraulic Fracturing: Journal of Geophysical Research, v. 92, p. 9407-9414.
- Foley, M.G., Beaver, D.E., Glennon, M.A., Mroz, T.H., Eliason, J.R., and Thiessen, R.L., 1988A, Application of Remote Geologic Analysis to Gas Exploration in West Virginia: Geological Society of America Abstracts with Programs, v. 20, p. A229.
- Foley, M.G., Eliason, J.R., Beaver, D.E., and Glennon, M.A., 1988B, Potential Benefits of Semiautomated, Synoptic Geologic Studies for Characterization of Hazardous Waste Sites: Proceedings, Spectrum '88, The International Topical Meeting on Nuclear and Hazardous Waste Management, Pasco, Washington, Sept. 11-15, 1988.
- Johnson, L.K., 1988, Computer Analysis of Remote Sensing and Geologic Datasets: M.S. thesis, Washington State University, Pullman, WA, 215 p.

Lutz, T.M., 1986, An Analysis of the Orientations of Large-Scale Crustal Structures: A Statistical Approach Based on Areal Distributions of Point Like Features: *Journal of Geophysical Research*, v. 91, p. 421-434.

Pratt, S., Robey, E., and Wojewodka, R., 1985, Eastern Gas Shales Geostatistical Lineament Analysis, Final Report: DOE/METC/21353-1987, U.S. Department of Energy, Morgantown Energy Technology Center, Morgantown, WV.

Springer, J.E. and Ader, M.J., 1987, In Situ Stress Project Technical Report Number 2: Televiewer Data Report for the Test Interval, 6250-6935 ft., Cajon Pass Well, California: U.S. Geological Survey Open-File Report 87-290.

Thiessen, R.L., 1986A, LINMNT: Lineament Analysis on an HP 9845: National Association of Geology Teachers Special Publication, Computer Software Designed for use in Undergraduate Education, p. 183-187.

Thiessen, R.L., 1986B, IMAGE: Digital Image Analysis on an HP 9845: National Association of Geology Teachers Special Publication, Computer Software Designed for use in Undergraduate Education, p. 188-196.

Thiessen, R.L., 1987, Lithologic Analysis of the Nevada Test Site: DIAL Symposium, Washington State University.

Thiessen, R.L. and Eliason, J.R., 1987, An Outline of Remote Sensing: Notes for Short Course Presented at Tri-Cities University Center, Richland, Washington, 126 p.

Thiessen, R.L., Eliason, J.R., Beaver, D.E., and Watkinson, A.J., 1988, Determination of Crustal Fractures in Northeastern Washington Using Geologic Analysis and Their Correlation to Mineralization Sites: Sixth Thematic Conference on Remote Sensing for Exploration Geology, Proceedings, p. 119.

Thiessen, R.L., Eliason, J.R., Johnson, L.K., Brougher, C.W., Foley, M., and Beaver, D.E., 1989, Structural Analysis of the Central Columbia Plateau Utilizing Radar, Landsat, Digital Topography, and Magnetic Data Bases: Eighth International Conference on Basement Tectonics, in review.

Thiessen, R.L., Johnson, L.K., Foote, H.P., and Eliason, J.R., 1987, Surface Reflectance Correction and Stereo Enhancement of Landsat Thematic Mapper Imagery for Structural Geologic Exploration: International Symposium on Remote Sensing of the Environment, Fifth Thematic Conference, Remote Sensing for Exploration Geology, p. 763-774.

Wadge, G. and Cross, A., 1988, Quantitative Methods for Detecting Aligned Points: An Application to the Volcanic Vents of the Michoacan-Guanajuato Volcanic Field, Mexico: *Geology*, v. 16, p. 815-818.

Watkinson, A.J. and Thiessen, R.L., 1988, Geometric Models of Folding at Loch Monar, Scotland, Using Computer Simulation: *Tectonophysics*, v. 149, p. 1-15.

Watkinson, A.J. and Thiessen, R.L., 1989, A Note on the Regional Context of the Loch Monar Synform: *Geological Magazine*, in press.

ESTIMATE OF UNOBLIGATED BALANCES

The total estimated unobligated balance for the project as of 12/6/88 is \$505.44. These funds are scheduled to be expended by the end of the program.

NOTE: DOE Report No. DOE/ER/13796-1 "Appendix C - 1988 Performance Report" was sent to BES as an appendix to the renewal proposal for the GSA project. Form 1332.16 was not submitted at that time, and so it is being included with the rest of the preprints and reprints.

END

DATE
FILMED

01/17/92

I