AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

58/13-93 J5(2)

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY,
UNDER CONTRACT DE-AC02-76-CHO-3073

PPPL-2914
UC-420,421,426,427

PPPL-2914

EVALUATION OF POTENTIAL RUNAWAY GENERATION
IN LARGE-TOKAMAK DISRUPTIONS

BY

H.H. FLEISCHMANN AND S.J. ZWEBEN

JUNE, 1993

PPPL

PRINCETON
PLASMA PHYSICS
LABORATORY

PRINCETON UNIVERSITY, PRINCETON, NEW JERSEY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

This report has been reproduced from the best available copy.
Available in paper copy and microfiche.

Number of pages in this report: 52

DOE and DOE contractors can obtain copies of this report from:

Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831;
(615) 576-8401.

This report is publicly available from the:

National Technical Information Service
Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161
(703) 487-4650

Evaluation of Potential Runaway Generation in Large-Tokamak Disruptions

H. H. Fleischmann, and S. J. Zweben

Plasma Physics Laboratory, Princeton University, Princeton, N. J. 08543
and
School of Applied and Engineering Physics, Cornell University, Ithaca, N.Y. 14853

Abstract

A detailed evaluation of various potential mechanisms for the generation of strong runaway beams during disruptions of large-tokamak devices, including TFTR, JET, DIII-D and ITER, is performed based on typical operating parameters of these devices and the presently accepted disruption model. The main results include: (i) In the existing devices, the evaporative "Dreicer" process by itself can lead to sizable runaway beams in disruptions of high-current-medium-to-low- n_e discharges. In ITER, such runaways are expected mainly for discharges with n_e values sizably smaller than the projected typical ones. (ii) Runaway generation also may occur during post-thermal-quench period through the untrapping of trapped hot-thermal electrons remaining from the pre-thermal-quench plasma; this process may be directly important in particular in disruptions of high- T_e discharges with details depending on the time required for re-closure of the magnetic surfaces. Both processes, (i) and (ii), will occur and be completed mostly during the initial few 100 μ sec after the thermal quench. (iii) Subsequently, close collisions of runaways with cold plasma electrons generally will lead to an exponential growth ("avalanching") of runaway populations generated by processes (i) and/or (ii) and/or others; this process will be effective in particular during the current quench phase and

will continue until the resulting runaway beam will carry essentially all of the remaining discharge current. In presently existing devices, possible avalanche factors of up to 10^2 - 10^5 may be expected; in ITER, avalanche factors of up to 10^{10} - 10^{15} - if not properly suppressed - are expected to lead to strong runaway beams in most disruptions, except those at particularly high densities. At the same time, avalanching will shift the main part of their energy spectrum down to relatively low energies around 10-20 MeV, and may sizably change the spatial distribution of the runaways. The behavior and decay of the generated runaway beams is to be investigated in a separate study.

List of Symbols Used

E	= B-parallel electric field
E_D	= Dreicer normalization field
f_{ee}	= $n_e e^4 \ln \Lambda / [4\pi \epsilon_0^2 (kT_e)^{3/2} m_e^{1/2}]$ = electron-electron collision frequency
f_{eo}	= $Z_{eff} f_{ee}$ = electron-ion collision frequency
$F(\tau)$	= normalized decay function of trapped hot electrons
g_o	= $(\epsilon_i - \epsilon_c)/\epsilon_i = j_{ra,o}/j_o$ = fraction of total current carried by runaways when Dreicer process stops (since ϵ falls below ϵ_c)
G	= (dn_{ra}/dt) = density rate for runaway generation
G_D	= $(dn_{ra}/dt)_D$ = rate density for Dreicer-like runaway generation
G_{coll}	= $(dn_{ra}/dt)_{coll}$ = collisional rate density for runaway generation
I_{tot}	= total discharge current
δI_{tot}	= change of total discharge current
$\langle j \rangle$	= $I_{tot}/\pi a b$ = average discharge current
j_{cr}	= $\epsilon_c(E_D/\rho)$ = critical current density below which Dreicer process effectively stops
j_o	= $(j_q \langle j \rangle)^{1/2}$ = "typical" initial current density, pertaining to pre-disruption plasma, generally used as basis for estimates
j_p	= current density carried by thermal plasma
j_q	= current density for $q(o) = 1$ on the magnetic axis
j_{ra}	= current density carried by runaways
$j_{ra,o}$	= $j_o - j_{cr}$ = runaway current when Dreicer generation of runaways effectively stops
j_{tot}	= $j_{ra} + j_p$ = total current density
n_e	= plasma density
n_{ra}	= density of runaways
P_c	= $(2m_e W_c)^{1/2}$ = electron momentum at critical Dreicer energy W_c
P_{ra}	= momentum of runaway
$P_{ra,o}$	= $j_o / e c n_e$ = percentage of relativistic runaways required for carrying full initial current density, j_o
P_{trap}	= percentage of trapped hot electrons

$p_{\text{trap},0}$ = percentage of trapped electrons just after thermal quench
 R_m = mirror ratio on field surface
 t' = time after thermal quench
 t_{acc} = $m_e c / eE$ = time required for runaways to reach relativistic speed
 t_f = time of reclosure of magnetic field lines after thermal quench
 t_{ra,j_0} = time at which n_{ra} reaches the level $n_e g_0 p_{\text{ra},0}$, at which the runaways would stop further runaway generation via the Dreicer process if they are fully relativistic
 t_{qu} = cooling time in thermal quench (generally $\sim$ few 100 μsec)
 $t_{\text{ra},0}$ = time when runaway generation via Dreicer process effectively stops (due to $\varepsilon < \varepsilon_c$)
 $t_{\text{tr},0}$ = time at which trapped percentage reaches $p_{\text{trap},0}$
 $t_{\text{trap,th}}$ = untrapping time of hot electrons having energy T_{e0} , used for normalization of untrapping times
 T_{e0} = electron temperature in predisturbance plasma
 v_{ra} = velocity of runaway
 v_t = $(2KT_e/m_e)^{1/2}$ = thermal electron velocity
 W_c = critical energy threshold for runaway generation via Dreicer process
 W_{ra} = energy of runaway
 δW_r = energy gain of relativistic electrons required for the generation of one next-generation runaway
 W_{rec} = collisional recoil energy received by plasma electron
 Z_{eff} = effective ion charge

$\alpha(Z_{\text{eff}}) = W_{c,\text{eff}}/W_c$ = correction factor for effective collisional threshold energy $W_{c,\text{eff}}$ vs. W_c (presently estimated $\alpha \sim 1-2$)
 ε = $E/E_D = KT_e/W_c$ = electric field normalized to Dreicer field
 ε_c = critical limit of ε below which direct runaway generation via Dreicer process becomes ineffective (about $\sim .025 - .03$)
 ε_i = $\rho j_0 / E_D$ = initial normalized E-field for j_0
 $\Gamma(\varepsilon)$ = $G_D / n_e f_{ee}$

- = normalized runaway generation rate for Dreicer process
(also dependent on Z_{eff})
- ρ = Spitzer-Haerm resistivity
- τ = $t'/t_{\text{trap},th}$
= time after thermal quench normalized to thermal untrapping time
- τ_{aval} = $2\alpha m_e c \ln \Lambda / eE$
= approximate exponentiation time for collisional avalanching
of relativistic runaways
- $\tau_{\text{trap}}(W)$ = exponential decay time of trapped high-energy electrons
having energy W .

I. INTRODUCTION

Runaway electrons, often with energies in the many-MeV range and sometimes carrying a large fraction of the plasma currents, have been observed in essentially all major tokamak devices and also have been analyzed theoretically (Ref.1). Earlier, attention generally has focussed on runaways generated and confined during the normal plasma discharges. Only recently, emphasis has shifted to runaways generated and/or accelerated during disruptive events in such discharges, in particular since it was realized that runaway beams carrying up to about 1/2 the normal current were generated in JET disruptions and may have produced significant damage in that device (Refs. 2); similar observations were made also on TFTR and JT-60 (Refs. 3 and 4). The generation of such runaway beams is not yet fully understood; but, based on these observations, even stronger beams with particle energies ranging up to several hundred MeV and total beam energies in the 100's MJ range have been projected for ITER, and are presently considered a potentially very serious damage source for that device (Ref. 5) as well as other future large tokamak devices.

In principle, the runaway beams observed during disruptions

might, of course, simply be remnants of runaway populations already existing before the disruption. However, this appears rather unlikely in general for various reasons: (i) Many otherwise similar non-disruptive discharges generally do not show indications of large runaway beams. (ii) The normal discharge conditions in these high- T_e devices, in particular their low loop voltage, often are not suited for the generation and acceleration of multi-MeV runaways. (iii) One would expect that most existing runaways generally will be lost from the discharge together with the hot thermal electrons due to the magnetic field perturbations existing during the initial disruption phases. (In TFTR (Ref. 13), this loss process sometimes is seen through the observance of hard-X-ray bursts just at the beginning of a disruption.)

Correspondingly, the present paper will present a systems-type analysis of the potential runaway generation in tokamak disruptions considering various mechanisms of particular importance for disruptions in large devices like TFTR, JET, DIII-D and ITER. This investigation will be based on our present understanding of the disruption physics and on the plasma parameters relevant to these large devices; on that basis, it will analyze runaway generation through three different processes, including (i) the "normal" drag-evaporation process originally investigated by Dreicer (Ref. 6) and others (Refs. 7 and 8), as well as other potential processes that are not normally considered, in particular the generation of runaways (ii) through the acceleration of trapped thermal high-energy electrons that survive the initial open-field-line phase of the disruption, and (iii) through collisions of previously generated runaways with thermal electrons (Refs. 9 and 10). Here, our study will focus mainly on the actual generation of the runaways. Questions of their subsequent acceleration and confinement, including their orbits, beam equilibria etc. - which obviously may have a significant influence on the finally observed runaway beams - will be treated only superficially; they will be the target of a subsequent, separate analysis.

The results indicate that processes (i) and (ii) alone may explain the observed strong runaway beams in some cases, with details depending on the actual plasma parameters in the post-thermal-

quench plasma. In addition, process (iii) can lead to large, avalanche-type enhancements of any existing runaway population, as well as a simultaneous sizable down-shifting of the resulting overall energy spectrum whenever processes (i) and (ii) by themselves will not lead to strong runaway beams. These latter enhancements can be expected to be particularly pronounced for the projected 20-MA discharges in ITER.

II. BASIC DISRUPTION PICTURE

As a basis for our subsequent discussions, we will briefly summarize the present, rather widely accepted, overall picture of tokamak disruptions (Refs.11, 12, 13). This picture envisions (see Fig. 1) in "Phase I" an initial growth of low (m,n) islands in the hot discharge over an extended period, leading to an overlap and reconnection of these islands. Subsequently, in Phase II, this reconnection then will result in a rapid cooling of the plasma, the so-called "thermal quench", which typically will occur over only a few hundred μ sec, most likely resulting from a streaming of the hot electrons to the wall along now open field lines. Often, in particular in high-density disruptions, some parts of this thermal quench also may be enhanced and/or even brought about through a radiational instability (Ref.14) triggered by a rapid influx of impurities. Although details are not yet well known, it appears that this process - possibly going through a brief intermediate phase at a few hundred eV (in the following called "Stage I") - will bring the plasma temperature down to well below 100 eV, probably to around 10 eV ("Stage II").

Also, the current profile generally appears to widen and flatten during the thermal quench (Ref. 13), leading to the well-known small positive (typically up to about 10%) spike in the observed plasma current lasting for about 1-2 msec (Ref. 15). In addition, transient current filaments (see Refs. 16 and 17) carrying significantly higher current densities may occur at this point.

During the subsequent "current quench" period, typically lasting from a few to about 20 msec, the total plasma current then will decay - mostly resistively with $T_e \sim 5\text{-}20$ eV (the latter as derived

by various analyses; no direct measurements seem to exist as yet) - either directly to zero, or to a new plateau, "current tail", at a level somewhere between about 10% and about 70% of the initial current I_0 . From that plateau - if so -, the current finally will decay to zero on a time scale of up to several hundred msec. It is generally assumed that the discharge current in the current tail is carried essentially completely by runaway electrons. (Ref. 2)

While recognizing its various uncertainties, we think this picture overall can provide a useful reference base for our discussion of potential runaway *generation*, i.e. of the physics mechanisms bringing these electrons to the critical energies from which they subsequently can actually "run away" to attain the projected multi-MeV energies.

Obviously, a serious question concerns the mechanism that will prevent the newly born runaways from running into the wall along stochastic field lines (as supposedly do the original hot thermal electrons during the thermal quench) before they obtain energies sufficiently large so that their drift orbits are less influenced by magnetic islands (Ref. 18). While a definite answer to this question cannot be given at this point, we notice that runaways actually are observed quite frequently in disruptions, and would like to offer a potential explanation: The original island formation generally is driven - at least in sizable part - by pressure gradients and a current density concentration in the inner, hotter parts of the discharge. After the thermal quench and the respective flattening of the current profile, these reasons for island formation have disappeared, as generally have the low- q resonant surfaces within the discharge. Correspondingly, it could be expected that the existing field perturbations will disappear - and reasonable magnetic surfaces be reestablished, probably on a resistive time scale which - near the plasma surface - could be as low as a few hundred μsec for $T_e \sim 5\text{-}10$ eV. Thus, the new runaways (gaining less than a few MeV during such time) may be prevented from hitting the wall quite soon after the thermal quench. In addition, it should be noted that at least two of the generation mechanisms discussed below - namely the Dreicer evaporation and the avalanching process - can remain active as long as plasma current densities comparable to the initial ones exist, i.e. generally for a few msec beyond the termination of the thermal quench. In addition, as shown

below, the de-trapping of trapped high-temperature electrons - in particular in combination with a subsequent avalanching - may be able to generate significant runaway currents for up to a few msec following the thermal quench.

III. RELEVANT PARAMETER REGIMES FOR LARGE TOKAMAKS

Table I summarizes the typical operating parameters of various large tokamaks which we will use for obtaining approximate values for various runaway-relevant parameters during disruptions:

The major and minor radii quoted in that Table simply refer to the vacuum vessel; the actual major radii of the plasma generally may deviate by up to about 20% both ways, while the plasma's minor radii may be smaller by up to about a factor two in some discharges. Similarly, the elongation ratios, b/a , toroidal fields, B_t , and total currents, I_{tot} , of actual plasma discharges quite often will be less than the maximum values quoted in Table I. The current density during the normal operation phase, of course, will depend on these parameters as well as the peakedness of the discharge: The two displayed current density values - j_q for $q(0) = 1$, and the "average" current density, $\langle j \rangle = I/\pi ab$, for a homogeneous current density over the entire vessel cross section - simply are derived from these machine parameters, and generally will bracket the current densities of actual full-current discharges. The presented "typical" values, j_0 , represent a geometric mean of the other two; quite interestingly, these latter values do not vary widely between the various devices. Finally, actual operational plasma densities, n_e , in these machines generally will vary over a range of up to a factor 2-5 above and below the "typical" values of Table I; in addition, it should be noted that recent preliminary experimental indications on TFTR as well as DIIID (Ref. 19) point to a general tendency of the observed line-averaged densities to rise during the initial cooling phase of the disruptions - potentially by factors of up to 2-3.

In the following, these "typical" operating values will be used as reference; any changes in the runaway-relevant parameters due to variations in actual operating parameters, as well as due to the mentioned potential rise in n_e during a disruption, can then be derived quite easily from the relevant scaling laws.

The main parameters relevant to the generation of runaways include the electron-electron collision frequency,

$$f_{ee} = n_e e^4 \ln \Lambda / [4\pi \epsilon_0^2 (kT_e)^{3/2} m_e^{1/2}],$$

of the cold thermal electrons, the electron ion collision frequency, $f_{ei} = Z_{eff} f_{ee}$, the effective B-parallel electric field component, E , and the scale time, $t_{acc} \sim m_e c / eE$, approximating the time needed for a runaway to reach near-relativistic speed. (The actual time needed to reach such speeds generally will be somewhat larger due to a decreasing $E(t)$; however, as will be seen below, E generally is not expected to decrease drastically during the time of *initial* runaway generation - through processes (i) and (ii), while changes of E during the later avalanche process are less important; thus, the above-defined t_{acc} still provides a good estimate for the relevant time scale.)

Clearly, the various parameters have to be estimated separately for both disruption stages. For this purpose, we assume the mentioned electron temperatures, namely $T_e = 300$ eV and 10 eV, and $Z_{eff} = 5$ and 3 for Stages I and II, respectively, with the latter being roughly consistent with a carbon dominated plasma at the respective electron temperatures. In addition, the quoted values for f_{ee} and f_{ei} assume plasma densities equal to the quoted "typical" operating values.

Concerning the B-parallel electric field component, E , we first note that the quoted electron collision frequencies all are high compared with the rates-of-change of current density etc.. Therefore, the electric field, E , actually seen by the electrons and relevant for runaway generation, is determined best from the electric fields needed for driving the resistive currents, i.e.,

$$E(x,t) = \rho(t)j_p(x,t) \quad (1)$$

with the current density, $j_p(x,t)$, actually carried by the thermal plasma, and the resistivity $\rho(t)$, for which the classical Spitzer resistivity is taken (Ref. 20). As a basic measure of this field, Table I shows the resulting values for $E_0 = \rho(T_e)j_0$ and t_{acc} for the given "typical" current densities, j_0 , and the assumed values of T_e and Z_{eff} . Understandably, the quoted values again vary little between the various devices, but they are very sizably different for the two stages.

IV. ANALYSES OF RUNAWAY GENERATION PROCESSES

Using the parameter values assumed or derived in Sec. III, we now will estimate the relevant time scales and relative effectiveness for each of the mentioned processes.

Basic Physics Assumptions and Equations

This analysis will be based on a zero-dimensional analysis of runaway generation in the cold post-thermal-quench plasma under the influence of the B-parallel electric field $E = \rho j_p$. The resulting runaway electrons are implicitly assumed to be confined within the plasma generating them. This assumption is justified at least during times when reasonably closed magnetic surfaces exist: Since - as outlined below - the time of actual runaway generation via processes (i) and (ii) generally appears limited to sizably less than a msec, the runaways will acquire during that time not more than about 10 MeV, and thus remain quite well bound to the flux surface of their birth. The various questions of actual runaway confinement - including orbital shift, equilibria of runaway beams, etc. - still can be expected to play a serious role during the subsequent current quench phase when the runaways may acquire the mentioned 100-MeV-type energies while I_{tot} and the confining poloidal field drop in a major way. However, as mentioned before, the present study is to focus mainly on the original

generation of runaways.

Also, we will neglect microinstabilities potentially generated by the streaming runaways (Ref. 9): While the existence of such instabilities cannot be ruled out *a priori* in all cases, their occurrence generally does not seem likely in a disruption in view of the low density of the runaways (relative to the plasma density n_e), their rather wide energy spread, and the high collisionality of the cold plasma.

In addition, we will assume that the total current density, j_{tot} , - initially fully carried by the cold plasma - will be equal to the quoted "typical" value, j_0 , just before the disruption. In case of current filamentation, any regions with higher j_{tot} can be expected to constitute particularly strong sources of runaways.

The remaining basic physics ingredients governing the generation of runaways in tokamak disruptions are sketched qualitatively in Fig. 2 and will be specified in more detail below: During the thermal quench, the electric field E first will rise with decreasing $T_e(t)$ while $j_p \sim j_{tot} \sim j_0 \sim \text{const.}$. At some time, t_1 , when E has attained a sufficient value (and the magnetic surfaces have sufficiently closed), effective runaway generation will commence. Due to their increasing population as well as velocity (before reaching relativistic speed) - the new runaways now will take over a continuously rising part, j_{ra} , of the total current, j_{tot} . This will reduce the plasma-carried current, $j_p = j_{tot} - j_{ra}$, and the effective E-field, $E = \rho j_p$; i.e., the generation of new runaways effectively chokes itself. Simultaneously, this same electric field E - being inductively supported by $-(\partial B_p / \partial t)$ - will determine the decay of the poloidal magnetic field, B_p , and of the total current density, j_{tot} . Obviously, the momentum, P_{ra} , and kinetic energy, W_{ra} , of any runaways at a given time, t' , will be determined by the electric field, $E(t)$, existing in the time interval between their "birth" as runaways and the time t' ; due to the inductive generation of that field, P_{ra} and W_{ra} will depend mainly on the effective change of the magnetic flux, $\delta\Phi$, through the runaway orbit, and thus mainly on the change of the total current, δI_{tot} . Introducing the normal inductance of the

plasma ring and the respective external equilibrium fields, one is led (see Appendix) to an energy gain of approximately 40-70 MeV for each MA of δI_{tot} , with details depending on the plasma's aspect ratio, the minor-radius position of the runaways, changes of the equilibrium field, etc.

Overall, this runaway generation process is governed by the following set of equations:

$$(i) \quad E = \rho(t)j_p \quad (2a)$$

$$(ii) \quad j_p = j_{tot} - e \int_0^{\infty} n_{ra}(P_{ra},t) v_{ra} dP_{ra} \quad (2b)$$

with v_{ra} denoting the velocity of the runaways, and with their time dependent momentum distribution, $n_{ra}(P_{ra},t)$, determined by

$$(iii) \quad (\partial n_{ra}/\partial t) + eE(\partial n_{ra}/\partial P_{ra}) = G(t)\delta(P_{ra}-P_c) \quad (2c)$$

with the critical momentum threshold, $P_c = (2m_e W_c)^{1/2}$, defined from the critical energy, W_c , (Ref. 8, see also Equ. (3a) below), and with

$$(iv) \quad G(t) = \Sigma_k G_k(E, n_e, T_e, t) \quad (2d)$$

denoting the total rate density of generation for new runaways - depending on the plasma parameters - made up by the generation rates, G_k , for the various generation processes (i)-(iii). In addition, $j_{tot}(t)$ and E , of course, are coupled through Maxwell's equations to the poloidal magnetic field distribution and its rate of change.

Using (2c) and the equation of motion for the runaways, it is easily shown that the resulting momentum spectrum of the runaways can be expressed by

$$n_r(P_r, t) = G(t''(P_r, t)) \quad (2c')$$

where t'' is the time of "birth" of the runaways that have a momentum

P_{ra} at the time t' ; in this, $t''(P_{ra}, t)$ has to be obtained from

$$P_{ra} = P_c + e \int_{t''}^{t'} E(t) dt \quad (2e)$$

Analysis of Runaway Processes

Obviously, the resulting overall runaway generation will depend critically on a quite complex interplay between the various plasma parameters and their time dependences, in particular on j_0 , $T_e(t)$, n_e etc. as well as the various G_k 's. A general analytic solution of these equations determining the important $E(t)$, and the actual runaway distribution clearly is not possible; any fully quantitative analysis will require the numerical treatment of a variety of specific cases as well as a detailed knowledge of the relevant plasma parameters.

In view of this situation, the following analysis of the relative effectiveness and time scales of the various runaway generation processes will be performed for a few idealized cases using the machine and plasma parameters quoted earlier. From this, an overall understanding will emerge from which reasonably correct gross projections of the effective runaway generation may be obtained. Although the three runaway processes (i)-(iii) generally may occur simultaneously, we will analyze them independently, and subsequently combine the results of these analyses to an overall picture.

A) "Normal" Dreicer Evaporation

As mentioned, the evaporation model of runaway generation, first pioneered by Dreicer (Ref. 6) has since been analyzed by a variety of authors (e.g. Refs. 7 and 8); here, we will essentially follow Ref. 8. All investigations consider the changes in the electronic distribution function occurring in the presence of an electric field E , and determine the generation rate of runaway electrons from the net flow of electrons across a critical energy level

$$W_C = n_e e^3 \ln \Lambda / 4\pi \epsilon_0^2 E \quad (3a)$$

$$= (E_D/E) kT_e = kT_e/\epsilon$$

containing the "Dreicer field"

$$E_D = n_e e^3 \ln \Lambda / 4\pi \epsilon_0^2 kT_e \quad (3b)$$

and the normalized electric field

$$\epsilon = E/E_D. \quad (3c)$$

where m_e , e , v_{th} denote the electrons' mass, charge, and thermal velocity $v_{th} = (2kT_e/m_e)^{1/2}$, respectively. For electrons above this energy level the electric acceleration will be larger than the average drag from electron-electron collisions. (Actually, this only applies in cases where $W_C \ll 511$ keV (Ref. 21), which, however, is well satisfied in all cases of interest here except for plasma current densities in the range $j_p < \text{a few A/cm}^2$ that are quite small compared with those of interest.)

Quite interestingly, using $E = \rho j$ with the usual Spitzer-Haerm resistivity (Ref. 20),

$$\rho = (1/\gamma_E) m_e^{1/2} Z_{eff} e^2 \ln \Lambda / 64 (2\pi)^{1/2} \epsilon_0^2 (kT_e)^{3/2}, \quad (4)$$

with $\gamma_E = .58$ and $.78$ for $Z_{eff} = 1$ and 4 , respectively, one obtains quite simply

$$\epsilon = (\pi^{1/2} / 16 \gamma_E) Z_{eff} (v_D / v_{th}) \sim (Z_{eff} / 6) (v_D / v_{th}) \quad (5)$$

where $v_D = j_p / en_e$ is the current-induced drift velocity of the thermal electrons.

The resulting runaway generation rates, $(dn_{ra}/dt)_D$, calculated by the various treatments are somewhat different (Ref. 8) - although not really significantly so: within a factor of a few, they are well

described by the formula

$$(dn_r/dt)_D = G_D(\epsilon(t)) = n_e f_{ee} \Gamma(\epsilon) \quad (6)$$

with the electron-electron collision frequency, f_{ee} , and the normalized source strength $\Gamma(\epsilon)$ which nowadays generally is written in the form (Ref. 8)

$$\Gamma(\epsilon, Z_{eff}) = K(Z_{eff}) (1/\epsilon)^{3(Z_{eff}+1)/16} \exp\{-(1/4\epsilon) - [(Z_{eff}+1)/\epsilon]^{1/2}\} \quad (7)$$

where the factor $K(Z_{eff})$ is of order unity. The function $\Gamma(\epsilon, Z_{eff})$ is reproduced in Fig. 3. Following Ref. 7, $K(Z_{eff}) = .35$ is chosen here, independent of Z_{eff} . The dashed lines represent the results of the numerical calculations of (Ref.7) as an indication of the differences between the results of the various theories. (As indicated by the difference between the numerical curve for $Z_{eff} = 10$ from that given by (7), a somewhat smaller value of K might apply for $Z_{eff} = 10$.) Also, it should be emphasized that Z_{eff} only enters through Eq.(7), while ϵ itself does not contain Z_{eff} .

Of this result, the points most salient for the present analysis are the very rapid rise of $\Gamma(\epsilon)$ by about 4 orders of magnitude within the range $\epsilon = .025 - .1$ (for $Z_{eff} = 1$) and its even faster decrease for $\epsilon \leq 0.025$ (decreasing by another factor of 30 and 10^4 for $\epsilon = .02$ and $.015$, respectively !). Inserting the actual plasma and time parameters of the experiments under consideration, we find that the runaway current, j_{ra} , created through the Dreicer process will not be able to directly contribute a significant part of the overall current, j_{tot} , whenever ϵ falls below a critical limit $\epsilon_c \sim .025-.03$; i.e., this type of runaway production will effectively cease whenever $\epsilon < \epsilon_c$. (Actually, a very similar effective lower limit of ϵ also applies to the normal high- T_e discharge where the runaway currents resulting from the time-integrated runaway rates still will remain quite small compared with the discharge current - even for discharges lasting several seconds - as long as $\epsilon < .025$.) Furthermore, we note that, due to the sharp rise of $\Gamma(\epsilon)$, the curves

for $Z_{\text{eff}} > 1$ - while sizably lower at some points - can be well represented by simply shifting the ($Z_{\text{eff}}=1$)-curve to larger ε by multiplying all ε values by about 1.2 and 1.5 for $Z_{\text{eff}} = 3$ and 10, respectively. Therefore, in view of the various theoretical and experimental uncertainties, the various relevant ε -values quoted in our following discussions mostly will refer to the ($Z_{\text{eff}}=1$)-curve of Fig. 3; for actual cases where $Z_{\text{eff}} > 1$, these ε -values will be larger by about 20 to 50% (for $Z_{\text{eff}} = 3$ and 10, respectively); obviously, this will shift the predicted effects to somewhat higher ε -values, but - due to the steepness of $\Gamma(\varepsilon)$ - otherwise essentially the same basic relationships and results are obtained. (Of course, it is again this very steep rise of Γ which renders the mentioned differences between the various theoretical calculations effectively non-significant, at least as far as the present analyses are concerned.)

Evaluation for Large Devices:

To orient the evaluation of this runaway process for large tokamak devices, the size of the relevant parameters for Stages I and II in the various devices are summarized in Table II, including an "initial normalized field",

$$\varepsilon_i = \rho j_0 / E_D, \quad (8)$$

calculated from the typical values of the initial current density, j_0 , the plasma density, n_e , and the temperature, T_e , as quoted in Table I.

Unfortunately, a general integration of the relevant equations does not seem possible even for this single generation process. Also, - as we will see below - the results will very strongly depend on the relative size of various time scales. Therefore, we will consider and evaluate a number of idealized cases: In particular, these will include - as a starting point - a Group (1) of cases where we assume that the T_e values quoted for Stages I and II - together with the respective resistivities ρ - will be attained instantaneously, i.e. on a time scale short compared with the time needed for significant runaway

generation to occur; subsequently, - in Group (2) of situations - we will consider briefly the consequences of a more realistic slower fall of T_e . In each of the two groups, we will consider three separate values of ϵ_i .

Group (1): Assuming instant drop of plasma temperature:

Assuming an instant drop in T_e , runaway generation will start with a rate determined by ϵ_i . Analyzing the ϵ_i -values given in Table II, while also noting their variability with the changes of the underlying discharge parameters (in particular densities!) as well as with changes during the thermal quench (apparent density rise!), it appears that quite generally $\epsilon_i < .025$ in Stage I (except possibly for very-low-density discharges and/or if T_e is significantly lower than 300 eV); thus, the runaway generation via this process during Stage I can be expected to be small, i.e., to lead to runaway currents, $j_{ra} \ll j_0$.

In Stage II, on the other hand, ϵ_i may fall into the critical range $\epsilon_i > .03$ (for $Z_{eff} = 3$) for a sizable range of operating parameters - in particular for full-current, low- n_e discharges. Although the details again will depend on the mentioned density rise during the thermal quench period, this conclusion appears particularly true for TFTR. The ϵ_i -value for ITER is sizably smaller, making this process less prevalent; however, it appears that densities actually used in ITER discharges may include also values sizably smaller than the rather high "typical" value presently projected for ITER in Table I.

Correspondingly, the following discussions will be limited to Stage II: Assuming that stage is reached suddenly at $t = "0"$ with $\epsilon_i > .025$, runaway generation will start from that initial value ϵ_i , and - following our earlier argument - the values of j_p , E and ϵ , then will continuously decrease due to the rising j_{ra} . Correspondingly, the generation of runaways will continuously decrease, and finally, will effectively cease when j_p falls to the critical level,

$$j_{p,cr} = \epsilon_c(E_D/\rho). \quad (9)$$

- at a time " $t_{ra,o}$ ". Since as mentioned earlier $j_{tot} \sim j_o \sim \text{const.}$, we find that the runaways - at that time - will carry a fraction

$$g_o = j_{ra,cr}/j_o = (\epsilon_i - \epsilon_c)/\epsilon_i \sim (\epsilon_i - .025)/\epsilon_i. \quad (10)$$

of the original current j_o . Clearly, this result alone could explain the sizable fractions of runaway currents observed in some disruptions.

For the following discussion of specific cases, we should note first that a very small density fraction of runaways,

$$P_{ra,j_o} = n_{ra,f}/n_e = j_o/en_e c, \quad (11)$$

will be sufficient to carry the full current density j_o whenever the runaways attain relativistic speed; taking the quoted plasma densities together with the typical current densities of Table I, we find $P_{ra,j_o} \sim 10^{-3} - 10^{-4}$ (see Table II).

Furthermore, we will have to distinguish the following times (all measured from our starting point " $t = 0$ " after the thermal quench):

- $t_{ra,c}$ = time at which the runaway population reaches a critical density, $n_{ra,c} = n_e g_o P_{ra,j_o}$, where these runaways, *if fully relativistic*, would carry the runaway current density $j_{ra,cr} = (j_o - j_{p,cr})$ that is required to stop further runaway generation; and
- $t_{ra,o}$ = time at which the runaway generation via the Dreicer process *actually will stop*.

Depending on the relationship of these times to the earlier mentioned acceleration time, t_{acc} , various cases can be distinguished:

- (i) Whenever $t_{ra,c}$ is sizably larger than t_{acc} , then most of the runaways will be at relativistic speeds when $n_{ra,c}$ is reached. Thus, further runaway generation actually will stop at that time, i.e. we will

have $t_{ra,c} = t_{ra,o}$ with most of the runaways already being relativistic.

(ii) Inversely, whenever $t_{ra,cr} \ll t_{acc}$, then the velocities of the runaways still will be badly non-relativistic at that point; in extreme cases, the energy of the runaways still might be lingering close to W_C , so that $v_{ra} \ll c$ (say $(1/10-1/20) c$). Then, we may have $j_{ra} \ll j_{ra,cr}$, and runaway generation still will continue until the runaway current - still rising due to the further increases in the population of the runaways as well as their average velocity - will reach the critical value $j_{ra,cr}$. In this case, we may expect $t_{ra,o}$ to be sizably longer than $t_{ra,cr}$.

Clearly, the actual results can be expected to depend strongly on the size of ϵ_i . Therefore, we will focus our following discussions on 3 separate situations distinguished by their values of ϵ_i , namely two extreme cases, (1a) and (1b), with small and high ϵ_i -values, respectively, and one case, (1c), for an intermediate ϵ_i :

Case (1a). for low $\Gamma(\epsilon_i) \sim (-6)$, i.e. $\epsilon_i \sim .035$ for $Z_{eff} = 1$ (or correspondingly, $\epsilon_i \sim .04$ for $Z_{eff} = 3$): In this case, the time, $t_{ra,jo}$, is relatively long. At the initial level of $\Gamma(\epsilon_i)$, this time might be approximated by

$$t_{ra,jo} \sim g_0 p_{ra,o} / f_{ee} \Gamma(\epsilon_i) = N_0 / f_{ee} \quad (12)$$

where $N_0 = g_0 p_{ra,o} / \Gamma(\epsilon_i)$ denotes the approximate required number of electron collisions for the runaway population to reach that level.

In view of the rapid decrease of the actual generation rate, this constitutes a significant underestimate; the actual value of $t_{ra,jo}$ (to reach, say, 80% or more of the needed runaway population) can be expected to be a few times longer. For the chosen $\Gamma(\epsilon_i) < 3(-7)$ and $p_{ra,o} \sim 3(-4)$, $t_{ra,cr}$ can be expected to amount to a few 1000 collision times. Although still amounting only to less than a few 100 μsec (at most), the actual times needed to reach p_{r0} thus often will be easily comparable and even larger than the t_{acc} values of Table I.

Thus, situation quite nearly corresponds to case (i) from above, with further runaway generation being stopped at that time. (As a specific example, we might consider the Stage-II case in TFTR with $\epsilon_i = .04$ (for $Z_{\text{eff}} = 3$), i.e., $\Gamma(\epsilon_i) \sim 3(-7)$, $f_{ee} = 1.6(8) \text{ sec}^{-1}$, $n_e = 4(13) \text{ cm}^{-3}$, $p_{ra,0} = 7(-4)$, and $g_0 \sim .03$, we get $t_{ra,j_0} \sim 10 \text{ } \mu\text{sec}$. Thus, the actual time for the runaway population to reach the critical level $p_{ra,0}$ will be roughly 30-40 μsec , which is quite comparable $t_{acc} \sim 27 \text{ } \mu\text{sec}$.)

Due to the shortness of the elapsed time, we actually will still have $j_{\text{tot}} \sim j_0$ (as indicated earlier) of which a part, $j_p \sim j_{cr} \sim (1 - g_0)j_0$, still is carried by the cold thermal plasma, while $j_{ra} \sim g_0 j_0$ is carried by relativistic runaways. Subsequently, the remaining j_p will decay resistively, while the runaways mainly will gain further energy without increasing their average velocity and current. Thus, assuming for the moment that all runaways remain confined till the end of the resistive phase (corresponding to the start of the "runaway tail" in the observed discharge current), then the current at the beginning of the runaway tail will be roughly equal to the initial runaway current $j_{ra} \sim g_0 j_0$. During that resistive decay phase, the runaways will acquire the very large projected energies of about 30-60 MeV for each MA of decrease between the initial discharge current and the current at the start of the runaway tail. From present, first estimates, a good confinement of these accelerating runaways by the decaying discharge current appears somewhat difficult to understand for current tails of less than about 50% of I_0 - which are often observed (except in the presence of fast-changing vertical fields). Clearly, as mentioned before, this final acceleration process will have to be studied in more detail.

Case (1b). for large $\Gamma(\epsilon_i) > 10^{-4}$, i.e. $\epsilon_i \sim .07$ (for $Z_{\text{eff}} = 1$) : As we can see from Table II, this situation may apply to disruptions of low-density discharges in TFTR, possibly also in some of the other machines (depending on the actual rise of n_e). Here, $N_0 = g_0 p_{ra,f} / \Gamma(\epsilon_i)$ will be quite small (about < 20). In this case, as seen from Tables I and II, the time $t_{ra,j_0} = N_0 / f_{ee}$ generally will be sizably shorter than t_{acc} , i.e. this situation corresponds to the case (ii) defined earlier.

From the relevant numbers, $t_{ra,j0}$ will be smaller than t_{acc} by a factor κ which may reach roughly up to $> 10-20$. Correspondingly, the generated runaways still are strongly non-relativistic ($v \sim c/(10-20)$), at that point, and further runaway generation will continue until the increasing runaway current reaches the critical level where $j_p \sim j_{cr}$. It appears that this limit is attained through the runaway population rising by somewhat less than a factor $\kappa^{1/2}$ (due to the falling $\Gamma(\epsilon)$), and its average velocity rising by somewhat more than $\kappa^{1/2}$. Correspondingly, the final runaway density percentage, $p_{ra,f}$, will exceed $p_{ra,0}$ by a factor ($\sim \kappa^{1/2}$) with the majority of the runaways still being sizably non-relativistic (roughly by a factor $1/\kappa^{1/2}$). In the extreme, i.e. when $t_{ra,j0} \ll t_{acc}$, we may get $p_{ra,f}/p_{ra,0}$ quite large, say up to 3-10, with the runaways still being equally non-relativistic. Subsequently, without further runaway generation, the remaining resistive plasma current will be further converted quickly into beam current through acceleration of the runaways, until the full discharge current is carried by the runaway beam. In view of the fact that this will necessitate only a velocity increase by a factor $\epsilon_i/(\epsilon_i - .025) = j_0/(j_0 - j_c)$ (generally < 1.5 or so), we may expect that the runaways still may be sizably non-relativistic even at that point, i.e., when the entire discharge current is transferred to the runaway beam. Pending our further studies, we may expect that the subsequent development of the generated runaway beam will depend on the gross dynamics of the decaying discharge, with various diverging sequences appearing possible. However, in view of the actually quite fall of T_e , this case probably may be realized only rarely in practice and thus not be important in reality (see later discussions).

Case (1c). for intermediate $\Gamma(\epsilon_i) \sim 10^{-5}$, i.e. $\epsilon_i \sim .05$ (for $Z_{eff} = 1$):

This case initially will develop similar to case (b): a large fraction of the runaways will still be non-relativistic, but near-relativistic, when runaway generation stops (i.e. when $\epsilon \sim \epsilon_c$); however, a large fraction of the runaways subsequently may reach relativistic speed before all of the remaining plasma current is transferred to the runaways. The final runaway beam will carry a current somewhere between $g_0 I_0$ and the full I_0 . The runaways then may be accelerated into the many-MeV range

during the resistive quench of the still remaining (if so) plasma current. Thus, the finally emerging runaway tail could be expected to show currents up to nearly the full current I_0 carried by many-MeV electrons. However, the final decay of this tail including the potential 100-MeV-type acceleration of electrons again will have to be studied further.

It should be noted that in cases (1b) and (1c) the time t_{ra,j_0} during which runaway generation occurs is shorter than in case (1a), so that the approximation $j_{tot} \sim j_0$ again is very valid throughout.

Group (2): Finite cooling time of T_e :

Finally, we will consider changes in the above conclusions related to the finite actual cooling times of the plasma when approaching Stage II. Obviously, these changes will sizably depend on the comparative time scales of: (i) the assumed, although not yet well defined, thermal-quench cooling time, $t_{qu} \sim$ "a few hundred μsec " - which determines the rise in resistivity and thus the build-up of the resistive field E - , and (ii) the time needed for the evaporative development of a sizable runaway beam which will take over some of the plasma current and thus diminish the resistive E-field. (iii), we should note that t_{qu} generally is larger than t_{acc} .

Since the time scale (ii) will depend drastically on ϵ , we will again discuss separately the three cases distinguished earlier. The earlier used parameter, $\epsilon_i = \rho(T_e \sim 10 \text{ eV})j_0/E_D$, now may no longer be reached actually in the process, but it still retains significance as the maximum possible value of ϵ ; clearly, and in agreement with our earlier conclusion, there still will not be any significant runaway generation if $\epsilon_i < .025$. Cases (2a),(2b) and (2c) are to refer to the same values of ϵ_i as the above cases (1a), (1b) and (1c), respectively.

Case (2a): According to our earlier analysis, the time scale for the development of the runaway beam in this case certainly is longer than t_{acc} , and - generally - quite comparable to or even longer than t_{qu} .

Thus, our earlier fast-drop assumption for T_e appears reasonably exact in general, and the earlier results should still hold approximately; in particular:

- (i) essentially all of the runaways will be at relativistic speeds when the evaporative runaway process effectively stops, and
- (ii) the total strength of the final evaporative runaway beam current, j_r , after the resistive decay of the remaining plasma current will be roughly as given in Equ. (8), i.e., $j_{ra} \sim g_0 j_0$, and this runaway beam may attain the envisioned 100-MeV-type energies in the subsequent resistive quench;
- (iii) the entire evaporative runaway generation will occur within a few 100 μ sec to at most a msec (so that still $j_{tot} \sim j_0 \sim \text{const.}$ during the generation of the runaways).

Case (2b): In this case, the earlier derived times for the runaway population to reach $p_{ra,0}$ as well as those needed for cutting off further runaway generation generally are sizably shorter than t_{qu} . Thus, our earlier assumption clearly will break down - except possibly if the risetimes of E actually are much faster, e.g. via a fast current filamentation process. Instead of E and ϵ advancing "suddenly" to their full potential values, $E_i = p j_0$ and ϵ_i , the actual dependencies $E(t) = p(t) j_p(t)$ and $\epsilon(t)$ now will be determined by an interplay between the rising $p(t)$ and the emerging runaway currents. In particular one can expect the following sequence:

- (i) $E(t)$ and $\epsilon(t)$ first will increase according to the $T_e(t)$ of the thermal quench until $\epsilon \sim .025$;
- (ii) subsequently, the further increases of $E(t)$ and $\epsilon(t)$ driven by the continuing drop in $T_e(t)$ will be strongly mitigated by the reduction of the plasma current $j_p(t) = j_0 - j_{ra}(t)$ due to the developing runaway current $j_{ra}(t)$;
- (iii) then, E and ϵ will reach maxima - where the further rise of these parameters driven by the falling T_e is balanced by the increasing $j_{ra}(t)$; clearly, this generally will occur somewhere at intermediate values of ϵ (see Case (1c)) where the time scales for runaway production and acceleration become comparable to t_{qu} ;

(iv) finally, E and ϵ will fall again, and evaporative runaway generation will stop when $\epsilon \sim .025$.

The details of this process and the resulting final runaway distribution will depend on the details of $T_e(t)$ etc. and will have to be analyzed numerically. However, since generally $t_{acc} < t_{qu} \sim \text{few } 100 \mu\text{sec}$, it appears that a major part of the runaways again will have reached relativistic speeds when ϵ again has decayed to $\epsilon \sim \epsilon_c$. Thus, depending on the ratio t_{acc}/t_{qu} , the resulting runaway beams probably are comparable to the results projected earlier for the Cases (1a) or (1c).

Intermediate Case (2c): With the ϵ_i values reduced from case (2b), but still with $t_{acc} < t_{qu}$, the final runaway beam will be even closer to that of Case (1a).

In all these cases, the results will be shifted more towards those of Cases (1c) or (1b) with instantaneous T_e drop, if the effective timescale of the final thermal quench to 10 eV turns out to be significantly faster than the presently projected few 100 μsec , or in case of fast filamentations.

Summary for Dreicer Process:

Overall, we conclude that the Dreicer process by itself can lead to relativistic runaway beams carrying a significant fraction of the initial discharge current, I_0 , whenever $\epsilon_i \sim > .025$; and, that this situation may occur for a significant range of full-current-low-to-medium- n_e discharges in all present large tokamaks - even if the mentioned density build-up in disruptions is as projected. However, this ϵ -limit generally will not be reached in most high- n_e discharges. In ITER, this process appears less effective in view of the projected lower j_0 values and the generally higher n_e in that device; however, the required ϵ -limit still may be reached even in that device in discharges with lower-than-projected n_e .

Furthermore, as indicated, whenever evaporative runaway generation occurs, most of this generation is expected to occur during the first few hundred μsec following the thermal quench and the reclosure of the magnetic surfaces. During that time, the energy gained by the runaways generally will be in the low-10-MeV range; the main energy gain normally will occur during the subsequent current quench which is to be investigated separately later.

(B) Runaway Generation from the De-Trapping of Trapped High-Temperature Electrons Surviving the Thermal Quench

According to our earlier disruption model, the thermal quench - at least in major part - results from the escape of the hot thermal electrons to the wall by streaming along the now open field lines. Although possibly needing some smaller modifications (e.g. including a bubble-like gross motion (Ref. 13) of the inner plasma parts to the surface which would reduce the required radial magnetic fluctuation fields, δB_r , to a level nearer to the observed levels), this picture basically appears well founded. However, it obviously applies only to passing hot electrons, while trapped hot electrons may be retained in the disruptions. If these hot trapped electrons are not lost in some other way (e.g. by diffusion - which does not seem likely) some of them may survive in the trapped state until after the re-establishment of magnetic surfaces. In that case, these electrons generally will run away whenever they become untrapped since their energy, $W_e > T_{e0}$, easily exceeds the rather low critical energy, $W_C < 1 \text{ keV}$ at $T_e \sim 10 \text{ eV}$. (With T_{e0} denoting the hot temperature of the pre-disruption plasma, the condition, $W_C < \text{few } T_{e0}$, sometimes may be satisfied also under the conditions of Stage I; i.e., runaway generation via untrapping could occur already in Stage I, if - against general expectations - surface reclosure becomes effective that early.)

In order for this process to be directly important (i.e. without the additional avalanching considered below), the percentage of trapped electrons, $p_{\text{trap}}(t_C)$, still remaining at the time, t_f , of field closure has

to be at least comparable to the earlier defined ratio $p_{ra,o}$, i.e. we need

$$p_{trap}(t_f) = n_{trap}/n_e \sim p_{ra,o}. \quad (13)$$

For a first estimate of the potential effectiveness of that process, we will now consider the purely collisional decay of the trapped hot electron population: According to Ref. 22, the lowest-order eigenmode of an electron population of energy W trapped by a mirror ratio, R_m , will decay exponentially due to collisions with the ions and electrons of the cold post-thermal-quench background plasma. (This projection neglects the energy diffusion of the electrons, which however will not significantly change the results for most situations.) While the various calculations vary by about a factor 2 (Ref.22), the exponential decay constant, $\tau_{trap}(W)$, for an electron having an energy, W , trapped in a field with mirror ratio, R_m , is approximately equal

$$\begin{aligned} \tau_{trap}(W) &\sim 3.5 \log_{10}(R_m) 4\pi\epsilon_0^2 W^{3/2} m_e^{1/2} / (Z_{eff}+1) n_e e^4 \ln\Lambda \\ &\sim 1.5 \ln(R_m) (W/kT_{eo})^{3/2} / (Z_{eff}+1) f_{ee}(T_{eo}) \end{aligned} \quad (14)$$

with the electron-electron collision frequency, $f_{ee}(T_{eo})$, at the temperature, T_{eo} , although with the $\ln\Lambda$ and the Z_{eff} of the cold plasma. Taking the effective mirror ratio of a flux line having a minor radius r

$$R_m \sim 1 + 2 (r/R), \quad (15)$$

one obtains approximately

$$\begin{aligned} \tau_{trap}(W) &\sim 3(r/R) (W/kT_{eo})^{3/2} / (Z_{eff}+1) f_{ee}(T_{eo}) \\ &= (W/kT_{eo})^{3/2} \tau_{trap,th} \end{aligned} \quad (16)$$

with

$$t_{trap,th} = 3(r/R) t_2(T_{eo}) \quad (17a)$$

and

$$t_2 = 1/(Z_{eff}+1) f_{ee}(T_{eo}). \quad (17b)$$

The total initial population of the lowest-order mode at an energy, W , will be approximately equal to the population fraction of thermal electrons having an energy W that is trapped in the pre-thermal-quench discharge. The fraction, $P_{\text{trap},0}$, of trapped electrons will be independent of W , but will vary with the minor radius due to its dependence on the mirror ratio, R_m . In the following, we will assume a "typical" value

$$P_{\text{trap},0} \sim 30 \% \quad (18)$$

Assuming a fully thermalized hot-electron distribution in the initial pre-disruption plasma, we then find that - at a time t' after the untrapped electrons have left - the total percentage, $P_{\text{trap}}(t')$, of still remaining trapped electrons (relative to the initial density n_e) will be approximately given by

$$\begin{aligned} P_{\text{trap}}(t') &= n_{\text{trap}}(t')/n_e = \\ &= P_{\text{trap},0} (4/\pi)^{1/2} \int_0^{\infty} x^{1/2} \exp[-x-(\tau/x^{3/2})] dx \quad (19a) \\ &= P_{\text{trap},0} F(\tau) \end{aligned}$$

with

$$F(\tau) = (4/\pi)^{1/2} \int_0^{\infty} x^{1/2} \exp[-x-(\tau/x^{3/2})] dx \quad (19b)$$

where $x = W/kT$, and where the time $\tau = t'/t_{\text{trap},th}$ is normalized to the untrapping time, $\tau_{\text{trap},th}$, for a thermal electron at $W = T_{e0}$.

For evaluation, we calculated the function $F(\tau)$ numerically for values $\tau \leq 100$; for $\tau > 50$, an asymptotic approximation (good to $< 20\text{-}30\%$) was obtained through first expanding the integrand of Eq.(19) around the minimum, $x_m = (3\tau/2)^{2/5}$, of the exponent $(x+\tau/x^{3/2})$, and then integrating it, with the result:

$$F(\tau > 100) \sim 2(8/15)^{1/2} (x_m^{3/2}/\kappa^{1/2}) \exp[-(x_m + \kappa)] \quad (20a)$$

with

$$\kappa = \tau/x_m^{3/2}. \quad (20b)$$

The numerical results together with those of Eq. (20) are graphed in Fig. 3.

The critical lower limit of trapped-electron percentage given by Eq. (13), is reached at a normalized time, $\tau_{f,0}$, when

$$F(\tau_{f,0}) \sim P_{ra,0}/P_{trap,0}. \quad (21)$$

Whenever the actual field closure time, t_f , exceeds the limit, $t_{f,0} \sim \tau_{f,0} t_{trap,th}$, the number of trapped electrons quite rapidly will become insufficient to directly create strong runaway beams.

The normalized $\tau_{f,0}$ -values relevant to the various machines are given in Table III together with the corresponding absolute critical time $t_{f,0} = \tau_{f,0} t_{trap,th}$. As mentioned, a typical value of $P_{trap,0} = 30\%$ was used for deriving the quoted $\tau_{f,0}$ -values; due to the steep decay of $F(\tau)$, the influence of realistic variations in $P_{trap,0}$ over the plasma cross section is not really significant at this point (except very near to the magnetic axis). On the other hand, the change of the scale time, $t_{trap,th}$, over the plasma cross section - due to its proportionality with (r/R) - will be more serious (being longest for $r = a$); the values given in Table III assume a typical radius, $r = (2/3)a$.

Overall, considering the results of Table III, it appears that this process normally will be directly effective - i.e. without additional avalanching - in disruptions of discharges with a predisruption $T_e < 5$ keV only for rather short magnetic reclosure times, $t_f < .5$ msec after the thermal quench, except possibly for very low n_e . (This result is particularly true if we accept a further density rise of a factor 2-3 during the disruption.) However, the permissible reconnection times will reach into the more realistic msec range in disruptions of discharges with $T_e \sim 15$ keV, even at typical n_e values. Correspondingly, this process generally may not be really significant by itself in the present devices; however, it may become so in high- T_e -medium- n_e discharges in ITER - depending on the actual reclosure times. Obviously,

the effectiveness of this process also will be increased whenever the high-energy tail of the electron distribution (in particular around or above $x_m T_{e0} \sim (8-10)T_{e0}$) is enhanced, e.g. through current drive, *if* at least a part of these electrons becomes trapped. In addition, the runaway generation via this process generally will be stronger at the outer radii, r , of the disruption rather than the center; as mentioned, our estimates assumed $r/a = 2/3$. Correspondingly, this runaway generation also will depend on the radial temperature profile, $T_{e0}(r)$, and may be influenced by any bubble-like motion.

Finally, we might note already, that the collisional avalanching discussed in the next section may sizably reduce the sensitivity limit Eq. (13), and thus extend the permissible delay time, τ_0 , between the thermal quench and the magnetic reclosure.

(C) Collisional Avalanching of Runaways

As indicated earlier, any thermal plasma electron acquiring a recoil energy $W_{rec} > W_C$ from a close collision with an existing runaway will have a good probability of becoming a new secondary runaway. Since this generation is proportional to the number of already existing runaways, it can lead to an exponential build-up of the runaway population. A more cursory earlier study (Ref. 9) - based on an investigation of the Focker-Planck equation - judged this process "negligible". Actually, however, this process can play a very important role in large-tokamak disruptions (Ref. 10). Re-analyzing and evaluating the process in more detail through considering directly the total cross section for the creation of a recoil electron with an energy $W_{rec} \geq W_C$ in close collisions between existing runaways and cold plasma electrons, and assuming $W_C \ll m_e c^2$, we found a collisional generation rate for runaways

$$(22) \quad (dn_{ra}/dt)_{coll} = (eE/2m_e \ln \Lambda) [1/\alpha(Z_{eff})] (1/v_{ra}) n_{ra}$$

with v_{ra} , n_{ra} denoting, respectively, the velocity and density of the

existing runaways; the factor $\alpha(Z_{\text{eff}})$ (determining the effective cutoff energy, αW_c , for collisional runaway generation) presently is estimated between 1-2 for $Z_{\text{eff}} = 1 - 5$, but this will need to be determined more carefully. As shown in Ref. 10, the number of next-generation runaways produced by each runaway before it reaches relativistic velocities actually is quite small (about $\leq .1$). However, after becoming relativistic, each runaway will collisionally generate one new next-generation runaway for each energy

$$\delta W_r = 2mc^2 \alpha(Z_{\text{eff}}) \ln \Lambda \sim 15 \alpha \text{ [MeV]} \quad (23)$$

it gains from the electric field (independent of any simultaneous energy losses the runaway may encounter during this time, e.g. through synchrotron radiation!). As indicated by Eq. (23), δW_r is largely independent of E and of all plasma parameters (*except* through the dependencies of $\ln \Lambda$ and α); this independence will break down, and $(dn_{ra}/dt)_{\text{coll}}$ will disappear only, whenever $W_c \sim m_e c^2$. That latter condition - simultaneously leading also to the collisional slowdown of any already existing relativistic runaways - can be satisfied quite easily in some high- T_e -high- n_e regimes of normal large-tokamak discharges; however, in a post-thermal-quench disruption it will occur only for uninterestingly small plasma current densities $j_p < \text{few A/cm}^2$.

Whenever the runaways are fully confined, such collisional multiplication will lead to an exponential rise of the runaway population in a plasma

$$n_{ra}(t) \sim n_{ra,0} \exp(t/\tau_{\text{aval}}) \quad (24)$$

with the exponentiation time, $\tau_{\text{aval}} \sim 2\alpha m_e c \ln \Lambda / eE$, being equal to the time during which a relativistic runaway picks up the energy δW_r . Of course, an incomplete confinement of the runaways will lead to a reduction of this growth rate. Assuming an average confinement time τ_{conf} , one obtains an effective growth time,

$$\tau_{\text{eff}} \sim \tau_{\text{aval}} \tau_{\text{conf}} / (\tau_{\text{conf}} - \tau_{\text{aval}}), \quad (25)$$

which, of course, becomes negative whenever $\tau_{\text{conf}} < \tau_{\text{aval}}$.

Obviously, the runaways generated by this process will contribute as any others to the total runaway current reducing the remaining plasma current, j_p . However, this multiplication process will stop only when $W_c \sim m_e c^2$, i.e. when the thermal plasma current, j_p , is reduced to a few A/cm².

Overall, the following conclusions can be drawn regarding the effectiveness of the collisional avalanching in post-thermal-quench disruptions:

(a) Time of avalanching: Generally, τ_{aval} will be longer than the initial few hundred μsec after the thermal quench where processes (i) and (ii) are most active; i.e., the energy gain of runaways during that time is smaller than or at most comparable to δW_r . Correspondingly, relatively little avalanching will occur during that time; most of the avalanching will occur during the subsequent current quench phase.

(b) Size of avalanche enhancements: Avalanche enhancements of the runaway population during the current quench phase of the disruption can be very sizable. According to the general estimate of (30-50) MEV/MA, the runaways may gain during that phase as much as $(2-3)\delta W_r$ for each MA of decrease in I_{tot} . Thus, if properly confined, the population of relativistic runaways will grow by up to about an order of magnitude for every (1-1.5) MA of δI_{tot} . While the confinement question will have to be studied in more detail later, it appears at present that the orbits of accelerated runaways normally might be confined in the decaying disruption quite well until I_{tot} decays to about (1/2) - (1/3) of the value it had when the respective runaways were "born". Thus, in the existing large tokamak devices having $I_{\text{tot}} \sim \text{few MA}$, the avalanche growth rates generally will not be significantly reduced by non-confinement of the runaways. Correspondingly, collisional avalanching may increase the runaway population originally generated by the other

processes by a factor of 100-1000 in the existing devices.

In a device like ITER with $I_{tot} \sim 22$ MA, our analysis leads to even larger avalanche factors of up to roughly $10^{10} - 10^{15}$ - if the avalanche process cannot be properly suppressed. Since about $2 \times 10^{10} \text{ cm}^{-3}$ of relativistic runaways will suffice to carry the usual 100 A/cm^2 , an exceedingly small initial runaway population (a few per cm^3 , or even less!) remaining from the original discharge, or created by other the processes may thus be amplified into runaway beams carrying sizable fractions of the initial plasma current.

Since avalanching simply will amplify the runaway populations generated by the other processes (as well as any runaways surviving the initial magnetic disturbances), it will effectively widen the ranges of plasma parameters for which strong runaway beams may be expected due to the other processes-plus-avalanching. In presently existing machines (TFTR, JET, DIID etc.), the critical minimum field, ϵ_c , for which runaway generation through the evaporative process can be observed, generally will be shifted down to about $\epsilon_c \sim .02$ (for $Z_{eff} = 1$), in more extreme cases maybe down to about .015. This will widen the range of operating parameters where disruption runaways can be expected; however, considering the range of n_e and T_e generally encountered in these devices, such a change still may not be really important overall. In ITER, however, avalanching may shift ϵ_c down to $\sim .006-.01$, so that sizable runaway beams may result even close to or at its projected large "typical" densities, n_e . Thus, it can be expected that runaway beams may prove to be much more common in ITER than in the smaller devices.

For runaway seeding via trapped thermal electrons - if such trapped electrons can survive the thermal quench at all -, the estimated avalanche enhancements will lengthen the permissible time limit for reconnection by a factor of 1-2 over the values given in Table III for the present machines. In even larger machines, like ITER, avalanching could easily stretch the time limit to several msec, so that runaway generation through untrapping and subsequent avalanching could become quite universal, except if the times needed for cooling and re-

connection will be much larger than that.

(c) Change in energy spectrum: Whenever such avalanching occurs, the energy spectrum of the runaways will be strongly influenced. Assuming full confinement and no energy losses of the runaways, the energy distribution of the runaways will be about proportional to $\exp[-W/\delta W_c]$ up to a maximum energy, $W_{\max}$, which is determined by δl_{tot} ; in a more realistic runaway confinement, the distribution may be cut off at a lower maximum energy and/or the exponential decrease may be sharpened (depending on the confinement details). In all cases, however, the majority of the runaways will be at quite low energies $\leq 10\text{-}20$ MeV.

(d) Changes in spatial distribution: Avalanching also can seriously change the spatial distribution of the runaways in the decaying disruption: Since the collisional generation of runaways will preferentially occur in the higher-density center of the discharge, and since the drift-related outward shift of 15-25 MeV electrons normally is quite small in the large tokamaks of interest here, it appears that the overall outward shift of the resulting total runaway beams could be much smaller than the increasing energy W_r of the initial seed runaways would require. Obviously, this result in particular together with (c) - might explain the quite frequent observation of apparent runaway damage on the inside limiter which is quite difficult to understand for 100's-MeV-type runaways.

(e) Influence on runaway current tails: It appears that avalanching also could seriously influence the decay and behavior of the runaway tails of the disruption whenever the decay rates become sufficiently large so that $\delta W_c < m_e c^2$. Clearly, this effect will require further attention in our subsequent study.

SUMMARY

Overall, the results may be summarized as follows:

(i) The usual evaporative "Dreicer" process by itself can quite easily generate sizable runaway beams in the existing devices, in

particular during disruptions of high-current-medium-to-low- n_e discharges. In ITER, such disruption runaways are expected to be limited mostly to discharges with n_e values sizably smaller than the projected typical ones.

(ii) The effectiveness of runaway generation through the untrapping of trapped hot-thermal electrons remaining from the pre-thermal-quench plasma will depend on the actual timed delay between the thermal quench and the reclosure of the magnetic field lines. In general, we expect that this process will not be important by itself in the present devices having $T_{e0} < 5$ keV; however, it might become effective in disruptions of the high- T_e and/or low- n_e discharges expected for ITER.

(iii) Both processes, (i) and (ii), will occur and be completed mostly during the initial few 100 μ sec after the thermal quench.

(iv) During the subsequent resistive quench period, collisional avalanching generally will generate a pronounced exponential growth of any runaway populations generated by processes (i) and/or (ii) and/or others, with an order-of-magnitude growth in runaway population generally occurring for about each 1-1.5 MA of drop in the discharge current. If sufficient numbers of runaways are generated initially, then this process will proceed until the resulting runaway beam will carry essentially all of the remaining discharge current. Maximum expected avalanche factors of up to 10^2 - 10^5 in the present devices will only slightly extend the range of operating parameters for which runaways may be expected; however, the very large avalanche factors of up to 10^{10} - 10^{15} - if avalanching is not properly suppressed - expected for ITER may lead to strong runaway beams over a sizable range of disruption parameters, except possibly those at particularly high densities.

(v) While strongly enhancing the strength of any runaway beams, avalanching will shift the main part of their energy spectrum down to relatively low energies around 10-20 MeV. Also, it may significantly influence the position of the runaway beams within the disrupting discharge.

The behavior and decay of the generated runaway beams is to be investigated in a separate study.

ACKNOWLEDGEMENTS:

A large part of this work was performed at PPPL during two summer and part-sabbatical visits of one of us (H. H. F.) with the financial support by PPPL. The authors would like to express their thanks in particular to Drs. K. M. Young, D. E. Post, K. M. McGuire, and D. M. Meade for their kind support and encouragement. Also, we would like to thank them as well as many other PPPL personnel, in particular Drs. M. G. Bell, E. D. Fredrickson, K. W. Hill, A. C. Janos, D. W. Johnson, D. Mansfield, S. Medley, R. Nafzikian, and J. F. Schivell, and Dr. A. G. Kellman of GA Technologies for numerous conversations contributing to the paper. The work was performed under the auspices of the Department of Energy under Contracts DE-AC02-76-CHO-3073 and, in part, DE-FG02-92-ER54183.

REFERENCES

- (1) For a review of early data, see H. Knoepfel and D. A. Spong, Nucl. Fusion, 19, 785 (1979);
- (2) O. N. Jarvis, G. Sadler, and J. L. Thompson, Nucl. Fusion 28, 1981 (1988)
- (3) G. W. Barnes, A. Janos, D. Losser, D. K. Owens and M. Ulrickson, Fusion Technol., 19, 1761 (1991)
- (4) H. Takatsu et al., Proc. Symposium on Nuclear Fusion Technology, Tokyo (1988);
- (5) K. A. Niemer, C. D. Groessmann, J. G. Gilligan, and H. H. Bolt, Proc. 13th Symposium on Fusion Engineering, Knoxville, TN, October 1989, p. 941; and A. J. Russo, Nucl. Fusion 31, 117 (1991) ;
- (6) H. Dreicer, Phys. Rev. 117, 329 (1960);
- (7) R. M. Kulsrud, Y. C. Sun, N. K. Windsor, and H. A. Fallon, Phys. Rev. Lett. 31, 690 (1973);
- (8) V. V. Parail and O. P. Pogutse, in REVIEWS OF PLASMA PHYSICS, Vol. 11, Consultants Bureau, New York, 1986, p. 1;
- (9) E. R. Harrison, Nucl. Energy, Part C, 1, 105 (1960) and ibid. 4, 7 (1962);
- (10) R. Jayakumar, H. H. Fleischmann, and S. J. Zweben, to be published in Phys. Letters;
- (11) K. McGuire et al., J. Nucl. Mater. 121, 329 (1984);
- (12) J. A. Wesson, R. D. Gill, et al., Nucl. Fusion, 29, 641 (1989);
- (13) E. D. Fredrickson, K. McGuire, M. Bell, C. E. Bush, A. Cavallo, R.

Budny A. Janos, D. Mansfield, Y. Nagayama, H. Park, J. Schivell, G. Taylor, M. C. Zarnsdorff, and J. Drake and R. Kleva, Princeton Plasma Physics Laboratory Report, PPPL 2785 (January 1992); and E. D. Fredrickson, K. McGuire et al., Rev. Sci. Instr. 59, 1797 (1988);

- (14) P. E. Stott, Nucl. Fusion, 28, 1469 (1988); and A. Gibson, Nucl. Fusion, 16, 546 (1976);
- (15) J. A. Wesson, D. J. Ward, M. N. Rosenbluth, Nucl. Fusion 30, 1011 (1990);
- (16) A. Bondeson, R. D. Parker, M. Hugon, and P. Smeulders, Nucl. Fusion, 31, 1695(1991);
- (17) G. Waidmann and G. Kuang, Nucl. Fusion 32, 645 (1992);
- (18) S. J. Zweben. B. V. Waddell, D. W. Swain, and H. H. Fleischmann, Nucl. Fusion, 20, 477 (1980); and H. E. Mynick and R. E. Duvall, Phys. Fluids, B1, 750 (1980);
- (19) A. G. Kellmann, private communication.
- (20) L. Spitzer, Jr., *Physics of Ionized Gases*, Interscience Publishers, New York, 1962 (p. 139);
- (21) J. W. Connor, R. I. Hastie, Nucl. Fusion, 15, 415 (1975);
- (22) R. F. Post, Nucl. Fusion, 27, 1577 (1987).

Figure Captions:

FIG.1: Qualitative changes of discharge current, $I(t)$, and electron temperature $T_e(t)$, during a disruption. (Time window shown is of the order of 10-20 msec)

Fig. 2 Qualitative time dependencies of total current density, j_t , plasma current, j_p , the B-parallel electric field, E , and the current densities, j_p and j_{ra} , carried by the cold plasma and the generated runaways, respectively.

Fig. 3 Normalized runaway generation rate, $\Gamma(\epsilon)$, via Dreicer evaporation from Eq. (7) (Ref. 8) for $Z= 1, 3, 10$. Dashed lines denote numerical results from Ref. 7.

Fig. 4 Normalized decay function $F(\tau)$ for percentage of trapped post-quench thermal electrons.

TABLE CAPTIONS:

TABLE I: Basic Plasma Parameters for Large Tokamak Devices

TABLE II: Normalized parameters and relativistic-runaway percentage, $P_{ra,o}$, required for carrying full j_o (see Eq. (11)) - for various machines as derived from parameters of Table I.

TABLE III: Parameters relevant for runaway generation via trapped hot thermal electrons.

TABLE I:

PARAMETERS	TFTR	JET	DIID	ITER
<u>Machine:</u>				
Major Radius, R [m]	2.6	3	1.7	6
Minor Radius, a [m]	1.0	1.1	0.65	2.15
Elongation, b/a	1	2	2	2
Max. B _{tor} [T]	5	3.5	2	5
<u>Operating:</u>				
Max. Current, I ₀ [MA]	2.5	6	2	22
Current Density [A/cm ²]				
j _q (q ₀ =1)	310	190	190	130
<j>	80	80	75	75
"typical", j ₀	160	120	120	100
Plasma Density, n _e [cm ⁻³]				
"typical"	4(13)	5(13)	7(13)	10(13)
<u>Runaway-Relevant Plasma Parameters During Disruptions:</u>				
<u>Stage I</u> (T _e = 300 eV, Z _{eff} = 5):				
El. Coll. Frequ. f _{ee} [sec ⁻¹]	1.4(6)	1.7(6)	2.5(6)	3.5(6)
f _{eo} = Z _{eff} f _{ee} [sec ⁻¹]	7(6)	8.8(6)	1.2(7)	1.8(7)
El. Field E ₀ [V/cm]	10(-3)	7(-3)	7(-3)	6(-3)
Time-to-Relat. t _{acc} [sec]	1.7(-3)	2.4(-3)	2.3(-3)	2.6(-3)
<u>Stage II</u> (T _e = 10 eV, Z _{eff} = 3):				
El. Coll. Frequ. f _{ee} [sec ⁻¹]	1.6(8)	2(8)	3(8)	5(8)
f _{eo} = Z _{eff} f _{eo} [sec ⁻¹]	5(8)	6(8)	9(8)	1.2(9)
El. Field E ₀ [V/cm]	.8	.6	.6	.55
Time-to-Relat. t _{acc} [sec]	2.1(-5)	2.7(-5)	2.5(-5)	3.2(-5)

TABLE II

PARAMETERS	TFTR	JET	DIID	ITER
p_{r0} (see Equ. (11))	7(-4)	4.4(-4)	3.4(-4)	2(-4)
<u>Stage I:</u>				
Dreicer Field, E_D [V/cm]	.58	.72	1.0	1.4
Critical energy, W_C [keV]	17	29	40	70
Initial Normalized Field, ϵ_i	.017	.011	.008	.005
<u>Stage II:</u>				
Dreicer Field, E_D [V/cm]	12	15	21	31
Critical energy, W_C [keV]	.17	.27	.35	.6
Initial Normalized Field, ϵ_i	.06	.038	.028	.017

TABLE II : Normalized field parameters and required runaway density, p_{r0} , (see Eq. (11)) for various machines as derived from parameters of Table I.

Table III: Parameters relevant for runaway generation via trapped hot thermal electrons

PARAMETERS	TFTR	JET	DIII-D	ITER
$P_{ra,o}$	7(-4)	4.4(-4)	3.4(-4)	2(-4)
$P_{trap,o}$ (assumed)	.3	.3	.3	.3
Normal. Time Limit $\tau_{f,o}$ (Eq. (21))	43	50	52	62
$T_{eo} = 5$ keV				
$t_{trap,th}$ [μ sec]	13	10	7.4	5
$t_{f,o}$ [msec]	.6	.5	.4	.3
$T_{eo} = 10$ keV				
$t_{trap,th}$ [μ sec]	37	28	21	14
$t_{f,o}$ [msec]	1.6	1.4	1	.8
$T_{eo} = 15$ keV				
$t_{trap,th}$ [μ sec]	70	50	40	25
t_c [msec]	2.9	2.6	2.0	1.6

Appendix

Gross Estimate of Potential Energy Gains of Runaways in Disruptions

In the following, we will summarize the basis for the potential energy gains of "30-60 MeV/MA" used earlier in the paper. In this, we will limit ourselves to a gross estimate of the approximate range of energy gains to be expected in large-tokamak disruptions. The actual energy gains in each case obviously will depend on the drop in discharge current as well as various details of discharge parameters and particle orbits which may vary from one device and discharge to another; although some of the numbers used below are taken from TFTR, it appears that they are not drastically different in other machines - except possibly in a redesigned ITER. Overall, it appears that the drop in discharge current is the main determinant.

For relativistic electrons, the rate of energy gain, $dW/dt = e E c$, is determined by the electric field, $E \sim V_{loop}/2\pi R$, where the overall loop voltage contains three main parts:

$$V_{loop} \sim d(L_{dis}I_{tot})/dt - d(\pi R^2 B_{vert})/dt - V_{ohm}$$

with L_{dis} = discharge self-inductance, B_{vert} = vertical magnetic field, and V_{ohm} = voltage induced by ohmic transformer. Integrating over time, each of the three components will contribute to the overall energy gain

$$\delta W \sim \delta W_{ind} + \delta W_{vert} + \delta W_{ohm}$$

These contributions will be estimated in the following

(a) Self-Inductive Energy Gains. δW_{ind} :

The effective self-inductance seen by a runaway depends on the shape parameters of the discharge and the current density as well as the orbital position of the runaway within the discharge. Assuming a uniform current distribution in a plasma of major radius R and minor radius a , we approximately

$$L \sim (\mu_0/2\pi)(2\pi R)[\ln(8R/a) - 2] \sim (\mu_0/2\pi)(2\pi R)\ln(R/a)$$

and

$$\delta W_{ind}/e \sim (\mu_0/2\pi)\ln(R/a)c \delta I_p = 60 \ln(R/a) \delta I_{tot,MA} \text{ [MeV]}$$

i.e.

$$(1/e)\delta W_1/\delta I_p \sim 60 \ln(R/a) \text{ [MeV/MA]} \sim 60 - 80 \text{ [MeV/MA]}$$

for $R/a \sim 3 - 4$. (About 25% less for $b/a \sim 1.6$ In practice, this basic "inductive potential" normally is reduced somewhat by two effects:

- (i) Shielding of the discharge by the conducting vacuum wall: This will depend on the relative current disruption time, τ_{dis} , vs. the (L/R) time of the wall, τ_W , and on relative inductances of wall and discharge. For the general situation with $\tau_W/\tau_{dis} \ll 1$, one obtains a fractional reduction of δW_{ind} somewhat smaller than τ_W/τ_{dis} . For TFTR, with $\tau_W \sim 1$ msec, and a fast current decay time for 2 MA disruption of about 4 msec this reduction will amount to about 20%.
- (ii) Partial exclusion/retention of discharge flux from area around major axis (e.g. due to thick copper coils, ohmic transformer etc.): This effect probably normally does not amount to ≤ 10 %.

Considering the variations in the various parameters, a range of $\delta W_{ind}/\delta I_{tot} \sim +(45-70) \text{ MeV}$ appears a reasonable estimate overall.

(b) Energy Gain due to Vertical Field Changes:

Assuming $R \sim \text{const.}$, one obtains

$$\delta W_{vert}/e \sim (R/2) c \delta B_{vert}$$

dependent on the actual change during the disruption. Taking the

initial vertical field

$$B_{\text{vert},0} = (\mu_0/4\pi R) I_0 \{ \ln(8R/a) + \beta_{\text{pol}} + I_i/2 - 3/2 \}$$

Assuming that the disrupting discharge were retained at the original radius, R , while $I_{\text{tot}} \rightarrow 0$, with $\beta_{\text{pol}} = 0$ and $I_i \sim 1/2$, we find that the energy of the runaways would be decreased by about

$$\begin{aligned} (1/e) \delta W_{\text{vert}}/\delta I_{\text{tot}} &\sim -c (\mu_0/8\pi) \{ \ln(R/a) + .8 \} \\ &\sim -28 \text{ [MeV/MA]} \end{aligned}$$

Actually, however, it appears that the equilibrium condition generally is not maintained during the disruption - at least on TFTR. On that device, the percentage change of the vertical field current during a disruption generally is only about $1/3 - 1/2$ that of I_{tot} . Correspondingly, it seems more reasonable to approximate

$$\delta W_{\text{vert}}/\delta I_{\text{tot}} \sim -.4 \times 28 \sim -11 \text{ MeV/MA.}$$

Again, this number has to be further reduced (by about the same percentage as mentioned for δW_{ind}) due to the shielding by the resistive vacuum wall.

(c) Energy Loss due to Ohmic Transformer Voltage:

As indicated above, the final runaway energy, of course, also may be reduced by applying a proper negative voltage, V_{ohm} , on the ohmic transformer. The respective reduction is:

$$(1/e) \delta W_{\text{ohm}} = -(c/2\pi R) V_{\text{ohm}} \tau_{\text{dis}}$$

Unfortunately, this effect generally is not very significant since V_{ohm} is much smaller than the resistive loop voltage within the disruption. For example, in TFTR, $V_{\text{ohm}} \leq 100 \text{ V}$, $R = 2.5 \text{ m}$, and $\tau_{\text{dis}} \sim 4 \text{ msec}$, so that $\delta W_{\text{ohm}} \sim 8 \text{ MeV}$ which can be significant in low- I_0 discharges, but is not really important in high- I_0 discharges.

Overall Energy Gain δW_{tot} :

As evident from the above discussion, the overall energy gain of runaway electrons will be influenced by the design details of the various machines. In general, an actual overall acceleration potential of about 30-60 MeV/MA appears to be a fair approximation.

However, we should note again that this does not necessarily mean that the runaways will actually accelerate to an average or even maximum energy given by that value; instead, the final energy value will depend also on other effects, in particular on the confinement of the runaways and their potential energy losses, e.g. due to synchrotron radiation.

Fig. 1

Fig. 2

Fig. 3

Fig. 4

EXTERNAL DISTRIBUTION IN ADDITION TO UC-420

Dr. F. Paoloni, Univ. of Wollongong, AUSTRALIA
 Prof. M.H. Brennan, Univ. of Sydney, AUSTRALIA
 Plasma Research Lab., Australian Nat. Univ., AUSTRALIA
 Prof. I.R. Jones, Flinders Univ, AUSTRALIA
 Prof. F. Cap, Inst. for Theoretical Physics, AUSTRIA
 Prof. M. Heindler, Institut für Theoretische Physik, AUSTRIA
 Prof. M. Goossens, Astronomisch Instituut, BELGIUM
 Ecole Royale Militaire, Lab. de Phy. Plasmas, BELGIUM
 Commission-Europeen, DG. XII-Fusion Prog., BELGIUM
 Prof. R. Bouciqué, Rijksuniversiteit Gent, BELGIUM
 Dr. P.H. Sakanaka, Instituto Fisica, BRAZIL
 Instituto Nacional De Pesquisas Espaciais-INPE, BRAZIL
 Documents Office, Atomic Energy of Canada Ltd., CANADA
 Dr. M.P. Bachynski, MPB Technologies, Inc., CANADA
 Dr. H.M. Skarsgard, Univ. of Saskatchewan, CANADA
 Prof. J. Teichmann, Univ. of Montreal, CANADA
 Prof. S.R. Sreenivasan, Univ. of Calgary, CANADA
 Prof. T.W. Johnston, INRS-Energie, CANADA
 Dr. R. Bolton, Centre canadien de fusion magnétique, CANADA
 Dr. C.R. James,, Univ. of Alberta, CANADA
 Dr. P. Lukác, Komenského Univerzita, CZECHO-SLOVAKIA
 The Librarian, Culham Laboratory, ENGLAND
 Library, R61, Rutherford Appleton Laboratory, ENGLAND
 Mrs. S.A. Hutchinson, JET Library, ENGLAND
 Dr. S.C. Sharma, Univ. of South Pacific, FIJI ISLANDS
 P. Mähönen, Univ. of Helsinki, FINLAND
 Prof. M.N. Bussec, Ecole Polytechnique,, FRANCE
 C. Moutet, Lab. de Physique des Milieux Ionisés, FRANCE
 J. Radet, GEN/CADARACHE - Bat 506, FRANCE
 Prof. E. Economou, Univ. of Crete, GREECE
 Ms. C. Rinri, Univ. of Ioannina, GREECE
 Dr. T. Mui, Academy Bibliographic Ser., HONG KONG
 Preprint Library, Hungarian Academy of Sci., HUNGARY
 Dr. B. DasGupta, Saha Inst. of Nuclear Physics, INDIA
 Dr. P. Kaw, Inst. for Plasma Research, INDIA
 Dr. P. Rosenau, Israel Inst. of Technology, ISRAEL
 Librarian, International Center for Theo Physics, ITALY
 Miss C. De Palo, Associazione EURATOM-ENEA , ITALY
 Dr. G. Grosso, Istituto di Fisica del Plasma, ITALY
 Prof. G. Rostangni, Istituto Gas Ionizzati Del Cnr, ITALY
 Dr. H. Yamato, Toshiba Res. & Devel. Center, JAPAN
 Prof. I. Kawakami, Hiroshima Univ., JAPAN
 Prof. K. Nishikawa, Hiroshima Univ., JAPAN
 Director, Japan Atomic Energy Research Inst., JAPAN
 Prof. S. Itoh, Kyushu Univ., JAPAN
 Research Info. Ctr., National Inst. for Fusion Science, JAPAN
 Prof. S. Tanaka, Kyoto Univ., JAPAN
 Library, Kyoto Univ., JAPAN
 Prof. N. Inoue, Univ. of Tokyo, JAPAN
 Secretary, Plasma Section, Electrotechnical Lab., JAPAN
 S. Mori, Technical Advisor, JAERI, JAPAN
 Dr. O. Mitarai, Kumamoto Inst. of Technology, JAPAN
 J. Hyeon-Sook, Korea Atomic Energy Research Inst., KOREA
 D.I. Choi, The Korea Adv. Inst. of Sci. & Tech., KOREA
 Prof. B.S. Liley, Univ. of Waikato, NEW ZEALAND
 Inst of Physics, Chinese Acad Sci PEOPLE'S REP. OF CHINA
 Library, Inst. of Plasma Physics, PEOPLE'S REP. OF CHINA
 Tsinghua Univ. Library, PEOPLE'S REPUBLIC OF CHINA
 Z. Li, S.W. Inst. Physics, PEOPLE'S REPUBLIC OF CHINA
 Prof. J.A.C. Cabral, Instituto Superior Tecnico, PORTUGAL
 Dr. O. Petrus, AL I CUZA Univ., ROMANIA
 Dr. J. de Villiers, Fusion Studies, AEC, S. AFRICA
 Prof. M.A. Hellberg, Univ. of Natal, S. AFRICA
 Prof. D.E. Kim, Pohang Inst. of Sci. & Tech., SO. KOREA
 Prof. C.I.E.M.A.T, Fusion Division Library, SPAIN
 Dr. L. Stenflo, Univ. of UMEA, SWEDEN
 Library, Royal Inst. of Technology, SWEDEN
 Prof. H. Wilhelmson, Chalmers Univ. of Tech., SWEDEN
 Centre Phys. Des Plasmas, Ecole Polytech, SWITZERLAND
 Bibliotheek, Inst. Voor Plasma-Fysica, THE NETHERLANDS
 Asst. Prof. Dr. S. Cakir, Middle East Tech. Univ., TURKEY
 Dr. V.A. Glukhikh, Sci. Res. Inst. Electrophys. I Apparatus, USSR
 Dr. D.D. Ryutov, Siberian Branch of Academy of Sci., USSR
 Dr. G.A. Eliseev, I.V. Kurchatov Inst, USSR
 Librarian, The Ukr.SSR Academy of Sciences, USSR
 Dr. L.M. Kovrizhnykh, Inst. of General Physics, USSR
 Kernforschungsanlage GmbH, Zentralbibliothek, W. GERMANY
 Bibliothek, Inst. Für Plasmaforschung, W. GERMANY
 Prof. K. Schindler, Ruhr-Universität Bochum, W. GERMANY
 Dr. F. Wagner, (ASDEX), Max-Planck-Institut, W. GERMANY
 Librarian, Max-Planck-Institut, W. GERMANY
 Prof. R.K. Janev, Inst. of Physics, YUGOSLAVIA

**DATE
FILMED**

9 / 9 / 93

END