APL/JHU
EQR/78-4

Quarterly Report

ENERGY PROGRAMS

at The Johns Hopkins University Applied Physics Laboratory

OCTOBER—DECEMBER 1978

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

THE JOHNS HOPKINS UNIVERSITY ■ APPLIED PHYSICS LABORATORY
Johns Hopkins Road, Laurel, Maryland 20810

~~RESTRICTED~~ DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

FOREWORD

The Applied Physics Laboratory issues the Quarterly Report series to provide the defense establishment and the scientific community with current awareness of selected APL activities. At present, the Quarterly consists of the following volumes:

<u>Programs</u>	<u>Report Designators</u>
<u>Department of Defense Programs</u>	
Surface Missile Systems	WQR
Research and Development	RQR
Space	SQR
Exploratory Development for Missile Propulsion	DQR
<u>Civil Programs</u>	
Energy	EQR
Biomedical Research, Development, and Engineering (Annual Report)	MQR

The nomenclature for the APL Quarterly Report is as follows. The designation for Quarterly Report, "QR," is preceded in each case by a letter that indicates the volume's program area. After the "QR," a virgule is followed by a year indicator (e.g., "77-") and a number from 1 to 4 to specify the calendar quarter.

The format is flexibly designed so that most technical articles can be presented on a single sheet of paper. Each article is given a section number (e.g., §24), which applies to the current Quarterly only. Each article is keyed to its major program area (e.g., Research and Exploratory Development), its technical instruction (e.g., Amorphous Semiconductors), its budget code (e.g., A13B), the Laboratory Group or Groups that performed the work (e.g., BBE), and the agency that supported it (e.g., SEA-033).

Certain Laboratory programs, including some which report a portion of their activities through the Quarterly Report, use document series other than the QR to report the bulk of their activities. Those series are available only to individuals and organizations that are directly concerned with the specific programs involved.

Requests for Quarterly Reports should be directed to: Supervisor, Technical Publications Group, Applied Physics Laboratory, Johns Hopkins Road, Laurel, Maryland 20810.

PREFACE

The Johns Hopkins University Applied Physics Laboratory, under contracts with the U.S. Department of Energy (DOE), the National Science Foundation (NSF), the U.S. Maritime Administration, the Maryland Department of Natural Resources, the U.S. Department of Commerce, and the U.S. Fish and Wildlife Service, is engaged in developing energy resources, utilization concepts, and storage methods. This Quarterly Report summarizes the work completed on the various tasks as of 31 December 1978.

The Energy Programs Quarterly Report is divided into four sections. The first, Geothermal Energy Development Planning, contains reports on the progress of major tasks where effort was concentrated during the quarter. These tasks include the on-going Atlantic Coastal Plain Geothermal Energy Market Survey and the Delmarva Geothermal Development Scenario, both for the DOE Division of Geothermal Energy (DGE). The first of a series of formal reports for both studies will be published in the near future. Another major task is a study for DOE/DGE to develop methodologies to evaluate alternate federal strategies to stimulate the commercialization of geothermal resources in the eastern U.S. The articles are followed by a section of comments on limited tasks that were performed in support of the major tasks.

The second section of the Quarterly, Operational Research, Hydroelectric Power Development, is supported by the Division of Resource Applications (RA) of DOE and contains the results of several major studies on dams and on the economic and institutional issues related to their redevelopment. The articles on these major tasks, performed as part of the DOE Hydroelectric Program, are followed by a section of comments on limited tasks.

The third section, Ocean Thermal Energy Conservation Development, contains progress reports on the Ocean Thermal Energy Conversion (OTEC) Program: Ocean Engineering, supported by the Division of Solar Engineering (DSE) of DOE, and Heat Exchangers for OTEC Systems, supported by the Division of Central Solar Technology (CST).

The last section, Energy Conservation and Storage Techniques, contains a report on flywheels supported by the Division of Energy Storage Systems (ESS) of DOE, and a report on an JHU-funded heat-pump application to the APL physical plant.

TABLE OF CONTENTS

GEOTHERMAL ENERGY DEVELOPMENT PLANNING

ENERGY MARKET STUDY, ATLANTIC COASTAL PLAIN

§11	Geothermal Energy Markets in the Atlantic Coastal Plain - Market Definition . . .	9
§12	Geothermal Energy Markets in the Atlantic Coastal Plain - Market Penetration. . .	11

REGIONAL OPERATIONAL RESEARCH, EASTERN U.S.

§13	Scenario of Geothermal Energy Development for the Delmarva Peninsula . . .	15
§14	Alternative Federal Strategies . . .	19

REGIONAL OPERATIONAL RESEARCH

§15	Comments on Limited Tasks, Geothermal Energy Development Planning . . .	25
-----	---	----

OPERATIONAL RESEARCH, HYDROELECTRIC POWER DEVELOPMENT

SMALL DAM HYDROELECTRIC RETROFIT PROGRAM

§16	A Method to Quantify Institutional Constraints .	29
-----	--	----

SMALL-SCALE HYDROELECTRIC

§17	Economic Study of Small-Scale Hydroelectric Projects . . .	31
§18	Institutional and Regulatory Constraints on Small-Scale Hydroelectric Development .	33
§19	Projection of Hydroelectric Development . .	35
§20	Insurance Issues . . .	37
§21	Institutional Problems in Developing Small-Scale Hydroelectric Power in the Ohio Valley . . .	39
§22	Comments on Limited Tasks, Small-Scale Hydroelectric Development. . .	41

OCEAN THERMAL ENERGY CONSERVATION DEVELOPMENT

OCEAN ENGINEERING

§23	OTEC Lightweight Concrete Investigation . . .	43
-----	---	----

HEAT EXCHANGERS FOR OTEC SYSTEMS

§24	Fabrication and Test Preparation of the APL Core Heat-Exchanger Unit	45
-----	---	----

ENERGY CONVERSION AND STORAGE TECHNIQUES

LOW-COST ADVANCED FLYWHEEL TECHNOLOGY

§25	Development and Demonstration Plan for a Low-Cost Flywheel	49
-----	---	----

ENERGY APPLICATIONS AT APL

§26	Energy Conservation Techniques in Use at APL	51
-----	--	----

TABLE OF CONTENTS

EQR

GEOHERMAL ENERGY DEVELOPMENT PLANNING § 11
Energy Market Study, Atlantic Coastal Plain

ZJ71CQO
Support: DOE/DGE
W. J. Toth
October-December 1978

GEOHERMAL ENERGY MARKETS
IN THE ATLANTIC COASTAL PLAIN—
MARKET DEFINITION

APL is performing a Geothermal Energy Market Study (GEMS) for DOE/DGE in those areas on the Atlantic Coastal Plain that offer some promise of geothermal resources (Fig. 1). The purposes of the study are to (a) identify existing energy requirements for space and water heating and process heat at temperatures below 250°F, (b) determine the technical feasibility of supplying these energy requirements with expected geothermal resources, (c) estimate the costs of geothermal energy for these applications, and (d) estimate the penetration of geothermal energy into those energy markets that are technically and economically attractive. The above tasks can be divided into two categories, market definition and market penetration. Some of the results of the market definition work are presented here. Metro Center is assisting in the market penetration work, which is described in Article 12 of this report.

To date, only the northern four areas shown in Fig. 1 have been investigated. Work is to begin in the southern areas by the spring of 1979. Efforts in the GEMS tasks are to be followed by development of resource-specific scenarios that will identify specific near-term users, outline the necessary tasks for resource development and commercialization, and schedule the tasks appropriately. Results of scenario development for the Delmarva Peninsula are presented in Article 13 of this report.

SUMMARY

Potential applications and markets for geothermal energy have been surveyed in the four northern resource areas (Fig. 1) and the data have been analyzed. Selected industrial and agricultural processes that require heat at temperatures below 250°F have been examined to determine the technical feasibility of supplying part or all of their thermal energy requirements with geothermal resources of low to moderate temperatures. Expected components in a complete geothermal energy system (the well, transmission and distribution pipelines, and heat exchanger) have been sized and priced approximately. Well-head and delivered costs of geothermal energy to residential users have been estimated. In some very favorable circumstances, residential heating costs using geothermal energy are competitive with current fuel-oil and natural-gas prices and are well below current costs of electric heating. A final report on the results will be published early in 1979.

DISCUSSION

The background and rationale for this work were presented in Ref. 1. The four study areas (southeastern New Jersey, the Delmarva Penin-

Fig. 1 The four areas of interest in the Atlantic Coastal Plain. (78-2/21)

sula, Norfolk, Virginia, area, and eastern North Carolina) have been chosen for the study to coincide with the progress of the DOE gradient drilling program. By the beginning of 1979, results of the drilling program and of gravimetric and seismic studies by the Virginia Polytechnic Institute and State University (VPI&SU) should be available in these areas. With information on both resource and market potential, DOE/DGE will then choose one or more sites for the location of a deep (5000 ft or greater) test well.

The two market study categories are (a) market definition, in which the types and total magnitudes of potential applications are defined and estimated; and (b) market penetration, in which the economic feasibility is determined for each application and the extent to which geothermal energy is likely to be used for each application is estimated.

Market Definition: Energy Market Survey. The potential areas of interest are space conditioning and water heating for residential, commercial, and military markets; and agricultural and industrial applications. Space conditioning may include both space heating and air conditioning. Some of the results for the residential, commercial, and military markets have been presented previously (Ref. 2).

The principal agricultural applications of interest are crop drying and space heating. Data have been obtained from the Bureau of the Census and the Department of Agriculture on crop-drying requirements. Of the four resource areas, North Carolina appears to have the greatest crop-drying requirements (for tobacco), and the Delmarva Peninsula, one of the largest poultry-producing areas in the U.S., has the greatest requirements for space heating. Estimates of heat for crop drying in each resource area are given in Table 1. Nearly all crop drying is done at temperatures of less than

Table 1
Crop drying requirements.

Resource Area	Btu per year
Southeast New Jersey	0.024×10^{12}
Delmarva Peninsula	0.450×10^{12}
Norfolk, Virginia	0.50×10^{12}
Eastern North Carolina	0.950×10^{12}

Fig. 2 Distribution and capacities of poultry houses in rural areas of the Delmarva Peninsula. Based on data from 11 of 13 companies. (78-4/31)

200°F; however, since crop drying is highly seasonal, it would be most practical to use crop drying as an off-peak use of a geothermal system that is dedicated to another use, such as space heating.

In areas of large poultry production, space heating of poultry houses appears to be a large potential market. For example, on the Delmarva Peninsula, poultry house capacity exceeds 82 000 000 chickens and production exceeds 380 000 000 chickens per year. Annual heating bills for the 6300 broiler houses exceed \$6 000 000 for well over one trillion (10^{12}) Btu. However, because of the wide distribution of poultry houses in rural areas, as shown in Fig. 2, only a fraction of this energy can be economically supplied by geothermal resources, i.e., where such resources co-exist with large concentrations of poultry houses. Again, it would probably be most economical to have this use tied into a dual-purpose district heating system.

In the industrial sector, the energy survey has dealt primarily with six industrial categories: food and kindred products, textiles, tobacco products, lumber and wood products, pulp and paper, and chemicals. The largest and most compatible industries for expected resources are food and related products and lumber. Within the food industry, poultry processing, vegetable canning, and crab processing are the largest heat-consuming activities. The first two often are comprised of large companies that could use nearly the entire thermal output of one or more geothermal wells and thus are candidates for early commercialization of geothermal resources. On the other hand, crab processors, which are quite numerous, are often small concerns that require steam at 250 to 260°F, are scattered

Fig. 3 Potential industrial market for geothermal energy on the Delmarva Peninsula. Potential in terms of a nominal well (10^{11} Btu/year). (78-4/32)

in sparsely populated areas, and thus are not attractive candidates.

In total, over 500 companies have been contacted, of which 25 to 35% have energy requirements compatible with potential resources. In order to compare the industrial market with resource locations, the supplantable energy consumption and the location of each company can be represented graphically by a symbol showing that portion of a nominally sized geothermal well that the company would use. Figure 3 shows that information for the Delmarva Peninsula. A nominal geothermal production well is defined as a well that produces 500 gpm of water whose temperature is reduced 50°F by extraction of thermal energy, thus producing about 10^{11} Btu per year. About half of the Delmarva market shown in Fig. 3 is poultry related. Similar maps have been prepared for each of the three resource areas.

FUTURE PLANS

The GEMS is essentially complete in the four northern resource areas on the Atlantic Coastal Plain. A report will be issued early in 1979 on the results of the study, which should prove useful to the DOE Site Selection Committee in selecting the locations of future exploratory wells.

The GEMS efforts will continue in the southern resource areas in South Carolina and Georgia beginning in the spring of 1979.

REFERENCES

1. Section 23, Quarterly Report, Jan-Mar 1978, APL/JHU EQR/78-1.
2. Section 12, Quarterly Report, Jul-Sep 1978, APL/JHU EQR/78-3.

GEOHERMAL ENERGY DEVELOPMENT PLANNING § 12 Energy Market Study, Atlantic Coastal Plain ZJ71CQ0.

Support: DOE/DGE

R. S. P. Weissbrod (JHU Metro Center) and W. J.
Toth, K. Yu, and F. C. Paddison (APL)

October-December 1978

GEOHERMAL ENERGY MARKETS IN THE ATLANTIC COASTAL PLAIN—MARKET PENETRATION

Metro Center is assisting APL in the Geothermal Energy Market Study (GEMS) for DOE/DGE. In order to determine the extent to which geothermal energy will penetrate existing and future energy markets, good estimates of geothermal energy costs must be developed and a methodology devised to predict rates of penetration. Computer modeling is necessary because of the many variables that influence geothermal energy costs.

Even with geothermal cost estimates and price projections for conventional energy sources in hand, the prediction of market penetration by geothermal energy remains a difficult task, primarily because of the lack of relevant historical experience (i.e., experience in the selection of new energy technologies at times of constantly rising real prices for conventional energy sources). In addition, the influence of other than purely economic factors (the environment, convenience, and reliability of supply) on market penetration can be quite substantial; such factors are being investigated.

SUMMARY

The Laboratory and Metro Center have each developed a computer program for analyzing the economic and financial costs of delivered thermal energy from a low- to moderate-temperature geothermal resource (100 to 220°F). Although both programs are designed to calculate the average cost of energy for residential or commercial users, they differ somewhat in details. The Laboratory's geothermal cost computer program (GTCOST) follows system design variations more closely while Geothermal Resources Economic Evaluation System (GREES), the Metro Center program, considers the matter of economics more carefully. The results obtained from these programs are comparable, enhancing our confidence in them.

Efforts are continuing in the review and extension of state-of-the-art methods to predict market penetration by geothermal energy.

DISCUSSION

Marginal Cost Estimates. While marginal costs are more relevant to price setting for an efficient allocation of resources, average costs provide a useful first approximation of the expense of providing geothermal space and process heating. They are the costs that a private entrepreneur must recover. By changing the relative sizes of the geothermal systems

and fossil-fuel peaking plants (through changes in the design temperature at which the peaking plant is turned on), the total output of the well and the number of households on the system can be varied. By changing the utilization factor in the industrial portion of the model, the marginal costs of providing additional geothermal heat can be determined. Thus, it is possible to estimate the marginal costs of adding an additional household or producing an additional Btu of geothermal energy. Marginal costs are important in determining the economically efficient size of the geothermal system.

Average Cost Estimates. Since there is relatively little experience with low- to moderate-temperature geothermal resources, cost data were taken from diverse sources, including studies dealing with higher temperature geothermal resources, nongeothermal district heating systems, and oil and gas production. The GTCOST and GREES programs were developed to bring together the available information in a form that would facilitate extensive testing of parameter values so that the impact on average costs could be determined. To our knowledge, the GTCOST and GREES programs are the first of their type to be developed specifically for low- and moderate-temperature geothermal resources in this country.

Computationally, the average cost models are simple and straightforward. The annual costs of each system are summed and divided by the number of Btu's consumed by participants in the system. However, considerable complexity arises from the close interrelationship of various system components. A change in one parameter value (e.g., design temperature) will affect several other system values, such as the total output of the well, the level of pumping energy required, and the length of the distribution system.

Although both programs are designed to calculate the average cost of energy for residential or commercial users, they differ somewhat in detail. The GTCOST program accommodates a greater degree of system design variations; the GREES program provides greater fidelity in economic considerations.

For a particular locale with a known annual temperature distribution, GTCOST will calculate parametrically as a function of resource characteristics the optimum mix of the geothermal heating system and a supplementary fossil-fuel-based peaking plant to take care of situations where the use of geothermal resources alone would be inefficient. It computes (if requested) the energy cost of a totally fossil-fuel-based district heating system to assess the contribution of geothermal utilization in reducing energy costs. The program is fast and can provide a quick-response economic analysis of a new system concept.

GREES, on the other hand, handles the amortization procedures with greater fidelity, but the optimum design temperature for the system is determined through parametric variation.

The utility of these programs to calculate average cost of geothermal energy is illustrated by the following graphic summaries of the cost predictions from GTCOST for the Salisbury, MD, area.

Figure 1 presents a typical example of how geothermal energy could be used for space heating residential buildings. The figure shows a geothermal well where a down-hole pump pumps water to the surface, through an accumu-

Fig. 1 Illustration of heating from a hydrothermal resource for community or industrial users. (78-4/33)

Table 1
Geothermal space heating, Maryland.

Ambient Design Temperature (°F)	Utilization (%)	No. of Residences Served* Townhouses†	
		ΔT 60°	ΔT 30°
10	20	390	194
20	24	476	238
30	30	612	306
40	38	857	428
50	46	1430	714

*One 500-gal/min well
†1500 sq ft

lator, to a heat exchanger, and then reinjects the water into the ground. The reinjection depth is assumed to be one-half the production-well depth. On the other side of the heat exchanger, clean heated water is circulated to residential buildings in a closed loop with the water being returned to the heat exchanger to be reheated.

Also shown in Fig. 1 is a topping system that adds an increment of heat to the circulating water on the coldest days. In addition the topping system provides a mechanism for matching the temperature of the heat available from a geothermal well to standard space-heating equipment. This system increases the number of residences that can be heated by a well.

Figure 2 shows the distribution of average temperatures for Richmond, VA; data for the Salisbury area are not available, but the Richmond area is comparable as it has approximately the same number of degree heating days. Table 1 lists the percent utilization of a single geothermal well and the number of residences

Fig. 2 Annual temperature versus duration. (78-4/34)

served (1500 sq ft townhouses) as a function of the temperature at which the peaking system is designed to operate.

Figures 3a and 3b show the cost of energy for three types of dwellings as a function of the peaking-system design temperature for two resource temperatures (wellhead temperatures of 125 and 145°F, both with reinjection temper-

(continued)

Fig. 3 Costs of space heating with a geothermal system, a mix of geothermal with fossil-fuel peaking, and fossil fuels only. (78-4/35)

Fig. 4 Costs of energy at the wellhead versus the use factor of the well, Delmarva area. (78-4/38)

atures of 85°F) that might be expected in the central Delmarva region of Maryland; a capital recovery factor of 11% (i.e., 10% interest on borrowed money for 25 years) is assumed. This is consistent with expected life of a geothermal well and other equipment - except down-hole pumps which require rework or replacement periodically. Figures 3c and 3d show similar costs for a capital recovery factor of 18%, which is appropriate for an investor-owned utility. The four plots show the range of costs for energy supplied for the following situations: (a) a geothermal system only, (i.e., no peaking system) with a design ambient temperature (DT) of 0°F; (b) the optimum mix of geothermal and fossil-fuel topping, with a design ambient temperature of 35°F; and (c) district heating with fossil-fuel topping only, with a design ambient temperature of 65°F.

In the case of the industrial user of geothermal water (Fig. 1), the cost analysis is simpler. The cost of energy at the wellhead versus the utilization factor of the well is plotted in Fig. 4 for conditions representative of the central Delmarva area of Maryland. In all of the cases mentioned, the costs of energy today from conventional fossil fuels used for space heating, including an estimated conversion efficiency, are

	\$/10 ⁶ Btu
Electric	10 to 11
Oil	5
Natural gas	4

A more detailed treatment of cost analysis is given in Ref. 1.

Market Penetration Analysis. The market penetration of new energy technologies is still difficult to project because of the lack of relevant historical experience. Metro Center is reviewing state-of-the-art modeling techniques in this field so that the more promising techniques can be applied to moderate-temperature geothermal energy.

Heating Demand Analysis. So far, Metro Center has gathered census and other data on building types and concentrations at the census tract level for three major cities in the East Coast study areas. These data have been used to plot density requirements for space and water heating as two-dimensional contour and three-dimensional perspective maps. The analysis of average costs of geothermal energy for space heating has shown the importance of high concentrations of heating demand in keeping the costs of geothermal energy acceptably low. The energy density maps for Atlantic City, Salisbury, and Norfolk indicate the level and spatial configuration of the demand in those cities and also the areas within them that can be served most economically by a geothermal system.

FUTURE PLANS

It is possible to determine from the results of the computation models important trade-offs among such factors as peaking temperature, well depth and resource temperature, and depth versus pumping energy. Additional information on technologies and specific resource characteristics in the Eastern U.S. Coastal Plain study areas can readily be incorporated into computational models. This degree of flexibility should prove more valuable now during the preliminary state in the economic evaluation of resources than it would for the more elaborate models that are designed to optimize systems in which the technology and resource conditions are more fully understood.

The analysis of average and marginal costs for a given community or area, such as those illustrated here for the Delmarva area of Maryland, will be provided for all of the areas included in current and future market surveys and scenario preparation.

REFERENCE

1. F. C. Paddison et al., "Direct Applications of Geothermal Energy in the Eastern United States, and Estimates of Life-Cycle Costs," APL/JHU QM-78-232, 30 Oct 1978.

GEOHERMAL ENERGY DEVELOPMENT PLANNING § 13
Regional Operational Research, Eastern U. S.
ZJ70CQO

Support: DOE/DGE

F. C. Paddison, C. S. Leffel, Jr., and J. E. Tillman
October-December 1978

SCENARIO OF GEOHERMAL ENERGY DEVELOPMENT FOR THE DELMARVA PENINSULA

The scenario of geothermal energy developments for the Delmarva Peninsula serves as a road map and focus for federal, state, and local interests, identifying for each the prerequisite steps and timing required to make geothermal energy available.

Development of hydrothermal geothermal energy is constrained to locations where a suitable resource exists, measured by the availability of economically recoverable warm water. The use of the energy will vary depending upon local heating and cooling requirements, demography, industry, agricultural development, and the temperature of the resource. Because of this great diversity, development initiative must stem from local entities. Accordingly APL, in its role as Regional Operational Research Contractor, is developing the scenario directly with concerned localities in the Delmarva area.

DISCUSSION

Early Scenarios. Scenarios in the form of bar charts, time phasing, and identification of the specific tasks required to develop the resource and bring power on line for the several resource areas have been published. Each of the following areas has been summarized briefly in previous Quarterly Reports:

1. The Madison Limestone Aquifer in western South Dakota,
2. The Coastal Plain in southern Arkansas,
3. The eastern Gulf Coastal Plain,
4. The Atlantic Coastal Plain, and
5. Hot dry rock.

These scenarios are documented in Refs. 1 through 5. Later narrative-style scenarios, written for distribution to interested local communities (in addition to DOE), were published for the Madison Limestone Aquifer (Ref. 6) and for the Indian town of Kyle, SD (Ref. 7).

The Delmarva Scenario. This scenario is the first of a new series that concentrates on a specific resource area. The series will include southern New Jersey; Norfolk, VA, to Morehead City, NC; Wilmington, NC; Charleston, SC; and Savannah to Brunswick, GA. The suggested contents of the scenario for the Delmarva area (Fig. 1) are a combination of a previous tabular bar chart that identifies task duration by organization entity and the time that each step must start with a description of the necessary steps in narrative form.

Since the new scenarios are intended for a larger and less informed audience, consider-

Fig. 1 Area of scenario development in the Delmarva Peninsula. (78-4/41)

able text has been included. The current status of technical, environmental, and legal efforts are explained as well as the expected economics of geothermal energy. Portions of these new scenarios are being written by local entities. The outline of the second draft of the Delmarva scenario is as follows:

- I. Background to Delmarva Scenario Development
 - a. Resource description
 - b. Present and future uses for low-grade energy
 - c. Reservoir engineering and applications engineering
 - d. Economic considerations
 - e. User community and identification of specific entities involved in outlined developments
- II. Development Scenarios - Delmarva
 - a. Sussex County, Delaware
 - b. Worcester, Wicomico, Dorchester, and Somerset Counties, Maryland
 - c. Accomack and North Hampton Counties of the eastern shore of Virginia

III. Issues To Be Defined and Addressed

- a. Technology Research and Development
- b. Environment
- c. Legal
- d. Institutional
- e. Socio-economic

Appendixes

1. DOE/DGE Resource Definition Plan
2. Federal Assistance Programs
3. Population and Land Use Data

References

1. DOE/DGE Eastern Hydrothermal Plan
2. State and County Development Plans in Resource Area
3. State Laws

A preliminary version of the scenario (Ref. 8) has been distributed to a limited audience. A revised version of the scenario, which will include the time phasing of the potential uses, will be available in late January 1979. The final version should be ready in February.

Potential Developments — Delmarva. Meetings were held with several groups to help them evaluate the technical and economic steps in using the geothermal resources in their area. In the second revision of the scenario, the following users were identified:

1. Industrial parks that are in either early or late planning stages at Worcester County near Ocean Pines, MD, and at the towns of Salisbury, MD, Melfa, VA, and Seaford and Georgetown, DE;
2. Future housing developments at Ocean Pines, MD, near Indian River Bay, and north of Bethany Beach, DE;
3. NASA, Wallops Flight Center, VA;
4. Year-round City Services Center and Recreation Facility, Ocean City, MD;
5. Eviscerating, brooding, and hatchery facilities throughout the Delmarva area; and
6. Small businesses and food processing industries throughout the Delmarva area, identified through market surveys, that could use all or a substantial portion of one well.

Interaction with Local Communities. The Maryland Regional State Planning Office in Salisbury conducted a workshop (Ref. 9) on 14 December for county planners and the general public to advise them of the status of DOE/DGE programs in resource assessment, market surveys, and scenario details pertaining to Wicomico, Worcester, Dorchester, and Somerset Counties. Material presented by APL is documented in Ref. 10.

Maryland has a Geothermal Act that was passed by the State Legislature early in 1978 (Ref. 11). To assist State Energy Offices, meetings were held with DOE/DGE representa-

tives in Delaware and Virginia (Refs. 12 and 13). To assist these states in considering geothermal legislation, the National Conference of State Legislatures conducted initial workshops in both states during the quarter. APL presented a summary of the market survey, scenario status, and scheduling at each of these workshops (see article 15, elsewhere in this Quarterly). The workshop in Virginia was held on 27 October (Ref. 14) and that in Delaware on 15 November (Ref. 15).

The Program Research and Development Announcement (PRDA). During the quarter, DOE issued a PRDA (Ref. 16). Considerable effort was required to notify all prospective respondents in the region of interest of its existence and to offer technical counsel on the application of geothermal waters in various locales and the prospective estimated costs.

FACT SHEETS

The Eastern States Fact Sheets are being refined and updated as information is obtained. Publication of the draft version is scheduled for early in 1979. The results of the 1978 election have required extensive revisions to the lists of legislative contacts and state departmental contacts.

FUTURE PLANS

The Delmarva scenario will be as complete as possible prior to receipt of definitive resource and temperature data obtained by pumping various strata in a deep well. It was hoped that scenarios for all three areas (Delmarva; Norfolk, VA, to Stump Point, NC; and southern New Jersey) considered for the deep test well could have been completed in time to compare them with (a) the existing market survey (see articles 11 and 12 in this Quarterly), and (b) the VPI&SU geologic data from the shallow gradient wells when the site of the deep well was selected. However, only the Delmarva scenario effort was made because of funding limitations. Work on scenarios for the other two areas will begin in the first and second quarters of CY 79.

Scenarios must be maintained and kept up to date if they are to serve as viable planning tools. Accordingly, the Delmarva scenario will be kept as current as possible within funding limits.

REFERENCES

1. "Geothermal Energy and the Eastern U.S., A Scenario for Geothermal Energy Development, The Atlantic Coastal Plain," APL/JHU QM-77-129, Oct 1977.
2. "Geothermal Energy and the Eastern U.S., A Scenario for Geothermal Energy Development, The Coastal Plain in Southern Arkansas," APL/JHU QM-77-129-1, Oct 1977.
3. "Geothermal Energy and the Eastern U.S., A Scenario for Geothermal Energy Development, The Madison Limestone Aquifer in Western South Dakota," APL/JHU QM-77-129-2, Nov 1977.
4. "Geothermal Energy and the Eastern U.S., A Scenario for Geothermal Energy Development, The Eastern Gulf Coastal Plain," APL/JHU QM-77-129-3, Feb 1978.
5. "Geothermal Energy and the Eastern U.S., A Draft Scenario for Geothermal Energy Development, Hot Dry Rock," APL/JHU QM-77-129-4, Mar 1978.

(continued)

6. "R. Freeman and R. Meier, "Potential Application of Madison Formation Waters for Community Heating - South Dakota," APL/JHU QM-78-042R, Sep 1978.
7. R. C. Eberhart and R. A. Freeman, "Geothermal Energy Development by the Oglala Sioux at Kyle, South Dakota," APL/JHU QM-78-226 (draft), Apr 1978.
8. "Scenario of Geothermal Energy Usage for Delmarva Area" (draft), Oct 1978.
9. "Geothermal Energy Workshop - December 14, 1978," memorandum from Maryland Department of State Planning, Lower Eastern Shore Regional Office, 16 Nov 1978.
10. F. C. Paddison, "Geothermal Energy in Delmarva - Presentation to 14 December 1978 Workshop," APL/JHU QM-78-266, 29 Dec 1978.
11. "Maryland Geothermal Resources Act," Maryland Senate Bill No. 1154 (81r3883).
12. J. E. Tillman, "Meeting with Dave Press and Ed Freel," APL/JHU QM-78-222, 29 Sep 1978.
13. F. C. Paddison, "Presentation of Geothermal Potential in Virginia," APL/JHU QM-78-249, 28 Nov 1978.
14. J. E. Tillman, "Presentation to the Virginia Study Commission on Coal and Energy," APL/JHU QM-78-235, 1 Nov 1978.
15. F. C. Paddison, "Geothermal Workshop - Delaware," APL/JHU QM-78-246, 17 Nov 1978.
16. "Engineering and Economic Studies for Direct Applications of Geothermal Energy," Program Research and Development Announcement, PRDA-03-79-ET-27004.

ALTERNATIVE FEDERAL STRATEGIES

APL is evaluating alternative federal strategies for developing geothermal energy. The project is in support of the DOE/DGE program to stimulate the commercialization of low- to moderate-temperature geothermal resources. In order to decide where emphasis should be placed, it is necessary to assess the eastern and central United States for prime prospects, to compare the advantages of stimulating development in each area, and to develop a methodology for reassessing these prospects as better data are developed. Although geologic and reservoir-engineering parameters must be considered, the ultimate suitability will be determined by the cost of geothermal energy in comparison to alternative sources for the particular application. The methodology described here combines the results of studies that quantify the geologic, engineering, and economic implications of development, permits the periodic reassessment of geothermal prospects, and suggests alternative courses of action.

This is the first report on progress in developing a methodology that appraises various strategies aimed at meeting the goals set in the DOE/DGE program plan (Ref. 1). A summary of the geologic rationale for selecting areas as prime prospects is included below. This is followed by a first attempt at comparing economic and physical advantages of a selected sample of potential resource areas in the eastern United States.

AREAS OF GEOHERMAL POTENTIAL

The first step in weighing the merits of alternative exploration and development targets is to define the geologic environment most likely to contain the desired resource. Areas of anomalously high heat flow are not known to exist in the central and eastern United States; therefore, a combination of physical conditions is necessary for the occurrence of a commercially exploitable geothermal resource. In addition to above-average heat flow, water availability is a crucial factor in determining the potential of a resource. If a resource area with above-average heat flow does not contain water, it must await the development of hot-dry-rock technology if it is to be developed at all. For near-term exploitation, resource areas must have ample amounts of extractable water (Ref. 2).

In the central and eastern United States, most if not all potential hydrothermal resources occur in sedimentary basins because of the following favorable characteristics: (a) in general, sedimentary rocks have low thermal conductivities and therefore act as an insulating blanket over areas of heat gen-

eration, whether normal or above average; (b) water availability is easier to appraise in a well-layered sedimentary sequence, compared to a crystalline complex; (c) drilling to given depths is easier and cheaper through sedimentary rocks than through crystalline rocks; and (d) many sedimentary basins have been explored for hydrocarbon deposits and therefore a great deal of subsurface data exist on these areas (Ref. 3).

Figure 1 shows the sedimentary basins that may harbor exploitable near-term hydrothermal resources. Table 1 shows a system for classifying the types of resources that may occur in some of the basins. The hydrothermal resources can be divided into conduction- and convection-dominated systems. Conduction-dominated resources consist of aquifers where elevated temperatures occur because of above-average heat flow from the rocks below. The performance of these aquifers can result from either primary permeabilities (e.g., in the coastal plains) or increased permeability resulting from fracturing (e.g., in the lithified rocks of the interior basins). Convection-dominated systems are areas where water has been circulated adiabatically along a fault or fracture zone, bringing up to a shallower horizon hot water that has been heated at depth.

Within these large resource areas further definition and evaluation will be based on available demographic, economic, thermal, and depth-to-basement data.

Analysis to date has concentrated on only a few of these areas: the Illinois Basin, the Gulf Coastal Plain, and the Arkoma Basin. The decision to begin analysis with studies in these areas was based on the relative availability of subsurface hydrologic data. The temperature data were taken from Ref. 4 and the depth-to-basement data from Ref. 5; the contours were plotted to a common scale so that regions where the gradient exceeded $1.8^{\circ}\text{F}/100\text{ ft}$ and the depth to basement exceeded 3000 ft could be located by county. Under these criteria, 55 counties in five states were eligible prospects. Table 2 exhibits the data assembled for these prospects.

ASSESSMENT METHODOLOGY

A "best" option from a number of alternative prospects may be selected by one of the two following formulations. When the selection is made after all alternatives have been stated, the problem is equivalent to evaluating the prospects with respect to some set of preferences. A related, but logically distinct, problem requires the selection to be made as the alternatives arise without knowing that all options have been considered; this problem is not discussed here. A simple evaluating procedure that can be reapplied when new data are acquired seems more appropriate to the current situation because the amount and quality of geothermal data are rapidly changing.

Comparing a given number of prospects requires that a basis for comparison be chosen that reflects the purpose and preferences for which the selection is undertaken. To illustrate a method for comparing geothermal prospects and the effect of different assumptions, a set of three broad categories has been chosen: geothermal resource characteristics, cost ele-

Fig. 1 Sedimentary basins that may contain exploitable near-term hydrothermal resources. (78-4/42)

Table 1
 System for classifying potential geothermal resource areas in the eastern United States.

1. Sedimentary Basins	Examples
A. Hot dry rock	
1. Conduction from concentration of radioactive material	Buffalo, eastern New Jersey, Peoria, Terre Haute, Crisfield
B. Hydrothermal	
1. Conduction dominated	
a. Simple aquifers	
- Unconsolidated sediments	Atlantic and Gulf Coastal Plains
- Sedimentary rock	
i. Primary permeability	Madison limestone, South Dakota
ii. Secondary permeability	Oriskany sandstone, Pennsylvania Triassic Basins
b. Geopressed aquifers	Gulf Coast
2. Convection dominated (adiabatic)	
a. Fracture/fault zone	
- Fractured rock reservoir	Arkansas, Virginia, New York
- Fault-fed aquifers	Balcones Fault - Coastal Plains Rough Creek Fault - Illinois Basin

(continued)

ments, and market factors. These categories are represented by single subheads as follows:

- I. Resource Characteristics
 - Heat flow (Btu/gal) data:
 - gradient, depth to basement
- II. Cost Elements
 - Drilling and casing data:
 - depth to basement
- III. Market Factors
 - Energy usage, household/commercial

The choice of this basis for comparison was dictated largely by the availability of data and by the desire to keep the example to a size that can be comprehended easily. A more nearly complete set of categories would include factors for development time and might include legal and social considerations; cost elements should include costs for plant and considerations of financing and taxes. Marketing factors might extend to projected as well as present markets and to the expected market penetration; it should certainly include the requirements for process heat.

The characteristics of the geothermal resource are summarized, for this example, by an estimated heat flow or extractable heat; the cost factors are summarized by the cost of drilling and casing an 8-in. well. Both heat flow and drilling costs are calculated at 75% of the depth to basement or to 3000 ft, whichever is greater. Heat flow is calculated on the assumption of a ground temperature of 55°F and a spent water temperature of 100°F. Drilling cost (C_W) is calculated using an equation derived by fitting the curves given in Ref. 6:

$$C_W = D \times 10^{[K + (D/171.4)]},$$

where

D = depth in hundreds of feet,
 $K = \begin{cases} 3.6 & \text{in hard rock,} \\ 3.2 & \text{in softer rock.} \end{cases}$

The estimates of these factors are displayed in columns 3 and 4 of Table 2.

Table 2
Comparison of geothermal prospects.

State/County	1 Basement (thousand ft)	2 Gradient (°F/hundred ft)	3 Heat Flow (Btu/gal)	4 Cost (\$ per hundred ft)	5 Population (thousands)	6 Population Density (No./mi ²)	7 Energy (trillion Btu)
Arkansas							
Calhoun	10.0	1.9	813.6	817.8	5.6	9.0	0.4
Clark	10.0	1.9	813.6	817.8	21.5	25.0	1.5
Cleburne	5.0	1.8	187.8	247.1	10.3	19.0	0.7
Cross	10.0	1.9	813.6	817.8	19.8	32.0	1.4
Drew	10.0	1.8	751.0	817.8	15.2	18.0	1.0
Franklin	5.0	1.8	187.8	247.1	11.3	18.0	0.8
Howard	10.0	1.9	813.6	817.8	11.4	20.0	0.8
Jackson	10.0	1.9	813.6	817.8	20.4	33.0	1.4
Jefferson	10.0	1.9	813.6	817.8	85.3	98.0	5.8
Lincoln	10.0	1.8	751.0	817.8	12.9	23.0	0.9
Little River	10.0	1.9	813.6	817.8	11.1	23.0	0.8
Lonoke	10.0	1.9	813.6	817.8	26.2	33.0	1.8
Ouchita	10.0	1.9	813.6	817.8	30.9	42.0	2.1
Pike	10.0	1.9	813.6	817.8	8.7	15.0	0.6
Poinsett	10.0	1.9	813.6	817.8	26.8	35.0	1.8
Sevier	10.0	1.9	813.6	817.8	11.2	22.0	0.8
VanBuren	5.0	1.8	187.8	247.1	8.3	12.0	0.6
Georgia							
Evans	3.5	1.8	75.1	178.7	7.3	39.0	0.3
Long	3.5	1.8	75.1	178.7	3.8	9.0	0.2
Montgomery	3.5	1.8	75.1	178.7	6.1	26.0	0.3
Tattnall	3.5	1.8	75.1	178.7	16.5	34.0	0.7
Toombs	3.5	2.0	125.2	178.7	19.2	52.0	0.8
Wayne	3.5	1.8	75.1	178.7	17.9	28.0	0.7
Illinois							
Coles	8.0	2.0	625.9	534.8	47.8	94.0	4.1
Macoupin	4.5	1.9	159.6	211.4	44.6	51.0	3.8
Madison	4.0	1.9	100.1	178.7	250.9	342.0	21.5
Menard	4.5	2.0	187.8	211.4	9.7	31.0	0.8
Shelby	7.5	1.9	516.3	476.8	22.6	30.0	1.9
Indiana							
Carroll	4.0	1.9	100.1	178.7	17.7	47.0	1.4
Clay	7.0	1.9	456.9	423.1	23.9	66.0	1.9
Davies	9.0	1.9	694.7	665.5	26.6	62.0	2.1
Gibson	10.0	1.8	751.0	817.8	30.4	61.0	2.4
Green	8.0	2.0	625.9	534.8	26.9	49.0	2.1
Knox	9.0	1.9	694.7	665.5	41.5	81.0	3.3
Montgomery	6.0	1.8	300.4	327.9	33.9	67.0	2.7
Morgan	6.5	1.8	356.7	373.6	44.2	109.0	3.5
Owen	7.0	1.8	413.1	423.1	12.2	31.0	1.0
Parke	6.0	1.8	300.4	327.9	14.6	33.0	1.2
Putnam	6.5	1.9	397.4	373.6	26.9	55.0	2.1
Sullivan	8.0	2.0	625.9	534.8	19.9	44.0	1.6
Vigo	7.0	2.0	500.7	423.1	114.5	276.0	9.1
White	4.0	1.9	100.1	178.7	21.0	42.0	1.7
Mississippi							
Grenada	11.5	1.9	892.9	932.9	19.8	46.0	0.9
Holmes	10.5	1.8	807.4	903.0	23.1	30.0	1.0
Lafayette	9.5	1.9	754.2	738.7	24.2	36.0	1.1
Madison	10.5	1.8	807.4	903.0	29.7	41.0	1.3
Monroe	8.0	1.8	525.7	534.8	34.0	44.0	1.5
Montgomery	11.5	1.9	892.9	932.9	12.9	32.0	0.6
Noxubee	12.0	2.0	959.7	932.9	14.3	21.0	0.6
Pontotoc	9.5	1.9	754.2	738.7	17.4	35.0	0.8

Energy consumption is given in Ref. 7 for household/commercial use of coal, petroleum, and natural gas. The consumption of petroleum, as given in this reference, was reduced by the quantity of asphalt used, assuming it to be a structural material rather than a fuel. With the further assumption that the household/commercial consumption of energy is used principally for space heating, the total consumption for the state was distributed among the counties in proportion to population. The resulting energy usage (column 7 of Table 2) and the population density of the counties (column 6 of Table 2) are taken as the only two bases of comparison reflecting market factors. Other comparisons suggest themselves: energy consumption per capita, the cost rather than the quantity of energy, or the number of gallons of flow required to accomplish a given level of market penetration.

The method suggested for evaluating the prospects requires the amalgamation of these data into a "score" for each prospect. The four categories of data entering the score are heat flow, cost, population density, and energy use (columns 3, 4, 6, and 7 of Table 2). A criterion for comparing the prospects within each category must be clearly stated. For this example, higher heat flows and energy use, and lower costs and population densities, are to be preferred. Alternatively, a preference for higher population density is considered in one case. In addition to being able to state preferences within each category, the "weight" that each category contributes to the score for each prospect must be assigned. Table 3 exhibits the weight assignments for a number of cases labeled R0, R1, ... R8, each case reflecting a different set of assumptions. The column numbers here agree with those in Table 2.

Table 3
Several cases representing different sets of assumptions.

Case	3 Heat Flow	4 Cost	6 Population Density	7 Energy Household/Commercial
R0	1	1	1	1
R1	1	1	-1	1
R2	2	1	1	5
R3	5	1	1	3
R4	1	3	1	3
R5	1	1	3	5
R6	1	3	5	1
R7	3	5	1	1
R8	3	1	5	1

Weighting R0 gives equal weights to each category in the basis of comparison. Weighting R1 also gives equal weights; the minus sign indicates a reversal of the assumption so that higher population density is now preferred. Weightings R2 and R3 emphasize heat flow and market; both are given to illustrate that the interchange of nearly equal assignments of weights does not greatly modify the ranking. As shown in Table 4, weightings R4 and R6, emphasizing drilling cost, shift the high ranks to Georgia counties, while R7,

Table 4
Data from Table 2 ranked by the assumptions of Table 3.

	R0	R1	R2	R3	R4	R5	R6	R7	R8
Arkansas									
Calhoun	6	27	4	4	31	1	28	31	3
Clark	13	21	7	8	34	10	34	36	9
Cleburne	30	37	40	40	13	21	9	9	37
Cross	17	20	11	11	38	14	36	37	10
Drew	31	41	20	20	43	22	35	44	17
Franklin	29	38	39	39	12	19	7	8	36
Howard	10	25	6	6	33	7	31	33	5
Jackson	19	19	13	12	40	16	38	39	12
Jefferson	35	13	15	15	42	47	47	42	21
Lincoln	33	40	21	21	44	27	40	45	19
Little River	12	22	9	9	36	9	33	35	8
Lonoke	18	18	10	10	37	15	37	38	11
Ouchita	22	16	14	14	41	23	41	41	14
Pike	7	26	5	5	32	6	30	32	4
Poinsett	20	17	12	13	39	18	39	40	13
Sevier	11	24	8	7	35	8	32	34	7
VanBuren	27	39	38	38	11	13	5	7	34
Georgia									
Evans	48	46	49	49	9	45	10	13	48
Long	38	50	45	45	2	25	1	6	41
Montgomery	44	49	47	46	7	34	2	10	43
Tattnall	47	47	48	48	8	40	6	12	47
Toombs	37	35	42	42	1	41	12	2	42
Wayne	45	48	46	47	6	36	3	11	45
Illinois									
Coles	5	2	27	27	25	32	24	22	28
Macoupin	36	34	41	41	10	37	13	3	40
Madison	50	15	50	50	14	50	48	25	50
Menard	25	30	37	37	4	20	4	1	38
Shelby	3	7	28	28	21	4	18	20	27
Indiana									
Carroll	41	42	44	44	5	43	11	5	46
Clay	15	5	30	31	19	31	19	17	31
Davies	16	8	23	23	27	30	25	27	24
Gibson	43	36	22	22	45	46	43	46	22
Green	2	3	26	26	24	5	21	19	25
Knox	23	6	24	24	28	39	29	28	26
Montgomery	34	29	36	36	16	44	17	16	35
Morgan	40	14	34	34	18	48	23	23	39
Owen	21	28	32	32	20	17	16	24	30
Parke	26	31	35	35	15	24	14	15	33
Putnam	14	9	33	33	17	26	15	14	32
Sullivan	1	4	25	25	23	2	20	18	23
Vigo	49	1	31	30	22	49	50	21	49
White	39	43	43	43	3	38	8	4	44
Mississippi									
Grenada	32	32	3	3	50	33	49	48	6
Holmes	42	45	16	16	47	35	44	49	15
Lafayette	9	11	17	19	29	12	27	30	18
Madison	46	44	19	17	49	42	46	50	20
Monroe	24	23	29	29	26	29	22	26	29
Montgomery	28	33	2	2	48	28	45	47	2
Noxubee	4	10	1	1	46	3	42	43	1
Pontotoc	8	12	18	18	30	11	26	29	16

which emphasizes heat flow as well, shifts the ranks toward Illinois. Weighting R5, which emphasizes marketing and social factors without much concern for cost, selects deep wells. Weighting R8 with its emphasis on heat flow is not remarkably different from R2 and R3.

Table 4 ranks the counties from Table 2 by the different weight assignments. The score for each prospect is calculated as the weighted sum of the four selected categories; the highest score is given rank 1; the lowest score is given rank 55. With such a simple scoring method, great importance should not be attached to the apparent insensitivity of the ranks to marketing and population factors that could be given greater emphasis by a different selection of units. The important observations are that the ranks can be shifted widely by the choice of the weights and that there is no way to avoid the necessity for selecting a set of weights appropriate to the purpose for which the evaluation of prospects is being made.

Work is in progress to extend this example to a wider range of states by accepting
(continued)

lower temperature gradients for eligible prospects. The method will also be refined by including a wider range of categories in the basis of comparison, in particular by including the marketability of process heat and some refinement of both the cost categories and market penetration.

REFERENCES

1. "Program Plan for Development and Utilization of Geothermal Resources in the Eastern United States," Department of Energy, Division of Geothermal Energy, Nov 1978.
2. J. E. Tillman, "Near-term potential for geothermal energy in the eastern U.S.," Abstract with programs, Northeastern Section, Geol. Soc. Am., 1979.
3. J. E. Tillman, "Eastern Geothermal Resources," GEO-HEAT, 1979.
4. "Geothermal Gradient Map of North America," U.S. Geological Survey, G74014, 1976.
5. "Basement Rock Map of the United States," U.S. Geological Survey, G67280, 1968.
6. E. L. Fox, "Contribution of Well Costs to the Price of Geothermal Energy," APL/JHU QM-78-078, 1 Jun 1978.
7. L. H. Crump, "Fuels and Energy Data," Bureau of Mines Information Circular 8722, 1976.
8. County and City Data Book, 1972, Bureau of the Census, 1973.

GEOHERMAL ENERGY DEVELOPMENT PLANNING §15
Regional Operational Research ZJ70COO
Support: DOE/DGE
F. C. Paddison
October-December 1978

**COMMENTS ON LIMITED TASKS,
GEOHERMAL ENERGY DEVELOP-
MENT PLANNING**

**PRESENTATION TO THE VIRGINIA COM-
MISSION ON COAL AND ENERGY**

On 27 October 1978, J. E. Tillman of APL participated in the first of a series of Geothermal Workshops sponsored by the National Conference of State Legislatures (NCSL) for Virginia. R. C. Harris of NCSL, who organized the meeting, delivered an opening address and distributed background materials to the chairman, Senator Michaels, and the 15 other Virginia State Senators in attendance. The first technical presentation was made by J. Lambiase of the Virginia Polytechnic Institute and State University who described the potential geothermal resource in Virginia and the progress of scientific programs to investigate its nature.

Mr. Tillman discussed the possible applications of the low-temperature hydrothermal resource that is believed to exist beneath the Virginia coastal plain. His talk included four topics: (a) applications of similar resources in various parts of the world, (b) the expected cost of geothermal energy in eastern Virginia, (c) the scope and results of the Energy Market Survey conducted in Virginia by APL, and (d) the purpose and progress of the Scenario for the Development of Geothermal Energy in Virginia being written by the APL staff.

The two areas of present interest in the Virginia coastal plain are Portsmouth and Accomack County. The resource is more attractive in Accomack County because the thicker sequence of insulating sediments coinciding with a high thermal gradient results in lower costs for extracting water at high temperatures. However, the present energy demand in this area is small and diffuse. At Portsmouth, where the energy demand is much greater, the sediments are not as thick but there is still a high geothermal gradient.

Two potential applications in Virginia for the low-temperature hydrothermal resource are space heating and food processing. The cost for geothermal energy relative to conventional fuels was discussed at the meeting for space heating of single-family dwellings, townhouses, and condominiums. It was shown that certain site-specific applications are competitive with oil and electricity. The temperature range of the geothermal water believed to be beneath parts of the Virginia coastal plain are compatible with those used by bottling companies and in the poultry industry.

Questions from the study commission dealt with transportation, future costs, amortization, well costs, and the life of a resource.

A. Giles of the Virginia Water Control Board (WCB) discussed the potential problems

of growth in the use of water-referenced heat pumps. He felt that present laws are adequate for "deep-hot" geothermal development as long as well completion standards were met and reinjection was back into the same aquifer. He said that the State WCB would oppose any shallower reinjection.

REFERENCE

1. J. E. Tillman, "Presentation to the Virginia Study Commission on Coal and Energy," APL/JHU QM-78-235, 1 Nov 1978.

**SEMINAR OF THE AMERICAN INSTITUTE OF
INDUSTRIAL ENGINEERS**

A paper (Ref. 1) was presented on 31 October 1978 to the American Institute of Industrial Engineers Seminar, in Washington, DC. The paper defined geothermal energy, described geothermal resources along the Atlantic Coastal Plain, explained the recovery of geothermal energy, described the uses of geothermal energy of moderate temperatures, and gave the cost of geothermal energy used for community space heating versus the cost of energy from traditional fuels.

REFERENCE

1. F. C. Paddison et al., "Direct Applications of Geothermal Energy in the Eastern United States and Estimates of Life Cycle Costs," APL/JHU QM-78-232, 30 Oct 1978.

**GEOHERMAL POTENTIAL IN ACCOMACK
AND NORTHAMPTON COUNTIES, VA**

On 3 November 1978, J. E. Tillman of APL presented a review of the DOE/DGE geothermal development program at the Eastern Shore Community College in Melfa, VA. The presentation was for the benefit of state planning personnel from Accomack and Northampton Counties and for the Accomack County Industrial Development Authority, which is planning an industrial park adjacent to the college. The geothermal water beneath Melfa is believed to be at a temperature of above 150°F. The sediments (sands and muds) beneath the coastal plain in this area are about 5000 ft thick. Utilization of the energy can be cost effective if reasonable flow rates can be obtained from the lower Cretaceous sand units.

Aside from general space heating and domestic hot water requirements of the industrial park, companies are being sought that have energy-intensive processes. Companies with requirements for water at low to moderate temperatures would be interested in using the geothermal energy if it were competitive with conventional fuels.

Brown and Root Co., Inc., is planning an offshore oil and gas support facility at Cape Charles, VA, and is interested in geothermal water for space heating the facility. The Northampton County Administration will supply expected new housing plans attendant to the facility.

Further discussions with industrial park personnel are planned.

REFERENCE

1. F. C. Paddison and J. E. Tillman, "Pre-

sentation of Geothermal Energy Potential in Accomack and Northampton, Virginia," APL/JHU QM-78-238, 8 Nov 1978.

TECHNICAL INTERCHANGE MEETING

The last Quarterly Report mentioned a technical interchange meeting held at APL on 19 September 1978 that included most organizations directly or indirectly involved in the hydrothermal program for the east (Ref. 1). On 8 November, a fully documented set of minutes was issued to the participants of the meeting and a group of other interested parties (Ref. 2). Additional copies of the minutes are available with the concurrence of the DOE/DGE.

REFERENCES

1. "Technical Interchange Meeting," Quarterly Report Jul-Sep 1978, APL/JHU EQR/78-3.
2. "Minutes of First Technical Interchange Meeting," APL/JHU Lett CQO-2319, forwarding APL/JHU QM-78-214, 8 Nov 1978.

PROJECTIONS OF GEOTHERMAL ENERGY ON-LINE IN DOE EASTERN REGION

On 8 November 1978, APL assisted DOE in preparing estimates of geothermal energy use in the Eastern U.S. by the years 1985, 1990, and 1995. These estimates had been requested by the Assistant Secretary for Energy Technology for use in work related to National Energy Plan 2. The estimates, obtained with the aid of DOE personnel, are shown below.

Hydrothermal Resources in the Eastern United States

1. Product: Direct use of hydrothermal geothermal energy for space conditioning, water heating, and industrial process heat.
2. Cost: \$3.40 to \$8.70/10⁶ Btu (1978 dollars) (assuming a nonprofit municipally owned district heating system. Wellhead production-only costs to industrial users lie in the range of \$1.10 to \$2.75/10⁶ Btu.)
3. Year of Introduction: Some small uses now. Development in prospective areas explored with U.S. assistance expected no sooner than 1982.
4. Estimate of Conventional Energy Displaced:
0.005 - 0.01 quads/year in 1985
0.05 - 0.10 quads/year in 1990
0.20 - 0.5 quads/year in 1995
5. Regions of Principal Interest:
Delmarva Peninsula
Norfolk, Virginia/Eastern North Carolina
Coastal South Carolina
Coastal Georgia
Balcones Fault Zone, Texas, to Hot Springs, Arkansas
Eastern Gulf Coast (Mississippi and Alabama)
Appalachian Basin
Illinois/Indiana Basin

REFERENCE

1. W. J. Toth, "Geothermal Production Estimates for DOE," APL/JHU QM-78-245, 15 Nov 1978.

SUGGESTED INITIATIVES TO AID THE DIRECT UTILIZATION OF AN EVENTUAL COMMERCIALIZED GEOTHERMAL ENERGY

A workshop was convened at Keystone, CO, by the University of Denver for DOE on 15 November 1978, to develop suggestions to aid in utilizing and commercializing geothermal energy. Reference 1, which was forwarded to the workshop, contained a discussion of the following items:

1. The virtues and limitations of the current DOE incentive programs
 - a. Loan Guaranty Program,
 - b. Program Opportunity Notice and Program Research and Development Announcement
2. Some suggested government actions to promote the use of low- to moderate-temperature hydrothermal resources
 - a. Operation of geothermal facility
 - b. Absorption of risk
 - c. Provision of expert aid
 - d. Resource management and some environmental problems
 - e. Tax incentives

REFERENCE

1. F. C. Paddison, "Suggestions for Considerations at Keystone, Colorado, Workshop," APL/JHU Lett CQO-2237, 14 Nov 1978.

DELAWARE STATE LEGISLATIVE COMMITTEE ON NATURAL RESOURCES

A Geothermal Workshop was held by the Delaware Legislative Committee on Natural Resources on 15 November 1978. This was the first of several to be conducted by the Delaware Legislature with the help of the National Conference of State Legislatures (NCSL). As part of the workshop, the Laboratory reported on its efforts in support of DOE/DGE to prepare a scenario for the cost of geothermal energy in the Delaware area and the results to date of the energy market survey. Reference 1 documents this presentation and the attendance.

REFERENCE

1. F. C. Paddison, "Geothermal Workshop - Delaware," APL/JHU QM-78-246, 17 Nov 1978.

PENROSE CONFERENCE ON HEAT TRANSPORT PROCESSES

During the week ending 17 November 1978, J. E. Tillman of APL participated in a Geological Society of America Penrose Conference on heat transport processes in the earth at Vail, CO. The conference was limited to 60 attendees from research laboratories, academic institutions, and industry and was designed to stimulate informal discussion. It was supported in part by DOE.

Although based on a central theme of heat transport, the conference covered the following range of topics: aquifer storage, radioactive waste storage, mantle convection, magma convection and emplacement, coal gasification, and oil shale retorting. In general, the discussions centered on approaches to the numerical

(continued)

modeling of thermal and hydrologic processes in the earth. The main points applicable to hydrothermal issues discussed at the conference are summarized in Ref. 1.

Some of the conclusions that can be drawn from the aquifer model talks are that (a) the amount of data available from testing does not warrant complex models - at this point analytical models are more useful; (b) in the Atlantic Coastal Plain reservoirs, a one-phase model is all that is necessary; and (c) fracture permeability is usually significant in sedimentary rock aquifers.

A point of interest to the APL geothermal effort was reported by T. Lewis of the Canadian Department of Energy, Mines, and Resources. Mr. Lewis reported that Canada is currently drilling into a Paleozoic sedimentary basin in order to recover 70°C water from a 2-km depth for space-heating applications (the Williston Basin beneath Regina, Saskatchewan).

REFERENCE

1. J. E. Tillman, "Penrose Conference on Heat Transport Processes," APL/JHU QM-78-251, 30 Nov 1978.

POTENTIAL FOR GEOTHERMAL ENERGY USE AT NEWPORT NEWS, VA

On 21 November 1978 F. C. Paddison and J. E. Tillman visited the town manager's office in Newport News, VA. A presentation was made of the current DOE/DGE program in Virginia, and the specific possibilities of using geothermal resources at Newport News were discussed (Ref. 1).

Newport News is a community with a population of about 125 000 people primarily supported by the ship building industry. The town of Hampton, which is approximately the same size and is nearby, is the site of Langley Air Force Base. The Newport News shipyard is expecting to build liquid natural gas (LNG) tankers and the next nuclear carrier for the Navy. After these ships are built the shipyard faces a 50% reduction in its 25 000 employees. The economic impact is, of course, considerable; however, the yard hopes to obtain financial help from the Office of Economic Opportunity (OEO) and other federal programs.

Two areas planned for industrial development in Newport News will probably be built with partial federal funding. The first is an industrial park and housing development near the Newport News airport. The second is a marina containing an industrial seafood processing area that will be built as part of the new tunnel and interstate highway to Portsmouth. Geothermal energy is probably not cost effective today for space heating in the Newport News area since the expected water temperature at the base of the sedimentary sequence is only 100 to 110°F. However, this resource might be adequate and cost competitive if it could be used in the industrial park.

The industrial park and the new housing development seem to be natural candidates for application of the Community Annual Storage Energy System concept (CASES, see Ref. 2), particularly since there are 25 large (40 by 15 by 100 ft) waterproof, earth-covered ammunition storage buildings on the site that could be used to store water.

The current Program Research and Development Announcement (PRDA) was discussed. Newport

News planning personnel will consider whether or not to respond.

REFERENCES

1. F. C. Paddison and J. E. Tillman, "Visit to Town of Newport News, Virginia," APL/JHU QM-78-248, 28 Nov 1978.
2. Section 18, Quarterly Report, Jul-Sep 1978, APL/JHU EQR/78-3.

PRESENTATION OF GEOTHERMAL POTENTIAL IN VIRGINIA

On 24 November 1978, a meeting was held with members of the Virginia Transportation and Natural Resources Department, the State Energy Office, and the Governor's Office to review the DOE/DGE Program on the Atlantic Coastal Plain and in Virginia, in particular. The Laboratory reported on the scenario preparation and the results of the energy market survey in Virginia. Reference 1 documents this presentation.

REFERENCE

1. F. C. Paddison, "Presentation of Geothermal Potential in Virginia," APL/JHU QM-78-249, 28 Nov 1978.

GEOTHERMAL RESOURCES COUNCIL MEETING

R. Weissbrod of Metro Center attended the Geothermal Resources Council Conference on the Commercialization of Geothermal Resources, held in San Diego, CA, on 28-30 November 1978 (Ref. 1). The conference was designed to provide financial/investment institutions with a background in geothermal energy, and to examine the major concerns and limitations of utilities, discuss the various funding programs currently available, and present case histories and comments from several operators, utilities, financial institutions, and engineering firms now involved in geothermal development. Papers were presented on a variety of topics, including an overview of worldwide geothermal developments; procedural requirements for developing geothermal resources; geothermal reservoir evaluation; economics, risks, and size of geothermal projects; geothermal energy legislation; federal geothermal loan guaranty and pending programs; geothermal energy market potential in industrial processing; a market assessment of geothermal growth and development in the western U.S.; leveraged leasing of a geothermal power plant; joint venturing for geothermal development; federal tax treatment of geothermal exploration and production; a review of western state tax laws applied to geothermal development; financing of a commercial geothermal development in terms of an operator's objectives and constraints; a utility's evaluation of potential broad-based geothermal development; and financing needs and constraints from a utility viewpoint. Participants included representatives of financial and academic institutions, utilities, government, private engineering and consulting firms, and corporate industry.

REFERENCE

1. "A Conference on the Commercialization of Geothermal Resources," Geothermal Resource Council, Nov 1978.

FINANCING OF GEOTHERMAL EXPLORATION

On 4-5 December, a seminar was held at New York University School of Continuing Education on Financing Oil and Gas Ventures, by W. A. Armfield, Jr. With the expectation that financing geothermal ventures could be similar in scope and attract the same type of investors, A. M. Stone of APL and R. Weissbrod of the Metro Center attended to learn whether there were sophisticated ways to attract risk capital. Mr. Armfield has had a successful career in putting together limited partnerships with risk capital of the order of \$10 million per venture. He is the author of How to Sell Oil and Gas Drilling Programs Successfully.

The course covered the following topics: sources of start-up capital, sources of additional equity capital, capital for initial growth, drilling programs for individuals, and sophisticated sources and approaches.

The area that applies to geothermal drilling programs in undiscovered reservoirs (wild-cattling) is a drilling program for individual investors. Basically, the risk taken is compensated for in large part by a favorable tax treatment of the investor's normal income (tax write-off of all losses) and retains the possibility of substantial return if the drilling turns up a usable field. Thus the tax-sheltered program appeals to investors in high income tax brackets with considerable funds to invest. The estimate is that up to \$250 million are available annually for drilling ventures. The tendency of late is to participate in fully registered limited partnership under the SEC Act of 1933, rather than Section 4(2) with Rule 146 interpretation exemption. Under certain sophisticated conditions of leverage, up to 200% loss of the amount at risk can be applied against other income. There appear to be precedents in the housing field for similar tax shelters. These technicalities are being investigated for possible application or precedent-setting to encourage commercial risk-taking in geothermal exploration.

GEOTHERMAL RESOURCES COUNCIL SECTION PLANNING MEETING

On 6 December 1978, APL personnel met with J. Renner and T. Vaught of Gruy Federal, Inc., to discuss the formation of a local chapter of

the Geothermal Resources Council (GRC) for the Mid-Atlantic States. It was agreed that a letter would be drafted to invite GRC members and other interested parties to attend an organizational meeting during the GRC Hot Springs, VA, meeting in April. Dr. Renner has obtained a list of GRC members and W. J. Toth of APL will obtain a list of invitees to the GRC conference.

GEOTHERMAL ENERGY POTENTIAL FOR WALLOPS ISLAND, VA

On 3 November and 15 December 1978, F. C. Paddison and J. E. Tillman discussed the potential of geothermal energy applications at Wallops Island with the management of the NASA center. The resource beneath the island is believed to be water hotter than 150°F at depths of about 5000 feet. Quantity and salinity of the water are unknown but reinjection or ocean dumping is thought to be necessary.

The NASA center at Wallops Island presently has a central steam plant (that burns No. 6 fuel oil) and a distribution system to most buildings. In most cases, the steam is used to heat water through a heat exchanger that circulates in a closed loop in each building. Steam is distributed in the winter for space heating and in the summer to help dehumidify. Such high use would result in lower costs when using geothermal energy.

The NASA center, which has an edict to decrease its energy consumption by 50% by 1980, has already achieved a decrease of 30%. They are interested in investigating geothermal energy at the center and have informally requested assistance from the Laboratory to assess their potential at Wallops Island and will determine how to implement conversion. Meanwhile, NASA will supply APL with daily temperature and utilization records.

A future meeting is planned with personnel from NASA Langley and NASA headquarters in attendance, probably in Washington, DC.

REFERENCES

1. J. E. Tillman and F. C. Paddison, "Visit to Wallops Island, NASA Station," APL/JHU QM-78-237, 8 Nov 1978.
2. J. E. Tillman, "Geothermal Energy Potential for Wallops Island, Virginia," APL/JHU QM-78-264, 18 Dec 1978.

A METHOD TO QUANTIFY INSTITUTIONAL CONSTRAINTS

APL is conducting an investigation for DOE to determine the institutional problems associated with the development of hydroelectric power at existing low-head dams in the eastern United States. The Laboratory is seeking to identify and understand the institutional, economic, and environmental constraints that affect hydroelectric resource development. We have interviewed large and small privately owned and municipal utilities; state energy, environmental, and water resource offices; public utility commissions; insurance companies; district offices of the Corps of Engineers; and entrepreneurs to determine the problems and prospects for hydroelectric development at existing dams. We are working with the Center for Metropolitan Planning and Research of JHU in an interdisciplinary economic/political study to determine the amount of a subsidy and how best to apply it for maximum leverage in encouraging hydroelectric development. To support the study, a data base for the Mid-Atlantic Region and a methodology for its use have been constructed. The purpose of this article is to describe the methodology and its potential use.

DISCUSSION

The methodology involves determining the potential hydroelectric energy output within a designated area versus the incremental costs of hydroelectric generation. The resulting hydroelectric energy supply curve (kWh versus ¢/kWh) is valuable for determining which governmental policies will encourage the greatest development of the resource. Here are some of the questions this tool should help to answer: What types of hydroelectric developers should be encouraged and how should that be done? What impacts do the present licensing procedures have upon the supply? What are the impacts of the present environmental and recreational requirements? What government subsidies, loans, assistance, and risk-sharing (e.g., a federally assisted liability insurance program) are needed?

To give an example of its potential value, the model was applied to existing nonhydroelectric dams within Pennsylvania. Figure 1 is a plot of the potential hydroelectric energy supply curve for those dams. Two cases are shown in Fig. 1: development of the potential by private developers and by public developers (such as municipalities and the state and federal governments). (Rural electric cooperatives are included in the category

Fig. 1 Potential hydroelectric energy for 347 nonhydroelectric dams in Pennsylvania versus two levels of annual fixed charge rates (AFCR). (78-4/43)

of public developers.) The key input to the model that distinguishes between types of developer is the annual fixed charge rate, which was assumed to be 17.9% for private developers and 10.4% for public.

For a price of electricity to the developer of 2.5¢/kWh (the average running rate for the Pennsylvania, New Jersey, and Maryland Power Pool), the expected annual output of hydroelectric energy from public developers is 9×10^8 kWh, or 3.8 times the energy expected if the developers are all private. Thus a 72% increase in the annual fixed charge rate results in a decrease in the supply by a factor of 3.8 for a price of 2.5¢/kWh. The significant impact of the annual fixed charge rate on the potential hydroelectric development within Pennsylvania must be factored into any governmental policies encouraging development of the resource. For example, if private developers were relied on for hydroelectric development, a government subsidy of 1.5¢/kWh over the 2.5¢/kWh price would be required for an equivalent development by public developers. This would mean an annual public expenditure of \$13.5 million within Pennsylvania alone.

REFERENCES

1. "Dams, Reservoirs, and Natural Lakes," Comprehensive Water Resources, Planning Inventory No. 1, Bureau of Engineers, Harrisburg, PA, Bulletin No. 5, 1970.
2. "Problems of Hydroelectric Development at Existing Dams, Interim Report on the Middle Atlantic States and the Ohio Valley," APL/JHU and Metro Center HE-003/QM-78-243, Nov 1978.

OPERATIONAL RESEARCH, HYDROELECTRIC POWER
DEVELOPMENT

§ 17

Small-Scale Hydroelectric ZP30CQO

Support: DOE/RA

J. W. Follin, Jr. (APL) and F. Bennett (JHU/Metro
Center)

October-December 1978

ECONOMIC STUDY OF SMALL- SCALE HYDROELECTRIC PROJECTS

The economic study of small-scale hydroelectric resources has been integrally related to the costs of redeveloping each dam site, but at the same time has focused on the potential markets as well as potential on-site uses for the power produced. Data on costs specifically associated with gaining access to the market (e.g., interconnection with the utility's distribution grid) have been collected. Estimates of benefits are based on what the various utilities say they would offer per kilowatt-hour to the hydroelectric developer. A life-cycle and cost-benefit analysis of each dam site is then carried out, taking into account projected increases in the real cost of electricity over the life of the project and the effects of inflation on nonfixed costs. Finally, the demonstrated economic feasibility or infeasibility of developing each site is related to key economic and/or market-related constraints.

Preliminary results indicate that the free market economics of small-scale hydroelectric development for the majority of low-head dams is unfavorable. Some dams (about 10%) are feasible for development at present. Other sites with cost-benefit ratios slightly less than 1 could show net benefits under life-cycle analysis or could be feasible depending on the particular developer's

fixed charge factor (i.e., government versus private developer).

The following economic factors have been found to militate against most potential sites for small-scale hydroelectric development: (a) high unit-capacity costs that are not competitive with those of baseload plants; (b) high interconnection costs (relative to the total cost of the project) that the developer must bear in most cases; (c) rates for purchase of the power by the utilities that include only energy costs and not capacity costs (rates are usually based on a particular utility's average hourly running rate, which ranges between 14 and 22 mills among Pennsylvania, New Jersey, and Maryland network utilities); (d) small quantities of firm power (even if a dam has a significant amount of firm power, the utility may not pay for it, if they have capacity in excess of their reserve requirements); and (e) the on-site use of power from dams without firm power that may have to be backed up by the utility, thus incurring standby charges and causing the developer to pay twice for capacity. However, the situation is highly dynamic and will improve as prices of fossil fuels rise, the regulatory process is streamlined, and the manufacture of small hydroelectric equipment becomes standardized.

The life-cycle economic analysis of the sites is entering its final stage, after which more definite conclusions should emerge.

**OPERATIONAL RESEARCH, HYDROELECTRIC POWER
DEVELOPMENT**

§ 18

Small-Scale Hydroelectric ZP30CQO

Support: DOE/RA

J. W. Follin, Jr. (APL) and S. Briscoe (JHU/Metro
Center)

October-December 1978

INSTITUTIONAL AND REGULATORY CONSTRAINTS ON SMALL-SCALE HYDROELECTRIC DEVELOPMENT

Research indicates that the types of legal and institutional constraints on the development of small-scale hydroelectric power and the various impacts of these constraints on the types of developer follow similar patterns in Maryland and Pennsylvania. In general, the constraints are felt in market accessibility, the time and complexity of licensing, and tax liability.

MARKET ACCESSIBILITY

Present limitations on market accessibility suggest that project development on a large scale will not be achieved without the participation of existing power distributors such as investor-owned utilities, municipal electric services, and rural electric cooperatives. Legislation mandating the assignment of retail service areas to existing distributors, as interpreted by state regulatory agencies, effectively precludes the formation of new utilities for retail service. The development of power for sale by nonutilities is restricted as to the number of customers by the states' definitions of public utility service. The sale of power produced by a non-utility for the wholesale market further depends on the willingness of existing distributors to purchase. The retail market for power produced by a nonutility is limited, not only in the number of customers but also in its geographic scope. Condemnation powers are restricted to sites adjacent to the dam itself. The development of power for their own use by individuals or businesses also faces geographic limitations. The obstacles to marketing nonutility power indicate that the active cooperation of existing distributors is required.

LICENSING PROCEDURES

Small-scale hydroelectric projects will require licenses and permits from four levels of government: federal, state, local, and regional river basin commissions. Exactly which permits must be obtained is difficult to determine since requirements vary according to the specific nature of the project.

Furthermore, because no project of this type has been licensed recently in either state, the licensing process itself has not been fixed. The sequence in which permits are obtained and the relationship among permits of the four levels of government have not been established. No single agency has been designated as a clearing house at the state, local, or federal level, for approvals needed at that level by all types of developers. Whatever informal pathways are presently in use are unlikely to continue in the near future. Pending state and federal legislation, the rewriting of existing relevant laws, the structural reorganization of administering agencies, and the promulgation of new agency rules and regulations may all significantly alter licensing procedures in the next few years.

TAX LIABILITY

State and local taxes, an important factor in project costs, vary significantly according to the type of developer. In general, investor-owned utilities are taxed most heavily, and municipal services and cooperatives the least. Nonutility tax liability falls between the two. High tax liability does not necessarily mean that the tax burden is correspondingly high. Because utilities are allowed to pass taxes along to their customers in the form of a surcharge, their tax burden is negligible. For developers whose markets are not guaranteed, such shifting of the tax burden may not be possible. In those cases, the individual tax burden depends on the writeoff of business expenses and taxes against federal income taxes.

FUTURE PLANS

An investigation of the issues identified in the course of research in Maryland and Pennsylvania is presently being carried out in New Jersey. All relevant departments in New Jersey are undergoing reorganization, and published data and interviews are difficult to obtain. This research is not expected to be completed before 15 January 1979.

PROJECTION OF HYDROELECTRIC DEVELOPMENT

As a part of the institutional-economic-environmental (IEE) study of hydroelectric development potential at existing dams, an attempt is being made to determine: (a) the small-scale hydroelectric installations that are currently in operation, (b) those that are in the process of development, and (c) those for which development is being considered in Delaware, Maryland, New Jersey, and Pennsylvania. In addition, several utilities are being contacted in each state to determine attitudes toward and interest in the development of small-scale hydroelectric power. Information is being gathered from individuals in state offices and utilities, the Army Corps of Engineers dam list, state dam lists, the Pennsylvania Master Siting Study, and research proposals submitted to DOE in response to the Program Research and Development Announcement (PRDA).

DISCUSSION

Developing or operating small-scale hydroelectric plants offers valuable inputs to the IEE study. Developers are the best source of information on costs that are required for developing a hydroelectric development model. An understanding of the problems that arise during development and the reasons why development is not being considered should help in making recommendations concerning government actions that could encourage small-scale hydroelectric development.

The existing dams available for hydroelectric development in the four-state area are listed in Table 1.

Of the Pennsylvania dams listed in Ref. 1, only 13% had a hydroelectric potential greater than 50 kW. However, the 13% possessed 87% of the energy potential.

Table 2 gives the status of existing dams within the four-state area that are presently proposed for small-scale hydroelectric development.

A few existing small-scale hydroelectric projects have been identified in the four states. The Hagley Dam on Brandywine Creek in Delaware is owned by the Eleutherian Mills-Hagley Foundation, Inc. The dam has a 28 ft head and a capacity of 500 kW. It has been producing electricity since October 1976 for use by the company. No major problems have been encountered during its development and operation. Parker Pond Dam is owned and operated by W. H. Hinman and is located on Beaver Dam Creek in Maryland. It is a small dam with a 7 ft head; it has been producing electricity for Mr. Hinman's home since 1957.

The Potomac Edison Co. has a number of small hydroelectric installations including eight small-scale hydroelectric sites located in Maryland, Virginia, and West Virginia that have a generating capacity of more than 10 000 kW. The company is examining the possibility of increasing the capacity at Dam No. 4 on the Potomac River, which presently has a generating capacity of 1000 kW.

Table 1
Number of dams found in Corps and state records.

	Corps Records	State Records	Comments about State Records
Delaware	68	33	Very little information on drainage area for each dam.
Maryland	145	145	APL and the state cooperatively determined the drainage areas for Maryland.
New Jersey	543	645	State information on microfilm; state records contain drainage area information.
Pennsylvania	901	2460	Ref. 1 contains drainage area information and is an excellent resource for dam information in Pennsylvania.

Table 2
Proposed hydroelectric developments at existing dams.

State	River	Dam	Owner	Head (ft)	Capacity (kW)	Remarks
Delaware	Red Clay Creek	Haveg	Haveg Industries	14	75	A feasibility study has been completed; electricity will be developed and produced when funds become available.
Delaware	Christina	Dayett's Mill	Mr. Johnson	26	-	Electricity will probably be generated during 1979 for use at the mill.
Delaware	Brandywine	Walker's Mill	Eleutherian Mills-Hagley Foundation	9	175	A proposal had been submitted in response to DOE but was not funded. Hydroelectric power will be developed when funds are available.
Maryland	Patuxent	Brighton	Washington Suburban Sanitary Commission	62.4	100-500	A feasibility study is being performed (DOE funded).
Maryland	Meadow Run	Meadow Run Dam No. 57	J. Davies	27	-	In initial stages of development. Mr. Davies is gathering information on hydroelectric generation and will use electricity for his nearby campground.
New Jersey	Passaic	S.U.M.	City of Paterson	70	4500	A feasibility study has been completed and an application has been submitted for a license to the Federal Energy Regulatory Commission (FERC), 2 Sep 1977.
New Jersey	Maurice	Union Lake	Wheaton Industries	15	-	A proposal submitted to DOE was not funded.
New Jersey	Passaic	Beatties	Passaic Valley Water Commission	32	4000	A proposal submitted to DOE was not funded.
Pennsylvania	Schuylkill	Felix	Pennsylvania Hydro-Electric Development Corp.	14	1000	Applications for preliminary permits were submitted to FERC 11 Jul 1977. Proposals were submitted to DOE but were not funded.
Pennsylvania	Schuylkill	Auburn	Pennsylvania Hydro-Electric Development Corp.	16	500	
Pennsylvania	Schuylkill	New Kernsville	Pennsylvania Hydro-Electric Development Corp.	19.5	1000	
Pennsylvania	Schuylkill	Flat Rock	Pennsylvania Hydro-Electric Development Corp.	36.7	1000	
Pennsylvania	Lehigh	Easton	Pennsylvania Hydro-Electric Development Corp.	21	1000	
Pennsylvania	Schuylkill	Black Rock	Pennsylvania Hydro-Electric Development Corp.	12	1500	A proposal submitted to DOE was not funded.
Pennsylvania	Schuylkill	Norristown	Pennsylvania Hydro-Electric Development Corp.	16	2800	A proposal submitted to DOE was not funded.
Pennsylvania	Conodoguinet	Conodoguinet	Borough of Carlisle	10	400	A proposal submitted to DOE was not funded.
Pennsylvania	Monongahela	Maxwell	Allegheny Electric Cooperative, Inc.	19.5	13500	A feasibility study is being performed (DOE funded). Lengthy licensing time with questionable outcome as the result of intervention by fishermen and environmental interests may hinder development.

A number of investor-owned utilities, municipalities, and rural electric cooperatives were contacted. Most of the utilities had no plans for hydroelectric development. The most common responses were that there are no suitable hydroelectric sites in the service area or that development was not economically possible.

REFERENCE

1. "Dams, Reservoirs and Natural Lakes," Comprehensive Water Resources, Planning Inventory No. 1, Bureau of Engineers, Bulletin No. 5, Harrisburg, PA, 1970.

OPERATIONAL RESEARCH, HYDROELECTRIC POWER DEVELOPMENT

§ 20

Small-Scale Hydroelectric ZP30ACL

Support: DOE/RA

I. R. Thrall

October-December 1978

INSURANCE ISSUES

Earlier reports (Refs. 1 through 3) have discussed efforts at APL to prove the widely held, but elusive proposition that general liability insurance for downstream exposures of low-head hydroelectric redevelopments is generally unavailable. As is usually the case in trying to prove the negative, this has not been easy; we still cannot say beyond a shadow of a doubt that such insurance is unavailable. However, all indications tend to support the view that liability insurance either cannot be purchased through normal channels or is available only at a price that is economically disproportionate to the expected return.

We have specifically sought and received the cooperation of the Special Risk Division of the Insurance Company of North America (INA) in our study. Regrettably, the INA declined our invitation specifically to cost out underwriting premiums for two contrasting hydroelectric projects in Vermont: the proposed Black River Project at Springfield and a small redevelopment of a single dam on the Ottauguechee River near its junction with the Connecticut. Having taken that position, the INA has promised to furnish us with a commentary of its engineering and underwriting approaches to dam liability insurance and has expressed a willingness to become involved in a broadly based underwriting of such coverage, provided it can obtain a formal re-insurance arrangement (possibly with the federal government) until enough premiums to cover catastrophic downstream exposures can be developed.

DISCUSSION

In the course of earlier investigations, we became aware of Senate Bill S-2437, which was passed by the Senate in June 1978 but died when it was not acted upon by the House of Representatives before the end of the session. A portion of S-2437 called for a federal program by which the government, in concert with the insurance industry, would create guarantees and indemnifications for certain dam owners. The arrangement apparently would provide the kind of financial backing suggested by the INA, although the INA has not specifically commented on S-2437 since it

was passed by the Senate. INA was not called upon to testify for or against the bill in hearings held during the spring of 1978. Our suggestion to INA - that it consider submitting comments on the bill to the appropriate Senate subcommittee - was declined. Although we believe that S-2437 contains a number of undesirable features (for example, it is tied to a federal/state dam safety program of questionable desirability), its very existence seems to support the proposition we have been attempting to prove. For this reason, our immediate future action will be directed toward interfaces with the appropriate Senate sponsors to ensure that DOE and the private insurance industry have an opportunity to make well-founded inputs into whatever version of S-2437 may be introduced in the forthcoming session of Congress.

At the same time, we are concerned that the cost of on-site insurance may be significantly higher than is popularly believed. A Federal Energy Regulatory Commission (FERC) document (Ref. 4) suggests that an insurance cost equivalent to 0.25% of plant investment is appropriate for inclusion in estimates of the operational costs of low-head hydroelectric redevelopments. Even if the suggested factor were 100% too low, it would probably not have a devastating impact on the expected returns. However, reliable information available to us indicates that the actual cost of insurance (exclusive of downstream liability insurance) may be 10 to 20 times higher than the FERC estimate. We believe it is important that would-be redevelopers have access to accurate insurance estimates. Therefore, we will direct future efforts toward resolving the obvious discrepancies between published estimates and actual case histories.

REFERENCES

1. Section 25, Quarterly Report, Jan-Mar 1978, APL/JHU EQR/78-1.
2. Section 22, Quarterly Report, Apr-Jun 1978, APL/JHU EQR/78-2.
3. Section 16, Quarterly Report, Jul-Sep 1978, APL/JHU EQR/78-3.
4. "Hydroelectric Power Evaluation," FERC, Aug 1978.

OPERATIONAL RESEARCH, HYDROELECTRIC POWER DEVELOPMENT

§ 21

Small-Scale Hydroelectric ZP30CQO

Support: DOE/RA

C. S. Leffel, Jr.

October-December 1978

INSTITUTIONAL PROBLEMS IN DEVELOPING SMALL-SCALE HYDROELECTRIC POWER IN THE OHIO VALLEY

The study of institutional and other restraints on the development of small-scale hydroelectric generating facilities (50 kW to 15 MW) for the Ohio Valley is continuing. For study purposes, the Ohio Valley is defined as the basin of the Ohio River and its tributaries (exclusive of the Tennessee River) plus the area to the north that is covered by the power grids belonging to the East Central Area Reliability Coordinating Agreement (ECAR). The investigation to date has consisted of visits to ECAR, to selected federal and state agencies, and to utilities in the Ohio Valley-ECAR region and Richmond, VA. The objectives of these visits are to determine: (a) what dams exist, (b) restrictions on impounded waters, (c) utility attitudes and policies concerning hydroelectric power, and (d) the energy problems of state agencies.

FUTURE PLANS

Information gathering in the ECAR region of the Ohio Valley has been essentially completed. A preliminary report on the institutional, financial, and legal restraints that impede the development of small-scale hydroelectric power will be published in early 1979. That report will be followed by a revision that will contain specific recommendations to aid and hasten the installation of small-scale hydroelectric capacity. Early in 1979, the information gathering process will begin in the southeastern states.

SUMMARY

Almost all the production of electricity in the Ohio Valley is from coal; excluding the Tennessee and Cumberland Valleys, less than 1% is generated by hydroelectric power. The price of electricity has been low compared to that of New England and the Middle Atlantic States (Ref. 1). As a consequence of this and of topographical factors, hydroelectric development has played a negligible part in the planning of private utilities. During the present quarter, further information has been gathered in Ohio, Kentucky, and Virginia. Ohio has made extensive water studies and is the one state in this region that possesses dam inventories that are independent of the Corps of Engineers' lists. However, hydroelectric development has been essentially ignored. Western Virginia, because of its high precipitation rate and peak electrical demands in winter, apparently is a favorable area

for small-scale hydroelectric development, but detailed studies of specific sites have not been made. The Kentucky Department of Energy has not regarded the Federal Small-Scale Hydroelectric Program as being very useful for them, chiefly for economic and marketing reasons. However, outside of economic feasibility, none of the agencies visited in the three states sees any serious state impediments to small-scale hydroelectric development.

DISCUSSION

The Water Division of the Ohio Department of Natural Resources (ODNR) has made extensive studies of the state's water resources and problems. Three of five regional water plans, which include water-use planning through 2020, have been completed. They include detailed information on stream drainage areas, precipitation, and minimum and average stream flows. One regional plan for southwest Ohio has been examined. It makes the point that, for that area, hydroelectric potential is negligible. However, ODNR has a list of 6432 dams, compared with 926 in the federal inventory. In Ohio, 89 of 223 Class I dams have been inspected under the National Dam Safety Program. The state also has an active dam inspection program of its own. The policy of ODNR is to not allow hydroelectric generation on any dam owned by the state (Ref. 2). ODNR issues data on flow duration for the river-flow gauging stations in the state. For the generation of electricity, the ODNR studies emphasize cooling problems of thermal plants and tend to ignore hydroelectric power, a point of view also found in the studies of the Ohio River Basin Commission (Ref. 3).

In Kentucky, the Division of Water Resources has no dam lists independent of the Corps of Engineers', nor does it publish a summary of water flow independent of the USGS tabulations. Twenty of the 40 nonfederal Class I dams in Kentucky have been inspected under the National Dam Safety Program.

According to the Kentucky Department of Energy, the state's energy problem is the lack of natural gas. Most (96%) of the state's electricity is generated from coal; the remainder is from hydroelectric power. An internal memorandum within the state's Department of Energy (Ref. 2) questions the value of the Small Hydroelectric Power Projects Act of 1977 for Kentucky because of the 15 MW power limit. However, the only impediments they see to the development of hydroelectric power are economic ones. The coal interests are not perceived as adversaries, since their overseas demand exceeds their supply capability. Kentucky Utilities, which operates a 1.7 MW hydroelectric plant on Lock 7 of the Kentucky River, questions whether the facility is worth keeping in operation since it must be shut off during the summer because lock operation requires all of the river flow. The three hydroelectric sites that have been retired in Kentucky are now state-owned. One private citizen is building a dam and hydroelectric facility for his own use.

The only part of Virginia in the Ohio Valley-ECAR region is west of Roanoke. The Division of Energy regards that part of the state as the most favorable for hydroelectric

development because of its high rate of precipitation (about 50 in./yr), relatively even stream flows, and winter peak for electrical power demand. They have calculated simple hydroelectric power output for several local governments but have not found the results economically promising. They feel that they have inadequate information on small turbines and their costs. The State Water Control Board has no independent dam lists, but summarizes the USGS stream flow data in the form of flow duration information and will complete a new publication in early 1979. Of Virginia's 200 Class I dams, 55 have been inspected under the National Dam Safety Program. The Water Control Board thinks Virginia has small-scale hydroelectric potential and favors such installations; it is somewhat surprised at the new federal interest in this subject after years of indifference (Ref. 4).

The Virginia State Corporation Commission (the utility regulating agency) has issued a new code that regulates the price and conditions under which a private utility can sell standby or parallel power to a user who has his own generating facility.

The largest utility in the state, Virginia Electric and Power Company (VEPCO), is not in ECAR, but its hydroelectric plans are interesting. VEPCO plans to install 2100 MW of pumped storage capacity in Bath County, VA, by 1982-83. This facility, which is designed to operate during the 4 h peak demand period, supplements its nuclear power generating capacity. During periods of low demand, it will be used to pump the water back up to the upper reservoir (1860 ft head). The only small-scale hydroelectric plant now operating (Cushaw, 7.5 MW) was never licensed by the Federal Power Commission. Under present law, it must be licensed by the Federal Energy Regulatory Commission

(FERC). However, the process has not gone smoothly. VEPCO is now considering a new application that will meet with FERC approval and not cost VEPCO an unreasonable sum of money.

The Richmond Department of Public Utilities, a municipal utility, now operates two small hydroelectric facilities on the James River (the largest is about 1 MW) and has plans for increasing its hydroelectric capacity. The plans have not been approved by the city and are unavailable at present. However, they are made, at least in part, in the expectation that the price the city now pays VEPCO for electricity will increase sharply in 1981. Richmond did not respond to the Department of Energy Program Research and Development Announcement (PRDA) ET-78-D-07-1706 because its plans were completed before it was aware of the PRDA.

REFERENCES

1. Section 15, Quarterly Report, Jul-Sep 1978, APL/JHU EQR/78-3.
2. R. von Briesen and E. H. Boyd, "Trip Report to the Ohio Department of Natural Resources, Division of Water Resources, Columbus, Ohio, the Kentucky Department of Energy and the Kentucky Department of Natural Resources, Frankfort, KY . . ." APL/JHU QM-78-257, 12 Dec 1978.
3. "Ohio Main Stem," Ohio River Basin Commission, 36 East Fourth St., Cincinnati, OH, Jan 1978.
4. R. von Briesen, C. S. Leffel, and W. Chapman, "Trip Report to the Virginia State Energy Office, State Corporation Commission, Water Control Board, Virginia Electric and Power Company, and the Richmond Department of Utilities," APL QM-78-254, 5 Dec 1978.

COMMENTS ON LIMITED TASKS, SMALL-SCALE HYDROELECTRIC DEVELOPMENT

COMMERCIALIZATION PLAN

APL generated the technical parts of a commercialization plan in cooperation with R. E. Burr of DOE. The plan contains APL's view of the basic technical steps and institutional, legal, and economic analyses required to permit the federal government to proceed with an action program that will lead private industry to redevelop hydroelectric power on old dams. Several of the key analyses needed to complete the action plan include: (a) methods to decrease the financial risk (so that financing becomes available) by reducing licensing procedures and time, reducing equipment costs, and simplifying connecting and safety equipment needed to tie to existing transmission lines; (b) methods to apply (and justify) a possible subsidy for maximum leverage; and (c) clarification of pricing policies of major utilities to permit valid economic analyses of proposed development.

SMALL-SCALE HYDROELECTRIC PROGRAMS AT FRANKLIN PIERCE LAW INSTITUTE AND DARTMOUTH COLLEGE

On 18 October, 8 November, and 12 December, R. J. Taylor of APL met with P. Brown from the Franklin Pierce Law Institute, D. Meadows from the Thayer School of Engineering at Dartmouth College, and their colleagues. On two of these occasions he also met with the Thayer School technical advisory committee on systems dynamics modeling of hydroelectric development in the United States. The purposes of the meetings were to: (a) exchange information concerning the hydroelectric studies at Franklin Pierce, the Thayer School, and APL, and (b) describe the Thayer School's approach to systems dynamics modeling and discuss the assumptions (and their validity) that are being used in the modeling.

On 12 December, Mr. Meadows gave an outline of the methodology used in systems dynamics modeling. First, the system to be modeled is described verbally including its constraints and goals and the key variables of interest. Second, the reference mode of the system is established by plotting the key variables of interest versus time over a period of history until the present and causal relationships are estimated. Third, a causal loop diagram is generated that indicates the relationships between the various components of the system

being modeled. These relationships are represented as feedback loops that control system behavior. Two types of causal variables, endogenous and exogenous, are shown in the causal loop diagram. Endogenous variables are controlled and influenced by other variables in the system; exogenous variables help determine system behavior, but are not acted upon or influenced by the system itself. Thus there are no feedback loops between the system and exogenous variables. Fourth, a flow diagram is made using the causal loop diagram as the model. The flow diagram employs a set of standard symbols so that the system can be easily understood. The symbols represent sinks (or sources), levels, rates, and flow. Fifth, the flow diagram is programmed into a computer using a computer language called DYNAMO, a language specifically designed for programming systems dynamics models.

CONTRIBUTION OF THE NATIONAL DAM INSPECTION PROGRAM TO THE SMALL- SCALE HYDROELECTRIC PROGRAM

Under Public Law 92-367, a dam inspection program is now being undertaken for Class I (high hazard) dams. In two states recently visited (Kentucky and Virginia), the program is one-third to one-half completed. The reports of these inspections, carried out by contractors under the direction of the Army Corps of Engineers, are sent to the state governors for action.

The few reports we have been able to examine add valuable information to the Corps of Engineers' dam inventory lists that is of interest to the small-scale hydroelectric program. The additional information includes (a) the history of the construction of the dam, (b) construction drawings if available, (c) current operation of the dam, (d) description and conditions of water inlets, penstocks, spillways, etc., (e) the drainage area, and (f) an evaluation of the dam's condition. The information would be of great value for resource assessment in general and to a prospective developer considering the installation of hydroelectric generating capacity at existing dam sites.

APL has recommended to DOE that they consider negotiating with the Corps for slight additions to the National Dam Inspection Program that would make it even more valuable to the small-scale hydroelectric program (Ref. 1).

REFERENCE

1. C. S. Leffel, R. von Briesen, and W. B. Chapman, "Possible Changes in the Dam Safety Inspection Program to Assist the Small-Scale Hydroelectric Program," APL/JHU QM-78-242, 15 Nov 1978.

LICENSING PROBLEM AT SMALL-SCALE HYDROELECTRIC SITES NOW OPERATING

A number of small-scale hydroelectric generating plants now operating are not presently licensed by the Federal Energy Regulatory Commission (FERC) (Ref. 1). We have encountered two such sites: the 17.5 MW installation at Monticello, IN, owned and operated by the Northern Indiana Public Service Company (NIPSCO); and the 7.5 MW installation at Cushaw, VA, owned and operated by the Virginia Electric and Power Company (VEPCO). NIPSCO has filed a brief with FERC (Ref. 2) requesting that its installation be declared not subject to FERC jurisdiction. VEPCO has filed for a license for its hitherto unlicensed Cushaw facility but has experienced difficulties meeting FERC requirements. It is now studying a new application attempt. Both of the plants have been operating for about 50 years.

The subject was discussed with F. Springer of FERC on 22 Nov 1978. The problem is complicated by changes in law and regulations since the Federal Power Commission (FPC) was created in 1920. At present, the jurisdiction of FERC extends to all hydroelectric plants, and its Short Form Minor Application can be used only for installations below 1.5 MW. No distinction now exists between new construction and installations that have been operating unlicensed for

years. The licensing of plants that are unlicensed but operating is a low priority item for FERC; this, combined with the reluctance of owners to complete properly the application, has often resulted in an adversary relationship.

FERC is now preparing a Short Form Major Application that will apply to existing dams, reservoirs, and hydroelectric sites for the operation or installation of hydroelectric plants with capacities greater than 1.5 MW. This form should simplify the licensing problems of NIPSCO and VEPCO and of new developers at existing dams.

Mr. Springer stated that FERC had considered issuing a booklet on licensing procedures and thinks that this publication should be a cooperative effort with DOE/Resource Applications (RA). FERC has reviewed, with severe criticism, a separate effort not supported by DOE.

REFERENCES

1. "Hydroelectric Power Resources of the United States, Developed and Undeveloped," Federal Power Commission, Washington, DC, Nov 1976.
2. "In the Matter of the Northern Indiana Public Service Company," letter from Eichhorn, Morrow, and Eichhorn, Attorneys at Law, to K. F. Plumb, Secretary, Federal Energy Regulatory Commission, Washington, DC, 11 Apr 1978.

OTEC LIGHTWEIGHT CONCRETE INVESTIGATION

The Ocean Thermal Energy Conversion (OTEC) concept requires a large cold-water pipe to transport water from a depth of 3000 ft to the ocean surface. Of the many materials studied, concrete seems to offer the best possibility of an economical structure. The feasibility of minimizing weight by developing a near-neutral-buoyancy concrete with adequate strength is being investigated.

SUMMARY AND CONCLUSIONS

The first phase of the two-phase lightweight concrete program has been completed. In this phase, two contractors, Portland Cement Association (PCA) and ABAM Engineers, have developed separate concrete mixes, each of which demonstrates adequate properties for use in the OTEC cold-water pipe.

The mix developed by PCA is made up of Livlite (an expanded shale), fly ash, and cement. It has a density of 76 lb/ft³ and a 7-day compressive strength of 3800 psi. It is only slightly more costly than regular concrete and requires no special mixing procedure. The ABAM mix is a combination of cement and cenospheres (a by-product of coal-burning power plants). It requires the addition of latex for adequate tensile strength and has a density of 75 lb/ft³ and a 7-day compressive strength of 4100 psi. However, both the cenospheres and latex are expensive, resulting in an appreciable cost increase.

Material tests to determine absorption, tensile strength, pull-out resistance, shrinkage creep, and modulus of elasticity have been completed or are under way. All of these follow expected trends and indicate adequate properties for an OTEC cold-water pipe. Absorption is higher than with normal concrete and has been measured as 20% of weight at pressures of 1400 psi (3000 ft depth). Further material characterization as well as large-scale structural tests will be completed in Phase 2.

The Lightweight Concrete Investigation is a part of the OTEC Ocean Engineering Program. A second part of the program consists of the at-sea cold-water pipe verification tests. In these tests a 5-ft-diameter 800-ft-long pipe is being deployed from an oil rig to measure its response to the sea. The experimental results will be correlated with analytical predictions. The rig is expected to be at sea in January, and test results should be available in the next quarter.

FUTURE PLANS

During the second phase of the Lightweight Concrete Investigation, which will begin in

January, the use of the material as a cold-water pipe will be explored. Material characterization will be continued, and large-scale (probably one-third-scale) models of the cold-water pipe will be constructed and tested. The hinge construction, an integral part of the proposed pipe, will be developed and tested in detail. Individual tests on the hinge elastomer and the reinforcing rod placement are planned.

DISCUSSION

Of the many materials studied for the OTEC cold-water pipe, concrete seems to offer the best possibility for an economical structure. However, such a structure presents a uniquely challenging problem in both design and construction. A "minimum" pipe made with conventional high-strength concrete would be 30 ft in diameter and 1 ft thick. Such a pipe, 3000 ft long, would weigh 21 000 long tons dry, and 13 000 tons submerged. Unfortunately, such a minimum pipe appears to be insufficient for the imposed stresses. Various computer analyses indicate a 100-yr design moment on the order of 10⁹ to 10¹⁰ ft-lb. This would require a pipe several feet thick, weighing hundreds of thousands of tons. The construction and emplacement of such a pipe would probably not be economically feasible.

Two technical innovations have been proposed in order to overcome this dilemma. First, it has been proposed to use a concrete of near-neutral buoyancy (i.e., 70 to 75 lb/ft³). Such a pipe would have a small net weight when submerged, which would greatly facilitate the construction and emplacement. To obtain the desired density, strength, and absorption resistance, a special concrete is required. Second, it has been proposed to use one or more "hinged" joints in the pipe to control the bending stresses. This would confine high stresses to the uppermost portions of the pipe.

A two-phase program was devised to develop these two concepts. The first phase would be devoted to design and testing of the mix, design of the pipe joints and flanges, development of construction methods, and development of a test program for the actual pipe. The second phase would encompass the fabrication and testing of pipe sections (or scaled models thereof).

Two contractors, PCA and ABAM Engineers, participated in the first phase to demonstrate the feasibility of fabricating a structural grade lightweight concrete. The work statement for each was established as follows: "Design and test a lightweight concrete suitable for use in the OTEC cold water pipe. It is desired to have the density as near that of seawater (64 lb/ft³) as practical, and the compressive strength as high as possible. The elastic modulus is desired as 0.5 to 1.0 × 10⁶ psi." To be a viable structural member, a compressive strength of 3000 psi was then established as a goal.

A number of different concrete mixes were made with densities ranging from 57 to 90 lb/ft³ as shown in Fig. 1. As expected, the lower weights have lower strengths, but a reasonable strength is obtainable with a density in the 70 to 75 lb/ft³ range. The exploratory mixes shown in Fig. 1 were used for selecting a pre-

Table 1
OTEC lightweight concrete mix 49, ABAM Engineers.

Mix Design	Weight (lb)
Cement	1000
Cenospheres	540
Latex	315
Antifoam	6
Water	210
Fresh unit weight (lb/ft ³)	75
7-day compressive strength (psi)	4100
Absorption at 1400 psi (%)	20
Tensile strength (psi)	450
Modulus of elasticity (psi)	1.25×10^6

Table 2
OTEC lightweight concrete mix 13, PCA.

Mix Design	Weight (lb)
Cement	540
Fly Ash	86
Coarse Livlite	363
Medium Livlite	392
Fine Livlite	312
Water	315
Fresh unit weight (lb/ft ³)	76
7-day compressive strength (psi)	3800
Absorption at 1400 psi (%)	20
Tensile strength (psi)	~200
Modulus of elasticity (psi)	2×10^6

Fig. 1 Early test results of OTEC lightweight concrete investigation. (78-4/44)

ferred mix to be developed and characterized by each contractor. The preferred mixes are shown in Tables 1 and 2.

Tests on the early mixes indicated a high water absorption under pressure. At a pressure of 1400 psi (3000 ft depth) absorptions as high as 30% of weight were measured. With the selected mixes, this has been reduced to 20%. Although it remains to be confirmed in Phase 2, it is assumed that the absorption curve is approximately linear with depth. Thus, the pipe is expected to have a deployed weight averaging about 84 lb/ft³ (76 lb/ft³ at the top, 91 lb/ft³ at the bottom).

Each of the mixes developed is suitable for a cold-water pipe. Optimization on the basis of cost and strength will be explored in Phase 2 prior to large-scale tests.

FABRICATION AND TEST PREPARATION OF THE APL CORE HEAT-EXCHANGER UNIT

Part of the APL concept for Ocean Thermal Energy Conversion (OTEC) plant-ships is the use of low-cost, "shell-less" aluminum heat exchangers having large diameter (3 in. OD) tubes containing ammonia as the working fluid. Each tube is approximately 700 ft long and is folded into 25 horizontal passes (or 43 for the core test unit, as described later). Seven of these tubes are nested in each vertical plane with 1.25 in. of clear space between the vertical planes to permit removal of biofouling from the outside surfaces with compatibly designed cleaning heads (brush or ultrasonic). Alternate planes are staggered, i.e., offset by 1.875 in. in the vertical direction. Seawater flows from a head pond above the tube bundle down through it and out the bottom of the plant-ship as shown in Figs. 1a and 1b.

A full-scale core test unit of the proposed heat exchanger consisting of three full-length folded tubes in a water box has been fabricated by the Trane Company, and preparations are being made to test this unit as an evaporator and a condenser at the Argonne National Laboratory (ANL) in Chicago, IL. This report describes the core test unit and the test plan.

SUMMARY

The core test unit, shown in Figs. 2 and 3, consists of three parallel 3 in. OD aluminum tubes folded into 43 passes each (14.33 ft straight horizontal runs) and contained in a water box 23.5 ft high, 3.9 ft deep, and 20 ft wide. Dummy half-tubes are included on each side of the three-tube bank to maintain flow simulation on the water side. The tubes are staggered relative to each other, and the water box includes a head pond 5.4 ft high to simulate features of the proposed plant-ship unit. In the evaporator testing phase, the unit will be connected to the ANL ammonia flow loop with conditioned liquid ammonia entering at the bottom of each tube and two-phase ammonia of approximately 60% vapor quality exhausting at the top into demisters.

The objectives of these tests are to provide a basis for validation of the APL analytical simulation and to estimate the performance of a full-scale heat exchanger of an operational plant-ship. The technical approach is to measure (a) the overall heat transfer of the unit with set fluid flow conditions, (b) the ammonia side (two-phase flow) and water side pressure drops, (c) the internal flow stability of the three parallel tubes, and (d) the effect of heat transfer enhancement on the ammonia side produced by swirlers contained in the first passes of each tube.

(a) Schematic diagram of APL evaporator

(b) Three-quarter view of 2.5 MW_e (net) condenser module having 1.5×10^5 ft² (1.4×10^4 m²) (nominal) surface area.

Fig. 1 The APL concept for multipass, two-phase-flow heat exchangers with the ammonia inside the tubes. (78-4/46)

The test plan for the evaporator consists of measuring the performance of the unit at nominal conditions (Table 1) and then varying one or more of the conditions over the ranges indicated to cover the expected variations of the plant-ship heat exchanger. The core test heat exchanger was delivered to ANL in mid-October; set-up of the unit was begun in late December and is expected to be completed in March 1979.

Table 1
Evaporator core test conditions.

Parameter	Nominal Condition	Range of Variation
Heat duty (Btu/h)	3.2×10^6	2.8×10^6 to 3.6×10^6
Water flow rate (gal/min)	3200	2800 to 3600
Ammonia flow rate (lbm/s per tube)	1.0	0.7 to 1.5
Ammonia inlet temperature ($^{\circ}\text{F}$)	72	55 to 72
Ammonia inlet valve pressure drop (psid)	3	0 to 4
Demister configuration	Individual for each tube	Single common
Swirl element configuration	Installed in first pass of each tube	Removed

Fig. 2 APL core test heat exchanger during assembly at the Trane Co. (78-4/48)

BACKGROUND

During the past two years, experiments investigating the heat transfer characteristics of the heat exchangers have been conducted at APL. Existing correlations for the internal (ammonia-side), two-phase heat transfer coefficients and the conditions under which significant vaporization begins have been validated in tests on an electrically heated tube simulating one pass of the full-scale heat exchanger (Refs. 1 and 2). The external (water-side) correlations for the circumferential heat transfer coefficients and for pressure drops through tube arrays have also been validated (Refs. 3 and 4). In addition, tests using the external flow unit are presently being conducted at Keahole Point, HI, to measure the effects of bio-fouling and cleaning techniques on the water-side heat transfer.

Fig. 3 APL core test unit assembled. (78-4/49)

FUTURE PLANS

A six-week testing period at ANL with the core unit operated as an evaporator is planned for March and April 1979. The unit will then be reinstalled in a different location in the test circuit and tested as a condenser (with the ammonia flowing down through the same tubes rather than up) in late summer or early fall of 1979.

DISCUSSION

The core test unit of the heat exchanger (Figs. 2 and 3) simulates the flow conditions and geometry of the proposed plant-ship heat exchangers (Figs. 1a and 1b) to the extent possible within cost and space constraints. Full-length, full-diameter, 3003-H14 aluminum tubes are used. Because of the limitations on water supply and space at ANL, only one tube per vertical plane is used - there is no nesting (see Ref. 5 for a discussion of nesting) - and the tubes are closer together in the lateral direction in order to achieve the plant-ship maximum design water velocity. To get a better simulation of water temperature drop through the bundle and a better balance between height and length of the core unit, there are 43 passes per tube instead of 25, so the pass lengths are smaller than in the full-scale heat exchanger.

Since an objective of the core test is to validate (or modify as necessary) the pre-

sent APL computer program for heat exchanger performance (Ref. 5), pretest performance estimates have been made specifically for the core unit. These predictions indicate performance similar to that of the plant-ship unit. If such performance predictions are satisfactory, design of the plant-ship heat exchanger will proceed.

REFERENCES

1. H. L. Olsen, P. P. Pandolfini, and J. L. Rice, "Internal Heat Transfer Experiments in a Simulated OTEC Evaporator Tube," APL/JHU AEO-76-066, Nov 1976.
2. P. P. Pandolfini, J. L. Keirse, and J. L. Rice, "An Experimental Investigation of the Onset of Nucleate Boiling in Ammonia Flowing Inside a Large-Diameter Smooth Aluminum Tube," APL/JHU BBP-78-28, 15 Mar 1978.
3. P. P. Pandolfini and R. A. Makofski, "Circumferential Heat Transfer and Pressure Drop in Tube Arrays with a Low-Lateral-Pitch Ratio in Crossflow," APL/JHU CP 066, Jun 1978.
4. Section 25, Quarterly Report, Apr-Jun 1977, APL/JHU EQR/77-2.
5. G. L. Dugger, H. L. Olsen, P. P. Pandolfini, and W. H. Avery, "Experiments on and Design of Low-Cost Aluminum Heat Exchangers for OTEC Plant Ships," APL/JHU AEO-77-073, Mar 1977.

DEVELOPMENT AND DEMONSTRATION PLAN FOR A LOW-COST FLYWHEEL

At the request of DOE, APL has prepared a proposal (Ref. 1) outlining a development plan aimed at demonstrating the feasibility of a very low-cost flywheel. The proposal was subsequently approved, and work on the program began in Oct 1977, with a scheduled completion date of 31 Dec 1978. The completion date was recently amended to 31 May 1979. The program's primary objective was to develop a flywheel capable of storing 20 Wh per dollar of flywheel cost. A secondary objective was to develop low-loss bearing systems with a long life for use in subsequent flywheel systems. A lesser objective was to demonstrate the low-cost flywheel in a complete energy storage system that could be charged through an ordinary home wall socket and could carry a typical home electrical load. The final objective was to translate a satisfactory design of a low-cost flywheel energy storage system into a home-sized unit.

BACKGROUND

Modern composite flywheels can be made from a variety of filamentary super-materials that could result in more energy per unit weight and volume than their isotropic flywheel predecessors. However, in most cases the cost of the new flywheels is actually higher due to manufacturing and other expenses. APL has recently developed new flywheel configurations that offer lower flywheel costs than were previously believed possible.

There are increasing applications for energy storage by flywheel where the flywheel cost factor is the dominant consideration, while flywheel weight and volume are relatively unimportant. Most of these are stationary applications, such as nighttime storage in the home or factory, where it has been determined that the low-cost flywheel system can pay for itself in a few years by making possible the use of low-cost off-peak power usually available from the utility company.

DISCUSSION

Flywheels made from three attractive low-cost materials have been evaluated in spin tests to destruction. During these tests, rotational speeds as high as 90% of the theoretical have been achieved, which appears to indicate that these materials are more than adequate for use in very low-cost flywheels. These spin tests have proven that all three materials look promising; however, two of them have problems that are expected to be resolved in the future. For example, the low-cost flywheel made from steel wire, while de-

Fig. 1 Vinyl/glass flywheel. (78-4/45)

monstrating a high degree of theoretical performance, has encountered fabrication problems because of the built-in "cast" of the wire. However, the wire manufacturer has indicated that this wire cast can be easily controlled in future production runs. Other than this, the low-cost flywheel made of steel wire appears to be a definite contender.

The second of the three basic materials is Metglas. The Metglas being used in the program consists of a 0.5 in. wide ribbon with a thickness of 0.002 in. Its principal virtue is that it apparently can be provided in a very high strength at a relatively modest cost, predicted to be something less than \$1.00 per pound. However, the experimental material that is presently being made available to the program suffers from two drawbacks. First, it is delivered in the "as cast" condition with raw edges, which results in a lower strength than required in the ultimate flywheel application. Second, it is apparently quite difficult to develop effective epoxy bonds with Metglas. This latter problem is being evaluated.

The third potential low-cost flywheel material that has been evaluated is polymer-impregnated glass strands. The particular material tested is vinyl-coated glass. Tests of flywheels made of the material have been quite successful. It has excellent winding characteristics, is apparently easily bonded, and is relatively inexpensive to produce. It is also extremely rugged. On a number of occasions, flywheels have been successfully spin tested after having been accidentally dropped to the chamber floor because of a rotor shaft failure or some other reason. Figure 1 illustrates a typical vinyl/glass low-cost flywheel. The final version of this flywheel will be approximately 24 in. in diameter and weigh a little over 70 lb. It will be capable of storing 1000 Wh of usable energy. In the demonstration energy storage system, it will be able to deliver this energy at an average rate of approximately 2000 W.

REFERENCE

1. "Unsolicited Proposal to ERDA for Advanced Flywheel Technology," APL/JHU report, 15 Apr 1976, revised 1 Mar 1977.

ENERGY CONSERVATION TECHNIQUES IN USE AT APL

A tremendous amount of energy is being wasted by many commercial and industrial complexes, including APL, through heat rejection from cooling towers. In addition to heat rejection by air conditioning equipment during warm weather, other cooling equipment extracts heat from computers, process coolers, and electronic equipment during most of the year. Unfortunately, the nature of the equipment involved and the temperature of the outside atmosphere used for evaporative cooling require that this heat be extracted at temperatures of 80 to 95°F. In the past, such temperatures have been too low for the energy to be used for heating domestic water, buildings, or other reasonable requirements.

DISCUSSION

In the spring of 1977, a high-temperature heat pump was proposed as a potential APL development project (Ref. 1). Two prominent air conditioning manufacturers expressed no interest in a joint development effort because of questionable sales volume, so the proposal became dormant. Six months later, a local Westinghouse agent asked if we might be interested in a new heat pump they had just placed on the market. It was exactly what we had in mind. Even though there were no local installations that we could visit, we ordered a 1 million Btu water-to-water unit.

The unit was installed and became operational early in August 1978. It saves APL approximately 10 gallons of oil each hour of operation and is expected to run about 4000 hours per year. The unit will thus save approximately 40 000 gallons of fuel per year, approximately 17% of APL's previous oil consumption.

The pump was installed in the mechanical room of Building 7 because major heat connections with Buildings 4, 7, and 3 (the Computing Center) were located there. Large amounts of heat are generated by the computers during their almost continuous operation throughout the year. The location already contained connections to the heating water system from the boiler plant in Building 4, which provides space heating and domestic hot water for Buildings 4 and 7. Figure 1 is a schematic of the application of this heat pump at APL.

The domestic water heating requirement of these buildings during the warm months of the year is much too small to use a significant percentage of the heat pump's capacity. Therefore, a new water heater was installed in Building 4 to provide domestic hot water to the existing water heaters in Building 2, the Building 5 cafeteria, the east and west wings of Building 1, and the Building 1 cafe-

Fig. 1 Schematic of high-temperature heat pump application. (78-4/50)

teria (Fig. 2). A new addition, Building 9, will also receive its domestic hot water from the heat pump.

During warm weather, the heat pump has been operating about 7 hours per day to provide domestic hot water. In colder weather, the system is running much longer (approximately 20 hours per day) since it also provides space heating for Buildings 4 and 7. The control system for the heat pump is integrated with the Building 4 boilers so as to raise the water temperature as the weather gets colder. The oil burners are automatically started when the heat pump is unable to provide an adequate supply of hot water.

The system has shown enough promise for us to order another unit that is twice as large for Buildings 6, 13, 14, 16, 18, and 21. The new installation will be used more in the summer and less in the winter than the Building 7 system because there are greater requirements for heat in the summer and less source heat is available in winter.

We have been improvising in order to adapt a new technology to existing systems in a financially responsible manner. If the various heating and cooling systems at APL could be completely redesigned, we would eliminate the original steam heating plant in

Building	Ft ²
1	173 265
2	49 379
3	15 161
4	72 700
5	18 400
7	83 631
9	33 854

Fig. 2 Arrangement of buildings involved in energy conservation experiments at APL. (78-4/51)

Building 1 that heats Buildings 1, 2, 3, 5, 6, and the Library. We would also have only

one cooling tower complex and a 90°F water loop throughout the entire plant. This loop could then provide condenser water for cooling systems and source heat for high-temperature heat pump heating systems. The heating and cooling demands of the entire Laboratory would cancel each other to the maximum extent within this single loop. The loop would be supplemented by one central cooling tower complex and one central heating system, each large enough to provide only the net shortfall for the entire plant.

The economics of heat pumps using condenser water as a heat source are very favorable. For example, the current system coefficients of performance (Btu output divided by Btu equivalent of electrical energy input) are as follows:

1. Warm and hot weather operation: source water, 95°F; heated water, 120°F; coefficient of performance, 5.7.
2. Moderate weather operation: source water, 95°F; heated water, 130°F; coefficient of performance, 5.3.
3. Very cold weather operation: source water, 80°F; heated water, 160°F; coefficient of performance, 3.4.

REFERENCE

1. A. C. Stucki, "Low Level Heat Recovery System," APL/JHU memo to W. H. Avery, 3 Mar 1977.

INITIAL DISTRIBUTION EXTERNAL TO THE APPLIED PHYSICS LABORATORY*

EQR/78-4

ORGANIZATION	LOCATION	ATTENTION	No. of Copies
U.S. GOVERNMENT AGENCIES			
DOE/ETS	Washington, DC	B. Miller	1
DOE/DGE	Washington, DC	B. G. DiBona	1
		A. Follett	1
		R. LaSala	1
		D. B. Lombard	1
		R. E. Oliver	1
		J. W. Salisbury	1
		M. Skalka	1
		D. Elmer	1
		G. P. Brophy	1
		R. A. Gray	1
		C. Carwile	1
		C. B. McFarlin	1
		M. R. Scheve	1
DOE/DSE	Washington, DC	H. R. Blieden	1
		R. Cohen	1
		S. Gronich	1
		H. Marvin	1
		J. F. Madewell	1
DOE/RA	Washington, DC	R. A. Black	1
		R. I. Gerson	1
		E. A. Peterson	1
		R. C. Stephens	1
		L. B. Werner	1
		B. Barnes	1
		F. Abel	1
		L. Fallick	1
		D. Clements	1
		S. Weiss	1
		G. S. McIsaac	1
		D. Greenwall	1
DOE/Dallas	Dallas, TX		
DOE/Geothermal Programs, San Francisco Operations Office	Oakland, CA		1
Idaho Operations Office	Idaho Falls, ID		1
DOE/Regional Offices Region 3	Philadelphia, PA		1
Energy Research Center	Morgantown, WV	J. Pasini	1
U.S.G.S.	Menlo Park, CA	R. Christianson	1
		P. Muffler	1
		D. Klick	1
U.S. Maritime Admin.	Reston, VA	J. Gross	1
	Washington, DC	J. Lisnyk	1
		M. Pitkin	1
		J. Seelinger	1
		I. M. Baill	1
		D. Attaway	1
Economic Development Admin.	Washington, DC		25
NOAA/OSG	Washington, DC		
NTIS	Springfield, VA		
DEPARTMENT OF DEFENSE			
Dir. for Energy Policy, DoD	Washington, DC	W. J. Sharkey	1
<u>U.S. Air Force</u>			
Hq. USAF/PREE Bolling AFB	Washington, DC	Code USAF/PREE	1
Hq. USAF/RDPDT	Washington, DC	A. Eaffy	1
AFAPL/POE	WPAFB, OH		1
<u>Department of the Navy</u>			
OASN (R&D)	Washington, DC	R. Leonard, Rm 5E 787	1
NAVFAC	Alexandria, VA	W. Adams	1
		W. F. Daniel	1
NAVPRO	Laurel, MD		1
NWC/China Lake	China Lake, CA	C. Austin	1
NAVMAT	Washington, DC	NMAT 08T3	1
U.S. Naval Academy	Annapolis, MD	D. Edsall	1

*Initial distribution of this document within the Applied Physics Laboratory has been made in accordance with a list on file in the APL Technical Publications Group.

INITIAL DISTRIBUTION EXTERNAL TO THE APPLIED PHYSICS LABORATORY*

EQR/78-4

ORGANIZATION	LOCATION	ATTENTION	No. of Copies
STATE GOVERNMENT AGENCIES			
<u>Colorado</u>			
National Conf. of State Legislatures	Denver, CO	D. M. Sacarto	1
<u>Delaware</u>			
Dept. of Public Safety, Div. of Energy Plann. and Oper.	Delaware City, DE	Director	1
University of Delaware Delaware Geological Survey	Newark, DE	State Geologist	1
<u>Georgia</u>			
State Energy Office	Atlanta, GA	Director	1
Dept. of Natural Resources Earth and Water Div.	Atlanta, GA	Director and State Geologist	1
<u>Maryland</u>			
Energy Policy Office	Baltimore, MD	W. Reinhardt	1
Maryland Geological Survey	Baltimore, MD	R. Nietubicz	1
Dept. of Natural Resources	Annapolis, MD	Director	1
Dept. of State Planning	Baltimore, MD	J. W. Vukovich	1
		J. D. Antenucci	1
		Library	1
Dept. of State Planning	Salisbury, MD	W. Livingston	1
<u>New Jersey</u>			
State Energy Office	Newark, NJ		1
Geologic Survey	Trenton, NJ	Commissioner	1
<u>New York</u>			
ERDA	Albany, NY	Dr. R. Wiley	1
<u>North Carolina</u>			
Dept. of Natural & Econ. Resources Office of Earth Resources	Raleigh, NC	Director	1
Dept. of Military and Vet. Affairs	Raleigh, NC	P. Hitchcock, Director	1
<u>South Carolina</u>			
Div. of Geology	Columbia, SC	State Geologist	1
Energy Management Office	Columbia, SC	Director	1
<u>Virginia</u>			
Energy Office	Richmond, VA	Director	1
Div. of Mineral Resources	Charlottesville, VA	State Geologist and Commissioner	1
LABORATORIES/UNIVERSITIES			
Argonne Nat'l. Lab.	Argonne, IL	P. F. Gustafson	1
Battelle Pacific NW Lab.	Richland, WA	D. W. Shannon	1
Brookhaven Nat'l. Lab.	Upton, NY	M. Steinberg	1
Civil Eng. Lab., NCBC	Port Hueneme, CA	J. M. Slaminski	1
Idaho National Eng. Lab.	Idaho Falls, ID	R. Chappell	1
Jet Prop. Lab.	Pasadena, CA	C. Fredrickson	1
Lawrence Livermore Lab.	Livermore, CA	A. L. Austin	1
Lawrence Berkeley Lab.	Berkeley, CA	K. F. Mirk	1
Los Alamos Scientific Lab.	Los Alamos, NM	R. C. Feber	1
		A. W. Laughlin	1
		J. Maxwell	1
		A. W. Nutt	1
Louisiana State Univ.	Baton Rouge, LA	B. Wilkins	1
Massachusetts Inst. of Tech.	Cambridge, MA	F. Van Dyke	1
New Mexico State Univ.			
New Mexico Energy Inst.	Las Cruces, NM	J. Marlin	6
Oak Ridge Nat'l. Lab.	Oak Ridge, TN	J. Griess	1
Oregon Inst. of Technology	Klamath Falls, OR	D. Karr	7
University of Texas at Austin	Austin, TX	D. Zinn	1
Virginia Polytechnic Inst. and State University	Blacksburg, VA	J. K. Costain	1

INITIAL DISTRIBUTION EXTERNAL TO THE APPLIED PHYSICS LABORATORY*

EQR/78-4

ORGANIZATION	LOCATION	ATTENTION	No. of Copies
COMPANIES			
A. D. Little, Inc.	Cambridge, MA	K. O'Neill	1
Delmarva Poultry Industry, Inc.	Georgetown, DE	W. Stevens	1
EG&G Idaho, Inc.	Idaho Falls, ID	J. D. Gertsch	1
Futures Group, Inc.	Glastonbury, CT	T. Wright	1
Gruy Federal, Inc.	Arlington, VA	J. Renner	1
Gruy Federal, Inc.	Houston, TX	A. Lohse	1
Raytheon Company	Burlington, MA	A. Slater	1
Science Applications, Inc.	LaJolla, CA	J. Wiegand	1
Sperry Vickers	Jackson, MS	D. J. Tearpock	1
Systems Development Corp.	Santa Monica, CA	F. Zimmerman	1
USS Agri-Chemical	Atlanta, GA	R. F. McFarlin	1