Nitrogen Oxide Abatement by Distributed Fuel Addition
Contract DE-AC22-87PC79850

Quarterly Report No. 3

DOE/PC/79850--3

DE92 005205

for Period

February 1, 1988 through April 30, 1988

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Prepared by

J.O.L.Wendt and J. Meraab
Department of Chemical Engineering
University of Arizona
Tucson, Arizona 85721

Submitted to

Diane Revay Madden, Project Officer
Environmental Control Technology Division
Pittsburgh Energy Technology Center
Department of Energy

June 27, 1988

INDEX

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This research is directed towards the development of engineering guidelines that define the application of distributed fuel addition as a technique for NO_x abatement. It is expected that multiple fuel and air addition in the post-flame of a combustion process will increase free radical concentrations which destroy nitrogenous species and thus help them decay toward their equilibrium concentrations, which can be very low in that region of the combustor.

Screening experiments were conducted on a laboratory scale downfired combustor. The objective was to compare NO_x emissions arising from various combustion configurations, including fuel and/or air staging. Although the primary focus of this research is on NO control, a secondary effort was directed towards the measurement of N₂O emissions from various coal combustion processes. N₂O has been identified as a trace gas responsible for stratospheric ozone depletion, and has been hypothesized to arise from combustion processes, in amounts roughly proportional to NO emissions.

Results presented in this report showed that the ratio N₂O/NO was far from constant. The introduction of secondary air into a combustion process was accompanied an increase in N₂O emissions. The measured N₂O was always less than 10 ppm even under the most favorable combustion conditions. Reburning with premixed fuel and air mixtures was not effective in reducing NO emissions.

INTRODUCTION

There have been considerable advances in control technology to reduce emissions of nitrogen oxides from stationary sources such as coal combustion processes. The use of fuel as a reducing agent to remove NO_x from the combustion products have been shown to be an effective method in NO_x emission control. This technology is referred to as "reburning" because the combustion products are reburned by introducing additional fuel downstream of the primary combustion zone. The variables which affect the reduction of NO_x by reburning have been widely investigated by various researchers (1,3,4,5). The following is a review of the effect of some of these variables on the reburning process.

The stoichiometric ratio in the primary zone has little effect on reburning effectiveness provided that sufficient oxygen or oxidizing radicals reach the reburn zone to break down the reburn fuel and generate hydrocarbon radical species. The CH radical is formed as a minor byproduct. It is the CH radical concentration which is the determining factor in reducing NO emissions according to the following path:

According to this theory, the key limitation to reburning is the availability of the CH radical. There may, however, be other, equally important, kinetic routes for the conversion of NO to N₂.

In the reburn zone, there is an interconversion of nitrogen species among the different fixed nitrogen compounds namely, NO, HCN and NH₃. Such a tradeoff would mask the actual effectiveness of reburning if only NO concentrations were monitored. The addition of burnout air would oxidize all the remaining fuel and the total fuel nitrogen (NO + HCN + NH₃) would be converted partially to NO and partially to N₂.

It has been found that the reburning process is more effective at higher levels of NO in the primary zone. Miyamae et al. (4) proposed that the ratio of hydrocarbon concentration into the reburning zone to that of the primary zone concentration of NO was an important variable in determining reburning effectiveness. An optimum reburn zone stoichiometric ratio of about 0.9 has been found by several researchers (1,3,4,5).

Reburning is most effective when the reburn fuel is introduced at the hottest location or as close to the primary flame as possible while leaving adequate residence time for the primary fuel to be completely consumed. Also, the burnout air should be introduced as late as possible to allow adequate time for the decomposition of the nitrogenous species.

Oxygen injected with the reburn fuel may cause direct consumption of the fuel and reduce the CH radical generation. Thus, means which slow the consumption of reburn fuel, such as slow mixing, might enhance the reburning action. Slow mixing is favored by low inlet velocities of the reburning fuel streams. Times for combustion of the reburn fuel and generation of CH

radicals can be also extended by distributing the reburning zone down the combustor through multiple fuel injection ports.

The proposed experimental plan and the experimental setup were described in a previous report (6). Preliminary experiments, described there, showed that the location of the reburn zone was less relevant at longer residence times and lower temperatures. Significant reductions in NO due to reburning could also be achieved with the reburn zone under overall fuel lean conditions.

N2O MEASUREMENTS

In the previous report (7), the significance of N2O emissions to the environment and some of the theories behind its formation were discussed. A reliable and reproducible analytical procedure was developed for on line sampling and analysis of N2O. The procedure was later modified to employ an electron capture detection temperature of 250 C. The presence of an electronegative compound such as oxygen would cause rapid deterioration in ECD performance. Employing a lower detection temperature would reduce the damaging effect caused by the presence of oxygen in the sample (2). The sensitivity of the ECD at 250 C was reduced by a factor of about 6 compared to that at 350 C. Nevertheless, N2O measurements as low as 0.3 ppm were still possible. Table 1 lists the instrumental parameters that are used in N2O measurements. Figures 1 and 2 show the effect of variable O2 and CO2 concentrations respectively on ECD measurements of N2O and Figure 3 shows the effect of water vapor. These compounds show little or no interference with N2O response. Figure 4 shows sample chromatograms at two different ECD temperatures.

It should be noted that, throughout this work, samples were withdrawn through a water quenched, water cooled sample probe. The water was then removed via a refrigerated knockout pot, and the sample analyzed chromatographically in-line. Many other researchers have analyzed samples which have been stored in sample bombs, with or without the water of combustion present.

EXPERIMENTAL RESULTS

Several experiments were performed under various fuel and/or air staging conditions. The results are shown in Table 2. To correct for dilution effects due to changes in stoichiometry and due to the addition of reburning fuel and/or air, all measured NO and N₂O concentrations were multiplied by the ratio of total calculated dry moles of flue gas to that of the total theoretical dry moles corresponding to a stoichiometric ratio of unity with respect to the primary fuel. This quantity is then proportional to the fraction of coal nitrogen finally converted to NO in the exhaust, if the amount of Thermal NO can be neglected.

Figure 5 shows NO and N₂O exhaust concentrations at different stoichiometric ratios for two different types of coal, a Utah Bituminous coal and a N. Dakota Beulah Lignite. NO emissions are as expected, but N₂O emissions are very low and less than 2 ppm. Figures 6 and 7 compare NO emissions for various combustion configurations, including air staging and reburning. It is obvious that reburning with a premixed fuel and air combination is not very effective in reducing NO_x levels and may result in higher NO emissions. As discussed earlier, this may be due to direct consumption of the fuel and consequent reduction in free radical generation. Some NO was formed at the point of final burnout air addition.

Figures 8, 9, 10 and 11 show NO and N₂O profiles as a function of residence time at different stoichiometric ratios. Low concentration levels of N₂O (less than 2 ppm) were obtained.

Figure 12 shows NO and N₂O profiles for a typical reburning experiment. Reburn fuel was added at 0.68s (denoted by the first vertical dashed line) and burnout air at 1.27s (denoted by the second vertical dashed line). Reburning lowered the NO profile by 60%. N₂O concentrations increased upon the addition of burnout air.

Figures 13, 14 and 15 show typical air staging combustion experiments. The addition of staged air resulted in a decrease in NO concentrations and an increase in N₂O concentrations, although the latter were still small (less than 9 ppm). The increase in N₂O concentrations might be due to the increase in HCN formation from char nitrogen. HCN is formed in the post flame gas phase from char nitrogen devolatilization and is a precursor to N₂O formation according to the following path as proposed by Kramlich (2):

However, the N₂O values obtained were far lower than anticipated. The temperature was kept in the 1150 - 1500 K range which is favorable for N₂O formation (2).

Figures 16, 17 and 18 show results of reburning experiments in which the reburn fuel was a premixed fuel and air combination. It appears that this type of reburning is not effective in NO reduction. The addition of air also resulted in an increase in N₂O emissions. Possible reasons for this

have been proposed above.

SUMMARY, CONCLUSIONS, AND FUTURE PLANS

Several coal combustion schemes were tested and temporal profiles of NO and N₂O concentrations were compared. For reburning to be effective, the consumption of the reburn fuel must be slowed down as much as possible. Consequently, reburn fuels would not be as effective when premixed with an oxidant. Reburning might be made more effective if the addition of reburn fuel were to be distributed down the combustor.

The N₂O concentrations that were measured were too low (less than 10 ppm) for any reliable conclusions to be made concerning the effect of fuel and/or air staging on N₂O emissions. However, the introduction of air into a fuel rich zone was always accompanied by an increase in N₂O emissions which might be caused by an increase in HCN formation from char nitrogen as discussed earlier.

The remaining screening studies will be conducted according to a statistically correct design of experiments. Response surface experimentation will be utilized for this purpose. This method allows the determination of an empirical relationship between the response and the controlled parameters in the experimental region of interest based on an experiment involving a minimal number of trials.

REFERENCES

1. Greene, S.B., S. L. Chen, W. D. Clark, M. P. Heap, D. W. Pershing and W. R. Seeker, "Bench Scale Process Evaluation of Reburning and Sorbent Injection for In-Furnace NO_x/SO_x Reduction," U.S. EPA Report EPA-600/7-85-012 (1985).
2. Kramlich, J.C., R. K. Lyon and W. S. Lanier, "EPA/NOAA/NASA/USDA N2O Workshop," U.S. EPA Report EPA-68-02-4247 (1987).
3. LaFond, J.F. and S. L. Chen, "An Investigation to Define the Physical/Chemical Constraints which Limit NO_x Emission Reduction Achievable by Reburning," U.S. DOE Quarterly Report DE-AC22-86PC91025 (1987).
4. Miyamae, S., H. Idebe and K. Makino, "Evaluation of In-Furnace NO_x Reduction," Proceedings of the 1985 Joint Symposium on Stationary Combustion NO_x Control, (1986).
5. Miyamae, S., T. Kiga, H. Ikebe and K. Suzuki, "Experimental Study on NO_x Destruction Characteristics by Reburning of Pulverized Coal," paper presented at the 1986 Fall Meeting of Western State Section/The Combustion Institute, Tucson, Arizona (1986).
6. Wendt J.O.L. and J. Meraab, "Nitrogen Oxides Abatement by Distributed Fuel Addition," U.S. DOE 1st Quarterly Report DE-AC22-87PC79850 (1987).
7. Wendt J.O.L., and J. Meraab, "Nitrogen Oxides Abatement by Distributed Fuel Addition," U.S. DOE 2nd Quarterly Report DE-AC22-87PC79850 (1988).

Table 1.

UNIVERSITY OF ARIZONA SAMPLING AND ANALYSIS TECHNIQUE FOR N₂O

ON-LINE SAMPLING

Sample withdrawn through a water quenched, water cooled, stainless steel probe. Sample then passes through refrigerated knock-out pot, through filters and CO and CO₂ NDIR analysers into GC sample loop."

GC INSTRUMENTAL PARAMETERS

Instrument: Shimadzu GC-8A

Column: Porapak Q, 12 ft x 1/8 in stainless steel conditioned at 220 C

Oven Temperature: 35 C

Detector: Electron Capture, Ni 63 at 250 C

Carrier Gas: Ar/5.22%CH₄ at 20 ml/min

Sample: 1 ml loop at 3 psig intake pressure

Calibration Gas:

15.14% CO₂, 1% O₂, 95 ppmv N₂O, Balance N₂

Carrier gas passes through a carrier gas purifier for O₂/H₂O removal and an indicating tube for O₂/H₂O detection before entering the GC

Recorder Input Voltage: 1 mV

Figure 1.

ECD @ 25°C, EFFECT OF CO₂ CONC. ON N₂O Response

Figure 2.

Effect of Water Vapor on N₂O Response Detector @ 350°C

N₂O CALIBRATION

Figure 3.

COMBUSTION OF BEULAH LIGNITE, -LOW Na

Figure 4
 Sample
 Chromatograms

TABLE 2.

BEULAH LIGNITE, LOW Na

CONC. VS. SR1 (COAL FEED RATE= 2.08 lb/hr) Data for Figures 5b & 6

SR1	O2 PCT	CO PCT	CO2 PCT	NO ppm	N2O ppm
---	---	---	---	---	---
1.23	4	0.5		770	2.1
1.19	3.45	1	15.7	715	1.75
1.16	3	1.2		650	1.15
1.11	2.1	0.8	16.9	605	1.2
1.1	2	1.6	16.8	528	1
1.06	1.25	2	17	445	1.25
1.04	2.1	1.15	17.25	463	1.05
0.94	0.8	1.8	17.9	295	0.85
0.84	0.3	2.6	18	140	0.35
SR1=1.11, SR2=0.86				162	1.9
SR1=1.23, SR2=1.10				438	1.1
SR1=1.06, SR2=0.90				133	0.53
SR1=1.06, SR2=0.9, SR3=1.07				176	2.9
SR1=1.06, SR2=1.07 (GAS+AIR)				453	1.15
SR1=1.06, SR2=1.07 (DOUBLE CHARGE)				523	

UTAH BITUMINOUS #2

COAL FEED RATE= 2.21 lb/hr

Data for Figures 5a & 7

SR1	O2 PCT	CO PCT	CO2 PCT	NO ppm	N2O ppm	PEAK T DEG K
---	---	---	---	---	---	---
0.75	0	3.75	16	206	0.365	1529
0.793	0	3.05	16.45	305	0.5	1594
0.843	0	2.2	17.15	403	0.59	1605
0.906	0	1.03	17.85	632	0.69	1609
0.983	0.15	0.18	17.85	804	0.95	1597
1.044	0.9	0.05	17.3	1000	1.55	1600
1.093	1.8	0.05	16.45	1070	1.25	1564
1.095	1.85	0.05	16.45	1110	1.33	1588
1.12	2.3	0.04	15.8	1020	1.34	1537
1.185	3.35	0.03	15.3	1110	1.15	1543
1.25	4.25	0.03	14	1120	1.28	1518
SR1=1.1, SR2=0.9				378	0.73	
SR1=1.1, SR2=0.9, SR3=1.1				426		
SR1=1.1, SR2=0.9, SR3=1.06				423	4.88	
SR1=1.1, SR2=1.06 (GAS+AIR) P3				1106	1.59	
SR1=1.1, SR2=1.06 (GAS+AIR) P5				1009	1.22	
SR1=0.64, SR2=0.88 (P3)				178	1.8	
SR1=0.64, SR2=1.09 (P4)				170	7.25	
SR1=0.64, SR2=0.72 (GAS+AIR, P3) SR3=0.9				166	3.53	
SR1=0.65, SR2=1.083 (P4)				215	3.76	
SR1=0.4, SR2=1.07 (P5)				187	6.96	
SR1=0.86				574	1.09	
SR1=0.86, SR2=1.08 (P4)				602	1.98	
SR1=0.86, SR2=0.89 (GAS+AR, P3) SR3=1.09				653	6.49	

PORT PROFILES:

BEULAH LIGNITE AT SR1=1.10 (2.08 lb/hr) *Figure 8*

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
0.45	3.3	0.35	16	601	0.9	1287
0.85	3.45	0.45	15.7	673	0.65	1281
1.26	2.6	0.75	16.7	665	0.65	1218
1.69	2	0.8	16.7	622	0.65	1180
2.54	2.5	0.8	16.4	629	1.2	1073
3.41	2	0.8	17	614	0.8	963
4.38	2.07	0.8	16.9	602	1.2	888

UTAH BITUMINOUS AT SR1=1.15 (2.16 lb/hr) *Figure 9*

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
0.24	1.3	0.1	16.8	845	1.35	1513
0.45	1.55	0.09	16.45	912	1.35	1477
0.66	2.2	0.07	16	914	1.35	1403
0.88	2.5	0.08	15.8	967	1.35	1364
1.31	2.5	0.09	15.8	995	2.3	1282
1.75	2.4	0.09	15.95	990	2.3	1173
2.22	2.62	0.08	15.75	973	1.15	1075

UTAH BITUMINOUS: SR1=1.1, SR2=0.9(P3), SR3=1.06(P5) (2.16 lb/hr) *Figure 12*

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
0.25	1.9	0.13	16	761	1.2	1513
0.47	1.5	0.09	16.8	907	1.2	1448
0.91	0.6	2.35	14.65	400	0.65	1373
1.65	3.15	0.07	14.35	381	2.3	1223
2.04	3.85	0.04	13.75	381	4.45	1161

UTAH BITUMINOUS: SR1=1.1, SR2=1.06 (GAS+AIR) (P5) (2.16 lb/hr) *Figure 16*

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
0.25	2.5	0.15	14.2	713		1573
0.46	2.45	0.14	15.3	814		1511
0.67	2.45	0.1	15.8	841		1481
0.89	2.55	0.08	15.8	896	1.3	1433
1.6	2	0.05	15.6	998	1.8	1287
1.98	2.8	0.04	14.5	906	1.15	1208

UTAH BITUMINOUS: SR1=0.64 (2.12 lb/hr) Figure 10

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.42	0	3.75	14.75	206	0.65	1463
0.8	0	4	14.8	250	0.55	1344
1.2	0	3.95	14.8	256	0.4	1307
1.6	0	4.05	14.9	243	0.4	1264
2.41	0	4.05	14.9	211	0.4	1178
3.22	0	3.75	14	178	0.5	1119
4.07	0	3.7	14.2	162	0.85	1065

UTAH BIUMINOUS: SR1=0.64, SR2=1.09 (P4) (2.12 lb/hr) Figure 13

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.43	0	3.55	15.5	217	0.6	1435
0.8	0	3.3	15.5	236	0.8	1383
1.19	0.4	2.35	15.9	229	2.25	1333
1.93	4.3	0.05	13.9	178	9.4	1204
2.42	3.95	0.04	14	178	8.75	1182
2.91	3.8	0.04	14.35	167	7.15	1120

REPEAT OF EXP, SR1=0.65, SR2=1.083 (P4) (2.21 lb/hr)

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.91	0	4.15	15	274	0.37	1398
1.27	0.2	3.75	15.15	241	0.455	1358
1.98	3.35	0.05	14.9	210	5.9	1194
2.46	3.4	0.05	14.8	209	4.1	1145
2.95	3.5	0.05	14.8	215	3.76	1073

Figure 18

UTAH BITUMINOUS: SR1=0.64, SR2=0.724(P3), SR3=0.9(P5) (2.12 lb/hr)

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.96	0.1	3.5	15.15	341	0.45	1411
1.5	0.1	3.6	14.2	278	0.65	1383
2.38	0.9	0.25	15.5	167	2.25	1253
2.84	0.8	0.1	16	162	3.45	1208

UTAH BITUMINOUS: SR1=0.86 (2.21 lb/hr) Figure 11

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.3	0.8	0.4	16.6	687	0.715	1548
0.56	0.55	0.57	17	802	0.81	1510
0.82	0.35	0.57	17.15	793	0.75	1468
1.09	0.25	0.67	17.3	769	0.735	1428
1.62	0.15	0.6	17.5	734	1.33	1320
2.16	0.1	0.75	17.35	669	0.7	1231
2.72	0.1	0.9	17.15	574	1.09	1173

UTAH BITUMINOUS: SR1=0.86, SR2=1.08 (P4) (2.21 lb/hr) Figure 15

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.7	1	0.35	16.6	809	0.79	1451
0.98	1	0.5	16.45	745	0.905	1373
1.68	4.2	0.04	14.05	594	3.09	1238
2.13	3.75	0.045	14.5	637	1.83	1228
2.59	3.6	0.04	14.35	602	1.98	1153

UTAH BITUMINOUS: SR1=0.86, SR2=0.89 (GAS+AIR, P3), SR3=1.09 (P5) Figure 17

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
0.69	0.5	0.54	17	698	1.07	1480
1.12	0.55	0.4	16.2	796	1	1425
1.83	3.85	0.08	13.3	663	4	1168
2.22	4.4	0.04	13.1	653	6.49	1118

UTAH BITUMINOUS: SR1=0.4, SR2=1.07 (P4)

RES. TIME	O2	CO	CO2	NO	N2O	TEMP.
SEC	PCT	PCT	PCT	ppm	ppm	DEG K
-----	---	---	---	---	---	-----
2.19	0	8.3	11.9	59	0.11	1325
3.88	2.8	0.04	15.75	187	6.96	1057

NO AND N2O in ppmv VS. SR

UTAH BITUMINOUS #2

NO AND N2O in ppmv VS. SR

BEULAH LIGNITE, LOW Na

Figure 5.

NO in ppmv vs. SRI/ BEULAH LIGNITE, LOW Na

Figure 6.

NO in ppmv vs. SRI/ UTAH BITUMINOUS #2

- no staging
- SR1 = 1.1 , SR2 = 1.06 (premixed gas + air)
- △ SR1 = 1.1 , SR2 = 0.9
- ▲ SR1 = 1.1 , SR2 = 0.9 , burnout air (SR3 = 1.1)
- Air Staging , SR1 = 0.65 , SR2 ~ 1.1
- Air Staging , SR1 = 0.64 , SR2 = 0.88
- SR1 = 0.86 , SR2 = 0.89 (premixed gas + air) , SR3 = 1.09
- + Air Staging , SR1 = 0.86 , SR2 = 1.08

Figure 7.

SR1=1.1, NOx VS RT in SEC

BEULAH LIGNITE, LOW Na

T°K	1287	1281	1218	1180	1073	963	888
-----	------	------	------	------	------	-----	-----

Figure 8.

SR1=1.15, NOx VS RT in SEC

UTAH BITUMINOUS #2

T°K 1513 1477 1403 1364 1282 1173 1075

Figure 9.

SR1=0.64, NO_x VS. RT in SEC UTAH BITUMINOUS #2

RESIDENCE TIME, SEC

NO + N₂O

T°K	1463	1344	1307	1264	1178	1119	1065
-----	------	------	------	------	------	------	------

Figure 10.

SR1=0.86, NOx VS. RT in SEC

UTAH BITUMINOUS #2

RESIDENCE TIME, SEC

□ NO + N₂O

T°K	1548	1510	1468	1428	1320	1231	1173
-----	------	------	------	------	------	------	------

Figure 11.

SR1=1.1, SR2=0.9, SR3=1.06 REBURNING

UTAH BITUMINOUS #2

T°K 1513 1448 1373 1223 1161

Figure 12.

SR1=0.64, SR2=1.09 AIR STAGING

UTAH BITUMINOUS #2

Figure 13.

SR1=0.65, SR2=1.08 AIR STAGING

UTAH BITUMINOUS #2

RESIDENCE TIME, SEC

□ NO + N₂O

T °K

1398

1358

1194

1145

1073

Figure 14.

SR1=0.86, SR2=1.08 AIR STAGING

UTAH BITUMINOUS #2

Figure 15.

SR1=1.1, SR2=1.06 GAS+AIR REBURNING

Figure 16.

SR1=0.86, SR2=0.887 GAS+AIR, SR3=1.09

UTAH BITUMINOUS #2

RESIDENCE TIME, SEC

□ NO + N2O

T°K

1480

1425

1168

1118

Figure 17.

SR1=0.64, SR2=0.72, SR3=0.9

UTAH BITUMINOUS #2

Figure 18.

END

DATE
FILMED
2 12 1 192

I