9-92 GS ①

ORNL/TM-11798

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

Development Studies for the Treatment of ORNL Low-Level Liquid Waste

D. O. Campbell
D. D. Lee
T. A. Dillow

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/TM--11798

DE92 004597

Chemical Technology Division

**DEVELOPMENT STUDIES FOR THE TREATMENT
OF ORNL LOW-LEVEL LIQUID WASTE**

D. O. Campbell
D. D. Lee
T. A. Dillow

Date Published - November 1991

Prepared for the
Office of Environmental Restoration and Waste Management
(EW 30 20 02 1)

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

LIST OF TABLES	v
LIST OF FIGURES	v
ACRONYMS AND INITIALISMS	vii
ABSTRACT	1
1. INTRODUCTION	2
2. EXPERIMENTAL RESULTS	5
2.1 TESTS WITH INORGANIC SORBENTS.	5
2.1.1 Experimental Methods	5
2.1.2 Removal of Cesium from Simulant Solutions with Inorganic Sorbents	8
2.1.2.1 Effect of High Alkali-Metal Concentrations	8
2.1.2.2 Effects of Cesium Concentration and Ferrocyanide Dosage	9
2.1.2.3 Removal of Cesium from High-pH Solutions with Dried KCoFC	12
2.1.2.4 Removal of Cesium with Other Transition-Metal Ferrocyanides. .	17
2.1.2.5 Removal of Cesium from Acid Solutions with Ferrocyanides	18
2.1.3 Removal of Cesium from MVST Supernate Solutions with Inorganic Sorbents	19
2.1.4 Removal of Strontium from Simulant Solutions with Inorganic Sorbents .	23
2.2 SIMULANT DECONTAMINATION WITH ORGANIC ION-EXCHANGE RESINS	24
2.2.1 Experimental Methods	25
2.2.2 Cesium and Strontium Removal with Chelating Resins	26
2.2.2.1 Batch Tests	26
2.2.2.2 Simultaneous Cesium and Strontium Removal with Mixed-Resin Column	29
2.2.3 Source Treatment Studies of Aluminum Decladding Solutions	29
2.3 CROSS-FLOW FILTRATION TESTS	36
2.3.1 Experimental Methods	37
2.3.2 Experimental Results	37
2.4 REMOVAL OF ⁶⁰ Co FROM SUPERNATE	38
2.4.1 Experimental Methods	38
2.4.2 Experimental Results	38
2.5 NITRATE REMOVAL	40
2.5.1 Experimental Methods	41
2.5.2 Experimental Results	41
3. SUMMARY	42
4. REFERENCES	44

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 Effects of sodium and potassium concentrations on cesium removal	9
2 Effect of cesium concentration on cesium K_d from W-29 simulant at pH 10	10
3 Effects of cesium concentration, pH, and NaNiFC concentration on cesium removal	12
4 Distribution coefficients of KCoFC and NaCoFC at different sorbent loadings . .	13
5 Percent removal of cesium at high pH with granular KCoFC	15
6 Cesium distribution coefficients at high pH with granular KCoFC	16
7 Cesium distribution coefficients at high pH with commercial KCoFC	16
8 Cesium distribution coefficients with granular KCuFC (100-200 mesh, 333 ppm) and NaNiFC slurry	18
9 Cesium distribution coefficients for acidified solutions with 100 ppm ferrocyanides	20
10 Cesium removal from acid solutions with 100 ppm NaNiFC at 4-d contact time .	21
11 Test of three-stage batch separation of ^{137}Cs from W-26 supernate	22
12 Strontium removal from W-29 simulant with inorganic sorbents	24
13 Batch Sr and Cs K_d s with simulant ($\text{Na} = 4.58 \text{ M}$, $\text{K} = 0.25 \text{ M}$, $\text{pH} = 12.9$, 150 L/kg resin)	27
14 Batch strontium and cesium K_d data for chelating and SRS resins (phase ratio: 1500 L liquid/kg resin)	28
15 Expected composition of aluminum target dissolution waste	32
16 Cesium and strontium removal from caustic aluminate solution with inorganic sorbents	33
17 Comparison of 60-80 mesh with 120-140 mesh SRS resin using simulated aluminate waste (72-h contact)	34
18 Removal of cesium and strontium from simulated aluminate waste using 60-80 mesh particle size SRS resin (72-h contact)	35

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1 Breakthrough curves for mixed IRC-718 plus SRS resin column	30

ACRONYMS AND INITIALISMS

CV	Column volumes
DF	Decontamination factor (C_0/C)
DOE	U.S. Department of Energy
KCoFC	Potassium cobalt ferrocyanide
KCuFC	Potassium copper ferrocyanide
K_d	Distribution coefficient
LLW	Low-level (radioactive) liquid waste
MVSTs	Melton Valley Storage Tanks
MWCO	Molecular weight cutoff
NaCoFC	Sodium cobalt ferrocyanide
NaNiFC	Sodium nickel ferrocyanide
NaT	Sandia sodium titanate
ORNL	Oak Ridge National Laboratory
ppm	Parts per million (amount of sorbent)
REDC	Radiochemical Engineering Development Center
TRU	Transuranic (waste)
WHPP	Waste Handling and Packaging Plant

DEVELOPMENT STUDIES FOR THE TREATMENT OF ORNL LOW-LEVEL LIQUID WASTE

D. O. Campbell
D. D. Lee
T. A. Dillow

ABSTRACT

An experimental program is under way to investigate potential separation methods for application to specific problems relating to the management of low-level liquid wastes (LLW) at ORNL. This report summarizes experimental results that were acquired during fiscal year 1990 and have not been previously reported elsewhere. Measurements are presented for cesium and strontium removal from simulated high-salt waste compositions, using both inorganic ion-exchange sorbents and organic ion-exchange resins, and for one experiment with actual LLW supernate solution from Melton Valley Storage Tank W-26, using inorganic sorbents. The purpose of the study was to acquire an extensive data base to support the development of flowsheets for decontamination of the LLW currently stored at ORNL.

Experimental measurements with inorganic ion exchangers focused on batch separations of cesium using several transition-metal hexacyanoferrate(II) compositions (ferrocyanides) and of strontium using titanium oxide-based sorbents. Cesium distribution coefficients in the range of 1×10^6 were generally observed with nickel and cobalt ferrocyanides at pH values ≤ 11 , yielding DFs of about 100 with 100 ppm sorbent in a single-stage batch separation. The ferrocyanides decompose at higher pH levels, but certain compositions can be stabilized by heat treatment and will maintain their effectiveness up to pH 13 for times of a few days. Ferrocyanides are stable in acid solutions and remain reasonably effective as the pH decreases into the acid concentration range of at least 1-2 M. Strontium distribution coefficients as large as 1×10^5 were observed with sodium titanate at pH 13, but these values decrease as the pH decreases.

Most organic ion-exchange resins are not very effective for cesium removal from such high salt concentrations, but a new resorcinol-based resin developed at the Savannah River Site was found to be considerably superior to any other such material tested. An unexpected effect of resin particle size was observed; that is, the larger resin particles showed more effective cesium removal than did the small particles. Several chelating resins were effective for removing strontium (along with other polyvalent ions) from the waste simulants. An ion-exchange column test successfully demonstrated the simultaneous removal of both cesium and strontium from a waste simulant solution.

The large distribution coefficients and poor physical form (degradation to small particles) of most inorganic sorbents favor their use in simple batch separation processes. Although distribution coefficients were smaller with organic resins than with the best inorganic sorbents, they were large enough, in some cases, to make batch processes possible. However, organic resins are generally more suited to column operations, and the distribution coefficients for these materials were entirely adequate for this application.

Experiments using ultrafiltration for particulate removal are described. Various methodologies were explored to remove ^{60}Co from supernate, including ion exchange and ultrafiltration. Scouting experiments are also described for nitrate removal from simulant.

1. INTRODUCTION

An experimental program was initiated to investigate potential separation methods for application to specific problems relating to the management of low-level liquid wastes (LLW) at ORNL. The wastes of particular concern include the contents of the Melton Valley Storage Tanks (MVSTs) and similar tanks associated with the LLLW evaporator, currently and future generated LLLW that is being, or will be, added to the MVSTs, and residual wastes in the inactive storage tanks that might be transferred to the MVSTs. Some of the methods under study may also be applicable to treatment of the process waste and of certain wastes at the point of generation — before they are diluted into and contaminate a large volume and are mixed with other constituents, creating a waste that is more difficult to treat.

At the beginning of this study, it was known that the major radioactive constituents in these wastes were alpha-emitting actinides, ^{137}Cs , and ^{90}Sr . Tank sampling indicated that the alpha content of the supernate was generally below the 100-nCi/g limit for transuranium (TRU) waste. Accordingly, the study was focused on removal of cesium and strontium from the supernate. The primary emphasis was placed on cesium removal because the activity level of cesium was higher than that of any other radionuclide; in addition, since it is the dominant gamma-emitter, its removal would allow subsequent waste processing operations (further decontamination, concentration, solidification, and transportation) to be conducted without the necessity of contending with a high gamma field. More recent analyses¹ have indicated that, although these are clearly the most significant activities, other constituents must also be considered, depending on the final disposition of the waste. These include

^{60}Co , ^{14}C , nitrate, RCRA* metals, and possibly others. The implications of these analyses and evolving specifications for liquid and solid wastes are considered in another report which is now in preparation.²

The objective, then, was to develop processes to remove cesium, strontium, and (if necessary) actinides from the waste supernate, thereby allowing the supernate to be disposed of on-site (either as a solid waste after treatment or possibly as a liquid discharge after adequate decontamination). The specific initial goals were (1) the separation of cesium and (2) the separation of strontium from alkaline solutions containing high concentrations of NaNO_3 , moderate concentrations of KNO_3 , and low concentrations of several other ions. Removal of enough supernate in this manner would reduce the volume of waste contained in the existing tanks so that they would be adequate to contain all of the LLLW sludge, which is a TRU waste, until the Waste Handling and Packaging Plant³ (WHPP) is built to process the accumulated LLLW for shipment to the Waste Isolation Pilot Plant. An alternative process to provide additional sludge storage capacity, direct solidification of supernate (without decontamination) into solid monoliths, has been used once and may be used subsequently. Decontamination of the supernate prior to solidification would reduce the radiation level and, therefore, the handling and disposal problems associated with these solid wastes.

The fundamental premise underlying this approach is that there is an inherent benefit if the waste can be divided into fractions of differing potential hazard. In this way, the quantity of more-hazardous waste is greatly reduced while the bulk of the waste is made much less hazardous, thereby meeting requirements for storage and disposal with less restrictive conditions or possibly even environmental release. This is possible, in principle, because the elements containing radioactive isotopes constitute only a small fraction of the total quantity of waste. The bulk components in the supernate are primarily water and salts such as NaNO_3 and KNO_3 .

Two general approaches have been followed in this study. One is the use of inorganic ion-exchange sorbents that have remarkably high affinity for the elements of interest. These reagents can be added during batch clarification or scavenging precipitation processes to enhance the removal of a variety of elements. Such processes are commonly used in Europe for treating low- and intermediate-level wastes.⁴ The other approach is

*Resource Conservation and Recovery Act.

conventional ion-exchange column separations using organic resins, which are commonly used for treating relatively pure (low-salt-content) water but are less satisfactory for high-salt solutions.

Based largely on an extensive literature base and experience with waste processing primarily in Europe,⁵⁻⁷ which are not reviewed here, the transition-metal hexacyanoferrate(II) compounds and formulations based on titanium oxide were selected as the primary candidates for cesium and strontium removal, respectively. Many other materials were considered but were concluded to be less promising for various reasons. Several zeolites have been used successfully for decontaminating water of relatively low salt content from both cesium and strontium, but they have little capacity with these LLLW solutions. Tetraphenyl borate has been used successfully for cesium removal; however, it is subject to serious interference from potassium, which is a major constituent in some MVST tanks; it also has secondary environmental problems. A new material, cobalt dicarbolyde,⁸ has recently been proposed, but it is currently very expensive and not well documented. An extensive literature review revealed that several inorganic sorbents (i.e., titanates, niobates, tungstates, titanium phosphate, zirconium phosphate, polyantimonic acid) have been shown to remove strontium under some conditions. These sorbents do not efficiently separate strontium from calcium, an important metal in the MVSTs; however, a new solvent extraction process, SREX,^{9,10} has been shown to separate strontium from most metals, even from the other alkaline earths. Studies of cesium removal with organic resins have centered on a new resin developed at the Savannah River Site specifically for cesium removal.^{11,12} At the same time, other organic resins suitable for removing other elements of concern (notably strontium) are being tested.

Prior experimental results have been presented in a letter report,¹³ and a paper has been published in the Proceedings of the Waste Management '90 Conference.¹⁴ These reports summarize extensive data covering the anticipated range of application of these sorbents to a MVST simulant solution. Additional experimental data are given in this report, much of which concerns extension of the study to a wider variation of conditions to establish more definitively the range of applicability of the inorganic sorbents. These studies include the removal of cesium and strontium from various solutions by use of both inorganic sorbents and organic ion-exchange resins. A wide range of conditions has been investigated because of the large variations that are anticipated in various waste streams that might be processed. In addition, a multistage, batch cesium-removal test with MVST W-26 supernate is reported.

2. EXPERIMENTAL RESULTS

2.1 TESTS WITH INORGANIC SORBENTS

2.1.1 Experimental Methods

All the data with inorganic sorbents have been obtained from batch contacts of the sorbent with the appropriate solution. Unless otherwise noted, a simulant solution derived from analysis of MVST W-29 was used; the W-29 simulant contained 3.9 M NaNO₃, 0.25 M KNO₃, 0.24 M NaOH, 0.14 M Na₂CO₃, 0.1 M NaCl, 0.001 M Zn(NO₃)₂, 0.0005 M Al(NO₃)₃, and 0.0001 M CaCO₃. The MVST tanks differed somewhat in overall composition; however, the potassium, calcium, carbonate, and acid concentrations varied by large factors. The W-29 simulant solution was spiked with cesium using a small amount of actual W-29 supernate (¹³⁷Cs predominant) and with strontium using ⁸⁵Sr tracer. Solutions were adjusted to the specified pH prior to the test, and usually the pH was checked again afterward; in most cases, the changes were small. Orion Research Model SA 520 and 811 pH meters were used. Some difficulty was encountered with pH determinations in the solutions of high Na⁺ and high pH, but the problem was traced to a certified pH standard that was in error. It was difficult to adjust to and maintain a stable pH in an experiment using actual MVST W-26 supernate, which was very low in carbonate ion; the addition of ~0.001 M Na₂CO₃ alleviated this problem.

A sorbent and a solution were mixed in 15-mL centrifuge cones using a "Roto-Torque" rotating mixer. The rotational speed and tilt angle were adjusted, by experiment, to give good mixing even with fairly large sorbent particles. After being mixed for predetermined times, the cones were removed and (unless stated otherwise) centrifuged prior to sampling. Variations in the clarification procedure included sedimentation, filtration, centrifugation following filtration, and double centrifugation.

Filtration was accomplished with 4-mm-diam Nalgene filter discs of cellulose acetate, 0.2- μ m pore size. Centrifugation was carried out in 15-mL centrifuge tubes using a 30-cm-diam IEC HN SII centrifuge. In most of the work, polypropylene tubes were used at 2600 rpm. Glass centrifuge tubes were used in the initial work, but they occasionally broke at 2600 rpm; as a result, they were centrifuged at about 2200 rpm. In all cases, the samples were centrifuged for approximately 10 min.

Samples of the clarified supernate (usually 1 mL) were removed with a pipette and transferred to sample vials for counting. It is often difficult to remove all of the sorbent crystals from the solutions; in many cases, reclarification led to a lower activity in the

sample and a higher decontamination factor (DF). Samples were counted using either a NaI well counter with an LBK Wallack Compugamma analysis system or an intrinsic germanium detector and spectral analysis system. Only relative counts are required in this work, but counters were calibrated against counting standards.

The transition-metal hexacyanoferrate(II) compounds can be prepared and used in several ways. Nearly all the work was concerned with nickel or cobalt ferrocyanide, but some experiments were also performed with the zinc, iron, manganese, and copper compounds. Four methods were used: (1) preparation in situ by adding (while mixing) a specified amount of 0.1 M metal nitrate solution, followed by the specified amount of 0.1 M $\text{Na}_4\text{Fe}(\text{CN})_6$ or $\text{K}_4\text{Fe}(\text{CN})_6$; (2) preparation in situ by adding the reagents in the reverse order; (3) preparation of a slurry by adding the reagents to water and then adding a specified amount of the slurry to the test solution; and (4) adding a weighed amount of solid prepared by filtering, washing, and drying a slurry. In many cases, the procedure of Prout, Russell, and Groh¹⁵ for preparing KCoFC was followed, substituting the metal of interest for cobalt (hereafter referred to as the Savannah River method). This method was carried to the point of preparing a slurry [for method (3)] or the dried solid [for method (4)]. In some cases, the slurries were diluted with demineralized water so that the volume to be added could be measured more accurately. All data in this report are derived from experiments using preparation method (3) or (4).

The first three methods gave similar results except that the difficulty of clarification varied considerably, depending on the exact procedure followed. Most work was done using the slurry (method 3) or a dried material (method 4). The ferrocyanide slurries were readily prepared by mixing a 0.1 M solution of $\text{Na}_4\text{Fe}(\text{CN})_6$ or $\text{K}_4\text{Fe}(\text{CN})_6$ with a 0.1 M solution of the metal salt (nickel or cobalt nitrate); a measured amount of the slurry was then added to the waste solution after pH adjustment. The ratio of metal to ferrocyanide was generally 1.5 to 1.7, and some excess metal probably precipitated as $\text{Ni}(\text{OH})_2$ or $\text{Co}(\text{OH})_2$, which would strongly affect the sedimentation properties. Results of early qualitative tests showed that clarification was more difficult if the metal/ferrocyanide ratio was less than about 1.5, and precipitate particle sizes are very small at best. However, in practice, lower ratios might be advantageous if solutions are clarified by filtration.

Since the ferrocyanides are usually not stoichiometric or are mixtures of compounds, the actual concentration used is subject to some uncertainty. The composition can be represented as $\text{A}_n\text{T}_{(2-n/2)}\text{Fe}(\text{CN})_6$, where A represents the alkali metal (Na or K), T is the

transition metal (Co, Ni, etc.), and $n < 4$. In this study, concentrations (as ppm, defined as mg solid/L solution) are calculated by assuming that all the metal (Ni or Co) and all the $\text{Fe}(\text{CN})_6^{4-}$ form a precipitate and, in addition, enough of the alkali metal (Na or K) is included to satisfy valency requirements. In practice, these sorbents do have slight solubilities and a small fraction of the metal may not be included in the compound but, instead, may precipitate as the hydroxide. Also, they are hydrates, which would increase their mass. Most work was carried out with a nominal 100 ppm by adding a pre-prepared slurry with concentrations corresponding to $5.7 \times 10^{-4} \text{ M Co}^{2+}$ or Ni^{2+} and $3.4 \times 10^{-4} \text{ M Fe}(\text{CN})_6^{4-}$, which calculate to be 104 and 108 ppm for the Na and K compounds, respectively.

The nickel ferrocyanides and sodium cobalt ferrocyanide (NaCoFC) yield powders when dried, but some compositions (including copper ferrocyanides and potassium cobalt ferrocyanide [KCoFC]) can be prepared as hard, granular material. Nickel ferrocyanides can be prepared as granular solids, but only by a long and tedious process.¹⁶ The granular solids can be used in ion-exchange columns.¹⁷ All of these sorbents may be used for cesium removal over the pH range from a maximum of about 11 down to moderately acidic solutions. Above pH 11, the compounds are decomposed and lose effectiveness. This happens rapidly with powders, but granular KCoFC, after proper conditioning, is relatively stable for many hours to several days at pH levels up to 13.¹⁷ Digestion at high pH (>13) eventually frees the cesium and ferrocyanide ion, leaving a nickel or cobalt hydroxide precipitate; in this way, the cesium could be recovered for further concentration, if desired.

The sorbents tested for strontium removal (sodium titanate, titanium oxide, hydrous titania, titanium phosphate, and zirconium phosphate) were used as particulate solids. The sodium titanate was obtained several years ago from a development program at the Sandia National Laboratory.¹⁸ The titanium oxide was Fisher reagent grade. The other materials were gel-derived microspheres made by the internal gelation process and prepared by J. L. Collins (ORNL).

The results of the experiments can be expressed by several different parameters that relate to the decontamination effectiveness. The distribution coefficient, which is useful because it is approximately constant over a reasonable range of conditions, is calculated as:

$$K_d = (C_o - C)V/mC = 10^6(C_o - C)/C(\text{ppm}), \quad (1)$$

where C_o and C are the aqueous concentrations (Bq/mL) of the radioisotope before and after treatment, m is the mass of sorbent (g), V is the volume of waste solution (mL), and ppm is the amount of sorbent in parts per million, expressed in this paper as mg sorbent per liter of solution. When successive samples were removed from the same experiment, the values of C_o and V were recalculated after each sample was withdrawn, taking into account the measured concentration and volume of the sample withdrawn.

The decontamination factor, as used in this report, is:

$$DF = C_o/C = 1 + 1 \times 10^6 (\text{ppm}) K_d. \quad (2)$$

Defined in this way, the DF includes concentration reduction due to dilution as well as ion exchange, but there are other definitions of DF that can be used, notably the total activity in the feed divided by the total activity in the product.

The reduction of activity (including dilution) can also be expressed as the percent removed:

$$\% \text{ removed} = 100(C_o - C)/C_o = 100(1 - 1/DF) = 100(\text{ppm})K_d/[10^6 + (\text{ppm})K_d]. \quad (3)$$

In the data reported as DF or as % removed, the correction for variations in concentration of successive samples has not been made. In effect, this causes the reported "% removed" to be slightly smaller than the true value in some cases.

2.1.2 Removal of Cesium from Simulant Solutions with Inorganic Sorbents

2.1.2.1 Effect of High Alkali-Metal Concentrations

Characterization data for the MVSTs¹ indicated that the potassium concentration was much higher in some cases than the ~0.25 M expected, up to a maximum of approximately 2 M in one tank and 0.5 M average in all tanks. Since potassium is the primary interference with cesium removal by most processes, a series of tests was performed to extend both the sodium and potassium concentrations to higher concentrations (8 and 1 M, respectively) than those of the W-29 simulant. Both sodium nickel ferrocyanide (NaNiFC) and KCoFC were tested as slurries at 50 ppm at pH 9.5 and with mixing times of 3 h to 4 d. The results (Table 1) indicate that NaNiFC is somewhat better, especially at the highest potassium concentration, but both are remarkably effective even with 8 M NaNO₃—

1 M KNO_3 . The data represent the average of two samples after mixing for 4 d; one sample was centrifuged twice, while the other was centrifuged and then filtered. Samples taken after centrifuging only once (including all samples at shorter contact times) showed comparable or slightly less effective cesium removal.

The NaNiFC compound was somewhat better, especially in cases of high KNO_3 and low NaNO_3 concentrations. There was an unexpected trend for KCoFC to be less effective in the lower NaNO_3 concentrations than in higher concentrations, but this may be related to clarification rather than ion-exchange properties.

Table 1. Effects of sodium and potassium concentrations on cesium removal

Na conc. (<u>M</u>)	% Removed at:			K_d at:		
	0.25 <u>M</u> K	0.50 <u>M</u> K	1.00 <u>M</u> K	0.25 <u>M</u> K	0.50 <u>M</u> K	1.00 <u>M</u> K
<u>50 ppm NaNiFC Slurry</u>						
2	99.4	98.7	97.6	3.0E6	1.3E6	7.1E5
4	99.1	99.1	98.2	2.0E6	2.0E6	9.7E5
8	96.5	98.3	98.0	5.7E5	1.1E6	9.1E5
<u>50 ppm KCoFC Slurry</u>						
2	97.9	94.7	89.7	8.3E5	3.2E5	1.6E5
4	99.3	99.2	91.3	2.6E6	2.6E6	1.9E5
8	98.0	98.0	98.0	9.1E5	9.0E5	9.0E5

2.1.2.2 Effects of Cesium Concentration and Ferrocyanide Dosage

Since significant loadings of ion exchangers can be achieved when very large phase ratios are used, even when the exchanging ion is quite dilute, a test was carried out to determine the effect of cesium concentration on the distribution coefficient. Stable cesium was added to yield concentrations from 2.5×10^{-7} to 1×10^{-5} M in W-29 waste simulant solution that was traced with W-29 waste supernate. The tracer added a negligible additional cesium concentration (about 1×10^{-9} M). The results (Table 2, upper half) show that the cesium K_d exceeded 1×10^6 for all mixing times of 1 d or more over the entire cesium concentration range when 100 ppm NaNiFC slurry was used. Corresponding cesium removals are generally in excess of 99.5%. With KCoFC , the K_d s were generally $< 1 \times 10^6$.

Most tests with ferrocyanide slurries have used approximately 100-ppm dosages. Tests with dried, granular material have used even larger amounts, commonly 333 to 500 ppm, because of the difficulty in accurately weighing the small amounts. Earlier tests with ferrocyanides for removing cesium from tap water were reasonably successful with smaller additions, down to <10 ppm. Accordingly, a parallel set of experiments was done with the W-29 simulant solution using slurry additions of 10 ppm of both NaNiFC and KCoFC (Table 2, lower half).

With 10 ppm NaNiFC, the K_d values were about 6×10^4 after 1 h, with a slight trend to decrease as the cesium concentration increased. However, they decreased to very small values after 1- and 6-d contact times with the lower cesium concentrations but increased somewhat at the highest cesium concentration. With 10 ppm KCoFC, there was no useful cesium removal at any time for cesium concentrations $<2.5 \times 10^{-6}$ M; at higher concentrations, however, there was significant cesium removal that increased with time.

Table 2. Effect of cesium concentration on cesium K_d from W-29 simulant at pH 10

Cs (M)	K_d at: 100 ppm NaNiFC			K_d at: 100 ppm KCoFC		
	1 h	1 d	6 d ^a	1 h	1 d	6 d ^a
2.5E-7 ^b	5.0E5	1.3E6	3.2E6	8.3E5	4.1E5	7.5E5 ^c
5.0E-7	7.2E5	2.0E6	2.1E6	7.2E5	3.8E5	5.8E5 ^c
1.0E-6	5.2E5	1.7E6	2.0E6	5.3E5	3.8E5	8.2E5 ^c
2.5E-6	7.2E5	1.2E6	3.3E6 ^c	4.9E5	3.6E5	8.1E5 ^c
5.0E-6	7.0E5	1.8E6	3.6E6 ^c	4.8E5	4.6E5	8.8E5 ^c
1.0E-5	6.5E5	1.5E6	3.4E6 ^c	4.4E5	4.0E5	1.0E6 ^c
	10 ppm NaNiFC			10 ppm KCoFC		
	1 h	1 d	6 d ^a	1 h	1 d	6 d ^a
2.5E-7	7.3E4	≈ 1	≈ 1	3.3E2	≈ 1	2.3E2
5.0E-7	6.3E4	≈ 1	≈ 1	≈ 1	≈ 1	2.1E2
1.0E-6	6.3E4	≈ 1	≈ 1	7.1E1	≈ 1	1.6E2
2.5E-6	4.4E4	2.1E4	9.1E3	3.9E3	1.9E3	1.1E3
5.0E-6	2.9E4	≈ 1	≈ 1	2.2E4	3.7E4	6.6E4
1.0E-5	3.3E4	4.9E4	5.6E4	1.7E4	3.2E4	5.8E4

^aThe 6-d samples are averages of three determinations: (a) centrifuged once; (b) centrifuged twice; and (c) centrifuged and then filtered. All other samples were centrifuged once.

^bRead as 2.5×10^{-7} .

^cIn these cases, K_d was larger in the samples clarified by method (c), indicating the presence of small particles not completely removed by centrifugation.

Cesium concentrations of 5×10^{-6} and 1×10^{-5} M yield cesium loadings in the 10 ppm sorbent of about 0.25 and 0.5 meq/g, respectively, when about half the total cesium is loaded, as was the case here. These results show that sorbent concentrations greater than 10 ppm are necessary for effective cesium removal from W-29 simulant at pH 10 and suggest that conversion of the sorbent to the cesium form (CsNiFC or CsCoFC), by exchanging cesium for the other alkali metals, stabilizes the ferrocyanides against decomposition.

A different set of experiments with slurries containing 10, 20, or 40 ppm NaNiFC and cesium carrier indicated that cesium removal is inhibited at pH 10, compared with pH 7 (Table 3). The effect of cesium concentration at pH 7 with 10 ppm sorbent appeared to be modest, with a small decrease in cesium removal as the concentration increased. The cesium loading of the sorbent was surprisingly large in the case of 5×10^{-5} M cesium, corresponding to 2.6 meq/g sorbent. At pH 10 with 10 ppm sorbent, cesium removal was about the same at 2.5×10^{-6} to 5×10^{-5} M at 1 h and 1 d but decreased after 4 d. Only in the case of 5×10^{-5} M cesium did cesium removal become very small. This is in contrast to the observation reported in Table 2, in which increased cesium concentration (to a maximum of 1×10^{-5} M) caused an improvement in cesium removal; however, at 5×10^{-5} M, more cesium is present than can be exchanged into the sorbent. Although an accurate cesium concentration has not been reported for the waste, earlier results indicate that cesium is <0.5 ppm, or $<4 \times 10^{-6}$ M, well within the range of these measurements. Therefore, the data indicate that the cesium loading from the MVST waste will not significantly reduce the efficiency of cesium removal.

At pH 7, cesium removal always increased with time; at pH 10, however, it decreased after 1 d in every case except that for 40 ppm NaNiFC. This observation again indicates that the ferrocyanides lose effectiveness as pH increases, probably as the result of decomposition (metathesis) of the sorbent to form the transition-metal hydroxide $[\text{Ni}(\text{OH})_2]$ as pH increases. As the sorbent dosage increases, this effect becomes less important. Thus, at pH 10 with low cesium concentrations, 10 ppm sorbent is relatively ineffective; however, there is only a small loss in effectiveness with time with 20 ppm NaNiFC, and with 40 ppm, the cesium removal increased over the test period. Other data have shown that effectiveness is lost at pH about 11 when 100 ppm sorbent is used.

Table 3. Effects of cesium concentration, pH, and NaNiFC concentration on cesium removal

Cs (M)	NaNiFC conc. (ppm)	pH	K _d after:		
			1 h	1 d	4 d ^a
2.5E-7	10	7	1.0E5	1.9E5	3.6E5
2.5E-6	10	7	7.3E4	1.4E5	3.2E5
5.0E-6	10	7	5.6E4	1.0E5	--
5.0E-5	10	7	--	--	6.7E4
5.0E-6	40	7	8.9E4	2.4E5	--
5.0E-5	40	7	--	--	1.4E5
2.5E-6	10	10	4.8E4	4.6E4	1.0E4
2.5E-6	20	10	9.1E4	1.2E5	6.1E4
2.5E-6	40	10	1.8E5	4.1E5	9.3E5
5.0E-6	10	10	4.3E4	5.0E4	2.9E4
5.0E-5	10	10	5.2E4	4.0E4	1.2E3

^aThe 4-d samples are averages of three determinations: (a) centrifuged once; (b) centrifuged twice; and (c) centrifuged and then filtered. All other samples were centrifuged once.

Results of a comparison of KCoFC and NaCoFC slurries prepared according to the Savannah River method¹⁵ showed that each product had limited stability at pH 11.1 (Table 4). In this test, different amounts of sorbent from 20 to 200 ppm were used. At pH 9.2, the two materials were generally comparable except for the 20 ppm NaCoFC series, which gave lower results than the others. At pH 11, both materials were ineffective at 20 and 50 ppm, but K_d increased with higher sorbent concentrations, 100 and 200 ppm. At pH 11 with 100 and 200 ppm sorbent, the K_d decreased from 1 or 6 h to 3 or 4 d. With 200 ppm sorbent at pH 11, NaCoFC gave larger K_ds than did KCoFC at longer times; however, at still higher pH levels, both compositions became ineffective.

2.1.2.3 Removal of Cesium from High-pH Solutions with Dried KCoFC

Since the dried, granular KCoFC is resistant to decomposition by solutions of pH higher than 11, a series of experiments was conducted at pH 9, 12, and 13 using amounts of

Table 4. Distribution coefficients of KCoFC and NaCoFC at different sorbent loadings

Time	Amount of sorbent (ppm)			
	20	50	100	200
<u>KCoFC, pH 9.2</u>				
12 min	3.1E4	6.9E4	4.5E4	1.1E5
1 h	6.8E4	1.5E5	1.5E5	1.8E5
6 h	2.3E5	3.3E5	3.4E5	3.6E5
3 d	6.7E5	6.4E5	7.9E5	8.6E5
4 d	5.5E5	5.0E5	3.0E5	2.4E5
4 d, filt.	8.4E5	1.1E6	1.9E6	2.8E6
<u>KCoFC, pH 11.1</u>				
12 min	4.4E2	3.7E2	5.2E3	2.5E5
1 h	~0	~0	5.4E3	4.9E5
6 h	~0	~0	3.7E3	4.1E5
3 d	~0	~0	1.7E3	3.4E4
4 d	--	--	--	1.9E4
<u>NaCoFC, pH 9.2</u>				
12 min	1.3E4	8.7E4	6.9E4	1.4E5
1 h	2.5E4	1.8E5	1.9E5	2.5E5
6 h	6.6E4	3.8E5	4.6E5	5.6E5
3 d	1.3E5	8.1E5	6.7E5	6.1E5
4 d	1.4E5	7.4E5	6.2E5	6.7E5
4 d, filt.	1.5E5	1.2E6	2.2E6	1.9E6
<u>NaCoFC, pH 11.1</u>				
12 min	41	~0	6.2E3	2.3E5
1 h	~0	~0	1.5E4	6.9E5
6 h	~0	~0	2.0E4	3.7E5
3 d	~0	~0	5.6E2	2.1E5
4 d	--	--	--	3.1E5

sorbent between 67 and 667 ppm. The KCoFC was prepared according to the Savannah River method,¹⁵ dried at 100°C, and screened to 100-230 mesh particle size. The results are reported in Table 5. At pH 9, the fractional cesium removal increased steadily with time and the amount of KCoFC added. It is apparent that, although a substantial degree of cesium exchange was achieved within a few hours, the fraction removed continued to increase even after 3 d.

At pH 12, the cesium removal increased to a maximum in the time range of 1 to 3 d and then decreased somewhat at 14 d. The exception to this is the test with the largest KCoFC addition, 667 ppm, in which cesium removal remained essentially constant from 1 to 14 d. Thus, with a relatively large amount of sorbent, effective cesium removal was achieved for contact times of at least 14 d at pH 12.

The performance was degraded considerably more at pH 13 than at pH 12. Cesium removal was decreasing within 1 d, but it was still >90% for 3 d in the case of the largest KCoFC addition. Thus, even at pH 13, significant cesium removal can be realized over a period of the order of 1 d to perhaps a few days if the amount of sorbent is large enough. These results also indicate that the storage of cesium-loaded sorbents at high pH levels will result in decomposition of the sorbent and release of the sorbed cesium.

The large range of sorbent concentrations obscures the actual exchange properties, and the same data are presented as K_d values in Table 6. Over the time interval up to 3 d, K_d values are generally larger at pH 12 than at pH 9, although they subsequently decrease at longer times at pH 12. It can be seen that, in most cases, the K_d value did not change significantly as the sorbent dosage increased by a factor of 10, from 67 ppm to 667 ppm. The major exceptions to this generalization are for the longest time of mixing at pH 12 and 13, at which K_d increased for the largest amount of sorbent.

It is clear that, at lower pH levels, K_d is smaller with the granular form of KCoFC (compare the pH 9.1 data in Table 6 with the pH 10 data in Table 2), probably because of a smaller surface area. The advantage of the heat-treated, granular sorbent is its resistance to high-pH solutions. The loss of effectiveness with increasing time at high pH is probably caused by slow metathesis of part of the sorbent to $\text{Co}(\text{OH})_2$, which effectively reduces the amount of KCoFC. Such a reaction to decompose part of the sorbent is apparently much slower with the granular KCoFC than with slurries that become ineffective at pH 13 within a much shorter time. Since decomposition of the sorbent is probably related to solubility products, excess sorbent can be added to compensate for the loss of effectiveness.

Table 5. Percent removal of cesium at high pH with granular KCoFC

Time	Granular KCoFC (ppm)			
	67	133	333	667
<u>pH 9.1</u>				
2 h	47	60	83	94
6 h	63	74	90	96.5
24 h	77	85	94	98.1
3 d	83	89	95	98.5
14 d	89	92	97	99.0
<u>pH 12.1</u>				
2 h	59	81	90	96.5
6 h	77	90	95	98.2
24 h	88	95	97	99.1
3 d	87	95	98	99.1
14 d	75	90	95	99.2
<u>pH 13.2</u>				
2 h	74	83	90	96.9
6 h	78	86	91	97.1
24 h	73	82	89	96.6
3 d	42	58	73	91.3
14 d	0	0	3	57.4

A commercial preparation of KCoFC that had been marketed by Bio-Rad some years ago, but is no longer available, was tested at pH 9, 11, 12, and 13; the results are shown in Table 7. The distribution coefficients increased with time at pH 9 but showed a maximum at some intermediate time at the higher pHs. The higher the pH, the shorter the time to the maximum. As in the cases reported above, the values tended to be smaller at pH 9 than at the higher pHs, except for the longer exposure times. After 4 d, this material is slightly superior to the preparation described in the preceding tables.

Table 6. Cesium distribution coefficients at high pH
with granular KCoFC

Time	Granular KCoFC (ppm)			
	67	133	333	667
<u>pH 9.1</u>				
2 h	1.4E4	1.2E4	1.5E4	2.3E4
6 h	2.5E4	2.1E4	2.6E4	4.1E4
24 h	4.8E4	4.1E4	4.7E4	7.7E4
3 d	6.9E4	5.8E4	6.0E4	9.8E4
14 d	1.1E5	8.7E4	9.8E4	1.5E5
<u>pH 12.1</u>				
2 h	2.1E4	3.2E4	2.3E4	4.3E4
6 h	5.0E4	7.0E4	5.2E4	8.2E4
24 h	1.1E5	1.4E5	1.1E5	1.7E5
3 d	1.0E5	1.4E5	1.2E5	1.7E5
14 d	4.6E4	6.5E4	6.0E4	1.9E5
<u>pH 13.2</u>				
2 h	4.3E4	3.8E4	2.7E4	4.7E4
6 h	5.4E4	4.6E4	3.1E4	5.0E4
24 h	4.1E4	3.5E4	2.4E4	4.2E4
3 d	1.3E4	1.1E4	8.5E3	1.6E4
14 d	5.2E2	7.7E2	7.7E2	2.4E3

Table 7. Cesium distribution coefficients at high pH with
commercial KCoFC^a

Time	pH			
	9	11	12	13
1 h	1.2E3	1.6E3	2.4E3	6.3E3
24 h	2.7E4	5.7E4	5.3E4	4.1E4
4 d	7.6E4	1.3E5	1.0E5	1.7E4
7 d	1.0E5	1.7E5	9.8E4	8.0E3
14 d	1.4E5	9.1E4	8.5E4	2.5E3

^a333 ppm of 20-50 mesh particles supplied by Bio-Rad.

2.1.2.4 Removal of Cesium with Other Transition-Metal Ferrocyanides

Scouting tests were carried out with copper, ferric iron, ferrous iron, manganese, and zinc ferrocyanides. Copper ferrocyanide (KCuFC) is available in limited quantities in France and has been studied in England. The material used in the tests was prepared according to the Savannah River method for KCoFC.¹⁵ The solid was dried at 75°C, crushed, and screened; a 100-200 mesh size fraction was used at a dosage of 333 ppm. The results (Table 8) show that this sorbent is comparable, or perhaps somewhat superior, to KCoFC at pH 9 (see Table 6) but loses its effectiveness at pH 11 or greater much more rapidly than does KCoFC. In an identical experiment, carried out for comparison, NaNiFC slurry was used at 100 ppm (Table 8). The results show that granular KCuFC is useful at pH < 11 but is not as effective as nickel or cobalt ferrocyanide slurries; at higher pHs, it is not as effective as granular KCoFC.

Several preparations of the zinc compound were tested, both as a slurry and as a dried solid prepared with a range of stoichiometric ratios. All forms were relatively ineffective with the W-29 simulant solution, yielding K_d values generally less than 1000 (10% cesium removal with 100 ppm sorbent). Since the material had been reported to be useful, some further tests were carried out. With normal tap water at pH 6.8, zinc ferrocyanide gave K_d values of about 2×10^5 ; with 1 M NaNO₃ at pH 8.6, the K_d was about 1×10^4 . It is concluded that, although this sorbent is reasonably effective in water or low-salt concentrations, it is not nearly as selective for cesium over sodium in high-salt solutions as are some of the other sorbents. Therefore, it was not studied further.

One set of tests was performed with manganous ferrocyanide slurry prepared in the same way as NaNiFC, using tap water and 3 M NaNO₃ at pH 7 to 8. With tap water, it was quite effective over short times (hours), with $K_d = 1.5 \times 10^6$; however, the K_d decreased with time and was only 5.6×10^4 after 14 d. With the 3 M NaNO₃ it was relatively ineffective at all times, decreasing from 1.5×10^4 after 12 min to 1.2×10^2 after 14 d. This material is an inferior sorbent for cesium from high salt solutions, and it was not investigated further.

One set of tests was made with potassium ferric ferrocyanide (Prussian blue) prepared by a slow crystal growth method. This compound normally has very small particles or is colloidal, but the slow crystal growth method yielded solids that could be handled. This sorbent was reasonably effective in tap water, giving K_d values of nearly 1×10^6 and 2×10^5 at pH 8 and 10, respectively. However, it was inferior to other sorbents in the W-29

Table 8. Cesium distribution coefficients with granular KCuFC (100-200 mesh, 333 ppm) and NaNiFC slurry

Time	Granular KCuFC at pH of			NaNiFC Slurry at pH of:		
	9	11	12	9	11	12
1 h	3.2E4	4.0E3	~0	8.6E4	4.1E4	2.7E4
24 h	2.4E5	8.9E1	92	7.4E5	3.8E5	5.9E3
4 d	3.8E5	2.4E1	5	2.2E6	7.1E5	5.9E1
7 d	3.7E5	2.2E1	9	1.5E6	6.0E5	~0
14 d	3.9E5	2.5E1	23	1.6E6	1.1E5	~0

simulant, giving K_d values of 2×10^4 and ~ 0 at pH 7 and 11, respectively. It was not studied further.

An experiment was made with potassium ferrous ferrocyanide prepared by drying the precipitate at 75°C , crushing, and screening the product; the 100-200 mesh size fraction was used. The material was generally less satisfactory than other sorbents for cesium removal from W-29 simulant, giving K_d s in the range of 3×10^3 to 5×10^3 at pH 9 and $< 1 \times 10^3$ at pH 11. It was not studied further.

2.1.2.5 Removal of Cesium from Acid Solutions with Ferrocyanides

Scouting experiments were carried out to test the ability of ferrocyanides to remove cesium from acid solutions. A process utilizing such compounds would be useful for decontaminating acidic waste solutions at the source. The base solutions were acidified W-29 simulant solution (high salt concentration) and water. Each was adjusted by adding a quantity of HCl calculated to increase the acid concentrations to 1, 0.1, and 0.01 M. This adjustment was reasonably successful in the case of water as the final pHs were 0, 1, and 2.3 (these solutions would be representative of a condensate from an acid evaporator, for example); however, the W-29 simulant was more alkaline than expected, and the final pHs were 0, 7.6, and 7.9. The only useful new data from the salt solutions are those for 1 M acid in high-salt concentration, which is a nontypical composition for a waste solution.

The results (Table 9) show that, while 100-ppm quantities of both KCoFC and NaNiFC slurries are reasonably effective with the acidic water solutions, NaNiFC is superior. Decreasing the pH below 2 has a deleterious effect, but cesium removal is about as complete at pH 2.3 as it is at high pH levels. Thus, the ferrocyanides are equally useful in water over the pH range from 11 to 2, with a small decrease in effectiveness as the pH decreases to 0. With the acidified W-29 simulant, NaNiFC is clearly superior to KCoFC, with about 90% cesium removal (DF of 10) being attained with 100 ppm of sorbent. It is clear that cesium can be removed from acidified salt solutions, even up to 1 M acid, but cesium removal is more effective at higher pH levels.

Additional experiments were conducted to test the effectiveness of NaNiFC slurries at higher acidities (Table 10). With 1 M acid, cesium decontamination was somewhat less effective than that reported in Table 9. However, reasonably good cesium removal was obtained from both 1 M and 2 M HNO₃, with about 90% of the cesium being removed with 100 ppm sorbent. The use of NaNiFC for cesium decontamination of acid solutions, such as evaporator condensates and decontamination solutions, is suggested if it is not practical to increase the pH of the solution to improve the effectiveness of the sorbent.

2.1.3 Removal of Cesium from MVST Supernate Solutions with Inorganic Sorbents

Results of one experiment conducted with supernate solution from MVST W-29 were reported previously.² Only a single stage of separation was used in that test. Since a larger DF is required to meet specifications for some waste forms, particularly discharges to the environment, another experiment was conducted to determine whether the decontamination effectiveness continued through multiple stages. It is not uncommon for a large DF to be achieved in the first treatment, leaving a small fraction of the activity that is much more difficult to remove, presumably because it is a different chemical species.

An experiment was conducted to test a batch processing flowsheet using three successive stages. Such flowsheets are described in a separate report in preparation. The experiment was conducted with 1 L of supernate from MVST W-26. This solution was obtained from an earlier sample taken prior to some recent solution transfers between the MVST tanks so there are no detailed composition data. The experimental results are summarized in Table 11.

Table 9. Cesium distribution coefficients for acidified solutions with 100 ppm ferrocyanides

Solution ^a	pH	Sorbent	Time			
			1 h	1 d	14 d	14 d ^b
Water	0	KCoFC	2.0E5	2.3E5	2.4E5	5.2E5
Water	1.0	KCoFC	5.6E5	5.1E5	6.1E5	1.4E6
Water	2.3	KCoFC	3.3E6	1.4E6	1.1E6	3.8E6
Water	0	NaNiFC	4.1E5	6.3E5	1.1E6	4.7E6
Water	1.0	NaNiFC	3.3E5	7.7E5	1.5E6	3.4E6
Water	2.3	NaNiFC	2.7E6	6.8E5	1.3E6	2.7E6
Sim ^c	0	KCoFC	6.7E3	5.7E3	4.8E3	5.5E3
Sim	7.6	KCoFC	2.9E5	4.0E5	4.0E5	2.2E6
Sim	7.9	KCoFC	5.6E5	1.3E6	1.9E6	1.7E7
Sim	0	NaNiFC	7.5E3	3.6E4	1.4E5	1.6E5
Sim	7.6	NaNiFC	2.4E5	4.9E5	1.5E6	3.3E6
Sim	7.9	NaNiFC	3.1E5	9.4E5	9.0E5	8.3E5

^aSolution is either water or MVST W-29 simulant plus HCl to adjust pH and a ¹³⁷Cs spike from MVST W-29.

^bSample filtered before counting.

^cSim = simulant.

In the first separation stage, 1 L of the solution was adjusted to pH ~10.5, NaNiFC slurry was added to 104 ppm, and NaT was added to 200 ppm. The slurry was mixed for 4 h and allowed to settle for 20 h. Most of the supernate, which appeared to be clear, was decanted from the solids by vacuum transfer. At this point, the DF was ~18. Centrifugation and filtration (0.2- μ m pore size) gave DFs of 104 and 108. Settling for longer times gave DFs that increased from ~18 to 32 after 36 h and 113 after 68 h. In all cases, DFs in the range 104 to 114 were attained with good clarification (filtration, centrifugation, or settling for a few days); therefore, the supernate decanted after settling 20 h contained about 1% of the cesium in solution and about 4.5% of the cesium associated with suspended solids.

A 250-mL portion of this supernate (sample A2, DF ~18) was then treated with 104 ppm NaNiFC (second contact), and the DF in the second stage increased from 110 after 9 min to 234 after 1 h and 490 after 20 h. The combined DF (both stages) was 2000 after

Table 10. Cesium removal from acid solutions with 100 ppm NaNiFC at 4-d contact time

Solution	HNO ₃ (M)	Sample ^a	% Removed	K _d
Water	1.0	cent	87.7	4.3E4
		cent/cent	88.1	4.5E4
		cent/filt	88.5	4.66E4
Water	2.0	cent	87.7	4.3E4
		cent/cent	89.8	5.4E4
		cent/filt	90.7	5.9E4
Simulant	1.0	cent	83.1	3.0E4
		cent/cent	83.8	3.1E4
		cent/filt	83.4	3.1E4
Simulant	2.0	cent	77.3	2.1E4
		cent/cent	78.2	2.2E4
Simulant	4.0	cent	63.0	1.03E4
		cent/cent	64.4	1.1E4
		cent/filt	64.9	1.1E4

^acent = sample centrifuged once; cent/cent = centrifuged twice; cent/filt = centrifuged and then filtered.

9 min and 9000 after 1 d (filtered samples). A third separation stage reduced the cesium activity to the limit of detection with the counting system available, with an overall DF of $>1.9 \times 10^5$ for the three cycles of decontamination.

This experiment confirms that cesium is present in exchangeable forms so that each of the successive stages of separation yields about the same DF, at least until nearly all the cesium has been removed. Such results clearly demonstrate that cesium can be reduced to a very low level, in the vicinity of permissible discharge limits. The primary uncertainty in extrapolating from this scale to a process level lies in the extended time (several days) that took place between the first and second batch contacts. Bench-scale testing on a more realistic schedule will be required to verify the process applicability. Similar data were not obtained for ⁹⁰Sr because of budget limitations.

Table 11. Test of three-stage batch separation of ^{137}Cs from W-26 supernate

Solution	^{137}Cs (Bq/mL)	Cs DF ^a cycle	Total DF ^a	Notes
Feed	1.89E5	---		
<u>First Extraction:</u> Add 104 ppm NaNiFC + 200 ppm NaT; mix 4 h; let settle.				
A1	1.10E4	17	-	First 250 mL decanted after 20 h
A2	1.03E4	18	-	Second 250 mL decanted after 20 h
B2	5.85E3	32	-	A2 after settling additional 16 h
C2	1.81E3	104	-	Same as B2 plus centrifuged
F2	1.75E3	108	-	Same as B2 plus filtered
B3	1.68E3	113	-	A2 after settling additional 2 d
B4	1.66E3	114	-	Duplicate of B3
<u>Second Extraction:</u> Add 104 ppm NaNiFC + 200 ppm NaT to A2; mix.				
2F1	94	110	2010	Filtered sample after mixing 9 min
2F2	76	135	2490	Filtered sample after mixing 14 min
2F3	58	178	3260	Filtered sample after mixing 30 min
2F4	44	234	4300	Filtered sample after mixing 60 min
2F5	21	490	9000	Filtered sample after 20 h
<u>Third Extraction:</u> Add 104 ppm NaNiFC to 2F5; mix.				
3F1	0	-	-	Filtered sample after mixing 2 min
3F2	3	-	-	Filtered sample after mixing 8 min
3F3	0	-	-	Filtered sample after mixing 30 min
3F4	1	-	-	Filtered sample after mixing 60 min
Average	1	21	1.9E5	

^aDF includes dilution factor of about 1.03 each cycle.

2.1.4 Removal of Strontium from Simulant Solutions with Inorganic Sorbents

Several inorganic sorbents have been examined in screening tests with the W-29 simulant solution containing ^{85}Sr tracer and a small amount of actual W-29 supernate for a ^{137}Cs spike. The data are summarized in Table 12. All materials removed strontium much more effectively at pH 13 than at lower pH levels, and all but the Sandia sodium titanate¹⁸ (NaT) and titanium phosphate were relatively ineffective at pH <11, which is the upper limit for long-term stability of ferrocyanides that might be used for cesium removal. At the higher pHs, NaT is clearly superior to all other materials tested. In a batch contact, 454 ppm removed 99% of the strontium at pH 13 and about 90% at pH 11, values that are in the range of practical application. This preparation had been formed into pellets and then ground to produce a granular product; it is anticipated that the original NaT, which was not heat-treated to form pellets, will have a larger K_d , and some of this material has recently been acquired for further testing.

A number of gel-derived microsphere preparations made by an internal gelation process were supplied by J. L. Collins, of ORNL. At lower pHs (10 and below), the titanium phosphate preparations were nearly as effective as NaT, although they were inferior at high pH levels. Some of the gel-derived microsphere preparations were much better materials to work with because of the absence of fine powders, although some preparations tended to degrade during mixing. All showed much slower rates of sorption, as would be expected because of the small surface area. The data in Table 12 are for 24-h mixing time; K_d s were observed to increase significantly over longer time intervals, up to >15 d in some cases. Such long times are not practical for most process applications. At a pH of 10 or less, the TiP exchangers are comparable to NaT, and it is likely that an improved form could be synthesized. Accordingly, these results are sufficiently promising that additional work would be worthwhile to attempt to prepare microspheres with better exchange characteristics by varying the porosity and crystallinity.

None of these sorbents showed any significant removal of cesium under any conditions.

Table 12. Strontium removal from W-29 simulant with inorganic sorbents

Sorbent type ^a	Sorbent (ppm)	pH 10		pH 11		pH 12		pH 13	
		K_d^b	% ^c	K_d^b	% ^c	K_d^b	% ^c	K_d^b	% ^c
NaT	454	7.6E3	78	2.1E4	91	3.7E4	94	1.9E5	99
TiO ₂	1820	6.0E1	10	1.1E2	17	6.4E2	54	2.9E3	84
SG-TiO ₂	~ 300			1.1E3	30			1.5E3	37
SG-NaT-B	~ 300			1.8E3	41			2.1E3	44
SG-NaT-C	~ 300			1.7E3	39			2.1E3	45
SG-ZrP	~ 300	1.3E2	4					1.7E4	85
SG-TiP-A	~ 300	4.1E3	58					2.2E4	88
SG-TiP-B	~ 300	5.5E3	65					1.9E4	86

^aNaT is granular sodium titanate made from the Sandia preparation; TiO₂ is reagent-grade titania (Fisher); SG codes are gel-derived microsphere preparations made by the internal gelation process of the following: TiO₂ is hydrous titanium oxide; NaT-B and NaT-C are hydrous titanium oxides treated with NaOH; ZrP is hydrous zirconium oxide treated with phosphoric acid; and TiP-A and TiP-B are hydrous titanium oxide treated with phosphoric acid.

^bValues after 24 h of mixing; K_d increased with longer times.

^c% refers to the percentage of ⁸⁵Sr activity removed from solution after 24 h.

2.2 SIMULANT DECONTAMINATION WITH ORGANIC ION-EXCHANGE RESINS

Organic ion-exchange resins have been used for removing various radioactive contaminants from low- and high-level radioactive liquid waste streams in the nuclear power industry for many years; they are especially effective in column configurations for the removal of trace amounts of specific constituents. In this study, organic ion-exchange resins, including a resorcinol-based resin developed and provided by the Savannah River Site¹² (designated SRS resin) and Duolite CS-100 phenol-based resin, were tested for their ability to remove ¹³⁷Cs and ⁸⁵Sr from MVST simulant solutions. The MVST solutions are >4 M in sodium and 0.25 to 1 M in potassium, which present problems in removing the small quantities of cesium and strontium (10⁻⁴ to 10⁻⁷ M) from solution.

The previous reports^{13,14} have included results from both batch distribution coefficient measurements and small ion-exchange column tests, using the resorcinol-based resin developed at the Savannah River Site and the Duolite CS-100. Since these resins were relatively ineffective for strontium removal, several other organic ion-exchange resins reported to be effective for strontium removal were tested.

2.2.1 Experimental Methods

The data obtained for organic ion-exchange resins resulted from both batch contacts of the sorbent with the appropriate solution and small, continuous ion-exchange column tests. In most cases, the simulant solution was as described in Sect. 2.1.1, based on analysis of MVST W-29. The solution was spiked with cesium using a small amount of actual W-29 supernate (^{137}Cs predominant) and with strontium using ^{85}Sr tracer. Solutions were adjusted to the specified pH prior to the test and usually checked afterward; in most cases, changes resulting from the ion-exchange contacts were small. Orion Research Model 811 pH meters were used.

Batch contacts of sorbent and solution took place in centrifuge cones using a "Roto-Torque" rotating mixer. The rotational speed and the tilt angle were adjusted by experiment to give good mixing even with fairly large sorbent particles. After mixing for predetermined times had been completed, the cones were removed and the resin was allowed to settle prior to sampling. Samples of the clarified supernate (usually 2 mL) were removed with a pipetter and transferred to sample vials for counting. During batch tests when successive samples were removed from the same centrifuge cone, the values of C_0 and V were recalculated after each sample was withdrawn, taking into account the measured concentration and volume of the sample. The samples were counted using a NaI well counter with a LBK Wallack Compugamma analysis system. Although only relative counts are used in this work, the counters were calibrated against counting standards.

Column experiments were conducted in a 1-cm-diam, 50-mL-capacity burette with a porous glass frit at the bottom to support the resins tested. Volumes of 3 to 5 mL of resin were used, and flow rates through the bed were controlled by a Cole-Parmer tubing pump at 0.25 to 1.25 mL/min, depending on the test. Fractions of the column throughput were collected using a fraction collector holding twenty-five 75-mL-capacity tubes. Two-milliliter samples were removed from the tubes for determination of the ^{137}Cs and ^{85}Sr activities that had come through the column. When the eluent activity had reached at least 50% of the feed concentration, the run was terminated and the resin was eluted with 2 or 4 M formic acid, 1 or 2 M HCl, or 0.5 M HNO_3 .

As described in Sect. 2.1.1, the results of the experiments can be expressed by several different parameters that relate to the decontamination effectiveness. For resin batch experiments, the distribution coefficient, K_d [Eq. (1)] is used based on the dry mass of the resin. Dry samples of the resins were obtained by washing the resins twice with ten resin

volumes of 2 M formic acid, twice with ten resin volumes of distilled water, five times with six resin volumes of 0.25 M NaOH, and then three times with ten resin volumes of distilled water. After being washed, the resins were air dried overnight on blotter paper. When the data obtained using the ion-exchange columns were analyzed, the distribution coefficient was based on the volume of resin present in the column:¹⁹

$$K_d^v = (C_o - C)V/CV_{\text{resin}} = K_d\rho, \quad (4)$$

where ρ is the tap density of the wet resin bed (g dry resin/mL resin bed) and V_{resin} is the wet-volume resin used in the column. The values of K_d^v were obtained from the breakthrough curves plotted on a probability-log graph of C/C_o vs the column throughput in resin volumes. The maximum capacity of the resin for the ion of interest is related to the resin volumes of feed passed through the column when ~50% C/C_o occurs and is approximately the K_d^v . The slope of the breakthrough curve is related to the ion-exchange kinetics of the resin.

2.2.2 Cesium and Strontium Removal with Chelating Resins

Several chelating resins were acquired for testing since they are expected to be particularly effective for the removal of polyvalent metals such as ^{90}Sr , as well as rare earths and actinides. These have been tested extensively by measuring K_d s in batch experiments and, to a much more limited extent, in column tests. The chelating resins tested appear adequate for strontium removal tasks.

2.2.2.1 Batch Tests

Several organic chelating ion-exchange resins have been obtained for study to remove ^{90}Sr from various waste solutions. They include Amberlite[®] IRC-718 (Rohm & Haas), Ionac[®] SR-5 (Sybron Chemicals, Inc.), and Lewatit[®] TP 207 and TP 208 (Bayer AG); all were -16+50 mesh. These four, plus the SRS and Duolite[®] CS-100 resins, were run in batch tests to determine the K_d s at a phase ratio of 150 (150 mL aqueous/1 g resin) using the standard W-29 simulant described in Sect. 2.1.1 and containing W-29 supernate and ^{85}Sr as tracers. Tests were conducted on undiluted simulant, as well as solutions of 1 part simulant plus 1 part water and 1 part simulant plus 3 parts water. The K_d s for ^{85}Sr removal using IRC-718, SR-5, TP-207, and TP-208 are shown in Table 13. With simulant solutions and dilutions that contained 4.58, 2.29, and 1.145 M sodium, 0.25, 0.125, and 0.0625 M

Table 13. Batch Sr and Cs K_d s with simulant (Na = 4.58 M, K = 0.25 M, pH = 12.9, 150 L/kg resin)

Resin	Dil.	1-h contact		24-h contact		48- to 72-h contact	
		K_d Sr	K_d Cs	K_d Sr	K_d Cs	K_d Sr	K_d Cs
IRC-718	0	940	0	5420	0	6110	0
	1:1	1990	0	11315	0	11300	0
	1:3	4300	0	23070	0	23480	0
SR-5	0	350	0	1760	0	2050	0
	1:1	890	0	4690	0	5075	0
	1:3	1780	0	12900	0	13830	0
TP-207	0	690	0	5415	0	10050	0
	1:1	910	0	13600	0	21080	0
	1:3	3250	0	31780	0	29170	0
TP-208	0	390	0	3890	0	6480	0
	1:1	1280	0	15900	0	17240	0
	1:3	4100	0	33550	0	25890	0
CS-100	0	95	35	563	100	270	55
	1:1	170	210	260	65	590	104
	1:3	500	120	1600	195	1720	190
SRS*	0	155	330	180	1120	190	1130
	1:1	340	930	390	2370	410	2140
	1:3	930	2350	1070	5290	1170	4490

*80-100 mesh.

potassium, and had pHs of 12.9, 12.7, and 12.5, TP-207 resin was slightly superior at long contact times (48 h); however, IRC-718 was slightly superior at short contact times (1 h).

The five resins, SRS, IRC-718, TP-207, TP-208, and SR-5, were also tested with the simulant solution at pH 12.7 and a phase ratio of ≈ 1500 (10 mg resin to 15 mL liquid) to determine whether some ion present at low concentration might interfere by loading in preference to the cesium or strontium. The results are shown in Table 14. The K_d s for strontium after a 72-h contact at pH 12.7 were 2900 for TP-207, 2500 for TP-208, 3600 for IRC-718, 1440 for SR-5, and 235 for SRS.

The same resins and feed materials were also tested at a phase ratio of 1500:1 at pH 12.3, 10.7, and 10.3 (Table 14). The highest and lowest K_d s occurred at pH 10.7 and 12.3, respectively, and the values varied between 1850 and 930 for SR-5, 4570 and 1100 for

Table 14. Batch strontium and cesium K_d data for chelating and SRS resins
(phase ratio: 1500 L liquid/kg resin)

Resin	Conditions			K_d s for Sr at contact times of:			K_d s for Cs at contact times of:		
	pH	Na(M)	K(M)	1 h	24 h	48 h	1 h	24 h	48 h
TP-207	12.7	4.58	0.25	241	1695	2922	29	1	0
TP-208				285	1702	2508	0	0	0
IRC-718				456	2268	3594	2	0	0
SR-5				246	1105	1440	0	3	0
SRS				147	204	235	237	665	522
TP-207	12.3	4.58	0.25	185	1068	1654	0	0	0
TP-208				192	1354	2238	0	0	0
IRC-718				324	1145	1098	0	0	0
SR-5				175	775	936	0	0	0
SRS				124	136	179	226	699	593
TP-207	10.68	4.58	0.25	231	3885	8064	0	0	0
TP-208				283	3837	6866	0	0	0
IRC-718				325	3210	4570	0	0	0
SR-5				194	1368	1846	0	0	0
SRS				38	37	51	199	565	388
TP-207	10.26	4.58	0.25	218	2691	5492	23	0	14
TP-208				219	2520	4470	21	4	3
IRC-718				382	2962	3777	14	0	0
SR-5				212	1277	1705	28	2	17
SRS				60	54	56	224	557	358

IRC-718, 8060 and 1650 for TP-207, and 6860 and 2240 for TP-208; however, the K_d increased above pH 12.3 and decreased below pH 10.7. For SRS resin, the strontium K_d decreased from 180 at pH 12.3 to 50 at pH 10.3. Both types of resins appear to be effective over a fairly wide pH range for the MVST supernate simulant. In addition to these results, samples taken at 1 h and 24 h of batch mixing for all pH levels indicate that significant time (>24 h) is required for equilibrium to be reached. Data for 24 and 72 h indicate that the exchange is slower at the lower pHs.

The removal of cesium was essentially zero for each of the four chelating resins under all conditions. In contrast, the SRS resin and CS-100 were effective for cesium removal. With the phase ratio of 150, cesium K_d s were 1130 and 55 with the SRS and CS-100 resins,

respectively. At a phase ratio of 1500, the cesium K_d for the SRS resin decreased from about 590 to 360 as the pH was decreased from 12.3 to 10.3 (Table 14), and the K_d observed after 24 h was larger than that after 72 h.

2.2.2.2 Simultaneous Cesium and Strontium Removal with Mixed-Resin Column

Both the chelating resin, Amberlite IRC-718, and the SRS resin were effective in simultaneous removal of both cesium and strontium in a mixed-resin bed column test. A column test with 2.0 mL of IRC-718 and 2.6 mL of SRS 80-100 mesh resin (dry volume, corresponding to about 0.72 and 2.17 g, respectively) in a mixed bed with W-29 simulant containing ^{85}Sr and MVST supernate for strontium and cesium tracing was operated for about 372 column volumes (CV) (based on the total wet resin volume of 7 mL). The breakthrough curves are shown in Fig. 1. Both strontium and cesium exceeded 50% breakthrough at the end of the run. Fifty percent breakthrough occurred at about 240 CV for cesium and at about 350 CV for strontium. The column residence time was about 15 min, which is one-half to one-fourth of the residence time required for a sharp, more vertical breakthrough curve. The results show that a slightly smaller fraction of the chelating resin would be needed to allow the more nearly simultaneous breakthrough of both cesium and strontium. The combination of the two resins does, indeed, remove both cesium and strontium, and column capacities are acceptable on an operational basis. The K_d s calculated from the breakthrough curves compare favorably with those measured in batch tests for both strontium with IRC-718 and cesium with SRS resin.

The elution of the resin used in the column run was completed, and the resin showed very little remaining activity. Less than 1% of the strontium and cesium activity was left on the resin, and a mass balance showed a recovery of 97.3% of the cesium activity and 99.85% of the strontium activity that had loaded. A total of 19 resin volumes of 2 M formic acid was used. The elution was performed very slowly with a flow rate of about one resin volume per day. Previous resin elutions were conducted much faster (1 resin volume per 5- to 15-min period) and resulted in the incomplete recovery of activity.¹³

2.2.3 Source Treatment Studies of Aluminum Decladding Solutions

There is increasing interest in treating certain highly active wastes at their source rather than mixing them with a very much larger volume of low-activity waste containing large amounts of salts. One important waste is generated by dissolution of the aluminum

Fig. 1. Breakthrough curves for mixed IRC-718 plus SRS resin column.

associated with aluminum-clad actinide oxide cermet irradiation targets at the Radiochemical Engineering Development Center (REDC). The caustic solution contains large amounts of aluminum and ^{137}Cs activity, plus some ^{90}Sr , but almost no actinides. The waste is expected to contain the composition shown in Table 15. Removal of cesium and strontium from this waste would substantially decrease the cesium input into the LLLW system anticipated over the next few years.

Batch equilibrium measurements of distribution coefficients with NaT, KCoFC, and the SRS resin were conducted on the REDC waste stream simulant. Synthetic solutions without the radioactive components were traced with W-29 supernate for ^{137}Cs and ^{85}Sr for analysis by gamma counting. Solutions at full strength, diluted two parts solution to one part water, one part solution to one part water, one part solution to two parts water, and one part solution to three parts water (1.055, 0.703, 0.528, 0.352, and 0.264 M sodium aluminate, respectively) were prepared. Because of the effect of pH on aluminum solubility, concentrated nitric acid was added to adjust the pH of these solutions, in intervals of 0.2 pH unit, to values calculated to be between 14.1 and 13.1. The measured pH range was 13.7 to 12.8.

Results of these tests are shown in Table 16 for the inorganic ion exchangers. Two of the solutions, at zero and 1:1 dilution, were tested for strontium removal by adding about 700 ppm of sodium titanate exchanger at the calculated pHs of 14.11 and 13.81. All five dilutions, at a calculated pH of 13.1, were tested for the removal of both cesium and strontium by adding a combination of 700 ppm sodium titanate and 500 to 600 ppm of KCoFC prepared according to the Savannah River method, dried at 100°F, and sized to 100-230 mesh. Results at all conditions and times showed promising decontaminations. After 72 h, the KCoFC still retained the ^{137}Cs that had been picked up at shorter mixing times, even though the pH was about 13. The heat-treated KCoFC was stable in pH 13 REDC-simulated waste solution for at least 3 d.

The five dilutions were tested with two particle sizes of the SRS resin, 60-80 mesh and 120-140 mesh, to determine whether particle size had any effect on the strontium and cesium uptakes. Results at 72 h mixing time are shown in Table 17. The results for cesium removal show that (1) the larger-size resin was more effective, by an order of magnitude, than the smaller size; and (2) there was no large change in the ratio with dilution, although the K_d for the larger-size particles tended to increase as the dilution increased while the K_d for the smaller-size particles was almost constant with dilution, even showing a slight

Table 15. Expected composition of aluminum target dissolution waste

Species	Concentration
	<u>M</u>
NaAlO ₂	1.054
NaOH	1.298
NaNO ₃	0.469

pH	14.1
	<u>Ci/L</u>
¹³⁴ Cs	2.9
¹³⁷ Cs	6.7
⁹⁰ Sr	0.11
¹²⁵ Sb	0.12
¹⁰⁶ Ru	0.009

decrease at the highest dilution. In contrast, strontium removal was very similar with the two resin sizes and K_d showed a uniform increase with dilution. The behavior of strontium was expected, but that of cesium was not. No reason is known for the effect of particle size on cesium distribution.

The 60-80 mesh SRS resin was also tested at other pH levels with each dilution for cesium and strontium removal; the results are shown in Table 18. In the zero-dilution, lowest-pH case, a white precipitate (probably an aluminum compound) formed after a few hours and may have interfered slightly with the removal of cesium. This test condition was not rerun. All the strontium was essentially removed in this one test, but in no other, so the precipitation may have been responsible for the very large K_d for strontium. The resin removed almost all the cesium under all conditions, and increasingly more strontium as the dilution increased. As the pH decreased, with each dilution, there was a decrease in K_d for cesium and an increase in the strontium K_d . The MVST simulant was not tested in this high-pH range, so comparisons between the results on the two different streams are not meaningful. It should be noted that these K_d values are large enough to make a batch process practical. The batch approach could be advantageous because of the difficulty with column operations, resulting from possible precipitation of aluminum during processing.

Table 16. Cesium and strontium removal from caustic aluminate solution with inorganic sorbents

Exchanger ^a	Contact time (h)	Al/OH/NO ₃ (M)	pH		Sr K _d	Cs K _d	Sr Rem. (%)	Cs Rem. (%)
			Value	Condition ^b				
NaTi-0	I	1.055	14.11	C				
	1	1.298	13.71	B	8650	32	85.09	2.05
	24	0.469	13.69	E	110961	20	98.70	1.10
	72				104565	15	98.61	0.55
TiFC-0	I	0.982	13.09	C				
	1	0.122	13.00	B	8317	12474	78.22	85.64
	24	1.523	12.97	E	39372	36627	94.60	94.67
	72				67083	34153	96.78	94.30
TiFC-2:1	I	0.672	13.09	C				
	1	0.124	13.01	B	26958	36317	92.73	94.51
	24	1.002	12.96	E	214881	89140	99.03	97.69
	72				327316	64187	99.37	96.83
NaTi-1:1	I	0.528	13.81	C				
	1	0.649	13.57	B	11973	23	89.47	1.60
	24	0.235	13.50	E	108884	31	98.75	2.25
	72				96761	38	98.60	3.07
TiFC-1:1	I	0.511	13.10	C				
	1	0.124	13.00	B	33825	31064	95.21	94.80
	24	0.731	12.96	E	169589	78141	99.01	97.88
	72				263839	67093	99.37	97.53
TiFC-1:2	I	0.345	13.10	C				
	1	0.127	12.99	B	37908	33249	94.67	93.99
	24	0.451	12.97	E	204746	120784	98.97	98.28
	72				219437	96335	99.04	97.85
TiFC-1:3	I	0.261	13.10	C				
	1	0.128	13.01	B	20372	20218	91.97	91.91
	24	0.308	13.02	E	112871	114918	98.47	98.48
	72				154491	120919	98.88	98.56

^a NaTi-0, 1:1 are 700 ppm sodium titanate at zero and 1:1 test solution dilution with water, respectively. TiFC-0, 2:1, 1:1, 1:2, and 1:3 are 700 ppm sodium titanate and 500 to 600 ppm potassium cobalt ferrocyanide at zero, 2:1, 1:1, 1:2, and 1:3 dilutions of test solution with water, respectively.

^b C, B, and E are the initial calculated pH, initial measured pH, and the measured ending pH, respectively.

Table 17. Comparison of 60-80 mesh with 120-140 mesh SRS resin using simulated aluminate waste (72-h contact)

Resin size (mesh)	Phase ratio ($\mu\text{L}:\text{mg}$)	Dilution	Calc. pH	$\text{AlO}_2^- / \text{OH}^- / \text{NO}_3^-$ (mol/L)	Counts/min		Sr K_d	Cs K_d	Sr Rem. (%)	Cs Rem. (%)
					Sr	Cs				
				Feed	-6000	-4500				
60-80	170	0	14.11	1.055	1673	16	375	37854	72.44	99.63
				1.298						
120-140	169	0		0.469	1410	192	470	3163	76.53	95.76
60-80	173	2:1	13.94	0.703	1126	15	605	43322	80.55	99.67
				0.865						
120-140	175	2:1		0.313	1100	198	683	3161	82.00	95.60
60-80	176	1:1	13.81	0.528	873	10	882	66872	85.59	99.78
				0.649						
120-140	169	1:1		0.235	869	190	870	3221	85.64	95.79
60-80	173	1:2	13.64	0.352	592	14	1340	45374	90.16	99.68
				0.433						
120-140	171	1:2		0.156	636	206	1246	3012	89.49	95.46
60-80	170	1:3	13.51	0.264	442	7	1835	89655	92.74	99.84
				0.325						
120-140	173	1:3		0.117	532	244	1524	2749	91.17	94.98

Table 18. Removal of cesium and strontium from simulated aluminate waste using 60-80 mesh particle size SRS resin (72-h contact)

Dilution	Phase ratio ($\mu\text{L}:\text{mg}$)	Calc. pH	AlO_2^- (mol/L)	Counts/min		Sr K_d	Cs K_d	Sr Rem. (%)	Cs Rem. (%)
				Sr	Cs				
	Feed			≈ 6000	≈ 4500				
0	170	14.11	1.055	1673	16	375	37854	72.44	99.63
	179	13.90	1.024	1425	19	467	35070	75.68	99.57
	179	13.67	1.005	1255	17	530	36922	77.98	99.60
	185	13.48	0.993	1183	25	574	25779	78.91	99.41
	188	13.28	0.987	1223	25	555	25445	78.09	99.40
	183	13.09	0.982	2 ^a	31	442087 ^a	19062	99.96	99.22
2:1	173	13.94	0.703	1126	15	605	43322	80.55	99.67
	176	13.70	0.688	954	14	766	45647	83.79	99.68
	179	13.50	0.680	827	21	887	30568	85.54	99.52
	181	13.29	0.675	786	27	925	23517	86.07	99.36
	179	13.09	0.672	810	17	892	36904	85.75	99.60
1:1	176	13.81	0.528	873	10	882	66872	85.59	99.78
	173	13.71	0.523	749	12	1025	57365	87.52	99.75
	176	13.50	0.517	665	14	1170	47211	88.80	99.69
	181	13.30	0.513	612	13	1290	49934	89.51	99.71
	180	13.10	0.511	659	19	1160	35028	88.52	99.58
1:2	173	13.64	0.352	592	14	1340	45374	90.16	99.68
	175	13.51	0.349	512	12	1561	53975	91.36	99.73
	176	13.30	0.347	443	17	1856	38676	92.62	99.62
	177	13.10	0.345	461	17	1749	39364	92.15	99.63
1:3	170	13.51	0.264	442	7	1835	89655	92.74	99.84
	172	13.31	0.262	375	11	2203	58052	93.85	99.76
	174	13.11	0.261	368	35	2234	19171	93.85	99.25

^a White precipitate formed.

2.3 CROSS-FLOW FILTRATION TESTS

Membrane separation technologies are used in the nuclear waste industry because they lend themselves to continuous processing, modular design, low energy use, and low maintenance requirements; in addition, they have broad applicability for a wide range of pollution control problems.²⁰ Cross-flow or tangential flow filtration allows for continuous processing because the bulk solution flows over and parallel to the membrane surface. System pressure forces part of the liquid through the membrane, and turbulence minimizes the accumulation of particulate matter on the membrane surface. Three classifications of cross-flow filtration membranes are used, depending on the particle size of the materials rejected. Microfiltration removes particulates from 0.1 to 10 μm . Ultrafiltration separates material in the 0.001- to 0.1- μm range, and reverse osmosis separates materials less than 0.001 μm in size. Both microfiltration and ultrafiltration allow a high concentration of the solids in the retentate and the production of highly pure permeate. Cross-flow filters can be configured into plate-and-frame, spiral-wound, hollow-fiber, and tubular arrangements, depending on the flow requirements, solids content, required resistance to fouling, and necessary membrane surface area.

Some of the materials that possibly need to be removed from the MVST supernate may exist in colloidal form, and the ferrocyanides used for cesium removal have very small particle sizes. Settling and/or centrifugation was often not enough to remove all of the fine particulates from the treated supernate; however, filtration through submicron filters generally removed the materials and resulted in a much enhanced DF (Table 11). In order to ensure that insoluble TRU, strontium, and cobalt compounds are removed from the supernate, microfiltration or ultrafiltration may be required. Ultrafiltration has been successfully used in the United Kingdom for the cleanup of alkaline plutonium-containing effluents, improving significantly on sedimentation or centrifugation,²¹ and other European countries have used a method that combined ion exchange and/or chemical precipitation with ultrafiltration to obtain the needed removal efficiency.^{22,23} Ferrocyanide colloidal particles used for ^{137}Cs removal and formed in situ have been removed by ultrafiltration.²⁴ Based on earlier experimental results at ORNL^{25,26} (the W-29 supernate used in these tests contained up to 0.5 wt % solids, while our studies have dealt with solutions with essentially no settleable solids) and the literature cited above, our experimental program was initiated to study filtration requirements and filter properties with various ferrocyanide slurries in both simulant and actual MVST supernate.

2.3.1 Experimental Methods

A small, stirred-cell ultrafiltration unit was used to test the filtration rates, the particulate separation efficiencies, and the applicability of ultrafiltration to the MVST supernate. The unit was a Micro Filtration Systems model UHP43 glass-and-Teflon cell of 70-mL capacity and capable of taking 70-psi pressure. The filters were chosen on the basis of chemical resistance (stability to pH >13), and the molecular weight cutoff (MWCO) was derived from work at Harwell in the United Kingdom.²⁷ The membranes were 43-mm-diam polysulfone ultrafiltration membranes with a 20,000 MWCO, type UK (pore size, 0.01 μm). The membranes were prepared for use by, first, installing them in the cell and, then, washing them with deionized water before adding the material to be filtered. After use, each membrane was cleaned using various solvents and acidic or basic solutions, rinsed with deionized water, and stored in deionized water until the next application.

When radioactively traced W-29 simulant was used in the ultrafiltration unit, vacuum instead of applied pressure was used to drive the filtration to prevent the spread of radioactivity in the event of an accident. Preliminary measurements of the permeate rate with distilled water using 20 to 22 in. Hg vacuum showed a rate of 0.8 mL/min. Filtering untraced simulant resulted in a lower filtration rate (0.35 mL/min). Using 15-psig applied pressure to the filter and vacuum on the permeate side when filtering simulant resulted in a rate of 0.45 mL/min.

2.3.2 Experimental Results

To test the removal of loaded, particulate ion-exchange material from the supernate by ultrafiltration, the ultrafiltration cell and membrane were first tested on simulant. Two tests were performed using simulant with added sodium titanate and ferrocyanide slurries to determine filtration rates, filterability, and volume reductions.

In the first test, a 500-mL batch of W-29 simulant plus 300 ppm sodium titanate and 115 ppm Savannah River-method sodium nickel ferrocyanide slurry was filtered through the 20,000-MWCO ultrafiltration membrane. The filtration rate was constant at 27.5 mL/min throughout the test, using a vacuum of 20 to 22 in. Hg to supply the differential pressure. The final permeate volume was 510.2 mL, and 4.3 mL of concentrate remained in the cell for a volume reduction factor of 119.6 and a final concentration of 48,300 ppm, or about a 5% slurry. In the second test, an approximately 3.7% slurry of sodium nickel ferrocyanide was filtered on the ultrafiltration membrane with a 550-mm-Hg pressure differential. The

suspension consisted of 2 g of $\text{Na}_4\text{Fe}(\text{CN})_6 \cdot 10\text{H}_2\text{O}$ and 2.2 g $\text{Ni}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$ in 14 mL of water, plus 100 mL of W-29 simulant adjusted to pH 11. After mixing, the slurry had a pH of 9.75. It was filtered over a period of several days at a constant filtration rate of about 5 mL per hour. At the end of the test, about 9 mL of slurry was easily removed from the cell, and another 3.5 mL was removed from the walls and filter. This resulted in a volume reduction ratio of ≈ 9 and a solids concentration of ≈ 336 g/L, or 30%. The slurry was very thick and did not pour easily, but it appeared to be pumpable.

2.4 REMOVAL OF ^{60}Co FROM SUPERNATE

Additional tests were initiated to determine whether ^{60}Co could be removed from the supernate when results showed that, following the removal of ^{137}Cs , it would be the primary contributor to the gamma field remaining in the supernate. Cobalt can be present in different physical and chemical forms, including colloids and anionic and neutral complexes, as well as the more common cationic species.²⁸ A variety of ion-exchange and clarification methods were evaluated in scouting tests that were initiated just before the experimental program was interrupted.

2.4.1 Experimental Methods

The batch K_d test methods outlined in Sect. 2.1 for ion-exchange materials and the methods described in Sect. 2.3 for the UF cell and membranes were used in these tests.

2.4.2 Experimental Results

In the first set of experiments, ultrafiltration was used to remove particulate ^{60}Co . Ultrafiltration on a 20,000-MWCO membrane, at pH 8.5, of the MVST W-26 supernate as received after one cycle of ferrocyanide/sodium titanate decontamination, resulted in no removal (within experimental error) of ^{60}Co . The supernate was then adjusted to pH 13 and allowed to equilibrate. Approximately 5% of the supernate volume precipitated upon pH adjustment. The supernate was then filtered by ultrafiltration, again with no measurable decrease in ^{60}Co activity.

A number of inorganic sorbents and organic ion-exchange materials were also tested for removal of ^{60}Co from supernate solution from MVST W-26. Residual solutions that had been used for several tests of ^{137}Cs removal from the W-26 supernate were composited and analyzed. Cesium had been removed sufficiently, using nickel or cobalt ferrocyanide

treatment, that ^{60}Co was the dominant gamma activity (about 180 Bq/mL), and essentially no cobalt had been removed during these cesium-removal tests. This composite solution (pH ~10.2) was used to test a number of processes that might remove ^{60}Co . The following gave no useful cobalt removal ($\text{DF} < 1.25$):

- Addition of granular KCoFC at pH 10.2
- Addition of $\text{Co}(\text{NO}_3)_2$ at pH 10.2, and then $\text{Na}_4\text{Fe}(\text{CN})_6$, to precipitate NaCoFC in situ
- Addition of $\text{Co}(\text{NO}_3)_2$ at pH 12.8, and then $\text{Na}_4\text{Fe}(\text{CN})_6$, to precipitate NaCoFC in situ
- Adjustment of pH to ≈ 1 before addition of $\text{Co}(\text{NO}_3)_2$; adjustment to 7.8 before addition of $\text{Na}_4\text{Fe}(\text{CN})_6$
- Addition of $\text{Co}(\text{NO}_3)_2$ at pH 1, followed by pH adjustment to 10.2 or 12.8 to precipitate $\text{Co}(\text{OH})_2$
- Addition of sodium aluminate to precipitate aluminum hydroxide
- Addition of cobalt hexacyanocobaltate at pH 10.2
- Manox A (MnO_2 ; claimed to be a specific cobalt sorbent) at pH 10.2
- Addition of KCuFC at pH 10.2
- Addition of sodium titanate at pH 10.2
- Addition of $\text{Co}(\text{NO}_3)_2$ plus TRU-Clear (potassium ferrate, strong oxidant that precipitates as Fe_2O_3) at pH 10.2
- Addition of Chelex 100 at pH levels of 2.7, 10.2, and 12.8
- Addition of Lewatit 208 at pH levels of 2.7, 10.2, 12.8
- Adjustment of pH to ≈ 1 ; addition of Co and H_2O_2 to try to break complex; addition of Chelex 100
- Adjustment of pH to ≈ 1 ; addition of Co and H_2O_2 to try to break complex; addition of Lewatit 208
- Adjustment of pH to ≈ 1 ; addition of Co and H_2O_2 to try to break complex; addition of Dowex 1
- Adjustment of pH to ≈ 1 ; addition of Co and H_2O_2 to try to break complex; addition of Dowex 50

Most gave no measurable DF. A few gave small DFs (up to about 1.2); these include (1) the solutions adjusted to pH 1, suggesting that an acid digestion step might convert the residual cobalt to an exchangeable form; and (2) the cobalt ferrocyanides after many days of mixing, suggesting that a very slow exchange of cobalt might be occurring between the ^{60}Co in the supernate and cobalt in the solid exchanger.

In summary, the data show that cobalt is not filterable even with ultrafilters of porosity corresponding to 20,000 MWCO, is not exchangeable with stable cobalt carrier over the pH range from 1 to 12.8, and is not exchangeable on ion exchangers under conditions that remove normal cobalt from solution. These results suggest that the residual cobalt in the waste supernate solutions is in some nonequilibrium form, possibly an inner-sphere complex, that is not in reasonably rapid equilibrium with the "normal" species of bulk cobalt in solution under the same conditions.

2.5 NITRATE REMOVAL

Solid sodium nitrate is currently an acceptable solid waste form for WIPP, provided the waste meets other criteria and has a TRU composition. Thus, much of the nitrate might be incorporated in solid TRU waste that is scheduled for shipment to WIPP. However, there is more NaNO_3 than required for this purpose, so less waste for shipment to WIPP would be generated if the excess could be disposed of otherwise. In the case of liquid waste, the reduction in nitrate concentration required to meet the specification for direct discharge of the treated waste to the environment (10 ppm N) is nearly 1×10^5 for nitrate.² Accordingly, some consideration has been given to nitrate removal processes.

The logical options are nitrate destruction to relatively innocuous gaseous products or recovery of nitric acid for recycle. Since the quantity of nitrate present is large, nitric acid recovery would produce about 380 m^3 (100,000 gal) of 10 M HNO_3 . Even if it is highly decontaminated, it is not obvious that this much acid could be used effectively (via recycle) or stored conveniently for future use. The alternative is nitrate destruction to species, such as N_2 or possibly NH_3 , that could be discharged to the atmosphere. An attractive option is to decontaminate and recover nitric acid, neutralize it, and use it for fertilizer on-site, perhaps for the grass cover over burial grounds which are already contaminated. For scoping purposes, the total amount of nitrate would provide the nitrogen requirement for about 200 acres of grass for 10 years.

Electrolytic reduction has been investigated to a considerable extent over several decades, and there are plans to study it further in another program here. Therefore, electrolytic destruction has not been investigated. Destruction of nitrate by chemical reducing agents is commonly applied to acid wastes but is not effective with alkali-metal nitrates in neutral or alkaline solutions. Thermal denitration can be used with polyvalent metal nitrates; but, again, it is not practical with alkali-metal nitrates. Chemical and thermal denitration yield NO_x , which can be largely recovered as nitric acid in a fractionation column.

2.5.1 Experimental Methods

Three scouting tests were performed in which sulfuric acid was added to MVST W-29 waste simulant to a $\text{H}_2\text{SO}_4/\text{NO}_3^-$ mol ratio slightly above 0.5; a typical feed consisted of 300 mL of W-29 simulant mixed with 40 mL of concentrated H_2SO_4 . The concentrate was diluted with water to yield 500 mL. The solution was evaporated until the temperature reached the range 150 to 200°C, and the condensate was collected in successive fractions. All samples were titrated for acid, and the concentrate and some condensate samples were analyzed for chloride.

2.5.2 Experimental Results

Most of the nitrate was recovered as HNO_3 in the condensate, and the extent of recovery varied with the final (maximum) evaporation temperature. Nitrate left in the salt concentrate ranged from 20 to 1.3% of the total present, the lower value when an air flow was used to sweep vapors to the condenser and the final temperature was $\sim 200^\circ\text{C}$. It is expected that a higher nitrate removal would be achieved if a larger excess of sulfuric acid had been used. In any case, it is possible to recover nitrate in this way.

Two potential problems were encountered in the practical application of this process. One was the formation of solids in the evaporator, primarily because alkali-metal sulfates are less soluble than the corresponding nitrates. In spite of the solids, no difficulty was experienced during evaporation even when almost no liquid phase was left. After partial cooling, the addition of water completely dissolved the solid residue, yielding an alkali-metal sulfate salt solution containing the residual nitrate. In the past, sulfate solutions have had much higher release limits than nitrate solutions. If not released, the solution could be treated, for example with lime, to produce NaOH solution for reuse.

The second problem resulted from the presence of chloride in the MVST simulant solutions at a concentration near 0.1 M. The chloride evaporated with the water and nitric acid, and the chloride concentration of the condensate decreased slowly as the evaporation proceeded. Essentially all the chloride ended up in the acid product. Chloride could cause a corrosion problem in the evaporator, although, with the small size required, a quartz evaporator could readily be used. Chloride is undesirable in the nitric acid product that would presumably be used for plant operations; however, proven removal methods are available.

3. SUMMARY

The experimental program being conducted to investigate potential separation methods for application to specific problems relating to the management of LLLW at ORNL has been described. Measurements are reported for cesium and strontium removal from simulated high-salt waste compositions, using both inorganic ion-exchange sorbents and organic ion-exchange resins, and for one experiment with actual LLLW supernate solution from Melton Valley Storage Tank W-26, using inorganic sorbents. The purpose of the study was to acquire an extensive data base to support the development of flowsheets for decontamination of the LLLW generated at ORNL.

Experimental measurements with inorganic ion exchange have centered on batch separations of cesium using transition-metal hexacyanoferrate(II) compositions and of strontium using titanium oxide-based sorbents. Cesium distribution coefficients in the range of 1×10^6 were generally observed with nickel and cobalt ferrocyanides at pH values ≤ 11 , yielding DFs of about 100 with 100 ppm of sorbent in a single-stage batch separation. Ferrocyanides are stable in acid solutions and remain reasonably effective as the pH decreases into the acid concentration range of at least 1 to 2 M. Strontium distribution coefficients as large as 1×10^5 were observed with sodium titanate at pH 13, and the values decrease as the pH decreases.

Most organic ion-exchange resins are not very effective for cesium removal from such high salt concentrations, but a new resorcinol-based resin developed at the Savannah River Site was found to be considerably superior to any other resin tested. An unexpected effect of resin particle size was observed, with larger resin particles showing much more effective

cesium removal than small particles. Several chelating resins were effective for removal of strontium from the waste simulants. An ion-exchange column test successfully demonstrated the simultaneous removal of both cesium and strontium from a waste simulant solution.

The large distribution coefficients and poor physical form (degradation to small particles) of most inorganic sorbents favor their use in simple batch separation processes. Although distribution coefficients were smaller with organic resins than with the best inorganic sorbents, they were large enough, in some cases, that batch processes might be possible. However, organic resins are generally more suited to column operations, and distribution coefficients were entirely adequate for this application.

Cross-flow filtration at the microfiltration and ultrafiltration level was investigated both for removing the suspended ferrocyanide ion-exchange material and as a means of reducing the concentration of ^{60}Co in the supernate. Tests with simulants containing NaNiFC or KNiFC/sodium titanate slurries showed that concentrations of up to 30% solids were possible. Tests of actual supernate using ion exchangers, ultrafiltration, and complex breaking reagents gave little, or no, measurable DFs. Nitrate removal was investigated using chemical denitration with sulfuric acid and resulted in the removal of greater than 98% of the nitrate from the salt solution.

4. REFERENCES

1. M. B. Sears, J. L. Botts, R. N. Ceo, J. J. Ferrada, W. H. Griest, J. M. Keller, and R. J. Schenley, Sampling and Analysis of Radioactive Liquid Wastes and Sludges in the Melton Valley and Evaporator Storage Tanks at ORNL, ORNL/TM-11652, 1990.
2. D. D. Lee and D. O. Campbell, Mass Balance of Low-Level Liquid Waste Storage Tanks and Requirements for Waste Processing, ORNL/TM, in preparation.
3. J. B. Berry, D. O. Campbell, D. D. Lee, and T. L. White, "Process Development for Remote-Handled Mixed Waste Treatment," presented at the 1990 AIChE Summer National Meeting, San Diego, Calif., August 1990.
4. International Atomic Energy Agency Report, Chemical Treatment of Low- and Intermediate-Level Aqueous Radioactive Waste, in final review (publication scheduled in 1991).
5. E. W. Hooper, B. A. Phillips, S. P. Dagnall, and N. P. Monckton, An Assessment of the Application of Inorganic Ion Exchangers to the Treatment of Intermediate Level Wastes, AERE-R-11088, Atomic Energy Research Establishment, Harwell, 1984.
6. B. A. Phillips and E. W. Hooper, Study of the Behavior of Inorganic Ion Exchangers in the Treatment of Medium Active Effluents, Part I. Preliminary Experimental Work on Absorber Preparation and Performance, AERE-G-2872, Atomic Energy Research Establishment, Harwell, 1988.
7. G. W. Beaven, J. E. Cross, and E. W. Hooper, Study of the Behavior of Inorganic Ion Exchangers in the Treatment of Medium Active Effluents, Part IV. Further Studies on Absorber Performance, AERE-G-4381, Atomic Energy Research Establishment, Harwell, 1988.
8. S. D. Reilly, C. F. V. Mason, and P. H. Smith, Cobalt(III) Dicarbolyde: A Potential ^{137}Cs and ^{90}Sr Waste Extraction Agent, LA-11695, 1990.
9. E. P. Horwitz, M. L. Dietz, and D. E. Fisher, "SREX, a New Process for the Extraction and Recovery of Strontium from Acidic Nuclear Waste Streams," Solvent Extr. Ion Exch., in press.
10. E. P. Horwitz, M. L. Dietz, and D. E. Fisher, Solvent Extr. Ion Exch., **8**, 199 (1990).
11. M. A. Ebra, R. M. Wallace, D. D. Walker, and R. A. Wille, "Tailored Ion Exchange Resins for Combined Cesium and Strontium Removal from Soluble SRP High-Level Waste," in The Scientific Basis for Nuclear Waste Management, S. V. Topp, Ed., p. 632, Elsevier, 1982.

12. J. P. Bibler, R. M. Wallace, and L. A. Bray, "Testing a New Cesium-Specific Ion Exchange Resin for Decontamination of Alkaline High-Activity Waste," Waste Management '90, Vol. 2, R. G. Post, Ed., pp. 747-51, 1990.
13. D. O. Campbell, D. D. Lee, and T. A. Dillow, Summary Report on Process Development Studies for LLLW Treatment, Letter Report to C. H. Brown, Sept. 28, 1989.
14. D. O. Campbell, D. D. Lee, and T. A. Dillow, "Low-Level Liquid Waste Decontamination by Ion Exchange," Waste Management '90, Vol. 2, R. G. Post, Ed., pp. 389-98, 1990.
15. W. E. Prout, E. R. Russell, and H. J. Groh, "Ion Exchange Absorption of Cesium by Potassium Hexacyanocobalt(II) Ferrate(II)," J. Inorg. Nucl. Chem. **27**, 473 (1965).
16. C. Loos-Neskovic, M. Fedoroff, and E. Garnier, "Preparation, Composition, and Structure of Some Nickel and Zinc Ferrocyanides: Experimental Results," Talanta **36**, 749 (1989).
17. J. Lehto and R. Harjula, "Separation of Cesium from Nuclear Waste Solutions with Hexacyanoferrate(II)s and Ammonium Phosphomolybdate," Solvent Extr. Ion Exch. **5**(2), 343-52 (1987).
18. R. G. Dosch, Final Report on the Application of Titanates, Niobates, and Tantalates to Neutralized Defense Waste Decontamination — Materials, Properties, Physical Forms, and Regeneration Techniques, SAND80-1212, 1981.
19. E. D. Collins, D. O. Campbell, L. J. King, J. G. Knauer, and R. M. Wallace, "Evaluation of Zeolite Mixtures for Decontaminating High-Activity-Level Water at the Three Mile Island Unit 2 Nuclear Power Station," pp. 43-51 in Inorganic Ion Exchangers and Adsorbents for Chemical Processing in the Nuclear Fuel Cycle, IAEA-TECDOC-337, 1985.
20. P. S. Cartwright, "Pollution Control Membranes: Continuous, Competitive, Clean," Chem. Proc., pp. 23-30 (July 1990).
21. P. Biddle and R. G. Gutman, Use of Ultrafiltration for the Cleanup of Alkaline Pu-Containing Effluents, AERE-R-10942, Atomic Energy Research Establishment, Harwell, 1983.
22. R. G. Gutman, I. W. Cumming, and G. H. Williams, Active Liquid Treatment by a Combination of Precipitation and Membrane Processes, EUR-10822, Commission of the European Communities, Luxembourg, 1986.
23. L. Cecille, I. W. Cumming, G. Gasparini, and J. F. Dozol, New Alternative Processes for the Treatment of the Alkaline Solvent Wash Waste, CEA-CONG-8759, Centre d'Etudes Nucleaires de Cadarache, France, 1986.

24. V. T. Le, L. P. Buckley, and G. J. McConeghy, Selective Removal of Dissolved Radioactivity from Aqueous Wastes by a Chemical Treatment/Ultrafiltration Technique, Proc. 2nd Int. Conf. Sep. Sci. Technol., Vol. 2, pp. 640-46, Can. Soc. Chem. Eng., Ottawa, Ont., 1989.
25. V. L. Fowler and J. D. Hewitt, Filtration of Oak Ridge National Laboratory Simulated Liquid Low-Level Waste, ORNL/TM-10653, 1989.
26. V. L. Fowler and J. D. Hewitt, Cross-Flow Filtration of Oak Ridge National Laboratory Liquid Low-Level Waste, ORNL/TM-10742, 1989.
27. J. E. Cross and E. W. Hooper, "Advanced Methods for the Removal of Actinides from Low and Intermediate Level Waste Effluents," Waste Management '89, Tucson, Ariz., 1989.
28. P. J. Durrant and B. Durrant, Introduction to Advanced Inorganic Chemistry, 2nd ed., John Wiley & Sons, Inc., New York, 1970.

INTERNAL DISTRIBUTION

1.	H. L. Adair	24-25.	D. D. Lee
2.	J. M. Begovich	26.	J. J. Maddox
3.	J. T. Bell	27.	R. C. Mason
4.	J. B. Berry	28.	A. J. Mattus
5.	W. D. Bond	29.	L. E. McNeese
6.	C. H. Brown, Jr.	30.	L. J. Mezga
7.	D. O. Campbell	31.	J. J. Perona
8.	R. M. Canon	32.	D. J. Peterson
9.	E. D. Collins	33.	D. J. Pruett
10.	K. W. Cook	34.	S. M. Robinson
11.	A. G. Croff	35.	T. F. Scanlan
12.	T. A. Dillow	36.	C. B. Scott
13.	S. M. DePaoli	37.	M. G. Stewart
14.	C. P. East	38.	P. A. Taylor
15.	W. Fulkerson	39.	J. R. Trabalka
16.	R. K. Genung	40.	D. W. Turner
17.	J. R. Hightower	41.	E. L. Youngblood
18.	L. Holder	42.	Cen. Res. Library
19.	E. K. Johnson	43.	Doc. Ref. Section
20.	C. M. Kendrick	44.	Lab Records
21.	T. E. Kent	45.	Lab Records, R.C.
22.	K. H. King-Jones	46.	ORNL Pat. Sect.
23.	J. R. Lawson		

EXTERNAL DISTRIBUTION

47. Office of Assistant Manager, Energy Research and Development, DOE-OR,
F. O. Box 2001, Oak Ridge, TN 37831-8600
- 48-57. Office of Scientific and Technical Information, P. O. Box 62, Oak Ridge,
TN 37831

END

**DATE
FILMED**

2 / 05 / 92