Invited Paper to be Submitted at the 5th Topical Meeting on the Technology of Fusion Energy, April 26-28, 1983, Knoxville, Tennessee

CONF-830406--6

DE83 009589

ENGINEERING TESTING REQUIREMENTS IN FED/INTOR*

By

M. A. Abdou and R. E. Nygren (ANL)
 G. D. Morgan and C. A. Trachsel (MDAC) ✓
 G. Wire, E. Oppermann, and R. Puigh (HEDL)
 R. E. Gold (W)

Robert L. Taylor
John L. Trachsel
A. L. Loria
per author file + aft

The submitted manuscript has been authored by a contractor of the U. S. Government under contract No. W-31-109-ENG-38. Accordingly, the U. S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U. S. Government purposes.

Submitted October 1982

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

* Work supported by the U.S. Department of Energy.

gmp
 DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ENGINEERING TESTING REQUIREMENTS IN FED/INTOR

M. A. Abdou and R. E. Nygren (ANL)
G. D. Morgan and C. A. Trachsel (MDAC)
G. Wire, E. Oppermann, R. Puigh (HEDL)
R. E. Gold (W)

The FED/INTOR critical issues activity has addressed^(1,2) three key testing requirements that have the largest impact on the design, operation and cost of FED/INTOR. These are: 1) the total testing time (fluence) during the device lifetime, 2) the minimum number of back-to-back cycles, and 3) the neutron wall load (power density in the first wall/blanket). The testing program activities were structured into three tasks in order to define the benefits, and in some cases, costs and risks of these testing requirements. The three tasks were carried out with wide participation of experts from a number of organizations in the United States. Similar effort was performed by Japan, the European community and the Soviet Union.

Structural Material Testing

This task is concerned with estimating the benefits and risks to DEMO based on structural material tests in FED/INTOR as the goal fluences for such tests increases from 0 to 6 MW-y/m². The "benefit" is simply the reduction of uncertainties in predicting materials' performance in DEMO that would result from higher test fluences (greater device lifetime) in FED/INTOR. The risk is the probability that the structural material will not achieve its design lifetime and performance goals in the DEMO.

Stainless steel and a vanadium alloy (representative of an advanced alloy not containing nickel) were considered separately. The main difference, between the two classes of materials are the availability of data and the usefulness of simulating the fusion radiation environment in fission reactors. For each of these two materials, two scenarios were considered based on whether FMIT is available for high energy neutron irradiation.

A simplified summary on recommended test fluences in FED/INTOR is given in the table below.

	With FMIT	Without FMIT
Stainless Steel	2-3 MW-y/m ² Low Risk	3 MW-y/m ² Low-Medium Risk
Advanced Alloys	3-5 MW-y/m ² Medium Risk	3 → 6 MW-y/m ² High → Medium Risk

Blanket Tests

The results of the analysis show that the minimum useful wall load for blanket tests in FED/INTOR is $\sim 0.4 \text{ MW/m}^2$ with a substantial incentive for higher wall loadings in order to adequately simulate the DEMO conditions. Specimens/components that are duplicates of the DEMO blanket will not provide useful test information if operated under FED/INTOR conditions. Special designs of test elements are necessary in order to account for the differences in power density, plasma duty cycle and other operating conditions between FED/INTOR and DEMO.

Solid breeder blankets require considerably longer "continuous" test time than liquid metal blankets. The minimum continuous operating time for tritium recovery of solid breeders is estimated to be 65 hours for a neutron wall load (P_w) of 1.3 MW/m^2 , 200-s plasma burn and 20-s dwell time. Much longer time is required for lower wall loads, shorter burn time and for the deeper regions of the blanket module.

The benefits of testing blanket modules in FED/INTOR to fluences above 0.2 MW-y/m^2 cannot be quantified at present. The primary reason is the prediction that fission reactor tests of solid breeders produce essentially the same results as fusion reactor tests at the same fluence. Fission reactor tests can be performed for fluences $\gg 0.2 \text{ MW-y/m}^2$ before FED/INTOR blanket tests take place.

Long-Term Component Operation

The long-term operation of FED/INTOR will provide useful data on life, failure rates and failure modes (i.e., reliability) of FED/INTOR components (e.g., magnets, auxiliary heating system, etc.). Testing for 3 to 5 times the required mean-time-between-failure of a component will in general create adequate confidence in reliability data. The FED/INTOR analysis shows that reliability data can be derived for most major reactor systems during a total reactor operating time of $\sim 20,000$ hours (i.e., $\sim 3 \text{ MW-y/m}^2$).

References

1. W. M. Stacey, et al., Final Phase 2A Report.
2. M. A. Abdou, et al., "Engineering Testing," Chapter XII, *ibid*.