AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

The radial scale length of turbulent fluctuations in the main core of TFTR plasmas

E. Mazzucato and R. Nazikian

*Princeton University Plasma Physics Laboratory,
P.O. Box 451, Princeton, NJ 08543*

Abstract

A new theory of microwave reflectometry in tokamaks has been developed which accounts for all the major characteristics of waves reflected from strong fluctuations near the cutoff layer. The theory has been used for studying the turbulence in the main core of neutral beam heated plasmas of the TFTR tokamak in the supershot regime. The results indicate that the radial correlation length of density fluctuations is a weak decreasing function of beam power, from ≈ 4 cm in Ohmic to ≈ 2 cm at 14 MW of heating power. This corresponds to the range of wavelengths $k_{\perp} \rho_i \approx 0.1 - 0.3$. Over the same interval of heating powers, the level of density fluctuations is observed to steadily increase with beam power by more than an order of magnitude. This trend is inconsistent with mixing length estimates of the fluctuation level.

PACS 52.55.Fa, 52.35.Ra, 52.70.Gw

After more than thirty years of research and on threshold of demonstrating scientific breakeven, the causes of anomalous plasma transport in tokamaks is still an outstanding issue. Although it has been accepted¹⁻⁴ for many years that the thermal and particle transport in tokamaks is enhanced by some kind of plasma turbulence, it has been exceedingly difficult to make progress in understanding this process. Theoretically, one is faced with the necessity of solving the equations of plasma dynamics which, even in the most simple cases, contain many coupled variables. Experimentally, the investigation of turbulence in the main core of tokamaks requires a level of machine accessibility and experimental time which has never been granted to these studies.

Various experimental observations⁵⁻¹⁰ have indicated that a small-scale turbulence exists in tokamaks in the range of frequencies around $\omega_* = k_\theta c T_e / e B L_n$, where k_θ is the poloidal wave number, and $L_n = |d \ln n / dr|^{-1}$ is the density scale length. While the initial observations⁵⁻⁷ on small size tokamaks showed a maximum in the spectrum at wavelengths of the order of the ion Larmor radius (i.e., $k_\theta \rho_i \approx 1$), subsequent measurements⁸⁻¹⁰ on larger devices showed spectra with monotonically decreasing amplitude with wavenumber. Although these measurements were performed with scattering techniques which could detect long wavelength fluctuations with only poor spatial resolution, they were still capable of spatially resolving fluctuations with a maximum of the turbulence spectrum at $k_\theta \rho_i \approx 1$. Hence, the possible conjecture that the scale length of turbulence in tokamaks is more sensitive to the size of the magnetic configuration than to the value of the ion Larmor radius. This is consistent with recent observations on TFTR¹¹ and JET¹² showing that the local plasma transport follows a Bohm-like scaling. The recent introduction of correlation reflectometry and beam emission spectroscopy on large tokamak experiments¹³⁻¹⁵ has been motivated by the need for new spatially localized measurements of long wavelength fluctuations.

In the method of correlation reflectometry, the spectrum of density fluctuations are inferred from the characteristics of waves reflected from closely spaced cutoff layers. This method was originally proposed in Ref. 13 and subsequently implemented on many tokamaks. However it was soon found that in the presence of a large level of density fluctuations, the measured radial correlation length could be as small as the free space wave length of the probe beam. These results were clearly inconsistent with measurements obtained using standard microwave scattering techniques. Moreover, a major difficulty in the correct interpretation of the data was

the inability of existing theory to account for the observed strong amplitude modulation and spectral broadening of the reflected waves.

In this Letter, we present a new theory of correlation reflectometry which for the first time accounts for all the major characteristics of waves reflected from strong fluctuations at the cutoff layer. A key result of our analysis is that the measured signal correlation is a strong function of the fluctuation level. The theory is applied to data taken in the core region of TFTR beam heated plasmas with a reflectometer operating in the X-mode and consisting of one fixed frequency (122 GHz) reference channel and one tunable frequency (111-123 GHz) channel. By stepping the frequency of the tunable channel every 20-30 ms, the cross correlation of the received signals was measured as a function of the spatial separation of the cutoff layers. The theory is used to infer the turbulence correlation length from the measured signals and the dependence of the turbulence correlation length with heating power is investigated.

In previous studies¹⁶⁻¹⁸, it was shown that in the limit of small amplitude fluctuations (i.e., $\tilde{n}/n \leq 10^{-3}$ for the case of this Letter) the scattered field originates in a small region near the cutoff when the radial wavelength λ_r of the density fluctuation is larger than approximately two times the vacuum wavelength of the launched wave. For X-mode reflectometry on TFTR, this corresponds to the condition $k_r = 2\pi/\lambda_r < 12 \text{ cm}^{-1}$ which is well satisfied by density fluctuations existing in TFTR plasmas¹⁰. In the same limit, the angular spectrum of reflected waves is linearly related to the poloidal spectrum of density fluctuations¹⁶. For $k_\theta \approx 0$, the scattered field corresponds to a phase modulation $\delta\phi$ of the reflected wave which, for long wavelength fluctuations, can be obtained from geometric optics. The importance of this result is that the geometric optics approximation is not limited to the case of small fluctuations. To find how this result is modified in the case of $k_\theta \neq 0$, we have solved numerically the wave equation in a 2-D geometry (r, z) where a plane wave is launched perpendicularly to a plane stratified plasma equilibrium perturbed by a density fluctuation of the form

$$\tilde{n} = a n(r) \cos(k_r(r-r_c)) \cos(k_\theta z), \quad (1)$$

where a is a constant, $n(r)$ is the unperturbed plasma density, and r_c is the radial position of the cutoff. In vacuum, the reflected wave can be expanded in a series of plane waves with wave-vector components $k_z = lk_\theta$, where l is an integer. Taking an equilibrium profile similar to that of a typical TFTR discharge, we find the spectrum of amplitudes displayed in Fig. 1 for the case of $k_0 = 25 \text{ cm}^{-1}$ (122 GHz), $k_r = 2 \text{ cm}^{-1}$, $k_\theta = 1.5 \text{ cm}^{-1}$, and for $a = 0.001, 0.01$, and

$a=0.02$. In vacuum, we obtain a similar spectrum of plane waves assuming that the plasma density fluctuation modulates the phase of the reflected wave by the amount $\Delta\phi=\delta\phi\cos(k_\theta z)$. The amplitudes of the plane waves are then given by $|J_l(\delta\phi)|$, where J_l is the Bessel function of the first kind of order l . For the cases of Fig. 1, this agrees with the solution of the wave equation if we take for $\delta\phi$ the value given by geometric optics for the density perturbation of Eq. (1) with $k_\theta=0$. Hence we conclude that, at least up to values of $a\leq 0.02$ and $k_\theta\leq 2\text{ cm}^{-1}$, the effect of density perturbations on the reflected wave can be approximated by a phase modulation given by geometric optics. Based on these findings, we present a theory of reflectometry in which the plasma is assumed to behave as a corrugated random phase screen of arbitrary amplitude. Such corrugations produce an angular distribution of waves in vacuum which are measured using directionally sensitive receivers. We may approximate the observable k_θ -spectrum of the reflected waves in vacuum by the expression

$$E(k_\theta, \omega) \propto \exp(i k_r r) \iint dz dt \exp(-i(k_\theta z - \omega t) + i\phi(z, t)) \quad , k_r = \sqrt{k_0^2 - k_\theta^2} \quad , \quad (2)$$

where $E(k_\theta, \omega)$ is a Fourier component of the wave amplitude,

$$\phi(z, t) = 2k_0 \int_0^{r_c} \sqrt{\epsilon(z, r, t)} dr \quad (3)$$

is the phase given by geometric optics, and ϵ is the plasma permittivity. For locally homogeneous stationary fluctuations the common power between two reflectometer channels with reflecting layers at r_1 and r_2 , respectively, is

$$\langle E_1(k_\theta, \omega) E_2^*(k_\theta, \omega) \rangle = \iint dz dt \exp(-i(k_\theta z - \omega t)) \langle e^{i\Delta\phi} \rangle \quad , \quad (4)$$

where $\Delta\phi$ is the difference of the phases given by Eq. (3) for the two channels, the brackets $\langle \rangle$ represent ensemble averages, and $\langle e^{i\Delta\phi} \rangle$ is the characteristic function of $\Delta\phi$. The spectral coherence for waves reflected from two closely spaced cutoff layers is then given by

$$\gamma_E(\Delta r_c) = \frac{\langle \tilde{E}_1(k_\theta, \omega) \tilde{E}_2^*(k_\theta, \omega) \rangle}{\langle |\tilde{E}_1(k_\theta, \omega)|^2 \rangle} \quad , \quad (5)$$

where Δr_c is the separation of the cutoff layers and $\tilde{E}(k_\theta, \omega) = E(k_\theta, \omega) - \langle E(k_\theta, \omega) \rangle$ is the random component of the scattered field. The correlation length in reflectometry is then obtained from the measurement of the coherence for a range of Δr_c . For small fluctuation levels the characteristic function need only be expanded up to second order in $\Delta\phi$ so that knowledge of the probability density of ϕ is not required. However, to evaluate the common power for

arbitrary fluctuation levels the characteristic function needs to be evaluated to higher order moments in $\Delta\phi$. For large amplitude fluctuations we must make the further reasonable assumption that the probability density of ϕ is approximately Gaussian

$$P(\phi) = \frac{1}{\sqrt{2\pi} \sigma_\phi} \exp(-\phi^2/2\sigma_\phi^2) , \quad (6)$$

where $\sigma_\phi = \langle \phi^2 \rangle^{1/2}$. Under this assumption the common power and spectral coherence may be expressed in terms of powers of the normalized correlation $\gamma_\phi = \langle \phi_1 \phi_2 \rangle / \sigma_\phi^2$ as

$$\gamma_E(\Delta r_c) = \frac{\sum_{n=1}^{\infty} \frac{\sigma_\phi^{2n}}{n!} \Phi_n(k_\theta, \omega, \Delta r_c)}{\sum_{n=1}^{\infty} \frac{\sigma_\phi^{2n}}{n!} \Phi_n(k_\theta, \omega, 0)} , \quad (7)$$

where

$$\Phi_n = \iint dz dt \exp(-i(k_\theta z - \omega t)) \gamma_\phi^n(z, t, \Delta r_c) . \quad (8)$$

Note that as σ_ϕ increases higher order terms in γ_ϕ begin to contribute to the observed spectrum and measured coherence. As we will show, assuming that γ_ϕ decreases monotonically with increasing Δr_c , the radial correlation length and correlation time of the received signals will decrease as the plasma fluctuation level increases. From Eq. (8), the angular spread of the reflected waves should also increase as higher order terms in γ_ϕ begin to dominate the scattered spectrum, as is also shown by the numerical results of Fig.1.

In order to evaluate Φ_n to all orders we assume an approximate Gaussian form for γ_ϕ as

$$\gamma_\phi = \exp(-r^2/2\sigma_r^2) \exp(-(z-vt)^2/2\sigma_\theta^2) \exp(-t^2/2\sigma_t^2) , \quad (9)$$

where v is the apparent poloidal velocity of the fluctuations, σ_r , σ_θ , σ_t , are the radial correlation length, poloidal correlation length and correlation time, respectively. Inserting Eq. (9) into Eqs. (8) and (7) we obtain for the signal coherence

$$\gamma_E = \frac{\sum_{n=1}^{\infty} \frac{\sigma_\phi^{2n}}{n!} \exp(-nr^2/2\sigma_r^2) \exp(-k_\theta^2 \sigma_\theta^2/2n) \exp(-(\omega - k_\theta v)^2 \sigma_t^2/2n)}{\sum_{n=1}^{\infty} \frac{\sigma_\phi^{2n}}{n!} \exp(-k_\theta^2 \sigma_\theta^2/2n) \exp(-(\omega - k_\theta v)^2 \sigma_t^2/2n)} \quad (10)$$

The spectrum of plane waves for any one reflectometer channel is proportional to the denominator of Eq. (10). Note that for $k_\theta \neq 0$ the peak in the frequency spectrum occurs for $\omega = vk_\theta$, independent of the fluctuation amplitude. If k_θ is known from the alignment of the receiver and transmitter to the plasma reflecting layer, then the plasma rotation may be inferred from the Doppler shift in the peak of the frequency spectrum. This is consistent with the notion

that the fluctuations at the plasma cut off act as a rotating diffraction grating where the non-specular reflection experiences a Doppler shift determined only by the scattering angle and the plasma velocity. Restricting the measurement to $k_\theta \approx 0$ and $\omega \approx 0$ we obtain the further approximation

$$\gamma_E \approx \frac{\text{Ei}(\sigma_\phi^2 \gamma_r) - \xi \ln(\sigma_\phi^2 \gamma_r)}{\text{Ei}(\sigma_\phi^2) - \xi \ln(\sigma_\phi^2)} , \quad (11)$$

where Ei is the exponential integral, $\xi=0.577$ is the Euler number and $\gamma_r = \exp(-r^2/2\sigma_r^2)$ is the radial component of γ_ϕ . In the limit of $\sigma_\phi \ll 1$ we arrive back at the linear or Born approximation where $\gamma_E = \gamma_r$, whereas for $\sigma_\phi^2 \gamma_r > 2.5$ we obtain from the asymptotic form of Ei

$$\gamma_E \approx \frac{1}{\gamma_r} \exp(-\sigma_\phi^2(1-\gamma_r)) . \quad (12)$$

An important result which is evident from Eq. (12) is that for sufficiently large σ_ϕ the value of the signal correlation may be much smaller than the corresponding value of γ_r . Expanding γ_r to second order it is readily shown that $\gamma_E \approx \exp(-r^2/2\sigma_E^2)$ where $\sigma_E = \sigma_r/\sigma_\phi$ so that the correlation length of the measured signal is a factor of σ_ϕ smaller than the correlation length of the geometric optics phase. It may also be shown numerically from Eq. (10) that the k_θ and ω spectrum of reflected waves broadens by a factor of σ_ϕ over the corresponding spectral width of the fluctuations. This broadening is also shown in the numerical results of Fig. 1. This theory of correlation reflectometry captures all the main characteristics of reflectometer measurements obtained on many plasma devices.

In order to relate the measured signal correlation to the plasma fluctuations we introduce the approximation for the perturbed phase $\tilde{\phi} = k_0 \int_0^{r_c} \tilde{\epsilon}/(\epsilon_0)^{1/2} dr$ which yields numerical results very close to those of Eq. (3). Also, since the measurement is localized to a narrow region around the cutoff¹³, we use the linear approximation $\epsilon_0 \approx (d\epsilon_0/dr)_{r=r_c}(r-r_c)$. From this we readily derive the result

$$\Gamma_\phi(k_r) \approx 2\pi \frac{k_0^2}{k_r |d\epsilon_0/dr|_{r=r_c}} [C^2(\alpha) + S^2(\alpha)] \Gamma_\epsilon(k_r) , \quad (13)$$

where $\Gamma_\phi(k_r)$ and $\Gamma_\epsilon(k_r)$ are the radial Fourier transforms of the phase and permittivity correlations, respectively, $C(\alpha)$ and $S(\alpha)$ are the Fresnel integrals, and $\alpha = (2k_r r_c/\pi)^{1/2}$. From these relations we may determine the correlation length of plasma density fluctuations from correlation reflectometer measurements.

The experimental results presented in this Letter have been obtained in neutral beam heated

TFTR discharges in the supershot regime¹⁹. The main plasma parameters were: minor radius 0.8 m, major radius 2.45 m, Toroidal field 4.2-4.8 T, plasma current 1.2 MA, central electron density $4\text{-}6 \times 10^{19} \text{ m}^{-3}$, central electron temperature 5-8 keV, central ion temperature 5-20 keV, and neutral beam power 2-14 MW.

Figure 2 shows the frequency spectrum of the reflected waves during the Ohmic and the NB phase of a TFTR discharge with $P_{NB}=14$ MW. These spectra were obtained from the common power between two closely spaced reflectometer channels at $r/a \approx 0.3$. The reflecting layers were separated by a distance of the order of 3mm. Consequently, in both cases the spectral coherence (also shown in Fig. 2) is close to unity over the entire spectral range. Note that the spike in the frequency spectrum at $\omega \approx 0$ during the Ohmic phase, which represents the unscattered component of the reflected wave, has totally disappeared in the NB phase of the discharge. This is evidence for a transition from weak to strong scattering. As suggested by the preceding theory, this transition should be accompanied by a broadening of the frequency spectrum as shown in Fig. 2, together with a narrowing of the signal correlation length as shown in Fig. 3 which displays the signal coherence at $\omega \approx 0$ as a function of the reflecting layers separation. Within the accuracy of the measurement, the data can be fit to a Gaussian. From these data it appears that during NB heating the spectral width of the signal increases by more than an order of magnitude over the Ohmic phase together with a corresponding decrease in the measured coherence length as predicted by our random phase screen model. By scanning the relative angle between transmitter and receiver we have determined that the Ohmic k_θ - spectrum is in the range $k_\theta \leq 1 \text{ cm}^{-1}$, which is of the order of the instrumental k -resolution of the receiver. The observed frequencies in the Ohmic phase also correspond to the drift wave range of frequencies for $k_\theta \leq 1$. In contrast, the NB spectrum is well outside the range of drift frequencies since during the heating phase the electron temperature increases by less than a factor of two, leading to no more than a factor of two increase in the drift wave frequency. The observed large spectral width can be explained in part by the Doppler broadening caused by the plasma toroidal rotation which is induced by NB injection. This broadening can be estimated from the measured plasma velocity if the poloidal magnetic field profile is known, which is rarely the case. Alternatively, the propagation velocity and hence the Doppler broadening may be directly obtained from the peak of the measured frequency spectra for $k_\theta \neq 0$. We conclude that although the Doppler effect is important, it cannot account for the observed frequency broadening of the signal. From our random phase screen model, we know that the spectrum of reflected waves must also be broadened by an increased level of turbulence, which for Fig. 2

corresponds to an increase of σ_ϕ from ≈ 0.4 to ≈ 3.6 radians. In fact, while the Ohmic value of σ_ϕ is small enough to guarantee that only the first term in the series of Eq. (10) is important so that $\gamma_E \approx \gamma_r$, the value of σ_ϕ during NB injection is much larger than unity and therefore higher order terms contribute to the measured spectral coherence. For large σ_ϕ we must apply Eqs. (11) and (13) to the measured coherence of reflected waves (Fig. 3) in order to derive the density correlation. The results can again be fitted by a Gaussian with a half-width (L_r) of the 1/e points which is a decreasing function of beam power, from ≈ 4 cm in Ohmic to ≈ 2 cm at 14 MW (Fig. 4). From the value of L_r we obtain the spectral width $\Delta k_r \approx 2/L_r$ corresponding to $\Delta k_r \rho_i \approx 0.1-0.3$. In the same range of heating powers the level of density fluctuation $\tilde{n}/n$ increases with heating power from 1×10^{-3} to approximately 1.5×10^{-2} as shown in Fig. 4. The steady increase of the measured density fluctuation with beam power is inconsistent with the mixing length criterion $\tilde{n}/n \approx L_r/L_n$ which, for the measured values of L_r and L_n , predicts a much weaker variation of the level of turbulence with increasing beam power. Finally, if we assume from simple random walk arguments that $\chi \approx L_r^2/t_c$ (where t_c is the correlation time) and we take $t_c \propto 1/\omega_*$ with $k_\theta \approx \Delta k_r$, then the trend shown by the data of Fig. 4 is consistent with the observation that the local thermal conductivity of both ions and electrons is only a weak function of beam power for these plasmas²⁰.

In conclusion, a new theory of microwave reflectometry has been developed which accounts for all the major characteristics of waves reflected from strong fluctuations at the cutoff layer. The theory has been applied to data taken in the main core of neutral beam heated plasmas of the TFTR tokamak in the supershot regime. The results indicate that the radial correlation length of density fluctuations is a weak decreasing function of beam power, from ≈ 4 cm in Ohmic to ≈ 2 cm at a neutral beam power of 14 MW. Over the same range of heating powers, the level of density fluctuations is observed to steadily increase with beam power. This is inconsistent with mixing length estimates given the weak variation of the density scale length with beam power in these plasmas.

The authors are grateful to the TFTR group for the successful operation of these experiments and to M. McCarthy for his contributions to the reflectometer. Many helpful discussions with N. Bretz, S. Scott, W. Tang, and M. Zarnstorff are gratefully acknowledged. We also thank K. Young for his continued support. This work was supported by US Department of Energy Contract No. DE-AC02-76-CHO-3073.

References

- ¹W. Horton, in *Handbook of Plasma Physics II*, edited by M.N. Rosenbluth and R.Z. Sagdeev (North-Holland, Amsterdam, 1984), p. 383.
- ²B. Coppi, S. Migliuolo and Y-K. Pu, *Phys. Fluids* **B2**, 2322 (1990).
- ³P.H. Diamond and H. Bigliari, *Phys. Rev. Lett.* **65**, 2865 (1990).
- ⁴W. Tang, *Nucl. Fusion* **18**, 1089 (1978).
- ⁵E. Mazzucato, *Phys. Rev. Lett.* **36**, 792 (1976).
- ⁶C.M. Surko and R.E. Slusher, *Phys. Rev. Lett.* **37**, 1747 (1976).
- ⁷Equipe TFR, in *Proc. 6th Int. Conf. on Plasma Physics and Controlled Nuclear Fusion Research, Berchtesgaden, 1976* (International Atomic Energy Agency, Vienna, 1977), Vol. 1, p. 35.
- ⁸E. Mazzucato, *Phys. Rev. Lett.* **48**, 1828 (1982).
- ⁹D.L. Brower, W.A. Peebles and N.C. Luhman, *Nucl. Fusion* **27**, 2055 (1987).
- ¹⁰N. Bretz, R. Nazikian, *et. al.*, in *Proc. 7th European Phys. Soc. Conf. on Controlled Fusion and Plasma Heating*, Amsterdam, 1990 (EPS, Petit-Lancy, Switzerland, 1990) Vol 4, p. 1544.
- ¹¹F.W. Perkins, C.W. Barnes, *et. al.*, *Phys. Fluids* **B5**, 477 (1993).
- ¹²J.P. Christiansen, B. Balet, *et. al.*, *Plasma Phys. and Cont. Fusion* **34**, 1881 (1992).
- ¹³A. Costley, P. Cripwell, A. Prentice, and A. Sips, *Rev. Sci. Instrum.* **61**, 3487 (1990).
- ¹⁴T. Rhodes, W. Peebles, and E. Doyle, *et. al.*, *Rev. Sci. Instrum.* **63**, 4661 (1992).
- ¹⁵R. Fonck, G. Cosby, *et. al.*, to be published in *Phys. Rev. Lett.*
- ¹⁶E. Mazzucato and R. Nazikian, *Plasma Phys. and Cont. Fusion*, **33**, 261 (1991).
- ¹⁷N. Bretz, *Phys. Fluids* **B4**, 2414 (1992).
- ¹⁸I. Hutchinson, *Plasma Phys. and Cont. Fusion*, **34**, 1225 (1992).
- ¹⁹J. Strachan, M. Bitter, *et. al.*, *Phys. Rev. Lett.* **58**, 1004 (1987).
- ²⁰S.D. Scott, C.W. Barnes, *et. al.*, in *Proc. US-Japan Workshop on Ion Temperature Gradient Driven Turbulent Transport, Austin, 1993* (to be published).

Figure Captions

Figure 1. Poloidal spectrum of reflected waves for the density perturbation of Eq. (1). Lines are from the numerical solution of the wave equation with $k_r=2 \text{ cm}^{-1}$, $k_\theta=1.5 \text{ cm}^{-1}$, and $a=0.001$ (dot line), $a=0.01$ (dash line), $a=0.02$ (solid line); symbols are from the geometric optics approximation.

Figure 2. Frequency power spectra of reflected waves during Ohmic (left) and NB injection (right) with $P=14 \text{ MW}$. $S_E(\omega)$ is the power spectrum; $\gamma_E(\omega)$ is the spectral coherence for a channel separation of $\approx 2\pi/k_\theta$.

Figure 3. Signal coherence (γ_E) at $\omega \approx 0$ as a function of reflecting layers separation for the two cases of Fig. 2 (open circles are for Ohmic, triangles are for NB). Lines are Gaussian best fits.

Figure 4. Density radial scale length (circles) and density fluctuation level (squares) as a function of NB power at $r/a \approx 0.3$.

Fig. 1

Fig. 2

Fig. 3

EXTERNAL DISTRIBUTION IN ADDITION TO UC-420

Dr. F. Paoloni, Univ. of Wollongong, AUSTRALIA	Prof. I. Kawakami, Hiroshima Univ., JAPAN
Prof. M.H. Brennan, Univ. of Sydney, AUSTRALIA	Prof. K. Nishikawa, Hiroshima Univ., JAPAN
Plasma Research Lab., Australian Nat. Univ., AUSTRALIA	Director, Japan Atomic Energy Research Inst., JAPAN
Prof. I.R. Jones, Flinders Univ, AUSTRALIA	Prof. S. Itoh, Kyushu Univ., JAPAN
Prof. F. Cap, Inst. for Theoretical Physics, AUSTRIA	Research Info. Ctr., National Inst. for Fusion Science, JAPAN
Prof. M. Heindler, Institut für Theoretische Physik, AUSTRIA	Prof. S. Tanaka, Kyoto Univ., JAPAN
Prof. M. Goossens, Astronomisch Instituut, BELGIUM	Library, Kyoto Univ., JAPAN
Ecole Royale Militaire, Lab. de Phy. Plasmas, BELGIUM	Prof. N. Inoue, Univ. of Tokyo, JAPAN
Commission-European, DG. XII-Fusion Prog., BELGIUM	Secretary, Plasma Section, Electrotechnical Lab., JAPAN
Prof. R. Bouciqué, Rijksuniversiteit Gent, BELGIUM	S. Mori, Technical Advisor, JAERI, JAPAN
Dr. P.H. Sakanaka, Instituto Fisica, BRAZIL	Dr. O. Mitarai, Kumamoto Inst. of Technology, JAPAN
Instituto Nacional De Pesquisas Especiais-INPE, BRAZIL	J. Hyeon-Sook, Korea Atomic Energy Research Inst., KOREA
Documents Office, Atomic Energy of Canada Ltd., CANADA	D.I. Choi, The Korea Adv. Inst. of Sci. & Tech., KOREA
Dr. M.P. Bachynski, MPB Technologies, Inc., CANADA	Prof. B.S. Liley, Univ. of Waikato, NEW ZEALAND
Dr. H.M. Skarsgard, Univ. of Saskatchewan, CANADA	Inst of Physics, Chinese Acad Sci PEOPLE'S REP. OF CHINA
Prof. J. Teichmann, Univ. of Montreal, CANADA	Library, Inst. of Plasma Physics, PEOPLE'S REP. OF CHINA
Prof. S.R. Sreenivasan, Univ. of Calgary, CANADA	Tsinghua Univ. Library, PEOPLE'S REPUBLIC OF CHINA
Prof. T.W. Johnston, INRS-Energie, CANADA	Z. Li, S.W. Inst. Physics, PEOPLE'S REPUBLIC OF CHINA
Dr. R. Bolton, Centre canadien de fusion magnétique, CANADA	Prof. J.A.C. Cabral, Instituto Superior Tecnico, PORTUGAL
Dr. C.R. James., Univ. of Alberta, CANADA	Dr. O. Petrus, AL I CUZA Univ., ROMANIA
Dr. P. Lukác, Komenského Univerzita, CZECHO-SLOVAKIA	Dr. J. de Villiers, Fusion Studies, AEC, S. AFRICA
The Librarian, Culham Laboratory, ENGLAND	Prof. M.A. Hellberg, Univ. of Natal, S. AFRICA
Library, R61, Rutherford Appleton Laboratory, ENGLAND	Prof. D.E. Kim, Pohang Inst. of Sci. & Tech., SO. KOREA
Mrs. S.A. Hutchinson, JET Library, ENGLAND	Prof. C.I.E.M.A.T, Fusion Division Library, SPAIN
Dr. S.C. Sharma, Univ. of South Pacific, FIJI ISLANDS	Dr. L. Stenflo, Univ. of UMEA, SWEDEN
P. Mähönen, Univ. of Helsinki, FINLAND	Library, Royal Inst. of Technology, SWEDEN
Prof. M.N. Bussac, Ecole Polytechnique., FRANCE	Prof. H. Wilhelmson, Chalmers Univ. of Tech., SWEDEN
C. Moutet, Lab. de Physique des Milieux Ionisés, FRANCE	Centre Phys. Des Plasmas, Ecole Polytech, SWITZERLAND
J. Radet, CEN/CADARACHE - Bat 506, FRANCE	Bibliotheek, Inst. Voor Plasma-Fysica, THE NETHERLANDS
Prof. E. Economou, Univ. of Crete, GREECE	Asst. Prof. Dr. S. Cakir, Middle East Tech. Univ., TURKEY
Ms. C. Rinni, Univ. of Ioannina, GREECE	Dr. V.A. Glukhikh, Sci. Res. Inst. Electrophys. Apparatus, USSR
Dr. T. Mui, Academy Bibliographic Ser., HONG KONG	Dr. D.D. Ryutov, Siberian Branch of Academy of Sci., USSR
Preprint Library, Hungarian Academy of Sci., HUNGARY	Dr. G.A. Eliseev, I.V. Kurchatov Inst., USSR
Dr. B. DasGupta, Saha Inst. of Nuclear Physics, INDIA	Librarian, The Ukr.SSR Academy of Sciences, USSR
Dr. P. Kaw, Inst. for Plasma Research, INDIA	Dr. L.M. Kovrizhnykh, Inst. of General Physics, USSR
Dr. P. Rosenau, Israel Inst. of Technology, ISRAEL	Kernforschungsanlage GmbH, Zentralbibliothek, W. GERMANY
Librarian, International Center for Theo. Physics, ITALY	Bibliothek, Inst. Für Plasmaforschung, W. GERMANY
Miss C. De Palo, Associazione EURATOM-ENEA, ITALY	Prof. K. Schindler, Ruhr-Universität Bochum, W. GERMANY
Dr. G. Grosso, Istituto di Fisica del Plasma, ITALY	Dr. F. Wagner, (ASDEX), Max-Planck-Institut, W. GERMANY
Prof. G. Rostangni, Istituto Gas Ionizzati Del Cnr, ITALY	Librarian, Max-Planck-Institut, W. GERMANY
Dr. H. Yamato, Toshiba Res. & Devel. Center, JAPAN	Prof. R.K. Jansev, Inst. of Physics, YUGOSLAVIA

**DATE
FILMED**

9 / 2 / 93

END