ENERGY AND PROTEIN PRODUCTION
FROM PULP MILL WASTES

MASTER

Quarterly Report
for the Period December 15, 1978-March 15, 1979

M. F. Jurgensen and J. T. Patton

Michigan Technological University
Houghton, Michigan 49931

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

March 15, 1979

Prepared for
THE U. S. ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION
UNDER CONTRACT E(11-1)-2983
7

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warrant, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately owned rights.

ABSTRACT

The objective for the past quarter included reversing the decline in productivity from the methane fermenters, confirming methane and yeast production from acetate, and making trial runs on Kraft mill and Semi-chemical mill effluents.

Although methane production remained low (20 cc/hr) addition of 2% methanol doubled production.

Progress has been made on identifying possible viruses that might be preventing higher methane production.

Confirmation that acetate can be used as a substrate for methane production has been obtained.

An initial test on the Decker filtrate from a Kraft mill gave 20 cc/hr methane production.

BACKGROUND

Nearly three million tons of lignin derivatives and other soluble organic compounds are generated as waste by-product annually by the sulfite pulping process.

Conventional mechanical treatment of the waste liquor to prevent pollution consists of evaporation of the water and burning of the dried solids. Although some cooking chemicals are recovered and energy is generated by the combustion, the evaporation consumes 20 to 50 percent of the heat generated, the burning creates air pollution, and the evaporate has an objectionably high BOD due to the presence of volatile organic compounds.

Conventional biological treatments such as the activated sludge process, storage oxidation and aerated stabilization seek to avoid water removal. Although these methods effectively remove the low molecular

weight organics, thus lowering the BOD, the levels of lignosulfonates and sulfur are not significantly reduced.

A newer biological treatment is fermentation by Torula yeast for protein production. Although this consumes the pentose and hexose sugars the levels of lignosulfonates and sulfur are not affected.

Research conducted at Michigan Technological University has attempted to degrade the lignosulfonates by continuous digestion with a mixed microbial culture containing the sulfur-reducing anaerobe Desulfovibrio Desulfuricans. This research indicated that the lignosulfonate molecule or its sulfur component is not readily metabolized.

The general lack of success with biodegradation of lignosulfonates suggests that a chemical pretreatment may be desirable. Stern and Gasner showed that ozonation of kraft mill waste liquor degraded its lignin derivatives and increased their susceptibility to fermentation. The Barber-Colman Company has shown that wet oxidation of sulfite paper-pulp waste also produces lower molecular weight compounds.

Both yeast growth and fermentation with Desulfovibrio should be aided by chemical pretreatment. In addition, methane-producing anaerobes seem ideally suited for subsequent fermentation. Benson and Partansky have estimated that if 25% of the carbon in desugared spent sulfite liquor (DSSL) could be converted by methanogenesis, the caloric value of the annual production would be equivalent to that of forty billion cubic feet of natural gas. Many anaerobic bacteria (i.e. Methanobacterium ruminantium, methanococcus, Methanosarcina, Methanospirillum, Methanobacterium omelianskii) are methanogens. Since 1975 work in this laboratory on the development of a process for converting the pollutants present in sulfite pulp mill waste to useful fuels and protein has been supported by a grant from the Energy Research and Development Administration (now

the Department of Energy). The process as currently visualized is shown in Diagram 1. The primary yeast fermenter converts wood sugars and other assimilable organics into protein and CO_2 . The ozonator modifies sulfur bonds and breaks down high molecular weight organics. The ozonated fragments are fed to the anaerobic digester where a mixed bacterial culture is employed because only a few specific organics can be utilized by methane bacteria and therefore other organisms (i.e. Desulfovibrio are needed to develop the substrate for methane synthesis. A secondary yeast fermentation is included to permit digestion of any unassimilated ozonated fragments that can be utilized by Torula yeast. Any BOD remaining is removed by standard treating processes such as the activated sludge process or soil infiltration. During the anaerobic digestion some organic sludge, biological solids and lignin will be produced. The solids are recovered in a thickener and can, after dewatering, be burned as fuel if no higher value alternative is available. By virtue of the work thus far completed, we believe the following conclusions are justified:

1. Desugared spent sulfite liquor reacts readily with ozone to produce lower molecular weight organic fragments which can be metabolized by a variety of microorganisms. Ozonation removes color bodies and increases BOD.

2. Production of protein through growth of Torula yeast on DSSL is enhanced by ozonation. Longer ozonation times reduce this effect.

3. Production of methane by anaerobic fermentation is enhanced by ozonation. Longer ozonation times increase this effect.

STAFFING

During this quarter major project direction was furnished by Dr. E. T. Williams replacing principle investigator Dr. J. T. Patton, who

is now Professor and Head, Department of Chemical Engineering, New Mexico State University. The co-principle investigator, Dr. M. F. Jurgensen, contributed approximately 5 percent of his time to project direction on the microbiological aspects of the research. Dr. Patton, also contributed 3 days to the project as a consultant. During the quarter it was necessary to replace Mr. Craig Bremmon, technologist in charge of microbiological research, and Mr. Sushil Dugar, Ph.D. candidate. Mr. Bremmon resigned to accept a position with Gulf Petroleum Corporation and Mr. Dugar, having completed the research necessary for his degree, left the University. Ms. Kathy Blue, a student in microbiology, was hired to replace Mr. Bremmon and a search is currently in progress for additional graduate students to fill the void left by Mr. Dugar.

RESULTS AND DISCUSSION

During this quarter the yield of 20 cc/hr of methane from 3 hr. ozonated SSL was maintained. Addition of 2% methanol increased the production to 40 cc/hr, but we were not able to obtain the 100 cc/hr rates that have been previously reported. Peak values of 45 and 60 cc/hr have been achieved for the unsupplemented and methanol supplemented fermenters, but could not be maintained.

Initial experiments on Kraft and Semi-chemical mill wastes were performed during the quarter. Results showed these streams were too dilute to achieve useful products. Ozonation data shows that complete decoloring of Kraft waste can be accomplished with a maximum ozone concentration of 2.37 gms/l.

New Kraft samples were obtained from the Mead Paper Company in Escanaba, Mi.. This stream is the Decker filtrate which contains a high concentration of wood sugars as well as 30% methanol. Initial gas production of 20 cc/hr has been obtained. The reason for this low gas

rate is believed to be pH fluctuations in the reactivity of the stream, and should stabilize as optimum operating conditions are approached.

The ability to produce methane from acetate was confirmed during this quarter. Yields for 10 cc/hr were obtained on a feed containing 15 gms/l sodium acetate. However, acetate was not effective as a substrate for yeast production.

SUMMARY AND CONCLUSION

The results obtained this past quarter provide the stimulus and direction for work to be conducted during the next period. Past experience in the operation of anaerobic digesters for waste treatment indicates wide fluctuations in productivity is to be expected. Although the factors responsible for this are not fully indentified or well understood, it is possible that our research fermenters are behaving similarly. It is hoped that subsequent work will identify the factors responsible for the poor performance. This would be a valuable contribution to the design and operation of methane fermenters in the waste treatment field.

Ozone is an effective method for removing color bodies in final Kraft mill waste. The more concentrated Kraft decker filtrate has great potential for methane and yeast production without pretreatment.

PLANS FOR THE FUTURE

During the last quarter, work will continue to concentrate on identifying the factors responsible for the low productivity of the methane fermenters. Plans are made to isolate viruses which may be attacking the bacteria. Additional work is planned on determining optimum methanol concentration in SSL, and optimum conditions for fermentation of the Kraft mill effluent.