recd 7-18-89

Nitrogen Oxide Abatement by Distributed Fuel Addition

DOE/PC/79850--8

Contract DE-AC22-87PC79850

DE92 005210

Quarterly Report No. 8

Received by OSTI

DEC 30 1991

for Period

May 1, 1989 through July 31, 1989

Prepared by

J. O. L. Wendt and J. B. Mereb
Department of Chemical Engineering
University of Arizona
Tucson, Arizona 85721

Submitted to

Diane Revay Madden, Project Officer
Environmental Control Technology Division
Pittsburgh Energy Technology Center
Department of Energy

August 25, 1989

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

The performance of the new combustor was tested. Experiments showed that this combustor has superior insulating quality than the previous one. Measured radial concentrations indicated uniform distribution of the primary fuel (coal) inside the fire tube resulting in reasonably flat concentration profiles. However, measured radial concentrations after the addition of the reburn fuel showed uneven distribution of the fuel resulting in parabolic concentration profiles, an indication of insufficient mixing in the reburn zone. In order to study mechanisms of nitrogenous species destruction in the reburn zone, it is necessary to achieve adequate mixing if the assumption of one dimensional plug flow behavior is to be valid. Thus, it became necessary to modify the injector design and the injection mode of the reburn fuel to achieve an adequate level of mixing which is the focus of this report.

The results show that a minimum reburn fuel jet velocity of 15 m/s (standard conditions) was required which is about 80 times the velocity of the primary effluent. The use of nitrogen gas as a transport medium for the reburn fuel was necessary to achieve the desired jet velocities

INTRODUCTION

A new combustor was constructed as discussed in the previous report. In previous studies, no special attention was given to the distribution of the reburn fuel in the reburn zone since the overall effect of reburning was of interest. In addition, adequate mixing would be achieved in the burnout zone due to the introduction of relatively high flows of burnout air. As discussed later, inadequate mixing in the reburn zone would affect the overall reduction in NO and the location of the optimum reburn zone stoichiometric ratio. However, this effect would be of minor significance if the overall effect of NO reduction is examined. The works of Chen et al. (1986), Greene et al. (1985) and Kolb et al. (1988) suggested that the degree of mixing would create a difference of less than 10% in the overall reduction in NO and an optimum reburn zone stoichiometry ranging from 0.8 to 0.9. On the other hand, the effect of mixing cannot be ignored when examining the kinetics of nitrogenous species destruction in the reburn zone which is the focus of the next Task. The chemical rates in a combustor are so fast that mixing becomes a rate limiting step in combustion. Consequently, a study was conducted to investigate the conditions under which a well mixed reburn zone could be obtained and the results are presented in this report.

Reburn fuel mixing with primary zone effluent is a significant factor in the reburning process because it controls the dispersion of the reburn fuel. Adequate mixing of the reburn fuel improves its effectiveness in destroying NO because of improved NO/CH exposure. Consequently, the destruction of NO can be achieved more effectively prior to the complete consumption of the reburn fuel. Therefore, it might be expected that improved mixing would result in higher reductions in NO by reburning. This has been suggested by the work of several researchers

(Chen et al., 1986, Kolb et al., 1988, LaFond and Chen, 1987, Miyamae et al., 1986 and Overmoe et al., 1986).

Overmoe et al. (1986) tested different fuel jet velocities and suggested that reburning effectiveness would increase with jet penetration and mixing. In addition, mixing effects were found to increase the effect of primary NO concentrations. Little impact of burnout mixing was detected. Similar observations were reported by Chen et al. (1986).

Kolb et al. (1988) also investigated the effects of mixing and concluded that improved mixing reduced NO emissions. They suggested that insufficient mixing would create non optimal local fuel rich and fuel lean zones. The fuel lean zones would not be favorable for reducing NO and the fuel lean zones would produce more HCN and thus more NO in the exhaust.

Greene et al. (1985) identified mixing as a minor parameter in reburning. Nevertheless, the researchers hypothesized that improved mixing would be beneficial to the reburning process because it would allow more HC/NO interaction before the consumption of the reburn fuel. Consequently, less fuel rich pockets would be formed in the reburn zone, less N-species and thus, less NO in the exhaust. In addition, higher temperatures could be obtained because of improved fuel/oxygen contact.

Chen et al. (1986) argued that in a well mixed reburn zone and for nitrogen containing reburn fuels, there would exist a tradeoff between less NO emissions and increased conversion of the nitrogen in the reburn fuel. The use of inert carrier such as nitrogen gas was recommended so that the reburn fuel would not

be oxidized in large excess of oxygen and that would reduce the conversion of fuel nitrogen.

The impact of mixing would be more severe as the scale of the system increases because of the larger distances across which mixing must occur. In other words, the larger the scale of the system, the harder it would be to achieve adequate mixing. The results of Myerson (1975) and Miyamae et al. (1986) would suggest that reburning in small, well mixed systems (bench scale), would create sharp dependencies on stoichiometry in the reburn zone. Also, reductions as high as 90% would be possible.

In short, poor mixing in the reburn zone would create local variations in stoichiometry which would prevent complete optimization of the reburning process. It would result in lower reductions in overall NO emissions and broader dependence on reburn zone stoichiometries. Therefore, it is essential to achieve adequate mixing in the reburn zone to avoid the problem of uneven distribution of the reburn fuel. This is a crucial requirement in studying the kinetic processes that occur in the reburn zone.

DISCUSSION

Experiments were conducted to test the insulating quality of the new combustor and to examine the extent of mixing in the reburn zone. Different injectors and injection schemes were tested and radial concentrations were measured. The purpose of the study was to identify an injection scheme that would achieve adequate mixing in the reburn zone. A well mixed reburn zone is essential in studying the kinetics of NO destruction which is the next step in this project.

Figures 1 and 2 show temperature radial profiles at different axial locations inside the combustor for a base coal burning test and a reburning test, respectively. Figure 3 compares the temperature axial profiles of the new combustor and the previous one. The data show that the furnace has good insulating quality that may be superior to that of the previous one. Temperatures exceeding 1400 C were possible at moderate coal feeds of 1.3 kg/h.

Figures 4 and 5 show radial concentrations for NO and O₂, respectively, before and after the injection of the reburn fuel. The injector that was used consisted of a water cooled stainless steel probe that could be inserted into the furnace laterally at the desired port. The injector tip was made of stainless steel tubing that was 2 cm long and had 20 holes 0.16 cm in diameter each. That allowed radial injection of the reburn fuel with respect to the axis of the injector. The radial concentrations before the injection of the reburn fuel (port 4) show even distribution of the coal inside the furnace. On the other hand, the radial concentrations after the injection of the reburn fuel (ports 6 and 7) indicate poor mixing in the reburn zone. Thus, it became necessary to modify the

injection scheme of the reburn fuel in an attempt to achieve a better mixed reburn zone.

Different tests were conducted to determine the effects of the injector hole size, the number of holes and the injection mode on the extent of mixing in the reburn zone. Radial and axial (with respect to the axis of injector) injections were tested. NO radial concentrations after the injection of the reburn fuel are shown in Figure 6. None of the tests produced sufficient mixing. Other tests were conducted in which two injectors were used, each introducing half the amount of the reburn fuel into each side of the furnace. The results are shown in Figure 7. Improved mixing conditions were obtained but the problem of poor mixing persisted at low reburn fuel feed rates as seen by the concentration profile at $SR_2=0.94$. Therefore, another alternative was needed.

Finally, tests were conducted in which nitrogen gas was used as a transport medium for the reburn fuel. The purpose of using an inert carrier was to achieve higher jet velocities. Two different hole sizes were tested and the results are shown in Figure 8. In these tests, the reburn fuel (plus carrier) was injected radially with respect to the axis of the injector. The results show that the degree of mixing is controlled by the jet velocity. The profiles of tests C and D show adequate mixing in the reburn zone. That corresponded to a jet velocity of about 15 m/s and that was about 80 times the velocity of effluent leaving the primary zone. In short, an inert gas is needed as a carrier medium for the reburn fuel to generate the necessary jet velocities that are needed to achieve a well mixed reburn zone.

Figure 9 shows the effect of reburn zone stoichiometry on NO reduction.

Nitrogen gas was used as a transport medium for the reburn fuel. The trend is similar to that in which no transport medium was used (reports 5 and 6).

However, the optimum reburn zone stoichiometry is closer to 0.9, as compared to 0.8 that was identified in earlier work. The maximum reduction in NO (75 # 5 %) is of the same order of magnitude as was seen in previous experiments. The claim that a well mixed reburn zone would result in more NO reduction cannot be made with certainty at this time and further tests would be needed.

SUMMARY AND FUTURE WORK

Temperature and concentration profiles indicate a satisfactory performance of the new combustor. To avoid insufficient mixing in the reburn zone, a reburn fuel jet velocity that is at least 80 times the velocity of the primary effluent is needed. That requires the use of an inert gas as a transport medium for the reburn fuel. This result will be used as a guide in conducting future experiments and radial concentrations will be periodically measured to verify the adequate mixing conditions in the reburn zone.

An optimum reburn zone stoichiometric ratio was detected at 0.9 when nitrogen gas was used as a transport medium for the reburn fuel. No significant difference in the reduction in NO due to improved mixing conditions in the reburn zone could be detected.

As mentioned earlier, a well mixed reburn zone is essential for the study of mechanisms of NO destruction which is next step in this research project. Different reburn fuels including hydrogen, carbon monoxide and coal will be tested. The effect of nitrogen content in the reburn fuel will also be examined.

REFERENCES

- Chen, S. L., J. M. McCarthy, W. D. Clark, M. P. Heap, W. R. Seeker and D. W. Pershing, "Bench and Pilot Scale Process Evaluation of Reburning for In-Furnace NO_x Reduction", Twenty-first Symposium (International) on Combustion, p. 1159, The Combustion Institute, Pittsburgh, Pennsylvania (1986).
- Greene, S. B., S. L. Chen, W. D. Clark, M. P. Heap, D. W. Pershing and W. R. Seeker, "Bench-Scale Process Evaluation of Reburning and Sorbent Injection for In-Furnace NO_x/SO_x Reduction", U.S. EPA Report EPA-600/7-85-012, March 1985.
- Kolb, T., P. Jansohn and W. Leuckel, "Reduction of NO_x Emission in Turbulent Combustion by Fuel-Staging / Effects of Mixing and Stoichiometry in the Reduction Zone", paper presented at the Twenty-second Symposium (International) on Combustion, The Combustion Institute, Seattle, Washington (1988).
- La Fond, J. F. and S. L. Chen, "An Investigation to Define the Physical/Chemical Constraints which Limit NO_x Emission Reduction Achievable by Reburning", U.S. DOE Quarterly Report DE-AC22-86PC91025, May 1987.
- Miyamae, S., H. Ikebe, K. Makino, K. Suzuki and J. Mogi, "Evaluation of In-Furnace NO_x Reduction", p. 24-1, Proceedings of the 1985 Joint Symposium on Stationary Combustion NO_x Control, Volume 1, EPRI Report CS-4360, January 1986.
- Myerson, A. L., "The Reduction of Nitric Oxide in Simulated Combustion Effluents by Hydrocarbon - Oxygen Mixtures", Fifteenth Symposium (International) on Combustion, p. 1085, The Combustion Institute, 1974.
- Overmoe, B. J., J. M. McCarthy, S. L. Chen, W. R. Seeker, G. D. Silcox and D. W. Pershing, "Pilot Scale Evaluation of NO_x Control from Pulverized Coal Combustion by Reburning", p. 21-1, Proceedings of the 1985 Joint Symposium on Stationary Combustion NO_x Control, Volume 1, EPRI Report CS-4360, January 1986.

FIGURE 1 . Temperature Radial Profiles

reburning: $SR1=1.2$, $SR2=0.8$ at port 5

FIGURE 2 . Temperature Radial Profile - Reburning at Port 5

FIGURE 3. Temperature Axial Profile

reburning: SR1=1.2, SR2=0.8 at port 5

FIGURE 4 . Effect of Reburn Fuel Introduction on NO Radial Concentrations

reburning: $SR1=1.2$, $SR2=0.8$ at port 5

FIGURE 5. Effect of Reburn Fuel Introduction on O₂ Radial Concentrations

reburning: SR1=1.15, SR2 at port 5

NO radial conc. different injector type

TEST A
SR2=0.91
radial inj. 20(0.02 in)

TEST B
SR2=0.85
axial inj. 28(0.02 in)

TEST C
SR2=0.80
open jet opposed to main axial 36(0.032 in)

TEST D
SR2=0.80
curved inj. radial 20(0.026 in)

TEST E
SR2=0.78
axial inj. 3.5 in tip

FIGURE 6 . Effect of Reburn Fuel Jet Momentum and Injection Mode on NO Radial Concentrations

reburning: SR1=1.15, SR2 at port 5

NO radial conc. 2 injectors, equal flow

FIGURE 7 . Effect of Reburning with Two Reburn Fuel Streams on NO Radial Concentrations

reburning: SR1=1.15, SR2 at port 5

NO radial profiles, N2 dilution

FIGURE 8. Effect of N2 as a Transort Medium for Reburn Fuel on NO Radial Concentrations

effect of SR2 on NO reduction

1.3 kg/h, SR1=1.23, NOP=1050 ppm

FIGURE 9 . Effect of Reburn Zone Stoichiometric Ratio on NO Reduction by Reburning

END

DATE
FILMED

2/11/92

I