CONF-841246--10

MATERIALS ENGINEERING FOR TFCX

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

F. W. Wiffen

FEDC/ORNL

Oak Ridge, Tennessee

CONF-841246--10

DE85 005363

ICFRM-1

Tokyo, Japan

December 3, 1984

MASTER

*Research sponsored by the Office of Fusion Energy, U.S. Department of Energy, under contract DE-AC05-84OR21400 with Martin Marietta Energy Systems, Incorporated.

gbe

TFCX

NOMINAL SUPERCONDUCTING OPTION

TFCX-S VACUUM INTERFACES

SIDE VIEW

END VIEW

ASSEMBLY DETAIL "X"

NOTES:

1. FLANGES MAY BE INCORPORATED AS A SEPARATE FLANGE PLATE
2. INTERIOR MANIFOLDING MAY PERMIT REDUCING PIPES TO ONE INLET AND 2 OUTLET

TFC COPPER TF CONFIGURATION

INTOR

TFCX

TFTR

MODULARIZED DESIGN APPROACH

AKKK-6406-029-TB-FRDC

CONDUCTOR CONFIGURATION

Nb_3Sn FORCED FLOW

Axxx-8406-026-SK-FEDC

FEATURES

SAME AS W-LCP BUT WITH THE FOLLOWING MODIFICATIONS

- INCOLOY CONDUIT - REDUCES COOLDOWN STRAIN AND INCREASES CURRENT CARRYING CAPABILITY
- LARGE HELIUM CROSS-SECTIONAL AREA - INCREASES HEAT REMOVAL CAPABILITY AND REDUCES PRESSURE DROP

TFCX-S TF WINDING CONFIGURATION

AXXX-8408-068-SK-FEDC

Winding Concepts are Feasible

(Dimensions in cm)

- Achieved Winding Current Density $\sim 3500 \text{ A/cm}^2$
- Insulation rad Dose Experienced
 - Nominal Performance 8×10^7
 - High Performance 4×10^8
- Nuclear Heat Load
 - Winding 0.36 kW Nominal 15 kW High
 - Coil Case 0.80 kW Nominal 34 kW High
- Peak Winding Temperature
 - Nominal Performance 4.5 K
 - High Performance 5.5 K
- Peak Coil Case Temperature 20 K

INBOARD SHIELD REQUIREMENTS/PERFORMANCE

ANX-6406-171-DL-FEDC

Maximum Dose in Epoxy Insulator for TF Conductor (rad)
(2×10^5 s of DT Burn Time)

INBOARD SHIELD REQUIREMENTS/PERFORMANCE

AXXX-8408-172-01-FEDC

Stainless Steel/Water Shield (80/20)

Nuclear Heating Rate to TF Conductor (mW/cm^3)
(Case Thickness is 5 cm)

SHIELD POST CONFIGURATION

Axxx-8408-078-DL-FEDC

MIDPLANE SECTION VIEW
60% SST Balls/40% Water

REQUIREMENTS

AXXX-6406-078-0F-FEDC

	<u>Nominal Performance</u>	<u>High Performance</u>
Nuclear Heating at TF Coil Winding, mW/cm^3	1	50
Dose to TF Coil Conductor Insulation (Bonded), rad	2.5×10^8	2.5×10^9
Dose to Thermal Insulation	5×10^9	5×10^{10}
Displacement Damage to Copper Stabilizer, dpa	2×10^{-4}	2×10^{-4}
Shutdown Dose Rate in Proximity of Outer Periphery of Device, mrem/h , 24 h after Shutdown	1.0	1.0

CONFIGURATION USED FOR THERMAL/MECHANICAL ANALYSIS

AXXX-8406-176-JH-FEDC

LIMITER DESIGN FEATURES EXPENDABLE PROTECTIVE SURFACE AND REUSABLE CORE

AXXX-8408-180-JH-FEDC

SIZE COMPARISON

TFTR

TFCX-S

INTOR

RF LAUNCHERS

LOWER HYBRID

ION CYCLOTRON

VACUUM SYSTEM

Limiter Design Features

BULK SHIELDING

Inboard
Intermediate
Outboard

80% SST Plate/20% Water
60% SST Balls/40% Water
100% Water

END VIEW

1.7 m TFCX-S
1.5 m TFCX+PS

6.6 m TFCX-S
5.5 m TFCX+PS

SIDE VIEW

6.0 m TFCX-S
5.3 m TFCX+PS

Material	Temperature (K)	Application	Dose Limit (rad)	
			Nominal	High Performance
Glass-Epoxy (G-10CR)	300	Bonded	5E8	5E9
		Unbonded	1E10	1E11
	4	Bonded	2.5E8	2.5E9
		Unbonded	5E9	5E10
Glass-Polyimide	300	Bonded	4E9	4E10
		Unbonded	4E11	1E12
	4	Bonded	2E9	2E10
		Unbonded	2E11	5E11
Ceramic (MgAl ₂ O ₄)	300	Coating	>2 × 10 ²² neutrons/cm ²

Parameter	Superconducting		Copper	
	Nominal	Hi Perf.	Nominal	Hi Perf.
MAJOR RADIUS (m)	4.08	3.61	3.35	2.60
MINOR RADIUS (m)	1.52	1.30	1.30	1.04
ASPECT RATIO	2.69	2.77	2.58	2.49
FIELD ON AXIS (T)	3.73	4.23	4.00	4.50
INBOARD SHIELDING (m)	0.62	0.36	0.12	0.015
FUSION POWER (MW)	267	270	229	197
WALL LOAD (MWm ⁻²)	0.69	0.92	0.85	1.17
PLASMA CURRENT (MA)	11.2	10.5	10.9	10.4
PULSE LENGTH (sec.)	€18	452	458	298
LHRF POWER (MW)	32	26	26	19
ICRF POWER Initial/Final (MW)	6/31	10/36	7/28	7/26
TF/ PF PWR (MW)	—	—	405/51	333/108
BETA (%)	5.51	5.35	5.76	5.95
IGN MIRNOV	1.5	1.5	1.5	1.5

(16) TF Coil And Case

OVERALL F. E. A. SIMULATION