AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**FOURTH QUARTER 1992
AND 1992 SUMMARY**

K-AREA ACID/CAUSTIC BASIN GROUNDWATER MONITORING REPORT (U)

KEY WORDS

hazardous waste
iron
KAC wells
specific conductance
sulfate

PUBLICATION DATE: MARCH 1993

Authorized Derivative Classifier:

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

123014

Abstract

During fourth quarter 1992, samples from the KAC monitoring wells at the K-Area Acid/Caustic Basin were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. New wells KAC 8 and 9 also were sampled for GC/MS VOA (gas chromatograph/mass spectrometer volatile organic analyses). Monitoring results that exceeded the final Primary Drinking Water Standards (PDWS) or the Savannah River Site (SRS) flagging criteria or turbidity standard during the quarter are discussed in this report.

Iron exceeded the Flag 2 criterion in wells KAC 6 and 7, and specific conductance exceeded the Flag 2 criterion in new well KAC 9. No samples exceeded the SRS turbidity standard.

Contents

	Page
Abstract	iii
List of Figures	vii
List of Tables	vii
Executive Summary	1
Introduction	2
Discussion	3
Groundwater Monitoring Data	3
Analytical Results Exceeding Standards	4
Turbidity Results Exceeding Standards	5
Water Elevations, Flow Directions, and Flow Rates	5
Results for Upgradient vs. Downgradient Wells	6
Conclusions	7
1992 Summary	8
Errata	9
References Cited	10
Appendix A – Final Primary Drinking Water Standards	A-1
Appendix B – Flagging Criteria	B-1
Appendix C – Figures	C-1
Appendix D – Groundwater Monitoring Results Tables	D-1
Appendix E – Data Quality/Useability Assessment	E-1

List of Figures

	Page
1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site	C-2
2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin	C-3
3. Water-Elevation Contour Map of the Water Table at the K-Area Acid/Caustic Basin	C-4

List of Tables

	Page
1. Constituents Exceeding Final Primary Drinking Water Standards in 1992	D-5
2. Constituents Exceeding Half the Final Primary Drinking Water Standard or Other Flag 1 or Flag 2 Criteria	D-5
3. Groundwater Monitoring Results for Individual Wells	D-6

Executive Summary

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the Savannah River Site (SRS) Groundwater Monitoring Program and to comply with the terms of a consent decree executed May 26, 1988, by the U.S. District Court (District of South Carolina, Aiken Division). During fourth quarter 1992, samples from the monitoring wells were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. Monitoring results that exceeded final Primary Drinking Water Standards (PDWS), other SRS flagging criteria, or the SRS turbidity standard are discussed in this report.

During fourth quarter 1992, wells KAC 6 and 7 at the K-Area Acid/Caustic Basin did not meet the purging and stabilization criteria for representative groundwater samples. Iron exceeded the Flag 2 criterion in wells KAC 6 and 7, and specific conductance exceeded the Flag 2 criterion in new well KAC 9. No samples exceeded the SRS turbidity standard.

Water-table elevations indicate that the groundwater flow direction is northwest (using SRS grid coordinates) at approximately 800 ft/yr.

Introduction

The K-Area Acid/Caustic Basin is located in the eastern portion of K Area at the Savannah River Site (SRS) near a tributary of Pen Branch. The basin, constructed in the early 1950s, is an unlined earthen pit that received dilute sulfuric acid and sodium hydroxide solutions and other wastes from several areas within SRS. The basin provided an area for the mixing and neutralization of the dilute solutions before their discharge to nearby streams. The K-Area Acid/Caustic Basin remained in service until new neutralization facilities became operational in 1982 (Heffner and Exploration Resources, 1991).

Four groundwater monitoring wells were installed at the K-Area Acid/Caustic Basin between October 1983 and July 1984. Under the terms of a consent decree executed May 26, 1988, by the U.S. District Court (District of South Carolina, Aiken Division), the basin became subject to requirements of Subtitle C of the Resource Conservation and Recovery Act (RCRA), the South Carolina Hazardous Waste Management Regulations (SCHWMR), and associated regulations. The basin monitoring wells were reevaluated during the summer of 1988 to ensure compliance with SCHWMR. As part of this compliance effort, three additional wells were installed at the K-Area Acid/Caustic Basin during third quarter 1988.

The revised Groundwater Quality Assessment Plan (WSRC, 1991), submitted to the South Carolina Department of Health and Environmental Control on April 30, 1991, proposed the installation of two additional water-table wells at the K-Area Acid/Caustic Basin. These wells, KAC 8 and 9, have been installed and were first sampled during second quarter 1992.

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the SRS Groundwater Monitoring Program and to comply with the consent decree.

Discussion

Groundwater Monitoring Data

The groundwater sampling procedure was modified beginning fourth quarter 1992 in response to regulatory guidance and advances in sampling equipment design (WSRC, 1992). The modified procedure requires evacuation of a minimum of two well volumes and stabilization of pH, specific conductance, and turbidity prior to sample collection. Stability is established when a minimum of three successive measurements, taken within a given time period, are within a specified tolerance range. If a well pumps dry before two well volumes are purged or before stabilization is achieved, it must be revisited within 24 hours for the data to be considered from a single sampling event. On the second visit within 24 hours, samples are taken without purging or stability measurements; thus, these samples may not be representative of the groundwater quality.

A further modification in the procedure is that samples collected for metals analyses are not filtered. Thus, the analyses are for total metals rather than dissolved metals. Variable-speed pumps have been installed in some wells in specific areas that have had a history of elevated metals. Samples from these wells are collected at a slower rate to minimize turbidity, which has been associated with elevated metal levels. Decreased aluminum and iron concentrations as well as lower turbidity values have been observed for samples from wells with variable-speed pumps. At present, well KAC 1 has a variable-speed pump.

During fourth quarter 1992, samples from the monitoring wells at the K-Area Acid/Caustic Basin were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. New wells KAC 8 and 9 also were sampled for GC/MS VOA (gas chromatograph/mass spectrometer volatile organics analyses).

This report describes monitoring results that exceeded the Safe Drinking Water Act final Primary Drinking Water Standards (PDWS) set by the U.S. Environmental Protection Agency (EPA) (Appendix A), the South Carolina final Primary Drinking Water Standard for lead (Appendix A), other SRS flagging criteria (Appendix B), or the SRS turbidity standard.

The drinking water standard for lead was changed to the South Carolina Primary Drinking Water Standard of 50 $\mu\text{g/L}$ fourth quarter 1992. Lead data for the earlier quarters of 1992 were made consistent with the 50 $\mu\text{g/L}$ standard for this annual report. The SRS flagging criteria are based on final and proposed PDWS, Secondary Drinking Water Standards, and method detection limits. For simplicity, results that either equal or exceed standards are described only as *exceeding* or *above* standards. Constituent levels that exceed the final PDWS, screening levels, or Flag 2 criteria are described as *elevated*, and constituent levels that exceed Flag 1 criteria are described as *slightly elevated*.

The final PDWS for individual analytes provided in Appendix A may not always match the SRS flagging criteria provided in Appendix B. The final PDWS are used as guidelines in this compliance report to meet regulatory requirements; the flagging criteria are used by EPD/EMS to identify relative levels of constituents in the groundwater and as guides for scheduling groundwater sampling.

Illustrations of the monitored unit at SRS (Figure 1), the individual monitoring wells (Figure 2), and the flow directions of the groundwater beneath the unit (Figure 3) are in Appendix C; monitoring results as well as analyses that exceeded holding times, the final PDWS, other flagging criteria, or the turbidity standard are presented in Appendix D; and a discussion of data quality and useability is in Appendix E.

Analytical Results Exceeding Standards

Results for any analytes that exceeded the final PDWS (see Appendix A) during fourth quarter 1992 are summarized in Table 1 (Appendix D).

Constituents that exceeded other Flag 1 or Flag 2 criteria (see Appendix B) during fourth quarter 1992 are summarized in Table 2 (Appendix D). Iron exceeded the Flag 2 criterion in wells KAC 6 and 7, with a maximum concentration of 1,800 $\mu\text{g/L}$. Specific conductance exceeded the Flag 2 criterion in well KAC 9 at 692 $\mu\text{S/cm}$.

Table 3 (Appendix D) presents all of the results for individual wells and indicates those analyses that exceeded holding times or the final PDWS. Table 3 also lists the number of well volumes purged from each well during fourth quarter 1992 at the K-Area Acid/Caustic Basin. Wells KAC 6 and 7 each failed to yield enough water to meet the purging and stabilization criteria. They were sampled later that day. The samplers noted that the water from well KAC 6 was brown, which is consistent with a high iron content.

Constituent results are compared with the PDWS in the database of values reported by the laboratory. Many constituents are reported to more significant digits in the database than in these reports. Thus, some constituent results in Table 3 that appear to equal the PDWS are not marked in the *D* column. Those results are below the PDWS in the database.

Some of the values for earlier quarters presented in the results tables of this report may differ from the values for those same quarters presented in previous reports, and reported values may not match reported sample dates. These differences result from the following: (1) the computer program that creates the analytical results tables was revised beginning second quarter 1992 to present the highest value for analytes with more than one result (previously, the program presented the first value encountered in the database); (2) a new computer program, which rounds numbers differently from the former computer program, was first used during third quarter 1992; and (3) some reanalyses may have been performed by the laboratories after the quarterly reports had gone to press. The sample dates in the tables are the dates when the field data were collected. These dates may differ from the dates of the laboratory analyses if the highest results were obtained for samples collected on different dates.

Turbidity Results Exceeding Standards

During fourth quarter 1992, wells KAC 1, 2, 3, 4, 5, 8, and 9 had turbidity values of less than 5 nephelometric turbidity units (NTU). Wells KAC 6 and 7 had values above 5 NTU but did not exceed the SRS standard of 50 NTU.

A value of 5 NTU, established by EPA (1986) as a general standard for acceptability of groundwater samples, is considered unrealistic for monitoring wells at SRS. Gass (1989) has documented turbidity measurements ranging up to 5,000 NTU from properly designed wells screened in poorly productive formations. During the 1989 RCRA Compliance Evaluation Inspection, officials from EPA Region IV indicated that the SRS turbidity standard of 50 NTU is conservative. These officials also agreed that water-table wells in this area often correspond to nonaquifer formations, rendering development of these wells more difficult due to the low yield and high proportion of mobile fines typical of these formations (Bergren and Bennett, 1989).

Water Elevations, Flow Directions, and Flow Rates

Water-table elevations and the groundwater flow direction beneath the K-Area Acid/Caustic Basin are shown in Figure 3 (Appendix C). Historical data indicate a ponding or losing stream effect (water entering the groundwater from the K-Area outfall effluent stream) in this area, creating a mound of groundwater to the east of the basin. Water-table elevations from this quarter, using data from KAC 8 and 9 (installed first quarter 1992) for the first time, indicate that the groundwater flow direction is northwest (using SRS grid coordinates). Determinations made over the past several years without wells KAC 8 and 9 consistently have indicated a direction of southwest or west-southwest.

The screens in wells KAC 4, 8, and 9 are submerged; thus, contours based on water elevations from these wells might not accurately depict water-table conditions.

The groundwater flow rate in the water table beneath the K-Area Acid/Caustic Basin is estimated using the following equation:

$$\text{Flow (ft/day)} = \frac{\text{Hydraulic Conductivity (ft/day)}}{\text{Porosity (unitless)}} \times \frac{dh \text{ (ft)}}{dl \text{ (ft)}}$$

A hydraulic conductivity constant of 4 ft/day is based on recent hydrogeological studies for this location (Atlanta Testing and Engineering, 1992). The effective porosity value is estimated at 20% (Killian et al., 1987), dh is the difference in head, and dl is the length of the flow path. Flow rate estimates vary depending on the vertical gradient between wells, the size of the area under consideration, and the number of data points. For this reason, the estimation of flow rate must be considered accurate only to an order of magnitude.

Flow rate estimates are calculated as follows: flow path length is calculated to the nearest foot. Flow rate per day is calculated to two significant figures using the above equation. This value is then multiplied by 365 and rounded to two significant figures for the flow rate per year.

Using the above equation with $dh = 9$ ft and $dl = 82$ ft (see Figure 3, Appendix C), the flow rate estimate for groundwater in the water table beneath the K-Area Acid/Caustic Basin is as follows:

$$\frac{4}{0.20} \times \frac{9}{82} = 2.2 \text{ ft/day}$$

$$2.2 \text{ ft/day} \times 365 \text{ days} \approx 800 \text{ ft/yr}$$

Results for Upgradient vs. Downgradient Wells

Wells KAC 3 and 5 are the designated upgradient wells. No constituents exceeded the final PDWS or other flagging criteria in these wells. Iron exceeded the Flag 2 criterion in wells KAC 6 and 7, and specific conductance exceeded the Flag 2 criterion in well KAC 9.

Conclusions

Iron exceeded the Flag 2 criterion in designated downgradient wells KAC 6 and 7, and specific conductance exceeded the Flag 2 criterion in new downgradient well KAC 9. Generally, constituents found in downgradient wells but not upgradient wells at a waste management unit are considered products of the waste management unit.

Wells KAC 1, 2, 3, 4, 5, 8, and 9 had turbidity values of less than 5 NTU. Wells KAC 6 and 7, which did not yield two well volumes prior to sampling, did not exceed the 50 NTU standard.

Water-table elevations at the K-Area Acid/Caustic Basin, using data for the first time from wells KAC 8 and 9, indicate that groundwater flow is toward the northwest relative to SRS grid coordinates; determinations without these two wells indicate that flow direction is southwest or south-southwest. The screens in wells KAC 4, 8, and 9 are submerged and may provide anomalous water-level data.

1992 Summary

Two new monitoring wells, KAC 8 and 9, were installed at the K-Area Acid/Caustic Basin during first quarter 1992.

During 1992, no constituents exceeded the final PDWS in the KAC wells. The 1991 results for these wells are similar except lead exceeded the South Carolina final Primary Drinking Water Standard of 50 $\mu\text{g/L}$ in well KAC 7 at 76 $\mu\text{g/L}$ during the first quarter.

Water-elevation data prior to fourth quarter 1992 indicated that groundwater flow direction is generally to the southwest. During 1991, the rate of flow ranged from approximately 280 ft/yr to 730 ft/yr. Estimates from first through third quarters 1992 ranged from 160 ft/yr to 300 ft/yr. During fourth quarter 1992, flow direction and rate were determined using newly installed wells KAC 8 and 9. These data indicated that groundwater flow is toward the northwest at approximately 800 ft/yr. The screens in wells KAC 4, 8, and 9 are submerged and may provide anomalous water-level data.

Errata

First Quarter 1992:

- No errata have been reported.

Second Quarter 1992:

- No errata have been reported.

Third Quarter 1992:

- Prior to third quarter 1992, the results of certain analyses for *nitrate-nitrite as nitrogen* were reported incorrectly by the General Engineering laboratory as *nitrate as nitrogen* results. The analyses in the results tables of this report are reported correctly (*nitrate-nitrite* results have been separated from true *nitrate* results).

References Cited

Atlanta Testing & Engineering, 1992. **Hydrogeology of the F-Area and K-Area Acid Caustic Basins, Savannah River Site**, WSRC-RP-91504. Westinghouse Savannah River Company, Aiken, SC.

Bergren, C. L., and C. B. Bennett, 1989. **Assessment of SRS Groundwater Monitoring Wells Impacted by Turbidity**, WSRC-RP-89-891. Westinghouse Savannah River Company, Aiken, SC.

EPA (U.S. Environmental Protection Agency), 1986. **RCRA Ground Water Monitoring Technical Enforcement Guidance Document**, OSWER-9950.1. Washington, DC.

Gass, T. E., 1989. *Monitoring Wells in Non-Aquifer Formations*. **Water Well Journal** 43(2):27-29.

Heffner, J. D., and Exploration Resources, Inc., 1991. **Technical Summary of Groundwater Quality Protection Program at the Savannah River Site (1952-1986), Volume I - Site Geohydrology and Waste Sites**, DPSP-88-1002. Westinghouse Savannah River Company, Aiken, SC.

Killian, T. H., N. L. Kolb, P. Corbo, and I. W. Marine, 1987. **F-Area Seepage Basins**, DPST-85-704. Savannah River Laboratory, E. I. du Pont de Nemours & Company, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1991. **F-, H-, K-, and P-Area Acid/Caustic Basins Groundwater Quality Assessment Plan**, WSRC-TR-91-178, Revision 1.0. Westinghouse Savannah River Company, Aiken, SC.

WSRC, 1992. **Hydrogeologic Data Collection Procedures and Specifications: Sampling Groundwater Monitoring Wells**, Manual 3Q5, Chapter 14, Revision 0. Environmental Protection Department, Environmental Monitoring Section, Savannah River Site, Aiken, SC.

Appendix A – Final Primary Drinking Water Standards

Final Primary Drinking Water Standards

<u>Analyte</u>	<u>Unit</u>	<u>Level</u>	<u>Status</u>	<u>Reference</u>
Arsenic	µg/L	50	Final	CFR, 1991
Barium	µg/L	2,000	Final	CFR, 1991
Benzene	µg/L	5	Final	CFR, 1991
Bromodichloromethane	µg/L	100 ^a	Final	CFR, 1991
Bromoform	µg/L	100 ^a	Final	CFR, 1991
Cadmium	µg/L	5	Final	CFR, 1991
Carbon tetrachloride	µg/L	5	Final	CFR, 1991
Chlordane	µg/L	2	Final	CFR, 1991
Chloroethene (Vinyl chloride)	µg/L	2	Final	CFR, 1991
Chloroform	µg/L	100 ^a	Final	CFR, 1991
Chromium	µg/L	100	Final	CFR, 1991
Copper	µg/L	1,300	Final	CFR, 1991
Dibromochloromethane	µg/L	100 ^a	Final	CFR, 1991
Dibromochloropropane	µg/L	0.2	Final	CFR, 1991
1,2-Dichlorobenzene	µg/L	600	Final	CFR, 1991
1,4-Dichlorobenzene	µg/L	75	Final	CFR, 1991
1,2-Dichloroethane	µg/L	5	Final	CFR, 1991
1,1-Dichloroethylene	µg/L	7	Final	CFR, 1991
cis-1,2-Dichloroethylene	µg/L	70	Final	CFR, 1991
trans-1,2-Dichloroethylene	µg/L	100	Final	CFR, 1991
2,4-Dichlorophenoxyacetic acid	µg/L	70	Final	CFR, 1991
1,2-Dichloropropane	µg/L	5	Final	CFR, 1991
Endrin	µg/L	0.2	Final	CFR, 1991
Ethylbenzene	µg/L	700	Final	CFR, 1991
Fluoride	µg/L	4,000	Final	CFR, 1991
Gross alpha ^b	pCi/L	1.5E + 01	Final	CFR, 1991
Heptachlor	µg/L	0.4	Final	CFR, 1991
Heptachlor epoxide	µg/L	0.2	Final	CFR, 1991
Lead	µg/L	50	Final	SCDHEC, 1981
Lindane	µg/L	0.2	Final	CFR, 1991
Mercury	µg/L	2	Final	CFR, 1991
Methoxychlor	µg/L	40	Final	CFR, 1991
Nitrate as nitrogen	µg/L	10,000	Final	CFR, 1991
Nitrate-nitrite as nitrogen	µg/L	10,000	Final	CFR, 1991
Nitrite as nitrogen	µg/L	1,000	Final	CFR, 1991
Nonvolatile beta ^c	pCi/L	5E + 01	Final	EPA, 1977
PCBs ^d	µg/L	0.5	Final	CFR, 1991
Pentachlorophenol	µg/L	1	Final	CFR, 1991
Selenium	µg/L	50	Final	CFR, 1991
Strontium-89/90 ^e	pCi/L	8E + 00	Final	CFR, 1991
Strontium-90	pCi/L	8E + 00	Final	CFR, 1991
Styrene	µg/L	100	Final	CFR, 1991
Tetrachloroethylene	µg/L	5	Final	CFR, 1991
Toluene	µg/L	1,000	Final	CFR, 1991
Total radium (Radium-226 and -228)	pCi/L	5E + 00	Final	CFR, 1991
Total trihalomethanes	µg/L	100	Final	CFR, 1991
Toxaphene	µg/L	3	Final	CFR, 1991
2,4,5-TP (Silvex)	µg/L	50	Final	CFR, 1991
1,1,1-Trichloroethane	µg/L	200	Final	CFR, 1991

<u>Analyte</u>	<u>Unit</u>	<u>Level</u>	<u>Status</u>	<u>Reference</u>
Trichloroethylene	µg/L	5	Final	CFR, 1991
Tritium	pCi/mL	2E + 01	Final	CFR, 1991
Xylenes	µg/L	10,000	Final	CFR, 1991

Note: The drinking water standard for lead was changed to the South Carolina Primary Drinking Water Standard of 50 µg/L fourth quarter 1992.

- ^a This value is the drinking water standard for total trihalomethanes (the sum of bromoform, bromodichloromethane, chloroform, and dibromochloromethane).
- ^b The standard given is for gross alpha including radium-226 but excluding radon and uranium.
- ^c This is the screening level above which providers of public drinking water should perform analyses for specific man-made radionuclides. The standard for the total dose equivalent from all such radionuclides is 4 mrem per year.
- ^d Analyses were conducted in 1992 for the following: PCB 1016, PCB 1221, PCB 1232, PCB 1242, PCB 1248, PCB 1254, and PCB 1260.
- ^e For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

References

CFR (Code of Federal Regulations), 1991. *National Primary Drinking Water Regulations*, 40 CFR, Part 141, pp. 578-715. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. *National Interim Primary Drinking Water Regulations*, EPA-570/9-76-003. Washington, DC.

SCDHEC (South Carolina Department of Health and Environmental Control), 1981. *State Primary Drinking Water Regulations*, R.61-58.5. Columbia, SC.

Appendix B – Flagging Criteria

Flagging Criteria

Beginning in 1991, the Savannah River Site Environmental Protection Department/Environmental Monitoring Section modified its guidelines for flagging constituents in the Groundwater Monitoring Program. These flagging criteria are as follows:

- Flag 2 criteria for constituents equal the Safe Drinking Water Act (SDWA) final Primary Drinking Water Standard (PDWS), the SDWA proposed PDWS, or the SDWA Secondary Drinking Water Standard (SDWS). If a constituent does not have a drinking water standard, the Flag 2 criterion equals 10 times the method detection limit (MDL) calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 1 criteria for constituents equal one-half of the final PDWS, one-half the proposed PDWS, or one-half the SDWS. If a constituent does not have an drinking water standard, the Flag 1 criterion equals 5 times the MDL calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 0 criteria are assigned to constituent levels below Flag 1 criteria, constituent levels below the sample detection limits, or constituents having no flagging criteria.

The following parameters are not assigned flagging criteria: alkalinity, calcium, carbonate, color, corrosivity, magnesium, odor, potassium, Eh, silica, sodium, total dissolved solids, total phosphorus, total phosphates (as P), and turbidity. In addition, common laboratory contaminants and cleaners including phthalates, methylene chloride, ketones, and toluene are not assigned flagging criteria.

<u>Analyte</u>	<u>Unit</u>	<u>Flag 1</u>	<u>Flag 2</u>	<u>Source</u>
Acenaphthene	µg/L	50	100	EPA Method 8270
Acenaphthylene	µg/L	50	100	EPA Method 8270
Acetone	µg/L	50	100	EPA Method 8240
Acetonitrile (Methyl cyanide)	µg/L	500	1,000	EPA Method 8240
Acetophenone	µg/L	50	100	EPA Method 8270
2-Acetylaminofluorene	µg/L	50	100	EPA Method 8270
Acrolein	µg/L	100	200	EPA Method 8240
Acrylonitrile	µg/L	100	200	EPA Method 8240
Aldrin	µg/L	2.5	5	EPA Method 8080
Alkalinity (as CaCO ₃)		No flag	No flag	Set by EPD/EMS
Allyl chloride	µg/L	250	500	EPA Method 8240
Aluminum	µg/L	25	50	Secondary DWS (CFR, 1991b)
Americium-241	pCi/L	3.17E+00	6.34E+00	Proposed DWS (EPA, 1991)
Americium-243	pCi/L	3.19E+00	6.37E+00	Proposed DWS (EPA, 1991)
4-Aminobiphenyl	µg/L	50	100	EPA Method 8270
Ammonia	µg/L	500	1,000	APHA Method 417B
Ammonia nitrogen	µg/L	50	100	EPA Method 350.1
Aniline	µg/L	50	100	EPA Method 8270
Anthracene	µg/L	50	100	EPA Method 8270
Antimony	µg/L	2.5	5	Proposed DWS (EPA, 1990)
Antimony-125	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Aramite	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
Arsenic	µg/L	25	50	Final DWS (CFR, 1991a)
Barium	µg/L	1,000	2,000	Final DWS (CFR, 1991a)
Barium-140	pCi/L	4.5E+01	9E+01	Final DWS (EPA, 1977)
Benzene	µg/L	2.5	5	Final DWS (CFR, 1991a)
alpha-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
beta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
delta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
Benzidine	µg/L	250	500	EPA Method 8270
Benzo[a]anthracene	µg/L	0.05	0.1	Proposed DWS (EPA, 1990)
Benzo[b]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzo[k]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzo[g,h,i]perylene	µg/L	50	100	EPA Method 8270
Benzo[a]pyrene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzoic acid	µg/L	250	500	EPA Method 8270
1,4-Benzoquinone	µg/L	50	100	EPA Method 8270
Benzyl alcohol	µg/L	100	200	EPA Method 8270
Beryllium	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Beryllium-7	pCi/L	3E+03	6E+03	Final DWS (EPA, 1977)
Bis(2-chloroethoxy) methane	µg/L	50	100	EPA Method 8270
Bis(2-chloroethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-chloroisopropyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl-ethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-ethylhexyl) phthalate		No flag	No flag	Set by EPD/EMS
Bromide	µg/L	5,000	10,000	EPA Method 300.0
Bromodichloromethane	µg/L	50	100	Final DWS (CFR, 1991a)
Bromoform	µg/L	50	100	Final DWS (CFR, 1991a)
Bromomethane (Methyl bromide)	µg/L	5	10	EPA Method 8240
4-Bromophenyl phenyl ether	µg/L	50	100	EPA Method 8270
2-sec-Butyl-4,6-dinitrophenol	µg/L	3.5	7	Proposed DWS (EPA, 1990)
Butylbenzyl phthalate		No flag	No flag	Set by EPD/EMS
Cadmium	µg/L	2.5	5	Final DWS (CFR, 1991a)
Calcium		No flag	No flag	Set by EPD/EMS
Carbon disulfide	µg/L	5	10	EPA Method 8240
Carbon tetrachloride	µg/L	2.5	5	Final DWS (CFR, 1991a)
Carbon-14	pCi/L	1E+03	2E+03	Final DWS (EPA, 1977)
Carbonate	µg/L	500	1,000	EPA Method 310.1
Cerium-141	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Cerium-144	pCi/L	1.31E+02	2.61E+02	Proposed DWS (EPA, 1991)
Cesium-134	pCi/L	4.07E+01	8.13E+01	Proposed DWS (EPA, 1991)
Cesium-137	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Chlordane	µg/L	1	2	Final DWS (CFR, 1991a)
Chloride	µg/L	125,000	250,000	Secondary DWS (CFR, 1991b)
4-Chloroaniline	µg/L	50	100	EPA Method 8270
Chlorobenzene	µg/L	5	10	EPA Method 8240
Chlorobenzilate	µg/L	50	100	EPA Method 8270
Chloroethane	µg/L	5	10	EPA Method 8240
Chloroethene (Vinyl chloride)	µg/L	1	2	Final DWS (CFR, 1991a)
Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
2-Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
Chloroform	µg/L	50	100	Final DWS (CFR, 1991a)
para-Chloro-meta-cresol	µg/L	50	100	EPA Method 8270
Chloromethane (Methyl chloride)	µg/L	5	10	EPA Method 8240
2-Chloronaphthalene	µg/L	50	100	EPA Method 8240
2-Chlorophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
4-Chlorophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Chloroprene	µg/L	1,000	2,000	EPA Method 8240
Chromium	µg/L	50	100	Final DWS (CFR, 1991a)
Chromium-51	pCi/L	3E+03	6E+03	Final DWS (EPA, 1977)
Chrysene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Cobalt	µg/L	20	40	EPA Method 6010
Cobalt-57	pCi/L	5E+02	1E+03	Final DWS (EPA, 1977)
Cobalt-58	pCi/L	4.5E+03	9E+03	Final DWS (EPA, 1977)
Cobalt-60	pCi/L	5E+01	1E+02	Final DWS (EPA, 1977)
Color		No flag	No flag	Set by EPD/EMS
Copper	µg/L	650	1,300	Final DWS (CFR, 1991a)
Corrosivity		No flag	No flag	Set by EPD/EMS
m-Cresol (3-Methylphenol)	µg/L	50	100	EPA Method 8270
o-Cresol (2-Methylphenol)	µg/L	50	100	EPA Method 8270
p-Cresol (4-Methylphenol)	µg/L	50	100	EPA Method 8270
Curium-242	pCi/L	6.65E+01	1.33E+02	Proposed DWS (EPA, 1991)
Curium-243	pCi/L	4.15E+00	8.3E+00	Proposed DWS (EPA, 1991)
Curium-244	pCi/L	4.92E+00	9.84E+00	Proposed DWS (EPA, 1991)
Curium-246	pCi/L	3.14E+00	6.27E+00	Proposed DWS (EPA, 1991)
Cyanide	µg/L	100	200	Proposed DWS (EPA, 1990)
p,p'-DDD	µg/L	2.5	5	EPA Method 8080
p,p'-DDE	µg/L	2.5	5	EPA Method 8080
p,p'-DDT	µg/L	2.5	5	EPA Method 8080
Di-n-butyl phthalate		No flag	No flag	Set by EPD/EMS
Di-n-octyl phthalate		No flag	No flag	Set by EPD/EMS
Diallate	µg/L	50	100	EPA Method 8270
Dibenz[a,h]anthracene	µg/L	0.15	0.3	Proposed DWS (EPA, 1990)
Dibenzofuran	µg/L	50	100	EPA Method 8270
Dibromochloromethane	µg/L	50	100	Final DWS (CFR, 1991a)
Dibromochloropropane	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
1,2-Dibromo-3-chloropropane	µg/L	250	500	EPA Method 8240
1,2-Dibromoethane	µg/L	100	200	EPA Method 8240
Dibromomethane (Methylene bromide)	µg/L	5	10	EPA Method 8240
1,2-Dichlorobenzene	µg/L	300	600	Final DWS (CFR, 1991a)
1,3-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,4-Dichlorobenzene	µg/L	37.5	75	Final DWS (CFR, 1991a)
3,3'-Dichlorobenzidine	µg/L	50	100	EPA Method 8270
trans-1,4-Dichloro-2-butene	µg/L	150	300	EPA Method 8240
Dichlorodifluoromethane	µg/L	5	10	EPA Method 8240
1,1-Dichloroethane	µg/L	5	10	EPA Method 8240
1,2-Dichloroethane	µg/L	2.5	5	Final DWS (CFR, 1991a)
cis-1,2-Dichloroethene	µg/L	35	70	Final DWS (CFR, 1991a)
1,1-Dichloroethylene	µg/L	3.5	7	Final DWS (CFR, 1991a)
1,2-Dichloroethylene	µg/L	25	50	EPA Method 8240
trans-1,2-Dichloroethylene	µg/L	50	100	Final DWS (CFR, 1991a)
Dichloromethane (Methylene chloride)		No flag	No flag	Set by EPD/EMS
2,4-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,6-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,4-Dichlorophenoxyacetic acid	µg/L	35	70	Final DWS (CFR, 1991a)
1,2-Dichloropropane	µg/L	2.5	5	Final DWS (CFR, 1991a)
cis-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
trans-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
Dieldrin	µg/L	2.5	5	EPA Method 8080

Analyte	Unit	Flag 1	Flag 2	Source
Diethyl phthalate		No flag	No flag	Set by EPD/EMS
Dimethoate	µg/L	50	100	EPA Method 8270
p-Dimethylaminoazobenzene	µg/L	50	100	EPA Method 8270
p-(Dimethylamino)ethylbenzene	µg/L	50	100	EPA Method 8270
7,12-Dimethylbenz[a]anthracene	µg/L	50	100	EPA Method 8270
3,3'-Dimethylbenzidine	µg/L	50	100	EPA Method 8270
a,a-Dimethylphenethylamine	µg/L	50	100	EPA Method 8270
2,4-Dimethyl phenol	µg/L	50	100	EPA Method 8270
Dimethyl phthalate		No flag	No flag	Set by EPD/EMS
1,3-Dinitrobenzene	µg/L	50	100	EPA Method 8270
4,6-Dinitro-ortho-cresol	µg/L	250	500	EPA Method 8270
2,4-Dinitrophenol	µg/L	250	500	EPA Method 8270
2,4-Dinitrotoluene	µg/L	50	100	EPA Method 8270
2,6-Dinitrotoluene	µg/L	50	100	EPA Method 8270
1,4-Dioxane	µg/L	50	100	EPA Method 8270
Diphenylamine	µg/L	50	100	EPA Method 8270
1,2-Diphenylhydrazine	µg/L	50	100	EPA Method 8270
Dissolved organic carbon	µg/L	5,000	10,000	EPA Method 9060
Disulfoton	µg/L	50	100	EPA Method 8270
Eh		No flag	No flag	Set by EPD/EMS
alpha-Endosulfan	µg/L	50	100	EPA Method 8270
beta-Endosulfan	µg/L	50	100	EPA Method 8270
Endosulfan I	µg/L	2.5	5	EPA Method 8080
Endosulfan II	µg/L	2.5	5	EPA Method 8080
Endosulfan sulfate	µg/L	2.5	5	EPA Method 8080
Endrin	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Endrin aldehyde	µg/L	2.5	5	EPA Method 8080
Endrin ketone		No flag	No flag	Set by EPD/EMS
Ethyl methacrylate	µg/L	50	100	EPA Method 8270
Ethyl methanesulfonate	µg/L	50	100	EPA Method 8270
Ethylbenzene	µg/L	350	700	Final DWS (CFR, 1991a)
Europium-154	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Europium-155	pCi/L	3E+02	6E+02	Final DWS (EPA, 1977)
Famphur	µg/L	50	100	EPA Method 8270
Fluoranthene	µg/L	50	100	EPA Method 8270
Fluorene	µg/L	50	100	EPA Method 8270
Fluoride	µg/L	2,000	4,000	Final DWS (CFR, 1991a)
Gross alpha	pCi/L	7.5E+00	1.5E+01	Final DWS (CFR, 1991a)
Heptachlor	µg/L	0.2	0.4	Final DWS (CFR, 1991a)
Heptachlor epoxide	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Heptachlorodibenzo-p-dioxin isomers	µg/L	0.00325	0.0065	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p-dioxin	µg/L	0.00325	0.0065	EPA Method 8280
Heptachlorodibenzo-p-furan isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p-furan	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorobenzene	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Hexachlorobutadiene	µg/L	50	100	EPA Method 8270
Hexachlorocyclopentadiene	µg/L	25	50	Proposed DWS (EPA, 1990)
Hexachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,7,8-Hexachlorodibenzo-p-dioxin	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280

Analyte	Unit	Flag 1	Flag 2	Source
1,2,3,4,7,8-Hexachlorodibenzo-p-furan	µg/L	0.002	0.004	EPA Method 8280
Hexachloroethane	µg/L	50	100	EPA Method 8270
Hexachlorophene	µg/L	250	500	EPA Method 8270
Hexachloropropene	µg/L	50	100	EPA Method 8270
2-Hexanone	µg/L	100	200	EPA Method 8240
Indeno[1,2,3-c,d]pyrene	µg/L	50	100	EPA Method 8270
Iodine	µg/L	500	1,000	EPA Method 415
Iodine-129	pCi/L	5E-01	1E+00	Final DWS (EPA, 1977)
Iodine-131	pCi/L	1.5E+00	3E+00	Final DWS (EPA, 1977)
Iodomethane (Methyl iodide)	µg/L	75	150	EPA Method 8240
Iron	µg/L	150	300	Secondary DWS (CFR, 1991b)
Iron-55	pCi/L	1E+03	2E+03	Final DWS (EPA, 1977)
Iron-59	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Isobutyl alcohol	µg/L	500	1,000	EPA Method 8240
Isodrin	µg/L	50	100	EPA Method 8270
Isophorone	µg/L	50	100	EPA Method 8270
Isosafrole	µg/L	50	100	EPA Method 8270
Kepone	µg/L	50	100	EPA Method 8270
Lanthanum-140	pCi/L	3E+01	6E+01	Final DWS (EPA, 1977)
Lead	µg/L	7.5	15	Final DWS (CFR, 1991a)
Lindane	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Lithium	µg/L	25	50	EPA Method 6010
Magnesium		No flag	No flag	Set by EPD/EMS
Manganese	µg/L	25	50	Secondary DWS (CFR, 1991b)
Manganese-54	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Mercury	µg/L	1	2	Final DWS (CFR, 1991a)
Methacrylonitrile	µg/L	250	500	EPA Method 8240
Methapyrilene	µg/L	50	100	EPA Method 8270
Methoxychlor	µg/L	20	40	Final DWS (CFR, 1991a)
3-Methylcholanthrene	µg/L	50	100	EPA Method 8270
2-Methyl-4,6-dinitrophenol	µg/L	250	500	EPA Method 8270
Methyl ethyl ketone		No flag	No flag	Set by EPD/EMS
Methyl isobutyl ketone		No flag	No flag	Set by EPD/EMS
Methyl methacrylate	µg/L	50	100	EPA Method 8270
Methyl methanesulfonate	µg/L	50	100	EPA Method 8270
2-Methylnaphthalene	µg/L	50	100	EPA Method 8270
Molybdenum	µg/L	250	500	EPA Method 6010
Naphthalene	µg/L	50	100	EPA Method 8270
1,4-Naphthoquinone	µg/L	50	100	EPA Method 8270
1-Naphthylamine	µg/L	50	100	EPA Method 8270
2-Naphthylamine	µg/L	50	100	EPA Method 8270
Neptunium-237	pCi/L	3.53E+00	7.06E+00	Proposed DWS (EPA, 1991)
Nickel	µg/L	50	100	Proposed DWS (EPA, 1990)
Nickel-59	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Nickel-63	pCi/L	2.5E+01	5E+01	Final DWS (EPA, 1977)
Niobium-95	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Nitrate as nitrogen	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Nitrate-nitrite as nitrogen	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Nitrite as nitrogen	µg/L	500	1,000	Final DWS (CFR, 1991a)
2-Nitroaniline	µg/L	50	100	EPA Method 8270
3-Nitroaniline	µg/L	50	100	EPA Method 8270
4-Nitroaniline	µg/L	50	100	EPA Method 8270
Nitrobenzene	µg/L	50	100	EPA Method 8270
Nitrogen by Kjeldahl method	µg/L	500	1,000	EPA Method 351.2

Analyte	Unit	Flag 1	Flag 2	Source
2-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitroquinoline-1-oxide	µg/L	50	100	EPA Method 8270
N-Nitrosodi-n-butylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodimethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiphenylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodi-propylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomethylethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomorpholine	µg/L	50	100	EPA Method 8270
N-Nitrosopiperidine	µg/L	50	100	EPA Method 8270
N-Nitrosopyrrolidine	µg/L	50	100	EPA Method 8270
5-Nitro-o-toluidine	µg/L	50	100	EPA Method 8270
Nonvolatile beta	pCi/L	2.5E+01	5E+01	Proposed DWS (EPA, 1986)
Octachlorodibenzo-p-dioxin isomers	µg/L	0.005	0.01	EPA Method 8280
Octachlorodibenzo-p-furan isomers	µg/L	0.005	0.01	EPA Method 8280
Odor		No flag	No flag	Set by EPD/EMS
Oil & Grease	µg/L	5,000	10,000	EPA Method 413.1
Parathion	µg/L	2.5	5	EPA Method 8080
Parathion methyl	µg/L	2.5	5	EPA Method 8080
PCB 1016	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1221	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1232	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1242	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1248	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1254	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1260	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1262	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
Pentachlorobenzene	µg/L	50	100	EPA Method 8270
Pentachlorodibenzo-p-dioxin isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-dioxin	µg/L	0.00275	0.0055	EPA Method 8280
Pentachlorodibenzo-p-furan isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-furan	µg/L	0.00275	0.0055	EPA Method 8280
Pentachloroethane	µg/L	50	100	EPA Method 8270
Pentachloronitrobenzene	µg/L	50	100	EPA Method 8270
Pentachlorophenol	µg/L	0.5	1	Final DWS (CFR, 1991a)
pH	pH	8	10	Set by EPD/EMS
pH	pH	4	3	Set by EPD/EMS
Phenacetin	µg/L	50	100	EPA Method 8270
Phenanthrene	µg/L	50	100	EPA Method 8270
Pheno!	µg/L	50	100	EPA Method 8270
Phenols	µg/L	25	50	EPA Method 420.1
p-Phenylenediamine	µg/L	50	100	EPA Method 8270
Phorate	µg/L	2.5	5	EPA Method 8080
2-Picoline	µg/L	50	100	EPA Method 8270
Plutonium-238	pCi/L	3.51E+00	7.02E+00	Proposed DWS (EPA, 1991)
Plutonium-239	pCi/L	3.11E+01	6.21E+01	Proposed DWS (EPA, 1991)
Plutonium-239/240 ^a	pCi/L	3.11E+01	6.21E+01	Proposed DWS (EPA, 1991)
Plutonium-240	pCi/L	3.11E+01	6.22E+01	Proposed DWS (EPA, 1991)
Plutonium-241	pCi/L	3.13E+01	6.26E+01	Proposed DWS (EPA, 1991)
Plutonium-242	pCi/L	3.27E+01	6.54E+01	Proposed DWS (EPA, 1991)
Potassium		No flag	No flag	Set by EPD/EMS

Analyte	Unit	Flag 1	Flag 2	Source
Potassium-40	pCi/L	1.5E+02	3E+02	Proposed DWS (EPA, 1986)
Pronamid	µg/L	50	100	EPA Method 8270
Propionitrile	µg/L	1,000	2,000	EPA Method 8240
Pyrene	µg/L	50	100	EPA Method 8270
Pyridine	µg/L	50	100	EPA Method 8270
Radium-226	pCi/L	7.85E+00	1.57E+01	Proposed DWS (EPA, 1991)
Radium-228	pCi/L	3.93E+00	7.85E+00	Proposed DWS (EPA, 1991)
Radon-222	pCi/L	1.5E+02	3E+02	Proposed DWS (EPA, 1991)
Ruthenium-103	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Ruthenium-106	pCi/L	1.5E+01	3E+01	Final DWS (EPA, 1977)
Safrole	µg/L	50	100	EPA Method 8270
Selenium	µg/L	25	50	Final DWS (CFR, 1991a)
Silica		No flag	No flag	Set by EPD/EMS
Silver	µg/L	25	50	Final DWS (CFR, 1991a)
Sodium		No flag	No flag	Set by EPD/EMS
Sodium-22	pCi/L	2.33E+02	4.66E+02	Proposed DWS (EPA, 1991)
Specific conductance	µS/cm	250	500	Set by EPD/EMS
Strontium-89	pCi/L	1E+01	2E+01	Final DWS (EPA, 1977)
Strontium-89/90 ^a	pCi/L	4E+00	8E+00	Final DWS (CFR, 1991a)
Strontium-90	pCi/L	4E+00	8E+00	Final DWS (CFR, 1991a)
Styrene	µg/L	50	100	Final DWS (CFR, 1991a)
Sulfate	µg/L	200,000	400,000	Proposed DWS (EPA, 1990)
Sulfide	µg/L	5,000	10,000	EPA Method 9030
Sulfotep	µg/L	50	100	EPA Method 8270
Surfactants		No flag	No flag	Set by EPD/EMS
2,3,7,8-TCDD	µg/L	0.00225	0.0045	EPA Method 8280
2,3,7,8-TCDF	µg/L	0.002	0.004	EPA Method 8280
Technetium-99	pCi/L	4.5E+02	9E+02	Final DWS (EPA, 1977)
1,2,4,5-Tetrachlorobenzene	µg/L	50	100	EPA Method 8270
Tetrachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
Tetrachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,1,1,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
1,1,2,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
Tetrachloroethylene	µg/L	2.5	5	Final DWS (CFR, 1991a)
2,3,4,6-Tetrachlorophenol	µg/L	50	100	EPA Method 8270
Tetraethyl dithiopyrophosphate	µg/L	50	100	EPA Method 8270
Thallium	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Thionazin	µg/L	50	100	EPA Method 8270
Thorium-228	pCi/L	6.25E+01	1.25E+02	Proposed DWS (EPA, 1991)
Thorium-230	pCi/L	3.96E+01	7.92E+01	Proposed DWS (EPA, 1991)
Thorium-232	pCi/L	4.4E+01	8.8E+01	Proposed DWS (EPA, 1991)
Thorium-234	pCi/L	2E+02	4.01E+02	Proposed DWS (EPA, 1991)
Tin	µg/L	10	20	EPA Method 282.2
Tin-113	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Toluene	µg/L	500	1,000	Final DWS (CFR, 1991a)
o-Toluidine	µg/L	50	100	EPA Method 8270
Total carbon	µg/L	5,000	10,000	EPA Method 9060
Total dissolved solids		No flag	No flag	Set by EPD/EMS
Total hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total inorganic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic halogens	µg/L	25	50	EPA Method 9020
Total organic nitrogen	µg/L	500	1,000	EPA Method 420

Analyte	Unit	Flag 1	Flag 2	Source
Total petroleum hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total phosphates (as P)		No flag	No flag	Set by EPD/EMS
Total phosphorus		No flag	No flag	Set by EPD/EMS
Total radium	pCi/L	2.5E+00	5E+00	Final DWS (CFR, 1991a)
Total silica	µg/L	500	1,000	EPA Method 6010
Total trihalomethanes	µg/L	50	100	Final DWS (CFR, 1991a)
Toxaphene	µg/L	1.5	3	Final DWS (CFR, 1991a)
2,4,5-TP (Silvex)	µg/L	25	50	Final DWS (CFR, 1991a)
Tributyl phosphate	µg/L	50	100	EPA Method 8270
1,2,4-Trichlorobenzene	µg/L	4.5	9	Proposed DWS (EPA, 1990)
1,1,1-Trichloroethane	µg/L	100	200	Final DWS (CFR, 1991a)
1,1,2-Trichloroethane	µg/L	2.5	5	Proposed DWS (EPA, 1990)
Trichloroethylene	µg/L	2.5	5	Final DWS (CFR, 1991a)
Trichlorofluoromethane	µg/L	5	10	EPA Method 8240
2,4,5-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,6-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,5-Trichlorophenoxyacetic acid	µg/L	2.5	5	EPA Method 8150
1,2,3-Trichloropropane	µg/L	5	10	EPA Method 8240
O,O,O-Triethyl phosphorothioate	µg/L	50	100	EPA Method 8270
1,3,5-Trinitrobenzene	µg/L	50	100	EPA Method 8270
Tritium	pCi/mL	1E+01	2E+01	Final DWS (CFR, 1991a)
Turbidity		No flag	No flag	Set by EPD/EMS
Uranium	µg/L	10	20	Proposed DWS (EPA, 1991)
Uranium alpha activity	pCi/L	1.5E+01	3E+01	Proposed DWS (EPA, 1991)
Uranium-233/234 ^a	pCi/L	6.9E-00	1.38E+01	Proposed DWS (EPA, 1991)
Uranium-234	pCi/L	6.95E+00	1.39E+01	Proposed DWS (EPA, 1991)
Uranium-235	pCi/L	7.25E+00	1.45E+01	Proposed DWS (EPA, 1991)
Uranium-238	pCi/L	7.3E+00	1.46E+01	Proposed DWS (EPA, 1991)
Vanadium	µg/L	50	100	EPA Method 6010
Vinyl acetate	µg/L	5	10	EPA Method 8240
Xylenes	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Zinc	µg/L	2,500	5,000	Secondary DWS (CFR, 1991b)
Zinc-65	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Zirconium-95	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Zirconium/Niobium-95 ^a	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)

^a For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

References

APHA (American Public Health Association, American Water Works Association, and Water Pollution Control Federation), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition. Washington, DC.

CFR (Code of Federal Regulations), 1991a. *National Primary Drinking Water Regulations*, 40 CFR, Part 141, pp. 578-715. Washington, DC.

CFR (Code of Federal Regulations), 1991b. *National Secondary Drinking Water Regulations*, 40 CFR, Part 143, pp. 758-762. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*. **Federal Register**, September 30, 1986, pp. 34836–34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals (Proposed Rule)*. **Federal Register**, July 25, 1990, pp. 30369–30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*. **Federal Register**, July 18, 1991, pp. 33052–33127. Washington, DC.

Appendix C – Figures

Figure 1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site

Figure 2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin

Figure 3. Water-Elevation Contour Map of the Water Table at the K-Area Acid/Caustic Basin

Appendix D – Groundwater Monitoring Results Tables

Key to Reading the Tables

The following abbreviations may appear in the tabular data:

B = sample collected from well using an open bucket bailer
 BA = Barringer Laboratories, Inc.
 CN = Clemson Technical Center, Inc.
 CS = carbon steel
 D = primary drinking water standard (PDWS)
 E = exponential notation (e.g., $1.1\text{E}-09 = 1.1 \times 10^{-9} = 0.0000000011$)
 EM = Environmental Protection Department/Environmental Monitoring Section (EPD/EMS)
 Laboratory
 GE = General Engineering Laboratories
 GP = Environmental Physics, Inc.
 H = holding time
 1,2,3,4,6,7,8-HPCDD = 1,2,3,4,6,7,8-heptachlorodibenzo-p-dioxin
 1,2,3,4,6,7,8-HPCDF = 1,2,3,4,6,7,8-heptachlorodibenzo-p-furan
 1,2,3,4,7,8-HXCDD = 1,2,3,4,7,8-hexachlorodibenzo-p-dioxin
 1,2,3,4,7,8-HXCDF = 1,2,3,4,7,8-hexachlorodibenzo-p-furan
 Lindane = gamma-benzene hexachloride
 mg/L = milligrams per liter
 Mod = modifier
 msl = mean sea level
 MSL = million structures per liter
 NTU = turbidity unit
 P = sample collected from well using a bladder pump
 PCB = polychlorinated biphenyl
 1,2,3,7,8-PCDD = 1,2,3,7,8-pentachlorodibenzo-p-dioxin
 1,2,3,7,8-PCDF = 1,2,3,7,8-pentachlorodibenzo-p-furan
 pCi/L = picocuries per liter
 pCi/mL = picocuries per milliliter
 PDWS = primary drinking water standard
 pH = pH unit
 PVC = polyvinyl chloride
 S = sample collected from well using a single-speed centrifugal downhole pump
 Sp. conductance = specific conductance
 SP = Spencer Testing Services, Inc.
 TCDD = tetrachlorodibenzo-p-dioxin
 TCDF = tetrachlorodibenzo-p-furan
 TM = TMA/Eberline
 TOC = top of casing
 V = sample collected from well using a variable-speed pump
 WA = Roy F. Weston, Inc.
 $\mu\text{g/L}$ = micrograms per liter
 $\mu\text{S/cm}$ = microsiemens per centimeter

Holding Times

Standard analytical methods include a limit, called holding time, on the maximum elapsed time between sample collection and extraction or analysis by the laboratory. In the data tables, a large dot (●) in the H (holding time) column indicates that holding time was exceeded. Analyses performed beyond holding time may not yield valid results.

The South Carolina Department of Health and Environmental Control allows only 15 minutes to elapse between sampling and analysis for pH. Thus, only field pH measurements can meet the holding time criterion; laboratory pH analyses will always exceed it.

Laboratory-initiated procedures for reducing the number of other analyses performed out of holding time include subcontracting analyses when difficulties with equipment, personnel, or work load would prevent timely analyses. Beginning fourth quarter 1991, SRS reduced the compensation to laboratories for analyses performed out of holding time.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific quality assurance/quality control information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by EPD/EMS and provided to the primary laboratories are defined below. These modifiers appear in the data tables under the column "Mod."

<u>Result modifier</u>	<u>Definition</u>
(Blank)	Data are not qualified. Number should be interpreted exactly as reported.
A ^a	Value reported is the mean of two or more determinations.
J ^a	Value is estimated because quantitation in the sample or in associated quality control samples did not meet specifications.
L ^a	Value is off-scale high. The actual value is not known but is known to be greater than the value shown.
M ^a	Presence of the analyte is verified but not quantified.
R ^a	Result was rejected because performance requirements in the sample analysis or associated quality control analyses were not met.
T ^a	Analyte was not detected; if present, it was below the criteria for detection.
V ^a	Analyte was detected in the associated method blank.
1	Result may be an underestimation of the true value due to analytical bias.
2	Result may be an overestimation of the true value due to analytical bias.

<u>Result modifier</u>	<u>Definition</u>
3	The associated result may be of poor precision (high variability) due to analytical bias.
6	The associated result is from a reanalysis performed out of holding time due to problems with an earlier analysis.

▪ These codes are based on the STORET codes from EPA.

Table 1. Constituents Exceeding Final Primary Drinking Water Standards in 1992

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q92</u>	<u>2Q92</u>	<u>3Q92</u>	<u>4Q92</u>	<u>Mod</u>
N ^a	None	N	N	N	N	N	N

^aN = not applicable.

Table 2. Constituents Exceeding Half the Final Primary Drinking Water Standards, Other Flag 1 or Flag 2 Criteria, or the SRS Turbidity Standard

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>4Q92</u>	<u>Mod</u>	<u>Flag</u>
KAC 1	Specific conductance	µS/cm	361	J	1
KAC 2	Specific conductance	µS/cm	328	J	1
KAC 3	Specific conductance	µS/cm	367	J	1
KAC 4	Iron	µg/L	295		1
KAC 6	Iron	µg/L	1,800		2
KAC 7	Iron	µg/L	689		2
	Specific conductance	µS/cm	314	J	1
KAC 8	Iron	µg/L	226		1
KAC 9	pH	pH	9.7	J	1
	Specific conductance	µS/cm	692	J	2
	Sulfate	µg/L	309,000		1

Note: These results do not include field data results.

Table 3. Groundwater Monitoring Results for Individual Wells

WELL KAC 1

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53167.0 E42614.8	33.212893 °N 81.657866 °W	229.0-199.0 ft msl	266 ft msl	4" PVC	V	Water table

SAMPLE DATE	02/18/92	05/22/92	08/01/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	219.5	218.9	218.6	218.1	ft msl
pH	6.0	5.6	5.7	5.9	pH
Sp. conductance	372	289	301	508	µS/cm
Water temperature	17.6	19.0	21.8	19.9	°C
Alkalinity as CaCO ₃	14	19	26	15	mg/L
Volume purged	4.0	5.0	4.0	2.2	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Barium	<6.6	<3.0	<4.0	<4.0		µg/L	WA	0
		Cadmium	1.0	0.38	<0.35	0.40	V	µg/L	WA	0
		Calcium	176	242	256	460	V	µg/L	WA	0
		Chloride	10,900	9,250	8,110	9,170		µg/L	WA	0
		Chromium	<1.1	<1.1	<1.1	<1.1		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	<1.1	<0.30	<1.1	<1.1		µg/L	WA	0
		Endrin	<0.11	<0.0060	<0.11	<0.12		µg/L	WA	0
		Fluoride	<100	<100	<100	<100		µg/L	WA	0
		Gross alpha	4.7E+00	<2.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		Iron	192	65	59	40		µg/L	WA	0
		Lead	<2.0	17	2.3	<2.0		µg/L	WA	0
		Lindane	<0.056	<0.0050	<0.056	<0.058		µg/L	WA	0
		Magnesium	102	187	167	327	V	µg/L	WA	0
		Manganese	3.1	4.0	3.7	1.4	J3	µg/L	WA	0
		Mercury	<0.20	<0.20	<0.20	<0.20		µg/L	WA	0
		Methoxychlor	<0.56	<0.50	<0.56	<0.58		µg/L	WA	0
		Nitrate as nitrogen	700	634	651	898		µg/L	WA	0
		Nitrate-nitrite as nitrogen		730				µg/L		
		Nonvolatile beta	5.7E+00	<2.0E+00	7.1E+00	<2.0E+00		pCi/L	CN	0
		PCB 1016		<0.54				µg/L		
		PCB 1221		<0.54				µg/L		
		PCB 1232		<0.54				µg/L		
		PCB 1242		<0.54				µg/L		
		PCB 1248		<0.54				µg/L		
		PCB 1254		<1.1				µg/L		
		PCB 1260		<1.1				µg/L		
•		pH	7.8	6.2	6.8	6.3	J	pH	WA	0
		Phenols	<5.0	<5.0	<5.0	<5.0		µg/L	WA	0
		Potassium	160	272	<34	322	V	µg/L	WA	0
		Radium-226	2.5E+00	6.6E-01	1.3E+00	<1.0E+00		pCi/L	CN	0
		Radium-228	<1.7E+00		<1.0E+00	<1.0E+00		pCi/L	CN	0
		Selenium	2.8	<2.0	3.5	2.2	J3	µg/L	WA	0
		Silica		5,110	4,780	4,590	V	µg/L	WA	0
		Silicon	2,660					µg/L		
		Silver	<0.70	1.0	<0.70	3.2		µg/L	WA	0
		Sodium	54,900	61,300	55,200	84,100	V	µg/L	WA	0
•		Specific conductance	271	313	312	361	J	µS/cm	WA	1
		Sulfate	91,900	101,000	94,400	151,000		µg/L	WA	0
•		Total dissolved solids	186,000	179,000	163,000	266,000	J	µg/L	WA	0
		Total organic carbon	4,130	1,540	800	<500		µg/L	WA	0
		Total organic halogens	5.8	48	20	6.4		µg/L	WA	0
		Total phosphates (as P)	57	466	46	64		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 1 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Toxaphene	<1.1	<0.24	<1.1	<1.2		µg/L	WA	0
		2,4,5-TP (Silvex)	<0.55	<0.090	<0.56	<0.53		µg/L	WA	0
		Tritium	2.2E+00	4.6E+00	9.2E-01	1.4E+00		pCi/mL	CN	0
		Turbidity	21	12	3.5	1.2	J	NTU	WA	0

WELL KAC 2

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53255.5 E42677.2	33.213191 °N 81.657873 °W	225.4-195.4 ft msl	257.5 ft msl	4" PVC	S	Water table

SAMPLE DATE	02/18/92	05/21/92	08/01/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	220.7	220.6	220.9	220.7	ft msl
pH	6.5	6.0	6.1	6.3	pH
Sp. conductance	445	341	349	378	µS/cm
Water temperature	17.8	20.5	22.9	20.4	°C
Alkalinity as CaCO ₃	43	56	81	52	mg/L
Volume purged	4.0	4.0	4.0	6.8	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Barium	<6.6	<4.0	<4.0	<4.0		µg/L	WA	0
		Cadmium	1.3	0.95	<0.35	<0.35	V	µg/L	WA	0
		Calcium	418	475	600	289	V	µg/L	WA	0
		Chloride	6,350	5,480	5,290	5,870		µg/L	WA	0
		Chromium	<1.1	1.6	1.6	1.2	J3	µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	<1.1	<1.1	<1.1	<1.0		µg/L	WA	0
		Endrin	<0.11	<0.11	<0.11	<0.11		µg/L	WA	0
		Fluoride	<100	<100	<100	<100		µg/L	WA	0
		Gross alpha	1.8E+00	<3.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		Iron	137	30	333	92		µg/L	WA	0
		Lead	<2.0	<2.0	4.1	<2.0		µg/L	WA	0
		Lindane	<0.056	<0.054	<0.056	<0.056		µg/L	WA	0
		Magnesium	238	284	345	181	V	µg/L	WA	0
		Manganese	5.2	1.4	5.4	<0.35		µg/L	WA	0
		Mercury	<0.20	<0.20	<0.20	<0.20		µg/L	WA	0
		Methoxychlor	<0.56	<0.54	<0.56	<0.56		µg/L	WA	0
		Nitrate as nitrogen	391	221	459	393		µg/L	WA	0
		Nonvolatile beta	2.0E+00	<5.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		PCB 1016		<0.54				µg/L		
		PCB 1221		<0.54				µg/L		
		PCB 1232		<0.54				µg/L		
		PCB 1242		<0.54				µg/L		
		PCB 1248		<0.54				µg/L		
		PCB 1254		<1.1				µg/L		
		PCB 1260		<1.1				µg/L		
		pH	7.7	6.4	6.5	6.6	J	pH	WA	0
		Phenols	<5.0	<5.0	<5.0	<5.0		µg/L	WA	0
		Potassium	301	254	<84	122	V	µg/L	WA	0
		Radium-226	1.0E+00	<5.0E-01	<1.0E+00	<1.0E+00		pCi/L	CN	0
		Radium-228	7.0E-01		<1.0E+00	<1.0E+00		pCi/L	CN	0
		Selenium	3.1	5.0	4.6	4.0	J3	µg/L	WA	0
		Silica		6,010	6,650	6,120	V	µg/L	WA	0
		Silicon	2,940					µg/L		

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

● = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 2 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Silver	<0.70	1.6	<0.70	<0.70		µg/L	WA	0
		Sodium	73,100	67,400	73,800	76,700	V	µg/L	WA	0
•		Specific conductance	333	327	348	328	J	µS/cm	WA	1
		Sulfate	116,000	80,500	91,400	98,800		µg/L	WA	0
•		Total dissolved solids	227,000	213,000	200,000	240,000	J	µg/L	WA	0
		Total organic carbon	1,420	927	1,300	<500		µg/L	WA	0
		Total organic halogens	<5.0	18	9.5	<5.0		µg/L	WA	0
		Total phosphates (as P)	80	51	180	40		µg/L	WA	0
		Toxaphene	<1.1	<1.1	<1.1	<1.1		µg/L	WA	0
		2,4,5-TP (Silvex)	<0.56	<0.56	<0.55	<0.52		µg/L	WA	0
		Tritium	4.8E+00	4.8E+00	4.4E+00	6.6E+00		pCi/mL	CN	0
•		Turbidity	110	19	115	2.7	J	NTU	WA	0

WELL KAC 3

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53201.8 E42723.9	33.213148 °N 81.657646 °W	225.8-195.8 ft msl	257.8 ft msl	4" PVC	S	Water table

SAMPLE DATE	02/18/92	05/21/92	08/01/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	221.3	221.0	221.1	221.1	ft msl
pH	6.6	6.3	6.3	6.5	pH
Sp. conductance	372	346	429	367	µS/cm
Water temperature	17.8	19.7	22.7	18.5	°C
Alkalinity as CaCO ₃	42	51	76	68	mg/L
Volume purged	4.0	4.0	4.0	9.1	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Barium	<6.6	8.9	7.8	<4.0		µg/L	WA	0
		Cadmium	1.4	0.92	<0.35	1.6	V	µg/L	WA	0
		Calcium	979	3,570	4,270	1,240	V	µg/L	WA	0
		Chloride	8,380	6,510	5,980	5,800		µg/L	WA	0
		Chromium	<1.1	<1.1	1.3	<1.1		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	<1.1	<1.1	<1.1	<1.0		µg/L	WA	0
		Endrin	<0.11	<0.11	<0.11	<0.12		µg/L	WA	0
		Fluoride	<100	<100	<100	<100		µg/L	WA	0
		Gross alpha	<1.8E+00	<3.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		Iron	17	6.8	16	15		µg/L	WA	0
		Lead	<2.0	<2.0	4.0	<2.0		µg/L	WA	0
		Lindane	<0.056	<0.054	<0.056	<0.058	V	µg/L	WA	0
		Magnesium	374	946	1,140	477		µg/L	WA	0
		Manganese	0.78	0.60	0.85	<0.35		µg/L	WA	0
		Mercury	<0.20	<0.20	<0.20	<0.20		µg/L	WA	0
		Methoxychlor	<0.56	<0.54	<0.56	<0.58		µg/L	WA	0
		Nitrate as nitrogen	281	273	437	266		µg/L	WA	0
		Nonvolatile beta	2.3E+00	<5.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		PCB 1016		<0.54				µg/L		
		PCB 1221		<0.54				µg/L		
		PCB 1232		<0.54				µg/L		
		PCB 1242		<0.54				µg/L		
		PCB 1248		<0.54				µg/L		
		PCB 1254		<1.1				µg/L		
		PCB 1260		<1.1				µg/L		

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 3 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
•		pH	7.7	6.5	6.6	6.6	J	pH	WA	0
		Phenols	<5.0	<5.0	<5.0	<5.0		µg/L	WA	0
		Potassium	458	956	862	224	V	µg/L	WA	0
		Radium-226	1.0E-01	<5.0E-01	<1.0E+00	<1.0E+00		pCi/L	CN	0
		Radium-228	<1.7E+00	<1.0E+00	<1.0E+00	<1.0E+00		pCi/L	CN	0
		Selenium	<2.0	<2.0	2.5	<2.0	V	µg/L	WA	0
		Silica		4,910	6,890	5,980		µg/L	WA	0
		Silicon	2,160					µg/L	WA	0
		Silver	1.6	1.3	1.0	<0.70		µg/L	WA	0
		Sodium	51,100	66,900	91,400	71,700	V	µS/cm	WA	1
•		Specific conductance	271	349	357	367	J	µg/L	WA	0
		Sulfate	75,800	95,500	112,000	84,300		µg/L	WA	0
•		Total dissolved solids	175,000	220,000	252,000	244,000	J	µg/L	WA	0
		Total organic carbon	685	<500	800	645		µg/L	WA	0
		Total organic halogens	<5.0	37	16	<5.0		µg/L	WA	0
		Total phosphates (as P)	<20	24	42	52		µg/L	WA	0
		Toxaphene	<1.1	<1.1	<1.1	<1.2		µg/L	WA	0
		2,4,5-TP (Silvex)	<0.54	<0.54	<0.55	<0.53		µg/L	WA	0
		Tritium	4.2E+00	4.2E+00	3.6E+00	3.7E+00		pCi/mL	CN	0
•		Turbidity	2.6	1.6	0.41	0.41	J	NTU	WA	0

WELL KAC 4

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53053.5 E42676.4	33.212743 °N 81.657484 °W	208.0-178.0 ft msl	260 ft msl	4" PVC	S	Water table

SAMPLE DATE	02/19/92	05/21/92	08/01/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	218.7	218.1	217.6	217.4	ft msl
pH	5.1	4.8	4.9	5.3	pH
Sp. conductance	88	79	71	86	µS/cm
Water temperature	18.4	20.0	21.5	18.5	°C
Alkalinity as CaCO ₃	2	3	1	1	mg/L
Volume purged	4.0	4.0	4.0	4.8	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Barium	4.6	8.2	5.1	<4.0		µg/L	WA	0
		Cadmium	0.45	1.8	<0.35	<0.35	V	µg/L	WA	0
		Calcium	361	427	343	342	V	µg/L	WA	0
		Chloride	9,900	8,610	7,230	7,970		µg/L	WA	0
		Chromium	1.7	2.9	1.3	7.3		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	<0.30	<1.1	<1.1	<1.0		µg/L	WA	0
		Endrin	<0.0060	<0.11	<0.11	<0.11		µg/L	WA	0
		Fluoride	<100	<100	<100	<100		µg/L	WA	0
		Gross alpha	2.4E+00	<3.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		Iron	44	32	13	295		µg/L	WA	1
		Lead	<2.0	<2.0	4.3	<2.0		µg/L	WA	0
		Lindane	<0.0050	<0.055	<0.056	<0.056		µg/L	WA	0
		Magnesium	399	463	418	350	V	µg/L	WA	0
		Manganese	4.2	4.7	3.2	3.2		µg/L	WA	0
		Mercury	0.28	0.21	<0.20	<0.20		µg/L	WA	0
		Methoxychlor	<0.50	<0.55	<0.56	<0.56		µg/L	WA	0
		Nitrate as nitrogen	383	191	205	400		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 4 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Nonvolatile beta	5.4E+00	<5.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		PCB 1016		<0.55				µg/L		
		PCB 1221		<0.55				µg/L		
		PCB 1232		<0.55				µg/L		
		PCB 1242		<0.55				µg/L		
		PCB 1248		<0.55				µg/L		
		PCB 1254		<1.1				µg/L		
		PCB 1260		<1.1				µg/L		
•		pH	5.7	5.6	6.0	5.7	J	pH	WA	0
		Phenols	<5.0	<5.0	<5.0	<5.0		µg/L	WA	0
		Potassium	269	420	<84	226	V	µg/L	WA	0
		Radium-226	1.3E+00	<5.0E-01	<1.0E+00	<1.0E+00		pCi/L	CN	0
		Radium-228	8.0E-01		<1.0E+00	<1.0E+00		pCi/L	CN	0
		Selenium	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Silica	6,870	5,990	6,040	5,860	V	µg/L	WA	0
		Silicon	2,920					µg/L		
		Silver	<0.70	1.8	<0.70	<0.70		µg/L	WA	0
		Sodium	13,800	12,800	10,800	13,500	V	µg/L	WA	0
•		Specific conductance	70	79	64	65	J	µS/cm	WA	0
		Sulfate	14,800	13,900	9,690	14,500		µg/L	WA	0
		Total alpha-emitting radium	1.4E+00					pCi/L		
•		Total dissolved solids	57,000	51,000	23,000	58,000	J	µg/L	WA	0
		Total organic carbon	1,020	<500	900	645		µg/L	WA	0
		Total organic halogens	<5.0	13	15	<5.0		µg/L	WA	0
		Total phosphates (as P)	31	49	46	51		µg/L	WA	0
		Toxaphene	<0.24	<1.1	<1.1	<1.1		µg/L	WA	0
		2,4,5-TP (Silvex)	<0.090	<0.55	<0.55	<0.53		µg/L	WA	0
•		Tritium	1.7E+00	<2.0E+00	1.4E+00	9.2E-01		pCi/mL	CN	0
		Turbidity	12	12	2.9	3.1	J	NTU	WA	0

WELL KAC 5

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53161.7	33.213047 °N	224.3-204.3 ft msl	259 ft msl	4" PVC	S	Water table
E42716.3	81.657589 °W					

SAMPLE DATE	02/29/92	05/21/92	08/01/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	220.7	220.7	221.0	220.8	ft msl
pH	5.1	5.1	5.1	5.2	pH
Sp. conductance	60	67	73	63	µS/cm
Water temperature	20.3	20.8	21.8	19.4	°C
Alkalinity as CaCO ₃	2	0	3	3	mg/L
Volume purged	4.0	4.0	4.0	3.7	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Barium	<6.6	4.3	<4.0	<4.0		µg/L	WA	0
		Cadmium	<0.35	0.92	<0.35	0.88	V	µg/L	WA	0
		Calcium	321	375	398	345	V	µg/L	WA	0
		Chloride	7,010	6,750	6,430	5,640		µg/L	WA	0
		Chromium	<1.1	<1.1	<1.1	<1.1		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	<1.1	<1.1	<1.1	<1.1		µg/L	WA	0
		Endrin	<0.11	<0.11	<0.11	<0.12		µg/L	WA	0
		Fluoride	<100	<100	<100	<100		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 5 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Gross alpha	1.1E+00	<3.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		Iron	95	50	68	93		µg/L	WA	0
		Lead	<2.0	<2.0	3.4	<2.0		µg/L	WA	0
		Lindane	<0.055	<0.055	<0.055	<0.058		µg/L	WA	0
		Magnesium	211	245	225	252	V	µg/L	WA	0
		Manganese	4.3	5.0	4.9	5.8		µg/L	WA	0
		Mercury	<0.20	<0.20	<0.20	<0.20		µg/L	WA	0
		Methoxychlor	<0.55	<0.55	<0.55	<0.58		µg/L	WA	0
		Nitrate as nitrogen	230	156	136	213		µg/L	WA	0
		Nonvolatile beta	5.6E+00	<5.0E+00	<2.0E+00	<2.0E+00		pCi/L	CN	0
		PCB 1016		<0.55				µg/L		
		PCB 1221		<0.55				µg/L		
		PCB 1232		<0.55				µg/L		
		PCB 1242		<0.55				µg/L		
		PCB 1248		<0.55				µg/L		
		PCB 1254		<1.1				µg/L		
		PCB 1260		<1.1				µg/L		
		pH	5.3	5.6	5.8	5.6	J	pH	WA	0
		Phenols	<5.0	<5.0	<5.0	<5.0		µg/L	WA	0
		Potassium	435	613	313	629	V	µg/L	WA	0
		Radium-226	6.0E-01	<5.0E-01	<1.0E+00	<1.0E+00		pCi/L	CN	0
		Radium-228	<9.1E+00		<1.0E+00	<1.0E+00		pCi/L	CN	0
		Selenium	<2.0	<2.0	<2.0	<2.0		µg/L	WA	0
		Silica		5,320	6,250	6,360	V	µg/L	WA	0
		Silicon	2,670					µg/L		
		Silver	<0.70	1.3	2.1	1.4	J3	µg/L	WA	0
		Sodium	8,930	10,500	10,700	10,300	V	µg/L	WA	0
		Specific conductance	49	60	61	51	J	µS/cm	WA	0
		Sulfate	9,380	10,900	8,880	9,140		µg/L	WA	0
		Total dissolved solids	44,000	41,000	22,000	50,000	J	µg/L	WA	0
		Total organic carbon	<500	<500	700	860		µg/L	WA	0
		Total organic halogens	32	41	11	7.6		µg/L	WA	0
		Total phosphates (as P)	<20	<20	39	69		µg/L	WA	0
		Toxaphene	<1.1	<1.1	<1.1	<1.2		µg/L	WA	0
		2,4,5-TP (Silvex)	<0.55	<0.54	<0.56	<0.53		µg/L	WA	0
		Tritium	4.3E-01	<2.0E+00	7.5E-01	8.8E-01		pCi/mL	CN	0
		Turbidity	0.30	0.76	0.20	1.0	J	NTU	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

● = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

WELL KAC 6

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53139.9 E42693.5	33.212962 °N 81.657606 °W	224.6-204.6 ft msl	259 ft msl	4" PVC	S	Water table

SAMPLE DATE	03/01/92	05/22/92	08/02/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	220.6	220.7	220.9	220.8	ft msl
pH	5.3	5.0	5.2	5.2	pH
Sp. conductance	92	79	87	100	µS/cm
Water temperature	18.8	23.9	21.5	17.6	°C
Alkalinity as CaCO ₃	3	7	2	3	mg/L
Volume purged	1.6	0.8	0.7	0.8	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	< 2.0	< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Barium	< 6.6	4.8	5.3	6.2	J3	µg/L	WA	0
		Cadmium	< 0.35	< 0.35	< 0.35	0.72	V	µg/L	WA	0
		Calcium	294	292	318	339	V	µg/L	WA	0
		Chloride	7,550	7,020	6,570	6,460		µg/L	WA	0
		Chromium	< 1.1	< 1.1	1.3	2.3	J3	µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	< 1.1	< 1.1	< 1.1	< 1.1		µg/L	WA	0
		Endrin	< 0.11	< 0.11	< 0.11	< 0.12		µg/L	WA	0
		Fluoride	< 100	< 100	< 100	< 100		µg/L	WA	0
		Gross alpha	2.5E + 00	< 3.0E + 00	< 2.0E + 00	< 2.0E + 00		pCi/L	CN	0
		Iron	518	109	103	1,800		µg/L	WA	2
		Lead	< 2.0	2.0	5.3	4.0	J3	µg/L	WA	0
		Lindane	< 0.055	< 0.056	< 0.055	< 0.058		µg/L	WA	0
		Magnesium	235	250	269	240	V	µg/L	WA	0
		Manganese	12	8.6	6.0	12		µg/L	WA	0
		Mercury	< 0.20	< 0.20	< 0.20	< 0.20		µg/L	WA	0
		Methoxychlor	< 0.55	< 0.56	< 0.55	< 0.58		µg/L	WA	0
		Nitrate as nitrogen	116	69	131	213		µg/L	WA	0
		Nonvolatile beta	2.8E + 00	< 5.0E + 00	< 2.0E + 00	< 2.0E + 00		pCi/L	CN	0
		PCB 1016		< 0.56				µg/L		
		PCB 1221		< 0.56				µg/L		
		PCB 1232		< 0.56				µg/L		
		PCB 1242		< 0.56				µg/L		
		PCB 1248		< 0.56				µg/L		
		PCB 1254		< 1.1				µg/L		
		PCB 1260		< 1.1				µg/L		
•		pH	5.4	5.5	5.7	5.6	J	pH	WA	0
		Phenols	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Potassium	280	206	336	171	V	µg/L	WA	0
		Radium-226	5.0E-01	< 5.0E-01	< 1.0E + 00	< 1.0E + 00		pCi/L	CN	0
		Radium-228	< 8.8E + 00		< 1.0E + 00	< 1.0E + 00		pCi/L	CN	0
		Selenium	< 2.0	< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Silica		5,880	6,680	5,170	V	µg/L	WA	0
		Silicon	2,850					µg/L		
		Silver	< 0.70	3.3	1.8	< 0.70		µg/L	WA	0
		Sodium	15,200	12,800	14,200	11,400	V	µg/L	WA	0
•		Specific conductance	76	61	82	76	J	µS/cm	WA	0
		Sulfate	20,300	16,100	19,500	19,700		µg/L	WA	0
•		Total dissolved solids	67,000	42,000	45,000	65,000	J	µg/L	WA	0
		Total organic carbon	1,310	788	< 500	645		µg/L	WA	0
		Total organic halogens	67	18	16	< 5.0		µg/L	WA	0
		Total phosphates (as P)	42	47	67	94		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 6 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Toxaphene	< 1.1	< 1.1	< 1.1	< 1.2		µg/L	WA	0
		2,4,5-TP (Silvex)	< 0.56	< 0.56	< 0.55	< 0.53		µg/L	WA	0
		Tritium	9.3E-01	< 2.0E + 00	7.2E-01	< 7.0E-01		pCi/mL	CN	0
		Turbidity	15	19	25	33	J	NTU	WA	0

WELL KAC 7

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53252.9 E42574.5	33.213018 °N 81.658139 °W	223.0-203.0 ft msl	265.1 ft msl	4" PVC	S	Water table

SAMPLE DATE	03/01/92	05/22/92	08/02/92	11/20/92
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation	219.5	219.1	218.8	218.2	ft msl
pH	6.0	5.7	5.8	5.5	pH
Sp. conductance	232	367	205	392	µS/cm
Water temperature	17.8	23.5	21.5	17.8	°C
Alkalinity as CaCO ₃	39	29	26	13	mg/L
Volume purged	0.8	0.7	0.6	0.7	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	< 2.0	< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Barium	< 6.6	7.0	4.2	4.4	J3	µg/L	WA	0
		Cadmium	< 0.35	< 0.35	< 0.35	1.2	V	µg/L	WA	0
		Calcium	2,590	2,980	1,850	1,590	V	µg/L	WA	0
		Chloride	8,950	8,090	8,590	8,590		µg/L	WA	0
		Chromium	< 1.1	< 1.1	< 1.1	< 1.1		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	< 1.1	< 1.1	< 1.1	< 1.1		µg/L	WA	0
		Endrin	< 0.11	< 0.11	< 0.11	< 0.12		µg/L	WA	0
		Fluoride	< 100	< 100	< 100	< 100		µg/L	WA	0
		Gross alpha	2.7E + 00	< 3.0E + 00	< 2.0E + 00	< 2.0E + 00		pCi/L	CN	0
		Iron	103	3,420	63	689		µg/L	WA	2
		Lead	5.0	14	3.5	22		µg/L	WA	0
		Lindane	< 0.056	< 0.054	< 0.055	< 0.058	V	µg/L	WA	0
		Magnesium	124	209	85	185		µg/L	WA	0
		Manganese	11	42	3.7	22		µg/L	WA	0
		Mercury	< 0.20	< 0.20	< 0.20	< 0.20		µg/L	WA	0
		Methoxychlor	< 0.56	< 0.54	< 0.55	< 0.58		µg/L	WA	0
		Nitrate as nitrogen	1,440	533	887	1,290		µg/L	WA	0
		Nonvolatile beta	3.3E + 00	< 5.0E + 00	< 2.0E + 00	< 2.0E + 00		pCi/L	CN	0
		PCB 1016		< 0.54				µg/L		
		PCB 1221		< 0.54				µg/L		
		PCB 1232		< 0.54				µg/L		
		PCB 1242		< 0.54				µg/L		
		PCB 1248		< 0.54				µg/L		
		PCB 1254		< 1.1				µg/L		
		PCB 1260		< 1.1				µg/L		
		pH	6.1	5.8	5.8	5.8	J	pH	WA	0
		Phenols	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Potassium	112	< 84	< 84	547	V	µg/L	WA	0
		Radium-226	5.0E-01	< 5.0E-01	< 1.0E + 00	< 1.0E + 00		pCi/L	CN	0
		Radium-228	3.8E + 00	< 1.0E + 00	< 1.0E + 00	< 1.0E + 00		pCi/L	CN	0
		Selenium	< 2.0	< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Silica		4,530	4,790	5,130	V	µg/L	WA	0
		Silicon	1,820					µg/L		

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

● = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 7 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Silver	<0.70	<0.70	<0.70	<0.70		µg/L	WA	0
		Sodium	41,700	65,200	34,700	56,100	V	µg/L	WA	0
•		Specific conductance	210	248	397	314	J	µS/cm	WA	1
		Sulfate	48,600	78,800	125,000	121,000		µg/L	WA	0
•		Total dissolved solids	152,000	164,000	214,000	257,000	J	µg/L	WA	0
		Total organic carbon	767	1,440	700	645		µg/L	WA	0
		Total organic halogens	68	13	17	<5.0		µg/L	WA	0
		Total phosphates (as P)	84	44	67	38		µg/L	WA	0
		Toxaphene	<1.1	<1.1	<1.1	<1.2		µg/L	WA	0
		2,4,6-TP (Silvex)	<0.55	<0.54	<0.55	<0.53		µg/L	WA	0
		Tritium	7.3E+00	6.7E+00	4.6E+00	7.6E+00		pCi/mL	CN	0
•		Turbidity	43	34	39	12	J	NTU	WA	0

WELL KAC 8

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53136.0	33.212869 °N	217.1-197.1 ft msl	267.1 ft msl	4" PVC	S	Water table
E42641.9	81.657734 °W					

SAMPLE DATE

06/09/92

08/02/92

11/20/92

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation		223.7	223.6	223.2	ft msl
pH		5.1	5.5	5.6	pH
Sp. conductance		271	298	277	µS/cm
Water temperature		21.0	21.9	19.3	°C
Alkalinity as CaCO ₃		7	9	5	mg/L
Volume purged		4.1	4.1	4.4	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic		<2.0	<2.0	<2.0		µg/L	WA	0
		Barium		16	24	15	J3	µg/L	WA	0
		Benzene		<5.0	<1.0	<5.0		µg/L	WA	0
		Bromodichloromethane		<5.0	<1.0	<5.0		µg/L	WA	0
		Bromoform		<5.0	<1.0	<5.0		µg/L	WA	0
		Bromomethane (Methyl bromide)		<10	<1.0	<10		µg/L	WA	0
		Cadmium		<0.35	<0.35	<0.35	V	µg/L	WA	0
		Calcium		2,020	2,030	1,290	V	µg/L	WA	0
		Carbon tetrachloride		<5.0	<1.0	<5.0		µg/L	WA	0
		Chloride		9,510	8,910	8,720		µg/L	WA	0
		Chlorobenzene		<5.0	<1.0	<5.0		µg/L	WA	0
		Chloroethane		<10	<1.0	<10		µg/L	WA	0
		Chloroethane (Vinyl chloride)		<10	<1.0	<10		µg/L	WA	0
		2-Chloroethyl vinyl ether		<10	<1.0	<10		µg/L	WA	0
		Chloroform		3.2	2.3	2.2	J	µg/L	WA	0
		Chloromethane (Methyl chloride)		<10	<1.0	<10		µg/L	WA	0
		Chromium		<1.1	1.7	1.1	J3	µg/L	WA	0
		Dibromochloromethane		<5.0	<1.0	<5.0		µg/L	WA	0
		1,1-Dichloroethane		<5.0	<1.0	<5.0		µg/L	WA	0
		1,2-Dichloroethane		<5.0	<1.0	<5.0		µg/L	WA	0
		1,1-Dichloroethylene		<5.0	<1.0	<5.0		µg/L	WA	0
		trans-1,2-Dichloroethylene		<5.0	<1.0	<5.0		µg/L	WA	0
		Dichloromethane (Methylene chloride)		8.1	5.0	<5.0		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid		<1.1	<0.30	<1.0		µg/L	WA	0
		1,2-Dichloropropane		<5.0	<1.0	<5.0		µg/L	WA	0
		cis-1,3-Dichloropropene		<5.0	<1.0	<5.0		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 8 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		trans-1,3-Dichloropropene		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Endrin		< 0.11	< 0.0060	< 0.11		µg/L	WA	0
		Ethylbenzene		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Fluoride		< 100	< 100	< 100		µg/L	WA	0
		Gross alpha		3.1E+00	3.5E+00	2.3E+00		pCi/L	CN	0
		Iron		11	133	226		µg/L	WA	1
		Lead		< 2.0	5.4	< 2.0		µg/L	WA	0
		Lindane		< 0.053	< 0.0050	< 0.055		µg/L	WA	0
		Magnesium		631	783	701	V	µg/L	WA	0
		Manganese		34	37	24		µg/L	WA	0
		Mercury		< 0.20	< 0.20	< 0.20		µg/L	WA	0
		Methoxychlor		< 0.53	< 0.50	< 0.55		µg/L	WA	0
		Nitrate as nitrogen		262	525	212		µg/L	WA	0
		Nitrate-nitrite as nitrogen			270			µg/L		
		Nonvolatile beta		< 5.0E+00	3.3E+00	< 2.0E+00		pCi/L	CN	0
		pH		5.9	8.4	5.8	J	pH	WA	0
		Phenols		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Potassium		457	947	248	V	µg/L	WA	0
		Radium-226		< 5.0E-01	1.7E+00	< 1.0E+00		pCi/L	CN	0
		Radium-228		9.8E-01	2.1E+00	< 1.0E+00		pCi/L	CN	0
		Selenium		< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Silica		6,850	7,040	4,540	V	µg/L	WA	0
		Silver		< 0.70	1.7	< 0.70		µg/L	WA	0
		Sodium		46,000	54,300	46,200	V	µg/L	WA	0
		Specific conductance		239	300	241	J	µS/cm	WA	0
		Sulfate		85,800	109,000	90,300		µg/L	WA	0
		1,1,2,2-Tetrachloroethane		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Tetrachloroethylene		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Toluene		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Total activity		3.3E+03	2.5E+03			pCi/L		
		Total dissolved solids		170,000	182,000	169,000	J	µg/L	WA	0
		Total organic carbon		838	696	1,080		µg/L	WA	0
		Total organic halogens		< 10	5.2	9.3		µg/L	WA	0
		Total phosphates (as P)		< 20	2,000	26		µg/L	WA	0
		Toxaphene		< 1.1	< 0.24	< 1.1		µg/L	WA	0
		2,4,5-TP (Silvex)		< 0.55	< 0.090	< 0.52		µg/L	WA	0
		1,1,1-Trichloroethane		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		1,1,2-Trichloroethane		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Trichloroethylene		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Trichlorofluoromethane		< 5.0	< 1.0	< 5.0		µg/L	WA	0
		Tritium		< 2.0E+00	1.7E+00	< 7.0E-01		pCi/mL	CN	0
		Turbidity			2.6	0.60	J	NTU	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

● = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

WELL KAC 9

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Formation
N53197.8 E42588.1	33.212918 °N 81.657996 °W	210.9-190.9 ft msl	262.2 ft msl	4" PVC	S	Water table

SAMPLE DATE	06/09/92	08/02/92	11/20/92
-------------	----------	----------	----------

FIELD DATA

Analyte	1Q92	2Q92	3Q92	4Q92	Unit
Water elevation		213.8	213.7	213.3	ft msl
pH		10.2	10.4	10.2	pH
Sp. conductance		935	930	919	µS/cm
Water temperature		21.6	21.7	19.4	°C
Alkalinity as CaCO ₃		131	126	88	mg/L
Volume purged		5.1	4.1	3.1	Well vol.

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Arsenic	< 2.0	5.4	3.1	3.1	J3	µg/L	WA	0
		Barium	17	17	19	19	J3	µg/L	WA	0
		Benzene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Bromodichloromethane	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Bromoform	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Bromomethane (Methyl bromide)	< 10	< 10	< 10	< 10		µg/L	WA	0
		Cadmium	0.78	< 0.35	< 0.35	< 0.35	V	µg/L	WA	0
		Calcium	27,600	23,900	22,200	22,200	V	µg/L	WA	0
		Carbon tetrachloride	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Chloride	13,900	22,600	14,200	14,200		µg/L	WA	0
		Chlorobenzene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Chloroethane	< 10	< 10	< 10	< 10		µg/L	WA	0
		Chloroethane (Vinyl chloride)	< 10	< 10	< 10	< 10		µg/L	WA	0
		2-Chloroethyl vinyl ether	< 10	< 10	< 10	< 10		µg/L	WA	0
		Chloroform	6.2	2.6	2.3	2.3	J	µg/L	WA	0
		Chloromethane (Methyl chloride)	< 10	< 10	< 10	< 10		µg/L	WA	0
		Chromium	27	13	6.9	6.9		µg/L	WA	0
		Dibromochloromethane	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		1,1-Dichloroethane	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		1,2-Dichloroethane	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		1,1-Dichloroethylene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		trans-1,2-Dichloroethylene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Dichloromethane (Methylene chloride)	7.5	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		2,4-Dichlorophenoxyacetic acid	< 1.1	< 1.1	< 1.0	< 1.0		µg/L	WA	0
		1,2-Dichloropropane	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		cis-1,3-Dichloropropene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		trans-1,3-Dichloropropene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Endrin	< 0.11	< 0.11	< 0.11	< 0.11		µg/L	WA	0
		Ethylbenzene	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Fluoride	318	229	193	193		µg/L	WA	0
		Gross alpha	< 3.0E + 00	< 2.0E + 00	< 2.0E + 00	< 2.0E + 00		pCi/L	CN	0
		Iron	50	19	113	113		µg/L	WA	0
		Lead	< 2.0	< 2.0	< 2.0	< 2.0		µg/L	WA	0
		Lindane	< 0.053	< 0.055	< 0.055	< 0.055		µg/L	WA	0
		Magnesium	593	907	1,100	1,100	V	µg/L	WA	0
		Manganese	1.3	3.5	9.5	9.5		µg/L	WA	0
		Mercury	< 0.20	< 0.20	< 0.20	< 0.20		µg/L	WA	0
		Methoxychlor	< 0.53	< 0.55	< 0.55	< 0.55		µg/L	WA	0
		Nitrate as nitrogen	814	1,030	711	711		µg/L	WA	0
		Nonvolatile beta	< 5.0E + 00	< 2.0E + 00	3.8E + 00	3.8E + 00		pCi/L	CN	0
		pH	11	9.9	9.7	9.7	J	pH	WA	1
		Phenols	< 5.0	< 5.0	< 5.0	< 5.0		µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Well KAC 9 continued

ANALYTICAL DATA

H	D	Analyte	1Q92	2Q92	3Q92	4Q92	Mod	Unit	Lab	Flag
		Potassium		2,240	1,910	2,010	V	µg/L	WA	0
		Radium-226		< 5.0E-01	< 1.0E + 00	< 1.0E + 00		pCi/L	CN	0
		Radium-228		5.6E-01	< 1.0E + 00	1.1E + 00		pCi/L	CN	0
		Selenium		2.0	2.2	< 2.0		µg/L	WA	0
		Silica		10,300	10,600	10,500	V	µg/L	WA	0
		Silver		< 0.70	< 0.70	< 0.70		µg/L	WA	0
		Sodium		150,000	158,000	155,000	V	µg/L	WA	0
•		Specific conductance		253	903	692	J	µS/cm	WA	2
		Sulfate		270,000	319,000	309,000		µg/L	WA	1
		1,1,2,2-Tetrachloroethane		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Tetrachloroethylene		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Toluene		2.0	2.6	< 5.0		µg/L	WA	0
		Total activity		6.9E + 03	5.7E + 03			pCi/L		
•		Total dissolved solids		519,000	610,000	619,000	J	µg/L	WA	0
		Total organic carbon		1,420	1,240	1,080		µg/L	WA	0
		Total organic halogens		28	< 5.0	18		µg/L	WA	0
		Total phosphates (as P)		90	94	142		µg/L	WA	0
		Toxaphene		< 1.0	< 1.1	< 1.1		µg/L	WA	0
		2,4,5-TP (Silvex)		< 0.55	< 0.55	< 0.52		µg/L	WA	0
		1,1,1-Trichloroethane		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		1,1,2-Trichloroethane		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Trichloroethylene		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Trichlorofluoromethane		< 5.0	< 5.0	< 5.0		µg/L	WA	0
		Tritium		2.4E + 00	2.1E + 00	2.8E + 00		pCi/mL	CN	0
•		Turbidity			0.65	0.70	J	NTU	WA	0

Note: Flagging levels, modifiers, and laboratories are for 4th quarter 1992 data only. See Appendix B for flagging criteria.

• = exceeded holding time for 4th quarter 1992.

■ = exceeded final primary drinking water standard for 4th quarter 1992.

Appendix E – Data Quality/Useability Assessment

Data Quality/Useability Assessment

Quality assurance/quality control (QA/QC) procedures relating to accuracy and precision of analyses performed on groundwater samples are followed in the field and laboratory and are reviewed prior to publication of results. The Environmental Protection Department/Environmental Monitoring Section's (EPD/EMS) review of the volume of analytical data acquired each quarter and presented in various reports is an ongoing process; its review of the QA/QC data cannot be completed in time to meet the deadlines for the reports required by the Resource Conservation and Recovery Act and associated regulations. Other site and regulatory personnel can obtain further information on the data quality and useability in a variety of ways, including those described below.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific QA/QC information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by EPD/EMS and provided to the primary laboratories are presented in Appendix D.

Assessment of Accuracy of the Data

Accuracy, or the nearness of the reported result to the true concentration of a constituent in a sample, can be assessed in several ways.

A laboratory's general accuracy can be judged by analysis of results obtained from known samples. The non-radionuclide contract laboratories analyze commercial reference samples every quarter at EPD/EMS' request. The results of these analyses are presented in the EPD/EMS quarterly report, *The Savannah River Site's Groundwater Monitoring Program*. The primary laboratories also seek or maintain state certification by participating periodically in performance studies; reference samples and analysis of results are provided by EPA. Results of these studies also are published in the EPD/EMS quarterly reports.

Analysis of blanks provides a tool for assessing the accuracy of both sampling and laboratory analysis. Results for all field blanks for the quarter can be found in the EPD/EMS quarterly reports. Any field or laboratory blanks that exceeded established minimums are identified in the same reports, in tables associating them with groundwater samples analyzed in the same batches.

Surrogates, organic compounds similar in chemical behavior to the compounds of interest but not normally found in environmental samples, are used to monitor the effect of the matrix on the accuracy of analyses for organic parameters. For example, for analyses of volatile organics by EPA method 8240, three surrogate compounds are added to all samples

and blanks in each analytical batch. In analyses of semivolatile organics, three to four acid compounds and three to four base/neutral compounds are used. Other surrogates are used in pesticides analyses. Percent recoveries for surrogate analyses are calculated by laboratory personnel, reported to EPD/EMS, reviewed, and entered into the database, but they are not published. If recoveries are not within specified limits, the laboratory is expected to re-run the samples or attach result qualifiers to the data identifying the anomalous results.

Sample-specific accuracy for both organic and inorganic parameters can be assessed by examination of matrix spike/matrix spike duplicate results. A sample is analyzed unspiked to determine a baseline set of values. A second portion of sample is spiked with known concentrations of compounds appropriate to the analyses being performed, typically 5 volatile organic compounds for volatile organic analyses, 11 semivolatile compounds for semivolatiles, 6 pesticide compounds for pesticides, all metals for metals analyses, and a known quantity of cyanide for cyanide analysis. The percentage of the spike compound which is recovered, i.e., measured in excess of the value obtained for the unspiked sample, is a direct measure of analytical accuracy. EPA requires matrix spike/matrix spike duplicates to be run at least once per 20 samples of similar matrix.

Matrix spike/matrix spike duplicate results are reported to EPD/EMS but are not published. For organic compounds, according to EPA guidelines, no action is taken on the basis of matrix spike/matrix spike duplicate data alone (i.e., no result modifiers are assigned solely on the basis of matrix spike results); however, the results can indicate if a lab is having a systematic problem in the analysis of one or more analytes.

In the case of inorganic compounds, such as metals, the matrix spike sample analysis provides information about the effect of each sample matrix on the digestion and measurement methodology. Data qualifiers can be assigned on the basis of the percentage of spike recovery and are reported in the published results tables.

Assessment of Precision

Precision of the analyses, or agreement of a set of replicate results among themselves, is assessed through the use of duplicates (laboratory-initiated) and blind replicates (provided by EPD/EMS). The results of duplicate and replicate analyses are presented in the results tables of the first, second, and third quarter reports as multiple entries for an analyte under a single well heading. The results of replicate analyses are presented in the results tables in first, second, and third quarter reports as two separate sets of results for the same well. Duplicate and replicate results are not presented in fourth quarter reports; the results tables present instead only the highest result for each analyte for each quarter of the year.

The laboratories assess precision by calculating the relative percent difference, or RPD, for each pair of laboratory-initiated duplicate results. During 1992, at least one of the contract laboratories used a data qualifier (J3) to modify metals analyses when the RPD for laboratory duplicates was greater than 20%.

Additional statistical comparisons of laboratory duplicate and blind replicate results, both intra- and interlaboratory, are presented in the EPD/EMS quarterly reports. The calculation used for these reports is the MRD, or mean relative difference, which is similar to EPA's RPD except that the MRD provides a single value for all of the analyses of a particular compound, either inter- or intralaboratory, during one quarter. Because detection limits may vary among samples, the MRD requires calculation of a reference detection limit, which is the detection limit at the 90th percentile of the array of limits in the population of all replicate and duplicate analyses for a given analyte during a particular quarter. The MRD is not method-specific.

Method-Specific Accuracy and Precision

The contract laboratories' EPA-approved laboratory procedures include QA/QC requirements as an integral part of the methods. Thus, knowledge of the method used in obtaining data is an important component of determining data useability. EPA has conducted extensive research and development on the methods approved for the analysis of water and waste water; information on the accuracy and precision of the method is available from EPA publications, as is full information on required QA/QC procedures. A listing of the methods used by the primary laboratories during first quarter 1992 is given below along with the source for the method description. Many, if not all, of these sources include presentations of representative accuracy and precision results.

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA120.1	Specific conductance	EPA EMSL 1983
EPA150.1	pH	EPA EMSL 1983
EPA160.1	Filterable residue (total dissolved solids)	EPA EMSL 1983
EPA160.2	Nonfilterable residue	EPA EMSL 1983
EPA180.1	Turbidity	EPA EMSL 1983
EPA200.7	Trace elements	EPA EMSL 1983
EPA206.2	Arsenic	EPA EMSL 1983
EPA208.2	Barium	EPA EMSL 1983
EPA239.2	Lead	EPA EMSL 1983
EPA245.1	Mercury	EPA EMSL 1983
EPA270.2	Selenium	EPA EMSL 1983
EPA279.2	Thallium	EPA EMSL 1983
EPA300.0	Inorganics, non-metallics	EPA EMSL 1991
EPA310.1	Alkalinity	EPA EMSL 1983
EPA325.2	Chloride	EPA EMSL 1983
EPA335.3	Cyanide	EPA EMSL 1983
EPA340.2	Fluoride	EPA EMSL 1983
EPA353.1	Nitrogen, nitrate-nitrite	EPA EMSL 1983
EPA353.2	Nitrogen, nitrate, nitrite, or combined	EPA EMSL 1983
EPA353.3	Nitrogen, nitrate-nitrite, or nitrite only	EPA EMSL 1983
EPA354.1	Nitrogen, nitrite	EPA EMSL 1983
EPA365.1	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA365.2	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA375.4	Sulfate, turbidimetric	EPA EMSL 1983
EPA376.2	Sulfide	EPA EMSL 1983
APHA403	Alkalinity	APHA 1985
EPA413.1	Oil & grease	EPA EMSL 1983
APHA415A	Iodine	APHA 1985

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA415.1	Total organic carbon	EPA EMSL 1983
EPA418.1	Petroleum hydrocarbons	EPA EMSL 1983
EPA420.1	Phenolics	EPA EMSL 1983
EPA420.2	Phenolics	EPA EMSL 1983
APHA705	Total alpha-emitting radium	APHA 1985
ASTMD3869C	Iodide	ASTM 1992
APHA5320	Dissolved organic halogen	APHA 1989
EPA6010	Metals	EPA 1986
EPA7041	Antimony	EPA 1986
EPA7060	Arsenic	EPA 1986
EPA7421	Lead	EPA 1986
EPA7470	Mercury	EPA 1986
EPA7740	Selenium	EPA 1986
EPA7841	Thallium	EPA 1986
EPA8010	Halogenated volatile organics	EPA 1986
EPA8020	Aromatic volatile organics	EPA 1986
EPA8080	Organochlorine pesticides and PCBs	EPA 1986
EPA8140	Organophosphorus pesticides	EPA 1986
EPA8150	Chlorinated herbicides	EPA 1986
EPA8240	GCMS VOA	EPA 1986
EPA8270	GCMS semivolatiles	EPA 1986
EPA8280	Dioxins and furans	EPA 1986
EPA9012	Total cyanide	EPA 1986
EPA9020	Total organic halides	EPA 1986
EPA9030	Sulfides	EPA 1986

An example of the available method-specific QA/QC information is that for the analysis of metals by EPA Method 6010/200.7 (EPA 1986/EPA EMSL 1983). The primary laboratories, General Engineering Laboratories (GE) and Roy F. Weston, Inc. (Weston), use this inductively coupled plasma (ICP) atomic emission spectrometric method.

The following precision and accuracy data are based on the experience of seven laboratories that applied the ICP technique to acid-distilled water matrices that had been dosed with various metal concentrates. (Note: not all seven laboratories analyzed all 14 elements.) The references give results for samples having three concentration ranges; the results here are for samples having the lowest values, similar to actual groundwater results for SRS.

ICP Precision and Accuracy Data

<u>Element</u>	<u>True value ($\mu\text{g/L}$)</u>	<u>Mean reported value ($\mu\text{g/L}$)</u>	<u>Mean percent RSD^a</u>
Beryllium	20	20	9.8
Manganese	15	15	6.7
Vanadium	70	69	2.9
Arsenic	22	19	23
Chromium	10	10	18
Copper	11	11	40
Iron	20	19	15
Aluminum	60	62	33

Element	True value ($\mu\text{g/L}$)	Mean reported value ($\mu\text{g/L}$)	Mean percent RSD ^a
Cadmium	2.5	2.9	16
Cobalt	20	20	4.1
Nickel	30	28	11
Lead	24	30	32
Zinc	16	19	45
Selenium	6	8.5	42

Note: In EPA (1986), the column heading is Mean Standard Deviation (%).

^a Relative standard deviation.

As another example, EPA Method 601/8010 (EPA 1991a/EPA 1986) is used by both GE and Weston for analyses of halogenated volatile organics. In the presentation of the method in both references, the following table gives method-specific accuracy and precision as functions of concentration. Contract laboratories are expected to achieve or at least approach these limits.

Accuracy and Precision as Functions of Concentration for EPA Method 601/8010

Parameter	Accuracy as recovery, X'^a ($\mu\text{g/L}$)	Single analyst precision ($\mu\text{g/L}$) ^b	Overall precision ($\mu\text{g/L}$) ^c
Bromodichloromethane	$1.12C - 1.02^d$	$0.11\bar{X} + 0.04^e$	$0.20\bar{X} + 1.00$
Bromoform	$0.96C - 2.05$	$0.12\bar{X} + 0.58$	$0.21\bar{X} + 2.41$
Bromomethane	$0.76C - 1.27$	$0.28\bar{X} + 0.27$	$0.36\bar{X} + 0.94$
Carbon tetrachloride	$0.98C - 1.04$	$0.15\bar{X} + 0.38$	$0.20\bar{X} + 0.39$
Chlorobenzene	$1.00C - 1.23$	$0.15\bar{X} - 0.02$	$0.18\bar{X} + 1.21$
Chloroethane	$0.99C - 1.53$	$0.14\bar{X} - 0.13$	$0.17\bar{X} + 0.63$
2-Chloroethyl vinyl ether ^f	$1.00C$	$0.20\bar{X}$	$0.35\bar{X}$
Chloroform	$0.93C - 0.39$	$0.13\bar{X} + 0.15$	$0.19\bar{X} - 0.02$
Chloromethane	$0.77C + 0.18$	$0.28\bar{X} - 0.31$	$0.52\bar{X} + 1.31$
Dibromochloromethane	$0.94C + 2.72$	$0.11\bar{X} + 1.10$	$0.24\bar{X} + 1.68$
1,2-Dichlorobenzene	$0.93C + 1.70$	$0.20\bar{X} + 0.97$	$0.13\bar{X} + 6.13$
1,3-Dichlorobenzene	$0.95C + 0.43$	$0.14\bar{X} + 2.33$	$0.26\bar{X} + 2.34$
1,4-Dichlorobenzene	$0.93C - 0.09$	$0.15\bar{X} + 0.29$	$0.20\bar{X} + 0.41$
1,1-Dichloroethane	$0.95C - 1.08$	$0.09\bar{X} + 0.17$	$0.14\bar{X} + 0.94$
1,2-Dichloroethane	$1.04C - 1.06$	$0.11\bar{X} + 0.70$	$0.15\bar{X} + 0.94$
1,1-Dichloroethene	$0.98C - 0.87$	$0.21\bar{X} - 0.23$	$0.29\bar{X} - 0.40$
trans-1,2-Dichloroethene	$0.97C - 0.16$	$0.11\bar{X} + 1.46$	$0.17\bar{X} + 1.46$
1,2-Dichloropropane ^f	$1.00C$	$0.13\bar{X}$	$0.23\bar{X}$
cis-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
trans-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
Methylene chloride	$0.91C - 0.93$	$0.11\bar{X} + 0.33$	$0.21\bar{X} + 1.43$
1,1,2,2-Tetrachlorethane	$0.95C + 0.19$	$0.14\bar{X} + 2.41$	$0.23\bar{X} + 2.79$
Tetrachloroethylene	$0.94C + 0.06$	$0.14\bar{X} + 0.38$	$0.18\bar{X} + 2.21$
1,1,1-Trichloroethane	$0.90C - 0.16$	$0.15\bar{X} + 0.04$	$0.20\bar{X} + 0.37$
1,1,2-Trichloroethane	$0.86C + 0.30$	$0.13\bar{X} - 0.14$	$0.19\bar{X} + 0.67$
Trichloroethylene	$0.87C + 0.48$	$0.13\bar{X} - 0.03$	$0.23\bar{X} + 0.30$

<u>Parameter</u>	<u>Accuracy as recovery, X'^a ($\mu\text{g/L}$)</u>	<u>Single analyst precision ($\mu\text{g/L}$)^b</u>	<u>Overall precision ($\mu\text{g/L}$)^c</u>
Trichlorofluoromethane	$0.89C - 0.07$	$0.15\bar{X} + 0.67$	$0.26\bar{X} + 0.91$
Vinyl chloride	$0.97C - 0.36$	$0.13\bar{X} + 0.65$	$0.27\bar{X} + 0.40$

- ^a X' = expected recovery for one or more measurements of a sample containing a concentration of C , in $\mu\text{g/L}$.
^b Expected single analyst standard deviation of measurements.
^c Expected interlaboratory standard deviation of measurements.
^d C = true value for the concentration, in $\mu\text{g/L}$.
^e $\bar{X}$ = average recovery found for measurements of samples containing a concentration of C , in $\mu\text{g/L}$.
^f Estimates based on performance in a single laboratory.

References

APHA (American Public Health Association), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition. Washington, DC.

APHA (American Public Health Association), 1989. **Standard Methods for the Examination of Water and Wastewater**, 17th edition. Washington, DC.

ASTM (American Society for Testing and Materials), 1992. **1992 Annual Book of ASTM Standards**, Volume 11.02, Water (II). Philadelphia, PA.

CFR (Code of Federal Regulations), 1991. *Analytical Methods, Title 40, Part 136*, Appendix A. Revised July 1, 1991. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. **Test Methods for Evaluating Solid Waste (SW-846)**, Volumes IA-IC. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1987. **Data Quality Objectives for Remedial Response Activities**. PB88-131870; EPA/540/G-87/003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1988a. **Contract Laboratory Program Statement of Work for Inorganics Analysis, Multi-Media, Multi-Concentration**. SOW No. 788. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1988b. **Contract Laboratory Program Statement of Work for Organics Analysis Multi-Media, Multi-Concentration**. SOW No. 288. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. **Guidance for Data Useability in Risk Assessment**. Interim Final. EPA/540/G-90/008. Washington, DC.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1979. **Handbook for Analytical Quality Control in Water Wastewater Laboratories**. PB-297 451; EPA-600/4-79-019. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1983. **Methods for Chemical Analysis of Water and Wastes**. Revised March 1983. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1991. **Test Method, The Determination of Inorganic Anions in Water by Ion Chromatography – Method 300.0**. Revised August 1991. Cincinnati, OH.

**DATE
FILMED**

8 / 4 / 93

END