USGS-OFR--78-105D

DE83 902137

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Audio-magnetotelluric Data Log and Station Location Map

for the

Saline Valley Known Geothermal Resource Area, California

by

R. M. Senterfit and D. D. Moeller

Open-File Report 78-105D

1978

MASTER

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE
PORTIONS OF THIS REPORT ARE ILLEGIBLE.
It has been reproduced from the best
available copy to permit the broadest
possible availability.

WHS

PURCHASE ORDER NO. 03X-50492
RECEIVED 5-23-83

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

AUDIO-MAGNETOTELLURIC STATION LOCATION MAP

SALINE VALLEY KNOWN GEOTHERMAL RESOURCE AREA, CALIFORNIA

R.M. SENTERFIT & D.D. MOELLER

SALINE VALLEY U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

KGRA pa = observed apparent resistivity in ohm-metres
 N = number of observations
 Er = standard error in ohm metres : - = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1 _{NS}	pa	102.6	131.8	283.2	101.0	137.1	—	—	—	—	103.5	—	9.7
	N	5	4	5	4	4					5		1
	Er	16.2	10.3	89.0	27.7	12.2					8.2		—
1 _{EW}	pa	124.3	64.5	17.6	13.7	20.3	7.1	—	—	—	17.8	—	12.0
	N	5	4	4	5	4	4				3		1
	Er	23.0	6.7	16.2	4.9	1.2	1.3				2.3		—
2 _{NS}	pa	66.8	49.8	39.0	13.7	8.0	3.2	—	—	—	46.3	16.2	7.1
	N	7	3	2	6	6	6				5	1	1
	Er	8.5	8.2	2.4	4.0	2.5	0.4				11.3	—	—
2 _{EW}	pa	31.5	42.0	—	5.7	5.4	2.9	—	—	—	5.6	5.9	4.7
	N	4	5		6	6	6				5	1	1
	Er	9.7	13.2		0.8	0.2	1.0				0.4	—	—
3 _{NS}	pa	51.5	70.4	67.9	4.5	2.3	3.3	—	—	—	—	23.4	19.5
	N	5	5	5	4	4	4					1	1
	Er	5.3	9.3	3.6	1.1	0.2	0.3					—	—
3 _{EW}	pa	54.7	61.7	36.7	2.2	1.8	2.9	—	—	—	11.6	29.7	5.1
	N	6	6	4	4	4	4				5	1	1
	Er	12.1	19.5	9.7	0.9	0.3	0.5				1.0	—	—
4 _{NS}	pa	19.3	10.1	8.6	13.9	10.2	2.1	—	—	—	47.2	14.6	1.5
	N	4	6	6	6	7	4				2	1	1
	Er	3.8	2.0	2.3	1.5	1.1	0.1				3.4	—	—
4 _{EW}	pa	12.0	6.4	5.7	6.9	4.0	—	—	—	—	1.8	7.3	2.2
	N	6	5	5	6	5					3.0	1	1
	Er	3.4	2.1	1.1	0.9	0.2					0.9	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

[illegible]