2

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

WSRC-IM--92-23

DE92 019347

SAVANNAH RIVER SITE COMPUTING STANDARDS AND GUIDELINES REFERENCE (U)

by

Computer Architecture and Standards Team

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

A technical report being deposited at OSTI

Received by OSTI
April 1, 1992

The information contained in this paper was developed during the course of work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this paper the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Savannah River Site Computing Standards and Guidelines Reference (U)

Received by DSA

APR 1 1992

Computer

Architecture and

Standards

Team

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

WSRC-IM-92-23

SRS Computing Standards and Guidelines Reference (U)

WSRC-IM-92-23

SRS Computing Standards and Guidelines Reference (U)

WSRC-IM-92-23

SRS Computing Standards and Guidelines Reference (U)

WSRC-IM-92-23

SRS Computing Standards and Guidelines Reference (U)

Savannah River Site Computing Standards and Guidelines Reference (U)

Publication Date: 4/1/92

Authorized Derivative Classifier

G. F. Hayhoe

Computing

**Architecture and
Standards
Team**

**Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808**

Prepared for the U. S. Department of Energy Under Contract No. DE-AC09-89SR18035

CONTENTS

Introduction (Rev 0, 4/1/92)

T0.0 Technology Guidelines (Rev 0, 4/1/92)

T1.0 Operating Systems Services Technology Group (Rev 0, 4/1/92)

T1.1 POSIX (Rev 0, 4/1/92)

T1.2 XPG3 (Rev 0, 4/1/92)

T1.3 C2 Security (Rev 0, 4/1/92)

T2.0 User Interfaces Services Technology Group (Rev 0, 4/1/92)

T2.1 X Windows (Rev 0, 4/1/92)

T2.2 OSF/Motif (Rev 0, 4/1/92)

T2.3 PEX (Rev 0, 4/1/92)

T3.0 Program Services Technology Group (Rev 0, 4/1/92)

T3.1 ANSI COBOL (Rev 0, 4/1/92)

T3.2 ANSI FORTRAN (Rev 0, 4/1/92)

T3.3 ANSI C (Rev 0, 4/1/92)

T4.0 Data Management Services Technology Group (Rev 0, 4/1/92)

T4.1 SQL (Rev 0, 4/1/92)

T4.2 NFS/RPC (Rev 0, 4/1/92)

T4.3 DCE (Rev 0, 4/1/92)

T4.4 RDA (Rev 0, 4/1/92)

T4.5 DES (Rev 0, 4/1/92)

T4.6 DAL (Rev 0, 4/1/92)

T5.0 Data Interchange Services Technology Group (Rev 0, 4/1/92)

T5.1 ODA/ODIF (Rev 0, 4/1/92)

T5.2 SGML (Rev 0, 4/1/92)

T5.3 CCITT III and IV (Rev 0, 4/1/92)

T5.4 TIFF (Rev 0, 4/1/92)

T5.5 CGM (Rev 0, 4/1/92)

T5.6 IGES (Rev 0, 4/1/92)

T5.7 EDI (Rev 0, 4/1/92)

T5.8 RTF (Rev 0, 4/1/92)

T5.9 Postscript (Rev 0, 4/1/92)

T5.10 X.400 (Rev 0, 4/1/92)

T5.11 X.500 (Rev 0, 4/1/92)

T5.12 ASCII (Rev 0, 4/1/92)

T6.0 Graphics Services Technology Group (Rev 0, 4/1/92)

T6.1 GKS (Rev 0, 4/1/92)

T6.2 PHIGS (Rev 0, 4/1/92)

CONTENTS

T7.0 Network Services Technology Group (Rev 0, 4/1/92)

- T7.1 Ethernet (Rev 0, 4/1/92)**
- T7.2 Token Ring (Rev 0, 4/1/92)**
- T7.3 FDDI (Rev 0, 4/1/92)**
- T7.4 OSI (Rev 0, 4/1/92)**
- T7.5 TCP/IP (Rev 0, 4/1/92)**
- T7.6 DECnet / LAT (Rev 0, 4/1/92)**
- T7.7 SNA (Rev 0, 4/1/92)**
- T7.8 XNS / IPX (Rev 0, 4/1/92)**
- T7.9 AppleTalk (Rev 0, 4/1/92)**
- T7.10 SNMP (Rev 0, 4/1/92)**
- T7.11 Kerberos (Rev 0, 4/1/92)**

T8.0 Hardware Interfaces Technology Group (Rev 0, 4/1/92)

- T8.1 CD-ROM Disk Format (ISO 9660-1988) (Rev 0, 4/1/92)**
- T8.2 RS-232 (Rev 0, 4/1/92)**
- T8.3 RS-449/RS-422/RS-423 (Rev 0, 4/1/92)**
- T8.4 V.35 (Rev 0, 4/1/92)**
- T8.5 SCSI (Rev 0, 4/1/92)**
- T8.6 Centronics (Rev 0, 4/1/92)**

P0.0 Standard Products

Attachment A. Computing Acronyms and Terms

Attachment B. Organizations Producing Standards Documents

Purpose

It is WSRC policy that site computing activities be based on standards (Reference 1). The primary reasons for defining the site's computing standards and guidelines are to promote interoperability of site computing systems and to facilitate the portability of programs, applications, and data between computer systems. This policy is necessary to obtain increased flexibility and cost effectiveness in carrying out the site mission.

The SRS computing standards will depend heavily on national and international standards, although standardization on dominant proprietary standards and on specific products will be required to reduce the total number of computer products supported at the site to a more manageable set. In other words, the emphasis on standards will be two-fold: standardization on the technologies required for information and process control systems integration, and standardization on specific products in order to keep the number of specific computer products that must be supported on the site to a manageable and economical set. Ideally, standard products will conform to the technology standards. However, there will be cases where existing standard products do not conform totally to the technology standards yet remain supported for reasons of continuity and economics.

A site-wide Computing Council has been formed (Reference 2) to coordinate and integrate computing activities at SRS. This organization consists of senior management representing each site division. It oversees the development and implementation of the site strategic computing vision in support of the site mission. The working arm of the Computing Council is the Computing Architecture and Standards Team (CAST). CAST is made up of representatives from all site divisions as well as other organizations that represent communities interested in computing, such as the Process Digital Equipment Committee (PDEC), the Engineering/Scientific Computer Committee (ESCC), and the Management Informations Systems Committee. CAST membership is knowledgeable in computing technologies and the use of computing to help perform the site's mission. This body is instrumental in setting standards for site computing and creating the site's computing architecture, as well as recommending computing policies to the Computing Council for consideration.

Technology Standards

A computing technology standard is defined by some international, national, industry consortium, or individual corporation as a standard way of accomplishing specific computing tasks or functions. These standards are "open" in the sense that the governing bodies publish the specifications in complete detail so that vendors may develop products that conform to the standards. In many cases the governing body for a standard will test and certify those vendor products that conform to the technology standard.

Various international and national bodies are developing so called "open" system standards for computing to promote non-proprietary means of achieving this sort of interoperability and portability. Such organizations include:

International Standards Organization (ISO)
American National Standards Institute (ANSI)
Open Systems Foundation (OSF)
Institute of Electrical and Electronics Engineers (IEEE)
National Institute of Standards and Technology (NIST)
Instrument Society of America (ISA)

Attachment B to this reference provides a more comprehensive list of standards organizations along with instructions on how to obtain standards documents.

The United States Government, in general, and the Department of Energy (DOE) in particular support these standards. As a standard matures, the government may mandate its use at government facilities. This has already occurred for computer communications protocols under the Government Open Systems Interconnection Profile (GOSIP) program (Reference 3).

This document defines the computing technologies adopted by CAST as site guidelines and represent those current and emerging technologies which are relevant to the site. These technologies provide a firm foundation for implementing the site computing architecture (Reference 4), in that they define specifications for interoperability and portability to which computing systems developed at or purchased by the site ideally should conform.

Technology standards can be characterized by their maturity and penetration in the computer industry as well as by their strategic importance for the future (Reference 5). Some standards are mature and well supported by the computer hardware and software manufacturers. Other standards are emerging; that is, they have been defined and generally accepted, but as yet few products implement the standard. In some cases the relevance of particular standards overlap. For example, a mature standard is likely to be superseded by an emerging one judged by the industry or the government to have more long term strategic importance. Implementers and purchasers of computer systems and applications often must choose between mature and emerging standards to support.

Today, many of the computer technology standards are in a state of flux. There are technologies for which multiple organizations are attempting to establish competing standards and others for which there is no existing or even emerging standard. The state of each of the technology standards defined in this document is explained to give some guidance to site personnel in choosing between standards. Because of the constant evolution of computer technology and standards, this document will be updated periodically.

Reference 6 describes those technology standards endorsed for use by the U. S. Government. Reference 7 provides the Department of Energy policy in support of Automated Data Processing (ADP) standards.

Standard Products

In addition to providing guidelines on the use of technology standards, CAST is working to establish site standards for specific computing products. These standard products will be established by CAST via competitive procurements or via endorsement of existing site de facto standards.

Site personnel who purchase computing products should determine whether site standard products that can satisfy their requirements exist. If so, then the site standard products should be used. In many cases, the acquisition of the standard products will be facilitated. It is the intent of the site policy for computing standards, MP 3.11, to allow the use of non-standard products by exception only. Such exceptions will require justification. In addition, when a purchaser of computer equipment needs capabilities not supplied by site standard products, then it is incumbent on the purchaser to consider the site computing technology standards as defined here, as well as interoperability requirements with existing systems and standard products. Relevant technology standards should be included as requirements in the technical specifications that new purchased products or developed systems are to meet.

This document defines the computing products that have been established as standards by CAST. Standard products generally are compatible with the site computing architecture and technology guidelines, but may reflect tactical compromises dictated by cost, past practices, or the commercial availability of certain technologies.

References

1. WSRC 1-01, *Management Policies*, MP 3.11, "Computing Standards and Guidelines"
2. WSRC 1-01, *Management Policies*, MP 3.12, "Computing Coordination and Integration"
3. WSRC 1-01, *Management Policies*, MP 3.14, "Government Open Systems Interconnection Profile (GOSIP) Compliance"
4. WSRC-IM- 91-18-1, Savannah River Site Computing Architecture
5. *Application Portability Profile (APP): The U. S. Government's Open System Environment Profile OSE/1 Version 1.0*, NIST Special Publication 500-187
6. *Federal ADP and Telecommunications Standards Index*, U. S. General Services Administration, Information Resources Management Service, April 1991

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: Introduction
Page: 4 of 4
Issue Date: 4/1/92
Revision: 0

Introduction

7. U.S. Department of Energy Order 1360.3B, *Automatic Data Processing Standards*, November 15, 1990

Attachments

Attachment A. Computing Acronyms and Terms

Attachment B. Organizations Producing Technology Standards

Technology Standards

The National Institute of Standards and Technology (NIST) has categorized computing technologies required to support portability of applications into the following areas:

- T1 *Operating Systems Services*
- T2 *User Interfaces Services*
- T3 *Program Services*
- T4 *Data Management Services*
- T5 *Data Interchange Services*
- T6 *Graphics Services*
- T7 *Network Services*

This document uses these categories to group technology standards and adds an additional one:

- T8 *Hardware Interfaces*

Many of the standards for computing technologies have been defined and published by international or national standards organizations. Attachment B to this document includes contact points for these organizations.

Table T1 is a summary of the technology standards guideline in this document. Each technology is categorized as to its maturity and strategic importance. "Mature" standards are complete and have been well accepted by the computer industry, and implementing products are commercially available. A "strategic" standard is one judged to be important to the site architecture's goal of achieving interoperability of heterogeneous systems and applications across the site. Timing may be critical in choosing between competing mature (but not strategic) and strategic (but not yet mature) standards. These choices must necessarily be made on a case by case basis and depend on the current state of the standards.

Note that specific products are not regarded as "technologies." Thus, for example, Motif as a standard graphical user interface methodology that is implemented by various vendor products is included as a technology standard, but products that provide a similar service, such as Microsoft Windows and Macintosh Operating System, are not.

Many of the technology standards defined in this reference are standards recommended for use by the U. S. Government. These are indicated by reference to a relevant Federal Information Processing Standard (FIPS) publication. At this time, mandatory consideration of these technology standards is limited to those required under the GOSIP program (see Reference 3 listed in the Introduction to this Reference).

Table T1
Technology Standards Summary

Technology	Standard	Section	Mature*	Strategic**
Operating System Services	POSIX	T1.1	√	√
	XPG3	T1.2	√	√
	C2	T1.3	√	√
User Interface Services	X Windows	T2.1	√	√
	OSF / Motif	T2.2	√	√
	PEX	T2.3		√
Program Services	COBOL	T3.1	√	√
	FORTTRAN	T3.2	√	√
	C	T3.3	√	√
Data Management Services	SQL	T4.1	√	√
	NFS/RPC	T4.2	√	
	DCE	T4.3		√
	RDA	T4.4		√
	DES	T4.5	√	√
	DAL	T4.6	√	
Data Interchange Services	ODA/ODIF	T5.1		√
	SGML	T5.2	√	√
	CCITT III and IV	T5.3	√	
	TIFF	T5.4	√	
	CGM	T5.5	√	
	IGES	T5.6	√	
	EDI	T5.7	√	√
	RTF	T5.8	√	
	Postscript	T5.9	√	
	X.400	T5.10	√	√
	X.500	T5.11		√
	ASCII	T5.12	√	
Graphics Services	GKS	T6.1	√	
	PHIGS	T6.2		√

**Table T1 - Continued
Technology Standards Summary**

Technology	Standard	Section	Mature*	Strategic**
Network Services	Ethernet	T7.1	√	√
	Token Ring	T7.2	√	
	FDDI	T7.3		√
	OSI	T7.4		√
	TCP/IP	T7.5	√	√
	DECnet /LAT	T7.6	√	
	SNA	T7.7	√	
	XNS/IPX	T7.8	√	
	AppleTalk	T7.9	√	
	SNMP	T7.10	√	√
	Kerberos	T7.11	√	√
Hardware Interfaces	CD-ROM	T8.1	√	
	RS-232	T8.2	√	
	RS-449/422/423	T8.3	√	
	V.35	T8.4	√	
	SCSI	T8.5	√	
	Centronics	T8.6	√	

* Mature - Complete and well accepted by the computer industry; implementing products are commercially available.

** Strategic - Important towards completing site architecture.

Operating Systems Services Technology Group

Description

Operating system services are the core services needed to operate and administer the application platform (the computer hardware) and provide an interface between applications software and the platform. Services in this area can be grouped as follows:

Kernel operations provide low level services necessary to create and manage processes, execute programs, clock services, process signal services, and provide file services and input/output to and from system peripherals.

Commands and utilities include facilities for the operator (user) to interact with the system to do such things as executing commands (starting programs), listing files, printing files, etc.

System management includes capabilities to define and manage user access, devices, file systems, job accounting, queues, user authorization, and system backup.

Operating system security services are specified in terms of controlling the access of users and processes representing users to data, functions, hardware, and software resources of a system.

Standardization of operating system services greatly facilitates program portability. For example, most applications utilize the system file services. On most systems, the system interaction with the file system is unique to that system and is a part of the application (often the major part) that must be reprogrammed to move the application to a different type of computer system.

Technology Standards

- T1.1 POSIX
- T1.2 XPG3
- T1.3 C2 Security

Related Technology Standards

- T2.1 X Windows
- T4.2 NFS/RPC
- T4.3 DCE
- T7.11 Kerberos

POSIX

Associated Technology Group

Operating Systems Services

Kernel Operations

Description

The Portable Operating System Interface standard - Part 1 (POSIX.1) defines a standard operating system interface and environment based on UNIX™ Operating System documentation to provide application portability at the source code level. The core requirements are a set of required services common to any programming language. These services include the creation and management of processes, execution of programs, inter-process communications facilities, file and directory management, and control of input/output processing to and from external devices. Applications that use POSIX programming interfaces to these operating system services are portable across POSIX-compliant operating systems.

This standard is alternatively known as FIPS Pub 142, ISO/IEC 9945-1, and IEEE 1003.1-1990. It is expected that POSIX will be implemented by most UNIX system vendors and some vendors of proprietary operating systems (DEC has announced plans to make VMS POSIX conformant, and IBM has a similar statement of direction for MVS).

Additional POSIX standards still under development include:

- 1003.2 - C, Ada, and FORTRAN language bindings to 1003.1
- 1003.3 - Shell and utility facilities
- 1003.4 - Verification and testing methods
- 1003.5 - Real time facilities
- 1003.6 - Secure / Trusted system considerations
- 1003.7 - Network interface facilities
- 1003.8 - System administration
- 1003.9 - Graphical user interfaces
- 1003.10 - Open Systems standards profiles
- 1003.11 - Overall guide to POSIX and Open Systems standards profiles

Advantages

- POSIX offers a standard programming interface to operating system services.
- Applications written using the C language and only POSIX system calls should be portable across a great number of diverse platforms.

Disadvantages

- POSIX.1 is not a complete operating system environment description, and the other parts of POSIX are still immature.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T1.1
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Recommended Usage

POSIX is both mature and strategic for use at SRS. It should be used as a technical specification for operating system procurements and a reference for applications programmers wishing to develop portable applications.

Related Technology Standards

XPG3

Support Contact

IRM, Advanced Technology and Architecture Section

References

IEEE Std 1003.1-1990, *IEEE Standard Portable Operating System Interface for Computing Environments*

FIPS Pub 151-1, *Posix: Portable Operating Systems Interface for Computing Environments*

XPG3

Associated Technology Group

Operating System Services

Kernel Operations

Description

The X/Open (consortium of UNIX users) Portability Guide Issue 3 (XPG3) is a UNIXTM operating system definition that incorporates other less complete standards definitions. XPG3 is the most complete and open of the UNIXTM system standards. It contains the POSIX 1003.1 definition, parts of the OS/2 model, SQL, and X Windows. XPG3 defines its own standards for system utilities, portable shell scripts, storage media compatibility, and system facilities (i.e., stored memory and message queues). It also includes the ISAM file definition from Informix.

X/Open has created a conformance testing suite of over 5000 tests that an implementation of UNIXTM must pass to be considered XPG3 conformant. X/Open has licensed XPG3 conformance testing to a few UNIXTM system vendors such as DEC and HP. Unlike the OSF and UNIXTM International, X/Open is not promoting its own technologies through the XPG3 definition.

Advantages

- It offers a standard programming interface to operating system services and utilities.
- XPG3 is the most complete and most open UNIXTM operating system definition.

Disadvantages

- XPG3 may still be incomplete in some areas.

Recommended Usage

XPG3 is both mature and of strategic importance. It should be used as a technical specification for operating system procurements and as a reference for applications programmers developing portable applications.

Related Technology Standards

POSIX.1

SQL

X Windows

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T1.2

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

X/Open Portability Guide Issue 3, Volumes 1-7, X/Open Company Ltd., Prentice-Hall

C2 Security

Associated Technology Group

Operating System Services

Security Services

Description

The Department of Defense (DoD) Trusted Computer System Evaluation Criteria (the Orange Book) was developed with three objectives in mind:

- to provide guidance to manufacturers as to what to build into their new trusted commercial products to satisfy trust requirements for sensitive applications.
- to provide users with a means to assess the degree of trust that can be placed in computer systems for the processing of classified or other sensitive information.
- to provide users a basis for specifying security requirements in acquisition specifications.

The Orange Book criteria are divided into four divisions, A, B, C and D, with A representing the most comprehensive security. Division C is divided into two classes, C1 and C2, where C2 represents a higher class of security.

Computer systems containing C2 security features provide for discretionary (need-to-know) protection and for accountability of subjects and the actions they initiate. Discretionary access control allows users to specify and control sharing of data or information under their control. The access controls provide that system objects are protected from unauthorized access.

Under C2 security, users are uniquely identified and authenticated via a password process. C2 systems must also provide for audit records for any access of information contained in the system. System events such as user identification and authentication, file access, program initiation, and operator actions are logged in the audit records. These records contain audit event data, including date and time, user, type of event, and success or failure of the events.

Advantages

- Each user of the system is uniquely identified and can be assigned to one or more user groups.
- Access to system objects is based on individual or group rights.
- Audit trails track user activities.
- Custom audit trails are supported.

Technology Standards

Disadvantages

- Work is required to establish user and group identities.
- Audit trails consume system resources.
- It is difficult to evaluate overall security of a system from audit data without automated analysis tools.

Recommended Usage

C2 is a mature and strategic site standard. All classified multi-user systems (except process control) must conform to the C2 standard by July 15, 1992. C2 security is recommended for multi-user systems that process Unclassified Controlled Nuclear Information (UCNI), that have a heterogeneous population base, or that might be vulnerable to attack by unauthorized personnel.

Related Technology Standards

None

Support Contact

Safeguards, Security, and Emergency Preparedness Department, Safeguards and Security Programs Section

References

DoD 5200.28-STD, *Department of Defense Trusted Computer System Evaluation Criteria*, December 1985

National Computer Security Center (NCSC) standards: NCSC-TG-003-87 (access control), NCSC-TG-001-87 (audit), and CSC-STD-002-85 (password management)

User Interfaces Services Technology Group

Description

User interfaces services define how a user may interact with an application. Such interfaces define the applications programming interface (API) between application programs and the graphical displays seen and manipulated by users. That is, these services define the "look and feel" of an application as seen by its user, as well as the programming details in creating the interface. Increasingly, the trend towards client-server computing allows the user interface to be on the personal workstation and the application on some remote "host" computer. Standards for User Interface Services permit the transmission of user interface "commands" across a network between the user workstation and the host application.

Industry trends are such that computer system manufacturers still define proprietary user interface services. The look and feel of these graphical user interfaces (GUI) are converging, but the programming interfaces remain unique for each system. Thus, the use of Microsoft Windows, IBM OS/2, or Apple Macintosh applications (the three most prominent examples of graphical user interfaces on personal computers) can appear very similar to users, but the programming required to create these applications is quite different among the three platforms.

The technology standards listed below are non-proprietary industry standards that are implemented on many different computer systems. As yet they do not replace the proprietary GUIs such as those listed above, but they are important in applications involving graphical user interfaces across a network of heterogeneous computer systems.

Technology Standards

- T2.1 X Windows
- T2.2 Motif
- T2.3 PEX

Related Technology Standards

- T1.1 POSIX
- T1.2 XPG3

X Windows

Associated Technology Group

User Interface Services

Description

The X Window System, or X, is a network-transparent window system that was developed at MIT in 1984. Since then, several versions have been developed, the most recent of which is X Version 11.5 (X11). X11 has been adopted as an industry-standard windowing system. X is supported by a consortium of industry leaders such as DEC, Hewlett-Packard, Sun, IBM, and AT&T that have united to direct, contribute to, and fund the continuing development of X. Almost all workstation vendors have accepted the X Window System as a standard interface to their workstation hardware. In addition to the system software development directed by the consortium, many independent developers are producing application software for use with X.

Advantages

- X provides a platform-independent graphical user interface (GUI) mechanism supported by all strategic SRS computer vendors.
- X supports the client-server applications architecture with the interface controlled by the application, not the workstation.

Disadvantages

- X does not define the look and feel of graphical applications; it only provides a mechanism for them. It is a necessary component of a window system standard but not sufficient to ensure similar look and feel.
- X typically consumes more resources and is slower than native, proprietary GUIs such as Macintosh.

Recommended Usage

The X Window System is mature and a strategic technology for use at SRS. It is appropriate for applications using a GUI that must be delivered to workstations from multiple vendors' products using different native GUI interfaces.

Related Technology Standards

OSF/Motif
PEX

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T2.1
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

References

Sheffler, Gettys, Newman, *X Window System*, Digital Press

FIPS Pub 158, *The User Interface Component of the Application Portability Profile*

OSF/Motif

Associated Technology Group

User Interface Services

Description

OSF/Motif, defined by the Open Systems Foundation (OSF), is a set of Application Programming Interfaces (API) combined with an X Window manager which define the look and feel of applications using the X Window System. These APIs take the form of widgets and intrinsics to use the X Window System terminology. A widget or intrinsic is typically a graphical construct like a scroll bar or a standard way of decorating windows. Since OSF/Motif defines these constructs and the window manager, application developers are given the means to build applications which look consistent and behave consistently.

It should be noted that while there are competing definitions for X Window System look and feel, all such definitions are fully interoperable.

The OSF promotes the use of Motif as a graphical user interface (GUI) standard by licensing source code of a reference implementation.

Advantages

- OSF/Motif is supported by most major workstation vendors (IBM, DEC, Apple, HP).

Disadvantages

- OSF/Motif is not supported by Sun, which currently has the greatest market share in the Unix workstation market.

Recommended Usage

OSF/Motif is both mature and strategic, and is useful both as a specification for the native GUI of a workstation and as an API for application development.

Related Technology Standards

X Windows
PEX

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T2.2

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

The OSF/Style Guide and *The OSF/Motif Users Guide*, Open Systems Foundation, Inc.

PEX

Associated Technology Group

User Interface Services

Description

PEX stands for Protocol Extensions to X. PEX represents the addition of 3-D graphics support into the X protocol. PEX is most often associated with the Programmers Hierarchical Integrated Graphics Standard (PHIGS) and once stood for PHIGS extensions to X. PEX as currently defined is more general than simply PHIGS support. It could provide support for another 3-D graphics representation. However, it currently is implemented only for PHIGS. PEX represents a set of extensions to the X protocols that provide the ability to distribute 3-D graphics objects in a heterogeneous environment.

PEX is the result of the efforts of the PEX Interoperability Group, a group of 10 companies working with the blessings of the X Windows Consortium.

One of the major differences between PEX and X is that while X is limited to a set of 2-D integer screen coordinates, PEX supports the creation and transmission of 3-D floating-point coordinates. PEX extends the X Window System to support the rendering of 3-D shapes in the same way that 2-D graphics are controlled in X Windows. PEX enables X applications to take advantage of 3-D hardware capabilities available in many high-performance workstations. It must be understood that PEX is not an API but an extension to the X protocol.

The current version of PEX will be available on the latest release tape X11R5 from the MIT X Consortium (Cambridge, MA).

Advantages

- PEX conserves network bandwidth by transmitting only changes to 3-D shapes over the network.

Disadvantages

- Because X and PHIGS operate in some fundamentally different ways, PEX is unable to deal with some PHIGS error conditions.

Recommended Usage

PEX is strategic for use at SRS but not yet mature. It should be used as a technical specification for graphics system procurements and as a reference for application developers building networked graphics applications.

Related Technology Standards

X Windows
PHIGS

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T2.3
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Advanced Technology and Architecture Section

References

PEX, MIT X Consortium, X11R5

Program Services Technology Group

Description

The procedural aspect of a computer application is embodied in the programming languages used to code it. There are hundreds of different programming languages, and it is not atypical that different system manufacturers' implementations of the same programming languages are different enough to make portability of computer applications between heterogeneous computer systems a difficult task.

The technology standards in this group represent industry standards for some of the more common programming languages. Adherence to these standards will greatly facilitate the portability of computer applications. Programmers must be aware, however, that many computer manufacturers support these language standards as a base set but in many cases extend the language with additional functionality, which is not generally portable between systems. Thus, if application portability of an application is a goal, the programmer must take care to use only those language features or constructs defined by the standard for that language.

In many cases, application portability is not a goal when an application is written. However, computer applications often outlive the computer hardware on which they run, necessitating a port to another system. This fact is another reason for choosing a standard programming language with which to build the application. There are, however, legitimate reasons for using nonstandard languages or features to build computer applications. Ultimately, the developer must weigh the benefits derived from using a nonstandard language versus the difficulty of transferring the code to a different computer system at some future time.

Several languages used at SRS are not listed below. In some cases, these languages are proprietary to a particular vendor. In other cases, the languages are relatively new and the standards efforts have not yet been completed. The list of standards for programming languages listed here is not intended to imply that these should be used exclusively for programming systems at SRS. However, if one of the languages listed below is used, the standard implementation of that language as described here should be employed.

Technology Standards

- T3.1 ANSI COBOL
- T3.2 ANSI FORTRAN
- T3.3 ANSI C

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T3.0
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Technology Standards

T1.1	POSIX
T4.1	SQL
T6.1	GKS
T6.2	PHIGS

ANSI COBOL

Description

COBOL is designed for programming self-documenting business oriented applications and has been in use since the early 1960s. It is very common for business applications developed on central computer systems, but it is also commonly available for most mid-size (minicomputers) and small computer systems (microcomputers). It is the most widespread programming language in use today and is a very mature standard.

The U.S. Government Federal Information Processing Standard (FIPS) and international standards (ISO) for COBOL are based on the American National Standards Institute (ANSI) standard, ANSI X3.23-1985 and Addendum X3.23A-189.

Advantages

- It is well supported by most vendors.
- It is suitable for general purpose business and financial applications.
- Many Computer Aided Systems Engineering (CASE) tools generate COBOL code.

Disadvantages

- COBOL has very limited utility for computationally intensive applications as well as other types of applications such as real-time and communications.
- Newer fourth generation languages provide more powerful database manipulation capabilities.

Recommended Usage

COBOL is both a mature and a strategic technology standard. It is recommended for the development of general business applications where program portability is a concern.

Related Standards

None

Support Contact

IRM, Information Systems Engineering Section

References

FIPS Pub 21-3, *COBOL*

ANSI X3.23-1985, *COBOL*

ANSI X3.23A-1989, *Addendum 1, Intrinsic Function Module*

ANSI FORTRAN

Associated Technology Group

Programming Services

Description

FORTRAN (FORMula TRANslator) is a general purpose programming language with capabilities for performing virtually any type of application function. It was originally developed to assist in the development of scientific and engineering calculations and models, but it has been used for business and process control applications as well. It remains the language most often used for scientific applications.

The language has evolved with added capabilities such as structured programming constructs. The latest FIPS is based on the ANSI standard (ANSI X3.9-1978), called FORTRAN-77. ANSI and ISO have recently adopted a new standard, FORTRAN-90. FORTRAN-90 is a superset of FORTRAN-77 and includes new capabilities including dynamic allocation of array, whole array operations, pointer data types, and data structures.

FORTRAN-77-compliant compilers are readily available for supercomputers, mainframes, minicomputers, and microcomputers.

FORTRAN-90 implementations are not yet generally available.

Advantages

- Mature, well supported by all major system vendors (FORTRAN-77).
- Suitable for scientific calculation applications.

Disadvantages

- Proprietary extensions to the language are often introduced by systems vendors, reducing the portability of FORTRAN applications.

Recommended Usage

FORTRAN is both a mature and a strategic technology standard. FORTRAN-77 is recommended for the development of scientific/engineering applications, especially where program portability is a concern. Specify FORTRAN-90 as desirable for future use.

Related Standards

None

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T3.2
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

SRTC, Scientific Computations Section

References

FIPS Pub 069-1, *FORTRAN*

ANSI X3.9-1978, *FORTRAN* (FORTRAN-77)

ANSI X3.198-1991, *FORTRAN* (FORTRAN-90)

ANSI C

Associated Technology Group

Programming Services

Description

C is a general purpose programming language with capabilities for performing virtually any type of application function. It was originally developed to assist in the development of the UNIX operating system and UNIX utilities, and thus has powerful operators for use in the development of system level software. It can also be used in the development of business, process control, and scientific applications. C has become the industry standard language for the development of applications for personal computers. It includes facilities for every level of programming, from low level (hardware control) operations to high level abstract functions and procedures. Data structuring, reusable library support, and memory management are included.

The language has evolved over the last 15 years. The latest FIPS and ISO (draft) standards are based on the ANSI standard (1989) under the control of the ANSI X3J11 committee. The ANSI X3 committee is considering the development of a second language standard for object oriented programming (OOP) based upon C. This language is called C++.

ANSI C-compliant compilers are readily available for supercomputers, mainframes, minicomputers, and microcomputers.

Advantages

- C is mature and well supported by all major system vendors.
- It is suitable for a wide variety of applications, especially on personal computers, operating systems, and real-time applications.

Disadvantages

- Complex syntax and powerful operations require relatively long times for programmers to master.

Recommended Usage

C is both a mature and a strategic technology standard and is recommended for the development of system level and process control applications where program portability is a concern.

Related Standards

None

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T3.3
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Information Systems Engineering Section

References

FIPS Pub 160, *C*

ANSI X3.159-1989, *Programming Language C*

Data Management Services Technology Group

Description

Central to most systems is the management of data that can be defined independent of the processes that create or use it, maintained indefinitely, and shared among processes. Data management services include the following:

Data dictionary / directory services allow users and programmers to access and modify data about data, called metadata.

Database management system (DBMS) services provide controlled access and modification of structured data. DBMS systems provide for concurrent access of data by multiple users or processes, supporting features to create, populate, move, retrieve, archive, backup, and restore data.

Distributed data services provide access to and modification of data in remote (across a network) databases.

Data management security services include control of access to and integrity of data stored in a system through specific mechanisms in the data management software.

Most data management services are proprietary to the computer software vendors. Since most computer applications depend on extensive data management services, this fact greatly restricts the portability of computer applications utilizing those services. Also, applications often require data from a variety of sources. That is, they need distributed data services. These two facts are driving current efforts to establish standards in the data management services area.

Technology Standards

T4.1	SQL
T4.2	NFS/RPC
T4.3	DCE
T4.4	RDA
T4.5	DES
T4.6	DAL

Related Technology Standards

T1.1	POSIX
T7.11	Kerberos

SQL

Associated Technology Group

Data Management Services

Description

Structured Query Language (SQL) defines the basic elements and operations of a relational database management system. The ANSI standard (X3.135-1989 and ISO 9075:1989) provides functions for designing, accessing, maintaining, controlling, and protecting a database. The standard does not define a secure DBMS, but it does provide mechanisms for defining secure interfaces to the DBMS. SQL includes integrity constraints, and language bindings to COBOL, Pascal, FORTRAN, and PL/1. The associated embedded SQL standard (ANSI X3.168-1989) adds Ada and C to the list of high level language interfaces.

SQL is a mature standard that has been adopted as the DBMS component of X/OPEN, OSF, SQL-Access, and other vendor consortia. The level of conformance to the standard varies between vendors (level 1, level 2, and integrity constraint), but all major vendors are committed to providing upwardly compatible products to the standard's planned revisions and extensions. The SQL FIPS requires level 2 SQL compliance and the flagging of any vendor supplied extensions. The next version of the ANSI standard (1992 +) will include additional features for schema manipulation, dynamic SQL, exception handling, enhanced integrity constraints, transaction management, and data administration. A future version (1995+) will include distributed database management functions and support for object-oriented database management.

Advantages

- Applications developed in compliant SQL are transportable across platforms.

Disadvantages

- Many vendors built proprietary extensions to ANSI standard SQL, limiting portability of application software.
- Until user-friendly SQL front ends are widely available, computer professionals are required to build SQL-compliant DBMS applications.
- The existing standard is specified for stand-alone, single environment databases (see 1995 future enhancements).

Recommended Usage

ANSI SQL is mature and is a strategic site technology standard. It is recommended as the standard access language for relational database management systems (RDBMS). RDBMS built upon SQL features are more portable and will have a larger pool of programmers available to maintain them throughout their life cycle.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T4.1
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Information Systems Engineering Section

References

ANSI X3.135-1989, *Database Language SQL with Integrity Enhancements*

ANSI X3.168-1989, *Database Language Embedded SQL*

FIPS Pub 127-1, *Database Language SQL*

NFS/RPC

Associated Technology Group

Data Management Services

Description

The Network File System (NFS) is a mechanism for sharing files across a network which preserves the semantics of local file access. NFS was created by Sun Microsystems Inc. and has become a de facto industry standard. Implementations exist for every major computer platform. NFS is based on TCP/IP and is generally associated with UNIX environments where it is ubiquitous.

NFS is implemented with Open Network Computing (ONC) Remote Procedure Call (RPC) technology. Remote procedure calls extend the notion of a local procedure call to embrace interactions between components of distributed systems. XDR (External Data Representation) provides for the exchange of binary data between heterogeneous systems with remote procedures and handles translations between different internal data formats.

Advantages

- NFS/RPC is supported by all major computer vendors. It is the de facto industry standard.

Disadvantages

- NFS has some security holes and lacks robustness and scalability.
- It is likely to be replaced as the industry standard by DCE.

Recommended Usage

NFS/RPC is a mature but not strategic technology standard. It represents the most mature implementations for remote file system and remote procedure calls but is expected to be supplanted by OSF's DCE in the future as the industry standard endorsed by the international and national standards groups. Use NFS for near term requirements, but specify DCE as a desirable feature in any procurement specifications.

Related Technology Standards

TCP/IP

DCE

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T4.2
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

References

RFC 1094, *Network File System Protocol*

RFC 1057, *Remote Procedure Call*

DCE**Associated Technology Group**

Data Management Services
Distributed Data Services and Data Management Security Services

Description

The Open Software Foundation (OSF) is a consortium of computer systems and software vendors which uses an open process to define standard technologies. These technologies are then made available in the form of source code implementations on certain reference platforms to members who port the code to their specific platforms and offer it as a binary product to end users. To generate these "standards," the OSF issues a Request For Technology (RFT). Anyone may respond with technology that meets all or part of the specification. Responses are evaluated and merged to form the reference implementation. The Open Software Foundation Distributed Computing Environment (OSF/DCE) covers a wide range of communications services supporting a client-server infrastructure. The services include a Distributed File System (DFS), remote procedure call (RPC), directory service, time service, security service, and threads.

The DFS is based on the Andrew File System (AFS) from Carnegie-Mellon University. It is a client-server file system that combines local and remote storage into a single, expanded file system with the location of individual files largely transparent to individual users. Directories, volumes, and entire servers may be replicated, providing reliability in the event of server failure. File caching is used to provide near local performance for remote file access.

The RPC portion of DCE includes high-level interface definition languages together with remote procedure calls. The interface definition languages are supported by compilers that convert high-level interface descriptions of remote procedures into C language source code. The resulting remote procedure calls extend the notion of a local procedure call to embrace interactions between components of distributed systems. DCE RPC is an enhanced version of Hewlett-Packard's Network Computing System (NCS).

The naming service maps information about network resources to widely accessible, meaningful names. It allows users and programs to refer to servers, files, disks, people, etc. by convenient names without knowing where they are located in a network. DCE naming service represents a combination of the DEC Distributed Naming Service (DECdns) and DIR-X X.500 service from Siemens.

The time service provides a clock synchronization service for component systems of a distributed environment. This feature is required by many distributed systems in order to determine the order of events or the intervals between events. The time service was contributed by DEC as the Distributed Time Synchronization Service (DECdts).

The DCE security service provides facilities for supporting confidentiality in remote procedure calls, a means for authenticating users and services, management of access permissions, and a registry for user account information. This technology is based on the Kerberos authentication system of MIT's Project Athena.

Threads are a technique for allowing multiple sequential flows of control within a single process. The DCE services all use threads, and OSF felt it was necessary to bundle a facility for providing threads into DCE so that implementations would not be constrained by operating systems that do not provide them.

Advantages

- Offers an integrated collection of services for a distributed computing environment.
- Committed to by many major computer vendors.

Disadvantages

- This is an emerging standard and is not widely implemented.
- In some areas, OSF/DCE competes with the Open Network Computing (ONC) environment from UNIX™ International. ONC represents more of a collection of existing distinct services.

Recommended Usage

DCE is a strategic technology standard that is not yet mature. It should be used as a technical specification for network-based applications, especially those involving a heterogeneous computing environment.

Related Technology Standards

TCP/IP
NFS
Kerberos
X.500

Support Contact

IRM, Advanced Technology and Architecture Section

References

Distributed Computing Environment, An Overview, Open Systems Foundation, Inc., April 1991

RDA

Associated Technology Group

Data Management Services

Distributed Data Services

Description

Remote Database Access (RDA) is an ISO draft standard that defines the interface required to establish a remote connection between some client application program and a database server. This interface defines the process that controls data transfers to and from the database, with emphasis on the SQL data access language. RDA allows client applications to establish connections to a variety of relational database management systems (RDBMS). Under RDA, SQL statements are sent across a network to the RDA server as a set of character strings, and the resulting data or exception conditions are returned.

This standard is currently undergoing draft approval balloting in the joint ISO/IEC (International Electrotechnical Committee) Joint Technical Committee 1 (JTC1). Several RDBMS vendors have developed early implementations for testing and have demonstrated the ability to access data in a heterogeneous RDBMS environment at industry trade shows.

The existing specification does not consider multiple simultaneous connections between a client and multiple servers. RDA assumed a standards-based network. Early implementations use OSI-compliant networks. TCP/IP-based networks will also be employed in RDA applications.

Final adoption of the RDA standard and the release of commercially available products are expected during 1992. At that time, RDA is expected to become a key information systems integration strategy at SRS.

Advantages

- RDA is promised support by most major RDBMS vendors.
- An ISO international standard will force wide vendor support, likely to be included in future GOSIP requirements.
- It rests upon SQL, TCP/IP, and OSI standards.

Disadvantages

- RDA is not yet commercially available.
- RDA supports single connections only.

Recommended Usage

Since RDA is an immature but strategic technology, it should be used as a non-mandatory technical specification for relational database management system and application and engineering development tool procurements.

Computing Standards and Guidelines Reference

Document:

WSRC-IM-92-23

Section:

T4.4

Page:

2 of 2

Issue Date:

4/1/92

Technology Standards

Revision:

0

Related Technology Standards

SQL
TCP/IP
GOSIP

Support Contact

IRM, Advanced Technology and Architecture Section

References

ISO/IEC DP 9759, *Remote Data Access (RDA)*

DES

Associated Technology Group

Data Management Services

Data Management Security Services

Description

The Data Encryption Standard (DES) is formally defined in ANSI X3.92-1981/R1987 and Federal Information Processing Standard Publication Number 46 (FIPS Pub 46). DES is one of the most widely used encryption systems today. It was developed in the 1970s and patented by researchers at IBM. IBM later made DES available for public use, and it was adopted as a standard.

DES is a bit permutation, substitution, and recombination function performed on blocks of 64 bits of data and 56 bits of key (eight 7-bit characters). The 64 bits of input are permuted initially, and then are input to a function using static tables of permutations and substitutions. The bits are permuted in combination with the 48 bits of the key in each round. This process is iterated 16 times (rounds), each time with a different set of tables and different bits from the key. The output of the DES function appears so unrelated to the input that the function is sometimes used as a random number generator. FIPS Pub 81 describes four modes of operation for DES and their use.

Advantages

- DES is the most widely used encryption method and is generally regarded as secure for sensitive (not classified) data applications.

Disadvantages

- DES protection is not sufficient for classified data applications.

Recommended Usage

DES is a mature and strategic technology standard and is an appropriate tool for use any time sensitive (non-classified) data encryption is required.

Related Technology Standards

Kerberos

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T4.5
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

References

ANSI X3.92-1981/R1987, *Data Encryption Algorithm*

FIPS Pub 46, *Data Encryption Standard (DES)*

FIPS Pub 81, *Data Encryption Standard (DES) Modes of Operation*

DAL

Associated Technology Group

Data Management Services Services
Distributed Data Services

Description

Data Access Language (DAL, formerly called CL/1) is an application programming interface (API) definition that allows the development of client-server applications using a variety of "front-end" clients against a variety of independent software vendors' relational database management systems (RDBMS) running on a variety of computer platforms.

Each server system contains a DAL server component that receives requests for data access in the DAL format and converts these requests into RDBMS-specific data access calls. All major RDBMS vendors are supported on IBM and DEC computers, as well as on UNIX platforms from a variety of vendors. Client applications exist for MS-DOS, OS/2, Macintosh, and UNIX operating systems. A variety of network transports support DAL, including AppleTalk, TCP/IP, DECnet, and SNA.

Advantages

- DAL is supported by Apple Computer and other vendors on a variety of client and server platforms.

Disadvantages

- DAL specifications are controlled by one vendor.
- It is likely to be supplanted by RDA.
- DAL is not implemented on all computer platforms or network protocols.
- Additional processing overhead is required as compared to direct RDBMS calls.

Recommended Usage

This product, though mature, is not strategic for long term use at SRS, as its capabilities will be duplicated by the ISO standard, Remote Data Access (RDA). However, DAL today remains a useful tool for client-server computing in a heterogeneous environment.

Related Technology Standards

RDA

Support Contact

IRM, Information Systems Engineering Section

References

DAL Programmer's Reference Guide, Apple Computer Inc.

Data Interchange Services Technology Group

Description

Data interchange services provide specialized support for the interchange of data between applications. Areas of data interchange services include:

Document services, which include the specifications for encoding data (e.g., text, pictures, numerics, etc.) and the structure of electronic documents.

Graphics data services, which include device (hardware) independent descriptions of picture elements.

Product data interchange services, which encompass those specifications that describe technical drawings, documentation, and other data required for product design and manufacturing.

Messaging services, which include the descriptions of electronic mail message formats, their network envelopes and exchange protocols, and the directory services used to support message exchange.

Technology Standards

- T5.1 ODA/ODIF
- T5.2 SGML
- T5.3 CCITT III and IV
- T5.4 TIFF
- T5.5 CGM
- T5.6 IGES
- T5.7 EDI
- T5.8 RTF
- T5.9 Postscript
- T5.10 X.400
- T5.11 X.500
- T5.12 ASCII

Related Technology Standards

- T8.1 CD-ROM

ODA/ODIF

Associated Technology Group

Data Interchange Services
Document Services

Description

Office Document Architecture / Office Document Interchange Format (ODA/ODIF) is the ISO standard that describes the document interchange format that assures receipt of a file which maintains the originator's intent with regard to formatting and presentation while maintaining the ability for the document to undergo further revisions. The multipart Office Document Architecture standard was developed in Europe in the 1980s by ISO, CCITT, and the European Computer Manufacturers Association (ECMA) for the processing and interchange of formatted documents typical in an office environment. The various parts of the standard define document structures, content structures, and the Office Document Interchange Format. The different data types coexist within the document. A major emphasis in ODA/ODIF is to facilitate transmission of the file to another user and to maintain document formatting and appearance just as the originator intended.

Advantages

- It preserves original document formatting and layout.
- The exchange format is application independent.
- ODA/ODIF will outlive the current proprietary word processing approaches.
- It enriches the usefulness of a document beyond creation and revision.

Disadvantages

- ODA/ODIF assumes the existence of a homogeneous document processing infrastructure.
- There are few commercially available packages that adhere to ODA formats.
- File format is limited to predetermined types of document components (e.g., vector, raster, text).

Recommended Usage

ODA is a strategic but not yet mature technology standard. It is useful for the creation and interchange of documents whose content will be further used in other document processing applications or documents whose components may have usefulness in other applications such as database, content-based retrieval, and infobases. ODA will be required in Version 2 GOSIP.

Related Technology Standards

SGML

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T5.1
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Advanced Technology and Architecture Section

References

ISO 8613, *Text and Office Systems—Office Document Architecture (ODA) and Interchange Format (Parts 1 - 8)*

SGML

Associated Technology Group

Data Interchange Services
Document Services

Description

Standard Generalized Markup Language (SGML) provides generic tagging of documents and management of pointers to external non-text files. After nearly a decade of work, ANSI and ISO issued the Standard Generalized Markup Language as ISO 8879:1986. SGML utilizes generic tagging of text and pointers to external data components (e.g., graphics), coupled with accompanying document type definition (DTD) files which describe the layout and format of the final form document. A DTD for any type of document may be written, and a different DTD applied to the same document will produce a different output without the need to alter the SGML file whatsoever.

Advantages

- SGML was created for structured documents; it provides a structured tagging of every element of every document.
- Non-text parts of the documents utilize standard formats.
- Documents are easily transmitted between applications and platforms.
- Recipients may apply the originator's or their own formatting rules, and create output in the preferred style.
- SGML will outlive the current proprietary word processing approaches.
- It enriches the usefulness of a document beyond creation and revision.

Disadvantages

- Document Type Definitions (DTDs) are difficult to write.
- Few commercially available packages adhere to SGML formats.
- Recipients are required to have an application that can open all the possible data types within a document.

Recommended Usage

SGML is both mature and strategic. It is useful for the creation and interchange of documents whose content will be further used in other document processing applications or documents whose components may have usefulness in other applications such as database, content-based retrieval, and infobases. Its focus is on classes of documents that adhere to a predetermined structure.

In 1989, a Federal Information Processing Standard (FIPS Pub 152) required that all federal agencies specify ISO 8879 in text-processing procurements.

DOE's Office of Scientific and Technical Information (OSTI) requires that electronic documents be transmitted as SGML by 1993.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T5.2
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Technology Standards

ODA
DoD CALS utilizes SGML as the document interchange format.

Support Contact

IRM, Advanced Technology and Architecture Section

References

ISO 8879-1986, *Standard Generalized Markup Language (SGML)*

FIPS Pub 152, *Standard Generalized Markup Language (SGML)*

CCITT III and IV

Associated Technology Group

Data Interchange Services

Graphics Data Services

Description

CCITT Group III and Group IV compression standards define the file format and compression schemes for describing a bitonal bitmap image file for disk storage or transmission across telecommunications networks. By describing a page as a series of zeroes and ones, the black or white state of a particular spec on a page can be defined. This method is used in image scanners and FAX machines. The CCITT standard describes the method by which the redundant patterns of zeroes and ones are compressed to reduce data storage and transmission requirements.

CCITT Group III compression occurs by storing the mode (0 or 1) and length of "runs" on a scanned line. (e.g., 136 white dots are stored as "136(0)" rather than a series of 136 consecutive zeroes)*. CCITT Group IV compression first uses the Group III scheme, and then differences each line from the one prior to it. Group IV compression typically achieves a 20:1 compression ratio for a typed page.

* This is not the actual syntax but is used to demonstrate the concept of runcode words.

Advantages

- CCITT compression reduces file storage and transfer requirements for bitmap images.
- The standard is in widespread use in FAX machines, scanners, and applications.

Disadvantages

- Compression and decompression require computing resources.
- Grayscale files cannot be compressed or stored with this format.
- Files with few runs of black or white can cause larger file sizes than decompressed files.
- The standard does not completely describe the file format; focus is on the compression scheme.

Recommended Usage

This standard is a mature technology and should be specified wherever possible in association with scanners, publishing systems, and image storage and retrieval systems to assure the interchange of image file data.

Related Technology Standards

TIFF

Support Contact

IRM, Advanced Technology and Architecture Section

References

"Standardization of Group 3 Facsimile Apparatus for Document Transmission," Recommendation T.4, Volume VII, Facsimile VII.3, CCITT, Geneva, 1985

"Facsimile Coding Schemes and Coding Control Functions for Group 4 Facsimile Apparatus," Recommendation T.6, Volume VII, Facsimile VII.3, CCITT, Geneva, 1985

TIFF

Associated Technology Group

Data Interchange Services
Graphics Services

Description

Aldus and Microsoft's joint venture into a common tag image file format (TIFF), a tag based file format that is used to promote the interchange of digital image data. TIFF was designed to make life easier for scanner vendors, desktop publishing software developers, and users of these two classes of products, by reducing the proliferation of proprietary scanned image formats. It is not a printer or page description language and is not intended to be a general document interchange standard.

Advantages

- TIFF allows pictures to be exchanged between IBM and Macintosh PCs.
- It is designed for future growth by including a tag to each field, thus allowing creation of new field types without invalidating the existing types.
- TIFF works with bilevel, grayscale, palette, and RGB type images.
- Three different compression schemes are implemented, saving disk space.

Disadvantages

- Some existing software cannot translate into or out of TIFF.

Recommended Usage

TIFF is a mature standard and is recommended for desktop publishing requiring inclusion of scanned images.

Related Technology Standards

None

Support Contact

IRM, Advanced Technology and Architecture Section

References

Tag Image File Format Specification Revision 5.0, Aldus Corporation

CGM

Associated Technology Group

Data Interchange Services
Graphics Data Services

Description

Computer Graphics Metafile (CGM) is an ANSI standard that defines how 2-D vector illustrations are to be encoded to transfer into and between technical publications packages. It supports lines, fill areas, polygons, and text graphics primitives. It is a metafile format that incorporates bitmapped and vector graphics. Many vendors of document publishing applications support CGM translators for import or export of graphics data into or from their applications.

Advantages

- CGM was conceived as the common public format for interchange of graphics files.
- Definition of illustrations through use of primitives simplifies the file itself and makes it easily transportable.

Disadvantages

- Many applications that are CGM-compliant do not support the full range of CGM features.
- Full-featured CGM generators and filters are not widely available.
- Many vendors are producing proprietary extensions to the CGM definition without ANSI approval.
- The standard has not been updated since 1986.

Recommended Usage

CGM is a mature technology standard and is recommended for specifications that will require some level of file interchange with yet-to-be specified products. Many product translators provide direct translations to other products with a higher degree of accuracy than that obtainable with CGM.

Related Technology Standards

None

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T5.5
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Advanced Technology and Architecture Section

References

ANSI X3.122-1986, *Computer Graphics Metafile for the Storage and Transfer of Picture Description Information*

FIPS Pub 128, *Computer Graphics Metafile (CGM)*

IGES

Associated Technology Group

Data Interchange Services
Graphics Data Services

Description

Initial Graphics Exchange Specification (IGES) is an ANSI standard for vector-graphic data representation that allows different Computer Aided Design / Computer Aided Manufacturing (CAD/CAM) systems to interchange product-definition data in an ASCII format. It defines hundreds of entity types, including circles, arcs, vectors, text, and the like, for rendering of mechanical drawings and technical illustrations. IGES is expected to be superseded by the Standard for The Exchange of Product Model Data (STEP).

Advantages

- IGES is robust enough to accommodate almost any CAD feature.
- A subset of the IGES standard is in widespread use in the DoD CALS program.
- Some IGES translators between specific products produce high quality results.

Disadvantages

- The large number of features defined by the standard makes a complete implementation nearly impossible.
- Use of translators requires some tailoring to assure entity type matching.
- Text handling is weak with respect to fonts and sizing.

Recommended Usage

IGES is a mature technology standard and is recommended for specifications that will require some level of CAD/CAM file interchange with yet-to-be specified products. Many product translators provide direct translations to other products with a higher degree of accuracy than does IGES.

Related Technology Standards

None

Support Contact

IRM, Advanced Technology and Architecture Section

References

ANSI Y14.26-1989, *Initial Graphics Exchange Specification*

EDI

Associated Technology Group

Data Interchange Services
Messaging Services

Description

Electronic Data Interchange (EDI) is the computer-to-computer interchange between companies and organizations of data contained in common business documents in computer-readable form under strictly defined standards. The EDI standard defines the way the documents are formatted, the information the documents contain, and mechanisms for determining whether the document should be transmitted. The standard has two parts: ANSI X12 for domestic transactions, and EDIFACT for international transactions. X12 and EDIFACT are not compatible.

Advantages

- EDI will allow electronic transactions for RFQ, purchasing, and other financial information.
- 90% cost savings are possible in the issuance of Electronic Funds Transfers over checks.
- EDI allows online access by vendors to RFQs rather than the mailing of printed copies.

Disadvantages

- Integration of EDI into existing applications could be expensive.
- Security aspects of EDI (e.g., electronic check payments) are uncertain.
- EDI and EDIFACT are not compatible, yet both are in the FIPS.

Recommended Usage

EDI is a mature and a strategic technology standard. It should be considered for purchasing systems that wish to conduct financial transactions or to distribute bid information electronically to potential vendors or suppliers.

In 1991, the Federal Information Processing Standard (FIPS Pub 161) required that all federal agencies specify X12 and EDIFACT in all EDI systems by 1996.

Related Technology Standards

None

Support Contact

IRM, Information Systems Engineering Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T5.7

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

ANSI ASC X12D/90-382, *EDI Implementation Reference Manual Guidelines*

FIPS Pub 161, *Electronic Data Interchange*

RTF

Associated Technology Group

Data Interchange Services
Document Services

Description

Rich Text Format (RTF) is the Microsoft word processing interchange format for describing text, formatting, and imbedded graphics exchanged with other applications and word processing packages. RTF uses encoding to produce an ASCII file that completely describes the document content and format. Many word processing packages and desktop publishing applications from a wide variety of vendors can read RTF.

Advantages

- RTF is a widely used and simple to invoke document interchange format.
- RTF files are structured in a manner that can be parsed so that the content information can be used by other applications.

Disadvantages

- RTF layout is limited to word processing layout capabilities; it cannot accommodate desktop publishing layouts.
- RTF is limited to the capabilities of Microsoft word processing packages, and might not transmit or accept a more robust format with another package.
- Although possible, few non-word processing applications (e.g., databases, spreadsheets) use RTF for text imports.

Recommended Usage

RTF is a mature but nonstrategic technology standard. It is the most common interchange format for Macintosh and PS/2 word processing applications. It should be used as the intermediate format for documents exchanged between applications or platforms (unless the capability exists to read another's native file format). In the future, ODA/ODIF will replace RTF for the exchange of word processing files.

Related Technology Standards

ASCII
ODA/ODIF

Support Contact

IRM, Advanced, Technology and Architecture Section

References

Microsoft Rich Text Format Specification, Microsoft Corporation

Postscript

Associated Technology Group

Data Interchange Services

Description

Postscript is a programming language popularized by Adobe Systems Inc. and adopted throughout the computer industry as a standard that allows for the description of pages for printing. The controller for interpreting the language resides in the hardware or firmware of the printer. It describes arbitrary shapes, geometric primitives, and painting (raster) primitives, and fully integrates text (as graphical shapes) from a wide variety of fonts. The Postscript file format (the output from a generator) can be manipulated, modified, or stored. Recent additions include color support and display Postscript (for non-printer output). Most instances of Postscript in files are actually Encapsulated Postscript (EPS). EPS is an almost complete subset of Postscript in which has some of the time-consuming or complex Postscript commands have been removed. EPS also includes the addition of a header definition which provides additional physical page size definitions and identifies the file as EPS. EPS is the form of a Postscript file that is typically achieved via "Save As Postscript" or "Print to Postscript" commands, or interchanged between computers (and sometimes to printers).

Advantages

- Postscript is widely used and supported by virtually every laser printer manufacturer.
- It is robust and extensible enough to handle any printing requirement.
- Postscript has remained stable since 1986.

Disadvantages

- Postscript is very verbose, especially in its description of raster files.
- Not all personal computer application programs support output to Postscript.

Recommended Usage

Postscript is a mature technology standard. Postscript printers are the de facto standard for desktop workstations and many laser printers. Its use as a data file interchange format is untested in most applications areas.

Related Technology Standards

None

Support Contact

IRM, Advanced Technology and Architecture Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T5.9

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

Postscript Language Reference Manual, Adobe Systems, Inc., 1985

X.400

Associated Technology Group

Data Interchange Services
Messaging Services

Description

X.400 is the standard defined by the International Telegraph and Telephone Consultative Committee (CCITT) and adopted by the International Standards Organization to define electronic message format and the protocol for exchanging electronic messages across a network. Under X.400, the user applications, called User Agents (UA), exchange messages with an electronic post office, called a Message Transfer Agent (MTA). X.400 defines the protocol used between UA and MTA, as well as between multiple MTAs. A set of interconnected MTAs comprise a Message Transfer System. MTAs plus UAs make up a Message Handling System (MHS). A principal feature of the MHS is that it operates in a store and forward manner. Heterogeneous electronic mail system can be linked together, if each supports the X.400 protocol for connecting MTAs.

X.400 mail exchange rests on top of an OSI protocol network. Long term direction for electronic mail requires integrated directory services based upon the X.500 standard.

Current GOSIP rules require the 1984 version of the standard, but later GOSIP versions will require that the X.400 Version 1988 be supported.

Advantages

- X.400 is a GOSIP standard so that all mail vendors do or will support X.400.
- Document content is not limited to text messages but can support arbitrary binary file transfers.

Disadvantages

- X.400 requires OSI network protocols.
- Effective use of X.400 requires Directory Services.
- There is limited use of X.400 except for public mail systems.

Recommended Usage

X.400 is a mature and strategic technology standard. GOSIP requires that all new electronic messaging systems procured for the U. S. Government (including SRS) support the X.400 messaging standard. In practice, X.400 will be used to link heterogeneous electronic mail systems.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T5.10
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Technology Standards

OSI
X.500

Support Contact

IRM, Computer and Telecommunications Management Section

References

CCITT 1988 Recommendation X.400, *Message Handling: System and Service Overview*

X.500

Associated Technology Group

Data Interchange Services
Messaging Services

Description

X.500 is an evolving joint standard of the Consultative Committee for International Telegraphy and Telephony (CCITT) and the International Standards Organization (ISO), and specifies how directory systems exchange information on a worldwide scale. X.500 services are to be closely integrated into X.400 message handling systems.

X.500 consists of two main components. The Directory User Agent (DUA) represents the user and provides a portal into the directory. The Directory System Agents (DSAs) are servers that each implement a portion of the directory.

The OSI model contains only one globally distributed hierarchical directory with an integrated, unified naming space. Every entity or object stored in the directory has a globally unique name. The directory is distributed over a collection of DSAs.

The most important parts of X.500 to be completed for a 1992 draft are replication and access control, which are essential for the commercial deployment of X.500.

Advantages

- X.500 is a future GOSIP requirement.
- It allows global directories for large interconnected enterprises.

Disadvantages

- Final version of the standard is not yet complete.
- There are no commercially available implementations.

Recommended Usage

X.500 is a strategic technology standard for the future. Vendors should be requested to provide X.500-compliant products, but proprietary directory services will still be required for the next few years.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T5.11
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Technology Standards

OSI
X.400

Support Contact

IRM, Computer and Telecommunications Management Section

References

CCITT 1988 Recommendation X.500, *The Directory—Overview of Concepts, Models, and Service*

ASCII

Associated Technology Group

Data Interchange Services

Document Services

Description

The American Standard Code for Information Interchange (ASCII) is the industry standard for the binary encoding and exchange of alphanumeric text. This standard uses 7 bits to encode 128 possible characters, including upper and lower case letters, the 10 numerals, punctuation characters, and a few special control characters.

Because ASCII is limited to a character set of 128 possible values, it is not suitable for the exchange of fully revisable word processing files. Nevertheless, word processing files are often converted to ASCII and exchanged between computer systems. When this is done, special formatting features such as bold text, headers, and superscripts are not preserved but must be recreated manually on the receiving system.

Advantages

- ASCII is a very mature standard supported by all computer vendors.

Disadvantages

- It is suitable for only alphanumeric text exchange.
- Computer word processing files contain many formatting codes that cannot be preserved under an ASCII text exchange.

Recommended Usage

ASCII is a mature technology standard which should be used as a lowest common denominator for exchange of alphanumeric text data.

Related Technology Standards

None

Support Contact

IRM, Computer and Telecommunications Management Section

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T5.12

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

FIPS Pub 1-2, *Code for Information Interchange, Its Representation, Subsets, and Extensions*

ANSI X3.4-1986, *Code for Information Interchange*

Graphics Services Technology Group

Description

Graphics services provide functions for creating and manipulating pictures. These services include display element definition and management, and graphical object attribute definition and management. These services are defined in specifications for describing multi-dimensional graphic objects in a form that is independent of output devices and managing hierarchical database structures containing graphics.

Technology Standards

T6.1 GKS
T6.2 PHIGS

Related Technology Standards

T2.3 PEX
T5.9 Postscript

GKS

Associated Technology Group

Graphics Services

Description

Graphical Kernel System (GKS) defines an applications programming interface for applications that produce computer generated two dimensional (2-D) pictures on vector or raster graphics output devices. GKS provides constructs and subroutine library calls for virtually any kind of 2-D graphic image. GKS includes program interface bindings for Ada, Pascal, and FORTRAN.

GKS functions include output of graphics primitives, obtaining graphics input, manipulating graphics metafiles, error handling, generating and control of segments, controlling graphics workstations, and controlling of coordinate systems and transformations.

Advantages

- GKS is a mature 2-D graphics programming interface standard.
- It is graphics device independence.
- It has good vendor support.

Disadvantages

- GKS provides 2-D graphics only.

Recommended Usage

GKS is a mature technology standard and should be used for developing 2-D graphics applications where device independence and/or program portability are desired.

Related Technology Standards

PHIGS

Support Contact

IRM, Advanced Technology and Architecture Section

References

ANSI X3.124-1985, *Graphic Kernel System*

FIPS Pub 120-1, *Graphical Kernel System (GKS)*

PHIGS

Associated Technology Group

Graphics Services

Description

Programmer's Hierarchical Interactive Graphics System (PHIGS) provides a functional interface between an application program and a configuration of graphical input and output devices. The functional interface contains basic functions for dynamic interactive hierarchical graphics on a wide variety of graphic equipment. The set of functions includes:

- definition, display, and modification of 2-D or 3-D graphical data
- definition, display, and modification of geometrically related objects
- modification of graphical data and the relationships between the graphical data

PHIGS implementations provide for graphics device independence and program portability by providing the programmer a standard subroutine library for 3-D graphics functions. In addition to providing the functionality of earlier graphical standards (GKS and GKS-3), this standard enables graphical (and application) data to be stored in a hierarchical data store. This standard is aimed for an environment requiring a high degree of interactivity, and it extends the GKS concept of the workstation to support a dynamic environment.

PHIGS is defined by ANSI and adopted by ISO as a standard. Language bindings are complete for Ada and FORTRAN, and planned for C and Pascal. A new standard, called PHIGS Plus, is being developed to add shading, lighting, and other advanced graphics programming capabilities not included in PHIGS.

Advantages

- PHIGS supports 3-D as well as 2-D graphics.
- There is good vendor support.

Disadvantages

- C language binding has not yet been completed.

Recommended Usage

PHIGS is a strategic but not yet mature technology. Where implementations are available, it should be used for developing graphics applications where device independence and/or program portability are desired.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T6.2
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Technology Standards

GKS
PEX

Support Contact

IRM, Advanced Technology and Architecture Section

References

ANSI X3.144-1988 and ANSI X3.144.1-1988, *Computer Graphics-Programmer's Hierarchical Interactive Graphics System (PHIGS) Functional Description*

FIPS Pub 153, *Programmer's Hierarchical Interactive Graphics System (PHIGS)*

Network Services Technology Group

Description

Network Services provide the functions to support the connections of workstations (terminals or personal computers) to host computer-based applications, the transfer of information across a heterogeneous computing environment, the sharing of computer resources such as disk drives and printers across a network, and distributed applications requiring data access across a heterogeneous computer network.

Technology standards for Network Services fall into the following categories:

Physical and data link level protocols represent the lowest level network protocols that describe the hardware and the basic transmission of bits of information.

Communications protocols are the rules that describe how data messages are transferred across a network, how the data is interpreted, and what basic application functionality is provided by the network.

Network security services include access, authentication, confidentiality, and integrity controls in the management of communications between senders and receivers of information in a network.

Technology Standards

T7.1	Ethernet
T7.2	Token Ring
T7.3	FDDI
T7.4	OSI
T7.5	TCP/IP
T7.6	DECnet / LAT
T7.7	SNA
T7.8	XNS/IPX
T7.9	AppleTalk
T7.10	SNMP
T7.11	Kerberos

Related Technology Standards

T8.2	RS-232
T8.3	RS-449/RS-442/RS-423
T8.4	V.35

Ethernet

Associated Technology Group

Network Services

Physical and Data Link Level Networking

Description

Ethernet (IEEE 802.3) is the LAN standard for shared media access with the widest vendor implementation support. Ethernet is an earlier standard developed jointly by DEC, Intel, and Xerox based on earlier Xerox research and is the standard upon which IEEE 802.3 is based. Version 2 of the Ethernet standard and IEEE 802.3 differ in small details, but products based on the two standards can coexist on a single LAN. Ethernet is implemented using 50 ohm coaxial cable (thick = RG8, thin=RG58) as well as fiber optic (62.5 micron multimode fiber) cables. The IEEE has also endorsed a new standard, called 10BaseT, for IEEE 802.3 or Ethernet use of unshielded twisted pair (UTP) cables. Newer site implementations are based on fiber optic cables linking buildings within an area and 10BaseT implementations within the buildings.

The basic data rate of Ethernet over all wiring schemes is 10 million bits per second (mbps). With coax cable, Ethernet end-to-end distances are limited to 1600 meters; fiber optic cables and repeaters extend this to 2800 meters; and network bridges extend a single physical network up to 28,000 meters. 10BaseT requires that Ethernet devices be located within 100 meters of a central wiring room. Each SRS area can be (and generally is) covered by an Ethernet LAN. Ethernet uses a time-shared bus technology that resolves multiuser contention for access to transmission on the cable with a fast yet simple algorithm called CSMA-CD. This technique is very fast and efficient at low levels of network use and can support overall network loading of about 70-80% of the basic transmission rate.

Advantages

- A very large installed base of products support Ethernet.
- Ethernet operates on coax, fiber optic, and twisted pair cables.
- It provides for simple installations with no tuning requirements.

Disadvantages

- Maximum data rate of 10 mbps is in danger of being exceeded by fast workstations.
- There is no priority mechanism for guaranteed network access under heavy loads.

Recommended Usage

Ethernet (IEEE 802.3) is a mature and strategic technology standard and is the primary site LAN standard. Its use is recommended for all site LANs except where special requirements dictate FDDI or Token Ring.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T7.1
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Standards

Token Ring
FDDI

Support Contact

IRM, Computer and Telecommunications Management Section

References

ANSI/IEEE Standard 802.3-1985, *CSMA-CD Access Method and Physical Layer Specification*

FIPS Pub 107, *Local Area Networks: Baseband Carrier Sense Multiple Access with Collision Detection Access Method and Physical Layer Specifications and Link Layer Protocol*

ISO/DIS 8802/3, *Local Area Networks—Part 3: Carrier Sense Multiple Access with Collision Detection*

Token Ring

Associated Technology Group

Network Services
Physical and Data Link Level Networking

Description

Token Ring is a physical and link level LAN specification. It has been defined by IBM and adopted by ANSI, IEEE, and ISO. ANSI/IEEE 802.5-1985 specifies the formats and protocols used by the token-passing medium access control sublayer, the physical layer, and the means of attachment to the token-passing ring medium. Token Ring is IBM's strategic direction for local area networks. It is particularly well supported by IBM for IBM Personal Computers and PS/2 connectivity in work group and IBM host interface applications. Token Ring utilizes unshielded twisted pair, shielded twisted pairs, or fiber optic cables at the basic data rate of 4 megabits per second (mbps). Newer products support 16 mbps as well as the slower rate. IBM's 16 mbps products also support 4 mbps, but a single ring may only run at one speed. Token Rings can be extended by using local or remote bridges so that several rings can be combined into one internetwork.

Advantages

- Token Ring is IBM's strategic product for mainframe - personal computer connectivity.
- It supports priority setting for predictable and dedicated response on heavily loaded LANs.

Disadvantages

- Token Ring's bridging procedures are not common with other IEEE standards.
- It has limited support from some minicomputer and large system manufacturers.

Recommended Usage

Token Ring is a mature technology standard but is not strategic for site use. Ethernet (IEEE802.3) is the primary site LAN standard. Token Ring is supported as an alternative for special requirements. Upper level protocols SNA, TCP/IP, and IPX have been supported on the site over a Token Ring LAN.

Related Standards

Ethernet
FDDI

Computing Standards and Guidelines Reference

Technology Standards

Document: WSRC-IM-92-23
Section: T7.2
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Support Contact

IRM, Computer and Telecommunications Management Section

References

ANSI/IEEE Standard 802.5-1985, *Token Ring Access Method and Physical Layer Specifications*

ISO 8802/5, *Local Area Networks—Part 5: Token Ring Access Method and Physical Layer Specifications*

FDDI

Associated Technology Group

Network Services
Physical and Data Link Level Networking

Description

Fiber Distributed Data Interface (FDDI) is an ANSI and ISO standard LAN technology developed to provide an order of magnitude improvement in speed over existing LAN technologies. FDDI is based on fiber optics communication using a form of token passing protocol for station access at speeds of 100 million bits per second. FDDI supports distances of up to 2 kilometers between stations in a standard configuration with extensions of up to 25 kilometers between stations with special optics (lasers and single mode fiber).

FDDI is supported by all major communications and computer system vendors. Equipment is being produced to allow the attachment of systems to an FDDI LAN and to use an FDDI LAN to interconnect Ethernet and/or Token Ring LANs together. The site LAN currently uses FDDI to link the IBM and Cray mainframe computers together and will be extended with further FDDI trunks in the future.

The FDDI standard is subdivided into four parts:

- PHY - Physical Protocol
- PMD - Physical Medium Dependent Protocol
- MAC - Medium Access Control Protocol
- SMT - Station Management Protocol

The U.S. Government OSI profile (GOSIP) Version 3 will sanction FDDI as an option to Ethernet or Token Ring for LAN implementations.

Advantages

- FDDI is the only standard for high performance (greater than 16 mbps) LANs.
- All major computer vendors support FDDI.
- It provides fault tolerant features.

Disadvantages

- FDDI interfaces are relatively expensive.
- No FDDI adapters are available for PS/2 or Macintosh personal computers.
- The station management protocol has not yet been finalized.

Recommended Usage

FDDI is a strategic technology standard but is not yet mature. Ethernet (IEEE802.3) is the primary site LAN standard. FDDI is supported as an alternative for special requirements.

Related Standards

Ethernet
Token Ring
OSI

Support Contact

IRM, Computer and Telecommunications Management Section

References

ANSI X3.139-1987, *Fiber Distributed Data Interface (FDDI) Token Ring Media Access Control (MAC)*

ANSI X3.148-1988, *Fiber Distributed Data Interface (FDDI) Physical Layer Protocol (PHY)*

ANSI X3.166-1990, *Fiber Distributed Data Interface (FDDI) Physical Layer Medium Dependent (PMD)*

ANSI X3T9.5, *Fiber Distributed Data Interface (FDDI) Station Management Protocol (SMT) (Draft)*

OSI

Associated Technology Group

Network Services
Communications Protocols

Description

Open Systems Interconnect (OSI) is a set of communications standards sponsored by the International Standards Organization (ISO) to facilitate the construction of open, heterogeneous computer networks. OSI protocols have been endorsed by the U. S. government. Government (including SRS) procurements for communicating computers must specify a subset of OSI protocols in the functional specifications for the systems. This is referred to as the GOSIP (Government OSI Protocols) requirement.

OSI is a feature rich, multiple-layered protocol family. OSI networks will use IEEE 802 (Ethernet and Token Ring), FDDI LANs, point-to-point links, or X.25 packet switch networks to provide standard applications such as virtual terminal (VTP), file copy (FTAM), and electronic messaging (X.400). Eventually, OSI protocols will replace TCP/IP and many of the proprietary network protocols in use at SRS, but OSI implementations are still immature.

Advantages

- OSI is an emerging international standard to be supported by all major computer vendors.

Disadvantages

- OSI products are immature and not widely available as yet.

Recommended Usage

OSI is a strategic but not yet mature technology standard. Today, certain parts of the OSI standards are more mature than others. OSI rests on existing LAN technologies in use at SRS. X.400 is the only standard for linkage of electronic messaging systems. Other OSI applications remain incomplete.

Related Standards

X.400
X.500
Ethernet
Token Ring
FDDI

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T7.4

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

Support Contact

IRM, Computer and Telecommunications Management Section

References

ISO 7498-1984, *Open Systems Interconnection—Basic Reference Model*

FIPS Pub 146, *GOSIP, Government Open Systems Interconnection Profile—Version 1*

FIPS Pub 146-1, *GOSIP Version 2.0*

TCP/IP

Associated Technology Group

Network Services
Communications Protocols

Description

Transmission Control Protocol / Internet Protocol (TCP/IP) is a family of communications protocols designed to support communications between heterogeneous computers. As such, it is now viewed as a precursor to OSI networking. Functions provided by TCP/IP include file transfer (FTP), electronic mail (SMTP), and support for terminal login across the network (TELNET). TCP/IP has been implemented to utilize most LAN physical and link level protocols (such as Ethernet and Token Ring). Any TCP/IP node has a unique address and node name. Network addresses and names are administered at SRS by IRM. These addresses are consistent with the global TCP/IP addressing scheme, so that if future TCP/IP links between SRS and off-site locations are developed, the addresses will not conflict.

At SRS, TCP/IP implementations are available for UNIX systems (including the Cray), the IBM mainframes, VAX VMS systems, and personal computers (both IBM and Apple). A robust TCP/IP routing network between SRS areas and major off-site work locations is in place.

TCP/IP protocols are defined by the Internet Activities Board (IAB) series of documents called Requests For Comment (RFC).

Advantages

- There is wide support across vendor lines (including Apple, Cray, DEC, and IBM) for TCP/IP.
- TCP/IP is supported over all LAN types as well as wide area networks.
- Some products are available in the public domain at no cost.

Disadvantages

- Each TCP/IP device requires a unique, static address.
- TCP/IP will be replaced by OSI protocols in the next several years.

Recommended Usage

TCP/IP is a mature and strategic technology standard and is the recommended protocol for linkage of heterogeneous computer systems. In the future, OSI communications protocols will supplement and later supplant TCP/IP.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T7.5
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Standards

SNMP
OSI

Support Contact

IRM, Computer and Telecommunications Management Section

References

RFC 791, *Internet Protocol*

RFC 793, *Transmission Control Protocol*

RFC 854, *Telnet Protocol*

RFC 959, *File Transfer Protocol*

DECnet/LAT

Associated Technology Group

Network Services

Communications Protocols

Description

DECnet is Digital Equipment Corporation's (DEC) implementation of DEC's proprietary Digital Network Architecture (DNA). DECnet provides a rich set of features for network communications between DEC systems. These features include virtual terminal logins, file copies, electronic mail exchange, remote file access, task-to-task communications, and network management. DECnet protocols, although proprietary to DEC, are published and have been implemented by a variety of vendors. There are DECnet implementations available for IBM mainframes (Interlink), IBM PCs, Apple Macintosh computers, and SUN workstations, to name a few.

DECnet utilizes unique addresses and names for each node on the network. Addresses are subdivided into area numbers and node numbers. IRM is responsible for managing the DECnet address assignments and has established DECnet areas to correspond to site areas. In 1992 DEC will distribute a new version (Phase V) which will make DECnet compatible with OSI networking protocols.

LAT (Local Area Transport) is a separate DEC LAN protocol for connecting LAN terminal servers to VAX computers. LAT software is bundled into the VAX/VMS operating system, and is very efficient.

Advantages

- DECnet and LAT are mature and full featured.
- They are integrated into DEC operating systems at little or no additional cost.

Disadvantages

- DECnet/LAT are not available for as many vendors' equipment as TCP/IP.
- LAT terminal servers connect only to DEC host computers.

Recommended Usage

DECnet is a mature technology standard and is the recommended protocol for linkage of Digital Equipment Corporation (DEC) computer systems today. TCP/IP is now supplementing DECnet on many VAX systems. In the future, DEC will change DECnet, basing it on OSI protocols. LAT is the recommended protocol for linking terminal servers to VAX computer systems. It is the site's long term direction to phase out terminal servers and LAT in favor of directly connecting personal computers to the site LAN using TCP/IP or OSI protocols.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T7.6
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Standards

OSI
TCP/IP

Support Contact

IRM, Computer and Telecommunications Management Section

References

DECnet DIGITAL Network Architecture (Phase IV) General Description,
Digital Equipment Corporation

SNA

Associated Technology Group

Network Services
Communications Protocols

Description

IBM's Systems Network Architecture (SNA) is IBM's unifying communications architecture for linking diverse IBM products from the desktop to the largest mainframe computer systems. It predominantly follows a hierarchical model with controls established at the mainframe, but is being extended to support local area networks and peer-to-peer services. SNA defines the protocols used to support the IBM 3270 terminal system as well as computer-to-computer links. SNA provides the strategic communications component of IBM's Systems Applications Architecture (SAA), IBM's blueprint for a computer application development and delivery environment.

Key SNA protocols have been published, and other vendors often use SNA protocols for communicating to IBM systems. The term SNA Gateway is often used to mean a device that speaks both SNA and non-SNA protocols, and provides the connection for non-IBM equipment to the IBM mainframe.

Advantages

- SNA is a de facto standard endorsed by many vendors as a means of communicating with IBM central computer systems.
- It is widely used in personal computer to mainframe links and Token Ring LAN-mainframe connections.

Disadvantages

- SNA is proprietary to IBM.
- It requires relatively large amounts of time, skill, and resources to support.
- It is strongly hierarchical in nature and requires coordination among different nodes in the network.

Recommended Usage

SNA is a mature technology standard and is one recommended protocol for communications with the IBM mainframe in the Central Computer Facility. TCP/IP is becoming increasingly more important for non-IBM systems communications with IBM mainframes, and OSI will be so in the future. IBM will work to supplement SNA with additional TCP/IP and OSI capabilities.

Related Standards

TCP/IP
OSI

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T7.7

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

Support Contact

IRM, Computer and Telecommunications Management Section

References

IBM Systems Network Architecture Concepts and Products GC30-3073-3, IBM Corporation

XNS/IPX

Associated Technology Group

Network Services
Communications Protocols

Description

XNS (Xerox Network Services) is a protocol family developed by Xerox Corporation, placed in the public domain, and used (and often modified) by many computer vendors. It follows a layered model much like the OSI model.

At SRS, XNS is used by Intergraph Computer-Aided Design (CAD) systems for interprocessor communications. A modified version of XNS, IPX (Internet Packet Exchange), is the basic protocol used in Novell's Netware operating system. Because there are many different versions of XNS, interoperability between vendors' versions is not assured. TCP/IP is recommended as a more standard method available today for multi-vendor communications, and OSI will be recommended in the future.

Advantages

- The version to support Novell's Netware (IPX) is widely implemented.

Disadvantages

- There are many different versions of XNS that are often incompatible.
- XNS and IPX will be replaced by TCP/IP and/or OSI in the future.

Recommended Usage

This is a mature but non-strategic technology standard. At SRS, XNS support is limited to Intergraph workstations. IPX is the standard protocol for Novell Netware implementations and is supported at SRS. This protocol is expected to be replaced by TCP/IP and/or OSI in the future.

Support Contact

IRM, Computer and Telecommunications Management Section

Related Standards

TCP/IP
OSI

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T7.8

Page: 2 of 2

Issue Date: 4/1/92

Revision: 0

Technology Standards

References

Novell API Reference Manual, Volume II

Intergraph Network Core User's Guide, Document Number DSYS017

AppleTalk

Associated Technology Group

Network Services
Communications Protocols

Description

AppleTalk is a family of communications protocols developed by Apple. AppleTalk is often confused with the LocalTalk physical networking standard. The AppleTalk protocol suite is full-featured, including support for datagrams (DDP), reliable data streams (ADSP), file sharing (AFP), and printing (PAP). AppleTalk has full routing capabilities for use in local and wide area applications. AppleTalk has been implemented to utilize most LAN physical and link level protocols, such as Ethernet (called EtherTalk) and Token Ring (TokenTalk), as well as Apple's LocalTalk wiring. Address assignment is done dynamically and transparently to the user.

At SRS, AppleTalk is primarily used to support work-group printers and Macintosh file servers. There are implementations available for UNIX, PC-DOS, and VMS systems that support file sharing and printing. SRS has implemented a robust AppleTalk routing network between SRS areas and off-site facilities.

Advantages

- AppleTalk supports all LAN types as well as wide area networks.
- Apple's LocalTalk wiring scheme and the AppleTalk protocols are supported by every Macintosh.
- AppleTalk for VMS is available for VAX integration.

Disadvantages

- It is not implemented on many large systems.
- AppleTalk is not as suitable for very large networks as TCP/IP.

Recommended Usage

AppleTalk is a mature technology standard for which support is limited to linkage of Macintosh computers to file and print services. Support for AppleTalk on the site Ethernet LAN is limited to AppleTalk Version 2. It is likely that this protocol will be transitioned to TCP/IP in the future and replaced by OSI in the more distant future.

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T7.9
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Related Standards

TCP/IP
OSI

Support Contact

IRM, Computer and Telecommunications Management Section

References

Inside AppleTalk, 2nd Edition, Apple Computer, Inc.

SNMP

Associated Technology Group

Network Services
Communications Protocols

Description

Simple Network Management Protocol (SNMP) defines a structure of data values associated with network objects (equipment on a network) called a Management Information Base (MIB) and a communications protocol that allows a management station to query information about the state of a network device and to change the operating characteristics of the device by storing a value in the MIB. SNMP also supports the concept of a "trap" whereby certain operating conditions trigger the transmission of a message from the device to the management station.

SNMP allows a network manager to manage (that is, monitor and configure) a variety of network equipment from a single workstation. SNMP is well supported by network equipment vendors, but implementations are currently limited to TCP/IP communications protocols.

Advantages

- SNMP is the de facto industry standard for management of a wide variety of network devices.

Disadvantages

- Implementations of SNMP are largely limited to TCP/IP communications products.

Recommended Usage

SNMP is a strategic and mature technology standard and is recommended for management of TCP/IP-based communications products. It is expected that OSI management protocols, as yet still evolving, will replace SNMP in the future.

Related Standards

TCP/IP

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23

Section: T7.10

Page: 2 of 2

Issue Date: 4/1/92

Technology Standards

Revision: 0

Support Contact

IRM, Computer and Telecommunications Management Section

References

RFC1157, *Simple Network Management Protocol*

RFC1156, *Management Information Base*

RFC 1158, *Management Information Base II*

Kerberos

Associated Technology Group

Network Services
Network Security Services

Description

The Kerberos security service provides facilities for supporting confidentiality in remote procedure calls, a means for authenticating users and services, management of access permissions, and a registry for user account information. This technology originally came out of MIT's Project Athena.

Under Kerberos, a trusted "authentication server" is used to verify users so that network servers are assured of the correct identities of clients requesting service. Thus, only a single authentication database (which may be replicated for reliability) is required for a network, rather than requiring each server to authenticate all users independently. Authentication procedures use DES encryption of passwords and permissions to provide additional security in a LAN environment.

Kerberos has been adopted by the Open Systems Foundation (OSF) as the Authentication Service provided by the OSF Distributed Computing Environment (DCE). This Authentication Service will be required by the other components of DCE, namely file services and remote procedure calls.

Advantages

- Kerberos is integrated with a wide collection of services for a distributed computing environment.
- Major computer vendors (including IBM and DEC) have announced products or statements of future support for Kerberos.
- Kerberos is part of the OSF DCE standard for network computing.

Disadvantages

- Kerberos is not widely implemented as yet.

Recommended Usage

Kerberos is a strategic and mature technology standard and should be used as a technical specification for operating system and network application procurements.

Related Technology Standards

OSF DCE
DES

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T7.11
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

IRM, Advanced Technology and Architecture Section

References

Kerberos Authentication and Authorization System, M.I.T., Project Athena

Hardware Interfaces Technology Group

Description

Hardware interface standards define industry standard (de facto or otherwise) interfaces that are used to join computer system components together. These standards are necessary for vendor independence in selecting components to put together complete computer systems and to join these systems to communications networks. These types of standards are not unlike standards found in the home electronics arena, (e.g., standard component interfaces allow plugging stereo receivers to "foreign" CD players) or even in plumbing connectors, and they serve the same purpose.

Technology Standards

- T8.1 CD-ROM Disk Format (ISO 9660-1988)
- T8.2 RS-232
- T8.3 RS-449/RS-422/RS-423
- T8.4 V.35
- T8.5 SCSI
- T8.6 Centronics Parallel Printer Interface

Related Technology Standards

- T7.1 Ethernet
- T7.2 Token Ring
- T7.3 FDDI

CD-ROM Disk Format (ISO 9660-1988)

Associated Technology Group

Hardware Interfaces

Description

ISO 9660 defines the physical attributes, disk format, and directory structure for CD-ROM disks used for data or applications storage (not music). While there is not a related FIPS, work is underway to identify the deficiencies and create a FIPS based on this standard.

Advantages

- ISO 9660 is widely used in the PC (DOS) industry.
- The standard is stable and simple enough that applications that state adherence usually are compatible.

Disadvantages

- It is primarily oriented toward DOS applications, and is not currently included in a FIPS.
- The disks do not behave as native disks to most computers; that is, they require interface software to appear as "mounted" disks.

Recommended Usage

This is a mature technology standard and should be used in specifying CD-ROM readers for use with DOS applications, and is a desirable feature for CD-ROM readers for other platforms as well. It is not the primary standard for non-DOS CD-ROM readers. While the ISO 9660 standard grew out of the High Sierra format, a High Sierra Group (HSG) drive will probably not read an ISO 9660 disk, and vice-versa. HSG drives and disks should be avoided.

Related Technology Standards

None

Support Contact

IRM, Advanced, Technology and Architecture Section

References

Volume and File Structure of CD-ROM for Information Interchange, Ref. No. ISO 9660:1988

RS-232

Associated Technology Group

Hardware Interfaces

Description

The Electronic Industries Association (EIA) RS-232 standard defines the industry standard interface for low speed serial data communications. The CCITT V.24 standard closely follows RS-232. Specifically, RS-232 defines the standard between Data Termination Equipment (i.e., a computer or terminal) and Data Communications Equipment (typically a modem). RS-232 C (Version C of the standard) is the most common implementation.

The standard provides either asynchronous or synchronous serial communications at data rates up to 20,000 bits per second. The standard defines the number and type of conductors in a multi-wire cable, the shape of the cable connectors, and the signalling conditions. RS-232 is well supported by computer equipment manufacturers.

Advantages

- RS-232 has wide industry support.
- The standard is stable and often provides a lowest common denominator for connecting dissimilar equipment.

Disadvantages

- RS-232 supports slow speed applications only.
- Equipment vendors feel free to redefine the configuration of RS-232 connectors, requiring special interface cables to connect equipment.

Recommended Usage

RS-232 (Level C or D) should be required for asynchronous terminals, serial printers, and slow speed modems.

Related Technology Standards

RS-449

Support Contact

DC&S

References

EIA Standard RS-232, *Interface Between Data Terminal Equipment and Data Communications Equipment Employing Serial Binary Interchange*

RS-449, RS-442, RS-423

Associated Technology Group

Hardware Interfaces

Description

The Electronic Industries Association (EIA) RS-449/422/423 standards defines an industry standard interface for moderate speed serial data communications. The CCITT V.24 standard closely follows these standards. Specifically, RS-449 defines the mechanical, functional, and procedural interface specifications. RS-422 and RS-423 define optional electrical characteristics; RS-422 defines balanced signals and RS-423 unbalanced signals over the interface. These standards provide great improvements over RS-232 in data communications speed and distances. RS-422 signalling is used in faster data rate applications, supporting rates up to 10 million bits per second.

Advantages

- These standards have wide industry support.
- They support low, moderate, and high data transfer speeds.
- RS-423 can interoperate with RS-232.

Disadvantages

- Many vendors provide V.35 interfaces instead of RS-422 for moderate speed applications.

Recommended Usage

This is a mature technology standard. Specify as an alternative to V.35 for serial communications applications for data rate between 20,000 bits per second and 10 million bits per second. Use RS-232 for lower speed applications.

Related Technology Standards

EIA RS-232
CCITT V.35

Support Contact

DC&S

References

EIA Standard RS-422, *Electrical Characteristics of Balanced Voltage Digital Interface Circuits*

EIA Standard RS-423, *Electrical Characteristics of Unbalanced Voltage Digital Interface Circuits*

EIA Standard RS-449, *General Purpose 37-Position and 9-Position Interface Between Data Terminal Equipment and Data Circuit-Terminating Equipment*

FIPS Pub 138, *Electrical Characteristics of Balanced Voltage Digital Interface Circuits*

FIPS Pub 142, *Electrical Characteristics of Unbalanced Voltage Digital Interface Circuits*

V.35

Associated Technology Group

Hardware Interfaces

Description

CCITT standard V.35 defines a moderate speed serial interface for linking data communications equipment to data terminal equipment. It provides a higher speed alternative for RS-232 in synchronous serial data communications. V.35 provides similar capabilities to RS-422, but is more commonly used than RS-422 for linking high speed communications devices to communications circuits. For example, digital telephone circuits (typically 56 kbps to 1.544 mbps) are supported by devices called CSU/DSUs. These devices connect to data communications equipment with V.35 interfaces.

Advantages

- V.35 is widely supported in the computer communications industry.
- It provides moderate data transfer speeds (at least 1.5 mbps).

Disadvantages

- Bulky cable and 34 pin connectors are not compatible with RS-232.
- V.35 is not suitable for very high speed interfaces (T3).

Recommended Usage

V.35 is a mature technology standard. Specify for serial communications applications for data rates between 20,000 and 2 million bits per second. Use RS-232 for lower speed applications.

Related Technology Standards

EIA RS-232
RS-449

Support Contact

DC&S

References

CCITT Recommendation V.35, *Data Transmission at 48 Kilobits/second Using 60-108 kHz Group Band Circuits*

SCSI

Associated Technology Group

Hardware Interfaces

Description

Small Computer Systems Interface (SCSI) is an 8-bit bus interface for up to seven computer peripherals (disk, tape, CD-ROM, etc.) which allows any two devices to communicate at one time (host to peripheral, peripheral to peripheral). It is commonly used to connect peripherals to microcomputers and workstations.

SCSI (SCSI-1) provides up to 5 million bytes per second data transfer and can connect multiple peripherals while taking only one expansion slot in the computer. SCSI-2 provides command queuing and a "Fast SCSI" synchronous option that provides 10MB data transfer (8-bit). With a secondary "B" cable for 16- and 32-bit data, "Wide SCSI" provides up to 40MB transfer (proposed 68-conductor "P" cable is a single cable solution for 16 bits).

Advantages

- SCSI is widely used in the PC, Macintosh, and workstation markets.
- The standard is stable and simple enough that applications that state adherence usually are compatible.
- Connection of SCSI devices is simple due to standardization in cabling and minimal allowable configuration parameters.

Disadvantages

- There is some confusion of SCSI addressing that can cause address conflicts when multiple devices are on the bus.
- The number of devices is limited to seven.
- Interruption of the bus during operations can cause loss of communications to all devices.

Recommended Usage

This is a mature technology standard. SCSI is a convenient interface for connection of disk drives, scanners, and other peripherals to small computers or workstations. The SCSI interface should be used in an environment of "portable" peripheral connectivity.

Related Technology Standards

None

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: T8.5
Page: 2 of 2
Issue Date: 4/1/92
Revision: 0

Technology Standards

Support Contact

DC&S

References

ANSI X3.131-1986, *Small Computers Systems Interface*

FIPS Pub 131, *Small Computers Systems Interface (SCSI)*

Centronics Parallel Printer Interface

Associated Technology Group

Hardware Interfaces

Description

The Centronics standard was developed by the Centronics company, which makes computer printers. The Centronics standard is a 36-pin single plug/connector with eight of the 36-pins carrying their respective bits in parallel (eight bits to one character), providing a faster transfer rate than serial transmission, which sends only one bit at a time. There are several types of Centronics male and female plugs and receptacles. The pinning (the location of and function of each of the 36-individual wires) is standard from one Centronics cable to another.

Advantages

- This standard has wide industry support.

Disadvantages

- Only limited distance are permitted between printer and computer.
- Connector sizes and shapes may vary.

Recommended Usage

This is a mature technology standard. Specify for printers and for personal computers for attaching printers to personal computers.

Related Technology Standards

None

Support Contact

DC&S

References

Centronics Parallel Printer Interface Standard

Standard Product Groups

CAST has defined the following Product Groups:

- P1 Desktop Office
- P2 High Performance Workstations
- P3 Minicomputer Hardware
- P4 Data Communications
- P5 Relational Database Management Systems
- P6 Intrasite Office
- P7 Computer Aided Design/Computer Aided Engineering

Note: CAST work to establish site standard products has not been completed. Each time standards for a product group are completed, this document will be updated.

Computing Acronyms and Terms

10BaseT	Ethernet over Unshielded Twisted Pair Wiring
ADP	Automated Data Processing
ADSP	AppleTalk Data Stream Protocol
AFP	AppleTalk Filing Protocol
AFS	Andrew File System (DCE)
ANSI	American National Standards Institute
API	Applications Program Interface
AppleTalk	Apple Computer's Communication Protocols
ASC	Accredited Standards Committee (ANSI)
ASCII	American Standard Code for Information Interchange
BSRI	Bechtel Savannah River Incorporated
C2	Computer Operating System Security Standard
CAD	Computer Aided Design
CALS	Computer Aided Logistical Support (DoD standard)
CASE	Computer Aided Software Engineering
CAST	Computing Architecture and Standards Team, WSRC
CCF	Central Computer Facility
CCITT	Consultative Committee for International Telephone and Telegraph
CGM	Computer Graphics Metafile
CSMA-CD	Carrier Sense, Multiple Access with Collision Detection (Ethernet access)
CSU	Channel Service Unit
CTM	Computer and Telecommunications Management Section, IRM
DAL	Data Access Language (Apple Computer)
DBMS	Database Management System
DC&S	Digital Control and Systems Department, WSRC
DCE	Distributed Computing Environment (OSF)
DDP	Datagram Delivery Protocol (AppleTalk)
DEC	Digital Equipment Corporation
DECdns	DEC distributed name service (DCE)
DECdts	DEC distributed time service (DCE)
DECnet	DEC's Communication Protocols
DES	Data Encryption Standard
DFS	Distributed Filing System (DCE)
DNA	Digital Network Architecture (basis for DECnet)
DTD	Document Type Definition (SGML)
DoD	U. S. Department of Defense
DOE	U. S. Department of Energy
DOS	Disk Operating System (as in PC DOS)
DSA	Directory System Agents (X.500)
DSU	Data Service Unit
DUA	Directory User Agent (X.500)
EBCDIC	Extended Binary Coded Decimal Interchange Code
ECMA	European Computer Manufacturers Association
EDI	Electronic Document Interchange
EDIFACT	EDI Protocol
EIA	Electronic Industries Association
ESCC	Engineering and Scientific Computing Committee
Ethernet	Local area network technology (DEC/Xerox/Intel)

FDDI	Fiber Distributed Data Interface
FIPS	Federal Information Processing Standard
FIPS Pub	Federal Information Processing Standard Publication
FTAM	File Transfer, Access, and Management Protocol (OSI)
FTP	File Transfer Protocol (TCP/IP)
GKS	Graphical Kernel System
GOSIP	Government Open Systems Interconnection Profile
GUI	Graphical User Interface (window-style interface to computer)
IAB	Internet Activities Board
IEC	International Electrotechnical Committee
IBM	International Business Machines Corporation
IEEE	Institute of Electrical and Electronics Engineers
IEEE 802.3	LAN standard for Ethernet
IEEE 802.5	LAN standard for Token Ring
IGES	Initial Graphics Exchange Standard
IPX	Internet Packet Exchange (Novell Communications Protocol)
IRM	Information Resource Management Department, WSRC
ISA	Instrumentation Society of America
ISO	International Standards Organization
kbps	Kilobit per Second (Thousand bits per second)
LAN	Local Area Network
LAT	Local Area Transport (DEC Communications Protocol)
ma	milliamp (analog signal)
MAC	Medium Access Control (FDDI)
Mac	Macintosh personal computer (Apple Computer)
mbps	Megabits per second (one million bits per second transmission rate)
MHS	Message Handling System (X.400)
MIB	Management Information Base (Network Management Database)
MOTIF	Graphical User Interface defined by OSF for X-windows
MTA	Message Transfer Agent (X.400)
MS-DOS	Microsoft Disk Operating System
NCS	Network Computing System (precursor to DCE by Hewlett-Packard)
NCSC	National Computer Security Center
NIST	National Institute of Standards and Technology
Netware	Novell Inc. LAN Operating System
NFS	Network Filing System (Sun Computer)
ODA	Office Document Architecture
ODIF	Office Document Interchange Format
ONC	Open Network Computing (UNIX International)
OOPS	Object Oriented Programming System
OS/2	Operating System / 2 (IBM)
OSI	Open Systems Interconnection (International Standards Organization)
OSF	Open Systems Foundation
OSTI	Office of Scientific and Technical Information (DOE)

Computing Acronyms and Terms

PAP	Printer Access Protocol (AppleTalk)
PC	Personal Computer (e.g., Macintosh, IBM PS/2)
PDEC	Process Digital Equipment Committee, WSRC
PEX	PHIGS Extensions for X
PHIGS	Programmer's Hierarchical Interactive Graphics System
PHY	Physical Protocol (FDDI)
PMD	Physical Medium Dependent Protocol (FDDI)
PS /2	IBM Personal Systems /2 personal computer
POSIX	Portable Operating System Interface (IEEE)
RDA	Remote Data Access
RDBMS	Relational DataBase Management System
RFC	Request For Comment (TCP/IP standards from Internet Activities Board)
RFQ	Request For Quotation
RFT	Request For Technology
RPC	Remote Procedure Call
RS	Recommended Standard (EIA)
RSA	Rivest, Shamir, Adleman encryption algorithm
RTF	Rich Text Format
SAA	Systems Applications Architecture (IBM)
SCSI	Small Computer Systems Interface
SGML	Standard Generalized Markup Language
SMT	Station Management Protocol (FDDI)
SNA	Systems Network Architecture (IBM Communications Protocols)
SNMP	Simple Network Management Protocol
SQL	Structured Query Language
SRS	Savannah River Site
STEP	Standard for The Exchange of Product model data
TCP/IP	Transmission Control Protocol / Internet Protocol
TELNET	Terminal Communications Protocol (TCP/IP)
TIFF	Tagged Image File Format
UA	User Agent (X.400)
UCNI	Unclassified Controlled Nuclear Information
UNIX	Portable operating system (trademark of AT&T)
UTP	Unshielded Twisted Pairs
VAX	Primary DEC computer family
VMS	Virtual Memory System (VAX operating system)
VTP	Virtual Terminal Protocol
VT100	A DEC character-based terminal
X.12	EDI Protocol
X.400	Electronic Messaging Protocol (OSI)
X.500	Directory Services Protocol (OSI)
WSRC	Westinghouse Savannah River Company
X/Open	Consortium promoting interoperability of UNIX systems
XNS	Xerox Network Systems (LAN protocol)
XPG3	X/Open Portability Guide Version 3
X-window	Standard for device-independent text and image network terminals

Computing Standards and Guidelines Reference

Document: WSRC-IM-92-23
Section: Attachment B
Page: 1 of 2
Issue Date: 4/1/92
Revision: 0

Organizations Producing Standards Documents

The following organizations produce documents that describe technology standards guidelineed in this document. The following list provides an ordering address and phone number for contacting each organization. The Technical Library in SRTC (773-A) can provide assistance in obtaining copies of standards documents.

ANSI, American National Standards Institute

Approved Standards:
ANSI Sales Department
11 W 42 St
New York, NY 10036
Phone: (212) 642-4900

Draft Standards:
Global Engineering
1990 M St. NW, Suite 400
Washington, DC 20036
Phone: (800) 854-7179

CCITT, International Telegraph and Telephone Consultive Committee

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Phone: (703) 487-4600

DoD, U.S. Department of Defense: DoD-STDS, MIL-STDS, MIL-SPECS

Defense Technical Information Center (DTIC)
ATTN: FDRA
Cameron Station
Alexandria, VA 22304-6145
Phone: (703) 274-7633

EIA, Electronic Industries Association

Electronic Industries Association
1722 Eye Street, NW, Suite 300
Washington, D.C. 20006
Phone: (202) 457-4900

IEEE, Institute of Electrical and Electronics Engineers, Inc.

IEEE Standards Office
445 Hoes Lane
Piscataway, NJ 0885
Phone: (908) 562-3800

ISA, Instrument Society of America

Instrument Society of America
67 Alexander Drive, P.O. Box 12277
Research Triangle Park, NC 27709
Phone: (919) 549-8411

Computing Standards and Guidelines Reference

Document:

WSRC-IM-92-23

Section:

Attachment B

Page:

2 of 2

Issue Date:

4/1/92

Organizations Producing Standards Documents

Revision:

0

NIC, Internet Network Information Center: RFCs

SRI International, Inc.
Network Information Center
333 Ravenswood Ave.
Menlo Park, CA 94025
Phone: (800) 235-3155

ISO, International Standards Organization

ANSI Sales Department
11 W 42 St
New York, NY 10036
Phone: (212) 642-4900

NCSC, National Computer Security Center

National Computer Security Center
9800 Savage Road
Fort Meade, MD 20755-6000
Phone: (301) 859-4452

NIST, National Institute for Standards and Technology

U. S. Department of Commerce
National Institute for Standards and Technology
Admin Bldg A41
Gaithersburg, MD 20899
Phone: (301) 975-2000

NTIS, National Technical Information Service: FIPS Pubs

U. S. Department of Commerce
National Technical Information Service
Springfield, VA 22161
Phone: (703) 487-4650

Open Software Foundation, Inc.

Open Software Foundation, Inc.
11 Cambridge Ctr
Cambridge, MA 02142
Phone: (617) 621-8700

X/Open Company, Ltd

X/Open Company, Ltd
1750 Montgomery Street
San Francisco, CA 94111
Phone: (415) 323-7992

BLANK PAGE

Purpose

It is WSRC policy that site computing activities be based on standards (Reference 1). The primary reasons for defining the site's computing standards and guidelines are to promote interoperability of site computing systems and to facilitate the portability of programs, applications, and data between computer systems. This policy is necessary to obtain increased flexibility and cost effectiveness in carrying out the site mission.

The SRS computing standards will depend heavily on national and international standards, although standardization on dominant proprietary standards and on specific products will be required to reduce the total number of computer products supported at the site to a more manageable set. In other words, the emphasis on standards will be two-fold: standardization on the technologies required for information and process control systems integration, and standardization on specific products in order to keep the number of specific computer products that must be supported on the site to a manageable and economical set. Ideally, standard products will conform to the technology standards. However, there will be cases where existing standard products do not conform totally to the technology standards yet remain supported for reasons of continuity and economics.

A site-wide Computing Council has been formed (Reference 2) to coordinate and integrate computing activities at SRS. This organization consists of senior management representing each site division. It oversees the development and implementation of the site strategic computing vision in support of the site mission. The working arm of the Computing Council is the Computing Architecture and Standards Team (CAST). CAST is made up of representatives from all site divisions as well as other organizations that represent communities interested in computing, such as the Process Digital Equipment Committee (PDEC), the Engineering/Scientific Computer Committee (ESCC), and the Management Informations Systems Committee. CAST membership is knowledgeable in computing technologies and the use of computing to help perform the site's mission. This body is instrumental in setting standards for site computing and creating the site's computing architecture, as well as recommending computing policies to the Computing Council for consideration.

Technology Standards

A computing technology standard is defined by some international, national, industry consortium, or individual corporation as a standard way of accomplishing specific computing tasks or functions. These standards are "open" in the sense that the governing bodies publish the specifications in complete detail so that vendors may develop products that conform to the standards. In many cases the governing body for a standard will test and certify those vendor products that conform to the technology standard.

END

**DATE
FILMED**

9 / 30 / 92