DOE Report No DOE/PC 90284-9

DOE/PC/90284--9

DE93 011622

February 1993

Quarterly Report

for

Grant No. DE-FG22-90PC90284

entitled

Molecular Accessibility in Solvent Swelled Coals

Lowell D. Kispert, Principal Investigator
Department of Chemistry
The University of Alabama
Tuscaloosa, AL 35487-0336

DISCLAIMER
This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

US/DOE Patent clearance is not required prior to the publication of this document.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PREVIOUS WORK COMPLETED

An EPR technique developed in this lab¹⁻³ is being used to determine the pore size and number distribution changes after swelling the coal samples with various solvents. Stable nitroxide radical spin probes of different sizes, shapes and reactivity are dissolved in an appropriate solvent, the coal sample is added to the resulting solution, stirred over night at elevated temperature, filtered, washed with a non swelling solvent to eliminate any spin probes that are not trapped in the pores and the spin concentration is measured. Comparing these spin probe measurements to DRIFT data have shown⁴ that the relative number distribution of acidic functionalities can be accurately predicted by the spin probe method. The spin probe method had also been used to predict⁴⁻⁵ the increase in elongated voids in Pittsburgh No. 8 (APCS No. 4) upon swelling with pyridine in agreement with independent SANS data. NMR relaxation data show³ that it is possible to deduce the pore (accessibility) distribution as a function of size (up to 6 nm). It has also been possible by variable temperature¹⁻³ and ENDOR measurements⁶ to determine the presence of hydrogen bonding as a function of pore shape and size. The advantage of the EPR method is that it permits molecules of selected shape and size to be used as probes of accessible regions of coal, thus providing information on the importance of molecular shape.

To expand the information base on molecular accessibility in solvent swelled coal, Argonne Premium Coal Samples (APCS) were swelled in polar, basic solvents before and after moisture loss and upon air oxidation. So far studies have been reported^{7,8} on the changes in pore size distribution as a function of temperature when polar basic swelling solvents are used. Additional studies employing EPR spin probe techniques performed on the breaking up of the hydrogen bonding between bedding planes^{9,10} were later confirmed by magnetic resonance imaging at Argonne National Lab and the University of Illinois.

A paper¹¹ was accepted in the Journal, *Fuel* on the micropore wall chemistry during swelling. Studies of spin probe retention with increasing spin probe polarity, provided valuable insight into the hydrogen bond cross-link density and oxygen functionality of APCS coals.

Eight Argonne Premium Coal Samples (APCS) were weathered in air and the structural and chemical changes that occurred upon swelling with toluene and pyridine were examined by our EPR spin probe method. The large structural changes were attributed to collapse of the coal structure. The results were reported at the ACS Fuel chemistry Division Annual meeting in Washington, DC., August 23-26, 1992 in the Symposium on Analytical Techniques for Characterizing Coal and Coal Conversion Products.

A paper was also published¹² on our study of the changes in the molecular accessibility in solvent swelled APCS coals that had been oxidized for over a period of 6 months in ambient air with the humidity less than 50%, and experiments on the effect of oxidation in zero percent humidity were completed.

Last quarter a study of the effects of dehydration on all eight APCS coals using EPR spin probe techniques was completed which provided insight into separating the effects of dehydration and oxidation on the molecular accessibility into the coal structure. Comparison to coals oxidized in air showed that the accessibility, as determined by EPR spin probe techniques, for vacuum dried coals was similar to that of air oxidized coals. This implied that the effects of air oxidation on coal structure could be attributed largely to dehydration. Also, a comparison of the swelling experiments run for vacuum dried, air oxidized coals and air oxidized coals in toluene with polar spin probes (COOH and NH₂), indicated that coals which were vacuum dried and then air oxidized had greater spin probe retention. It was concluded that vacuum drying coals facilitates the oxidation of coal, and that the presence of water will greatly alter the effects of coal oxidation in air.

SUMMARY OF CURRENT ACTIVITIES

This quarter a detailed analysis of the data collected from the swelling of coals oxidized in a moisture free environment was completed. The coal samples were evacuated for several hours in order to reach a state of complete dehydration. Weight loss was measured, and each of the APCS coal samples was split into two aliquots. One of these aliquots was used in the weathering experiments done last quarter to study the effects of dehydration. The other was placed under a pure oxygen environment in a glove bag with zero percent humidity. Samples of each coal were taken out and swelled with spin probe solutions at various time intervals over a 64 day period. Particular care was taken during the swelling procedures to avoid exposure of the coal samples to air or moisture. EPR spectra were then obtained for these 300 samples.

The data for the spin probe retention of fresh coal weathered in air, vacuum dried coal weathered in air and vacuum dried coal oxidized under pure oxygen were plotted three dimensionally to get a more complete picture of the effects of oxidation and dehydration. A 3D plot was made for each of the conditions listed above and spin probe, solvent combination. These plots provide an effective way to compare the over 800 samples obtained from oxidation studies. In general, the results verified that the effects of oxidation on coal are greatly influenced by the presence of moisture. The retention of polar spin probes in toluene or pyridine was greater in vacuum dried, weathered coals than in fresh, weathered coals, and much greater in vacuum dried, O₂ oxidized coals.

Subtracting out the results of vacuum drying the coals for each specific spin probe, solvent combination showed that much of the change in micropore wall chemistry observed by spin probe retention was due to the presence of oxygen, and not primarily due to dehydration. Other topographical features of these plots may provide more specific information about individual coals. It was determined from this information that Illinois #6 would be the best APCS coal to study with short term oxidation experiments.

An example of the 3D plots produced from our data is shown in figure 1 below.

Figure 1, Retention of spin probe VI vs weathering and rank.

STUDIES PLANNED FOR NEXT QUARTER

Next quarter, the EPR spin probe technique will be used to examine the swelling behavior of 2% to 12% cross-linked polystyrene-divinylbenzene (PSDVB) copolymers in order to gain insight into the molecular accessibility of covalently cross-linked coal. It is hoped that these experiments will help to provide a more complete picture of solvent swelling in the presence of both hydrogen bonding and/or covalent cross-linking in coal.

REFERENCES

1. Wu, S.K.; Kispert, L.D. *Fuel* **1981**, *64*, 1681-1686.
2. Kispert, L.D.; Cooray, L.S.; Wu, S.K. *Prepr. Pap. Am. Chem. Soc., Div. Fuel Chem.* **1987**, *32*, 286-292.
3. Cooray, L.S.; Kispert, L.D.; Wu, S.K. *Prepr. Pap. Am. Chem. Soc., Div. Fuel Chem.* **1988**, *33*, 32-37.
4. Goslar, J.; Kispert, L.D. *Energy to Fuels* **1989**, *3*, 589-594.
5. Goslar, J., Cooray, L.S., Kispert, L.D. *Fuel* **1989**, *68*, 1402-1407.
6. Goslar, J., Kispert, L.D. *Fuel* **1990**, *69*, 564-569.
7. Spears, R.; Goslar, J.; Kispert, L.D. in "Techniques in Magnetic Resonance for Carbonaceous Solids," Botto, R., and Sanada, Y. Eds., ACS Symposium Series No. 229, In Press.
8. Spears, R.; Kispert, L.D.; Piekara-Sady, L. *Am. Chem. Soc. Div. Fuel Chem. Prepr.* **1991**, *36*, 29.
9. Spears, R.; Sady, W.; Kispert, L.D. *Am. Chem. Soc. Div. Fuel Chem. Prepr.* **1991**, *36*, 1277.
10. Spears, R.; Kispert, L.D.; Piekara-Sady, L. *Fuel* **1992**, *71*, 1003.
11. Spears, D. R.; Sady, W.; Kispert, L.D. *Fuel* **1992**, In Press.
12. Sady, W.; Kispert, L.D.; Spears, D.R. *Am. Chem. Soc. Fuel Chem. Prepr.* **1992**, *37*, 1151.

END

DATE
FILMED

5 / 14 / 93