KEYWORDS:
Process Modeling
Models
Computer Codes

RETENTION:
Lifetime

**NUMERICAL BENCHMARKING OF SPEEDUP™
AGAINST POINT KINETICS SOLUTIONS (U)**

M.V. GREGORY

FEBRUARY 1993

WSRC-RP--93-320

DE93 012819

APPROVALS

M.R. Buckner, Manager
Scientific Computations Section

DATE: 03/02/93

R.R. Beckmeyer, Manager
Computing Technology Group

DATE: 02/23/93

K.L. Shanahan, Technical Reviewer
Analytical Development Section

DATE: 2/22/93

Westinghouse Savannah River Company
Savannah River Technology Center
Aiken, SC 29808

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY UNDER CONTRACT
NUMBER DE-AC09-89SR18035

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Summary

SPEEDUP™ is a state-of-the-art, dynamic, chemical process modeling package offered by Aspen Technology. In anticipation of new customers' needs for new analytical tools to support the site's waste management activities, SRTC has secured a multiple-user license to SPEEDUP™. In order to verify both the installation and mathematical correctness of the algorithms in SPEEDUP™, we have performed several numerical benchmarking calculations. These calculations are the first steps in establishing an on-site quality assurance pedigree for SPEEDUP™.

The benchmark calculations consisted of SPEEDUP™ Version 5.3L representations of five neutron kinetics benchmarks (each a mathematically stiff system of seven coupled ordinary differential equations), whose exact solutions are documented in the open literature (see Reference). In all cases, we found the SPEEDUP™ solutions to be in excellent agreement with the reference solutions. A minor peculiarity in dealing with a non-existent discontinuity in the OPERATION section of the model made itself evident.

The Point Kinetics Equations

The first step in qualifying SPEEDUP™ is to formally verify the correctness of its installation on the SRTC VAX computer cluster, and to demonstrate the accuracy of the code's differential-algebraic solver in computing known solutions. We already had in hand several benchmarks that have been used in the past to assess newly developed or acquired nuclear reactor kinetics codes, thus it proved convenient to run SPEEDUP™ against those well-known problems. The problems were implemented in the "artificial" chemical process context required by the software through defining the point reactor to be a "unit operation," with reactivity as the "input" to the process, and neutron density and precursor concentrations as the "product." This is probably the first such application of SPEEDUP™.

The neutron kinetics benchmarks consist of solutions of the nuclear reactor point kinetics problem, with one ordinary differential equation (ODE) representing the prompt neutron density, coupled to six other ODE's representing the delayed neutron precursor concentrations. In conventional notation, the point kinetics equations are:

$$dn/dt = [\rho(t) - B]n(t)/\Lambda + \sum_j \{\lambda_j C_j(t)\} \quad (1)$$

$$dC_j/dt = \beta_j n(t)/\Lambda - \lambda_j C_j(t) \quad \text{with } j=[1,6] \quad (2)$$

where: n = prompt neutron density
 C_j = delayed neutron precursor concentration in group j
 ρ = reactivity (the driving function), dimensionless
 β_j = delayed neutron fraction for group j
 $B = \sum_j \beta_j$
 λ_j = decay constant for group j , 1/sec
 Λ = neutron generation time, sec
 j = precursor group number ranging from 1 to 6

The mathematical stiffness of the above set of equations is determined by the kinetics parameters Λ and λ_j which vary over a wide range (see Table 1), especially for the benchmark problems characterizing a fast reactor.

Benchmark Specifications

The benchmark parameters taken from the Reference are summarized in Table 1. The five cases which constitute the benchmark problems are defined in Table 2. Each case consists of a selection of reactor type (thermal or fast) and then a definition of the reactivity driving function. The SPEEDUP™ problem file as run is reproduced in Attachment 1. Note that this is all that is required to fully specify the model: SPEEDUP™ *automatically and transparently* generates all the executable FORTRAN for the actual solution algorithms solely from this input. In addition, the different case variations were all implemented as distinct OPERATION sections, all of which are reproduced in Attachment 2.

Computed Results: Cases 1 - 4

The SPEEDUP™ results obtained in the present work are compared to the exact reference solutions in Table 3. Note that all the cases represent very rapid transients with significant changes in the "state" variables in a few seconds. In Cases 1 through 3, there is excellent agreement between the exact solutions and the SPEEDUP™ results: the fractional differences are of the order of 5×10^{-5} , about at the level of single precision machine round-off. In Case 4, which represents an almost pathological response of

the reactor, the fractional difference is still no worse than approximately 4×10^{-4} . For this case, the SPEEDUP™ calculation of the 1.05 sec datum (which was not presented in the benchmark solution) is given to demonstrate the exponentially growing character of the reactor response. Thus for all four of these benchmark cases, the SPEEDUP™ results are interpreted as essentially duplicating the reference exact solutions.

"Discontinuity" in OPERATION Section: Case 5

For Case 5, where the driving function is represented by a series of ramps, the agreement between SPEEDUP™ and the exact solution is somewhat worse, with a fractional error of the order of 1×10^{-3} . Several minor variants of the SPEEDUP™ problem were run to pin-point the source of the discrepancy, with the entire focus on characterizing the calculation of the first $t=0.5$ sec datum. In all the sub-cases, only the definition of "rho" in the OPERATION section (see Attachment 2) was changed. In Case 5A, the OPERATION section was set up with the initial reactivity ramp being sustained beyond 0.5 sec. In Case 5B, the initial ramp was unchanged, but a logical test was simply added at $t=0.5$ sec. And in Case 5C, the only change was to shift the logical test to $t=0.501$ sec. The results are illuminating:

	<u>Case 5 Variations</u>		
	<u>t = 0.5 sec</u>	<u>t = 0.8 sec</u>	<u>identifier</u>
exact solution	1.721422	n/a	"benchmark"
SPEEDUP™ Case 5	1.719811	n/a	"full case"
SPEEDUP™ Case 5A	1.721446	3.183210	"long ramp"
SPEEDUP™ Case 5B	1.719811	3.182703	"add IF test"
SPEEDUP™ Case 5C	1.721437	3.182697	"delay IF"

Case 5 which retains all the original reactivity ramps in the OPERATION section results in a fractional error of 9×10^{-4} at 0.5 sec. If we go to Case 5A which simply consists of an extension of the initial ramp beyond 0.5 sec, the fractional error at 0.5 sec drops to 1×10^{-5} , the level of round-off. Then in Case 5B, we simply insert the logical test at $t=0.5$ sec, but make the ramp unchanged no matter the outcome of the logical test so there is no actual discontinuity: this "degrades" the solution back to the original, larger discrepancy.

The reinitialization of the solution algorithm that SPEEDUP™ performs automatically at every point of "discontinuity" is clearly the cause for the difference. That is, SPEEDUP™ will integrate up to the point of an

explicit or implicit discontinuity (identified as the multiple possible outcomes of IF-THEN-ELSE tests), then "step over" the discontinuity by reinitializing the restart of the integration on the other side. Thus Case 5B inserts that possible (but non-existent) discontinuity at 0.5 sec, forcing a reinitialization.

If we shift the time of the logical test to $t=0.501$ sec as in Case 5C, the solution at 0.5 sec is restored back to essentially the reference value since now SPEEDUP™ does not perform the reinitialization at the time of interest. Clearly the presence of the logical test in the OPERATION section is changing the way the solution algorithm functions: the reinitialization, even in the absence of a "true" discontinuity, does not exactly reproduce the original algorithm.

The clearest comparison is between Cases 5A and 5B which should be computationally identical, but appear to be algorithmically different. Both represent the identical reactivity ramp, with only a logical test which does not change the actual definition of the ramp inserted in the "midst" of the ramping interval. If we continue the same ramp beyond $t=0.5$ sec (which the reference benchmark did not), there is still a clear difference in the $t=0.8$ sec values calculated by Cases 5A, 5B, and 5C. Thus the effect of the logical test and the ensuing reinitialization due to the OPERATION section is still evident beyond the time of the logical test.

Obviously, all these differences are quite minor and would be unnoticeable in a "real-life" simulation. The differences are noted here only because the current subject is numerical benchmarking.

Quality Assurance Archiving

In order to retain the specific SPEEDUP™ files describing these benchmarks in perpetuity in an unmodifiable form, said files have been stored in the Scientific Code Management System (SCMS). The save file contents duplicate electronically the material provided in Attachments 1 and 2 to this document.

Reference

J.A.W. da Nobrega, "A New Solution of the Point Kinetics Equations," Nuclear Science and Engineering: 46, 366-375 (1971).

Table 1. Benchmark Parameters

Precursor Group	Thermal Reactor		Fast Reactor	
	λ_j	β_j	λ_j	β_j
1	0.0127	2.850×10^{-4}	0.0129	1.672×10^{-4}
2	0.0317	1.5975×10^{-3}	0.0311	1.232×10^{-3}
3	0.115	1.410×10^{-3}	0.134	9.504×10^{-4}
4	0.311	3.0525×10^{-3}	0.331	1.443×10^{-3}
5	1.40	9.600×10^{-4}	1.26	4.534×10^{-4}
6	3.87	1.950×10^{-4}	3.21	1.540×10^{-4}
	B = 0.00750		B = 0.00440	
	$\Lambda = 5 \times 10^{-4}$ sec		$\Lambda = 1 \times 10^{-7}$ sec	

Table 2. Benchmark Cases

Case	Reactor Type	Reactivity Driving Function
1	fast reactor	$\rho(t) = 0.0022$, step of \$0.5 @ $t=0$
2	thermal reactor	$\rho(t) = -0.00375$, step of -\$0.5 @ $t=0$
3	thermal reactor	$\rho(t) = 0.0075$, step of \$1 @ $t=0$
4	fast reactor	$\rho(t) = 0.0044 \cdot t$, ramp of \$1/sec
5	thermal reactor	$\rho(t) =$ from $t=[0,0.5 \text{ sec}]$: $0.0075 \cdot t$, ramp of \$1/sec from $t=[0.5,1.0 \text{ sec}]$: $-0.0075 \cdot t$, ramp of -\$1/sec from $t=[1.0,1.5 \text{ sec}]$: $0.0075 \cdot t$, ramp of \$1/sec from $t=[1.5,10 \text{ sec}]$: 0.00375 , constant \$0.5

(Note that in standard reactor physics terminology, "\$1" of reactivity means a value of ρ equal to B, "\$0.5" means $\rho=B/2$, etc.)

Table 3. Comparison of SPEEDUP™ to Exact Solution

Prompt Neutron Density Values

Case 1

	<u>t = 0.1 sec</u>	<u>t = 1.0 sec</u>	<u>t = 10.0 sec</u>
exact soln	2.075317	2.655853	12.74654
SPEEDUP™	2.075315	2.655856	12.74667

Case 2

	<u>t = 0.1 sec</u>	<u>t = 1.0 sec</u>	<u>t = 10.0 sec</u>
exact soln	0.698925	0.607054	0.396078
SPEEDUP™	0.698893	0.607053	0.396076

Case 3

	<u>t = 0.1 sec</u>	<u>t = 0.5 sec</u>	<u>t = 1.0 sec</u>
exact soln	2.515766	10.36253	32.18354
SPEEDUP™	2.515853	10.36303	32.18540

Case 4

	<u>t = 0.5 sec</u>	<u>t = 1.0 sec</u>	<u>t = 1.05 sec</u>
exact soln	2.136407	1207.813	n/a
SPEEDUP™	2.136446	1208.307	5.479 x 10 ²⁷

Case 5

	<u>t = 0.5 sec</u>	<u>t = 1.0 sec</u>	<u>t = 1.5 sec</u>	<u>t = 2.0 sec</u>
exact soln	1.721422	1.211127	1.892226	2.521601
SPEEDUP™	1.719811	1.210937	1.890366	2.520794
	<u>t = 10.0 sec</u>			
exact soln	12.04711			
SPEEDUP™	12.04442			

- Notes:
1. initial value in all cases was 1.0.
 2. SPEEDUP™ runs were all performed with a report interval of 0.1 sec and sufficient reporting intervals to span the time range, with all options at their default settings.

Attachment 1. SPEEDUP™ Problem File

TITLE

Point Kinetics Benchmarks from da Nobrega (NS&E.V.46,p.366,'71)
M.V. Gregory, Westinghouse Savannah River Co., January 1993

OPTIONS

EXECUTION

Target = File
Printlevel = -1
External = OFF

DECLARE

TYPE

DENSITY = 1.0 :0.0 :1E37 UNIT = INV_CM3
DENPTIME = 1.0 :0.0 :1E37 UNIT = INV_CM3_SEC
INVTIME = 1.0 :0.0 :1E37 UNIT = INV_SEC
NOUNIT = 1.0 :0.0 :1E37 UNIT = NONE

STREAM MAINSTREAM

SET

NGRP = 6

TYPE

DENSITY, DENSITY(NGRP)

MODEL POINT_REACTOR

#Implementation of da Nobrega neutron point kinetics benchmarks#
#M.V. Gregory, Westinghouse Savannah River Co., January 1993#

SET

ngrp

TYPE

neutron_density, ndummy AS DENSITY
precursor_density, pdummy AS ARRAY (ngrp) OF DENSITY
prec_product AS ARRAY (ngrp) OF DENPTIME
beta AS ARRAY (ngrp) OF NOUNIT
decay AS ARRAY (ngrp) OF INVTIME
rho, betasum, jdum, ncase AS NOUNIT
lambda AS TIME

STREAM

OUTPUT IS ndummy, pdummy

EQUATION

```
prec_product(1:ngrp) = decay(1:ngrp) * precursor_density(1:ngrp);
$neutron_density = (rho-betasum) * neutron_density / lambda +
                    sigma(prec_product);
$precursor_density(1:ngrp) = beta(1:ngrp)*neutron_density/lambda
                    - prec_product(1:ngrp);
# need dummy variables since stream can not pass state variables #
ndummy = neutron_density;
pdummy(1:ngrp) = precursor_density(1:ngrp);
jdum = ncase
```

```
****
FLowsheet

STREAM phony OUTPUT OF reactor IS PRODUCT
****

UNIT reactor IS A point_reactor
SET
    # specify number of delayed neutron precursor groups #
    ngrp = 6
****

OPERATION

# set up of da Nobrega case data #
# case number 1 #

SET
    WITHIN reactor

    ncase =          1,

                        # model constants for each case #
                        # fast reactor data #

    decay =          <0.0129,0.0311,0.134,0.331,1.26,3.21> ,

    beta =           <1.672e-4,1.232e-3,9.504e-4,1.443e-3,4.534e-4,1.54e-4> ,

    betasum =         0.0044 ,

    lambda =          1.0e-7 ,

                        # reactivity input for each case #

    rho = betasum/2.0

INITIAL
    WITHIN reactor
        neutron_density = 1.0 ,
        precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,
        precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,
        precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,
        precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,
        precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,
        precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))
****

EXTERNAL

TRANSMIT
    reactor.neutron_density      IS "zdens"
    reactor.precursor_density(1) IS "pdens1"
    reactor.precursor_density(2) IS "pdens2"
    reactor.precursor_density(3) IS "pdens3"
    reactor.precursor_density(4) IS "pdens4"
    reactor.precursor_density(5) IS "pdens5"
    reactor.precursor_density(6) IS "pdens6"
```

RECEIVE
reactor.rho IS "react"
reactor.lambda IS "plifet"

REPORT output_nobrega

FIELDS

&10 = reactor.jdum;
&20 = t;
&25 = reactor.rho;
&30 = reactor.neutron_density;
&40 = reactor.precursor_density(1);
 &50 = reactor.precursor_density(2);
 &60 = reactor.precursor_density(3);
 &70 = reactor.precursor_density(4);
 &80 = reactor.precursor_density(5);
 &90 = reactor.precursor_density(6);

FIELDMARK ?

DISPLAY

Results for da Nobrega Benchmark -----> Case Number : ????????

At time : ??????????? sec

Reactivity : ?????????????????????????????

Neutron density : ?????????????????? per cm³

Precursor densities:

group 1 ----> : ??????????? per cm³
group 2 ----> : ??????????? per cm³
group 3 ----> : ??????????? per cm³
group 4 ----> : ??????????? per cm³
group 5 ----> : ??????????? per cm³
group 6 ----> : ??????????? per cm³

Attachment 2. OPERATION Sections for Various Cases

OPERATION

```
# set up of da Nobrega case data #  
# case number 1 #
```

SET

WITHIN reactor

ncase = 1,

```
# model constants for each case #  
# fast reactor data #
```

decay = <0.0129,0.0311,0.134,0.331,1.26,3.21> ,

beta = <1.672e-4,1.232e-3,9.504e-4,1.443e-3,4.534e-4,1.54e-4> ,

betasum = 0.0044 ,

lambda = 1.0e-7 ,

```
# reactivity input for each case #
```

rho = betasum/2.0

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6)) ,

OPERATION

```
# set up of da Nobrega case data #  
# case number 2 #
```

SET

WITHIN reactor

ncase = 2,

```
# model constants for each case #  
# thermal reactor data #
```

decay = <0.0127,0.0317,0.115,0.311,1.4,3.87> ,

beta = <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,

betasum = 0.0075 ,

lambda = 5.0e-4 ,

```
# reactivity input for each case #
```

rho = -betasum/2.0

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))

OPERATION

```
# set up of da Nobrega case data #  
# case number 3 #
```

SET

WITHIN reactor

```
ncase =          3,
```

```
          # model constants for each case #  
          # thermal reactor data #
```

```
decay =          <0.0127,0.0317,0.115,0.311,1.4,3.87> ,
```

```
beta =          <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,
```

```
betasum =        0.0075 ,
```

```
lambda =         5.0e-4 ,
```

```
          # reactivity input for each case #
```

```
rho = betasum
```

INITIAL

WITHIN reactor

```
neutron_density = 1.0 ,
```

```
precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,
```

```
precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,
```

```
precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,
```

```
precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,
```

```
precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,
```

```
precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))
```

```
****
```

OPERATION

```
# set up of da Nobrega case data #  
# case number 4 #
```

SET

WITHIN reactor

ncase = 4,

model constants for each case #
fast reactor data

decay = <0.0129,0.0311,0.134,0.331,1.26,3.21> ,

beta = <1.672e-4,1.232e-3,9.504e-4,1.443e-3,4.534e-4,1.54e-4> ,

betasum = 0.0044 ,

lambda = 1.0e-7 ,

reactivity input for each case

rho = betasum*T

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))

OPERATION

```
# set up of da Nobrega case data #  
# case number 5 #
```

SET

WITHIN reactor

ncase = 5,

```
# model constants for each case #  
# thermal reactor data #
```

decay = <0.0127,0.0317,0.115,0.311,1.4,3.87> ,

beta = <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,

betasum = 0.0075 ,

lambda = 5.0e-4 ,

```
# reactivity input for each case #
```

rho = IF T <= 0.5 THEN

betasum*T

ELSE IF T <= 1.0 THEN

betasum/2.0 - betasum*(T-0.5)

ELSE IF T <= 1.5 THEN

betasum*(T-1.0)

ELSE

betasum/2.0

ENDIF

ENDIF

ENDIF

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))

OPERATION

set up of da Nobrega case data #
case number "5A": isolated just initial ramp

SET

WITHIN reactor

ncase = 5,

model constants for each case #
thermal reactor data

decay = <0.0127,0.0317,0.115,0.311,1.4,3.87> ,

beta = <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,

betasum = 0.0075 ,

lambda = 5.0e-4 ,

reactivity input for each case

rho = betasum*T

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))

OPERATION

set up of da Nobrega case data #
case number "5B": extend initial ramp

SET

WITHIN reactor

ncase = 5,

model constants for each case #
thermal reactor data

decay = <0.0127,0.0317,0.115,0.311,1.4,3.87> ,

beta = <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,

betasum = 0.0075 ,

lambda = 5.0e-4 ,

reactivity input for each case

rho = IF T <= 0.5 THEN

betasum*T

ELSE

betasum*T

ENDIF

INITIAL

WITHIN reactor

neutron_density = 1.0 ,

precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,

precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,

precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,

precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,

precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,

precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))

OPERATION

```
# set up of da Nobrega case data #  
# case number "5C": extend initial ramp, modify time discriminator #
```

SET

WITHIN reactor

```
ncase =          5,  
  
          # model constants for each case #  
          # thermal reactor data #  
  
decay =          <0.0127,0.0317,0.115,0.311,1.4,3.87> ,  
  
beta =           <2.85e-4,1.5975e-3,1.41e-3,3.0525e-3,9.6e-4,1.95e-4> ,  
  
betasum =        0.0075 ,  
  
lambda =         5.0e-4 ,  
  
          # reactivity input for each case #  
  
rho = IF T <= 0.501 THEN  
          betasum*T  
      ELSE  
          betasum*T  
      ENDIF
```

INITIAL

WITHIN reactor

```
neutron_density = 1.0 ,  
precursor_density(1) = beta(1) * neutron_density / (lambda * decay(1)) ,  
precursor_density(2) = beta(2) * neutron_density / (lambda * decay(2)) ,  
precursor_density(3) = beta(3) * neutron_density / (lambda * decay(3)) ,  
precursor_density(4) = beta(4) * neutron_density / (lambda * decay(4)) ,  
precursor_density(5) = beta(5) * neutron_density / (lambda * decay(5)) ,  
precursor_density(6) = beta(6) * neutron_density / (lambda * decay(6))  
****
```

END

**DATE
FILMED**

6 / 17 / 93