DOE/BC/14958--71

QUARTERLY TECHNICAL PROGRESS REPORT
GREEN RIVER FORMATION WATER FLOOD DEMONSTRATION PROJECT, UINTA BASIN, UTAH

~~DE-PS22-92BC14804~~

FC 22-93 BC 14958

Lomax Exploration Company
Salt Lake City, Utah

DOE/BC/14958--T1

Award Date: October 21, 1992
Anticipated Completion: October 1, 1995

DE93 010072

Program Manager:
Bill I. Pennington, Lomax Exploration Company

Principal Investigators:
John D. Lomax, Lomax Exploration Company
Dennis L. Nielson, University of Utah Research Institute
Milind D. Deo, Department of Chemical and Fuels Engineering, University of Utah

Technical Project Officer:
Edith Allison, Bartlesville Project Office

Reporting Period: October 21 - December 31, 1992

OBJECTIVE

The Green River Formation of the Uinta Basin, Utah, contains abundant hydrocarbons that are inefficiently produced by primary means. However, secondary recovery projects have only been rarely implemented, largely because of complex geology and hydrocarbon chemistry. An evaluation of the successful Lomax Monument Butte Unit water flood will be performed under this contract, and based on this information, water floods will be initiated in nearby Travis and Boundary units. The project will also develop new techniques to characterize reservoir heterogeneity and the response of the reservoir to water flooding.

In 1987, Lomax Exploration Company successfully implemented a water flood on their Monument Butte Unit which has a geologically heterogeneous low energy reservoir with a high paraffin crude oil. Production of about 5% of the OOIP from primary methods was increased through the water flood to an estimated recovery of 20% OOIP. The project will: 1) perform a technical evaluation of the successful Monument Butte Unit; 2) based on this information, extend the successful water flood to nearby Travis and Boundary units; 3) develop new characterization techniques and 4) transfer the technology to operators, regulators, government agencies, and the financial community.

SUMMARY OF TECHNICAL PROGRESS

The Monument Butte #10-34 was spud on 10/2/92 and drilled to a depth of 6400'. On the 38th day after the spud date, logging of the #10-34 was started. Based on the results of logging, 5 1/2" casing was cemented in the hole. As of 11/24/92, the #10-34 has been completed. Our objective was to complete in the Castle Peak, Black Shale, "A" and the "D" intervals of the Green River Formation. All four intervals have been perforated and fractured. From 11/27 through 1/27/93, oil production has been 3,393 barrels (54 barrels per day).

MASTER

EP

DISSEMINATION OF THIS DOCUMENT IS UNRESTRICTED

The Travis #14a-28 was spud on 10/6/92 and drilled to a depth of 6190'. On the 20th day after the spud date, logging of the #14a-28 was started. Based on the results of the logging and coring, 5 1/2" casing was cemented in the hole. We have completed in the Lower Douglas Creek and the "D" intervals of the Green River Formation. However, due to the fracturing of the Lower Douglas Creek, only the "D" sand interval was put on production. From 1/1/93 through 1/28/93, the #14a-28 has produced 2,947 barrels of oil (105 barrels per day) and 1.9 Mcf of gas (107 Mcf per day) from the "D" sand interval. Due to the success of the "D" sand, other Travis unit wells with "D" sand intervals behind pipe will be recompleted. Further study of the Lower Douglas Creek interval will be done before an attempt to put the interval on production.

A full-diameter core was taken in the upper portion of the Lower Douglas Creek in Travis #14a-28. This core has been logged in detail and five plugs have been analyzed using thin-sections and X-ray diffraction. Horizontal and vertical permeability, porosity, oil and water saturation and grain density have been determined on the same plugs. The sandstone units are composed of packages of planar-laminated fine-grained sandstone that exhibit varying degrees of dewatering and soft-sediment deformation. These are separated by either slightly disrupted siltstone or massive very fine-grained sandstone with abundant clasts. The planar-laminated sandstones occur in 15-foot thick packages with an intraclast-rich base and a dewatered top, and are interpreted as moderate- to low-density turbidite channels.

The strongest oil shows are in planar-laminated sandstone. The rocks are cemented largely with calcite and dolomite. Late, secondary porosity was formed through dissolution of feldspar. Most of the clay in the planar-laminated sandstone is non-swelling illite and chlorite.

The DOE program has allowed Lomax Exploration to utilize state-of-the-art methods to evaluate the geological processes that influence the water flood. The Schlumberger Fullbore Formation MicroImager ("FMI") and the Numar's Magnetic Resonance Imaging Log ("MRIL") were used in the evaluation of the Monument Butte #10-34 and Travis #14a-28 wells.

The Schlumberger FMI was used to evaluate the stratigraphic sequences of interest to develop a better understanding of the stratigraphy and depositional environment of potential reservoir beds. This log is also valuable in locating fractures along with determining the orientation and size of the fractures. Fractures were found in areas where they had not previously been detected. This information is critical to selecting completion intervals and designing stimulation treatments. The FMI log is also very useful for thin bed evaluation, and for locating the best places to take rotary sidewall cores. A large amount of fracturing was seen in the Travis #14a-28 well using this log. The fractures normally occur in the sandstone units and are bounded by shales. A histogram of 18 fractures shows an orientation from E-W to WNW-SES, parallel the trend of the Duchesne fault system (Fig. 1). From inspection of the core, it was found that the fractures were developed both during soft sediment deformation and dewatering and by later tectonic activity. Initial analysis of bedding orientation suggests that the turbidite sequences and slumping that are well exposed in the core were derived from the northwest of the well.

The second advanced research log that we have used is Numar's MRIL. This log was used to evaluate the movable fluid content of the reservoir rock, and to determine the effective permeability within the reservoir. At least one zone that by sample and core analysis appeared to be non-commercial in the Monument Butte #10-34 well, was indicated by the MRIL to have movable hydrocarbons. Subsequent completion has established commercial production.

In the Monument Butte Unit, an average well has approximately twenty sands with production potential. Ten sands will usually be eliminated as being too discontinuous or too thin. The ten remaining sands have to be evaluated with regard to their relative permeability. The evaluation of effective permeability has been most difficult information to obtain, and yet it is critical to making a commercial completion. Early indications are that prudent use of these new logs may enhance completion practices and reduce the cost of well completions.

Gas analyses have been completed on the wells sampled (Table 1). There were no significant composition differences between the two gas samples. Both gas samples consisted of approximately 50 weight percent methane, 20 percent each of ethane and propane and 10 percent heavier hydrocarbons and non hydrocarbons (71 mol% methane, 13 ethane, 9 propane and 7 other).

Approximately 30 weight percent of material boils above 1000°F. The high-boiling fractions will not pass through the gas chromatograph during standard operations, and are retained in the injection port and column. This accumulated material breaks down during later runs and makes it impossible to interpret the results. This problem is solved by "conditioning" the injection port and the gas chromatograph column after each test. This is done by increasing the injection port temperature to 750°F and by keeping the oven temperature at 600°F for 80 minutes. This drives the contaminants off and allows further tests.

The amount of high-boiling material in the samples was determined using a modification of ASTM Standard Method D2887. Running successive samples of the same crude oil, with second sample mixed with a known amount of a standard material, allows the amount of high-boiling material in the sample to be calculated. The modified test method was found to be quite reproducible. See Figure 2 for a comparison of the three crude oil compositions.

The #10-35 well crude has a slightly heavier material. The fact that #10-35 delivers oil from the B and D zones compared to the #12-35 only delivering from the D zone, suggests that the B zone is a somewhat heavier oil.

REFERENCES/PUBLICATIONS

"Waterflood Project in the Monument Butte Field, Uinta Basin" presented by John Lomax, Annual meeting of the Interstate Oil and Gas Compact Commission, December 6-8, 1992, Salt Lake City, Utah

WELL GAS ANALYSES
Monument Butte Unit Wells.

Mass fraction of gas components

<u>Component</u>	<u>Well 10-35</u> <u>B and D-1 Sands</u>	<u>Well 12-35</u> <u>D-1 Sands</u>
methane	51.44%	54.85%
ethane	19.42	17.35
propane	19.84	16.33
isobutane	0.92	0.66
n-butane	6.18	5.52
isopentane	0.34	1.79
n-pentane	0.90	2.17
hexanes	0.97	1.31

TABLE 1

FIGURE 1

FRACTURE ORIENTATION AS DETERMINED FROM FMI
LOG OF TRAVIS # 14A-28.

FIGURE 2

END

DATE
FILMED

4 / 15 / 93