2 :
DOE/PC/91310--4

DE93 004923

**THE USE OF SOLID-STATE NMR TECHNIQUES FOR THE ANALYSIS OF
WATER IN COAL AND THE EFFECT OF DIFFERENT COAL DRYING
TECHNIQUES ON THE STRUCTURE AND REACTIVITY OF COAL**

by
Daniel A. Netzel

Quarterly Report: June 1, 1992 - August 31, 1992

Work Performed Under Grant Agreement
DE-FG22-91PC91310

For
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236-0940

By
University of Wyoming Research Corporation
a.k.a. Western Research Institute
Laramie, Wyoming

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED Sp

THE USE OF SOLID-STATE NMR TECHNIQUES FOR THE ANALYSIS OF
WATER IN COAL AND THE EFFECT OF DIFFERENT COAL DRYING
TECHNIQUES ON THE STRUCTURE AND REACTIVITY OF COAL

by
Daniel A. Netzel

Quarterly Report: June 1, 1992 - August 31, 1992

Work Performed Under Grant Agreement
DE-FG22-91PC91310

For
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236-0940

By
University of Wyoming Research Corporation
a.k.a. Western Research Institute
Laramie, Wyoming

U.S. DOE Patent Clearance is not Required Prior to the Publication of
this Document

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES.....	iii
INTRODUCTION.....	1
OBJECTIVES.....	1
EXPERIMENTAL.....	2
RESULTS AND DISCUSSION.....	3
CONCLUSIONS AND FUTURE WORK.....	4

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Weight Percent Water in Coal as a Function of the Reaction Time.....	5

INTRODUCTION

One area for improvement in the economics of coal liquefaction is coal drying, particularly for the lower rank coals. However, there is considerable evidence to show that drying has a detrimental effect on the liquefaction behavior of coals. Regarding the liquefaction of coal, there does not appear to have been any systematic study of the methods of coal drying on coal structure and the role water plays in enhancing or lessening coal reactivity toward liquefaction. In part, this may have been the result of not having the techniques that are now available, such as solid-state nuclear magnetic resonance (NMR) spectroscopy.

OBJECTIVES

The overall objectives of this study are to develop an NMR method for measuring the water in coal, to measure the changes in coal structure that occur during coal drying, to determine what effect water has on retrograde/condensation reactions, and to determine the mechanism by which water may enhance coal reactivity toward liquefaction. Different methods of drying will be investigated to determine if drying can be accomplished without destroying coal reactivity toward liquefaction, thereby making coal drying an attractive and economical method for coal pretreatment.

The objectives for this quarterly report period were (1) to determine the moisture content by ^1H NMR of Eagle Butte and Usebelli subbituminous coals and (2) to conduct microwave drying experiments.

EXPERIMENTAL

The moisture contents of Eagle Butte and Usebelli coals were determined using the ^1H NMR methodology described in the previous reports but modified to measure the change in moisture content as a function of time. The modification is as follows: one-half gram of coal was weighed into a 10 ml centrifuge tube followed by 2 ml of 0.2 N $\text{CH}_3\text{SO}_3\text{H}$ in CH_3OH and 1 ml of the reference standard cycloheptane. To this mixture was added 4 ml of dimethoxypropane. The total mixture was stirred and then centrifuged for 10 minutes. At 2, 4, 6, and 8 hours, one-half milliliter aliquots of the solution were removed, diluted with one-half milliliters of CDCl_3 and the ^1H NMR spectrum recorded. Prior to removing each aliquot, the solution was stirred and centrifuged.

Microwave drying experiments using a CEM model MDS 81-D laboratory microwave oven were conducted on the Eagle Butte coal. The microwave power was calibrated at 10% power intervals using a 1-kg sample of water. The data from two calibration runs of microwave power versus microwave power setting show good repeatability although there is some deviation at the higher power setting. This deviation will not affect the microwave coal drying tests which are conducted at lower power levels.

RESULTS AND DISCUSSION

The results of measuring the change in moisture content of the Eagle Butte and Usebelli coals as a function of time are shown in Figure 1. As expected, the measured moisture content increases with time and reaches a maximum after about 8 hours. Two different types of sorbed water are removed sequentially. Free or surface sorbed water is rapidly removed followed by the water in the micropores of the coal as the reagents migrate into the pore structure.

There appears to be an induction period of about 4 hours for the Eagle Butte coal before the moisture content increases more rapidly with time due to the reactions of the more "tightly bound or "pore" water with the reagents. Hopefully, this observation will be confirmed in later experiments.

The chemical drying experiment was repeated twice for the Usebelli coal. In the first experiment, aliquots of the reaction mixture were removed sequentially, and in the second experiment separate coal samples were prepared and allowed to stand until the appropriate time for the NMR spectrum to be acquired. Excellent reproducibility was obtained.

Both coals were thermally dried by heating to 110°C for 1 hour. The moisture content was determined by weight loss. Using the thermal drying method, the Eagle Butte coal had a moisture content of 16.6 wt % and the Usebelli coal a moisture content of 14.1 wt %. These values are near the moisture content of coal as determined by chemical drying.

Preliminary experiments using microwave energy to dry the Eagle Butte coal gave a moisture content ranging from 18 to 22 wt %.

CONCLUSIONS AND FUTURE WORK

The methodology for measuring the moisture in coal by chemical drying has been successful for both the Eagle Butte and Usebelli (Alaskan) coals. It is anticipated that the water content in Argonne coal samples will be determined during the next quarterly report period.

Also during the next quarterly report period, the methodology for microwave drying of coal should be nearly completed.

WRI has recently acquired a "Borgialli" microreactor from the Wilsonville Two-Stage Advanced Coal Liquefaction Research Facility for the liquefaction experiments on the dried coals. It is anticipated that preliminary experiments in coal liquefaction will be conducted near the end of the next reporting period.

Figure 1. Weight Percent Water in Coal As a Function of the Reaction Time

**DATE
FILMED**

1 / 12 / 93