DOE/PC/89-

DOE/PC/89764--T7

DE92 019735

May 3, 1990

RE: DOE-PETC Grant No. DE-FG22-89PC89764,
"Permeability Changes in Coal Resulting from Gas Desorption"
2 years: August 16, 1989 - August 15, 1991
Principal Investigator: Jeffrey R. Levine
Co-Principal Investigator: Frank Tsay
Participating Faculty: Duk-Won Park

SECOND QUARTERLY REPORT: 11/15/89 - 2/15/89
90

Copy 1 of 7:

Sayeed Akhtar
PM-40, MS922-206
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

✓ Copy 2 of 7:

Cynthia Y. Mitchell
Contract Specialist
AD-22, 921-165
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Copy 3 of 7:

Kay Downey
Office of Technology Transfer
Mail Stop 58-M217
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

Copy 4 of 7:

Johnny M. Rogers, Director
Office for Sponsored Programs
The University of Alabama
Box 870104
Tuscaloosa, Alabama 35487-0104

Copy 5 of 7:

Jeffrey R. Levine
Department of Geology
The University of Alabama
P.O. Box 1945
Tuscaloosa, Alabama 35487

Copy 6 of 7:

Frank M. Tsay
Department of Mineral Engineering
The University of Alabama
P.O. Box 870207
Tuscaloosa, Alabama 35487-0207

Copy 7 of 7:

Duk-Won Park
Department of Mineral Engineering
The University of Alabama
P.O. Box 870207
Tuscaloosa, Alabama 35487-0207

MASTER
db

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

12

"Permeability Changes in Coal Resulting from Gas Desorption"

Quarterly Report:

11/15/89 - 2/15/90

PROJECT OBJECTIVES

To test the hypothesis that the desorption of gases (particularly methane) from coal results in shrinkage of the coal matrix, bringing about a net increase in permeability.

This project has been subdivided into 5 component tasks:

- 1) Sample Collection, Specimen Preparation, and Compositional Characterization
- 2) Physical Strength Testing
- 3) Determination of Sorption/Desorption Isotherms
- 4) Experimental Measurement of Swelling and Shrinkage of Coal Specimens during Sorption and Desorption
- 5) Experimental Measurement of Changes in Permeability to Gas Flow during Sorption and Desorption

MAJOR ACCOMPLISHMENTS,

Task 1 (Sampling, Specimen Preparation, Characterization):

(No work performed during this period.)

Major Accomplishments, Task 2 :

(No work performed during this period.)

Major Accomplishments, Task 3 (Sorption Isotherms):

Measurement of sorption capacity of coals by microbalance in a high pressure environment requires that corrections be made for the buoyancy of the gas that is displaced by the solid coal. As the pressure increases, the gas density increases, requiring that a correction factor be applied to the weight of the sample as measured by microbalance. A brief report summarizing this correction is attached as Appendix A.

Major Accomplishments, Task 4 (Measurement of Swelling and Shrinkage):

A brief report summarizing activities in this area is attached as Appendix B.

Major Accomplishments, Task 5 (Permeability Testing):

A brief report summarizing activities in this area is attached as Appendix C.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Corrections for a High Pressure Thermobalance for Coal Sorption Experiments

by
Charles Hager

Summary

High pressure thermobalances have been developed over the past two decades to study the weight change in high temperature and high pressure reactions. These balances use flowing gases to for continuous reaction, temperatures up to 1,100 degrees C, and pressures up to 500 atmospheres (7,500 psi). While the majority of literature is written on using the thermobalance under such extreme conditions, the conditions for coal experiments are not so severe. The temperature of sorption will be limited to 50 degrees C and 1000 psi. Furthermore, there will not be any flowing gas and the system will be in static equilibrium as much as possible.

Experimental Procedure

Convection Problems

One of the biggest problems encountered with high pressure thermobalances, is convection currents. Convection currents occur because of a temperature difference within the high pressure cell. In low temperature experiments, a bath of liquid nitrogen is usually placed beneath the coal sample. The cold nitrogen causes convection currents with the room temperature gas which is injected into the pressure cell. As the gases convect, the moving gases create additional forces upon the sample pan which alter its weight. In addition, the higher the pressure in the cell, the greater the weight fluctuations. On the other hand, a reaction is often needed to be performed at a very high temperature (1,100 degrees C) with the use of a thermocouple. Again, the higher temperature zone at the reaction will cause convection currents with the room temperature gas.

For the sorption studies of coal, the complete system will be isothermally maintained to eliminate any convection currents. To do this, a large insulated box was constructed to house the entire experiment. The box is heated with infrared light bulbs and maintained with a power controlling thermocouple. The only convection problem which I can possibly predict occurring would be from the inlet gas. If there is any gas leak, the regulator on the gas tank will inject more gas into the pressure cell to maintain the pressure. This gas will be at room temperature (22 degrees C) and enter into a 50 degrees C cell. If this problem occurs, I would suggest investigating the safety of placing the tank of gas into the isothermal box to completely maintain the temperature of all the gases. Other than this previous discussion, there should not be any convection currents. On additional correction method is to insert 1/8" Vycor cylinders into the pressure cell to act as baffles and to dampen any gas velocities.

To disturb the system as little as possible, the gas inlet port should be as ^{small (in diameter)} as possible. For coal experiments, I suggest no larger than 1/8" tubing for the inlet gas. In addition, a metal plate should be affixed to the covering of the opening to stop the inlet gas from entering and traveling to the middle of the pressure cell. The damper serves to slow the entering velocity of the inlet gas and diverts its path to the edges (See Fig. 1).

B uoyancy Correction

The next major focus for correction is buoyancy. As the gas pressure increases, buoyancy forces can substantially alter the observed weight of the coal sample. Furthermore, there are two buoyancy corrections which need to be done separately and for each different gas.

Volume of the balance arms

The first buoyancy correction is for the difference in the volumes of the balance arms. To explain the theory, let look at the equation for an ideal gas.

$$P \cdot V = n \cdot R \cdot T$$

$$n = \text{MASS} / M$$

$$\text{Mass} = M \cdot P \cdot V / (R \cdot T)$$

Assuming a constant temperature, and molecular weight, the equation becomes:

$$\Delta \text{Mass} = M \cdot P \cdot \Delta V / (R \cdot T)$$

Where:

ΔMass = change in observed mass

M = molecular weight of gas

P = gas pressure

ΔV = difference in volume of sample arms

R = constant

T = temperature of system

n = number of moles of gas

This equation can be used for the determination of the volumetric difference in the two arms. Determining the volumetric difference is extremely important for one main reason. As the pressure increases, the buoyancy factor of the arms will alter the observed weight.

To perform the experiment, attach the sample pan to the microbalance and tare it to zero. Pressurize the system without anything in the sample pan. Record the change in mass for the given pressure. Also, note the temperature and molecular weight of the gas. For example, if there is a 8.4 mg change @ 25 degrees C in 135 atmospheres of Nitrogen, the difference in the volumes of the arms is .053 ml. Depending on which arm has more volume, the change in mass will be positive or negative. If the sample pan arm has more volume, the weight will decrease, but if the weight increases, the volume of the other arm is larger. Therefore, this should be a linear correction with pressure and subtracted from the results.

Sample Buoyancy

The second correction is for the decrease in weight as a result of the sample buoyancy. As the gas pressure is increased, the buoyancy force will increase, creating a greater error in weighing. The most basic form of correction is to use the formula:

$$\Delta W = V_s \Delta \rho_g$$

W = change in weight

V_s = volume of sample

$\Delta \rho_g$ = change in density of gas

However, the volume of a sample is very difficult to determine without altering it. Therefore, I would like to propose a new method for buoyancy correction for the coal sample which seems much more efficient.

Begin with 20 gram samples of coal and weigh each sample separately. Secondly, into a volume of water, add a sample of coal in the water and weigh the sample suspended in the water. This change in weight in water can be used to determine the volume of coal. Finally, using the weight before it is in the water, the density of coal can be determined. Take an average of the samples for a more accurate answer. The proof is given as follows:

Weight in air = Vol. Coal * Density Coal -- Vol. Coal * Density of Air

Weight in water = (Vol. Coal * Den. Coal) -- (Vol. Coal * Den. Water)

Weight in air -- Weight in water = (Volume Coal * Density Water) -- (Vol. Coal * Density Air)
= Volume Coal * (Density Water -- Density Air)

To determine the density of water, refer to Table 3-28 which can be found at the end. Read the first two significant figures down and the third across. The density of water @ 25.1 C is 997.019 kg/m³.

To determine the density of air, begin with the standard density of air at 0 degrees C and 1 atm, and the density of dry air is 1.2928 gm/l (or .0808 lb/ft³). Apply the ideal gas law $PV=nRT$ to correct for temperature and pressure. Finally enter the psychrometric chart Fig. 20-11 to correct for humidity. The room temperature is the Dry bulb temperature and go straight up to cross the appropriate relative humidity. Finally, travel to the right to determine the moisture content in kg water/ kg air. This value can be used to correct the density assuming 1 liter of air in the calculation. A sample calculation follows:

After applying PVT correction, an air sample is .0013 kg/l (1.3 g/l) and the relative humidity is 70% @ a temperature of 20 degrees C.

Entering Fig. 20-11 the moisture content is .01 kg water / kg dry air

The moisture content is then:

$$.01 \text{ kgW/kgAir} * .0013 \text{ kgAir/L} = .000013 \text{ kgW/L}$$

Therefore the total density is:

$$.0013 \text{ kgAir/L} + .000013 \text{ kgW/L} = .001313 \text{ kg/L}$$

Finally, the Density of Coal = Weight in air / Volume of Coal

Remember to average the sample densities. I suggest using a sample pan which hangs down to allow the coal sample to be immersed in water. Again, take the buoyancy factor of the sample pan into account when it is lowered into the water. To determine the buoyancy factor of the sample pan, weigh the pan in and out of the water and apply the formula

Weight in air -- Weight in water = Volume Pan * (Density Water -- Density Air)

Note the given moisture of the sample density because the moisture content can change the density of the sample. As a close approximation, for a 1% change in moisture, there is a 1% change in density.

With the coal density, a much simpler correction can be performed for buoyancy. When using in an isothermal system, the following formula will apply:

$$\text{real } \Delta W = (1 + (\rho_g / \rho_c)) * \text{apparent } \Delta W$$

real ΔW = real weight change
 apparent ΔW = apparent weight change
 ρ_g = gas density at new pressure
 ρ_c = coal density (calculated above)

This equation is found in the article "Modification of a Thermobalance for High Pressure Process Studies by Dobner, Samuel, et. al. page 15. There should not be a negative weight change, because during a sorption process the weight is always increasing; however, if there is a decrease in density, try using the simplified buoyancy formula $W = Vc * \rho_g$.

Looking at the equation, the apparent weight change is always multiplied by a number greater than 1. Furthermore, as the pressure increases, the gas density increases for a constant coal density. This makes the correction factor increase with increasing pressure, as would be expected. Therefore, I suggest that this formula be used for sample buoyancy correction after the microbalance arm correction is made. There is no need for using a gas which will not react with the coal to generate a buoyancy curve, thereby eliminating an extra step and we are still using a completely theoretical method of correction.

Calibration

The calibration of the microbalance was briefly discussed in one article. The sample pan should be tared by the addition of counterbalance weights. Fractional analytical weights are put into the sample pan to calibrate. The voltage output is adjusted by the span calibration and scale expansion controls. A chart recorder should be hooked up to observe weight changes. The chart paper can be read at +/- .1 divisions, which is approximately +/- .02mg.

Grain Size

One article (Apparatus for the Determination of Methane Sorption on Coal at High Pressures by a Weighing Method by Daines, M.E., pg. 317) discussed the grain size to be used in the sample pan. The article stated that the coal grains should be less than 210 micron size particles (<72 BSS Mesh). Particles which are larger than this have an equilibrium time which is too long for this experiment.

Pressurization

The gas pressure should also always be increased instead of decreased. Water vapors and possibly coal grains can escape if gas is released. It is believed that the pressure should be increased and equilibrium weight observed and then increasing the pressure again. This method will prevent any factor from leaving the system, such as water vapors.

Vacuum Pump

A vacuum pump is going to be attached to evacuate the cell before gas is injected. A vacuum should not be applied more than 2-3 minutes to avoid stripping moisture away from the coal (Daines, M.E., pg. 319). This is a very good point since moisture amount can greatly alter results. Furthermore, salt solutions will be used to regulate the relative humidity of the sample chamber. The solution can either be placed in the bottom of the hangdown tube or in a pan sitting on the microbalance. I would suggest pouring the solution into the hangdown tube to keep any threat of harming the microbalance to a minimum.

Converting gas to STP

The final topic of discussion is the conversion of weight changes. After buoyancy corrections, the increased weight can be attributed to sorption of gas. At each pressure, the weight of gas sorbed should be converted to volumes of gas at STP. This volume of gas should then be divided by the sample weight to give a volume sorbed per unit mass of coal. This will allow comparisons between coal samples and different experiments.

On final correction for converting gas to STP from high pressure is the use of Z factors. The Z factor is used to convert the property of an ideal gas to a real gas. The ideal gas formula is changed as follows:

$$P*V = n*R*T \quad (\text{ideal gas})$$

$$P*V = Z*n*R*T \quad (\text{real gas})$$

To find the Z factor for a given gas, use the provided critical Temp. and critical Pressure constants (T_c and P_c). Divide the present temperature and pressure by the respective critical values. This gives the reduced temperature and pressure (T_r and P_r). Go into Fig. 2-7 and determine the Z factor. Without using Z factors the experiment's range of pressures and temperatures, there will be up to 11% error. Critical constants and the Z factor graph (Fig. 2-7) are included.

Carbon Dioxide: $T_c=547.9 \text{ R}$ $P_c=1071 \text{ psia}$

Nitrogen: $T_c=227.6 \text{ R}$ $P_c=493 \text{ psia}$

Methane: $T_c=343.4 \text{ R}$ $P_c=667.8 \text{ psia}$

For example, Methane at 1000 psia and 560 degrees R has a $T_r=1.63$ and $P_r=1.5$. Going into the chart, the Z factor = .91. This is a substantial difference from ideal gas behavior.

Note: Degrees R (Rankin)=Degrees Fahrenheit + 460

Discussion of Weight

Gas which occupies a void space does not add to the weight of an object unless it is bonded to the object. To prove this, imagine a box which is completely hollow, yet all of the sides are solid. A hole is drilled in only one side. We now weigh the box and subject it to a pressured atmosphere. The gas will occupy the space both inside and outside of the box; however the hole which the gas passes is not very large. The gas on the inside of the box will not add any weight to it, yet is in the interior of it. Therefore, for any gas to actually add weight to an object, the gas must become an attached part of the block.

To further expound on this subject, imagine another hollow box with all six sides sealed. At a given pressure, the box will weigh less due to buoyancy effects. In addition, the volume of the box is the volume of the sides plus the space inside the box. If the box is now opened, it would appear to have gained weight because there is actually less buoyancy effect, because the volume of

the box is only the volume of the sides. Therefore, while there is no actual weight change, there would appear to be.

This theoretical idea is possibly what is happen during the sorption process of coal. The gas could be entering void spaces which would otherwise be contributing to the buoyancy effects which are being subtracting out. Therefore, it is possible that calculating the density of coal which is ground as fine as possible will give more accurate results, because more internal void spaces would be eliminated. While gas is filling up the void spaces, it is increasing the calculated weight because the assumed density includes void spaces, even though the gas is not being sorbed. This is a problem which can only be solved by determining the coal density with a gas which cannot be sorbed by the coal.

There is another side to this argument. Coal is naturally strewn with cracks and void spaces; therefore, the increase in mass due to a cancelling of buoyancy forces could be considered as adding weight to the coal sample. While the gas occupying the void spaces is not sorbed by the coal, it is in fact within the coal structure. Imagine a beaker half full of water on a scale. It will have a certain weight.. If we now lower a weight into the water, the scale reading will rise proportional to the volume of the weight, not proportional to its weight. This additional weight is cause by the addition of a buoyancy force. The weight is not actually attached to the beaker or is a part of it, yet causes the weight to increase. This idea can be associated to coal by saying that the weight goes up because of the addition of gas negates the already present buoyancy force. As one can see, both sides of the argument are arguing the same thing. It is up to petrologists to decide if the negation of buoyancy force is actually an increase in weight, or in other words, if the void spaces are actually an intrinsic part of the coal and should be included.

References Used:

Dobner, S., et. al. "Modification of a Thermobalance for High Pressure Process Studies", 1975

Williams, J.R., and Wendlandt, W.W. "A High Pressure Thermobalance", Thermochimica Acta, 1973, 253-260

Brown, H.A., Elwin, C.P., and Callahan, J.J. "An Apparatus For High Pressure Thermogravimetry", Thermochimica Acta, 1971, 271-276

Fuller, E.L.Jr., "Physical and Chemical Structure of Coals: Sorption Studies", American Chemical Society, 1981, 293-309

Thompson, K.A., Fuller, E.L.Jr., "Computer Controlled Vacuum Microbalance Techniques for Surface Area and Porosity Measurements", American Chemical Society, 1987, 699-703

Fuller, E.L.Jr., Thompson, K.A., "Chemical and Geometric Factors in Physical Adsorption/Desorption of Gases on Solids", 1987, 713-721

Fig. 1

TABLE 3-28 Density (kg/m³) of Water from 0 to 100°C*

t, °C	ρ, kg/m ³									
	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9
0	999.839	999.846	999.852	999.859	999.865	999.871	999.877	999.882	999.888	999.893
1	999.898	999.903	999.908	999.913	999.917	999.921	999.925	999.929	999.933	999.936
2	999.940	999.943	999.946	999.949	999.952	999.954	999.956	999.959	999.961	999.962
3	999.964	999.966	999.967	999.968	999.969	999.970	999.971	999.971	999.972	999.972
4	999.972	999.972	999.972	999.971	999.971	999.970	999.969	999.968	999.967	999.965
5	999.964	999.962	999.960	999.958	999.956	999.954	999.951	999.949	999.946	999.943
6	999.940	999.937	999.934	999.930	999.926	999.923	999.919	999.915	999.910	999.906
7	999.901	999.897	999.892	999.887	999.882	999.877	999.871	999.866	999.860	999.854
8	999.848	999.842	999.836	999.829	999.823	999.816	999.809	999.802	999.795	999.788
9	999.781	999.773	999.765	999.758	999.750	999.742	999.734	999.725	999.717	999.708
10	999.699	999.691	999.682	999.672	999.663	999.654	999.644	999.635	999.625	999.615
11	999.605	999.595	999.584	999.574	999.563	999.553	999.542	999.531	999.520	999.509
12	999.497	999.486	999.474	999.462	999.451	999.439	999.426	999.414	999.402	999.389
13	999.377	999.364	999.351	999.338	999.325	999.312	999.299	999.285	999.272	999.258
14	999.244	999.230	999.216	999.202	999.188	999.173	999.159	999.144	999.129	999.114
15	999.099	999.084	999.069	999.054	999.038	999.022	999.007	998.991	998.975	998.958
16	998.943	998.926	998.910	998.894	998.877	998.860	998.843	998.826	998.809	998.792
17	998.775	998.757	998.740	998.722	998.704	998.686	998.668	998.650	998.632	998.614
18	998.595	998.577	998.558	998.539	998.520	998.502	998.482	998.463	998.444	998.425
19	998.405	998.385	998.366	998.346	998.326	998.306	998.286	998.265	998.245	998.224
20	998.204	998.183	998.162	998.141	998.120	998.099	998.078	998.057	998.035	998.014
21	997.992	997.971	997.949	997.927	997.905	997.883	997.860	997.838	997.816	997.793
22	997.770	997.747	997.725	997.702	997.679	997.656	997.632	997.609	997.585	997.562
23	997.538	997.515	997.491	997.467	997.443	997.419	997.394	997.370	997.345	997.321
24	997.296	997.272	997.247	997.222	997.197	997.172	997.146	997.121	997.096	997.070
25	997.045	997.019	996.993	996.967	996.941	996.915	996.889	996.863	996.836	996.810
26	996.783	996.757	996.730	996.703	996.676	996.649	996.622	996.595	996.568	996.540
27	996.513	996.485	996.458	996.430	996.402	996.374	996.346	996.318	996.290	996.262
28	996.233	996.205	996.176	996.148	996.119	996.090	996.061	996.032	996.003	995.974
29	995.945	995.915	995.886	995.856	995.827	995.797	995.767	995.737	995.707	995.677
30	995.647	995.617	995.586	995.556	995.526	995.495	995.464	995.433	995.403	995.372
31	995.341	995.310	995.278	995.247	995.216	995.184	995.153	995.121	995.090	995.058
32	995.026	994.997	994.962	994.930	994.898	994.865	994.833	994.801	994.768	994.735
33	994.703	994.670	994.637	994.604	994.571	994.538	994.505	994.472	994.438	994.405
34	994.371	994.338	994.304	994.270	994.236	994.202	994.168	994.134	994.100	994.066

*From "Water: Density at Atmospheric Pressure and Temperatures from 0 to 100°C," *Tables of Standard Handbook Data*, Standartov, Moscow, 1978. To conserve space, only a few tables of density values are given. The reader is reminded that density values may be found as the reciprocal of the specific volume values tabulated in the "Thermodynamic Properties: Tables" subsection.

TABLE 3-30 Densities of Gases at Standard Conditions (0°C, 1 atm)*

Gas	Formula	Mol. wt.	Density	
			G./l.	Lb./cu. ft.
Acetylene.....	C ₂ H ₂	26.02	1.1708	0.0732
Air.....			1.2928	0.0808
Ammonia.....	NH ₃	17.03	0.7708	0.0482
Argon.....	Ar	39.91	1.7828	0.1114
Bromine.....	Br ₂	159.83	7.1388	0.4460
Butane.....	C ₄ H ₁₀	58.08	2.5985	0.1623
Carbon dioxide.....	CO ₂	44.00	1.9768	0.1235
Carbon monoxide.....	CO	28.00	1.2501	0.0781
Carbon oxychloride.....	COCl ₂	98.91	4.5313	0.2830
Carbon oxydisulfide.....	COS	60.06	2.7201	0.1700
Chlorine.....	Cl ₂	70.91	3.2204	0.2011
Chlorine monoxide.....	Cl ₂ O	86.91	3.8874	0.2428
Cyanogen.....	C ₂ N ₂	52.02	2.3348	0.1459
Ethane.....	C ₂ H ₆	30.05	1.3567	0.0848
Ethyl chloride.....	C ₂ H ₅ Cl	64.50	2.5700	0.1793
Ethylene.....	C ₂ H ₄	28.03	1.2644	0.0783
Fluorine.....	F ₂	38.00	1.6354	0.1022
Helium.....	He	4.00	0.1769	0.0111
Hydrogen.....	H ₂	2.016	0.0898	0.0056
Hydrogen chloride.....	HCl	36.47	1.6394	0.1024
Hydrogen fluoride.....	HF	20.01	0.9218	0.0576
Hydrogen iodide.....	HI	127.94	5.7245	0.3576
Hydrogen selenide.....	H ₂ Se	81.22	3.6134	0.2258
Hydrogen sulfide.....	H ₂ S	34.08	1.3392	0.0961
Hydrogen telluride.....	H ₂ Te	129.52	5.8034	0.3625
Krypton.....	Kr	82.90	3.6431	0.2275
Methane.....	CH ₄	16.03	0.7167	0.0448
Methyl chloride.....	CH ₃ Cl	50.48	2.3044	0.1440
Neon.....	Ne	20.40	0.8713	0.0544
Nitric oxide.....	NO	30.01	1.3401	0.0837
Nitrogen.....	N ₂	28.02	1.2507	0.0782
Nitrous oxide.....	N ₂ O	44.02	1.9781	0.1235
Nitrosyl chloride.....	NOCl	65.47	2.9864	0.1865
Oxygen.....	O ₂	32.00	1.4289	0.0892
Phosphine.....	PH ₃	34.05	1.5293	0.0955
Silicon fluoride.....	SiF ₄	104.06	4.6541	0.2907
Sulfur dioxide.....	SO ₂	64.06	2.9268	0.1828
Xenon.....	Xe	130.20	5.7168	0.3570

*For other tables see Atack, "Handbook of Chemical Data," pp. 90, 91, Reinhold, New York, 1957; "Smithsonian Physical Tables," 9th ed., Table 255, 1954; "American Institute of Physics Handbook," p. 2-200, McGraw-Hill, New York, 1957.

NOTE: For ideal-gas behavior, density may be calculated as MP/RT .

Generalized plot of compressibility factors at low reduced pressures. Courtesy Gas Processors Suppliers

Strain-Elongation Sorption Experiment

The pressure cell which is going to be used to maintain the experiment has been completed and is ready for use. Referring to Fig. 1, there is a diagram of the pressure cell. The cell is a cylindrical steel bomb with 1" thick walls. The top and bottom lids are sealed with 3/16" O-rings (NOTE: we avoided using Viton O-rings because they will react with methane and other hydrocarbons). Furthermore, a thin layer of vacuum grease was applied to increase the sealing potential.

To hold the samples and maintain the humidity, a small tray and bowl is set inside the cell. The bowl will contain a saturated salt solution which will maintain the relative humidity within the cell. For this experiment, Potassium Sulfate (K₂SO₄) will be used to maintain the relative humidity at 97%. In addition, Lithium Chloride Monohydrate will be used to maintain the relative humidity at 12%. The tray is made from stainless steel and is mounted on three legs.

To determine the elongation of coal upon sorption, strain gauges will be attached to the coal samples in various orientations. To pass strain gauge wires out of the high pressure cell, a Conax model #TG-20-A 16-T wire feed through was purchased. This will allow sixteen 20 gauge wires to be passed through the wall of the cell. Furthermore, the pressure gauge is a bourdon type Solfrunt 4.5" dial pressure test gauge (Cat. #1404-2000).

The cell was pressure tested up to 1200 psi using water as the test fluid. A leak kept occurring at the stem of the pressure gauge. After releasing the pressure, tightening, and repressuring, the rate of leakage was decreased. Upon last testing, no leakage was detected after one hour. This leak resulted in a change of procedure. Instead of injecting gas to a certain pressure and closing the valve, the gas tank regulator will be set to maintain pressure if any gas leaks out.

Coal Preparation

The next step was to begin experimentation on sample preparation. Numerous methods were tried and the results will be discussed. The coal blocks were first coated with an epoxy to give the coal extra integrity. The epoxy will be removed before used in an experiment.

The band saw was tried first. For the block of coal used, each cut took an extremely long period of time. After one hour, only about three inches was cut through. Furthermore, the band saw tends to stray and failed to give flat slabs.

The automatic diamond saw was not even considered because it uses kerosene as a lubricating fluid. We believe

that the kerosene would be absorbed by the coal and alter its properties.

The best method tried was the 12" rock saw. It uses water as a lubricating fluid and can handle large blocks of coal. The saw is raised and lowered into the block of coal which is held by a vice. After cutting halfway through, the block is turned over to cut the other side. This method allows for approximately 10" cuts. Finally, the cuts are extremely flat and the coal is still strong.

Coring was tried for the triaxial and compression tests. Using a verticle drill, no samples were successfully cored. Using a 1" and 2" bit and coring with and without water yielded the same results. The cored sample crumbled in the core barrel. Coring will either be abandoned or another machine will be tried in the future. The coal sample and drill were not very stable and may have added to the problem.

Pressure
Cell
Figure 1.

MAJOR ACCOMPLISHMENTS, TASK 5 (PERMEABILITY TESTING)

1. EQUIPMENT PROCUREMENT:

Orders have been placed for digital pressure gauges and mass-flow meters and these equipments are expected in 2 weeks time.

2. EXPERIMENTATION WITH COAL POWDER PACK :

A coal sample from Black Warrior basin was collected for study. The coal sample was crushed and sieved through a 20-30 mesh screens. The coal powder was compacted by packing tightly into the core holder. Several test runs were made with nitrogen at pressures ranging from 50-450 psi. Flow rates were measured using a differential pressure gauge and a wet test meter. Saturation time was varied to study the effects. Saturation time is the time for which the powder pack was kept under pressure at each different inlet pressures prior to measuring flow rates. A constant pressure drop of 10 psig was maintained across the core. The permeability was calculated using Darcy's law. The flow measurements were taken at different saturation time intervals ranging from 2 hours to 18 hours at various inlet pressures. At low pressures upto 150 psi the permeability increased with longer saturation times. The sufficient accuracy of results can be obtained only by use of mass flow meters. Presently test runs are being made using carbondioxide.

3. The experimental set up is shown in figure 1. An example set of permeability obtained using nitrogen is shown in table 1.

saturation time: 10 hrs.

pr (psig)		pr. drop (psig)	Q cc/sec	k darcy
inlet	outlet			
55	45	10	2.838	0.160
105	95	10	3.974	0.224
155	145	10	4.226	0.238
205	195	10	3.784	0.213
255	245	10	3.674	0.207
305	295	10	3.784	0.213
355	345	10	3.674	0.207
405	395	10	3.784	0.213

TABLE 1

sample calculation:

DARCY'S LAW

$$K = \frac{Q * \mu * A}{L * \Delta P}$$

WHERE Q = FLOW RATE IN CC/SEC.
 A = CROSS-SECTIONAL AREA OF CORE BARREL IN SQ.CM.
 μ = VISCOSITY OF GAS IN CENTIPOISE.
 L = LENGTH OF CORE BARREL IN CM.
 ΔP = PRESSURE DROP ACROSS THE CORE IN ATM.

AT 55 PSIG INLET PR.

$$K = \frac{2.838 * 0.0174 * 27.94}{12.65 * 10/14.7}$$

$$= \underline{\underline{0.160 \text{ DARCY.}}}$$

END

DATE
FILMED

10 / 23 / 92