DOE/ER/13764--T3

DOE/ER/13764--T3

DE93 000647

ANNUAL TECHNICAL PROGRESS REPORT
FOR 1991/1992 PERIOD

ON

INTERFACIAL AREA AND INTERFACIAL
TRANSFER IN TWO-PHASE FLOW SYSTEMS

G. Kojasoy (Formerly Kocamustafaogullari)
Department of Mechanical Engineering
University of Wisconsin-Milwaukee
Milwaukee, Wisconsin 53201

August 1992

Prepared for
U.S. Department of Energy
Under Grant No. DE-FG02-87ER13764

ProgRept.DOE/Kojasoy

DOE/ER/13764--T3
1992 11 12
MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ja

ANNUAL TECHNICAL PROGRESS REPORT FOR 1991/1992 PERIOD

A research program which mainly dealt with studying the interfacial structure of horizontal two-phase flow has been underway at the University of Wisconsin-Milwaukee. It has been conducted both experimentally and theoretically.

The major accomplishments of the experimental work during the period of 1991/1992 fiscal year are summarized.

1. A double-sensor resistivity probe technique, which was developed under this program and results of which have been published for 50.3 mm-ID horizontal air-water bubbly two-phase flow [1-3], was extended for 25.4 mm-ID horizontal air-water bubbly two-phase flow. For this purpose 25.4 mm-ID horizontal loop was designed and constructed parallel to the existing 50.3 mm-ID test section. A series of bubbly flow experiments has been already completed. The experimental results are being interpreted to investigate the pipe size effects on local interfacial parameters listed below:

- void fraction,
- interfacial area concentration,
- bubble interface velocity,
- bubble chord-length and bubble size distribution,
- bubble frequency distribution.

Preliminary results which are not conclusive yet indicate differences in bubble size and void fraction and interfacial area concentration distributions. This study will be completed in September 1992, and will be submitted for archival publication in September or October of 1992.

2. The bubbly two-phase flow development in the axial direction has been experimentally investigated for 50.3 mm-ID piping, and major findings of this study were presented at the International Conference on Multiphase Flows' 91-Tsukuba, September 21-27, 1991, Tsukuba, Japan [4]. An expanded form of this publication has been submitted to the Int. J. Experimental Thermal and Fluid Science [5].

3. Stratified-wavy two-phase flow patterns, i.e., stratified-2D waves, stratified-large amplitude waves and wavy-atomizing flow patterns, were visually investigated, and wavy flow pattern transition lines were identified on two-dimensional flow-pattern map in terms of liquid and gas superficial velocities. In addition to the flow visualization experiments, a new conductance probe test section was developed to measure the interfacial wave parameters of horizontal stratified-wavy two-phase flow patterns. Basically, the wavelength, the most probable wave frequency, wave amplitude and speed of propagation of interfacial waves were measured in 2D wavy, large-amplitude wavy and stratified-atomizing wavy flow patterns. Effect of flow variables on the wave parameters were investigated. The results of this experimental investigation were documented in Mr. J. Shi's Master thesis, which was completed and defended on June 9, 1992.

4. A similar test section to that described in Item #3 has been developed for the purpose of measuring interfacial wave characteristics in a horizontal annular two-phase flow. The test section was constructed and calibrated. Although the test section was ready for some time, due to the bubbly flow and stratified-wavy flow experimentation on the same loop the experimentation has not been accomplished yet. This experimentation is tentatively planned for early fall of 1992.

5. Development of a four-sensor resistivity probe, which will be an extension of the double-sensor resistivity probe successfully used for bubbly flow, has been underway for some time. The four-sensor probe will be used to measure interfacial area concentration and void fraction distribution in a horizontal slug flow-pattern. With this probe it will be possible to obtain separate data on long gas bubbles and follow-up small bubbles in the slug flow. This multi-sensor probe will use horizontal slug flow data in 25.4 mm and 50.3 mm loops in fall of 1992.

A series of theoretical studies was undertaken to mechanistically model the various interfacial parameters for a horizontal two-phase flow system. The major accomplishments of this series of investigations are summarized below:

1. Analytical modeling of the bubble interfacial area which involved the modeling of void fraction and mean bubble size was completed. Results of this investigation were partially documented in publication [6]. The complete paper on this study which, was submitted to the J. Nuclear Engineering & Design, has been under review [7].

2. A theoretical model describing the maximum stable drop size and size distribution in an annular two-phase flow was developed. The model was based on the break-up of drops by dynamic pressure forces generated by turbulence generated around a drop. This work which was already documented in Mr. Steven Smit's Master thesis has been further improved by T. He, and now it is ready for publication.

3. An interfacial stability analysis by asymptotic method has been in progress as a Master's thesis by Mr. Garry Memmel. It was anticipated to be finished in Spring of 1992.

However, extending the analysis to the third order approximation delayed completion of this work. Hopefully, it is going to be ready in the fall of 1992.

4. Based on the experimental observation an interesting similarity analysis was initiated to investigate concentration similarity. This study has not been conclusive yet in terms of a complete understanding in geometric similarity of these parameters. Further work is needed on this before archival publication.

LIST OF PUBLICATIONS CITED

1. Z. Wang and G. Kocamustafaogullari, "Interfacial characteristic Measurement in a Horizontal Bubbly Two-Phase Flow," AN Winter meeting, Proceedings of Nuclear Thermal Hydraulics, Vol. 6, pp. 342-351, Washington, D.C., November 11-16, 1990. THIS PAPER HAS RECEIVED "BEST PAPER AWARD" on November 11, 1991.
2. G. Kocamustafaogullari and Z. Wang, "An Experimental Study on Local Interfacial Parameters in a Horizontal Bubbly Two-Phase Flow," Int. J. Multiphase Flow, Vol. 17, pp. 553-572, 1991.
3. Z. Wang, W.D. Huang, S. Srinivasmurthy and G. Kocamustafaogullari, "Interfacial Characteristic Measurements in Horizontal Bubbly Two-Phase Flow," DOE/NE13764-4 Report, 1990.
4. W.D. Huang, Z. Wang and G. Kocamustafaogullari, "Local Phase Distribution and Interfacial Area in a Horizontal Bubbly Two-Phase Flow," Proc. Int. Conf. on Multiphase Flow, Vol. 1, pp. 479-484, Tsukuba, Japan, September 24-27, 1991.
5. G. Kocamustafaogullari and W.D. Huang, "Axial Flow-Pattern Development of Bubbly Two-Phase Flow," Int. J. Experimental Thermal and Fluid Science (Under Review).

6. G. Kocamustafaogullari, W.D. Huang and T. He, "Measurement and Modeling of Interfacial Area Concentration," 27th National Heat Transfer Conference, Proceedings of Nuclear Thermal Hydraulics, Vol. 7, pp. 53-62, San Diego, CA, August 9-12, 1992.
7. G. Kocamustafaogullari, W.D. Huang and J. Razi, "Measurement and Modeling of Average Void Fraction, Bubble Size and Interfacial Area," J. Nuclear Engineering and Design (Under Review).
8. J. Kitscha, C.T. Chang and G. Kocamustafaogullari, "Characteristics of Horizontal Two-Phase Flow Determined by Experimental Techniques," Proc. 9th Int. Heat Transfer Conf., Vol. 6, pp. 15-23, Jerusalem, Israel, August 19-24, 1990.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

DATE
FILMED

12 / 7 / 92