Report on Technical Progress

December 1, 1992

Project Title: Fast Algorithms for Transport Models
DE-FG02-90ER25086

Principal Investigator: Thomas A. Manteuffel
University of Colorado at Denver
Computational Mathematics Group
Campus Box 170
PO Box 173364
Denver Colorado 80217-3364
Telephone: 303 556-4810
Fax: 303 556-8550

Abstract

The objective of this project is the development of numerical solution techniques for deterministic models of the transport of neutral and charged particles and the demonstration of their effectiveness in both a production environment and on advanced architecture computers. The primary focus is on various versions of the linear Boltzman equation (see Section II.A.). These equations are fundamental in many important applications.

This project is an attempt to integrate the development of numerical algorithms with the process of developing production software. A major thrust of this project will be the implementation of these algorithms on advanced architecture machines that reside at the Advanced Computing Laboratory (ACL) at Los Alamos National Laboratories (LANL).

Previous work under this project includes the development of fast algorithms for the solution of the steady-state, monoenergetic, linear Boltzman equation in slab geometry (see Section II.B.). For isotropic scattering, a multigrid in space algorithm was developed [15] [18]. It is very effective in the thick diffusive limit, yielding a convergence factor that goes to zero in this limit. It is significantly faster than the Diffusion Synthetic Acceleration

(DSA) method. For anisotropic scattering, a multilevel in angle method was developed [25]. It is effective for highly forward peaked scattering in the thick limit. It is the first algorithm to yield a convergence factor bounded away from 1 in the thick Fokker-Plank limit. Both algorithms have been implemented on the Thinking Machines Inc. CM-200 at Los Alamos National Laboratories (LANL). The codes are highly parallel and represent the state-of-the-art for slab geometry [16] [17].

The proposed research includes extension of these ideas to two and three dimensional geometries and the implementation of the resulting algorithms on advanced architecture computers as well as in production quality software at LANL and at Lawrence Livermore National Laboratories (LLNL). Both new discretization schemes and new solution algorithms will be explored. A further goal is to develop software for the solution of coupled photon/electron scattering in slab geometry.

This project will depend on continued close collaboration with Jim Morel at LANL and Milo Dorr at LLNL. Steve McCormick from the University of Colorado at Denver will also remain an important part of the team.

I. The Mathematical Model

This project is focused on the numerical solution of mathematical models of particle transport. In particular, we are interested in various versions of the linear Boltzman equation,

$$\frac{\partial \psi}{\partial t} = -\underline{\Omega} \cdot \nabla \psi - \sigma_t \psi + \sigma_s \int \int K(\underline{x}, \underline{\Omega}' \rightarrow \underline{\Omega}, E' \rightarrow E) \psi d\underline{\Omega}' dE' + Q,$$

where the unknown $\psi(\underline{x}, \underline{\Omega}, E, t)$ represents the flux of particles at position $\underline{x}$, moving in direction $\underline{\Omega}$, with energy E at time t . Here $\sigma_t dx$ represents the expected number of interactions (absorptive or scattering) that a particle will have in traveling a distance dx . In a similar manner, $\sigma_s dx$ represents the expected number of scattering interactions while $\sigma_a = \sigma_t - \sigma_s$ represents the expected number of absorptive interactions. Finally, $Q(\underline{x}, \underline{\Omega}, E, t)$ represents the particle sources.

We concentrate on the solution of the steady-state, monoenergetic Boltzman equation,

$$\underline{\Omega} \cdot \nabla \psi + \sigma_t \psi - \sigma_s \int \int K(\underline{x}, \underline{\Omega}' \rightarrow \underline{\Omega}) \psi d\underline{\Omega}' = Q,$$

where now $\psi(\underline{x}, \underline{\Omega})$ depends only on direction and position. The solution of equations of this type is the fundamental step in the solution of the full equation. The time dependence can be resolved, for example, by an implicit time differencing such as Crank-Nickelson. The energy dependence is usually resolved by a multigroup approximation in which particles are allowed to possess one of a discrete set of energies. Scattering to another energy level is reflected as absorption while in-scattering from other energy groups is reflected in the source term. This yields a coupled set of equations. Treating the in-scattering from other levels as known, a monoenergetic equation can be solved at each level. Since particles generally lose energy, starting at the highest level and proceeding to lower levels usually yields a convergent iteration. In terms of linear algebra, this corresponds to a block Gauss-Seidel iteration on the coupled system. The lowest energy level usually involves the smallest particle loss to other levels and is the most difficult to solve.

The steady-state, monoenergetic problem becomes ill-posed when there is little absorption or scattering to other energy levels and when the mean-free-path between collisions becomes small compared to the physical size of the problem. This is called the optically thick diffusion limit and is characterized mathematically by $\sigma_t \gg 1$ and $\frac{\sigma_a}{\sigma_t} \rightarrow 1$ while $K(\underline{x}, \underline{\Omega}' \rightarrow \underline{\Omega})$ remains unchanged. The name diffusion limit arises from the fact that transport resembles diffusion in this limit. Away from this limit, the equation is relatively easy to discretize and solve numerically. Unfortunately, it is precisely this limit that is of interest in many applications.

The limit operator is singular. Any function, $\psi(\underline{x}, \underline{\Omega}) = \psi(\underline{x})$, that is independent of direction (angle) is in the null space. The limiting behavior of a singularly perturbed operator can usually be determined by restricting the operator to the null space of the limit operator and projecting the image back onto the null space. The inverse of this projected operator normally describes the dominant term in the inverse of the perturbed operator. However, for the Boltzman operator, the projected operator is

$$\sigma_t \psi(\underline{x}) - \sigma_s \int \int K(\underline{x}, \underline{\Omega}' \rightarrow \underline{\Omega}) \psi(\underline{x}) d\underline{\Omega}' = (\sigma_t - \sigma_s) \psi(\underline{x}).$$

In many applications, this operator is zero (no absorption) or goes to zero as $\sigma_t \rightarrow \infty$.

This unique behavior of the Boltzman operator in the thick diffusion limit complicates two important issues. The first is the construction of discretiza-

tion schemes that are accurate in the thick diffusion limit. This project has addressed the numerical solution of the discrete S_N or P_N approximations. The S_N and P_N approximations assume that the angular dependence can be expanded in a discrete number of spherical harmonics. The P_N equations result from using a Galerkin formulation to close the equations while the S_N equations result from collocation at Gauss quadrature points on the sphere. In slab geometry, the spherical harmonics become Legendre polynomials and the S_N and P_{N-1} approximations are equivalent. The spatial discretization is then achieved through either a finite difference or finite element approximation. For many standard spatial discretization schemes, accuracy depends upon $\sigma_t h$ where h is a mesh parameter. That is, as $\sigma_t \rightarrow \infty$, these schemes require that $h \rightarrow 0$ in order to insure numerical accuracy, even for well behaved solutions. Consequently, they require an inordinately fine mesh. In the past decade, much work has been done to construct discretization schemes for which the accuracy depends upon h even as $\sigma_t \rightarrow \infty$ ([6] [9] [10] [12] [24]).

The second issue is the numerical solution of the discrete equations. Prior to this project, the arsenal of methods for the numerical solution of S_N equations was somewhat limited. For problems with isotropic scattering, that is, when the probability of scattering in any direction is equal, the Diffusion Synthetic Acceleration(DSA) method is very effective [2] [7] in one- and two-dimensional geometries. It is based upon the observation that, in the thick diffusion limit, scattering becomes diffusive in nature. The solution becomes independent of direction (angle) and, asymptotically, satisfies a diffusion equation. The DSA method solves a diffusion equation at every step of an iteration as an acceleration or preconditioning [4] [8].

The balance between the discretization used for the Boltzman equation and the discretization used for the diffusion equation is delicate. If it is not done consistently, the DSA scheme can behave poorly. In slab geometry (see below), this difficulty has been overcome, while in general geometries it is still an open question ([1] [2] [5] [7] [13]).

For anisotropic scattering, especially highly forward-peaked scattering, that is, when the probability of scattering through a small angle is higher than the probability of scattering through a large angle, the DSA algorithm performs poorly. Highly forward-peaked scattering is important in models of charged particle transport. For models of charged particles, as the problem becomes optically thick, that is, as $\sigma_t \rightarrow \infty$, the average change in direction per unit path length remains unchanged. This is known as the thick Fokker-

Plank limit and is characterized mathematically by $\sigma_t \rightarrow \infty$, $\frac{\sigma_s}{\sigma_t} = O(1)$ and $K(\underline{x}, \underline{\Omega}' \rightarrow \underline{\Omega})$ evolves in such a way that the cosine of the average scattering angle $\bar{\mu} = 1 - O(\frac{1}{\sigma_s})$. The DSA convergence factor approaches 1 in this limit [21] [22].

II. Prior Accomplishments

The previous work of this project was concerned with the development of fast algorithms for solving the steady-state, monoenergetic, linear Boltzman equation in slab geometry. The physical domain is a semi-infinite slab of width $b - a$ in the x dimension. Although three dimensional, the flux of particles is assumed to be independent of the y and z coordinates. Thus, the linear Boltzman equation reduces to

$$\mu \frac{\partial \psi}{\partial x} + \sigma_t \psi - \frac{\sigma_s}{2} \int_{-1}^1 \psi(x, \mu') d\mu' = Q(x, \mu),$$

for $x \in (a, b)$, $\mu \in [-1, 1]$, where $\psi(x, \mu)$ represents the flux of particles at position x traveling at an angle θ from the x -axis ($\mu = \cos(\theta)$). The solution is well defined if the flux of particles entering the slab is given as boundary conditions:

$$\psi(a, \mu) = g_a(\mu), \quad \psi(b, -\mu) = g_b(\mu) \quad \mu \in (0, 1).$$

This project has developed a multigrid in space algorithm for the solution of the S_N equations with isotropic scattering in slab geometry [15] [18]. The algorithm was developed for the Modified Linear Discontinuous (MLD) discretization in space which is accurate in the thick diffusion limit [24]. It uses a red/black two-cell μ -line relaxation. This relaxation solves for all angles on two adjacent spatial cells simultaneously. It takes advantage of the rank-one property of the coupling between angles and can perform this inversion in $O(N)$ operations where N is the number of discrete angles.

The MLD scheme approximates the solution by linear elements across each spatial cell. In the thick limit the red/black two-cell μ -line relaxation leaves an error that is independent of angle and continuous up to $O(\frac{1}{\sigma_t h})$. The error is also sublinear across each two-cell pair, that is, the error at the boundary between cells of a two-cell pair is less than the average of the errors at the outer boundaries of the two-cell pair. The size of the kink can be determined analytically [19], but it is more practical to let the relaxation yield the information. In this sense, it is an operator induced interpolation.

The resulting interpolation is a kinked linear interpolation. The restriction used is a full weighting, that is, the transpose of linear interpolation. This restriction and interpolation yields coarse grid equations that are not MLD on the coarse grid. However, the new coarse grid operator can be solved by a recursion of the same relaxation and further grid coarsening. It has the same structure as the MLD operator and is amenable to the same efficient red/black two-cell μ -line relaxation. Each subsequent coarsening is accomplished by a kinked linear interpolation and a full weighting restriction. The product of all of the interpolations from the coarsest grid, which contains only two cells, up to the finest grid can be viewed as kinks on kinks. It resembles the exact solution of a homogeneous equation with isotropic boundary conditions.

The multigrid algorithm is very effective. For $\sigma_i h \gg 1$, the convergence factor is $\rho = O(\frac{1}{\sigma_i h})$. With no absorption the convergence factor is $\rho = O(\frac{1}{(\sigma_i h)^2})$. In the thin limit, that is, $\sigma_i h \ll 1$ the convergence factor is $\rho = O((\sigma_i h)^3)$. The slowest convergence occurs when $\sigma_i h \simeq .01$ on the finest grid and yields $\rho \simeq .01$. We compare this to the DSA algorithm in slab geometry, which has a convergence factor bounded by .23 independent of the size of σ_i . In general, the convergence factor for DSA is between .1 and .23 for $\sigma_i \gg 1$ and all ranges of $\sigma_i h$. Depending on the particular computer architecture, the multigrid algorithm takes 2-4 times as long per iteration, but the extremely fast convergence rates of the multigrid algorithm yield an algorithm that is faster in all regimes. The multigrid algorithm has turned the problem inside out. It is now easier to solve the problem in the thick limit and easiest with no absorption.

A version of the multigrid in space algorithm was programmed on the Thinking Machines Inc. CM-200 located at Los Alamos National Laboratories [16] [17]. The two-cell μ -line relaxation is inherently parallel. It was discovered that on the CM-200 a block Jacobi type iteration was more efficient than the block red/black iteration. Given sufficient processors all two-cell block inversions can be carried out simultaneously with a small number of parallel steps. The bottleneck is the need for sums of N values, where N is the number of discrete angles, each from a different processor. These are carried out by machine intrinsic functions and are well optimized. The overall algorithm has computational complexity $O(\log(M))$, where M is the number of spatial cells. The algorithm is very efficient and represents the

state-of-the-art for isotropic problems in slab geometry.

For anisotropic scattering in slab geometry, a multilevel in angle algorithm was developed [25]. This algorithm uses a shifted transport sweep as a relaxation. It has the form,

$$\mu \frac{\partial \psi^{j+1}}{\partial x} + (\sigma_t - \alpha) \psi^{j+1} = (\sigma_s - \alpha) \int_{-1}^1 K(x, \mu' \rightarrow \mu) \psi^j d\mu' + Q,$$

where j is the iteration number. The shift α is chosen to reduce the error in the high Legendre moments. The residual is then projected onto the first $N/2$ Legendre moments. The coarse level correction is the result of solving an $S_{N/2}$ problem with the projected residual as the source. This coarse level problem is solved in the same manner, with a shifted transport sweep followed by a correction from an $S_{N/4}$ problem. The shift parameter changes from level to level and is dependent on material properties. It is chosen to reduce the error in the highest half of the moments at each level. The coarsest level is an S_2 problem. The proper shift yields an isotropic problem that can be solved by the multigrid in space algorithm described above. In this context, one v(1,1)-cycle yields an exact solution of the S_2 problem. The algorithm has a v(1,1)-cycle convergence factor of .36 for highly forward-peaked Fokker-Plank scattering. This is the first algorithm to have a convergence factor bounded away from 1 in the thick Fokker-Plank limit.

A parallel version of the multilevel in angle algorithm has also been developed. Upon first glance, the shifted transport sweep has limited parallelism. Once the right-hand-side has been computed, the sweep is completely parallel in angle, becoming N uncoupled initial value ODE's. It appears that the integration of these ODE's is sequential. However, we have developed a cyclic reduction algorithm that renders it parallel with complexity $O(\log(M))$. The multilevel in angle algorithm visits $\log(N)$ levels, where shifted transport sweeps are performed. The overall complexity is $O(\log(N)\log(M))$. The algorithm has been coded on the CM-200 and is in the debugging stage.

III. Research Plan

Our current focus is on three areas. First, we are extending the multilevel in angle algorithm to two and three dimensional spatial geometries. Since the direction variable is represented by the surface of the unit sphere, these geometries represent 4 and 5 dimensional problems respectively. We believe that the algorithm can be used for both S_N and P_N approximations. The basic algorithm remains unchanged. Shifted transport sweeps will be used to reduce the error in the direction of the higher spherical harmonics. The sweeps are naturally parallel in angle, appearing as uncoupled ODE's. If the discretization is logically rectangular in space, they can again be solved by a cyclic reduction algorithm. The complexity of the sweeps will be $O(\log(M_x)\log(M_y)\log(M_z))$ where M_i represents the number of cells in each spatial coordinate. After the error becomes smooth in the angle variables the residual will be projected onto lower degree spherical harmonics. The number of spherical harmonics will be reduced by approximately 1/4 at each level. This will leave an S_2 or P_1 problem at the coarsest level. The S_2 scattering operator will be rank 4 while the P_1 scattering operator will be rank 3 in two dimensions and rank 4 in three dimensions. Thus, the scattering operator of the S_2 or P_1 problem will have either 3 or 4 eigenvalues, one with value σ_s and the rest with values less than σ_s . A sequence of shifted transport sweeps with properly chosen shift parameters will leave the error nearly isotropic. This final error can be eliminated through a either multigrid in space algorithm or a diffusion approximation. The overall complexity should be $O(\log(N)\log(M_x)\log(M_y)\log(M_z))$.

Secondly, we are developing a multigrid in space algorithm for isotropic problems in two and three space dimensions discretized with S_N in angle and bilinear or trilinear discontinuous elements on logically rectangular grids in space. Our first approach is an application of the same ideas as in the slab geometry. Now, however, the relaxation will involve solving for all angles on a two-by-two cell patch in two dimensions and a two-by-two-by-two cell cube in three dimensions. The scattering operator remains rank-one, and thus, the block inversions can be carried out very efficiently. The major issue will be determining the interpolation and restriction operators that define the coarse grid operator. In one dimension, the kinked elements are relatively easy to determine. In two dimensions, for example, visualize a piecewise bilinear function across a two-by-two cell square. In the thick limit, the

error after relaxation will be nearly continuous, independent of angle and sublinear. Determining the proper interpolation to match this shape is an area of current research.

The third focus of our project is the construction of difference schemes for isotropic or mildly anisotropic scattering that maintain accuracy in the thick diffusion limit. As mentioned above, the usual approach to singularly perturbed problems is to look at the null space of the limit operator. Let L_{σ_t} represent the Boltzman operator parameterized by σ_t . Let $P = \int d\Omega$ be the projection onto the space of functions independent of Ω , the null space of L_∞ . In the thick limit we have

$$\begin{pmatrix} PL_{\sigma_t}P & PL_{\sigma_t}(I-P) \\ (I-P)L_{\sigma_t}P & (I-P)L_{\sigma_t}(I-P) \end{pmatrix} = \begin{pmatrix} O(\frac{1}{\sigma_t}) & O(1) \\ O(1) & O(\sigma_t) \end{pmatrix}.$$

Here the block structure of the operator corresponds to the subspace of functions independent of Ω and its orthogonal complement. The dominant term in the inverse is the Schur compliment of the dominant term in the array above:

$$[PL_{\sigma_t}P - PL_{\sigma_t}(I-P)[(I-P)L_{\sigma_t}(I-P)]^{-1}(I-P)L_{\sigma_t}P]^{-1} = O(\frac{1}{\sigma_t}).$$

The difficulty begins when L_{σ_t} is discretized. The truncation errors of the discrete analogues of the above terms must balance in a precise way in order to preserve the correct behavior in the limit.

Consider the scaling $P + \frac{1}{\sigma_t}(I-P)$. It is easily applied and easily inverted. The scaled operator

$$\hat{L}_{\sigma_t} = (P + \frac{1}{\sigma_t}(I-P))L_{\sigma_t}(P + \frac{1}{\sigma_t}(I-P))$$

is not singular in the thick limit. It is somewhat more complicated than L_{σ_T} , but not excessively. In homogeneous material, that is, for smooth σ_t , many difference schemes will yield an accurate solution, which can be unscaled to yield an accurate solution to the unscaled problem.

This approach has been analyzed for isotropic scattering in homogeneous material in slab geometry and the results are very promising. Simple schemes like upwind differencing and piecewise linear continuous finite elements applied to the scaled problem yield unscaled solutions with accurate

solutions independent of σ_t . A potential hurdle is the possibility of discontinuous σ_t , which may result from nonhomogeneous material. We believe that this difficulty can be overcome by prescribing jump conditions in the scaled solution across material interfaces. We hope this approach will lead to a formalism for constructing discretization schemes that are accurate in the thick limit.

IV. Software Development Plan

A major thrust of this project is the implementation of the resulting algorithms in software, both on advanced architecture computers and in production codes. This will require continued close cooperation with Jim Morel at LANL and Milo Dorr at LLNL. Our development plans include the following:

1. Complete the parallel implementation of the multilevel in angle and multigrid in space algorithms for slab geometry on the CM-200 at Los Alamos. Vectorize the serial versions for the Cray Y/MP and perform a study of the relative efficiencies of the parallel and serial versions.
2. Implement the multilevel in angle code in the 2-dimensional anisotropic production code NIKE that is under development at Los Alamos. This code will use either S_N or P_N in angle and bilinear discontinuous finite elements in space. On the coarsest level the isotropic problem will be solved by either a multigrid in space or a diffusion approximation.
3. Implement the 2-dimensional multilevel in angle algorithm on the CM-200. The shifted transport sweeps will be performed by parallel cyclic reduction.
4. Develop a code for coupled electron-photon transport in slab geometry. The code will use S_N in angle and Linear Discontinuous (LD) discretization in space. The serial versions of the slab geometry codes described above will be an integral part. We will use scattering cross-section files from the production code ADEPT (formerly CEPXS/1LD) developed at Sandia National Laboratories. This will allow our code to do actual production calculations. We hope to demonstrate marked

superiority in performance over existing production codes. We will target the resulting code for workstations and mainframes like the Cray Y/MP.

References

- [1] M. L. Adams and W. R. Martin, "Diffusion-Synthetic Acceleration of Discontinuous Finite-Element Transport Iterations," to appear in *Nucl. Sci. Eng.*
- [2] R. E. Alcouffe, "Diffusion Synthetic Acceleration Methods for the Diamond-Differenced Discrete-Ordinates Equations," *Nucl. Sci. Eng.*, **64**, 344 (1977).
- [3] Allen Barnett, J. E. Morel, and D. R. Harris, "A Multigrid Acceleration Method for the One-Dimensional S_n Equations with Anisotropic Scattering," *Nucl. Sci. Eng.*, **102**, 1 (1989).
- [4] V. Faber and T. A. Manteuffel, "Neutron Transport from the Viewpoint of Linear Algebra Integral," *Transport Theory, Invariant Imbedding and Equations*, (Nelson, Faber, Manteuffel, Seth and White, eds.), Lecture Notes in Pure and Applied Mathematics, **115**, pp. 37-61, Marcel-Dekker, April, 1989.
- [5] E. W. Larsen, "Unconditionally Stable Diffusion-Synthetic Acceleration Methods for the Slab Geometry Discrete Ordinates Equations," *Nucl. Sci. Eng.*, **82**, 47 (1982).
- [6] E. W. Larson, "On numerical solutions of transport problems in the diffusive limit," *Nucl. Sci. Eng.*, **83**, pp. 90-99, 1983.
- [7] E. W. Larson, "Diffusion-synthetic acceleration methods for discrete-ordinates problems," *Transport Theory and Statistical Physics*, **13**, pp. 107-126, 1984.
- [8] E. W. Larsen, "Transport Acceleration Methods as Two-Level Multigrid Algorithms," *Operator Theory: Advances and Applications*, Vol. **51**, p34-47, (1991).

- [9] E. W. Larson, J. E. Morel and W. F. Miller, "Asymptotic Solutions of Numerical Transport Problems in Optically Thick Diffusive Regimes," *J. Comp. Phys.*, **69**, p. 283, 1987.
- [10] E.W.Larsen, J.E. Morel, "Asymptotic Solutions of Numerical Transport Problems in Optically Thick Diffusive Regimes II," *J. Comp. Phys.*, **83**, 212 (1989).
- [11] M. S. Lazo and J. E. Morel, "A Linear Discontinuous Galerkin Approximation for the Continuous Slowing Down Operator," *Nucl. Sci. Eng.*, **92**, p. 98, 1986.
- [12] E. E. Lewis and W. F. Miller, Jr., *Computational Methods of Neutron Transport*, John Wiley and Sons, (1984).
- [13] L. J. Lorence, Jr., E. W. Larsen, and J. E. Morel, "An S_2 synthetic acceleration scheme for the one-dimensional S_N equations," *Transactions of the American Nuclear Society*, **52**, p. 417, 1986.
- [14] L. J. Lorence, Jr., W. E. Nelson and J. E. Morel, "Coupled Electron/Photon Transport Calculations Using the Method of Discrete Ordinates," *IEEE Trans. on Nuclear Science*, *NS-32*, p. 4416, 1985.
- [15] T. Manteuffel, S. McCormick, J. Morel and G. Yang, "Fast Multigrid Solver for Neutron Transport Problems," Proceedings of the IMACS First International Conference on Computational Physics, Boulder, Colorado, June 11 - 15, 1990.
- [16] T. Manteuffel, S. McCormick, J. Morel, S. Oliveira, and G. Yang, "Parallel Multigrid Methods for Transport Equations," *Proceedings of the Copper Mountain Conference on Iterative Methods*, Copper Mountain, CO, April 9 - 14, 1992.
- [17] T. Manteuffel, S. McCormick, J. Morel, S. Oliveira, and G. Yang, "A Parallel Version of a Multigrid Algorithm for Isotropic Transport Equations," to appear in *SIAM J. Sci Stat. Comp.*
- [18] T. Manteuffel, S. McCormick, J. Morel, S. Oliveira, and G. Yang, "A Fast Multigrid Algorithm for Isotropic Transport Problems," submitted to *SIAM J. Sci. and Stat. Comp.*, October 1992.

- [19] T. Manteuffel, S. McCormick, J. Morel, S. Oliveira, and G. Yang, "A Fast Multigrid Algorithm for Transport Problems with Absorption," in preparation.
- [20] J. E. Morel, "Fokker-Planck Calculations Using Standard Discrete-Ordinates Codes," *Nucl. Sci. Eng.*, **79**, p. 340, 1981.
- [21] J. E. Morel, "A synthetic acceleration method for discrete ordinates calculations with highly anisotropic scattering," *Nucl. Sci. Eng.*, **82**, p. 34, 1982.
- [22] J. E. Morel, "The Fokker Plank Operator For Forward-Peaked Elastic Scattering," *Nucl. Sci. Eng.*, **64**, 344 (1982).
- [23] J. E. Morel, "Multigroup Legendre Coefficients for the Diamond Difference Continuous Slowing Down Operator," *Nucl. Sci. Eng.*, **91**, p. 91, 1985.
- [24] J. E. Morel and E. W. Larsen, "A Multiple Balance Approach for Differencing the S_N Equations," *Nucl. Sci. Eng.*, **105**, 1 (1990).
- [25] J. E. Morel and T. A. Manteuffel: "An Angular Multigrid Acceleration Technique for the S_N Equations With Highly Forward-Peaked Scattering," *Nucl. Sci. Eng.*, **107** 330 (1991).

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**DATE
FILMED
01/21/93**